THE BADIO TECHNOLOGY LEADER

A SUPPLEMENT TO RADIO MAGAZINE





SOLID: Performance • Reliability • Support

Upgrade to Presenter Now and We'll Convert Your Audio For Free! Our Performance, Reliability and Support Mean Bottom Line Savings For You.

The Best Choice for Your Studio System:

Presenter (800) ENCO-SYS



Simplicity Made Smarter





DIGITAL CONSOLE

Less than a decade ago building infrastructure at even the most modest radio facility was difficult and costly. Today, AoIP is making it possible to replace miles of cables and closed systems with routers that use standardized network protocols. The JetStream Mini brings you the benefits of this new technology, and nothing is easier to use, faster, or less expensive. Add a Pilot control surface that includes the basic operating features your staff will need and you have the most cost effective AoIP networked audio system available.

The Pilot is easy on the eye and the budget and like the JetStream Mini, Logitek has built it with ease of use and durability in mind. The Pilot is a tabletop control surface that includes all of the basic engineering features your staff will need- and more-including 4 Program busses, 3 monitor sections and 24 mix minus busses. It is available in frame sizes for 6 to 24 faders.



Looking for lots of power in a small footprint? The JetStream Mini lets you load up to 64 channels of I/O into a 2 rack unit and the Pilot will service even the most constrained spaces with ease. Configure your system with microphone inputs and analog/digital I/O to suit your specific needs; our use of standardized IP protocols ensures advanced AoIP networking with fast and easy setup... all for a price that won't break the bank.



GIVING YOU THE TOOLS TO CREATE GREAT RAD **iMediaTouch Radio Automation Software**

Please visit us at the 2011 NAB Radio Show in Chicago - Booth 711



Scan our QR code to see a live video of iMediaTouch today.

For more information please contact our sales department at 888-665-0501 or via email at sales@imediatouch.com



2011 Product Source

The Source for New Products

You're a technology professional. You rely on the latest technology to do your job and to keep your stations at their peak. You're always on the lookout for the right technology for the job. So are we.

At Radio magazine, we are on a constant quest to find new tools and new products to help you make great radio. We bring them to you in each monthly issue. We cover them in our twice-monthly New Products Extra email newsletter. And each year we assemble this compendium of the latest new products for our annual Product Source.

This issue is packed with new products. While many debuted at the 2011 NAB Show, we discovered others by looking outside the traditional broadcasting connections and into the pro audio and IT channels. Regardless of where it came from, everything in this special issue fills a need in radio.

We have gathered some products into special sections as well. These products fit unique needs outside the studio facility.

You'll also find everything in this issue posted at our website for easy reference: RadioMagOnline.com. Use the QR code below to quickly access the index from your mobile device and you can take it all with you.

What you find within is an extensive mix of new products and services, but we know there's always more. If you have found an interesting device, product or service, tell us about it. Like you, we want to know about the latest new technology, and we want to share it with our readers.

- Chriss Scherer, editor



Take new products with you on the go. Just scan this QR Code with your smartphone.

Special Section Index

8 | Portable Production

12 | Station Services

16 | Beyond These Walls

20 | Out & About

26 | Reference Room



Radius Curve: Featuring robust 6mm "Waterfall" table top trim, with 3mm PVC trim on vertical panels, Radius Curve has more seating options with the addition of a new smaller utility cabinet and three adjustable metal legs. The multiple interview and co-host areas are created with radius cuts of as much as 180 inches. These large curves are integral to the basic table top and add to the overall appearance of the studio. Radius Curve is available in stand-up or sit-down in 12 configurations that can be modified to suit. All configurations are shipped flat pack or fully assembled.

970-225-1956; www.graham-studios.com; rod@graham-studios.com

IP transmission system WorldCast Systems APT SmartIP with Sur-

eStream: Part of the SmartIP suite of IP techniques and features, APT SureStream enables delivery of broadcast-grade audio quality over cost-effective, public ADSL or



wireless links. SureStream uses inexpensive IP links such as wireless 3G and 4G IP networks, LAN, WAN, Wi-Fi and simple ADSL. A combination of these can be used for increased redundancy. SureStream does not alter the audio to ensure continuity of service, nor does it switch between links depending upon performance, but rather it uses resequencing technology to seamlessly stream high-quality audio.

305-249-3110; www.aptcodecs.com ussales@worldcastsystems.com

UPS system Middle Atlantic Products

UPS-2200R-81P: This line of UPS systems provides true individual outlet control, both remotely via RS-232 and IP, and locally using Middle Atlantic Power Manager, a Web-based interface for local monitoring and control. The system allows users to control each of the eight outlets independently, allowing users to restrict unauthorized use of outlets for additional security, and when integrated with a control system via RS-232, can support up to eight-stage sequencing in any combination, with any delay; no separate sequencer is necessary. The UPS also features Pure Sine Wave technology, integration with AV control systems and a unique sliding rear rackrail mount. The easy installation functionality of the UPS simplifies rack integration.

973-839-1011; www.middleatlantic.com; sales@middleatlantic.com

ACCESS IP Codecs Make Remotes as Simple as 1-2-3-4G!

4G Wireless Technology has completely changed the game for remote broadcasts. 4G services offer lots of bandwidth, low delay and incredible performance improvements over 3G. And now, Comrex makes it super easy for you to utilize 4G with no external routers, no difficult configuration... just plug-and-play, 4G Simplicity.

- Buy a pair of ACCESS IP Codecs and you'll get a pair of BRIC-TS Licenses FREE (a \$500 Value). BRIC-TS makes it easy for your codecs to connect even when they are behind routers and firewalls. Comrex will create your BRIC-TS Account and configure your codecs before they ship.
- Obtain a 4G account and 4G USB modem* from your favorite wireless provider.
- Connect an ACCESS codec to your studio's Internet connection (no static IP required). Connect your 4G USB device to your ACCESS codec in the field.
- 4G) Look for your "Studio" icon ** to appear on your "Remote" unit. Then Select and Connect and you're on the air!
- *To see a list of supported 4G USB modems and complete promo details, go to:http://www.comrex.com/promo

Or scan the QR code with your Smart Phone:



UPGRADE YOUR ACCESS CLASSIC TO SUPPORT 4G - FREE!


Your ACCESS Classic can be upgraded for 4G support... absolutely FREE! Just update your firmware to the latest version, available on our website: http://www.comrex.com/support/products/access.html



IP - 3G - WI FI - 4G - BGAN / VSAT - PSTN - DSL

2USB





Acoustic panels **Acoustics First**

Sonora Series: These acoustical panels absorb sound to dry up echo and reverberation. The sound gets lost in the landscape of acoustical fibers to improve speech intelligibility and silence room overtones. Removing the excess sound of the room improves the ability of broadcast equipment to efficiently produce crystal clear sound over the airwaves. Sonora panels mount to the walls or can be configured as ceiling tiles, baffles or clouds. Available in many standard sizes and colors, they can also be custom cut to meet specific requirements or shaped to create designs and accentuate room decor.

888-765-2900; www.acousticsfirst.com; info@acousticsfirst.com

AoIP console Axia Audio

Radius: A compact networked mixing console with four stereo buses. eight faders, 16 audio I/O ports and cn Ethernet switch with Gigabit, Radius features automatic mix-minus for every fader. Other features include: talkback. networkable, four GPIO machine-control ports, four



instant-recall Show Profile snapshots, record mode with one-touch recording, monitor controls for an adjacent studio, fan-free mixing engine, and desktop mount. Additionally, Radius has switchable VU/PPM LED bar graph meters, 100mm conductive plastic faders, aircraft-quality switches with LED lighting, onboard NTPcapable clock, event timer and high-resolution OLED readouts on each fader strip.

216-241-7225; www.axiaaudio.com; inquiry@axiaaudio.com

Network audio interfaces

AudioScience

Connect CobraNet: This series has 12 pre-configured devices for the most popular I/O combinations. These networked audio interfaces are built in a 1RU format and provide up to 16 channels of CobraNet receive and transmit. These units feature a Texas Instruments 32-bit floating point DSP that allows sophisticated switching/mixing. A graphics display on the unit's front panel shows peak meters and CobraNet status. AudioScience provides application software that may be used to set up all the Connect Series units. ASIControl sets up all internal features of the unit and allows CobraNet routing connections to be set up between the Connect Series units and any other CobraNet device on the network. 302-324-5333; www.audioscience.com; sales@audioscience.com

Stereo audio monitor

Henry Engineering

SAM: A digital/analog stereo level and phase meter, SAM uses single stereo display technology to display both channels of a stereo audio signal using one LED meter. The display utilizes tri-color LEDs, showing the left channel in green, the right channel in red, and both (L+R) channels displayed in yellow. By watching the display, an observer can easily read the levels of both audio channels, see the balance between the channels, and instantly see if a channel is missing. SAM uses a second single stereo display to show the

sum (L+R) and difference (L-R) components of a stereo signal. An observer can instantly see if excessive L-R levels could

indicate phase error or a polarity reversal in the audio chain. The meter accepts either an AES/EBU digital input or analog inputs. It accurately indicates system levels over a range of -25 to +3 VU. A headphone jack is provided for aural monitoring.

626-355-3656; www.henryeng.com; info@henryeng.com

Digital FM/HD exciter Continental Electronics

802E, 802Ex: The 802E FM digital exciter is the base system for the 802Ex FM/HD Radio exciter. The 802E incorporates the basic



spectrum readings and display and can easily be field upgraded for IBOC with the addition of the CEC Exgine card, iBiquity software and an 800EXP Embedded Exporter. Software features of the 802Ex include Continental's exclusive Insight HD Radio performance monitoring system. which shows spectral, constellation, filter and adaptive precorrection performance. Standard in the 802Ex exciter is Continental's fully adaptive, real-time forward precorrection, allowing changes in transmitter or RF system performance to be automatically sensed and corrected: software-selectable HD Radio power levels of -20dB, -10dB or any power level in between; hi-res color LCD screen for maximum clarity and accuracy; built-in stereo generator; built-in audio delay (up to 16.4 seconds); synchronization using GPS 10MHz signal; multiple AES3 digital audio inputs; AES3 audio output; standard composite input and two baseband SCA inputs.

800-733-5011; www.contelec.com; sales@contelec.com



THE BROADCASTER'S SECRET PLAYBOOK

THE REMOTEMIX 4 PUTS THE GAME ON THE LINE AND COORDINATES YOUR TEAMFOR THE ULTIMATE COVERAGE

RemoteMix 4 combines a four channel field mixer with a four channel headphone amplifier to give you the ultimate front end to your POTS, ISDN or IP CODEC. Just connect RemoteMix 4 to the send and receive jacks of your CODEC and you're on the air. Our four telecom interfaces provide plenty of backup for transmission, monitoring, and station cues. Easy to set up, yet flexible enough to accommodate your individual demands.

Plus...IT SOUNDS GREAT! The RemoteMix 4's Master XLR Output (pre-limiter) provides full range

audio, while a soft limiter prevents overdriving the phone line interfaces. For that extra "kick", Bass Boost increases the low end before sending it down the phone line. There are convenient 3.5mm send and receive jacks for recording in full bandwidth, or mixing in your prerecorded material. The individual headphone level controls provide plenty of low distortion power to cut through the crowd noise.

RemoteMix 4 can be powered by batteries or the included AC adapter, so you'll never lose a connection, even during a power outage!



This calls for Teamwork...

Combining a four-channel field mixer with a four-channel headphone amplifier, a phone-line hybrid, a universal PBX handset interface, a wireless phone interface and Bluetooth® Wireless Technology to connect to cell phones and portables, the RemoteMix 4 is ready to work just about anywhere you are.



Portable Production

iPhone, iPod, iPad condenser mic IK Multimedia

iRig Mic: The iRig Mic features a highly unidirectional electretcondenser microphone capsule that provides quality recording, in both close mic and long-distance mic conditions, and real-time monitor-

ing with its dual



+39 059 285496; www.ikmultimedia.com



USB ribbon microphone **MXL** Microphones

UR-1: The UR-1 microphone (patent pending) takes the classic, mellow sound of a ribbon microphone and integrates it with today's USB technology. This new mic uses modern electrical circuitry to match the input requirements of analog-to-digital converters and USB output with low-noise and high dynamic range. The UR-1 is housed in an all-metal body with a double-shielded grill. A volume control and headphone jack on the unit allow for real-time monitoring without any latency.

800-800-6608; www.mxlmics.com; sales@mxlmics.com



Four-channel **USB** mixer Alesis

MultiMix 4 USB:

A four-channel desktop mixer with a USB digital audio interface built in, the MultiMix 4 USB outputs not only line-level analog audio, but also stereo 16-bit, 44.1kHz digital audio

over USB for low-noise, easy computer connection. Monitor back from a computer through the same USB connection. All four input channels accept a 1/4" line input. XLR microphones can be plugged into channels one and two, including condensers thanks to the mixer's switchable 48V-phantom power supply. Channels one and two offer switchable high-pass filtering at 75Hz to eliminate low-frequency rumble, handling and wind noise. The MultiMix 4 USB has a two-channel, five-stage, multicolor LED meter for visual monitoring the main output level. A stereo, 1/4" headphone output has its own level control

800-5-ALESIS; www.alesis.com; info@alesis.com

Handy gadgets for production on the go

Audio cables Hosa

Technology

Pro Interconnect Cables: The combination of cable for enhanced signal transmission and audio quality, REAN connectors by Neutrik AG, and world-class



workmanship, Hosa Pro Interconnect Cables are available in all pro audio terminations, including XLR, 1/4" TRS (tip, ring, sleeve), 1/4" TS (tip, sleeve) and RCA. All cable models utilize a z nc die-cast housing, a quadrangle design, chucktype strain relief, and rubber boot kink protection. The cables feature 24 AWG oxygen-free copper (OFC) conductors and a 90 percent OFC braided shield for effective EMI and RFI rejection. The 1/4" TRS and TS cables employ nickel-plated contacts for efficient signal transfer and rugged durability while XLR and RCA cables incorporate silver-plated contacts for enhanced signal transfer.

714-522-8878; www.hosatech.com; sales@hosatech.com

Audio recorder **Olympus**

LS-7: Compared to previous LS series recorders, the LS-7 offers features including a pre-record buffer that captures two seconds of audio before the record button is pressed, an omni-directional mic to pick up lower bass frequencies, a switchable low-cut filter that eliminates unwanted low-frequency noise and voice guidance for users with assistive needs. The new features come in a compact, lightweight, metal body with uncompressed 24-bit/96kHz linear PCM recording format.

888-553-4448; www.olympusamerica.com

Audio recorder


Audiofile Engineering

Fire 2: A new version of Audiofile Engineering's field recording app, Fire 2 has been redesigned and rewritten with a hos of new features for the latest iOS devices. Fire 2 features: An advanced editing suite with SmartEdits, Bezier fades, change gain, normalize, looping playback, regions and more; improved transport screen with faster and smoother drawing and larger waveform view; EQ and dynamics effects; iTunes file transfer; enhanced input processing powered by iZotope; record in background; and Dropbox integration.

www.audiofile-engineering.com



SANITIZED FOR YOUR PROTECTION



SOME WORDS SHOULD BE OBSCENE AND NOT HEARD



Eventide Broadcast Delays are designed to keep profanity off your air, and angry listeners, embarrassed advertisers, and the FCC off your back. We invented the obscenity delay and have a solution for stations large and small that provides up to 80 seconds of the highest quality revenue and license-protecting delay.

Our new HD compat ble BD600, 24-bit delay, comes standard with AES/EBU, and provides up to 80 seconds of memory — twice as much as other delays. There are fully adjustable Delay and Dump functions, and a Sneeze function which "edits" audio entering the delay, allowing the host to sneeze, cough, or make a short comment without being heard on air.

The BD600 offers two different methods of delay buildup and

reduction: Eventide's catch-up and catch-down system, and an exclusive fast-entry-and-exit feature which allows starting a broadcast with the delay already built up to a safe amount and ending it with a rapid reduction of delay.

For HD, the BD600 offers MicroPrecision De ay[™] mode which allows up to 10 seconds of delay to be adjusted in real time in 100 nanosecond increments. This is useful for synchronizing analog and digital signals while or-air, without audible artifacts, to maintain a seamless user experience.

Whatever your size, whatever your format, you can't expect to protect the integrity of your air and the foundation of your business without an Eventide Broadcast Delay in your rack.

Eventide®

HD COMPATIBLE



Studio monitors

Fostex

PMO.5n: Offering 70W of bi-amped power, the PMO.5n features full-range performance with neutrality even at high sound pressure levels. The compact dimensions also enable accurate placement in confined or awkward spaces. Dispersion from the two-way ported enclosure is tailored to deliver superb sound almost regardless of room acoustics. The headphones feature a UFLC 20mm soft dome HF unit and 130mm LF woofer and input gain control.

800-7-FOSTEX; www.fostexinternational.com; sales@fostex.com



Telephone talkshow system Comrex

STAC VIP: STAC VIP takes advantage of advances in VoIP and SIP-based technologies that allow for high-quality voice calls to be made from IP-based PBX systems, Smartphones, PCs and through popular VoIP providers. It provides a way to manage not only traditional POTS calls, but also VoIP and SIP calls from Smartphone apps (like Comrex ARC), "soft codecs" and even Skype.

800-237-1776; www.comrex.com; info@comrex.com

Broadcast furniture Omnirax

Phoenix Line: A budget-friendly version of the Innova line, the Phoenix Line is a distillation of proven custom designs built with the same rugged materials and constructed with the same exacting techniques. The initial offering consists of three basic configurations: Air, Production and Talk, each available with a variety of add-ons that afford additional space or functionality. The entire line is flexible and fluid, allowing for further modifications. Curved lines enhance the experience of both operator/host and quests, creating more real estate close at hand. The guest positions are scalloped so anyone is positioned just right to be heard on the mic, reach the cough switch or make eye contact with the host.

800-332-3393; www.omnirax.com info@omnirax.com

FM transmitters BW Broadcast

Aptus: The Aptus highperformance FM transmitter range will be a fully equipped multi-purpose solution. Featuring a touch front panel, these transmitters have built-in audioover-IP decoding, RDS encoder and comprehensive metering/ analysis functionality. The models also have advanced multi-band DSP audio processing as standard and onboard memory for local backup audio, Ethernet and serial remote control, silence detection and source switching, built-in stereo generator, SCA inputs, and allnew sophisticated alarms and notifications

866-376-1612 www.bwbroadcast.com info@bwbroadcast.com

Relocation software

V-Soft Communications

XField: Station engineers can use XField when re-locating FM translator stations to frequencies that are second or third adjacent to full service stations or otherwise protected translator stations. To consider the vertical elevation field of a given antenna the XField program must calculate the ERP of the translator antenna along the ground or at a

user-selected height at various azimuths and distances from the translator antenna. XField employs the translator's vertical elevation field and azimuth pattern to produce a graph or table of the points where the 40dB limit is exceeded. A translatorstation can



then be brought into compliance by either reducing its ERP, using an antenna with more bays (keeping the higher signal strength away from theimmediate tower location) or increasing the translator's antenna height. XFIeld also includes an IBOC interference calculator, which will calculate the self? interference caused to a hybrid IBOC station when its antenna is not the antenna used by the hosting station.

800-743-3684; www.v-soft.com; info@v-soft.com

Power amplifier Stewart Audio



AV100: Built for driving both subwoofers and full range loud-speakers, the AV100's lightweight design and convection cooling give this AB Class power amplifier fidelity for a multitude of applications. Pole and universal mounting brackets are available. With its compact, half-rack form factor, this 100W monaural amplifier is optimized to drive 4 and 80hm loads and, with the inclusion of a low-pass filter, is well-suited for driving subwoofers. The AV100 also uses an ultra-efficient switch mode power supply for its conversion of electrical power. It provides a push-button switch to toggle between full range and subwoofer modes and provides LEDs for visual confirmation of power and clipping.

209-588-8111; www.stewartaudio.com info@stewartaudio.com

iPhone microphone adapter

Tieline Technology

Mic Adapter: When newsgathering using Report-IT Live on an iPhone4, attach pro cynamic microphones with Mic Adapter.

> The adapter features a professional XLR mic input and dual headphone outputs for live interviews between the remote site and the studio. It also has adjustable mic gain at-

tenuation, automatic gain control on/off, a stereo line level input and is selfpowered using two AAA batteries. Importantly, the Mic Adapter also features a mini-USB power input for iPhone charging during long broadcasts. The adapter can also be used for a variety of other iPhone Pro Audio apps. It is currently going through the Apple Accessory Certification process and the company expects it to be shipping before mid-year.

888-211-6989; www.tieline.com; sales@tieline.com

Headphones Mixware

Reloop RHP-10:

With the RHP series. Reloop introduces a modern, lightweight design and a robust construction. In spite of the enormous driver units, the ear cups are constructed in

a plain and compact way. The bracket's

aluminium bar grants stability and lightness, adjustment allows an accurate alignment and the double casing with the upper made of artificial leather and the lower side made of fluid-absorbing Climabsorb net-nylon guarantees wearing comfort and robustness. Two enclosed cords (plain and spiral) are Reloop standard.


786-362-5757; www.mixware.net; info@mixware.net

Database maintenance

Matrix Solutions

Virtual Sales Assistant: Virtual Sales Assistant is a service that works in collaboration with sales teams by performing on-going database maintenance in key areas keeping Matrix databases up to date. This service integrates, cleans, reconciles and delivers the sales information necessary to make good business decisions.

877-687-9066; www.matrixformedia.com; sales@matrixformedia.com



Station Services

Live Stream

1923 Wtts
RIADIANAPOUS

For the Summer
Ray Lamontagne
& the Pariah Dogs
God Willin' & the
Creek Don't Rise
2010, RCA Records

Audience connection app Boost Media & Entertainment

MyStationApp: This service is designed to connect fans to their favorite radio station live no matter where they are, by porting PLS streams (multimedia files) onto their smart phones. The app has struck a chord with independent stations that believe apps can enrich the relationship with their audience. MyStationApp features a low implementation cost and a short development time - less than a week in many cases - yet can be completely customized by each station to create a one-of-akind product.

317-624-0300
www.boostmediaentertainment.com
info@boostmediaentertoinment.com

What can these companies do for you?

Song tagging service Broadcast Electronics

Twitter Tagging for TRE: This application makes song tagging possible on any portable device that supports Twitter. By taking advantage of a Twitter feature known as "favorites," TRE is enabling stations to offer iTunes tagging to listeners whatever their device of choice, including the Web. With this new option for its data management system, TRE enables song tagging using the common social network Twitter, so listeners with Blackberries, Androids, and other devices can tag the songs they hear on the radio. Stations set up a Twitter feed with now playing events using TRE, which establishes a unique iTunes URL link for each song event as part of the Twitter feed. Listeners with iPhones and other devices with iTunes tagging can click on links to purchase songs as they're played on the air. Listeners with Blackberries, Androids and other devices lacking iTunes tagging capability can mark songs as "favorites" for eventual purchase through the iTunes music store.

217-224-9600; www.bdcast.com; bdcast@bdcast.com

Audience measurement Triton Digital Media

Triton Engagement Labs: A testing ground for innovative audio applications and online integration that broadcasters can use to maximize Engagement Labs will identify driving factors and online. By directly measuring the effect that Triton is able to tailor programs more closely to the and online promotions, stations are able to better and offers to their loyal listeners.

818-528-8860; www.tritondigitalmedia.com solutions@tritondigitalmedia.com

Contest management NeoGroupe

NeoWinners Version 3: NeoWinners Version 3 provides a range of enhancements including a more intuitive interface; support for all major RDBMSs (Microsoft SQL, Oracle, MySQL, DB2, Informix, AS/400) for easy, tight integration in an IT environment; and multichannel contest management with unique Internet distribution capabilities to increase audience loyalty.

603-203-1331; www.neogroupe.com info@neogroupe.com

Streaming service Liquid Compass

Mobile Streaming Division for Radio: The new Liquid Compass mobile streaming division will develop and deploy apps designed to enhance the overall listening experience for the end-user and, for the broadcaster, build audience share and time spent listening. The new LC ProM app includes enhanced Now Playing, social networking, Favorites and On-demand features that benefit broadcasters and their end-users with: station branding for the broadcaster, allowing them to keep their brand prominently displayed on one of five available "skins" (custom skins are optional) at all times while the listener is tuned in; and functionality for listeners, allowing them to rate, like or tag songs for later purchase without having to leave or close the app. Listeners can send playlist and like (stations or songs) updates to their Twitter or Facebook pages directly from the app.

303-839-9400; www.liquidcompass.net; info@liquidcompass.net

Advisory service

BIA/Kelsey

Social Local Media: Dedicated to covering the growing and dynamic social media ecosystem and the best opportunities for driving revenues with social platforms, Social Local Media (SLM) will spotlight those engaged in the use of social media tools and techniques to forward customer relationships. It will focus on helping media companies and social platform suppliers identify the best integration strategies for implementing social across medic, marketing and advertising channels in a manner that drives revenues. SLM coverage will center on: new local monetization models for social networks; metrics that measuresocial initiatives; social media transactions; social media valuations and valuation models; social commerce; Facebook's continued evolution; social's role in e-mail, reputation and presence management; next steps for check-inservices; and industry analysis of how various media segments are utiliizing social channels.

703-818-2425; www.bia.com; info@bia.com

MEET SAM... A COOL WAY TO MONITOR AUDIO LEVELS, BALANCE AND PHASE



When it comes to audio, a quick, accurate and intuitive way to know what's happening is essential for a successful result. That's where SAM comes in.



The **Stereo Audio Monitor (SAM)** is a stereo level and phase meter that incorporates Single Stereo Display* technology. SAM provides a visual indication of the levels and phase relationships of a stereo audio signal. The unit indicates the usual Left and Right channel levels, and also displays the Sum and Difference components of the stereo signal.

SAM's dual tri-colored Single Stereo Displays show this information in an intuitive and easy-to-comprehend format. Both analog and AES/EBU digital signa s can be monitored with SAM. Its compact size allows monitoring three stereo audio sources in only 1 RU of your valuable rack space.

Slip SAM into your audio chain and see what you've been missing.

(*Patent pending)



WE BUILD SOLUTIONS.

DIGITAL SOLUTIONS. ANALOG SOLUTIONS. FUNCTIONAL, RELIABLE. AFFORDABLE.



Visit www.henryeng.com for all of Henry's solutions!

Henry Engineering • 503 Key Vista Drive, • Sierra Madre, CA 91024 USA T: 626.355.3656 • F: 626.355.0077 • email: Info@henryeng.com



Line-powered telephone units Sonifex

CM-TBU, CM-TLL: These small line-powered telephone balance and telephone line listen units act as two to four-wire converters for IFB applications. The CM-TBU is compatible with all analog direct exchange lines and provides a four-wire communications system to interface with the telephone network. The high degree of separation between send and receive signals makes it suitable for use in telephone IFB (interrupted foldback) applications and the high drive capacity at the four-wire output enables a presenter's earpiece to be

connected directly to the unit without an external amplifier. The CM-TLL provides a low-loss interface to receive audio from a telephone line. The line-powered unit is compatible with all analog direct exchange lines and includes an LED indication of incoming calls. It is intended to be used with an earpiece amplifier to receive an audio feed by telephone from a studio. The line and telephone set are connected to the unit via the RJ-11 connectors in order to make an outgoing call. A telephone may not be required if calls are only incoming, because telephone line ringing is indicated by a flashing LED built into the unit.

+44 1933 650 700; www.sonifex.co.uk; sales@sonifex.co.uk

Audio/EAS monitor

Innovative Broadcast Services

Studio Hawk. 8: The Studio Hawk. 8 monitors audio and EAS receivers at a studio and communicates problems via e-mail, text messaging and signaling devices. The base system includes Studio Hawk software and hardware to monitor eight status channels, analog channels and relays. It records EAS data (transmitted and received) and can be expanded to monitor up to six EAS receivers. Users will also receive multiple contacts for each alarm with delays between messages, a daily dead air report PDF by e-mail and filtered EAS alerts.

662-324-2769; www.hawkremote.com; support@hawkremote.com

Trafficking software

Wide Orbit

WO Traffic 6.5: This upgrade includes new tools to tag programming for spot placement compatibility or copy violations, create custom, multi-level order approval workflows and book, bill and report on detailed non-linear Internet campaigns. WO Traffic v6.5 enables media companies to manage multiple stations, channels and platforms, as well as multiple media from a single system. WO Traffic is a scalable, enterprise-wide solution with real-time, flexible reporting that delivers visibility and control at all levels of a media business.

415-675-6700; www.wideorbit.com; mzinsmeister@wideorbit.com

Internet radio app

Modulation Index

StreamS HiFi Radio: This Internet radio app for iPhone/iPod Touch/iPad hardware supports and lists thousands of high-quality AAC and HE-AAC streams including AM/FM stations and NET streams via the StreamS directory. Without having to register on a website, users can add their own streams within the



StreamS app, which is only necessary if these streams are not already listed in the StreamS directory. Users can search, save streams and stations as favorites, view recents, save titles, and purchase on iTunes. StreamS supports social networking - users can publish current title to Facebook, MySpace and Twitter. It even provides a world StreamMap showing what other users are listening to. StreamS optimizes the user experience by displaying album art and artist title information in a fast, easy-to-use, mobile-oriented interface

> 909-860-6760; www.indexcom.com info@indexcom.com

Telco control surface JK Audio



Guest Modules: Up to eight Guest Module control surfaces provide remote control of the switch matrix over CAT-5 cable. Guest Modules are hot swappable without losing calls, and feature line selection buttons that change color to indicate call status. Guest Modules are available in 1x6, 2x6, and 1x12 desktop and rack mount versions. They feature durable aluminum and steel construction with a sealed rubber keypad

800-552-8346; www.jkaudio.com; info@jkaudio.com

Audio switcher **Digital Alert Systems**

MultiPlayer: MultiPlayer eliminates the restrictions of sharing a single Emergency

Alert Systems (EAS) encoder/decoder system with relays and switches by providing multiple and completely independent EAS switching, playout and control to simultaneously cover the EAS requirements of multiple program streams. MultiPlayer is configurable for analog or AES switching of up to four program streams and networks to any DASDEC system for management and logging. In addition, the integrated switching and multiple GPI/Os for each channel makes facility integration easy.

585-765-2254; www.digitalalertsystems.com; info@digitalalertsystems.com





Encoder/decoder

Monroe Electronics

One-Net: The R189 One-Net SE EAS encoder/decoder is the second generation of Monroe's IP-based emergency messaging platform. New



features include an option for up to four independent network connections, better security, faster processing and flash memory. These will prove

valuable as FEMA and the FCC move into the Next Gen EAS, and as cable systems move toward a more IP-centric head-end design. With a standard 10/100 BASE-T Ethernet connection this device can communicate via a network with new digital platforms or be accessed via the Internet for monitoring or downloading upgrades.

585-765-2254; www.monroe-electronics.com; eas@monroe-electronics.com

Aluminum transmission line **ERI-Electronics Research**

1329Line: These aluminum outer/copper inner conductor rigid transmission line systems are available in 31/8", 41/16", and 61/8" (both 50 and 75 ohm) sizes. The elimin nation of the copper outer conductor reduces component prices and weight, decreasing the support component complexity, cost and installation effort. ERI's bellows

expansion compensator accommodates the differential expansion between the inner and outer conductor and vertical and horizontal spring hangers are designed to support the system and compensate for differential expansion between the tower and vertical and horizontal runs. The systems also include galvanic adapters to allow

interconnection to new or existing brass and cop per components




812-925-6000; www.ERlinc.com; sales@ERlinc.com

Captioning solution

Enco Systems

enCaption 2.0: enCaption 2.0 is a fully automated captioning solution for live and production events aimed at providing cost-effective captioning on demand, enCaption 2.0 is speaker independent and improves accuracy over time by building a locale dictionary using script and text input, enCaption 2.0 prevents FCC and ADA fines for content creators and presenters and is available in a number of languages. For radio, the system could be used to transcribe alk shows.

800-362-6797; www.enco.com; sales@enco.com




Beyond These Walls



High-power, high-efficacy lamps Ledtronics

PAR Series: Operating either in 120Vac dimmable or in a wide-voltage input range of 90-290Vac, the line of Edison medium screw-base and GU24 bi-pin base bulbs come in various PAR20, PAR30 and PAR38 styles. With energy consumption ranging from 7W (PAR20) through 12W (PAR30) and up to 15W (PAR38). the lamps directly replace incandescent and halogen lamps that consume up to 100W, and even compact fluorescent bulbs up to 26W, resulting in tremendous energy savings. These state-of-the-art PAR lamps boast 20 percent higher efficacy than the previous generation of LEDtronics PAR lamps. All of the 120Vac dimmable PAR lamps are UL listed

> 800-579-4875; www.ledtronics.com webmaster@ledtronics.com



Soundproof cabinet Silentium

AcoustiRack Active: Harnessing the power of Active Noise Control (ANC) theory (which demonstrates that by producing an opposing signal with the same amplitude as the noise to be reduced, but in the opposite phase, the noise is eliminated). Silentium developed the AccoustiRack Active (ARA). This sound proof cabinet provides up to 30dB(A) sound reduction, or 96 percent elimination of environmental noise. ARA also provides 8kW of heat dissipation by allowing free air movement

and heat exchange with the outside of the unit while maintaining a dust-free environment, extending the life of equipment.

+972-8-946-8664; www.silentium.com info@silentium.com



WP-8011-BK: Use this 24-position wall plate whenever multi-channel American Recorder Technologies audio is being passed through walls from one room to another. The mounting holes are 16" across, allowing for securing mounting screws directly to wall studs. The panel is machined from heavy duty, 0.125" thick aluminum, then coated with a durable black anodized finish. Panel size is 5.5" x 16.75" with 24 D-style mounting positions. Connectors not included. 800-777-9580; americanrecorder.com; sales@americanrecorder.com



Power, airflow, lighting accessories

Enclosure Accessories: These power, airflow and lighting accessories for enclosure products, include a power distribution unit (PDU), a rack-mounted blower and a lineup of new rack lighting configurations. The accessories can be integrated into Crenlo's standard lineup of Emcor enclosures, custom enclosure solutions and other racks/enclosures. The high-current PDU offers 30A of gower distribution at 120V with a dual-circuit design and a total of 24 outlets. The blower utilizes 2RU and provides 250 CFM of airflow at 60Hz. Rack-

mounted lights utilize 1RU and provide illumination for an entire rack of electronic equipment, enabling the user to adjust illumination by dimmer switch while performing service to electronics. Lamp sets provide lighting on a specific area within a rack, without taking up any rack space.

www.crenlo.com; cabsales@crenlo.com

Temperature-managing equipment enclosures Eltek Valere

3030 Enclosures: The upgraded 3030 cabinet is both front and rear accessible and front and rear mountable. featuring an optional separate battery chamber that enables carriers to minimize the footprint necessary for their equipment.

All Eltek Valere 3030 family cabinet products offer carriers tailored temperature management with thermal systems that include air conditioners, heat exchangers and heaters.

469-330 9100; www.eltekvalere.com/us sales.us@eltekvalere.com

Extra long range extender Gefen

DVI ELR Extender S/R: A single CAT-5 cable can deliver highresolution 1920x120C DVI resolutions up to 330' with this extender.

ELR technology, based on HDBaseT standards enables this longer distance extension. This streamlined extender

comes in convenient, wall-mountable sender and receiver units. A single CAT-5 cable connects the sender and receiver, offering an instant delivery of DVI with no latency, delays or interruptions. Gefen supplies local and pass-through EDID management options to ensure a constant signal delivery from computer to display, regardless of the distance the signal must travel. Both sender and receiver units are equipped with locking power supplies.

800-545-6900; www.gefen.com; gsinfo@gefen.com



PDM is Program Delay Reinvented...



"PDM is a beautiful design with features I never knew I could get in a delay unit. It performs as good as it looks, and is backed by some of the smartest guys in the business."

-BILL TRAUE

Chief Engineer Riverbend
Communications Blackfoot ID



"We use PDM at Radio Free Europe/Radio Liberty for listener call in programs on our Radio Azadi (Afghani) and Radio Farda (Persian) language services. The device is easily programmed though a browser interface, and the front panel controls are intuitive. PDM's Livewire option let us quickly and seamlessly integrate the devices in our Axia IP based audio distribution system."

-BILL CLINE

Director of Broadcast
Engineering Radio Free
Europe/Radio Liberty Prague



"Talk about piece of mind.
On the rare occasions that
our "red button" gets pushed,
PD-Alert emails me two pieces
of audio. I can instantly hear
the "raw" version of what
didn't make it to air, and
the "clean" version that did.
25-Seven's PDM system with
PD-Alert is the decent way
to make sure your license is
protected"

-GRACE BLAZER

Program Director WTKK Boston MA



PD-Alert™ e-mails audio files so you know what happened when material is "dumped". With 90 seconds of profanity delay and transparent audio expansion/compression, the user-friendly PDM is for stations serious about protecting their licenses.

It's about time





Radio console

Audioarts Engineering

X-12 Digital: Featuring a low-profile 12-fader control surface thatis as simple to install and use as an analog console, the X-12 Digital's modular I/O design allows the use of analog or AES digital sources or a combination of these. Input channels each have selectable A/B sources, LED-illuminated on, off, and cue switches, and access to three stereo program buses. Monitoring facilities with volume control are available for control room and studio. Thereis a built-in cue speaker and a built-in headphone jack, both with their own amplifiers and level controls. In addition to the main program bus meters, there is a stereo pair of switched LED bargraph meters that can monitor a variety of signals. The X-12 Digital is also equipped with a patchable USB port for audio transfer to and from a computer or other device.

252-638-7000; www.wheatstone.com; sales@wheatstone.com

Transmitter reseller

Transcom Corp

Pre-owned transmitters: With many years of experience and service to broadcasters, Transcom provides used AM and FM transmitters and is a manufacturer representative for new antenna, cable, STL equipment and audio equipment.

800-441-8454; www.trcorp.com; transcom@amfmtv.com

Studio monitor Adam Professional Audio

A77X: The A77X features an X-ART tweeter, new woofers and amplifiers, and completely re-designed speaker cabinets. It is equipped with



the same advanced technologies as the A7X, but it produces much higher, compression-free maximum sound pressure levels and dynamics. Due to its power and radiation characteristics, it is suited for near- and midfield monitoring. The "X" stands for "eXtended frequency response" and the Accelerating Ribbon Technology has been improved in terms of frequency response that now extends all the way up to 50kHz. The A77X's two 7" woofers feature 1.5" large voice coils and powerful amplifiers. The woofers cover different frequency bands: one handles the (sub-) bass frequencies to approximately 400Hz, while the other reproduces most of the midrange

+49 30 86 30 0970; www.adam-audio.com; usa-info@adam-audio.com

Outdoor buildings Reliant Shelters

Telecommunication and Equipment Shelters: Steel reinforced pre-cast concrete buildings are suited for use as a ground mounted equipment shelter. Because the floor structure is concrete, they can be placed directly on the ground without concern for deterioration resulting from damp conditions. The six sided concrete structure is inherently secure, bullet resistant and highly resistant to vandalism.

410-676-3700; www.reliantshelters.com sales@mobilemodular.com

Transmitter site audio playback Nautel

Push Radio: Designed for VS Series transmitters, Push Radio manages audio content to centralize operations at the transmitter site. Building on the local audio storage capabili-

ties of Nautel VS transmitters and leveraging the AUI control system, Push Radio uses Internet distribution to send audio files and playlists to the transmitter, which then plays the content locally. The system will be expanded to send the as-played logs back





to the station. A scheduler automates switching audio inputs, playlists, processor or other settings based on time and date rules, while a playlist editor provides draganddrop editing. The Orban Inside audio processor provides the audio playback.

207-947-8200; www.nautel.com; info@nautel.com


MADI router

Nova29: A compact 16-port MADI router, Nova29 delivers transparent signal routing for 1024 x 1024 signals, an integral intercom function, and many easy-to-maintain features. The Nova29 can be used as a stand-alone unit with third-party equipment or networked seamlessly with Lawo on-air consoles, enabling homogenous studio networking.

+49 7222 1002 0; www.lawo.de; info@lawo.de

Audio delay system 25-Seven Systems

Program Delay Manager Version 2.0: Available in both



Livewire IP audio and standard digital/analog I/O configurations, Program Delay Manager (PDM) offers up to 99 seconds of delay protection against unwanted broadcast content while providing excellent audio performance, flexible remote control via Web browser, 8x8 GPI/O or RS-232. 25-Seven's PD-Alert system instantly emails key staff when the dump button is pressed. This alert contains separate audio files of material blocked from airing, as well as the audio that went to air, eliminating second-guessing about what was and was not aired during the incident. Version 2.0 software expands IP-based remote control capability and provides a new data delay feature to keep PAD data streams in precise synchronization with the audio delay.

888-257-2578; www.25-seven.com; info@25-seven.com

Automation system

OMT Technologies

iMediaTouch v4.2: In addition to full support of 32- and 64-bit versions of Windows 7, the iMediaTouch V4.2 release has significant feature enhancements. iMediaTouch OnAir now provides "quick links" to a variety of social networking sites, auto ducking for Liner EOM adjust, and a new audio library screen added to the blade section. Other feature additions include a new quick access library view in Log tools, Info and Backsell tabs with social networking links added to Voice Tracking, and a "Show Profiles" feature for iMedialmport that allows fully automated ingest of Internet delivered show content. OMT has also introduced new features in our iMediaArchive product designed for large radio groups and NPR stations looking to house very large SQL-based audio libraries. iMediaArchive provides Web browser-based enhanced customizable Boolean search capabilities within the database supporting such fields as composer(s), soloist(s), conductor(s), chorus, master genre and so on. iMedia-TouchArchive users can now access audio content from within the iMediaArchive library screen and insert the files right into the MediaTouchOnAir log. Users can also create, edit, delete and save play lists within iMediaArchive and then insert those play lists to any position in the iMediaTouch OnAir log.

888-665-0501; www.omt.net; omt@omt.net

Audio processor Omnia Audio





Omnia.9: Omnia.9 features separate processing cores for FM and HD-1 and (optional) HD-2 and HD-3. It also supports encoding to MP3 (Mpeg-1 Layer 3), MP2 (Mpeg-1 Layer 2), AAC, HE-AAC (including RTSP/3G for streaming to mobile phones), Ogg Vorbis and WMA Pro formats. A 7" touchscreen front panel, full remote control, on-screen keyboard, dynamically updatable RDS encoder, selectable SSB (Single Sideband) stereo encoder, and adjustable dynamic bass clipping are part of the toolkit. HTTP push support for automation, such as dynamic RDS and streaming song titles, is also standard, as well as scheduled processing preset selection by dapart. Omnia. 9 also has dual, independent power supplies and native Livewire network connectivity, in a 2RU package.

216-241-3343; www.omniaaudio.com; info@omniaaudio.com



Out and About



Live-use mics Beverdynamic

Touring Gear Series: A complete product range of more than 25 different microphones for live performance, the Touring Gear Series showcases a uniform and elegant design, top specifications, and a clear, easy to understand classification system. The four categories include: TG 30 - an entry level series for large sound on a small budget; TG 50 - high-quality and style for vocals, instruments, drums, headsets and lavaliers; TG 70 - even better technical characteristics and even higher-quality materials; TG 90-very top class especially crafted in both design and sound for the most demanding requirements on the stage.

800-293-4463; www.beyerdynamic-usa.com info@beyerdynamic-usa.com

Light tower

Night Scan: These towers extend up to 30' (vertical mounted towers) or 15' (roof-mounted towers) for up to 4x as much light Will-Burt coverage area. These towers are 42 percent lighter than other towers meaning there's not need for roof reinforcement and less weight to transport using less fuel over the life of a vehicle. The light fixtures illuminate as soon as the tower elevates to its vertical position. Full dual tilt means 50 percent of the light forward 330-682-7015; www.willburt.com; mastlite@willburt.com and 50 percent backward.

Wireless intercom system **Anchor Audio Communications/Portaco**

ProLink 500: This digital wireless intercom system is easy to configure and easy to operate. The system allows duplex communication by four users with a master belt pack and three remote belt packs. It has a 500' line of sight range, and builtin Bluetooth capability. The transmitter and receiver operate utilizing in the FCC license free 902-928MHz range for the United States without the need for a base station. The ergonomically designed belt packs have a sturdy XLR headset jack, two heavy duty antennas, headset volume control, microphone gain control, A/B channel selection and PTT or always on mode. The out of range LED indicator tells each user when to move closer to the master belt pack. A gang charger is available to charge up to four belt packs on one device.

800-262-4671; www.anchoraudio.com

Useful items at simplify remotes

PA speaker Mackie

TH-12A: Efficient Class-D Fast Recovery amplification in the TH-12A provides 400W of total system power, tuned to match the customdesigned 12" high-precision woofer and 1" compression driver. The TH-12A delivers thump,

user-adjustable three-band EQ and Mackie Active electronics. Also features mic/line input, polypropylene enclosure, pole-mounting and floor wedging, and ight weight (25.5lbs).

800-898-3211; www.mackie.com; productinfo@mackie.com



Headset mics AKG

HSC171, HSD 171, HSC 271, HSD 271: Condenser microphone models (HSC 171, HSC 271) and dynamic microphone lines (HSD 171, HSD 271) now feature closed-back earpiece design for high ambient noise attenuation and signal isolation. The 271 models are circumatral (full-size) and the 171 models are supraaural (on ear). All have a detachable cable. Each headset has a flexible microphone arm that moves through a 270-degree arc and automatically mutes the mic as it's moved up, eliminating the need for a mute button. The 271 models also feature automatic headphone muting. The microphane can be worn to the left or the right, and the microphone is shock mounted to attenuate mechanical noise and protect the capsule from damage.

818-920-3212; www.akg.com; akqusa@harman.com

Portable PA systems

JBL Professional

EON515XT, EON210P: With improved input sensitivity, lowered noise floor, added user-selectable EQ control and re-voiced system, the two-way EON515XT incorporates a JBL 2414H high-frequency neodymium compression driver and a 15" JBL 265F-1 Differential Drive

dual-voice-coil woofer with a proprietary Crown


Class Damplifier. The system has been re-voiced for better clarity and frequency balance and now delivers a 132dB maximum SPL. The EON210P includes two 10", two-way speakers, an eight-channel powered stereo mixer with four digital effects, two 15' speaker cables and a storage compartment. The mixer and storage compartment attach to the rear of the speakers. At 33 pounds, the EON210P is 20 pounds lighter than most other package PA systems in its class.

800-852-5776; www.jblpro.com; info@jblpro.com

ARRAKIS SYSTEMS INC.

Pre-End of the World Sale... 25% off !!!

the Mayan calendar predicts the end of the world in 2012 so this sale lasts until December 31st, 2011




- Fast delivery & often in Stock
- Hundreds of Configurations
- Fully Custom designs available



ACCENT is a contemporary blend of brushed metals, pleasing colors, and interesting textures. The metal structure is artfully integrated into the visible design decor of the cabinetry. Cabinetry and electronic equipment complement each other to create a bold visual environment for talent, guests, and clients alike.

Call us today at 970-461-0730 ext 309 for a free quotation



THE NEXT GENERATION ANALOG CONSOLE

- analog & digital with USB sound card modules
 - Cat5 cabling for today's infrastructure
 - Control room & Studio monitors
 - = 15 channels, 30 inputs
 - much more

MARC-15-15 MODULAR ANALOG CONSOLE

the MARC is a next generation analog console that mixes analog and digital technologies with USB PC sound card modules (on air software included). For today's cable infrastructure the MARC uses CATS cabling and RJ45 connectors (cables included).

Three stereo buses plus dual conferencing phone hybrid mix minus buses handles the big jobs.

\$6,499

conductive plastic faders and LED lighted switches for reliability. Socketed ICs for fast on site repair.

very low
profile tabletop
design & fast access
to level adjustments and cabling

CAT 5 cables for all input/output

MARC-15-12 ... \$5,499

Digilink-Xtreme Automation



Join the hundreds of others on air with Digilink-Xtreme, the best automation system in Radio. Full featured, it is easy to install, use, and maintain. Best of all, it is easy to buy. Choose from either the no contract \$100 per month 'Solutions Program' or buy 'Xtreme-Complete' outright for only \$6,500.

With the \$100 per month 'Solutions Program,' you receive Xtreme software (On Air, Production, & Scheduling) and "Bridge" hardware PLUS training, support, and upgrades for your ENTIRE radio station. You supply the PCs or we can supply them for you. For less than the cost of a good cell phone contract you can be on air tomorrow with Xtreme, the best automation system in Radio.

With 'Xtreme-Complete' for \$6,500, you purchase a complete system ready for air: DELL business PC, Arrakis 'Bridge', and Xtreme software for on air, production, scheduling, voice tracking and more. The system comes with a full year of the 'Solutions Program' with training, support, upgrades, and next business day 'Bridge' replacement if it should fail. The DELL PC comes with 3 years of next business day, on site service from DELL.

Order your system today and receive it tomorrow, call us at 970-461-0730 ext 309



Nearfield monitors Transaudio Group Sonodyne SM

The SM 50Ak is the smallest monitor in the Sonodyne range. Its active bi-amp design delivers 45W to the 5.25" woofer and 45W to the tweeter to smoothly reproduce 70 to 22,000Hz. Its aluminum enclosure and shape contribute to the sound. The next model up is the SM 100Ak, also biamplified, offering 80W to a 6.5" woofer, and the same 45W powered tweeter. The SM 100Ak delivers lowend response, a large sweet spot in front, and high SPL.

702-365-5155; www.transaudiogroup.com

High-intensity LED strobe Dialight

Vigilant L-856: This high-intensity system consists of three flash heads, three power supplies per level and one controller for the entire system. Up to 18 synchronized flash heads can be used on a tower. The three



flash heads provide 360 degree coverage. The working voltage is less than 200Vdc, which is significantly less than tradition Xenon flashtubes. The units are sealed for protection from the elements. Patented optics provide sharp cutoff to minimize light pollution and ground scatter.

800-835-2870; www.dialight.com; info@dialight.com

Audio network interface Wheatstone

Razor Blade: The Razor Blade brings WheatNet-

IP Intelligent Network connectivity to places where the cost of a full-featured blade isn't justified, or where a full Blade I/O complement isn't needed. Featuring one AES digital input, one AES digital output, and six bidirectional logic ports, it's ideal for interfacing an ISDN codec, a telephone hybrid, or any other single I/O device to the network. The front panel has two pairs of 10-segment LED bar graph meters that display the input and output signal levels. There's also a power LED and communications status LED to indicate the network connection is active. The rear panel has AES inputs and outputs on XLR connectors, a WheatNet-IP Gigabit Ethernet port, and an RJ-45 connector that carries the universal logic ports. The unit is set up, configured and controlled via Wheatstone's WheatNet-IP Navigator software.

252-638-7000; www.wheatstone.com; sales@wheatstone.com

High-Power RF "Nobody does it better!"







www.contelec.com (214) 381-7161



USB 2.0 LSlot interface Lvnx Studio Technology

LT-USB: This compact add-on card, mounted in the back of an Aurora converter, provides up to 16 I/O channels of 24-bit 96kHz digital audio or 8 channels at 192kHz. Compatible with both Mac and PC, the LT-USB is controlled via the Aurora Remote Control program that is shipped with the card, offering 16x16 mixing capabilities as well as extensive control options.

714-545-4700; www.lynxstudio.com sales@lynxstudio.com



HD Radio monitor Inovonics

INOmini 632: The INOmini 632 combines all the features of a professional grade HD Radio monitor/receiver with important diagnostic and troubleshooting tools for analog FM and IBOC FM stations. Along with essential alarms, AES digital output and balanced analog outs, the INOmini 632 is the first scalable HD Radio monitoring system, and the first Inovonics product to offer a "no blend" mode, meaning the receiver will not fall back to analog if the digital signal is lost. It can decode HD Radio multicasts up to HD8 streams, and displays PSD, RDS and RT+ tagging data. Front-panel alarms for carrier loss, digital program loss and audio loss are also available on the rear panel asially outputs

800-733-0552; www.inovon.com info@inovon.com

Emergency management software

Riverview Software Solutions

Disaster Resource Navigator: This application provides an organized method of keeping track of important information and offers quick navigation of local resources providing important services such as shelter, food, water, ice, generators and fuel. With the Disaster Resource Navigator, this information is just a mouse click away saving valuable time for the broadcast staff, listeners and viewers. The software design is based on an actual four-day disaster event that took place in Alabama in April 2011.

256-486-3397; www.riverviewsoftwaresolutions.com



Program Automation & Control is at the heart of today's broadcast facilities.

ENCO delivers Performance demanded by today's talent, engineering and management.



ENCO designs software for high Reliability required for mission critical 24/7 operations.

ENCO delivers the Best Support in the Industry with a 20+ year history under our original founding ownership.

When you upgrade to DAD or Presenter, you're assured of World Class Digital Audio Delivery System Performance, Reliability and Support. If you upgrade now, we'll convert your library at no charge using our Intelligent Conversion Engine. Call us and learn how our experience can pay off for you.

ENCO - Providing the tools & technology to positively impact your Bottom Line.



www.enco.com sales@enco.com +1-248-827-4440 **800-ENCO SYS**


Reference Room

BEYOND **POWERFUL** COMMUNICATOR'S INTERNET AGE VALERIE GELLER

Elsevier/Focal Press

Beyond Powerful Radio: Based on the successful books, "Creating Powerful Radio" and "The Powerful Radio Workbook," this combined edition provides even more methods for preparing and delivering powerful radio content. Valerie Geller explains the techniques of producing and presenting information. storytelling, news, talk and personality radio. New material is provided on: show prep, interview techniques, news, integrating radio and television, promotion and air checking techniques.

A Broadcast Engineering Tutorial for Non-Engineers: Radio and television broadcasting is the type of profession many people fall into. This book is for new hires, as well as for anyone that needs to have the basic vocabulary in broadcast. This new edition builds the previous edition by adding new standards and defining emerging digital technologies that are revolutionizing the field. Written in a non-technical fashion to appeal to trainees, managers and creatives.



Moving Media Storage Technologies

Moving Media Storage Technologies:

Complex media storage computer systems are employed to capture, store and retrieve moving media content on systems that will preserve the original integrity of the content over time and technological transition. This book provides detailed information related to the concepts. applications, implementation and interfaces of video file servers, intelligent storage systems,

media asset management services, content distribution networks, and mission critical platforms. A tutorial and case example approach is taken to facilitate a thorough understanding of the technologies, using numerous illustrations, tables and examples. The text and appendices are designed to provide easy to access valuable reference and historical information.

781-221-2212; www.elsevier.com; usbkinfo@elsevier.com

Select ons for your bookshelf reference

Music Libraries

APM Music

ReverbNation Music: An exclusive production music library supplying high-quality independent artist music via a partnership with Reverb Nation.com, Reverb Nation Music is the leading online marketing and promotion platform for over 850,000 musicians, labels, managers and venues. APM established the partnership to address issues affecting the licensing of indie music into programming and is founded upon the pillars of quality content and representation, fair price for artist and client, and freedom from worry about copyright claims.

323-461-3211; www.apmmusic.com info@apmmusic.com

Manchester Music

Manchester Music Library: Manchester Music Library is high-quality royalty free music with tracks that feel custom-scored, in genres ranging from rock, jazz and ambient to traditional classical. Music can be listened to from beginning to end before licensing. Each of the royalty free music CDs are available for instant download, and also available as a physical CD. All tracks or CDs are available in either WAV or MP3 formats.


413-369-4331; www.manchestermusiclibrary.com manchesterproductionmusic@gmail.com

Disco Funk: This collection of Disco beds features 70sstyled grooves from the dance floor. Funky rhythm guitar and bass, layered with synths, keyboards and classic drumbeats give these tracks the feel and motion to keep visuals moving along. "Disco Funk" is available on CD or can be downloaded in MP3 and WAV file formats. 888-821-7515; www.Music2Hues.com

Woodrow Wilson Center Press

Radio Free Europe and Radio Liberty: The CIA Years and Beyond: This book examines the first 20 years of the organization, policies, and impact of Radio Free Europe and Radio Liberty, arguably one of the most important and successful policy instruments of the United States during the Cold War. The book is based on extensive archival research in the United States, Germany, Poland and Hungary, as well as interviews and the author's own experiences. It uses Central Intelligence Agency materials, in part declassified at the request of the author, Johnson concentrates on the origins and role of RFE/RL in the context of U.S. national security strategy, with particular attention to the role of the CIA in covertly organizing and funding RFE/RL from 1949 to 1971. And he details RFE activities during the most important East European crises of the era ñ uprisings in Poland and Hungary in 1956 and in Czechoslovakia in 1968. The study concludes with an analysis of the factors that accounted for RFE/RL's effectiveness.

202-691-4029; www.wilsoncenter.org/press; press@wilsoncenter.org



The Perfect Combination



Available from



www.scmsinc.com 1-800-438-6040 sales@scmsinc.com

MidSouth: 1-877-391-2650

SouthAtlantic: 1-770-632-1295

1-315-623-7655 NorthEast:

Central: 1-731-695-1714

NorthCentral: 1-513-376-8600

1-210-775-2725

SouthWest: 1-513-399-3036 MidWest:

West Coast: 1-366-373-9267

Pro Audio: 1-377-540-8205

Latin America: 1-760-550-1427

Bradley Div.: 1-300-732-7665

FM Transmitters



BW Broadcast range of FM transmitters is perfect for LPFM. Offering transmitters from 1 watt to 1500 watts. BW Broadcast transmitters are reliable, efficient and full of great features. For peace of mind all our products come with our 2 year warranty.

Audio Processors




The BW Broadcast range o" audio processors are popular with broadcasters around the world. Powerful and dynamic our processors guarantee your station will make an impression on your listeners whether in FM, AM or HD.

The perfect combination for your Low Power Radio Station



www.bwbroadcast.com

bw broadcast





ARMSTRONG TRANSMITTER CORPORATION

Tel 315-673-1269 ▲ sales@armstrongtx.com ▲ www.armstrongtx.com

New Products



RF components listings RF Parts

Online catalog: A worldwide distributor for 34 years, RF Parts has released an expansion of its online catalog at www.rfparts.com. The newly expanded catalog provides an easy and efficient listing of product information, product applications and product ordering with the company's secure ordering system. The catalog lists a complete line of power tubes for broadcast, industrial and communications, including Eimac, Amperex, Taylor, Svetlana, RFP and Econco brands along with a full range of sockets through 20kW. In addition, the company stocks a large inventory of popular and hard-to-find RF transistors and power modules from Motorola, Toshiba, MA/COM, Mitsubishi and Microsemi. High-voltage doorknob capacitors and rectifiers are also stocked.

800-737-2787; www.rfparts.com

Digital MP3 recorder Olens Technology MiCorder:

This recorder converts any stereo output into an MP3 file. The Mi-Corder records onto a standard SD card and is



connected to any device with a stereo output. It features more than 10 hours life time for recording and play back from the polymer lithium-ion battery.

805-489-3636; www.olenstechnology.com info@olenstechnology.com

Equipment sales and service Mooretronix

Used equipment dealer: With more than 20 years experience in design, construction and maintenance of every configuration imaginable, Mooretronix is able to assist you in making your operation as efficient and cost effective as possible.

800-300-0733; www.mooretronix.com rrmoorejr@aol.com



IP audio encoder/decoder **WorldCast Systems**

APT Stream In/Stream Out Silver:


Stream-In Silver is an IP audio encoder features a large range of algorithms including Enhanced Apt-X, MPEG 4 AAC-HE and linear audio. The unit is 1/2 x 1RU unit, which is fully compatible with all other APT and N/ ACIP-compliant codecs. The Stream-Out Silver IP audio decoder offers headphone monitoring, audio backup courtesy of either an on-board USB port or ShoutCast server, embedded auxiliary data and auto-detection of an incoming IP stream. Incorporating Audemat's ScriptEasy software, the unit can also be utilized for remote control of other units at a remote site using TCP/IP.

305-249-3110; www.aptcodecs.com ussales@worldcastsystems.com

IP link for IPAWS

VSAT Systems

IPReady: Ka You Communications and VSAT Systems provide an IP link to the IPAWS gateway. The solution includes a business-grade satellite-based IP link that can



866-306-1328; www.vsat-systems.com; customercare@skycasters.com



Digital series FM transmitters Ecreso

Helios NextGen: Encompassing several power ranges up to 10kW, the core of this range is Ecresois new Helios NextGen, a world-class exciter

that incorporates an FM band "direct to frequency" digital modulator. Fully protected against overheating, VSWR and lightning, this digital exciter is available as a standalone modulator in 20W or 100W versions or can be combined with the new Goliath NextGen amplifiers for applications requiring higher power. For medium power applications (750W to 2.5kW), broadcasters can also opt for an integrated compact solution that combines the Helios NextGen into the new Goliath NextGen unit to reduce space, cabling and hardware requirements.

305-249-3110; www.ecreso.com; infos@ecreso.com

uddenly StudioHub!



\$100 FREE of any StudioHub+ connecting cables, adapters, or accessories with the purchase of a qualifying Radio Systems Distribution Amplifier.

> \$500 FREE of any StudioHub+ connecting cables, adapters, or accessories with the purchase of a qualifying Radio Systems Broadcast Console.

Studio Tu

StudioHub+ THE broadcast analog and digital CAT-5 wiring standard is everywhere.

NOW purchase any Radio Systems StudioHub+ ready product and get \$100.00 or \$500.00 towards any of the cables, adapters or accessories you need to pre-wire your Console or Distribution Amplifier. It's like getting a free installation!



This is your free opportunity to experience the power of StudioHub+. Call your favorite dealer or Radio Systems today!

601 Heron Drive . Logan Township, NJ 08085 Phone: 856-467-8000 • www.radiosystems.com sales@radiosystems.com





Bamboo acoustic products

Auralex Acoustics

Sustain Diffusor Series:

Made from 100 percent ecofriendly bamboo, the Sustain Diffusor Series includes the WaveArray, WaveCoupler, Quadratec, Peak Pyramid Diffusor and KeyPacs. WaveArray eliminates flutter echoes and other acoustical anomalies. WaveCoupler's open-boxed design scatters

and redirects acoustical energy. Quadratec Diffusor's tiered design provides scattering, resulting in a warm, musical character to the dispersed sound. Peak Pyramid Diffusor provides high quality sound diffusion while also doubling as an effective bass trap when filled with absorptive material. KeyPacs are magnet-based panels that have the ability to mount to Auralex ProPanels or Studiofoam. Since most rooms are not dedicated to one particular application, these perforated absorption covers allow users to have a more live or dry room on the fly without having to reconfigure the entire space.

317-842-2600; www.auralex.com auralexinfo@auralex.com

Ethérnet control surface

Radio Systems

Millenium Console Platform: Available in 8- and 12-channel versions, Millennium Consoles The Platform is 100 percent IP. All devices are Ethernet connected. Multiple surfaces, screen-based clients and remote setup and control screens all connect by LAN, WAN and the Internet. Each channel features a select key, four program buses, solo bus, send bus, fader, conference, talk, record and cue buttons, rotary encoder that selects any Platform source displayed on the two-line LCD to the channel strip and calls a list of auxiliary sources available via the center pushbutton knob, option button that sends selected source directly to studio monitors and metering scenes, take button selects a new source to the channel and activates functions called by the option button. The Platform's 7" LCD touchscreen provides access to the home screen and auxiliary input/output screens. The system is supported by an external frame that houses the system DSPs, input/output channels, GPIO interconnects, and connectivity to Ethernet and USB transports.

856-467-8000; www.radiosystems.com sales@radiosystems.com

Field strength program

RF Software

RF Investigator v3: The most obvious change in this version of the software is a new button on the tool bar. This button selects AM or FM studies from the same program without the need for additional software. Multiple monitor support allows the user to move the various windows as he likes to more efficiently display the data and control functions. Maps are resizable to a rectangle. The entire map display can be easily copied and pasted into another application, such as a word processor or graphics editor.

352-336-7223 www.rfsoftware.com; alex@rfsoftware.com



BROADCAST FURNITURE





The Engineer's Choice



Choose Omnirax for your next project, and we guarantee you'll become a customer for life!



Made in the USA since 1985

We'll make your "furniture headache" go away! Call for your free CD Presentation


P. O. Box 1792 Sausalito, CA 94966 800.332.3393 415.332.3392 FAX 415.332.2607 www.omnirax.com info@omnirax.com

www.RadioMagOnline.con



partnership with Broadcast Devices, Smart Switch is an update for the ERI line of motorized switches. The Smart Switch allows an Ethernet cable connection for control and status when connecting an ERI switch to an ERI ACS-100 switch controller and the PWR-100D power sensor and directional coupler. This allows for complete SNMP connectivity between this family of ERI/BDI products for monitoring and protection of RF systems for a simpler and cleaner installation versus the traditional methods that use multiple wires and significant installation labor. The system adds RF sensing to prevent the switch from moving while RF power is applied


> 812-925-6000; www.ERlinc.com sales@ERlinc.com




FM+HD audio processor Vorsis

AirAura: The AirAura provides extensive measurement of pre- and post-processed audio, allowing the user to visualize in real time exactly what the processor is doing. Details such as when and how the AirAura clipper's distortion management system is operating, and the dynamic range in each part of the audio spectrum are viewed via dual front panel widescreen displays that show detail about the processor's operation. In addition to real-time measurement of input, output and RMS output levels, its comprehensive metering also shows all gain reduction activity. The AirAura also offers extensive remote control via wired 10-100BaseT Ethernet and on-board 802.11G wireless

> 252-638-7000; www.vorsis.com sales@vorsis.com





Web: http://www.acousticsfirst.com



K-Sun

Green Machine: This label maker features 50 percent recycled plastic cartridges that are recyclable/returnable, auto power shut-off, and meets a variety of environmental directives. Choose from numerous font styles and seven backgrounds for custom designs. Label design preview eliminates errors and wasted tape. Other features include: six bar code formats, 60 sizes/colors of industrial-strength polyester adhesive tape, 11 heat-shrink tube sizes/colors and 1 size/color of wire-wrap.

Auto-tape size detection saves time/waste. Flash memory holds 99 files/5,000 characters and requires no hazardous storage batteries. Use repeat and mirror printing to save time, enlarge printing for sectioned labels up to 4" high, use the built-in printer handle for field work and an international ac adapter will work anywhere in the world.

800-622-6312; www.ksun.com; info@ksun.com

Grounding wire Nott Ltd.

Copperweld: Not now distributes Copperweld grounding wire. This wire has been used by the electric utility industry for many years and just now comes to broadcasting. Standard Copperweld wire is not annealed. making it very springy. However, the ground wire is annealed and handles just like pure copper wire. It can also be silver soldered like pure copper. Tests indicate erosion may occur at the ends of buried wires but will go no more than two wire diameters into the metal. In the case of #10 wire. this is less than 1/4". RF current travels only on the outer surface of a wire

due to skin effect, so most of the current will be flowing in the copper skin. Bending it into a sharp radius does not cause the copper skin to crack. Wrap it as tightly as needed, then silver-solder it.



Mixing control surface Logitek

Pilot: Available in multiples of six faders (from 6 to 24), the Pilot offers full access to the sources available on a Jetstream or Audio Engine router along with simple bus selection and intuitive monitor controls. The Pilot, combined with the Jetstream Mini, provides a cost-effective way for facilities to implement IP audio routing and mixing. Features include: cue switch over every fader with built-in cue speaker; room for 16 character source names on bright, wide-angle displays; change button over every channel and central select knob for easy access to new sources; 12 user-configurable soft keys; quick route button for selection of program, auxiliary and two user-defined sources for monitoring; buckets full of mix-minus; four GPI inputs and eight GPI outputs on back of surface along with RJ-45 for connection to audio engine; simple tabletop mounting and 20W power consumption.

800-231-5870; www.logitekaudio.com info@logitekaudio.com



OUTSTANDING specifications and pricing on professional quality receivers for EAS, monitoring and translators.

The AFC3 is a three receiver rack mount that is configured to your EAS or monitoring specific application. Each receiver has internal frequency selection (PLL) switches, front panel controls and indicators, and rear panel connections.



Price: Approximately \$1,300 (depending on receiver choice)

Select three receivers from our FM or FM/SCA, NOAA Weather, Public Service and/or AM Monitor/Receivers. All receivers are PLL (synthesized) designs using the latest state of the art components and are available as stand alone receivers as well as in AFC3 combinations.

DAYTON INDUSTRIAL CORPORATION

2237 Industrial Blvd., Sarasota, FL 34234 Tel. (941) 351-4454 Email: sales@DaytonIndustrial.com WebSite: www.DaytonIndustrial.com

Quality Receivers Designed and Manufactured in the USA since 1980



Advanced Waffchman monitor/alarm

Coaxial Dynamics

81094: The Model 81094 is the first in a series of Internet/intranetaccessible Advanced Wattchman wattmeter/alarm systems that will monitor forward and reflected power

in two transmission lines with only one controller. The front-panel display shows power on both systems simultaneously. Operating conditions may also be displayed on a PC from any location on the Internet/intranet. The Model 81094 is designed to work with a series of specialized line sections from 7/8" to 6-1/8" and standard Coaxial Dynamics elements for analog or digital applications. Elements are available from 1W to 100kW and from 2MHz to 2.3GHz.

800-COAXIAL; www.coaxial.com; sales@coaxial.com

Talkshow system

Broadcast Bionics

PhoneBOX VX: Broadcast Bionics is now a software development partner for next-generation Telos phone systems. PhoneBOX VX is a scalable, SIP-based talkshow system that integrates directly with Telos VX systems to manage and integrate callers, e-mails, SMS and control of ISDN and IP codecs into a single converged system. This gives talent comprehensive control of interactive audience participation such as listener polls and competitions. It integrates with Axia networks and consoles.

+44 1444 473999; www.phonebox.com; info@phonebox.com

EAS encoder/decoder

Sage Alerting

Digital Endec: The Digital Endec incorporates the latest developments in DSP and other digital techniques. It uses an



Internet connection to allow remote, secure activation, system monitoring and uploading of software releases and redundancy. Its network-centric design allows logging, printouts and control and automation interface via a network or Internet connection. It now has text-to-speech capabilities and will be fully compliant with the FEMA-specified CAP 1.1 standard.

914-872-4069; www.sagealertingsystems.com; info@sagealertingsystems.com

Air-cooled FM transmitter Harris


Flexiva: This VHF FM solid-state transmitter provides radio broadcasters with a single platform to support analog and alobal digital standards.



FM. FM+HD Radio, HD Radioonly or DRM+ digital broadcasting, while the transmitter incorporates Harris Real-Time Adaptive Correction (RTAC) technology to optimize power and minimize adjacent-channel interference. Flexiva transmitters are built on the legacy of Harris radio broadcast transmitters, including the ZX Series and its efficient power supply, cooling and control designs. Available in power levels up to 20kW, Flexiva transmitters also leverage Harris PowerSmart technology to create a compact, cost-efficient transmission solution with high power density and low operating costs.

800-622-0022 www.breadcast.harris.com broadcast@harris.com





Sabre designs, manufactures and installs towers to meet your broaccast specifications. We offer everything from custom FM support sections to turnkey AM installations. Committed to customer service, we deliver quality products at competitive prices with the shortest lead times.

Call Sabre today for all your tower needs.



1-800-369-6690

broadcastsales@sabrecom.com

CAP-DEC 1

CAP-to-EAS decoder system

Gorman-Redlich

CAP-DEC 1: This standalone unit translates received CAP alerts into EAS headers, which will be transmitted by current EAS equipment in the same manner as they already are. Features include: RJ-45 Ethernet LAN connection for network/Internet receipt of CAP alerts; RS-232 Serial connectivity with Gorman-Redlich EAS units for fast alert transmission of CAP-to-EAS translated alerts; frequency shift keyed (FSK) output of CAP-to-EAS translated alerts for compatibility with a wide range of legacy EAS equipment; monitors up to three CAP alert server URLs (expandable for additional monitoring); internal logging of CAP-to-EAS translation activity: internal storage of received CAP alerts and attached audio files; ability to log activity to USB or network printer; ability to send activity logs via email; text-to-speech converter to generate alert audio if no attached audio is present with the received CAP alert.

740-593-3150; www.gorman-redlich.com; jimg@gorman-redlich.com

On-air warning lights

Sandies

Warning lights: Sandies' bright red, back-lit on black letters will keep staff informed. Dimensions are: 5"H x 10"W x 2-1/2" D. These warning lights are 110V and use two 7W bulbs. The text on the lens reads On Air. They are available in 12- and 24Vdc as well as custom text/foreign language by special order. Sandies also has a three-sided on air light that measures 5"H, 31/8"W, 23/8"D.

215-547-2570; www.sandiesusa.com; service@sandiesusa.com

Video IP codec

Comrex

LiveShot: Weighing in at less than five pounds, the compact LiveShot will attach to a professional camera's battery mount and will get on the air with live, real-time, low-latency video and audio optimized to perform well on challenging 3G/4G cellular and satellite IP data networks. Live-Shot also accommodates Wi-Fi and wired IP data connections and offers a store-and-forward feature that will capture, manage and send higher-resolution video to an FTP server when a live shot is done. Video return, integrated IFB, Wi-Fi and Bluetooth interface are just a few of the additional features. The





codec can be controlled and configured locally or remotely via the Comrex LiveShot Central server.

800-237-1776; www.comrex.com; info@comrex.com

new HIGH EFFICIENCY **TRANSMITTERS** series

NEWS:

- Efficiency up to 84%
- . TFT Screen & Touch Keyboard
- Consumption optimization & noise decrease by means of the speed control of cooling fans
- Remote control & Telemetry



SERIES:

- EM 1500
 - EM 9000

EM 12000

EM 3000





3100 NW 72nd. Ave. Unit 112 · Miami, FL — 33122 USA · www.omb.com Pol. Ind. Centrovía · C/Paraguay, 6 (La Muela) · 50198 Zaragoza (Spain)



Tower manufacturer/ installer Sabre Towers

Towers: Sabre designs, manufactures and installs towers to meet broadcast specifications. The company provides guyed towers in sizes ranging from a 12" face tubular lightweight tower to an 84" face solid round knock down tower. Sabre offers everything from custom FM support sections to turnkey AM installations.

800-369-6690 www.sabretowersandpoles.com

On-air lights CBT Systems

Value, Style: Value shares the same dimensional footprint as the case aluminum Classic, but will be available at a reduced price.

Value is manufactured from polished formed aluminum.

Additionally, LED illumination is also now available for Value and the full line of CBT Systems on-air lights. Style takes on-air lights feature a stylized design and highly polished solid cast aluminum chassis. On-air and recording legends will now be standard in blue, red and black. All CBT Systems on-air lights are UL listed and available in 120 to 240Vac and 12Vdc models.

858-536-2927; www.cbt-net.com; info@cbt-net.com

Right-angle RJ45 cable L-com Global Connectivity


TRD815RA: TRD815RA, TRD815RA2 and TRD8 1 5RA3 feature patent pending channelized right angle pair guide and load bars, which give the cables a true Cat 5e rating. TRD8 15A features one straight plug and one right-angle plug with the key on the bottom; TRD815A2 features one straight plug and one right-angle plug with the key on the top; and TRD815RA3 features two right-angle plugs with the keys on the bottom.

800-341-5266; www.l-com.com sples@L-com.com

Studio automation system **Broadcast Software International**

Op-X: Op-X was built from the ground up and has been designed for both intuitive operator interface and ease of maintenance. The system has been in fulltime operation at more than 30 stations nationwide for the past 18 months, as product features have been enhanced and real-life testing has proven successful. The system features clock-builder and time-bending functions, as well as a satellite interface.

888-BSI-USA1; www.bsiusa.com info@bsiusa.com



Broadcast Furniture

Graham Studios

Call GRAHAM STUDIOS or your DEALER today. | (866) 481-6696 | www.graham-studios.com



Analog, digital translator Armstrong **Transmitter**

TRX-HD series: De-

signed to transition a translator station from analog-only broadcasting to digital, the TRX-HD receives an FM station's entire signal payload over the air, including its HD Radio digital component. The signal content is transferred to the TRX-HD transmit side for retransmission on the translator frequency. The TRX-HD10 provides 10W in the hybrid digital mode, the TRX-HD50 provides 50W hybrid digital, and the TRX-HD100 is a 100W hybrid digital translator. Higher hybrid power levels are achieved by adding an Armstrong solid-state amplifier.

315-673-1269; www.armstrongtx.com; sales@armstrongtx.com

Equipment sales and service

Progressive Concepts

Broadcast equipment dealer: Founded by Eric Hoppe in 1990,

Progressive Concepts is a broadcast equipment supplier with its sales office and warehouse in the Chicago area. Progressive Concepts has provided its customers with high-quality products and services for 20 years. The company's philosophy is that the products it sells are of such high quality that there will be no reason to return them. Some items sold feature an exclusive 30day no-fault guarantee, so items can be returned for a full refund.

630-736-9822; www.progressive-concepts.com sales@progressive-concepts.com

RBDS subcarrier generator **OMB** America

RDS 5000: The RDS 5000 implements a radio digital data system to be used in FM stations. The most advanced technology is used in the design of this new transmission system, really useful for all radio stations. The RDS 5000 is easy to program and install, and it is able to transmit 50 words of eight characters each. It provides other parameters like time, data; TP, TA and M/S remote controlled functions; PTY (type of program management) and radio text management. The RDS doesn't disturb the audio signal. All necessary software is included.

800-662-4872; www.omb.com/en; usa@omb.com

Radio console network

Arrakis

AARC-NET: One of the important features of AARC-NET is that it integrates standard analog and digital consoles onto the network. Consoles already owned can be integrated into the system. AARC-NET is world standard CobraNet, not a custom one-of-a-kind network. Features include Ethernet audio networking, and cable and punch block replacement with one CAT-5 cable. It altogether eliminates or reduces the need for stand-alone routers, distribution systems, and long multi-pair cables, as well as the time and expense for configuration, maintenance and installation for traditional wiring.

970-461-0730; www.arrakis-systems.com; sales@arrakis-systems.com



The ASI5211, Not another dumb card. With a microphone input, including a low noise pre-amp and 48V phantom power supply, on-board DSP. increased analog I/O level of +24dBu and a new GPIO that adds two opto-isolated inputs and two normally open relay outputs, the ASI5211 is one smart card. And considering it's priced the same as cards without all these features, it's one smart choice, too. For information, call +1-302-324-5333 or email salesasi@audioscience.com

ASI 5211 features:

- · +24dBu balanced analog and AFS/FBUI/O
- 24bit A/D and D/A converters
- · 16, 24, and 32bit PCM formats
- . Up to 4 cards in one system
- . Mic input with 48V phantom power
- · Parametric Eq and Compressor/Limiter
- · 2 in. 2 out GPIO
- · Windows XP, 7 and Linux drivers

Advanced Wattchman Monitor®/Alarm For Analog and Digital Broadcasting



The Model 81094 is the first in a series of Internet/Intranet accesible Advanced Wattchman® Wattmeter/Alarm systems that will monitor both forward and reflected power in two transmission lines with only one controller. Unlike previously available systems that needed one controller for each transmission line, the Advanced Wattchman® will monitor two lines (4 ports). The front panel display shows power on both systems simultaneously. Operating conditions may also be displayed on a PC from any location on the Internet/Intranet.

It is designed to work with a series of specialized line sections from 7/8" to 6-1/8" and standard Coaxial Dynamics elements for either analog or digital applications.


Coaxial Dynamics 6800 Lake Abram Drive • Middleburg Hts, OH 44130

Phone: 440-243-1100 Toll Free: 800-COAXIAL Fax: 440-243-1101 sales@coaxial.com • www.coaxial.com



www.audioscience.com





- Modular Operation in Op-X allows for a tierec system at a fraction of the cost of it's competitors.
- Each studio client is capable of accessing all Audio Server modules on the network.
- Remote voice-tracking allows for creation of content for remote studios also running Op-X.
- The revolutionary design of Op-X's clock builder turns the previous task of scheduling satellite programming into a few simp e clicks.
- Share serial devices from any machine using the Op-X Serial Server.
- Importing logs now gets its own module that takes confusion out of the process.
- Engineers will enjoy Op-X because it's easy to install, maintain, and has automatic backup features.



AUTOMATION

SIMPLE • POWERFUL • REDUNDANT

Not since Axia audio-over-IP was introduced to the broadcast industry have we at BGS been so excited! It is with great enthusiasm we'd like to invite you to take a look at the new Op-X Radio Automation delivery system for any single or multistation cluster. Op-X's versatility allows it to operate seamlessly with either Axia IP-Audio networks or legacy audio consoles.







50W FM station in a box

Ramsev Electronics

PXB Series: LPFM and FM licensees often need a way to quickly get on the air at either temporary field locations or in the interim to their installed studio transmitter locations, Each PXB is factory prewired and

tested, and ready to go on the air the moment it is received.

The compact PXB5006D1 is specifically designed for standard domestic use or at other locations where the primary power is 110/120VAC, 60Hz. If you are looking for an export version designed for 230VAC, 50Hz overseas use, order the PXB5006E1. Features include 50W RF output continuous duty, 5-input stereo audio mixer, CD and MP3 playback, CD-R record, cassette playback and record, two dynamic mics, stands and cables, 3.4dB gain omnidirectional antenna and cable, and FCC certified under parts 2, 73 and 74.

800-446-2295; www.ramseyelectronics.com; sales@ramseymail.com

Obscenity delay

Eventide

BD600E: The BD600E offers 16 bipolar opto-isolated inputs that may be configured to drive many BD600E functions or as general-purpose delay inputs; 16 open-collector outputs that may be configured to display BD600E status indicators or to pass through delayed versions of the inputs; and an RS-232 output to provide a delayed version of the input for driving a time display or for other control purposes. The BD600E features improved audio performance and expanded obscenity delay capabilities up to 80 seconds. Other features include the exclusive panic function, which stores a .WAV file on a compact flash card to be played when the button is pressed. While the file, which may be a jingle or station ID or any other message, is played, the delay buffer is rebuilding, allowing programming to as soon as the jingle has completed. 201-641-1200; www.eventide.com; audio@eventide.com

Introducing CBT Systems On-Air Lights Made in the U.S.A.

Custom Legends Available Dealer Inquiries Welcome



858-536-2927

www.cbtsystems.tv



Weather receiver **Dayton Industrial Corp**

AF630: A NOAA weather receiver housed in a 1 RU chassis, this receiver offers a front panel that has a built-in monitor speaker with volume control. There are two 10-segment LED indicators, one for the modulation level indication and the other to indicate received signal level. The receiver has tone detector circuitry for the alarm circuit with front-panel indicator, test and reset controls. Rearpanel outputs are Line (RCA), SPKR (RCA), Relay (DIN) and balanced output (DIN). Input power is derived from a 12Vdc wall-mount converter. The receiver is phase lock loop controlled with the frequency of operation selected using an internal three-position DIP switch. A continuous receiver LINE audio output is provided. The SPKR output audio is controlled automatically by a tone detector circuit that monitors the receiver audio for the presence of a 1050Hz tone signal.

941-351-4454; www.daytonindustrial.com sales@daytonindustrial.com



Digital telephone hybrids **Telos Systems**

Hx1, Hx2: The single-hybrid Hx1 and dual-hybrid Hx2 are packed with new features. Symmetrical wide-range AGC and noise gate from Omnia automatically manages levels and EQ. Built-in auto-answer, caller disconnect detection, audio-leveling and anti-feedback routines for enhanced open-speaker applications, call screening and line-hold features, front-panel send, receive audio metering and an internal universal power supply are all standard on Hx hybrids. Other features include advanced POTS hybrid algorithms, digital dynamic EQ and adjustable smart leveler, separate EQ high and low display meters. high-contrast icon display of line status and front-panel hold button.

216-241-7225; www.telos-systems.com telos-info@telos-systems.com



SkimmerPlus

Skimming, Logging and Air Checks with ease.

SkimmerPlus Features

- Creates high-quality and highly compressed files simu tancously
- Supports multiple professional audio formats, such as PCM MP2, and MP3
- Supports recording from triggers
- · Automatically manage hard drive space
- Up to 24 record decks available
- · Individually customizable title bars and record features for each deck
- · Create and save event logs for fully custom izable unattended recording
- · Control over record break points for long-term recording
- Central skimming for multiple-station clusters

Web Server Features

- · Access mic checks from the Internet with Web Interface
- · Emailing of ftp links or audio files from Web Interface
- Supports user account creation · Easily browse recordings with an intuitive web design
- Listening to last week's records is just a calendar's click away

www.bsiusa.com

For More Information Call: 1-888-BSI-USA-1 ~ Email: sales@bsiusa.com



Gallery



www.lpfmplanet.com





PROGRESSIVE CONCEPTS 305 S. BARTLETT RD., STREAMWOOD, IL 60107 E MAIL: sales@progressive-concepts.com PHONE: 630.736.9822 FAX: 630.736.0353

Gallery



The CAP-DEC1, Gorman-Redlich is a standalone CAP-to-EAS converter for use with your existing emergency alerting equipment. This cost-effective device allows broadcasters to easily meet Common Alerting Protocol (CAP) compliance requirements mandated by the FCC without requiring the purchase of an additional encoder/decoder system or other costly

equipment. The CAP-DEC1 is CAP 1.2 compliant and requires only one unit of rack space. Trust the experts with over 35+ years experience in the emergency alerting industry to help you meet your broadcasting needs. Visit our website or contact us today for more information about the Gorman-Redlich CAP-DEC1. We continue to support equipment we made 35 years ago.

GORMAN-REDLICH MFG. CO. CAP-DEC 1 CAP-to-EAS Converter Unit



- Compatible with any existing EAS encoder/decoder made by any manufacturer
- Powerful 1.6GHz dual core processor and 1GB of memory
- Built-in text-to-speech conversion functionality
- FAST Gigabit network capability with built in firewall for security
- Options to print, store or email logs via built-in email server
- Nearly limitless storage capacity for logs and audio messages

- Five (5) USB ports for peripherals
- Automatic clock synchronization via NTP servers
- Software can be updated via LAN or USB
- Print alert reports to USB or network printer
- Polling 3 URL's currently with room for future expansion
- FEMA independent lab affirms CAP 1.2 compliance
- Built-in email server to send log information

Gorman-Redlich Mfg. Co. www.gorman-redlich.com 257 W. Union Street, Athens. OH 45701 Phone: 740-593-3150

nott ltd

3801 La Plata Hwy Farmington, NM 87401 Phone 505-327-5646 Fax 505-325-1142

Folded Unipole



Antennas

Detuning Systems



Gilastat Lighnimg Dissipation Systems




Nello Towers

Radian/Rohn **Towers**

www.nottltd.com info@nottltd.com

Broadcast Engineering Propagation Software



Professional software packages for FCC applications and predicting coverage.

- Create stunning "real-world" coverage maps and interference studies using Longley-Rice, TIREM, ITU-R P.1546-1. PTP, FCC and others with Probe 4™
- Search FM channels under spacings and contour protection using FMCommander™
- Prepare AM skywave and groundwave allocations studies and map FCC contour coverage using AM-Pro 2™
- Plot STL paths and coverage over 3D terrain with Terrain-3D™



The leader in broadcast engineering consulting software.

www.v-soft.com

800 743-3684

Disaster Resource Software for the Broadcast Industry

PRICE \$1350



Disaster Resource Navigator

Radio and TV broadcasters can provide a critical role in furthering the safety of life and property during disaster situations; including tornadoes, hurricanes, ice and snow storms, floods, widespread power failures, etc; by quickly informing the public about the post-disaster services that are available.

This software application provides an organized method of keeping track of important information and offers quick navigation of local resources providing important services such as shelter, food, water, Ice, generators and fuel. With the Disaster Resource Navigator, this information is just a mouse click away saving valuable time for the broadcast staff, listeners and viewers.

BE PREPARED FOR THE NEXT DISASTER

Riverview Software Solutions, LLC 256-486-3397 www.RiverviewSoftwareSolutions.com



Our 11th Year

Our client list continues to grow. Thank you for your confidence and equipment purchases.

We Re-Condition

Pacific Recorders BMX I-II-III, AMX, ABX and RMX, Stereo-Mixer and Mixer News-Mixer products.

We Have

Replacement Wind Screens and Blast Filters for the SM-5B microphone.

We Repair & Re-Crystal

STL Transmitters, STL Receivers, and RPU equipment.

See the "News-Update" page at our website.

Tel: 800-300-0733 Fax: 231-924-7812 WWW.MOORETRONIX.COM

E-Mail us at: rrmoorejr@aol.com

Fine Used AM & FM Transmitters Authorized Representatives for all major equipment manufacturers

USED FM TRANSMITTERS

BE Fml1405 (XPl10 & Idi10), solid state 14+5 KW HD 2005 BE FM20S, solid state 20 KW 2005 30 KW 1996 QEI FM 30,000B Continental 816R-5C, solid-state IPA 35 KW 1998

USED AM TRANSMITTERS

2005 Harris DX10 10 KW 1986 Nautel Ampfet-ND10 60.KW 2000 Nautel XL60

Please see our current listings on our website









Crown Broadcast

TV Transmitters- Analog and Digital

Used FLO TV Transmitters **Rohde & Schwarz**Harris Maxiva New TV Transmitters- Analog and Digital OMB, Pineapple and Technalogix

VHF and UHF TV Antennas (10 W to 10 KW) TV STL

citers & Miscellaneous Equipment *New* 30W Synthesized exciters

(2008) BE FM100C exciter, new, never used BE FXi250 FM & HD exciter with **EXGINE** card

BE XPi 10, HD Generator **Bird Wattmeter with Elements** Orban Optimods 8200, 8100XT, 8100A BE FC30, SCA Generator

Please visit our web site, www.fmamtv.com for additional listings or CALL US FOR A QUOTE!

2655 Philmont Ave. Suite 200, Huntingdon Valley, PA 19006 800-441-8454 215-938-7304 Fax: 215-938-7361

WATTS to KILOWATTS



Transmitting & Audio Tubes Semiconductors

Taylor Eimac *Amperex* MA/Com



Motorola Toshiba Thompson Mitsubishi

Se Habla Español

· We Export

760-744-0700 • 800-737-2787 Fax: 760-744-1943

www.rfparts.com



FCC Certified FM Stereo Transmitters



GET ON-THE-AIR, STAY ON-THE-AIR!

- ✓ 50W RF output continuous duty!
- Auto protect, auto soft fail, auto restore!
- Automatic battery backup!
- Digital display of all parameters!
- ✓ Simple to install!

What's the bottom line? To stay on the air! The PX50 was designed with that in mind! Auto monitoring of all parameters, with automatic power reduction and restore on VSWR and temperature errors! No more down time AND no more trips to the tower site! Plus the PX50 is FCC Certified under parts 2, 73, & 74 (PF3PX50) and Industry Canada approved (IC: 4318A-PX50) so you never have to worry about non compliance! Make your life easy with the PX50 from Ramsey!

THE ORIGINAL. "STATION-IN-A-BOX"

Since the introduction of our 'Station-In-A-Box" hundreds have een put in service worldwide! From temporary locations, rapid deploy-

nent installations, to emergency broadcast facilities, there is no quicker way to get on the air!

Custom designs include full audio production and control, record and playback of CD's, CD-R's, MP3's, MD's, and cassettes. Quick deployment antennas with LMR cable make installation a breeze. When you simply have to get on the air anywhere, rely on the proven and original "Station-In-A-Box" from Ramsey!

Your low cost solution to monitoring audio and EAS receivers! EAS Received: 2/19/2009 7 26:12 AM

Whether providing scheduled, detailed, dead air reports for local management, or as it's currently being used to monitor one of the industry's largest satellite teleports, The Studio Hawk is a power-packed product exceeding expectations.



Gallery





ADVERTISER INDEX

Advertiser's Name Pag	ge #	Advertiser Hotline	Advertiser Website
25 Seven	17	888.257.2578	www.25-seven.com
Acoustics First			
Adam Audio	15	516 681 0690	www.adam-audio.com
Armstrong Transmitter Corporation			
Arrakis Systems 21, 22, 23, 43			
AudioScience			•
Broadcast Bionics	32	+44 1444 473999	www.bionics.co.uk
Broadcast Software Int'l 37	7, 39	888-BSI-USA-1	www.bsiusa.com
BW Broadcast	27	866-376-1612	www.bwbroadcast.com
CBT Systems	38	858-536-2927	www.cbtsystems.tv
Coaxial Dynamics	36	440-243-1100	www.coaxial.com
Comrex	5	800-237-1776	www.comrex.com
Continental Electronics	24	800-733-5011	www.contelec.com
Dayton Industrial Corporation			
Digital Alert Systems			
Enco 1	, 25	800-ENCO-SYS	www.enco.com
Eventide			
Gorman Redlich			
Graham Studios			
Henry Engineering			
iMediaTouch			
Inovonics			
JK Audio			
Logitek			
Mooretronix			
Not Ltd.			
OMB Broadcast			
Omnirax			
Progressive Concepts			
Radio Systems			
Ramsey Electronics			
RF Parts			
RF Software			
Riverview Software Solutions			
Sabre Industries			
Sage Alerting Systems			0 ,
Sandies			
The Studio Hawk			
Transcom Corp.			
V-Soft Communications			
VSAT Systems	11	866-306-1328	www.vsat-systems.com

This index is a service to readers. Every effort is made to ensure accuracy, but Radio magazine cannot assume responsibility for errors or omissions



NEW~WAVE Automation

NEW WAVE

NEW WAVE

Part day case

948:57 AM

Windows 7

compatible

the BEST automation in Radio... period!

Introductory Sale

\$ **75 0**

Perfect for Broadcast & Internet 3 play... On Air Live, Automate, & Cue Simultaneous Recording for Production Voice track recording for perfect Automation Powerful Music scheduling
Supports Traffic & Music imports
ROS and Streaming service interface
Easy to learn and use & Autofills empty hours

NEW~WAVE is a Windows PC based software solution for today's and tomorrow's professional radio applications. It is designed specifically for playing audio files from hard disk, internet streams, FTP stored audio files, MP3 players, smart phones, text to speech, and much more. NEW~WAVE brings together all of the newest technologies to produce an exciting show for your radio audience. Play live broadcasts, automated broadcasts, podcasts, and stream for internet radio... all at the same time. Most important, NEW~WAVE is quick to learn and easy to use. Designed for both novice and professional alike, it has the simplicity required to get to air quickly and yet the sophisticated features for advanced users. Highly fault tolerant, NEW~WAVE will not allow dead air in automation. Also, if connected to an Arrakis 'Advanced Radio Console' (ARC series), the console and software merge to complete a powerfully integrated radio workstation. NEW~WAVE supports the Windows 7 operating system.

Order your system today, call us at 970-461-0730 ext 309

ARRAKIS SYSTEMS INC.



ACCENT is a contemporary blend of brushed metals, pleasing colors, and interesting textures. The metal structure is artfully integrated into the visible design decor of the cabinetry. Cabinetry and electronic equipment complement each other to create a bold visual environment for talent, guests, and clients alike.