BIG SAVINGS OVER OTHER CATALOGS

#### SPECIAL 100 WATTS MUSIC POWER POWER LOUDSPEAKER STOCK NO. AD1255/HP PA and Guitar Speakers 10,000 GAUSS

Res., 15-7,500 CPS. 12 inch, 2th.. T7-Alnico Magnet

8 ohm . 2 inch VOICE COIL.

AD-1255/HP Speaker is constructed to handle higher wattage than average speakers. It will carry up to 100 watts MUSIC power. Norelco is one of the best Public-Guitar speakers we can sell. The voice coil is wound in a self-supporting form and highly impregnated to prevent burn out and off-centering. This is the SPEAKER where high quality and performance is needed.

Has Whizzer Cone 44 THE CHA For Highs

> OUR STOCK NO. AD 1255/M7

THE FAMOUS 5200M 12" TWIN-CONE **FULL-RANGE** 

SPEAKER THOUSANDS SOLD FOR \$39.95

4 99 2 For 12 134,000 Maxwell 11,000 Gauss \$47.50

The 520M Norelco has been called the finest full range speaker ever built regardless of price, by many speaker experts. Has 2 bs. of T-7 Almico magnet which is the very finest magnet material, and approximately 30% stronger than our generally used Almico 5. The superiority of this speaker is in part, by the aluminum wire voice coil, which helps the mid-ranges. Free air response is below 50 cycles and goes easily to 15,000. Not many do, but if you wish you can add a tweeter, when this fine full range 5200M first was brought into US A, It was sold as high as \$70,00. We sold thousands at \$39,95. McGee price \$24,99, 2 for \$47.50.

Fr eq.

AD 7065/W8 BEST VALUE 6½ inch 1", 8 ohm,

**VOICE COIL WOOFER** 



HIGH-OUALITY WOOFER resonance frequency 28 hz 8 ohm VC 1 lb magnet AD7065 W8

NORELCO, WORLD'S BEST 61/2

\$ 795 TWO for \$15.00

WORLD'S BEST VALUE 10" FULL RANGE 10 INCH TWIN-CONE NORELCO SPEAKER



**10** INCH FULL RANGE

11/4", 8 ohm VOICE COIL

18 oz. of T7 TICONAL MAGNET WHICH IS 33% STRONGER THAN ALNICO-5 MAGNET.

STOCK NO.

Whizzer cone AD 1050/M7

Whitzer cone 525.00 Model AD 4000M, Norelco 10' full-range high quality, high-fidelity apeaker. Probably the best 10" speaker value in America. Rated at 10 watts power handling. Ticonai magnet, 98,000 maxwells total magnetic flux. 8 ohm voice coil at 1 kHz. Resonance frequency 50Hz Constant voice-coil impedence throughout the entire frequency range, so that the output always has a perfectly matched load. Very smooth response curves.

Clear bass response without boom effects, because of

Clear bass response without boom effects, because of mechanical damping at low frequencies. Resonance frequency 50 Hz.

AD 8065 / W8 1971

8 in HIGH-QUALITY WOOFER

HEAVY DUTY 8-INCH WOOFER OLT MIVOICE COLL, 19: OLT MATCHES OUR AD-0160/T8 2-WAY NETWORK, BEST SPEAKER R A TEN DOLLAR BILL, WT. 488 35 Watts 0 50 100 200 300 900Hz T

NEW - 1072 - HEAVY DUTY WILD WOOFER SPEAKER OIL, 20 OZ., 'ALNICO 5 MAGNET 2 inch

T STRUCTURE

PRICE

eav

\$ \$4.00 to KIT price for THRIFTY -3 KITS PHONE: AREA (816)- 812-5092

ZIP CODE, 64108

SEE INDEX ON INSIDE LAST PAGE

If undeliverable as addressed

DO NOT RETURN

Page 147

BULK RATE U S POSTAGE PAID Kansas City, Mo. Permit No. 667

E

# FINEST AUTOMATIC TURNTABLES FOR OVER 50 YEARS

1c SA YOUR CHOICE SHURE OR PICK CARTRIDGE FO



\$134.50 With Shure MalE Cartridge, (Less Base) \$6.50 Extro New Synchro-Lab Motor provides

flawless, silentsynchronous speed. Low-mass tonearm of Afrormosia wood set into aluminum, floats virtually fric-tion free in a gyroscopically gimballed

mounting. Fully adjustable counterweight. Fully damped, single control cueing. Viscous damped slow descent of toncarm during manual and automatic play. Exclusive two-point record support at center and edge during automatic play. Permanently accurate anti-skating control of patented sliding weight design. Stylus pressure gauge with window scale. Slide in cartridge clip. Full size turntable. (less have and cartridge) \$129.50



2 SPEED AUTOMATIC TRANSCRIPTION TURNTABLE

With Shure M91E (Less Base) \$ 1899e

- Magnetic Anti-Skating Control Toncarm Safety
- Restrictor Illuminated Strobascope
- Rotating Manual Spindle 12" Turntable, Matched & Balanced To Garrard's Synchro-Lab Motor
- . Convenient Control Tabs
- 33-1/3 and 45 RPM Zero Tracking Error Advance Pivotry For Minimal Friction On The Tonc Arm

Adjustable

Ship. Wr.

Automotic Record Cleaner



sl65B chro-Lab Motor guarantees perfectly constant synchronous record speed, unwavering musical pitch. Low-mass, tubular aluminum tonearm dynamically balanced with adjustable countertonearm dynamically balanced with adjustable counter-weight. Record support overarm moves to rear when playing single records, Slide-in cartridge elip assures positive rigid arm alignment. Fully adjustable anti-skating control. Viscous damped, single lever cueing protects stylus and records. Turntable of heavy alumi-num meticulously balanced and oversized for record support Precision stylus pressure gauge with optical scale. The ideal turntable for a major percentage of fine music systems. Sess base and cartridge) \$79.50



B) Bose \$5,50 Extra New, redesigned version of the exceptional automatic turntable featured in overwhelming majority of all music tems preselected and featured by 'ers. For the first time in a unit of ous damped, single lever cueing, minum tonearm with fixed isolated in cartradge clip assures positive any to adjust stylus pressure control ig-away overarm moves to the rear. manual play. Two interchangeable itive trip. Oversize turntable with it. Compatible with fine amplifiers. 48. (less base and carridge) \$44.50

\$64.50 with Shure M93E that brings flawiess, silent synchronous speed and viscous damped cucing to medium cost music systems. Record support overarm swings to the rear, out of the way, when playing a single record, light weight, tubular aluminum tonearm with fixed-position damped counterweight and slide-in cartridge clip provides excellent tracking capabilities for the latest, high compliance cartridges. Built-in stylus force adjustment and optical scale. Viscous damped, single-lever cueing affords convenience and record stylus protection. Fully adjustable anti-skating control. Oversized turniable with



records to be intermixed in size; one piece east alumi-num tonearm; simple, accessible stylus pressure adjustment, two interchangeable spindles; super-sensitive of Dupont Delrin to offset friction. Heir haie) \$3









COMPLETE s99.50

A superb instrument with the most advanced Garrard automatic turntable features, Revolutionary, new Synchro-Lab Motor guarantees perfectly constant record speed. unwavering musical pitch. Exclusive two-point record support at center and edge, during automatic play. Stylus force adjustment with window scale Pencil-thin ultra-low-mass libutar aluminum tonearm meticulously balanced for correct tracking. Fine stereo magnetic cartridge with elliptical diamond stylus. Permanently accurate sliding weight anti-skating control. Fully damped, single control cueing. Viscous damped slow descent of tonearm during manual and automatic play.

Diamond Stereo magnetic MODULE AUTOMATIC TURNTABLE

SLX-2 WITH WAGNETIC CARTRIDGE BASE

Incorporates quality leatures for which Garrard is lamous including the brilliam Synchro-Lab Motor which provides the definitive advantage of silent synchronous speed under all operating conditions. Specially selected, pre-installed magnetic cartridge with high compliance diamond stylus assembly. Ultra-low-mass tubular aluminum tonearm with counterweight, provides perfect dynamic belance. Ball bearing prvotry. Built-in stylus pressure adjustment. Unique, swing-away overarm moves to rear, out of way, for playing single records manually. Oversized turntable with distinctive aluminum trim ring. Single lever cueing and pause control.

## MODULE $\chi$ -10 MODULE $\chi$ -11

COMPLETE WITH CERAMIC CARTRIDGE.



PRECISION AUTOMATIC MODULE TURNTABLE WITH MATCHED STEREO GERANIC CARTRIDGE BASE AND DUST COVER

55250

A complete 3-speed record playing source, ready to plug in and use. The X-10 has a first quality sterior ceramic cartridge with high compliance litip-over diamond stylus matched to the utira-low-mass tubular aluminum tonearm. Correct stylus force is pre-set for excellent tracking. Single lever control for convenient cueling and pausing in automatic and manual play. "Swing-away" overaitm moves out of the way when playing single records, Oversize turntable with decorative mat. Simplified apped/size controls. Plays 7", 10", 12" records at 33%, 45 or 78 rpm.



Xell 'DEMI"

\$39<sup>95</sup>

4-SPEED AUTOMATIC TURNTABLE WITH STERED CERAMIC CARTRIDGE BASE AND DUST COVER COMPLETE \$39.95

45 RPM

Here's a miniature but excellent automatic record changer that's just perfect for the young at heart. It's small enough to fit on a bedside table or small shelf. "Swing-Away" overarm steedies a stack of 1 to 5 records in automatic play... moves out of the way, when you play single records manually Professionally inspired tubular alluminum tonearm of advanced design, precisely balanced for correct tracking Fine stereo caramic cartridge pre-installed with flip-over diamond LP stylus. Automatic control tocks and unlocks tonearm automatically from its rest. Automatic shut off.

Stylus-Diamond-.6 spherical

#### MC GEE SPECIAL SAVE MONEY ON THESE GRADO STEREO CARTRIDGES.

595 MODEL FCR

List \$25.00

11/2-31/2 grams

Output-4 Millivolts @ 3.54 CMV - 45° Frequency Response—10-35,000 Hz (cps)

-25DB Channel Separation-Dynamic Full Range-(CBS STR III L & R Channel Square Wave)

MODEL FCE\$9.95

11/2-31/2

COMPLETE \$52 50

List \$35.00 grams

Stylus-Diamond - .6 x .3 elliptical GENERAL ELECTRIC



Fig. 1 Fig. 2 Fig. 3 Fig. 4 Fig. 1, V-15 Type II Dynetic W/ Elliptical Stylus

Tracks at 1/2 grams, Response 20-20,000 cps. 3.5MV output; 25 db separation. Diamond stylus. 3.567.50 Fig. 2, M75E Hi-Track Dynetic W/Elliptical Stylus Trucks from % to 14 grams. Response 20-20,000 cps. 6.6 MV output; 25 db Separation. Retractible diamond stylus .0007 x .0002. Built-in stylus guard... \$39.95

Fig. 3, Shure M44E Dynetic with Elliptical Stylus 

Shure M44C Stereo Dynetic with Stylus Tracks from 3 to 5 grams. Response 20-20.000 cps. 9.3 MV output. \$17.9 N44C Stylus for Shure M44C. \$9.0

Fig. 3, M44-7 Tracks 11/2 to 3 grams..........\$19.95

Fig. 4, M31E Dynetic with Elliptical Stylus Tracks at 1 to 2 grams. Response 20-18, 500 cps.

Fig. 4, M32E Dynetic with Elliptical Stylus

Fig. 2, M55E Dynatic with Elliptical Stylus 20-20.000 cps; 25 db separation. Tracks P/ATE 2005" x.0010" \$9.95 1/4 to 11/2 grams..... FAMOUS SHURE M3D STEREO CARTRIDGE

Mc



## MODEL M91E

# liiitrack

**EASY-MOUNT** STEREO DYNETIC®

From 20 to 20,000 Hz. PHONOGRAPH CARTRIDGE

Model Number	Diamond Stylus Replacement	(1,000 Hz. at 5 cm/sec.)	5tylus Color Grip	
м91E \$49.95	N91E Elliptical Side Contact Radius: .0002" (.005 mm) Frontal Radius: .0007" (.018 mm)	5.0 millivolts Tracking (Grams) % to 11.	Black	
M93E \$39.95	N93E Elliptical Side Contact Radius: .0004" (.010 mm) Frontal Radius:	6.2 millivolts  11/4 to 3  TRACKING GRAMS	Light Green	

VR 1000-5 WITH DIA. NEEDLE \$14.95 VR 1000 STEREO CARTRIDGES

VR 1000 STRRIO CAFFRIDGES
Officis the purest musical response, even at frequencies above the normal range of human hearing. You hear every subtle overtone without distortion. Unique suspension and damping system prevents loss of higher harmonies, reproducing them to proper relationables to fundamentals. Wigasteroe separation assures clean, precisesteree reproduction. Triple, mumetal shielding diminates hum. Tracking Ferces 3-7 grams

GENERAL ELECTRIC MONO CARTRIDGES LESS STYLI GE VRIIS SINCLE STYLL MONO LESS STYLL NET 55.95

GE VR 113 TURN AROUND MONO FOR 2 STYLL LESS STYLL, NET, 6.95

DIAMOND SINGLE NEEDLES FO

SAPPNINE SINGLE NEEDLES FOUNT OF THE SAPPNINE SINGLE NEEDLES FOR SPECIFY TIP DIA. NET. \$1.50

R-5D SENERAL ELECTRIC 0005 DIAM DIAMOND STYLI FOR REPLACEMENT IN THE VR-1000-5 STEREO CART, NET. 58.95

L PICKERING HI-FI 3 to Tyrams CARRIDGE SALE .0007" P/AC spherical \$6.95

Stereo/Mono 2 to 5 grams

REPLACEMENT DIAMOND NEEDLES FOR POPULAR MAGNETIC CARTRIDGES

7 Mil. 7 Mil. 9×2 Ell. 7×4 Ell. 7×2 Ell. 7×2 Ell. 7×2 Ell. 7×2 Mil. 4×7 Mil. 6 Mil. For Cart. No. M7D-M3D M3D M55E-M44E M44-7 M75E Make Shure Shure Type N3D N21D N55E N44E Shure Shure Shure N44-7 N75E VN15E N31E N32E N91E Shure V15 Type M31E M32E M91E Shure Shure Shure Shure Shure M93E M75 19.50 6 Mil 7 Mil 7 Mil M75 U38AT V15/AM-3 V15/AT-3 V15/AME-2 V15/ATE-2 V15/ATE-2 VR-1000-5 VR-1000-5 N75-6 D3807AT D1507AM-3 D1507AT-3 D1500AME-2 D1500ATE-2 DR-7D DR-5D Pickering Pickering Pickering Pickering Pickering 7 Mit 7 Mit 7 Mit .9x.2 Ell .7 Mit .9x.4 Ell .7 Mit .7 Mit 19.90 10.95 17.95 6.83 8.20

VR-1000-5

100% MUSIC POWER DCF® Series Stylus Nominal Tracking Application Price Type Output Force

Was \$11.76. Used in thousands of stereo systems.

Has .0007" conical-tip diamond stylus. Response:

MANUAL T.T. 1/2 to 1 XV-15/750E Elliptical 4.4 mv \$59.95 gram CHANGERS MANUAL T.T 3/4 to 11/2 XV-15/400E Elliptical 5.5 my \$49.95 grams CHANGERS. 1 10 3 AUTOMATIC XV-15/350 Spherical \$39.95 6.0 my TURNTABLES grams XV-15/150 Spherical AUTOMATIC 2 10 5 \$34.95 8.0 my TURN TABLES grams

Model V15/AME-3 V15/AM-3 V15/ATE-3 V15/ATE-3 V15/ACE-3 V15/ACE-3

PICKERING

17acking 34x11/2 Grams 1-3 Grams 2-5 Grams 2-5 Grams 3-5 Grams 3-7-Grams

Pickering G.E. G.E.

V-15/3 Series Micro-Magnetic Cortridges **Styrus** Elliptical Conical Elliptical

Diamond .9x.3'Mil .7 Mil .9x.4 Mil .7 Mil .9x.4 Mil .7.Mil 34.95 39.95 29.95 29.95 Conical Elliptical Conical 29.95 24.95

XV-15 10 to 25 000 CPS 35 DB. CHAN SEP. AND FINEST GIA. NEEDLE

Pickering Cortridges are furnished with 4 Snop Mounting brackets for Gorrard, Dual and BSR changers.

## Dual Auto/Professional Turntables w united audio

Auto/Professional series have earned world-renown for excellence. DUAL 1219 AUTO/PROFESSIONAL

3-SPEED AUTOMATIC TURNTABLE \$ 17501 WITH CHOICE OF CARTRIDGE LESS CARTRIDGE AND BASE



The Dual 1219 three-speed Automatic Turntable with more precision than you may ever need. Dual's best turntable has every deluxe feature to meet the demands of the most critical listener, Full 12' dynamically balanced 7 lb. platter, Mode sciector lowers arm base to provide a perfect 15 degree stylus tracking (0 degree vertical tracking error) when set for single play, raises base for multiple play. Motor combines absolute speed accuracy with high torque. Has 66 variable pitch control for tuning records to synchronize with tape recorders or musical instruments. Cue-control system silicone damped in both directions to prevent bounce. Elastically damped counterbalance has 0.01 gram click stop for precision balancing. Adjustable stylus overhang. Automatic or manual operation at 33-1/3, 45. 78 rpm. Multiple play spindle holds up to 6 records. Dimensions: 14-13/16" x 12-1/8". Ship. Wt. 24 lbs. Model 1219 with choice of Shure M93E or Pickering V15/ATE-3 elliptical-stylus cartridge.... \$175.01

DUAL 1218: AUTO/PROFESSIONAL 3-SPEED AUTOMATIC TURNTABLE

\$13950 LESS CARTRIDGE AND BASE

With Choice of Cartridge Shura M93E Reg. \$39.95

The Dual 1209 three-speed Automatic Turntable loaded with fine features at a moderate price. Has synchronous/hi-torque motor; lowmass tubular arm; flawless 0.5 gram tracking; pitch control. Plays 33-1/3, 45 and 78 rpm manually or up to 6 records automatically. Size: 10½" x 12½". Ship. Wt. 301bs. Model 1209 with choice of Shure M93E or Pickering V15/ATE-3 elliptical stylus cartridge... \$129.51

DUAL 1215 AUTO/PROFESSIONAL 3-SPEED AUTOMATIC TURNTABLE

LESS CARTRIDGE AND BASE \$9951 With Choice of Cartridge Shure Pickering M93E V25/ATE-3 Reg. Reg. \$39.95 3% 1b.

The Dual 1215 three-speed Automatic Turntable with Dual precision features in the medium price range. Counterbalanced tonearm; Direct-dial tracking force; Pitch control; silicone damped cue-control. Plays 33-1/3, 45 and 78 rpm manually or up to 6 records Auto. Size: 10½" x 12½" Ship. Wt. 30 lbs. Model 1215 with choice of Shure M93E or Pickering V15/ATE-3 elliptical stylus cartridge.... \$99.51

ACCESSORIES FOR

## Auto/Professional **Turntables**



WB-19 Oiled Walnut Base for use with 1219\$14.95 WB 19X Custom Oiled Walnut Base with \$29.95

Drop-down Front for accessory storage. For 1219 DC-2 Plexiglass Dust Cover for use with WB-12 and WB-93.....\$10.95

DC-9 Custom Pleziglass Dust Cover. Combines 

Deluxe, Custom Dust Cover. \$24.95 For use with WB- 19X

CH-12 Extra Cartridge Holder for 1212...\$3.95

AS-12 45 RPM 7" Record Automatic Spindle for Model 1212...........\$5.95

AW-3 Automatic Spindle - for 12" records to 1209, 1212 and 1219 turntables....\$6.70

MS-1 Single play spindle for 1212......70

RS-1 Single play rotating manual spindle (or 1209

#### BIGGEST HI-FI CHANGER BUY ONLY 300 TO SELL

BSR, McDONALD 4 SPEED RECORD CHANGER. SHURE MAGNETIC CARTRIDGE M-71 VALUE SIZE: 1114" X 13

COLOR, BLACK with BRIGHT TRIM

PRICE EACH

SERVICEMAN'S SPECIAL FACTORY CARTON OF 4 CHANGERS

\$10000 PER CARTON

CHANGER BASE CA-68 BLACK PLASTIC WITH TRIM.

4-SPEED, 4-POLE INDUCTION MOTOR
LARGE 11" TURNTABLE
COUNTER WEIGHTEO TONE ARM
MUTING CONTROL
CHANGER CONTROLS... STOP/START/AUTO.
BOTH FOR \$7.95
16/33/45/78 RPM, SELECTOR. 7"/10" 12"
ALL PHONO LEADS AND A.C. CORO FURNISHEO.

YOU MUST HAVE A MAGNETIC INPUT ON YOUR AMPLIFIER TO USE THIS CARTRIDGE

## SOUNDESIGN 483 STEREO 8-TRACK CARTRIDGE TAPE PLAYER DECK

plays standard 8-track stereo tape

automatic and manual channel selector

channel indicator lights

frequency response: 30-15,000Hz color: walnut finished wood cabinet

3 1/2" x 8" x 9 3/4" size:

TOP QUALITY 8 TRACK PLAYER DECK NICE WALNUT CABINET PLAY YOUR 8 TRACK CARTRIDGES AT HOME SOUNDESIGN 483.....

# This new Dual integrated module comes just as you see it: with base, dust cover and cartridge.

## But that's not why you should buy it.

DUAL CS 16 IS A REAL BEST BUY.

We can give you many reasons for buying the new Dual CS 16. The least important is the convenience of its being complete with base, dust cover and Shure magnetic cartridge. And with all tonearm settings for this cortridge — balance, tracking pressure and onti-skating — set at the factory for optimum performance.

A much better reason is that the CS 16 is a Dual, with many of the precision features that have long made Dual first chaice of hi-fi experts. For example Dynamically-balanced low-mass tonearm that tracks flawlessly at as low as 0.75 gram. Constant-speed historque motor. Pitch-cartral to compensate for affipath records. Salicone-domped feathertouch cue-

control. Elevator action changer spindle
When you think of your Investment in necords—
which may be hundreds or even thousands of dollars
—we think you'll agree that the component that handles those records should do so with the utmost care and precision.

Now you know the most important reason of all for buying the Dual CS 16. There is still one more, however its modest price \$119.50

United Audio Products, Inc. 120 So Columbus Ave. Mt. Vernon, N.Y. 10553



DUAL CS-16 COMES COMPLETE WITH MAGNETIC CARTRIDGE, WOOD BASE AND DUST COVER AT....\$119.95

# GREATEST RECORD CHANGER SALE EVER

SAVE ALMOST 509

## **Professional Series**



The 500 A Total Turntable is actually a full-sized 600/X with a lighter turntable, conical stylus and standard base and dust cover. It features the same record-handling phisticated controls.

BSR McDocapabilities. motor, and so-

### RSR McDonalds 00A utomatic Turntable \$ 64.50

### Shure | Magnetic Cartridge M-44-7 | 24.50

### BSR PB-2 Base | 5.50

### BSR DC-2 Dust Cover | 5.50 \$100.00

MC GEE FULL SIZE TURNTABLE. Deep-drawn turntable platter provides full record

AUTOMATIC TONE ARM LOCK: Automatically locks tone arm to rest whenever unit is in the "off" position Eliminates possibility of accidental stylus or record damage.

SWING BACK CONTROL ARM. Allows unobstructed manual play operation. POP FILTER: Eliminates annoying "pop" which occurs in any turntable due to A.C. switch arcing when unit shuts off.

SUSPENSION SYSTEM: Scientific spring mounting system in conjunction with low mass tone arm overcomes susceptibility to external shock common to other turntables.

MICROMETER STYLUS PRESSURE CONTROL: Precision micrometer wheel provides continuous, infinita stylus pressure settings between 0 to 6.0

BSR

REPLACE THE OLD WORN CHANGERS

45" RPM SPINDLE ADAPTOR

27/8 in. toll price 1/2 in thick. 99¢ 1 1/2 in. wide Stock no. PS-900 Fits most all BSR lote

models except mini-changer FITS UA15-55 UA18-55T A25 30 35 40 65 70 AND DONALD 400 500 5004 600

MINICHANGER \$1 4 95

9 Volt Battery operated Stock no. PS-1398

NEW FOR 1972, NEW V-M CHANGER 4 SPEED DELUXE STEREO RECORD CHANGER THE SAME UNIT THAT MOST AMERICAN MANUFACTURERS USE IN THEIR STEREO PHONO SYSTEMS Stock No.

72-V M 1297

Price.

CARTRIDGE DIAMOND NEEDLE

New '72' V-m Record changer plays all records 79', 10". 12" automatically. Size;13'4" long X 12" wide. Space required to is 2½" above and 3½" below the bed plate. Base color is BLACK with a 11½" heavy tum-table, both record hold down tone arm aluminum color. 4 speed, 2 pole. 117 volt 60 cps moto Base for 72-VM1297, Stock No. B72VM \$4.95

Short flat 45 rpm Adaptor, No. 435SF,

Size: 11 7/8" long by 8 3/8 wide. requires only 31/2" space above the turntable and is just 2" deep This changer is identical to the

UA-50-2 except the motor operates on 9 volts battery or 9 volt DC supply. Gray base with Cream color tone arm

with No 146 Astatic 3 volt cartridge.

Price \$14.95

FOR BSR A-14 CHANGER ONLY DUST COVER, AND PLASTIC BASE

STOCK NO BC-14 BOTH for \$7.95

## SYLVANIA CUSTOM



BSR BEST QUALITY CHANGER 10" TURNTABLE WITH RUBBER MAT Slim Tetrad Cartridge with Diamond Needle 4-SPEEDS ... Size: 111/4" x 13-1/8"

This is the best changer in the BSR line. Has the New Tetrad super slim cartndge with a dismond needle. Soft black finish with silver trim. Custom made for Sylvania, Regular \$39.95, McGee Price \$22,95 Shipping Weight 10 pounds.

# BSR MODEL UA-50-2 STACKS Ship. Wt.



COMPLETE WITH BASE & DUST COVER

> PB-4, Bose \$5.00 DC-4, Dust cover. \$5.00

DC-4, DUST COVER PB-4 BASE and MINICHANGER. Stock No. UA-50-DC . PB-

NEW CHANGER FOR



## **DELUXE VM CHANGER**



Oversized 11" Turntable, White with Gold trim. Tubular Tone Arm with a Turnunder Stereo Cartidge, diamond styll. Ready for easy installation. Includes audio cables and A. C. tine cord, Ind vidually Boxed .....\$26.95

#### **ECONOMY VM CHANGER**



**PRODUCTION** (WIRED & BOXED)

Attractively styled, white with gold trim, New tholder tone arm, latest stereo cartridge with diamond needle. Ready for installation. With sudio cables & A.C. line cord. Individually boxed for easy storage & handling.

STOCK NO Sole Price UA-A21-142

Servicemon Special Master Carton of

with ASTATIC

UA-A21-142, for \$66-00 142 cortridge Deluxe 4 speed stereo record changer made by BSR. Model A21 STOCK NO UA-A21-142 Complete with Astatic 142 cartridge. Tubular tone arm, attractive black and chrome coloring. Large, 101/2" diameter decorative turntable. Solid mount style (no springs)

## BIGGEST BUYS ON RECORDING TAPE IN AMERICA

RECORDING TAPE



1200 FT. PLASTIC

Stock No. 5WP 1200 10 FOR \$9,00

MCGEE TAPE SPECIAL 79 Stock No TOC-3-275

TAPE HOME A LETTER



Six 3 inch reels, each with 150 feet of recarding tape and 6 mailing bares. Stock no. 666-P Ship wt 11: Ibe.

3 PACK OF 3 INCH-400 Ft. 400 FT. MYLAR 400 FT. 400 FT. \$1.49 9 2 packs 52.90

Three 3 inch reels, each with 400 feet of Mylar recording tape. Up to 4 hours recording time at 1% in. per Ship wt. 1% lbe. Stock no 3405

2-3/8", 150 Ft. Reels Tope FITS MOST JAPANESE MADE RECORDERS INCLUDING CONCORD F20 AND F85

29¢ Each 10 for \$2.75 Stock No. TP2-38 Empty 2-3/8" Reals Stock No. EPT2-38 10¢ Ea. 10 for 90¢

McGEE SCOOP RECORDED TRACK CARTRIDGES ORIGINALLY SOLD FOR \$1.4910 FOR \$6.95

TOO MANY DIFFERENT TITLES
TO OFFER A SELECTION---

ALL ARE GOOD I

Largest Manufacturer PLASTIC BASE RECORDING TAPE

Reel of 600 ft. PLASTIC TAPE

600MP 600 ft. x 1 4" 75c 10 for \$6.90

1800 FT. PLASTIC

29 EACH 10 For \$12.00

NEW/ITEM "TERRIFIC VALUE!" "SHAMROCK" BLACK OXIDE Recording 1800 FT Tape Finder 7" \$ HI-FI LUBPICATED PECCHDING TAPE \$18.90

SPECIAL PURCHASE! 275' AMPEX Tape

10 for \$3.00 35¢ No 4275 Ampex Tape A Letter Plastic re-useable malling box with a 275 ft, 3" reel of AMPEX 1 mill tape A big value, 35c

EXTENDED PLAY TAPE

1200 FT. \$1.39 1200 Feet on 5" Reel. Genuine 1/2 mill tensifized MYLAR packed in an Individual box. Very good Quality... 

600' MYLAR RECORDING TAPE

**OUALITY** 



P3Eeon, Trapic Pley 1/2 Mil Tensified Mylur, non-feet on 3." Refs : slead when long, uninterrupted recognings are required, individually based.

MADE IN U.S.A. BY ONE OF AMERICAS FINEST TAPE RECORDER MFGR.

FAMOUS SHAMROCK BRAND MYLAR" BASE

Lotest HI-FIDELITY \$1.49 10 for \$12.50 BLACK OXIDE I

Shamtock Shamrock for many full range

Stock No. 031-Black oxide-lubricated-112 Mili MY LAR. Computer-Audio grade. 7' reel, 1200 feet, Individually boxed. \$1,49 per reel. 3 reels for \$4.00, 10 for \$12.50.

Brown Oxide \$129 s11.90 50 FOR \$50.00

Stock No. 031-Brown-oxide-lubricated-1\(^1\) MII MYLAR. Computer-Audio grade. 7' reels, 1200 feet, Individually boxed.\$1.29 per reel. 10 for \$11.90, 50 for \$0.00

MEGEE BREAKS THE PRICE ON HI-FI LUBRICATED RECORDING TAPE

\* Manto by World's MYLAR BASE RECORDING TAPE

5" 900 FT. MYLAR 99c EACH

1 to 9 10 up Each Each \$0.99 \$0 90 Stock No. Osscription 900MS 900 ft. x 1/4"

EMPTY PLASTIC REELS

3" 7¢ Eoch 100 FOR 65¢
31/4" 9¢ Eoch 100 FOR 85¢
4" 12¢ Eoch 100 FOR \$1.10
5" 19¢ Eoch 100 FOR \$1.00
100 FOR \$1.80
100 FOR \$1.80
100 FOR \$1.98
4 Eoch 100 FOR \$1.98 10% INCH NAB HUB \$1.95

EXTENDED PLAY RECORDING TAPE SPECIAL

2400 FT. \$2.79 2400 feet on a 7 inch reel. Genuine 1/2 mill tensilized Mylar. Packed in individual baxes. Very good quality Stock on M2400-S \$2.79 10 for 25.00

3600 FT. \$3.79

3600 feet on a 7 inch rect. Genuine 1/2 mill tensilized Mylar. Pocked in. individual boxes. Very good quality.

Stock no. MJ600-7 \$3.79 10 for \$35.00 Shipping weight to or, per rest.

EMPTY MINNESOTA MINING TAPE REEL BOXES BULK EMPTY REELS

INCH - Minnesota Mining, Limited Quentity Available teck No. B-SWPMM-7-----39e wach, 10 for-----\$3.50.

McGEE Special TRI-PAK C60 CASSETTES

SAVE 50% ON

AUDIO MAGNETICS

Compact Cassette

BONUS PACK

BONUS PACK No. 1

C-120 and C-60 Fam \$1.69

BONUS PACK No. 2

BONUS PACK No. 3

C-60 and Headeleaner 99¢

TREMENDOUS VALUE

6- C60 CASSETTES

MAILER BOXES Plus BLACK LEATHERETTE

STORAGE CASE\*\*\*\*

6 EMPTY PLASTIC

C-90 and C-30 For

\$ 1300 W

BAOK

\$1,29

For CASSETTES





MAGNETICS CORP CARTRIDGES AUDIO CASSETTE



AC-30

69¢

BLANK TAPE CARTRIDGES 10 FOR \$6.50 10 FOR \$7.50

10 FOR \$11.00 10 FOR \$14.00

4T-35, 8T-35, 8T-70

BEST QUALITY

1 4Q 4 TRACK CLEAR TOP CARTRIDGE — 35 Minutes Playing Time ... \$1.49 10 FOR \$14.00 8 TRACK CARTRIDGE — 35 Minutes Playing Time ... \$1.49 10 FOR \$14.00 8 TRACK CARTRIDGE — 70 Minutes Playing Time .... \$1.59 10 FOR 15.00 #4T-35 #8T-35

#8T-70

AC-120

AUDIO

	SCOTO	CH E	BRAN	ID RI	ECC	ORDI	NG T	APE					AND VI	DEO TAPE		SCOT	CH ACE	SSORY	ITEMS
	206 HIGH OUTP		CATALOG NUMBER	LE	NGTH	REEL S12E	PER	LI	ESTED ST 1CE		CONSUMER CONSUMER COST			EATALUG PAGNUM	LENGTH SI		SUGGESTED LIST PRICE	CONS	TREAL LIMER ST
	LOW NOISE 1.5 MIL "POST-TRAK" BACKING	\$96-	1/4-866	60	RIN.	yn .	12	5 6	.75	5 4,49		5 4.04	LIVING LETTERS TAPES	131-1/4-150LL 200-3/4-300LL 250-3/4-600L1	150° 3" 500° 5" 600° 3"	12 12 12	\$ 1.05 2.05 2.95	5 .72 1.46 1.99	\$ .65 1.31 1.79
	207 HIGH OUTPI LOW NOISE 3 MIL "POST-TRAK"		1/4-R90	90	10[10,	7"	12	5 g	.55	\$ 5.69		\$ 5-12	102 1.5 MIL POLVESTER	102-1/6-600 102-1/6-1200 103-1/6-2500-4	600° 5° 7′′ 2500° HJ8	12 12 12 17	5 7.80 4.48 6.80	5 1.86 2.91 5.87	\$ 1.67 2.65 5.20
	BACKING 282 SANDWICH 1.3 MIL POLYESTER	282- 282-	1/4-600		00'	She yes	12	\$ 2 3.	.50 .85	\$ 1-68 2-58	Į	5 1.51 2-32	] ,,,	111-1/4-150 111-1/4-600 111-1/4-1709	150' 3° 5' 1200' 7'	12 12 17	\$ .85 7.70 4.00	5 .55 1.77 2.67	5 .49 1.60 2.40
7	290 .5 MIL TENSILIZED		1/4~1800 1/4-5600		00'	5 <sup>84</sup> 7 <sup>14</sup>	12	\$ 7		\$ 4.97 7.99	T	5 6.43	PLASTIC	111-1/4-2500-H 2-111-1/4-2500-R0	3500, 00	6 12 12 12	8.10 11.10	3.59 7.42	4.85 6.67
	EXTENDES RANGE	D PACK	Microfore	AILER" zef	ere to	the white	sold-color	matle post	al-approve	d mailing	e contain	Me.	= 131 1.5 HIS PLASTIC	131-1/4-600 131-1/4-1200 131-1/4-2500-h 2151-1/4-2500-h0	2500° 5° 1200° 7′° 1200° 100° 100° 100° 100° 100° 100° 10	12 17 17 17 17	\$ 7,95 4,55 9,55 12,60	\$ 1.96 3.02 6.36 1.30	\$ 1.76 2.72 5.72 7.5h
1	CASSETTE	S	CATALOG			LENGTH		ER Tru,	GGESTED LIST PRICE		INDUSTRI CONSUME COST		138 115 MIL POLYESTER	158-1/4-1700 138-1/4-7500-M 0138-1/4-2500-R0	1200° 31° 2500° HUE 2500° 10	B 12 12 12 12	\$ 3.25 9.55 17.60	\$ 3,50 6,36 4,38	5 3.15 5.72 7.55
1	,5 MIL "POSE-TRAK" BACKING	S-C-3	O ALBUM E	MATLER	15 #	HIM. EA. S	SIDE	48	\$ 2.25	5 1.1		5 1.32	ISO L MIL	150-1/4-908 150-1/4-1800 150-1/4-3000-H	100° 3" 1800° 7" 1600° Huli	17 12 12 12	\$ 5.60 6.20 11.75	\$ 2,40 4.11 7.82	\$ 2.16 3.70 7.05
	,5 MIL "POSE-TRAK" BACKING	S-C-0	60 ALBUM E	MATLER	30 /	MIN. EA.	300€	48	5 2.6\$	\$ 1.5	99	\$ 1.79	POLYESTER	(150-1/4-1000	\$600, 10	172" 12	1 14.60	9.86	3 3.76
	JB HEL "POSE-TRAK" BACKING	\$-C-1	95 ALBUM E	MATLEN	45 1	HEN, EA. 1	5 IDÉ	48	\$ 4.00	5 7.5	99	\$ 7.69	LUGRICATED	175-1/4-600	600' 5"	12	3 2.50	\$ 1,68	\$ 1.51
	.25 MIL "POSI-TRAK" BACKING HIGH	5-6-	350 VERTW		60 1	MIN. EA. !	SIDE	62	5 5.15	5 5,5	99	\$ \$-59	1.5 MIL PTENZARY	175-1/4-1200 175-1/4-2500-H P175-3/4-2500-R0	7500° 10	u 12 12 12 17 17	3.85 8.45 11.35	2.58 5.63 7.55	2,32 5,02 6,85
	ENERGY CASSETTE		TALOG		LENGTH	н	PER CTN.	LF	ESTED ST ICE	1-11	COST		200 .5 MIL TENSTLIZED POLYESTER	700-1/4-1700 800-1/4-2400 800-1/4-4400-8/5-	2400° 10	17 177 <sup>11</sup> 6	\$ 5.85 10.05 22.65	5 1.87 5.64 15-11	\$ 1.49 6.07 13.60
	-5 MIL "POSI-TRAK" BACKING -5 MEL		SO HE ALBU		IN. EA.		48	5 3		\$ 7.5		5 2.15	201 "DWAFA 1.5 ML 1.5 ML	201-1/4-2500-H	500° 5° 7° 7° 7500° +U		5 7.80 6.10 9.55	\$ 2.05 3.08 6.36 8.38	\$ 1.8h 2.27 5.72 7.5h
	"POSI-TRAK" BACKING		90 HE ALBU		IN. EA.		48	3 5		5 9.75		\$ 2.51	202 "DWWAR	2701-1/4-2500-RG	500° 10	1/2"   12	\$ 7.85 h.75	\$ 2.09	5 1.88
-	MPOST+TRACH BACKING	3-4-	JU -E ALSU	43 84	ere SA	. 3100	70	1					POLYESTER	202-1/4-2500-RD	2500° Hb 2500° 10	8 17 12	9,55	6.34	5.72 7.55
	4.70/5~	CATA	ER		LENGTI		PER CTN.	1 LI	ICE	1-11	CONSUME CONSUME COST		203 "DYTHALLS I MIL PULYESTER	203-1/4-900 NGC 33-1/4-1800 205-1/4-1620-H E203-1/4-1620-H PALSO available on	1800' 7'' 5600' (G	3 '2" 12	6.85 14.65 17.65	5.05 9.75 11.77	6.54 8.18 10.60
-	6-TRACK CARTRIDGES	5-011 5-011	WO JHQ BINDEK	EDNGITUDIO SYSTEM + L	WIFA O	HEATED Y	IDEO TAPE I DE + IMPAD	I AS MANY DI NED SIGNAL	.40 UTSTANDIN TO NOISE R	C AQVACI ATIO • EX	CEICENT /	2.47 LAYY GUTY AUGIG 446		5/16" (ETA) contof	to 1/2" playtic re hole (identified	an RPS3 at th	e tame price.		
	36		HEAD LI			ATMENT PA	REVENTS INT	EGUNT - M	PPAGI, SCA		AND ATTR	ACHON OF	[5	pitch   Taphyck	SIZE	ÇRI.	LIST PRICE	12 <u>0</u> 051	120
		PLAYING					REELS MAI	TEN		NET P	RICE		and of	理學型 41-1/2-12.5	1/2"×150"	12	\$ .53	5 ,48	5 .43
1	AMPEX 4800,	TIME minutes	CAT	ALOG 48ER	TAPE			(6bs.) 1-B	10-24	25-40	50-99	100-240 25	toe.	41-1/2-12-3 41-1/37-66 41-1/2-66 41-3/4-66	7/32"X66" 1/2"X66" 3/4"X66"	12 12 17	1,69	1.16 1.52	1.04
	AMPEX 4800, 5000, 6000, 7000 SERIES	31 62 32	380-1-15 380-1-30 380-1-30	GC-R135 GC-R135 GC-R876	A A	11581 112951 11681	5 2 5 3	(4m.) 1-8 5 144,95 5 58.95 0 39.00	642.70 66.96	25-49 641 36 65.15 36.88	50-99 140-46 53.95 35.10	#39.33 #36 52.46 86 34.13 33	21 56	41-7/3/-66 41-1/2-66 41-3/6-66 50, 41-1/2-12.	7/32"x66" 1/2"x66" 5/4"x66" \$ 1# wackared on a 2/32"x66"	12 12 17 1 corn in a pl	1,29 1,69 exit bise, without	1.16 1.52 a dispensor.	52.28
	AMPEX 4800, 5000, 5000, 7000 BERIEB SÖNY EV-200/200	31 62	380-1-15 380-1-30	600-R139 600-R139 600-R878 860-R318 860-R318	A A A A A A A A A A A A A A A A A A A	17587 172957 57487 57487 276857	5 2 5 3	(48s.) 1-8 5 944.95 5 58.95 0 39.00 0 58.95 4 19.70	642.70 56.95 37.05 56.95 18.59	25-49 641 36 85.15	50-99 940-46 53-95	\$39.33 \$36 52.46 \$6 34.13 33 52.46 50	21 96 15 96 22 Szalet	1-3/3/-66 1-1/2-66 1-3/6-60 100, 61-1/2-12. 1021-2/32-66 1021-1/2-66	7/32"x66" 1/2"x66" 5/4"x66" 5 1 * wackared on a	12 12 17 17 18 core in a pt	1.29 1.69 extic base without 53.25 487	1.16 1.52 a dispenser. 53,25 4.87	52.28 5.91
	AMPEX 4800, 5000, 8000, 7000 SERIES SÖNY EV-200/200 AMPEX VR-1500, VR-1500, VR-600S	31 62 32 63	380-1-15 380-1-30 380-1-24 380-1-24 3808-2-3	000-R135 000-R135 000-R178 000-R178 000-R178 000-VR18 000-VR18 000-VR18 000-VR18	A A A A B B B B B	17587 172957 57487 57487 276857	5 2 5 3 5 2 5 3 12 2	(ties.) 1-8 5 144.95 5 895 0 39.00 5 95 4 19.70 31.00 2 52.32 6 235	642.70 56.95 37.05 56.95 18.59 28.45 49.82 59.23	25-49 641 36 85.15 35.88 65.15	50-99 140 46 53.95 35.10 53.95 17.73	939 33 138 92.46 80 34.13 33 52.46 50 17.24 18 27.13 28 45.78 44	21 26 15 96 22 35 47	1-7/3-66 1-1/7-66 1-1/7-66 1-1/7-66 1-1/2-66 1-1/2-66 10. 01 5914511 10. 01 5914511 10. 01 5914511	7/32"xL0" 1/2"xL0" 5/"xL0" 5 is eackared on a 2/32"xL0" 1/2"xL0" 1/2"xL0" 1/2"xL0" 7/32"x150"	12 12 17 a core in a pl 12 12 14 15 17 18 to spice e 1 "PASI-TRAS."	1.29 1.63 eotic base etitoout 53.75 98.87 11 "Scoten" brand backing.	1.16 1.52 a dispenser. 53,25 4.87	52.28 3,41
	AMPEX 4800, 5000, 5000, 6000, 50000, 50000	31 62 32 63 74 32 48 84 86 730 260	380-1-15 380-1-30 380-1-24 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3	00-R139 00-R139 00-R138 86-R318 860-R318 900-VRB 900-VRB 900-VRB 900-VRB 900-VRB	A A A A B B B B B B B B B B B B B B B B	17x8" 17x9%" 17x8%" 17x8" 17x8" 27x8W" 27x8" 27x80 27x10W" 27x10W"	5 2 5 3 5 5 2 12 2 12 2 1 1 2 2 2 2 3 3	(idea.     1-9     1-9	642.70 56.96 37.05 56.95 18.59 29.45 49.82 59.23 83.06 104.64 196.29	28-49 641 36 65.15 35.88 65.15 18.03 28.52 48.33 57.36 80.44 101.34 189.12	50-99 140-46 53-95 35-10 53-95 17,73 27,90 47-34 56-12 78,59 99-14 185-01	\$39.33 \$34 52.46 \$6 34.13 33 52.46 50 17.24 18 27.13 28 45.78 44 64.56 53	21 26 15 96 22 35 47	#1-7/37-66 #1-7/37-66 #1-7/37-66 #1-7/37-66 #1-7/37-66 #1-7/37-66 #1-7/37-66 #1-7/37 to #1-7/37 to	7/32"xLb" 1/2"xLb" 5/4"xLb" \$ is eackard on a 2/32"xLb" 1/2"xLb" an Tape tage be use plicing tages with	12 12 17 a core in a pl 12 12 14 15 17 18 to spice e 1 "PASI-TRAS."	1.29 1.63 eotic base etitoout 53.75 98.87 11 "Scoten" brand backing.	53,25 kecordiuc Tame	52.28 3,41
	AMPEX 4800, 5000,	31 62 32 63 76 32 48 84 86 280 280	3604-15 3604-15 3604-26 3604-26 3608-2-2 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3	60-7818 60-7818 60-7818 60-7818 60-7818 60-788 60-788 600-788 600-788 600-788 600-788 600-788 600-788	A A A A A A A A A A A A A A A A A A A	17x8* 17x8* 17x8* 17x8* 17x8* 27x6* 27x6* 27x10** 27x10** 27x10** 27x12** 27x12** 27x12**	5 2 3 3 5 2 12 2 12 3 12 2 2 3 1 2 2 2 1 1 1 2 2 1 1 1 1	(46m.) 1-9 5 5 44.95 50 0 39.00 0 69.95 4 19.70 6 31.00 2 52.32 5 62.35 6 79.43 4 110.15 9 45.00 0 70.00 7 95.00	642.70 86.96 37.05 56.95 18.59 28.45 49.82 59.23 83.06 104.84 196.29 42.50 88.50 90.25	25-49 641 36 85.15 35.88 65 15 18.03 28.52 49.33 57.36 90.44 101.34 189.12 41.40 64.40 97.40	80-38 840 46 53.85 35.10 53.95 17,73 27.80 47.34 56.12 78.89 39.14 185.01 40.50 83.00 85.50	\$39.33 \$34 52.46 \$6 34.13 33 52.46 50 17.24 18 27.13 28 45.78 44 64.56 53	211 96 15 96 15 96 17 97 97 97 97 97 97 97 97 97 97 97 97 97	1-7/3-66   1-17-66   1-1	7/32"xtb" 1/2"xtb" 5 is eachaped on a 2/32"xtb" 1/2"xtb" 1/2"xtb" 1/2"xtb" 1/32"x150"  packaged on a cel	12 12 12 17 18 core in a pl  12 14 15 core in a pl  17 16 core in a pl  17 17 18 17 18 17 18 18 18 18 18 18 18 18 18 18 18 18 18	1.79 1.60 eetic bse, without 55.27  9.87 11 "Scoton" brand backtor. 51.89	1.16 1.52 1.25 1. a dispensor. 53.25 1.87 Necordine Tame.	\$2,28 3,41 6. Alvavo usp
	AMPEX 4900, 5000, 5000, 6000, 5000,	31 62 32 63 76 32 63 70 68 84 86 33 86	3601-15 360-1-30 360-1-32 360-1-32 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3	100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-100-713-1000-713-	A A A A B B B B B B B B B B B B B B B B	17x8"	5 2 5 3 3 12 2 11 2 2 1 1 1 2 2 1 1 1 2 2 1 1 1 2 2 1 1 1 2 2 1 1 1 2 2 1 1 1 2 2 1 1 1 2 2 1 1 1 1 2 2 1	(then.) 1-9 5 5 544,95 5 88 95 0 39.00 0 89 95 6 39.00 6 31.00 6 31.00 7 6 31.00 7 7 9 9 45.00 7 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	642.70 56.99 37.05 56.99 18.59 28.45 49.82 59.23 83.06 104.64 196.23 42.50 88.80 90.25	25-49 641 36 8515 3588 6515 18-03 28-52 49-33 57-36 90-44 101-34 189-12 41-40 64-40 87-40 97-93 8A10 - £	50-39 140 46 53 35 10 53 35 10 53 35 17 73 27.50 47 34 56 12 78.53 39 14 185 01 40 50 65 50 76 05 576 GIS - XCELLEN	939 33 134 55 52 46 55 52 46 55 52 46 55 52 46 55 52 46 55 52 46 55 52 52 65 5	221 231 246 25 222 25 25 25 25 25 25 25 25 25 25 25	#1-7/3-66 #1-7/3	7/32"XLU" 5/4"XLU" 5/4"XLU" 1/2"XLU" 1/2"XLU" 1/2"XLU" 1/2"XLU" 1/2"XLU" 1/2"XLU" 1/32"X150" packaged on e ee! LENCTH 1000' 1000' 1000' 1000' 1000' 1000'	12 12 12 12 12 12 12 12 12 12 12 12 12 1	1.79 1.60  octic bas, whiteout  \$1,25  \$1,25  \$1,25  \$1,25  \$1,25  \$1,25  \$1,25  \$2,25  \$1,25  \$2,25  \$1,25  \$2,25	1.16 1.16 1.16 1.16 1.16 1.16 1.16 1.16	\$2.28
	AMPEX 4800, 5000, 5000, 5000, 5000, 5000, 5000, 5000, 5000, 5000 5000, 5000	31 62 32 63 74 32 48 84 86 730 280 33 84 84 84	GAT: NUM 360-1-15 360-1-24 360-1-24 3608-2-2 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-1 3608-2-1	100-R135 100-R175 100-R175 100-R175 100-R175 100-VRB 100-VRB 100-VRB 100-VRB 100-VRB 100-VRB 1000-VRB 1000-VRB 1000-VRB 1000-VRB 1000-VRB 1000-VRB 1000-VRB 1000-VRB 1000-VRB	A A A B B B B B B B B B B B B B B B B B	1"x8" 1"x8%" 1"x8%" 1"x8" 1"x8" 2"x8" 2"x8" 2"x8" 2"x8" 2"x10%" 2"x10%" 2"x12%" 2"x7" 2"x7	5 2 5 3 3 12 2 12 2 12 2 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 2 1 1 2 2 2 2 1 1 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 2 2 2 1 1 2 2 2 2 2 2 1 1 2 2 2 2 2 2 2 1 1 2	(time) 1-9 5 544.95 59 0 58.95 0 58.95 0 58.95 4 19.70 6 31.00 2 2 52.32 5 62.33 7 67.43 4 110.15 3 206.57 9 45.00 0 79.00 0 79.00 0 79.00 0 88.5 MARY 0VID SIGNAL UT COUNT. 07.01.2718.5	442.70 56.95 37.05 56.95 18.59 28.45 49.82 59.23 83.06 104.84 196.23 42.50 88.50 90.25 80.28 0.015ISIANDIL TO BOISE HURNIY CO.	25-40 641 36 65.15 35.88 65.15 18.03 28.52 48.33 57.36 90.44 101.34 149.12 41.40 64.40 97.40 77.34 ING ADVAN GAIVO - E RATEMING TREQUIR	50-99   140-46   63-95   17.73   27.90   17.73   27.90   47.34   56.12   78.59   39.14   185.01   40.50   83.00   65.50   78.05   87.60   5.50   78.05   87.60   5.50   78.05   87.60   65.60   78.05   87.60   65.60   78.05   87.60   65.60   78.05   87.60   78.05   87.60   65.60   78.05   87.60   65.60   78.05   87.60   78.05   87.60   78.05   87.60   78.05   87.60   78.05   87.60   78.05	639 33 134 55 246 55 34.13 33 52.46 56 17.24 16 27.13 28 27.13 28 27.15 27.6 50 74 65 76 65 77 6	221 231 246 25 222 25 25 25 25 25 25 25 25 25 25 25	11-7/3-66 11-7/4-66 11-7/4-66 11-7/4-66 11-7/4-66 11-7/4-66 11-7/4-66 10-7/4-7/4-66 10-7/4-7/4-66 10-7/4-7/4-10-7/	7/32"XLU" 5/"XLU" 5/"XLU" 5/"XLU" 5 is eackayed on a 7/32"XLU" ng Tape bags be use piteing tapes with 7/32"X150" packaged on a ee!  LENSTH  1000' 1000	12 12 12 12 12 12 12 12 12 12 12 12 12 1	1.79 1.60  out to bee, without  55,25  687  11 "Scot on" brand backing.  51.89  card.  LEST POICE  5 7.75 4.50  mutarite order 1: leader Tane has a 1/2 mil white miles of 1/2 mil white miles.	1.16 1.16 1.16 1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	52,28 5,41 51,52 51,65 2,70 7,70 20 Leader Tape tite pleasite
	AMPEX 4800, 5000,	31 62 32 63 32 64 84 96 63 63	GAT: NUMBER OF STREET OF S	00-8139 00-8139 00-8139 00-818 800-818 800-918 800-918 000-918 000-918 8000-918	A A A A A A A A A A A A A A A A A A A	17:8" 17:2%" 57:8" 57:8" 57:8" 57:8" 57:8" 57:8" 27:80 38:81 38:81 48:81	5 2 5 3 3 12 2 12 12 12 12 12 12 12 12 12 12 12 1	1.9 5 5 14.185 10 10 10 10 10 10 10 10 10 10 10 10 10	442.70 56.95 37.05 56.95 18.59 28.45 49.82 59.23 83.06 104.84 196.29 42.50 68.80 90.25 80.28 0.41STR NOISE MICHILY CO	25-40 641 36 65.15 35.88 65.15 18.03 28.52 48.33 57.36 90.44 101.34 149.12 41.40 64.40 97.40 77.34 ING ADVAN GAIVO - E RATEMING TREQUIR	50-99   140-46   63-95   153-95   153-95   1773-27.50   1773-27.50   185-01	539.33 534 55 55 55 55 55 55 55 55 55 55 55 55 55	15 15 16 22 2 2 33	#1-7/3-66 #1-7/3-66 #1-1/3-66 #1-1/3-66 #1-1/3-66 #1-1/3-66 #1-1/3-66 #1-1/3-66 #1-1/3-66 #1-1/3-7-66 #1-1/3-8	7/32"XLU" 5/4"XLU" 5/4"XLU" 5/4"XLU" 6 Is eachared on a 6/32"XLU" 7/32"XLU" 7/32"XLU" 7/32"XLU" 7/32"XLU" 7/32"XLU" 1/2"XLU" 7/32"XLU" 7/32"XLU" 1/2"XLU" 7/32"XLU" 1/2"XLU" 1	12 12 12 12 12 12 12 14 15 core in a pt  12 16 core in a pt  17 17 18 core in a pt  17 18 core in a pt  17 18 core in a pt  1	1.27 1.60  exist bas, without to 1.62  51.27 9.87  11 "Scoton" brand teachior.  51.89  card.  1.57 POICE  5.7.50  4.50  carder Tane has a 1/2 mil whise p. 1.60  5.90  5.90  5.90	1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	\$2.28 \$.94 \$.94 \$.94 \$.1.52 \$1.52 \$1.52 \$1.52 \$2.70 \$2.70 \$2.70 \$2.70 \$2.70 \$2.70 \$2.70 \$2.70 \$2.70 \$2.70
1	AMPEX 4800, 5000, 5000, 6000, 5000,	31 62 32 63 32 64 84 96 63 63	GAT, NUMBER OF STREET OF S	00-8139 00-8139 00-8139 800-818 800-818 800-918 900-VRB 900-VRB 900-VRB 900-VRB 900-VRB 900-VRB 1350-VSRB 1350-VSRB 1350-VSRB 1350-VSRB 1350-VSRB 1350-VSRB 140-45110 1515-VSRB 1515-VSRB 1515-VSRB 1515-VSRB 1515-VSRB 1515-VSRB 1515-VSRB	A A A A A A A A A A A A A A A A A A A	17:8" 17:2%" 57:8" 57:8" 57:8" 57:8" 57:8" 57:8" 27:80 38:81 38:81 48:81	ARYON WY.  5 2 5 3 12 2 12 3 12 2 1 2 1 2 2 1 2 2 1 2 1 2 2 1 1 2 2 1 1 2 2 1 1 2 1 1 2 1 1 2 1 1 2 1 1 3 1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(tim.) 1-9 55 44.355 50 0 58.95 0 0 59.95 4 19.70 6 31.00 6 39.95 6 23.5 7 62.35 7 62.35 6 110.15 1 110.15 1 206.57 8 4 50.00 1 10.15	442.70 56.90 37.05 56.93 18.59 28.45 49.82 59.23 83.05 90.25 80.28 00.1518 NOI. 104.64 195.29 42.50 90.25 80.28 00.28 MASTER CARTON WITCHES	25-49  641 36 85.15  35.88 65.15  18.03 28.52  49.33 57.36 90.44  101.34 189.12  41.40 64.40 97.40  77.34  NOUCLIVE CHAPTENING TREQUISE TR	60-96   60-96   63-96   63-96   73-510	### ### ### ### ### ### ### ### #### ####	21 15 16 16 17 18 18 18 18 18 18 18 18 18 18 18 18 18	#1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-66 #1-7/3-7 #1-7/	7/32"XLU- 1/2"XLU- 3/4"XLU- 3/4"XLU- 1/32"XLU-	12 12 12 12 12 12 12 14 15 core in a pt  12 16 core in a pt  17 17 18 core in a pt  17 18 core in a pt  17 18 core in a pt  1	1.79 1.60  exist bas, without  51,27  9,87  11 "Scoton" brand inchion.  51,89  card.  157 PRICE  5 2,75 4,50 4,50 4,50 4,50 4,50 4,50 4,50 4,5	1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	51.52  52.28 5.41  52.28 5.41  6. Absert use 51.52  51.65 7.70 7.70 7.70 7.10  120 120 120 120 120 120 120 120 120
	AMPEX 4800, 5000,	31 62 32 63 32 64 86 84 86 63 33 84 86 63	GAT: 45 300-1-15 300-1-24 350-1-24 350-1-24 350-2-2 350-2-1 350-2-2 35	00-8139 00-8139 00-8139 00-818 800-818 800-918 800-918 000-918 000-918 8000-918	A A A A A A A A A A A A A A A A A A A	1"18" 1"29%" 1"18" 1"18" 1"18" 1"18" 2"18" 2"18" 2"18" 2"110%" 2"110%" 2"110%" 2"110%" 2"110%" 2"110%" 2"110%" 2"110%" 2"110%" 3"110%"	5 2 5 3 3 12 2 12 12 12 12 12 12 12 12 12 12 12 1	(time) 1-9 5 544.95 5 5 849.95 0 58.95 0 58.95 4 19.70 6 31.00 2 52.32 5 62.33 7 67.43 4 110.15 3 206.57 9 45.00 0 70.00 0 70.00 0 70.00 0 888.55 888	442.70 56.95 37.05 56.99 18.59 28.49 49.82 59.23 83.06 104.64 196.23 42.50 68.80 90.25 80.28 0.01552400 LTO ROISE HURNIY COULDED LTO ROISE HURNIY COULDED LTO ROISE HURNIY COULDED WASTERN WAS	25-49  641 36 85.15  35.88 85.15  18.03 28.92 48.33 97.36 90.44  101.34 149.12 41.40 97.40  77.34  18.03 77.36  AND PARENTE CATCHING TREQUES	60-86   840-46   63-86   83-86	### 1375 1: 13	21 21 22 22 22 22 23 24 25 26 25 26 25 26 26 25 26 26 26 26 26 26 26 26 26 26 26 26 26	1-7/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	7/32"xtb."  1/2"xtb."  5 is eackaged on a  7/32"xtb."  1/2"xtb."  1/2"xtb."  1/2"xtb."  1/2"xtb."  1/2"xtb."  1/32"x150"  packaged on e ee!  1/32"x150"  packaged on e ee!  1000"	12 12 12 12 12 12 12 12 12 12 12 12 12 1	1.77 POICE  5 2.75 LIST POICE  5 .90 for color draft: LIST POICE	1.16 1.16 1.16 1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	52,28 5,41  52,28 5,41  6. Alwaye use  51,52  12a  5 1,65 7,70 7,70  20 Londer Tape the nightle  12e  5 .54 .55  5 .56 .55  12e
-	AMPEX 4800, 5000,	31 62 32 63 32 63 32 63 76 76 76 76 76 76 76 76 76 76 76 76 76	GAT: NUMBER OF STREET OF S	00-8139 00-8139 00-8139 00-81878 650-818 650-818 650-918 650-918 650-918 600-918 600-918 600-918 1000-918	B	1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 2"x8" 2"x8" 2"x8" 2"x10" 2"x10" 2"x12" 2"x7" 2"x	5 2 3 3 5 2 3 12 2 12 2 12 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 1 1 1 2 1	(time) 1-9 5 5 44.95 5 5 89.00 0 59.95 4 19.70 6 31.00 2 59.95 4 19.70 6 31.00 0 70.00	442.70 56.95 37.05 56.99 18.59 28.45 49.02 49.02 49.02 104.64 196.23 42.50 69.80 90.25 80.28 0.015tanoi t of Boist HUBHY CO LIPPARE, SS 4 LONG PRA CARTON WT. (Ibs.)	25-49 441 36 451 15 461 36 88 451 16 461 36 463 36 463 37 463 37 463 37 463 37 463 37 463 37 463 37 463 37 463 37 463 37 463 47 47 47 47 47 47 47 47 47 47 47 47 47 4	60-98   60-98	939.33 344.33 35.246 55.32.46 55.32.46 55.32.41 36.36 35.24.31 36.36 35.24.31 36.36 35.26.30 36.36 36.	221 15 16 16 17 16	1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-66 1-1/3-166 1-1	7/32"xtit"  1/2"xtit"  5 is eackaged on a  7/32"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/3"xtit"	12 12 12 12 12 12 12 12 12 12 12 12 12 1	1.77 POICE  5 2.75 4.50  LIST POICE  5 .90  for color draft  LIST POICE  5 .95	1.16 1.16 1.16 1.16 1.16 1.16 1.16 1.16	52,28 5,41  6. Abwave use  51,52  12a  5 1,65 7,70 7,70 20 Leader Tape the oldstic  12a  5 1,54  12a  12a  12a  12a  12a  12a  12a  12
	AMPEX 4800, 5000,	31 62 32 63 32 63 32 63 76 76 76 76 76 76 76 76 76 76 76 76 76	GAT: NUMBER OF STREET OF S	00-8139 00-8139 00-8139 00-81878 850-8318 850-8318 850-9318 850-9318 900-VR8 900-VR8 900-VR8 900-VR8 900-VR8 900-VR8 900-VR8 900-VR8 900-VR8 1 60AGIEUR 3351-X-121 361-X-241 361-X-241 361-X-124	B	1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 2"x8" 2"x8" 2"x8" 2"x10" 2"x10" 2"x12" 2"x7" 2"x	ARYON WY.  5 2 5 3 7 2 7 3 12 2 12 3 12 2 12 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2	(time) 1-9 5 5 44.35 5 5 89.55 68.95 68.95 4 19.70 6 31.00 6 39.50 6 31.00 6 3	442.70 56.95 37.05 56.95 18.59 28.45 49.82 59.23 83.06 104.64 195.29 42.50 68.50 90.25 80.28 00.15 RATON VICTOR CARTON VICTOR CA	25.49 641.36 85.15 35.88 65.15 18.03 25.82 49.33 57.36 89.44 101.34 189.12 41.40 97.40 97.40 17.34 NC ADVA 189.12 18.50 18.95 14.95 14.95 21.50	60-96   60-96   60-96   63-96   78-96   78-96   77-73   78-96	# 13 75 1: 19.89 1: 20.19 1: 36.75 3	21 21 22 23 24 24 24 24 25 25 26 26 26 26 26 26 26 26 26 26 26 26 26	1-1/3-66   1-1/3-166   1-1/3	7/32"XLU"  1/2"XLU"  5/4"XLU"  5/4"XLU"  1/2"XLU"  1/32"XLU"  1/32"XLU"  1/32"XLU"  7/32"X150"  packaged on a sell cinr tapes with 1000"  1000	12 12 12 12 12 12 12 12 12 12 12 12 12 1	1.17 POICE  1.15T POICE  5 2.75 4.50 4.50  Translate of the second of th	1.16 1.16 1.16 1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	52,28 1,04 1,37  52,28 3,41 a. Abwave use  51,52  12a 5 1,65 2,76 2,70 20 Leader Tape the nightle  12a 5 ,54 5 ,55 2,70 2,70 2,70 2,70 2,70 2,70 2,70 2,70
	AMPEX 4800, 5000,	31 62 32 63 32 64 8 84 86 63 33 84 65 63 86 63	GAT: NUMBER OF STATE	00-8139 00-8139 00-8139 00-81878 850-8318 850-8318 850-9318 850-9318 900-9788 900-9788 900-9788 900-9788 1600-9788 1	B	1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 2"x8" 2"x8" 2"x8" 2"x10" 2"x10" 2"x12" 2"x7" 2"x	ARYON WY.  5 2 5 3 12 2 12 3 12 2 1 2 1 2 1 2 1 2 1 2 1 2 1 1 2 1 1 2 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3	(iden.) 1-9 5 5 44.95 5 5 8950 0 0 99 85 4 19.70 6 31.00 2 5 62.95 7 67.43 4 110.15 3 206 57 8 45.00 0 70.00 1 84.50 6 45.00 1 84.50 6 45.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 6	442.70 56.95 37.05 56.95 18.59 28.48 49.82 59.23 49.82 59.23 49.82 69.80 90.25 80.28 0 UISTENDL 10 MOSE MORE CARTON WT (Ibs. 1) 15 4 4 5 6	25.49 641.36 85.15 35.88 65.19 18.03 25.82 49.33 57.36 89.44 101.34 189.12 41.40 97.40 97.40 17.34 NC ADVANCE OF THE OF T	60-96   60-96   60-96   63-96   78-96   78-96   77-73   78-96	### 1375 1: 19.89 1: 20.19 1: 36.75 3 3 4: 30.30	221 366 376 386 387 387 387 387 387 387 387 387 387 387	#1-7/3-66 #1-7/3	7/32"XLU"  1/2"XLU"  5 is eackaged on a  7/32"XLU"  1/2"XLU"  1/2"XLU"  1/2"XLU"  1/2"XLU"  1/2"XLU"  1/2"XLU"  1/2"XLU"  1/2"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/3"XLU"  1/4"XLU"  1/4"XLU"  1/4"XLU"  1/4"  1/4"XLU"  1/4"XLU"  1/4"	12 12 12 12 12 12 12 14  15 core in a pl  16 core in a pl  17 16 core in a pl  17 17 18 core in a pl  18 core in a pl  19 core in a pl  10 cor	L157 PPICE  1.57 PPICE  5 2.75 4.50 4.50  L157 PPICE  5 2.75 4.50  MADDITE Tane has a 1/2 mll white a 1/2 mll	1.16 1.16 1.16 1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	52,28 1.04 1.37  52,28 3.41 6. Abware use 51,52  51,65 7.70 7.70 20 Leader Tape the oldstic  12- 5.56 .54 17- 5.70 2.70 2.70 2.70 2.70 2.70 2.70 2.70 2
	AMPEX 4800, 5000,	31 62 32 63 32 64 8 84 86 63 33 84 65 63 86 63	GAT: NUM 300-11-15 300-11-20 360-1-20 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-3 3608-2-1 3608-2-2 3	00-8139 00-8139 00-8139 00-81878 850-8318 850-8318 850-9318 850-9318 900-9788 900-9788 900-9788 900-9788 1600-9788 1	A A A A A A A A A A A A A A A A A A A	1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 2"x8" 2"x8" 2"x8" 2"x10" 2"x10" 2"x10" 2"x10" 2"x10" 2"x10" 2"x10" 3"x10" 3"x10" 4"x10" 4"x	ARYON WY.  5 2 5 3 12 2 12 3 12 2 1 2 1 2 1 2 1 2 1 2 1 2 1 1 2 1 1 2 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3	(iden.) 1-9 5 5 44.95 5 5 8950 0 0 99 85 4 19.70 6 31.00 2 5 62.95 7 67.43 4 110.15 3 206 57 8 45.00 0 70.00 1 84.50 6 45.00 1 84.50 6 45.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 1 84.50 6 75.00 6	442.70 56.95 37.05 56.95 18.59 28.48 49.82 59.23 49.82 59.23 49.82 69.80 90.25 80.28 0 UISTENDL 10 MOSE MORE CARTON WT (Ibs. 1) 15 4 4 5 6	25.49 641.36 85.15 35.88 65.19 18.03 25.82 49.33 57.36 89.44 101.34 189.12 41.40 97.40 97.40 17.34 NC ADVANCE OF THE OF T	60-96   60-96   60-96   63-96   78-96   78-96   77-73   78-96	### 199 1 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1	221 366 376 386 387 387 387 387 387 387 387 387 387 387	1-1/3-66   1-1/3-166   1-1/3	7/32"xtid"  1/2"xtid"  5 is eackaged on a  7/32"xtid"  1/2"xtid"  ag Tape tage be use piteing tages with  7/32"x150"  packaged on a sel  LENGTH  1000"  1000	12 12 12 12 12 12 12 12 14  12 14 15 to spice e  1 "PRAT-TRAM"  17 17-dispension  17 17 12 12 12 12 12 17 20 11 17 20 12 12 12 12 12 12 12 12 12 12 12 12 12	1.157 PPICE  5.25  6.87  1.157 PPICE  5.27  4.50  4.50  4.50  4.50  4.50  4.50  5.55  5.55  5.55  6.50	1.16 1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	\$2.28 3.93 a. Abuser was \$1.55 2.70 2.70 2.70 2.70 2.70 2.70 2.70 2.70
	AMPEX 4800, 5000,	31 62 32 63 32 64 8 84 86 63 33 84 65 63 86 63	GAT: NUMBER OF STATE	00-8139 00-8139 00-8139 00-8188 60-818 60-818 60-918 600-918 0	A A A A A A A A A A A A A A A A A A A	1"x8" 1"x8" 1"x8" 1"x8" 1"x8" 2"x8" 2"x8" 2"x8" 2"x8" 2"x10% 2"x10% 2"x10% 2"x10% 2"x10% 2"x10% 3"x10% 3"x10% 4"x10% 4"x1	5 2 3 3 12 2 12 12 12 12 12 12 12 12 12 12 12 1	(time.) 1-9 5 5 44.155 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	642.70 56.95 37.05 56.95 18.59 28.46 49.82 59.23 80.26 104.84 196.23 60.28 04.55 60.55	25.49 441.36 451.15 35.88 55.15 18.03 35.88 55.15 18.03 35.85 18.03 18.0	60-98   60-98	### 199 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	221 15 16 16 17 16 17 16 17 16 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18	1-7/37-66   1-7/	7/32"xtid"  1/2"xtid"  5 is eackaged on a  7/32"xtid"  1/2"xtid"  ag Tape tage be use piteing tages with  7/32"x150"  packaged on a sel  LENGTH  1000"  1000	12 12 12 12 12 12 12 12 14  12 14 15 to spice e  1 "PRAT-TRAM"  17 17-dispension  17 17 12 12 12 12 12 17 20 11 17 20 12 12 12 12 12 12 12 12 12 12 12 12 12	1.157 PPICE  5.25  6.87  1.157 PPICE  5.27  4.50  4.50  4.50  4.50  4.50  4.50  5.55  5.55  5.55  6.50	1.16 1.16 1.16 1.16 1.17 1.18 1.18 1.18 1.18 1.18 1.18 1.18	\$2.28 3.93 a. Abuser was \$1.55 2.70 2.70 2.70 2.70 2.70 2.70 2.70 2.70
	AMPEX 4800, 5000,	31 62 32 63 32 64 84 86 63 33 84 86 63 63 63 64 65 63 65 65 65 65 65 65 65 65 65 65 65 65 65	GAT: NUMBER OF STATE	00-8139 00-8139 00-8139 00-8139 00-818 80-818 80-818 80-918 800-918 00	A A A A A A A A A A A A A A A A A A A	1"sB" 1"sB" 1"sB" 1"sB" 1"sB" 2"sB" 2"sB" 2"sB" 2"sB" 2"sB" 2"sB" 2"s10%' 2"s10%' 2"s10%' 2"s10%' 2"s10%' 2"s10%' 3"s10%' 3"s10%' 3"s10%' 3"s10%' 4"s10%' 4"s1	5 2 3 3 12 2 12 12 12 12 12 12 12 12 12 12 12 1	(iden.) 1-9 5 5 44.35 5 5 62.35 6 31.00 0 39.00 0 59.95 4 19.70 6 31.00 0 70.0	442.70 56.96 37.06 56.95 18.59 28.49.82 59.23 83.06 68.50 90.25 80.28 00.28 00.25 18.00 90	25.49 44.136 45.15 35.88 55.15 35.88 55.15 18.03 35.88 55.15 18.03 37.06 44.03 37.06 47.07 48.10	60-98   60-98	# 13 / 5   1   1   1   1   1   1   1   1   1	221 Seatch 15 15 16 222 Seatch 15 16 222 Seatch 16 222 Seatch 17 20 E 70, 51 ALLPAIN 18 27 E 70, 51 ALLPAIN 18 28 28 28 28 28 28 28 28 28 28 28 28 28	1-1/3-16-6	7/32"xtit"  1/2"xtit"  5 is eackaged on a  7/32"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/2"xtit"  1/3"xtit"  1/32"xtit"  1/32"x	12 12 12 12 12 12 12 12 14  12 14 15 to spice e  1 "PRAT-TRAM"  17 17-dispension  17 17 12 12 12 12 12 17 20 11 17 20 12 12 12 12 12 12 12 12 12 12 12 12 12	1.27 POICE  5.25  Card.  1.89  Card.  1.87 POICE  5.25  4.50  4.50  Manufit rader I.  List POICE  5.27  4.50  4.50  5.189  Card.  List POICE  5.25  6.50  6.50  6.50  6.50  6.50  6.50  6.51  6.51  6.52  6.55  6.55  6.55  6.55  6.55  6.55  6.55  6.55  6.55  6.55  6.57  6.57  6.58  6.59  7.59  7.50  7.50  7.50  7.50  7.50  7.50  7.50  8.13  13.00  7.70  7	1.16 1.16 1.16 1.16 1.16 1.16 1.16 1.16	\$2.28

UNRECORDED MAGNETIC TAPE IN THE BEAUTIFUL BOX
Manufactured by AUDIO DEVICES, INC. a Capitol Industries Company

\$1.40

1.60

1.70

1.75

1.95

2.25

2.90

1.70

1.80

1.85

2.05

2.35

3.10



Capitol






McGee Bought o Worehouse Stock of BLANK TAPES

## 60000 TAPES SAVE! SAVE! SAVE!

SWP-AC-60 CASSETTE 59:10 FOR \$5.00 SWP-AC-90 CASSETTE 99 (10 FOR \$9.00 CASSETTE 49 ¢ SWP-AC-30 10 FOR \$4.00 SWP-8T-35 8 TRACK \$1.19 10 FOR \$11.00 SWP-8T-70 8TRACK \$1.39 10 FOR \$13.00

Recording tope on 7 inch Reels in Good quality boxes.

SWP-020 1800 FT. ACETATE \$1.19 For 11.00 SWP-030 1200 FT. MYLAR 994 10 FOR 9.00 SWP-120 1200 FT ACETATE 89¢ For \$8.00 SWP0-40 1800 FT MYLAR \$1.49 to, 14.00





## MONEY BACK GUARANTEE

Record Time	Tape Length	Reel Diam.	Wabash Catalogue No.	Net	prices
TIME	<u> </u>	DI ditt.	Catalogue No.	1-9	10 UP
1 Hour	2400'	7"	900TV-A-1-2400-60RB	22.50	21.50
1/2 Hour	1200'	7"	900TV-A-1-1200-60RB	13.35	13.00
4 Hour	1200'	5 1/8"	900TV-A-1-1200-62RB	13.35	13.00
20 Min.	800'	4 5/8"	900TV-A-1-0800-61RB	9.10	8.70
Pro	duct Desc	ription			
Record	Tape	Reel	Wabash	Net	prices
Time	Length	Diam.	Catalogue No.	1-9	10 UP
1 Hour	3000' 1500'	9 3/4"	1000TV-A-1-3000-73RB 1000TV-A-1-1500-73RB	38.75 26.50	36.50 25.25
-7 HOUL	2303	/ -			

Cassettes (Low Noise) PRICE C-30 (15 Min. ea. Side) .69 25-530-106 25-530-107 C-60 (30 Min. sa Side) 25-560-106 25-560-107 12 .79 1.19 C-90 (45 Min sa Side) 1.09 25-590-106 25-590-107 12 C-120 (60 Min. ea Side) 25-512-106 25-512-107 12 2.49 1.49 CHC (Cassette Head Cleaner) 25-500-106 25-500-107 12 Cartridges (8 Track) 32 Min. 150 Ft 27-432-106 27-432-107 12 1.89 .99 40 Min. 190 Ft. 27-440-106 27-440-107 12 1.99 1.29 64 Min 300 Ft 27-464-106 27-464-107 12 2.29 1.39 80 Min. 380 Ft. 27-480-106 27-480-107 12 2.39 1.49 8HC (Cartridge Head Cleaner) 27-400-106 27-400-107 1.19 .79 Reel to Reel (Splice Free Polyester) 189 1.19 5" x 500' 6M 1.5 Mil 21-706-102 12 21-609-102 2.39 1.49 5" x 900' '9M 1.0 MII 12 5" x 1200' 12M T .5 MII "T" \* 21-312-102 12 2.69 1.69 21-315-102 3 69 2.29 2.49 21-712-102 7" x 1200' 12M 1.5 Mil 12 12 3 19 1,99 21-618-102 3.99 2.49 7" x 2400' 24M T 5 M "T"\* 21-324-102 12 7" x 3600' 36M T .5 Mil "T" 21-336-102 5.99 3.99 \* Tensilized Polyester

> NEW LOW PRICES ON SCOTT - HIGHLANDER CASSETTES PLASTIC CONTAINERS.



H-C-30, 30 min \$ .79 H-C-30 H-C-60, 60 min H-C-60 \$ .99 H-C-90, 90 min H-C-90 \$1.59 H-C-120, 120 min H-C-120 \$2.69

DS CASSETTES TDK IS TOPS

# 

SUPER'S



#### SUPER DYNAMIC (SD) CASSETTES

"The Tape That Turned the Cassette Into a High Fidelity Medium"

Gamma fernic oxide, an exclusive TDK high-resolu-fillion, high-efficiency magnetic formulation, has made it possible to achieve fidelity in the cassette medium that could previously be obtained only with resil-to-met decks. The tape offers the following features:

Frequency response from 30 to 20,000 Mg • Increased output level • Minimum distortion
 Expended dynamic range • Lowest noise, best signal-to-noise ratio • No shedding or head wear
 High-reliability jamproof cassette construction

The cassette housings are made of high-impact, heat-resistant styrene plastile of the finest quality, head together with screws. Tipe width for ell sizes le 0.15 inch, Super Dynamic (SD) cassettes are evaliable in the following tope langths, packaged in hinged clear-plastic boxes.

Type	Thickness	Tape Long th	Running Time (Dospie Frack)
C-3080	0.7 mil	150 BL	30 (13 a 2) m mules
C-608D	0.7 mil	300 ft.	60 (30 x 2) minutes
C-0086	0.5 mil	450 R.	90 (45 v 2) minutes
C-1208D	0.38 mc	900 Pt.	120 (60 g 2) minutes



#### MAVERICK CASSETTES

Quality performance at bargain prices. There is no settings in YDX's renowned precision or quality control, Nor is there any attimiging on reliability, internal construction and all drive components used in the cossistic arts identical to the exclusive, ultra-reliable design restured in SD and Deliura Low-Noise TDX.

cassettes
The see-through cassette housings, made of smoked clear acrylic plastic, offer incontestable proof of the premium influence construction. Maverick Cassettes are available in the following tape lengths, packaged in ceruboard mailing boxes:

Туре	Tepe Thickness	Longth	Running Time (Double Track)
C-30F	G.7 mil	150 m.	30 (15 o 2) minutes
C-60F	0.7 mil	300 M.	80 (30 a 2) monutes
C-90F	0.5 mit	950 PL	90 (45 x 2) minutes

WE HAVE FOUND THAT TOK MAVERICK CASSETTES ARE MUCH BETTER THAN OTHER HIGHEST

PRICED CASSETTES



## LOW-NOISE CASSETTES

This "standard" besselle tape by TDK criterie, is acually a high-quelity formulation that is superior to tapes designated as standard in other brands. It is second in quality only to Suber Dynamic tape, with which it has much in common. Many of the malistical used are the same, and the same axtreme care is taken to control quelity and precision through the manufacturing process.

• Extended frequency response • Low noise • High output • No signed dropouts • No shedding • No heed wear • Jamproof cassette construction

The cassette housings are made of high-impact, neat-regalant styrens placified the finest quality. Taps width for all sizes is 0.15 inch. Deluxe Low-holse cassettes are swellable in the following tape lengths, packaged in hinged clear-plastic boxes:

Туре	Tape Thickness	Taps Length	Running Time (Double Treck)
C-30 LN	0.7 mml	150 Pt.	30 (15 a 2) minutes
C-60 LN	0.7 mrl	300 R.	80 (30 a 2) minutes
C-90 LH	0.5 mil	450 RL	90 (45 a 2) minutes
* C-120 LN		600 PL	120 (60 x 2) m-nulins

#### SUPER DYNAMIC (SD) OPEN-REEL TAPE

Engineered for the next generation of tape recorders. TDK Super Dynamic tape on open reets is capable of dramatically improving the performance even of recorders that are old or of modest quality. With reasonably good home equipment, it can produce professional, studio-quality results. TDK-developed gamme ferric oxide is a high-resolution, high-efficiency formulation, consisting of ultrafine particles, that makes possible frequency response far above the capability of human hearing at the normal, high-fidelity tape speed of 7½ inches per second. SD tape yields fidelity as good as other tapes at 7½ lps or better, resulting in twice as much recording time on every reel of tape. Available on 7-Inch clear, smoked-plastic reels and 10-Insh metal reels. Engineered for the next generation of tape recordmetal reela.

Lowest noise, best signal-to-noise ratio . No shed-\* Lowel hoise, best signs-10-noise setto - No shed-ding or head wasr - Frequency response from 20 to beyond 30,000 Mz - Increased output level Au-dibly isse harmonic dislocation - Expended dynamic range - Minimum print-through and "schoes" - Mirror-smooth oxide aurisce - Unmatched output unitarmity - Easy-tood, precision reels



Typs	Capraill Tapp Thinkness	Tape Length	Rarni (Double) (File i)(s)	ng Time ig Track) (3% lps)
1200SB (Large, low- torque hub)	L5 mil	1200 FL	66 (30 o 2) min.	120 [ 60 a 2) min
secos b (standard hub)	1.5 mil	1800 %.	90 (45 s 2) mis.	180 ( 90 x 2) min.
3600\$0 (10-inch reel)	1.5 mil	3600 PL	180 (98 a 2) mia,	360 (160 x 2) min
120	0 SE		52	50

1200 SD (150H-7SD)	\$3.59
1800 SO (150H-7SD)	\$4.99
3600 SO	\$12.49

#### BUDGET PRICED MAVERICK

C-30 F GREEN	\$0.85
C-60 F	\$0.99
C-90 F BLUE	\$1.49

#### **DELUXE LOW-NOISE** CASSETTE WITH PLASTIC BOX C-30 LN

\$1,09

GREEN	100/
C-60 LN RED	\$1.29
C-90 LN BLUE	\$1:99
C-120 LN	¢2 99

### **High Fidelity SD**

the state of the s	
C-30 SD GREEN	\$1.69
C-60 SD RED	\$1.99
BLUE	\$2.99
C-120 SD	\$3.99

#### DELUXE **LOW-NOISE OPEN REEL TAPE**

"standard" tope by TDK's demanding criteria, but comparable to the highest premium-quality tapes available from other manufacturers. It is subjected to the same quality-control procedures as SD tape and shares many of its characteristics. Available on 7-inch clear, smoked-plastic regis.

• Extanded frequency response Low noise High eutput • No signal dropouts No shedding No head weer Mirror-emooth oxide eurace Easyload, precision reels

#### [December Trace) [The spe] [The lips] Tape Tape 2 mil 1200 ft. 60 (30 x 2) min. 120 ( 60 x 2) min. 1.5 mil | 1200 H. 60 (30 x 2) mia. 120 ( 60 x 2) mia. 1.5 mil 1800 ft. 90 (45 x 2) min. 180 ( 90 x 2) min. 1 mil 2400 h. 120 (80 + 2) min. 240 (120 x 2) min \$2.25 150-5 900 \$2.50 100-7 \$2.75 150H-7 \$3.50 150-7 \$5.00 200-7

DEALERS WRITE FOR QUANITY

New 4501 Portable Electronic Calculator. \*\$239.95 manufacture pested retail price.

Craig fills the void in electronic calculators.



decimal point positioning. Pocket size with cord-free capability.

Automatic

rechargeable nickel cadmium batteries.

Mistaken entry clearance without clearing accumulated numbers.

Repeated multiplications or divisions by a single constant, without re-entry of the constant.

> McGEE SPECIAL

The big void: Until now there was no truly portable electronic calculator selling at a low price and performing big desk top machine functions. Now there is one. Craig's new 4501 WHOLESALE Electronic Calculator.

It's even more compact than you'd expect. Only 3" wide, 51/8" long. And an incredible 11/2" slim. Completely portable and rechargeable. Yet it sells for only \$239.95\* and offers all of the big machine features.

NET. \$149.95

List \$239.95

LOWEST COST

MADE IN U.S.A.

CALCULATOR PRICES ON TDK CASSETTES AND OPEN REEL

#### Model DCX2500K Stereo Receiver

# Stereo Receiver

**EQUIPPED FOR 4 CHANNEL STERED** 

The receiver made for the expandable stereo

It's designed for the individual who wants to begin moderately with 2 channel stereo sound ... and eventually, upgrade to a breathtaking 4 channel stereo system

The emphasis is on performance and features that are compatible with 4 channel operation. This solid state unit combines a FM tuner section, with maximum sensitivity and selectivity, and an amphi-fier stage with sufficient power for outstanding 2 channel stereo music reproduction.

Our design concept takes into consideration that power requirements for each of the 2 stereo amplifiers in a 4 channel system can be much less than

A REAL BEST BUY

for the single stereo amplifier in a 2 channel stereo

For example, if fistening room requirements necessitated a 40 watt stereo amplifier as the basic amplifier in a two-channel stereo system, the basic front channel amplifier need only be 24 watts in a four-channel system. The additional stereo ampli-tier required for four-channel operation would normally provide the 22 watts of additional power required for optimum listening levels in the listen-

This receiver was designed for 4 channel operation with the Sanyo Decoder 4, DCA1700X 4-chan-nel decoder-amplifier. The total power of the 2 units in a 4 channel system is 120 watts

## MODEL DCX2300K



#### Stereo Receiver

EQUIPPED FOR 4 CHANNEL STEREO.

This stereo receiver combines a superb quality net stereo lapes

AM/FM/FM Stereo tuner with a direct coupled The DCX2300K also functions perfectly as a 60-watt stereo power amplifier in a compact, high basic two-channel stereo receiver in a two-channel.

performance Instrument stereo system
The DCX2300K is designed for operation as the and outputs. stereo tuner and front channel amplifier in a 2 The performance of the DCX2300K should salisfy channel stereo or four channel stereo system. In the most sophisticated listener. The tuner section conjunction with the Sanyo Decoder 4 DCA1700X has extraordinary clean sound with 2 microvolt it becomes a moderately priced 140 watt four sensitivity (IHF) and unusually low distortion. Frechannel stereo system which reproduces 4 channel quency response is from 10 Hz to 100 KHz 2 db. sound with concert half realism from any two channels.

121111

A REAL BEST BUY

stereo system, it has all necessary controls, inputs

The performance of the DCX2300K should satisfy



# \$12995 BEAUTIFUL WALNUT CABINETS

2 2 2 2 2 2 2 2 2 2 ...

2 1 1 7 7 1 1 7 5 7 8 8

#### Features:

- · Field effect transistor (FET) front end
- Integrated circuit (IC) IF amp mujffplex and power amplifier
- · Fifter and loudness controls
- . Tuning meter

Specifications:

FM SECTION

Frequency range

Antenna impedance Sensitivity (IHF):

Harmonic distortion

Signal to noise ratio

Image rejection: IF rejection: Selectivity:

Stereo separation:

AM SECTION Frequency range

Selectivity:

AMPLIFIER SECTION Total music power (IHF):

Frequency response: Power bandwidth (IHF): Input sensitivity.

langle tuqui mu Hum and noise ratio: Below rated output

For fated output:

Recording output:

suous power (RMS)?

Inputs and outputs for both 2 channel and 4 channel sterso operation

88 MHz to 108 MHz 10.7 MHz 300 ohm balanced 2.5 pV HF

Better than 60 db

e.s db Better than 70 db Better than 70 db Better than 40 db Better than 30 db af 1,000 Hz

540 KHz to 1600 KHz

455 KHz 25 pV at 1,000 KHz 45 db at 1,000 KHz

Better than 25 db

40 watts at 4 phms 30 watts at 8 phms (THO 1.0%)

Less than 1.0% at rated

Less than 1.0% at rated output

100 mV at phone input

Less than 1.5 mV at 8 ohms

20 Hz to 40,000 Hz 30 Hz to 15,000 Hz

Phono 2.5 mV Aux 100 mV Tape 150 mV

Phone 60 db Aux 70 db

2.5 db

Less than 0.8% (400 Hz, 100% Mod.)

Bass control Trebie control
High fillet:
Loudness contro

Volume at -30 db below maximum ower supply. Power consumption

4, 8, 16 ohms ±10 db at 50 Hz ±10 db at 10 KHz 3,000 Hz cutoff ±10 db at 100 Hz ±5 db at 10,000 Hz AC 120V, 60 Hz 55 watts at full power Walnut Tuning Balance Bass Treble

Function selector Phono-AM-FM Auto-aux 1-aux 2 tapa Power Loudness High filter Tape monitor (on function selector) FM stereo light

Stereo headphone jack Speaker output system A, B
Recording output
4 channel output
Phono for magnetic
cartridge
Aux input 1
Aux input 2
Tape play imput

Antenna terminetat

Waight:

Tuning meter.

Headphone jack

Indicator

FM 300 ohms balanced AM external terminal 17%" (W) x 12%" (D) x 5" (H) 12 pounds

ABOUT SANVO: One of the world's largest lindustrial complexes with over 17,000 employees, and more then 300 acres of manufacturing facilities its diversities products cover some 100 categories including radios, television, car stereo, home entertainment systems, audio components, and electronic calculators.

WARRANTY SUMMARY: 1 year repair or replacement of any factory defective component part, exclusive of labos, 90 day free labor.

For full details read the warranty certificate accompanying this product.

SANYO

DECODER 4 DCA1500X

40 WATT STEREO AMP

\$8995

## \$16995

#### Features:

- e Field effect transistor (FET) front end
- · Integrated circuit (IC) IF amp
- e Filter and loudness controls
- · Tuning meter
- Stereo headphone jack
- e FM stereo indicator light
- e Microphone input
- Microphone on/off switch
- Microphone input level control

#### Specifications:

FM SECTION Frequency Renge

Antenna impedance Sensitivity (IHF): Harmonic distort

Signat la noise ratio Capture ratio Image rejection; IF rejection

AM SECTION Frequency range

Sensitivity. (IHF). Selectivity

Better than 70 db Better than 40 db Better than 30 db at 540 KHz to 1600 KHz 455 KHz 25 <sub>A</sub>V at 1,000 KHz 45 db at 1,000 KHz

88 MHz to 108 MHz 10.7 MHz

300 ohms balanced 2.1 aV IHF

Better than 60 db 2.5 db Better jhan 70 db

Less than 0.8% (400 Hz, 100% Mod.)

AMPLIFIER SECTION Total music power (IHF);

Continuous power (RMS):

Frequency response: Power bandwidth (IHF): input sensitivity For rated Output

Recording output: Maximum input signat. Hum and noise ratio: Below rated output

Notes at minimum

60 watts at 4 ohms 45 watts at 8 ohms

Better than 25 db

30 watts at 8 ohms (THD 1 0%) Less than 0.8% at rated output Less than 0.8% at rated purput

20 Hz to 50,000 Hz 20 Hz to 20,000 Hz

Phono 2.5 mV (50 K ohms) Aux 100 mV (60 K ohms) 100 mV at phono input

Pnono 60 db Aux 70 db Less than 1,5 mV at 8 ohms Demping factors Speaker impedance Bass control: Trable control: High filter Loudness contr

Volume at -30 db below maximum Power supply

Power consumption

20 at 8 ohms 4, 8, 16 ohms ±10 db at 50 Hz ±10 db at 10,000 Hz 3,000 Hz cutoff ±10 db at 100 Hz ±5 db at 10,000 Hz AC 120V 60 Hz

105 watts at full power

Treble
Function selector
Aux-phono-FM
sterao-FM-AMI
Speaker selector A
system, B system
Fower
Loudness
High filter
Tape monitor
Mode
Microphone
AMI-FM peak juning
EMI sterao light

Tuning mater. Indicator: Headphone jack: Microphone iack:

Phong for magnetic certridge Aux Tape play input FM 300 ohms balanced AM external terminal 1746" (W) x 1246" (D) x 5" (H)

FM stereo light Stereo headphone jack Microphone input jack

Speaker output system A, B Recording output Stereo 4 channel output

ABOUT SANYO: One of the world's largest industrial complexes with over 17,000 employees, and mager than 300 acres of manufacturing facilities. Its diversified products cover some 100 categories: including radios, television, car stereo, home entertainment systems, audio components, and electronic calculations.

WARRANTY SUMMARY: 1 year repair or replacement of any factory detective component part, exclusive of labor, so day free tabor. For full details read the warranty certificate accompanying, this products.

## ANOTHER MC GEE SPECIAL

DCA I500X WITH 2

#### Features:

- Decodes 4 channel information from any 2 . Use with any Sanyo or other stereo music
- e Built-in power amplifiers (40 watt)
- e Input and output jacks make it essy to connect to an existing stereo music system
- · Has its own balance, tone, and volume controls

#### Specifications:

All solid-state Circultry: Amplifier response: 20 - 20,000 Hz 40 watts Power output:

Volume, tone, balance

Dimensions: Weight:

17%" (W) π 9%" (D) 3½" (H)

Model DCA1500X Decoder 4 Stereo 4 Channel Decoder-Amplifier



MODEL AD DA 8N3N NORELCO SPEAKER

> SYSTEMS \$139.95

## 1972 FAMOUS AR SPEAKERS & AI

LATEST MODELS OF FINEST QUALITY HIGH-FIDELITY SPEAKER SYSTEMS BY WORLD FAMOUS AR Inc.

INC. WORLD FAMOUS FOR EXCELLENT HIGH-FIDELITY SOUND

New Model AR-4X 8-in. 2-Way System

8-in. Woafer 2½ . in. Tweeter



OILED WALNUT ENCLOSURE

Low Priced AR System
Ourstanding Wide Range Sound
Extremely-Compact Design

Model AR-3A 12-in, 3-Way System

12-in. Woofer 2-in. Midrange

1-3/8-in. Tweeter OILED WALNUT



AR's Finest Speaker System

Level Controls and Cross-

Level Confroit und control to the co Model AR-2A 3-Way Speaker System...... \$250.00 Model AR+2X 10-in. 2-Way System

Monfee Woofer

35-in. Tweeter



8 ohms Impedance

Model AR-2X, 2-Way Speaker System....... \$102.00

Model AR-2AX 10-in, 3-Way System

10-in. Waofer 31/2-In. Midrange 1-3/8-in. Twecter

OIL ED WALNUT

Wide-Dispersion Tweeter Independent Level Controls Enclosure Fiberglos-Dampened

Model AR-2AK, D." 3-Way Speaker System gives outstanding performance at a moderate cost. Features a 10-in, acoustic-suspension woofer with a powerful 3½ lb, magnet, plus a 3½ in advance speaker and an efficient 1-3/8" dome-type super-tweeter, Oited willnut enclosure is packed thrusout with freegiess, Independently adjustable level controls and L-C crossovers at 2000 and 2500 cps. Response. 42-20,000 cps. Requires amplifier fated at least 20 waits per channel. 8 ohms imp. 13%24x123." Spp. 43lbt Model AR-2AX, 10" 3-Way Speaker System...... \$128.00 Famous AR "XA" Turntable



With Shure M3D Cartridge

With Shure M44E Cartridge

Superb manual tumtable. Viscous-damped 12" arm. 33-1/3, 45 rpm belt drive, 3½ 1b platter With walnut base, dust cover, stereo cartridge. 5½ x 16¼ x 12½" 115 VAC. Shipping Weight 20 lbs.

#### 100 WATT STEREO HIGH FIDELIT

AR AMPLIFIER THE CRITICS CHOICE



\$250 00

STEREO

Walnut Cabinet \$15.00 extra AR rates amplifier at 100 watts per channel 4-0. -2 db over a 20-20.000Hz

WRITE FOR LAB SHEET

BIGGEST BARGAIN SPEAKER SYSTEM EVER OFFERED IN ECONOMY SPEAKER SYSTEMS.



STOCK NO. RM-84

PRICE

WALNUT-VINYL COVERED CABINET. BEAUTIFULL DARK MATCHING GRILLE CLOTH.

SIZE: 18" long, 10" wide and 51/2" deep. TOP QUALITY SPEAKERS 4" TWEETER,

8" WOOFER, 10 oz. Ceramic, 8 ohm SPEAKER

QUAL TO OTHER SYSTEMS, SELLING AT \$35.00 TO \$45.00

AM/FM



A - 8

BY SELECTRON INTERNATIONAL A good quality

AM-FM receiver 1 watt per

channel. This is a special buy. Only 100 to sell at this low price.

SPEAKER SYSTEM Beautitul Hand Rubbed

With NORELCO 8"

Model AD 8065/W8 WOOFER And NORELCO AD0160/T8 DOME TWEETER

SEE OPPOSITE PAGE FOR EXCEPTIONALLY GOOD BARGAINS IN COMPLETE MUSIC SYSTEMS USING THESE SPEAKER SYSTEMS.

OILED WALNUT NORELCO AD 8065 W8 BAFFLE

8 in HIGH-QUALITY WOOFER 8 ohm, 11/4" VOICE COIL.

1 Ib. CERAMIC MAGNET.

Stock No. DA8N3N

2 FOR \$60,00

CABINET CONSTRUCTED FROM HEAVY 3/4" PARTICLE BOARD WITH FINE HAND RUBBED WALNUT FINISH

CABINET SIZE 10" High, 19" Wide, and 9" Deep

This Norelco 2-way, we believe makes a better system than some big brand units selling up to \$80.00. The cabinet is top quality 3/4" particle board with Genuine Walnut Veneer nubbed finish. The Norelco AD0160T8 Tweeter used in this new system has been acclaimed by several speaker experts as best at any price. We have never seen abetter low cost 8" Woofer. Ship. Wt. 25 lbs. McGee Sale Price \$32.95 each, Two for \$60.00.

# 4-CHANNEL STEREO COMPONENT SYSTEM

STEREO 4-CHANNEL DECODER-AMPLIFIER

A major new development in fright fidelity music

reproduction in designing high fidelity equipment, the engineering goal is a system to bring the sound of live music to the home. Two channel stered was a major step forward in realistic music reproduction. Our stereo 4 channel system is a major technological advance beyond two channel stereo

When recording stereo music in a studio, a number of when recording stereo music in a studio, a number of microphones are usually used to pick up direct sound from the front, as well as radiated sound from the sides and rear. This information is captured on a multi-track tape recorder, then compressed into 2 stereo channels for producing stereo discs and tapes. But all this multi-channel information from various microphones is satill contained within these. 2 stereo channels.

still contained within these 2 stereo channels


The DCA1700X decodes the 4 channel audio information already contained in 2 channel stereo discs, tapes or FM multiples broadcasts, and amplifies it through its stereo power amplifies not a real channel stereo speaker system. The result magnificent stereo 4 channel sound system. The result imagnificent stered 4 channel sour with the breathtaking original sound of the recording studio or concert has

The solid state DCA1700ft, plus a pair of speakers) is all the equipment needed to upgrade any 2 channel stereo system to 4 channel, it greates breathtaking 4 channel realism from any 2 channel source, tapes, discs or broadcasts.

\$169.95

amplifier for any stereo system to reproduce discrete 4 channel 8 track tape cartridges or reel-to-reel tapes But the exciting multi-dimensional sound of the Sanyo stereo 4 channel system goes beyond any other system in

The DCA1700X has built-in pre-amps and all the controls




## Model **DCA1700X**

AMP AND DECODER

Our Decoder-Amplifier also functions as a second stereo

reproducing and creating the effect of live music. Hearing is believing

inputs and outputs necessary for convenient operation and



80 WATT STEREO

#### Model DCA1700X AUDIO AMPLIFIER SECTIO

80 watts at 4 ohms 60 watts 88 8 ohms

East than 0 8% Frequency 10 Hz to 100 response (HHF) KHI F±2 db Power 15 Hz to 100 tendedet (MMF) KHz to 100

2.5 mV (50 K ohms) 2.5 mV (50 K shew)

100 mV 100 mV (100 K ofms) Tape play 3-ch 100 mV (100 K ohms) 4-ch 100 mV 1100 K ghms

100 (50 Hz pt 6 obms)

±12 do (a) 10 KHe? High filter Louisness 5 Ame 6 ab/act

Phono 2, Main separation

AM BECTON BEAUTIFUL BRUSHED ALUMINUM FRONT PANEL

120 V 60 H 100 satts

FM SECTION

400 Hz.

Image rejitt

OF SHIP 69

300 onms

LBaVIN

Better than

Better Hun 80 db

Better than 50 db

200 ohms

Batter Sturt 35 dip at 1,000 Hz

Model FMT1400K Model DCA1400

Pewer Imply:

AUDIO AMPLIFIER BECTION

Image rejection Better then 50 db

Bighat to make Better than 1810 50 00

Better than 30 db 0 7 solt ±3 db

120 V 60 Hz

8105

Frequency (007) (0) Hz to 100 responses (007) (0) 1+2 db Power 15 Hr to 100 hondwidth, (MF) KHz I . 1 doi:

2.5 mV (50 K olems)

100 mV (100 W shrms Aux 3 100 mV 100 mY (100 K phms.)

75 db Let below refed output]

Dumping Sector 100 ISO Hz at

3:12 db (a) 50 Mg1 5 KH2 -6

> 100 Hz +10 pt Aun 1, Aun 2, Turen, Face play

Speaker A Speaker A Speaker System B Pre-amp out Rec out Headphone (acti Irraria panel) 4 channel output

300 watts 11%\*(0) 10\*(0) =

Model 7980S

8 shaped arm with lateral belance. Plug-in cartridge

1815"(W) x 15"(D) x 7%\*(EH)

#### SANYO Model FMT1400K AM/FM STEREO TUNER



ONE OF THE BEST TUNERS WE EVER

TESTED

Stereo receivers have been accepted in audio engineerin circles as cheving good performance at some cost saving, compared to separate components. But a combination tuner and amplifier represents a design compromise with inherent problems of noise, resulting from a common power supply and close proximity of electronic circuitry components

Our objective in designing this 4-channel system was uncompromised performance. So, our tuner and our amplifier are in separate housings. Each with its own

The performance requirement we established for our tuner was a unit with the most perfect (noise-free) FM stereo consistent with extreme sensitivity reception obtainable. and selectivity for excellent reception in both strong and weak signal areas

Our conservatively rated performance specifications for sensitivity, selectivity and capture ratio are proof of design excellence. The very low harmonic distortion, 75 db image rejection, 65 db signal-to-noise ratio, and remarkably flat frequency response are further evidence of our achieving exceptionally clean, noise-free undistorted reception.

Both the front end field effect transistor (FET) and integrated circuits (IC) ireflect the latest state-of-the-art in electronic design to make this tuner one of the most outstanding available today.

Other features include:

- Selective muting circuitry
- Switchable multiplex noise filter Back-lighted tuning dial
- Turing meter
- Precision fry-wheel turting

## **SANYO** ■ Model DCA1400 STEREO AMPLIFIER



80WATT STEREO AMP REAL PRO LOOKS NO BETTER STEREO AMP \$139°5 ANYWHERE ...

This 80 wait component has power enough to drive almost any-speaker system

It assures no loss of music centent by providing an exceptionally flat frequency response from 10 Hz to 100 KHz Harmonic distortion is well below 1% at rated output. Signal-to-noise ratio is better than 75 db with tuner input. The DACA1400 has a full complement of operating controls to allow anyone to completely control the sound to his listening tastes. There are two speaker system outputs, separate pre-amp output, main amplifier inputs, several phono inputs, tape recorder inputs and outputs and

In combination with the Sanyo FM1400K stereo tuner and the DCA1700X 4-channel decoder-amplifier DCA1400 amplifier creates a high power (160 watts) 4 channel music system that is completely unique in performance and significantly superior in sound to any 2 channel stereo system

One of the world's targest industrial complexes with over 17,000 employees, and more than 300 acres of manufacturing facilities. Its diversified products cover some 100 categories: including radios, television, car stereo, home entertainment systems, audio components and electronic calculators. largest industrial. components, and electronic calculators

#### \$139°5 Model TP80S **AUTOMATIC STEREO TURNTABLE**



BEAUTIFUL WALNUT CABINET DUST COVER COMPLETE WITH SHURE M 933 CARTRIDGE

YOU MAY SELECT ANY OTHER RECORD CHANGER OF EQUAL PRICE OR VALUE 2-DA8N3N
FOR YOUR COMBINATION SYSTEM. 2-DAILY-3

TO COM CONTROLLAND WITHOUT STATES AND CONTROLLAND WITHOUT STATES AND CONTROLLAND WITHOUT STATES AND WITHOUT

ospencts on how wall fills machanical campaneous person. The FRBGS time motor primates precisely regulated sweet to wood won flutter and fredisinery abbrerations, requising from minute sceed variable it is a four-pole hysteries synchronous motor with a sceed regulation of 99 fills, regardless of varying line voltage its self-aligning bearings eliminate any cogging action and performance deterioration due to finance.

bearing west.

Transmitting power to the drive motor is accompossed through its temperature humidity stabilized but system.

This assumes the longest listing and unpromises energy transmission to postate the furnitable. This satisfaction is a summum, machiging to close tolerance the summum, the stable platform with practice, long-testing sover-registration. The tone arm has adjustments for stable batteries, and to tracking force adjustment from 0.5 is 4 ginners. The "Sime or arm is deligible Any standard selection carridge may be plugged in.

The Samys TROS can be operated manually of programmed for automatic fore arm return and automatic stop at the end of a stereo disc. To prevent camage to discs, a practision curing system gently owners the tone arm at any overice position on the disc.

ONE OF THE WORLD'S FINEST TURNTABLES

### COMBINATION OFFER OF SANYO

\$579.80

1- DCA-1700X

1- FMT-1400K

1-DCA-1400

1- TP-805 All for \$579.80 plus Four speaker systems

obsolutely FREE 2-DAILY-3

SPEAKER SYSTEMS This is the biggest Quad stereo VALUE in 1972. Equals better

than a 20% discount.

## **LENCO B55** LENCO L75 LESS BASE AND DUST COVER DELUXE BASE LESS BASE AND DUST COVER DUST COVER \$1 95

The Lenco B 55 is a superb turntable unit which was developed for the discriminating music lover.

The technical advantages of the B 55 are as follows

#### Head of tone-arm

Interchangeable light metal head-shell, for use with all cartridges

For accurate setting of the needle, to achieve a minimum tracking-error.

The turntable is driven through an accurately ground idler wheel by a very quietly running 4-pole-motor. The idler wheel is movable along the conical shaft of the motor so that the speed of the turntable may be adjusted continuously between 30 and 86 r, p, m.

tens he-plate of chest-steel Sheph 375 K300 mm (A,p.r.21 8 in

pol of tens-arm above mounting: 52 mm 2.9 in-leance necessary under int-ng-plate \$2 mm 2.4 in-

Weightin.
Turnishin of sheet blest 6-979 fits.
Shick is a special player
Total weight of record player
BE 9, 12 E 85.
Gross weight 63 bg 14,8 fb.

4-pais complaint velocity matter with consical shaft Setting bit 115 at 220 vorts, 50 or 80 cyclen Phone naguland at 889 V, 40 or 85 cyclen 14 or 85 cyclen 15 v.

#### Manual switch

There is a knob for turning on the motor and hydrauli-cally lowering the tone-arm onto the record. This arrangement protects both the needle of the carfridge and valuable records. Automatic disengagement of the

DELUXE BASE DUST COVER

\$1995

All the speeds available are selected with one lever, including the accurately pre-set speeds of 169/s, 331/s, 45 and 78 r, p. m.

The tone-arm rests horizontally on two inverted v-sha-ped fixed metal bearings that are entirely free of play and vertically on two special ball bearings. The pressure of the cartridge upon the record can be adjusted accurately by means of the aliding counter-metable.

Antiskating bias compensation to minimise inner groove distortion

#### ol «Renectarialica continuously sojusioble from Speed continuously adjustable to 30 to 66 x p m. Positive cliest-in expedier to 45. 137s, 45 and 16 r g, m

Temp-rents:
Propours of forte-from to adjustible
eith a counter-weight
binimum pressure for playing its 1/5 s.
Rencovable rightnessight plug-in Read
for use well at laceholdes
Length ell pane-arm. 286 ozen § 08 at

Weights

Weights

1.2\* Waights

According to DNI dates

1.2\* Toniclose of discovered print

From Figure 4 vinitable

4 db unit complete distribute

7 void enging of vinitable

4 db unit complete distribute

7 void enging of firmatible

8 db units of firmatible

7 void enging of firmatible

9 db units of firmatible

7 void enging of firmatible

9 db units of firmatible

9 db units of firmatible

7 void enging of firmatible

7 void enging of firmatible

7 void enging of firmatible

9 db units of firma Speed Change for ± 10 % major voltage change = 2.5 - 2 × 17 miles voltage change = 2.5 - 2 × 17 miles (2.6 75 - 6 miles) = 10.7 miles (2.6 75 - 6 miles) = 10.7 miles (2.6 75 - 6 miles) = 10.7 miles (2.6 75 - 6 miles) = 10.5 miles (2.6 75 - 6 miles) = 10. 8 05 0

### Swiss quality is built into the Lenco L75

The sophisticated Lenco L 75 is a superb turntable unit which was developed for the discriminating music lave are. The L 75 is a further development of the world—ignored by the use of a heavier and dynamically—balanced turntable. The achieved specification has been improved by the use of a heavier and dynamically—balanced turntable. The achieved specifications exceed in all cases the values stipulated by the DIN stansord for high quality record players.

The technical advantages of the L 75 are as follows—Dynamically balanced non-magnetic lurntable decast from zinc alloy weighing 4 kg, with a large dismeter of 312 mm.

Infinitely variable speed adjustment, which quality 4-pole motor with conscal rotor shaft.

High quality 4-pole motor with conscal rotor shaft.

Hi

Pick-up are Pick-up are with counter weight Raftle edge Bearings Stylus presenter adjustable from 6.5 for 5.6. bit shelling counter beforced General Pick-Up are shelling are shelling as the shelling as the shelling are shelling as the she emicelly beranced turntable reulically operated lifetimes. e and hulter means ording to DHz elad

TONE ARM HOLDS ANY STANDARD CARTRIDGE

#### BIGGEST BARGAIN IN U S A. IN 3 WAY 12" SPEAKER SYSTEM

24" HIGH, 14" WIDE and 10" DEEP MADE OF %" PARTICAL BOARD COVERED WITH THE NEW WALNUT VINYL LAMINATED FINISH

SIZE:

S TOCK NO DAILY-3

TWO for \$58.00 Shipping Weight 40 lbs. Power handling up to 40 watts

1- 12" CTS., WOOFER, Accordism edge high compliance.

10 oz. Alnicp V' magnet 8 ohm Voice coil
1- 8" MID-RANGE, Fully enclosed back.

MATCHES ANY

2-3X5' NEW TWEETERS, Fully enclosed back. 8 OHM SYSTEM.
BUILT IN CONDENSER CROSS-OVER FREQ. RESP. 45 to 17,000 CPs. Model DAILY - 3., A low cost Speaker System featuring a 12', 3 way conderser cross-over system, with 8'' mid-range and two 3X5 tweeters Exceptionally good base response, matches any 8 ohm amplifier

NEW LOW PRICE ON 3 WAY SPEAKER SYSTEMS WITH THE FAMOUS No. C177A GOODMAN 12 in. WOOFER



SIZE; 24" HIGH, 14" WIDE and 10" DEEP.

CARTRIDGE NOT FURNISHED

and

HIGH QUALITY 8 in. MID-RANGE PLUS 2, 3X5 SPECIAL TWEETERS. WITH BUILT IN CONDENSER CROSS-OVER STOCK NO.

**DG-3** 

Power handling up to 75 watts MUSIC POWER

FREQUENCY RESPONSE 35 to 18,000 CPS TWO for \$78.00 SHIPPING WEIGHT SO LBS. MATCHES ANY 8 OHM OUTPUT.

MODEL DG-3, A 12°, 3 way Speaker System gives outstanding performance at a low cost. Features a GOODMAN 12° woofer with a powerful 2 lb, 12 oz. ceramic magnet, plus a 8° mid-range speaker and two 3X5 special tweeters The condenser cross—over is adjusted at 2000 and 6500 cps. Response 35 to 18,000 cps. System will handle up to 70 watts music power, 8 ohms imped.

This Beautiful Laminated Vinyl Finished WALNUT wood baffle and Speakers makes one of the funest lower cost speaker systems that we have ever offered to seil. The baffle is made by a new process. It is constructed of %" partical board covered with vinyl. WALNUT ( looks like hand rubbed finish) Entire baffle is made of one flat sheet of wood grooved and assembled. This process produces a cabinet with out seams at the corners, very hard to scratch or mar.

## JVC'S NEW DIMENSIONS IN FULL SYSTEM STEREO COMPONENTS

5444 C STOCK NO. 5550 STOCK NO 5020 000 STOCK NO 5010 **၁၁**၁၁၁ 0000

> JVC TONE IS THE REAL KING WRITE FOR FULL DISCRIPTION ON ANY THESE MODELS.

JVC IS JAPAN'S OLDEST ELECTRONIC MANUFACTURERS ratio is an exceptional 0.8dH, spurious rejection

5444

PRICE

200 Watt FM/AM 4-Channel Stereo Receiver with S.F.C., SEA.

Receiver with S.F.C., SEA.

Now one of the world's few discrete 4-channel stereo receivers, the JVC 5444, is ready for your living room. Incorporating a 4-channel preamplif fier, a 4-channel power amplifier, JVC's unique S.F.C. (Sound Field Composer), advanced 4-channel SEA tone control system and sensitive FM & AM tuners, the 200 watt 5444 receiver is years shead of it's time in every respect. The S.F.C. element means you can continue to enj oy your 2-channel program sources in the new 4-channel format, as well as discrete 4-channel program sources as they become available rich in IC and FET circuitry, and complete with just about every type of accessory circuit imaginable the 5444 offers a wide 20 to 50,000Hz frequency response and limits distortion of any kind to a response and limits distortion of any kind to a mere 0.8% or less. Complete with walnut cabnet 5-7/8"H x 22-7/8"W x 13-W"D. 33lbs.

5550 PRICE

220 Watt FM/AM Stereo Receiver with Advanced SEA.


This is the top of the line of JVC's new senes of steren receivers. Powered at a big 220 watts, it is ready to brung you 4-channel stereo in 3 ways by coupling it with a 4-channel decoder for the 4-channel FM broadcasts of the future: by 4-channel IN broadcasts of the index. Of the coupling it to a discrete 4-channel tape recorder or record player to enjoy, discrete 4-channel tapes and records now, and by teaming it with the Sound 4 teld Composer-equipped \$100 steres 40 Watt FM Stereo/AM Receiver with FET FM Frontend to the Sound 4 teld Composer-equipped \$100 steres 40 Watt FM Stereo/AM Receiver with FET FM Frontend power amplifier to enjoy your present 2-channel records and tapes and FM stereo broadcasts in 4-channel format. The \$550's layest circultry includes two I I Is and two ICs, it boasts a truly exquisite EM tuner section, a wide 15Hz to 30KHz power bundwidth, plus advanced SI A 1Sound Effect Amplifiers super tone control system, and much, much under, 5-7.8°H x 19-3/8"W x 14-1/2"D, 28-6 lbs.


JVC FULL SYSTEM STEREO COMPONENTS

NEW BREAK-THRU IN TONE CONTROL SYSTEM

SOUND EFFECT AMPLIFIER (SEA) CONTROL SYSTEM

SEA Frequency Control Characteristics





degree of precision unattainable in other tone control equipment. Most simply stated, it allows any person to tailor sound to fit any size room. With SEA you can create sound, almost any sound you prefer at any time. And you can also forget about acoustical problems in your room which may play havoc with more conventional stereo receivers.

The Charts above compare the characteristics of SEA and those of standard tone controi systems. Note that SEA provides a steep rising slopa, whereas the normal tone conlimited to 6 db/oct. Note also that the SEA frequency band can be increased or decreased in narrow widths, from 10 to 12 db/oct. This is the kind of performance that allows the user to compensate for complex frequencies.

The extraordinary thing about this JVC innovation is how it converts any room into a first-class music room. SEA is made for experimenting, testing and enjoying the widest range of sound you've ever heard.

There are many ways to document the superior quality of JVC's developments in stereo equipment, but none better than the recent experiment which compared a JVC Sound Effect Amplifier (SEA) with a live orchestra. During this unusual performance, the Japan Philharmonic Orchestra ceased playing at a predetermined note and the JVC stereo equipment completed the musical selection. Of the 1,621 audio professionals and music critics who comprised the audience, less than I per cent were able to detect when the live sound ended and the recorded sound began. Even more astonish-

ing, however, was the fact that JVC used the

same stereo equipment for this experiment

From very powerful and professional components to all-in-one compact units, JVC makes a line of stereo equipment that is

hardly rivalled today by any audio manufac-turer. This line is complete and offers the

consumer a rare flexibility of choice, a wide

price range, yet uncompromising standards

Of all JVC stereo developments, the one

which probably has attracted the greatest interest among sound experts is the Sound

Effect Amplifier, a super tone controller quite unlike the tone control used in any conven

What SEA does so well, is permit tone com-

pensation in any style room by dividing the audio frequency band into five or seven fre-

quency ranges. This permits tones throughout

the eudio frequency band to be adjusted with

of quality.

tional amplifiers.

that is available to the home stereo fan.

140 Watt FM Stereo/AM Receiver with Advanced SEA.

In the same great tradition as the 5550 is this 140 watt receiver that is perhaps without peer in the medium power range. Like its more powerful sister model, the 5540 is equipped to give you access to the new world of four-channel stereo in any of three ways, so its a wise investment for the future. The I M tuner combines a 4-gang tuning capacitor and two K's, plus four double-duty ceramic filters (equal to eight ordinary onest, and two HTs, Its capture

90dB and HIP sensitivity is an exquisite 1.7 V. The 5540 is also complete with a 12dB SEA super tone control system, a'linear FM dial scale, two tuning meters, a versatile speaker selector control, and front-panel TAPE RE-CORDING and PLAYBACK jacks, 5-7/8"H x 19-3/8"W x 14-3/8"D, 25.3 lbs,



\$24995

75 Watt Stereo Receiver with Advanced SEA

Mall Stereo Receiver with Advanced SEA Big receiver price tag. The finest stereo value ever in the medium, power range, the 5020 gives you advanced SEA control within 2 12db with control click stops every 2db, a new FM linear dial scale especially effective in FM-flooded metropolitan areas, IC and FET circuitry and enough power to drive two speaker systems simultaneously. Technical features include a built-in muting switch, and automatic FM stereo switching. You'll do a lot of hopeless searching to find anything more complete. 5-7/8"H x 20"W x 13-3/16"D 28.6 lbs. (with wooden cabinet).

Ideal for those who don't require prodigious power, but who want something more than just music. Unsurpassed in its range, the 5010 offers advanced SEA with knobs that click up or down in 2db, steps within a range of ±12db, it also adapts the new FM linear dial scale, and features an improved FET front end for greater FM sensitivity and selectivity. Complete with a special protector circuit and capacity to power too speaker systems at once, the 5010 features a modern black (ace dial and expensive wooden cabinet as standard equipment, 5-3/8"H x 16-11/16"W x 13"D.

SOLID STATE FM/AM MULTIPLEX STEREO TUNER AMPLIFIER

\$399°5 AA-8500



Only one word "COMPLETENESS" can de scribe this Solid State AM/FM Multiplex Steron Tuner Amplifier by AKAI. Equipped with every connection for Wide and Diversified

Imaginative Styling with NEW TYPE DIAL MECHANISM. Years ahead in performance with Space Developed Integrated Circuits and Field Effect Transistor.

240 W (120 W/120 W) at 4 D 180 W (90 W/20 W) at 8 D 170 W (85 W/86 W) at 4 D 930 W (85 W /86 W) at 6 D Lusy then 0.05% at 8 S 20 to 30,000 Mz at 8 D

20 to 50,000 Hz (-3 d6) 20 to 50,000 Hz (-3 d8)

Setter than 60 dB Better than 60 dB RIAA Last than 1 dB

SHIP WEIGHT BO LBS.

AMPLIFIER SECTION

Power Cutput Music Power (IMF)

thermore Dimerman.
Power Bandwork (IMF)
Frequency Respons:
Als assemble terming treat
Aut
Power
Prono
Also
Helia

Din Pre President Programme State President Pr

FM Mute Audio Mute

#### OUTSTANDING FEATURES

OUISTANDING PEATURES
2 and WIZO WINNER Pear II New Diel Machanien 6 Rg Carenic
Figure 6 FET (Fleid Effect Translater) and IC (Integrated Creatif altered
Figure 6 FET (Fleid Effect Translater) and IC (Integrated Creatif altered
Prisonpolities and files Ampetitor, Use of musti-channel amention possible,
6 All Silicen Translaters of Translater Protester Cerost 6 Fet and Ast digital
extengis means and FEE Automater Frequency Control for prefer tuning.
8 State Type Statem, Trails, and State Commission with only mid-range certifies
Between Mediciner and DRI Automater Between Statement and Peters.

B System, A + 8 System, and OFFI if Lost Filter, High Filter
2 A D.

	240
ECIFICATIONS	-WATTS
FM TUNER SECTION	MAIIS
Frequency Range and IF Frequency Frequency Range	MUSIC
IF Frequency	POWER
Mono Law then 0.3%	
Storeo Less than 0.8% (Modul Signal to Redox Hatto Bertis than 70 dB	ation 100% 400 Hgl
Selectivity Butter then 85 d8 Capture Retire 1.5 dm (1965)	
Frage Fraguetcy Reco Better then 100 dB at IF Rejection	
Spurious Radiation	unbalanced
FM Stereo Separation Better then 40 dB	

AM TUNER SECTION Frequency Range and IF Fre Frequency Range IF Frequency Sensitivity (IHF) Quintry 535 kMs to 1605 Hz 455 kMs

10 dB at 1 MM/s 100 at V/M Better then 80 dB at 1 MHz Better then 80 dB at 1 MHz DX Better then 60 dB h. Fill Service then 75 dB at 12 dB 0 0 m. (400 Mz 30% Abod. AM Distortion ... Her then 55 de 1400 Hz 30% Mod S/N Retre .....

SEMI-CONDUCTORS

Silicon Tr 85, FET 1, IC 2 Hors, PET, and IC

POWER REQUIREMENTS

100 V to 240 V (50/80 Mz) 350 W 19-1/4" (M1 to 14-1/2" (D1 to 2" 34) 487 (W1 to 346 (D1 to 165 th) pres 35/3 (bs. (16 kg)

3-WAY Stock no. MAT-1040

Price MATCHED

\$78.00

KI-FI

Speakers

0 95

Fine Furniture Quality Base ported back Guality Base ported back

HEAVY WEIGHT 40— WATTS

4 SPEAKERS IN A 3-WAY SYSTEM

1 SPEAKERS IN A 3-WAY SYSTEM

1 SPEAKERS IN A 12-20,000

BAFFLE 18 MADE OF 1 IN HIGH DEN

SITY WOOD PARTICAL BOARD WITH A

WALNUT SURFACE AND BOT LACOURE

LOW USTER FINISH. SPEAKERS IS THIS

SYSTEM ARE FACTORY MATCHED SETS

FROM NATIONAL OF JAPAN () IDENT
FIED IN U.S.A AS PANASONIC ALSO

MATSUSHITAL EXCELLENT BASE RES
PONSE AND SOUND SISTRIBUTION.

SIZE 24 X 14 X 10 IN, DEFP

Mode By MATSUSHITA

4 speakers in each Baffle

2-10" WOOFERS with 1 lb. magnet 2 -4" Mid-range 4 - 23/1" Tweeters.

# AA-6600 1299°



THREE YEAR WARRANTY

#### OUTSTANDING FEATURES

- . FET (Field Effect Translator) front-and for
- extra FM exembleity IC (Integrated Circuit) in IF stages for high
- intertienty \$20 W (80 W/80 W) music power FM-AMI signal scientish meter and contentuming meter for perfect tuning

#### SPECIFICATIONS AMPLIFIER SECTION

POWER OUTPUT MUSIC POWER (INF)

CONTINUOUS POWER
MARMONIC DISTORTION
POWER BANDMIDTH (HIFF
FREQUENCY RESPONSE
(AN NORMAL LISTENING
LEVEL)
POWER AMPLIFIER
SECTION

AUX
INPLIT SENSITIVITY
Ifor retail output
PHONO
AUX
TAPE MONITOR
IPID Jack

TAPE MONITOR (OIN)
RECORDING OUTPUT
(Pin Jack)
(OIN)
HUM AND NOISE VOLUME MINIMUM

AUX
CHANNEL SEPARATION
(as raid output) PHONO OUTPUT IMPEDANCE

PHONO
CONTROLS AND SWITCHES
BASS CONTROL
TREBLE CONTROL
LOUDNESS CONTROL

LOW FILTER

MIGH FILTER MODE SWITCH SELECTOR SWITCH SPEAKER SWITCH

+10 dB --10 dB at 50 Hz +10 dB --10 dB at 10 KMz 100 Hz + 6 dB 10 KMZ + 3 dB (Volume control at -30 dB) -8 dB at 50 Hz -6 d8 of 10 KHz STEREO/MONO. 1, PHONO 2, AM 3, FM 4, FM MUTE 5, AUX 1, OFF 2, SYSTEM A 3, SYSTEM 6, 4, SVSTEM A + 8

Better than 50 dB Better than 50 dB 4 ~ 16 G

120 W 660 W/60 W/ et 4 B 100 W (50 W/50 W) et 8 Q 75 W (27.5 W/37.5 W) et 8 D Late then 0.8% at rated outpu 20 ~ 30,000 He et 8 B

20 ~ 50,000 Hz ~ 3 dB 20 ~ 50,000 Hz ~ 3 dB

200 mV

200 mV

BIAA

Electro-Voice high fidelity electronics are guaranteed for three years from date of purchase against failures due to defects in workmanship and materials. If such failure occurs, unit will be repaired or replaced (at our option) if derivered to Electro-Voice or its service agency. There will be no charge for parts or return freight during the entire length of the warranty puriod, no charge for labor will be made during the first year of the warranty puriod, warranty does not cover findshes or failures due to above or operation at other than operfigir failings. Repair by other than Electro-Voice or its authorized service agencies will word this guarantee.

120

WATTS MUSIC

POWER

re jack, DIN Jack

#### TUNER SECTION

MAGE PREJECTION
FREJECTION
FM STERED SEPARATION
FM STERED SEPARATION
SPURIOUS RESPONSE
REJECTION
SPURIOUS RADIATION
ANTENNA INPUT
IMPEDANCE

AMPEDANCE

AMPEDANCE

FREQUENCY RANGE

SENSITIVITY (INE)

IMAGE FREDUENCY

SEMICONOLUCTORS

SEMICONOLUCTORS

TRANSISTORS, FET & IC

DIODES

VARISTORS

POWER NOCUTAGE

POWER CONSUMPTION DIMENSIONS

Awtometic FM derrest/mentures switchin FM reception is au tometically excited from metero to standard switchin room metero transp.
 Speaker system selector for hazading one two cerest speakers in reverse redividually smillsnootouly (System A. Bystem Svesena A. B see OFF)
 Troc mentures descriptly derived.

Titus manifer Switch, Stereo mude of Levilleus control
Levi filter, High titler
Base control Trable control

FM
PREQUENCY RANGE
SENSITIVITY
HARMONIC DISTORTION
SIGNAL TO NOISE RATIO
SELECTIVITY
CAPTURE RATIO
IMAGE PREQUENCY
REJECTION
SELECTION


88-108 MHz 2 gV (INF) 3 see than 0,8% Better than 60 d8 Better than 60 d8 at 98 MHz 2 d8 (IMF)

535 ~ 1,805 KHz 20 mV at 1 MHz

Better than \$0 dB at 1 MHz Better than 20 dB at 1 MHz Tr. 33, FET 1, IC 1,

100 ~ 240 volts 50/60 Hz 180 W (mae.) 5-1/4" x 17/4/2" x 13/3/8" 11/37 x 46/x 340 mm) 24/4 fbs (11/1 hg)

#### McGEE GIVES YOU A PAIR OF THESE BEAUTIFUL SPEAKER SYSTEMS - FREE-



WITH EITHER THE AA8500 OR AA6600 AKAI RECEIVERS SHOWN ABOVE THIS IS A HOT BUY A McGee SPECIAL .; FOR FULL DESCRIPTION OF THE DG-3 & DAILY-3 SPEAKER SYSTEMS SEE OPSITE PAGE .

Purchase a Model AA-8500, AKAI Receiver at the regular price \$399.95, and receive 2 - model DG-3 speaker systems priced at two for \$78.00 ABSOLUTELY FREE. This is the buy of '72. Stock No. AA8500-DG-3 Special \$399.95

Model AA-6600, AKA1 Receiver at the regular price\$299.95 and two FREE, Model DAILY-3 speaker systems priced at two for \$58.00. Stock no. AA-6600-DAILY-3, SPECIAL \$299.95.

#### FVR-1 Electro-Voice -K- Electro Voice <- } Electro-Voice

110 watts AM/FM stereo receiver





Many important features clearly mark this receiver as a top value, Power output of 110 writis (complete openifications on tast page).

All sifteem will civitate elecutity built on modular, extended-circuit boards savires long-term reliability and maintenance of original specifications.

Outstanding EM tome pur formance in achieved by coupling a winstiver FET (feeld effect transitor) front end to a highly workfleated, low distortion if section. Two ceramic filters plus two integrated circuits in the IF section offer superby electricity, excellent interference rejection, and low distortion. An additional IC in the AM section greatly improves standard broadcast performance. A fourth IC in the multiplex section provides unistanding stereo separation and reduces distorition to inagenflicate levels.

The preamptifile-fine control section in 01 extremely wide-range, low-distorition design.

The powerful output section utilizes the latest efficient power transitions for dependability and is completely protected against accidental short circuits. Features include a center-tune EM meter (tywhed weighted tuning action, built-in EM arternal play 75- and 300-ohm terminals, built-in AM aniconal and external terminals, tape output sacks, connections and switching for two vets of steres speakers, headphone Jack, writched AC outlet, 4-position input selector, strend from the vettor, stereo signal, whichable buddness compensation, balance control, and separate bases and treble controls.

#### PERFORMANCE SPECIFICATIONS

AMPLIFIER SECTION	EVR-1	EVR-2	EAII-3
Output Power			
Total Human power 21 dB into 4 ohms	140 watts	125 watts	300 marts
Total 1995 power into 4 shims	90 watts	140 watts	250 main
Total RM5 power into 6 ohms	34 watts	54 watts	90 watti
Total Harmonic Distortion			
[Maximum to full syred output]	012%	0.25	0.2%
Intermodulation (IM) Discorden			
(to full cases output -60 & 7000 Hz)	0.2%	0.2%	0.2%
Fower Bandwidth - In Ha	15-20.000	15-20,000	16-20,000
Frequency Resource at 1 wast £23 dB) Hz	10-50,000	10-50,000	10-10,000
Input Sensitivity for full owenur-	-		
Magnetic Phone	2.5 mV	2.5 mV	2.5 mV
Auxiliary/Tape	250 mV	250 mV	250 mW
Tage Monitor		25 D m/V	250 mV
Num & Naise-Phone	-60 dB	60 dB	-60 48
Applitary/14pe	-70 dB	-70 dB	-10 dB
Tone Control Range - Bass (at 100 Hiff	*10 dH	\$10 dB	110 48
Treble [at 10,000 Hz]	#10 46	\$10 dB	±10 dB
High-Filter Action—as 10,000 Hz			-3 48
Slope			6 d5/octave
	1	1	01

AM/FM stereo receiver

		-	-	Л
specifications for amorganization of the process of	Here's a receiver loaded with features and topnoists specifications for the performance-minded audiophile at a price within reach of any component buyer. Power or other in a robust 15 watts (complete specifications on law page). It's watts (complete specifications on law page), includes all the design leadures described at leff rilusions of the specification of th			
FM TUNER SECTION	1	1		
Tuning Range MHz	25-106	88-108	<b>88</b> -108	
Sensitivits - IHF	2.3 uV	2.0 uV	1.9 uV	
Signal-to-Noise Ratio	65 d9	65 48	65 48	
Capture Ratio	2.5 📫	2.5 18	2.3 48	
Total Harmonic Distortion at 1000 Hz (Mahimum, to 100% modulation)	0.8%	0.3%	0.3%	
Soundus Response Rate crion	70 dB	70 dB	70 dB	
MULTIPLEX SECTION				
Steren Separation at 1900 Have 100% modulation	10 dH	)D d9	35 dB	
19 kNs Resection	60 48	60 48	60 dB	
38 kHz Resction	70 de	70 48	90 dB	
AM TUNER SECTION				
Tuning Range MHa	\$15-1605	535-1605	\$35-1605	
Spenitrety uV Meser	125	125	125	1
Image Rejection - at 600 kHz	60 dB	60 dB	60 DB	

DIMENSIONS-ALL UNIO

AM/FM stereo receiver

For those who writ occup:

The final power of the f

These are 3 of the few receivers made in USA. Write for prices on complete systems using these or other receivers in this catalog. Will

answer at once.

THESE RECEIVERS ARE DESIGNED, ENGINEERED, AND MANUFACTURED IN THE U.S.A.

## DENON

RAdoption of FIT (field Effect transistors) at the FM front end and three-gaint variable capacitor improve the effective selectivity, cross modulation and image ratio as well as sensitivity and signal to noise ratio.

Music output power attains 80 watts (peak music power) due to the use of SEPP OTL circuft, and high performance silicon power transistors.

The FM multiples section is equipped with an electronic monaural secret automatic sanschung circuit, and ai pilot lamp

The Indi multiples secretal is equipped with an execution, monospia sector association for the secretal interpretation of the steero programs. Permits easy, connections to two sets of stereo speaker systems, heady only if simple lunds turns systems simple landerously or one at a time.

systems smultaneously or one at a time Provided with steepo headphore lack to permit private listening. Provided AC outlet (200 watts maximum) Provided Tape input and output lack When opening the control to the control to the control comes into switch on automatically Built-in RSI line cond antenna with remixable connection Built-in RsI sensitivity AM territe ancema.

BEST YET!

SOLID STATE AM/FM STEREO RECEIVER

MODEL MX-996

\$139.95

SPECIEIC ATIONS.

FEATURES:

SPECIFICATIONS:		No.
Circuit	21 transistors (including )	FET) plus 3 transistors for FM MPX and FM Sterep Indicator, 19
	diodes Super Heterodyne	System
Function	AUX TAPE FM STEREO	M. AM. PHONO.
Power Source	AC 130 V 60Hz	The second secon
Power Comsumption	Q.4A	
Output Power	80 Walts peak music pow	ver
Output Impedance	4 16 ohm!	The state of the s
Anténna	FM. Line cord anterwa buil	t-in and 300 phras symmetric external antenna terminals equipped
-	Add High Sensitivity ferry	te bar antenna.
Standard broadcast (AM): "(III	Tuning cange	535 1605 KHz
	Loop sensitivity	(d0 KHz 200gV/m
		1400 KHZ 1\$0#V/III
the state of the s	20 dB 5 N Sensitivity	600 KHz 300aV,m 1400 KHz 200aV,m
	Image Reject	1400 KHz 44 dB
	(E. Reject	600 KHz 33 dB
	ACA	600 KHz 30 dB
	AVC Figure of ment	45 dB
4	IF.	455 KHz
FM:	Tuning range	00~108 MHz
· ·	Max Sensitivity	90 MHz 8eV, 108 MHz 8eV
,	30 dB quiet Sensitrvity	90 AME TOWN 108 AME 10sV
	Image Reject	108 MHz 45 d8
	AM Suppression	0 0
	1 d0 Limit	30 aV
. L 0	DIF Sensitivity	7.5 gV
	FM MPX Separation	30 pB
	S.C.A. Attenuation	36 dB
	19+38 KHz Leakage	35 d8
	Steren Tripper	10 aV
	LE CONTRACTOR OF THE PARTY OF T	10.7_MHz
inputs and Audio Sensitivity	ALIV. St. ask! (fine manufacture)	cartridge or others) (moedance 300 K ohms
MONEY WAS VINED MANUALAN	TAPE PLAY	90 mV
	PHONO	1.5 mV (for manufic cartridge) Impedance SOK obms.
-		4-5-8" (D) 1943 × 454.5 × 373 mm)
Dimensions:		The state of the s
Weight	15 1 fbs (6.85 kg)	

#### WHY BUY A CHEAPIE FOR \$99.50

Whem you can buy this full 20 watt AM-FM Receiver with Garrard changer & big heavy speaker systems with 8" waafers.

Calumbia Nippan is one of Japan's aldest electronics manufacturers. Price.... \$139.50

WHEN YOU CAN BUY A DENON 20 WATT SYSTEM WITH A GARRARD CHANGER FOR ONLY

CHANGER FOR ONLY
PLUS A \$12.95 RETAIL MEADPHONES
FREE SPECIAL BUY WHILE 200 LAST.
MADE BY NIPPON COMMBIA CO. UTO,
ONE OF THE BEST OF JAPAN
STOCK HO WEIGHT 20 LBS.



41H, 16 L, 810 20 TRANSISTORS AND 15 010DS, 20 WATTS MUSIC POWER

PHONO-FM STEREO-FM-AM-TAPE TWO SPEAKER ENCLOSURES
WITH A 8" WOOFER AND 2" TWEETE
SIZE: 14" LONG, 9" HIGH AND 52" O

#### New EICO Silicon Solid State HI-FI "CORTINA-2"



Factory Assembled 169.95

MODEL 3780 - SILICON SOLID STATE 50 WATT AM-FM STEREO RECEIVER. 'LOOK' on back pages for more EICO

· AOVANCEO FIELD EFFECT TRAN-SISTOR (FET) AND ALL SILICON

SEMICONOUCTOR DESIGN. PRE-ASSEMBLED AND PRE-ALIGN-ED RF. IF. AND MPX SECTIONS.

UNBEATABLE VALUEI TRUE COM-PONENT SOLID STATE STEREO AT A LOW PRICE.

At last! A complete AM-FM FM-Stereo receiver at a price everyone can afford! We eliminated all frills, which add nothing to your listening pleasure and included everything you need to assure you fine AM and FM reception with high quality audio reproduction

All silicon Solid State circuitry pulls in full-fidelity Stereo FM plus AM. Feature packed preamp has controls, inputs and outputs for every music program source



Factory Assembled 109.95



MODEL 3080 - SILICON SOLID-STATE 50 WATT STEREO AMPLIFIER

NEW SILICON SOLID STATE STE-REO AMPLIFIER AT AN EXCEP-TIONALLY LOW PRICE.

. EXTREMELY COMPACT "LOW SIL-HOUETTE" OESIGN IDEALLY SUIT-ED FOR BOOKSHELF OR CABINET INSTALLATIONS

. PRICE INCLUDES VINYL CLAD METAL CABINET.

• FULL COMPLEMENT OF CONTROLS FOR EVERY SOURCE.

The amplifier that has changed people's thinking about what quality stereo prices should be. Here is the natural transparency of transistor sound, the ruggedness and long life of silicon solid-state circuitry. completeness of control and amplification; new compact styling, in a word TOTAL PERFORMANCE- all at a price



Factory Assembled 109.95

MODEL 3300 - SILICON SOLID STATE FET AM-FM STEREO TUNER.

. AN OUTSTANDING NEW SOLID STATE STEREO TUNER VALUE!

PERFECT COMPANION TO "COR-TINA-2" 3080 STEREO AMPLIFIER.

PRICE INCLUDES VINYL METAL CABINET WITH CUSTOM MOLOED ENO CAPS.

PREASSEMBLEO FRONT END, MUL-TIPLEX, IF's.

Advanced FET wideband circuitry for maximum sensitivity, selectivity, separa tion and stability; outputs for direct "off the air" tape recording; completeness of operating features; styling that delights the eye; and versatility of installation-everything you want in a quality stereo tuner, at a price considered unbelievable until EICO

designed and manufactured in the U.S.A



AKAI JET STREAM

HOTTEST LITTLE SPEAKER SYSTEMS ON THE MARKET TO-DAY

AKA! SW-30

PRICE \$44.95 pr.

4"(10 cm) full range high compliance speaker. 50-17,000 Hz. 8 ohm., 95 db/W(at 20")(50 cm) 10 W (Music Power)

Walnut cabinet with 10 ft speaker cord. Wt. 6% lbs. Ship. Wt 9 lbs. SIZE: 14-3/8 H x 5-3/8 W x 101/3

To obtain the group officiality the file of the control grants 6 bears, any families and a support and distinction parameter and 6 bears, The control of the support of and attention parameter and the control grants. The control of the grant parks for the last the control from the lasts, last of specific to a fine period of the lasts and of the parts and of fine parameter of the parameter of parameters. This papers and digners of this specific is observed in plants and the control of plants and the control of plants and the control of plants are the control of plants and the control of plants are the control of the control of



## E-V 1244X STEKED-4" AMPLIFIER ELECTRO-VOICE.



Because the E-V 1244X has full switching and control facilities, it may be used with an existing stereo system for 4-channel tape playback. Either open reel or cartridge machines may be used. The E-V 1244X may also be used independently as the heart of a fine 2-channel stereo

SPECIFICATIONS
SPECIFICATIONS
Power Output.

STEREO 4' DECODER \$149.95 Power Output,

IHF Music Power:

65 watts into 4 ohms, 50 watts into 8 ohms 18 watts per channel ± 1.5 dB.

20-20,000 Hz at rated output ± 1.5 dB 20-30,000 Hz at 1 watt

BEST VALU



HOME ENTERTAINMENT CENTER AM/FM and MULTIPLEX with HEADPHONE JACK

Nome Stereo Squard Center w/AM, FM: FM Multiples Radio and Ties Matched Wateral Sorokers

one (Player) 15% W + 9720 a 47H (Speaker) 57W a 57D + 9 7/87H

Model HLX-2534

Invention Section Ford Micromodes Strips having an Invention Section State outstand. To elable at enthics little Built on Alle and Following and Section Assessed Semigration. Compact along the Section and Continuing with Existing Artifaction.

SALE PRICE Fraid Found Micromodes along the Section Strips Assessed.

I ID VAC NO No

na A grape shill Martin



PORTABLE 8-TRACK STEREO TAPE PLAYER (Battery or AC Operated) For indoors or outdoors, cars, boats, etc. Swingaway/detachable speaker enclosures Automatic program indicator lights Push button manual channel changer Separate volume and tone controls Batteries and carlighter adapter included

The E-V 1244X amplituer provides easy expansion of an existing stereo system into 4-channel operation. In addition to two complete amplifier channels with full controls, the E-V 1244X includes the Electro-Voice STEREO-4 integrated circuit decoder. By decoding records and FM stereo broadcasts which have been previously encoded with 4-channel material, four distinct sources of sound can be recreated in the home using conventional stereo phono cartridges and standard FM stereo tuners. No portion of an existing stereo system

becomes obsolete. In addition to the recovering of four channels from a STEREO-4 encoded program, the E-V 1244X decoder creates a remarkable enhancement of conventional twochannel program material. While this enhancement is not "real" four-channel, the effect ranges from pleasing to astounding, depending upon the information contained in the stereo signal. If four-channel playback or enhancement is not desired, the decoder is easily bypassed for conventional system operation.

Continuous Sine Wave: Frequency Response:

STA-1101 Stereo Receiver 200 watts of pure power,



METAL CABINET STOCK NO

\$239.95 (NK

STOCK NO STA-6010

STA-1101 STA-1101 Stereo Receiver

STOCK NO

FINE WALNUT CABINET

200 watts of pure power, Six FET's for maximum insitivity (1.5 microvolts) and modular circuits for greater dependability. The handsome black-out glass panels light up according to the function selected; independent AM and FM tuning, and a signal strength meter plus two sensitive VU meters for precise stereo channel balancing. Six professional-type slide controls for bass, treble, and volume; an exclusive separate level control for the remote speaker system. Two stereo headphone receptacles, a speaker compensator for loss of low frequency response in compact speaker systems. Separate amp/pre-amp ompact of purposes of the control of outputs permit selection of one of these functions for AC power receptacles.

SPECIFICATIONS FREE SPEAKERS

SPECIFICATIONS
Tuner Section
AM S/N 20 dB 100µV/m
Hum and Noise FM 60 dB
AM 60 dB
Capture Ratio FM 1.5 dB
Distortion FM Mono 0.5%
FM MPX 0.8%
Modulation 0.8%
FM Separation 1 KHz 40 dB
Selectivity FM ± 400 KHz 55 dB
AM ± 10 KHz 25 dB
Pre-Amp/Amplifer Section
Music Power (IHF) 112 W @ 8 ohms This unit has been

RMS Power Rating
(both channels driven) 74 W @ 8 ohms
Frequency Response Main ± 1 dB 10 Hz – 70 KHz
Aux. ± 1 dB 15 Hz – 40 KHz
Distortion Rated Output 0.3%
1-W Output 0.3%
Intermodulation
(1-W Output) 0.1%
30-W Output 0.2%
Signal-to-Noise Ratio Mic 65 dB
Tape 75 dB

Tape 75 dB Phono 70 dB Aux. 75 dB Semiconductor Complement 6 FET

21 Diodes 1 Z. Diode 3 Crystal Foil 1 Ceramic

accepted as one of

best of it's kind.

A-8010 Stereo Receiver

STA-8010

he new NIKKO look, Handsome black-out glass lights to reveal a wide, easy-to-read tuning scale; two sters for precision tuning—one indicates the strength of the Incoming signal, the other is a guide to optimum stereo separation (1.8 microvolts sensitivity).
"Firmset" controls for Tape Monitor (source-tape comparisons), Loudness (to boost low frequencies). Muting (for quieter tuning), and Lo and HI filters. Separate control for remote speaker system, 110 watts of power. A six-function input terminal board; stream-lined AM bar antenna with an independent adjustment crew; and color-coded "plug-in" connectors

STA-8010 Stereo Receiver

SPECIFICATIONS FREE SPEAKERS Tuner Section

Sensitivity FM.IHF 1.8  $\mu$ V

AM S/N 20 dB 150  $\mu$ V/m

Hum and Noise FM 55 dB

AM 50 dB Capture Ratio FM 3 dB Distortion FM Mono 0.5% FM MPX 0.8% AM 30%

Modulation 1.0% FM Separation 1 KHz 40 dB Selectivity FM ± 400 KHz 45 dB AM ± 10 KHz 25 dB

Pre-Amp/Amplifier Section Music Power Rating 110 W ± 1 db @ 8 ohms Music Power (IHF) 85 W @ 8 ohms **RMS Power Rating** (both channels driven) 38 W @ 8 ohms Frequency Response Main ± 1 dB 20 Hz—

Distortion Rated Output 0.8% 1-W Output 0.2%

Intermodulation (1-W Output): 0.4% 20-W Output 1.0% Signal-to-Noise Ratio Tape 55 dB

Phono 60 dB Aux.65.dB

Semiconductor Complement 32 TR

SOOS FREE SOOS FREE SOOS ONE PAIR OF GOODMAN 100 SPEAKER SYSTEMS FREE with STA-1101

ONE PAIR OF DAILY -3 FREE WITH STA-8010



PAGE 13 for description of DAILY-3

FREE FREE FREE FREE FREE with STA-6010 A PAIR of MIDLAND Model 21-520



70 watts and all solid-state circuitry. Behind the modern black-out glass panel is the new, wide tuning scale—a signal strength meter for precise tuning (1.8 microvolts sensitivity). Convenient front panel stereo headphone receptacle, "Firmset" controls for Tape Monitor, Loudness, and Lo and Hi filters, A six-function input terminal board; AM bar antenna with adjustment screw; and color-coded "plug-in connectors.

STA-6010 Stereo Receiver

METAL CABINET

SEE SPECIFICATIONS FREE SPEAKERS **Tuner Section** 

Sensitivity FM IHF 1.8 µV AM S/N 20 dB 150 µV/m Humand Noise FM 55 dB

AM 50 dB Capture Ratio FM 3 dB Distortion FM Mono 0.5% FM MPX 0.8% AM 30%

Modulation 1.0% FM Separation 1 KHz 40 dB Selectivity FM ± 400 KHz 45 dB AM ± 10 KHz 25 dB

Pre-Amp/Amplifier Section Music Power Rating 70 W ± 1 dB @ 8 ohms Music Power (IHF) 55 W @ 8 ohms

(both channels driven) 30 W @ 8 ohms
Frequency Response Main ± 1 dB 20 Hz
Distortion Rated Output 0.8% 1-W Output 0.2%

Intermodulation (1-W Output) 0.4% 15-W Output 1.0% Signal-to-Noise Ratio Tape 55 dB

Phono 60 dB Aux, 65 dB

Semiconductor Complement 30 TR

LAST WORD IN HEAD SETS. STOCK NO **77S** PRICE

2995

77S Stereo Headphones

An 8 ohm set with a frequency response of 18-21,000 Hz. Features Nikko's exclusive Varistor diode protection circuit. Harmonic distortion is 1% or less at an input power of 1 mw; maximum input power is 30 W; and sensitivity is 105 dB/mw. Lined, adjustable headband with specially-designed earpiece that fits snugly, yet comfortably.

PAGE 30 or description of GOODMAN-100



Quadaptor?\*\* is shown with two A-10's. These compact and linex sive, yet high quality full range speakers are ideal for use as the k speakers in a four-dimensional stores system.

The new A-10's development was spurred by the requirement for a high quality, yet compact and low cost full-range speaker system for the back speakers of a fourdimensional playback system. The A-10 uses the same tweeter as the A-25, and its 61/4" wooler has the same magnet structure as that of the 10" woofer of the A-25. Yet its compactness and light weight (under 12 lbs.) make it ideal for unobtrusive mounting on a back wall. Mounting receptacles are built into the rear of the A-10 (and A 25) cabinet to facilitate hanging each speaker on a wall. Except for the bottom 1/2 octave, its frequency response character istics are virtually identical to that of the A 25. Their use as main speakers in a budget system would result in extra ordinary performance at minimal cost.

The new Dynaco A-10 aperiodic speaker only \$99.95 per pair.

Ouadaptor

PRICE: Kit \$19.95 Assembled \$29.95

### TRANSISTORIZED **STEREO** PREAMPLIFIER

PAT-4

PRICE: Kit \$ 89.95 Assembled \$129.95



SPECIFICATIONS

Frequency Response: Nigh Level inputs ±0,3 do from 10 Mz to 100 kHz. Low Level inputs ±1.0 from 20 Hz to 20 kHz tequelized)

Distortion at rated 2 wet extent FND less then 0.05%, 20 Mz to 20 kHz; this less than 0.05%, with any combination at less frequencies.

Hum and Redec: Magnetic Phone 70 do below a 10 mV input signal, Migh Level, 85 do below a 0.5 vot input signal.

Gaini Magnetic Phone 70 do below a 10 mV input signal, Migh Level, 85 do below a 0.5 vot input signal.

Maximum Output 10 voits into high impedance 5 voits into 600 ohms. Impedances: Magnetic Phone. 47,000 ahms. To Tape: from low layel inputs, 100,000 ohms. Migh Level. 10,000 ohms. To Tape: from low layel inputs, 10,000 ohms. Migh Level. 10,000 ohms. To Tape: from low layel inputs, 10,000 ohms. Migh Level. 10,000 ohms. To Tape: from low layel inputs, 10,000 ohms. Analytic report. Nominat lead 10,000 ohms on highe level. 10,000 ohms of high level. 10,000 ohms of high level. 10,000 ohms on high level. 10,000 ohms on high level. 10,000 ohms on high level from the level of high level from the level of high level. Nominate level - obtained to 10,000 ohms on high level high level for TV, etc. Front panel high level.

Inputs, Low level or high level Right level. Outputs (and switched by front panel papt), Front panel output and part of the level for TV, etc. Front panel high level. 2 Audio outputs (and switched by front panel papt), Front panel output. Section switch by the part channel output, 10,000 of the level for Translate output, 10,000 of the level for Translate output, 10,000 of the level of the other level for channel output, 10,000 of the level for Translate output, 10,000 of the level for channel output, 10,000

Dynaco Stereo 120 Solid-State Power Amplifier



D Individual left and right channel etched circuit boards are preassembled and binctrumt tested at factory.

B Regulated power supply circuit board, als:
eassembled and in-circuit lested at factory.

Weavy gauge, nichal plated steel chassia.
3000 gift output coupling electrolytic ca.

Overnite standard power transformer ha. dual primary windings for 30/240 V, 50 ot 94 AC.

4800 gift total capacitance in regulated power supply.

2 Color coded sprease terminals are spaced to accommodate double canana plugs as well as spade lugs or stranded wine.



armonic Distortion: Loss than 0.3% at any power laws up to 60 watts ms per channel into 8 ohms at any frequency between 20 Hz and 20 Hz

NAST both channels operated with out of phase signels. Distortion reduces at lower power levels. Intermodulation Distortion: Less than 0.5%, at eny power level up to 6.0 wetts rms per channel into 8 ohms with any combinetion of rest frequencies. Distortion reduces at lower power levels, by \$6 fower Bandwidth IINP): 5 Mz to 80 kHz half power output at less than 0.5% total hermonic distortion into an 8 ohm load Clipping Point at 1000 Mz, and channel only: 60 wetts rms minimum at 8 and 4 shims; 35 watts rms minimum at 16 ohms. Noise: 95 do below rated output unweighted with shorted Input; 100 db down by INF stendards. Separation: In access of 70 db from 20 Hz to 20 kHz. Input: 100.000 shims, 1.5 voits far 60 watts rms output. Semiconductor complement: 15 diedes. 15 frans-stors. Dimensions: 13" s 101%" s a" high Weight 20 los (9 l kg). Power consumption 35 wets guisscent, 400 watts mum, 50-60 Hz, 100-120 or 220,200 AC.

DYNACO STEREO 80 POWER AMPLIFIER

Kit \$119.95 Assembled \$159.95

## Nuvaco SPEAKER SYSTEM

RATED BEST BUY



# dyvaco

4-DIMENSIONAL STERFO CONTROL **AMPLIFIER** SCA-80Q



KIT \$169.95

ASSEMBLED \$249.95

The SCA-80Q is a one-piece transistorized amplifier consisting not only of a stereo power amplifier and stereo preamplifier, but with the Quadaptor™ circuitry built-in as well. No external adaptor is required to enjoy fourdimensional stereo when you use the SCA 80Q. Just connect four Dynaco (or other matched 8-ohm) speakers to the stereo outputs provided-two for the front speakers and two for the back.

The power amplifier section is the same as the Stereo 80; the preamplifier has all the quality and most of the features of the PAT-4. The far right rocker switch has, in addition to the normal "FOUR" dimensional, a "NULL" position which assures that the system is properly balanced for optimum front-to-back separation. The same switch also has facilities (the "FRONT" position) for turning off the back speakers so that normal, two channel stereo can be heard as well. Alternately, the "FRONT" position also enables selecting between a standard two-channel system in one room and remote speakers in another.

Sopnisticated switchable features such as loudness, filters, blending and tape monitor are provided, yet the SCA-80Q is simple to operate with a basic two-knob control action. The front panel headphone jack automatically turns off all speakers when stereo headphones are inserted. Listening is greatly enhanced by the extraordinarily quiet preamplifier section-even when the volume control is at its full setting.

PRICE: Kit \$169.95

Assembled \$249.95

STEREOMATIC FM MULTIPLEX DYNATUNER



dynacc


PRICE: Kit \$149.95

Assembled \$249.95

#### new FM-5 transistorized tuner

Mutings 60 d8, Threshold=4 pV Output @ 100% modulation 18V ± 1 d8 Signal to noise level: 55d8: @ 100% modulation Audio hum. →65 aB Input signel requiled for full limitings: 1.1 pV Drift: <50 kHz

Dirtit: CSU BH?
Selectivity (afternate Channel): 65 dB
AMI suppression: 58 dB
Surero separation: © 1000 Hz 40 dB
© 10 NHz 30 dB
© 10 NHz 30 dB
10 NH





# EIGHT-TRACK

Model 3303, AMERICAS LOWEST COST COMPLETE SYSTEM Stereo-Cartridge AM/FM Radio-Recorder System. A complete system combining AM/FM stereo receiver with eight-track cartridge recorder and player. Craig Advanced Automatic Level Control system for music recording, and easy-to-aperate slide controls for play, volume, balance, and tone. Has matching speakers with walnut grain finish wood cablnets. Model 3303 List Price \$249.95

Model 3303. Mc Gee Sale Price.....\$199.50



Make and Play Your Own Auto Stereo Cartridges

TRACK STERED CARTRIOGE RECORDER/PLATER WITH PRE-AMPLIFIERS. IN-CLUDES TWO VU METERS WITH CHANNEL SWITCH AND INDICATOR LIGHTS CUDES TWO VU METER: WITH CHANNEL SWITCH AND INDICATOR DURING WITH PUSH BUTTON OR AUTOMATIC PROGRAM SELECTION. RECORD ONE CMANNEL OR ALL FOUR IN SERIES. A TTRACTIVE WALLULY BASE MOUNTED UNIT, MONITORING SWITCH 2 DINAMIC MIKES INCLUDED. MAKE TOUR OWN 6 TRACK CARTRIDGES AND PLAY THEM THRU TOUR HOME STEREO OR IN TOUR AUTO TAPE PLAYER. OPERATES ON 117 VOLT AC HOUSE CURRENT

coludes cabinet.

CORTINA MODEL 3150 190-WATT STEREO AMPLIFIED

SAVE UP EICO "Cortina

TO 40% ON THESE

**CORTINA 3150 All Silicon Solid State** 

Designed especially for the discriminating purist.

the 3150 is acclaimed as the best buy in High-power

190 Watt Stereo Amplifier

BEAUTIFUL EICO KITS AND WIRED AMP

AND RECEIVERS integrated amplifiers. Has total control and 3150 HAS ALMOST 190 Watts (+1db) into 4 ohms: 97 Watts into 8 50 WATTS PER ohms. Harmonic Distortion less than 0.15%. Power Bandwidth 20Hz to 20KHz. Size (HWD); 31/6"x144/"x

CHANNEL AT TRUE RMS RATING

EICO IS AMERICAN MADE.



81/2". Wt. 101/2 Ibs. KIT \$149,95, WIRED \$225.00.

WALNUT GRAIN WOOD CABINET

Brushed Chrome Panel

**Model 3302** 

50

Illuminated program indicators

91/2" Wide 4" High

Ship. Wt. 16 1bs.

Stereo Eight-Track Tape Recorder Deck. Now make your own tapes for the can and the home. Has the advanced Craig automatic Level Control for music recording. Special selector allows one, all, or continuous repeat program choice. Record signal meter shows adequate input level. Model 3302

# RECORDING DECK



**OUTSTANDING FEATURES** 

STEREO ONE-MICRON GAP HEAD FOR EXTRA RECORDING INDICATOR LAMP WIDE FREQUENCY RESPONSE TWO VU METERS

# FAST FORWARD

SOLID STATE PRE-AMPLIFIER WITH 2 IC TWO MATCHING HIGH COMPLIANCE

■ UNIVERSAL VOLTAGE SELECTOR (100 V to 240 V; 50/60 Hz)

FREQUENCY RESPONSE: 50 to 16,000 Hz

DIN JACK AND STEREO HEADPHONE **JACK** 

Recording Level Indicator Recording System

3-3/4 gm Fast Ponwa
Less main 0.25% rms riscording 0.50 is 16-000 ref 11-368 Better than 45 did Microphone Jack More than 50 mV Janestore, Ling anch Microphone Jack More than 50 mV OVL 61.23 V rms Correct aqualisation file proteopoc of the processing of the processing to the processing than 15 ms VU Mitters 150 mV Power control of the processing of the processing than 150 ms VI Mitters 1

ton the Tone VU Meters 6 Track Starso Recording Syst wo Heads Recording/Ptoyback and Month

Fast Forward Time

AKAI

CR-80D

230 seconds uping a 300 ft card

AUTOMATIC STOP CONTROL

SPEAKERS (OPTIONAL)

#2 AC 100 V to 240 V t6 voltage se trons) , 50/60 Hz Homl , 50/60 Hz 60 W 13-1/2 x 10 x 6-1/2" 1345 x 250

CORTINA MODEL 3770 SOLID STATE

AM/FM MULTIPLEX STEREO RECEIVER

SAVE UP TO 40% ON THESE TWO EICO KITS STEREO by

CORTINA 3770 All Solid State 80 Watt DISCOUNT PRICES M-FM Stereo Receiver

3150 KIT \$119.95

SOLID STATE

WIRED \$149.95 3770 KIT

> \$129.95 3770 WIRED

> > \$179.95

All on one chassis: The full capability 3070 Stereo Amplifier plus a precision AM-FM Stereo Tuner (whose RF Multiplex and 1F sections are aiready pre-assembled and pre-aligned). Size (HWD) 4%" x 16" x 9". Wt. 14 lbs. KIT \$189.95. WIRED \$279.95. Includes cabinet.



## THE BEST CASSETTE CHANGER LOOK THE WORLD OVER, NONE BETTER.

PRODUCTS OF MIPPON COLUMBIA CO., LTD.

- Equipped with selector switch for continuous playback or automatic stop after a single cassette played. All-solid-state circuitry, including 15 transistors and 7 diodes ensure acoustic stability and performance reliability
- Soft touch key function buttons
- · Equipped with automatic shut-off
- 30 minutes stereo recording (45 minutes with C-90 philips type cassetto).
   Equipped with record indicator lamp and instant stop.

#### SPECIFICATIONS:

FEATURES:

Appearance Descriptions:	
Cabinet.	Wooden **
Panel.	Metel (harring finish)
Control Knobs.	(A) Reject (B) Rewind (C) Play (O) Fast forward (E) Pause (F) Selector swirch
Prior Lamp:	Equipped
Dust Cover.	Moulded plastic
Dimensions	23.51/64" (351 m/m) W x 8.5/6" (219 m/m) H x 6.9/16" (167 m/m) D
Weight	Appros. 13.4 lbs (6.1 kg)
technical Specifications;	
Operations	Push button control (Reject-Rew-Play-F.FPause)
Tape:	Philips type cassette C-60, C-90, mass 12 pcs available
Power Supply:	AC 115/230V 50/60 Mg
Priwer Switch	Self hold relay system
Power Consumption:	Less than 25 With
Record & Erase	AC bias, AC crase
Continuous Play Time	6 hours at C-60 (12 pcs)
Auto-changing Time	8 MX
F.F. & Rewind Timite	60 sec (C-60)
Wow & Flutter	Better than 0.2° , (WRMS)
Level & Impedance	Input - 22 dem 100 KΩ. Dutput = 0 dem 10 K/t
Frequency Response	50 - 10,000 Hz
S/N Ratio	Better than 43 dB
Cross Falk.	Bett is than 50 dB botween track). Better than 26 dB (between channel)
Tape Speed	1% Ips
Semiconductors	15 Transistors, 2 Diodes
Accessores 7 per Miles	1 nr Demo Cassette 1 nr C-60 Blank Cassette 2 nrs Patch Cond

STOCK NO. REGULAR TRC-798 PRICE \$229.00 MCGEE SPECIAL PRICE \$17995

THE COLUMBIA NIPPON CORP, INC., Dates back to the old phonograph days, they used the name COLUMBIA from our COLUMBIA PHONOGRAPHS. It's one of the oldest and quality aranted company in the field of electronics in JAPAN.

TOP OF THE LINE OF CASSETTE RECORDER AND CHANGER. NOTHING QUITE LIKE IT ON THE MARKET TODAY

> SOLID STATE STEREO CASSETTE AUTO-CHANGER RECORDER DECK WITH PRE-AMP MODEL TRC-798 (CASSEMATIC-12)



A Devilishly Clever Automatic Stereo Cassette Changer Recorder Deck with Pre-Amp

Now - the trinking man's machine-a fine stereo cassette that offers sex full hours of continuous entertainment by Changing cassette tapes automatically -untouched by human hands. This high quality, fully self-contained AC unit is compact and light weight, but provides full, rich tone through main Amplifier and speakers. A total of twelve stereo cassette tapes may be accommodated at a time and played continuously—or rejected at your option. Functions include rewind, pause, a handy autostop switch and, of course, record—along with the other normal operations. An amazing new appreach to satisfying your taste for listening pleasure with the ultimate in convenience. Smart styling in a fine-finish wooden cabinet will make it vour pruudest possession

Stereo Receiver New 1972 Model

DIVISION OF MIDLAND INTERNATIONAL 22 Watts RMS per Channel

Latest design panel

Model 19-552



#### New Professional AM/FM Stereo Receiver

Micotron's new high-performance AMFM stereo multiplex receiver was designed for the discriminating audiophile F.E.T. front end for increased sensitivity in FM. Micro integrated circuitry in stereo' preamplifier provides wide, stable channel separation over a broad frequency range. Special pushbutton circuits for multing, loudness compensation, high filter, tape monitor, and stereo/mono. Complete input versafility makes this receiver the perfect base for a deluxe stereo system. Rotary switch selects main and remote speaker systems individually or combined ideal for multi-room speaker arrangements. Modern slide-type volume and lone controls assure precise adjustment and accent the professional control panel. Handsome back-lighted "midnight" in this individual function flights. Illuminated signal strength motor Energed in beautiful. luning dial has individual function lights, illuminated signal strength meter. Encased in beautiful walnut-finish wood cabinet

Model 19-552

- valnut-Innish wood cabinet

  FM (88-108 MHz), AM (540-1600 KHz)
  30 transistors, I F.E.T., 2 integrated circuits, 10
  diodies, F.E.T. SM front end
  Power output 22 watsi/channel RMS @ 19 THD,
  6 ohms, power frequency response, 20-30,000 Hz
  at rated output 100 with ±1 db music power.
  Channel separation 35 db or better on FM MPX,
  45 db on magnetic phono, 55 db on auxiliary
  FM sensitivity: 3.5 uV (IHF)
  Hum and noise. —70 db
  Controls Stide-type controls for left and right
  volume, bass, treble with pushbuttons for loudness,
  high filter, muting, lape monitor, and sereo/mono,
  Rotary controls for luming, AM/FM-Sereo/Phono/
  Mike/Aux... power on/off with speakers A/B/A+B.
  Mag./ceramic phono slide switch.
- Inputs, RCA-type jacks for phono, auxiliary lines, tape in, and tape monitor, Phone jack for microphone, lerminals for external EM and AM. antennas
- Outputs: Terminals for main and remote speakers (speakers A and B), RCA-type jacks for tape out, headset phone jack, two unswitched auxiliary
- Walnut-finish wood cabinet with black acrylic and champagne-tone aluminum control panel, chrome-color mim
- · Complete with 2 speaker cords and FM dipole
- Sizet 17" a 4%" s 12%"
- · Shipping weight: 22 lbs.

# 100 WATT AM/FM

GLASS & X'TAL FERRITE HEADS

AUTOMATIC REVERSE 3-HEAD, 3-MOTOR STEREO TAPE DECK.

PRICE \$399.95

5XC22

GLASS & X'TAL FERRITE HEADS AUTOMATIC REVERSE 3-HEAD, 3-MOTOR STEREO TAPE RECORDER

Total music power 30W, at 8 ohm PRICE \$479.95

LIFETIME GUARANTEED DUST FREE. WEAR FREE, FOCUSED FIELD GX (Glass & Crystal Ferrite) RECORDING AND PLAYBACK HEADS

The new GX-HEAD will elways, regardless of environment, produce magnificantly clear playback sound. Imagine a head guaranteed for 150,000 hours of service life and to which dust will not adhere!

ı	Attractive design to match construction
•	quality.
1	Track System 4-track 2-channel, steron/monaural system Maximum Rest Capacity 2 real
•	Topic Speed
•	Wow and Fluitter Lam than 0.00% RNS at 7-55 tos
	Law then 0.12% PMS at 3-5 cm Law then 0.20% PMS at 1-50 cm
۰	Equalization Correct equalization for playback of
	Learn recorded to NAB ourse
ľ	Frequency Response
	30 Hz to 19,000 Hz (+3 off) at 3-15 lips 30 Hz to 0.000 Hz (+3 off) at 1 To ice
	Outprison
ı	Signal to Name Ratio Better then 50 d9
ı	Eranu Ratio
ı	Cross-telk
ı	Bus Frequency
J	Hunds 3 Hands
	4-track GX Recording and Playback Handa 4-track Erner Hand
ľ	Motors 3 Motors
I	Hysterains Syrepronous 3-speed reptor
1	for capatan altive and two dispole addy
ı	current outer reter motors for supply
ž	and take-up real drive,

## DUTSTANDING FEATURES

4-Truck Starso/Moneural Recording and Reytech, For playheth, the GN-2200 requires on external power empirities and a per of speakers 25 Speeds 11-76, 3-95, and 1-79 tool 3.

3 Heads (Eram, Recording, Reyback), GN-Head FOCUSEO FIELD.

ng Statement synchronique 3-spand motor for capaten driv na mala nurram musp-rator, masses for malory and false up ra

Tred Imperials VV Mitters
Horstonial & Vertical Oberstron
SRT Tape Button (for less when using AIRAI Suber Range Tape)
S.O.S. button for Squed-On-Sound obersheri

could be 4 hours associated quiety a 5-200 ft specified in 1788 (as 1788 cm street) and 1788 (as 1788 cm street) and 1788 (as 1788 cm street) and impedence may be seen as the specified in the s acording Conscrip Dutous Jacks . .

inner IC : 2 30 V to 740 V AC, 50/80 Pts

AKAL GX-220. TAPE RECORDER \$479.95

DECK

4-CHANNEL SURROUND STEREO The same AKAI robust mechanism for top-rate

NEW 4-CHANNEL "SURROUND STEREO", THE GREATEST SENSATION IN THE MUSIC WORLD OF THE '70s', DEEP DIMENSIONAL "SENSE OF PRESENCE" SOUND.

Nothing is lacking in the performance of the new model 17300-SS 4-channel SURROUND STEREO tape deck. Playback of five performances an exact. replics of original concert hall sound.

STOCK NO 1730D-SS

DECK ONLY

\$279.95

1730-SS RECORDER WITH 2 CHANNEL

AMPLIFIER STOCK NO

> ONLY PRICE

\$329.95 FEATURES

é train 4 (hannel/2 channel compatible stereo

7" 7 1/2 8 3-374 to 15 151 0 1248 MS of 7-172 to 0 1548 MS of 3-374 to 3047 to 25 00047 to 3-38 of 3-172 to 1, 3047 to 15,00042 15368 of 3-374 to 1, Better then 50till Less than 1.5% 47 1/2 cm2 11,000Hz "O" VU recording? Better then 70d8

Correct equalization for playback of laper recorded to NA® curve 100kHz

Forward & Rewind onds 88 50Hz 11,700fg, tape) onds 85 50Hz 11,700fs, tape) performance and endurance. Design is centered around operating convenience. Rectangular shaped control panel with proportionately balanced controls for attractiveness and operating ease. AKAI's durable 2 lever system for extra dependa-

bility. Two erase heads (2-channel and full track) enables complete compatibility with 2-channel stereo as well.



HEADPHONE JACKS

ne Lecks filer were requestering the private headphone has

PAUSE CONTROL

A smale SF1 of the Pause Love
sig level Also convenient for ed

A shipt water country of

. 4 Line Sustant Jack 1
Output Level 1 23V
Mar Load Impedimen more shan
20x1
2 Headshore Jacks 61 ea. Front/salt 1, 811
- 6 Shir Imput Jacks 1, 0 Amt/35833
- 4 Line Imput Jacks 1, 0 Amt/35833
- 4 Line Imput Jacks 1, 0 Amt/35833
- 0 Could have 10 IM Jacks
- 0 Amt March 10 IM Jacks
- 0 Amt March 10 IM Jacks
- 1 20011 Impl
- 2 Channel Street 1 This 68 7-1/2 statuting
- 1 20011 Impl
- 2 20011 Impl

Motor Semi-Conductors Integrated Circuits Power Supply Power Contumption Dimensions 8 Linear IC AC 100 to 740V, 50/60H/

iow 120(W) > 450(H) + 240(D) mm 16.1/2" > 18" + (\$-1/2") 15kg (33 to: )

#### AA-6100 SURROUND STEREO AMPLIFIER • 80W music power for more dynamic 4-channel

The AA-6100 4-Channel Pre-Main Amplifier was designed and produced to match and enhance the performance of AKAI SURROUND STEREO Tape Qecks. Connection of Model 1730D-SS with the AA-6100 will bring out the overflowing "sense

of presence" produced by Surr- and Stereo.

stereo sound. · Systematically arranged and easy to operate front

 Two complete sets of line connections for Surround Stereo operation plus two DIN jacks.

Accomodates both 4-channel and 2-channel stereo

 Bass and treble, front and rear Balance Controls. QUAD 4 CHANNEL AMPLIFIER



System

Los than SmV Bass 12/2B 100Hz

ptire : 12:18, 10kHz Tipe Monitor IP 6.5, 4 Tuner, 4 Aux, 7 eater Out, 4 Rec Out, 1 Headpho

79 Silicon transitors 8 Diodes 8 Thermisters 8 / 130W AC 100 to 240V, 50/80Hz 420W1 it 100H3 k 240(D) min (18.8° k 4° x 9.8°) 8 6k g (18 Rts.)

#### GX-2800



PRICE \$49500

#### A UNIQUELY DESIGNED 3-HEAD 3-MOTOR STERED TAPE DECK

....with worldwide acclaimed AKAI robust

LIFETIME GUARANTEED GLASS & CRYSTAL FERRITE Recording and Playback Heads. Amezing Frequency Response of 30 to 24,000 Hz.

Signal to Noise Ratio better than 50 dB

#### OUTSTANDING FEATURES

- PUTSTANDING FEATURES

  First and quality & makes system. A KAI's exclusive SERVOEONTROL MOVO' the law event copytant driver and two didy countent
  outer retour motors for seeming shall latter up and drived.

  GARVERAL

  ERRITTE READ for removing shall latter up and drived.

  CARVERAL

  10 12 00000 FADS for removing shall latter up and drived.

  ERRITTE READ for the removing end objective. Then features enables
  monitoring actives separat white recording Errequency Response from
  30 to 20 000 FADS for removing and pulsarians. Then features enables
  monitoring actives separat white recording Errequency Response from
  30 to 20 000 FADS for the control of Errequency Response from
  30 to 20 000 FADS for the control of Errequency
  Livrangements of command product
  Livrangements of the feature of the control of the control of the control of the control

  Finals Billion and Control of the control of the control of the control

  Errey SOUND ON SOUND appearance in control or second on second

  Errey SOUND ON SOUND appearance in our and are professional

  Description of the control of the control or second on the control

  Errey SOUND ON SOUND appearance in our and are professional

  Professional Control of the control of the control or second on the control

  Errey SOUND ON SOUND appearance in our and are professional

  Professional Control of the control or second on the control

  Errey SOUND ON SOUND appearance in our and are professional

  Professional Control

  Errey SOUND ON SOUND appearance in our and are professional

  Professional Control

  Errey SOUND ON SOUND appearance in our and are professional

  Errey SOUND ON SOUND appearance in our and are professional

  Errey SOUND ON SOUND Appearance in our and are professional

  Errey SOUND ON SOUND Appearance in our appearance in our and are professional

  Errey SOUND ON SOUND Appearance in our appearance in our and are professional

  Errey SOUND ON SOUND Appearance in our appearance in our and are professional

  Errey SOUND ON SOUND Appearance in our appearance in our appearance in our appearance

- or flat per independent Line and Mic for musing signels from two separate recording sources. With AKA'S Remote Control Unit RC-16 (optional accessory), all operating functions of the Model GX 2000 can be remote control.
- operating functions of the Model services in a large service land land. Super Renge Tape # S.R.T. Sustain I For use series using AKA) Super Renge Tape

#### Model GX-2800 SPECIFICATIONS

Frank Sustam Mesonum Real Cases Tape Speed Wow and Flutter .... otherback Minds, Break Head.

2.-seated Servic Control.

Outerrotor
motor for direct cashtan drive.
Tass. 6-pole. Eddy current, Outer-midd.
Honoror- for supply 8-take-up reed drawle.

Tens Farward and Resemb

ALL NEW GLASS HEAD DECKS ♦ AR-GX ♦

Orbit top quality materials and used in the construction of Model (IX-280D Taps Deer Not note the rew GX-RED Taps Deer Not note the rew GX-RED Taps and SE RVD to the construction of Model (IX-280D Taps Deer Not note that the construction of the GX-RED Taps Construction of the GX-RED Taps Construction of Model (IX-RED Taps Construction) and the Construction of Taps and Construction of Constructio

travel is scapilized. Because of the speed adjusting completely effectively destricted control everythe scapilities are always gardently adjusted. Therefore, topo spiseds and passenger and received. The property of the speed and property and the season. The property of the speed and the speed an

#### GLASS & CRYSTAL FERRITE

AUTOMATIC STOP/SHUT OFF

When the ISL'STOPPSTGT OPP
When the ISBO engle or is accidentally broken
the Automotic Scop(Shut-Off Lever at the
leased and real implement stops, if the conmatic Shut-Off Burton is depressed, when the
Shut-Off Burton is depressed, when the
unit is call at Is.

S.R.T. SUTTON

For any when using AKAI Super Renge Tape This is a new low noise tape and is high! renomineeded for aupanor performance.

SOUND-ON-SOUND BUTTON

Convenient for language training as a professional or fun (ss). Also indepe Live and Mic circuits for mixing fitter and entirelising

DIRECT FUNCTION CHANGE

A PERFECT MATCH

AKAI Turrus Amolitise and Soletier Systems
are designed to match and enhance the pa-terment of AKAI Tube Recorder and
Cocks Models Ad 3500 Tube Amplifer and
SW 176 Speaker System are highly recommendet for use together with Model GX-2800
Type Deck

STANDARD ACCESSORIES

T' Empty Metalist Resi DR 111 Connection Cord Sensing Tape


# KAI M-10

WORLDS STANDARD IN REEL TO

KAIX-33 REEL TAPE RECORDERS MULTI-PURPOSE PROGRAM

2

REE MOTORS AUTO. TAPERECORDER MINDER REVERSE



MODEL M-10: THIS THREE MOTORS, OUTSTANDING PEATURES MODEL M.10: THIS THREE MOTORS.

AUTO. REVERSE SOLID STATE STEREO

AND AUTOMATIC REVERSE PLAYBACK
WITH CONCERT HALL SOUND:

WITH CONCERT HALL SOUND:

AUTOMATIC REVERSE PLAYBACK

AUTOMATIC REVERSE PLAYBACK

WITH CONCERT HALL SOUND:

AUTOMATIC REVERSE PLAYBACK

AUTOMATIC REVERSE PLAYBACK

WITH CONCERT HALL SOUND:

AUTOMATIC REVERSE PLAYBACK

AUTOMAT

- CROSS-FIELD HEAD
- 40W MUSIC POWER SOLID STATE AMPLIPIEN \* Manual reverse (Auto, reverse)
  WITH TWO INTEGRATED CIRCUITS

  \* Sheef type head for high \$ Mirates
- 2-SPEED CAPSTAN DRIVE MOTOR · SENSING TAPE CONTINUOUS REVERSE (AUTO.
- REVERSE MANUAL REVERSE

BIGGEST BUY
MODEL M 10

TAPE SPEED WOW AND FLUTTER

FREQUENCY RESPONSE

DISTORTION SIGNAL TO NOISE RATIO SIRUT LEVEL

FOUALIZATION

HECORDING BIAS
FREQUENCY
RECORDING LIEVEL
INDICATOR

ATIONS
1-778, 3-34 and 2-1/3-lps
Less than 0.081- RMS of 7-1/2-dn
Less than 0.081- RMS of 7-1/2-dn
Less than 0.071- RMS of 3-324-dn
Less than 0.071- RMS of 3-324-dn
30 to 19,000 Mz g 3-do of 7-1/2-dn
30 to 19,000 Mz g 3-do of 3-3/4-lps
30 to 5-300 Mz g 3-do of 3-3/4-lps
30 to 5-300 Mz g 3-do of 3-3/4-lps
Wither 2\*, 5-000 Mz g 3-do of 3-7/8-lps

FAST FORWARD AND

POWER SUPPLY
POWER CONSUMPTION
DIMENSIONS

MOTOR

Within 2\*, \$ 000 Hz 0VM Britis Han 50 no more than 0.3 mV Line more than 0.3 mV Line more than 0.4 mV LOVI 15 W maximizer are recorded to MV 1910-41 Undistanted Power, total 30 W 20 W maximizer per optic thanest at Muse

Menual reverse
Sheed type need for high \$ 81 rules
Sheed type need for high \$ 81 rules
Sound an sound
Automatic stop stut off, instend alog control with stert button
Automatic prich, wheel release, Automatic lever rateaus
Trockers system ensures dependable and durable operation
Track scienctor for simple operation between sterse and mon
sural

Freeta Secretor Notes (Senare d and record operation (Saure)

Facilities to East, Senare d and record operation (Senare documents)

From Senare Secretor (Senare documents)

Freeta control Bass control

Fito steries headshore jacks

Facilities headshore jacks

Facilities of the Senare documents of the MICH LOW input

Facilities of the Senare documents of the Senare

RE VAND TIME 75 accords sums 1,700 four superat 50 Hz 60 sections at 60 Hz. RECORDING CAPACITY

# REEL/CARTRIDGE/CASSETTE STEREO TAPE RECORDER\*\*\*

REEL/CARTRIDGE/CASSETTE RECORDER WITH CROSS@FIELD & DNE-MICRON HEADS

MODEL 2000 SD

Three-in-one recorder combines REEL with CARTRIDGE and CASSETTE recording and playback

Transfer music from reel to cartridge, and from reel to cassette, for auto and home 8-track and cassette players REEL SECTION

4-track stereo/mono record and playback

· 4 speeds (15 IPS with included adapter)

CASSETTE SECTION

· Automatic shutoff; pause control; index counter; tape lifter

 Built-in reel retainer; tape speed equalizer CARTRIDGE SECTION

**OUAL VU METERS** SLOT-LOADED CASSETTE ONE-MICRON

CROSS FIELD SYSTEM

RECORU/PLAY HEAD PANEL PUSH-BUTTON CONTROLS

Permits 8-track stereo record and playback; transfer from reel to cartridge; 3% iPS speed 2 heads (erase and 1-micron head); program selector and indicator lamp; automatic stop

4-track stereo record and playback; transfer from reel to cassette

• 1% IPS speed; 2 heads (erase and 1-micron play head)

Push button controls; automatic stop; index counter Complete unit includes 2 built-in speakers; 2 slide-type VU meters; on/off speaker switch; multiple connection jack

Accessory pack has 2 dynamic mikes w/stands; 7" reel; prerecorded demo cassette; 15 IPS kit; fuse; silicone olf kit; head cleaner pen.



\$495.00 MODEL X 33D DECK

\$395,00 PERFORMANCE SPECIFICATIONS

TAPE SPEED WOW AND FLUTTER

FREQUENCY RESPONSE

Type of Young of IATE on Press. Shere recently of IATE on Press. Beans recordly hundreds and bus heads.

I morals Hysteries synchronism. Support minutes for capital gines. Two our reformations of the press.

8 hours mornard excepting all 1.7/8 up 11,200 tout hours it hours shore recording at NT-8 un

105 W 18-3.4 × 13-3.4" × 0.1.3" 1474 × 350 × 242 mmi 48-4 8m 172 ku

DISTORTION

SIGNAL TO NOISE RATIO

POWER OUTPUT

NPUTLEVEL

THE X-330 ENABLES TO ENJOY DIFFER. OUTSTANDING FEATURES

ATIONS

1-78, 3-74 and 7-112 vp.

1-78, 3-74 and 7-112 vp.

1-78, 1-79,

Berter than 50 db Microphone

Win Dr nade arom

15th maximum secti channel at UNDSTORTED POWER, total 20th 20th maximum secti channel at MUSIC POWER, total 40th STANDARD or LOW NOISE TARE

TAPE RECORDER

el l

effect
100 NNt brased for f M multi-own recording
100 NNt brased for f M multi-own recording
110 NNt protect carbridge leads (Direct recording and pleyback from
turn table). Server brasphone jack, DNt yea
11 Remote controllable, AC outlier seth, sourced to the visit of twitch
12 Remote controllable, AC outlier seth, sourced to the controlla
13 are channel. 9 digit index counter with rest button, VI meters
14 are channel. 9 digit index counter with rest button, VI meters
15 are channel. 9 digit index counter with rest button. VI meters
15 are channel.

RECORDING BIAS FREQUENCY

RECORDING LEVEL INDICATOR RECORDING SYSTEM

PB seconds using 1,200 foot time 17\*\*
teeth at 50 Ma, 60 seconds at 60 Ma.

hadb Etine, plantack, recentle
and leas heath.

BINET

V U

WALNUT

RUBBED

AUTI

BE

and least health registers. Synchronous 3 seasos erator for countain drawn Three 6 parts surply current out rospi implians for supply and takin set meet drawn with lach siner.

2 475 87 and 87 reds 2 475 87 speekers AC 108 to 240 V, 50/60 Hz 160 NA 14 3/4" • 17:1/8" • 8 3/4" (3/5 + 435 • 238 avri) 48 4 line (22 hg)

REEL SIZE SPEAKER POWER SUPPLY POWER CONSUMPTION DIMENSIONS



## AKAI

COMING SOON NEW LOWER PRICED

BUT WITHOUT THE CASSETTE RECORDING FEATURE.





requency Response ower Rating pedance ossover frequency mamic Force.

Barcelona (873A) 20-20 000 Hz

Granada (875A)

20-20,000 Hz

60 watts 8 onms 600 Hz

12 ps. 29% Pst 27% W x 24 D ent type, 807 type, 811B, N801-8A May be used in home entertainment use with ampliful out power rating SHIP WT, 150 L65 ng up to equal cont W T. 130 LBS.

1971

With more hand-sanding and hand-Altec finishing for finer cabinetry. The handrubbed natural walnut cabinets of Altec's new Barcelona and Granada feature an 1. New Santana Speaker System (879A) 2. Seville Speaker System (847A) infinite baffle design inside the enclosure with snap-on fretwork grilles outside

890C

17900

MODEL 770A ELECTRONIC CROSSOVER

BARCELONA WITH 770A BUILT IN \$750.00
GRANADA WITH 770A BUILT IN \$650.00
MODEL 724A AM FM STEREO TUNER
PRE AMP FOR USE WITH WITH BI AMP
SPEAKER SYSTEM TO COMPLETE FINE
KLFF NET \$550.00

Bolero Speaker System (890B)

String, Wt. Barry 1-94" He a 2544" No 62" D

40-22,000 Fiz 25 watts 8 ohms

3,000 Hz 14%" H x 25%" W'x 12" D

The finest available at any price. Bolero's realistic

sound will fill even the largest rooms without dis-toriion. The heavy, specially designed Altec 10°

LF speaker is reinforced by a totally new 10" free-suspension phase inverter, providing a lowend response matched by few large systems. The

LF speaker is powered by a massive 10 lb, mag-netic structure identical to the Aftec 414 #2"

speaker as used in the full-size Malibu. The Alter

3000H HF compression driver with cast-zinc nulticell horn extends the range of the Bolero to 22,000 Hz. A unique snap-on grille permits easy change of grille cloths to match any room decor.

LATEST ALTEC LANSING FOR 1971



Specifications \$195.00

Frequency Response Impedance rossover Frequency Speaker Components

tinuous power rating

contemporary gried wainut with a com-position state top and is hand-finished and N-3000E two-section crossover neton all four sides so it can be placed work are the speaker components that anywhere in the room. The systems give the Seville its rich sound. The cabinet impedance is 8 ohms and it can be used, is elegantly finished in hand-rubbed walwith amplifiers having continuous power nut, and highlights, a striking fretwork ratings up to 45 walls

\$249.00

Santana (879A) Seville (847A) 35-18 000 Hz 40-20 000 Hz 5 watts 35 walts 2500 Hz 25% H x 201 > W x 17 D 3000 Hz 26 H ± F

Seaker Components 420 A Birliest and direct 414-8B 3000H N-3000E SHIP WT 62 LBS radiating tweeter 5 KIP WT, 60 LBS, May be used in home entertainment Use with amplifiers having up to equal con-

This all-new two-way speaker system! The speaker system occupies only 2 sq features Aftec s patented 15 inch Biflex. It of floor space yet its sound range and speaker with a 10½ lb magnetic structure together with a high frequency; systems. The Aftec 12 inch 414-8B low tweeter. The uniquely styled cabinet siot frequency speaker. 3000M high frequency.



VOICE COIL 15 \$99.50 1971 411-8A Dynamic Force

Power Bating 60 watts 20 Hz to 1 kHz 15 Hz 512 203 (bs.

"May be used with amplifiers in home entertainment use having up to equal continuous power rating

New Dynamic Force Wooter (411-8A low frequency Loudspeaker)

This 15 inch speaker with a heavy cast aluminum frame is a high performance, high compliance unit designed specifically to be front or rear mounted in infinite baffle enclosures. The new Dynamic Force Woofer possesses a robust 4 inch voice coil assembly with edge wound copper ribbon utilizing an aluminum coil support and a heavy wide angle cone it is capable of high power handling and when used in a suitable infinite baffle enclosure, it has exceptionally low dis-tortion An 18 lb magnet structure allows this speaker to develop a dynamic force of 16 lbs for extremely good transient

#### Altec Full-Range Bookshelf Speaker Systems

Madera Speaker System (892A)



Speaker System 892A \$14500

Hand Rubbed Walnut

One of Altec's newest and most attractive bookshelf speakers, designed to reproduce an unusually wide dynamic range. It features wide band frequency response of 45-18000. Hz with extremely low distortion, wide angular distribution and a 50 watt power handling capability.

The Madera enclosure is the infinite baffle design with the Alter Model 406 high compliance low frequency encyl10" speaker for optimum bass response. The high frequency end includes a compression driven exponential horn of die cast aluminum. The crossover network utilizes a crossover frequency of 2500 Hz, and produces extremely smooth response throughout the range. Finish is beautiful hand-rubbed walnut, with a contemporary styled snap-on grille

equency Response

45 ~ 18,000 Hz 50 watts\* 50 watts 8 ohms 2500 Hz 13" H x 23%" W x 11%" D pedance . psyover Frequency

Corona Speaker System (893A)



grille

Hand Rubbed Walnut

CORONA

SPEAKER

SYSTEM 893A

\$8550

The Corona is an attractive two-way bookshelf sys tem that delivers excellent sound throughout a wide frequency range. It has a continuous power tating up to 40 walts but may be used with amplifiers rated as low as 15 watts per channel.

The Corona has a frequency response of 50 to

18,000 Hz. A high compliance 10" speaker mounted in an Infinite baffle provides optimum bass response. High frequencies are reproduced crisp and clear by a new Altec 3" direct radiating HF speaker. Ofstor-

tion is extremely low.

The dividing network is tailored to the over system, using a crossover frequency of 2500 Hz. includes high frequency attenuation in 3 dB steps above 2000 Hz.

The enclosure finish is a rich, hand-rubbed walnut, with a contemporary styled snap-on grille

50-18,000 Hz Frequency Response: Power Rating: Impedance: Crossover Frequency:

70 W215 8 ohm\ 2500 Hz 12 ¼ "H x 22"W x 9½ "D

Full-Size Altec Speaker System Famous "The Voice of the Theatre"



\$51250



SHIP WT. 170 LBS.

he famous A7-500 "The Voice of the Theatre" in a hand-finished, sculptured walnut cabinet patterned in natural wood grain, with a delicate, curved wood-fretwork grille. Inside, it's identical to the A7-500. Now you can enjoy the tandard of recording studios and theatres attractively styled for your home. Speakers are mounted and individually tuned for the ultimate in performance.

Power Rating 50 WATT mpedance Crossover Frequency 44" ff = 32" 1

ower Rating

npedance rossover Frequency's

# tec Acousta-Voicette It balance all sounds - all frequencies - to a flat acoustic response.

STEREO EQUALIZER For the perfect balance of sound.

fits between amp and pre amp. to make sound fit room accoustics



After Acousta-Voicing, your customers will hear the original sounds that were recorded—the original acoustics rather than the acoustics of their own listening rooms.

Altec 729A

Frequency response range: Equalization center trequencies: Filter type:

Maximum Insertion loss (1 section): Maximum reinsertion 17 dB

Input level:

2 channel active filter critical band equalizer 20 Hz to 20 KHz ± 1.0 dB at less than 0.5 THO From 63 Hz to 12.5 KHz at the standard ISO 1/2 octave centers 48 active filters, designed for 7dB fielf pad crossover with adjacent filters

-14 d8 at section center frequency

4.5 Vrms maximum with GAIN control at minimum

Output tevel: Input impedance: Output load: Noise level:

Channel separation: Operating controls:

4.5 Vrms with 10K ohm load 100K ohm 10K ohm nominal 80 dB below maximum rated

output

Greater than 60 dB down One Variable Equalizer Control for each 16 octave center frequency (48 total) from 63 Hz to 12.5 KHz per channel, one Variable Reinsertion GAIN Control per channel, and one Tape In/Out Switch

#### BARGAINS IN LOW COST HI-FI SPEAKER SYSTEMS and EXTENSION SPEAKERS.

A NEW HI-COMPLIANCE, LOW COST HI-FI SPEAKER SYSTEM

WALNUT Grained Hardwood

.95 FOR \$35,00

8" CTS High Compliance

WOOFER 4 INCH TWEETER



Stock No. HI-C8-4 Speaker System. Wainut grained hardwood bookshelf system with attractive, removable Cane Grille front, Includes New HC-CT5-8 RE HI-compliance 8" Woofer with Rolled Edge cone, 1/2 1b Ainico V Magnet, 1/2 in. V.C. plus a 4" Tweeter & network Size. 10"x 18" x 4/4" Ship. Wt. 12 lbs.

A NEW LOW COST, REAL HI-FI SPEAKER SYSTEM WITH ROLL EDGE WOOFER

WALNUT GRAINED

HARDWOOD

\$14.95

2 FOR \$29.00 8" CTS Accordion

WOOFER 4 INCH TWEETER



Stock No. CAS-W 8-10-8. Walnut grained hardwood book shelf Hi-Fi Speaker system, wood Baffle with Cane grille front. Includes a 8" CTS Hi-Fi Roll edge Woofer, 1" VC. 8 ohn imped, and 10 oz. ceramic magnet plus a 4" Tweeter and network. Size 10" X 18" X 41/4" Shipping Wt. 121bs.

## BLUE STREAK SPECIAL

NEW! 2-Way System WALNUT Vinyl Covered Hardwood

2 FOR \$28.50

WOOFER 4 INCH TWEETER



Blue Streak Twin speaker system. Response from 30 to 17,500 cps. at 20 music watts power. Size; 18 in. long 13½ in. tall and 6 in deep Pully englosed baffle with port. Made of heavy wood, finished with walnut grained vinyl covering. Equiped with the 12" woofer speaker XS-5830 and the popular 3½; TS-5051 tweeter.

Stock No. BF-TWT51

Price \$14.95

2 for \$28,50

#### 3 SPEAKER SYSTEM MEGA-Q McGEE



1932" Long \$ 7 6" Front

10" Tolk SALE PRICE

TWO FOR 529.00 UUTSTANDING FEATURE

VINYL COVERED EMI 8"X 131/2" WOOFER WOOD BAFFLE

MEGA-QHi-Fi Table Top or Shelf speaker system features a vinyl covered wood fully enclosed and ported baffle. Completelyaccoustically lined, including the back. Has 3,-matched speakers, One 8' \ 13\sqrt{5}' mid-range and woofer with two 3' tweeters. The total system match 4 ohm. A cross-over capacitor connects the twin tweeters to the 8' \ 13\sqrt{3}\sqrt{9}' woofer. The isallent features of the woofer are very interesting... Made in England by E. M.I. with conposite oval cone. The elliptical center cone is a grade of pure aluminum. It's reproduction of the low-middle audio tones and the upper-middle tone is superb. From the outer edge of the aluminum portion is a heavy moided paper cone. Results in fess cone breakup and better audio reproduction. The powerful Alnico V magnet drives this unique cone system. Shipping Wt. 12 its. McGee offets this system for only \$14.95

## HEAVY DUTY PM SPEAKER IN OIL WALNUT FINISHED WOOD CABINET



Stock Nov PMB-8W

\$7.95

With Level Control

This beautifully finished wood cobinet with elegant plastic grille cloth comes complete with a heavy PM speaker and fader control. Big sound in the smallest possible enclosure.

Size; 12" W. X 8%" H X 5" D .Walnut finish

# 2 for \$ 15,00

## COMPACT EXTENSION SPEAKERS

TWO CABINET SIZES

Stock No. ST-14W Stock No. ST-14M

\$8.95 ... Shipping Wt. 41/2 lb

Stock No. ST-16W Stock No. ST-16M

\$9.95

Shipping Wt. 61/2 lbs.

A Hi-Fi Speaker System only 13" long, 7%" (all and 4%" front to back. Sloid wood cabinet, finely finished, Volume control on front panel, Features special woofer and tweeter, Imput 4 to 8 ohms.


Stock No.ST-14W WALNUT PHICE\$8.95

Mahogany Price \$8.95 Stock NoST-14M

Larger cabinet using same speakers as above Size; 16" long, 19" tall and 5" front to back Rated at 8 watts.

Stock No.ST-16W WALNUT Price \$ 9.95 Stock No.ST-16M MAHOGANY Price \$9.95

#### NEW HI-FI 2 SPEAKER SYSTEM 10" ACCORDION EDGE WOOFER AND 4" TWEETER



Walnut Grained Vinyl Covered CABINET

Stock No. CA-CT-10-4

2 for \$25,00

CTS 10" WITH 6.8 Oz. 11/2" VOICE COIL.... 4" TWEETER

Cabinet 16-1/8" W x 11-7/8" H x 516" D Shipping Weight 11 lbs.

This system uses our CTS 10" 6 8 Oz. Alnico v magnet and 11/1" voice coil woofer CTS-10WF and 4" Tweeter, Case is 5/8" heavy plywood with a walnut viny! covering, Range 40 to 15,000 cps. Makes a very good extra speaker for wall mounting.

### 1972 BUY IN SPEAKER & BAFFLES



patio, rec., room and many other uses

#### NEW EXTENSION SPEAKER



Stock No. EXT-SPK-46 McGEE Price

\$2.95

10 for \$27.50 Walnut vinyl covered

Small Extension Speaker with Walnut Vinyl covered wood baffle. Use on any radio, auto radio or amplifier for extension speaker, Size; 9x5x3". Size of speaker, 4x6PM, 8 chm VC. Ship. Wt. 2½ lbs. Stk. No. EXT-SPK-46. Price \$2,95. 10 / \$27,50

#### SQUARE EXTENSION SPEAKER

mall size only 6x6x3 Vinyl covered all wood baffle 5"PM, 1.47 Mag., 8 ahm VC. \$295 Stock No.

**SQ-5** 10 for \$27.50





#### EXTENSION SPEAKER Walnut wood Grained Viny GOOD QUALITY 6" SPEAKER 8 Ohm

2.15 Oz. Alnico V Magnet

\$ 249


Stock No. CAS6-215 8" + 10" + 3" CORNER BAFFLE COMBINATIONS

STOCK NO. C12UT 12", 6.8 oz. SPEAKER and BLOND CORNER BAFFLE COMBINATION 10 for \$65.00 \$6.99 STOCK NO. CIZRA 12", 6.8 oz. SPEAKER and WALNUT CORNER BAFFLE COMBINATION PRICE

10 for \$65.00 \$6.99



## **WORLD FAMOUS NORELCO SPEAKERS**



**NEW 1972** 8" **FULL RANGE** "TWIN CONE" NORELCO SPEAKER

MCGEE SPECIAL

2 For

\$25.00

NWB-8-5

McGEE

SPECIAL

Stock No.

NWB-8JR

5 Oz. CERAMIC MAGNET 8 Ohm 3/4" Voice Coil

RRIFICVALUE Model \$2.99 2 For \$5.50

New 1972. AD8080/M8 8" Norelco full range speaker is equal to the former Model 3800. Has 5 Oz. Ceramic Magnet. Norelco's special voice coll case strung of aluminum wire instead of copper, gives this speaker greater mid-range output. This makes for more pleasing sound. Range 50 to 14,000 cps. This speaker is fine for background music and is used as a full range speaker generally, but a tweeter may be added if you wish.

AD8080 M8 Norelco Full Range Speaker, \$2 99 each, Two for .....\$5.50

#### WALNUT FINISHED HARDWOOD BOOKSHELF BAFFLE WITH TWIN SPEAKER SYSTEM NORELCO 8" SPEAKER AND 5" TWEETER





16" Long, to" High, 5-3/4" Desp 50 TO 20,000 CPS

Stock No. NWB-8.5. Hardwood Twm Speaker Bookshelf System with Noreico 3820 full range 8" apeaker with 5 oz. Ceramic Magnet, plus a 5" tweeter. Walnut finished baffle with cane grille cloth. Size: 18" long, 10" high and 54" deep. Fully enclosed and ported. Response 50 to 20,000 cps. Stock No. NWB-8-5, McGee Sale Price \$12.95 each, Two for ......\$25.00

## NORELCO JR. SHELF SPEAKER

NORELCO 8" FULL RANGE SPEAKER WALNUT VINYL FINISH BOOKSHELF SPEAKER





2 FOR \$17.50

13" long, 10" high and 5%" deep

50 TO 14,000 CPS

Stock No. NWB-8JR., Shelf Speaker System with Norelco 38 20, full range 8" speaker with 5 oz. Ceramic Magnet and 8 ohm 3/4" voice coil in fully enclosed baffle constructed of \(\frac{1}{2}\)" plywood and covered with walnut grained vinyl. Has a beautiful matching brown grille cloth front. Size: 13" long. 10" high and 5\(\frac{1}{2}\)" deep. Frequency response 50 to 14,000 cps. Ideal for low priced bookshelf speaker to use with stereo. Price \$8.95, 2 for \$17.50.

# Deluxe High Quality \$4950 Speaker System 2 For \$98.00 12" NORELCO HIGH-FIDELITY

5200M FULL RANGE SPEAKER WITH WHIZZER CONE Deluxe Speaker System contains the famous Norelco Model 5200M, 12° Full Range speaker with Whizzer cone. Full 2 lbs. of T-7 Alnico magnet and 8 ohm Aluminum wire voice coil, plus TS-6070 tweeter with crossover condenser. Response 30 to 18,000 cps. Deluxe Walnut finish wood baffle constructed of ¾° special baffle material. Finished on 4 sides. Set of legs for floor use, 9 % extra Stock No. WLD-S200-6070, Speaker System....\$49.50, 2 for \$98.00




1972 VERSION OF FAMOUS "CHAMP" 5200M

12 INCH FULL RANGE

THOUSANDS SOLD FOR \$39.95 Model \$2499 2 For 5200M 5200M

"Yes, the Champ of Champs is back in stock". The World Famous Noretco 5200M, 12" "Twin-Cone" full range speaker with full 2 bs. of T-7 Alnico magnet which is the very linest magnet material and approximately 30% stronger than our generally used Alnico 5. The superiority of this speaker is in part due to the aluminum wire voice coil, which helps the mid-range. The Whizzer Cone accents the brilliance of the high range. Free air response Is below 30 cps and goes easily to 15,000 cps. Not many do, but if you wish you can add a tweeter. When this fine full range speaker was first brought into U.S.A., it was sold as high as \$70,00. We have sold thousands at \$39,95. McGee Sale Price now \$24,99, Buy two for \$47.50.

#### 10 INCH TWIN-CONE NORELCO SPEAKER



## 10 INCH FULL RANGE NORELCO SPEAKER

14", 8 ohm VOICE COIL

18 oz. of T7 TICONAL MAGNET WHICH IS 33% STRONGER THAN ALNICO-5 MAGNET.

STOCK NO.

Model

AD 1050/M Whizzer cone

Whitzer cone "10.50/VI 2 107 \$25.00 AD 1050/M., Norelco 10" full-range high quality, high-fidelity apeaker, Probably the best 10" speaker value in America. Rated at 10 watts power handling. Ticonal magnet, 98,000 maxwells total magnetic flux. 8 ohm voice coli at 1 kHz. Resonance frequency 50Hz. Constant voice-coli impedance throughout the entire frequency range, so that the output always has a perfectly matched load. Very smooth response curves.

Clear bass response without boom effects, because of mechanical damping at low frequencies. Resonance frequency 50 Hz.

## FINEST CONSOLETTE IN U.S.A.

VENEERED

FOR THE PRICE OF A BOOKSHELF SYSTEM





12" NORELCO 5200M and TS-6070 TWEETER Stock No. DA52TS

2 For \$98.00

A very attractive Walnut Consolette with famous Norelco 5200M, 12 inch full range speaker with Whizzer cone and our TS-5070 Tweeter with crossever condenser. A pair of these will add to the decor of any room and provide outstanding reproduction. Much more desirable than bookshelf system where space allows. Consolette constructed of %' Walnut veneered special buffle material. Heavy foam interior and fully enclosed. 19%' H, 16%' W, 11" D on 2%' base. Has matching grill cloth with distinctive weave. Stock No. DA52TS. Walnut Consolette, \$49.50. Two for. OILED WALNUT WOOD FINISH





BUILD THE FINEST EUROPEAN SPEAKER SYSTEM USING THE WORLD FAMOUS NORELCO SPEAKERS MADE BY PHILLIPS OF HOLLAND

## NEWNORELCO AD1256/W8 12 inch SPECIAL WOOFER



Butyl-Rubber rolled edge, heavy 1 piece cone Free moving for best response. AD1256/W8 WORLD FAMOUS 121,000 Mx 10,000 Gs

NORELCO QUALITY

Ship. Wt. 10 Lbs.

NORELCO AD1055/W8 1972 MODEL NEW

10 inch HIGH-QUALITY WOOFER



2 FOR \$54.00 40 Watt

In Completely Closed Baffle 2 lb.

TICONAL MAGNET

Butyl-Rubber rolled edge AD1055/W8 heavy 1 piece cone.

Ship. Wt. 10 Lbs.

8 OHM 130,000

Maxwells 9000 Gauss

These 10" and 12" Woofers hove been proclaimed by some specker experts as the best made today for fully closed baffles. These speakers have 11/2" voice coils & 2 lb. Ticonal magnets, which is 30% stronger than our regular Alnico V, making these speakers probably the most efficient Woofers today. 12" has resonance freqvency of 15 and the 10" Woofer has a resonance frequency of 20.

## NORELCO AD 0160/T8 1 inch HIGH QUALITY DOME TWEETERS

10 Oz. Ceramic Magnet \$ 795 2 FOR \$14.00

With Mylar Diaphram

Width 3-5/8", Mtg. Hole 3", 11/6" Depth. Ship, Wt. 2 lbs.

AD0160/T8

25 WATTS RATED AS One of the WORLDS BEST

This Tweeter has been chosen by several of the Biggest Manufacturers for their best 1971 Speaker Systems, It is Tap Quality!

Application

Reproduction of frequencies from 1500 Hz to over 20 kHz in Hi-Fi two and three-way systems.

Construction

Magnet mass 250 g
Total Magnetic flux 27,000 Mx
Flux density 12,000 Gs.

Diaphragm

The diaphragm is dome shaped, giving a nearly ideal polar diagram; because of its low mass, transient distortion is negligible.

IDEAL FOR USE WITH NORELCO WOOFERS

NEW 1972 NORELCO SPEAKER SYSTEM GREATEST LITTLE SYSTEM SINCE MAXIMUS 1

AD2070/T8 2 1/4 in TWEETER

> With Mtg. Clamps \$ 79 NET EACH

1 Oz. Square Ferrite. Magnet 6900 Maxwells 6900 Gauss

SET OFFERING Stock No. NOR-T8W8 ADSONO W8 & 1-TWEETER

OHM

AD5060/W8 \$ \$ 95 HI-COMPLIANCE 5 in WOOFER NET EACH

10 Oz Round Ferrite Magnet 39,000 Maxwells 9300 Govern

Constant flux through moving voice coil Rigid paper cone with a highly flexible butyl-mibber suspension.



This is the Finest 5"Hi-Compliance Speaker we have tested.

SPEAKER SYSTEM WITH AD5060/W8 5" WOOFER AND AD2070/T8 24" TWEETER 1695 2 FOR Stock No. \$ DA5WT8 Cobinet 14"H x 81/2"W x 51/2"D

Constructed of Heavy W' particle board with genuine Walnut veneer finish.



# BEST BUY

3/4 LB. CERAMIC MAGNET 1", 8 Ohm Voice Coil New Roll Butyl Rubber Edge FREQUENCY RESPONSE 28-5000 \$ 799

Stock No. AD 8060/8

2 FOR \$15.00

NEW SPECIAL DESIGN

This new 8" Norelco is the hottest woofer to come to our shore in the last few years. The very special design spider & Butyt nubber cone edge, makes this speakers cone flex easily so it has very good bass response and like all Norelco speakers they seldom have voice coil troubles. This speaker is designed for 2 way systems and works well with Norelcos AD-0160/T8 Dome Tweeter with just a 4 mid. non-polarized condenser for network. This speaker boxed in a tight baffle (No Port) is good for amplifiers up to 30 Watts. Shipping Weight 2 lbs.

# MEWNOREL

16 OZ. CERAMIC MAGNET, 14", 8 OHM V.C. BUTYL RUBBER ROLL EDGE CONE RESPONSE BELOW 25 CYCLES...

Stock No.

AD-1265W8

\$1495 2 FOR \$28.00

This new 12° Norelco lives up to these high standards. Easy floating cone for best bass response. Is probably the best buy in any woofer below \$25,00. This speaker has 1/2°, 8 ohn voice coil, good for systems up to 30 watts. This speaker is designed for usein fully closed baffles, McGee Special Price \$14.95 each. Two for \$28.00

#### SETS OF NORELCO SPEAKERS FOR STEREO

Stock No. NOR 1

(2) AD4052W8

8" WOOFERS (2) AD0160T8 TWEETERS

(2) 4 Mfd. N.P. Condensers

Shipping Weight 8 lbs.

Stock No. NOR 2

(2) AD-1265W8

12" WOOFERS (2) AD0160T8 TWEETERS

(2) 4 Mfd. N.P. Condensers

Shipping Weight 10 lbs.

### BEST ASSORTMENT OF SMALL FULL RANGE SPEAKERS

AMERICA





# FULL RANGE SPEAKER BEST 5" WE HAVE TESTED!

NORELCO SPEAKERS ARE MADE BY PHILLIPS OF HOLLAND
AND JOBBED IN AMERICA BY AMPEREX

MADE IN WORLDS LARGEST AND MOST EFFICIENT SPEAKER PLANT

Maxwells......29,400 Gauss.......9,800 10 OUNCE

CERAMIC

Size: 4-3/" x 21/" Deep AD 5060/ M8

MCGEE \$4.95

8 FOR \$37.95

Primary application

Ship. Wt. 2 lbs.

5-8 litres acoustic enclosures.

Technical performance



Details

Equipped with a very sensitive Ferroxdure magnet system.

Special textile cone rim allows large amplitudes of the cone movements at low frequencies. This results in an optimum bass reproduction in the smallest enclosures. Low resonance frequency and wide frequency range.

# HEAVY DUTY 5" FULL RANGE

1". 8 OHM VOICE COIL 10 OZ. CERAMIC MAGNET



XS-510 \$3.49 EACH Size: 41/2" D.

50 to 10,000 Cycles

Brand New 5" Hi-Compliance Woofer with 1" 8 ohm Voice Coil and 10 Oz, Ceramic Magnet This: heavy duty 5" is very similar to big name, amail speakers that sell for up to \$15.00, Freq. Range 50 to 10,000 cycles, Our CTS-3 tweeter goes well with this unit, Has Roll Edge and aluminum center dome. A real buy at \$1,53.49 ea.

# NEW & BETTER SMALL C.T.S.

Tests All Around Better than XS-510

1972
ROLL EDGE
FULL RANGE
10 0Z.
CERAMIC MAGNET
8 OHM 1" VOICE COIL

Stock No. \$399 Ship. Wt.

#### ROLLA HIGH COMPLIANCE

Most Ideal Full Range for shelf speaker systems. This speaker goes below 50 cycles and is much better on base than the 4" and 5" versions. Has a heavy 10 oz. Ceramic Magnet and 1" voice coil. A real High Compliance speaker with roll edge cone suspension. Goes good with CTS-3 tweeter shown on this page. McGee Sale Price......\$3,99

## FULL RANGE 4 1/2 IN. SQ. PM DYNAMIC

SPEAKER

SPECIAL 5000 to SELL

\$ 249 Stock No.

W-78-C

SOLD BY OTHERS FOR \$4.95

CLOTH ROLLED EDGE CONE FULL RANGE SPEAKER.

Ideal speaker for small systems.

5 oz, ALNICO '5' MAGNET, 16 ohm, V.C.
USE TWO OF THESE SPEAKERS
IN YOUR MID-RANGE OF THE
SPEAKER SYSTEM FOR THE BEST
RESPONSE. A WELL KNOWN
MANUFACTURER IS USING THIS
SPEAKER IN THEIR MID-RANGE.

SIZE: 412" x 23/1" DEEP Ship, Wt. 13/4 lbs.

## AMERICAS HOTTEST BUY

# SYSTEM

2 WALNUT VENEER

ENCLOSURES 13½'' × 8½'' × 5-5/8''

Each One Contains 6CTS-10-8, 6½" Woofer DSCT-35, 3½" Tweeter Crossover Condenser

EACH 2 FOR

1499 \$2900 Ship. Wt. 12 lbs.

Finest quality cabinets anywhere, at any price. Manufacturer makes cabinets for some of the biggest name brands on market. Constructed of %" particle board with Genuine Walnut veneer. Fully enclosed and packed with polyeurerhane foam. Attractive matching grill cloth. This system with speakers shown at right and crossover condenser provide sound quality unusual in systems at this price. Stock No. DA6-35, \$14.99, 2 for \$29.00.

# BIG MCGEE BARGAIN-1000 ONLY NEW 8 OHM 6½ INCH SPEAKER

514" x 214" Deep

61/2" V.C. ROLL EDGE
10 OZ. CERAMIC MAGNET
WOOFER \$3 9

Response, 35 to 10,000 CPS.

Model 6CTS-10-8, Now has 8 ohm Voice Coil, 10 oz. Square Magnet and same Ralled Edge cone as above speaker.........\$3.99

## 31/2" CINAUDAGRAPH TWEETER



3 OZ. CERAMIC MAGNET MCGEE SALE PRICE

8 OHMS

Stock No. DSCT-35

FULLY ENCLOSED BACK

Stock No.

DA6-35

## A NEW CONCEPT IN SPEAKER DESIGN AND USE

Response 38 to 12,500 cps EXTRA FINE SOUND EQUAL TO SPEAKERS Response 3 TIMES AS BIG 38 to 17,500 CPS

FOR NEW SUPER CERAMIC WOOFER

Stock No. XS-5948

195

WOOFER 1971

Characteristics of the speakers: 12 Oz. High density Ceramic Magnet with 1" 8 onm voice coil. A Woofer 6" cloth surrounded mass controlled: resonance 40 cycles; frequency response 38-12,500 cps. Rated 12 watts-18 peak program material. 34" tweeter with Domephasing cap; edge treated to decouple and ac leve smooth peak free response; 8 ohm. 12 oz. Ceramic Magnet. Ship. Wr. 5 lb

New 1971 Design 12 Dz. Magnet....



Ship. Wt. 5 lbs.

61/2 INCH WOOFER Stock No. XS-TS63-67 WITH MATCHING TWEETER

Super Quality



Build your own baffle for this new set of matched Hi-Fl speakers and have a system worth \$30,00 or more. If your listening area is small, 12 x 20" or less, you can have Hi-Fi at low-fi prices. Most astounding 6" woofer, that responds from 38-12,500 cps. Not only do the base notes reproduce clearly but the math range is extremely fine. A new design by an American engineer and made in USA. Normally we would class this by sound as one selling for 3 times our selling price of only \$3.95. Rated at 12 watts with 18 watts peak programing when used in a proper baffle. The 3½ inch tweeter has an enclosed back. Its response is from 2000 to 17,000 cps. It works with the 6" speakerto reinforce high frequency response and augment the overall system. The 3½ inch tweeter is a supreme value at only \$2.95. Already connected to the tweeter is a 4 mfd. N.P. capacitor crossover. Order both 6" Big Sound Woofer and Tweeter at the same time for \$7.99, or order 2-sets alike for stereo at only 141.95 Baffle dimensions and wiring schematic are included with each set of speakers. When ordering both woofer and tweeter Stock No. XS-TS63-67

GIANT 20 Oz. CERAMIC MAGNET SAME CONE AS ABOVE 61/1" SPEAKER

SPEAKER OF THE YEAR

Plays like adding 5 watts to your Amp.



Ship. Wt. 41/2 Lbs.

MOST SENSATIONAL SPEAKER VALUE
AMONG THE NEW SMALL WOOFERS.
Stock No. XS-6071, 64," Woofer with a Giant
20 Oz. Ceramic Magnet, 8 Ohm Voice Coli.
Cone is cloth surrounded mass controlled, The
edge is treated to give free movement. Speaker
will out perform other 5." or 6." speakers which
sell at up to 3 times our price.

Above Woofer can be used with TS-5051 or TS-6070 Tweeter.

#### BEAUTIFUL OILED WALNUT CABINET

IDEAL FOR PRINCESS SPEAKERS

Cut for 61/2" & 31/2" SPEAKERS

2 FOR \$15.00

Stock No. R6535

Constructed of Heavy with genuine Walnut veneer finish.

14"H x 812"W x 512"D Shipping Wr. 8 lbs.

NEW 1971 C.T.S. TWEETER

Stock No. \$399 2 FOR TS-7171 \$37.50

6 OZ. CERAMIC MAGNET 37' VOICE COIL - 8 OHM

This new 34/1 Tweeter is being used by several large Manufacturers in their 1971 Hi-Fi. This Tweeter has a new dampering cushion made of felt, back of cone. This enables the Tweeter to reproduce more smoothly the Hi notes. Has a 6 oz. Ceramic magnet, 4/2 voice coil. Furnished with a 3 5 Mfd. N.P. condenser & Hook-up sheet. Overall size 44/2, 11/2 deep. Ship. Wt. 1 poind. Stock No. TS-7171, \$3.99 each, Two for \$7.50

NEW 1971 HEAVY DUTY 6 INCH 11/2" VOICE COIL- 8 OHM 20 OZ. CERAMIC MAGNET WOOFER



EACH

There is nothing quite like this new 6 inch XS-60-20. It's probably the heaviest 6 inch speaker made. Has 20 Oz. Ceramic magnet with over 3 lbs, magnet structure. Having 144" voice coil, this speaker will stand up to 25 watts if correctly baffled. Uses same cone as XS-5948 speaker at top of page. Works equally good with either TS-5051 or TS-6070 tweeters listed directly above. Stock No. XS-60-20, \$7,49

NEW SUPER 10 Oz. CERAMIC MAGNET

TWEETER

Stock No. TS-6070

95

MHO

New Super Sensitive 31/1"
Tweeter, 10 Oz. Ceramic Mag-net with 8 ohm Voice Coil & a crossover condenser, Respon-se 2000 to 17,500 cps. Stock No. TS-6070, \$3.95 Em. Ship Weight 21b.

OHM

CINAUDAGRAPH Stock No.

DSCT-35 \$ 3 OZ. CERAMIC MAGNET

Response 900 - 17,500 CPS

Shipping Wt. 1 lb.

IDEAL FOR USE WITH SMALL WOOFERS

GET THIS 1972 PRINCESS SPEAKER SYSTEM MOUNTED IN BEAUTIFUL WALNUT

CABINET...READY TO USE Constructed of 3/4" particle board with genuine
Walnut Veneer Finish.

14" x 14" H x 81/1" W x 51/2" D, Ship. Wt. 13 lbs.

61/2" WOOFER & 31/2" TWEETER

1695 2 For \$33.00




This Special Cone used in all the Princess Speakers is designed to give better reception than other small speakers on midrange. All Princess speakers will go to 50 cycles in good tight cabinets. With our special Tweeters TS-5051 or TS-6070 these speakers make a fine combination for listening pleasure.





# OOFER' SPEAKER SYSTEM EVER OFFERED FOR



STOCK NO. WL D-12-6067 Shipping Wt. 35 lbs. Size - 25H, 14 1/4 W. 111/4 D HAND RUBBED WALNUT



12 INCH "WILD WOOFER"


TS-6070

31/2" TWEETER

2 FOR

This fine speaker system contains a 12" special design speaker with roll poly-faam edge. 1 lb. Alnico V Slug magnet and 2" vaice coil. Tweeter is our famous TS-6070, 3½" speaker with full 10 oz. ceramic magnet. Extra fine Walnut heavy duty ½" plywood cabinet with fine walnut finish. Response 28 to 18,000 cps. Matches 8 ahm.

IF YOU PAID UP TO BETTER THAN \$200.00 YOU MIGHT



Ship. Wt. 64 lbs. Size: - 25H, 14 1/4W, 111/4D

HAND RUBBED WALNUT

This Goodman 100X is probably one of the best Backshelf speaker systems ever made. Cabinet is constructed of extra heavy particle board with Walnut veneer finish. Cabinet is of far better quality than generally used. The network is a LC type has a Tweeter and

20-22,000 cps

C-177A 12" WOOFER 8" FULLY ENCLOSED BACK MID-RANGE

NEW -11/2 VOICE COIL

DOME TWEETER

3-WECN, CROSS-OVER

NETWORK

GOODMAN 100X

2 FOR \$148.00

Mid-Range Presence controls.

Domed tweeter works with built-In network, The cabinet is foom filled to damper any vibrations. The network crosses over at 800 cycles, Stk. No. Goodman 100 McGee Special price for this speaker system, \$69.95 2 for \$148.00

HAND RUBBED WALNUT 1972 GOODMAN SPEAKER 2-WAY



TS-6070 TWEETER C-177A 12" WOOFER

SALE PRICE 2 FOR \$98.00

This fine 2-way system contains the famous Goodman 12" woofer and our TS-6070, 3½" tweeter with full 10 oz. ceramic magnet. Extra fine heavy duty plywood cobinet with fine walnut finish. Fiberglass lined, Response Is 20-18,500 cps. Matches 8 ohms.

#### **HOT 3-WAY 1972 GOODM** 70 SPEAKER SYSTEM CT-6



12" WOOFER

Tweeter

C6-11/2MR MID-RANGE-61/2"

Steck No. GOOD-70 95 \*

2 FOR \$118.00

The Goodman 70 Speaker System with 12" Goodman woofer, C6-11/MR, mid-ronge speaker and a CT-6 Horn Tweeter giving additional brilliance on the highs. Response 20-22,000 cps. Same fine wolnut cabinet as used in above systems.

SOME OF THE BEST SPEAKER SYSTEMS ... MADE WITH GOODMAN OF ENGLAND

HI-COMPLIANCE SPEAKERS, FOR 1972 GOODMAN OF ENGLAND ( HI-COMPLIANCE )

HIGH-COMPLIANCE 12" WOOFER

HEAVY DUTY 23/4 LB. CERAMIC MAGNET

1 95

PAIR FOR \$48.00

SPEAKERS

C-1774 DO NOT USE N A PORTED BAFFLE

The low DC resistance of this woofer Voice coll makes it ideal for new Hi-Fi, High powered Transistor receivers and amplifiers. Matches 4 or 8 ohms.

May be used in a boffle as small as 2 cubic feet NOT PORTED Stock No. May be used in obottle os smoll os 2 cubic feet NOI PURIE Goodman of England professional quality 12 inch low frequency woofer 25 to 5000 cps) features a die cast frame with 2 lb. 12 oz. ferite magnet in a 9 lb. magnet structure. Very high flux density of 14,000 gauss and a total flux of 157,000 Maxwell's is more than 10% higher than American made speakers selling for \$50.00 or more. The sophisticated woofer cone is treated front and back for good cone action. The 2" voice coil matches HI-Fi ampeinter of either 4 or 8 ohm impedance. Free air resonar 25 cps. Rated up to 55 watts (Music Power) 5\%" depth is required behind the baffle speaker board. Hole template and rubber mounting gasket is furnished. Shipping Weight 18 lbs. Price FOB Kansas City, Missouri. When sending full remittance include postage. Any extra sent with order will be refunded.



#### GOODMAN HORN TWEETER

Stock No. PDAL-C33

PDAL-C33, Goodman Hom Tweeter, Response: 3,000 to 30,000 cps. May be used with a 25 watt system when limiting the frequency ranges to 3,000 cps on the low end. Use with a 2 Mid. N.P. condenser connected in series. Impedance is 8 ohms. 7/1" Deep, Outerhom d.a. 2//". Stip. Wt. 11b. Hom has a husky Ainico V magnet, Made by Goodman of England. This is a tremendous value at only \$9,95. Limited quantity available.

#### NEW 1972 DOME TWEETER MODEL L15E MADE BY THE LONG ENGINEERING, INC.

OOFER

New special design made to stand up to more watts

than any DOME speaker. TRUE 25 WATTS rating New from Long Engineering, 1½ inch SUPER DOME mid-range and/or TWEETER. 1½ inch coil dealign for greater power handling. Spherical shaped Mylar diafragm for pleasant mids and highs. Response 1000 to 20khz. Recommended maximum cross—over cap—10 ufd with 1 mh inductor. Ideal for 2 & 3 way systems

Stock No L15E

C-177A WOOFER Price \$995 2 for \$19.00

BUILT TO STAND UP UNDER MORE AUDIO WATTS THAN ANY OTHER MID\_RANGE MADE. 25 WATTS RATING New 11/2" vaice, DOME type cone is made of treated

HEP-DOME

\$12952 FOR \$25,00

# HEPNER'S NEW DOME MID-RANGE SPEAKER

phenolic cloth and protected by a metal cover. 8 ohm 1½° voice coil with a large 6.8 oz Alnica 'V' magnet. Large 4½° mounting frame, requires a 2° hole to mount. Resonance, 500 to 5000 cps to proper network.

**NEW GOODMAN 100 SYSTEM** 



HOTTEST SPEAKER SYSTEM IN AMERICA

> Stock Na. SCL-100-S

8-MRC/8 MID-RANGE

With GOODMAN 12" WOO FER No . C- 177A

LT-11/2 SPHERICAL TWEETER

8-MRC/8 MID-RANGE 3-WECN CROSSOVER



LONG TWEETER

3-WECN

WALD CROSS-OVER



Make yourself a \$150,00 plus system with these speaker components. Minimum solid box baffle can be as small as 2 cubic feet.

A fine set of speakers to bulld in your own hi-fi baffle or cabin etry. A crossover, CN-3 is furnished. It has a seperate volume control to adjust the volume of the mid-range and tweeter speakers, to your needs, It makes one of the finest sound systems at low budget prices. Rated 50 watts, Freq. response 25 CPS to 20,000 CPS.( Woofer and mid-range described on this page Shipping weight 25 lbs.

Stock No. GD-12-5M-31/2CTS-CN-3

Price \$39.95





CROSSOVER NETWORK

ORIGINAL 2-WAY MAXIMUS CROSSOVER USED IN MAXIMUS 1 SPEAKER SYSTEM

MAX-1-CROSS

MAX-I-CKUS

This well constructed crossover consists of one inductance coll and a 20 Mfd. N.P. condenser used on the woofer speaker, one inductance coll and a 4 Mfd. paper capacitor used on the Tweeter Speaker. For 15 Watt systems. Freq. range 45 to 20,000 cps. All components are mounted on a 4" x 5"-"," thick plywood board with terminals and 15" long wires for attaching to the speakers. Net price \$3.95 Ea.

## McGEE'S NEW 1972 "WILD WOOFE

OUR NEW 1972 ... 12" AND 15" WILD WOOFERS ARE CUSTOM DESIGNED FOR McGEE BY C.T.S. THESE SPEAKERS ARE THE LATEST WORD IN WOOFERS FOR MEDIUM AND SMALL TIGHT ENCLOSURES WHICH ARE SO MUCH IN VOGUE AT PRESENT. SPEAKERS HAVE POLYEURETHANE ROLL EDGE SUSPENSION.

> POLY-FOAM ROLL EDGE CONE 60 WATTS MUSIC 8 OHM 2 INCH POWER 8 OHM VOICE COIL Fully Enclosed VOICE COIL

Lb. Machined Alnico V Magnet 1 Lb. Machined Alnico V Magnet Stock No. \$ 1 795 2 For 15R-16-8

Stock No. \$ 1 4 95 2 For 12R-16-8 \$28.00

16 THESE SPEAKERS HAVE A BRAND NEW CONE MATERIAL, MADE AND DEVELOPED IN C.T.S. OWN LAB. VERY HEAVY WITH SOFT C.P.S.

\$35.00

BACK TO GET THE LOWEST RESPONSE POSSIBLE. DESIGNED FOR USE IN COMPLETELY ENCLOSED BAFFLES. America is still the Blg leader in the speaker business, design and manufacturing skill and almost immediately available to the consumer. McGee offers for it's first time, Woofers with very low free air resonance, brought about by a newly available Polyeurcthane outer cone suspension system. This results in a sort of accoustical shock absortion and smoother long travel cones, It is molded in one

piece to fit the outer cone edge (Frame to cone fastening area) with a convex curve, allowing the cone smoother, easier action and longer travel yet high efficiency. Two sizes are affered, 15" & 12". All at prices every audio Engineer can afford. We think they are warth 2 times more than our offering price, but we have always offered fine speaker values for any pocketbook.

AMERICAS BEST SELLING SPEAKER SYSTEM Reprint of Feb. 1969 Popular Electronics Instructions included 1 Lb. No. 18 Magnet Wire Beiden 8075, \$2.95 Extra

AS ADVERTISED IN FEBRUARY 1969 POPULAR ELECTRONICS

12" "WILD WOOFER" Model 12R16-8 Stock No.
6" MID-RANGE Model C6-11/2 MR THRIFTY 3 MID-RANGE SUPER TWEETER Model TS-6070 \$ 25 Mfd .-- NP CAPACITOR

NEW-1972- SUPER-THRIFTY 3X, KIT New 12"Super Heavy-duty WILD-WOOFER Shawn on front page. Model 12F20-8 WITH; C6-11/2 MR, TS-6070 and 25 mfd. 54

New Thrifty 3-15, Same system as above except using 15" "Wild Waafer, 6" Midrange C6-1½MR, 3½" Super Tweeter TS-6070 and a 25 Mfd. N.P. Capacitar. Stack No. Thrifty 3-15, McGee Sale Price.....\$24,95

## **NEW 1972 3-WAY SPEAKER SYSTEM** MCGEE 3-WAY SPEAKER SYSTEM

Stock No.

A BETTER SET OF SPEAKERS THAN WOULD NORMALLY BE USED BY A MANUFACTURER IN A \$90.00 SHELF OR CONSOLE

12" 20 C.P.S. WILD WOOFER ALL

6" MID-RANGE 31/2" TWEETER

FOR

Plus 3 WAY CKUSSOVER NETWORKS Matched set of 3 Hi-Fi Speakers with a 3-Way Crossover Network. All for only \$26,95. Just make your own baffle or mount them in a cabinet or in a wall. Audio Response 20 cps to 20,000 cps at 50 12WL D-63·CN-3 watt peak audio programing. Easy to wire instructions are included with the crossover network. You get the 12" Woofer, Model 12RUB 16-8 plus 6" Mid-range, Model CG-1½MR, plus 3½" tweeter, Model SPT-3½-8 and a Regulor S8.95 Model 3-Way crossover. It has a volume control for the Mid-range and a valume control for the tweeter. A fine set of high fidelity speakers for the low budget. 2 FOR Stock No. 12WLD-63-CN-3, 3 speakers & crossover, \$29.95 \$58.00

New 15WLD-63-CN-3, Same system as above except using 15" "Wild Waafer", 6" Midrange C6-1½MR, 3½" Tweeter Madel SPT-31/2-8 plus CN-3, 3-Way Crassaver. Stock Na. 15WLD-63-CN-3, McGee Sale Price...... \$32.95

## 972WILD WOOFERS JUNIOR 8-10-12

THIS LINE OF SPEAKERS IS BUILT FOR MCGEE BY C.T.S, --- FOREMOST SPEAKER MANUFACTURERS OF U.S.A. THESE 3 SPEAKERS ARE SPECIALLY DESIGNED TO OPERATE AS A 2- WAY SYSTEM AND ARE USED BY THE "Big Names" IN VARIOUS APPLICATIONS IN MANY OF AMERICAS BEST HI-FI SYSTEMS.

ROLLED EDGE CONE

8% OUNCE MACHINED

ALNICO V. MAGNET 1½ INCH VOICE COIL

Stock No. 12E8540CTS

McGEE S 095 Special

\$19.00

Response 28CP5

Ship, Wt. 6 lbs.

This Custom design 12" Woofer is primarily for 2 Way Systems, as this Woofer goes from approximately 30 to 5,000 cycles. Speaker has a heavy 1 piece cone with cloth roll edge and free breathing center piece. This speaker is used by several Hi-Fi manufacturers in medium priced enclosures. We find that all 3 of these speakers work out real good with a network condenser and a tweeter. Stock No. 12E8540CTS, 39.95, 2 for \$19.00

## **WOOFER JUNIOR**



OHM

TREATED ROLLED EDGE CONE 8% OUNCE MACHINED

ALNICO V. MAGNET 1% INCH VOICE COIL

Stock No. 8E8540CTS

McGEE Ship. Wt. Special

\$795 2 For \$15.00

Again this CTS 8" is also designed for 2-way Systems, Response 33 cps. It is no doubt the best 8" woofer being sold for \$7.95. McGee buys all speakers at lowest OEM prices and passes these savings on to you. This speaker has a heavy cone and cloth roll edge treated to stay flexible. Has all the speaker characteristics of the other 2. Stk. No. 8E8540CTS, \$7.95

# "DO-IT-YOURSELF"

MOUNT YOUR OWN SPEAKERS

Foom Filled

Removable Grill Front... Uncut Mounting Board

BAFFLE 24"H x 1410"W x 10"D Stock No. **DBF-10** 

BAFFLE 26"H x 15//"W

Stock No. NVDB-12

12", NEW TYPE VYNAL WALNUT FINISH.

10" OILED

WALNUT WOOD VENEER

These two very fine cabinets are made for us by a North Carolins Cabinet factory, who makes cabinets for some of the best manufacturers. These are so constructed that you can cut the baffle board to for your speakers.

ROLLED EDGE CONE 8% OUNCE MACHINED ALNICO V. MAGNET

TREATED

1% INCH VOICE COIL

Stock No. 10E8540CTS

30 CPS

McGEE \$ Q95 OHM Special

2 For \$17.50

Ship. Wt. 5 lbs. This 10<sup>36</sup> speaker was especially designed by CTS for a major Hi-Fi Mfgr. Has a heavy treated cone with cloth roll edge, vented center Dome. Spkr. is so designed with the machined 8½ Oz. Ainico V magnet that performance in low end would be affected if magnet weight were increased. We think these Wild Woofer Jrs. are about all the speaker there is for stereo. Up to 30 watts RMS per side. Stock No. 10 E8 540 CTS \$8.95, 2 for \$17.50

## FOR USE **WOOFER JUNIOR SYSTEMS**


2-WAY SPEAKER NETWORK

WITH ATTENUATOR WITH TWEETER

CONTROL \* 3,000 cps. CROSSOVER

PANEL MOUNTED \$399

Front



Model 840. The Calrad 2-Way Speaker Network has been carefully designed and assembled on a metal plate, ready for easy installation in back of your speaker enclosure. A fully adjustable level control is incorporated to control output of the tweeter with the L-C type crossover network permitting both speakers to be perfectly matched for maximum sound reproduction has pushbutton terminals. Size: 4" W x 5½" H x 1" D. ( No. 840, \$3.99)

## CTS SUPER TWEETER



CUSTOM DESIGNED TO MATCH WILD WOOFER JUNIOR SPEAKERS

8 OHMS.

5 Oz. CERAMIC MAGNET Res : 900 to 20,000 CPS Stock No. C-31/2-8

Shipping Weight 1 lb.

The special cone is damped by accoustic padding for very smooth high frequency response. A plastic pot cover adds to the appearance and keeps the sound from mixing with other audio inside the baffle and also permits proper manufacturing technique. Use with a 2 Mfd. or 4 Mfd. N. P. Condenser to add to your existing woofer. Normal \$6.00 Value. C-31/78, \$3.99

## OZ. CERAMIC MAGNET

STOCK NO DSCT-35

Response 900 - 17,500

OHM FULLY ENCLOSED BACK

8 Stock No. DSCT-35, Cinaudagraph 34/1 Tweeter has similar cone construction to above tweeter so it covers midrange and highs. Is a Super Value for \$1,99. Use with 2 or 4 Mfd. N.P. condenser. 8 ohm, 3 oz. Ceramic Magnet. Response 900 - 17,500 cps. 14/2 D. Fully enclosed back maintains proper resonance. Stk. No. DSCT-35 HIGH COMPLIANCE

## HI-FI WOOFERS & FULL RANGE SPEAKERS



10" WOOFER

95 EACH 2 FOR \$15.00

\*\*CTS-10WF CTS 10' Woofer. 114'' 8 ohm Aluminum voice Coil. 6.8 oz. Ainico V Magnet equal to 10 Ounce. Special cone is accordion edge suspended for easy movement. Long throw-construction for best base elficiency. Extra gasket on front to keep cone from stretching your grill cloth, Resonance frequency 39cps. Very good base and mid-range response. Tweeter required to extend high frequency response. 22n.nn 11st value. McGet Price 56.95 Ea. 2 for \$12.95. Net Wi. 4 lbs. Shipping wt. 4 lbs. TS 5051.

MAGNET **ALL-PURPOSE** WOOFER LONG TRAVEL CONE

> Stock No. CTS-10WF



HOTTEST 8" WOOFER IN AMERICA FOR \$4.95

HEAVY 10 OUNCE CERAMIC MAGNET

Heavy ribbed cone, Treated cloth rolled edge for free move-ment. 8 ohm, 1" voice call. Heavy 10 oz. Ceramic magnet. Frequency response 33 to 10,000 cps. Only 3½" deep. Stock No. 8-10-8, Ship. Wt. 2½ lbs. Net Price..........54.95

## HOTTEST BUYS IN HEAVY DUTY HIGH COMPLIANCE 8 INCH WOOFERS I LB. ALNICO 5 RING MAGNET

11/2 inch 4 loyer 16 ohm Voice coil

DESIGNED BY ACOUSTICAL LABS., INC.

THESE ARE THE TYPE OF WOOFERS USED IN \$ 100.00 CLASS SHELF SYSTEMS.

Rolled Edge Cone suspension.

INCH

**O** 95

WOOFER 2 for \$17.50 Model 8164-16RFE

RESPONSE 24 CPS to 6000 CPS This design requires a fully inclosed baffle Ship wt. 41/2 lbs. 15 n.usic watts



Stock No. 10EM8A

**SQ** 95

2 FOR \$17.00

This new hi-compliance woofer has an accordion edge cone for free movement and on 8 ohm 4 layer voice call. This speaker is same type speaker that is used in many big brand shelf speakers that sell up to \$100.00. Built on the new principle of machining the 10 oz. magnet to fit right into the 1½" voice coil. This makes for a more efficient speaker. Response relow 35 cycles. Model 10EM8A Sole Price \$7.95, 2 for .... \$15.00

## 61/2 IN. ROLL EDGE WOOFER

RESPONSE: 38 TO 8000 CPS 1 INCH 16 OHM 4 LAYER VOICE COIL 10 OZ. CERAMIC MAGNET




Ship. Wt. 21/2 lbs.

\$3.99

WILL OUTPERFORM MOST ANY 6%" SPEAKER WITH 10 OZ. MAGNET OR IN IT'S PRICE RANGE

This cone has the new treated cloth roll edge suspension for easy cane action and good low end efficiency. Popular in todays compact and shelf speakers. It can be used with or without a tweeter added. Stack No. 6-16-4-10-CRE, Net price \$3.99.



Stock No. CTS8-11/-8 MCGEF SALE PRICE

SE95 2 FOR

ONE OF THE BEST BUYS

C.T.S. 8" WOOFER SPEAKER

New CTS8-11/2-8, 10 Watt sktro fine Woofer. Features a full 6.8 Oz. Alnica V Magnet. 1½" heavy duty valce coil. The Woofer cone is one piece malded with rib reinforcement. The outer edge is accordion design of treated plastic for long-life and easy cone movement. May be used with any tweeter you have or used as a single speaker far mellow sounding background music. McGee sale price \$5.95, Two for......\$11,50

1972

SPECIAL DESIGN

TWEETER Price

Stock No. \$3.69 31/2TB6077 TWO for \$7,00

3½ inch TWEETER 6 oz. Squore CERAMIC MAGNET

8 ohm. 34 inch dia. VOICE COIL

This is the TWEETER that is used in the high priced Hi-Fi speaker systems. Using 2 to 4 in each system per channel. A special dampener pad is built-in under the cone to smooth out resonance at the higher end. The cross-over condenser is attached to the tweeter THE RESULTS ARE SUPERB

Stock No. 31/2T B6077 Price \$3.69 ea.

NEW CTS TWEETER IS IDEAL COMPANION FOR CS ABOVE SPEAKERS SUPER 3 Oz. CERAMIC MAGNET

Stock No. \$1.99 2 For CTS-3 \$3.80 Manufacturers tests exceed 20,000 CPS

Special designed molded hard cone moves slightly bringing it down into mid-range. Hi-Fl manufacturers use 2 of these with a Woofer and Mid-range speakers for excellent Full Range Coverage. A Best Buy Tweeter!



C.T.S.DESIGNED

8
3" TWEETER
Ohm
3 Oz. CERAMIC MAGNET
Ck No. \$1.99
2 For
\$5.3
8 Solution of the second of the seco



CROSSOVER NETWORK University
SPHERICAL TWEETER and a University Spherical Tweeter (Mige's Type) Sale Price (1997)

McGEE SALE PRICE \$15.95

## BUYS IN HI-FI GENERAL PURPOSE 12" 8" NEW 1971 MODEL LL RANGE 8 INCH

Model 8-10-AL-FR



10 OZ. ALNICO V Net FOR MAXIMUM DEPENDABILITY

Model 8-10-AL-FR, A special design made for McGee by a big speaker manufacturer. Features 11/4" long travel 8 ohm voice coil. Extra hard ateel Alnico V magnet, equal to over 11b of ceramic magnet. The inner cone increases the high frequency response to 13,000 cps. The long travel, easy moving cone is accordion edge suspended and goes down to 40 cps. Rated 30 musical watts. Very efficient even at 1 watt. Beyond this, for better performance, you will spend many dollars for a speaker that has only a little better response. Wt. 4 lbs.

Buy Two for Sterec for \$13.00

SPEAKER MATCHED PAIR ■37 TO 15,000 CPS FOR STEREO \$9.50 41" 8 OHM VOICE COIL

10 Oz. CERAMIC MAGNET

INCH HI-FI 12-WATTS

**\*HI FREQUENCY DISPENSER CONE** LONG TRAVEL MOLDED 8" CONE ACCORDION EDGE SUSPENSION

#\$20.00 LIST VALUE

**FULL RANGE 8 IN** 

This New CTS-FR-8, Full Range Speaker has full 1" voice coil, and new curved I piece cone with Whizzer Center. The accordion edge and very large 4" spider make for very easy cone movement, We feel this speaker should self for dollars more. A very BIG McGee Bargain. \$4.95, 2 for \$9.50

## LAST MINUTE BARGAINS IN FULL RANGE SPEAKERS





## SPEAKER FOR 1971 NEW EVER OFFERED

NEW 12 Oz. CERAMIC MAGNET
1" 8 OHM VOICE COIL \$

Stock No.

X \$7433

HI FREQUENCY CONE 45 TO 15,000 CPS .... 4' WIDE SPIDER

2 FOR \$9.50

This 64/" Full Range Speaker is newly engineered by McGregor Mfg. Co. of McGregor, lowa. It has a new plastic back voice coil baked at over 700 degrees for long life. Has full 1" voice coil and a 4" free moving spider. Accordion edge cone with Whitzer center to better highs. This apeaker will give besutiful base response in a small fully enclosed baffle, but also can be used in multiples in larger ported enclosures. This apeaker is being used by several manulacturers in their new 1971 small Hi-Fi enclosures. Stock No. XS7433, McGee Sale Price \$4.95, Buy two for only........\$9 50.

## NEW 5" FULL RANGE SPEAKER FROM NORELCO



5 Oz. CERAMIC

AD5080/M8 5 in STANDARD SPEAKER With Whizzer Cone

16 For \$30,00

WORLD FAMOUS NORELCO QUALITY

THESE SPEAKERS MAKE THE SWEETEST "SWEET 16" EVER

These new 5" Norelco speakers are an outstanding value at this low price. They are all Full Range with Whizzer Center Cones, 5 oz. ceramic magnets. Stock No. AD5089/M8, Ship. Wt. 1 lb., Sale Price \$1.99, 16 for only \$33.95.

NEW 61/2" FULL RANGE SPEAKER FROM NORELCO 50z, CERAMIC OHM

CTS-FR-8


AD7080/M8 MAGNET 61/2 IN STANDARD SPEAKER

With Whizzer Cone

10 For \$22.95 Moxwells.....17,000

Gouss.....9,800 Norel co's finest 61/1" Full Range speaker with Whizzer Center Cone, 5 oz. ceramic magnet. Offered at an unusually low price. A Pig Bargain for you. Stock No. AD7080/M8, Ship. Wt. 11/1 lbs., \$2 49 each, 10 for only...\$22.95

OUR BEST OFFERING OF A



8. OHM VOICE COIL 10 OZ. ALNICO V MAGNET 40 to 12,500 CPS

Stock No.

EACH

CTS-12DT-10 WA \$15.00

Stock No. CTS-12DT-10, Extra Deep Throat Electronic Organ Speaker made by C.T.S. for McGee. This is similar to speakers that are used in big name electric organs. A very fine all purpose speaker. The deep throat design gives exceptional reproduction. 5%' required behind the baffie board. Shog. Wt. 6 lbs. Stock No. CTS-12DT-10, Net Price \$7.95 each, Two for \$15.00

GREATEST NEW 8" FULL RANGE YOL-U- SOUND SPEAKER

8 ohm. I'' voice coil WHIZZER CONE for highs. POLY-FOAM EDGE CONE 20 oz. CERAMIC MAGNET Freq. Resp. 32 to 18,000 cps Stock No. VOL-U-S OUND, 8/20

Price

**2**95

This speaker is a special design for McGee, by a large speaker manufacturer. Features a 1'', 8 ohm voice coil, 20 oz., ceramic magnet and a whizzer center cone for extra highs. Large cone spider allows longe travel of voice coil for low frequency to 37 cps. Rated power 30 watts music power. THIS SPEAKER WILL, OUT PERFORM ANY OTHER SPEAKER OF LS'S SIZE.

NEW VOL-U-SOUND, 8-20

\$5.95

#### ATLAS SOUN HORN TYPE SUPER TWFFTER **RESPONSE 2000 TO 17,500 CPS** 8 OHM- 6 OZ. Model \$1495 ALNICO V MAGNET

si MHR-3T, 3% watt, intergrated program "Super Tweeter" is the laters Jevelopment in a versatile high frequency reproducer. A super efficient tweeter with a silky smooth response, wide angle distribution and complete freedom from distortion. All parts of the accoustic path constructed of precision die castings. Every diaphragm checked for weight and compliance to assure top quality, Frequency response 2000 to 17,500 cps. Front opening 2"x 6". Area 3"x 7%"x 6%" deep overall. Impedance 12 to 16 ohms. Finished in black with gold trim. Shipping weight 3 pounds. Model MHR-3T tweeter, List \$27.50. Sale Price, \$14.95 ac., 2 for \$29.00

OHM **RESPONSE 2000 TO 17,000** 16 OHM- 2½ OZ. ALNICO V MAGNET \$15.00

Mode to sell for \$15.00 net. Stock No. RP203 REAL McGEE BUY AT \$7.95

Made from Die-cast zinc. Front opening 2" x 6". Overall 3" x 74" x 44 deep. Ship., Wt. 2 lbs.




Mode by ATLAS And 3-Way Crossover

Buy your "Super Tweeter" with a \_way cross-over network for use with any good wonfer or wide range speaker, Nodel CN-3imported cross-over network divides the audio signal between acofer and tweeter. Adjustable for 2500 or 3500 'yele crossover. Attenuation 6 db per octave, 8222 44"x 3"x 2"," high. Nodel NH 3-3T Super Tweeter with CN-3 crossover,

# Hi-Fi Crossover Network

NEW UNIVERSAL 3-WAY **Dividing Network** 

CROSSOVER AT 500 and 3300 CPS
Another Fine Quality Imported Value SALE \$ Q 95



USE TO CONNECT WOOFER MID-RANGE AND TWEETER TO

2 FOR

\$ 29.00

Its simple to connect 2 or 3 speakers to this Crossover and feed them from any sudlo amplifier, input 8 to 16 olams. Separate output connections for wooter, mid-range and tweeter. 6 db attention per octave. Crossover points 500 cps and 3300 cps. 'L' pads built-in control, instructions furnished for 2-way and 3-way speaker systems. Metal case is finished in gold and black color. This imported crossover is equal to American made units that cost from \$19.00 to \$30.00. This is a regular \$27.50 value, Stock No. CN-3 crossover network. McGee Sale price, 50.05 each.

Special Offer CN-3 CROSSOVER **TWEETER** 

Order the imported CT-6 tweeter and CN-3crossover network together and save. Buy both for Specify Stock No. CT-CN-3

FREGUENCY RESPONSE 900 to 20,000 CPS

OVERALL SIZE 10" x 11%" x 4"

Midrange HORN

20

WATT

# Midrange HORN RESONANCE 600 CYCLES

Stock No. 9489 95 8 OHMS VOICE COIL (DC)

MAX. POWER 10 WATTS. 1.47 oz. MAGNET SIZE: 4" x 101/2" WIDE. 11" LONG FRONT OPENING: 3" 1/4 91/7"

THIS HORN IS USED BY ONE OF THE BETTER MANUFACTURERS.

NEW 1972-CTS- NEW DESIGN HIGH

QUALITY DOME TYPE TWEETER

STOCK NO

CTS-2TA3 \$

This NEW CTS- Dome type Super tweeter, flange mounting Tweeter, can be mounted both front or rear in the baffle. The 1½" cone is mounted on a phenolic 2½" ring onto the metal 4½" flange

frame. The tweeter cone has a new dampening cushion made of felt in back of the cone. Freq.

CTS SUPER 4" TWEETER

3 OZ., CERAMIC MAGNET

8 OHM, VOICE COIL

PRICE

395

#### NEW MODEL 1500 TO 20,000 CPS. REQUENCY RESPONSE TWO Model FOR CH26SQ08G \$15.00 MANUFACTURED

BY OXFORD TRANSDUCER CORP. New model all metal hom tweeter with 3 oz. Alni co V magnet. Hom opening 2 X 6 in overall size 3X74X6. Rated at 25 watts. I.P.M. from 1500 cps. to 20,000 cps. Crossover freq uency is 2000 cps Impedence 8 ohms. NetWt. 2 lbs. This is the type of twweter used in \$1,000.00 home hi-fi systems.

COMBINATION OFFER

CH26SQ08G and Both For \$8.95 Crossoves

1000 LUCKY TO BUY! HORN Ship. 21/2 And MIDRANGE Res: 900 to 20,000 CPS Size: 7¾" [.. x 4" x 10½"
Front Opening 3" x 9½"

Stock No. \$ 595 ОНМ TMH8 11/2 Oz. Magnet

Polyfoam Protected Driver

WATT

Ship. Wt. 2 Lbs.

Stock No. \$4 95

FRONT OPENING... 3" X 9" FRONT UPENNS... 3" X y

Model CH20B08-2, Oxioro Iweeter and Vid.
Range Horn. 20 Watt, 8 ohm with 2 oz. Vinico
V Magnet. A very efficient horn with a frequency response of \$0010 20,000 cps. Has wide
angle distribution. All of the horn is constructed of die cast aluminum with black finish
and red trim. Front opening 3" x 2". Overall
size: 10" x 11½" x 4". Model CH30B08-2.
Dxford Tweeter-Midrange Horn. List \$14.25.
14 Gee Sale Price........ 37.99 WATT

OHM

Model

CH39308-2

HORN TYPE SUPER

Stock No. CT-6 SUPER TWEETER

RESPONSE 1500 TO 20,000 CPS

8 OHM - 1½ Oz. MAGNET Polytoom Protected over frequency of 3,000 cps. Mounts in a 1½'s cabinet opening. Size: 7½'' L. × 3'' × 6'', Opening 2' × 6''

Ship. Wt. Stock No. 6 95

Rated by one of our Customer Hi-Fi accounts as Best Tweeter Ever I



Size: 8½" tall x 3½" x 8"
Mounting centers 2½" x 6¾"

Ship. Wt. 2 lbs.

HEAVY PLASTIC HORN

### MID. RANGE CROSS.OVERS



assures accurate alignment of voice ceil and magnet with dust cover Response 2,000 to 27,000 cps.

Power capacity 20

Sixe: 214" x 234 weedle. fimpedance: 8-chmf: 13,000 Gauss.

Stock No. CT-5

\$299

31/2" SUPER 10 oz. TWEETER

95



New Super Sensitive 3½"
Tweeter, 10 Oz. Ceramic Mag-net with 8 ohm Voice Coil & a crossover condenser. Response 2000 to 17,500 cps. Stock No. TS-6070, \$3.95 Ea. Ship. Weight 21b.

NEW

### CTS 3%"



6 Oz. Ceramic MAGNET

### 3/" VOICE COIL - 8 OHM

This new CTS 31/2" Tweeter is being used by several large manufacturers in their 1971 Hi-Fi. This Tweeter has a new dampering cushion made of felt, back of cone. This enables the Tweeter to reproduce more smoothly the Hi notes. Has a 6 oz. Ceramic magnet. 4/2" voice coil. Fumished with a 3,5 Mid. N.P. condenser and Hook-up sheet. Overall size 44/2" dia. 11/4" deep. Ship. Wt. 1 pound. Stock No. TS-7171, \$3.99, Two for \$7.50.

31/2 "TWEETER

1.47 oz. magnet

8 ohm voice coil Fully enclosed back

TS-7171

Shipping wt. 1/4 lbs. Stock No. LTV Price \$1.59

Stock No. FW-4 IMPORTED 4"



8 ohm TWEETER \$1.10 2 FOR \$2.00 Fully enclosed back 14" deep

PARASOLIC EXTENDS RANGE OF ANY SPEAKER TO 20,000 CPS.



Stock No. 5-MAG-T SPECIAL PRICE

2/3" de ep Shipping wt. 11b.

Use in a 20 watt system when coupled thru a 2 mfd. cross-over condenser. Price \$1.99

### SPECIAL PURCHASE CLETRON 3" X 5" MIDRANGE



Stock No. 35MR \$ 99 10 For

\$19.00 8 Ohm, 1.47 Oz. Magnet

### Usually used 2 to a System FULLY ENCLOSED BACK

NEW in 1972. 5" MID-RANGE SPEAKER

3 OZ. CER AMIC MAGNET 8 ohm VOICE COIL FULLY ENCLOSED BACK STOCK NO 5-PC-28 PRICE 2.99

Most American manufacturers use two mid-range speakers in their systems. Only 5' diameter and 1M' deep. The treated rolled edge cone is fully en-closed. Freq. range entire mid-range.

### 31/2" HARD CONE TWEETER

2 hale mounting

l'oz magnet, 45 ohm Voice coil

Stock No. 350-45

Price \$1,39 1.7

### 31/2" Hard cone **TWEETERS**

BARGAIN PRICES.



Stock no. Size 350-4 .99 loz. 4 .99 1.29 350-8 1 oz. 8 3½ 3½ 350-47-8 1.47 oz 8 1 oz. 8



41/2" Hard cone TWEETERS

> AT BARGAIN PRICES.

Stack no. Size Mag.wt. VC Price 1,47 oz. 8 4T215 2.15 oz. 8

### NEW 6" MID-RANGE

SPEAKER



3.16 oz.Alnico V Magnet, 11/2 inch voice coil, 8 ohm impedance.

Made by one of the best speaker manufacturers. Power handling equal to to your woofer Shipping wt. 2 lbs. Stock No. 21411 deep

Price C6-11/2MR

2.99

### NEW 5%" MID-RANGE SPEAKER

5 oz. sq. ceramic magnet, 1° - 8 ohm voice coil.


Stock No. 525-MR Price

\$ 2,49 only 1-7/8" deep

Shipping wt. 11/2 lbs.

### HOTTEST NEW 1972 MID-RANGE

PINCUSHION



Stock No. 450-CTS

\$499

This new C.T.S Mid-range Is being used by some of Americas largest Hi-FI Manufacturers. Has fully enclosed back and roll edge cone., S oz. Ceramic Magnet. The special construction of this new speaker makes it very efficient on the middle ranges......\$4.99

NEW HORN LOADED DOME RADIATOR TWEETER \$ E 95 TWO FOR 3 \$11.00

sell these Other company weeters for \$10.00 and more

- A Fine Dome Rodictor, Formed Of Low-Moss Mylar, With The Added Efficiency Of Horn Loading • Exceptionally Smooth Response And High Output At Frequencies • Magnet Structure Enclased With Non-Re-sonant, Closed Cell Foom

### SMALL NON-POLARIZED

**ELECTROLYTICS** 


FOR CROSS-OVER NETWORKS.

Imported CALRAD



2 Mfd. at 50 volt rating. .29¢ 4 Mfd. at 50 valt rating .29¢

8 Mfd. at SO volt rating .29e PLANET NON-POLARIZED



CONDENSERS Made In USA

may have wires or lugs for connectors 2 mfd. 50 V.N.P. .49¢, 10 for \$4.50 aprox. size 1/x2

4 mfd. SO V.N.P. ..54¢, 10 for \$5.00 aprox. size 5/8x11/4

8 mfd. 50 V,N,P. .49¢, 10 for \$4.50 aprox. size 5/8x1-5/8

10 mfd. 25 V.N.P. .49¢, 10 for \$4.50 aprox. size 4x14/ 25 mfd. 50 V.N.P. .61¢, 10 for \$5.50 aprox. size 1x21/4

BARGAIN Non-Polarized crossover electrolytic condensers.

5 mfd. 10 V.N.P. .29¢, 10 for \$2.50 5 mfd. 10 V.N.P. .29¢, 10 for \$2.50 10 mfd. 10 V.N.P. .29¢, 10 for \$2.50 25 mfd. 15 V.N.P. .29¢, 10 for \$2.50 33 mfd. 25 V.N.P. .29¢, 10 for \$2.50 50 mfd. 15 V.N.P. .29¢, 10 for \$2.50 These condensers vary in sizes; but none are under 1/2x11/4 or over 1x3.

CLETRON NEW 1972 MID-RANGE



3.16 MAGNET 1" VOICE COIL

8 OHMS Stock No.

8MRC8 10 FOR \$35,00

RED

CURVELINEAR CONE

CINAUDAGRAPH



Stock No. DSCT-35

8 OHM 3 Oz. Ceramic Magnet

Response 900 to 17,500 cps.

FULLY ENCLOSED BACK Ship. Weight 1 lb.

### L-PADS, T-PADS, AUDIO AND HI-FI ACCESSORIES

WALD ELECTRONIC CROSSOVER NETWORK L.C. TYPE INDUCTANCE/CAPACITANCE



REAR

PRICE \$595 3-WECN Complete 3-way speaker cross-over, with presence controls, for TWEETER and MIDRANGE.
All parts are mounted on the latest type printed circuit board. Very easy to mount into the cabinet. Easy to wire to speakers, All wires are coded.
BLACK WIRES to WOOFER, RED WIRES TO MID-RANGE, WHITE WIRES TO TWEETER.
SIZE: 4% X 5. Ship. WT. 1 lb.

SOLID STATE PREAMPLIFIERS Model 14-592



Monaural **Transistors** 

6" W x 3-9/16" D x 2-1/16" H

Model 14-594—Solid State \$ Stereo Pre-Amplifier

4 Transistors Cross Talk: More than 40 db Specifications for Monaural and Stereo

Input Sensitivity: Noise Ratio: Power Source:

32 db Input Impedance: Over 59,000 ohms -59 db or more 117V AC, 50-60 Hz

W x 3-9/16" D x 2-1/16" H Ship. Wt. 2 lbs.

**CN-3** 3-Way Dividing Network \$995



Basy to connect 3 or 2 speakers to this crossover and feed them from any audio amplifier. Input 8 to 16 ohms. Separate output for woofer, mid-range, & tweeter. 6 db attenuation per octave. Crossover from 500 to 3300 cps. Metal case finished gold and black, This imported crossover is equal to the American made units costing from \$19.00 to \$30.00 Stock No. CN-3 crossover network. 

### 2-WAY DIVIDING CROSSOVER NETWORK



Compact two way crossover will channel high and low frequencies to proper speakers. High to tweeter and low to woofer.

Crossover frequency 3000 cps. Lug terminals 3 inches long x 2 inches wide Indv, Boxed with instructions

VARIABLE CROSSOVER

<sup>5</sup>1.99



Variable Crossover to match any Wooler-Tweeter combination maintaining accurate balance between the two with one control maintaining accurate balance between the two with one control replication of the control of the

Cat No CV-150



Variable A A Blook 1 Crossover Model 14-565 14 = 355 MIRLAND \$2.95 PASSER PASSE

This crossover will match any Woofer-Tweeter combination. The crossover is 2,500 Hz to infinity. All screw terminals are clearly marked for easy hook-up, Benutiful gold and black finish, size; 43/2° long x 23/2° wide x 1-5/8° high.

Stock No. 14-565



HOTTEST NEW 2-WAY SPEAKER NETWORK WITH ATTENUATOR

WITH TWEETER CONTROL 3,000 cps. CROSSOVER PANEL MOUNTED

Special Price Stock No.

\$395 2 far \$7.50 \$7.50

Model 840, The Cairad 2-Way Speaker Network has been carefully designed and assembled on a metal plate, ready for easy installation in back of your speaker enclosure without the need of complicated wiring. A fully adjustable level control is incorporated to control the output of the tweeter with the L-C type crossover network permitting both speakers to be perfectly matched for maximum sound reproduction, Input Impedance 8 nhms, Output Impedance: Woofer, 8 ohms, Tweeter 8 ohms, Inserteion Loss: Approximately 3 db. Crossover Frequency: 3,000 C/S. Has convenient push-button terminals. Size: 4" W x 5½" H x 1" D.

MULTIPLE SPEAKER SWITCH for Constant Impedance Circuits

\$149

A constant impedance multiple speaker selector switch selects from one to six speakers, keeping impedance constant with proper 2-watt resistors in circuit. Uses six SPST slide switches, mounted on brass plate. With instructions. Individually packaged. 3-1/2" long, 2-5/8" wide, 1" deep. Car. No. CSS-1

### FC-40 Hi-Fi Fader Control

An attractive fader control for one or more remote speakers mounted on a gold hammer-tone finished plate, with attractive black pointed knob Control has a resistance of 20 ohms, Individually packaged, complete with instructions and mounting screws Cat. No. FC-40

59¢ 10 FOR \$5.50

### CSS-3 Stereo Selector Switch

Calrad stereo Selector Switch permits re-mote selection of any 3 pairs of speakers. Constant inspedance will handle up to 60 watts of audio power. Mounted on gold-finished, steel plate matched to fit electric outlet wall

**\$2.49** 

### 3-SPEAKER, 7-WAY WALL PLATE SELECTOR SWITCH

Speaker selector switch mounted on brass wall plate, fits standard single wall boxes. Selects speakers: 1 or 2 or 3, or 1 and 2 or 1 and 3, or 2 and 3, or all. Marked screw terminals. Instructions included, individually pockaged, 4½ x 2½ x 2½ deep. Cet. No. CSS-2  $\$\,195$ 

### SW-15 3-Way Switch

Tringural Stares Speaker Selec-Vinaural Stereo Speaker Selector Switch enobles you to cauple up to 3 individual sets of speakers for stereo use. Hos 3 separate togale switches built into the iront popel. This unit can be used either for monaural or stereo. Finished in gold hammertone and black.

Size: 48" L # 35" W # 18" D

\$ 2 = 49

67

The state of the state of

SURFACE MOUNT HI-FI 3-SPEAKER 7-WAY STEREO SELECTOR SWITCH

me as C\$\$3 stereo selector switch fo hill speaker systems. Constant imped ence, will hendle up to 60 wert at sealing power. Mounted in completely enclosed metal bos, ideal for mounting on well or cabinet.

Stock No. N.6

Stereo "L" Pad SLP

Cat. No. SLP\_8 8 ohms Cot. No. SLP-16 16 ahms 245

A dual stereo "L" pad with single knob con-tral for maintaining proper output level enob-ling the batnicing of two speakers from the amplifier providing positive equal audio power each speaker. Has 7/8" threaded bushing.

LUCKY BUY! Triple Element - 25 Watts T- PADS AT NEAR THE PRICE Eddad OF "L" PADS \$1.69



8 OHM CONSTANT IMPEDANCE

\$1.69 10 For TP8

Best way to control speaker volume is with a constant impedance 25 watt wire wound triple element T-pad, With knob and plate, CROSSOVER NETWORK Stock No. 99

Made up in bright metal case, Size: 3¼ L. x 2½ W x 1½ D. Made for Adm miral, Has a 100 mfd. NP condenser and choke across speaker voice coil



8 16 OHM "L" PADS, \$1.49 EACH

and 16 ohm "L" Pade (level controls). A flat frequency sponse and natural reproduction are obtained by adjusting or the difference in efficiency retion. Adjustment plus or inus 17% of the normal rated impedance. "L" gaid are a 16 ohms impadance. Black plastic knobs. Apibrated it of the product of the prod instructions. Stock No. LP-8, 8 ohm "L" pad, \$1,49 eech, 10 for \$12.50. Stock No. LP-16, 18.chm "L" pad, \$1,60 ee., 10 for \$12.50.

CALRAD 3 WAY DIVIDING 8 OHM NETWORK for most systems.



FADER CONTROL - 20 OHMS 39¢ 10 FOR \$3.50

20-ohm volume control for use as new seat speaker fader control. Front, rear or both. Can also be used as a volume control for any small speaker having a voice contimpedance of 4, 8 or 16 ohms. 14" diameter, 4" threaded bushing. %" stotted knurled shaft, Supplied with nut and washer.

Cat. No. VC-20



FADER CONTROL - 20 OHMS

10 FOR \$4.00

Fader control with back cover, 20 ohm volume control for use as rear seal speaker fader control, front, rear or both. Can also be used as a volume control for any small speaker having a voice coil impedance 4, 8, or 16 ohms. 1½° diameter, ½\* threaded bushing, ¾\* slotted knurted shaft, Supplied with nut and washer, Indv, packaged. Cat. Na. VC-22



HUM BALANCE CONTROL

-100 OHMS 10 FOR \$3.50

100-ohm wire-wound volume control to be used for Cat. Ma. VC-100 speakers having a voice coil impedance of 4 to 45 ohms. Excellent for use as a hum balance control in all amoliflers. 11/6 inch dia. Va. in. threaded bushing. Slotted knurled shaff. Supplied with nut and washer.



AMERICAS BEST BUYS IN GUITAR AND BASS AMP SPEAKERS.

FOR THE PROFESSIONAL WHO WANTS A SPEAKER THAT WILL HOLD UP UNDER UNUSUAL REQUIREMENTS, FEATURES A HEAVY DUTY CONE .... MEGEE'S BEST BUY . MADE IN U.S.A. SPECIALLY FOR MEGEE BY C. T. S. RATED 70 WATTS PEAK . SO WATTS MUSIC POWER, RESPONSE 29 TO 9000 CPS

CUSTOM MADE BY C.T.S. FOR MC GEE IN 12 and 15 INCH SIZES

STOCK NO. BG-60PM

EXTRA HEAVY DUTY

FOR GUITARS AND BASE AMPS.

TWO FOR \$54.00

BG-60 P.M. A 12 inch extra heavy duty C.T.S. built speaker with the same 3½ lb. magnet and 2 inch voice coil as the 15 inch model BG-70 shown to the left. The same power and frequency response rating. Ship wt. 14 lbs. Net \$27.95 2 for 54.00

SINCH HEAVY DUTY FOR GUITARS AND BASE AMPS. FOR

re is a real 1 inch speaker value. Custom made In U.S.A. 1x Gee by C.T.S. It will handle 50 warts, 70 warts peak, rect for an all purpose wooter, but designed primarily for use in professional guitar amplifiers and base amplifiers. Will certar audio power down to 29 cps. and up to 9000 cps. e voice cail is 8 ohms and is 2" in diameter, wound on a

DESIGNED 12 INCH AND 15 INCH SPEAKERS FOR BASS AMPS. Straight grain 1 1b.

FOR

SILVER NICHROM VOICE COIL LEADS

Ainico V. magnet

ship wt. 10 lbs.

DULLY

Another

McGee best buy.

ALUMINUM BASE HIGH TEMP. McGEE SALE PRICE BG-40-15

TWO FOR \$29.00

VOICE COILS. B ohms imp. C.T.S. designed for American guitar manufacturers. Features a streight grain Alnico V. machined magnet. Fitted deep in the 2 inch voice coil. for highest eff. Better sound than speakers of older design having up to 21b. magnets. The wide heavy magnet structure has little or no magnetic field loss. The next best buy to the 31/2 fb. magnet speakers shown above.

EAVYDUTY One pound Alnico BASE AMPS.

2 for \$25.0@

ship wt. 9 lbs.

HIGH FIDELITY ACCORDION EDGE WOOFERS. INCH **12 AND** BIG ALUMINUM 2 INCH VOICE COIL EXTRA

VOICE COIL FOR BETTER BASS RESPONCE.

Model BG40-12FE

INCH \$1295

WOOFER

2 for \$25.00

C.T.S. Stock no. BG40-12FE Shipping wt. 9 lbs. TREATED ACCORDION EDGE CONE RESPONSE 30 to 10,000 cps

Rated 30 music watts New 1972 12 in all purpose woofer companion speaker to the 15 inch offered to the right. Thes two are fine in most any inclosier.

New 1966 custom designed 15 inch woofer and all purpose speaker. Low loss magnet structure 1 lb magnet nested inside the voice coil for best audio reproduction. 8 ohms imp. Rated 35 music watts.

WOOFER 2 for \$29.50

C.T.S. Stock no. BG40-15FE. Shipping wt. 10 lbs.

**GUITARS** 

TREATED ACCORDION EDGE CONE RESPONSE 28 to 10,000 cp



50 WATT

OHMS

**NEW ORGAN PEDAL SPEAKER** 15 INCH 8 OHM VOICE COIL

FLUX DENSITY 145,000 MAXWELLS 50 WATTS (PEAK PROGRAM WATTAGE) RESPONSE 25 TO 8000 C.P.S.

FREE AIR RESONANCE 30 C.P.S. DOWN TO 18 C.P.S. IN BIG BAFFLES

Made in U.S.A. ... A Woofers . Woofer ! List Value \$35.00

ONE PIECE MOLOEO CONE WITH VINYL TREATED EDGE

Stock No. PEDAL, 15-16-8, New 15" Organ Pedal Woofe.
McGee's New 15" Woofer to respond even to Organ pedal tones. Not only a good addition to your organ but you can design your own 2 or 3 way Hi-Fi system. Equipped with a 1 lb. Alraico V magnet, actual magnet weight. The 2" voice coil is impregnated to give better heat dislipation and longer life. Response to 3000 cps. Add a mid-range speaker if you want to use with Hi-Fi Systems. Stock No. PEDAL15-16-8, \$14.95

MODEL PEDAL 15-16-8 \$1495 2 \$2900

Shipping Weight 10 lbs.

AMERICAS BEST BUY IN FULL RANGE 15 INCH



HEAVY DUTY

GIANT 54 OZ. FERRITE MAGNET 2" 8 OHM VOICE COIL RATED 70 WATTS PEAK - 50 WATTS MUSIC POWER Frequency Ronge 28 - 17,500 CP\$

WITH WIZZER

**FULL RANGE** 

FLEX EDGE CURVED CONE

BG-70FEF

McGEE Special! Stock No. \$1 \$5900

Shipping Weight 20 lbs.

BG-70FEF, A 15" Full Range speaker features a Giant 54 Oz. Ferrite BG-70FEF, A 15" Full Kange speaker restures a Grant 34 Gz. Ferrite magnet of a new high density magnet material, 2 inch, 8 ohm voice coil and a flex edge Curvelinear cone with a Whizzer cone. It will handle 70 watts peak and 50 watts music power. Frequency range 28-17,500 CPS. Speaker has a net weight of 19 lbs. Shipping Weight 20 lbs. Model BG-70FEF, McGee Special \$29.95, Buy two for only \$59.00

## McGEE'S 1972 HEAVY DUTY GUITAR & BASE AMP SPEAKERS

\$70.00 LIST VALUE

NEW 1972 20 Oz. Alnico Tapered Magnet

60 WATT CONTINUOUS DUTY

 $\mathbf{H}_{\mathbf{N}}(\mathbf{H})$ MUSICAL AMP SPEAKER

Stock No. EM15-MA8 17.9 2 FOR \$35.00

8 OHM, 2"

Voice Coll..... Aluminum Bobbin... Epoxy Impregnated And Baked at 500°

Heavy One piece cone with Vinyl treated edge and Vented Aluminum Dome center

and Vented Aluminum Dome center

Stock No. EM 15-MA8, All the Musical Amp speaker there is at any price. This 15" speaker will operate continuously at 60 watts. Has 20 Oz. Ainleo 5 Tapered magnet which manufacturer says has a force equal to our speaker with 54 oz. Cerame a magnet with only 1½ do lower output. This heavy duty speaker has a 2" voice coil incorporated with a solld aluminum bobbin with the 3 ohm winding Epoxy coated and baked at 500 degrees, Made to standup under more aidio watts than any voice coil yet designed. The heavy one piece come has Vinyl treated edge and a vented dome center. Ship. Wt. 10 lbs. Terrific Buy in a 15", 60 watt speaker. Stock No. EM 15-MA8, McGee Sale Price \$17.95. Two for only.....\$35.00. Stock No. EM 12-MA8, Same Specitications us above 15" but in a 12". 50 Watt Continuous Duty Musical Amp Speaker. A good buyl Stock No EM 12-MA8, Sale Price \$15.95. Two for only.....\$31.00.



**GUITAR SPEAKER** A PAIR OF THESE WILL TAKE

BEST 15" GUITAR SPEAKER VALUE 1 Lb. ALNICO V MAGNET \$ 14 95

Stock No. EM-15G 16 2 for \$29.00

Voice Coll on Aluminum bobbin is Epoxy Impregnated and baked at 500 o

Impregnoted and baked of July

A tremendous 15" speaker. Made in U.S.A. by
Eminence Co. special for McGes. Made like the 10
inch speaker above. We don't offer a 12" size in
this design because it would be too near the price
of a 15". This model features a new cone structure special for Guitars and Lead Guitars. The outer cone edge (1") is plastic vulcanized to give a
very bung life and line cone action. Ship. Wt. 101bs.
Stock No. EM-15G 16, \$14.95 each, 2 for ....\$29.00



GUITAR SPEAKER

BEST 12" GUITAR SPEAKER VALUE SAME AS ABOVE EXCEPT IS 12" 1 LB. ALNICO V MAGNET 2" 8 OHM VOICE COIL

Stock No. EM-12G16 95 2 For \$25.00

Shipping Weight 8 lbs.

LEAD GUITAR & PA SPEAKER



Model 57.49 \$14.5)

Model EM 10 G10, 10" - 10 Oz. Alnico V magnet. The 1½" dta. 8 ohm impedance coil features all copper winding, seal ed in high temp. baked on impregnating material; for long life and burnout protection. Flux density 90,000 maxwells. Peak program wattage 35. Res. in free sir 85 cps. Best audio response range from 55 to 10,000 cps. Made in U.S. A for use in PA, Sound Columns and for lead guitars. Use in groups of twos, 4's & 8's for hi-powered audio and good sound distribution. 10 oz. Alnico V magnet is piston nested in voice coil giving speaker a higher efficiency for a given input than normal 6.8 Oz. or 10 Oz. full range 8" speakers. Better mare drum, cymbal & voice response. A 2½" Aluminum disc in cone's center enhances mid high range audio res. 4-5/8" Depth. Wt. 4 lbs. Ship. Wt. 5 lbs.

Model **BLG-70** 

80 WATT

MUSIC POWER

EXTRA HEAVY DUTY

SPEAKER

FOR BASE & LEAD GUITAR

2 " 8 OHM VOICE COIL

2 FOR \$5900

GIANT 54 OZ FERRITE MAGNET MADE IN U.S.A. BY C.T.S. FOR McGEE

BLG-70, Made in U.S.A. by C.T.S. for McGee, a Glant S4 Oz. ferrite magnet lead guitar speaker features 2 inch, 8 ohm vaice call and a special heavy ribbed cone with treated surround. A Better and more costly speaker than normally comes with your instrument. If you want to add speaker to your guitar system, build your own baffle and use speaker. A \$70.00 list value. Ship, Weight 17 lbs. McGee's price \$29.95 each, 2 for..........559.00

70 WATT MUSIC POWER HEAVY 12" SPEAKER Model BLG-60 FOR BASE & LEAD **GUITARS** 

GIANT 54 OZ FERRITE MAGNET 2" 8 OHM VOICE COIL

MADE IN USA BY CTS

FOR \$5400 BLG-60, 12" lead guitar and base guitar speaker. Same magnet size and same quality speaker, only in 12" size, Slightly different cone structure but performs similar to 15" model BLG-70. Ship. Wt. 14 lbs. Rated 70 watts music power. Has 2", 8 ohm voice cail. McGce's price \$27.95 each, 2 for......\$54.00

For instrument and gultar amplifier use. STOCK NO. CTS 12-10

MCGEE'S INCH SALE

FAR 10 OZ. TAPERED ALNICO V MAGNET FEATURES NEW SILICONE OUTER EDGE



SPECIAL GUITAR SPEAKER RATED 25 WATTS **NEW 1970 DESIGN** 

Here is McGee's enswer for a good all purpose guitor and music amptifier speaker for replecement use. Full range response from 35 to 10,000 cps. The 11/2 inch 8 whm vaice call will metch most all audio emps. The heavy ribbed cone has silicone rubber malded in the edge for langer life and better cene mevement. The 10 or straight grained elaics V, magnet is equal to a 1 lb, ring magnet and better then 20 ex, ceremic. The speaker is about twice as good as usually comes in the cases of particle P.A. amps. Shipping wt. 5 lbs. Stock no. CTS 12-10. List value \$17.50 Ner \$7.95 eo.
Two for \$15.00. Another McGoe first in speakers. Another McGee first in speekers.

BUTY 1972

**GUITAR SPEAKER** 

A PAIR OF THESE WILL TAKE TS TRUE

BEST 10" GUITAR SPEAKER VALUE

BEST 10" GUITAR SPEAKER VALUE

1LB. ALNICO V MAGNET

2° - 8 0MM VOICE COIL

5° - 8 0MM VOICE COIL

5° - 8 0MM VOICE COIL

4 Giant oi a 10 inch speaker. Just like comes with one of Americas big name, high priced electric guitars, If you need an extra powerful speaker and don't have room for a 12" speaker, this is McGee's answer. Never before have we offered such a speaker. Shpg.

Wt. 8 10s. Stock No. CTS-10-G-16. A 530,00 value.

McGee net price \$12.95 each, Buy 2 for only \$25.00

### GUITAR SPEAKERS AND ASSEMBLIES NEW

# Lifetime Guarantee

1% lbs. MAGNET 1½" Voice Coil

RESONANCE 60 CPS 8 Ohms. 41/4" Depth



\$3450

Model 421A

LEAD **Guitar Speakers** Magnet Type: Ceramic-Ferrimag

Power: 100 watts Diameter: Impedance: 8 ohms Voice Coll: 3" edge wound Magnetic Structure copper ribbon

Weight: 17.5 lbs

15-5/16"

Depth: 6% Weight: 21 lbs

50

421A

LM I-125

LMI-155/EM-1550.

ELECTRONIC MUSICAL INSTRUMENT

> LOUDSPEAKERS The Jensen LIFETIME Electronic Musical Instrument Loudspeaker group includes four fully LIFETIME GUARANTEED loudspeakers. These 12" and 15" loudspeakers designed especially for bass guitar, string bass, fully instrumented guitar and electronic accordion are fully guaranteed against loudspeaker shatter and diaphragm

Musicians no longer need to take chances on speaker failure in the middle of a performance. LMI-152 Bass Guitar New design features and engineering advances make this lifetime guarantee possible. Heavy duty high temperature voice coils prevent electrical burnout. A special high-stress mechanical suspen-

tetime quaranteea

amplitudes without damage. Unusually heavy magnetic structures and proper air gap design also materially, aid the overlead capability of these unique loudspeakers.

When you buy original or replacement speakers for bass guitar, string bass, fully instrumented guitar or electronic accordions you'll want a Jensen-the speaker with lifetime guarantee.

Jensen model EM-1520 15 inch guiter speaker, 3½ 1bAlnico Vmag. 2 inch 8 ohm voice coil. Ship wt. 17½ ibs.

Jensen model EM-1220 12 inch guitar speaker. 1% 1b Syntox 6 mag. 1% inch 8 ahm voice coll Ship wt. 81/2 lbs.



LM-122

Bass Guitar \$34.62 net

1% Ib Syntox Magnet.

\$66.30 net. 31/2 Lb. Alnico V. Morgnet sion allows high power surges and large diaphragm

418 B Giant 3" VOICE

COIL

OHMS

AND MUSICAL INSTRUMENT SPEAKERS 417-8C Model 417-8C

Model 418 B

HEAVY CAST ALUMINUM FRAME

### When You Care Enough To Use The Very Best

Specifically designed for electric guitars, string bass instruments and electric organs, the new Altec 417A and 418A musical instrument speakers will delight the most sophisticated amateur and discerning professional. After engineers have created these professional quality speakers, which cover the instruments full tonat range, enhancing the natural brilliance and sharp, precise bass, resulting from electronic amplifica. tion. These Altec speakers, developed from many experimental prototypes, have been critically evalu-FROM THE FIRST NAME IN ated and heartily approved by both professional and amateur musicians. The famous Altec "Voice of the Theatre" commercial speaker systems have set the standard of quality for many years and now the 417A and 418A musical instrument speakers have taken a place in the ranks, proudly bearing the Altec

100 rhese new Altec speakers are ruggedly built to withstand high level audio. Avoiding filmsy stamped parts, NET the frames are made of heavy cast aluminum. The massive magnet structures house an Alnico V magnet, The three-inch voice coils, made of edgewound aluminum ribbon, attached to a sturdy diaphragm having a light weight aluminum dome, gives a brilliance of sound found in no other speaker of its kind. A high gap flux density means precise control of the moving cone and extreme high efficiency which gives greater acoustic output.

NET

Altec Model 417-85 12" Speaker with heavy cast aluminum frame: 75 Watt music power, 8 ohms impedance, 3" edge wound aluminum ribbon voice coil, 2.4 lbs. Ainico V Magnet, Depth 5-5/8". Total Weight 16 Pounds Free air resonance 48 Hz, 13,000 gauss.

After Model 418 B, 15" Speaker with heavy cast aluminum frame: 100 Watt music power, 8 ohms impedance, 3" edge wound aluminum ribbon voice coit, 2.4 lbs Ainico V Magnet, Depth 7", Total weight 17½ Pounds. Free air resonance 35 Hz, 13,000 gauss.

WORLDS BEST BUY IN HEAVY DUTY

15" GUITAR SPEAKER THE 1972 EMINENCE "BIG BRUTE"

> 30 OZ. GE TAPERED ALNICO 5 MAGNET 2½" Aluminum base. Epoxy treated V.C. Heavy seamless cone-Viny treated edge 100 WATTS IN PROPER BAFFLE

Stock No. \$2999 2 for \$58.00

12EM30 12" Size 22799 2 for \$55.00

This new Eminence 15" Gultar Speaker is the most speaker we ever offered at this low price. Eminence Speaker Corp. probably makes more heavy duty 12 % 15" speakers than any other Mfr. They are used by most all music instrument Mfrs. This speaker has large 24" voice coil baked at 500 degrees with the latest Epoxy glues. It exceeds other very popular 54 oz. ceramic speakers in both handling power & output, These speakers are tested at better than 100 watts on the line. This speaker is also ideal for heavy duty Public Address work. Shipping Weight each, 16 pounds.



S ORIGINAL LIGHT WEIGHT EQUIPMENT SPEAKERS.

### NEW 1972 HI-FI FULL RANGE SPEAKERS, - -- WOOFER SPEAKERS --- BASS AMP SPEAKERS.

1972 HI-FI FULL RANGE SPEAKERS for STEREO and EXTENSION and SINGLE SPEAKER CABINETS.

(These should aut perform any of the small



cheaper three way systems.)

STOCK NO

CTS-FR 12-20-8 95

12 inch FULL RANGE SPEAKER

2 For \$35.00

Accordian edge cane 20 az. Alnica '5' magnet 8 ohm, 2in., Vaice cail

Whizzer cane for highs Resonance freq., 26 cps. Shipping wt., 9 lbs.

One of These 6 Microphones Will Answer Your Replacement Problems



A real value. Designed to fit most essette-type recorders. Complete with dual plugs faudio end remote control) plus adaptor for recorders using coexial remote control plug. Impedance: 500 ohms. Sensitivity: -70 db 9 1KMz. Response: 60.12,000 Mz. Remote switch and 5-foot cable. Net \$3.95

C H

For Norelco, VM, Phillips, Uher, cassettetype recorders, Dual Hishman (Dia) plugfor audio end remote control. Impedance:
500 ohms. Sensitivity: -70 db @ 1KHz. Response: 60-12,000 Hz. Remote witch and
5-foot cable.

For casette recorders with extremely low impedance (200 ohms). Complete with dual plugs (guidle and remote control) and adapter for recorders using 14.5 remote control plug. (Sonyl Sensitivity: -70 db @ fKMz. Remote switch and 5-loot cable. Nat \$3195

8 Designed for tape recorders requiring a high quality microphone with a single miniature live. Supplied with an adapter to convert from miniature 10 standard 1/4/5

plug Has on-off switch. Impedance, 500 phms. Sensitivity: -70 db

Personne: 60-12,000 Hz. Supplied with 5' coble.

DX-132 B

DX-133

DX-211 B

DX-242 B

Net \$12.95

Matched Pairs Only

Ouality microphone for stereo tape recorders. Supplied with adapters to convert from minia-ture to standard ¼" phone plug. Imped-ance: 500 ohms. Sensi-tivity: -70 db @ 1 KHz.

Response: 60-12,000 Hz. Supplied with 5' cable.

\$12.95

\$4.25

\$3.95

\$3.95

Net \$3.95

HEAVY DUTY GUITAR BASE AMP

**18-INCH** 

EXTRA



SOFT PLIABLE PLASTIC

Stock No. BG-80PM

No others have this speaker at this

Here is a real 18 inch speaker value! Custom made in U.S. A for McGre by



COATING ON THE OUTER INCH OF THE CONE GIVES LONGER CONE LIFE

LOW PRICE

Custom made in U.S. A for McGze by C.T.S. It will handle 50 watts, 70watts peak. Perfect for an all purpose Woofer, but designed primarily for use with professional guitar amplifiers & hase amplifiers. Will take extra audio power down to 29 cps and up to 9000 cps. The voice coil is 8 ohms and is 2" in diameter, wound on a laminated aluminum and paper molded voice coil form. The magnet is 3½ lbs.of a new high density ferrite magnet material. The speaker has a shipping Wt. of 18 lbs. A \$90.00 list value. McGees net price is \$39.95 each, Two for \$78.00



A low-cost replacement for recorders requiring high impedence (50k ohms). Sensitivity:
61 db © 1KHZ Response 50-10,000 Hz.
Remote switch and plastic stand. 5-foot coble. (Blister pack model has dual plugs for audio and remote control; no stand.)

VOL-U-SOUND SPEAKER

CUSTOM DESIGN for McGEE **NEW FOR 1972** AMERICAN MADE 10" WOOFER, ROLL EDGE CONE NEW BUTYL RUBBER 20oz. CERAMIC MAGNET, 80hm 1" VOICE COIL freq res. 30 CPS Stock No. Price \$695 VUS-10-20 \$60,00

NEW-1972, HI-FI FULL RANGE 15" SPEAKER



BUY THIS SPEAKER FOR YOUR STEREO. HI-FI AND SOME P. A. INSTALLATIONS, IDEAL FULL-RANGE SOUND IN A PROPER TYPE McGEE

BAFFLE.

STOCK NO

SALE PRICE CTS-FR-15-20-8

15-inch FULL

RANGE SPEAKER

TWO FOR

\$39.00

Accordion edge cone 20 az., Alnica '5' magnet 8 ahm, 2 in., Vaice cail

Whizzer cone for highs Resonance freq. 22 CPS. Shipping weight 10 lbs.

The BIG-BRUTE series, 30 az., ALNICO '5' magnet speaker, (shown below) is better in construction and the 30 az., magnet and the 2½ inch Vaice cail has 1 db over the 54 az., 2 inch ceramic magnet speaker. The heavy square ceramic magnet causes shipping problems as they will shift (ar move) during rough handling by the carriers.

NEW 1972 --- BIG BRUTE HIGH-FIDELIT DO NOT USE ON MALL AMPLUTIERS
12 and 15 inch, WOOFER

28 WATTS RMS
OWER

2½ inch VOICE COIL, 8 ohm impedance 30 oz. ALNICO "5" MAGNET ACCORDIAN FREE EDGE CONE FREE AIR RESONANCE 20/25 CPS BIG BRUTE 15-FE BIG BRUTE 12-FE

Two for \$58.00 Twa for \$55,00

lwa for \$50.00 I wa for \$55.00

Here is the best woofer made for full response. This speaker would be considered low efficiencent arequiers power greater than 10 watts to reproduce properly." This is the newest concept of sound. Hi-Fi amplifiers played at higher output levels and having lower output volume at the speakers for best response. The new longer two layer volce coil and large spider allows the voice coil to move freely and be fully energized the length of the cone travel. This enables the sneaker to have the best response at the lower end.

Here is a brand new heavy duty Hi-Fi Woofer that has a giant 30 oz, Alnico 5 magnet and a 2½ inch voice coil. This speaker has a greater power handling and output then the popular 54 oz, ceramic magnet speakers of late years. Also ships much better than heavy duty ceramic type. Which is plasted with magnet splitting and moving on base frame. The 15" speaker weighs 11 ibs. and 12" weighs 10 lbs. This speaker is ideal for the new high output Transistor amplifiers.

### AMERICAS HOTTEST BUYS IN COMPACT SPEAKER SYSTEMS

### 2 OF THE HOTTEST VALUES!



TWIN 61/2" SPEAKER SYSTEM SAME SYSTEM AS TWIN-8 EXCEPT USING TWO OF OUR 6CTS-10-8 WOOFERS AND ONE 4" TWEETER IN CABINET

> Stock Na. TWIN 61/2


SPEAKER WITH WIZZER

One of the best full-range speakers we have tested

2 For \$35.00

"Twin 6%" Speaker System in cabinet constructed of 1½" plywood with wainut grained vinyl covering. Size: 16½" L x 11½" H x 5½" D. Ship. Weight 12 lbs.


### VOLUMETRIC 4 IN. SQ. PM DYNAMIC SPEAKER




• 5 Watt 10 Watt Peak

This speaker has most of the features of the \$503 speaker described above. They both have a new type territe magnet which is a great deal mare powerful than neretotore. Impedance 8 ahms, in-4 95 dividually boxed.

Cat. No. 5502



### VOLUMETRIC 5 IN. PM DYNAMIC SPEAKER



• Frequency 40-17,000 cps

• 71/2 Watt 15 Watt Peak

This economy model will out-perform many larger speakers. Ideal where space is limited. Closer fitting voice coil gives excellent transfer of energy. It will improve your system. Voice coil 8 ohm impedance. Individually boxed. Cat. No. \$515


5 95 Ship. Wt.



Sold by others for \$8.95

3 Lbs.

### VOLUMETRIC 6 IN. PM DYNAMIC SPEAKER WITH WIZZER



• 10 Watt 20 Watt Peak

A new approach has been used in the design of this speaker for good compliance and omplitude. A new type voice coil. A special type of paper and the configuration of the cone. The membrane material which supports the edge of the cone is unique. Impedance 8 ohms.

Cat. No. \$503 \$ 2 For \$15.00

4" P.M. and 2½" TWEETER

Uses Above

\$502

SPEAKER

And 21/2"

TWEETER

Shipping Wt.

10 Lbs.

TWO WAY

SPEAKER SYSTEM

2 For \$33.00

\*ESPONSE 35-17,500 CPS

. WALNUT CABINET

. CROSSOVER NETWORK \* 11" H. = 46" W. = 2" D.

# CALRAD VOLUMETRIC 8" PM DYNAMIC

Quality

Import

Ohm



will be amazed with its performance. Individually boxed.

Frequency 30 to 20,000

· Ferrite Magnet

20 Oz.

• 15 Watt 30 Wolf Peak



Cat. No. 5518

BUY

### BIG BARGA COMPACT II VOLUMETRIC TWO WAY SPEAKER SYSTEM



No. \$\$54

Response: 35-18,000 CP5 **Walnut Cabinet** Crassover Network

**HEAVY DUTY** 6" WOOFER 21/2" TWEETER

2 FOR \$45.00

An improved acoustic innevation, will improve most present systems. Enclosed in a beautiful walnut cabinet. 20 Watt output R.M.S., 30 Watt program. Impedance 8 ohms, Response 35-18,000 cps. Compact in size, only 13" H. x8%" W. x 7%" Detthis is a giant in performance, for it is a full-fledged two-way system using a proper crossover network and providing superb compliance and amplitude, extending beyond both ends of the audio spectrum. spectrum. Shipping Weight 12 Lbs.



COMPACT III VOLUMETRIC

• RESPONSE: 30 TO 20,000 CPS

. POWER CAPACITY: 40 WATT PROGRAM



# An accoustic innovation, sounds like a system much larger. Completely enclosed in a beautiful walnut cabinet. 10 Watt output R.M.S. 29 watt program. Impedance 8 ohm. Small in size but a Giant in performance. Cat. No. SS-53....\$16.95 THREEWAY SPEAKER SYSTEM

Ship. Wt.

3% Lbs.


. HEAVY FERRITE MAGNETS

. CROSSOVER NETWORK

WALNUT CABINET: 19½" H. x 10" W. x 7¼" D.

Looks beautiful, sounds excitingly different, like some of the largest and most expensive speaker systems. Scientific principle adds extra pratection to high tones, re-creates music with startling fidelity. Ideal for stereo or monaural speakers-2 specially-designed high compliance woofers, and one tweeter extends response 30 to 20,000 cps. Cabinet of walnut with oiled finish. Impedance 8 ohms. Shipping Weight 17 Lbs.

Cat. No. SSSA Uses (1) 21/2" Tweeter, (1) 5" and (1) 8" similar to above speakers





FOR 1972

# McGEE'S BEST SPEAKER VALUES

WATT FOR WATT ... DOLLAR FOR DOLLAR ... CYCLE FOR CYCLE



MODEL \$20-71 29 TO 17,500 CPS

\* AMATCHED SPEAKERS

★15" E15-3/4-8FE WOOFER ACCORDION EDGE 3/4 LB ALNICO V MAGNET 14" VOICE COIL

+ 12 INCH HARD CONE MID-RANGE

2 - 4" TWEETERS READY TO INSTALLIN YOUR ENCLOSURE



WATTS 20 TO 17,500 CPS

FEATURES

- \* OXFORD HORN TWEETER
- MEW CTS 15 INCH WOOFER with LONG TRAVEL - EASY MOVING ACCORDION EDGE CONE. Plus A 2" Voice Coil
- # 2 6" MIDRANGE

Stock No. \$20-71, 'Big Sound'', Our latest model "Big Sound' high-fidelity speaker system that will outdo many \$100.00 systems, is all American made 4 speakers wired together with proper crossover networks to reproduce good music on a low badget. Two 4" tweeters plus a special 12" 68 oz. magnet hard cone Midrange and Base midrange plus a 13" Woofer with 3/4 1b. Alnico V magnet and 1½" voice coit, accordion edge cone. System response 29 cps to 17,500 cps. Will take 30 watts music power but will also sound good on even 10 watt amplifier. Impedance 8 ohms. NOT MAILABLE, Shipped Express ore by truck only. Model \$20-71, Shipping Wt. 20 lbs. McGee Net Price \$19.95

The "Big Sound" and "Super Big Sound" are ready-to-use Speaker Systems mounted on 5/8" plywood, 16 x 32" baffle boards. Speakers are connected together with proper networks and ready to connect only 2 wires to the 8 ohm top on your Hi-Fl audio amplifier. Use them singly or buy 2 for stereo. Shipping Weight on either model is 20 lbs. NOT MAILABLE...Shipped TRUCK OR EXPRESS ONLY. You can cover them with grill cloth or build them in your own enclosure. You don't need high powered audio amplifiers to play your big sound system, even a 10 watt amplifier will give you loud volume and Hi-Fi Music reproduction. These are McGee's Best Speaker Values......

# BAFFLE BOARD

This 18 inch speaker has an accordion edge free moving cone for best base res.

**FEATURES** 2-5" MID-RANGE

31/2"CTS

MODEL C-31/2-8

Speakers are mounted and wired. Ready to install in your Baffle.

Response 18 to 17,500 CPS

CUSTOM SYSTEM SUGGESTED BY CTS ENGINEER AND USED BY HIM FOR HIS OWN PERSONAL HI-FI SYSTEM

Stock No. ALC, McGee's 1971 "Big Sound" is mounted on a 20 x 30 inch, 5/8" plywood baffle board, wired and ready to install in your baffle box or in a wall or anywhere you please. It features American made 18" CTS Woofer custom designed and built for McGee. A 3½1b. giant ferrite magnet plus a 2" diameter, 8 ohm voice coil and cone with accordion edge. Combined with two 5" CTS mid-range and two CTS 3½" Tweeters makes up a system with a recovery CTS 3½" Tweeters makes up a system with a response from 18 to 20,000 CPS. These speakers working together, is one of the best Sound with systems costing much, much more. Ship. Wt. 20 lbs. Sale Price \$59.95, buy 2 for stereo for only \$.118.00. The Woofer alone may be purchased for only \$39.95. Truly a Big McGee Value.



This 18 inch speaker has a accordion edge free moving cone for best base res.

High Fidelity AND AMPS. 31/2 LB. 2INCH 2095 COIL Stock No. BG-80FE

Stk. No. BG-80FE Here is a real 18" speaker value. Custom made in U.S.A. for McGee by CTS. It will handle 60 watts, 80 watts Peak. Perfect for an all purpose woofer and professional amplifiers and base amplifiers. Will take extra audio power down to 18 cps and up to 9000 cps. The voice coil is 8 ohms and is wound on a 2" heavy duty laminated molded voice coil form. 3/2 1b. High density Ferrite magnet. Ship. Wt. 20 lbs. List Value \$90,00. McGees sale price \$39.95. 2 for \$78.00

PLASTIC 3/4" wide. ELECTRICAL TAPE



Top quality imported value, McGee offers good standered M" plastic electrical tape at less than half the cost of American made plastic tape.

PB-66 B BLACK

66 FT. 10 FOR \$5.50 1/2 INCH WIDE PLASTIC

ELECTRICAL TAPE

EXTRA HEAVY DUTY



10 For \$3.50

Plastic Electrical Tape consists of high dielectric strength and flexiable streech, anug wrap, water proof and will resist oil, gasoline, water, salt water, alkalis and sunlight. Color

will result water, alkalis and sunlight. Color RED, Individually cellophane wraped and packaged ten to a master carton. Specify color when ordering. 66 ft., %" wide. Stock No. 15MR-RED

### EQUIPMENT CABINET...BAFFLES...RECEIVER...SPEAKERS

ULTRA-COMPACT AC-DC RADIO KIT \* OUR BEST HI-FI CONSOLETTE POWERFUL 5-TUBE SUPER HET SPECIAL BUY STOCK NO 205

PRICE \$11.95 ea

NO PRINTED CIRCUIT. POINT TO

SCHEMATIC PICTORIAL AND STEP-BY-STEP INSTRUCTIONS FOR EASY ASSEMBLY ARE INCLUDED WITH EACH KIT.



DILED WALNUT FINISH With Very Attractive Brown ENCLOSURE ONLY

FOR 12"SPEAKER Cut for 12" SPEAKER

1 or 2 3%" TWEETERS Srock No. 524 95

2 For \$48.00 nather ted of all Partiete Board h Olded Walnut Venner Finish are Filled Accounts Liming 194, H & 181, W & 11" D m 24" bar 24" bar Shipping Weight 38 lbs.

OILED WALNUT BAFFLES AND SPEAKER SYSTEMS

### Nald

MODEL 800 PRINCE EDWARD GILED WALNUT SPEAKER BAFFLE

nclosure only for 8" and 31/2" speakers.

Model WOS

SLDPING-FRONT

OILEO WALNUT

SPEAKER

BAFFLE

FOR

8 "

SPEAKER

Heavy duty 3/4" walnut cabinet with solid walnut \$19.95 teams, oil finished. Ship Wr. 15 ths
A compact Size — 22H, 11W, 83/4D



enclosure only for 12' and 31/2" speakers.

Ship, we, 20 lbs. Size — 25M, 14 1/4W, 111/4D 1200 taure! Enclosure is accounstically dispersioned. Rugged 1/4" throughout, Walnut \$22.95 WALD MODEL TW8

### BI DIRECTIONAL

2 WAY COVERAGE OILED WALNUT

SPEAKER BAFFLE With Mounting Brocket FOR


8" SPEAKER

SIZE
91/4 High
111/2" Wide
41/4" Deep Ship. We. 6 Ibs.

DELUXE WALL HANGING SIZE 12 High 113/4" Wide Tapered 7 to 41/3

hed walnut, colid walnut frant for cloth. Mounting bardware. Baifte ker. 12" thigh, title" Wide, Tape

STANDARD OIL WALNUT FINISH



Ship We. 8 lbs.

REFLEX CABINETS FULL 3/4" WALNUT PLYWOOD APARTMENT SIZE

FOR 12" SPEAKER

23" HIGH 15" WIDE

12" DEEP Stock No. JBR-221512

LOW COST HIF CONSOLE SPEAKER BAFFLES

> FULL SIZE FOR \$3495 12" OR 15" SPEAKER

DILED WALNUT 30" HIGH 23" WIDE

Stock No. 12" DEEP BRSTAN-1215

ment size high Fartrity Speaker Saffre, Ideal Full ears sigh Fidelity Speaker Baffre, Ideal for use with any 12" speaker and if you order a speak with any 13" or 12" speaker, Cut for 18" and shipped with a 12" reduced board, Take \$2.00 of 10 to Baffre piece. We see 12" reduced board, Take \$2.00 of 10 then you will be a 12" reduced board. Take \$2.00 of 10 then you will be a renderd oil Innian. The base reflex the waith of the see 12" of 10 the 10 then you will be a standard oiled Walnut Innian have most any speaker you have sound better. To 30" 32" is 12" innealising plus the base reflex the see 10 the 10

### 61/2 INCH FULL RANGE SPEAKER

THE BEST 20 oz.

PRICED BELOW MANUFACTURERS COST

STOCK XS-6171

20 OZ. CERAMIC 1" 8 OHM VOICE COIL 50 TO 15,000 CPS

8 OHM NEW 1972 VOL-U-SOUND

LL RANGE 12 IN. INCH HI-FI SA 95 25 WATTS SPEAKER 2 For \$13.00


Stock VOL-U-SOUND 12/20 1" 8 OHM VOICE COIL 25 to 17,500 CPS. 20 of CERAMIC MAGNET STEREO

HI FREQUENCY WHIZZER CONE LONG TRAVEL MOLDED CONE MOULDED POLLY-FOAM ROLL EDGE CONE

IDEAL FOR PUBLIC ADDRESS WORK This new |2" Full Range Speaker is fine for upgrading small hi-fi systems, Has new | piece cone with polly-foamedge for full base response. Full 1", 8 ohm voice coil and 20 oz. ceramic magnet. Is rated at 25 to 30 watts music power, This speaker is also ideal for Public Address work. VOL-U-SOUND 12/20, Full Range 12" Speaker, \$6,95, Two for \$13.00 2-WAY

SPEAKER SYSTEM

TWO for \$29.00 70 to 17,500 cps.



8 WOOFER 31/2TWEETER

Mounts Flat against Wall

may be stood one end or on shelf. OILED WALNUT BAFFLE

TWO FINE SPEAKERS ARE IN THIS ALL PURPOSE SPEAKER SYSTEM AN 8 IN. C.T.S. 10 OZ. MAG. ROLL EDGE WOOFER WITH HIGH COMPLIANCE. PLUS A 3 1 IN. TWEETER. VERY GOOD FOR HOME AND DUSINESS MUSIC. EXTENDS FROM THE WALL OR SHELL LESS THAN 4 INCHES, VERY NEAT IN LOOKS MADE OF SPECIAL HIGH DENSITY WOOD PARTICLE.

WALNUT VINYL COVERED BOOKSHELF SPEAKER SYSTEM.



STOCK NO ECA-8

PRICE

**S** 2 95

2 FOR \$11.50

POPULAR 8 inch FULL RANGE large magnet and 8 ahm voice coil FULL RANGE SPEAKER

Size; 10" High, 13" Long, 5\%" Deep. Matching Impedance is 8 ohms.

Shipping weight 7 lbs.

This is a Speaker system that is designed to use where economy and sound quality is a factor. It will improve any small Music system having small speakers. The baffle is made of 5/8" partical board and covered with a Walnut Vinyl cover. The grille front, is covered with gold and brown cain grille cloth. The system will handle the power of any of the small music amplifiers.

McGEE HAS MANY MORE GREAT BARGAIN SPEAKER SYSTEMS.

### HIGH FIDELITY SPEAKER SYSTEMS IN WALL CABINETS

10" WOOFER 2-3X5" MID-RANGE Plus 3" TWEETER



Front View

MCGEL MODEL LR-10353 SALE PRICE 95

MATCHED PAIR FOR STEREO \$23,50



Bock View

Model LR-10353. Full range 4 speaker system for wall mounting. Features a 16" x 12" x 6½" sloping to 4½" all wood wall baffle with simulated Walnut Vinyl covering. Full cane style grill front, Features a 10" Woofer, Two 3x5" midrange speakers and a 3" tweeter, Capacitor coupled midrange and tweeter. Only 2 wires to connect to the 8 ohm impedance tap of your ampelifier, Good Musical and voice response. Ship. Wt. 8 Ibs. Sale Price \$11.95, 2 for.......\$23.50

9 X 15" WOOF ER 2-3X5 MID-RANGE Plus 3" TWEETER



Front View

MODEL DLR-15253

MCGEL SALE PRICE




**Back View** 

Model DLR-15253, Deluxe full range 4- speaker system for wall mounting. Features a 164." x 13 x 7½." sloping to 5", all wood baffle with a simulated Walnut Vinyl covering. Full came style grill front. Features an RCA 9x15" woofer, Two 3x5" Miderange speakers and a 3" tweeter. Capacitor coupled mid-range and tweeter speakers. Only 2 wires to connect to your 8 ohm impedance tap on your Hi-Fi amplifier. A very good Hi-Fi wali speaker system at a low budget price. Ship. Wt. 101bs. McGee Sale Price \$13.95. 2 for. \$27.50

4-61/2"WOOFERS, 2-3X5 MID-RANGE 1-5" TWEETER

A NEW HOT 3-WAY HI-COMPLIANCE SYSTEM



MODEL DS-46-3x5-5 Weight 20 lbs

MCGFF SALE PRICE •

MATCHED

PAIR FOR STEREO \$38.00

Back View

Size: 18" long, 14" high and 6" deep

This is really a fine wall or desk system. Has four CTS, 61/3" Roll edge woofers, two true mid-range 3X5 speakers and one 5" tweeter. The frequence-response is equal to many of the higher priced units. 30 to 17,500 cps.

Because of the high compliance speakers used in this system, it should not be used on any Amplifier having less THAN 10 WATTS POWER

### 8" HI-FISPEAKER SYSTEM



SALE PRICE 195 2 for \$19,00

8" WOOFER 3X5 TWEETER & **MID-RANGE** FINE TONE QUALITY

Deluxe decorator styled hi-fi wall speaker system available in viny! walnut or blond covering Matching grill cloth front. Has a heavy duty 8" wide range PM speaker with 10 oz. magnet and condenser coupled 3X5 tweeter mid-range speaker. Response 50 to 17,500 cps. Ship. Wt. 7 lbs. Size: 121/1' high, 12' wide, 51/1' at top to 3' at bottom.

BCWS-83, Blond finish WFWS-83, Walnut finish

Price \$9.95 ea., 2 for \$19.00

NEW 1970 SHELF SPEAKER WITH FAMOUS NORELCO 5200M 12" SPEAKER




Size: 14"H x 19"W x 61/2"D---Ship. Wt. 15 lbs.

4 SPEAKER WALL SYSTEM Front View

HI-FI FOR ONLY 7795

2 FOR \$45.00





21" Lang - 17" Tall - 6"Deep Stanting to 4"

### ALMOST CONSOLE TONE FROM THIS SUPER WALL BAFFLE

4 speakers accoustically matched to give hi-fidelity audio response. 21'long, 17'' tall, 6'' slanting to 4''. Easily mounted on the wall. Made of heavy plywood and are finished in walnut vinyl covering. Response from 30 to 17,500 cps at 25 music watts. Features a 1 lb. Alnico V Magnet woofer, Two 5'' miderangespeakers and a 5''tweeter. Capacitor crossover network. Terminal impedance 8 ohms. Shipping Weight 20 lbs Stock No. Hi-Fi-15-3X5-WB, McGee Sale Price \$22.95 each. Two for \$45.00

### FOUR SPEAKER SYSTEM with 12", JENSEN WOOFER

12" JENSEN WOOFER Two 3X 5 MID-RANGE One 3%" TWEETER



Stock No. JN12-353WW BIGGEST VALUE IN A WALL SPEAKER SYSTEM

Here is a real fine speaker system using our new 12" JENSEN Waafer. This system is designed for those who want the best in bass response in small space. This 4-way really goes all out. Baffle is heavy plywood with walnut vinyl finish, nice enough for any Response 28 to 15,000 cps. Size: 19" L. 14" H & 5" slanting to 3" Ship Wt. 151bs

Not mailable, use UPS, REA, EFD, or Trucking Co.

### NEW 15" HI-FI AND PA SPEAKER

that will me et most af your HI+FI, P.A. needs CTS-15 in. 10 oz., 8 ohm, 1" Voice coil.



ideal for use with any high fidelity audio amplifier where you want very good all around audio response, plus exceptionally good bass response, Features a 1º, 8 ohm, voice coil, one piece mold ed cone and a 10 oz. Ceramic magnet. Rated at 18 watts from 38 to 10,000 cps. Shipping wt. 7 lbs.

STOCK NO. 15-584015X PRICE \$6.95

### 15" WALL SPEAKER BAFFLE WALNUT, vinyl covering with motching front grill, HEAVY WOOD

CONSTRUCTION SIZE; 17X18X8

Stock No. WB-15

Price

Shipping Wt. 12 lb

Conbination of one 15-584015X Speaker and one WB-15 Boffle. Stock No. WB-584015 Price \$12.40 2 \$24.00

BEST BUY YET, in 8" PM SPEAKERS for back ground music Installations. Where you need good musical respondentian and need lots of speakers, Here is a real buy , 1.47 oz mog. and 8 ohm VC. Rated at 5 watts

Stock No. 8-584210X \$219 Price: \$2.19., 2/4.10

10 for \$19.95

Here is a good speaker, for use in multi speaker installations. Use in parallel or series to match 4 and 8 ohm line or with 70.7 v. line transformers. 8" speaker, 2.15 knob mag., 4 ahm VC. Rated 5 watts. Shipping Wt. 2 lbs. \$ -

Stock No. 8-6308N

Pricet \$2.19., 2 for \$4.10 10 for \$19.95

BIG MUSIC OPERATORS SPECIAL NEW MODEL MU-085

BORTELE THE MAGNETSOTHERS OFFER! 3.16 oz. Alnico 5 mag.

8 ohm. 1" VC. Shipping
Wt. 2/4 lbs.
Price \$ 2 7 9 10 For \$26.00
100 For \$250.00
Work Wo. 1 MU-085 Transfermer Mountings
10 for \$28.00 400 for \$250.00, A good But of race the price!

### NEW 12" HI-FI&PA

GENERAL PURPOSE SPEAKER

Ideal for HI-FI, Public address and background sound systems.

12", 10 oz. Ceromic mog. 8 ohm, 1" VC.



This speaker is our beat offering of 12"

P.A. and general purpose use, Due to the latest type of construction and flat 10 o.z., ceramic magnet, the speaker is only 4½" deep. Holes to mount line transformers are in the frame This 12", 10 o.2 ohn speaker should thi all of your needs. Shipping wt. 5 ib.

STOCK NO. SKO-100X PRICE\$5.95

12" WALL SPEAKER BAFFLE WALNUT vinyl covering over heavy

wood construction with natching Plostic grill cloth.

SIZE: 13 X 13 X 7 Sloping to 4/4"

> Stock No. 9572

> > Price

Shipping Wt. 6 lbs.

Combination of one SKO-100 speaker and one 9572 wall baffle

Stock No. SKO-WB Price \$8.50 2/17.00

8" WALL SPEAKER BAFFLE

WALNUT vinyl covering over good wood construction, with matching grill cloth.

SIZE; 91/4 X 91/4 X 41/4 Sloping to 31/4"

Stock No. B9570 Price

Shipping weight, 4 lbs.

### NEW " A REAL LUCKY BUY"

only 200 to sell,

12" Fully ENCLOSED CORNER BAFFLE & good 12", 10 az.,8 ohm SPEAKER. Brown vinyl covered.

Stock No. SFB-C12

Price \$995

Ship. Wt.

Size: 14¼11 wide, 15¼11 wide and only 7¾11 deep 11 lbs.



NEW 10" HI-FI AND



Model No., 19-350X Another MeGEE scoop, on an extra well built 10", 10 watt all purpose P M speaker with 1" dia., 8 ohm voice coil Fine for all Audio use. Shipping WT, 5 lbs STOCK NO. 10-350X PRICE \$3.95

10" WALL SPEAKER BAFFLE WALNUT vinyl covering over heavy wood construction, with motching plostic

SIZE: 12 X 12 X 6 Slanting to 4"

> Stock Na. B-9571

> > Price

Shipping Wt. 4 lb

Combination of one 10-350X speaker and one B-9571 baffle

Stock No. 95-10-350. Price \$5.85, 2/\$11.50

12" ECONOMY BAFFLE WITH GOOD QUALITY 12" SPEAKER

Stock No. PCB-12 \$ 595 PAINTED 3/8" Plywood construction

Can be spray painted any color desired



15½" W x 13½"H x 8"D Tapering to 6" Deep. GENERAL PURPOSE SPEAKER

PUBLIC ADDRESS, PAGING & MUSIC

This is a real good buy in a 12 inch speoker combo. The boffle is splatter finish (Buff), Makes o good surface far painting any calar you wish. Has a 12" Oxfard speaker with 5 oz Alnico V &1" VC. Good far about 10 watts.

Stock No. PCB-12

Shipping Weight 8 lbs.





# BAFFLES AND QUAM HEAVY DUTY 8"

FAST BECOMING THE MOST POPULAR WALL BAFFLES USED BY MUSIC OPERATORS IN U.S. DO NOT CONFUSE THESE HIGH QUALITY ITEMS WITH INEXPENSIVE SPEAKERS AND BAFFLES SOLD BY OTHERS

**8**" WALL BAFFLE

OUAM 8 INCH SPEAKER

DELUXE 8" WALL BAFFLE



AND 8 INCH SPEAKER QUAM

2 for \$11.75 10 for \$55.00

10-1/8" × 10-1/8" × 4"

Stock No. CC8SS 5/8" 5 Ply Construction WALNUT WOOD GRAINED VINYL (Cloth Backed) COVERED Attractive matching Grill Cloth

Shipping Weight 5½ lbs. Stock No. CC8-570V, Speaker & Baffle with 5 watt 70 volt line trans & control... \$7 9



Response 50 to 12,000 CPS

AND 8 INCH SPEAKER QUAM

2 for \$13.50 10 for \$65.00

Stock No DCC8SS 5/8" 5 Ply Construction

WALNUT WOOD GRAINED VINYL (Cloth Backed COVERED Attractive matching Grill Cloth Shipping Weight 6 lbs.

Stock No. DCC570V, Speaker & Boffle with 5 watt 70 volt line trans & control..\$8.95

Beat 8" speaker yet, has massive 1" voice coil with 10 Oz. Ceramic Magnet, giving it efficiency equal to much larger magnet. This speaker will handle 15 watts power, insuring you many years of service without replacement. This speaker is used in both baffle models.

### **NEW TWIN 6" WALL SPEAKER SYSTEM**

2-SPEAKERS GIVE BETTER SOUND DISTRIBUTION

WALNUT VINYL COVERED 5/8" PLYWOOD CONSTRUCTION

2-6" SPEAKERS 2.15 Uz. Magnet... 8 Ohm Vaice Cail

Stock No. \$5.95 2 FOR \$10.50

Reor View

Shin, Wt.

Ship. Wt. 7 lbs.

Stock No., Twin 6215, New Wall Speaker System with Twin 6' speakers, 2 15 oz. Alnico V magnet, 8 ohm voice coil. In Walnut Vinyl covered Baffle with removable grill front. S5 95, Two for \$10.50

### **NEW TWIN 4×8"** WALL SPEAKER SYSTEM

2-SPEAKERS GIVE BETTER SOUND DISTRIBUTION WALNUT VINYL COVERED 5/8" PLYWOOD CONSTRUCTION

2-4×8" SPEAKERS

5 Oz. Magnet... 8 Ohm Vaice Cail

Stock No. \$5.95 \$10.50 Twin 485

Ship. Wt. g 1bs.

Rear View

14" W x 10" H x 4" D

Stock No., Twin 485, New Wall Speaker System with Twin 4x8" speakers, 5 oz. Ceramic magnet, 8 ohm voice coil. In Walnut Vinyl covered baffle with removable grill front, Two speakers give much better sound distribution. \$5.95, Two for...\$10 50.

### SPEAKER & BAFFLE



Rear View

McGEE HOT BUY! WALNUT VINYL COVERED 5/8" PLYWOOD CONSTRUCTION

CTS 10" SPEAKER

3 oz. Alnico V Magnet...8 ohm, 1" VC 2 FOR

Stock No. \$10.50 CA\$1035

8 1bs.

14" W x 12" H x 41/2" D

Stock No. CAS1035, New 10" CTS speaker & New Baffle. Speaker has 3 oz. Alnico V magnet and 8 ohm 1" voice coil. In Walnut vinyl covered baffle with removable mont grill. \$5.95, Two for \$10.50

### SPEAKER & BAFFLE





Ship, Wt. 10 1bs.

A McGEE HOT BUY! WALNUT VINYL COVERED 5/8" PLYWOOD CONSTRUCTION

OXFORD 12" SPEAKER

4 oz. Alnico V Magnet...8 ohm, 1" VC

2 FOR Stock No. \$7.95 CAS134 \$15.00

Stock No. CAS134, New Oxford 12" Speaker and Baffle, This Full Range speaker with 4 oz. Alnico V magnet & 8 ohm 1" voice coli ideal for Public Address & Paging. in Walnut vinyl covered baffle with removable grill front, \$7.95, Two for \$15.00

DELUXE 8" SLANTING WALL BAFFLE and 8" QUAM SPEAKER... Same construction as the DCC8SS shown above. Size, 14" long 11" high and 5" wide at the top and sloping to 4" at the bottom. at the bottom.



STOCK NO. SLDC85

SHIPPING WEIGHT 7 LB. 10 FOR \$65.00

Stock No. SLD570V, Speaker & Baffle with 5 watt 70 volt line trans. & control...\$8.95

MUSIC OPERATORS SPECIAL FULL RANGE Stock No.



U.S.

2

10 for 100 for \$37.50 \$350.00

Music Operator Special Stock No. 8C10-PAX MAGNET 10 oz POWER HANDLING (Watts): 15 8 Ohm VOICE COIL IMP. voice coil diameter of 1 inch.

Transformer Mounting Holes:

Minimum 2 In-Maximum 23/4 In-NET WEIGHT: 21/2 lbs.

# BEST BUYS SPEAKER-BAFFLE COMBINATIONS U.S.A. FOR WALL MOUNTING, FEATURING

FINISHED HARDWOOD AND WALNUT GRAINED VINYL COVERED WOOD BAFFLES AND SPEAKERS

NEW TREND BAFFLE with 7" CLETRON
SAME CONE AREA AS 8" SPEAKERS



FRONT VIEW

3.16 oz. SPEAKER Magnet TRS-77

SLIM LINE BAFFLE

BIGGEST BAFFLE AND SPEAKER VALUE

EVER OFFERED

8" CLETRON with Aluminum Voice Coil 10%" TALL, 9%" WIDE, 4%" TAPERING TO 2%" Model- TRS-77-870V.

SAME AS ABOVE EXCEPT



REAR

### WITH 70 VOLT LINE TRANSFORMER AND VOLUME CONTROL

The best value in a combination speaker and baffle. The fine quality speaker is made in U.S.A. The baffle is made of wood veneer, with grained vinyl WALNUT covering. Grill front is govered with good quality plastic grill cloth.

The speaker has a 3.16 oz. Almico V Magnet. The voice coil is 8 ohm and %'' in diameter for longer life. This is a better quality speaker than used in ordinary systems. Some 8'' speakers offered by others has smaller voice coils, down to 9/16''. A McGee Special Purchase Value!

MODELTRS\_77 Speaker & Boffle only,

54.99

MODEL TRS-77-870V Speaker & Baffle with

\$6.99 70 V. Trons. & Control

NEW DELUXE WIDE BAFFLE WITH NORELCO FULL RANGE 8"

NEW 1972 TREND BAFFLE

BEAUTIFUL

SPEAKER

STOCK NO. TNOR\_8

WALNUT VINYL COVERED BAFFLE

SPEAKER

10 FOR \$57.50 11,3/8" WIDE, 914" HIGH, 4-1/8" TAPERING TO 2%"

STOCK NO. **TNOR -870V** Same as obove EXCEPT

WITH 70 VOLT LINE TRANSFORMER AND VOLUME CONTROL

10 FOR \$77.50

This new wide 3" Baffle with 3" Norelco Full Range speaker is a very fine wall unit for so low a price. The speaker has a 5-oz. Ceramic magnet. The Norelco speakers are remarkable in that they seldom have voice coil trouble. Over all tone quality of this speaker is as good as some much higher priced units. Speakers are 3 ohm.

Model TNOR-8 Speaker & Boffle only..... \$5.95

Model TNOR-870V, Speaker & Boffle with

70 V Trons. & Control......\$7.95

### NEW MODELS "SUPERFINE" CTS SPEAKER SPEAKER IN



WALNUT VINYL COVERED BAFFLE

6.8 oz. Alnico 'V Magnet 1½ Inch VOICE COIL

5/8" Plywood Construction BAFFLE

15 WATT DEEP CONE

Stock No. **WONG-12** 

13" X 13" X 7¾" D Tapering to 4-3/8"

SPEAKER & BAFFLE \$7

Ship. Wt. 14 lbs.

ONLY

New Superfine 12" CT5 Speaker and Hollywood Baffle. Size: 13" H x 13" W x 7½" D, tapering to 4-3/8". Wolnut vinyl covered. CTS wide range speaker, 8 ohm 1½" voice coil and 6.8 oz., Alnico 'V' magnet. Response 35 to 15,000 cps, up to 10 wotts. This is a better quality speaker than used in ordinary systems. Offered as speaker & baffle only, or with 10 watt 70 voit line transformer & volume control mounted in baffle. Specify the type you desire by stock number. Stock NoWONG-12 Speaker & Baffle only, \$12.95 2 for \$25.50

Stock No. WONG-1270V Speaker & Baffle with 10 watt, 70 volt line transformer & volume control...... \$15,50, 2 for \$30,50

### SPEAKER SYSTEMS DELUXE 12" CLETRON

MHO 8

13" x 13" x 71/4"D

Tapering to 4-3/8"

WALNUT VINYL COVERED

BAFFLE 6.8 OZ ALNICO Mognet 1" Aluminum

VOICE COIL 5/8" Plywood construction

BAFFLE Stock No.

CAS12CLE SPEAKER & BAFFLE ONLY

2 For \$19.00

Ship. Wt. 10 lbs. This new 12" Hollywood Speaker and Baffle is one of our best buys.

Vinyl covered 12" Baffle with 12" Cletron, 6.8 az. Alnico V magnet. A speaker especially made for public address work, good for up to 30 watts. Hos Heavy 1" Aluminum voice coil. Baffle size:

13" H x 13" W x 7\%" D topering to 4-3/8", wainut vinyl covered.

Offered as a speaker and Baffle only or with our 10 watt 70 volt line transformer and a volume control mounted in the baffle, specify.

Stock No. CAS12CLE, Speaker and Baffle only......\$9.95

# MODELS 8" HOLLYWOOD WALL BAFFLE SPEAKER SYSTEMS

WITH GENUINE TREND BAFFLES CTS SPEAKERS

SAVE MONEY AND TIME - SPEAKERS ARE INSTALLED READY TO USE WOOD BAFFLES WITH FULL DECORATOR GRILL

DELUXE 8 10 OZ. CERAMIC SPEAKER

IN PRE-FINISHED
TREND SLANTING
BAFFLE

TREND TD-8

\$745

FULL RANGE RESPONSE

THINLINE DESIGN
WALNUT VINYL FINISH

2 for \$14.40 10 for \$70.00

New Thinline TREND Deluxe wall baffle for background music systems. Features Vinyl pre-finished WALNUT color all wood baffle with full decorator cloth covered front. Baffle is only 71-3/8" wide, 9\%" high and 4-1/8" tapers to 3\%" sides. The speaker is the latest 10 oz., Ceramic magnet, 1" diameter, 8 ohm voice coil. Made by CTS, Response from 40 to 1,2000 cps, Maximum power is 10 watts.. Shapping wt, 5 lbs.

TREND TD-8, CTS Speaker and TREND baffle, 57,45 ea, 2 for \$14.40

BIG 1971 SALE OF A 10" SPEAKER & BAFFLE FOR THE PRICE OF A 8" SPEAKER AND BAFFLE



Upgrade all your sound installations with 10" speakers and baffles. The baffles are made of wood, and covered with vinyl plastic covering. The speakers are made bu CTS. 10". 3.16 oz. 8 ohm, voice coil. The baffle size: 11½" X 11½" X 6" slanting to 4".

Shipping Wt.6 lbs. Stock No. 95-10-350 \$5,85 ea., 2 for \$11.50

ARGOS CARRYING CASE



CARRYING CASE

\$28.95 McGEE Net.

PORTABLE
CARRYING CASE
WITH TWO 12" SPEAKERS

Stock No. \$39.95 SC-2510

IDEAL FOR USE WITH WRS-35A WRS-60A WRS-100A IMPERIAL AMPLIFIERS

Stock No. SC-2S10, Portable Speaker Case with two 12", 10 Oz. Ceramic magnet speakers, plus 25 feet of speaker wire per speaker. Connecting plugs for any of above Amplifiers, Shpg. Wt. 29 lb.

STOCK NO. SC-2810..... \$39.95



Stock No.

DELUXE 8
5 OZ. CERAMIC
SPEAKER
IN PRE-FINISHED

\$645

TREND SLANTING WALL

TREND-WT-8

2 for \$12.40

FULL RANGE RESPONSE 10 FOR \$60.00

ALL WOOD CONSTRUCTION, A HOT VINYL FINISH

New Deluxe 8" Hollywood type TREAD wall baffle and a genuine CTS. 8" high efficiency 5 oz. ceramic PM with 1", 8 ohm voice coil, speaker installed in the high quality, all wood, vinv! walnut finished baffle. 1 1-3/8" wide X 9\%" long. Sloping sides, 4-1/8" to 2\%". Rated at 7 watts power, Frequency response is 40 to 12,000 cps.

TREND-WT-8. CTS speaker & TREND baffle, \$6.45 ea., 2 for\$ 12.50

# BIG McGEE Special



1000 TO SELL!

SPEAKER SA 99

> 2 for \$9.80 10 FOR \$48.00

7" Alnico V SPEAKER 1" V.C. 3 Oz. Mag.

# PORTABLE CASE FOR TWO 12" SPEAKERS WITH SPACE FOR YOUR P.A. AMPLIFIER



New smaller size portable case 19½ x 16 x 13¾" outside dimensions.
18¾ x 14½ x 13" inslde dimensions.
Cut for 2-12' speakers. Handsome leatherette covered plywood body.
RX-125, Net Price............\$16.95
Shipping Weight 15 Pounds.

Standard size portable case 22" H., 17" W., and 13" D. Cut for 2-12" speakers. Space inside for most amp lifters. PSD-12, Net Price... \$23.95 Shipping Weight 17 lbs.

SPEAKER CASE ALONE

\$16.95

PSD-12. Portable case and two heavy duty 12 inch 10 oz. Alnico V magnet, 8 ohm, 1½ inch voice coll speakers. (our CTS 12DT 10) and 25 feet of speaker wire strached and installed in case. Sppg. Wt. 28 lbs.

Stock No. PSD-12DT 10. Net Price...... \$38.95


### SOUND ENGINEERED GRILLS McGEE'S BEST VALUE

### INDUSTRIAL SOUND GRILLS



Stock No. 104-8A, 12/2" Brushed Aluminum Grill with speaker mounting bolts for any 8" speaker. 104-8A, Brushed Aluminum Grill Saie price \$1.69 104-8W, Painted White Sale price \$1.69 \$1.60 in lots of 4, Package of 2) for \$30.00

Stock No. RSS-8A. 12%' diameter spun Aluminum Grill made for any 8' speaker. Mounts flush to ceiling or watt. Brushed Aluminum finish. Net price \$2.99 ea., 4 for \$10.75, 25 for \$6.2.50



Stock No. TM-8AA, attractive brushed aluminum ceiling baffle. 12" square for any 8" speaker. 9/16" flange is turned under to replace any 12" accountical tile and make the baffle flush with ceiling. Fine satin aluminum finish. NET, \$3.40 each, 4 lot, \$3.10 each, 25 lots, \$2.80 each

Stock No. FLAT-13, an all aluminum flat 13" sq. grill for any 8" speaker. Mounts flat against any ceiling or ceiling tile. Not intended to replace an accoustical tile block, but to mount on top of it. NET, \$3.30 each, 41ot, \$3,00 ea. 25 lot \$2.80 ea.



RECESSED METAL BAFFLE.

CW.8

EACH

### NEW METAL LOUD SPEAKER BAFFLE

For any 8" speaker SIZE: 101/2" X 101/2" square raised 5-16" Stock No.

\$189 NBH-8

Model NBH-8 The essence of modern styling, simplicity, clean lines, completely functional design-this resessed baffle will blend into any surrounding. Rugged and compact, yet versatile, with an 8" speaker capacity-big enough to fill any commercial intercom or background sound need, Moreover, it has a strong metal protective screen covering the speaker opening, rounded contents and wide beveled edges. The baffle is constructed of 18 guage steel with a WHITE baked enamel finish. Size: 10½" X 10½" square

ALL WHITE PLASTIC CEILING BAFFLE & MOUNTING RING





Stock No. FJM-BW GRILL AND MOUNTING TO MINUTES INSTALLATION TIME IN HIGH-LAPACE WHIEE PLASTIC - 12'1" DIAMETER 4- SPEED NUTS-HELD IN PLACE... NO PUMBLING 3 49 NET

### ROUND SURFACE MOUNT ALUMINUM BAFFLE

DEEP

Easy to Install ! No Holes to Cut ! Model LCS8-MG





### BEAUTIFUL BRUSHED ALUMINUM FINISH

### ACCOUSTICALLY LINED BAFFLE

ACCOUSTICALLY LINED 3AFFLE LCS8-MG, 4" deep, Round Surface mounted ceiling beffle with brushed satin aluminum finish. Will house any standard 8" speaker, Features case of installation. Speaker is mounted on accoustically lined perforated fine mesh metal grill. Fasten the steel back plate to ceiling with a screwa or direct to 4"x4" electrical outlet box. Baffle fastens to back plate with 4 metal screws. Ready to connect.

### BRUSHED ALUMINUM CEILING BAFFLE RECESSED CEILING SPEAKER BAFFLE



For any 8" Speaker 10 FOR \$57.50

360° Sound Dispersion for perfect coverage in any location. Constructed of rugged 18 ga. aluminum in buffed satin finish with clear lacquer protection.

BAFFLE FOR Normal Collings FLUSH MOUNT CEILING BAFFLE 1225 NET



surface Mount Baffle ha getting, tade

BAFFLE for YERY LOW CEILINGS



11 63 mounting Model SYL8-A

No. XPC-84 BACK COVER For all LOWELL baffles 380 2 for \$7.00 4 for \$13,00

### LOW CEILING RECESSED BAFFLE

BRUSHED 8" SPEAKER BAFFLE 649

SOUNDOLIER MODEL 68-8 RECESSED BAFFLE Soundoller Model &-d. Attractive Receased Battle for low ceiting. Brusherd Alammun time ring feedinging a superior of the ceiting and the superior of beautiful and the company of the ceiting a superior of beautiful and the ceiting and the

soundoller VALUE



NET

SAVE ON BACK BOXES 2 FOR 4 FOR \$7.00 \$13.00 EACH MADE OF HEAVY STEEL

ACCOUSTICALLY LINED

### 8" PLASTIC SPEAKER GRILL

For Industrial sound systems

FLAT CEILING GRILLS For 8" Speakers Surface mounted- no plaster rings needed



Model LS-8W

No. LS-8w, latest white styron, 124" diameter round grill for use with any 8" speaker, may be painted to match the celling if desired. Stock No. LS-8w, \$1,49 ca. 2 for fi2.90. 10 for \$13,90



Model CR-80P

No.CR-80P, latest 10" iquare white plastic grill supplied with 4 screws to mount any speaker. Ma be painted to match ceiling if desired. CR-80P CR-80P, \$3. 19 each, 10 for \$30.00



Model ADS-80P

339

No. ADS-80P, latest 10" square white plastic grill supplied with screws to mount any 8" speece. Beautiful white finish. Concentric spirals designed to add beauty and comouliage speaker. ADS-80P, \$3.39 each, 10 for \$32.50 10 for \$32.50

### soundolier

PLASTIC BAFFLES

FOR MOUNTING 8" SPEAKERS With mounting bolts & screws
EASY TO INSTALL

High Impact Polystyrene. No Rust Recessed Trim Ring. Can Be Painted, Speaker is Completely Hidden, Speaker Screws do not snow.

Model P-900 (round)

123/4" diam.

\$1.19 Eoch





Model P-910 (small square) 101/2" x 101/2" Eoch

Model P-912 (large square)

121/2" x 121/2"

§1.29





### DRIVERS, TRUMPETS AND ACCESSORIES Paging/Talk-Back Speakers



	IB-A/MIL-A		18-T/MIL	T	UH/UHT				DECT
MODEL	FREQUENCY	POWER RATING (1)	IMPEDANCE (VOICE CDIL)	DISPERSION	SOUND PRESSURE LEVEL (8)	SENSITIVITY AS MICRO (7)	DIMENSIONS (S)	SHIPPING WEIGHT	NET PRICE
DLC-0	400-10,000 Hz	71/2 w.	5 ohms	1200	104 dB	-30 DBM	5%" dia, x 4" d. (A)	134 lbs.	13.82
DLC-7	1400-10,000 141	773 07.	8 ohms (2)	ALU	104 00	-30 DBM	5%" dia. x 6%" d (A)	243 lbs.	22.37
UH-45 UH-45 UNY	220-16,000 Hz	32 W	8 ohms 45 ohms 8 ohms (3)	120° (91	126 dB	-26 DBM	10½" dia_ x 10%" d. (P) (10)	5 lbs. 5 lbs. 5% lbs.	29.13 30.42 40.10
18-A4 18-A8 18-A45	250-13,000 Hz	30 w.	4 ohms 8 ohms 45 ohms	1050	126 dB	20 DBM	1014" dlm. # 9" d. (A)	41/2 lbs.	28.20 26.40 28.20
18-T			8 onms (4)				101/4" dig. x 11 7/15" d. (A)	SNA IDE.	35.36
CIB-A4 CIB-A5 CIB-A45	250-13,000 Hz	30 w.	4 ohms 8 ohms 45 ohms	120°×60°	126 dB	-22 D8M	14" w. x 7%" h. x 12" d. (A)	6 103.	33.05 32.05 33.05
CIO-Y			8 ohms (4)				14" w. x 74s" h. x 1492" d. (P)	644 1bs.	42.59
MIL-AI MIL-AI	350-13,000 Hz	10 w.	4 ohms 5 ohms 45 ohms	120°	119 dB	-23 DBM	7 13/16" die. 1 6% d. (A)	31/4 10ts.	23.35 21.80 23.35
MILT			B ohms (S)				7 13/16" dia. x 9 13/16" d. (A)	4 lbs.	31.55
CMIL-A4 CMIL-A8 CMIL-A43	350-13,000 Hz	10 w.	4 ohms 8 ohms 45 ohms	120°x60°	119 d8	-26 D8M	91/2" w. # 616" h. # 81/2" d. (P)	4 lbs.	26.75 25,00 26,75
CMIL-T			8 ohms (S)				91/2" w. x 61/4" h. x 10 7/16" d. (P)	4% Ibs.	35.70

- 1) Capacity in watts IPM (Music Power).
- Voice call impedance 8 ohms. Integral transformer terminals are labeled in waitage consumed and impedance on 70.7 and 25 voit constant voltage lines. Taps: 7.5/5/2.5/1.25/.65 watts.
- Voice coil impedance 8 ohms. Integral switch selected transformer is labeled in wattage consumed and impedance on 70.7 and 25 V, "constant voltage" lines. Wattage taps: 32/15/10/5/-1.25 W, Transformer Impedances (70.7 V.): 161/335/500/1000/2000-hms.
- Voice coil impedance to hms. Integrat transformer terminals are labeled in wattage consumed and impedance on 70,7 and 25 v. "constant voltage" lines. Wattage Taps: 30/15/10/5/2.5/1.25 w. Transformer impedances: 167/135/500/1000/2000/4000 chms.
- Voice Coil impedance 6 ohms. Integral transformer terminals are labeled in wattings consumed and impedance on 70,7 and 25 v. "constant voltage" lines, Wattage Taps: 10/7,5/5/25/1.25/55 Transformer Impedances: 500/667/1000/2000/4000/6000 ohms.


SPL reading taken 4 ft. on axis with "Full-Renge" power input. Reduce by 6 dB each time distance is doubled. Reduce by 3 dB if power input is halved; increase by 3dB when power input ledoubled.

An (A) after a dimension indicates a horn of spun aluminum with baked-on acrylic paint. A (P) after a dimension indicates a horn of color-impregnated high-impact plastic.

10) Dimensions are without Sound Dellector. With Deflector, add 1/2 to diameter and 4-1/16" to length.

10-29

II-M WEATNER-PROOF BUAL-RANGE SYSTEMS



-				
Listiversity	Frequency	Prissure	D41-	W. A.D. a.M.
MLC	(50-18-000)  ta	11. do	1200	174, # 10, * # A)1,
GLC	SU-15 INN HA	Lis do	1504	22 % dis. x 12 % d

Model CLC Demanding budget epplications, 30 watts; 6 came impedance Shipping Weight 23 lbs... 23 lbs... Medel WeiC A Heavy Duly System, 50 watts, 5 chme impedance.

NET PRICES MODEL

MLC \$ 46.76 MODEL

CLC \$ 80.72 MODEL

WLC \$217.77

MOSEL 10-20 (28 watts) For apeech and music systems requiring moderate sound power, Designed to deliver maximum penetration in high douse areas Rugged, wishing the 10-20 (28 highly efficient, produces a clear, penetration and distortion-free sound.

MOSEL 10-30/10-307 (39 watts) Exceptional for inatallations requiring analy medium power units or multiple driver/horn combinations. These high quality drivers produce mustain balance and speech penetration with a performance superior for higher cost competitive modes in representation with a performance superior for the power is a compact combinations. These high quality drivers produce mustain balance and speech penetration with a performance superior to higher cost competitive modes in represented voice cost.

MODEL 10-30/10-307 (39 watts) Exceptional for installations requiring ainstend of the produce of the penetration of the produce mustain balance and speech penetration with a performance superior for produce mustain in high power is a compact combination. These high quality drivers produce mustain balance and speech penetration with a performance of 16/3835/.

MODEL 10-40A/10-40T(40 watts) Extend and according high noise areas.

MODEL 10-40A/10-40T(40 watts) Extend and according high noise areas.

MODEL 10-40A/10-40T(40 watts) Extend and extend and extended and extended

THE OF SET	sabtiourns with	B HOIRE PLAN	Maria			-
MODEL	RESPONSE	POWER	VOICE COIL IM- PEDANCE	DIMENSIONS (Overall)	SHIP. WT.	PRICE
ID-20	120-6500 Hz	20 watts	16 ohms	31/2" dia, 314" d.	242 lbs.	18.15
ID-30	85-7500 Hz	30 watts	16 ohms	41/6" dia. 374" d.	3 IDS.	23 05
ID-30T	85-7500 Hz	30 watts	variable*	41/6" dia. 6" d.	4 lbs.	33.50
ID-40A	80-12000 Hz	40 watts	16 ohms	41/2" die. 41/4" d.	41/a Ibs.	28,00
1D-40T	80-12000 Hz	40 watts	variable*	S" dia. 61/4" d.	544 lbs.	39 20
ID-60	70-12000 Hz	60 watts	16 ohms	4-11/16" dia. 5" d.	536 bs.	40 60
ID-60T	70-12000 Hz	60 watts	variable*	6¾" dia. 6¾" d.	634 lbs.	50.40
		75 watte	16 ohros	416" dia, 316" d.	S Ibs.	40.14



RLH, RPN, RSH

DIRECTIONAL MODELS CH, LM, PH, SMH For maximum noise penetrotion and distance of projected sound. Reflex design for highest conversion efficiency. Fully weatherproof, baked finish.

WIDE ANGLE COBREFLEX Parented twin folded exponential horns with two air columns in a single assembly. High efficienty and smooth radiation patterm. Can be used in Cluster arrays. Rugged, fully weatherproof.

WIDE ANGLE MODEL CLM Patented design and construction Wide angle bell and long air column for maximum low frequency response. Omnidirectional bracket for vertical and horizontal rotation to eliminate feedback and overshoot "dead apots". Can be used in cluster arrays. Rugged fiberglass horn.



HORN	CUT-OFF	DISTRI	COLUMNI LENGTH		BELL RBIONS	SHIP. WT.	Nat Price
GH	#5 Nz	659	6Vs IL	38"	32"	22 Ibs	65.85
LH	120 Hz	75"	evs IL	19"	2514"	161/2 (ba	42.30
PH	150 Hz	#\$P	34s H.	15%"	2019"	11% ibs	30.63
SMH	200 HE	951-	217 H.	12"	1616"	Bld Itrs	25.30
RLN	120 HZ	360°	S PL	1605"	285hi"	25 1D4.	64.97
RPH	140 Hz	3604	& FL	1370611	2510"	19 ibs.	45.20
ASH	180 Hz	3600	3 1%	11"	19"	13 lbs	43 32
COBRE-	200 HZ	120°×60°	29/2 fL	1044" 1	31/2"#914"	1014 IDS	31.73
CLH	120 Hz	120°±60°	45/g 12	2011 2:	"מווג"מו	134a ibs	37.50
SH	350 Hz	100°	11/2 ft.	7"	314"	24s Its.	28.25
ZWP	350 Hz	120° each	14½ ft.	2042"	E75	4Va Ibs	27.92



PMA adapter Fits standard % dis-shreaded pipe to any University "U" mount-ing bracket—for special applications requir-ing pipe mounting. Net \$3.12

RTA ADAPTER Fits University trumpets to Western Electric and RCA drivers having 1 7/16-16 threads. Shpg. ut. ½ th. Not 36 23

WEA ADAPTER Fits University drivers to Western Electric and RCA trumpets having 1 7/16-16 threads, Shpg wt. 16 h



Corner baffles with the clip-on front that hang as easily as a wall baffle

SPECIFY

Blend or Wolnut Vinyl

Stanting corner baffle

\$6.95 \$6.75 \$4.95 \$4.65 \$3.55 Contractors' top seller for years SPECIFY Regular corner baffle Bland or Walnut Vinyl

WB-120

AMPGOS

Regular

WALL BAFFLES

WB-98--Fer 6" speaker maximum speaker depth 4º12". Capacilly 400 cubic inches. Ship Wh. of teo. 8 lbs.

WB-6 x 90-Line WB-60 except for 6 + 9 inch speaker

WB-100-For 10" speaker maximum speaker depth 5%" Capacity 800 cubic victor 55-b Wr of two 10% los

WB-120—For 12" sceakes, maximum speaker depth 6%" Capacity 1180 cubic mohes Ship Wt of two 13% (bs.

SPECIFY: Bland or Walnut Vinyl



Regular and Deluxa Baifle Speaker Siza

REDUCING RING \$1.45





\$13.25

CB-129

### WALL BAFFLES in richly finished natural hardwood

hardware already limity fixed in place:

DW9-14. Takes 8" "speaker, maximum speaker depth 21g."

Internal capaciny 400 cubic inches Ship Wr of two 6 lbs.

Size 10" 8104" 85%" 56, 40

DW9-186.—Takes 12" speaker, maximum speaker depth 5½"

Internal capacity 1180 cubic inches. Ship Wr of two, 11 lbs.

Size 13%" x 14" 85%" 59,25

THINLINE WITH 8 INCH SPEAKER INSTALLED

"THINLINE" Slanting corner
speaker baffle combination ARGO5



2

"THINLINE" Stanting corner speaker baffle combination

Magitran Conquers Speaker Space



Model

10 for \$37.50

INCH Model designation: RF-8 Poly-Planat Power capability: 20 watts peak

Frequency range: 40 Hz-20 KHz Sensitivity: 90 dB/M for 1 wast electrical input Input Impedance: 8 ohms

100 for Operating temperature range: -20°F to † 178°F Size: Round 8" diameter, 1" depth

\$350.00 Weight: #1 oz.

NEW FLY WEIGHT SOUND COLUMN WITH 6 MODEL R P-8 SPEAKERS



McGee TREND Wall Baffles Best Quality-Value in U.S.A.

BEST QUALITY

Model 17-100 inch THIN LINE \$3.99 ea 10 for \$37.00

FITS MOST 8 IN.
CERAMIC MAGNET
SPEAKERS 11 4 3 3/4
4 SLOPING TO 2 1 DEEP
SHIP WT. 4 LBS. WAUNUT FIN



Model \$3.99 14-100 10 for 3 inch \$37.00

STANDARD FITS MOST & IN.
SPEAKERS, SLIGHTLY
DEEPER THAN BAFFLE
SHOWN ABOVE, 10;
9; 5; TAPLENING TO
3 7/8 IN. WALULT FIN.
SHIP WT. 4 LBS.



Model 16-100

THIN LINE

\$5.95 10 for \$55.00

TOP VALLE BAFFLE FOR USE WITH 12 IN. BEAKERS. 13 1 13 8 IN. TAPERING TO 6 IN FIRST MCGEE OFFER OF THIS QUALITY AT \$8 95 WALHUT FIN. SHIP WT.

POLY New PLANAR Concept in SUPER-THIN Super-Thin Speakers



Loud Speaker **Designs** 

MCGEE HAS SPEAKER FOR NEED.

FLY-WEIGHT SOUND COLUMN SUPER TH SC-RP-84

EQUIPPED WITH 4

POLY - PLANER SPEAKERS

JUST TOSS IT IN THE CAR OR MOUNT IT ON THE WALL. TWO OF THESE WILL HOLD DOWN 60 WATTS PEAK AUDIO. 10 X 35 1 X 2 5/8 DEEP. SHIP WT. 10 LBS. EQUIPPED WITH 4.R P-8 POLY PLANAR MAGITRAN

# SOUND COLUMN SPEAKER SYSTEMS McGEE

Consider that some other models are selling up to 5 times McGees price. We charge nothing to Engineer. You get the Full Value with no extras added. LATEST ENGINEERING - CONTROLLED FEED-BACK AND SOUND DISTRIBUTION - WALNUT GRAIN VINYL COVERED BAFFLES

1971 ECONOMY MODEL With 6 - 4" x 8" SPEAKERS

With 5 Oz. CERAMIC MAGNETS

BIG McGEE BARGAIN

Speakers alone ore worth more than our selling price of \$17,95

New Six- 4" x8" speakers with 5 oz. Ceramic magnets, "" dia, voice coils and large 2'y" spider for free movement of voice coil to produce better Basa res-

Stock No. \$1795 6-48-3 6-48-3

2 FOR \$35.00



NOT MAILABLE

Ship UP5 up to 49 lbs.

New ECONOMY 4-8" SO WATTS

SOUND COLUMN

4 CLETRON "Super 8" With 6 Oz. Mognets

8 OHM, 1" VOICE COILS

Stock No. MCGEE \$29.95 SC4CL E-86

COLUMN 48" TALL, 10" WIDE, 6" DEEP MADE OF HEAVY 5-PLY PLYWOOD WALNUT VINYL PLASTIC COVERED

Model SC4CLE-86, Quad 8" Sound Column speaker system. Walnut grain vinyl covered wood construction with full grill cloth covered front. 48" tall, 10" wide and 6" front to back. Complete with Four 8" Cletron speakers with 6 oz. Alnico V magnets and 1", 8 ohm voice coils. Ship. Weight 30 lbs. List Value 560.00. Response 35 to 13,500 CPS at 30 watts. Net....\$29.95

HEAVY DUTY 5" SPEAKERS ARE CHOICE ON MOST SOUND COLUMNS

> SPEAKER SOUND COLUMN \$100.00 LIST VALUE SALE PRICE \$3495

2 FOR \$69.00

Ship. Wt. 30 lbs.

HEAVY DUTY

5° Wolverhampton Eng-lish speakers with %° voice coils & 3 oz. of Al-nico 7, the worlds finest magnet. The Voice coils made in such a way to stand hardest of service. These are truly the wor-lds finest 5" PMs. Speakers alone are worth more than

we are pricing Columns.

Model

125C-12C5

FREQ. RESPONSE

WALNUT GRAIN VINYL

60 TO15,000 CPS

COVERED Model 125C-12C5

Model 128C-12C5. 12 speaker sound column. Walnut grain vinyl covered with full grill front. 68" long, 7" wide and 3%" deep. Weight 30 lbs., Rated up to 40 musical watts at from 60 to 15,000 cps. Ideal for Church systems, atudios etc. Anywhere you desire a good sound system. Equipped with 12-5" Ainico V. PM Speakers. Impedance 3 ohms. Out performs any PA speaker ever built. Model 128C-12C5.

Over 49 lbs by Truck

SPEAKER SOUND COLUMN TRUE HI-FIDELITY 11/2" Voice 8 OHM Coil 6.8 oz. Mag. 2 For

1495 Stock No. V 4-12

This 4 12 in. speaker sound column will handle 60 peak audio watts at from 40 to 12,500 cps. The column is of heavy wood construction and vinyl covered with a full grill cloth front. Accoustically designed and equipped with four 12 in. 6.8 oz. alnico V magnet speakers, 2 are full range and 2 have stiff cones for mid range. Full 11/4 in. voice coils.

\$85,00

Ship. Wt. 60 lbs 54" Long, 14" wide 5" deep.

S in SPEAKERS EIGHT SOUND COLUMN WITH NORELCO AD 5080 / M8 With 5 Oz. Ceramic




2 For 539.00 Stock No. SC-NOR5 Ship. Wt.

13 lbs.

Sound Column: 30" x 12" x 4" Sound Column: 30' x 12" x 4"
The Mini-Columns such as this Eight 5'
Norelco PMs are used widely in Europe.
Small cones in multiple, allows working
of mikes closer to speakers than larger
single units. These fine 5' full range
speakers have 5 oz. Ceramic magnets and
"vivoice coils. Good for full 20 watts.

4 HEAVY DUTY 12" 2 NEW 1971 SOUND COLUMNS USING NEW 5" & 61/2" **FULL RANGE SPEAKERS** 

TWELVE 61/2 in SPEAKERS SOUND COLUMN



With 5 oz. Ceramic Magnet SC-NOR12-6 4 4 95 2 FOR \$85.00 SOUND COLUMN


WALNUT VINYL COVERED

HEAVY 5 - PLY PLYWOOD

> Ship. Wt. 30 LBS.



This new Sound Column with 12 - 6" Norelco speakers gives better sound dispersion than single speakers, also far less feedback under same conditions. These full range speakers have heavy 3/4" voice coils & 5 oz. ceramic magnets. Good for a full 40 watts.....\$44.95





NEW " BIG CHIEF" SOUND COLUMN

SPEAKER Ship. Wr. **SYSTEMS** 

ОНМ

38 Lbs.

Stock No. BIG CHIEF 100

95 With 4 - CTS

SPEAKERS
1 Lb. Alnico V Mag.
2" 8 Ohm V.C

Matched Pair \$135.00

100 WAT1

PEAK **AUDIO** 

"BIG CHIEF" SOUND COLUMN 54" Long, 14" Wide, 61/2" Deep

Quenemo Big Chief, 100 watt sound column features four 10" C.T.S. Speakers with 1 lb, Alnico V Magnets and big 2" voice coils. Never before has McGee offered such a powerful speaker in a sound column. The baffle is made of all 3" wood covered with simulated wainut Vinyl. Full Grill cloth front. An excellent sound column even for portable use or mounting on walls. Two speakers will fill small auditoriums with directed sound. This speaker even makes a good sound column for portable use. Rated at 100 watts peak, however we recommend using two when you have a 110 watt audio amplifier. You should have speakers equal to twice the power of your amplifier to get good results and insure against speaker overload, Sale Price \$69.95 each, Matched Pair, \$135.00

# Shipping Weight 80 lbs.

8 OHM

"BIG BRAVE" 50 WATT HI-FI SOUND COLUMN

MUSIC & P.A.

Stock No. SC-HI-FI-SO

2 For \$100.00

1-12" WOOFER CTS 28 Oz. 8 - 4X8 MIDRANGE 2-5" TWEETERS

541/4" L, 14"W, 614" D Walnut Grained Vinyl Covered

Full %" Plywood construction Reinforced Corners

Very Attractive Full Grille Front matches brown enclosure and most any decor. Ship. Wt. 45 lbs.

"CHIEFTAIN"

### SOUND COLUMN

SPEAKER SYSTEM

STOCK NO. CHIEFTAIN "70" PRICE

With four 17". EM-19G10 speakers 10 oz. magnet, 14". 8 ohm. voice coil.

70 WATT PEAK AUDIO POWER

54"L, 14"W,61/2"D.

Same construction & covering, color and Grill clots, as the Dig Chief-100, eec bove on this page

e recomend the use of two systems on a 70, watt Amplifier, this allows over-load protection.

CHIEFTAIN 70 rice \$49.95 atched pair \$98.00

(see Back page for info. on EM 10G 10)

"SWEET SIXTEEN"

### PLUS FOUR SOUND COLUMN



40 WATT 8 Ohms HIF 8 Ohms MUSIC AND P.A. Stock No.

SC-SW16P4

Matched Pair \$90,00

SPEAKERS - 6" MID-RANGE 2 - 5" TWEETERS

60" long, 14" wide, 5" D. Here is an all purpose Music and Hi-Fi P. A. Sound Column. This was designed in our Audio 1.ab around the Sweet 16 speaker system of a few years back. With 16 5" speakers stacked vertically & with Two 6" midrange and Two 5" tweeters we have a very directing sound column. Two will cover the average school auditorlum. For microphone and music. Full range audio response at up to 40 watts audio. 8 ohms impedance. A special feature of this sound column is its very high effeciency. With 10 watts audio power you can get as much sound as many other columns using 20 watts inputMade of all wood construction with walnut Vinyl covering. Full grill cloth front. Ready to connect to the 8 ohm tap of your audio amplifier. Stock No. SC-SW16P4. Sale Price \$49.95 each, Matched Pr. \$90.00 60" long, 14" wide, 5" D.

WHY USE A SOUND COLUMN

\*\*\*\*\*IMPORTANT NOTICE\*\*\*\*\*

\*\*\* KEEP ALL OF THE ORIGINAL PACKING CARTONS FOR RETURN OF MERCHANDISE IF NECESSARY.\*\*\*\*\*\*\*\*\*\*\*\*
ALL UNIT MERCHANDISE, (SUCH AS SOUND COLUMS, RECORDCHANGERS, SOUND AMPLIFLERS, SPEAKER SYSTEMS IN
CABINETS AND ANY OTHER ARTICLE THAT HAS BEEN
PACKED PROPERLY.). ALL RETURN MERCHANDISE MUST BE REPACKED IN THE ORIGINAL PACKING AND DOUBLED BOXED TO PREVENT DAMAGE IN RETURN SHIPMENT ....

\*\* OTHERWISE WE WILL MAKE A SERVICE CHARGE \*\*

Without Question Sound Columns should be considered for your commercial sound. Starting in 1966, the use of Sound Columns has doubled, tripled and quadrupled. What Does A Sound Column Do? By having your speakers mounted in the proper enclosures and one above the other, sound spreads out horizontally and compresses vertically. This gives a better sound angle for auditoriums etc. It also permits working each speaker at lower level and gives better accoustical coupling of the speaker to the air.

### McGEE HAS EVERYTHING FOR CUSTOM AUDIO INSTALLATION



McGEF5 & 10

IMPORTED 25 and 70.7 VOLT

AUDIO LINE

TRANSFORMERS

CALRAD 5 WATT-25 VOLT MATCHING LINE TRANSFORMER Stk. no S-25 Universal 25-volt, 5 watt audio line transformer

for speaker mounting and remotely connected to an audio amplifier enabling volume adjustment at the speaker. Matches 4 or 8 ohm, voice coil speakers. Impedance taps are. .31, .62, 1.25, 2,5 and 5 watts.

Stock No. S-25V

Price ea. \$1,29

10 tor \$11.95, 20 for \$2 2.00

CALRAD 10 WATT-25 VOLT MATCHING LINE TRANSFORMER Stk. no. 10-25V \$1.49

Universal 25-volt, 10 watt audio transformer for speaker mounting and remotely connected to an audio amplifier 25 volt output. Volume can be adjusted at the speaker. Impedance taps are, 31, 62, 1.25, 2.5 and 0.625, 1.25, 2.5, 5.0 and 10 watts. Matches 8 ohm volce coil, speakers.

Stock No. 10-259

\*\*To for \$13.95

\*\*To for \$26.00

10 for \$13.95, 20 for \$26.00

10-70V

CALRAD S WATT-70.7 VOLT MATCHING LINE TRANSFORMER Stk. no. 5CV70 \$1.29

A universal 70.7 rolt, 5 watt audio line matching transformer for speaker mounting or remote. Volume of power can be adjusted at the speaker. Matches 4 and 8 ohm. speakers, Impedance taps in watts are: .31, .62, 1.25, 2.5 and 5 watts.

Price ea. \$1.29 Stock No. SC V70 10 for \$11.95, 20 for \$22.00

CALRAD 10 WATT- 70.7 VOLT MATCHING

LINE TRANSFORMER Heavy duty 10 watt 70,7 volt audio line output transformer. For use with 4 or 8 ohm speakers, Impedance taps are in watts. Can adjust power to the speaker. Transformer can be mounted on the speaker. Taps are: .625, 1.25, 2.5, 5 and 10 watts.

Stock No. 10-70V 0V. Price ea. \$1.49

CALRAD 10 WATT 70.7 VOLT MATCHING LINE TRANSFORMER, WITH A SCREW TERMINAL BOARD.



T10-70V \$229

.0 for \$20.00

Heavy duty 10 watt 70.7 volt universal line transformer for 4 or 8 ohm voice coil speakers, output of transformer is taped for adjusting the volume at the speaker, All wires are attached to a six terminal strip. Marked in wattage, .6, 25, 5 and 10 watts. Mounting centers of strip are 2-3/8 inches.

Stock No. T10-70V

Price ea.

BIG VALUE IN SPEAKER and

CEILING GRILL \$349

Our 1948A CEILING GRILL and 8-584 210, 8" SPEAKER Easy to assemble and Stock No. C 1-510 \$3.49 10 for \$33.00, 100 for \$300.00



10 for \$19.95

Stock No. 8-58 42 10 X. 8" PM Speaker for back-ground music. A \$5.00 list value, McGee's sale-price, \$2.19 each Buy a large quanty and save. Where you need a good musical reproduction and need fots of speakers in one installation. Here is a real speaker value, Features a %", 8 ohm voice coil and a 1.47 oz magnet, Better tone and high effections. Parted at 5 water. and high effeciency. Rated at 5 watts

### AMERICAN MADE 70 VOLT AUDIO LINE TRANSFORMER

10 WATT AUDIO TRANSFORMER 50-W-14 TO 4 OR 8 OHM VOICE COIL \$1.99EA.

### UNIVERSAL LINE TRANSFORMER



For 8 watt, 25 and 70.7 volt Speaker, Transformer has wattage taps for- 14,12,1,2, 4 and 8 watts. Size: 1-7/8 x 1½ x 1½ Strap mounting.

25 VOLT LINE TRANSFORMER 10 FOR\$15.90 169 Each

Stock No. 6W-25V, 25 Voit Audio Line Transformer. Matches 3 Ohm Speakers, Tapped at .31. .62, 1.25, 2.5 and 5 watts: Response 20 wire Wound Speaker Volume Control to 15,000 cps. Regular atrap mounting, 2-3/8" aunting centers price 51 69 each, 10 for \$15.90 No. CTS-60W. 89 Ea., 10 for \$8.50

INTERCOM EQUIPMENT ENCLOSURES STEEL PLATES AND BOX UNITS FOR CUSTOM INTER-COM INSTALLATIONS

MASTER SPEAKER

PLATE For S" PM Speaker

289 Pioto

4 FOR \$8.00

Box 7" x Sty" x 3"
Model CSYNAMC, 18 sa. steep the has a 90
bevel i 1,16" edge with a lare perforated steel
mech grife. For 5" [11] speaker. That has suffrigent area to hamile up to sax stations-wellector

SUB-STATION SPEAKER BOX For 3%" PM Speaker

24 WATT

70.7 VOLT LINE TRANSFORMER

8 AND 16 OHM

10

\$12.50

Stk. No. LP-8, 8 ohm, \$1.49 each, 10 for \$12.50 Stk. No. LP-16, 16 ohm, \$1.49 each, 10 for \$12.50

ONLY 400 TO SELL FOR \$1.99 ea

SPEAKER VOLUME CONTROL

16 OHM " L " PAD

"L"-PAD SURFACE MOUNT SELF-CONTAINED BOX WITH HEAVY DUTY "L" PADS

30 - 378

A flat frequency response and natural reproduction are obtained by adjusting for the difference in efficiency ratios. Adjustment ± 17% of the normal rated impedance "L" pads as available in 16 owns impedance Calibrated 1 to 10 Black plastic contour knob Very attractive gold finish case, 3% x 2% i 1%". This control can be mounted externally or can set file. Has two terminals at either end, simplifying hook up. Requires no knowledge to

6-W-6 HFL

PRIMARY 707 VOLT LINE SECONDARY 4-8-16 OHMS

24 WATTS

QUALITY TRANSFORMER

70 VOLT LINE TRANSFORMER

\$950

\$ 1 95 E ..

329

Plote 4-9/16" x 7-1/8" Box 3-7/8" x 61" x 2" CB3X-MG small receased speaker box or an plate has 45 deg, bevel; box heat with provisions for mounting CB3X-51G. Plate it box, \$1.29 ex.

Small size: 2-3/8" strap mounting, 5/8" core. Three color coded leads for use ELACK & RED, for 45 ohm BLACK & YELLOW for 8 This transformer has multi-

CUSTOM MADE IN U. S. A. - BY CTS - FOR MCGEE

NEW HIGH EFFICIENCY CERAMIC MAGNET

GET THE BEST POSSIBLE MUSIC FROM YOUR AMPLIFIER

Name with same volue engineered for bester distributed high tidelity prefessional round. Custom designed and manufactured by Chicago Talephone and Salichboord for McGos, Oasigned and made in U.S.A. Offered in the popular 8° size. 2 Madels, Heavy Duty 8 with 5 Oz. caromic magnet and Super Heavy Duty 10 Os. caromic magner. For the industrial seund installer and MI-Fi background music business operate, this gives the letast in speaker design, Both the 5 Oz. and 10 Oz. madels are offered with whizzer comes or one piece madelling comes line comes line comes.

8 INCH 449
10 OZ. MAGNET
SUPER N. D. Standard Cone
C.T.S. Super Heavy Delty of Pd. Pawer setting

cps. The 19 occ crisms hancet incorporated in this speaker, given the 17 water cell is annual magnet defively and would nave be be doubted in the control of the control of

With

OZ. MAGNET





45 OHM AUDIO LINE TO 8 OHM TRANSFORMER.

Convert any 8 ohm speaker to 45 ohm Intercom system

Stock No. T-50867

\$1.39 EA.

10 for \$12.90

line matching to 8 ohm, Stock No. XA-180-1

10 for \$19.50 Price. \$1.99 ea.,

No.












99

NEW 5 AND 10 OZ. CERAMIC MAGNET SUPER 8 SPEAKERS MCGEE'S FINEST BINCH CUSTOM BACKGROUND



100 for \$190.00

FULL I" VOICE COIL (1) WITH STANDARD CONE (2) WITH WHIZZER CONE

# Electro Voice P.A. AND HEAVY DUTY MUSIC SYSTEMS

sound reinforcement loudspeakers

FULL RANGE SPEAKER SYSTEM

High Power-Capacity 100 WATT RMS



NEW

MODEL ELIMINATOR 1

\$45570 Eliminator 1

A three-way, full-range loudspeaker extremely high audio system for level, high quality sound reinforce ment and playback. Rugged and ef ficient 15" SRO/15 musical Instrument loudspeaker, coupled to 55 Ha folded exponential horn cabinet for maximum efficiency and power-handling capacity. Midrange is handled by an BHD Diffraction Horn and special driver, Two special very high frequency compression drivers and horns cover the extended bigh range, Continuously-variable level control for vhf drivers and twoposition midrange control. Ruggedia built enclosures in black vinyl with metal corners, carrying handles, and trim, Response: 55-15,000 Hz. Cross overs: (electrical) 1800 Hz and 3500 Hz. Power handling capacity: 100 watts RMS (white noise shaped to lead guitar frequency spectrum). Dispersion: 100° main-tained to beyond 15 kHz, EIA sense tivity rating: 56 db. Sound pressure 122 db at 4' with full power input. Dimensions 37%" high, 22%" wide, 23-1/8" deep. Weight: 118 lbs

NEW 1972 MODEL MUSICASTER 11A WITH 12" RADAX DUAL-CONE WIDE RANGE DRIVER And T35A TWEETER



MUSICASTER IIA \$ 9261

Same fine performance and housing Musicaster IA with addition of T35A vnf compression tweeter for extended high-frequency response and wider, more uniform dispersion above 5000 Hz. Smooth response from 80 to 16,000 Hz. Net weight,

HI-POWER 3 WAY SPECIAL DESIGN FILL RANGE FOR GUITAR USE 125 WATT RMS

1 FLIMINATOR 2



NEW Eliminator 2

ELIMINATOR 2 \$36260

Similar to Eliminator 1, for even higher power-handling capacity and sound pressure output with some what reduced high-end response and high-frequency dispersion, Ideal for the rigid requirements of Acid Rock groups and similar stringent applica tions. Same cabinet and incorporates same components as Eliminator with exception of vhf drivers. Re sponse. 55 to 10,000 Hz. Crossover (electrical) 1800 Hz. Power handling capacity: 125 watts RMS (white noise shaped to stringent lead guitar frequency spectrum). Dispersion 100 EIA sensitivity rating: 57 db. Sound pressure level: 124 db at 4 with full power input. Dimensions. 22% wide, 23-1/8 deep. Weight: 112 lbs.

NEW 1972 MODEL MUSICASTER 1A WITH 12" RADAX DUAL-CONE WIDE RANGE DRIVER



MUSICASTER IA

\$ 7350

Redesigned and improved version of famous Musicaster, providing high fidelity performance in a compact portable, completely weatherproof system. Now with 12" Radax dualcone, wide-range driver in extremely rugged, one-piece, compression molded, glass-filled polyester housing. Bass-reflex design of housing assures excellent bass re-sponse. All parts fungus proofed. Sandwich of Acoustifoam between speaker and grille repels water with out affecting sound dispersion. Bracket for mounting at any angle or for use as carrying handle, Tough, scuff-resistant olive finish. Response: 80-10,000 Hz. Nominal impedance 8 ohms. Dispersion: 120°, Power handling capacity, 60 watts peak, Sound pressure level, 111 db at 4'. Size: 21%" high, 21%" wide, 8%" deep Net weight, 20 lbs.

Electro Voice 18

THE MOST OUT STANDING SPEAKER SYSTEM MADE

PRICE MODEL SENTRY IV \$49500



High Power-Capacity Speaker System for Studio & Broadcast Monitoring and Heavy-Duty Sound

SENTRY IV: Extraordinary new professional sound reinforcement and monitoring and Heavy-Duty Sound

SENTRY IV: Extraordinary new professional sound reinforcement and monitorion loudspeaker. Altrady preferred in trading studies. Three-way, all horn-baded system offers absolute minimum distortion over wide frequency range, unrequality efficiency and uniformity, high power handling capacity, uniform and wide dispersion flurating singularity and tweeter handling capacity, uniform and wide dispersion florance first significant new sectoral design in 25 years. Vertical dispersion 60°, and horitorial dispersion for "dead" spots Folded horn woofer with two entirity new 12" conditions of the first provides almost linear response down to 30 Hz. High-frequency components may be operated with separate ampliture. Heavy, well braced wood enclosure, untilty black, 4-position high-frequency rolloff switch allows higher power handling capacity in excess of 125 watts RMS with attenuared highs. Response: 50 to 18,000 Hz 50 watts RMS at full range. Sound Pressure Level: 117 d81. Impedance: 8 ofins 50% h., 27% of 18% Ligh-frequency sub assembly only from Scnity IV. Includes midrang and tweeter sectoral horns.

STILL AMERICAS

STILL AMERICAS BEST ALL-METAL LOW COST HORN

30 WATT 8 OHM 250 Hz. To 13,000 Hz.



MODEL 844A \$2646 MEDIUM ANGLE

Model 844A

medium-angle sound distri-Features smooth response with better lows to provide natural paging without feedback, Handles 30 watts-to reduce costs. Rugged diecast horn, plus field-replaceable voice coil keeps service costs at a minimum. Fraquency response, 250-13,000 Hz; power handling capacity, 30 watts program; nominal impedance, 8 ohms; nominal dis-persion 90°; EIA sensitivity rating, 54 db; sound pressure level, 123 db; dimensions 9-7/8" diameter, 7-7/8" deep. Net weight, 11-1/4 lbs.

LINE RADIATION SPEAKER SYSTEM WITH NINE 3" X 5" SPEAKERS AND 3 3½" CONE SPEAKERS

MODEL LR4A \$13524 50 WATT

200-10,000 Hz. FULL

RANGE 8 OHMS

Model LR4A Curved-design' overcomes unwanted

high-frequency dispersion at ends, eliminating echo and feedback, Con tuins nine 3" by 5" and three 315" cone speakers, 160° horizontal dispersion: 60° vertical dispersion, Fretioency response: 200-10,000 Hz. Power handling capacity: 25 walts program, 50 watts peak, Nominal impedance: 8 ohms Size: 49" high, wide, 13" deep. Mesa finished wooden enclosure. weight, 26 lbs.



20 WATT RMS LINE RADIATOR

MODEL LR2SA \$6174

200-10,000 Hz.

WEATHERPROOF With 3 - 5X7" SPEAKERS

Short. easily LR4SA with somewhat greater vertical dispersion (45°). Smooth response from 200 to 10,000 Hz. Impedance: 8 ohms. Power handling capacity 20 watts program. Size 24-1/2" long, 6-5/8" wide, 4-7/8" deep. Net weight, 15 lbs. Two model 460 brackets furnished for wall, floor, or heavy-duty stand mounting.

Compound Diffraction Projector (CDP) EXCLUSIVE COMPOUND HORN



30 WATT MODEL 848A \$5586

Combines FC100 Compound Oiffraction Horn plus 1828C driver for finest wide-angle sound, lowest distortion, highest quality of any projector. Specifications: Frequency response, 150-10,000 Hz; impedance, 8 ohms; dispersion, 90° x 120° power handling capacity, 30 watts. sound pressure level, 120 db; di-mensions, 10%" x 20%" x 20". Net weight, 13% lbs.

WEATHERPROOF LINE RADIATOR SPEAKER SYSTEM FOR INDOOR OR OUTDOOR USE

> Lightweight Extruded ALUMINUM CASE Finished In FAUN METALLIC

> > Flortso Voice MODEL

LR4SA \$10584 40 WATT 200 - 10,000 Hz.

FULL RANGE

WITH SIX 5X7" SPEAKERS

Model LR4SA

Completely weatherproofed Line Radiator loudspeaker for outside or indoor sound installations. Extruded aluminum case is lightweight, rugged, attractive. Finished in Faun metallic, the speaker fits with any decor. Electrical filters remove end speakers from circuit as frequencies increase, eliminating high frequency lobes at ends. Smooth, carefully tailored frequency response from 200 to 10,000 Hz for true high fidelity sound reinforcement at greatly increased sound pressure levels Impedance: 8 ohms. Power handling capacity: 40 watts program Ols-persion: 30° vertical, 160° horihorizontal Sound pressure level. 116 db (at 4' with 40 warts input 750-1250 Hz.) Size: 48-3/8" long, 6-5/8" wide, 4-7/8" deep. Net weight 25 lbs. Complete with universal mounting bracket and chain as well as one Model 460 bracket for heavy-duty stand mounting.

### WIDE-ANGLE DISPERSION HORN SPEAKER

WITH FIBERGLASS HORN Electro Voice



MODEL 847A 385

WATT

Model 847A

250-10,000 Hz.

Utilizing the famous CDP speaker principle—this wide angle unit provides higher articulation without ennoying "peaked" response over a uniform 120° x 90° area Low distortion results from use of TWO diffraction horns. 25-watt power handling capacity. Fiberglass horn has Mesa Tan color molded in. Frequency response, 250-10,000 Hz; power handling capacity, 25 watts; sound pressure level, T14 db; dispersion 90° x 120°; impedance, 8 ohms; dimensions, 11%" length, 7%" width, 104" depth. Net weight, 8



HIGH FIDELITY Speakers-Systems-and Enclosure **Famous Altec Duplex Speakers** 

New Super Duplex 604E Loudspeaker

New Super Duplex" 604E Loudspeaker Alrec's 604 speakers are the most widely used by professional recording studios of all speakers made! The original 604 has been improved to provide superfaire purity of mid-raine, exceptional attack time, and distortion-free frequency rainge of 20-22,000 Mz when used in giptimum enclosure. The massive 604E uses a true muticell HF horic combined with a high-compliance 15" cone for perfectly controlled distribution and the point-source relationship obtainable only from a co-assalty mounted speaker. Extremely low cone reconance permits use in cabinets as small as 4 cu. ft.

Duplex" Loudspeaker 601-8D

The best 12" speaker made, the 601C is excellent for reproducing heautiful sound from enclosures as small as 3 cubic feet. This true two-way system uses After N-3000E crossover network for opti-mum frequency division. High-compliance UF cone and center-mounted multicell cast-zinc born combine for smooth, realistic sound and perfect

20 walts (30 walts peuk) 30-22,000 Mz 8 ohms 19 Hz 9 lbs., 11 oz. Almon V 4000 Hg, full-section (furnished with speaker 12%" 5%"



419-8B

35 watts (50 watts peak) 20-22,000 Hz 8/16 ohms (LI) 20 11 lbs, Alaica V

604E

1500 Hz, dual full sent

Full-Range Small Speakers

speaker 195,00

# :163°°



605B Duplex Loudspeaker

Essentially the same system as the 604E, with efficiency (ust 3 dB less. Has a 15" high-compilance cone and a true multicell HF hom. Like the 604E, the 605B provides pure mid-range, exceptional attack time, and distortion-five frequency range of 20-22,000 Hz (when used in ophimum



405A Full-Range Mini-Speaker

Though only 4" in diameter, the new 405A is a high quality, full-range speaker that is ideal for high "idelily applications in miniature book-shelves, in auto-stereor tape systems, or any other use requiring extremely small size.

405A

Full-Range

Two-Way Speaker Components for

Either the #14A or 4068 Low Frequency Speakers

can be used in combination with the 3000H High Frequency Speaker and the N-3000E Network.

[H 414-88 Low Frequency Speaker. A heny 12" speaker offering the cleanest reproduction of low frequencies of any speaker its size. 3" edge-wound voice coil and cast-aluminum lzame.

408 BC Low Frequency Speaker. Has cast-aluminum frame, 9 lbs., 7 ozs., magnetic struc-ture, highest efficiency and exceptional base response in a small enclosura. May be front or

9 lbs. 7 azs Alnica V 15 lbs

1 OHM 5 6 00

5%" Weight: 11% lbs

Weight:

Power Rating: 25 wath Frequency Response: 30-4,000 Hz Impedance: 8 OHM Cone Resonance: 30 Hz Diameter 12 %

Fower Rating. 25 watts Frequency Response. 25-4,500 Hz Impedance a OH M Cone Resonance 28 Hz

Diameter Baffle Cut-out Depth: Magnet Structure:

Small Enclosures

Mini-Speaker

### Altec Full-Range Biflex Speakers

The patented multiple compliance of the "Biflex" achieves unusually wide frequency range by allowing a malter center cone and new aluminum dome to operate independently for more efficient reproduction of high frequencies. The entire cone area functions to reproduce the lower frequencies. Exosover is effected mechanically at 1000 Hz through the patented mid-cone compliance.





ower Ratingly equency Response:

### 755 E Wide-Range Speaker

733 E Witte-Rarige Speaker
The extended-range Beaker
Interpretation or walf-mounted speaker because of its
flat, pancake shape. It projects a large volume of
smooth sound with minimum distortion from enclosures as small as one cubic foot. An excellent
choice for a bookshelf enclosure. Ceramic-type
magnet permits speaker depth of only 2½ inches,
and the flat come design priorides an unusually
wide-angle, 90° sound distribution.

75 watts 40-15,000 Hz B-ohms 52 Hz 8%"



8" 3075 Wide-Range Speaker

A7-500 Speaker Components



ments as used in the After A7-500 the same components as used in mic nate: Ar-3-and A7-500W-1 speaker systems. This two-way system with its 500 Hz crossover is made up of the finest components available at any price. (A) 4166A .ow Frequency Speaker. The finest 15" If spealer made. Vrice coll of edge-wound copper ribbon, V in diameter. Rigid cast aluminum frame.

Prover Rating III walls
Frequency Re-printe: 20-1 600 Mg
Impedance: 80 OH MS
Cone Resonance: 25 Mr
Diameter: 15-5/16"
Ratific Qui-cost 71%" Magnetic Structure

10 lbs Binz, Almen V 17% lbs.

Weight

(E) 511B High Frequency Horn. A massive from 500 Hz to beyond audibility.

Famous

A7-R

Voice of

the Theatre

Weight

from 900 Hz to beyond audition from 900 Hz frequency Cut-off: 500 Hz frequency Cut-off: 500 Hz frequency Cut-off: 90° horizonal 40° vertical: 100° Hz x 25-5/36° W a 1805° D

(F) 8.08 - 8.4 High Frequency Driver, The ultimate in smooth sound from 500-22,000 Hz. When enoupled to the Alter 518 sectoral horn, the 802D reproduces from below the mid-range to beyond audibiting without a crossover in the critical high-frequency range.

Frequency Range. 500-22,000 Hz 5116 with N-500G

Power Rating: Impedance: Diameter: Depth: JO Watts 8 OHMS 5 78 50

(G) NS01-8 A Dividing Network. A precision, two-section, crossover network designed to

8 OHMS

work with the 802D Driver \$6100

6 dB in 1%-dB steps 500 Hz 12 d8/octave

### Full-Size Altec Speaker Systems

Famous "Voice of the Theatre"® Speaker System A7-8

Speaker System A 7-8
Standard with Ihealtes, recording studios and concert halls because of its unmatched power and perfection. A great value for audiophites who wish to build it in or enjoy its superb sound in a utifity cabinet. Extremely wide frequency range and large power-handling capacity. Uses Altec's 806A high-frequency driver with large, cast-aluminum 8118 excital horn to smoothly distribute frequencies above 800 Hz over a write angle. After's 416A 15\* flow frequency speaker, mounted in a front loaded wooden exponential horn Cabinet, faithfully reproduces the lowest orchestral frequencies.

30 - 22,000 Hz Power Rating 42" H x 30" W x 24" D (HE horn within end mure) 416-8 A . 807-8 A . 811 B N 801-8 A

### "Voice of the Theatre" Speaker



A7-500-8 Voice of

Speaker System

38200

### "Voice of the Theatre"® Speaker System A7-500-8

identical to the A7 except that it has a lower crossover of 500 Hz to provide hom coverage of the lower mid-range. The higher efficiency 8200 Hf driver coupled to the larger cast-aluminum 5118 sectoral horn provides the cleanest, most realistic sound of any speaker ever made.

10-22,000 Hz BOHMS 42" If x 10" W x 24" D OHF horb within enclo

416-8.A. 808-8.A. 511 B Power Rating
N 8.01-8.A Frequency Response.
Crossoper.
Recommended Impedance:

Depin

(1) 3000H High Frequency Speaker. A castzine multicell hom and integrally mounted
draws. A true super hweeter, the 3000H vatends
system range to 22,000 Hz with excellent dispersion of highest frequencies.

B Power Rating:
20 waits
Frequency Response: 3,000-22,000 Hz
Crosscore:
3,000 Hz
5 5 5 39<sup>50</sup> N-1000E 90° horizontal 40° vertical 8 phms

13 gances 3-3/16" H x 4%" W x 4-5/16" D

Omerosons: 3-3/16" M x a h;" W n 4-3/16"

(K) N-3000E Dividing Network. Provide: accurate crossover at 3000 Hz between the 414A or 4668 wooder and 3000H tweeter. Continuously variable shelving control Impedance: B ohms HF Attenuation Control: variable variable Crossovet: 3000 Hz 2055

Weight: 1 hb., 5 ounces

Reching to the second s

### A7 Speaker Components



These speaker components are identical to the ones used in the Affec A7, Valencia, and Flamenco speaker systems. Superb quality two-way system with 800-Mz crossover.

### "Voice of the Theatre" Speaker Components by Altec

(A) 4re-BA Low Frequency Speaker. The finest 15° LF speaker made. Voice coil of edge-wound copper ribbon, 3° in diameter. Rigid cast-aluminum frame.

Power Rating:
Frequency Response
Frequency Response
Come Responser
Come Responser
Diameter
Baffle Cul-out:

30 watts
20-1,800 Mz
9-1,800 Mz
9-5 Hz
15'-516'
13''." Depth; Magnetic Structure. 10 lbs., 8 oz. Alnico V 17% lbs.

Weight: 17/2 loss.

(B) 8118 High Frequency Horn. A massive sectoral horn of heavy cast-aluminum. Operates from 800 Hz to beyond audibility.

Frequency Cut-off 800 Hz \$ 2 8 00

Frequency Cut-off Recommended Driver Sound Distribution:

(C) 807-8 A High Frequency Driver, Provides the ultimate in smooth sound from 800 to 22,000 Net by allowing the critical mid-range to be reproduced in a sectoral horn without distortion and no crossover in the critical high-frequency tange. Frequency Range:

> Power Rating: Impedance: Diameter Death

30 Walls \$ 6700

(D) N801-8 A Dividing Network. A precision two section crossover network designed to work with the 806A Driver.

Input Impedance; HF Atlenuation Control: Crossover; Slopes of Crossover:

8 OHMS \$ 5380 6 dB in 1% dB steps 800 Hz 12 dB/octave

### Altec Patio Speaker System

MODEL 829 A PATO SPEAKER
USES A 755E BINCH SPEAKER
0 20 WATTS 60 TO 15000 CPS.
WT. 10 1 LBS DIM 15817X12.
IMPED 8 OHMS NET \$82.50
MCGEE WILL HAVE ANY ALTEC ITEM
THEY MAY BRING OUT IF YOU DONT
SEE IT HERE JUST DROP US A NOTE.

FANON FANON FINE QUALITY PAGING AND TALKBACK SPEAKERS FANON

ATLAS SOUND Model SC-15 SUPER VALUE 15 WATT

WE HAVE SOLD OVER 2,000 OF THESE HORNS IN THE PAST TWO YEARS



\$1595 \* STAR 2 for

\$30.00 8 ohm

VOICE COIL

Totally weatherproof Built in 15 watt driver

VALUE \* 7/2 WATT \$ 99 8 OHM FANON MODEL HDA-5-8

Diamentions: 6½" bell dia. X 6-5/8 D

Adjustable mounting bracket Shipping weight: 2½ lbs

"MULTI-TAP" SPEAKERS

Compact high power speaker that measures 6" diameter by 6½" long. IS worts continuous duty, Excellent response and acoustical output of voice & non-critical music for its size. Full-range swive mount with positive a locking action.

PAGING AND TALK DACK

30 WATT 8 OHM FOR \$35.00 FANON SPEAKERS ARE HOT LACQUER GREY FINISH

FANON

MODEL HDA-10-8

Higher power version and improved low frequency response of HDA-5 and HDA-6. Rated at 30 watts continuous output and has 10" diameter bell. Hos a sound pressure of 124db or double the efficiency of speakers of same size and input rating, Good wide-range response. Full-range swivel mount with positive locking action.



BELL DIAMETER 81/2"

2 FOR \$45.00

POWER TAPS

Now match the power you need merely by "rotating a plug". No screwdrivers needed or formulae to compute. Four different power selections on each horn. Fanon's "Multi-Tap Speakers, with built-in matching transformers. Saves costly installation time. These quality loudspeakers offer unexcelled reproduct-

Model No	Frequency Response	Power Reting	(voice coll)	Dimensions
HDA-15T	250-13 KHz	15,7.5, 3.5, 2 walls	8 ohm	895" x 11"
HDA-30T	250-13 KHz	30, 15, 7.5, 4 5 watte	8 ohm	10" x 12"
-		ATL	AS S	OUND

### BELL DIAMETER 10"

ion for general paging purposes and are high-ly efficient when used as a microphone in an intercom system. Complete with molded plug and 18" speaker wires. Ruggedly construct-ed of aluminum with boked enamel finish, sturdy weatherproof design that assures you dependable service.
For purpose of impedance matching these waltages can be connected

Model HDA-15T	15W	7.5W	3.5W	2W
	330 ohm	670 ohm	1.65K ohm	2 5K ohm
Model HDA-30T	30W	15W	7 5W	4.5W
	165 ohm	330 phm	670 ohm	1K ohm

ALUMINUM

Ship Wt. 61/2 Iba.

stock no.

AP-30

3" Reflex TRUMPET SPEAKER \$4.95

\* CB Use

\* Public Address

Extension Speaker

Concealed

Installations Model 21-401

3¼" 0.D. x 1-7/8" D.

Aluminum reflex baffle & hom with adjustable mounting bracket with thumb screws for easy installation and sound direction. Gold anodized finish, Has 6" Lead.



SUCTION CUP Mounting Bracket For TRUMPET SPEAKER ideal for Mobile Use Stock No. \$ 295 B807

Bracket with 4 Heavy Duty Suction Cups

MADE IN

Mighty ATLAS AP -30

### 30 WATT

ALL IN ONE HORN and DRIVER best for music and voice LIST \$45.50

NET. \$27.30

100% WEATHERPROOF USE IN OR OUTSIDE

MUSIC AND VOICE RESPONSE

225 to 14000 C.P.S. 3-Way adjustable mounting brocket. EXTRA FEATURE - EASY TO REPLACE THE DIAPHRAM IN THE FIELD. ATLAS AP-30T Rated 30 watts. Bost buy for music and sound, 8 ahms imp. Dimensions, 10 in. wide 9½ in. tall and 10½ in. front to back, Made in U.S.A. Model AP-30T. Has built in adjustable 70 valt weatherproof line trans. 6 wattage tops to control volume. List \$59.00 Net Price \$35.40

# OXFORD 30 WATT

HORN

ship wt. 9 lbs. All Heavy Duty Metal Construction NEW 1972 Model

Bigger, Better, Heavier than any other \$20.00 Horn

\$39,00 Model OPSAMBP

YEAR ROUND OUT DOOR

95 2 for DEWXE SWIVAL \$49.00

Model OP8AMBP-70V

8 OHM MODEL MATED 30 WATTS
FROM 228 TO 13000 CPS. F.EG.
SUG. NET OVER \$30.00 MCGEES
SALE PRICE \$19.98 TWO FOR \$39
WATTS PWB 45 OHM TAP. RATED 30 WATTS FROM 225 TO 13000 CPS. REG. SUG NET OVER \$38.00 OUR PRICE \$24.95 2 FOR \$4

### OUTDOOR REFLEX SPEAKER

The Model DH12 Trumpet Horn Speaker is a combination type of the Trumpet Horn Speaker with the Driver Unit enclosed within the horn Complete Waterproofing and Rustproofing with Shock-proof construction has made this speaker a rugged Trumpet Speaker for rough use. Its lightweight aluminum construction and small size give versatility in use. Complete with swivel mounting bracket furnished in grey Hammertone finish, and connecting cord. Model DH12......\$13.95

\$1495 2 For \$29.50

Model **DH12**  Power Rating: 12 Watts
Voice Coil Impedance: 8 ohms
Frag. Range: 340-7,000 cps.
Horn Opening: 5" x 8"
Overall Length: 8 inches Net Weight: Approx. 3 lbs.



### FM-AM Background Music

000

AMPLIFIER

With

Tuning Selector, Mike Volume. Tuner/Phono Volume, Tone (w/power swit 12 Transistors, 8 Diodes

Power.

"AMPLIVOICE"—SOLID STATE POWER BUILT-IN FOG HORN MEGAPHONES AND SIGNAL ALARM

Marine Use

Law Enforcement

Building Construction Agencies

Sporting Events

Civil Defense Agencies

May be used as PA System with Detachable Microphone

Microphones used on these units alone are worth \$30.00

Will outperform other similar roted units by far.



2583 - Solid State Power Megaphone. Supplied with detachable cardioid microphone. 9 ft. extension cable, shoulder strap and batteries. Bell dia. 93/4" 1.

PORTABLE PA SYSTEM

2589

WATT AMPLIBOX SOLID STATE

\$6495

TWO

ELLIPTICAL

SPEAKERS

DYNAMIC

BACKGROUND MUSIC AND A PAGEING SYSTEM TOO. Model RA-69A

INSTRUCTIONS AND

Audio Section

Frequency Response Harmonic Distortion Input Jacks Innut Sensitivity

Hum and Norse

Output Impedance

Timer Section **CENT Section** 1

Lumng Range Sensili Image Rejection Ratio Band Width Linput 64 dh)

tAM Sections Tuning Range

Sensitivity Image Resection Ratio Rejection Ratio Band Width

50 - 13,000 cps. Less than 10% at 10-watt output

108 - 108 MHz.

10 # V at 30 dh S/N.

35 db at 106 MHz.

35 dh at 40 MHz.

535 - Jan 5 KHz

200 m/s 50 dh at 600 KC

35 dh nt 600 KC; 25 KC at 6 db down.

300 KHz at 6 dh down

Microphone, Phono tees, I Mike, Hi-z Mike. Lo-Z More than -50 db Micronhone Phono More than -60 db 4, 8, 16 ohms. 25V & 70V line output.

15 mV 3 mV.

M I.bs. WILL POWER FROM ONE TO TWENTY SPEAKERS.

AC 117V 60 c/s.

SOLID STATE 15 WATTS R.M.S AM/FM RECEIVER

USE WITH ANY HIZ OR LOW Z MIKE.

SALE PRICE

MODEL **RA-69A** 

Watt MOB \* Operates on 12 Volts DC at 1.9 amps. \$

\* Far Police, Fire & CD Emergency Vehicles

\* Includes all hardware, Spare Fuse & Bulb DYNAMIC MIKE

\* High Impedance Mike Output

WITH ON-OFF SWITCH \* 4-Transistor Circuit \* Push-to-Talk Mike Circuit



A compact solid state 15 Watt Mobile P.A. Amplifier, can be used in any 12 voit car, truck, boat or plane, positive or negative ground. Input is provided for high impedance mike, tape or phono. Output impedance of 4, 8, or 36 ohms. Complete with all mounting hardware, operating instructions, fused battery cables, and speaker plug. Size: 2" H. x 4" W. x 444" D.

SOLID STATE P.A. AMP. MOBILE (12 V. D. C.) or 117 V. 60 CPS

40 WATTS OUTPUT Sturdy Adjustable Mounting Bracket



AM-49A

20 WATTS RMS

\* 25 and 70.7 V Output

\* Two Mike Inputs (Low or High Imp

An excellent all around amplifier for churches, achools, etc. Includes controls for mike 1 and 2, volume, Phono/Aux, volume and tone, Mounting bracket. Size: 9% W, x 3% H. x 8 D. 110-120 v. AC, 60 cps. and 12 volts DC. Shpg. wt. 18 lbs.

SOLID STATE AC-BATTERY **PUBLIC ADDRESS** AMPLIFIER 2 MICROPHONE INPUTS



PA230

· Supplied with 2 Female Mike Connectors,

one 34" phone plug and one phono plug

• Fused Line

Selector Switch for either AC or OC

· Ideally suited for both crisp and clean sound whether using amplifier for voice

control dynamic microphone with wind screen and batteries. Size: 9" x 8" x 3½". Weight 4 lbs. HOT NEW ITEM

CARDIOID MICROPHONE



### SPECIFICATIONS FOR MODEL PA230

Specifications:

Solid State Circuit: 6 transistors,

Frequency Response: 50-18,000 Hz

Line Outputs: 25 volts and 70 volts Power Output: 45 watts (peak power) Output Impedance: 4-8-16 ohms, polarized 12 Volt terminals

> Power Requirements: 12 V DC and/or 117 V AC. 50-60 Hz

30 WATTS PEAK POWER OUTPUT



### JNIVERSITY SOUND

ALTEC DIVISION OF AFTY LING ALTEC. INC.

### POWER-LINE

### WIDE RANGE HIGH **EFFICIENCY AMPLIFIERS**

A. MODELS UPBEOT and 100T BOOSTER AMPLIFIERS. 50 and 100 watt RMS solid state
booster amp designed for dependable operation. Ideal for use wherever undistorted high
power is required.
Computer Logic Circuit protection prevents
damage to amplifier under any adverse load
condition. Response ± 1.5 dB. 50 to 15,000 Hz.
Inputs: Hi Z 50,000 ohm. Optional plug-ins
provide 10k ohms bridging, 600 ohm line. An
additional optional plug-in capability provides
low Z ohms for microphone, RIAA meg Phono,
NAB Tape Head. Outputs: 25v and 70v Isolated,
8 ohms, and 2nd-16 ohms. 5" x 15½" x 10½".

117 VAC shpg. wt. 21 lbs. \$201.95 \$233.20

E. MODEL MPA-2B TWO CHANNEL MIKE PRE-AMP. Adds 2 additional mike inputs to UPL amplifier. Has full level controls, hi-lo impe-dance switch, facilities for remote or prece-dence controls. \$46.17

F. MODEL RAC-1. Rack mounting adaptor for Power-Line. Simple screwdriver installation. Oesigned for use with standard 19" rack. \$17.97

S17.97
G. MODEL CAM-12 PORTABLE CARRY CASE. Doubles as portable P.A. system. Houses two M-12 extended range Mustang high fidelity speakers. Slide in rack for amplifier and storage strap for microphone. \$82.43
I. MODELS ULT 5 and 10. University exclusive vine matching transformers. To be used at speakers when transformerless installation is made. ULT5 \$2.93 10 \$4.43

MODEL LOZ. Balanced - to - Ground Micro-none Transformer. An "in-line" transformer phone Transformer. An "in-line" transformer allowing use of balanced-to-ground mikes with Power-Line amplifiers. \$11.55

K. RCB-2A REMOTE VOLUME CONTROL. For use with LDR-1. Provides remote level control for 2 different input signals. \$12.44

L. MODEL LDR-1 PRECEDENCE CONTROL. Plug in accessory permits user to provide source precedence from remote location, \$6.30

M. MOOEL UMX-4. Mixed/Preamp. 4 mic Hi-Lo Z w/built-in transformers and Aux Input. Outputs Hi-Lo Z mic, Aux and mix huss. Master Level Control, Cannon connectors 339.95

N. MODEL UPB-10T. 10 watt amplifier with Hi-Lo Z mic, Aux and optional inputs. Outputs 16 ohm, 25 and 70v. \$59,95

O. LDS-60T. 60 watt RMS Mixer amplifier, 4 mic inputs w/Cannon connectors Hi or Lo Z. Mag Phono and Aux on common fader. 4-12 ohms, 25 and 70 v. outputs. \$298.08

P. LDS-100T. As above, but 100 watt RMS.\$351.69



A MODELS UPBOOT and 100T



F. MODEL RAC-1.





I.MODELSULT 5 10.

J. MODEL LOZ.



K. RCB-2A

L. MODEL LOR-1

UPLEOT (WITH/XFMR) \$141.90

50-15kHz, ±11/2 dB

120w

\$141.90

60W at less than 5% THD

more mics available on optional pre-amp Gain Control (fader) for Aux. 1 & Aux. 2

31 All-silicon



N. MDDEL UP8-10T.

MODELS

FREQUENCY

PEAK POWER

POWER DUTPUT

INPUTS
(IMPEDANCE)
(All mike inputs
specially suitable
for guitar and
music inputs.
CONTROLS

SEMI-CONDUCTORS



**UPL35T (WITH/XFMR) \$117.57** 

\$117.57

35W at less than 5% THD

70w.

2 Mic (hi or lo Z unbalanced)
hi Z: 47k ohms, lo Z:
150 ohms
Aux (2 inputs on fader)
300k ohms
Pridging hi Z (5K)
2 Indiv. Mic.
2 more mics available on optional pre-amp
1 Gain Control (fader) for
Aux. 1 & Aux. 2

50-15kHz, ±11/2 dB

35 All silicon




10000001

MODEL CAM-12

E. MODEL MPA-2B

O



200w.

2 Mic (hi or lo Z unbalanced)
hi Z: 47k ohms, lo Z:
150 ohms
Aux (2 inputs on fader)
300k ohms
Bridging hi Z (5K)
2 Indiv. Mic.
2 more mics available on
optional pre-amp
1 Gain Control (fader) for
Aux. 1 & Aux. 2 2 Mic (hi or lo Z unbalanced) hi Z: 47k ohms, lo Z: 150 ohms Aux (2 inputs on fader) 300k ohms Bridging hi Z (5K) 2 Indiv. Mic.

SENSITIVITY

SIGNAL TO NOISE RATIO

TONE CONTROLS

(feedback)
POWER INPUT
OIMENSIONS SPECIAL FEATURES


Mic (lo Z): 0.25 mv. Mic (hi Z): 4,0 mv. Aux: 250 mv. Bridging: 1V Power Amplifier: -80 dB Aux: -70 dB, Mic: -60 dB 3(ITPUTS: XFMR Models 25V & iSolated 70.7V line
(All models: Tape and 4, 8 & 16 ohms on terminal strip
Bridging outputs) 2 quick disconnect octal sockets Bass: ±10 db at 100 Hz Treble: ±10dB at 10kHz

95-130V AC 60 Hz 5" high x 1542" wide x 1012" deep

Hi or to Z mlc input selection by means of slide switch Switched AC outlet Spkr. protection circuit (Dutput current limited to rated power to prevent overdriving the speakers) Fused AC time Power consumption less than SW when Idding, resulting in low operating temperatures & long component life.

### UNIVERSITY SOUND UNILINE SOUND COLUMNS

32 All silicon



Medel		GSD-66	CEO-46	C2-3M .	GS-2	C2-30 "	
Column Hei	ght	60/5,,	4135"	48"	325g"	32"	
Speakers		four 8" plus two 8" Dual Cone	two 8" plus two 8" Dual Cone	six 4"x6" plus two tweeters	51x wide-range 5"	six 5"	
Frequency F	tonge	65-14.000 Hz	70-17,000 Hz	150-10,000 Hz	175-12,000 Hz	200-10,000 Hx	
Power Capacity		120 watts IPM	75 watts IPM	25 watts IPM	30 watts IPM	30 watts IPM	
Impedance		16 ohms	8 ohms	16 ohms	8 ohms	8 onms	
S.P.L.*		124.5dB	121.5dB	112dB	111d9	109dB	
Dispersion	Vertical 16° Horizontal 120°		180	20°	25"	20°	
Dispersion			1200	120°	165°	120°	
Dimensions		5012"x1134"x712"D	413a"x12"x7 13/16"D	48"x714"x616"D	3298"x712"x612"D	32"x7"x454"	
Shipping Wo	night	63 fb.	40 tb.	28 lbs.	14 lb.	14 fbs.	


\$ 69.17 \$ 61.29 \$156.87 \$101.90 \$217.35 UNILINE is a registered trademark of UNIVERSITY SOUND \*4 ft. on axis, re .0002 dynes/cm at rated power \* Dilad Walnut Finish



### SPECIALLY CONSTRUCTED FOR "AROUND-THE-CLOCK" BACKGROUND MUSIC OPERATION - Continuous Duty

RUGGEDLY CONSTRUCTED AUDIO AMPLIFIERS FOR "ROUND-THE-CLOCK" OPERATION

ALL-SILICON SOLID STATE MODEL 795



MODEL 793 - 30 WATTS RMS - MODEL 801

Raymer all-silicon solid state audio amplifiers are raggedly constructed, and employ the latest transition design so as to provide continuous operation around the clock at temperatures from =20 C. (=4 F.) to =85 C. (=149 F.), Special circuitry and the use of circuit breakers prevent damage to the swhen the output is accredientable shorted, unbaseded, or mismatched. All amplifiers are supplied with AC convenience outlets wired to the power on and off switch so that turning off the amplifier also turns off the equipment plug in the convenience outlet. All amplifiers are housed in attractive, sturdy metal cabinets.

MODEL	804-100	795	793	801A	
	\$169.95	\$49.95	\$94.95	\$79.95	
Power Output RMS	100 WATTS	10 WATTS	30 WATTS	30 WATTS	
Inputs	I mic —high impedance of the impedance inhalancial I aux —high impedance MI-IMP BROOMS	1 mic —high impedance se les impedance. unbelences 150 7502 1 aux —high impedance high total	3 m-c —high inhpedance or four impedance unbalanced 150 2502 3 aux —high impedancy high lovel	1 mic —high impossors or five impossors unbalanced 150 2501 T sut —high impossors high level	
Micrographica Precedence	Yes	No	Yes	Vary	
Output Impedance	t6 OHM,25 VOLT UNE (6,25 OHM) 70 VOLT UNE (50 OHM).	411 611 25 Volt line (623) FO Volt line (6002)	81) 25 Voll Line (float (mis) — 715 70 Voll line (float (mis)—1660	80 25 Velt line (Reat vsp)—210 72 Velt line (Neat mg)—(56)	
Fraguency Response	2 78h 20Mz to 20kMz	+0246, 30Hz to 25 little	- 0 260, 50Hz 60 25M4z	+ 0 340. 2014r to 191	
Bertsdoning	Mes 4MV (HI-Z) Aura, 3MV (HI-Z) BREGING: 1 VOLT	Mig: EmV (In E), 6mV (Lo E) Rus. EV	Afric Smitt dip 23, britt (Lo 23 Age: 37	Mrs. 2 Sant (Mr. ID. Ann right ID Ann 2V	
Temp Epotral Num & Marts Bullow relies outputs	-124b et 10sing Mic -454b Nur -704b		—L2db at 10kHa Mist — 61db Aus — 70db	— 18db at 10kHz Mrc —65db Aus —10gb	
Sameanductors	Pin Tryesisters.	8 Fransislans.	12 Transiques	® Transistors	
All Silicon	7 Diedes	4 Diodes	5 Diades	E Diddes	
Panels; 120 Vales AC 68 Cycles	130 WATTS	35 Watts	95 warrs	05 Watts	
SAVE	15½×10×6-1/8**	91/1 • 3" • 31 16"	135," = 10-7/8" + 3.1, 16"	13%" - 103/8" - 19/1	
Shaping Weight	26 US.	1 ths	11 hs	38 fbs	
Stack Pagel Mounting	No	with RPH L Ka	with MPH 2 Rd	with RPN 2 Kd	

### FEDTRO HIGH QUALITY TRANSISTORIZED MEGAPHONES

Go with FEDTRO...the proven sound of champions

INDUSTRY - SPORTS MARINE



FEDTRO...THE WORLD'S LEADING SUPPLIER OF TRANSISTORIZED MEGAPHONES proven sound around the world

FEOTRO MEG-1000, POWERHOUSE TRANSISTORIZED MEGAPHONE \$ 2995 SPECIAL PEATURES: « M Simulation Combustion » Separate Clarity and Fund Quarty » Burneto Carying Siray « Junior Sallary Landing » Sales-Committing Strengtons » Property Volume Control » Parts Publish Saudification

SPECIFICATIONS: - ILLETRIC POWER SOURCE is salts - OUTFUT: 5 wars - BATTURES & Fausingshifting Contact (Incomp. 8796. Gargess & Elizabeth 2 - OUTFUT: 5 wars - PATTURES & Fausingshifting Contact (Incomp. 8746. Lungshift) 2 - SPECIFICATION FOR THE STATE OF THE STATE

FEDTRO MEG-1200 MICRO-MEG POWERHOUSE TRANSISTORIZED \$ 3495" Materproof MEGAPHONE the ultimate in transistorized miniaturization

SPECIFICATIONS: - RECEIVED FORE SOURCE SOURC

FEDTRO MEG-3300 DELUXE POWERHOUSE TRANSISTORIZED MEGAPHONE

PRECIAL FEBRURES: 1 The Dynamic Managhamas, John Builton and Additional -Thing for Managhama Public 1 The Dynamic Managhamas, John Builton and Additional -Thing for Managhama Public 1 Thing For the Property of the State of Contraction of Managhama Public 1 Thing For the State of Contraction of Managhama Public 1 Thing For the State of Contraction of Property of Managhamas and Property of Managhamas (Contraction Complete State of Contraction of Property State of Contraction of Property State of Contraction of Property State of Contraction of

FEOTRO MEG-3600 DELUXE POWERHOUSE TRANSISTORIZED MEGAPHONE

PEUTNU MEG-SOUL DELGAE POWERHOUSE TRANSISTORIZED MELAPHONE SPECIAL PERIODES in Special Processor (1998) and in the Committee of the Committee

FEDTRO MEG-5000 ULTRA DELUXE POWERHOUSE TRANSISTORIZED

FEDTRO MEG-5000 ULTRA DELUXE POWERHOUSE TRANSISTORIZED
MEGAPHONE the finest instrument of its kind in the world
2.5 WATTS
SPECIAL FEATURES \* Space angle out Power 'The Ultimate is Chianty and Yaund Quality \* Preventing
\* Destinative Miles \* Vive 4 Ways \* Partial Grey \* Over \* Shouware \* Fraged Milyart \* Over \* Securities
\* All Research Construction \* Program Visiones Central \* Asstractic Company Story and Minister Condition
\* Instinct Refere to Land U.S. Committee Central \* Asstractic Control \* Story and \* Minister Condition
\* Instinct Refere to Land U.S. Committee Central \* Asstractic Control \* Story and Minister Condition
\* Instinct Refere to Land U.S. Committee Central \* Control \* Instinct Control
\* Instinct Refere \* Inspection \* Programmes \* Instinct Control
\* Sept. Control
\* Land U.S. Committee \* Visiones\* Control
\* SPECIAL PROBLE \* LECTRIC POWER SOURCE \* Synder \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Control U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* Power
\* Rand U.S. Committee \* OutPart 25 with \* AATEENES \* Insulation \* OutPart 25 with \* AATEENES \* OutPart 25 with \* AATEENES \* \* Insulation \* OutPart 25 with \* AATEENES \* OutPart 25 with \* AATE

Shipping Wt. 16 Lbs. Not Mailable

\$61,50

LIST

VALUE

UNIVERSITY

PH

ensen 30 TT DRIVER WITH PH TRUMPET

30 WATT DRIVER MCG-30 Stock No. PH-MCG30

Both For

PH TRUMPET with MCG-40 40 WATT DRIVER Stock No. PH-MCG40 \$4495

McGee money saving offer. PH University trumpet and 30 watt Jensen dri ver, both for \$39.95. Re-entrant horn design gives more useful volume over the entire range. Low frequency cut-off 150 cps. 41" air column length. 85° dispersion. 20-38" bell diameter. 15-3/4" long less driver. The Jensen 30 watt driver unit will take peaks up to 60 watta. Response 70 to 12,000 cps. A regular \$30.00 value driver. Weighs 4½ lbs. Matches 16 ohm output tap. This high efficiency driver can be used with any amplifier from 10 to 40 watts. Stk. No. PH-MCG30

Stock No. PH-MCG40. The University PH Trumpet and a 40 Watt driver, both for \$44.95, 2 for \$86.00. Matches 16 ohm output tap and can be used with any amplifier from 10 to 50 watts. Stock No. PH-MCG40......\$44.95

FANON **MMM-11** 

SOLID-STATE MONO MICROPHONE MIXER

SOLID-STATE STEREO MICROPHONE MIXER

MMS-12 \$ 1 95



This low-cost mixer permits up to 4 high impedance sources to be fed into a single high impedance input. Separate volume control on each input allows fading and mixing. A full 6 dB gain is normal with a minimum input of 1.5 volts. Maximum signal output is 2.5 volts. Inputs take standard 1/4" phono plug. Standard phono photo plug, standard photo pin plug outputs. Standard 9V. battery is required. Black and aluminum, 6" x 244" x 3%".



Four channels allow use with any high impedance microphone, phono, tuner, etc. Stereo or monaural mixing is possible by the stereomono selector switch. In the stereo position, two channels are available on each side for fading and mixing. Inputs take standard ¼" plug. Outputs are through standard phono pin jacks. Maximum signal output 2.5 volts. Operates on standard 9V. battery. Black and aluminum. 6" x 2¼" x 3¾".

### RECEIVERS FOR BACKGROUND MUSIC AND GENERAL PURPOSE

WITH MICROPHONE PAGING



MODEL 834 AND MODEL 840 FM

MODEL 869 AM-FM

NEW: Model 872, with 30 watt RMS power amplifier, Otherwise the same as the Model 869, AM-FM Receiver. Price \$159.95 Model 872

WITHOUT MICROPHONE PAGING



MODEL 858 AM-FM

Model 834 Mono Background Music and Paging Receiver is a complete Solid State High Fidelity Music System consisting of a sensitive FM Tuner complete with AFC, and a self-contained audio amplifier with microphooe preamplifier. The Tuner has a special circuit design that guarantees no drifting. Features include a volume control for program or phonograph music, a separate volume control for microphone level for paging, and a function switch for source selection. A microphone precedence circuit is incorporated so as to suppress the music, if desired, when turning on the microphone. The unit is supplied with a rugged brushed gold aluminum panel and is encased in a sturdy Model 840 is identical to Model 834 except that it has an audio output of 30 watts RMS.

Model 858 Mono Background Music Receiver is a Model 869 is identical to Model 834 except that it has the addition of AM tuning. complete High Fidelity Music System consisting of a sensitive AM-FM Tuner complete with AFC and a self-contained audio amplifier with 7 watts audio output. The Tuner has a special circuit design that guarantees no drifting, also a Volume Control for program or phonograph music, a function switch for source selection, and a sturdy metal cabinet with bronzetone front panel.

All models have illuminated full vision dial-AFC defeat switch-Jack for multiplex adaptation-Additional jack permitting tuner to be used with external amplifier or tape recorder-Tone control-AC convenience outlet. Any of the receivers may be rack mounted with RPK-2 Rack

### TUNERS FOR BACKGROUND MUSIC AND GENERAL PURPOSE



MODEL 805 FM

MODEL 802

MODEL 852 AM-FM

MODEL 807 RECEIVER

Raymer Mono Tuners are designed for 24 hour-a-day continuous service in cold or hot climates. Bulldog AFC Circuitry provides positive no-drift FM operation. Hum and noise level: -55 db. All tuners are housed in handsome tan metal cabinets that may be rack mounted when using Raymer RPK-1 Rack Panel Kit.

Model 807 Mono Background Music Receiver is a complete solid state High Fidelity Music System consisting of a sensitive FM Tuner complete with AFC and a self-contained audio amplifier with 10 watts RMS output. Features include a Volume Control for program or phonograph music, a function switch for source selection, and a sturdy metal cabinet with bronzetone front panel.

Model 858 is identical to Model 807 except that it has the addition of AM tuning.

RECEIVER SPECIFICATIONS


6134 05

TUNER SPECIFICATIONS

10 05

	\$112.95	\$134.95	\$129.95	\$109.95		\$49.95	\$39.95	\$69.95	\$89.95
MODEL	834	840	869	858	MODEL	805	8 02	852	807
Туре	FM Solid State	PM Solid State	AM-FM Solid State	AM-FM SOLID	Туря	FM	FOUR	AM-FM	FM Solid State
Audio Inputs	I mie —high or low impedance unbalanced	I mic—high or low impedance unbalanced.	I mic -high or low impedance unbalanced;	1 phono/aus high impedance	Solid State	Yes	CHANNEL	Yes	I phono/aux high impedagce
	1 phone/aux	1 phone aux	I phone aux	2011	Frequency Range	88 LOB/mHz	MIXER	AM 550-1650hHz	No Pague
Paging	Yes	Yes	Yes	No			4 MICROPHONE		10 WATTS
Output	15 Wates RMS	30 Watts RMS	15 Watte RMS	10 WATTS RMS	Sensitivity	2mV	HI-Z OR	AM: 10mV FM: 2mV	RMS
Output Impedance	80, 25 Volt Line. 70 Volt Line	Bir, 25 Volt Line, 70 Volt Line	811, 25 Vall Line, 70 Volt Line	Str. 25 Volt Line, 70 Volt Line	Frequency Response	20Mz to 20kHz ± 1db	LO-Z	AM 20Hz to 5kHz ± 3db FM: 20Hz to 20kHz ± 1db	FREQ. RES. 50HZ-20KHZ.
Amplifier Frequency Response	504s-20kHz	50H2 70kH2	SOME ZÜNME	50Hz-20kHz	Semiconductor Tube Complement	6 solicon transistors 7 diodes	A L L TRANSISTOR	9 silicon transistors 9 diodes	AL L TRANSISTOR
Semiconductors or Tubes	14 silicon transistors 12 diodes	14 silicon transistors 12 diodes	15 silicon transistors 13 diodes	ALL TRANSISTOR	AFC with on aff Switch	Yes	OUT PUT	Ves	80, 25 Velt Line, 70 Velt Line
Tuner Frequency Range	FM 88 108mHz	FM 88 108mHz	FM: 88 108mHz AM: 510 1650kHz	FM 88-108mHz AM: 510-1650mHz	Jack for Stereo Multiplex Adaptation	Yes	25.000 OHM FREQ. RES.	Yes	FM 88-108mHz AM: 510 1680mHz
Tuner Frequency Response	FM. 20Hz 20kHz ± 1db	FM 20Hz 20hHz = 1 db	FM 20Hz 20hHz ± 1db AM 20Hz 5HHz ± 3db	FM: 20Hz 20hHz ± 1db AM 20Hz 5kHz ± 3db	Artenna Provision	3000	S HZ TO BOKHZ	AM: Suif contained Ferrite loopstick FM 3000	FM: 20Hz 20kHr ± 16t AM: 20Hz-51 Hz ± 3db
Tuner Sensitivity	FM 2mV	FM 2mV	FM, 2mV, AM: 10mV	FM: 2mV AM 10mV			6 DB GAIN		
Power Consumption	30 Watts, LIF Votts AC,	50 Warts, 117 Volts AC	30 Watte 117 Volta AC	60 Watts, 117 Volts	Full Vision Olal	Ves	OVERALL	Yes	FM: 2mV AM: 10mV
	60 Cycles	60 Cycles	60 Cycles	AC. 60 Cycles	Power Consumption	5 Walte	5 WATTS	5 Watte	60 Wetts, 117 Volts AC, 60 Cycles
Size	131 <sub>2</sub> + 101 <sub>2</sub> " + 3.9 16"	13% x 10% x 3.9 16"	13% • 10%" • 3-9-16"	13½" x 10%" x 3-9/16"	Size	9%" x 7" x 3%"	9%" = 7" = 3-1/16"	91/1" x 7" x 31/4"	13%" × 10%" × 3-9/16
Shipping Weight	12 lbs.	16 lbs.	32 lbs.	13 lbs.	Shopping Waight	5 lbs	5 LBS.	5 lbs	13 ths.

RPK-1 RACK PANEL KIT \$11.95



**RPK-2 RACK PANEL KIT** 

RPK-2 RACK PANEL KIT provides the panel and hardware to tack panel mount Models 707, 758, 801-A, 834, and 861. The rack panel measuring  $3\lambda^{\prime\prime} \times 10^{\prime\prime}$  is standard gray hammertone but may be repainted to match or harmonize with other equipment. Shipping weight 2 lbs.

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108

\$13.95

# Grommes-Precision PUBLIC ADDRESS AMPLIFIE

FIERS IN AMERICA WITH FOUR MICROPHONE INPUTS

LATEST MODELS TRANSISTOR SOLIO STATE

3 - MODELS Feature Full RMS Power Rate

4 MIKE INPUTS

ST-100

100 WATT



ST-35 35 WATT

List \$187.50

19 lbs.

ST-50

List \$224,95 25 lbs.

List \$274.59 31 lbs.


All 3 models are in the same case size, 6" H x 15½" W x 10" D. Response 20 to 2 0000 cps, plus or - 1 db. All 3 have 4 low impresponse 20 to 2 4000 cps, plus or - 1 ab. All 3 have 4 low impedance mike inputs and magnetic phone input. All 3 have base & treble tone controls. All 3 have 4-8-16 chm output impedance connections plus 25 volt and 70 volt lines. All are for 117 volt AC operation with hum level a very low 65 db down. Made in U.S.A.

### SPECIFICATIONS ON GROMMES-PRECISION DIIRLIC ADDRESS AMPLIFIEDS

MODELS	ST-35	\$7-90	\$7:100	\$138000	ST-39	5T-00	ST-100
POWER OUTPUT	35 watts Distortion 5%	50 watts Distortion 2%	100 watts Distortion 2%	GUTPUT	4 fl L6 ohms 25 v Line (till ohms)	4 8 16 shirts 25 v Line (12 5 shirts)	4 8-16 ohms 25 v Line 15 25 ohms)
FRE OR ENCY RESPONSE	- 1 Hb 20-20 000 M1	- 1 sb 20 20,000 Mr	* 1 <b>a</b> 20-20,000 Hz	IMPEDANCE	70 volt (143 shins)	79 velf t100 shost	70 volt 150 alerral
NPETS	4 Mic flow imp 1 Mag Phóng 2 Aux Hi Imp In Level	4 Mic Now imp ! Mag Phono 2 Aux Hi Imp Hi Leval	4 Mic (low imp ) Mag Phono 7 Aux Hi Imp Hi Level	TONE CONTROL RANGE	Bass * 15 db 50 cm Treble * 15 db 10,000 cm	Bass ± 15 de 50 cps Troble = 15 db 10,000 cps	Bens = 15 de 50 ops Freble = 15 d 10,000 ops
A MON				SEMI- CONDUCTORS	14 Francistors 2 Glodes	14 Transators 4 Diodes	26 Transistors 4 Diodes
COLSE Balow rated output	Mic—65 db Aux —75 db	Mic—67 db Aux —17 db	Mc70 db Aux80 db	POWER	105-125-volts AC 50-60 Cy.	105-125 voits AC 50 60 Cy.	105-125 voits AC 50-60 Cy.
(EREPTERTY		Mrc—G S mv Phono Aux G (S v Mag Phono S mx		OMENSIONS	15% 1W 6" H 10" D	15% "W 6" H 10" D	15% W 6"H 10"B
IAM	Mic 115 db Arx 60 db	Wic 117 db	Mic-120 db	SAMPPING WEAGHT	29 Rs.	25 lbs.	31 the.

WORKING CLOSE QUARTERS, HAVING TROUBLE WITH FEEDBACK? HERE'S THE AMPLIFER FOR YOU, IDEAL FOR CHURCHES, SCHOOLS, AUDITORIUMS AND ALL PLACES WITH POOR ACOUSTICS.

An amplifier, acoustic equalizer and compression control... for customers who can only afford an amplifier! ACOUSTA-MASTER AMPLIFIER



Bogen's new Acousta-Master" CT Series has acoustic equalization and compression built right in!


ost with a customer, who needed equalization he couldn't efford or a separate compression unit that easn't in his budget

New Bogen CT Series has declarative Agouste-Masses. Five Bail-ten and accuste-Masses. Five Bail-ten and accuste-Masses five Bail-ten accuses volume at the "feodulencas" shall most often cayar leedback. Usable power can be aubstantially increased with cleaner acousted response under the most deflicant conditions.

And Bogen's instantly responsive compression control can be set to maintain volume at any desired level regardrises of input. Inglas offers that non-professional speaker furns away from the mitte, or when he shouls went

The whole Bogen CT Series in 30-, 60- and 100 wet models and a preamp-miser, A8 a silable with high- to low-impersance inputs. Another first from Bogen to give yet and another salver-to-self amplifier hise.





Five equalities filters with slide controls provide unique anti-feedback and tona-control circuit

fall solid-arare sensitraction; silicon transistors and drades used exclusively.

Optional plug-is transformers provide balanced micro-phone inputs of SO, 200 and 500 ohms in CTM Series

Bamota volume and microphono pracedance on two MIC and one AUX input channel with Sogen accessaries. CT-30 \$180.00

CT-100 \$255.00 CT-60 \$210.00 SHIP. WT. 22 LBS. LIST \$350.00

Red panel kit everlable for ract mounting.

500/600-shim religitions like input ar output with accessory WMT-1 transformer.

May be operated from 24 vile source or two 12-velt duto betterles.

Line cord terminated in 3-prong plug pravides outernatic grounding when connected to 0-select electrical outer.

Three-conductor broadcast type connectors provided for input of each MIC channel. Two preamplifiers can be bridged together to increase num ber of inguts.

SHIP. WT., 19 LBS. LIST \$300,00

30 Wat 1 kills at less than 30 W ±2 dh, 60 Hz, —12 kHz at 5% distortion \$1.5 db from 60 Hz to 12 kHz.

2 Jb. 18 allicon translators.

16%"Wx 12%"Dx414"H.

19 lbs. Resettable Circuit Breaker. 1.25A

60 Wat 1 kHz at less than 2% distortion 60 W ±2 db, 60 Hz, —12 kHz 41 5% distortion ±1.5 db from 60 Hz to 12 kHz. 2 db 2 db 120 V, 50/60 Hz. 1,6 A, 170 W. 20 silicon transistors. Ezener diode, 7 silicon diodes 16%" W x 1334" D x 414" H

22 lbs. Resettable Circuit Breaker 2.5A.

100 Was I kHz at less than 100 W ±2 dh, 60 Hz, —12 kHz at 5 ff distortion. ±1.5 db from 60 Hz to 12 kHz. LIR db 2 db 2 db 120 V, 50/60 Hz, 2.9 A, 300 W. 22 silicon transistors, 1 Zener diode, 7 silicon diodes, 1636° W x 1334° D x 454° H. Resettable Circuit Breaker.

HI-Z MIC, 3mV; LO-Z MIC, 0.3 mV, Bridging Input, 30 mV; AUX, 0.3 V. Bridging, 30 mV; Tape, 0 68 V.

Bridging, 30 mV; Tape, 0.68 V. MIC, 60 db below rated output for both low and high impedance; AUX, 70 db below rated output; Fundamential. 80 db below rated output, 4 H1-Z MIC inputs, each convertible to I,O-Z MIC; 2 AUX inputs with fader control; Bridging input; 500/600 It telephone line with optional WMT-1 accessory; 2 inputs for remote volume control. 4, 8, 16-ohm speaker taps; 25-volt CT and 70 V halanced liner. Tape, booster and bridging outputs; 500/600 It telephone line output with WMT-1 optional accessory.

4 MIC Volume: AUX 1/AUX 2—rader; MASTER VOLUME: 5 Equalizer Filter Side Controls; 1 Limiter; 1 Power Switch; 1 Indicator Lamp.


±10 db variation at the following frequencies: R0, 300, 1 kHz, 5 kHz, 10 kHz,

LOW IMPEDANCE TRANSFORMERS: WMT-1, TELE- LINE 500/600\$11.85 TM-50.80 PHM \$13.30, TM-200, 200 OHM \$13.30. TM-500, 500 OHM \$13.80

McGEE'S IMPERIAL HEAVY DUTY PUBLIC ADDRESS AMPLIFIERS

Made In U.S.A

All are same physical size and have same number of controls



### MODEL WRS-35A 35 -WATT PA AMPLIFIER

SPECIFICATIONS

Frequency Response 4.0 —208 20 to 20,000 CPS frequency Response 4.0 —208 20 to 20,000 CPS frequency Response 4.0 —208 20 to 20,000 CPS frequency Response 5.2 microphone (high impondance) phono, auxiliary, Mag. phono .01V Certrels, Microphone 1, Microphone 2, Phono and Auxiliary Fader, Marter Volume, Bass, Trable, Poner Swritch, Output Indicator Level Adjust, Mic. 2 - Mag. Phono Swritch Tone Central Bange Bass 4 8 to —15 08 @ 50 CPS, Treble 4 7 to —13 DB @ 10 Microphone A 8 18 https://doi.org/10.000.000.000

Dutput Impedance 4, 8, 16 ohms, 25 volt (18 ohm) 70 volt (143 ohm) lines, high impedance for booster amplifier

nign imperance for posser amplifier.

Output Regulation. 208

Hom and Narier Phases: 7009, file: 6008 below rated output

Tubes and Diades 2 - 6017, 604, 2 - 7868, 5 silicon rectifiers

Power Sacres: 105 - 1259 AC 50:60 cycles - 135 watts Dimensions 15%"W x 6"H x 10"D

### MODEL WRS-60A 60-WATT PA AMPLIFIER McGEE SALE PRICE

SPECIFICATIONS

Dutput Impedance: 4, 8, 16 ohms, 25 volt (10.4 ohm), 70 wilt (84 ohm) lines high impedance for booster amplifier

high impedance for booster amplifier

Output Regulations 209

Hum and Reise: Phono 73 08 Mile: 63 08 below rated output

Tubers and Diedes: 2 - 6EU7, 6C4, 2 - 6GF8, 0A2, 5 silicon rectifiers

Power Saurce 105 - 125V AC 50-60 cycles - 200 watts

Dimensions: 15½ W a 5 H a 1010

### MODEL WRS-100A 100 -WATT PA AMPLIFIER McGEE SALE PRICE

SPECIFICATIONS

Pawer Octaut: 100 watts

Pawer Detput: 100 wats
Frequency Response: 40 —208: 20 to 20,000 CPS
Inputs: 2 microphones 0 migh impedance! phono, ausiliary, mag. phono
Seasitivity: Micr. 0,039; Phono and Ausil. 39; Mag. Phono: 0,139
Controls: Microphone 1, Microphone 2, Phono and Ausiliary Fader, Master Volume,
Bass, Troble, Power Switch, Output Indicator Level Adjust, Mic 2 - Mig. Phono Switch
Tone Control Range: Bass +8 to —1508 @ 50 CPS; Troble +7 to —3308 @ 10,000 CPS

Output Impedance 16 ohms, 25 solt (6.25 ohm) 70 solt (50 ohm) lines, high impedance for booster amplifier Output Regulation: 208

Output Impedences

Circuits:

verput negatation: 208

Hom and Mritt: Phono 75 08, Mile; 65 08 below rated output

Tubrs and Diodes 2 - 6EU7, 6CA, 4 - 6GT5, DA2, 5 silicon rectifiers

Power Saurce; 105 - 1259 AC 50-60 cycles - 300 watts

Dimensione: 15 ½ W x 5" H x 10" D

Skipping Weight: 28 lbs.



### FOUR-SPEED MATCHING PHONO TOP FITS TOP OF ALL IMPERIAL AMPLIFIERS

Complete record player with turnover cartridge, 45 rpm adapter. Automatic off-on switch. Motor, turntable and tone arm all mounted on rigidized plate, spring-cushioned. Fastens to top of amplifier models \$-35, \$-60, \$-100. For 110-125 volt, 60 cycle AC.

Dimensions 4½ "H x 11½" W x 8½" D

Shipping weight 7 lbs.



Amplifiers for P.A. Pool Power Output 40 worths Music Systems Frague

40-Watt RMS. 80-Watt Peak Power Transistorized Amplifier Model \$8995

Powerful solid state amp her features 2 mike inputs with separate controls, plus 2 auxiliary inputs with fader, master volume, bass & treble controls, 110-120, 50-60 cycle AC operation. MANUAL TRANSISTORS ARE BROTECTED BY A MANUAL TRANSISTORS ARE BROTECTED BY A

Fraguency Response 50-20,000 MHz MIDLAND6

Mic. -1, Mic. -2 .... 2me or Full Power

Mic. -1, Mis. 2 2mV or Full Power PHONO 300mV at Full Power AUX 300mV at Full Power 4, 8, 16 ahm 25 and 70 Volt Line

Outputs
Alic 1, Volume central
Alic 2, Volume central
PHOND/AUII Volume central
Master Volume Central
Irebin Tone Central
Base Fone Contral

WATT

35-Watt AC Power Model 13-635

**Power Output:** 30 Warrs RMS Model Manie Passacc 35 Worm 13-635

Freevency Response 30 45,000 MHz \$ 6 9 9 5 Mic 1, Mic. 2 AUX/PHONO

Mic. -I., Mic. 2 5mV at Full Power PHONO 300 mV at Full Power AUX 300 mV at Full Power

P. A. Amplifier 8, 16, 250 chm and 20 Valt Lin Outputs Output Impedance:

Mic. I., Volume control
Mit. 2, Volume control
PHONO/AUX Volume control
Master Volume Control
Trabla Tane Control
Bass Tone Control 7-Jube, 2 Sillicon Diode.

WATT

High quality P.A. amplifier features 2 microphone inputs with separate controls, plus 2 auxiliary inputs with fader,

master volume, bass & treble controls. Medium power uses such as bands, combos. 110-120 Volt 50-60 cycle AC operation. A RUGGED TUBE TYPE AMPLIFIER WITH PUSH.

Specifications for Model 502 Microphone/Transmitter

Frequency Range Standard Frequencies:

25 45 MHz 30.84 MHz, 31 36 MHz, 33.14 MHz, 35.02 MHz 26 25 MHz (broadcast use only) otherwise same/wit: floored Heapensies available

HOTE: 33,84 MHz suppleed unit to the 73.45 MHz range

Fower Input: Frequency Busintien: Microphone Coment Audio Frequency New 200 mW (100 mW radiated) ±, 20 kHz at seemal voice levels p. 20 late at mormal voice levels Ceramic 20:20,000 Mr ± 1 dB 125 or reunelent 12 18 hours up to 1000 feet 1" duemetr, 51(\* long 7 owners i Shipping weight—I pound) 7 owners i Shipping weight—I pound) Battery: Battery Life. Transmission Ranga:

Specifications for Model 504 Transmitter

Frequency Range: Standard Frequencies:

23-35 WHZ, 31 16 MHz, 33 14 MHz, 35 02 MHz 26:25 MHz (troodcast ask only) otherwise socials. Suppose Heavencies realistic

MOTE 32 14 MHz traplied w

on the 25 85 this; Powel I liput; Frequency Deviation. Audio Frequency Risponse Input Impedance; Input Level; Battery, Ele, Transmission Ronge, Dimensions. Dimensions. Weight:

200 mile (100 mile radiated) ± 2G lifts at normal voice 20 20 000 Mz ± 1 dB 30 600 chms 40 dBm to -- 70 dBm 286 of equivalent £2-18 hours up to 1000 feet 2" a 34" x 1" 7 ounces (Shipping weight—£ pound)

Made to use with any audio amp.

WIRELESS For 1971 MICROPHONES VEGA ELECTRONICS

Specifications for Model 503 Microphone/Transmitter 25.45 MHz 30.86 MHz, 31.16 MHz, 33.14 MHz, 35.02 MHz 26.25 MHz (broadcast ast cally) a attention specified. Special frequencies socilegies

note 11 14 May supplied a on the 25 45 MHz rac 200 mW (100 mW radiated) net 8595.00 ± 20 kHz at normal supre-levels
Dynamic Cardinol Shure 555-A
20 20,000 kHz 3 lib
126 or equivalent
12-18 hours
up to 1000 feet

Fower Input,
Frequency Desirtion;
Microphona Element,
Rudio Frequency Response, Battery: Battery Life: Transmission Ronge:

1" diameter, 5%" long 7 ounces (Shipping =eight--- a gound) Specifications for Model 501 FM Receiver

**FM Frequency Ranges** 

Intermed-ate Fraquency; Automatic Fraquency— Control Range; Sensitivity; Signal Questing (Squelch); Audio Fraquency Response Signal-to-noise Batte; Destoriani;

men sions Weight Remote Control; (optional) 25-45 MHz Continuous luning from 25-28 MHz or from 30 37 MHz 10.7-MHz

± 100 bHz
0 5 M×crovoli
Codell squelch of normal squelch
20 20,000 Mz ± 2 dB
> 70 dB 2% (complete system) Mike teret —50 dBm 200 tt balanced Line level 0 dBm 600 12 belanced

0 dBm 49/23 uses a use of the Monator I mm, 600 31 unbalanced Collapsube in polemena supplied 24 standard equipment External antenna mey be used Rec valgable inchet cadmium 120 volts 50/50 Me 5 = 11 (220 volts on spannal order) 55/7 e 4 Me 7 = 8 mey campaigned to the collapsub for the monator of the campaigned to the collapsub for the monator of the campaigned to the ca \$570.00

5 pounds (Shipping weight—7 pounds)
Vegatori \* carrier operated relay plus remote signalling relay operated by push button on fransmitter



System 506 includes Model 501 FM Receiver and Model 503 Micro-

net \$370.00 0 -1 - 0 -

System 507 includes
Model 501 FM Receiver
and Model 504
Extern 1 lew less
Transmitter
milk required.

## PORTABLE CARRYING CASE



SALE PRICE

ARGOS SC-2C For use with WRS-35A WRS-60A WRS-100A

IMPERIAL AMPLIFIERS Stock No. SC-2810, Portuble Speaker case with two 12', 10 oz. Ceramic magnet speakers, plus 25

feet of wire per speaker. Connecting Plugs, attached for any of above Amplifers.

STOCK NO. SC-2S 10.... \$44.95

### BOGEN SOUND SYSTEMS

### FLEX-PAK\* DELUXE PA AMPLIFIERS



Li st Price \$380.75 \$243.00



MX60A/MX30A Shown with MMS-1, Monitor speaker, 529,90 extra

MX60A List Price \$401.75

MX30A

\$210.00



Shown with MSK-1 Monitor speaker

M330A List Price \$220,50

M60A List Price

\$288.75 \$180.00

	M120	MX60A	MX30A	M330A	M60A
POWER	120 w. rms @ 3%	60 w. (g) 2% (Ful) pwr. 2) 30,000 cps ±1 db)	30 w to 2% (Full pwr: 21 40,000 cps = 11/2 db.)	30 w. @ 2%	60 w. & 3%
PEAK POWER	200 watts	85 watts	50 watts	50 watts	100 watts
POWER CONSUM.	320 watts	180 watts	125 watts	120 walts	160 watts
FREQ. RESPONSE	±1 db, 20-20,000 Hz	±11/2 db, 10-38,000 cps	± 2 86, 10-40,000 cps	- 2 db, 20-20,000 cps	± 2 db, 20-20,000 cps
SENSITIVITY	Mic.: 9 MV; Mag.: 24 MV; Aux.: 0.4-v	Mic.: 3.5 MV (high imp); Mag.: 2 MV; Aux.: 0.15-v	Mic.: 3.5 MV (high imp); Mag.: 2 MV, Awx.: 0.15-v	Mic.: 6 MV; Map.: 50 MV; Aux.: 0 3-v	Mic.: 9 MV; Mag.: 24 MV; Aux.: 0.4-v
GAIN	Mic.: 125 db; Mag.: 118 db; Aux.: 99 db	Mic.: 125 db: Mag.: 120 db; Avx.: 85 db	Mic.: 125 db; Mag.: 120 db; Avx.: 85 db	Mic.: 120 db; Mag.: 105 db; Avx.: 95 db	Mic.: F22 db; Mag.: 115 db; Aux.: 96 db
HUM and NOISE (below rated output)	Mic.: -65 db; Mag.: -65 db; Aux.: -80 db	Mic 70 db	Mic 70 db	Mic65 db; Aux 80 db	Mic 65 db; Aux80 db
INPUTS	3 mic. (convert to low impedance with T200, T500 or T50 transformer or 2 convert to mag.); 1 aux. channel (2 inputs fader control); 1 600-ohm balanced telephone line with WMT-1 transformer, Note: 4 inputs can be simultaneously mixed and faded.	4 mic, (convert to low Impedance with T200, T500 or T50 transformer); 1 mic, (high imp., or mag, tape); 2 aux, (high imp. high	4 mic. (convert to low impedance with T200, T500 or T50 transformer): 1 mic. (high imp or may, tape); 2 aux. (high imp. high i	3 mic, (high or low imp. — 2 convert to mag.); I auu, channel (2 inputs) fader con-troll); I 600-ohm balanced felephone line with WAAT1 transformer, Note: a Inputs can be simulfaneously mixed and faded.	3 mic. (high or low imp. — 2 convert to meg.): 1 aux, channel (2 inputs) fider control): 1 600-ohm balanced telephone line with WAT1 transformer. Note: 4 inputs can be simultaneously, mixed and faded.
OUTPUT IMPEDANCE	8. 16 ohms, bal'd 25-v (5 ohms), bal'd 70-v (41 ohms), bal'd 25-v center tap (1.25 ohms); tape booster jack	4, 8, 16 and 83 ohms, balanced 25-v. line, balanced 70-v. line	4, 8, 18 and 163 ohms, balanced 25-v. line, balanced 70-v. line	4, 8, 16 ohms, balanced 25-v (16 ohms), 70-v (163 ohms)	4, 8, 16 ohms, balanced 25-v (16 ohms), balanced 70-v (82 ohms)
CONTROLS	3 mic. • aux. 1-2 • master vol. • bass • treble • power switch • provision for remote control or precedence for mic.	d individual mic. (each with speech filter switch) = 1 mic/mag,/tape with speech filter switch) = 1 mic/mag,/tape with speech filter switch = aux. 1/aux, 2 = master vol. 2 = master vol. 2 = master vol. 2 = master vol. 3 = power switch = call-brated fow freq. cut-off of all inputs = provision for remote control or precedence of all six inputs and master vol.	d individuat mic. (each with speech filter switch). 1 mic./ mag /tape with speech filter switch). 2 mic./ mag /tape with speech filter switch aux. I/aux. 2 = master vol. a bas's treble = Dower switch = calibrated low treq. (filter (variable) determines low freq. cut-off of all inputs. = provision for remote control or precedence of all six inputs and master vol.	3 mic. • asrx. 1/2 • master vol. • bass • treble • power switch • provision for remote control or precedence for mic.	I mic. • aux. 1/2 • master vol. • bass • freble • power switch • provision for remote control or precedence for mic.
TONE CONTROL ACTION	Treble (10 KHz) —12 db to —14.5 db; Bass (50 Hz) —15 db to —9.5 db	Treble (10 kc) +13 db to -15 db; Bass (50 c) +15 db to -10 db	Treble (10 kc) +13 db to -15 db; Bass (60 c) +15db to -10 db	Trebie (10 kc) +10.5 db to -14.5 db; Bess (50 c) +13.5 db to -9 db	Treble (10 kc) + 12 db to -15.5 db; Bass (50 c) + 15 db to - 9.5 db
TRANSISTORS or TUBES	7 tubes: 4—8417. 1—7247. 2—6EU7 plus 3-silicon rectifiers	8 tubes: 3—12AX7A, 3—7247, 2—8417 plus 5-silicon rectifiers	8 tubes: 3—12AX7A, 3—7247, 2—7868 plus 5-silicon rectifiers	5 tubes: 2—7868, 1—7247, 2—6EU7 plus 2-silicon rectifiers and 1-bias silicon diode	Stubes: 2—8417, 1—7247, 2—4EU7 plus 2-silicon rectifiers and 1-bias silicon diode
DIMENSIONS	161 2" W, 12" O, 434" H	161/2" W, 12" D, 43/4" H	161/2" W, 12" D, 43/4" H	14%" W, 9%" D, 5%" H	147/e"W, 97/e"D, 53/4" H
SHIP. WEIGHT	36 lbs.	40 lbs	34 lbs.	20 lbs.	28 lbs.
	NOW NOW	Concent in	Super Thin	Loud Speak	ker Designs



SYNCHROCOM CONFERENCE Magitran Conquers Speaker Space PHONE

Write for Brouchure for complete details.

# A new dimension in phone communicatio

Conference Calls

Calls be flick of a switch, up to five people (no ey are located) are conferencing with you ther helping you make those all-important if you are out of your office, your secre your conferences is seconds, and connect

Transfer Calls

WATS Line. Call your office and Conference Caller auto matically ties you into your WATS Line; slashes long distance phone charges and time.

000000000000000

ory Capabilities — I his unique feature alka I your phone conversations and confere

nchroCom Conference Caller can be installed on dial or touch tone multi-line support of the companible with phone company equipment, and is

New Concept in Super-Thin Loud Speaker Designs



RINCH POLY PLANAR SUPER-THIN SPEAKER and BAFFLE STOCK NO. PPT-8

SPACE SAVING COMBINATION 8 ohm, voice coil impedance SPECIALLY MADE TREND EXTRA THIN BAFFLE AND A SUPER THIN MAGITRAN 8" POLY-PLANER SPEAKER IDEAL FOR PATIO, RECREATION ROOM AND ANY OTHER WALL
INSTALLATION. THIS SPEAKER IS SO CONSTRUCTED THAT IT
WILL REPELL MOISTURE ON THE FRONT SIDE. (most cone type
speakers will not lost under wet weather conditions.)

EXTRA THIN WALNUT FINISHEO WALL BAFFLE, WITH FULL SIZED CANE GRILLE CLOTH FRONT. THE EXTRA THIN SPEAKER AND BAFFLE IS ONLY 1½" THICK AND 10½" SQUARE. MOUNTS FLUSH TO THE WALL, MOUNTING HANGERS ARE FURNISHED.

GIVE PAGE NO., AND STOCK NO., WHEN ORDERING

### BOGEN SOUND SYSTEMS



100 WATT PA AMPLIFIER List Price \$267.00

\$171.00

**CHS 100** 

105-125 v. 50-60 Hz

50 WATT PA AMPLIFIER List Price \$216.50



**CHS 50** 105-125 v. 50-60 Hz

> 35 WATT PA AMPLIFIER List Price \$178.25

\$115.50

CHS35 & CHS20

Can be used

70 T . . .

**CHS 35** 105-125 v. 50-60 Hz 12-15 VDC @ 3A

20 WATT PA AMPLIFIER List Price \$156,75

2 20 2 4


Mobile

CHS 20 105-125 v. 50-60 Hz 12-15 VDC @ 2A

# Challenger


### BEST \$ VALUE FOR \$ SPENT Challenger "CHS" series SOLID STATE PA AMPLIFIERS

	CHS 100	CHS 50	CHS 35	CHS 20
POWER DUTPUT	100 W. or 5%	50 W. 44 5%	35 W. # 5%	20 W. 6 5%
PEAK POWER	200 W.	100 W.	70 W.	40 W.
FRED. RESPONSE	40-20,000 Nz = 2db	40-20,000 Hz ±2db	50-15.000 Hz ≃ 2db	50-15.000 Nz ±2db
SENZITIALLA	Mic. (Lo-imp.) 0.3 mv Mic. (Hi-imp.): 4.0 mv. Am. 0.3 v. Bridging: 1.0 v.	Mic. (Lo-imp.): 0.5 mv. Mic. (Hi-imp.): 3.0 mv. Aux., 0.2 v. Bridging, 1.0 v.	Mic. (Lo-imp.): 0,6 mv. Mic. (Hi-imp): 4.0 mv. Aux. 0.5 v. Bridging: 1.0 v.	Myc. (Lo-imp.): 0.6 mv. Mic. (Hi-imp): 4.0 mv. Aux.: 0.5 v. Bridging: 1.0 v.
INPUTS (impedance)	2 Mic. (Ni or Lo imp. unbal.) Hi imp.: 100k ohms Lo imp.: 200 ohms Aux (2 inputs on fader): 300k ohms Bridging: Hi imp. (1.0 v.)	2 Mic. (Hi or to Imp. unbal.) Hi imp. 100k ohms to imp. 200 ohms Aut.: (2 imputs on fader): 300h ohms Bridging: Hi imp. (1.0 v.)	2 Mic. (HI or to long, unbat.) Hi imp.: 100k ohms to imp.: 200 ohms Aux: (2 inputs on fader): 300k ohms Beldging: Hi imp. (0.6 v.)	1 Mic, (Hi or Lo imp. unbal.) Hi imp.: 100k ohms Lo imp 200 ohms Aun. (2 inputs on fader): 300k ohms Bridging: Hi imp. (1.0 v.)
See Page 46 for BIG VALUE in Solid-State P.A. AMP.	2 indiv. mic. (plus 2 on PMA-2 preamp.) 1 vol. (fader) for Aux. 1 and 2 Master Volume Bass Trebie Power Switch Provision for remole control or mic. precedence (all impuls)	2 indiv. mic. (plus 2 on PMA-2 preamp.) 1 vol. (lader) for Aux. 1 and 2 Master Volume Bass Treble Power Switch Provision for remote control or mic. precedence (all inputs)	2 indiv, mic. (plus 2 on PMA-2) preamp.) I vol. (fader) for Aux. 1 and 2 Master Volume Bass Trable Power Switch Provision for remole control or mile, precedence (all inputs)	I mlc. (plus 2 on PMA-2 preamp.) I vol. (tader) for Aux. 1 and 2 Master Volume Bass Treble Power Switch Provision for remote control or mic. precedence (all inputs)
GUTPUT IMPEDANCE	2, 8, 16 ohms 25 v. bal. (e.t.) = 6 ohms 70 v. bal. = 49 ohms 2 quel-disconnect sockets and screw terminals. Tape/Booster 10k ohms 5.0 v. Bridging: Hi imp. © 0.5 v.	4, 8, 16 ohms 25 v. bal. (c.t.) = 12 ohms 70 v. bal. = 100 ohms 2 quick-disconnect sockets and screw terminals 7ape/Booster: 10k ohms 5,0 v. Bridging: fir imp. @ 0.5 v.	4, 8, 16 ohms 25 v. = 16 ohms 70 v. = 143 ohms 2 queh-disconnect sockets and screw terminals Tape /Booster-10k ohms 5.0 v. Bridging: Hi imp. ⊕ 0.5 v.	4, 8, 16 ohms 25 v. = 31 ohms 70 v. = 250 ohms 2 quich-disconnect sockets and screw terminals Tape/Booster: 10k ohms 5,0 v. Bridging Mi imp, © 0.5 v.
TONE CONTROLS	Bass. +10db to -10db # 50 Hz Treble: +10db to -10db # 10 KHz	Bass: +10db to −10db @ 50 Nz Treble: +11db to −12db = 10 KMz	Bass: + 8db to -23db ⊕ 50 Hz Treble: +8db to -15db ⊕ 10 KHz	Bass: +8db to -19db & 50 Hz Treble: +12db to -15db & 10 KHz
NUM & NOISE (below rated output)	Mic.: 65db Aux.: 70db	Mic. 67db Aux.: 70db	Mic.: 64db Aux.: 67db	Mic.: 66do Aux.: 70db
POWER CONSUMPTION	105-125 v. 50-60 Hz	105-125 v. 50-60 Hz	105-125 v. 50-60 Hz 12-15 VDC @ 3A	105-125 v. 50-60 Hz 12-15 VDC @ 2A
SEMI-CONDUCTORS	Total 14 All-silicon	Total 12 All-silicon	Total 11: 9 silicon 2 germanium	Total 10: 8 silicon 2 germanium
DIMENSIONS	51/2"Hx101/2"Dx151/4"W	51/2"Hx101/2"0x151/4"W	51/2"Hx101/2"0x151/4"W	51/2"Hz 101/2"Dx 151/4"W
SHIPPING WEIGHT	24 lbs.	21 lbs.	J17 lbs.	15 lbs.











(O) RACK PANEL MOUNTING KITS — Available for all Bogen amplifiers and tuners. Finished in trey metallilistre.

Equipment	Rack Paper	Size	LIST	NET
CHB100, CHB50, CHB35A, MU1250	APK-14	19" x 7"	\$37.40	22.45
CHB20A	RPK-15	19" x 7"	37.40	22.45
MTX308, MX60A MX30A, M120, MXM-A	RPK-16	19" x 7"	37.40	22.45
MO200A, MO100A, MO30A, MT100, MBT60	RPK-18*	19" x 7"		22.45
RTP-I	RPK-20	19" x 3"2"	29.90	17.95
M330A M60A	RPK-21	19" x 7"	34.90	22.45
MTAto	RPK-23	19" x 7"	*84.90	20.95
MTA30 MTA60	RPK-24	19" x 7"	37.40	22.45
MTM	RPK-26	19" x 514"	34.90	20.95
CH5100, CH550; CH535, CH520	RPK-27	19" x 7"	37.40	22.45
MX6A-T	RPK-28	19" x 7"	34.90	20.95

(L) PMC-1 — Plug-in magnetic cartridge module for use with MTA30, MTA60 and MTM. Converts mic. input to mag. phono/tape. List \$14.90 \$8,95 Net \$8,95 Net

(M) PMA-2 — Panel-mounted preamplifier for CHS100/50/35/20; provides 2 additional high or low impedance mic. inputs — each with votume control. No transformer required for low impedance mics. Knobs appear on front panel of amplifier. List: \$34.96 \$32,95 Net

Knobs appear on front panel of amplifler. List: \$34.99 \$32,95 Net

(8) PEAK LIMITERS — LYP-1; in addition to its use as a remote controller of Aux imputs (with RVC-1) in MX50A, MX30A, a second chassis socket permits installation of another LVP-1 to provide automatic limiting of amplifier output to any predetermined level. Mx50A, Mx30A have built-bin limiter sensitivity control.

List: \$11.25 \$6.75 Net

PYP-1: provides automatic limiting of output of MTM preamplifier to any predetermined level. (Requires 1LVP-1). List Price: \$13.75 \$8.25 Net


MMS-1; monitor meter and speaker for models MTX30B, MX50A, M330A — allows operator to check sound levels both by ear and by eye. List: \$48.85 \$29,90 Net

MSK-1: monitor speaker for models MTX30B, MX50A, M330A, M330A, M30A, M30A — allows operator to check sound levels. List: \$14.80 \$8.95 Net

\$8.95 Net (J) STANOBY CONTROLLER - Lengthens amplifier life, reduces high voltage power consumption

LIST NET Stand by Controller MU200A, MO100A \$62.50 41.25

# OGEN



### SELF-POWERED/ALL SILICON SOLID STATE

\$83.75

MX6A-T MIXER-PREAMPLIFIER

ADD UP TO 4 MICROPHONES TO SYSTEM
This practical, efficient and eco inficial mixer will
allow you to add four more signals (high or low impedance mikes, guitars, phono players, tape recorders, etc.) by simply plugging them in.

SPECIFICATIONS:

Frequency Rasponse: 50 — 20 kc =2db Output: 6V. @ 2% 4V. @ 1%

SPECIFICATIONS:
Gain: Mic. (high-imped. —60 db) —4 dw. @ 4V. output
(low-imped. —80 db) —0.4 mv. @ 4V. output
Aux. —20 db —0.4V. @ 4V. output

Hum/Naise: 68 db below SV. Semiconductors: 6 transistors, 2 diodes (all silicon)

Finish: Black textured enclosure, chrome plated pol-ished steel front panel

Dimensions: 91/4" x 6" x 21/4" Shipping Weight: 5 lbs.

### "CHB" SERIES PA AMPLIFIERS

Models CH8100, CH81250, CH850 and CH835A share these outstanding features: systems-lested circuitry for continuous, heavy-duty operation; protection against circuit damage caused by accidental shorting or disconnecting of loudspeaker lines; no "fouble duty" control devices; built-in remote control circuit permits volume adjustment from up to 2,000 feel away; Memory Level Markers.

	CHB100	CHB50	CHB35A	CHB26A
POWER	100 w.	50 W.	35 w.	20 w
OUTPUT	at 5% distortion	at 5% distortion	at 5% distortion	at 5%
FREGUENCY				distortion
FREQUENCY RESPONSE	±2 db, 20 lo 20,000 cps	±2 db, 20 to 20,000 cps	±2 db, 20 lo 20,000 cps	± 2 db, 20 to
WEST ONSE	zu,uou cps	20,000 Cp3	zo,ooo cps	20,000 cps
	2 Mic. (hi-	2 Mic. (h)	2 Mic. (hi-	
	impedance! 1 Mag.	Impedance) 1 Mag.	Impedance)	† Mic. (hi- impedance)
	Phone	Phone	1 Mag. Phone	2 AML (his
INPUTS	2 AWL (DI-	2 Aug. (hi-	2 Aug. (hi-	impedance
THI O IS	Impedance	Impedance	Impedance	hi-level)
	hi-level)	hi-tevel)	hi-level)	Provision
	Provision	Provision	Provision	for
	for WMT 1	for WMT 1	for WMT 1	WAT 1
	ANIMIT I	WW.L.1	MWI 1	
HUM &				
HOISE	MJc70 db	Mic70 db		Mic65 db
(below rated	AUX -80 db	Aus80 db	AUL -80 db	AUL -80 db
output)				
	AAJC, 5 mv	Mic. 5 mv	MIC. 4 my	441n A
SENSITIVITY	Asz. 3-V Mag. Phone	AUL .3-V Mag. Phone	AVIL .2-v Mag. Phone	Aex. 5-v
38.437111111	Mag. Phone	Mag. Phone	Mag. Phone	MU13-V
	15 mv	15 mv	12 mv	-
	AAIc. 125 db	Mic. 120 db	Mic. 125 db	
1 N	AWIL 100 db	Aug. 95 db	Mic. 125 db Aul 100 db	Mic. 125 db
GAIN	May. Phone	AUL 95 db May, Phone	May, Phone	Aug. 100 db
	115 db	110 db	115 db	
	4, 8 and 16	4, 8 and 16	4, \$ and 16	4, 8 and 16
	ohms, 25-v	ohms,	ohms	ohms, 25-v
	line bai-	25-y line	25-v line	line balanced
	anced, (6 ohms)	(12 ohms)	(18 ohms)	(3) ohms),
OUTPUT	70-v line	70-V (Ine	70-V line	70-v line
IMPEDANCE	(50 ohms)	(100 ohms)	(143 ohms)	(250 ohms)
	2 speaker	2 speaker sockets and	2 speaker sockets and	2 speaker
	sockets and	screw	SCIEW	sockets and
	SCIEW	terminats	terminats	screw
	terminals	- 11		terminals
	Treble (10 kc)	(10 kc)	(10 kg)	(10 kc)
	± 12 db to	+10 db	+10 db to	+10 db to
TONE	-15 db	to 15 db	-16 db	—16 db
CONTROL	Bass	Bass	Bess	Bass
ACTION	(50 cps)	(50 cps)	(50 cps)	(50 cps)
	+14 db	+11 db	+ 14 db to -10 db	+14 db to
	-0 -7 00	10 10 00		—10 db
			Tetal of 5	
The second	Tetal of 7	Tetal of S	tubes, 2	Total of
	tubes and	tubes and	silican	3 Pubes, 2
TUBES or	silicen rectifier:	silicen rectifier:	Pectifiers and 1-silicon	silicen rectifiers
TRAN-	1-4EU7	1-6EU7	diade:	and 1-silicon
SISTORS	1-12AX7	112AX7	1-6EU7	diode:
	4—7868 1—4C4	2-6L4GC	2-7868	1-6EU7
	1-404	1-6C4	1—12AX7	2—6GW8
			1-4C4	
		100		
	300 w	150 w.	125 W	90 w
POWER	105-125 VAC	105-125 VAC	105-125 VAC	105-125
CONSUMP-	50-60	50-60	50-60 cycles	(VAC)
TION	cycles	cycles		50-60 cycles
			1 470 11 45	63/4" H
DIMEN-	634" H, 1534" W.	63/4" H. 1546" W.	67/4" H. 153/4" W.	1534 " W
SIONS	10" O	10" D	10" D	15%" W.
	100	-10	100	1
SHIPPING	25 lbs.	21 lbs.	21 lbs.	17 lbs.
WEIGHT	25 105.	21 195.	41 103.	

### 100 WATT **CHB100** List Price

\$233.75 148.50

50 WATT CHB50 List Price

\$181.25 \$114.00



CH8100

BOGEN "CHB" SERIES P.A. AMPLIFIER S



CHB50/CHB35A

35 WATT CHB35A List Price \$149.75 \$97.50

FINEST P.A. AMPLIFIERS IN THE WORLD



CH820A

BOGEN

SOUND SYSTEMS



INPUTA CRYSTAL PHOND ONLY

Bogen Challenger new C series All TronsistorPublic oddress at prices near the CHB series.

C-30 C-60 C-100 all have 6 controls and look like picture

MODEL C-100 LIST \$249 95 SAME INPUT AND OUTPUT SPECIFICATIONS AS CHB-100 EXCEPT ALL TRANSISTOR TALL. SHIP WT. 18 LBS. 2 HI Z MIKE INPUTS: AUR. INPUT. BASS AND TREBLE TONE CONTROLS AND MASTER GAIN CONT

MODEL C - 60 LIST ST 99.90 SAME INPUT AND OUTPUT SPECIFICATIONS AS CHB-50 EXCEPT ALL TRANSISTOR.
14 & IN. WIDE 13 EN. DEEP 3 EN.
TALLSHIP WT. 16 LBS. 2 HI Z MIKE
INPUTS. AUX INPUT. BASS AND TREBLE TONE CONTROLS MASTER GAIN

MODEL C - 30 UST \$156.25 SAME INPUT AND OUTPUT SPECIFICATIONS AS CHB-35 EXCEPT ALL TRANSISTOR. 14 1 IN. WIDE 12 1 IN DEEP 3 1 IN. INPUTS. AUX INPUT SASSAND TREBLE TONE CONTROLS. MASTER GAIN CONT.

### MANUAL PHONO-TOPS FOR SERIES MTX, MX MU, CH



MANUAL PHONO-TOPS - Each is complete with all necessary hardware, tone arm and term-over cartridge. The — 3 indicates 3-speed, the — 4 indicates 4-speed.

Ampilier	Phono-Top
MTX30B, MX60A, MX30A, M330A, M60A, M120, MTA30, MTA60, MU130, MXM-A, CHB100, CHB50, CHB35A, CHB20A, CHB10A, CHS100, CHS50, CHS35, CHS20	LPC-4
MU1250, CHS35, CHS20	LPD-3

LIST PHONO-TOP NET \$29.25 I PC-4 \$46.25 LPD-3 Discontinued

LPC-4, 4 Speed Phono-Top In addition to the four standard speeds, (16, 33, 45, and 78 rpm) each speed is adjustable for perfect pitch over a range of plus or > 5% around the nominal speed.

### OGENMobile Amplifiers minimi

### MU1250; 50w Mobile Transistor PA Amplifier

Universal PA amplifier, operates on 12 VDC or 117 VAC, within a temperature range of 20°C, to +65°C. (-4°F, to 149°F). This amplifier offers a variety of inputs: 2 mic., 2 aux., and 1 mag, phono/tape. A host of matching accessories are available: phono-top, control-guard locking plate, rack panel mounting kit, carrying case, and more. Power Output: 50 w. at 10% (continuous). Peak Power: 70 w. Power Consumption: Full power: 116 w. (117 VAC); 6.7 amps. (12 VDC). Quiescent, 16 w. (117 VAC); 3 amps. (12 VDC). Freq. Response: 30 to 15,000 Mz ±2 db, Caln: Mic. 125 db; Aux. 95 db. Hum and Moise (below rated output): Mic. -65 db; Aux. -70 db. Output Imped:: 4, 8 and 16 chms; 25 V. bal. line; 70 V. (122 chms) bal. Inputs: 2 mic. (h) or low imped., no transformer required): 2 aux.; 1 mag, phono/tape. Transistors: 11 transistors and 3 silicon rectifiers. Tone Controls: Treble (10 KM2) -17 db; Bass (50 M2) -10 db to -17 db. Dimen:: 15¾" W, 10" D, 6¾" M, Ship. Wt.; 23 lbs. List Price: 52 96.2 5

### BT35A; 40 w. Mobile Transistor PA Amplifier 55-watts when used as electronic siren,

Excellent for police, fire, CD, and boats; radio receiver connects easily to aux. input. Splash-proof gasket seals chassis in cabinet. Temperature range =20°C, to ±65°C. (149°F.). Polarity protection. Accessory siren tone-tog horn generator. Adjustable fixed-lock bracket. Built-in RF/line filters.

RF/line filters.

Power Outputs 40 w. at less than 10% (continuous); 55 w. with siren generator, Peak Power:

55 w. Power Consumption: Full power 4.4 amps; Quiescent, 0.42 amps 12-15 VDC. Freq.

Response: 150-15,000 Hz = 3 db. Inguts 1 mic. (low imped ½ 1 aux., =1 (high level) sciencestory (tone signal), Galin mic. 110 db; aux, 90 db. Num and

Noise: (below rated output) mic. =90 db; aux. =95 db. Sensitivity: mic. 1 My; aux.: 0.4 V.

Output Imped: 4, 8, 16 ohms (output socket for accessory siren/log hom generator). Controls:

1 mic: 1 aux, volume: 1 selector switch/power (4 position); power off, mic., radio, aux. Transistors: 5 transistors, 1 silicon diode. Oimen: 8" W, 6¼4" D, 3" M. Ship. Wt.: 8 lbs. List Price:

184.80 BT20A; 25w. Mobile Transistor PA Amplifier 🗆

Power Output: 25 watts // less than 10% (continuous), Power Consumption: Full power: 2.8 amps. Quiescent: .26 amps: 6-15 VDC (6 w. output on 6 VDC). Inputs: 1 mic. (low impedance); 1 aux. (tuner, tape, phono). Gains mic., 110 db; aux., 90 db. Hum and Moise: mic. 90 db (below rated output); aux., -95 db (below rated output). Sensitivity: mic., 1 MV; aux., 04 volts. Output impedance: 4, 8, 16 ohms. Controls: 1 mid.; 1 aux./power. Transisters: (5) 2—2N2926 1—40234, 2—DTG-110. Olmensions: 4½" W, 4" D, 6½" M. List Price: 113.25



666666

BT35A

### BOGEN **PREAMPLIFIERS**

1 atest Models

MXM-A MIXER-PREAMPLIFIER







MTM ALL-SILICON TRANSISTOR MIXER-PREAMPLIFIER

Professional, alt-silicon transistor, self-powered unit (operates from 120 VAC or 12-15 VDC). Mixes 6 input signals (4 may be low impedance microphones). Unbalanced low impedance microphone inputs convert to balanced (50-600 ohms) with T525U plug-in transformer - or convert to mag. phono/tape input with PMC-1 plug-in module 2 aux. (high impedance, high level) are connected to a fader control. Up to 3 MTM's may be paralleled to provide 18 inputs. Output level may be monitored aurally (head set) and visually (built-in meter). Sockets accept individual remote control, precedence and compressor plug-in units. Speech filters in mic. channels 1 and 2. R.F. filters in all mic. channels. Temp. range: 20°C to -70°C (158°F). Output: at 0 db: 1.8 V. into 500 ohms (0.5%); at +12 db: 7 V. into 500 ohms (2.5%); output transformer is built-in; no high impedance output. Freq. Response: 40-15,000 Hz  $-1\frac{1}{2}$  db. Output imped.: (split output) 125/150 ohms or 500/600 ohms balanced. Input Imped.: imped.: (spitt output) 125/150 ohms or 500/600 ohms balanced. Input Imped.: Mic.: low imped. unbalanced (balanced with T525U transformer); Aux.: 0.2 Meg. Sensitivity: low imped. Mic. 0.1 MV; Aux. 0.15 V. Gain: Mic. 75 db; Aux. 6u db; Bridging 60 db. Bass Cut: -15 db at 50 Hz. Treble Cut: -15 db at 10 KHz. Hum: Mic.: 65 db; Aux. 70 db. Power Consum.: 5 watts at 117 VAC 50/60 Hz; 12 A at 12 VDC. Transistors: 11 silicon plus 5 silicon diodes. Dimen.: 16¼" W. 8½" D, 3¾" H. Ship. Wt.: 9 lbs.

MTM Preamplifier with five Inputs. List \$249.75, \$156.00

"MO" SERIES BOOSTER AMPLIFIERS

MXM-A MIXER-PREAMPLIFIER

Professional, trooccast quality, sell powerse unit which accommodates x mined logged copents simulationalway (\$6 may be from high are the linguistance alogs). One still: logic converts to an equalized map groups carrivdge or tope playback basis. Two dam: frequency high severt are convected to a loder convers. Bridgings (appl accepts separate from a revolve promptifier or a revolve promptifier and provided to a loder convers. Bridgings (appl accepts separate from a revolve promptifier or a revolve promptifier and provided provided to a provided provided to a loder conversion from conversing high imped to balanced too imped, microchone signific by uning other in trainitional provided too conversion from conversing high imped stop hanced too imped, microchone signific by uning other in trainitional provided too from the provided provided too from the provided too fro \$202.50

RTP-1 ALL-SILICON TRANSISTOR PREAMPLIFIER

Octioned for the tree broadcast quality, the RTP-1 will differ any number of booster amplifiers or packaged amplifiers over 0 500;000 own inter-even several mices away, largets include 2 884c, (high or low impediance), 3 Aim, on footr central, 1 bridging Too, RTP-1's can be paralleled to previde a mixed inquite, Extremely, low battery drafts. Postures include: Hoped plane monitor acids on translational postures are calculated to 10 U and the 112 VAC of 12 UOC operation interiors batteries of extremel DC power supply; Buildelia hartery heater, Previde Orther's at 9 6th; 16 V. into 500 ohms (1/5)/2 of 4/2 fth; 7 V. into 500 ohms (1/5)/2 of 4/2 fth; 7 V. into 500 ohms (1/5)/2 of 4/2 fth; 7 V. into 500 ohms (1/5)/2 of 4/2 fth; 7 V. into 500 ohms (1/5)/2 of 4/2 fth; 500 ohms (1/5)/2 of 4/2 fth; 5/2 of 4/2 ft Dissist 9" W. Ma" D. 312" H. Ship WE: 412 Ms. List Prices 5241.25 \$148.50

BOGEN

MO200A List Price \$500.00 \$300.00

MBT60 List \$216.25 Net \$129.75



MOIDOA List Price \$275.00

M0200A

MODEL MT 100 100 WATT BOOSTER List Price \$425.00



MODEL NTB250 250-350 WATT BOOSTER AMP


LIST PRICE \$875.00



### ACCESSORIES BOGEN FOR PA AMPLIFIERS

PLUG-IN TRANSFORMERS - Microphone and line transformers designed for plug-in use with

Bogen amplifiers





SHIPPING

Heren	MO298A	MOTEGA	MBT60 TRANSISTOR	NTB250	MT180° ALL-SILICON TRANSISTOR BOOSTER
POWER OUTPUT	200 w at less than 2% distortion Full power 21 50,000 cps + 1 db at 5%	100 w. at less than 2% distortion Full Power: 21-50,000 cps ± 1 db at 5%	60 w. at less than 3% distortion 20 C to -70 C (158	at less than 5% from 50-12,000 Hz . 250 w rms at less than 5% from 35 20,000 Hz . 25% w rms	100 w. at 1% Full Power: 29-20,000 cps ±1 db at 5%
FREQUENCY RESPONSE	8-50,000 cps * 1 db	8-50,000 cps * 1 db	12-20,000 cps ±1 db	at less than 3% from 40-5000 Hz e	15-35,000 cps ±1 db
OUTPUT HMPEGANCE	balanced 8 ohms, balanced 25-v (34) C T <sub>1</sub> balanced 70-v (250) C.T and 115-v (660) (for industrial uses)	balanced 16 ohms, balanced 25-v (6,250) C.T., balanced 70-v (490) C.T. and 115-v (1320) (for industrial uses)	Bai 2.5.8 and 16 (10.4 ohms) bai. 25-v C.T bai. 70-v (82 ohms)	### 20-30,000 Hz	belanced 160, belanced 25-v (60) C.T., belanced 70-v (490) C.T. and 115-v (1320) (for industrial uses)
INPUTS	High impedance 0.5 megohms Low impedance: 500/600 ohms with TL600 line transformer	High impedance: 0.5 megohnsLow impe- dance: 500/600 ohms with TL600 line transformer	th imped: 0.1 mag shms, Low imped: 500/600 ohms with TL600 transformer: 10,000 ohms with TL10K transformer	704 (201) 1204 (571), 812 (44 74) For 350 W. output; 704 (14.319) 811 (534.) High imped: 1.44, for 250 W. output Low imped: 600 offms.	High impedance: 0.1 magohms.Low impe- dance: 500/8000 with TL600 trans- former 10,0000 with TL10K transformer
SENSITIVITY	High impedance bet- fer than 2 v. Low im- pedance with TL600 transformer, better than 0.5-v.	High impedance bet- ter than 2-v Low im- pedance with TL600 transformer, better than 0.5-v	High imped: 0.15-v, Low imped with iTL600 transformer, 0.04-v	with TL 600 trans- former, 0.3v, for 250 w, output, 0.35v, for 350 w, output —83 db below 250 w —85 db below 350 w	High impedence: 0.75-v.Low impe- dance: with TL600 transformer, 0.2-v
HUM (below rated output)	80 db	80 db	-78 dfa	29 all silicon transistors.	80 db
TUBES or TRANSISTORS	(10) tubes and (3) silicon rectifiers: 2-7247, 8-8417	(5)-tubes and (3) silicon rectifiers: 1-7247, 4-8417	(7) all silicon translators and (7) diodes	4 stabistor diodes, 7 rectifier diodes, 2 Zener diodes	All-silicon transistors plus 3 zener diodes
POWER CONSUMPTION	500 watts	250 watts	115 watts 105-125 VAC, 50/60 cps	105-125V AC. 50/60 Hz 565 w. (250 w. output) 700 w (350 w. output); 24 VDC a: 25 A. (250 w. output) 171/m" W (19"	Full Power: 215 w. (117 VAC): Guisecant: 50 w. (117 VAC) Full Power: 11.5 amps (14 VDC)
OIMENSIONS	16" W, 111/3" D, 6" H	8" W, 13" O, 614" H	8" W, 13" D, 6¼" H	with furnished brackets). 1135" D. 916" H	8" W, 13" D, 6" H

### REMOTE CONTROLLERS

(A) REMOTE CONTROLLERS — One, two and four-channel remote control units permit mixing, fading and frequent changes in Rem of individual channels, even from distances up to 2,000 feet.

Amptivier Modal	Remote Controller	LIST	NET
MX60A, MX30A, M330A, M60A № 120, MXM-A, MU130, CHB100, CHB50, CHB35A	SR2 (two channel)	19.90	13.4
MX60A, MX30A, M330A, M60A, M12U, MXM-A	SR4 (four channel)	27.50	17.85
MX60A, MX30A, MXM-A, CHS100, CHS50, CHS35, CHS20	LVP-1 ①	11.25	6.75
MT100, MBT60	LVP-1 ®	11.25	6.75
MTX30B, MTA30, MTA60, MTM	LVP-1 ①	11.25	6.75

- ① provides channel muting for precedence or remote volume control (of Aux. channel or master gain) with RVC-1.
- @ provides standby. (with RVC-1, provides remote volume control)
- ② provides channel muting for Mic. precedence (In Aux. channel). Use 1-LVP-1 and 1-RVC-1 in each Mic. channel for remote volume control.
- RVC-1 Remate volume controller (see footnotes () () () above) List Price: \$17.40 Net \$10.45

\* Used with Amplifier Models M330A, M60A, M120, MU130, MTX30B, MX60A, MXM-A, and RTP-1

Used with MT100, MO30A (Run C), MO100A

(Run E), MO200A (Run B)

† Used with Amplifier Model RP-2.

†† Used with MXM-A, MT100A (Run E), MO200A (Run B), MO30A (Run C), MBT-60
†† Used with MTA30, MTA60, MTM to convert unbalanced to balanced Mic Input 50 to 600 ohm.

### CONTROL-GUARD LOCKING PLATE


Tampering fingers will never disturb pre set controls when protected by a unique Bogen Control-Guard Locking Plats.

NET LIST Locking Pleta MU1250, MU130, CHB100, CHB50 CHB35A, CHB20A, CHB14A \$6.65 11.10 MTX30B, MX60A, MX30A, M120, MXM-A LK-6 14.90 LK-8 6.95 MIA30 MIA60 LK-9 CHS100, CHS50, CHS35, CHS20 19,90 11.90



# Microphone Stands, Accessories





No.	Finish	Adjust.	Diameter	Lbs.	Each
MS-10C	Gray Shrivel	35"-63"	10"	10	8.67
MS-12C	Gray Sbrivel	34"-62"	10"	12	9.17
MS-11C	Full-Chrome	34"-62"	10"	13	11.16
MS-14G	Gold	34"-62"	10"	12	14.34
MS-4:	Gray Shrivel	25"-65"	10"	10	13.01
MS-20	Gray Shrivel	37"-66"	12"	15	14.00
MS-25*		38"-67"	17"	22	22.67
CS-1	Cadmium plate	23"-62"	Collapsible	5	17.00
C\$-32	Chrome Legs	36'-64"	Demountable	4	10.34
CS-33/	Chrome Legs	26"-64" 34"-62"	Demountable	9	12.09
CS-42 CS-52	Gray Shrivei Gray Shrivei	34"-62"	15"	9	9.84

telescoping tube, 1 /2 base tube, 1 "Safety Air Lock Cushlon" rents accidental or sudden slippage of telescoping section, collapsible, (Collapses to min. 22 1/2" in 3 sections.

SLEEVE-ACTION STANDS

Provide full automatic means of adjusting the height of the stand, Sight forward pressure on "sleeve-action" control permits towering of telescoping section. Cannot change position without deliberate pressure on the actuating sleeve cootrol.

MS-115 Full Chrome 39"-62" 10" 13 \$19.50 MS-128 Gray Shrivel 39"-62" 10" 12 17.84



Attas No. 05-4 Dock Stand—Offers new look in stand dealgn. Highly polished phenolic base; beige color. Excellent accessory for tape recorders. Light weight. Base 5 dia. Tube anniahed \$1 92 in chrome. Tube, 4\*, Shps. Wt. 5 lb. Net Each. ... \$2 lb. Net Cach. ... \$2 lb. Net Cach. ... \$2 lb. Net Cach. ... \$2 lb. Net Each. ... \$2 lb. \$2 lb.

Atias No. 05-14 Contemporary Dock Stand—For slim, etongated microphones. Gun-metal shrivel base, 3° chrone finish. \$3.50 tube, with hads, Shig, Wit. 2 lbs. Net Each. \$3.50 Atias No. 58-1 Switchboard Mike Support—Holds mike over switchboards, etc. Flexible 12° goose-neck on spring-loaded swivel so mike can be swung saide. Feed-through hides cable. Heavy, gray shrivel base rear loaded to prevent tipping. Base 9° x 6°, rubber bumpers. Weight, 13 ibs. Net Each. \$13.83

NS-1

Attas No. T5-8 Adjustable Banquet Stand—Modern low sli-houette 8° base and upright with "super chrome" finish. Adjust-able 14½° -26°; "Full Grip" control. Shpg. Wt., 5½ lbs. \$8.51 Net Each.

MICROPHONE BOOMS

Atias No. 85-36 Prefessional Boom Stand—All advantages of "Floating Action" plus secure and dependable looking. Features "Air-Lock Cushion" and new gyromatic swivel joint at milke end. Boom 62° long, adjustable 48° to 72° vertically. All tubular section "super-chrome" plated. Modern base, shipping \$55.83 Weight, 36 lbs. Net Each.
Atias No. 85-36W mebbile—Identical to Model 88-36, except has bail bearing, hard rubber, swivel caster base. Bhipping \$63.33 Weight, 35 lbs. Net Each.
Atias No. 85-1" "Baby Boom" Arm—Attaches to any mike stand: looks in any position. Castings in gun-metal shrived. Boom \$6.92 31° long; chrome plated. Threaded %"-27. Wt., 3 lbs. Net \$6.92

Atlas No. US-2 Multi-purpose Mike Support—Vertical and horrontal spring-load adjust. Cable feeds through swivel and boom. Allow vertical; 360° rotation. Not arm 12%° long. Adjusts \$7.50 atlas No. N. M. 150° rotation. Not arm 12%° long. Adjusts \$7.50 atlas No. N. M. 150° rotation. Not arm 12%° long. Adjusts \$7.50 atlas No. N. M. 150° rotation. Not arm 12%° long. Adjusts \$7.50 atlas No. N. M. 150° rotation. Not arm 12%° long. Adjusts \$7.50 atlas No. N. M. 150° rotation. Not arm 12%° long. Adjust \$7.50 atlas No. 86° 1 Bracket Clemp - Usable with BB-1. Col-13 etc. Can be removed and top dange boited into position. Chrome tube 6' long; 2° 27 thread. Shps. Wt. 1 lb. Net Each. \$3.17 atlas No. CM-1 Cable Manger — Proven necessity on every mike stand. Fits all tubes. Single serve mounting. Chrome \$2.25 mish, Net Each.
Atlas No. F5-1 Mike Foot Switch—Press-to-open switch, normally closed, thereby shorting mike. For all mikes having single-ended inputs. Gray enamel finish. Size, 2° as Net Each. \$10.50 after No. Chrome plants have 3° 27.0 atlas No. Chrome plants have 3° 27.0 atlas No. Chrome plants have been supported Mike Meider—Adjustable there ways so make is always in a suitable "close stailing" position; reduces acoustic feedback. Wt. 6 os. Net Each. \$5.00 atlas No. SW-1 Swives—Permits mike adjustment to any annie locks in position. Chrome plated. Net Each. \$4.17; Atlas No. LO-2 Lock-Lon Accessory—Permits mike adjustment to any annie locks in position. Chrome plated. Net Each. \$4.17; Atlas No. LO-2 Lock-Lon Accessory—Permits mike adjustment to any annie locks in position. Chrome plated. Net Each. \$4.17; Atlas No. LO-2 Lock-Lon Accessory—Permits mike adjustment to any annie locks in position chrome tand quickly, without threading, Positive locking design, pushbutton release. Net Each. \$5.00 atlas No. 50-1 Snap-On Accessor—Identical to LO-2 but Ires pushbutton release. Net Each. \$5.00 atlas No. 50-1 Snap-On Accessor—Identical to LO-2 but Ires pushbutton release. Net Each. \$5.50

### MICROPHONE ADAPTERS AND FITTINGS



MICROPHONE ADAPTERS AND FITTINGS

Model	Description	Ke
AD-1	%"-27 Female to 1/2" pipe	
	thread Male (RCA) Adaptor	.80
AD-1	16"-pipe F to 16"-27 M	-57
AD-3	16" pipe F to 16"-27 F	-63
AD-4	14" long, 16"-27 M thread	-47
AD-S	16"-27 F to 16"-27 F coupling	-63
AD4	%"-27 F to %"-27 F coupling	1.14
AD-7	3" long tube 16"-27 M throads	.78
AD-8	6" long tube 16"-27 M threads	-80
AD-9	%"-27 F to %"-27 F	.86
AD-10	% "-24 F to %" -27 F (W.E. Adaptor)	1.28
AD-11	Flange 16"-27 Female	-86
AD-12	Flange %"-27 Male	-86
AD-13	%"-27 M to %"-27 F	-86
AD-14	Right Angle tube 16"-27 M & F	1.34
AD-15	"Feed-Thru" 14"-27 M & F	1.25

Note: Thread sizes specified as 14' pipe are I.P.S. (Electrical fitting); measures approx. 14' dis. All adapters chrome plated.

### NEW BANSHEE VOICE SPEAKERS

Banshee voice speakers produce vocals that cut through instrument amplification and crowd noise with sound intensity over 123 db. Minimize feed-back, boom and annoying harmonics. Bansnee speakers may be used singly, in pairs or in fours. Banshee voice speakers may be used singly, in pairs or in fours. Banshee voice speakers can also be used as music speakers. Just plug into Banshee for clear, clean high-frequency effects for innovations. For easy installation, an easy-off adapter males a Baby Banshee with any mike stand. Single-iwing-nut adjust makes alming and adjusting remarkably

easy. Ebony fiberglass construction is practically indestructible. **BABY BANSHEE** CJ-125 CJ-40 produces 40 watts, 30 watts continuous Response: 150

- 14,000 Hz. Impedance: 8 ohms Shipping Weight: 8 lbs. NEW BABY BANSHEE Model CJ-40 Price . . (less stand) \$39.45

CS-1A, Popular Triped for use with BABY BANSHEE. Extends to 6 ft. Fully collapsible. Ship.Wt. 6 lbs. PRICE \$17.00

### BIG BANSHEE

CJ-125 125 wild watts crowd-shattering power. Pair up Big Banshees for up to 250 watts. produces 125 watts, 100 watts continuous Response: 100 — 12,000 Hz. Impedance: 16 ohms, Ship Weight: 211/2 lbs. BIG BANSHEE Model CJ-125

Price ... (less stand) \$78.60 SS-4 Weighted Base

speaker stand occupies minimum

floor space — attractive wrinkle finish base, bright chrome steel tubing. Extends to over 6 feet in height.

Price \$18.33 Price \$18.33



ATLAS SS-2 Stand ONLY 35 00 30 Watt Driver SS-2

UNIVERSITY PH

Ideal for Auditoriums, Football Fields Etc.

Stand

UNIVERSITY PH Trumpet 40 Watt Driver 55-2

Stand

Model \$5-2 Heavy duty all porpose speaker support stand. The base stability due to the wide surface spread offers adequate support for heavy speakers and under adverse wind conditions. All parts are of steel properly plated and paint finished. The vertical adjustment includes a "double lock device providing an extra margin of safety against accidental release. The \$5-2 is rugged and will support several hundred pounds. Equipped with an "Easy Off" top adaptor to facilitate removal or attachment of speaker. Height extension 5 to 10 feet. Shipping Wt. 29 lbs. Stand only......\$35.00



LO-2 ATLAS PORTO-STAND

10 TO 10

Only the new Atlas Sound Porto-Stand answers the musican's need for a portable Microphone stand that assembles and disassembles fast and packs away neatly for transport. Consists of the following items: One, PSTIC Deluxe chrome stand

One, P\$12C Standard grey stond.
One, BB-1, Baby boom arm.
One, CH-1, Cable hanger
Two, Lockec Lockeon occassory
One, Carry case.

One, Carry case.

Assembly Instructions:

1. Assemble Microphone Stand
2. Attach one LO-2 on stand.
3/ Attach the BB-1 to the LO-2 on the Microphone stand.

MS-12C 4. Attach one LO-2 to the BB-1.
5. Attach the CH-1 to the stand.

PSIIC- DeLuxe Stand Wt.20lbs.

Price \$31.17 PS12C- Standard Stand. Wt. 191bs.

Price \$29.16

# AKG MICROPHONES · HEADPHONES



### HEADPHONES

AKG Model K-60 — Stereo dynamic headphone that has revolutionized headphone listening. It has become an outstanding example in headphone design which offers full fidelity listening experiences, yet provides complete comfort over extended periods. Music can be reproduced at concert hall level with silky deep bass, smooth mid range response and brilliant highs without distortion; a truly remarkable objective sound reproduction. Net Each \$39.00

### CONDENSER MICROPHONES

AKG Model C-451E—All FET condenser modular microphone features interchangeable omni, cardioid, selectable 3-pattern, shotgun capsules. Easily powered from your amplifier without separate power supply. Basic C-451E combination includes cardioid capsule, preamplifier, stand adapter, windscreen. Accessory modular capsules, optional power supplies and wiring information for direct amplifier powering available on request. Net Each \$179.00

### CARDIOID DYNAMIC MICROPHONES

AKG Model D-190TS—Cardioid dynamic microphone provides clean and effortless sound transmission over 40-15,000 Hz, ±3 dB. Sensitivity, —53 dB (200 ohms). Size, 61/4 "x11/2". Weight, 6 oz. Comes with on-off switch, high-impedance transformer, phone Jack, cable and case.

\$65.00

AKG Model D-190E—Same as D-190TS, but low impedance and without on-off switch.

Net Each

AKG Model D-109—Miniature lavalier dynamic for inconspicuous use. Professional fidelity with low frequency compensation for speech use against the chest. Adjustable mask for high frequency control. Frequency response, ±5 dB, 30-15.000 Hz. Sensitivity, -56 dB. Impedance. 200 ohms. Size, 23/"x3/". Net Weight. 1.5 oz. Includes neck cord, cable, case. Net Each \$49.00

### D-200 SERIES TWO-WAY CARDIOID MICROPHONES

AKG Model D-200TS—High impedance. With on/off switch. Net Each

AKG Model D-202E—Same two way cardhold dynamic design as D-200E, except with 0-20 dB at 50 Hz bass attenuation switch, response of ±2 dB, 30-15,000 Hz, and cardioid front-to-back ratio 02 dB. Length, 8⅓". Net Weight, 9.5 oz. Net Each

\$130.00

AKG Model D-202E with Boom Mount—Same as D-202E except with special elastic boom suspension, front and rear windscreens. Net Each \$190.00

### OMNI-DIRECTIONAL DYNAMIC MICROPHONES

### SPECIAL PURPOSE MICROPHONES

AKG Model D-58E—Anti-noise differential dynamic for close-range voice use in noisy areas. Cancels unwanted sound. Use close to PA speakers. Response, ±3 dB, 70-12,000 Hz. Sensitivity, —58 dB. Impedance, 60 or 200 ohms (specify). Noise rejection, 25 dB. Size, 1½ "x1½", Net Weight, 1.1 oz. With connector, case. Net Each

D-900E

..\$50.00

### MICROPHONES, INSTRUMENT PICK-UPS AND ACCESSORIES



580SA DEL 1888A. High imposance Dutput 59 (0 (0 m) \$42.00 SPHER-O-DYNE SHURE MODEL \$ 34 00 MODEL \$ 34 00 High Impedence Law Impedance

580\$B

Model

Your Swingin' Customers will have Boll with New Shure SphereO-Dyne Here is a hounew Shure Dynamic Omnidirectional Microphone with cuseline appeal is the growing market of young Rock "N' Roll and "Good-O-brede."

Race 'N' Roll and "Go-Go bends.

FEATURES

I. Large mash screen with bulletin onli- "Pop" filte.
Permits close up microphens technique-sellminates
explosive breath sounds.

2. Compact design for comfertable handling.

3. Bulletin On-Off switch.

4. Frequency response 40 to 11,000 cps.

5. Choice of Migh or Law Invedence Models.

6. Removeble cobile for Model 53356 has ottoched
aCCF-type connector. \$3356 has MCZM-type.

MODEL SSAA LAVALIER DYNAMIC MIKE Programmy Respondent: The 20 PM year of a large are Output be beginninged; 10 St 20 August 20 Au



MODEL 565-Cold Fleish \$70.80
List Price \$118.00 \$70.80
WORK CLOSE UP-OR AT A DISTANCE

### MODEL 560 DYNAMIC LAVALIER

- 100 B C | 100 560 \$29.40 that the section is a section of



Model 585SAV SOLVE YOUR OVERLOAD PROBLEMS

SATIN CHROME FINISH

HIGH IMPEDANCE

HIGH IMPEDANCE

The Model 58 SSAV is one of the most ingenious microphones ever designed because the volume-control on the microphone case enables the user to change the loudness of the p.A. system at the microphone location, ideal for applications where the amplifier controls are insuccessible or where the singer wants to control volume for dramatic effects.

SPECIFICATIONS

Frequency Responses 30 to 12,000 ftc.

Impedants and Object Levely
Models 1855A and 3855AW 1856ot, one-conductor the ideal with an Amphanol MCIF Type Connector

Models 1855AW, Let Zeversen 1858ARV. 349.80

585 SBV, La Z version of 585 RAV... \$49.80

### NEW CABLE TYPE TRANSFORMER

Model A95A \$11.40

SHURE

A95P

AGSE

A95FP

### **GUITAR MICROPHONE** FOR "F" HOLES



Stock No. G-112

Improves the tone of your present guiter. Control the volume of each string. Features separate tone & volume controls. Supplied with detachable cord and mounting accessories. No. G-112

Models 5888A & 5888B UNISPHERE 8 UNIDIRECTIONAL DYNAMIC MICROPHONE MOUNT OH STAND OR HOLD IN HAND USE ANYWHERE - EVEN LOW BUDGET JOHS HEW! USE ANYWHERE — EVEN LOW BUDGET JOBS
Choice of high tikigal 5885A) or tow (Model 5885B) impedance models
GUPERIOR "POP" REJECTION QUIET OPERATION
TROUBLE-FREE CANNON CONNECTOR
SUPERB FEEDBACK CONTROL

SUPERB FEEDBACK CONTROL

ON-OPF SWITCH

The Operation and section of the control of the con

0 9 2 2 3 5 5 combos, and vocalists ... both indoors, and outdoors, Ship. Wr. 2 Ibe

Shure mike line transformers for long runs Frequency Response 20 to 20,000 Hz

Low Impedance: High Impedance:

Case Diameter:

MUSICAL CRYSTAL

CONTACT MIKE

\$1.95

Case:

50,000 ohms

Full magnetic shield Steel with Gray enamel

2. Female cannon XLR 3 13 low imp. to MC1M Amphenol HI imp. A 95 F net. \$13.20

3. Female cannon XL 3 13 low impd. to stand. phone plug hi imp. A 95 FP \$14.40

\$2.99 No. V1712

MUSICAL CONTACT A high impedance crystal contact microphone equipped with a built-in volume control. Permits user to control his volume without going to the amplifier itself. Microphone is made of molded plastic, light in weight and easy to handle. Complete with 8-ft of shielded cable, and clamp bar. IDEAL for GUITARS and other stringed instruments.

MUSICAL INSTRUMENT PICK-UP With Tone and NET

Big Saving I Compare at \$35.00

radel 110, Musical Instrument Pick-up with tone and volume control. Same type and quality as most expensive pick-ups. Fell base mike unit fits under stellings and stides up end down for best consisteet. Bright chrome plate. Willy bs. Complete with a Ft. coble and plug......

Makes conversion of round hole Spanish-type guitar or ukulele to an electric easy. Contact type pickup is Makes conversion of round hole Spanish-type guitar unusually conversion of round hole Spanish-type guitar unusually designed for maximum output on guitar frequencies. Equipped with separate volume and tone controls. Cord is 48" long and has standard guitar amplifier plug attached. Individually boxed. No. \$1713

MICROPHONE WITH CLIP

LAPEL CRYSTAL



HI IMPEDANCE 200-8000 CPS.

SENSITIVITY

LM 38 10 for \$8.50



No. LM103

Looks and is a very attractive gold finished tie clasp with a jewel insert, but actually is complete miniature microphonel Fine for secret sound pickup. 2500 ohms impedance



### SLIM MIKE STAND HOLDER

ALL METAL

SATIN CHROME FINISH

Stock No. SMH-100

Fits most Calrad mikes up to 1" Diameter -- 5/8"-27 Thread

MAGNETIC DASH BOARD MIKE HOLDER

Powerful magnet attaches to any steel surface. You can then hang mike up on any metal surface such as car dash of transceiver case. No holes to drill in mike or car dash. Cot. No. MH 200





## SHURE

SHURE

BROADCAST SMS 9-29/32" Long X 412" Dia

SMSA \$25500

SHURE

BROADCAST SMS6

With Built-in Shock Mount

OVER-ALL DIMENSIONS

4-3/4" Long X 1-15/64" Dla.

Model \$9600 SM56

Dual Impedance, Hi at Low,

SM5B

SM56

## PROFESSIONAL PRODUCTS

LOW-Z For Newest Transistor and Professional Tube Type Equipment

BROADCAST LAVALIER

'Flex-Grip" lavalier assembly

OVERALL DIMENSIONS

2-19/32 L. x 25/32 Dia.

Model \$6600

Model \$ 7200

Shure Model 570, New small size protessional Dynamic Lavalier mike. Only 25, long and 25/32° disa, Less than 1° diameter. Low impedance, 50-250 dhas, Response 50 to \$2,900 cps. Omnedirectional pick up pattern. Equipped with 30 feet of 2 conductor cable. Has a nonrefelection grey case with standess steel eril?:

BROADCAST SM33 Long X 2-1/16" D.

MODEL SM33 DUAL IMPEDANCE \$ 15000 NET

OMNIDIRECTIONAL

BROADCAST SM50 6-9/16" Long X 11/2" Dia.

\$ 7800 NET

DUALIMPEDANCE

he microsimme shall have a Response Selector switch to provide radual low frequency resident

MODEL

SM50


3t," Long

570

7-15/16"

SHURE

MICROPHONE MIXER & CIRCUITRY PRODUCT **ACCESSORIES** 



AC60 ATTACHE CARRYING CASE. For Mixers.

A68B RATTERY POWER SUPPLY For all M68 Series Mixers.



A68C OUTPUT CABLE KIT.



A68P PHONO PREAMP



A68L LOCKING PANEL



A68R RACK PANEL KIT for use with the M68.



A68S STACKING KIT.

Write for Shure Booklet on mixers & Audio circuitry components

#### IMPEDANCE BROADCAST AND RECORDING STULLO QUALITY, MATCHES NEWEST SOLID STATE EQUIPMENT SHURE SH JURE

BROADCAST SMS7 With Buillyin Shock Mount VER-ALL DIMENSIONS

5-23/32" L = 1-15/64 D. 200

Dual Impedance

pattern, Re dle cast ca bracket file

\$75.00

SM57

BROADCAST 5M58 /16" Long X 2" Dia. 6-7/16 MODEL

\$ 9600 NET SM58 DUAL IMPEDANCE

\$M58.....\$96 .00 Shune Model SM33.....\$150 .00

OMNIDIRECTIONAL BROADCAST SM76 8-9/32" Long X 25/32" Dio. DUAL IMPEDANCE

\$120 O NET MODEL

Model SM76 Omnidirectional Dynamic Microphone. Unusually extended and amonth response for cell field applications in broad assistance for cell field applications in broad assistance for cell working conditions, Steel case for a magnetic shielding, Supplied with also-in award adapter for 5/8"—27 assistant thread, Prequency response; 45 to 20,000 Hz. Pollar Pattern, Omnidirectional, Impedance: Dual. Stand 15: ohms. Quiput 1, evel; 460 db. Street, 15/5 and 15: ohms. Quiput 1, evel; 460 db. Street, 15/5 firsts. With 20-foot cubic with Cameron X.6. 2-10 Connector. Weight: Net (less cubic) 7 a.c., Shu, Wi. 2 lba., 2 s.g.

549.20 Shore Model SM76, Omnidirectional Dynamie Micro-\$120.00

BROADCAST SM60 6-7/32" Long X 1'." Dia.

Impedance 150 Ohms \$ 4920 NET

SMod Omnidirectional Dynamic Microphone, leaf choice for in-cances, or investige use by lies and Micha for studies and remute inters, news, spirits, and a variety of similar appears, news, spirits, and a variety of similar appears, should natural bound and built-in wind riport little to minimize beath and wind noincludes alipsin served adapter for \$/8" = 27 threat, Prequency response; 48 to 15,000 Hz, lipsing the property of the second of the second of the second of the lipsing the

MODEL

SM60

NEW MODEL

SHURE

MODEL SHET DYNAMIC LAVALIER MICROPHONE

MODEL SMS1 DYNAMIC LAVALIER MICROPHONE

Thade! BMS1 Dynamic Lavalier therephone, A small
ranged dynamic lavalier methydrine specifically
designed for use in television, mostern pretures,
cadio, and airsil ar applications in which a aimsil,
we arable methydrine of phylosophical quality is required, included in a postitive locking lavalier hoider with adjustable holding clay and a belt clip
for the cable. Smooth exterior cultiours and recess
ed grilly for minimum clothing notice. Frequency

AVALIER

Shren McCel SMS1 - With Schlort, nondetachable, touc
conductor shielded cadle, Vegalit, Net (less cable)
2 o.e., shipping weight 1 e 1/2 lbs.

Shren McCel SMS1 - Denne Lavalier Microphone

Shure Model SMS1. Dy name Lavaties Micr. \$72.00

UNIDIRECTIONAL DYNAMIC MICROPHONE 15300 15300

PRICE \$114.00 MODEL M688 STEREO MICROPHONE MIXER

> Write for Shure booklet on

MIXERS AND AUDIO CIRCUITRY COMPONENTS

Designed to be used with stereo tape recorders and sound reinforcement systems. It has four dual impedance microphone inputs: three switchable to either left or right channel and the fourth with a pan control (any position between L and R). Two aux, inputs, Individual volume controls plus a stereo master volume control, Mono/stereo switch, Stereo high impedance, hi level outputs, plus L and R mic, level output, hi or lo impedance, 120V. AC or 30V. DC operation, (Use XLR-3-12 Type or Switchcraft A3M matting connectors for mic, Inputs). Shpg. wt. 7 lbs. \$114.00

The overall dimensions shall be 7.164" (182.0 mm) in length and 1.5" (38.1 mm) in disruptor. SHURE MODEL M675 \$150.00 **BROADCAST PRODUCTION MASTER** PRICE



When used with the Shure Model M67 (above) provides four additional channels for magnetic phono and line inputs with cue provision for previewing the material supplied to these added inputs. The M67-M675 combination makes a compact console, permitting moting of four microphones, four line inputs, and two turntables. I For mic. inputs use XLR-3-12C or Switchcraft A3M mating connectors). Battery or M67 powered. Stacking hardware included, Frequency response: 30 to 20,000 Hz ± 2 dh. Distortion: less than 1% THD. Shpg. wt. 8 lbs.

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108

\$150.00

SHURE

FIRST, WHAT IS AN EQUALIZED SOUND SYSTEM?

EQUALIZED SOUND SYSTEM MICROPHONES

An equalized sound system is one which has had its frequency response specifically tailored to the room in which it is installed. The primary purpose of "equalizing" a system is to (1) increase usable volume without feedback, and (2) to improve the intelligibility of the system.

The procedure for "equalizing" a sound system is quite involved since precise acoustic measurements of the "room response" and "resonances" must be made and the sound system response precisely adjusted accordingly.

### NIDYNE IV Microphone MODELS 548 - 5488 - 549

The premier member of the world famed Unstyre family of microphones. An utita high quality, super-rupped microphone with an unusually effective reduced packup pattern. Unusually smooth, wide range response for voice and misic, has all the superb feedback and "boom" suppressing characteristics of the Unidyre III (below), combined with exceptionally rugged contraction. Easily serviced in the field, Specially

reinforted cartridge Cannon 1,pe connectors. Model 548 Unidyne IV: For stand or hand usage includes AZSB swittel adsolet. List Price: \$100.00 \$6.9 0 0 Net Model 5485 Unidyne IV. Mounted on a lifetime switch that also content where switch that \$105.00

\$72.00 Net

Model 549 Unidyne IV: Professional, stege version of Unidyne IV. Special vibration-isolation shock mount to insulate against exhiption and mechanical shucks, Special "storage" packaging, a ideal for performets who carry their own unit to clubs and institutional desirable. Combination impedance selection-on-off switch: Ear Price. \$150.00 - \$10.5.00 Net

Impedance and Output tower Mode's 548 5385 Dual tow —57 db 10 db m 1 mall watt per 10 micrelansis 131 militarite micrelan. High 55db 30 db — 3 vett per micrelan. High 55 micrelan.

Model 349-duel (50 phms) -- 56 db (0 db =

millioest per 10 microbars): Cof millioests microbar, M (250 chims) -- 50 dis 10 millioest millioest 548 per 10 microbars, 149 millioest microbar.

Cable Models 548, 5455 15-foot, two conductor \$69.00 with load with Cannon XIR3-HC Canneter on Net microphone and Model 549, test cable 8ut Carnen type XIR3-HC cable connector included

\$93.00

髅

Mudel 548S

\$72 00 \$105 00

## MEN UNIDYNE III Microphone MDDEL 547 STAGE VERSION

Recommended for use in any increase where for disco-presents good sound reproduction. Small and sirial right handsome, the atoliative design of the Bhidyne III M prophores approaches the

theorytical ideal of the uniform cordicid pickup patter. A faces to close for singers and emerts note.

good for pickup of drums and bass instruments Model 547 - Duel - 170 NS

Model 547 - Duel 1, ISO oloms; -56 db (0 db = 1 mill west per 10 merchant); 087 mill-volts microbar, M (250 ohms) -56 db (0 db = 1 milliwest per 10 microbar, M (250 ohms) -56 db (0 db = 1 milliwest); 670 ohms); 149 millipoths; microbar, Frequency Responses 40 to 35,000 Ms. Model 547 Liva Cable ban Connon type XLR 3 TSC paths form; consultation of the control of th

cable conserver challed.

Model S47 Unidyna IIII Stage version of Model 546 Includes storage case.

List Price 5.1 85.00

MODEL 533SAV Spher-O-Dyne OMNIDIRECTIONAL Adjustable Valume Control HIGH IMPEDANCE

\$39.00 NET

to del \$33 SAV omni directional dynamic michiphore has include control on the michiphore done but wishes control on the michiphore done but wishes the component of cetting, dead for applications where application in cetting, dead for applications where application to the control of cetting and the michiphore of the control of cetting and the cetting of the cetting and the cetting

erduction of voice and dusic, combined byte of discounting the state of the combined byte of

533\$A and 533SAV High Impeda

## SHURE MODEL M68FC Microphone Mixer



Case Dimensions 78% hoph, 11% wide, 5%; deep The Bhort kacrophone Masers are operating, efficient and economical way of increasing the efficiency, use full need and flew fitting the endough of the endo

type (Uses XLV-3-12C type Mare) Las Price: 51 80.00 \$90,00

Model Mail Misse, Inpu Ust Price:\$1.40.00 \$84.00

MDDEL M67 Professional Mixer



Gein. 90 db man.: 150 ohm micro into 500 oh

MODEL M62 V AUDIO LEVEL CONTROLLER

#### PRICE AUDIO LEVEL CONTROLLER 5700

teneral: The Share Mort Mot as a transitionized variable emploier especially designed in key the electrical mutual constant although the sopiol signal from the microphone graves considerable.

The Sodio Level Controlleration MODCL M62V

Permitting appearance review for the property of the property

Reduces food more caused by severy stand vibration. Prevents accidental feedback from becoming "exception

\$1470 Net

Model **ES50** Low Impedance LIST PRICE \$90.00

Model

**ES51** 

Dual Low Impedance

LIST PRICE

\$140.00

The Basic difference between the ES50 and ES51 is that the 50 can be hand held where the 51 is shock mounted and screw on the floor or desk

ES50, 150 ohm impedance Dynamic Cardioid (Unidirectional design assisted by a Nationally known PHD for more output before audio feed back. 61%' long, 1½' diameter. Die Cast case finished in non-reflecting grey. Shipping Weight 1 lb. Model ES50, List Price \$80.00......\$45.00 E\$51, Dual low impedance Dynamic. \$0 ohms or 150-250 ohms (switchable). Shock mount. Both models fit 5/8" x 27 standard mike stands. \$1ze: 5-3/8" long x 1½" dia. Ship. Wt. 2 lbs...\$78.00

SHURE

List Price: 5270.00 \$162.00 Net

## Vocal Sphere 579SB DYNAMIC

MICROPHONE OMNIDIRECTIONAL LOW IMPEDANCE EXCEPTIONALLY QUIET OPERATION

\$45°°

REMOVES THE "VEIL" FROM BETWEEN

#### THE PERFORMER AND THE AUDIENCE

A superb sounding microphone that fills the bill when you need extremely lifelike, natural and intelligible voice reproduction for a vocalist or speaker, Peak-free, linear, wide-range response and uniform omnidirectional pickup pattern minimize voice coloration. Effective built-in wind and "pop" filter make the Vocal Sphere the ideal microphone for intimate close-talking situations. Free, response 50 to 15,000 Hz. Impedance 150 coloms to match 25 to 200 ohms, Output Level: 1,000 Hz, response Open Circuit voltage-80.0 db. Built-in 'fon-off'' switch with lockplate. 20ft. two-conductor cable with Cannon XLR-3-11C connector, Satin chrome finish, 6-3/8'' long x ½'' diameter (1-9/16" at head) Shipping Weight 2 lbs,



Shure Mixers & Mikes ore 2nd.

in volue MODEL M68RM \$117.00 The Shure Model M68R311s a four-th completely transistorized portable mike mixer with built-in REVERBERATION for use with public address systems and tapo recorders. McGee Price.....\$117.00

SHURE AUDIO MASTER AUDIO CONTROL CENTER LIST PRICE \$9600 \$160.00



Model M63 Audio Maerer, Designed to give mantimum flexibility in the control of volume, bass response, trebis response, high and low frequency roll-off, to any high level input source. Work aideally as a funal controller when used in conjunction with the Shure M68 Series of mixers. The m63 provides the means to shape freeze the model of the means of the model of the

## Microphones

GENERAL PURPOSE MICROPHONES

NEW "UNIDYNE III" MOVING COIL, WIDE-RANGE CARDIOID

Smallest varied dynamic microphone available. Wide range reprotuetion of voice and music, highly fiexible for hand or stand use. Dependable for fine quality F4 asystims, take recording, etc. Reduces of eliminates feedback and background noise in adverse acoustic condition. Jermits placement at 75 generate firstance from sound source than possible conditions. Jermits placement at 75 generate for years without deviate from officinal standards. Frequency Responses 50-15 000 rate for years without deviate from officinal standards. Frequency Responses 50-15 000 rate for years without deviate from officinal standards. Frequency Responses 50-15 000 rate for years without deviate from officinal standards. Frequency Responses 50-15 000 rate for the property of the \$57.60

DUAL-IMPEDANCE 3-05 DYNAMIC
A compart, modern ite merophisme with high output dynamic clerent at a modernich merophisme with high output dynamic clerent at a modernich merophisme with the property of the pr

UNI-DIRECTIONAL DYNAMIC

MICROPHONES "5.55" mail expension of the model of the mod

Shure Medel "abs" Small \$57.00 Unidyne— Net Each

Model 55SW (with switch)

\$ 58 .80



## HEADQUARTERS FOR MICROPHONES BY TURNER



GENERAL PURPOSE AND PUBLIC ADDRESS MICROPHONES

MINLMIKE LAVALIERS.

TRANSISTORIZED

DESK PAGING

Model 35A

Model 35 Series dynamic lavaller microphenes—new wery small, very light weight, designed specificatily for transfer applications, including a tailored response over the entire spectr range with no discrimination or dis-sprison. Demokracitional pickup pattern, Lavalier cord and clothing clip included. Desert gold limits

and clothing clip included, Desert gold firmsh.

Meart 35 %" diameter by 3" length High lion impe-dance combination 25 hoot, tince conductor, shelded cable. Weight only 41 grams. 60 db output level 50-12 000 97 frequency range. Net 541, 16. Moret 354, 2%" long. %" diameter. 150 ohm impe-dance 25-foot, two conductor, shelded cable. Weight only 29 grams. 60 db output level. 50-12,000 Nb fre-ouency range. List price s 80.00 Net 547,04 6-18 stand adapter (light 56.00 G-15 stells stand liss 58.00) are complementary accessories.

DESK PAGING Models 251/253

DESK PAGING Models 201/203

Madels 251/253. Work-horse utility microphones so adaptable they've found their way into many applications. Designed to stand on a table, the one piece die cast case incepporates a touch hair to actuate real spring switches, and a "litch of the finger" ligitimity level to permit either momentary or locked on use of the touch bar. Wide range dynamic microphones. Sain from microphones. Sain show the real properties of the real properties. The real properties of the real properties. The real properties of the real proper

Model 251: With lift switch—microphone may be switched either with the touch bar or by lifting from the table surface. List pric\$65.00 Net \$38.22 the table surface. List price Madel 253: Without lift switch, 7 fact cable. List price Net \$32.34

700 Series

Not \$38.22

500-06: S-500: 510-505-

CARDIOID DYNAMIC QUALITY STANDARDS

S-500 Series:

\$-500 Series. The standards for difficult applications where background house creates a problem and where extreme fidelity of approduction to required. Wide range amonts response fundaming of performance, microphone to indexephone. Each microphone indevidually adjusted during quality lests. Front to back discrimination is unmatched on the industry.

5:500 Ni/less emperance combination. 35 db output level 40:15:008 Nz frequency range. Typically 20 db discrimination over the range Detachable 20 foot, three conductor, shielder cable Positive action retain good switch with clearly defined positions. N or \$61.74

Model 500-06 Matched stereo pair of 5-500's 5-210-00 Net Net \$123,48 Medial 505: Adds the acoustrial advantages of an adjust-able bass response, controlled by a rotary switch, min-mormal" and "less bass" markings. Net \$70.56

hormal and selectionally flat response, recommended by audio consulting experts for use with noten-filter sound systems. Low impedance only. Net \$88.20

150 OHMS OR HIGH IMPEDANCE

Model 585

Model SR5850

GOOSENECK PAGING 585 Series

SBS Series: Grocery check-out counters, switchboards, air line announcing stations—anywhere a
lipid installation is needed is the place for the 585.
Die cast incrophone on 16° flexible arm with 3-hole
lange for installation, 150 ohm or high impedance 58
do output level. Three or four conductor thus shredeel
cable extends 4 feet from timpe. Net \$23,52.
Model 588 As described, list price \$40.00

Model (8530) Willia switch, switch housing mounted on flex arm DPDT real spring switch for long life and maximum utility. Momentary contact One pole is normally closed (line shorting) in the mike circuit and one pole is normally open for external relay control or misse morting. Available with both switches normally open. List price 550.00 Net \$29,40 Net \$29.40

Model RA-50 REMOTE AMPLIFIER

Model 50: Contains its own framistor amplifier and battery power source is the solution to the problem of long likes before mitophone and amplifiers 60:0.000 Hz Requency range 7 do output level 150 or 600 ont impedance Dnotf switching Volume control Satin chrome finish ease. List price \$60.00

Madel IA 50. Renote implifier with ornaft switch 150 gr 600 ohm impedance, 50 do gain controlled by integrals volume control self contained 9-yelf power source, reliable those stage transistic amplifier Can be wall impusted or clip to microprone stand. Used in feeding long lines are combining many microphones into a single imput; 2" x 2" x 3"x", sist price 580,00

Net \$29.40

Model +50

Net \$47.04



TURNER

### COMMUNICATIONS AND CITIZENS BAND MICROPHONES



New Model +3 Transistorized Pre-Amplifier Plus mee mover-thal instantiation or re-ambilitier Plus Modulatine Guard. All of the bimelets of a timen transstorated pre-ampliand volume control with some added new benefits—all new modern styling end ecompression amplifier circuit mixing justeds. Against over modulation. Regardless of volume setting, your signal comes on loud and cover no mixed splat and souther. We arend aguiter. Yeu cannot over modulate and interfere with other channels. Also, new ceramic interior, 300,3,000 fits frequency range for best voice transmission. Touch to talk front bar, viide lock for extended transmission Self-contained battery. Output tree: 23 do. Three conductor (1 shielded) coiled cord. Comes complete with wiking instructions for over 100 popular transconvers. Absolutely the best base station microphone you can buy East price, \$75.00. Net \$44.10



Model +2 Transistorized Fre Amplifier Transistor Model +2 Transstorred \*Tre Amplifer. Trensstor-ized base station incropance with variable output level, which will increase the signal strength and range of your transcareer. Two stage suicon trensistor empli-fier with volume control. Light dive firsts diet cast case marching three conductor (1 shelded) colled cord Binght chemie front black put in trans bet and lever spot control. Relay or electronic swetching. Sed constances on with batters. Enswerch is resolved. contained 9 volt bettery Frequency response 300 3 s00 Hz Output level 23 db Weight I ib 8 oz Booklet with complete Installation instructions for over 100 transceiver models is included. List pnce.





## WITH BUILT-IN TRANSISTORIZED AMPLIFIER



The "990" is designed specifically for the CB. Communications and Brunness Radio field. This microphone incorporates a two-stope transistantized amplifier to provide a gain of 15 db over Conventional Ceromic mobile microphones Model "990" has the copability of fully modulating any transmitter, due to its high aurput level. Output level on the mility advisable has a semi-created can be easily adjusted by a semi-recessed calibrated volume control located on the tear of the case. The ceramic element is unaffected by extremen of temperature or humidity. To achieve maximum temperature stability, the amplifier in built with silicon

Then "990" is wired for relay switching closing an external set of contact, with no ground connections. Additional switching contacts are provided by the three pole double throw switch to provide greater switching flexibility and companishing with most transfervers. Self-contented batteries, retroctable cable, Includes mounting clip.



Model 254X, The Most Popular Base Station Micro phone in Use Today: Provides optimum performance at minimal cost. Die cast case in light grey hemmer at minimal cost, the cast case in light grey nemmer-tions finish. Crystal interior with a high output feet for high impedance, tube Eyes, Franceivers incurring relay or electronic partitiong. Push to fall front bar, lever tect. 7 feet, three conductor shielded, straight. leyer lest in legal, invite conductor sineaped, straight, cond 100 8 000 Mg frequency range. 48 8 bo utbull level 7 Mg. height 5 Mg. appth 5 hopping weight 3 pounds Monde 2346, Sahre es 2348, with cet mic interior and 34 db output level. N e t \$18,82 Model 350, Mont Used Mobile Microphine Model 3506, and the most endry accepted only and equipment model on the most endry accepted original equipment model.



Net \$8.82

Net \$8.82 Model #350 fransisterated mobile dynamic micro prome from stage where franking mobile dynamic micro prome from stage where franking mobile drive rath gays could be staged from the franking staged from the franki



Model 139C Grp fe-fah Sentch Ceram with July grp for Jas suitch. Three conductor (1 sh coined ceral 1977-200 February 19

Net \$10.00

TURNER



Model 454K, Base Station Microphone: Offers single successive seasons and the control of the seasons o

List price, 536.00

Net \$21.17



on 360, Reduced Size and Weight Comprehents the est splid state transcrivers. Options element for operation three conductor (1 sheed 3 000 Hz Immuercy 65 mb output ... case Model 3 300 Barre, erred ter N e 2 \$10,00 Model 360R: Cart videt Immumum 0 4444 for eathy switching. But community communities cord Bio birm impedance. 2004 a 2000 for trequency range. 15 db autorut even N e 1 \$12,35 adei 300 Le-2: High capacity ceramic for transceive in requiring a literary appealance in the shout. N e t \$10.58



impediance miss short. Net \$10.00.

Alloy case in satin chearins with accidingly from hengar button. Relay southern specifically received from hengar button. Relay southering entit professional guidality detecting teed type switchess. 8900-50 Dynamic, hi impediance, 200-10,000 kt (requestly range, \$2.00 output level Trist a conductor (a shielded) could cord. \$4800 & Dynamic, 200-00 horizontal production (a shielded) could cord. \$4800 & Dynamic, 200-00 horizontal production (a shielded) coulded cord. Usid spreads, \$4.5.00 Net \$26.46

Model \$8908: Carlium micropring billy and minimum distortion 200.4 000 HJ frequency range, conductor unshielded colled

### TURNER BALLADIER MUSICIAN'S CARDIOID DYNAMIC MICROPHONES WITH CARRYING CASE



Specifically designed for reproduction of musical groups and high volume of sound. Each Balladter microphone is in a carrying case with 20-Ft, cable and phone plup for direct plug in to any guitar amplitudes adaptor for in-hand or on-stand use. Built-in blast filter eliminates "pop, "how!" or wind noise. All are high impedance.

VOLUMETRIC CERAMIC MOBILE MIKE, Stock No. 991, Price \$6.95 push to tolk circuit. High impedance. (Not amplified)

GIVE PAGE NO., AND STOCK NO., WHEN ORDERING





Model 631PC-One model 631 (Hi-Z) with phone plug. Microphone and cable packed in convenient carrying

"HAND AND STAND" DYNAMIC-High quality entertainer's microphone. Omnidirectional, Lightweight, rugged, and shockproof, Effective 4-stage filter allows use close up without blasting, pops, or distortion. Silent, magnetic on/off switch with removable actuator button.

Response: 80-13,000 Hz. Output: -55 db. Hi-Z

With cable and 310 stand clamp. Size: 6" long, 1-3/8" head diameter, ½" shank diameter.



Model RE16

SUPER CARDIOID- Similar to Model RE15 except incorporates integral blast and pop filter around head of microphone. Specifically designed for close-up vocal use and virtually eliminates pickup of breath noises. Strong, protective metal screen prevents damage in use, Specifications identical to RE15, 7-3/8" long, 1-7/8" diameter (%" shank diameter). Net weight, 8 oz., not including cable.



MODEL 670

Model 670

Newly designed "Single-D" cardioid for professional per formers who want bass boost when using mic close up. Use on stand or hand held. Lightweight, but rugged. machined aluminum case with new anodized Top Brass finish, Highly effective internal air-damped shock mount construction with microphone head completely isolated from case prevents pickup of shock noises, protects against damage with hardest use. Built-in superior pop filter. Very high degree of cancellation of sounds from sides and rear of microphone plus extremely smooth and flat response reduces possibility of feedback and allows increased gain from sound system Built-in professional type Switchcraft A3M connector. With on/off switch. User replaceable head. Response: 60-14,000 Hz. Output: -58 db. Hi-Z or Lo-Z selectable. With cable and model 300 stand clamp. Size: 7%" long, 1-3/8" max. dla., 1" shank dia. Net weight: 6 oz.



Model 670V

VOLUME CONTROL MICRO-PHONE- Identical to Model 670 with volume control instead of on/ off switch. Control knob easily operated by thumb while using microphone, Control turns microphone off in lowest position.

Model RESS

WIDE-RANGE DYNAMIC- Extremely wide range, flat response for the most exacting professional applications. May be used as secondary laboratory standard, Widely versatile in recording broadcast, or sound reinforcement of symphony orches-tra, organ piano, etc. Also comfortable and convenient when used hand-held by performers and for interviews. Smooth wide-range response, 40 to 20,000 Hz, High out mechanical shock. Acoustalloy dia mechanical sincit. Acoustalloy dis-phragm La-Z, Sired case in fam-beige Micomatte finish eliminates hot spots for "on carrera" use, 18" 2-conductor shedded broadcast type cable with Switchcraft A3F concacle with Switchcraft A.Sr con-nector. Model 310A clamp and metal carrying case provided 10%" long overall 1%" major diameter 1%" shank diameter). Net weight, 8% oz. mithout cable

\$132.00

\$ 39,75

Model DS35

Newly designed "single-D" cordiold microphone for the most exacting professional performing and recording applications. Emphasizes low frequencies when used close. New bead design and seclusive Valumetric helogram-developed diaphragm provides exceptionally wide, linear response at all angles of incidence, for high gain-before-feedback in sound reinforcement applications and virtual elimination of off-axis colsenten. Highly effective, internally air-damped shock-mounts construction with mike head completely isolated from the case prevents pickup of shock noises; and protects against damage with hardest use. Built-in superior pap filter. Use replaceable head. Extremely rugged turned steel case, with non-reflecting from being Micomatte finish. Response: 60 to 17,000 Hz. Impedances Lo-Z. Output: 58 dBs. 18 "2-conductor shielded breadcust cable with Switchcraft ASF connector. Sires 17%" long. 1-7/8 in. die. (%" shonk dia.). With metal case and model 312 ciamp. Net Wes. 8.2 oz., not including the cable.

**RE85** 

\$**78**20

**OUIET LAVALIER - Extremely free** 

from friction or shock noise due to

new double case design with internal

element suspended in compliant

rubber; hard, smooth case finish

avoids friction noises; specially de-

signed, smooth cable, isolated from

inner capsule, prevents pickup of cable noises. Rugged and durable

with turned-steel case and solid.

slotted front piece. Extremely flat

response in chest-lavaller position: 90

to 10,000 Hz. Output: -61 db.

Acoustalloy diaphragm. Omni-directional. Matches all low-

impedance inputs. Integral 30" two-

conductor shielded cable. Finish:

non-reflecting Champagne Length, 205/8". Max. dia., 15/16". Net weight: '8 ounces. Neck cord

assembly, tie clasp assembly, belt

PROFESSIONAL CARDIOID

MODEL

**DS35** 

**\$79**38

clip, and zipper pouch furnished.

MICROPHONE

Model DS35

**OMNIDIRECTIONAL** 

\$75.00 \$ 59.70 THIS MIKE CONTAINS

AII/2 VOLT PEN BATTERY AND TRANSITER.


45,00

MAKES THIS MIKE

VERY HIGHOUTPUT SO CAN BE USED WITH LONG CABLE

\$ 75.00 UP TO 200 FEET.

Electro Voice **ELECTRET CONDENSER MICROPHONE** 



Latest engineering breakthrough. Genuine condenser mikes with superior performance specifications at surprisingly low cost. Generating element permanently charged eliminating costly and troublesome power supply electronics. Ruggedness and long life previously available only in dynamic microphones. Excellent frequency response, transient response, and sensitivity make these units RECTIONAL suitable for professional and serious home recording and high quality sound reinforcement.

1751: Cardioid pickup pattern reduces sensitivity from sides and rear. Single-D type emphasizes bass used close up. Rugged aluminum case with permanent anodized beige finish. On/off switch. Low handling or shock noise. Built-in breath filter. Has small internal impedance matching circuit with AA-size battery (not furnished). Response: 60 to 15,000 Hz. Lo-Z balanced to ground. (Because of high output may be used with low, medium, or high impedance inputs.) Output: -43 dB. Separate cable with professional connector and mounting clamp furnished.

1750: Cardioid, similar to 1751 for less exacting applications. Response: 80 to 13,000 \$45.00 Hz. Output not balanced to ground. Cable integral with microphone.

1711: Omnidirectional, picks up sound equally from all directions. Wide-range, smooth response for highest quality recording applications. Rugged aluminum case with permanent anodized beige finish. On/off switch. Very low handling or shock noise. Built-in breath filter. FET circuit for impedance conversion uses AA-size battery (not furnished). Response: 60 to 15,000 Hz. Impedance: Lo-Z balanced. (May be used with high, medium, or low impedance inputs.) Output: -50 dB. Separate cable with professional connector and mounting clamp furnished. \$59.70

1710: Omnidirectional, similar to 1711 for less exacting applications. Response: 80 to 13,000 Hz. Output not balanced to ground. Cable integral with microphone. \$39.75

76



Model RE50

Net weight, 9% oz.

Model RF15

SUPER CAROLOID- New, for

exacting professional applications on

boom, stand, or hand held Super-

cardioed directional pattern provides

maximum rejection at 150 off axis,

maintains essential cardiold pattern

at other positions. Response virtually

identical at any position around

microphone, eliminating off-axis coloration. With "bass till" switch,

Rugged case and inner construction

Favor beige Micomatte finish. Re-

sponse: 80 to 15,000 Hz. Impedance,

Lo-Z. Output: -56 db. 18' 2-

conductor shielded broadcast cable

with Switchcraft A3F connector. 6-7/16" long, 1-3/8" diameter (%)

shank diameter). With metal case and

model 310A clamp, Net weight, 6

ENTERTAINERS "Single D"

"HAND AND STAND" DYNAMIC-

High quality entertainer's micro-

phone. Omnidirectional, Light-

weight, rugged, and shockproof. Effective 4-stage filter allows use

close up without blasting, pops, or

distortion, Silent, magnetic on/off

switch with removable actuator but-

ton. Satin chrome one piece case.

Response: 80-13,000 Hz. Output-

MICROPHONE

MODEL

631

SPECIFY

oz., not including cable,

**Omnidirectional** 

Microphone

Model 631

weight, 6 oz.

Model 641

microphone. High

NOISELESS HAND & STANO-Omnidirectional microphone especi ally designed for vocals, interviewing, etc. Widely used for instrumental broadcast and recording, also Extremely low susceptibility to me chanical shock, handling and cord noise, or breath pops due to unique double case design separated by rubber isolating mounting. Same ruggedness and electrical characteristics of 635A. Vartually self-windscreened for outdoor use even in high wind. Four-stage pop and dust filter, Nonreflecting fawn beige Micomatte finish. Response: 80 to 13,000 Hz. Output: -55 db. Acoustalloy diaphragm. Low impedance, Switchcraft A3M connector, 18' cable, 300 clamp furnished. Size: 7%" long, 1-15/16" max, dia., 1" shank dia.



OYNAMIC- Ideal for P.A., recording, and general use. Use on stand or in hand. Omnidirectional. Response 60-12,000 Hz. Output level: -56 db. Acoustatloy diaphragm. Dual Lo-Z and Hi-Z. E-V OC-4M cable connector allows easy change of impedance without tools by moving a single pin Pressure cast case, satin chrome finish, Tiltable head, On/off switch, 5/8"-27 thread, Size: 7%" long, 1-5/16" diameter, 15' cable,



GENERAL PURPOSE

Model 676

CAROLOLO OYNAMIC- Similar to 674 microphone, except less mounting stud and on/off switch. For use with stand mounting clamp [Model 300 supplied) so microphone can easily be removed and used handheld during performance, Response 60 to 15,000 Hz with low-frequency attenuation switch. Output -57 db. Dual Lo-Z and Hi-Z, E-V QC-4M cable connector allows easy change of impedance without tools by moving a single pin. Satin chrome finish. 15' cable. Size: 7-3/8" long. 1'4" diameter (shank 1" diameter). Net weight, 12 oz.

## Electro-Voice professional broadcast and recording microphones SETTING NEW STANDARDS IN SOUND

BROADCAST Microphones MODEL REI5

Omnidirectional DYNAMIC Model 635A BROADCAST \$15582

Model 635A

MODEL 635A \$5174

BROADCAST DYNAMIC- Completely redesigned and improved omnidirectional microphone, perfect for hand and stand use by enter-tainers and vocalists. Light weight turned steel case is extremely rugged and provides magnetic shielding. Fawn beine Micomatta finish, Effect ive four-stage pop and dust filter Hz. Output -55 db. Acoustallov diaphragm. Low impedance. Switch craft A3M connector. 2-conductor clamp and lavalier neck cord assemlong Microphone size: 6" diameter (%" shank di-

virtually eliminates need for external wind screen. Response: 80 to 13,000 18' cable. Supplied with Model 310A ameter). Net weight, 6 oz.



"HAND-ANO-STAND"— enter-tainer's "Single O" microphone Redesigned and improved in response and with increased output level when used close to mouth. Emphasires low frequencies used "close up." Lightweight, rugged construction, with built-in pop and dust filter. Smooth, peak-free response shaped for voice presence New model has greatly strengthened cable connector threads. With on/off switch, Black satin chrome finish. Response 60-13 000 Hz. Output: -58 db, HI-Z or Lo-Z must be specified. With cable and 310 stand clamp. Size: 6-1/8" long, 1-5/8" max. dia., %" shank dia. Net weight, 8 oz.



641

\$2587

PUBLIC ADDRESS

HOME RECORDING

PAGING SYSTEMS

Modern two-tone design dynamic

wide-range response. For public ad-

dress, home recording communi-

cations, electronic teaching aids,

paging systems. Integral on/off

switch, wide frequency response, 70 to 10,000 Hz. Output -57 db. 15'

cable. Case is chrome plated die-cast

zinc and gray high impact plastic Standard 5/8"-27 thread stand con-

nector, Hi-Z or balanced Lo-Z must be specified. Size: 4-1/2" long.

1-3/4" diameter not including stud.

Net weight, B oz. less cable.

MODEL 664 \$5233 RECORDING & P.A.

Model 664

MIKE

dioid dynamic microphone with Variable O' feature, for quality tape recording, communications, and pub fic address applications. Allows close talking without "booming" or base attenuation and discriminates against unwanted sound. Blast lilter mini mizes wind effect, and Acoustalloy diaphragm is shielded from dust and nagnetic particles. Qual Lo-Z and Hi-Z. E-V OC-4M cable connector permits easy change of impedance by moving a single pin, Risponse 60-15,000 Hz. Output -58 db. On/ off switch, pressure-cast case with chrome finish, 15' cable. Size: 7'." long (less connector), 1-7/8" dus. Net

weight, 1 lb.,10 oz. \$52.33 Model 664A-Non-reflecting gray Wired for Lo-Z. Each \$52.33

Model 664G-Gold finish.

Each

Dynamic Cardioid Microphone BROADCAST QUALITY MODEL SUPER REIO 80 - 13,000 Hz \$9173 LO-Z Output Model RE10

SUPER CARDIOID- Similar nd construction to the Model RE15, but for applications requiring slightly less rigid performance toler ances. Fawn beige Micomatte finish with black grill and "backbone Response: 80-13,000 °Hz, Impedance: Lo-Z Output -56 db. 18' 2-conductor shielded broadcast cable. Switchcraft A3 connector. 6-5/8" long, 1-3/8" diameter (shank diameter). With metal case and 310 clamp. Net weight, 6 oz.



674 DUAL LO-Z and HI-Z

\$ 5586 GENERAL PURPOSE

Madel 674

CARDIOID DYNAMIC- Radically new design brings truly professional quality to public address, recording communications, and other general purpose microphone applications, An exclusive Continuously Variable-D microphone" which assures uniform symmetrical cardioid pattern at all frequencies. Frequency response 60 to 15,000 Hz. Highest discrimination against feedback and unwanted sound. Exclusive three position switch offers controlled lowfrequency attenuation to overcome rumble and feedback when microphone is used at a distance. Studmount for use on floor or desk stand with \$/8"-27 threads. Incorporates on/off switch. Slim design permits full view of person speaking, Rugged high pressure die-cast construction. Acoustatloy diaphragm. Qual Lo-Z and Hi-Z. E-V OC-4M cable connector allows easy change of Impedance without tools by moving a single pin. Output, -27 db, Satin chrome finish, 15' cable, Size: 7-7/8' long, 1%" diameter (not including Net weight, 18 oz.



OVNAMIC LAVALIER- Smallest high quality microphone in the entire public address field delivers big microphone performance Extremely rugged dynamic construction assures lung life, Frequency response, 70 to 10,000 Hz. Acoustalloy diaphragm Hi-Z or balanced Lo-Z must be specihed. Output: -60 db. Non reflecting gray finish 18' cable, Complete with neck cord, clip, and stand mounting clamp, Size: 315" long, 15" diameter. Net weight, 2 oz.



SUPER CAROLOIO- Similar to Model RE10 except incorporates integral blast and pop filter around head of microphone. Specifically designed for close-up vocal use and virtually eliminates pickup of breath noises. Strong, protective metal screen prevents damage in use. Specifications identical to RE10. 7-1/8" long, 1-7/8" diameter (shank %" diameter), Net weight, 8 oz.

MORE TULIP HEAD MIKES Made By Electro-Voice USED IN TV AND BROADCASTS THAN ANY OTHER MIKE

HIGH FIDELITY, HIGH-OUTPUT DUAL IMPEDANCE DYNAMIC MICROPHONE



Model 630

HIGH FIDELITY, HIGH-OUTPUT DYNAMIC- Famous for quality at low cost. Response 60-11,000 Hz. Output level: -55 db. Unaffected by heat or humidity. Acoustalloy diaphragm Tiltable head, Built-In MC-3 connector. On/off switch, Satin chrome finish. Dual Lo-Z and HI-Z. E V OC 4M cable connector allows easy change of impedance without tools by moving a single pin. Size: 64" long, 2" diameter. 15' cable. Net weight, 1 lb.



MINIATURE LAVALIER MODEL 649B \$6762

MINIATURE LAVALIER - Smallest dynamic lavalier - weight is only 31 grams without cable, length 2%", and diameter is %", Ideal for programming where unobtrusive or concealed microphone placement is desirable Frequency response, 70 to 10,000 Hz (rising), Output: -61 db. Acoustalloy diaphragm, Omnidirectional Matches all low impedance inputs. 30' shielded cable, Aluminum case finished in non-reflecting gray. Complete with neck cord, belt clip, model 310A stand mounting clamp, and protective suede pouch





#### MICROPHONE

The Sonotron Cordless Microphone transmits on exclusive, non-interfering FM frequencies.

With a flat frequency response of 60 to 14,000 Hz, and a failsafe range of 70 feet, \*\* this unit provides state of the art sound reproduction.

- Cardioid microphone
- Typical range = 100 to 200 feet\*\*.
- Lightweight, 8 ozs. with battery
- Powered by a 7 volt battery · Diameter - 1 Inch shank
- Overall length 8-1/4 inches Anodized aluminum case
- Regood construction
- into from feedback
- 300 hours bettery life
- Dependable solid-state circuitry
- · Base emphasis

TOP VALUE FOR Model WM-88 MOST POPULAR SIZE MINIATURE FM WIRELESS MICROPHONE

Model 1071

RECEIVER AND MIKE

\$330.00

The cordless Sonotron may be used with any standard FM radio. However, for optimum per

formance, Sonotronics has designed a special mat-

For more information about the Sonotron System

(Better yet, give him a call - 303 / 484-9400)

Weight: 71/2 oz.

(with case)

BUILT-IN

lises 9 Volt

Rattery

TIE CLIP MIKE

\$2.95 Ea.

Stock No. TC-295

MIKE

ching receiver which offers the following:

· Lighted Power Switch Balanced Squelch Control

Convenient Tuning Slug

Self-contained Antennas

Contact J. R. Pruyne, President

990 Savings Building Fort Collins, Colorado 80521

Anodized Aluminum Case

FM Tuning Meter

BROADCASTS OVER ANY FM RADIO UP TO 100 FEET

Model WM-88

■ COMPACT—built-in microphone, so small it fits into a pack of cigarettes.

Size: 3" x 11/4" x 21/4" (with case),

■ COSTS SO LITTLE—far less than reyer before possible.

PERFORMS with perfect fidelity

Just tune to brank spot between 88-108 mc on any FM tuner, table model, portable, or car FM and begin broadcasting. You'll come through loud and clear Model SFM-304, Complete with battery and Carrying case.

MODEL 751 FM TUNER IDEAL FOR USE WITH WIRELESS MICROPHONES, WIRELESS GUITARS & MUSICAL INSTRUMENTS, SINGLE FREQUENCY TUNING IN BACKGROUND TRANSISTO. MUSIC INSTALLATIONS.

SALE PRICE \$ 6995



## FIXED FREQUENCY FM TUNER IS ESPECIALLY DESIRABLE FOR INSTALLATIONS IN HOTELS, APARTMENT HOUSES ETC.

FOR INSTALLATIONS IN MUTELS, APARTMENT PRODUCT STATES APARTMENT PROJECT STATES AND A CONTROL OF THE ACTION OF THE FEATURES

Illuminated center scale busing meter — Semi-fixed screed-new tuning adjustment — Butlog AFC circuitry — AFC on-off switch — Squeich threshold adjustment — Squeich on off switch — Separate output packs for music or microphone reproduction — Operation indicator light — Detachable telescopic working advance External antenna migredances of 72 SPECIFICATIONS

FREQUENCY RANGE: 88 to 108 mc — SENSITIVITY: 2 microvorts — FREQUENCY RESPONSE: 20-20:000 cycles =1 db — MUM LEVEL: 55 db below 100 % modulation — TUBER: 1 - 60HBA 3 6AUS, 1 valicon translator, 1 silicon organization of tuber 1 silicon power rectifier, 2 germanium signal diodes — POWER CONSUMPTION: 21 watts. 117 volts, AC, 60 cycles — SIZE 9½ x 7" x 213/13" — SHIPPING WERGHT: 6 lbs.

## SONOTRONICS, LTD.

CORDLESS MICROPHONE

The only FCC type" approved, Broadcast Quality Wireless Microphone System


WM-670 MIKE



THIS WM-670 WORKS GOOD BY TUNING THRU ANY BUT HAS FAR BETTER F-M RECEIVER. PREFORMANCE WITH IS'S 1072 RECEIVER.

NEW AND BETTER F.M. Model WM-98

POCKETABLE WIRELESS MIKE BROADCAST OVER ANY FM RADIO UP TO 100 FEET



NO LICENSE REQUIRED!

Model WM-98

49.95 VALUE!

FM WIRELESS MICROPHONE

MURA ELECTRET WIRELESS MICROPHONE Model WM-127

USES REGULAR 9 VOLT BATTERY

This FCC-approved wireless electret microphone was designed to transmit over any FM radio. It is ideal for public signed to transmit over any FM radio. It is ideal for public address systems, stage performances and industrial in-plant communications. There are also a host of uses for it around the home — watching children, monitoring sick rooms, home entertainment.

This compact, low-cost wireless microphone is powered by a readily available No. 216 9-volt battery. Tunes from 88MHz to 108MHz, and comes complete with entenna, tuning tool and battery. It measures 5-1/4 x 7/8 x 1-3/16° and weights only 3 ounces

NEW 1972 MODEL

FM WIRELESS MICROPHONE

COMPACT **★ DURABLE** 

\* STATIC FREE

\* WILL NOT DRIFT SIZE: 4%" x 1" x 1" WEIGHT: 3½ OZ.

is a precision-engineered microphone, designed to transmit over any FM radio. It gives professional performance with full fidelity. Will not create static or other interfering noises. Does not "drift" but remains stable and reliable hour after hour. When powered with two long-life batteries (not supplied) the WX-127 will operate up to 200 ft from the audio source, Conforms to all

WIRELESS MODEL WX-127

FCC requirements as to power output, frequency tolerance, etc. Measuring 4%" x 1" x 1", it is easily concealed. Can be used in many applications such as for PA systems, theatrical production, audience participation or wherever remote pick-up is required--all without messy, cumbersome wires. Priced amazingly low for such a quality instrument.

## VIDLAND. **Stereo Multiplex**

SOLID STATE Receiver

F.E.T. Front End Stereo Indicator Light

Model 19-549 Sole Price.

50 WATTS

**500**95

Special Purchase Sale



- spart 40 manufacturing to the second section of the second second

## "SPECIAL BUYS"



Calrad NEW PROFESSIONAL

DYNAMIC STEREO HEADPHONES!

COMPARE WITH PHONES COSTING UP TO \$30.00

SENSITIVITY

ITS dill at 1,000 fts 1 mW MODEL \$1795

RIPH QUANCE

Be dhima, back channed 15-114

REP QUANCE COROL 13 R called gard and: 37 phone plug

COROL CTONG COROL 13 R called gard and: 37 phone plug

A phone plug

Le projection development of coroling and the projection development of patient with grade to the sacky advisable with returns correct on each proper with good ten trapping or corpores full riping and male is the production development. The projection of the pro

## MCGEE SPECIAL



AKAI STEREO HEADPHONES UNEXCELLED REPRODUCTION FROM 20 TO 20,000 HERTZ ASE-9S Dynamic Stereo Head-

phones with Tone Con-

SALE PRICE \$ 19<sup>95</sup> ASE-20 Dynamic Stereo Headphones with Volume Control.



## Super Deluxe Professional Stereo HEADPHONES

The Ultimate for Music Clatening " Complete States Separation " Privacy and Comfert COMPARE WITH PHONES COSTING UP TO \$60.00 FREQUENCY RANGE: 16 to 22,000 MATCHES 8-16 OPMS.

SENSITIVITY: 1000 do or Frequency Labout 15-115 124 95 NET of 600 for 1 mW

## OGEN50-Watt STEREO AMPLIFIER A HIGH QUALITY SO WATT AMERICAN MADE AMPLIFIER AT PRICE OF AN IMPORTED AMPLIFIER!

With inputs for phono, tape and tuner, plus front-panel headphone output.

TA 150 50-watt All-Silicon Solid State Stereo Amplifier

25 - WATTS PER CHANNEL



flat from 20-50,000 Hz., distortion less than 0.5%. And a hefty 50 watts

Accidental shorting of speaker wires will not blow transistors
FUSED FOR COMPLETE PROTECTION
SPECIFICATIONS POPER OUTPUT MARIMUM INP 0 and continue. 25 watto per abutes 1) 50 watto continued.

PEAK POWER: 35 muits per channels, 70 wests desce-

NAMONIC DISTORTION Love then 0.5% INTERMODULATION DISTORTION (Love, then 0.5% POWER BANDWIDTH 20 Note 20,000 Hz. PROQUENCY REPOWER 19 do., "Bit to 00,000 Hz. (Subsected Replant 20 Hz.). The Control of the Control of

SEASITY VIEW Hoper removed the full over-th Photo-Med. 7.5 mer, AUX, 125 my. NOISE AND MUN (Buden; retred over-th) TO sh. Phuan Mus. 55 dt., Fundaner

CHANNEL CROSSTALES 50 00 01 1006 Ha.

POWER CONSUMPTION Lifting, 26 water, Full Power

Both Channels, 100 watth.

PONT PANEL CONTROL to Selector Seatch, Mode
Septch, Loudones Control, Power Switch, Boisence
Control, Bass Control, Treble Control. Surjah, Louderes Control, Power Surjah, Selence Control, Bann Control, Troble Control. OUTPUTS: Speakers 12 part), Tape Output and Head-

OUTPUT IMPEDANCES & B. In minus INPUTS Phone Blat, Tape Amp. AUR, Tuest.

SEMI-CONDUCTOR COMPLEMENT: 20 transjujers, DIMENSIONS 1401" mide a 10" deep e 314" high-

WEIGHT 11 pounds

# THRMER 4 Ft.

MINIATURE CARDIOID MICROPHONE

LOW IMPEDANCE PAGING PUBLIC ADDRESS AND

GENERAL PURPOSE \$1195 \$2850

\$40.00 List Value

A ministure cerdioid. weighing loss than three ounces. Length, six inches; head diameter, 1-3/16", m model 52850 Dynamic Cardiold Microphone

A new addition to the line and an outstanding value. May be used in the hand, or, utilizing the handy accessory included, as a lavalier, or place it on a table-top. Highly directional, it effectively Cancels sounds arriving from the rear. Smooth, peak-free response to sounds arriving from the front, Range 70 to 12,000 Mg. Tough, durable Cycolac housing, Low Impedence.

4 ft. cable. 150 ohms -62 db (0 = 1 mw./10 microbars).

## Mc GEE SPECIAL OFFER

WITH TWO ADAPTERS
Temphylor Lett of heavy daily shalled
freeholder lett of heavy daily shalled
freeholder lett with translate distanphone connectors an each and Adepare convert to "S" phone give or "S"
freeholder lett of the shaller letter or the
freeholder letter of the shaller letter of the
freeholder letter or "B" phone given, duty,
areywing sea. This averaged assessment
freeholder makes are "B" a system once Bas.

When purchased with above Microphone MICROPHONE EXTENSION CABLE KIT

Cur Ma 25 MT Regular \$2.99



Bookshelf speaker system with console sound reproduction



12" 3-WAY 3-SPEAKER SYSTEM REGULAR NET \$99.95 EACH HERITAGE HS1-C SOLD ONLY IN PAIRS

PAIR

ONLY AT MCGEE CAN YOU BUY THIS POWERFULL SPEAKER SYSTEM AT OUR LOW PRICE

12" MEAVY DUTY WOOFER has a large (1-1/2") value coil and 20.0 exemic magner. MIDRANGE COMPRESSIDN NORN is molded of a non-resonant fibre. 3.0 aunce examic magner, 1" voice call diameter for excellant efficiency and response. S<sup>16</sup> TWEETER has a closed steel from to prevent intermodulation from the back pressure of the woofer. RESPONSE: 30/19,000 Nz. PEAK POWER HANDLING: 40 wolfs. IMPEDANCE: 8 ohms. TYPE CROSS-OVER: N.P. copocitor. SMIPPING WEIGHT: 46 pounds. CABINET SIZE: 15 x 25-3/4 x 14" deep. 3/4", 5 ply, cross-banded, hand-rubbed, etled wolnut veneer finish. 1/2" fibre glose on three inside surfaces. Internal volumes 4.135 cubic Inches. Equiped with a brilliance control on the tweeter

LIGHTWEIGHT HEADPHONES

Calrad monaural headphone for educational use, complete with deluxe ear cushions, cable and 2 way phone plug, impedance 8 ohm.

No. 15-122

No. 15-123




### 337 STEREO HEADPHONES

- air-cushioned soft rubber earpads
- 8-16 ohms impedance per phone
- frequency response: 20-18,000Hz
- for use with stereo units:
- individual volume control on each

black/ivory color:







High quality, low cost steren headphones. An excellant buy. Covered headband, foam pads, six foot cord with 3 conductor phone plug.. Frequency Response; 30-18,000Hz. Impedance; 8 ohms. Power handling 1/2 Watt



99

Squipped with padded whedbend, padded e-roups, tost, coiled cord and the Novest type 81:00 Yolone and Tone Controls. Each side equipped with newest type Tyler disphragm accessor for excellent tone quality.



Made in western Germany

20-249

Cairao deluxe pillow speake: with volume contrai employing bone conduction principal. Perfect tone reproduction hi-impact case, black HEADPHONE vinyl finish.

STEREO HEADPHONE "Y" ADAPTER Stock No. \$199

839 Far dual hookups, 36 in. cable has two 3-circuit 1/4" jacks one end, and a 3-circuit plug on other end. Stock No. 839

HEAVY DUTY 20 DELUXE COILED STEREO HEADPHONE EXTENSION CABLE Stock No. CE4R

Heavy duty 20' deluxe coiled stereo headphone extension cable. Stretches out to 20' when fully extended, Complete with molded 3 conductor plug and Strain relief for extended usage. No. EC4R

39 EAR-1

CRYSTAL EARPHONE Extremely lightweight, compact and 10 FOR sensitive high-impedance type ear\$3.75 phone. Has clear plastic aspiece which may be removed in allow use as crystal mile. Fer use with pocket radios, etc Complete with cord. Packed in clear plastic bag. Less plut and inch.

DYNAMIC EARPHONE

#### EARPHONE WITH PLUG & JACK

Low impedance (IS ohms) high quality reproductions frequency response, 50.
4,000 cgs. Flesh colored plastic case and the cord with ministure phone plus and closed circuit Jack. Connects directly by the secondary of outpet transformer; excellent for private radia and IV listensesses and the color of the private radia and IV listenses to the color of the c



#### DYNAMIC EARPHONE REPLACEMENT

FOR USE WITH
EMERSON ROLAND
MOTORDLA SENTINEL CAVALIER PHILCO WESTINGHOUSE ZENITH R-SOO

9¢10 FOR most Transistor Radios Cat. No. DE-451 -- lew Impedanc



#### DYNAMIC EARPHONE REPLACEMENT

Cat No. 49¢ 10 FOR Transistor Radia \$4.50 tat. No. DE-152 - for impolan



## REPLACEMENT EARPHONE FOR MOST JAPANESE RADIOS

FOR MOST JAPANESE RADIOS

WITH USTRA INIVIATURE PLUG

Low impedance eriphone with

ours our support. This earphone has the
sub-ministure plug needed for most

Japanese transistor radios. Dynamic

DE-153 10 FOR \$4.50 hearing or type for high quality



## DYNAMIC EARPHONE

Low Impedance Dynamic Eerphone with 20-ft, cord. Specifically adopted for TV sets. Ideal for private listening. Has many other uses. Includes plug. Indi-industry packaged on plastic bar Cat. No. 69¢ 10 FOR DE-156 69¢ \$6.50

## HI-FI STEREO AMPLIFIER FOR HEADPHONES



No.AHIC

The size of this little amplifier deceives the most discriminating Hi-Fi enthusiast. When headphones (it has provisions for two pair of stereo headsets) are plugged in, the recreation of acund coming from the phone, tuner, recorder or other audio device is as near to the original as possible. Has separate level control for each channel. Completely transistorized. Comes in an attractive wainut cabinet.

STEREO JUNCTION BOX



CHANGE FROM SPEAKER TO HEADPHONE Simply slide switch to change

The Colrad Junction Box Is designed to add one or two pair of Sterea Headphones to a one or two pair at Sterea Meadphones to a sterea amplifier or receiver or two mono amplifiers used in sterea. Sterea headphones volume may be adjusted independently. The selector switch allows the speakers to be turned on while the headphones are on for monitaring or turned off for private listening. Size: 2½" x 4½" x 1½" high. Slanting front. Complete with wiring diagram.



FSP-R \$95.00

PRO-4A \$50.00 KO-727B \$34 95

Fomous PRO-4 A PROFESSIONAL HEADSET

A newly improved headset engineered to meet the most rigid requirements. Augged construction makes it both shock and shatterproof. Adjustable, spring steel headband has extruded plastic cover and foam oad for total comfort. Fluid-filled eushions fit head contour for efficient seal, providing almost complete attenuation of ambient noise. Specially designed drivers in acoustically tailored enclosures furnish an unusually smooth frequency response. Knurled knob on left cup is mechanical mount for boom









SP-3XC

\$19.95

microphone attachment. Removable cushions and 10' colled cord. Impedance: 4.50 ohms. \$5,0.00

Electrostatic and Dynamic models. Extra fine audio sound.

## PRO-4 AA net. \$60.00 Similar to A model but more bass. WIDE RANGE STEREOIKO \_ 727 B

Designed to provide breathtaking, full dimensional This is sound to stereo with outstanding realism delight the truly discriminating audiophile. Highly sensitive sound reproducers will accept up to 80 watts per channel from any normal program source. The adjustable headband is combined with foam filled ear cushions to furnish comfortable, private listening for hours on end. This close, yet comfortable fit also accounts for the exceptionally high cancellation of external noise. Can be used with systems having DESIGN BREAKTHROUGH GIVES DISTORTION 2% OCTAVES MORE THAN CONVENTIONAL 1% at maximum output of 143 db SPL. Complete FREE, WIDE RANGE FREOUENCY RESPONSE HEADPHONES — Push-pull electrostatic elements with 10 coiled cord.

\$34.95

## **ELECTROSTATIC STEREOPHONES**

ESP-7

NEVER BEFORE POSSIBLE IN HEADPHONES give smooth, peak-free response, 35-13,000 Hz : 6 db. Exceeds performance of finest speaker systems with out disturbing room reflections

Sound is heard as originally recorded, without loss adjustable, stainless steel headband with extruded headband cover and foam pad; coupling transformers and speaker/headphone transfer switch are located listening environment exactly tailored to the human externally for light assembly weighing only 17 ounces Fluid-filled cushions for excellent seal.

\$95,00 with SE-7 Self-Energizer and speaker accessory cable,

## K-6LC COMFORTABLE LIGHTWEIGHT DESIGN -- Wide LEVEL CONTROL STEREOPHONES

combination of the famous Koss sound and com fortable, efficient fit, with the added convenience of a volume control in each cup. These controls allow the wearer to make fine adjustments in volume as well Fluid-filled cushions for excellent seel.

as balance without returning to his receiver or control

SELF-ENERGIZED FOR CONVENIENCE — Use with center. 10° coiled cord. Impedance: 4-16 ohms

\$29.95

\$50.00

with SE-7 Self-Energizer and speaker accessory cable. All the features of the K-6LC, above, except the level machine-run response curve and instructions. \$79,00 controls. Spring steel headband and foam filled cushions form an effective seal to make possible the wide frequency response. Impedance: 4-16 ohms 10' coiled cord \$26,50

#### this Koss model under \$20.00 SP-3 XC STEREOPHONES

The standard of quality. Will reproduce any sound the human ear can hear. Extremely sensitive 3%" sound reproducers mounted in each ear catch the hidden sounds of your recordings. Vinyl covered foam ear cushions provide lightweight comfort for extended listening periods. Impedance: 4-16 ohms. \$19.95 10' coiled cord

#### K-6LC \$29.95

## STUDIO MONITOR ESP-9

WIDE RANGE RESPONSE for critical, controlled monitoring of finest recording sources. 10 audible octaves, 16-15,000 Hz ± 2 db, 4 octaves beyond ordinary headphones

DISTORTION-FREE PERFORMANCE through precision electrical balancing of push-pull acoustical cir cuitry to give fatigue-free listening through long recording sessions. Elements cancel all 2nd harmonic distortion, unlike conventional units.

LIGHTWEIGHT FOR COMFORT - Fluid-filled outhions for distributed gentle pressure with good seal. Coupling transformers and circuitry are located in E-9 energizer. Adjustable stainless steel headband with wide cushion for perfect fit and restful listening

NO SPECIAL AMPLIFIERS REQUIRED -Connects to low impedance speaker terminals of any good amo:

Model ESP-9 Studio Monitor Electrostatic Steragphones, complete with E-9 Energizer, ac line cord, machine-run response curve and instructions. \$150.00

#### ESP-7 ore all three

These ESP-9 ESP-6

ESP-6

\$26.50

Reproduces 9 of the 10 audible octaves. A new era in personal listening is now available to the discriminating music lover at 10% the price of the finest speakers of stereo from wall and ceiling reflections. Spurious room resonances are banished by the controlled Completely self-energized and self-contained Frequency response: 27-19,000 Hz + 5 db

Model ESP-6 Electrostatic Stereophones: Complete SE-7 Self-Energizer contains all necessary circuitry.

with 10' coiled cord, T-3 connector box and speaker with 10' coiled cord, T-3 connector box and speaker Model ESP-7 Electrostatic Stereophones Complete STEREOPHONES K-6 run response curve.

#### REMOTE CONTROL STATION

T-10. Provides Stereophone and speaker control from remote location. Has jacks for 2 sets of Stereophones. Left and right channel volume controls and speaker on/off switch. Metal cabinet. \$9.95 and speaker on/off switch. Metal cabinet.

#### EC:25KK

COLLED STERED EXTENSION CORD

25' long. Can be used with any Stereophones fined with 3 conductor, stendard phone plus. \$7.95

## Genuine accessories for Koss Stereophones.

2 PHONE EXTENSION CABLE

TPA

STEREO PIN-TYPE ADAPTER CARLE

For connecting Stereophones to portable phonogers plug-in speakers. Stereophone jack on one and, 2-pin-plugs on other and.

#### SPEAKER/HEAOPHONE/TRANSFER SWITCH

Connects 2 sets of Stereophones to single headphone lack. Provides a speaker on/off swritch and a Stereophone Adds 3' to phone cord length. \$5.95 jack. Connects to speaker terminals of amplifier of jack. Connects to speaker terminals of amplifier or receiver. Adds low impedance jack to system for w \$7.95 range performance of Stereophones

STEREO PHONE PLUG ADAPTER CABLE

\$3.75 Same as 0.5 G but for phonos and tage recorders with 21 \$6.75

#### SHURE STEREO PRE AMP



Mo d e I A low-cost, versatile, compact, low distortion and low noise stereo preamplifier that provides Mo d e I gam, equalization, and choice of impedances and level to solve an unusually broad variety of magnification

IDEAL AS A BROADCAST PHONO

Can be used as a high-quality, low-cost phono preamplifier in broadcast applica-tions with the simple addition of Shura A95A external Line Matching Transformers for balanced line output. des 13.5 or 32 do gain with 7½ (PS NAB equalization for tape decks contain-o electronics. May be used to feed signal directly from tape head through hi-li-to preamplifier.

BOOSTS MICROPHONE OUTPUT

EQUALIZES AND AMPLIFIES

SOLVES DEALER DEMONSTRATION

CONVERTS PHONOS TO ACCEPT MAGNETIC CARTRIDGES

Converts caramic phono inputs for use with magnetic cartridges. Permits use magnetic cartridge with "package system"—high fidelity" consoles supplied wit ceramic cartridges. Allows smoother, more natural sound.

## TRIMM HEADSETS: GROUP INDIVIDUAL LISTENING LORGNETTE PHONES Model BEST FOR CHURCHES 124-2K NET\$695

ship, wf. oprox 8 oz per item.
The most widley used earphone for group hearing oid and systems for churches. Order the model 124-2K for use with the 460 or 461-10K. Connect to the 70 volt audio line of your amplifier. The 124-2K will also work on 16 ohm, but the arder the 460 or 461 1K Each lorgnette has a 6 foot gord and phone plugto use withe the volume control boxes shown below.



VOLUME CONTROL AND OUTLET BOXES
For use with lorgnette phones
formed metal boots measuring 39% 27% 17%. All edges and corners
are rounded Analiable in Brown and in Gloss lovery,
specify color and control res. net \$360

Single Control - Single Jack Outlet Boxes

Resistance Brown 461-10K FOR 7 tyory 460-1K 460-10K

82

# ship wt. oprox 2 lb:

TRIMM


Model 632 net. \$750

> Two for \$14.50 Trimm 24-8

and 631 control as illus.

Headset Kits For TV and Radio

Provides a simple means of attaching headsets or extension speakers to TV or radio sets. Has remote on-off switch for loudspeaker, a volume control for the headset and two jacks for multiple listening. Complete kit includes headset or single earphone with plug, control box and 15 ft. of connecting cord.



A superior low-cost headset.
Recommended for crystal sets,
code training, etc. Black bakelite
shell and eap. Chrome steel magnet. Double headsets, brailded 4/4
feet thiset cord, chinic headsets, led
vinyl 44/4 cooked (20,00ms) Net Each.



No. 24-Double (2K ohms). Net Each Ho. 24-Double (4K ohms). Net Each.

### TRIMM STEREO AND REG. HEADPHONES

Intended especially for high quanty communication systems requiring extended from years. Particularly suffeble for tendency years. Particularly suffeble for tendency training systems, broadcast stations, the and stereo, in addition to a variety of military communication uses. Lightweight and more comfortable to wear than most high-grade headsels. Extremely durable construction. Actual sound generaling unit is enclosed in a capsule Uses mylon-braided 6-foot cord. Standard headest, terminated with No. 510 plug. stereo type (50-14) with No. 516 plug (0.250 dla.) Double headsets are available in impedances istated below. No. 654, 655 and 656 ear cushions may be used, decending.



individual et 352

Trimm No. 50-06 -600 ohm. Net Each

Trimm No. 50-08-8 ohm. Net Each. Trimm No. 50-2M 2K ohm. Net Each. Trimm No. 50-12M 12K ohm. Net Each.

\$14.11 Trimm No. 50-14-6M-6 K stereo, Net Each. .... All Trimm Model 50 Series phones are equipped with a standard headphone plug.

TRIMM

made in U.S.A. 24-9-2K 11 st \$5.40

\$319 \$300 2 pair

Regular Trimm headphones with standard phoneplug as illus. 2000 ohms imp. work on most anything, most popular



#### "TELEX COMBO" Headset \$19.95 STEREO

Impedance | ELEX Hi-Fi



No. 6

## Professional Quality SERENATA No.1 Stereo

SERENATA No. 1 Stereo

Bere's the all new TELEX headset with professional quality stereo sound features and performance never before offered, Electronic tone control. -- asy knob adjustment of ear cup pressure -- smooth, clean design -- completely adjustable for greatest comfort. Equid filled cushions; detachable 8-ft cord Frequency response 22-20,000 cps, distortion at normal tistening tevel less than 1/2%. Color -- dark brown and beige. Impedance 8 ohms. SERENATA S FOR 600 OHMS. pedance g ohms.

\$44.95 THOUSANDS SOLD FOR \$59.95

TELEX MAGNETIC PILLOW SPEAKER



SMYSA 15 ohm

\$3995

Model EN-5

#### AMERICAN MADE HI-FI HEADPHONES AT THE PRICE OF **FELEX** acoustics IMPORTS

Wt. 10 Oz. NEW TELEX "ENCORE" MODEL EN-5

50-18,000 Hz STEREO HEADPHONES

Special cup design provides extremely light weight stereo headphones with wide, adjustable headband, foam filled vinyl corcushions, for ultimate comfort & excellent stereo sound. B' cord & stereo phone plug.

McGEE SALE PRICE \$ 95

SUPERB PERFORMANCE FROM UNBREAKABLE ECONOMY CLASSROOM SETS

Telex 300/600 series surpass the specifications applied to general purpose classroom headphones. Magnetic elements reproduce voice communications with accurate fidelity, Attractive and rugged construction in brown and white high impact ABS plastic make these units shockproof, moistureproof and childproof. Spring steel headbands allow ample adjustment. Equipped with 5' hill flex tinsel cord and molded %" plug of unique size to fit both straight and right angle applications. Available in 600 or 2000 ohim impedance, Telex 300/600 series headphones are so economically priced as to be suitable for equipping entire classroom installations.

EARCUSHIONS - models 600 and 610 come with circumaural earcushions which lock in transmitted sound and Insure long hours of convenient latening. Most institutions prefer cushions because they are economical, comfortable, and are removable for easy cleaning. BOOM MICROPHONE — model 600 offers a choice of either a noise

cancelling dyanmic or high impedance ceramic boom microphone. Microphones are designed for operational ease and adjustability. Cadmium-bronze twin shielded cordage extends the flex-tife of the units.



SERIES 318, 010, 807 SPECTFURTHERM

adaptions — Magnesia:
Impedance 400 ohm or 2,000 ohm Isse ordering information).

Sensibitive 103 do 3PL 2 80b at 8 % with 1 mm Input.

Frequency Response 40-10,000 Ns useois.

Moles Cens alling Opnamic. Impedance 300 ohm.

Noise Cens alling Opnamic. Impedance 300 ohm.

Sensitivity (sepen circuit) 48 do 5 2 8 b below 1 volt per information of 1 6c.

Effective Reposition 13 do

Frequency Response 100-8,000 Ns 2 7 db.

Ceremic. High Impedance.

Sensitivity Ipohn circuit) 48 do 2 8 db below 1 volt der microber st 1 6c.

Frequency Response 50-8,000 Ns.

Get and Terminations 18 ft. cards. Moddas plugs 1,200 dks.1 ftr both straight and right ample apericuses Mic. plug ridd.





310 HEADPHONE

610 HEAOPHONE 600 / DYNAMIC MICROPHONE 600 / CERAMIC MICROPHONE

Order Catalog Number	310-1
Headphone Impedance	600 ohm
Earcushions Removable for Cleaning	None
Boom Microphone Type	-
Weight - Complete Unit	6 oz
Educational Net Price Each	\$5.96

010-1	010-2	QUU- I
600 ohm	2000 ohm	600 ohm
Yes	Yes	Yes
		dynamic
8 oz	8 oz	12 oz
\$6.95	\$6.95	\$19.95

600-3	
600 ohm	
Yes	
ceramic	
12 02	
\$21.95	- 60
	600 ohm Yes ceramic 12 oz

## TELEX Hi-Fi Accessories ALL NEW "ADJUSTATONE"

Stereo Headset with "Forward Sound"

ONLY \$15.95

TEL-1595

Greal Interrupt — all a new lots price. Big 3½ " speakers deliver terrufic beas response and glean, clear highs. Head phones are eversable in provide rout from "genomial" in head a serve sound effect, as desired. Floan conhibition rugged telephone stype plantic code and greenance, rungged telephone stype plantic code and greenance, components. Charcool of lewern soler with allver trim. Fre quericy response 18-10-00 ups. Impedance 316 ulnes. Card length 8 (eest. Colors assistable: Charcool of Brown. Specify when ordering. Addjustation.



## **TELEX "1200"**

### TELEX BRAND. Hi-Performance Language Lab Headset

amic boom mecrophone headset. Ex [186] at critical puests. Noise carresting sty built to meet the most stringers (187 name marcophone resistes 310 degrees uncernst) of language reachings. Field Fully desibation, can be wern under the recolder tamper proof designs. My lar (this High impact plastic and statutes see driver. Four filled vivry) ear steel the reduced of the rentre of a country of the rentre of

WITH BOOM MIC 1200-22 — Brown & White 1200-12 — Gray & White

S32.60 1210-02 — Brown & White \$24.75



MADE U.S.A.

TELEX "MONOSET"

TELEX -TELESET" (HM-100) MADE IN U.S.A.

\$7.55



TELEX STEREO EXTENSION CORO STX-1 \$4.50

\$10.50

TELEX DYNAMIC PILLOW SPEAKER

since absorber sing Safe tary. Queaty attached radio. TV or amplifier a Replaceable cord and id SDN-2A \$6.55 SDM-2A 50 00



Unique TELEX continuous piece tone arm ... for greater sound depth and charity. Replaceable foam plassife ear tips, tided unit for moustoring, secretarial use, home latering 5 ft rurd. Frequency response 60 to 6,000 cps

HFR-91 15 ohms HFX = 1000 ohms HFW = 125 ohms HFY = 2000 ohms HFW = 500 ohms

## THE FANON "CLASSIC" SERIES INTERCOMS

Feature: Integrated Circuits for optimum performance and reliability



IN-505 - 2-CHANNEL WIRELESS INTERCOM SYSTEM

Features hi-power IC circuit for extra range and sensitivity. Two-channel operation permits wider use with less interference. Special filter circuit minimizes background line noise. Operates room-to-room or between buildings on the same line. Units have pilot light, on/off volume control, talk-listen switch with lock position for continuous transmission and channel selector switch. System can be expanded by adding several extra single stations, Model IN-500, Ivory/brown with wood grain accents. 117V AC. 7" x 3½" x 2". 3¼ lbs. \$31.95 PAIR

IN-500 Single wireless station, 1% lbs. \$16.95 each.

## Master-to-Master New Concept!



Exclusive design features plug-in connectors for "instant installation", Fully selective; any station can speak to one or more other stations. Up to five stations in a system. Permits conference calls. Two separate conversations may proceed simultaneously, 50 ft, multi-conductor cable with plugs Included, Anyone can hook up entire system in minutes. No tools required!

Powerful IC circultry allows distances of 500 ft. between first and last master station. Press-to-talk switch has lock position for continuous transmission. Pilot light, Ivory/brown with wood grain accents. 7" x 3½" x 2".

3% Ibs. 117 V AC. \$29.95

6C-50 Additional 50 ft, length of cable with plugs. Used optionally with IN-600. Several cables can be plugged end-to-end for desired length. 11/2 lbs.



See Accessories Below IN-302 - NEW HI-OUTPUT 2-STATION SYSTEM

The IN-302 features IC circuit for greater output and sensitivity. Decorator styled with unique press to talk bar. Master has lock for continuous talk, on/off switch, volume control, pilot light. Remotes can signal master even when system is "off". Accepts one additional indoor or outdoor remote station, 50 ft, cable supplied. Ivory/brown with wood grain accents.117 V AC. 7" x 3½" x 2". Shipping Weight: 3¼ lbs. \$19.95 PAIR



#### IN-404 - "STARTER SET" 3-STATION INTERCOM SYSTEM

Versatile system features the IN-400 Mester Station, two IN-2 Indoor Remote Stations, two lengths of 50 ft, cable. Master unit accepts up to four remote stations, indoor or outdoor, Master calls any or several rooms desired. IC circuit for greater output and sensitivity. Pilot light, Remotes have "beep call" signal, Ivory/brown with wood grain accents. 7" x 3½ x 2", 117 V AC. 4¼ Ibs. \$32.95 SET OF 5

#### ACCESSORIES FOR IN-302 & IN-404

MODEL IN-2 - Indoor Remote Station with 50 ft. cable for IN-302 & IN-404. 134 lbs. \$8.50 each.

MODEL IN-1 - Outdoor Remote Station with 50 ft. cable for IN-302 & IN-404. 11/4 lbs. \$8,50 each.

MODEL 2C-100 - 100 ft. cable with plugs for IN-302 & IN-404.1/2 lbs. \$3.75

## **Pocket Paging Systems**

Choice of 20 and 110 capacity systems.

· Far reaching · incredibly simple to install and operate · The Fanon pocket system is a radio controlled method of signalling to selected personnel within your building or up to half a mile away from a central location.

The persons selected to receive these private signals simply keep a small receiver, weighing only 2 oz., in their pocket or clipped to their belt. If any one of them needs to be contacted, your switchboard operator presses the specified numbered buttons on the central push-button selector console, and a beep is emitted by the receiver of the person being paged. The beep will remain on until the individual turns it off.

The system operates on a 5 watt Class C Citizens Band signal on a frequency of 27.255MHz. The receivers are each powered by two mercury batteries that will give up to 500 hours of life. Each receiver has a built-in operations-battery tester.

Model EN-20 offers a capacity of up to 20 pocket paging units. Model EN-110 can start with as few as 5 units, but has a built-in capacity for enlargement to 110.

## THIS SYSTEM HAS ALREADY BEEN INSTALLED IN LARGE UNIVERSITIES AND HOSPITALS

IT IS WORKING UP TO 3 MILES WITH A LARGE OUT SIDE





Masters available in 5 or 10-station capacity; operate universally on 110-120 volts, AC or DQ U.L. Listed. Sub-Stations do not require connection to an electrical outlet, start a system with 1 Master and 1 or more Subs. Add Subs later as necded. Works willingly for pennies a day.

Master can tafk and listen to any Sub-Station individually, more than one Sub at once, or to all Subs aimulaneously. Subs can reply and originate calls to Master, but not talk to one another. Built-in control enables Subs to function "privately" or "non-privatel", and locked in position desired, Master remains "private" in either case. When "non-private" you can reply at a distance from Sub without using controls. Master cannot listen-in to Subs when system is "private". Master and Sub can originate calls to each other whether system is "private" or "non-private". Master's rugged, high-gain transistonzed amplifer is built to

Master's rugged, high-gain transistonzed amplifier is built to withstand continuous use and to require a minimum of maintenance. Volume adjusts from a bare whisper to the full output of the powerful, high-gain amplifier.

Transfucent Indicator, illuminated by permanent-type bulb on Master, shows when system is "on".

Master, shows when system is "on". In modern, custom-designed cabinets that combine the look and feel of fine gramed feather with the strength and rigidity of side. Beautifully finished in charcost gray and brushed chrome. Resists abuse and use... even corrosive industrial liquids and atmospheres. Hi-Power Sub-Station K-HP-MV) and Horn K-C-20(V) can be used in place of regular Sub. Ideal for paging and for large and noisy areas. Provides 2-way conversation (as does regular Sub); also provides origination-of-call when used with K-S-100 Wall Switch K-HP-3V) furnishes more than twice the volume of K-LR-3 regular Sub; K-C-20(V) furnishes 4 times greater volume than regular sub.

K-AC HI-VOLUME MASTER. The K-AC-9406 Master and K-AC-9411 Master operate as above with the added feature of 10 times volume output. Use in place of K-ML-10 Masters where stations will be located in large or noisy areas, and for paging. For 120 volts, AC only, U.L. Listed.

#### OPTIONAL EQUIPMENT

Wall Switch (Model K-S-100), when combined with K-HP-3(V)
Hi-Power Sub or K-C-20(V) Horn enables the K-HP-3(V) and
K-C-20(V) to also originate calls to Master.

K-C-20(V) to also originate calls to Maxter.

Cradle Phone (Optional, add Suffin "H"), can be installed on any Master or Sub (except Models K-LR-3R, K-MP-3(V) and K-C-20(V). Provides listening privacy and greater speaking convenience. Diminishes background noises in noisy areas. Cuts off incoming volce from loudspeaker when in use.

Wall Mounting Brackets (Optional, Model K-WI), for use with Models K-LR-3 and K-LR-3M deak style Subs. Enables these Subs to be mounted on wall, sade of deak, etc. with front panel upward, downward or aideward. One pair required per station.

Surface Mounting Accessory (Optional, Model K-SM-L). Use with K-ER-3R for mounting on wall, side of desk, etc.

#### MASTER SELECTIVE MODELS

Model Description Stre	List Each Net Each
IC-MIL-B Muster for up to 5 Sub-Stations.	\$65.00 \$49.96
103' wa 83' 0 x 33' 6, Wt , 7 Stations	\$105.00 \$61.60
K-AC-5406 N- Volume Meater for up to 5 Subs 10%" wa 8%" d a 3%" h, WI., 7 lbs.	\$105.00 \$61.50
K-AC-8651 Hi-Valume Master for up to 10 Subs. 103/2 w 6 6%" 8 + 3%" H. WI . 3 The.	\$125.00 \$73.80
IE-LIE-3 Desk style Sub. Deluce finish. 7)(" or 1 4)(" d a 2)(" h. WL, 4)( lbs.	\$37.50 \$21.95
K-LR-308 Same as K-LR-3, but in prained, based enamed knesh. \$36" wis 850" 4 x 236" h. W1, 436 lbs.	\$29.95 \$17.50
IC-W1 Wall Mounting Brachate for K-LR-3 and K-LR-3M. Wt. per pair, 1 st.	1.00 % 600 %
K-LR-SR Same as 4:27-3, but for flight wall mounting, Stanless Steel foot panel measures 416/w a 76/4. Wall Opening: 436 w a 65/4 a 2*6, 91, 4 bis	\$29.96 \$17.50
K-BBI-L. Surface Mounting Accessory for K-LR-30, 4% w x 9% d a 7% h, WL, 5 lbs.	\$8.96 \$5.25
NPCP-3 Nu-Power Suo, With 6" speasor and 5-well handling rapporty, Charcost Gray metal cobinet, 12" is x 6" d x 12" h, Wt_ 9 lbs.	\$39.50 \$23.20
K-MP-3Y Same as above, but with purities solume control, edjustable to full autout	\$48.20 \$28.20
K-C-39 Ni Power Re-entrant Horn, 15-watt capacity, For Indoor and Outdoor use. Chercoal Gray, 9", Wt., 6 lbs.	\$56.50 \$33.00
K-C-20V Same se above, but with built-in weather resistant volume control, adjustable to full output.	\$73.50 \$43.00
K-S-100 walt Switch for originating calls through K-HP-3(v) or K-C-20(v), 58° w x 8 N°	\$8.50 \$4.95
d x 1 N N, WL 1 to K-SH11 Wall Mounted Cradiz Phone	\$79.00 \$46.00
"'H" Optional Credit Phone Accessory for any Master or Sub except Models H-ERSR.	
N-HP-3(V) and N-C-20(V), And THT to Model No, when ordering, WL, 3 lige, "Add par station	\$66.00 \$36.00
\$389 3-conductor cable (shielded) for connecting Subt to Master. Provides nose-title cable bres in Office, Industry or Home. For independent outdoor use Approx. O.D.: Nr. WE per 100 ft., 2 lies.	
\$300 3 conductor indoor cable for connecting Subs to Master Approx. O.D.(1 %", Wis, per ICD N., I lin.	7¢ % 4¢ %
	code campant.

All systems are transistorized and come com-



K-LC-2 Carries messages with the speed of sound. Ideal for use in the Office, Home, Factory, Farm and any other commercial or private application.

- Always ready to serve you instantly. Built to witnistand continuous use, this system incorporates modern, custom styling with economy, quality and dependable performance. Works willingly for pennies
- . A complete system . . . includes a Master Station, a Sub-Station and 50 feet of interconnecting cable. Additional cable is available for distances up to 2000 feet, Easy to install and operate.
- . Master and Sub-Station can originate calls to each other and carry on a 2-way conversation. Built-in feature enables Sub-Station to be ou a 2-way conversation, butter reactive matures above substantion to be used "privately" or "non-privately", Master remains "private" in either case. When Sub Is "private", Master cannot listenin to Sub; yet Sub can answer and originate calls. When "mon-private", persons can reply at a distance from Sub without operating con-trols. Master and Sub can originate calls to each other whether Sub is "private" or "non-private",
- Master is equipped with Translucent Indicator, illuminated by permanent-type bulb to show when system is "on".
- · Russed, high-gain transistorized amplifier is built to withstand continuous use and to require a minimum of maintenance. Volus in adjustable from a bare whisper to the full output of the powerful, high-gain amplifier.
- Only the Master Station plugs into an electrical outlet, Master operates universally on 110-120 volts, AC or DC, U.L. Listed.
- In modern, custom-designed cabinets that combine the look and feel of fine grained leather with the strength and rigidity of steel Beautifully finished in charcoal gray and brushed chrome. Resists abuse and use . . . even corrosive industrial liquids and atmospheres. Sub-Station cabinet is of same style and color, but is in grained.

Model Description Size	Each Each	Net Each
K-LC-2 Complete 2-Station System includes 1 Masser, 1 Sub and 50' of #503 cable. Master: 10%' w.x. 850' d.x. 250' b. 505' Typ" w.x. 850' d.x. 250' b.x. Will, 11% (bz.	\$66.00	\$81.80
6393. 3-conductor (affielded) cable for use where additional lengths are required between Master and Sub. Provides noise-free cable lines in office, industry and home. For inflore and outdoor use. 8 ppros. O.D.: 1/4" Wt. per 100 ft., 2 lbs.	The por	8 ∳€ ner
5303. 3-conductor indoor cable for use where additional langths are required between Master and Sub. Approx. O.D.: 16" Wt. per 100 ft., 1 fb.	78 n	4¢ per
"H" Optional Cradle Phone Accessory for Master and/or Sub (specify which). Add "H" to Model No. when ordering, Wt., 3 lbs.	\$66.00	\$30.00
K-W1 Optional Wall Mounting Brackets, Wt. per pair, 1 or.	1 .00 per or,	80¢ per pr.

System is transistorized and comes com-plets with easy-to-follow instructions, read-to install


\*Add per station

#### NEW TALK-A-PHONE SUPER SELECTIVE SYSTEMS

A system of up to 10 Master Statione. Each station can call and communicate with any other, selectively and privately. Several separate 2-way conversations can be held at the same time.







ALL-TRANSISTOR INTERCOM

H-AC MARKE MARTER The K-AC-505 and K-AC-510 Market Sistems operate as above with the adoled feature of 10 times volume output. Use in place of K-35-5 or K-15-50 Markets where stations with the located in large an asset years. For IT havelet, AC could be an interesting the AC-510 to Markets with the located in large an asset years. AC-510 to Markets with the AC-510 to Ma

#### SUPER SELECTIVE MODELS

Model Description Stra	Liei Each	Net Each
K-L5-5 5-Station Master, 1036" w x 8%" d x 3%" h, Wt., 7 lbs.	\$85.00	\$49.95
K-LS-10 10-Station Master, 10%" et 8%" d s a 3%" h. Wt., 7 lbs.	105.00	\$61.50
K-AC-505 Mi-Volume 5-Station Moster, 10%" w a 8%" d > 3%" h, Wt., 7 fbs.	1 05 .00	\$61.50
K-AC-510 Hi-Volume 10-Station Meeter, 1050 w x 830 g x 330 h, Wt., 7 lbs.	\$125.00	\$73.30
**M** Optional Cradle Phone Accessory for any Master, Add "H" to Model No. when order- ing, VR <sub>M</sub> 3 lbs.	\$65.00	\$38,00
5505 (8-conductor) cable for connecting K-LS-5 or K-AC-505 Masters. For Indoor and Outdoor use. Approx. O.D.: X**, Wt. per 100 ft., 3 lbs.	per It. 19¢	per RL 11¢
9011 (11-conductor) exhib for connecting K-LS-10 or K-AC-510 Mexhers. For Indoor and	per ft.	per R.
Outdoor use, Aseros, O.D.; Wr. Wt. per 100 ft.,	38 €	216

All systems are transistorized and come complete with easy-to-follow instructions, ready to install.

Master's regard. Rabiguit transacturard amplifer is built to with a surface amplifer and amplifer in built to with a surface amplifer and amplifer in most account of the surface amplifer and amplifer and without commonte are mel to require a measure of motion amount and surface course is in a common and works without commonte and in account and amplifer and amplifer and amplifer in the surface amplifer and amplifer and amplifer and amplifer in the surface amplifer.

Each Manter min call and carry an a 2-way amovemention with any office Manter, uthorizely and privately, of hold anticenters yeth 2 or more Manters, feveral reports 2-way consertations can be held tomologically willout interfering with our daughter.



## TALK-A-PHONE

Finest Intercom Values... Made in U.S.

#### "CHIEF REDI-POWER" MASTER STATIONS NEW TALK-A-PHONE ALL-TRANSISTOR

Only the TELN-R-PHONE CHIEF' and CHIEF REDI-POWEN' give you all those feelings

INCOMING CALL CHIEFE, a standard feature of Mamers, industris that page Master is being called Caller talks, you exply

with no division of output as you call more stations at once. Connect REDI-POWER Masters with CHIEF Masters and Staffs in the same system in any desired arrangement. Add K-RW-10 or K-RW-20, and REDI-POWER Masters can page any group of stations with a single station selector button. Paged stations can also be used fills intercommunication, as well as reply to paged calls. Operates on 120 volts, AC only, U.L., Listed, Works willingly for pennies a day, in cabinets of same size, style and color as CHIEF Master Stations. These units have all the operational features of the "Chief" Master Stations, plus the additional feature of built-in extra power (up to XI waits) for use when and as needed. Provides reserve volume for calling many stations at once, or noisy locations singly. Needs no sparate power booker, which would eliminate return speech Return speech as requested at "Red-Power" Masters at normal room volume. REDI-POWER Missters have a self-compensating amount of volume, whether you call 2, 10 or 20 stations simultaneously. Each station called receives its pre-determined volume.

#### COMPLETE LIETINGS AND PRICES LIST Net Each Each Model D Model Dascription Model Description "CHIEF" MASTER STATIONS \$191,00 \$112.00 \$214.00 \$125.00 \$258.00 \$149.00 \$295.00 \$173.00 \$338.00 \$196.00 K-C-4906 6-Station Capacity, WL, 15 lbs. K-C-4912 12-Station Capacity, WL, 15 lbs. OPTIONAL EQUIPMENT, continued K-C-4920 30-Station Capacity. Wt., 16 lbs. K-C-4930 30-Station Capacity. Wt., 18 lbs. K-5-181 Walf Switch for origination-of-call to one Master through K-C-20 or K-HRS. 5%\* = 2 %\* = 1 %\* 1 lb. 5 7 7 .5 0 | \$ 1 0 .3 0 K-C-4940 40-Station Especify Wt., 20 lbs. CHIEF REDI-POWER" MASTER STATIONS K-8-102 Wait Switch for origination-of-call selectively to two Masters through K-020 or K-HP-3, 5%" w x 2 x" d x T k" h, WI, 11b. K-CRP-5932 19 Station Capacity, W1, 29 lbs. \$325.00 \$1.91.00 K-CRP-5939 30-Station Capacity, W1, 21 lbs. \$366.00 \$214.00 K-CRP-5939 30-Station Capacity, W1, 23 lbs. \$406.00 \$237.00 2 N° d x 1 N° N. Wt. 1 RD. K-RW-10 Right-of-Way Relay, 4 N° x 9 N° 2 3 N° 7 lbs. \$84,00 \$49,00 K-RW-20 Right-of-Way Relay, Wt., 14 lbs. \$158,00 \$91,00 CHIEF" STAFF STATIONS K-MP-50 Power Booster, Wt., 74 lbs. \$167.50 K-C-41 Originates to 1 master. Deluse Finish: 71% w x 83" d s 2 %" N. Wt., 6 tox. \$51,00 \$29,90 \$98.00 K-W1 Wall Mounting Bracket for K-Cu1, K-C-41M per pr. K-Cu2 & K-C-42M Staffs, Wt., 1 oz. pair. 1,00 K-SM1. Surface Mounting Accessory for K-C-41R, K-C-42R, 44% in x 2 x 1 of 3 7% in, Wt., 2 lbs. 58.95 per pr R-G-61M Same as K-C-41, but has Baked Ename! Finish 1% 48% d 12% h. Wt. 54bs. \$42.00 \$24.50 58.28 K-C-ITR Same as K-C-41, but for Itush wall mount-ing. Stantess Steel Front Panel. I'Ns" a 7hs", Wall Opening 4%" w x 6%" h x 2" d. WII, 4 lbs. \$42.00 \$24.50 Cables have virite plastic 175° F individually covered conductors with over all plastic jacket. For indoor or outdoor use. For the full performance of you Talk-A Phone Units, use only the cable specified. Per it. Per it. K-C-42 Organizes selectively to 2 Masters Deluise Firesh 7%\* wilk 8%\* dis 2 %\* h. Wt., 5 fps. \$63 .20 \$37.00 K-C-42M Same as K-C-42, but has Baked Ename \$84.50 \$32.00 8296 Cable (3-peln) for connecting K-G-41, K-G-41R K-G-42, K-C-42R, K-HP-3, K-G-20 with ongination-of-call. Apx. O.D. N°. Wt. per 100 ft., 4 lbs. 110 6214 Cable (7-pair) for interconnecting K-C-4906 Mas-ters, apa, O.D. 5s.\*, Wt., per 100 H., 7 lbs. 396 23€ Isra, app., Q.D., ½; Wt., per 100 H, 7 lbb. 8225 Cable ("Spair) for interconnecting K-C-6912, K-C-4920, R-C-4920, K-C-6920, K K-HP-3 M Power Sub-Station for wall mounting. Charcoat-gray metal case 17 ws 8" d s 17 h. Wt. 9 lbs. 539, \$0 \$23.20 Objectost-gray meral case for a very superior with built-in volume control, adjustable to full durant. \$48.20 \$28.20 440 K-C-28 H-Power Re-entrant Harm, 15 west capacity. Charcoal gray, For Indoor /Outdoor use 9", WL, 5 lbs. \$56.80 \$33.00 K-C-20V Same as above, but with built in weather resistant volume control adjustable to full output. \$73.80 \$43.80 K-S-111 Wall Mounted Cradle Pages. \$79.00 \$46.00 430 216









All "Chief" and "Chief Regi-Power" Master Stations come complete with junction lips and built-lift power supply attached by 6" flexible cable. Each system contains easy to follow instructions and is ready to install.











K-W1 (ON K-C-41R) K-HP-3V HI-



TRANSISTOR

TALK-A-PHONE

BYYLIR®, Both Maters and Staffs in modern, creton-designed columns that common the limb and find of his grained feature with his strength and rightly of Staff Boundfully findshed in the cold july and insubsid chicken Renatz share and time ... even controlled mixtures liquid his disminusplant, Modern \$4C-[4] in the Colon had been controlled mixtures liquid his disminusplant, Modern \$4C-[4] in the Colon had been controlled mixture share and colon. But Staff in the Colon had been controlled to the Colon had been controlled to

#### TALK-E-PHONE "CHIEF" UNIVERSAL STAFF STATIONS

or Sub-Status (McHPs) and Hopes (KcC-10, can be aved of regular Staff, blen) for purpose mil for force and may review 2-very conservation to down legalar Staff, also for the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the order of the staff of the staff of the staff of the order of the staff of the staff of the staff of the order of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the staff of the order of the staff of the staff of the staff of the

"CHIEF" AND "CHIEF REDI-POWER" SYSTEMS

WORITORING SIGNAS, a standard feature of Massers and Staffs (Businessed by permanent-type bulb, muselly induces to a "temperature" status that at a being monocond. BUSY SIGNAL, a mondard featura of Mannes and Mammoud by permanent type buly visually indicates when you call is "buty" Mesters and Staffs have facility to "buty signal" for receive than calls

DYEASONIC BELECTOR, he exclusive priceined Tablus-Personal receives intertracing of Matter and Staff Statums available of performance Add assumes to syndem or early performance and assume upsteen as any performance of Mattern within syntem at anytime estimate discussion within syntem at anytime estimate discussions.

MULTI-MAGIC STATION SPLECTOR, a patented and ex-claimed Figh-A-Planta (enture, anables arbiction of up to 10 stations with not). If going business will an O and 19 stations with 16 push business..., in the taking advectors caloner style and size

BESPROCAL POWER BUPPLY, a Mandard Scoture of Masters Each Master operates on 110-170 volts, AC costs, and Masters Each Master operates on 110-170 volts, AC costs, and should list placed in Where the electrical caster is a estable, up to 30°, of the Mosters in the system size operate visitous being pringer—in 816 distance do not connect to an electrical caster.

- Wall Switchas (Models K-S-101 and K-S-102), when combined with K-HP-3(V) Hi-Power Sub or K-C-20(V) Horn enables the K-HP-3(V) and K-C-20(V) to originate calls to Master.
   "LO "Long Distance (Optional, add Suffix "LD"), for use over cable lines of 2,000 feet, 5,000 ft, 10,000 ft, or miles without loss of volume. Euroctions only between LD Masters. .. not between an LD Master and non-LD Master, or Staff, Built-in at factory at additional coast.
- LD Master and non-LD Master, or Staff, Built-in at factory at additional coats.

  Right-of-Way Relay (Optional, Model K-RW-10 and K-RW-20), Recommended with Redi-Power Master Stations to page all, or any group of stations smalliameously by depressing a ungle station selector button K-RW-10 capacity, 10 stations; K-RW-20 capacity, 20-stations, connects to one Master. Other Masters also utilize facilities. Requires a station number in system.

  Power Paging Booster (Optional, Model K-HP-50), for use with "Chief" Master Stations to provide paging volume. 30 watts output. Can be used in one of two methods: 1. Connect a group of paging speakers as K-C-20(V), K-HP-3(V) to K-HP-50, then connect K-HP-50 to nearest Master. Paged stations cannot reply but endanged staffs in the system; thus stations being used for normal communications can also be paged. Paged stations cannot reply, but can originate calls in their normal manner, Use maximum of 25 station "All Call" with a single K-HP-50 or feetive Paging volume. For greater "All Call" with a single K-HP-50 and additional Right-of-Way Relays. Under method 1 or 2, K-HP-50 connects to only one Master and requires a station number in system Other Masters also utilize facilities K-HP-50 operates on 120 Volts, AC only, U.L. Listed.

  Cadele Phona (Optional, add Suffix "H") can be installed on any
- Cradle Phona (Optional, add Suffix, #IT) can be installed on any Master or Staff (except Models K-C41R, K-C42R, K-HP-3 (V)and K-C20(V). Provides listening privacy and greater speaking convenience Diminishes background noties in notity areas. Eliminates use of controls in conversation between Masters. Clus off ancoming voice from loudspeaker when in use.
- voice from loudspeaker when in use.

  Wall Mounting Brackets (Optional, Model K-W1), for use with Models K-C41, K-C41M, K-C42 and K-C42M deak style Staffs Enables Staff to be mounted on wall, side of deak, etc. with front up, front down or front sideways. One pair required per station.
- Surface Mounting Accessory (Optional, Model K-SM-L), for use with Model K-C-41R or K-C-42R flush mounted Staff. Enables Staff to be mounted on wall, side of deak, etc.

MON TO DETERMINE CABLE REQUIREMENTS: To inter-connect Manter Stations, measure from first Master to second. Master only, from second to third Master only, etc., until the last unit is the system is reached, and total, far KC-9200 and KC-RP-3920, use two lengths of 6226 Cable; and for KC-9200 and KC-RP-3920, whe two lengths of 6226 Cable; etc. To connect KC-41, KC-20, KC-41 or K-4P-35 Staff Stations, measure from Staff Station to the Master(s) to which Staff originates calls. KC-42 Staff Stations requires a separate length of cable to see the of the two Master Stations to which Staff originates calls. (For each KC-41 or K-C-42, follow same procedure).



CRADLEPHONE





Size of Master Stations-14" w x 3 %"h x 8 %"d.

















## HOME INTERCOM-RADIO SYSTEM-

CENTRAL MASTER STATION

CENTRAL MASTER STATION

Versattie unit can call any station for donversing or monitoring, as desired. Unit contains the amplifier for the whole system, plus built-in radio (optional). Only one Central Master is required for a system, but Additional Masters may be used where separate radio facilities are desired in addition to the Central Master radio. Both Central and Additional Masters can be recessed in wall for flush mounting; or, for cabinet or shelf mounting utilize Housing Assembly HT-SM (as Fig. B). Sizes Front panel, 15½ x 5½.

Phaster ring, 14½ x 2½ x 3½.

Model H-S Central Master (Fig. A)—Flush wall mounting: 8 station capacity; Without radio. Plaster ring and in-truction provided. Likes battery. List Price \$105.00...\$6150

-TRANSISTORIZED

Model H1-5 sub-Station (Fig. C)—With pushbutton to connect regular doorbell or chime; and, illuminated name plate. May be answered by any Master or Staff; no controls of its own, Weather resistant speaker; flush mounting panel 3% x 5%; regulared 2'x 2' x 2' x 2' wall opening, List Price \$31.00 \$1820.

Net Each.

Model K-LR-2R Alternate Sub-Stattes (Fig. D)—For flush mounting. Stainless steel front panel 41% sq. Has no pushbutton or name plate. Plaster ring supplied. Regulate 6% sq. \$ \$17.50.

Medel O-SM Mountine Accessey—Optional unit for surface mts. K-LR-2R on wall. List \$6.30. Net Each...\$3.70



Write for complete information on Talkaphone Home intercom and apartment systems

TALK-A-PHONE INTERCOMSYSTEM 119211111 K-CL-S OR K-AC-405 MASTER K-LR 2 OR K-LR-2M SUE



K-MP-3V HI-POWER SUB



K-C-20V HORN



A system combining 1 or more Master Stations with 1 or more Sub-Stations, up to a combined total of 10. Masters can call and communicate any station. Suba can reply at a dis-ce, but Suba cannot originate calls Masters can answer at a distance. or be "private".

TRANSISTORIZED

TALK-A-PHONE

INTERCOM SYSTEMS

Rugged, high-gain (transistonized amplifier is built to withstand continuous use and to require a minimum of maintenance. Volume is adjustable from a bare whisper to the full output of the powerful, high-gain amplifier.

BUHUUHUM

165116711551171717

PHOTOPHARMA

Translucent Indicator, illuminated by permanent-type bulb on each Master, shows when unit is "on".

In modern, custom-designed cabinets that combine the look and feel of fine graned leather with the strength and rigidity of steel. Beautifully finished in charecoal gray and brushed chrome. Resist abuse and use... even corrosive industrial liquids and atmospheres.

abuse and use...even corrower industrial requision and amospheres. His Power Sub-Station K-HP-3(V) and Horn K-C-20(V) can be used in place of regular Sub. Ideal for paging and for large and more than twice the volume of K-LR-2 regular Sub; K-C-20(V) furnishes about 4 times greater volume than regular Sub.

K-AC MI-VOLUME MASTER. The K-AC-605 and K-AC-610 Master Stations operate as above with the added feature of 10 times volume output. Use in place of K-CL-10 Masters where stations will be located in large or noisy areas. For K-AC-610 Masters with K-CL Masters, or with any other Masters.

Wall Mounting Brackets (Optional, Model K-WI), for use with Models K-LR-2 and K-LR-2M desk style Subs. Enables these Subs to be mounted on wall, side of desk, etc., with front panel upward, downward or sideward. One pair required per station.

Surface Mounting Accessory (Optional, Model K-SM), for use with Model K-LR-2R flush mounted Sub. Enables K-LR-2R to be mounted on wall, side of desk, etc.

odel Description Size Lief Each Net Each (CCL-5 3-Station Master, 10%) # 6 8% 4 \$ 1 02 .00 \$69.95 3% h. Wt., 7 lips. K-CL-18 10-Station Master, 10"% # 4 8%" (\$123.00 \$72.00 33' N. Mt., Pilos.

K.A.C-805, Hi-Volume 5-Station Mester \$123.00 \$72.00

10/5' w a 85, 0 x 33' N. Mt., Pilos.

K.A.C-815 Hi-Volume 18-Station Mester \$142.00 \$83.30

10/5' w a 85, 0 a 33' N Mt., Pilos. K-W1 Wall Mounting Brachets for K-LR-2 and K-LR-2M, W1, per pair, 1 oz. 201 pr. K-LR-2R Same as K-LR-2, but for flush mail mounting Wall-Opening 4½" w = 4½" h = 2" d \$2.9.95 \$17.50 stances 5 test front panel measures 4%" w = 41%" h = W1, 41bs K-SM Surface Mounting Accessory for KiLR-2R 4"46" sq. -2%" d. WI. 1 lb 57.96 \$4.65 K-HP-3 In Power Sub. With 8" speaker and \$39.60 \$23.20 cabinet 12" w 18" d 1 12" h. Wt. 9 lbs. K-HP-IV Same as above, but with built in solume control, requisitable to full output \$46,20 \$26,20 K-C-28 M Power Re entrant Hors, 15-watt capacity, Charcost gray for Indoor and Out-door use 9" WL. Sibs. 556.60 \$33.00 K-C-20V Same as above, but with built in weather saystent column control, adjustable to \$73.50 \$43.00 \$79.00 \$46.00 K-S-111 Wall Mounted Cradle Prione 6218 (5-pair) cable for interconnecting K-CL-5 or K-AC-635 Masters. For Indoor and Outdoor use, Approx. O.D.: No. Will, per 100 ft., 5-tas. 20¢ 6225 (13-psis) cable for interconnecting K-CL-10 or K-AC-610 Masters, For Indoor and Outdoor use: Aporox. O.D.: 50°, Wt. per 100 ft. 44¢ 6902 (2-conductor) cabla for connecting K-LR-2, K-LR-2M, K-LR-2R, K-HP-3(V) or K-C-20(V) to nearest master. Approx. O.B., %.\*. WL per 100 ft., I lb.

List Each

HOW TO DETERMINE CABLE REQUIREMENTS: Matter Cable—measure from first Master to second Muster only, from second Master to third Master only, etc., and total Sub-Station Coble—measure from each Sub-Station to nearest Master only. Connect KS-FII at any conviente point in the cable line between the remote speaker and the Master Station.

\*\*MCL Masters available in 5 and 10-station capacity; operate universally on 110-120 votts, AC or DC. U.L. Listed.

Sub-Stations do not require connection to an electrical outer. Start a system with 2 or more stations falt least one must be a Master. Add Master or Subs later as needed. Works for pennet a day. Masters can call and carry on a conversation with any other station selectively, or with any group of stations simultaneously. Several esperate 2-way conventations can be held at the same time without interfering with one another. Sub-Stations function "mon-privated"; thus Sub can reply at a distance, and Master can monitor Sub. If desired, Sub can be exclusive to one or more Masters. Subscannot originate calls or converse with each other.

Built-in control enables Masters to be switched "private" or "non-private" as wilched "private", other stations cannot insten-in. Master can receive calls from other Masters whether in "private" or "non-private" position. In this system, Sub-Stations are always "non-private" position. In this system, Sub-Stations are always "non-private".



SELECTIVE RINGING COMMON TALK PHONES MODEL TOGA 7 STATION PHONE MODEL TO12A 13 STATION PHONE
LIST VALUE Net each
\$43.50 \$3135 \$38.75 \$2780

TO-6A 6 Button Hendast (up to 7 may be used in a system).
TO-12A 12 Button Hendast (up to 13 in a system).
PRS-1A Power Supply for TO-6 and TO-12, \$25.00 4 iba....

TRA Phone-Page Adopter. Adapta Series TO phones for paging through your P.A. system. Needs no separate power supply. Volume control permits setting volume levels for paging and reproducing music, ex4x2". Shipping Wt. 5 lbs.........\$31.65

Connecting Cables for Bogen Phones

## WISEST BUY

#### SERIES TSL MULTI-CHANNEL BOGEN-PHONES

Uniquely (Berkille di-Master phone system for wirtually any need, and offering 100% trunkage. Any phone can converse with any other in the system (up to 4 simultaneous conversations in Sephone systemed in 16 phone system). Any omber of stations may engage in a conference salup (TSL-8 can call up to 7 stations individually or together, TSL-16 can call up to 15 stations individually or together, TSL-16 can call up to 15 stations individually or together, TSL-16 can call up to 15 stations individually or together, TSL-16 can call up to 15 stations individually or together, TSL-16 can call up to 15 stations individually or together, TSL-16 can call up to 15 stations individually or together, TSL-16 can call up to 15 stations in the phone can be used on deak or wall-mounted. Birst, 3/x50/x38/". Use unshielded cable with at levet 3 conductors made than the total number of stations in the system. Only one PRS-16 power supply (below) required for each phone system.

TSL-8 8-Station Moster, Cen call up to 7 other stationa individually

T5L-16 16-Station Master, Can call up to 15 other stations individuals or together, Wt. 4 lbs.

TRC Phone-Page Adapter, Adapta Series TSL phones for paging through your P.A. system, Needs no separate power supply. Volume control permits setting volume levels for paging and reproducing music. 48427. Shipping Wt. 6 lbs. \$31.65

| Sampping | Sampping

## ECONOMY 2-STATION INTERCOM MIDLAND 13-201B Model

Transistorized amplifier. 65-Ft cable, plugs, 9-Volt bottery.

.Room-to-room

Bosement-to-bedroom

.Family room-to- nursery

. Office-to-office

Office to-warehouse

3447 126 per Ft. - 7 were cable connects up to Four TO6A or TQ12 8449 186 per Ft. - 9 were eable connects up to Six TO6A or TQ12 8747 186 per Ft. 12 were cable connects up to 9 TO6A or TQ12 8748 226 per Ft. - 18 were cable connects up to 12 TO6A or TQ12



MPC-10 \$39.95 adds talk-back and intercom facilities without wiring changes Model MPC-10. A 10 SUB STATION MASTER unit, tor

use with your 10 watt amplifier or any other amplifier Our ME 10, 10 watt or SYL 5 AMP, ampliflers will operate this unit, Stock No. MPC-10 \$39.95 Model PSW-10, 10 Station switch strip. Pits in place of Commander name plate on Master, Increases Positions to 20 stations on MPC-10, \$9.95 net.

plate on Master, Increases Positions to 20 stations on MPC-10, \$9.95 net.
MPC-10, Wiring Requirements; 2-Conductor twisted pair plus 2-Conductor.
J8-14, Junction box with 28 Terminals.(Price ductor shielded poir to 10 worth intercom amplifier. 2-Conductor 5hleided pair and twisted pair to RPS-1 Sub-Station. A complete wiring diagram is shipped with each Master Unit.

Belden 8461- Twisted Pair, Per F

STATION

\$11.95 Ea.

Model RPS-1, sub Stationa for use with MPC-10 Master.

Belden 8737- Shielded 2-Conductor, 6¢ Belden 8461- Twisted Pair, Per Ft. 6¢



0

-(0)

STATIONS

## DYNAMIC MICROPHONE DUAL IMPEDANCE OMNI-DIRECTIONAL



Type: Dynamic moving coil Frequency response: 50-13,000 Hz.

Output level: High -54db (at 1,000 cps)
Low -72db (0 db=1V/microbar)

Impedance: Dual 50K & 150 nhms

Finish: Diecast lustrous satin chrome finish with black

Cable; 20 fL 1-conductor shielded

Switch: ON-OFF (normally open)

Stand thread: Standard 5/8"-27 threads Dimensions: 9-1/4" Length 1-1/4" Diameter

MCGEE SALE PRICE \$95 2 1900

A \$20,00 VALUE

Net weight: 15.75 oz. (less cable)

## MUSIC & SOUND, INC. BUILT-IN

INTERCOM YSTEM

COMPLETE SYSTEM W/SPEAKERS, CABLE AND HARDWARE AS ILLUSTRATED









3

#### Rough-in kit and Walnut Trim Case

Who needs more than an invitation to greater home enjuyment? Add to your home the charm of music that makes everyday work and play more enjoyable. Music is a constant expression of modern living, for all ages, for the entire family. Wonderful FM radio provides music to any mood or tempo. ready for a party, or a patio cook-out. The outstanding styling of the Model 20A system tastefully and elegantly combines

authentic detail of "MEDITERRANEAN," "COLONIAL," or "TRADITIONAL" accents to hand finished radio escuticheom for an exciting and distinctive face panel. To further comple-ment your choice of a style you can select an antiqued color in Gold, Copper, or Silver.

The Model 20A features Individual buttons on the master unit that turn room speakers OFF and ON or to MONITOR, Any combination of speakers can be selected and a variety of features programmed to one or more speakers simultaneously, even when you are monitoring. One or more speakers can be munitored while other speakers receive regular radio and intercom at the

same time, All Music and Sound systems answer the door from any room speaker without presetting the master unit. Model 20A as illustrated with automatic clock is also available synthout clock at reduced prices. Optionally priced eight-inch speakers provide more quality in-areas where extra music reformance is desired.

## MODEL 20A

Illustrated System With Clock Radio

\*184.95

\$169.95



TECHNICAL DATA Transistors: 13 Plus 5 Diodes AM Band: 540 kc to 1600 kc FM Band: 88 mc to 108 mc Amplifier: Push Poll Circuit 10 Watts Peak Power

Dist. 1.6% @ 4 Watts Response: Down 3 db at 40 and 17,000 cps ± .5 db Hum Level: —60 db F. Stages: 7 Tuned

Speaker Impedance:
45 Ohms
System Capacity:
12 Speakers
Power Required: 117v, 60cy,
22w

Packaged System: 3 Cartons Weight: 22 lbs.

MODEL RP-1 Player for use \$9950 NET

save 5300 to 5400!

do-it-yourself

burglar alarm

system kit

ome the inexpensive, way!

Da-it-yourself and save from \$300 to \$400 on installation costs. Kit contains all the materials required for

complete installation. Battery operated. Protect you

ACCESSORIES

FOR MODEL 20A

MODEL 208A

Delune att

\$1695

MODEL 20 Standard 5" Indoor Speaks

\$895

MODEL 208

Deluxe 8" Indoor Speaker

\$1695

MODEL 205A

\$895

## THE NEW EMERSON-RITTENHOUSEINTERCOM SOUND SYSTEMS ... sound like a symphony, sell for a song

ent control of local stations. Overall size: 8½" x 5-5/6" Rough-in plaster ring opening, 7½" x  $\theta_0^{\rm eff}$ . Mounts in standard 2" wall.

mplete System Includes; Master Station AM/FM) • 3 Indoor Remote Stations • 1 Indoor Remote Station (Gold anodized atuminum) • Rough-In Kit (120 ft 5 wife color-led cable, plaster frames and power transformer) • AM and FM Radio Antennas

RM-22 AM-FM MASTER IR-24

INDOOR REMOTE \$9.95 Eo. OR-26 DOOR REMOTE \$7.95 Ea.
Rough-in Box Included

Moster's Station Model RM-22 AM/FM - All translators. Transporter the Moster's Station Model RM-22 AM/FM - All translators. Transporter than the Moster's Station when the Moster's Station of Stations of Stati

ndoor Remote 1R-24 - Standard indoor Remotes include rotary volume con-rol with full off position and three-position, rotary function switch. "Stand-y" position permits huming off rade at local stations without shutting off ecsplies of intercom calls from glaster Station. Provides complete, independ-

#### COMPLETE SYSTEM AS LISTED ABOVE

NEW "DO NOT DISTURB" SWITCHING - Standby station ON/OFF switch, on Master Station, permits door answering and intercom calls from Master and remote stations without disturbing remote stations in STANO-BY position. With the switch on the Master Station in the OFF position, the remote stations with their function switch in "STANO-BY" position will not receive calls,

COMPLETE PRIVACY...no eavesdropping — By setting remote stations at "LISTEM"...you can receive intercomm calls (and listen to radio or recorded music)...but no one can eavesdrop on your station. With most low-priced systems, privacy can be obtained only by shutting off the station completely.

FULL-TIME DOOR ANSWERING SERVICE — Answer the door from any room, at any time, from Master Station or remote stations.

Optional Electronic Chime pipes clear chime notes to all stations in "LISTEN"

"HANDS FREE" ANSWERING - With your remote station STAND-BY" In "STAND-BY" you can answer calls from the Master Station from as far away as across the room. No need to drop everything or jump-up to answer calls.



Comes complete with | all items shown above.

Regular net \$79.50 McGEE SPECIAL

BA-K

## STANDARD

Converts your AM car radio in a few moments to an FM/FM Multiplex radio. Automatic stereo switching for the utmost in enjoyment. FM Beacon Light, Tone and Volume Control to blend Stereo broadcasting to perfection. Local/Distance Switch. Under-dash mounting or almost

Regular Net Price on ALL YRANSISTOR.

PRI 935 is \$49.95 \*\* MAI LOCAL DISTANCE SWITCH AM RADIO.

REP-935 is \$49.95 \*\* MAI LOCAL DISTANCE SWITCH SWITCH

without speaker McGee Special with good 54" speaker & grill.

**RF-935** 

Converts your AM radio to receive EM stereo. Without aftering your present AM radio installation, you can empty, the world, of FM stereo in your can empty. He world, of FM stereo in your can empty the world, of FM stereo in your can be added to the control blend stereo broadcasting to the control blend stereo broadcasting to the desired FM station. Return to AM instantly, Local/distant switch adds to recoprise quality. Sim design allows easy mounting underdash or on top of dash 12 volts youther or negative. With mounting bracket and accessories, Size: 636 25 35 262 66.

FM MULTIPLEX STEREO

CAR RADIO CONVERTER



1 mil tip net

ASTATIC 310-1,414-1,434(Late),6011 d.609 318 64TS Plast: Hang. 118,120,124,310TS,314TS, 316TS,420,422,424TS,426TS,436,452,456,458,

LAFIMOA 409A(11-2); (22-3);409B(11-2); (22-3); (29); 409C(46-1-1); (-4); (53-1); (53-2);(73-2,-41) 98C120-1;8SY:118:120;124;125;240 2078A2-1

FLECTRO-VOICE 

GENERAL ELECTRIC RT1051\_RT2734\_RT3424 EA1000\_AT271T

MAGNAVOX

(560) 176; 180, 180-2; 180-3,209-1; 209-2; 236-1; 288-1; 288-2, 560313-; 3; 5 R.C.A.

10330,973013-1,1401767,124215 105482,106776,111196,111197,973705-; 2; 8.

RONETTE

NT67-1.8A-: 283-T; 284-; OS; OY: P; T; US; V; VS: V2-MAX; OV: 395 -1; -1N; -1S; S; -5; -5; V\$1 V2-NAX, OVI.398 -1: -UN: -IS: \$: -\$: -\$!
DT-00: -OV. -P: -T. US: 322: -222-\$: P1-04.
P-101,P-1-222,T-222,TC-201,T0-222: -A1;
PF. T0-244: Nax: N: 0. OV. (OV.FP: P. PX; T.
TS: US: V: VS: T0-286: T T0-287: -\$: T0-386:
\$: T0-400. 0: OV: P: -200: -222: 225: T0-222/;
7825: 9655.OV/6045: OV/9121: OV/9121: P/#234

1-3 mil tip Two Tops net

N62sd ASTATIC ADMIRAL

409C60-: 2: 4.78C233-; 2: 4 GENERAL FLECTRIC

N350-1d 1 mil tip net

GENERAL ELECTRIC RPX-; 404A; 401A; 050A; 051A; 052A, 053A; 061A; 063A; 145; 146; 147, 0PX-111, C-13S R.C.A.

Section 1 1 mil tip N351-1d net

GENERAL FLECTRIC 4G-041,4G-061,4G-5-810,4G-5-013 4GD-01D-; 023; 020,4GD-018-023 4T11,4G-050,4G-052,4G-053

1-3 mil tip

net

N671sd R.C.A.

78769A .RPX-041A

103422 .37-5

SONOTOFE-ASTATIC 37-; B; L8-D. L8-SD; L8-1S; AST.763; d; 771

N6743d 1-3 mil tio Two Tion net ADMTRAL

409A24,2T; 5; D; LB-D,9980, Dy LB; 5 MAGNAVOX

560161: -1; -2,560224-1 1; 2,560225-2; 560228-; 1; 2,560229-2,27-8,27-0,27-08 27-LB-DS-9980; D; D; S

R.C.A. 78746 79807.100653 27-1 Dt DS 8; SONOTONE-ASTATIC 2T; -D; -LB-D; -LB-SD; -LBS; S; SD,9980; -D; -LB; -LB-S; S; SD,5T,7T-: D: LB-D; LB-SD; LB-SS; SSD,2TA-; D; LB-D; LB-S; LB-SD; S; SD AST,7B1; d; 752

STEREO NEEDLES

N41sd Two Titos

-7-3 mil tip net

ASTATIC SIEREO 17,17d,17da,135da,217d ADMIRAL

51EREO 409C55-1 1: 3.409C56-1 1: 3. GENERAL ELECTRIC SHEEFO EASTISS

Stereo Needles N2 sd .7-3 mil tip Two Time

ASTATIC SHIEO 195d(163d Check Needle Type Carefully 2 Different Needles Used) 560345-; 1: 2.560350-: 1: 2 ELECTRO-VOICE

51EREO 275: 0,5166 | D

MAGNAVOX STEREO 560345-; 1; 2,560350-; 1, 2,

2 .7 mil tip N8-7d net

ASTATIC STEED 704,7078,7415,7415,76758,78,320. ADMIRAL 324.474 310-7.350

STERFO 409C45-1; 2,409C58,409C70-2,

FI.FCTRO-VOICE SIETO 121,142,143; D.144,145; D.146; D.167, 196,5204,5213,5215,5216,5219,5227,5228

GENERAL ELECTRIC STETEO RS-: 2923; 3109; 3800 Non. 4186 V.a., 4722,6090,6091,15353-1, 67305,27-0, 871054,85-6720 FAGNAVOX

STEREO 560288-; 1; 2,70-45

R. C. A. SHEEO 100718,110304,973705-; 1; 8, 12;

N752sd .7-5 mil tip Two Tips

ADMIRAL STEEO 409084-2,T80238-2 None,409085-4 2| 4.780239-1 2; ELECTRO-VOICE

311110 5245 Tetrac N754sd .7-3 mil tip net

ADMIRAL SKIEG 780239-3

\$111 10 5100 : D.5101

VACO

.7-3 mil tip N770sd

net ASTATIC ENERG 1190; 4,1199

ADMIRAL STEELO 409C75-; 1; 2,940M1-; 6; 5; 7.

ELECTRO-VOICE

TETRAD STEREO 2-340-M1-7; SN1, 3-320-A,5-320-; B;

M18,5-328-8,5-34D-; M1-4; SN1, 6-32D-; 75-1; A; A1,6-32S-;A2;75-2;233-2 AST.1190d / N882sd .7-3 mil tip Two Tem net

ZENITH SIGNO 142-1 1504 1511 163; 166

N601-7d .7 mil tip net

ADMIRAL. 516810 409A37-, 1; 2,409C(37-1); (37-2); (41-1); (42-1)(106 FLECTRO-VOICE

STEREO 95,96",97,98 GENERAL ELECTRIC

STERIO 83-3100, RD3480, Nos. RS3587 MAGNAVOX BITTIO 560277-: 1: 2

RONETTE SHIRLD Stereo-; DV, DV-1; T; T1; 208, Stereo: 103; SD; -1: -2; -3; -4; -D; -1D, 106; -1-9121; -1; -2; -3; -4; -D; -1D, 200; -1; 2, T0208-2, T-MTG, 91; 93, P105, DC-500 (Non.)

8F-401 35 -47 -0 N676sd @ .7-3 mil tip net

ADMIRAL SIGIRO 409034- 5: 1-1: 1-2.87-4; D: 5: ED GENERAL FLECTRIC

MACNAVOX SHITO 560248-; 1; 2,560247-1,560259-; 1; 2. SONOTONE-ASTATIC

SIERO 80.87.874.87-4; D: 5; SD.87-4-; 4-S: 4-577; 4-D; 4-SD; AST.754; D: 786

N686sd .7-3 mil tip Two Tres net

ADMIRAL SIERO 4090-43-1 11 2,4090-48-1 1; 2 GENERAL FLECTRIC STEREO ES3478

SONOTONE STEPPE Sonoties N-9916,167-; Sr SD: S77,816TA-, SD: 377; 9T,8TA Series AST.760; d, 736; d # N721sd ./-3 mil tip

net 201 TELEPUNKEN

SIEREO 120,120/1,720/0,120/2,720/05,722, 122/2,AST.11023, d N230sd .7-3 mil tip

STATIC net STEREO 1101d, 1412d, al 13d, 1114d, 1139d, 1140d. 1141,1167d,1168d,1169d,1170; 6,2171d. 1172d,1173d,1212d,1235d

EL ECTRO-VOICE STEPFO 51060,5112,51140,51150,51190,52580. 5266D,5304D,5317D,5318D,8322D,5380D,

T FTRAD SHEETO 1-110-M1, 2-110-7 JL; J3; MC-1; S-2;

5-26: V6: V8, 3-11D-; AB2: P7; S-11: S-11A.
3-115-; P6: P11. S-31D-Y20, 6-11D-; ESR-6.
BSR-7; N-9: N-13: N-20 N-21: P-2. P-4;
P-10: S-1: Y-11. V-24. 6-115-P-1 AST.1201d

.7-3 mil tip N732sd net Two Tipe ...

ASTATIC [STEREO] 1102d,1103d,1104d,1117d,1118d, 1118d,1177e,1178d,1179d,1180d,1181d, 1236d

EL ECTRO-VOICE 5275D, 5276D, 5300, 5320D, 5321D, 5382D,

TETRAD SHORO 1-210-1 M2; M4: V15,2-210-1 BSR-24 85R-4; V6: V7 5-41D-301-: 3; 5, 6-21D-; RSR-5; NW-1: 3-5: 3-14; 5N4 V2; V7,6-215-V1 6-41-D-; 512; 812A,2-41D-BSR31 AST.1102d

N734sd .7-3 mil tip net

ASTATIC SILIO 11054,11064,11214,11224,11594, 1160d, 1185d, 1186d, 1187d, 1188d, 1189d, 1230d

ELECTRO-VOICE SHIFT \$1000,51000,5110,51200,52600,52680, 5288D,5281D,5299D,8315D,5361D,5362D,

TETRAD STEREO 1-310-; RSR-15; SN4, 2-310-AR3, 3-31D-88R-19; V23, 5-31D-; 3-10; V5; V10, V14; V23, 6-31D-, H3; H5; H6; H8; H114 H20; SN4; V12,6-315-H6 AST,1105d

.7-3 mil tip N736sd net ASTATIC STITLO 1107d .1191; 6,1208d ,1201d

ADMIRAL SIEREO 409C78-: 1: 2: 5: 8: 7 78C235-; 1; 2, 5; 0; 7,76-; 2; 5; 6; 7,233-,582;

ELECTRO-VOICE SIFEED \$1020,\$103,52530,5254,52920,52930. 53060 .53160 Tetrad

TRAD (815 1-330-; G3; 852-21, 2-100-82, 3-330-; 1-330-; A3; 78-1 BSR-21; G3; SK5, 6-10D-M1; 6-33D-; A3; 78-1, 6-335-; A4; SK2; 78-2; 235-2,8-33D-; G2; SK4

N738sd .7-3 mil tip net ASTATIC

SIERIO 11276 d.1199; d.1240d ELECTRO-VOICE SHIREO 5118D,51221 D,5124,5009D Tetrad 5352D . 5356D

ETRAD STEREO 2-520-; SN1: SN1X, 2-530-8, 2-535-; 8: EX. 2-54D-A, 3-52D-C, 3-525-B, 3-53D-CM1, 5-52D-Z1, 5-529-Z2, 6-52D-A; B; BSR-20, 6-52S-; C; Z7, 6-53D-; B; G5 AST.1127d

,7-3 mil tip

ELECTHO-VOICE \$1610 265; D 268,269,270,271,272,273, 274,5344 BSR,5369,5370 ZENITH

N302-7d

ACM IRAL STREO 409A16-; 1; 8,409B(32)-1); (33-1); (33-1-1): (33-2-1), 21,280ST,0126; 8; 0; 30 FIFCTRO-VOICE

STERIO (560) 232-X; 233-1; 233-2; 233-3;

-8 .7 mil tip

21-1 D: DST: NO: MS: 8,22-1 D 26: D: DST: DV: MST: NOT: ST: 4 27: 0.0126; D: DS: 8 MAGNAVOX

233-4; 249-1; 250-3; 260; 290-1; 290-3; 296-3,266,2657,012605 N307sd .7-3 mil tip

Two Fips ADMIRAL SHITO 409059+; 1; 3,409051-1

ELECTRO-VOICE STEEO 148.1410.149,1498,1498,150,1500. 1908.137.1870.158.1580.169.1690.186 Ser., 280; 0.256; 0.257; 0.258; 0.270; 0

MAGNAVOX SHRED 360310-; 1: 2,560311-; 1: 2, 560315-: 1: 2,560340-; 1: 2,560342-1 N311sd .7-3 mil tip

ELECTRO-VOICE 516810 117,131,1310,148,1480,154,2540, 259: D.260. D

net

N314sd .7-3 mil tip net

Two Figs. ELECTRO-VOICE

MAGNAVOX STEED 560305-1 1: 24 3,560307-3 SHEETO 325-6076

N50sd S .7-3 mil tip net Two Tips ASTATIC 510000 123,1336,137,1374,1304,2334

2336+,2376,459,459d,463,483d,485d,4971 d ADMIRAL SHIRO 409C50-: 1 . 2

N56sd A net Two Tage ASTATIC 51710 183: A; d; r; rd,137; 4; d; A; rd, 157; A; d; R; rd,341; d,343; d,343; d,461; d,453,478d,461; d,499; d

A 7" | TAL SIRIO 409682-; 1; 2; 3; 4; 6,780225-; 4; 2; 3; 4; 6; 780249-2,409083-; 1; 2; 3; 6 780778: 1; 2; 3; 4

N60sd .7-3 mil tip net Swee Tops

.7-3 mil tip

SHEREO 138,1384,140,1406,140rd ADMIRAL.

ASTATIC

STRIO 409061-1 21 41 6,6,780224-6, GENERAL FLECTRIC STRIO 15355-1,83-6510 N64sd \$ .7-3 mil tip net

ASTATIC STEREO 167,1674,169,1694,1814,1874.

N72sd .7-3 mil tip net


ASTATIC SIEUO 124,142,1424,142r,142rd,496 ADMIRAL GENERAL ELECTRIC

STERIO 15337-2,15358-; 1; 2,15355-1; 3, EA1009,EA1066,EA1836,RS-6518

54. N425sd .7-3 mil tip net ASTATIC STEREO 713; d.714; d.718; d716; d

718, d,719; d,721; d,722; d,724d,725d, 7280,150 ADMIRAL SHEEC 40052-1 1; 2, 400054-; 1; 2, 400657-; 1; 2; AUEC RO-VOICE 511210 221; 0,222; 0,223; 0,224; 0,225;

516060 UB.D-9.610.011 Series MAGNAVOX



#### NEW LOW PRICES ON CARTRIDGES SAVE UP TO 50 PERCENT

JOBBER BOXED RAYTHEON TUBES NOT SHOWN ON OUR CURRENT PRICE LIST RJB SPECIAL AT UP TO 75% OFF LIST SPECIFY RJB When Ordering from this list Types shown may be hard to find at local jobber

6856 70¢ 12 F8 \$1.08 12FX8\$1.21 12L6GT 896 12SL7 GT\$1.24 6BH 8 \$1.15 6BJ 8 \$1.11 684 BN6 \$1.19 3 B N 4 6C10 93¢ 6CN7 \$1.11 125N7 GRA \$1.07 3 D K 6 15LE8 \$1.90 6DA4 93¢ 6DV4 \$1.61 15FM7 \$1 00 3 B U 8 \$ 1.22 \$1.22 6EU8 93¢ 17AV8GA 6FA7 80¢ 17AX3 68¢ 6H6GT \$1:44 17GV5 \$1.08 BAU4 854 \$1.01 6HD8 \$1.00 198 G6GA \$1.73 807A C7 \$1.43 Q7GT \$1 8JV8 \$1.10 21HJ5 \$1.50 65A7GT \$1.3825CW6 \$1.50 25EH5 93¢ 34GD5A 74¢ 36AM3 63¢ .18 8BQ5 94¢ SAVEGT \$1.30 8 GN 8 51.08 7247 \$1.01 6AX3 85;

904 Prices shown 12827 54.04 12EK6 90¢ 6 B E 8 85¢ are net

ASTATIC CARTRIDGE SALE

142 Stereo Crystal 2.0 Volt

146 PACKED

\$2.9

Mono Crystal 3.0 Volt

RAYTHEON

Color Sale 1 Jobber Boxed Fresh Stock BIG BUY SAVE

RA-22\$23.95

Color

Sale !

The 22 TUBES listed in this Kit, list at \$93.75 per KIT These are the most used 19 tubes in repair service. Our SELLING price is \$23.95 per kit. Discount over 75% off list price of each tube. (There will be a 10% increase after the freeze is lifted).

1-3A3/3AW3 1-6AQ5A/6HG5 1\_6BK4C/6EL4A 2\_6FQ7/6CG7 1\_6BL8/ECF80 1\_6GF7A 1\_6BZ6 3\_6GH8A

1-6DQ6B/6GW6 1-6HM5/6HA5 1-AEAS

1\_6GU7

1-6106 1-6JS6C 1-6LQ6/6JE6C 1-8FQ7/8CG7 1-12AX7A/ECC83

RAYTHEON

1-6CGRA 1-6CJ3/6DW4B/6CL3

BIG McGEE

SPECIAL

PRICED

STOCK NO TUBE KIT. RA-22 PRICE

KLEEN

Jobber Boxed Fresh Stock

GENERAL CEMENT 8666

SPRAY KLEEN ELECTRICAL CONTACT CLEANER SPRA

AND LUBRICANT Non-Flemmable

MeGEE

CLEANER

AND

LUBRICAN



ALL PURPOSE

TUNER AND CONTROL

6 Oz. Spray Can CLEANS AND RENEWS MCG TC IN ONE OPERATION

Will Not Change Capacity Nor Harm Insulators

NON FLAMMABLE

89 2 for \$1,70 Crystal Cartridge FOR STEREO AND MONAURAL RECORDS Imperial \$1.49

JM-451

10 for \$14,00

McGee's special purchase, Fignorer Staree trystal phone certridge, Four connectors shipped with an 18" shielded lead to make it easy to Install in your present record chenger, Standard mounting centers, Equipped with a ,7 mil and 3 mil sepphire needle. Excellent chabrel separation, 1/2 voir output. Completely zomparible; plays all Stares and monaumal resteeds of all speeds, Frequency response from 30 to 13,000 epr. Stock No. Stares Filmpettol territoigs, List value 39,95.



RCA TYPE 45 RPM CARTRIDGE 990

CX-310, imported 45 RPM cryetal cartridge with 1 mil supphire needle I voit output. Replaces RCA, Rasponse 50-10,000 cps, Sale price, 99c es

HIGH OUTPUT CRYSTAL CARTRIDGE 2 4 9 9 9 C

No. A-101K, imported lightweight \$6 volt output corridge. All aluminum with thumb acress needle chuck, Replaces Asiatic L-73, L-83, Shure \$650 etc. A terrile purchase by McQue makes this 95c price possible. Sicok No. A-101X, 30, volt crystal Cartridge. Sale price 99e each, 5 for \$3,99.

Imperial

ARTRIDGE \$1 39 FLIP-OVER CX-312 3 VOLT OUTPUT

Imported replacement file-over crystal carridge Replaces Ronette T0-222, Has separate 1 and 3 mil seponire needles. Normal subut voltage. Sale price \$1.39, 2 for \$2.6

## STEREO DELUXE TONE ARM

ASTATIC

\$2.29 Modern plastic tone orm

This Stereo model replaces many U.S. and Foreign made record player pickups, Included is our crystal cartridge with our (.7s & 3s) sapphire needle. 2 valt output. List Price: \$4.95.

MONAURAL DELUXE TONE ARM MODEL LM

11.79

This Mono model is an exact replacement for Sears Raebucks. Silvertone and replaces many toreign record player pickups. Included les our cartridge with (15, 3s) sapphire needle. High output 3 valts crystal can be used for all speeds. Output

MC GEE NON-RESIDUE SUPER FROST TEST CIRCUIT COOLER

6 Oz.

SPRAY CAN

Stock No. SF-99

McGee Super Frost Circuit Cooler, All Freen 12, not Freen 11 but best of 12. Best quality leaves no residue. To locate thermally def-ective capacitors, resistors, and coils.

McGEE

NON-DRIFT COLOR TUNER SPRAY MCGEE TUNER & CONTROL CLEANER NON-DRIFT

TUNER CLEANER

and lubricant for

COLOR THE MASTICS Charle !

AND LUBRICANT \$ McGee Color Tuner Cleaner and Lubricant, Non-Drift, Safe for all plastic material. Finest quality. A very necessary item for the co-lor TV serviceman. 6 Oz. spray can with fine whole nozzel exten-der. Net \$1.79, 2 cans for \$3.50 2 Cans

• FAST DRYING

WILL NOT DETUNE

• NOT HARMFUL TO PLASTICS NON FLAMMABLE

For \$3.50 Stock No.

McGEE

SUPER

TEST

ND-179

12846- 128E6- 17446- 35W4- 50CS

AATK-159 10 Kits For

LUCKY PURCHASE BULK PACKED uphonics STEREO

-838.7 Mil \$1.99

U-s with Mtg. - . / Mtl and 3 Mil Sapphire Needles - Q .7 MII \$ 7

U-9 Same as U-8 except has .7 Mil diamond and 3 Mil Sapphire

-10.5 \$1

U-10.5 with mounting bracket, with .7 Mil and 3 mil Sapphire needles

U-112 2 2.9 U-11 Same as U-D except :.as .7 Mil diamond and 3 Mil Sapphire

NEW VACO / VARCO STEREO CARTRIDGE Model CN 72

.9 Volt \$1.9

Model CN 75 2 Volt output

BOTH CARTRIDGES HAV \$229



Save 50 percent on Astatic, bulk packed cartridges. Most popular no's Astatic Bulk 133D cart. \$4.95 Stereo ,5 volt ceramic. Astatic Bulk 140 D cart \$3.95 Stereo cart. 1 volt output.

BSR SC5H \$1.99

CRYSTAL STEREO CARTRIDGE
3 VOLTS HIGH OUTPUT, POPULA
CLIP IN REPLACEMENT, HAS 7/
AND 3 MILL FUP NEEDLE.

STFREO XTAL with mtg with mtg

2.0 Volts \$1.99 Output: Tracking Force: 7 gr Black with needle Color:

with mtg bracket MONO XTA BSR X2HE

and needle
Output: 1.1 Volts
Tracking Force: 7-10 gr



PHONOGRAPH CARTRIDGES

numbers of Genuine Astati U Jobber Boxed Phono cart. in Stock

Dealers net, is 40% Off Astatic list prices. Give Astatic part no. when ordering. Also give some description.

ALL AMERICAN TUBE KIT IMPORTED

\$23.50



60% OFF LIST

ON FACTORY FRESH-JOBBER BOXED GENERAL ELECTRIC RECEIVING TUBES WHEN YOU BUY 10 OR MORE AT A TIME.
McGEE HAS MIDWEST'S LARGEST STOCK OF TUBES.

Tube List Net Net	Tube List Net Net	Tube List Net Net	Tube List Net Net	Tube List Net Net
Type Price 1-9 10 up 0Z4/0Z4A 3.85 1.74 1.54 1A7GT 5.40 2.43 2.16 1AD2 3.85 1.74 1.54 1AD2A 3.95 1.78 1.58 1AY2 3.55 1.60 1.42	Type Price 1-9 10 up 3GK5 3.85 1.74 1.54 3HM5/3HA5 3.85 1.74 1.54 3HQ5 5.65 2.55 2.26 3HS8 4.30 1.94 1.72 3JC6A 5.05 2.28 2.02	Type Price 1-9 10 up 5V6GT 3.70 1.67 1.48 5X8 4.15 1.87 1.66 5Y3GT 2.95 1.33 1.18 5Z3 4.45 2.01 1.78 6AB4 3.60 1.62 1.44	Type Price 1-9 10 up 6BR3/6RK19 4.55 2.05 1.82 6BR8A 4.70 2.12 1.88 6BS8 5.00 2.25 2.00 6BU8 5.05 2.28 2.02 6BV8 3.30 1.49 1.32	Type Price 1-9 10 up 6ER5 4.20 1.89 1.68 6ES5 2.85 1.29 1.14 6ES8/ECC1895.45 2.46 2.18 6EU7 3.95 1.78 1.58 6EU8 3.70 1.67 1.48
1AY2A 4.05 1.83 1.62	3KT6 3.80 1.71 1.52	6AC7 5.75 2.59 2.30	6BV11 4.95 2.23 1.98	6EV5 4.25 1.92 1.70
1BC2 2.90 1.31 1.16	3Q4 3.35 1.51 1.34	6AC10 4.25 1.92 1.70	6BW3 3.45 1.56 1.38	6EV7 3.25 1.47 1.30
1BG2 2.80 1.26 1.12	3S4 3.40 1.53 1.36	6AD10 8.15 3.67 3.26	6BW4 2.75 1.24 1.10	6EW6 3.55 1.60 1.42
1BH2A 3.90 1.76 1.56	3V4 4.45 2.01 1.78	6AF3 4.05 1.83 1.62	6BW8 4.70 2.12 1.88	6EW7 6.50 2.93 2.60
1DG3 4.10 1.85 1.64	4AU6 3.85 1.74 1.54	6AF4 4.90 2.21 1.96	6BW11 5.35 2.41 2.14	6EY6 5.00 2.25 2.00
1DK1 3.20 1.44 1.28	4AV6 2.95 1.33 1.18	6AF9 3.50 1.58 1.40	6BX7GT 5.90 2.66 2.36	6EZ5 5.05 2.28 2.02
1DK27 4.05 1.83 1.62	4BC8 4.00 1.80 1.60	6AF11 5.20 2.34 2.08	6BY5GA 4.80 2.16 1.92	6EZ8 3.55 1.60 1.42
1DK29 2.80 1.26 1.12	4BL9/	6AG5 4.30 1.94 1.72	6BY6 3.40 1.53 1.36	6F3 5.85 2.64 2.34
1DN5 4.40 1.98 1.76	XCF80 2.40 1.08 .96	6AG7 7.70 3.46 3.08	6BY8 2.70 1.22 1.08	6F6 6.15 2.77 2.46
1G3GT/	4BN6 4.05 1.83 1.62	6AG9 6.25 2.82 2.50	6BZ3 4.45 2.01 1.78	6FD6 3.55 1.60 1.42
1B3G 3.40 1.53 1.36 1G3GTA/ 1B3 3.95 1.78 1.58 1H2 3.95 1.78 1.58 1K3A/1J3 3.95 1.78 1.58	4BS8 4.25 1.92 1.70 4BU\$/4GS8 4.45 2.01 1.78 4BZ6 3.70 1.67 1.48 4BZ7/ 4BQ7A 4.45 2.01 1.78	6AG11 6.00 2.70 2.40 6AH4GT 3.25 1.47 1.30 6AH6 5.80 2.61 2.32 6AH9 4.75 2.14 1.90 6AK5/EF95 4.50 2.03 1.80	6BZ6 3.10 1.40 1.24 6BZ7/6BQ7A 5.00 2.25 2.00 6C4 3.70 1.67 1.48 6C5 5.35 2.41 2.14 6C9 5.50 2.48 2.20	6FD7 5.70 2.57 2.28 6FG5 5.35 2.41 2.14 6FG6/EM84 3.30 1.49 1.32 6FG7 4.60 2.07 1.84 6FH5 5.00 2.25 2.00
1L6 12.55 5.65 5.02	4CB6 2.70 1.22 1.08	6AK6 2.55 1.15 1.02	6C10 3.70 1.67 1.48	6FH8 4.40 1.98 1.76
1LH4 7.60 3.42 3.04	4CS6 3.85 1.74 1.54	6AK10 5.05 2.28 2.02	6CA4 3.75 1.69 1.50	6FJ7 4.15 1.87 1.66
1N2A 4.40 1,98 1.76	4CY5 2.70 1.22 1.08	6AL3/EY88 2.60 1.17 1.04	6CA5 3.00 1.35 1.20	6FM7 4.60 2.07 1.84
1R5 5.20 2.34 2.08	4DE6 2.95 1.33 1.18	6AL5 2.95 1.33 1.18	6CA7/EL34 5.90 2.66 2.36	6FM8 3.95 1.78 1.58
1S2A/DY87 2.55 1.15 1.02	4DK6 3.40 1.53 1.36	6AL7GT 8.85 3.99 3.54	6CB5A 9.85 4.44 3.94	6FQ7/6CG7 2.95 1.33 1.18
1S5 3.40 1.53 1.36	4DT6 3.85 1.74 1.54	6AL11 5.70 2.57 2.28	6CB6A/6CF6 3.25 1.47 1.30	6FS5 4.10 1.85 1.64
1T4 3.85 1.74 1.54	4EH7 3.55 1.60 1.42	6AM4 7.20 3.24 2.88	6CD6GA 6.65 3.00 2.66	6FV6 4.45 2.01 1.78
1U4 3.85 1.74 1.54	4EJ7 3.55 1.60 1.42	6AM8A 4.60 2.07 1.84	6CE5/6BC5 3.25 1.47 1.30	6FV8A/6BR8 5.20 2.34 2.08
1U5 3.40 1.53 1.36	4ES8 5.50 2.48 2.20	6AN4 6.15 2.77 2.46	6CG3/6CE3 3.90 1.76 1.56	6FW5 4.90 2.21 1.96
1V2 2.40 1.08 .96	4EW6 3.55 1.60 1.42	6AN8A 5.20 2.34 2.08	6CG8A 4.30 1.94 1.72	6FY5 2.75 1.24 1.10
1X2C/1BX2 4.10 1.85 1.64	4GK5 3.85 1.74 1.54 4GM6 2.15 .97 .86 4GX7 4.60 2.07 1.84 4HA5/PC900 2.30 1.04 .92	6AQ5A/	6CH8 5.65 2.55 2.26	6FY7 3.50 1.58 1.40
2AF4 4.10 1.85 1.64		6HG5 3.40 1.53 1.36	6CJ3/	6G11 6.00 2.70 2.40
2AV2 3.10 1.40 1.24		6AQ6 3.25 1.47 1.30	6DW4B 3.70 1.67 1.48	6GB5/EL500 3.80 1.71 1.52
2BN4A 3.55 1.60 1.42		6AQ7GT 4.70 2.12 1.88	6CK3 3.70 1.67 1.48	6GC5 5.65 2.55 2.26
2BU2/2AS2A 3.90 1.76 1.56		6AQ8/ECC85 3.00 1.35 1.20	6CK4 3.55 1.60 1.42	6GE5 5.70 2.57 2.28
2CN3B 4.10 1.85 1.64	4HA7/4HC7 4.25 1.92 1.70	6AR5 2.45 1.11 .98	6CL6 4.75 2.14 1.90	6GF5 3.80 1.71 1.52
2CW4 4.90 2.21 1.96	4HM6 3.10 1.40 1.24	6AR8 5.90 2.66 2.36	6CL8A 4.60 2.07 1.84	6GF7A 5.35 2.41 2.14
2CY5 4.85 2.19 1.94	4HQ5 4.60 2.07 1.84	6AR11 5.35 2.41 2.14	6CM3 4.90 2.21 1.96	6GH8A 3.20 1.44 1.28
2DS4 4.90 2.21 1.96	4HS8 3.70 1.67 1.48	6AS5 4.00 1.80 1.60	6CM6 3.85 1.74 1.54	6GJ5A 6.15 2.77 2.46
2DV4 6.45 2.91 2.58	4JC6A 5.05 2.28 2.02	6AS8 5.35 2.41 2.14	6CM7 4.15 1.87 1.66	6GJ7/ECF8013.10 1.40 1.24
2DZ4/2AF4B 4.10 1.85 1.64	4JD6 4.60 2.07 1.84	6AS11 6.05 2.73 2.42	6CM8 4.05 1.83 1.62	6GK5/
2EN5 3.20 1.44 1.28	4JH6 3.40 1.53 1.36	6AT6 2.05 .93 .82	6CN7 4.45 2.01 1.78	6FQ5A 4.60 2.07 1.84
2ER5 3.70 1.67 1.48	4KE8 6.05 2.73 2.42	6AT8A 5.20 2.34 2.08	6CQ8 4.60 2.07 1.84	6GK6 3.70 1.67 1.48
2FH5 3.70 1.67 1.48	4KN8/	6AU4GTA 4.85 2.19 1.94	6CR6 2.95 1.33 1.18	6GL7 5.75 2.59 2.30
2FS5 4.85 2.19 1.94	4RHH8 7.40 3.33 2.96	6AU5GT 5.20 2.34 2.08	6CS6 4.10 1.85 1.64	6GM5 3.05 1.38 1.22
2GK5/	4LJ8 4.40 1.98 1.76	6AU6A 2.95 1.33 1.18	6CS7 3.75 1.69 1.50	6GM6 3.85 1.74 1.54
2FQ5 4 3.85 1.74 1.54	4LU6 3.40 1.53 1.36	6AU8A 5.65 2.55 2.26	6CU5 4.00 1.80 1.60	6GM8/
2GU5 4.50 2.03 1.80	5AM8 4.90 2.21 1.96	6AV5GA 5.20 2.34 2.08	6CU8 4.60 2.07 1.84	ECC86 4.35 1.96 1.74
2HA5 3.85 1.74 1.54	5AN8 5.20 2.34 2.08	6AV6 2.70 1.22 1.08	6CW4 5.65 2.55 2.26	6GN8/6EB8 5.65 2.55 2.26
2HK5 3.85 1.74 1.54	5AQ5 3.70 1.67 1.48	6AV11 4.40 1.98 1.76	6CW5/EL86 2.75 1.24 1.10	6GQ7 3.75 1.69 1.50
2HQ5 3.85 1.74 1.54	\$AR4/GZ34 4.25 1.92 1.70	6AW8A 4.45 2.01 1.78	6CX8 5.20 2.34 2.08	6GS7 3.55 1.60 1.42
3A2 5.50 2.48 2.20	\$AS8 4.40 1.98 1.76	6AX3 3.40 1.53 1.36	6CY5 4.85 2.19 1.94	6GT5A 6.35 2.86 2.54
3A3A/3AW3 3.40 1.53 1.36	\$AT8 4.45 2.01 1.78	6AX4GTB 3.70 1.67 1.48	6CY7 3.05 1.38 1.22	6GU5 4.10 1.85 1.64
3A3C/3AW3 4.05 1.83 1.62	\$AV8 4.05 1.83 1.62	6AX5GT 3.85 1.74 1.54	6CZ5 4.75 2.14 1.90	6GU7 4.15 1.87 1.66
3AL5 2.70 1.22 1.08	\$B8 5.50 2.48 2.20	6AY3B/6BS3 3.70 1.67 1.48	6D10 4.65 2.10 1.86	6GV5 4.10 1.85 1.64
3AT2 3.70 1.67 1.48	5BC3A 3.40 1.53 1.36	6AY11 5.90 2.66 2.36	6DA4A/	6GW8/
3AT2B 3.90 1.76 1.56	5BK7A 4.05 1.83 1.62	6AZ8 5.55 2.50 2.22	6DM4 3.70 1.67 1.48	ECL86 3.05 1.38 1.22
3AU6 2.95 1.33 1.18	5BT8 3.10 1.40 1.24	6B10 4.45 2.01 1.78	6DB5 5.00 2.25 2.00	6GX7 4.60 2.07 1.84
3AV6 2.95 1.33 1.18	5BW8 4.30 1.94 1.72	6BA6/EF93 3.25 1.47 1.30	6DC6 3.85 1.74 1.54	6GY5 4.60 2.07 1.84
3AW2A 4.05 1.83 1.62	5BZ7/5BQ7A 4.30 1.94 1.72	6BA7 5.90 2.66 2.36	6DE4/6CQ4 4.15 1.87 1.66	6GY6/6GX6 3.45 1.56 1.38
3BE6 2.70 1.22 1.08	\$CG8         4.00         1.80         1.60           \$CL8A         4.90         2.21         1.96           \$CQ8         4.10         1.85         1.64           \$CZ5         4.45         2.01         1.78           \$DH8         5.50         2,48         2.20	6BA8A 5.20 2.34 2.08	6DE6 3.25 1.47 1.30	6GY8 5.10 2.30 2.04
3BL2 3.55 1.60 1.42		6BA11 4.90 2.21 1.96	6DE7 4.45 2.01 1.78	6GZ5 2.70 1.22 1.08
3BM2 3.60 1.62 1.44		6BC4 5.50 2.48 2.20	6DG6GT 3.85 1.74 1.54	6H6 5.75 2.59 2.30
3BN2A 4.00 1.80 1.60		6BC7 3.60 1.62 1.44	6DK6 3.55 1.60 1.42	6HB5 4.60 2.07 1.84
3BN4 3.40 1.53 1.36		6BC8/6BZ8 4.90 2.21 1.96	6DN3 3.50 1.57 1.40	6HB6/6HA6 4.45 2.01 1.78
3BN6 4.75 2.14 1.90 3BU8/3GS8 4.90 2.21 1.96 3BW2/ 3BS2A 4.20 1.89 1,68 3BY6 3.00 1.35 1.20	5DJ4 3.55 1.60 1.42 5EÅ8 5.65 2.55 2.26 5ES8 5.50 2.48 2.20 5EU8 4.00 1.80 1.60 5EW6 4.00 1.80 1.60	6BD6 2.30 1.04 .92 6BD11 6.15 2.77 2.46 6BE3 4.45 2.01 1.78 6BE6 3.40 1.53 1.36 6BF5 3.35 1.51 1.34	6DL5/EL95 2.95 1.33 1.18 6DN6 7.00 3.15 2.80 6DN7 4.60 2.07 1.84 6DO5 8.15 3.67 3.26 6DQ6B/ 6GW6 5.35 2.41 2.14	6HB7 4.30 1.94 1.72 6HD7 3.30 1.49 1.32 6HE5 4.60 2.07 1.84 6HF5 8.70 3.92 3.48 6HF8 5.90 2.61 2.36
3BZ6 3.70 1.67 1.48	5FG7 4.60 2.07 1.84	6BF6 2.80 1.26 1.12	6GW6 5.35 2.41 2.14	6HG8/ECF86 3.70 1.67 1.48
3CA3 3.70 1.67 1.48	5FY8/5BR8 4.90 2.21 1.96	6BF11 5.05 2.28 2.02	6DR7 5.05 2.28 2.02	6HJ8 3.10 1.40 1.24
3CB6/3CF6 2.30 1.04 .92	5GH8 4.90 2.21 1.96	6BG6GA 7.15 3.23 2.86	6DS4 5.65 2.55 2.26	6HK5 3.90 1.76 1.56
3CE5/3BC5 2.95 1.33 1.18	5GJ7 2.95 1.33 1.18	6BH6 4.00 1.80 1.68	6DS5 3.65 1.65 1.46	6HL8 3.05 1.38 1.22
3CF5/3BC5 2.95 1.33 1.18	5GM6 3.25 1.47 1.30	6BH8 4.60 2.07 1.84	6DT5 3.55 1.60 1.42	6HM5/6HA5 3.85 1.74 1.54
3CN3B 4.10 1.85 1.64	5GS7 3.45 1.56 1.38	6BH11 4.70 2.12 1.88	6DT6A 3.25 1.47 1.30	6HM6 2.95 1.33 1.18
3CS6 3.70 1.67 1.48	5GX7 4.60 2.07 1.84	6BJ3 3.25 1.47 1.30	6DT8 3.75 1.69 1.50	6HQ5 5.05 2.28 2.02
3CU3A 4.90 2.21 1.96	5HA7 4.25 1.92 1.70	6BJ6 4.95 1.83 1.62	6DV4 6.45 2.91 2.58	6HR5 2.55 1.15 1.02
3CY3 3.75 1.69 1.50	5HB7 3.40 1.53 1.36	6BJ7 2.95 1.33 1.18	6DX8/	6HS5 7.73 3.49 3.10
3CZ3 4.35 1.96 1.74	5HG8/LCF86 3.70 1.67 1.48	6BJ8 4.45 2.01 1.78	ECL84 2.95 1.33 1.18	6HS6 3.70 1.67 1.48
3DA3/3CX3 4.20 1.89 1.68	5HZ6 3.25 1.47 1.30	6BK4C/6EL4 7.70 3.47 3.08	6DZ4/	6HS8 4.75 2.14 1.90
3DB3/3CY3 4.45 2.01 1.78	5J6 3.60 1.62 1.44	6BK5 3.45 1.56 1.38	6AF4A 4.90 2.21 1.96	6HV5 7.75 3.49 3.10
3DC3 4.60 2.07 1.84	5JK6 4.20 1.89 1.68	6BK7B 4.90 2.21 1.96	6DZ7 10.35 4.66 4.14	6HZ6 3.20 1.44 1.28
3DF3 4.20 1.89 1.68	5JL6 4.20 1.89 1.68	6BL7GTA 6.05 2.72 2.42	6E5 5.65 2.55 2.26	6HZ8 5.50 2.48 2.20
3DG4 5.90 2.66 2.36	5KE8 6.05 2.73 2.42	6BL8/	6EAB 3.90 1.76 1.56	6J5 4.60 2.07 1.84
3DJ3 4.25 1.92 1.70 3DK6 3.55 1.61 1.42 3DT6 3.25 1.47 1.30 3DZ4/ 3AF4B 4710 1.85 1.64	5KZ8 4.25 1.92 1.70 5LJB 4.40 1.98 1.76 5MB8 3.65 1.65 1.46 5T8 4.20 1.89 1.68 5U4GB/ 1.65 1.22	6BM8/ ECL82 2.90 1.31 1.16 6BN4A 3.95 1.78 1.58 6BN8 4.30 1.94 1.72	6EH4A 8.20 3.69 3.28 6EH5 3.55 1.60 1.42 6EH7/ EF183 3.85 1.74 1.54 6EH8 3.50 1.58 1.40	6]6A 4.45 2.01 1.78 6]7 6.35 2.86 2.54 6]11 5.75 2.59 2.30 6]B5 4.75 2.14 1.90 6]B6A 6.35 2.86 2.54
3EH7/ XF193 2.55 1.15 1.02 3EJ7/XF184 2.55 1.15 1.02 3ER5 4.45 2.01 1.78 3FS5 4.30 1.94 1.72	5AS4 3.05 1.38 1.22 5U8 4.70 2.12 1.88 5U9/LCF201 2.95 1.33 1.18 5V3/5AU4 3.80 1.71 1.52 5V4GA 4.30 1.94 1.72	6BN11 5.35 2.41 2.14 6BO5/EL84 3.90 1.76 1.56 6BO6GA/ 6CU 5.40 2.43 2.16 6BO6GTB 5.40 2.43 2.16	6EJ4A 9.35 4.21 3.74 6EJ7/EF184 3.55 1.60 1.42 6EM5 4.45 2.01 1.78 6EM7/6EA7 5.70 2.57 2.28 6EO7 2.95 1.33 1.18	6]C6A 4.45 2.01 1.78 6]C8 3.30 1.49 1.32 6]D5 7.75 3.49 3.10 6]D6 4.60 2.07 1.84



## General Electric Factory Cartoned Tubes at 60% Off List in Lots of 10 or More



		THE RESERVE			
Tube Type	List Net Net Price 1-9 10 up	Tube List Net Net Type Price 1-9 10 up	Tube List Net Net Type Price 1.9 10 up	Tube List Net Net Type Price 1-9 10 up	Tube List Net Net Type Price 1-9 10 up
6JE6C/ 6LQ6 6JE8 6JF6 6JG6A	8.65 3.90 3.46 3.70 1.67 1.48 7.25 3.27 2.90 6.50 2.93 2.60	6V4/EZ80 1.50 .68 .60 6V6 6.80 3.06 2.72 6V6GTA 4.45 2.01 1.78 6W4GTA 3.30 1.49 1.32 6W6GT 4.60 2.07 1.84	10T10 5.35 2.41 2.14 10Z10 6.15 2.77 2.46 11AF9 3.10 1.40 1.24 11AR11 5.35 2.41 2.14 11BM8 5.45 2.46 2.18	12FQ8 5.20 2.34 2.08 12FX5 3.25 1.47 1.30 12FX8A 3.85 1.74 1.54 12GA6 2.70 1.22 1.08 12GB3 9.35 4.21 3.74	17GV5 4.20 1.89 1.68 17H3 3.70 1.67 1.48 17HB25 7.65 3.45 3.06 17JB6A 5.85 2.64 2.34 17JM6 5.90 2.66 2.36
6]H6 6]H8 6]K6 6]K8 6]M6	3.60 1.62 1.44 5.50 2.48 2.20 4.20 1.89 1.68 4.05 1.83 1.62 5.70 2.57 2.28	6X4 3.40 1.93 1.36 6XSGT 3.55 1.60 1.42 6XBA 4.45 2.01 1.78 6X9/ECF200 2.95 1.33 1.18 6Y6GT 3.55 1.60 1.42	11BQ11 5.35 2.41 2.14 11BT11 6.50 2.93 2.60 11CA11 7.50 3.38 3.00 11CF11 7.80 3.51 3.12 11CY7 4.80 2.16 1.92	12GC6 4.35 1.96 1.74 12GE5 5.20 2.34 2.08 12GT5A 5.35 2.41 2.14 12H6 4.45 2.01 1.78 12HE7 6.80 3.06 2.72	17JN6 5.35 2.41 2.14 17JT6A 5.60 2.52 2.24 17JZ8 3.55 1.60 1.42 17KV6 8.60 3.87 3.44 17Z3 4.40 1.98 1.76
6]N6 6]N8 6]Q6 6]S6C 6]T6A	5.35 2.41 2.14 3.65 1.65 1.46 3.85 1.74 1.54 7.50 3.38 3.00 5.85 2.64 2.34	6Y9 3.10 1.40 1.24 6Z10/6J10 6.20 2.79 2.48 7A7 7.15 3.22 2.86 7AU7 3.10 1.40 1.24 7B5 8.35 3.76 3.34	11FY7 3.70 1.67 1.48 11HM7 5.85 2.64 2.34 11JE8 3.85 1.74 1.54 11KV8 6.50 2.93 2.60 11LQ8 5.90 2.66 2.36	12HG7/ 12GN 5.65 2.55 2.26 12HL7 4.90 2.21 1.96 12J5 4.10 1.85 1.64 12J8 4.35 1.96 1.74	18A5 5,20 2,34 2,08 18AJ10 5,90 2,66 2,36 18FW6 2,45 1,11 .98 18FX6 2,95 1,33 1,18 18FY6 2,95 1,33 1,18
6JT8 6)U8A 6)V8 6)W8/ ECF802	4.45 2.01 1.78 4.40 1.98 1.76 4.40 1.98 1.76 3.10 1.40 1.24	7C5 3.30 1.49 1.32 7C7 3.40 1.53 1.36 7EY6 3.70 1.67 1.48 7F7 7.50 3.38 3.00 7F8 8.25 3.72 3.30	11LT8 4.00 1.80 1.60 11R3 4.90 2.21 1.96 11Y9/LFL20 3.70 1.67 1.48 12AB5 3.85 1.74 1.54 12AC6 2.10 .95 .84	12]N6 3.90 1.76 1.56 12]N8 3.70 1.67 1.48 12]Q6 3.70 1.67 1.48 12]T6A 4.95 2.23 1.98 12K5 3.45 1.56 1.38	18GB5 5.15 2.32 2.06 18GV8/PCL8 4.65 2.10 1.86 19AU4GTA 4.35 1.96 1.74 19BG6GA 6.65 3.00 2.66 19CG3 3.60 1.62 1.44
6]Z6 6)Z8 6K6GT 6K7 6K11/6Q11	4.60 2.07 1.84 13.55 1.60 1.42 4.00 1.80 1.60 5.50 2.48 2.20 3.80 1.71 1.52	7GS7 4.40 1.98 1.76 7GV7 3.90 1.76 1.56 7HG8/PCF86 2.75 1.24 1.10 7N7 7.10 3.20 2.84 8AC10 5.05 2.28 2.02	12AC10A 5.05 2.28 2.02 12AD6 3.50 1.58 1.40 12AE6A 3.10 1.40 1.24 12AE10 5.75 2.59 2.30 12AF3 4.25 1.92 1.70	12L6GT 3.55 1.60 1.42 12MD8 4.85 2.19 1.94 12R5 3.30 1.49 1.32 12SA7 5.50 2.48 2.20 12SF5 3.95 1.78 1.58	19DE3 4.50 2.03 1.80 19EA8 4.45 2.01 1.78 19EZB 5.40 2.43 2.16 19GQ7 3.80 1.71 1.52 19HV8 4.70 2.12 1.88
6KA8 6KD6 6KE8 6KL8 6KM6	4.90 2.21 1.96 8.85 3.99 3.54 6.05 2.73 2.42 2.95 1.33 1.18 8.85 3.99 3.54	8AL9 8.15 3.67 3.26 8AR11 5.35 2.41 2.14 8AU8 3.85 1.74 1.94 8AW8A 5.35 2.41 2.14 8B10 4.40 1.98 1.76	12AF6 3.15 1.42 1.26 12AL5 2.75 1.24 1.10 12AL8 6.20 2.79 2.48 12AL11 5.65 2.55 2.26 12AQ5 3.45 1.56 1.38	12SG7 4.70 2.12 1.88 12SJ7 4.30 1.94 1.72 12SK7 5.25 2.37 2.10 12SL7GT 4.95 2.23 1.98 12SN7GTA 4.30 1.94 1.72	19JN8/19CL 3,20 1.44 1.28 19KG8 3.10 1.40 1.24 19TB 4.90 2.21 1.96 20AQ3/LY88 3.30 1.49 1.32 20EZ7 3.45 1.56 1.38
6KM8 6KN6 6KN8/ 6RHH8 6KR8	3.45 1.56 1.38 7.20 3.24 2.88 7.40 3.33 2.96 4.25 1.92 1.70	8BA11 5.50 2.48 2.20 8BM11 4.70 2.12 1.88 8BN11 4.35 1.96 1.74 8BQ5 3.75 1.69 1.50 8BQ11 4.30 1.94 1.72	12AT6 2.75 1.24 1.10 12AT7/ECC8 3.55 1.60 1.42 12AU6 3.55 1.60 1.42 12AU7A/ ECC82 3.40 1.40 1.24	12SQ7 4.95 2.23 1.98 12T10 4.65 2.10 1.86 12V6GT 4.45 2.01 1.78 12W6GT 4.90 2.21 1.96 12X4 2.25 1.02 90	21GY5 4.60 2.07 1.84 21HB5A 4.75 2.14 1.90 21JS6A/23J 12.45 5.61 4.98 21JY6 4.60 2.07 1.84 21JZ6 4.85 2.19 1.94
6KS6/6BN6 6KT6 6KT8 6KU8 6KV6A		8BU11 5.00 2.25 2.00 8CB11 5.60 2.52 2.24 8CM7 2.70 1.22 1.08 8CN7 3.05 1.39 1.22 8CS7 3.95 1.78 1.58	12AV5GA 5.45 2.46 2.18 12AV6 2.30 1.04 .92 12AV7 4.60 2.07 1.84 12AX3 3.00 1.35 1.20 12AX4GTB 3.30 1.49 1.32	13CW4 5.05 2.28 2.02 13DE7 4.75 2.14 1.90 13DR7 5.70 2.56 2.28 13EM7/15EA 6.40 2.88 2.56 13FD7 5.25 2.37 2.10	21KA6 4.45 2.01 1.78 21KQ6 12.75 5.74 5.10 21LG6A 8.95 4.03 3.58 21LR8 4.75 2.14 1.90 21LU3 4.75 2.14 1.90
6KV8 6KY8A 6KZ8 6L6 6L6GC	5.85 2.64 2.34 7.70 3.47 3.08 4.05 1.83 1.62 10.20 4.59 4.08 5.90 2.66 2.36	8CW5 2.55 1.15 1.02 8CX8 4.40 1.98 1.76 8EM5 4.10 1.85 1.64 8ET7 4.15 1.87 1.66 8FQ7/8CG7 2.95 1.33 1.18	12AX7/ ECC83 2.80 1.26 1.12 12AX7A/ 7025 2.80 1.26 1.12 12AY3A/	13GB5/XL50 4.35 1.96 1.74 13GF7A 5.20 2.34 2.08 13JZ8 5.05 2.28 2.02 13V10 5.90 2.66 2.36 13Z10/13J1 6.20 2.79 2.48	22BH3A 3.10 1.40 1,24 22BW3 4.15 1.87 1.66 22DE4 4.20 1.89 1.68 22]F6 7.25 3.27 2.90 22]G6A 6.75 3.05 2.70
6LB6 6LB8 6LC8 6LE8 6LF6	8.85 3.99 3.54 4.70 2.12 1.88 4.75 2.14 1.90 5.55 +2.50 2.22 8.45 3.81 3.38	8GJ7/ PCF801 2.90 1.31 1.16 8GN8/8EB8 4.15 1.87 1.66 8JU8A 3.35 1.51 1.34 8JV8 4.30 1.94 1.72	12B3A 2.90 1.31 1.16 12AZ7A 4.00 1.80 1.60 12B4A 4.00 1.80 1.60 12BA6 2.80 1.26 1.12 12BA7 5.90 2.66 2.36	14BL11 7.30 3.29 2.92 14BR11 5.80 2.61 2.32 14GT8 3.50 1.58 1.40 14JG8 4.00 1.80 1.60 15AF11 4.75 2.14 1.90	22]R6 6.80 3.06 2.72 22]U6 6.80 3.06 2.72 22KM6 8.20 3.69 3.28 23Z9 4.75 2.14 1.90 24BF11 5.20 2.34 2.08
6LF8 6LJ6A/6LH6 6LJ8 6LM8 6LN8	5.10 2.30 2.04	8KA8 4.65 2.10 1.86 8KR8 6.20 2.79 2.48 8LC8 4.75 2.14 1.90 8LT8 4.00 1.80 1.60 9A8/8A8/PC 2.65 1.20 1.06	12BD6 2.30 1.04 .92 12BE3 3.45 1.56 1.38 12BE6 3.05 1.38 1.22 12BF6 2.30 1.04 .92 12BF11 5.75 2.59 2.30	15BD11A 5.50 2.48 2.20 15CW5/PL84 2.45 1.11 .98 15DQ8 3.55 1.60 1.42 15FM7/13FM 4.00 1.80 1.60 15FY7 3.90 1.76 1.56	24JZ8
6LQ8 6LR6 6LR8 6LT8 6LU8	5.55 2.50 2.22 8.15 3.67 3.26 4.75 2.14 1.90 4.00 1.80 1.60 4.75 2.14 1.90	9AH9 5.05 2.28 2.02 9AK10 5.05 2.28 2.02 9AQ8 7.15 3.22 2.86 9AU7 2.95 1.33 1.18 9BJ11 5.85 2.64 2.34	12BH7A 3.85 1.74 1.54 12BK5 3.75 1.69 1.50 12BL6 3.70 1.67 1.48 12BN6 4.60 2.07 1.84 12BQ6GA/12 4.20 1.89 1.68	15KY8A 6.35 2.86 2.54 15LE8 7.65 3.45 3.06 15MF8 5.10 2.30 2.04 16A8/PCL82 3.45 1.56 1.38 16AK9 6.80 3.06 2.72	25BQ6GA/ 25 4.35 1.96 1.74 25BQ6GTB 4.35 1.96 1.74 25C5 3.70 1.67 1.48 25CA5 3.60 1.62 1.44
6LX8/ LCF802 6LY8 6M11 6MB8	2.60 1.17 1.04 3.90 1.76 1.56 5.75 2.59 2.30 3.65 1.65 1.46	9BR7 3.15 1.42 1.26 9CL8 2.95 1.33 1.18 9GH8A 4.10 1.85 1.64 9GV8 3.40 1.53 1.36 9JW8 3.25 1.47 1.30	12BQ6GTB 4.20 1.89 1.68 12BR3/12RK 3.60 1.62 1.44 12BR7 3.05 1.38 1.22 12BT3 3.45 1.56 1.38 12BV11 4.80 2.16 1.92	16AQ3/ XY88 2.70 1.22 1.08 16BQ11 5.35 2.41 2.14 16BX11 6.20 2.79 2.48 16GK6 3.05 1.38 1.22	25CD6GB 6.40 2.88 2.56 25CG3 3.40 1.53 1.36 25DK4 2.20 .99 .88 25DN6 6.60 2.97 2.64 25E5 6.65 3.00 2.66
6MD8 6ME8 6MF8 6MG8 6MJ8	5.35 2.41 2.14 5.65 2.55 2.26 4.75 2.14 1.90 2.45 1.11 .98 4.60 2.07 1.84	9KC6 4.35 1.96 1.74 9KZ8 2.95 1.33 1.18 9MN8 4.45 2.01 1.78 9R-HR2 4.90 2.21 1.96 10AL11 4.55 2.05 1.82	12BW4 3.30 1.49 1.32 12BY7A/ BV7 3.55 1.60 1.42 12BZ7 4.15 1.87 1.66 12CAS 3.95 1.78 1.58	16GY5 4.85 2.19 1.94 16KA6 6.25 2.82 2.50 16LU9A 7.25 3.27 2.90 17A8 5.90 2.66 2.36 17AB9 6.05 2.73 2.42	25EC6 6.95 3.13 2.78 25EH5 3.70 1.67 1.48 25F5A 3.85 1.74 1.54 25L6GT/ 25W 3.70 1.67 1.48
6MK8A 6MN8 6MQ8 6MU8 6MV8	4.30 1.94 1.72 4.75 2.14 1.90 3.80 1.71 1.52 5.20 2.34 2.08 5.40 2.43 2.16	10BQ5 2.75 1.24 1.10 10C8 6.05 2.73 2.42 10CW5/ 1L86 2.55 1.15 1.02 10DE7 4.90 2.21 1.96	12CN5 3.25 1.47 1.30 12CR6 2.95 1.33 1.18 12CT8 6.40 2.88 2.56 12CU5/12C5 4.30 1.94 1.72 12CX6 2.75 1.24 1.10	17AB10/17X 5.50 2.48 2.20 17AX3 2.60 1.17 1.04 17AX4GTA 3.55 1.60 1.42 17AY3A/17B 3.70 1.67 1.48	25W4GT 3.70 1.67 1.48 25Z6GT 3.85 1.74 1.54 26HU5 12.05 5.43 4.82 26LX6 9.50 4.28 3.80 27 5.10 2.30 2.04
6N7 6RP22 6S4A 6SA7 6SC7	5.05 2.28 2.02 9.95 4.48 3.98 3.70 1.67 1.48 5.50 2.48 2.20 5.35 2.41 2.14	10DX8/ LC1.84 2.75 1.24 1.10 10EG7 4.40 1.98 1.76 10EM7 4.90 2.21 1.96 10EW7 5.25 2.37 2.10	12D4 3.05 1.38 1.22 12DB5 2.60 1.17 1.04 12DE8 3.10 1.40 1.24 12DQ6B/ 12GW6 5.35 2.42 2.14	17BE3 3.70 1.67 1.48 17BF11 5.90 2.66 2.36 17BR3/17RK 3.35 1.51 1.34 17BW3 3.20 1.44 1.28	27GB5/ PL50 3.70 1.67 1.48 29GK6 3.60 1.62 1.44 29KQ6 11.75 5.29 4.70 30AE3 3.25 1.47 1.30
6SF5 6SG7 6SH7 6SJ7 6SK7	5.00 2.25 2.00 5.60 2.52 2.24 6.15 2.77 2.46 5.35 2.41 2.14 5.00 2.25 2.00	10GF7A 5.45 2.46 2.18 10GK6 4.45 2.01 1.78 10GN8 4.90 2.21 1.96 10GV8 3.55 1.60 1.42 10HF8 5.35 2.41 2.14	12DS7 5.40 2.43 2.16 12DT5 3.10 1.40 1.24 12DT8 3.55 1.60 1.42 12DW4A 5.45 2.46 2.18 12DY8 7.95 3.58 3.18	17C9 7.15 3.22 2.86 17CK3 3.55 1.60 1.42 17CT3 2.95 1.33 1.18 17CU5/17C5 3.10 1.40 1.24	30AG11 6.45 2.91 2.58 30[Z6 6.15 2.77 2.46 30KD6 8.05 3.63 3.22 31AL10 6.35 2.86 2.54 31]S6A 7.30 3.29 2.92
6SL7GT 6SN7GTB 6SQ7 6T8A 6T9	4.90 2.21 1.96 4.00 1.80 1.60 4.95 2.23 1.98 4.70 2.12 1.88 4.40 1.98 1.76	10JA5 5.05 2.28 2.02 10JT8 4.70 2.12 1.58 10JY8 3.65 1.65 1.46 10KR8 4.25 1.92 1.70 10KU8 4.85 2.19 1.94	12ED5 2.70 1.22 1.08 12EG6 3.45 1.56 1.38 12EK6/ 12DZ6 3.60 1.62 1.44 12EQ7 2.75 1.24 1.10	17DM4 4.05 1.83 1.62 17DE4 3.65 1.65 1.46 17DO6B/	32ET5A 2.40 1.08 .96 32HQ7 7.70 3.47 3.08 33GT7 6.95 3.13 2.78 33GY7A 6.40 2.88 2.56 33JV6 4.60 2.07 1.84
6T10 6UBA/6AXB 6U9 6U10 6V3A	5.55 2.50 2.22 3.90 1.76 1.56 2.90 1.31 1.16 4.05 1.83 1.62 4.55 2.05 1.82	10LB8 4.70 2.12 1.88 10LE8 5.90 2.66 2.36 10LW8 5.30 2.39 2.12 10LY8 3.90 1.76 1.56 10LZ8/10JA 4.15 1.87 1.66	12FZ6 3.55 1.60 1.42 12F8 3.25 1.47 1.30 12FK6 2.55 1.15 1.02 12FM6 2.60 1.17 1.04 12FQ7 3.70 1.67 1.48	17EW8/ HCC8 2.75 1.24 1.10 17GE5 4.35 1.96 1.74 17GJ5 6.05 2.73 2.42	34CE3/34CD 3.90 1.76 1.56 34GD5 2.95 1.33 1.18 34R3 3.45 1.56 1.38 35BS 3.20 1.44 1.28 35C5 3.20 1.44 1.28

General Ele		ned Tubes at 60%		f 10 or More
Tube List Net Net Type Price 1-9 10 up 35EH5 3.40 1.53 1.36 35GL6 2.90 1.31 1.16 35L6GT 3.85 1.74 1.54 35W4 1.95 88 .78 35Y4 4.50 2.03 1.80	Tube List Net Net Type Price 1-9 10 up 38HK7 7.10 3.20 2.84 40KG6A 10.05 4.53 4.02 42KN6 7.20 3.24 2.88 45B5/UL84 2.80 1.26 1.12 50B5 2.95 1.33 1.18	Tube List Net Net Type Price 1-9 10 up 50HK6 2.15 .97 .86 50HN5 2.75 1.24 1.10 50JY6 7.00 3.15 2.80 50L6GT 4.45 2.01 1.78 53HK7 8.35 3.76 3.34	Tube List Net Net Price 1-9 10 up 6931 3.40 1.53 1.36 6973 5.05 2.28 2.02 7027 A 7.40 3.33 2.96 7189 A 4.40 1.98 1.76 7199 5.65 2.55 2.26	Tube List Net Net 77pe Price 1-9 10 up 7591A 2.80 1.26 1.12 7695 4.40 1.98 1.76 7868 5.65 2.55 2.26 7868 4.75 2.14 1.90 8417 5.65 2.55 2.26
3525GT 3.40 1.53 1.36 36AM3B 2.55 1.15 1.02 36KD6/ 40KD6 8.85 3.99 3.54 38HE7 7.25 3.27 2.90	\$0C5 3.05 1.38 1.22 \$0DC4 2.40 1.08 .96 \$0EH5 3.55 1.60 1.42 \$0FE5 4.45 2.01 1.78 \$0HC6 4.15 1.87 1.66	60FX5 2.95 1.33 1.18 80 4.80 2.16 1.92 117Z3 4.50 2.03 1.80 5879 5.35 2.41 2.14 6267 2.80 1.26 1.12	7247 4.05 1.83 1.62 7355 3.65 1.65 1.46 7408 3.20 1.44 1.28 7544 3.25 1.47 1.30 7581A/KT66 6.15 2.77 2.46	8425A/ 6AU6 3.25 1.47 1.30 8426A/ 12AU6, 3.75 1.69 1.50
RAYTH	EON RECEIVIN	IG TUBE 70%	OFF LIS	JOBBER BOXED NET PRICES ARE 70 % OFF LIST
Tube List Type Price Net OZ4 3.85 1.16 1AD2 3.85 1.16 1BC2 2.90 .87 1B3GT (use 1G3GT/1B3GT) 1.02	Tube List Price Net 6AX4GTB 3.70 1.11 6AY3B/6BS3A 3.70 1.11 6B10 4.45 1.34 6BA6/EF93 3.25 .98 6BA11 4.90 1.47	Tube List Type Price Net 6EM7/6EA7 5.70 1.71 6EU7 3.95 1.19 6EV5 3.55 1.07 6EW6 3.55 1.07 6EW7 6.00 1.80	Tube List Type Price Net 6RB11 3.65 1.10 6RHH2 (use 6BC8/6BZ8) 1.47 6RK19 (use 6AF3/ 6BR3/6RK19) 1.07	Tube List Price Net 12SQ? 4.95 1.49 13DR7 5.25 1.58 13EM7/15EA7 5.85 1.76
1G3GT/tB3GT 3.40 1.02 113K29 3.00 .90 1J3 (use 1K3/1J3) 1.19 1K3/1J3 3.95 1.19	6BC8/6BZ8 4.90 1.47 6BE6 3.40 1.02 6B16 4.00 1.20 6BJ6 4.05 1.22 6BK4C/6EL4A 7.70 2.31	6FG7 4.60 1.38 6FM7 4.60 1.38 6FQ5A (Use 6GK5/6FQ5A 61Q7/6CG7 2.95 .89	6RP15 4.65 1.40 6RP22 10.70 3.21 6S4A 3.70 1.11 6SL*GT 4.90 1.47 6SN*GTB 4.00 1.20	15BD11A 5.50 1.65 15EA7 (usc 13EM7/15EA7) 1.76 15KY8A 6.35 1.91 16CB28 9.75 2.93 17AX4GTB 3.55 4.07
1R5 4.45 1.34 1V2 2.40 .72 1X2B 4.10 1.23 2AS2 3.90 1.17 2AV2 3.10 693	6BK7B 4,90 1.47 6BL8/ CF80 2.70 81 6BM8/ECL82 2.90 .87 6BN4A 3.95 1.19 6BN6 4.50 1.35	6EV8A (Use 6BR8A/6FV8A 1.41 6CB3A 5.40 1.62 6GB6 4.60 1.38 6GB7A 5.30 1.59	6T8A 4,70 1.41 6T10 5.55 1.67 6U8A/6KD8 3.90 1.17 6U10 4.05 1.22 6V6GTA 4.45 1.34 6W6GT 4.60 1.38	17AY3A/17BS3A/ 17DW4A 3.70 1.f1 17BB14 9.80 2.94 17BE3 3.70 1.11 17BF11 5.90 1.77
2CY5 4.40 1.32 2FQ5A (use 2GK5/2FQ5A) 1.16 2GK5/2FQ5A 3.85 1.16 3AA73AW3 3.40 1.02 3AT2 3.70 1.11	6BNs 3.70 1.11 6BQ5/FL84 3.90 1.17 6BQ6GTB/6CU6 5.40 1.62 6BQ7A/6BZ7 5.00 1.50 6BR3 (us 6AF3) 6BR3/6RK19) 1.07	6GC5 5.00 1.50 6GE5 5.70 1.71 6GF7 5.35 1.61 6GH8 3.20 .96 6GJ7/ECF801 3.10 .93	6X4 3.40 1.02 6X5GT 3.55 1.07 6X8A 4.45 1.34 6Z10/6J10 6.20 1.86 7AU7 3.10 .93	17BR3/17RK19 3.35 1.01 17BS3 (use 17AY3/17BS3A 1.11 17D4A/17DM4A 4.05 1.22 17DM4A (use 17DM4A/17DM4A 1.22
3AW3 (use 3A3/3AW3) 3.40 1.02 3BU8/3GS8 4.90 1.47 3BZ6 3.70 1.11 3CA3 3.70 1.11	6BR8A/6FV8A 4.70 1.41 6BS3A (use 6AY3B/6BS3A) 1.11 6BX8 (use 6BC8/6BZ8) 1.47	6GK6 3:70 1.11 6GK17 (Use 6AU4GTA) 1.46 6GM6 3.85 1.16 6GN8 5.05 1.52	7G\$7 4.40 1.32 7MP18 5.30 1.59 8AW8A 5.35 1.61 8Bs 5.80 1.74 8B10 4.40 1.32	17DQ6B/17GW6 5.25 1.58 17DW4 (usc 17AY3A) 1.11 17GW6 (usc 17DQ6/17GW6) 1.58
3CB6/3CF6 2.30 .69 3CF6 (usc 3CB6/3CF6) 2.30 .69 3CY5 3.75 1.13 3DHH12 3.65 1.10	6BU8 5.05. 1.52 6BZ6 3.10 .93 6BZ7-{usc 6BQ7A/6BZ7} 1.50	6GS7 3.55 1.07 6GU7 4.15 1.25 6GV5 4.10 1.23 6GW6 (Use 6DQ6B/6GW6) 1.38	8CW5/XL86 2.55 .77 8CG7 (use 8FQ7/8CG7 8FQ7/8CG7 2.95 .89 8JV8 4.30 1.29	17HB25 7.65 2.30 17JM6 5.90 1.77 17JN6 5.35 1.61 17JZ8 3.55 1.07 18RAL1 5.80 1.74
3DHH13 7.15 2,13 3DT6A 3.25 .98 3MP26 4.30 1.29 3GK5 3.85 1.16	6CA4/EZ81 3.25 .98 6CB6/6CF6 3.25 .98 6CD3 (use 6CG3/6CE3/6CD3) 1.17	6GW8/ECL86 3.05 .92 6GX6 (Use 6GY6/6GX6) .96 6GX7 4.60 1.38	8KR8 6.20 1.86 8LT8 4.00 1.20 9JW8 3.90 1.17 9MHH3 4.15 1.25 9MP12 4.30 1.29	19AU4GTA 4.35 1.31 19MR9 2.45 .74 19TB 4.90 1.47 21GY5 4.60 1.38
3GS8 (use 3BU8/3GS8) 1.47 3HA5 (use 3HM5/3HA5) 1.16 3HM5/3HA5 3.85 1.16	6CE3 (use 6CG3/6CE3/6CD3) 1.17 6CF6 (Use 6CB6A/6CF6A .98 6CG3/ 6CE3/6CD3 3.90 1.17	6GY6/6GX6 3.20 .96 6HA5 (Use 1.16 6HB7 4.30 1.29 6HE5 4.60 1.38	9RAG 7.65 2.30 9RAL1 (use 10DE7) 1.47 10CW5/LL86 2.55 .77 10DE7 4.90 1.47 10EW7 5.25 1.58	21]S6A 12.45 3.74 21]Z6 4.85 1.46 21LR8 4.75 1.43 22BW3 4.15 1.25 22DE4 4.20 1.26
3HQ5 5.65 1.69 4BZ6 3.70 1,11 4CB6 2.70 .81 4DT6A 3.25 .98	6CG7 (Use 6FQ7/6CG7) 6CG8A 4.30 1.29 6CJ3/ 6DW4B/6CL3 3.70 1.11	6HF8 5.25 1.58 6HG5 (Use 6AQ5A/6HG5) 1.02 6HM5/6HA5 3.85 1.16 6HQ5 5.05 1.52	10GK6 3.45 1.04 10GN8 4.90 1.47 11BM8 5.45 1.64 11KV8 6.50 1.95 12AD6/12GA6 3.50 1.05	23JS6A 12.45 3.74 23Z9 4.75 1.43 25BB14 10.50 3.15 25L6GT 3.70 1.11 30KD6 8.05 2.42
4EH7/LF183 3.55 1.07 4EJ7/LF184 3.55 1.07 4GS7 3.70 1.11 4HS8 3.70 1.11 4JC6A 5.05 1.52	6CL3 (Use 6CJ3/6DW4B/6CL3) 1.11 6CL6 4.75 1.43 6CL8A 4.60 1.38 6CM7 4.15 1.25	6H55 7.75 2.33 6HS8 4.75 1.43 6HZ6 2.90 87 6J5GT 4.60 1.38 6J6A 4.45 1.34	12AF3/ 12BR3/12RK19 4.25 1.28 12AT6 2.75 .83 12AT7/ECC81 3.55 1.07 12AU6 3.55 1.07	30MP23 3.70 1.11 30MP27 3.80 1.14 33GY7A 6.40 1.92 35C5 3.20 .96 35L6GT 3.85 1.16
4MP12 4.30 1.29 4MP26 4.30 1.29 4RHH2 4.45 1.34 5AQ5 3.70 1.11 5AR4/GZ34 4.25 1.28 5CG8 4.00 1.20	6CQ8 4.10 1.23 6CS6 3.30 .99 6CS7 3.75 1.13 6CU5 4.00 1.20	6J10' (Use 6Z10/6J10 6JC6 6JD6 6JD6 6JE6C (Use 6LQ6/6JE6C) 2.55	12AU7A/ECC82 3.10 .93 12AV6 2.30 .96 12AV7 4.60 1.38 12AX4GTB 3.30 .99 12AX7A 2.80 .84	35W4 1.95 .59 35Z5 2.95 .89 38HE7 7.25 2.18 50C5 3.05 .92 50EH5 3.55 1.07
SCG8 4.00 1.20 SCL8A 4.90 1.47 5EA8 5.05 1.52 5GH8A 4.90 1.47 5GS7 3.65 1.10 5KE8 6.05 1.82	6BQ6GTB/6CU6) 1.62 6CW4/6DS4 5.65 1.70 6CW5/EL86 2.75 .83 6CX8 5.20 1.56 6CY5 4.25 1.28	6]H6 3.60 1.08 6]H8 5.50 1.65 6]M6A 5.70 1.71 6]N6 5.35 1.61 6]S6B 7.50 2.25 6]U8A 4.40 1.32	12AZ7 4.00 1.20 12B4 4.00 1.20 12BA6 2.80 .84 12BB14 10.50 3.15	50L6GT 4.45 1.34 7025 2.80 84 NEW ADDITIONS TO THE RAYTHEON- JOSEER BOXED TUBE LINE. 3AW2 3.20 .96 3DG4 5.90 1.77
5LJB 4.40' 1.32 5MHH3 3.60 1.08 5MK9 3.90 1.17 5RK16 5.20 1.56 5U4GB 3.05 .92	6CZ5 4.75 1.43 6DE4 3.55 1.07 6DE6 3.25 98 6DE7 4.45 1.34 6DHH12 3.75 1.13 6DHH13 7.30 2.19	6JY8 7.30 2.19 6JZ8 3.55 1.07 6K6GT 3.45 1.04 6KA8 4.90 1.47 6KD6 8.85 2.66	12BE6 3.05 .92 12BH7A 3.85 1.16 12BR3 (use 12AF3/ 12BR3/12RK19 1.28 12BY7/(use 12BY7/12BV7) 1.07 12BY7/12BY7 3.55 1.07	3 JC6 5.05 1.52 5GM6 3.25 .98 6AB8 3.85 1.15 6AC10 4.25 1.27 6AD10 8.15 2.45 6BX6 3.05 .92 6ES8 5.45 1.64
5U8 4.70 1.41 5Y3GT 2.95 .89 6AB4 3.60 1.08 6AF3/ 6BR3/6RK19) 3.55 1.07 6AF4A	6DK6 2.95 .89 6DQ5 8.15 2.45 6DQ6B/6GW6 4.60 1.38 6DR7 5.05 1.52 6DS4 (Use	6KD8 (Use 6U8/6KD8 6KE8 6.05 1.82 6KT8 5.40 1.62 6KY8A 7.70 2.31	12C5 (use 12CU5/12C5) 1.29 12CU5/12C5 4.30 1.29 12DQ6B/12GW6 4.95 1.49 12DT8 3.55 1.07	6ES8 5.45 1.64 6HV5 7.75 2.33 6LT8 4.00 1.20 6LY6 3.90 1.17 9AQ8 4.40 1.32 9GHB 4.10 1.23
(use 6DZ4/6AF4A 1.47 6AH6 5.20 1.56 6AK5/EF95 4.50 1.35 6AL3 2.60 .78	6CW4/6DS4) 1.70 6DT6 3.25 .98 6DW4B (Use 6CJ3/6DW4/6CL3) 1.11 6DX8/ECL84 2.95 .89	6KZ8 4.05 1.22 6L6GC 5.90 1.77 6LB6 8.85 2.66 6LE8 5.55 1.66 6LF8 5.10 1.53	12DW4 5.45 1.64 12EX5 3.25 .98 12GA6 (use 12AD6/12GA6) 1.05 12GB3 9.35 2.81	11M\$8
6AL5 2.95 89 6AM8A 4.60 138 6AN8A 5.20 1.56 6AQ5A/6HG5 3.40 1.02 6AS5 4.00 1.20	6DZ4/6AF4A 4.90 1.47 6EA7 (Use 6EM7/6EA7 1.71 6EA8 3.90 1.17	6LJ8 4.40 1.32 6LM8 4.90 1.47 6LQ6/6JE6C 8.50 2.55 6LU8 4.75 1.43 6MD8 5.35 1.61	12GB7 (use 12DQ6B) 1.49 12GK17 (use 12AX4GTB) .99	18GV8 4.65 1.40 21KQ6 13.65 4.09 25E5 7.10 2.13 25HX5 8.60 2.58 29KQ6 12.60 3.78
6AU4GTA 4.85 1.46 6AU6A 2.95 .89 6AU8A 5.65 1.70 6AV6 2.70 .81 6AW8A 4.45 1.34	6EH7/EF183 3.85 1.16 6E17/EF184 3.55 1.07 6EL4A (Use 6BK4C/6EL4A 2.31	6ME8 5.65 1.70 6MHH3 (Use 6J6A) 1.34 6MP17 5.50 1.65 6MP18 5.35 1.61 6RA6 6.80 2.08	12GW6 (use 12DQ6B/12GW6 1.49 12HB25 8.20 2.46 12HL7 4.90 1.47 12RK19 (usc 12AF3/	29LE6 10.55 3.17 30AE3 3.25 .98 34CE3 3.90 1.17 34R3 3.45 1.03 40KG6 10.05 3.01 50JY8 7.50 2.25
		6RA9 4.00 1.20 INVENTORY OF THE ABOVE RA		

## For sharp 82-Channel TRUE COLOR TV POWER-200M / TOP ATTACHMENT RATED! Model VU-8PZ

For that extre gain in the worst UHF reception areas, just attach the optional Power Zoom, 3 element UHF director to any VULFinder Plus boom. See "gen curves for typical 2 oft to 4 88 resulting increases Leants in the

High Caid

Lightning Protection Low Hoise Figure . Flat Frequency Responsi

Universal Mounting

Elements \$6.50

NET \$3.90

Installations are a stage with Jerroid VU-Finder
Plus antennas. There go top quick and easy Once
top-Plus antennas. There go top quick and easy Once
top-erform fair winds that guil others on the grand of the Pu-Finder Plus antennas are super-depth gas
top-there star up. These highward tested models
perform fair winds that guil others on the grand earlies destrict the transported activity. The performance is top rated as skimm by
the curvat and specifications from the Jerroid areas
the curvat and specifications from the Jerroid areas
and engineers specify Jerroid because they have the proposed fair of the performance of th

Reception Area Weight (Lbs.) Boom Length Hode I Net 50' \$25.75 Local 10-431 Metro-\$34.25 66" 5% 19-632 99" 6.0 \$47.25 19-653 Suburban Suburban 6 Fringe \$58.75 \$35.25 113" 7.0 **75-04** \$73.25 Pringe

powermate plus

PREAMPLIFIERS Jerrold

SIGNAL SPLITTER,

VHF-TV, UHF-TV AND FM-

MODEL VU-935 \$43.95

## THE NEW LOOK OF POWERI

#### PERFORMANCE TESTED FOR BEST COLOR RECEPTION

- e Unsurpassed Color Recuption
  o Rugged Top Bated Construction
  o Attractive to Line Design
- & Lass of Installatius
- Ezcellent March Provides Highest Output
   300 Ohm Coloraural Convertible to 75 Ohm

LIFE-LIKE COLOR TY

BROADBAND VHF ANTENNAS SUPERB BLACK & WHITE AND COLOR FROM SUBURBAN TO EXTREME FRINGE AREAS

TOP RATED! Model VIP-307 NET \$53.37 For Deep Fringe Reception Areas

"COLORAXIAL CONVERTIBLE" NET \$1.50

MATCHING TRANSFORMER.

Alt W sil-channes and sing-on transformer single si

.u \$2.50 Medel STO 82 "F" Sitting ...

## PARALOG 300 PL

VHP-TV & PM ANTENNAS

Saires of seem highligatin periodic-type antennas sawilar to Vülnder series but for VHSTP channels and all FM stations. Unabasity flat ne-sponse across the full frequency range? Repar entenas provide strong, cizar signals, even fin difficult reception ateas. Easily convenient rem 300-ohm to 73-ohm. CeleptasisfTM downland by shap-on transformer, floods 510-42.

Reception Boom Weight List

#### ALL-CHANNEL COAXIAL CABLE Model CAD

Next low-loss coassel cables comes raidy for lestallation, each is complete with F comectors and weithsroot installed. Date display-packed sizes \$20.55
\$20.55
\$28.35

Į	Hodel	Area	Length	(Lbs.)	Price	Net
1	Y1P-301	Local	32"	45	\$18.95	\$11.3
	VIP 382	Hetro- politan	56"	6	\$27.95	\$16.7
1	Y1P 303	Suburban	845"	8	\$37.25	\$22.3
ı	V1P-304	Suburban & Fringe	1095"	10	547.50	\$ 28.5
ı	VIP 305	Fringe	126"	14	\$\$7.95	\$34.7
ı	91P 306	Deep Fringe	150"	15	\$67.95	\$40.77
*	VtP-307	Deepest	196"	20	\$88.95	\$ 53.3

### ANTENNA

## MATCHING TRANSFORMER

ALL CHANNEL MODEL MUV-382 \$2.10

The MUV-382 is an all-channel universal snap on trainformet. Will, URF, Fill and All-Channel universal snap on trainformet. Will, URF, Fill and All-Channel universal can be changed from 300 chms. By 55 obns. for a coasial cash downlead. The snap on clap fits square and non-discoversames and the Petable metal strates all connect to any configuration of 380-all terminals. The clip limb transformer isolation at 380-all terminals. The clip limb transformer isolation of 380-all terminals. The clip limb transformer isolation of 380-all terminals. The clip limb transformer isolation of subprocedured with snapon mounting clip. F655 gennector, WB 61 weetherbeat and seeinging ring Trainformer focus not pass as:

#### TV/FM SOLID STATE INDOOR AMPLIFIED COUPLERS

ALL-CHANNEL 4-SET AMPLIFIER, MODEL TA-84





### Jerrold Outdoor Preamplifier Selection Chart

Desired Channels	Type of Reception Area	Possible Interference	Notas	Recommended Model	Gain	List	Net
-	3	08-Ohm Models for Areas Remove	d from Powerline and Ignition Interference				
VHF, UHF, FM	Deeper Frings	Nearby TV or FM station	Super version with higher gain, lower noise figure, 2-set output.	4213-5	V 15	\$52.95	\$35.26
VHF, UHF, FM	Deep Fringe	Local FM station	Equipped with 2-set output.	4253	y 11:5	\$43.95	\$ 29.27
VHF, UHF, FM	Deep Fringe	Local FM station	Equipped with 2-set output, has separate VHF and UHF inpuls.	4283-2	¥ 13:5	\$46.75	\$31.14
VHF, FM	Deeper Frings	Local FM station	Does not pass DHF, 2- set output, function performed by older Model APM-106L.	4214	V 13	\$32.95	\$21.9
VHF	Deeper Frings	Nearby VHF-TV or FM station	Super version also passes UHF, 2-set output, tunction performed by older Model SPM-106L	4203-5	V 15	\$47.75	\$31.08
UHF	Fringe	Local UHF station	Passes VHF and FM, 2-set output, function performed by older Model UPM-104L.	4003	U 11.5	\$39.75	\$ 26.47
	153 -	75-Ohm Moders for Areas Subjec	to Pawerline and Ignition Interference				

Signal Booster JERROLO SOLID-STATE PREAMPLIFIERS

Jerrold Powermate Plus, Powermale and De-Snower mod-els provide exceptional high gain and flow noise figures for smow-free felewissip and distortion-free Fill radio, Powermates insure "Color-Perfect" pictures at all fra-

Mounted at the antenna, these units tate full advantage at extremely weak signets by overcoming holes pickup and enlends downlead losses. Specific models smptify VHF, FM, UHF, and All-Dhannel signals—300-ohm, or Zo-him Colerative impediance—for home reception and master antenna system applications. There is a Jerrold presemblem model to meet the combination of acching praemptifier model to meet the combination of acching an acchingual.

VHF, UHF, FM	Deeper Fringe	Nearby TV or FM station	
VHF, FM	Deeper Fringe	Nearby VHF-TV or FM station	
UHF	Deeper Fringe	Nearby UHF station	

FOR VHF-TV, UHF-TV, FM
NEW VHF-TV, UHF-TV AND FM SIGNAL SPLITTER,

ALL-CHANNEL MATCHING TRANSFORMER! SPLITTER, MODEL FSX-1314

Efficient, Well-Balanced Unit for All Signal Areas

Jerrola Model FSX 131.4 is an allchannel (54 is 850 896) transformer.
Type spiriting network for rea-distant
mounting. It serves a dual function
mounting it serves a consideration
mounting it serves a consideration
mounting it serves a prise
mounting it serves a prise
mounting it serves a prise
mounting it serves
mounting serves
mounting serves
mounting it is to the TV set.
HPVUT, 75 others, all channel (54 to
1890 latty) DUTPUT, 300 ohms, indireduct VHT CST to 721 MHz and UTV
MFT TVFERM MATPUTS. \$2.10

VHF-TY/FM MATCHING TRANSFORMER, MODEL T-1000

Economical Transformer for General Use Model 8-1000 to a 75-ohm to

V 15

4207-\$

ALL-CHANNEL MATCHING TRANSFORMER, MODEL T-379 General Purpose MATV Transformer

1 12,5 \$50.25 \$33.47 \$47.75 \$31.80

U 12.5 \$56.75 \$ 37.80


Model 1.379 is as all-channel (YMF/UMF) matching transformer for 75-bm operation to a common for 1.50 to 1.50

MODEL T-378

General Purpose MATV Transformer \$1.59 Model F-378 is a VMF matching transformer Appearance and physical construction are similar to Model T-378. Unit features 60 Mz ac isolation Air F-59A connector is provided.

VHF-TV/FM MATCHING TRANSFORMER. MODEL T-373 Flush Mounting Unit \$3.30

Model T-373 is a VMF 300/75-ohm matching transformer. Unit has a flat response across the fraquency range of 54-216 MHz and provides acids resolution. Added for flush mounting 8-59 cable bushing its provided.



SPECIFICATIONS



	ALL-CHANNEL	WIF	
MODEL	TA-M	TANK	
FREQUENCY RANGE (MHz)	54-890	54-216	
NUMBER OF OUTPUTS	4	4	
IMPEDANCE (ohms)	300	300	
INPUT CAPABILITY (300-ohm, aV; 75-ohm, d8mV)	VHF: 16,000 (4 ch.) UHF: 15,000 (3 ch.)	16,000 (4 ch.)	
MINIMUM GAIN (dB) Internal	VHF. 15 UHF: 12.5	15	
6-eet:	VHF: 7.7 UHF: 4.5	7.75	

\$2.61 Jerrold Model 37-1203 is an at-channel termination network for connecting a 75-ohm coasial tap line to the TV receiver's 300-ohm input terminals. This unit is ideally suited to MATV applications for at-channel atore systems

ALL-CHANNEL LINE TERMINATING UNIT, MODEL ST-1203

Unit passes all channels (2 to 83) and provides ac power solution. Whether etached to the TV receiver at not, top line signal is unaffected.





ALL-CHANNEL MATCHING TRANSFORMER,

SIGNAL SPLITTERS

NEW WHF-TV, UHF-TV AND FM S MODEL FS-1314-FM S MODEL FS-1314-FM SIZE FS-1314-F

**MODEL T-2000** 





3441

3550

GIBRALTAR VHF-TV/FM AMPLIFIER. MODEL 3550 NET \$69.00

GIBRALTAR

### GIBRALTAR

#### **BROADBAND AMPLIFIERS**





FEATURES

Solid State Tunable FM Tree State Lightness Projection

**NET \$55.50** 

GISRALTAR VHF-TV/FM AMPLIFIER, MODEL 3661 **NET \$132.00** 

## FEATURES

Louistic FM Trap Solid State Boin Contral

lecred Model 3651 to a broadcord VMS-TV/FM amprimer for one distance distribution systems. Built to stacting standards. The 3661 hay a galler greater Stan 45 die wills output copolity more than 451 dien's gar channel for seat of sense classes. Housele FM tops, legitime, protes tim and gan ambried gam to 3651 great Nex-briefy bis operication. 75-dam important



GIBRALTAR
VHF-TV/FM AMPLIFIER, MODEL 3880 NET\$297.00

## VHF-TV/FM AMPLIFIER, MODEL 3441 FEATURES

FEATURES (1)

- o high Dulput.—1 Vall for Each of Seven Cago Hig
- o Stod Money of Transpires Against Solidate Depression to High Temporalisms

GIBRALTAR ALL-CHANNEL

AMPLIFIER, MODEL 4400

The Jernick Model JBBO is: g superingly gain and output VMFTWFRK, sphriband, solid state amplifier for sits till single-power VMFTWFRK distribution systems. Special resturns emblast separate VMFT on based and VMF dip Load linguist. I switch for combining the signifix, consists gain control for each Bond, ligarining protection at this late Baggill gains and sealed VMT tesp.



NEW

o free Channel 2 thru 83 Measured Spins o Fair Response = 1.25 60 to 900 MHz o Reghest Owlori Capacity of Any Ali Channel Anguller o Tonado FMI Fray - Books Lightong Principe o Spance (FMI ded MHI Stock Committed

NET \$177.00



Terroid solid state "Obtrafter" Blooks 3550 is a highgain, brondhand applicat for medium size distribution systems, Smiller to blooks 3441, and part parties 33 off immension gene strongly deep of light transference coupled mones feed-back transactor steps. Single manual gain control in provided flagment and business improvided Flagment and business improvided Flagment and business specified in 5 of the state of the st

The 3441 amplifier to a troublend device intended for use in up to medical size wide-TW/FM autriculfice systems. The compact 3441 province instead performance for its state. Fast response across to TV and TM bands insures accelerations and FM to the compact state of the performance of the performa





.

- op a name water, were goods, affects as Tuesdale FM Tree a Dieda Lightman

  - Toroccus
     Toroccus



GIBRALTAR ALL-CHANNEL AND FILE AND FILE

#### SPECIFICATIONS-GIBRALTAR SERIES

	att denamer						
-	9464	464	-	201		2001	
-	Marin. Cham	00-230 MO-MI	94-5(R. 570/096	\$0.00E, 210.7EB	94-250	90-818	
-	400 M MW 35		50	49	36	22	
par eliffer total reli-	-Haway	9/3	10	1.0	***	8-0	
ERRIE	器:线线	# :A1:	Add. Feb.	w85, F at.	-SE10	+42.7 st.	
-	Pi	75	N	H	Pé	75	
many respect sills	禁計	- The Control of the	•	,	10.00	•	
N 707 48	*	26, 2000	-	25, 2000	6.45	Mi, femalitie	
Pullban of Controls	27 112	ZX.	263	pla	112.6	26.75	
			ACVAT				

**NET \$30.97** 

#### COLORCASTER-PLUS SMALL SYSTEMS AMPLIFIERS

#### FEATURES:

- FIN Trap
   Diede Lightning Protection
   Said State
   All Channel Ampirication
   Ill Lightn

ASI.-CHANNEL MODEL TAC-81
Giptower Protected
The new Richards TaC-81 protects the ideal
shalten for small distribution systems to alvolushalten for small distribution systems to alvolushalten for small system semiples by dealer 
shalten success to the state of the shalten 
shalten shall system may be a shalten 
shalten special post of 
sixten grant part of the shalten Righer 
gard overface capability and semiprocapporarios.

The input and nutrait terminals of the implifier accept lerrold 75-she threaded. "I" time brings, neithful for CAC or an equivalent type of cable

ALL-CHANNEL MODEL TAC-84 NET \$33.27

permits all channel TAC 86 is similar to the TAC-81. The IAC-84 is equipped with an internal spiriter which provides floor 25-shim outputs. These new improved units feature bigine gain, isolation and modern appearance.

## | In-Stand | 54-395 | | In-Stand | 174-214

WHE MODEL TO-M NAME

A small system annihilar united themes the visit (in the hand) by unit in prosition with the court of the state of the sta

niteració (alle (alle) | l'eternol 100 CAPACIAL COLUMN CONTRACTA SOLI 

SPECIFICATIONS SMALL SYSTEMS AMPLIFIERS

#### **DE-SNOWER MODELS** PREAMPLIFIERS



## DE-SHOWER MODEL OSB-107 SYSTEM-NET \$68.10 VHF Broadband-75-Dhm "Colorazial"

#### UHF-TY BROADBAND NET \$85,00 MODEL DSU-105 75-OHM MINISTER BAR AND AND SOCIAL 222

Jerrold Model DSS-105 in a high-pain, con-miss. 75-shis tube-79 gap-multifor. The use of online stripline constructed transitions with few radial lead inductance aptimizes noise liquid uses the life band Named In-oragem and impelling deciliating costing, the presentable Its read-ial models benchmark for inducer insenting power supply leads (105 to also applied. The 75-shis liquid impelling on a high the soft is perfect to statch in the 3-275 antenne for system applications. Faur F-609 connectors swarfled

#### FM Band Rejection Filter, Model FMR-75 7.50

1.77

3,05



derrond Momes FMM-75 vs a band regiction filter which reduces FM input signer stronger by a minimizer of ME ME, FMM/75 in recommended in cases where heral FM stronger cases beneathed amplified minimizer of a virties in excellent leaversine size. VMF, DEF-TV channels in 1 ME, FM hand it alternated in ME, imposed in 75 downs, March for red TV channels in 23 dd income 1.2.72. User as mental 14 dB PSWM 1.5.12.

#### FM BAND REJECTION TRAP, MODEL FMR-300

Mudel: FRR-300 measures: FRR Lignais by 286 st. Reducing: FMR signar level prevents attorn FMR stations: From: causing beforegation and investigating of the TV set amplifier or amplified troubler: the FRR-300 can be mounted integers of quillions at the nationa. List Prior, 68.50



#### ANTENNA SWITCHES ATTENUATORS

#### 2-POSITION SWITCH, MODEL 823

Jerrald-Tuco Switch, Model R22, as a "pessible artism? 2-position sides switch unlich provides a serection Settlement for antennas feoding is ingite act, as a ingite antenna settlement for the processor of the

#### ANTENNA ATTENUATOR, MODEL 835

A Jernat-Tace position attanuates watch, adjustable to 0-15-30 dll attanuation settings Designed for Jecchious where signal overloading is a problem. Fackaged in Jack-Sul Dools, lab per carbon. List Price. \$5.05

#### 3-POSITION SWITCH, MODEL 873



#### MULTI-SET COUPLERS. PASSIVE

#### ALL-CHANNEL, 2-SET COUPLER, MODEL MF-82

Jackel M & Tealists unique Gaters punding circuity. Uncupelly logs fills ulticaser, 35 dB than at such solds own indeterm at 13 dB, make dl a truty significant orill recompet the & Cohomos require diskips. Delyand the color recombine. Display packed.



#### ALL-CHANNEL, 4-SET COUPLER, MODEL MF-84

For connecting there as four TV FM sets to a single intenna impedence 100 when Efficient transference design Positive match. Law loss—less then 9 dff. Includes at least 15 dft. Outplay packed. 3.45



#### FM PASS FILTER, MODEL TX-FM

retrute finite states for specific states for specific states and specific states and specific specific states and s



TYPICAL APPLICATION OF FILTER

#### CAC-6, CAC-11 COAXIAL CABLES NEW FOR PROFESSIONALS

w available from lerrold are two distinctly new 82 channel coasial cables with lower loss, greater mechanical strength and superior shield-ing to common "RG," "RG-Foam" or "foil-drain wire" types

CAC 6 and CAC-11 have been engineered and manufactured to the ex-c acting requirements of 82 channel color MATV systems, as shown in our specifications thank. Both cables achieve 80 dB shielding and retains this characteristic with hending and pulling, because of the aluminum braided shield covering the thick mylar-alumnum foil tape. This adds tional traided shield (instead of drain wires) provides mechanical protection to the fail and makes for easy connector installation in the field. Available in reels of 1000 ft. Specify CAC 6 1000 and CAC-11-1000. Also available in 500 ft.s CAC 6-500 8e/ft.

CAC 6-1000 7 1/2 eft CAC-11-1000 12e/ft

	CAC-8	CAG-11			
Impedance	23 stems	75 minus			
Rotors Lass Márichi	Better II	un 20 di 0 line			
Attenuation dil/1887 Ch. 2 64 Miles	16	0.96			
Ch. 19 (236 Mind	3.2	Z10			
Ch. 14 1470 MHs	4.5	2.3			
Ch 83 (890 NRs)	8.6	4.6			
Center Conductor LANG & Copper World:	18	14			
Distoctric O.B. (Callular Polyethylane)	0 T89.	0.205*			
First Shold Repub		2"			
Second Shield Benid	34 AME				
Jacket Q.D. Law Temperatury Polyment Chroman	0.296**	8.407*			
Cortified Super Compilance	Y	Yes			

#### FEATURES CAC-S AND CAC-11

## PROFESSIONAL ALL-CHANNEL ANTENNA INSTALLER'S FSM MODEL AIM-718 NET \$197.00 Jeroid's Model Alth/18 is the first Signar Strength Idear designed specifically for the professional activities intelligence and a portable, legitive-gird long 4 lips, 6 al.2 heatery operated, and housed to 6 regard case with large, tomerated accessory compariment.

SPECIFICATIONS-MODEL AIM-710



- . Separate VIII and UNF tamers
- · Auder collect jook, crystal sarphone
- a Top belitäs 30 dil attacastars
- Safety contrib horse all power whose cover in closed
- 80 of to 2,000 ub hasic scale.
  500 off to 20,000 off milk one attenuator highly.
  5,000 off to 200 000 off with two Estenuators in vor/new --- 20 to 4 db books train
  Vor/new --- 50 to 4-30 db with one attenuation "to"
  vor only 4 14 to 4-40 db with free attenuation to 20 alf of 75 plans 45 alf at 1000 plans W 200 1 0 mg miner | 9" h i d to " to o" o "For 75-ohis operation invoce are \$4 scale regions." Arbite overage signal layer.

Arter reads Greetly in object fand intersealth) to show exact internal requirements, and provides continuous coverage 54 to 215 Marc for VMF TV-FM 070 to 850 Mary for UNIV-TV, logat is 300 Mark of 75 others with secretal sides.

300 ohn receptacts. It must be sprong be-manyly provided for much lamb-lead parametries. Type 5 connectes for Pa-man our on matching fails.

## TV-FM RECEPTION AND DISTRIBUTION FOUIPMENT

homes, apartment houses, schools, TV dealer showrooms, motel hotels

## TAP-OFFS AND OUTLETS

"ULTRA TAP" TV OUTLETS

Jerrold "Ultra Tap" television signal tap-offs are the finest on the market for master antenna systems in hoteta, motets, schools, apartment houses, or other commercial and industrial buildings. Each model is a precision until designed to master the absence of discontinuities which might create standing waves and degrade the overall system performance Equipped with "Camma" receptacles, units accept Jerrold 75 and 300-ohm pushon piegs. Simple crimp on universal bushings and positive gripping clutch permits Tash solderless connections to the feeder. Units can be flush mounted in standard 2" x 4" for combinational bush and sold with Jerrold UTP I or UTPS cover places. Design is such that standard electrical outled cover plates can be used to meet the requirements of special decor A houring model UTSM, is available for surface mounting of outlets where required in existing construction Where two TV oulputs are required from a single outlet use Utira Splitter Model 15726.

ALL-CHANNEL WALL TERMINAL FOR VHF/UHF-TV AND FM, MODEL UT-12

Model UT-12 is an "Utilar Tap" all-phannel TV feed thru unit (dc to 890 MHz). It provides a flush-mounted terminal outfel for spittler or tap off units (such as Jerroid Models 1405, 1406, 1407) located elsewhere, input terminal as "T" type; output "G" type F-659 cable convector supplied The tap ferminal accepts G-59, PG-59 and G-56 push-on connectors Net \$2.10

ALL-CHANNEL WALL TERMINAL UNIT FOR SEPARATE TV AND FM. MODEL UT-13 Net 52.85

Similar to Model UT-12 except provides an additional FM outlet attenuated 10 dB below the TV signal level:

COVER PLATE, MODEL UT-PI Net .39

Single outlet cover plate of sturdy molded plastic, work color.

COVER PLATE, MODEL UT-PS Net .66

Single outlet cover plate of brushed stainless steel

MOUNTING BOX MODEL UT-SM Net .54

Single outlet surface-mounting housing for use with all Ultra Tap Units. Made of sturdy molded plastic, ivory Color.

ALL-CHANNEL MALE CABLE ADAPTER-300-OHM, MODEL G-300A

This 75/300 ohm adapter combines G-59 type push-on fitting with "mo-strip" type crown washer terminals. Provides quick connection or disconnection of 300-ohm binited to "0" type chassis fittings. Resistive network provides 300-ohm source match to TV receiver. Unit is direct replacement for G-300. Fits any UT outlet.

Jerrold Model 1596A is a hybrid atlichannel two-way network covering the passband of 20 to 890 MHz. Maanwan splitting loss is 3.5 de 41 VHF and 4.0 dB at UMF. Isolation between outputs is 18 dB minimum at 20 to 216 MHz. 12 dB minimum at 470 to 890 MHz. Patent peeding

Jerrold Model 1502A is a resisting all-channel splitter covering dc to 890 MHz. Maximum splitting loss is 6.5 dB. Isolation between outputs is 6.8 dB.

UHF/VHF SPLITTER, 2-WAY, MODEL 1563 Net \$4.17

New Jerrold 2-way hybrid splitter equipped with patented bushing lused on F-659 connectors) to convenient, last, germanent splitter installations. Use ET 659 to expand cable bushing to CAC (RG-6)

VMF SPLITTER, 2-WAY, Net \$3.45

New convenient-size, 2-way splitter for use in systems requiring a frequency range of 5-300 MHz Shipped both in multiples of 24, less connectors.

UHF/VHF SPLITTER, 2-WAY, MODEL 1502A Net \$5.97

**ALL-CHANNEL 75-OHM** 

Net 69

ALL CHANNEL TAP-OFF UNITS UT-42 \$2,85 FOR VHF/UHF-TV AND FM, Net \$3,45 MODELS UT-82, UT-83 UT-83

Ultra Tap Models UT-82 and UT-83 are all-channel (20-890 MHz) tap-o units available in a selection of four color-coded isolation values. Ex-clusive Isrrold universal bushings and positive-gripping clutch make fast solderless cable connections. Ultra Taps use Gamma ("G") fittings for reliable pushion TV set connections. Select G-59, PG-59, G-56 or G-300A connections depending on installation requirement Ultra Tap Model UT-83 provides 300 ohm terminals for simultaneous connections. of both a TV and FM receiver. Specifications for both models, including video insertion loss, are shown in the table.

The system installer obtains greater flexibility from Jerroid's new Ultra Taps, with a reduction in required invantery. The universal cable connection (based on the new patented F-659) will fit RG-59, RG-6, CAC or CAO'6 type cables. It is not necessary to state cable size when ordering new Ultra Taps. Shipped RG-59 size, the universal bushing its easily expanded (Espansion Tool, ETM-659) to fit CAC (RG-6) size cables. knother new feature of the Ultra Tap line is the availability of a blue value of isolation for more efficient high-rise system layouts

HOW TO DEDER Specify model number and isolation color desired. For example, Ultra Tap UT-82-Y.





Worls 9T-82

SPECIFICATIONS-ULTRA-TAPS, A-Isoletien Lots MODELS UT-82, UT-83

8-America Loss

FRERDENCY IND	STINU LINK AND COM VOICE		MEB	TELLOW	BLDE	
0-10	Q-10 MHz B	0.5	0.5	0.7	1.0	
55.25	2 8	34 0 0 25	26.5 0.5	22.0 0.7	18.0 0.75	
211.25	13 A	29.5 0.3	25.5 0.8	29.5	13.0 1.5	
471.25	14 A	29.5	24.D 1.0	87.0 1.25	11.00 1.75	
885.25	83 B	28.5	21 0	140	11.0	

ULTRA SPLITTER MODEL 1572G

Net \$5.55



This economical solitter plugs into rold Outlief ISTO-75F, UT-12, 13, a Jerrold Dutter to 18 to instantly 18, 22, 33, 82 or 83) to instantly device convert from a single outlet device to dual outlet. See Splitter section

#### LINE SPLITTERS Net \$5.55 Net \$10.77 UHF/VHF SPLITTER, 2-WAY, MODEL 1596A

UHF/VHF MULTI-TAPS MODELS 1405, 1406, 1407A Models 1405, 1406, 1407A Jerrold "Multi-Taps" are all-channel, surface modelted line-Tap networks designed for small distribution systems, particularly for 17 dealer, appliance store or department store TV showrpoms. Each unit will feed four receivers.

Models 1405 and 1406 are six terminal units (four isolated taps, input and output). Model 1407A is a five terminal tap for installation at the end of a feeder line, timpedance of all units is 75 obms.

Universel free firms 1405 and 1405 and any unived terminals on 1407A should be properly terminated (TR-75F or ST-1203).

Mounting hardware and F-659 connectors for installation are supplied with each

ISDLATION AND FEED-THRU LOSS CHART

A = tratetion & = feed-Thru Lass (values in dil)

ALL-CHARMEL MULTI-TAP, MODELS 1403, 1486, 1467A

NA.	MODEL MAMBER		1405	1406	1407
-	VHF DC-235 MHz	1	27.0 ± 1.0 0.0	20.0 ± 1.0 1.8	13.0 ±
597 \$10.50	UHF 470-890 MHz	A	24.0 ± 7.0	19.5 ± 2.5 2.2	13.0 ±
(Com.)	- Che	-	ALL-CHAN	NEL IN-LINI	E TAP.

UHF/VHF SPLITTER, 4-WAY, MODEL 15 rold hybrid splitter Model 1997 passes frequen-cies 20-890 MHz. Unique design is patent pending. Units are highly efficient splitters with loss less than 7.0 dB. Uses F connectors. Five 1-699 con-nectors and two wood screws shipped with unit.

OUTOOOR HOUSING, MODEL HB-1 Model H8-1 is an infolled metal housing used to protect "blister can" units such as splitters when used in outdoor installations. Mounts to antenna mast, messenger wife or wall. All necessary mounting hardwara is provided

Net \$5.70

ALL-CHANNEL IN-LINE TAP, MODELS F-1412, F-1416, F-1426, F-1430 Net \$3.30 Jerrold's "F" series of in-line taps are housed in compact diamnium die castings and are all channel (0.890 MHz) units for indoor or outdoor use. They are surface mounted, resistive taps awaitable in 4 values of materioris 12 dB, 15 dB, 26 dB and 36 dB, (3) F-559 connectors supplied. Recommended replacements for 1401—6, Y, R. 0-890 G.2 36 75

## VHF/UHF VARIABLE TAPS

Moduls VT-75U and VT-300U are resistive flat teps designed for use on high-level, all-channel feeder lines of MATV systems. The tap attenuation of each unit is adjustable through a potentiometer accessible from the front of the units when the cover plate is removed.

The tap units are designed for installation in standard electrical outlet boxes and are shipped with cover plates. Model VT-75U accepts a 75  $\Omega$  coaxial tap-off cable for which a cable plug is provided. Model VT-300U accepts 300  $\Omega$  twin lead as the tap-off cable.

SEPARATE WALL PLATE INCLUDED—parmits easy alignment of outlet in well box.
 ACCEPTS CAC, CADIG, RG-50/U OR RG-6/U FEEDER CABLES—

no changes or adopters necessary.

SAYES INSTALLATION TIME—test, easy to instalt.

Fits standard Wining Boxes—244" W x 442" H x 134" 0.

## SPECIFICATIONS OMNI-TAP

Frequency	Insertion Loss	Isolation Loss
VT-300U 54-216 MRz 470-890	0.75-0.50 dB 1.50-0.75 dB	12-23 dB 12-20 dB
VT-75U 54-216 MHz 470-890	0.75-0.50 dB 1.50-0.75 dB	12-25 dB 12-21 dB



8.6

VT-300U

NEW]

VT-75U

Net \$2,40

VHF MODEL 14250 Net \$3.30

ALL-CHANNEL SPLITTER/MIXER

Model 1425C is a VHF

Spiriter/Mixer which

can be used as an an-

tenna mixing network

## ANTENNA MIXING NETWORKS

#### ALL-CHANNEL MODEL 1460C

All-Channel Splitter / Mixer for combitting

VHF and UHF segnals Net 2.85 into a single Jownlead, or as a splitter for separating VHF and for separating or com-

UHF signals at the TV receiver input terminals, bining high-band and low-band VHF TV signals.

Designed for outdoor mast mounting. Circust Unit is designed for outdoor mast mounting is a highly efficient low-loss crossover network, and enclosed in a weatherproof housing, Input with separate \HF and UHF passband circuits and output impedance is 300 ohms for birth motalism, 300 obms

#### VHE HILLO SPLITTER/MIXER MODEL LHS-76 Net \$8,70

This unit is specially

This unit is specially designed to split or may VMF-TV high-band and low-band signals. This low-loss mixer comprises complementary low-pass and high-pass filters with a crossover fraqueacy at approximately 140 MMZ. VSWR is less than 1.3.1. Passband is do to 108 MMF for the low-band, and 174 to 216 MMz for the high-band, isolation between bands is greater than 30 dB. Impedance at all terminals is 75 ohms Model LNS-76 is housed in a sturdy bifster can 2-5/16" x 1-5/16". The unit is shipped with three F-59A solderless coaxial cable connectors.

MODELS AMN-HI, AMH-LO

Model FC0-320 is a frequency prosesover net-work designed for splitting the All-Channel range (dc to 890 MHz) into a VHF band (dc to 216 MHz) and a UHF band (470 to 890 MHz), or as a masse to combine the VHF and UHF frequency bands latto a single all-channel out-put. The crossover frequency is 320 MHz, Unit a designed for indoor meeming and uses F61A littings. Three F-559 coaxial cable connectors and mounting hardware are provided, Imped-ance—75 ohms. MODEL FC0-320

Net \$7.17

## 75-OHM ANTENNA MINING NETWORKS, 0-890 MHz, MDDEL FCO-47

MODEL FCO-320

Both units are held tunable, designed for indoor mounting at the system head-end, and shipped with the necessary hardware and connectors.

amm nt Net

\$26.25

Model AMPINI is a VHY fom-loss mining network for for separating the O to 47 MHz frequency combining into a simple output up to 4 non-adjacent range from the 54 to 850 MHz frequency lings have television channels 0. through 13), received range Can also be used as a mixing net-from simple channel anetenas or amplifiers. May also be used in fewerse as e channel spitter, impedance 15 to combine "bestered it is necessary be used in fewerse as exhaunced spitter, impedance to 50 nbms insertion Loss is 2.0 60 maximum statement of the combine "bestered with VHY-FUMF signals." Insertion loss is 1.0 88 and isolal adjacent low band channels 22 through 61. Impedance it in between outputs is 30 dB and isolal signals. Insertion loss is 1.0 88 and isolal signals. The service of the combine of the combine



Net \$36.75

### DIRECTIONAL COUPLERS Net \$9,22

WHF-TV DIRECTIONAL COUPLERS, MODELS DC-8, DC-12, DC-16
Models DC-8, DC-12, and DC-16 are back-matched directional coupler type top units featuring high isolation between the tag terminal and the output terminal, a low insertion loss between the input and output, and excellent match on the input, output and lap terminals.

ALL-CHANNEL DIRECTIONAL COUPLER, MODEL DC-12UV

Jerroid's NEW DC.12UV is a matched directional coupling network for tapping VR/PUHF-IV and FM. Isolation is a manamum of 12 dB. Impedance —75 ohms Unit is designed for indoor mounting and housed in a blighter can Fittings are F-518. Supplied with three F-659 cable connectors and mounting hardware.

## GROUNDING BLOCK.

MOOEL GB Jerrold Model LGB is a grounding block assembly for positive grounding of tead-in cable shield. The LGB can be mounted in any position on a flat surface, indoors, or outdoors; two wood screws are supplied for this purpose F61A connectors.

The ground connection is made with a heavy gauge copper wins connected to a grounding rod or to a nearby cold water pipe





## COAXIAL CONNECTORS.

Jerrold solderless connectors are designed for permanent installation to all types of RG-59, RG-6, RG-11 and "CAC" coaxial cables with simple crimping tools. The connectors shown are carefully machined of brass and all exposed surfaces are heavily plated.



Universal Connector



NEW G-SERIES PUSH-ON CONNECTORS

S1.04

F-59 Male Cable Connector For use with RG-59/U type cable. Mates with F-61A, F-81B, A-61. 75-ohm use. Use Crimping Tool PL-602 or PL-659. Separate ferrule supplied.

Similar to type F-59 except unit has a built-on ferrule.

ADAPTERS. FITTINGS.

HEW

\$4.11

\$2.70

BNC-F Adapter

PL-F61 Adapter

GF-81 Adapter

**FERRULES** 

1051

BAG OF 5 FOR

New universal connector for a variety of cables. Each F-659 is equipped with a unique split bushing, which fits cable dielectric sizes from RG-59 through CAC. Connectors are shipped RG-59 vize. To fit larger cable size. To fit larger cable spread the bushing with expansion tool ET-659 or ETM-659. Ferrules and ET-659 tool supplied with each bag of 25 connectors

BAG OF 5 OR 25

NEW

.37 EACH

Patent Pending

NEW

NEW ET-659 EXPANSION TOOL Plastic tool for expanding F-659 connector to CAC/RG-6 size.

BAG OF 5 FOR .21

F ANO C-SERIES COUPLINGS


HEN F-818 Female Coupling .66 EACH

Universal center clutch will adapt to all sizes of cable, RG-59 through RG-11. Accepts F-56, F-56A. F-59, F-59A or FHC-404



F-71 Male Coupling Adapter \$1.14 Mates with F-61A, F-81B, or

C-81A Female Coupling



COLORAXIAL CABLE

6-FOOT LENGTHS WITH FITTINGS

WEATHER BOOT

WB-56 weather boot for CAC and RG-59/U cable connec

MODEL CAC-6GF



Jerrold's Model CAC-6GF is a 6-foot length of exclusive double-shielded CAC-6 cable with factory-installed connectors. It is used to connect a TV set via a matching transformer to a TV distribution system outlet. A "6" connector is installed on one end and an "F" connector on the other. The "6" connector mates with any Jeroid Ultra Tap and the "F" connector connects to the television matching transformer. Display packed

FOR RG-59/U CABLE

PG-59 Male Cable Connector

This improved push-on connector is designed for installations where repeated connections and disconnections are required. Mates with any Jarrold "6" chassis fittings. Silver plated brass center pin. .37¢

6-59 Male Cable Connector

Used with Jerrold "G" type chassis fittings, this fitting provides firm, reliable connections or rapid disconnections. Features built-on ferrule.

FOR CAC AND RG-6/U CABLE 6-56 Male Cable Connector

Similar to Model G-59 except has separate ferrule and is designed for use with Jerrold "CAC" type coaxial all-channel 60¢

6-61 Female Chassis Fitting

Accepts PG-59, G-59 and G-56 push-on type male cable connectors.

AND C-SERIES CHASSIS FITTINGS AND ADAPTER

F-61A Female Chassis Fitting Accepts F-59, F-59A. F-56, F-56A. F-659, FHC-404, TR-72F, AF-101 and AF-201. Mounts in 1/4" diam-eter chassis hole. Uses clutch type collet. 75-

Accepts C-52 or A-61. Mounts in 5/16" diameter chassis hole.

A-61 Adapter Fitting

Adapts older type C-61 fe-male fitting to F-59 or F-56 male connectors.

NEW GF-90

Push-on, Right-Angle Adapter This new adapter mates with any "F" Cable connector and G-61 Chassis fitting. \$1.50

NEW

.45

.08

# 16

TERMINATIONS

1

For RG-11 cable at 75 ohms, mates with F-81B, F-61A, and A-61. Use Crimping Tool PL-602.

FHC-404 Cable Connector

For CAC-11 or RG-11 foam coaxial cable, mates with F-61A, F-81B. Ferrule supplied.

PF-59 Male Coupling Adapter Adapts F-59 or F-59A for

push-on use.

\$1.70 C-52 Male Cable Connector Mates with C-61. For RG-59/U type cable used for 75-ohm applications. Use Crimping Tool PL-602 or PL-659. FOR CAC, CAC-6 AND RG-6/U CABLE

F-56 Male Cable Connector For RG-6 cables at 75 ohms. Mates with F-61A, A-61, F-101, F-81B and AF-201. Separate ferrule supplied.

F-56A Male Cable Connector Similar to type F-56 except unit has a built-on ferrule. Built-on CAC size ferrule.

FOR CAC-11 AND RG-11/U CABLE AF-101 Adapta-Fit Male Connector \$1.50

\$1.26

F AND C-SERIES CABLE CONNECTORS

FOR RESOUR CARLE

..37

\$1.80

· @.

= .37

.37

علك

HAND TOOLS

TOOLS

... {th "G"

2.16

.21

ADAPTERS

PL-F61 adapter is for interface between connectors and UHF (SO-238) annectors

FOR USE WITH JERROLD SOLDERLESS CONNECTORS

1026 Ferrule-For use with RG-6/U cables.

1051 Ferrule-For use with RG-59/U cables.

1095 Ferrule—For use with RG-11/U cables.

BAGS OF 100

1026 BAG OF 100 ... 2,16

1082 BAG OF 100... 4.35

1095 BAG OF 100 ... 4.35

BAG OF 100 ...

1082 Ferrule-For use with Jerrold CAC Cable.

for splicing together one can-

fitting to cable with "F" fitting.

HEW ET-659 Expansion Tool Plastic tool for expanding F-659 connector to CAC/RG-6 size.

BAG OF 5 FOR

WEN ETM-658 Expansion Tool Metal tool for expanding F-659 connector to CAC/RG-6 size 12.78

Crimping Tool PL-602

Crimps Ferrules 1026, 1051 and 1095. Used for connectors to RG-6/U, RG-59/U and RG-11/U.

\$8.10

Crimping Tool PL-659 Crimps Ferrules 1051 and 1082 for connectors to RG-59/U and CAC type coaxial cables.

\$3.59

.90

Model TR-75F — This precision 75-ohm termination for F-61A or F-81 connectors should be used for VHF, UHF, and all-channel systems. TERMINATING RESISTOR, MODEL TR-72

ALL-CHANNEL TERMINATING RESISTORS.

Model TR-72 is a close-tolerance 75-ohm resistor for line or equip-ment termination. Mates with C-61 or C-81 connectors. Return loss is a minimum of 26.0 dB.

MODEL TR-75F



.90

TERMINATING RESISTOR. MODEL TR-75G \$ .90

75-ohm terminating resistor for "G" type chassis fittings. Return loss is a minimum of 26.0 d8.



## MODEL TR-728

Model TR-728 is an All-Channel inexpensive 75-ohm terminator for use with B-59 type bush-logs. Terminates Ultra Tap outlets models UT-82, UT-83, Variable Taps VT-75 or VT-300. Re-turn loss is a minimum of 26.0 dB.



## **ATTENUATORS**

ALL VALUES \$4.05 EACH

FIXED ATTENUATORS. PDA-SERIES

Models PDA-1, PDA-3, PDA-6, PDA-10, PDA-20 are fixed attenuator pads for 75-ohm circuits and use a resistive tee-network. They are ideal for in-line use. All models are for all-channel (dc.890 MHz) applications. Fittings are type F-61A, and are equipped with universal center clutch which adapts to RG-59 through CAC-11 cable sizes. Aftenuators can be cascaded using Jerrold F-71 male coupling connectors. Return Loss 2.10 dB. VSWR: 1.2-1. Impedance: 75 ohms. Overall Length: 2½7\_Replaces PDL's.

#### SPECIFICATIONS-PDL-SERIES ATTENUATORS

POL-20

VHF (dc to 216)

ATTENUATION (dB) 1.0+0.2 3.0±0.3 6.0±0.3 10.0±0.5 20.0±1.0 PASSBAND (MHz) All-Channel (dc to 890)

VARIABLE ATTENUATOR, MODEL A-18

The A-18 attenuator is a new all channel device equipped with slide switches to provide 0, 6, 12 or 13 dB of attenuation. Input and output impedance is 75 ohms. Match at VHF is 24 dB (VSWR 1.135:1); UHF is 16 dB (VSWR 1.38:1).



Cable Drills CO-11, -12

Cuts hole through jacket and shield of coaxial cable for installing Jerrold pressure taps. CD-11 is for "A" series blocks and CD-12 is for "B" series blocks

Model CD-11 5 3, 55 Model CD-12 5 5.00

CT-2, -4 Cutting Tips CT-2 is replacement tip for CD-11 Cable Drill. CT-4 is replacement tip for CD-12 Cable Drill.

Model CT-2 5 1.40 Model CT-4 5 1.65



ANTENNA ATTENUATOR, 300-OHM MODEL 835

A Jerrold-Taco three-position attenuator switch, adjustable to 0-15-30 dB attenuation settings. Designed for localtions where signal overload-ing is a problem. Packaged in individual boxes,





Americals highest gain VHF FM entennal. The wedge design of the SC 2000 is a completely new concept in VHF-FM. TV antennas. The SC-2000 is designed to give you perfect often and black and white reception on deep tringe area signals that most antennas can't deliver—more gain on Channels 2 thru 13 and FM than any VHF-FM antenna. Vertical beam phasing lilatiens and clongates the vertical beam and eliminates spurious fobes rejecting interferences such as airplain flutter and auto (graftion. VHF capture area is doubtled, ower gain is doubtled over that of a single bay and ghost signals are picterively rejected, as no signals are picter up above or below the antenna. The SC-2000 is much shorter and more mechanically stable than other stacked configurations would be to obtain comparable gain.

Not mailable Ship wt. 24 lbs. The SC-2000 features a built-in, weatherproof cartridge housing as an integral part of each antenna. A complete line of preamplifiers, single channel traps, 8 color spectrum filter and a 75 dom terminal board are available to fit into the cartridge housing of the antenna, Sharp directivity and super high pain are provided by patented. Electro-Lens director system and impedence correlators. Emiliarse FM control elements not only provide high gain on the FM band but also permits you to attenuate FM in areas where strong signals interfere with I'V signats. The SC-2000 has elements of gold anodered tigh tensile aluminum with reinforced locking clips connected to an elispsoidal boom by wrap-around insulators, making first antenna one of the strongest ever constructed.

54 Elements Boom length 108 in. Not mailable Ship wt. 24 lbs.

NOT motifable Ship wf. 24 lbs. America's highest gain 82 channel arrannal. The wedge design of the SC 1000 is a completely new concept in ultral high gain 17 antennas. Designed for deep fringe viff-UHF-IM reception.— More gain on Channals 2 thru 13 than any Viff-oilly antenna — as much gain on UMF as a well designed 8 parabolic antenna! — more gain on FM than cut to channel, 8 element FM yegif Vet. In spite of its unequated performance. Winegard a SC 1000 Super Coloriton is surprisingly compact with low wind resistance due to its unique wedge design. This antenna is in a performance league by itself.

The SC 1000 features a weather proof carfridge nousing as an integral part of each antenna. A complete, line of prampfillers: single channel traps: a color spactrum filter and a 75 ohm ferminal board are available to this carfridge housing of antenna. Sharp directively and high gam are provided by patented. Electro-Lens direction system and impedance confetators. The SC 1000 has elements of gold anodized high tensile aluminum connected the illustration from the connected the illustration. connected to ellipsoidal boom by wrap-around in sulators, making this anienna one of the strongest evi constructed.

## T.V. PRE AMPLIFIERS FOR WINEGARD

ADD ANTENNA AMPLIFIER PRICE TO ANTENNA PRICE

Example:

Model CW 1000 with 823 B pre amplifier price

\$94.00

Use With Any of the ANTENNAS Directly above

B Winegard ALL CHANNEL UHF-VHF-FM HIGH POWERED ANTENNA MODEL AMPLIFIER (A) AC 823 B \$29°5

FOR USE WITH

ANTENNA AMPLIFIERS (PREAMPLIFIERS)
Salid Stote off translater pre-emplifier for use with any Colortron ANTENNAS
Salid Stote off translater pre-emplifier for use with any Colortron
Very timple to use, a Medule plags in (A) which is part of the entenna. (B) is pluced by the T.V. set. If you have a navy T.V. platter with your present T.V. antenna or in any area signal os little os 200 micro-volts. This amplifier with o Super Colortion will give a good T.V. picture, color or black and white. Add \$
to any Colortion entenna, SC-79 thru 110 Vols AC operated all silicon trans.

Winegords exclusive solid state plug-in pre-amplifiers fit in the antenna mounted cartridge holder. If you are in a low signal area just pick the one you need from the models listed below. Select the pre-amplifier cart, for the type of down lead you want to use.

Pre-amp model AC-895B for 75 ohm coox lead amplifies UHF VHF FM list \$47.20 net \$32.95

Pre-amp model AC-423B for 300 ohm down lead amplifies UHF passes VHF FM List \$37.40 \$24.95

Pre-amp model AC-495B for 75 ohm coax lead omplifies UHF passes VHF FM list \$37.40 \$24.95

Pre-amp model AC-223B for 300 ohm down lead amplifies VHF FM List \$36.70 Net \$24.95

Pre-amp model AC-295B for 75 ohm coax lead amplifies VHF FM List \$36.70 Net \$24.95

ill models furnished with 110 volt AC power supply. DC to power is Pre-amp is fed up to the antenna to the pre-amp thru down lead.

AC-HIB, (Fig. A) Housing to mount to other makes of antennas to contain printed board amplifiers AC-423B, 295B etc....\$2.95

Please order this item if the antenna you have is not a Winegard that i equipped with the AC-HIB, Net \$2.95

## RED HOT 24 DB GAIN T.V. PRE AMPS

#### SUPER COLORTRON HIGH GAIN, LOW NOISE

Specially designed preamplifiers for moderate to deep fringe area reception — High gain and low noise figure insures perfect snow-free color reception. The performance of each solid state amplifier is certified by the Winegard Company to meet gain, noise figure, and response specifications.

These preamplifiers feature a two section high pass filter and switch selectable FM trap to eliminate interference caused by transmissions below the VHF TV band and limit strong local FM stations. A unique lightning protection circuit effectively shunts to ground lightning surges which would cause amplifier fallure, Ideal for MATV installations — fits all Super Colortron cartridge housings or ACH-1B universal cartridge housing.

Four models to choose from --- 75 ohm only, connector suitable for RG-11/U downlead. Three F-59 connectors and power supply

	\$34.97	\$34.97	\$34.97	\$41.97	
MODEL No.	AC-926	AC-973	AC-913	AC-982	
Gain VHF UHF	24db NA	24db NA	24db -1.8db	24d5 9.3db	
Bandpass VHF	50 to 108MHz	160 to 250MHz	52 40 235MH2	52 to 235MHz 425 to	



1000MHz 1000MHz VHF FM BOOSTER COUPLER

ALBIZOB TOT SET \$15.95 Winegard OR 709 O FACH OF 2 SETS

82 channel UHF VHF FM

BC-830 Net \$15.95

SOLID-STATE "RED-HEAD 82"

Winegard 75 OHM COAX LIST-\$32.50 \$ 21 50

RD 870 RD 870 75 OHM PANT. COAX DOWNLEAD

300 RD 830 300 OHM RD 830 0

Winegard's Red-Head 82. Solid State VHF-UHF-FM Pre-amplifiers are designed to amplify signals from any VHF-UHF-FM antenna, VHF-FM or coupled VHF-FM and UHF antenna. Mounts easily on any antenna or mast. 100,000 microyotts input. High gain, low noise, excellent temperature stability. Includes 117VAC. 60CPS power supply. 70

82 Charinel. Solid State Antenna Pre-Ampliffer with 75 ohm output for renning coax download to TV set. 300 ohm input through no-strip Malco terminals. One F-59 output connector supplied.

RD 830

Same as apour, but with 300 ohm input and autput connections, no-strip Malco type

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108





\$12.98

VHF-TV BROADBAND ANTENNAS

300-OHM

SPECIFICATIONS-YAGI ANTENNAS

INDOOR ANTENNA, 300-OHM ... engineered for color TV MODEL JIN-5

LIST \$14.95

NET \$8.97

NET

#### V & FM Electronics TV & FM Antennas from Best for B/W or COLOR ANTENNA CORPORATION & the best antenna value available for deep fringe areas. For black and white or color UHF-VHF reception and for FM. ANTENNA CORPORATION & AC.RO2 10 UHF Elements Antenna Pre-Amp **8 VHF Elements** Lightning protection diode 5-Way Mounting Hardware AC isolated power supply 96" Boom Length 72" Turn Radius Mod. AC 802 \$16.00 eliminates shock hazard. No Strip Malco terminals E-Z Mount Boom Brace Model AC. 806 AA 33 VHF AA 83 UHF/VHF AA 87 75 Ohm Net \$20.95 SUPER-POWEH 82 Channel (UHF-VHF-FM) SUPER-STRENGTH Genuine Band Separator 144" Boom Length 35 Active Elements Snap out elements Mod. AC 806 Net St bright gold finish Net \$15.85 82 Channel Booster Coupler Lightning protection diode No Strip Malco terminals TRAVEL-TRON FM Attenuation UHF-VHF-F BA 83 300 OHM Net \$13.50 BA 87 75 OHM Net \$13.50 Campers-Boats KC Mobile Homes 8 FM Elements seconds for travel 94" Boom Length 15' 75 OHM Coax Booster Coupler 4 — Outputs 10 OB to each output FM Attenuation 200,000 My Input Band Separator Mod. AC 700K Net \$19.95 54" Turn Radius Permanent Gold Finish AC106 Net \$14.95 Latest overlay transistor No Strip Malco terminals "GANGBUSTER" Complete Kit HSV 43 UHF Net \$20.95 HSV 47 75 OHM Net \$23.95 UHE-VHE-EM Complete Kit Universal Mount 11 Active elements 82 Channel Booster Coupler OMNI Directional Lightning protection dioge No Strip Malco terminals Band Separator Model AC 711K FM antenna METRO-TRON AC 103 FM Attenuation Net \$10.20 Net \$ \$6.60 Commercial quality steel cabinet 8 OB to each Output 100,000 My Input HS 483 UHF/VHF Net \$26.95 HS 487 75 OHM Net \$28.70 UHF-VHF-FM 4-Bay Bowtie Model AC 320 Mounts anywhere Complete Kit HOT BOX Signal Multiplier Net \$4.80 Stacks 2 Identical antennes for double Band Separator Shiefded Color Cable Mod. AC 700UK 300 OHM Mod. AC 700UKC (Coax) Net \$9.60 Net \$12.50 power gain. Stacks 2 antennas în Oifferent 12-position Fine Tuning directions to eliminate rotor. Run 2 Sets from 1 antenna. Band Separator | Filter 12-position Fine Tuning Channels 2-83 VHF-UHF Signal Filter PX 86 UHF/VHF Net \$2.40 7-Section Chrome VHF-UHF Isolation Network Switch Dipoles The Model SX-38 band separator Channels 2-83 12-Position Switch Channels 2-83 Two, 3 Sectional Di-Poles Die cast chrome Low Loss (.5) No Splitter Loss. No Strip Malco Terminals. Tip Proof Base Topola Proof, Wide Spread Base | Watnut Grain Top Panel Mod. AC 200 Net \$7.80 Mod. AC 300 10.6db gain to each of 4 — 300 ohm outputs BC-210 Home TV UHF - VHF Band Separator SX 38 Mod. AC 40 Net \$3.60 Home TV and FM The Model SX-78 band separator Mod AC 20 ANTENNA UHF - VHF Band Separator UHF-VHF ANTENNA DISTRIBUTION SYSTEM SX 78 SEPARATOR 4 SH BOOSTER-COUPLES NUMBE Built in matching transformer to change 100 Fra-Cannects One Lead-in to Both from 75 ohm to 300. Inputs on TV Sei 4 Standard Flush Wall Plate Antonna Outlets with Pluas. STOCK NO 82 Channel Distribution Amplifier 835 22DB Gain MCGEE Lightning protection diode Max, Output 500,000 My Max, Input 40,000 My FM Attenuation 99 STOCK SPECIAL \$ 2450 10 for \$9.00 stack H 5210-4X MS 187 UHEAVHE Net \$43.50 8 Easily connects one lead-in wire to both UHF & VHF terminals on back of TV set. Use with black & white or color TV. No signal loss. VHF - FM Distribution Amplifier PAGE BC-210 Ch. 2-13 VHF BOOSTER-COUPLER WINEGARD DRIVES Lightning protection diode Max. output 1,000,000 Mv. Max. Input 40,000 Mv. TV/FM SPLICER for SHIELDED 300 ohm TV/FM ANTENNA LEAD MENTION MODEL 894 PRICE 49¢ ing, yer beauty more destore sertions, Size 2-7 mm de 4-7 mm de 2-1 mm de 2-2 mm de 2-MSV 17 VHF

82 CH. SOLID-STATE

BOOSTER-COUPLER

BOOSTER-COUPLER
WHE AND UHF
BC-382
WINEGARD
MOME
4-5db gain to each of four outputs, Amerilians
300 ohm imput, 4-307 ohm output
BC-382 BOOSTER \$ 3 265
Animal Triangle States with the country of the show the show the country of the show the country of the show the country of the show the show the country of the show the country of the show t

Coupler - Solitte

Net \$1.93

Net \$3.19

Net \$53.90

Indoor-Outdoor Mounting hardware. Low Loss - High Isolation.

PX 82 2 Set Net \$2 10
PX 84 4 Set Net \$3.58
SC 27 2 Set Coax Net \$5.98
SC 47 4 Set Coax Net \$11.10

PLEASE

MALE COAX CONNECTOR For 72 Ohn
WITH SOCKET

Precision made of allverplated brars, for 72 ohm Table. Chassis mount socket has low loss insul-tion. CS10 with hdw. a instructions.....99c each

10 for \$5.00

Solderless Connection



NEW 8290 SHIELDED 300 OHM TV LEAD New 1966 shielded 300 ohm lead, nest for UHF-VHF COLOR. Eliminates line interference, Ldw Loss per 100 ft., Tape to Mast, run thru gutters, conduits or underground. Antenna end terminals attached.

8290-C 50' \$595 8290-C 100'\$1015 8290-C75' \$805 8290-\$500' \$4790



### BELDEN 300 OHM TWIN LEAD WITH TERMINAL CONNECTORS

A Type 8225, For TV and FM antennas. 7X28 stranded copper conductors. Fist polyethylene jacket. 58 emil web thickness. For outdoor use. Wt. per 100 ft., 1½ lbs. Has connecting terminals on each end.

8225-50,	50' 0	Coil;;	34
8225-100,	100'	Coll.,,\$2.	14

B Type 8230, Weldohm design for increased strength and conductivity. 7K28 stranded, copper-coated steel wire. Almost twice as strong as plain copper. Perfect for long leading. 70-mil web. 2 lbs. per 100 feet. Has connecting terminals on each end.

8230-50,	50. Coll\$1.43	
8230-100.	100' Coil	

ALL-CHANNEL MATCHING TRANSFORMER. MOOEL T-2000 82-channel

Best Balance for Local Pickup Rejection

This new Jerrold T-2000
Matching Transformer is a significant advancement in the field of MATV transformers. High braid rejection, good balance, low Insertion loss and excellent match growide greater direct gickup reject



match provide greater direct pickup rejection while maintaining the signal match between cable and TV.

### OPEN TV LINE AND STANDOFFS

4-4-4 No. 2500 Copperwater- 400 Ohm OPEN WIRE TRANSMISSION LINE 100'..\$3,49 250'-\$7.95 No. 2502 d-. 300 Ohm SAXTON 100..\$3.49 250'-\$7.95 COWEST LOSS OF ALL LINES—or distactive—or typess spacers — hilly

OPEN WIRE STANDOFFS No. 6000-5" Nail 14¢ Each

No. 6003- 5" Serew

No. 6005- 5" Pote Type W/glamp. 19# Each.

Specially useigned for open wire Takes up slack, Used for either 190 or 450 ohms. Use to make a simple efficient matching slub.

## UNGAR 6760 SOLDER GUN

net \$10.95 with 3 tips.

HI-LO SWITCH IN HANDLE FOR 500 OR 900 DEG. F. 510.95 INC. 8753 6754 6755 TIPS.

6755 Long Chisel Tip 6753 Short Chisel Tip

6753 Short Chisel 6754 Pyramid Tip

F-RG59U FOAM FILLED CO - AXIAL CABLE

F.RG391, Foom Filled Co-oriel Coble. Attenuetten reduced 23% because distorted is made at foom rathen told applyphilons, Outside Distortion; 242, Codestors 22 study, Impedance 75, V.P.St. 75, Mer/M 16.6, Attenuetted 847 O

50 FT. \$ 225 4he per Ft.

1000 FT. 3995



## F-RGIIU FOAM FILLED

= 500 FT. \$54.00

II g per Fr.

Feem Filled Cu-rulel Cable. Attenuation is reduced 25% because dislocatic is foom rather than solid polyathylane, Outside dismension. 465. Conductors 7/20, lapedoness. V.P., Nr. 73. Mm/Fhz. 23.8. Ayramation dis/100 fts. 1,50% 100 ms.

## C Type 8275, UHF-VHF type. High quality, tow-loss lead-in for all TV and FM installations. Ideal for color TV. Cellular polyeth-ylene core is filled with inert gas. Polyeth-ylene jacket. 7X28 copper-coated steel conductors. 3½ ibs. per 100 foot coil. Has connecting terminals on each end. 8275-50, 50' Coil.....\$2.85 8275-100, 100' Coll. ......\$4.86

D Type 8285, Low-loss 300-ohm UHF-VHF. Recommended for color TV. Provides unchanging electrical and physical characteristics, Durable, for any application. 22-gauge, 7X30 copper-weld conductors. Polyethylene insulation and webbing. Cellular polyethylene jacket. Outside dia. ¼X15/32° Shpg. Weight 3½ ibs. per 100 ft, Has connecting terminals on each end, Ready to attach. \$285-50. 50° Coil. \$3.08

8285-50,	50' C	oil\$3.	0
8285-100,	100'	Coll\$5.	1



#### **BEST PERFORMING** UHF CONVERTERS



### SOLID-STATE TWO TRANSISTOR DELUXE UHF CONVERTER HAS BUILT-IN AMPLIFIER!

Updates any VHF TV Set to receive any of the 83 UHF/VHF Channels. Low noise, driftfree operation. Simple hook-up. Charcoal Gray Hi-Impact Plastic Housing has Silver-matte finish front panel. Features accurately call-brated UHF dial, UHF/VHF antenna switch, advanced pilot light indicator, and tuning control. Model (UF-300 \$16.95

UF-880 AG\$ Super converter, \$22,95

Similar to UF-300 except more power. Added amplification stage for better picture with less snow, net. \$22,95

#### Ungar Extractors



INSTANT SPRING LOADED PUSH BUTTON REMOVAL OF TRANSISTORS ETC FROM PRINTED BOARDS.

C TRANSISTORS NET \$2.00 . \$1.76 EA. IN LOTS OF 10

NO. 6982 I.C. EXTRACTOR FOR REMOVAL OF DUAL IN LINE I.C. NET \$2.00 EA 51.75 EA, IN 10

## Ungar 6939 Desoldering Kit \$14.70

CONTAINS PRINCESS HANDLE WITH 18 WATT HEAT UNIT AND 6945 6947 6948 TIPS MADE TO USE WITH UNGAR EXTRACTORS LISTED ABOVE.

## 8228 REIDEN DUOFOU

GZZU BELDEN BOOTOIE	
100% SHIELDED 82 CHANNEL	last.
75 OHM COAXIAL CABLE	
8228-100 100 Ft	. \$6.75
8228-500 500 Ft	. \$22.00
8228-1000 1000 Ft	\$43.95
0220 1000 1000 11111111111111111	

## COAXIAL CABLE

"CAC" COAXIAL CABLE. CAC-500, CAC-1000 -



Jerrold "Coloraxial" all-channel "CAC" cable is manufactured and sweep-tested for distribution systems carrying both UHF and VHF. 75-ohm Impedance. Supplied in spools 500-foot length-CAC-500; and 1000-foot length-CAC-1000.

### COAXIAL CABLE LOSS (PER 100 FEET

VHF CHANNELS (loss-dB)				UHF	CH. (los	s—dB		
4	6	FM	7	10	13	14	47	83
1.96	2.2	2.45	3.3	3.5	3.6	5.7	6.9	8.2

CAC 500 ft. weight 30 lbs net. \$39.15 CAC 1000 ft, weight 46 lbs. net \$77.40

Close out Electro Voice Patio Speaker \$28.00 Value

McGee Special





Now, enjoy music in every room or your home even outdoors—with the American ROAMER accretion in the American ROAMER High fidelity response portion in the fidelity response in the portable, conside. If or component high a thefus is. Or you may permanently mount
if where you wish, indoors or oul!

Superb high fidelity sound le assured by the high-efficiency of component-quality ROAMER peaker. And the handsome, acoustically correct pease; And housing protects this performance desc and weather and hardknocks. RO AMER beauty its scuff-groat, with color locked in for life

Back yerd, patro, recreation room, gool, of picnic—wherever you want to add the fu usic—plug in a ROAMER

at 30 watts gudio peox. B ohms impedence. For putdoor or indoor Bie. 16% high 17 wide and 6

front to back. Attractive grey color. Ship wt. 10 lb Many sold by others tor over \$28.00

BELDEN 1000 FT. 8225 SPOOL

18 🤒

7x 2s Stranded Copper.

FULL GAUGE - FULL WIDTH . Polyethylene Jacket McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108


BEST TV LEAD

VALUE IN

AMERICA

UNCONDITIONALLY GUARANTEED

## Belden Electronic Wire and Cable



Made with 80C vinyl plastic compounds for high delectric strength and best physical properties; small size, free stripping and tear resistant. Conductors are paired with a short-lay twist for conductor balance to assure a quiet circuit, free from crosstalk. Vinyl insulated, 122 tinned copper conductors cabled in pairs, chrome vinyl jacket. Suggested voltace, 200 v. working.

Belden	No. of	Strand-	Nem.	I Net	Each, Spe	el et		COTOK CODING
No.	Pairs	Ing	0.0.	100	1 500	1000	Polc	
8749		Solid	.150*	2.821	10.05	20.10	No.	Celer Cembination
8741	2	Solid	.201°	4.68	18.85	37.70	1	Binck paired with Red
8742	3	Solid	.240"	6.12	26.25	52.50	2	Black paired with White
8757	4	Solid	.255°		26.25	69.50	3	Black paired with Green
8743	6	Solid	.305*	10.05	46.15	92.30	4	Biack paired with Blue
8747	6	7 x 30	.340*	12.15	55.90	111.60	5	Biack paired with Brown
8744 8748	9	Bolld	.334*	14.65	69.00	138.00	6	Black paired with Yellow
8753	11	7 x 30 Solid	.3R9*	18.75	89.30	178.60	8	Biack paired with Orange Red paired with Oreen
8754	13	Bolld	409	21.004	100.50	201 00	ő	Red paired with White
8745	18	Solid	.420*	25.804	119.30	238.60	10	Red paired with Blue
8741	15	7 s 30	425*	30.75	145.50	291.00	11	Red paired with Yellow
							12	Red paired with Brown
				. 1			13	Red guired with Orange
8748	27	Bolld	.550"			412.50		Green paired with Blue
8753	27	7 ± 30	.595*	6	S¢ FT.	564.00	15	Oreen paired with White
61		HELDED IN	TERCOM	CARLE /	MOT ILLE	16.3	16	Green paired with Brown
		/22 AWO					17 18	Oreen paired with Orange
		pairs. Shie					19	Green paired with Yellow White paired with Blue
wranned	with fol	side out an	d a 422 (7	K 3(1) at	randed dr	alb wire	20	White paired with Brown
		ket and over					21	White paired with Orange
		200 volts.			,		22	White paired with Yellow
Note: Ad	ijacent c	olor-coding	table does	not app	ly to Bel	den 1 000	23	Bive paired with Brown
8751; col	or-codin	g to availabl	e on reque	at.			24	Blue paired with Orange
8751	51	Bolld	.745*	Salery 1	.17 FT.	1 002 .00	25	Blue paired with Yellow
		customer's					26 27	Brown paired with Orange
maximun							27	Brown paired with Yellow

MULTIPLE UNPAIRED INTERCOM CABLE (FIG. E)
annunciator and communication circuit applications. Waterproof, oil and weather
lightweight, small in diameter, tear resistant and easily stripped. Tinned copper
y plantic insulation, cabled in chrome viny! jacket. Suggested voltage, 200 v. working.
flack, Z. Red. 3. Green. — White, S. Brown, 6—Blue, 7—Orange, B.—Yellow, nductors are Black and Red

Belden		AWG and	Nem.	1	Het	Each, Se	teel of	ALC: N
Na.	Corod.	(Stranding)	0.D.	15'	25	100	500	1400
8443	3	22 (7 x 30)	.180*		1.40	3.66	14.65	29.30
1444	4	22 (7 x 30)	.168*	******	1.59	4.83	19.95	39.90
8445	5	22 (7 x 30) 4-22 (7 x 30): 2-18 (16 x 30)	.180*	1 83	1.83	5.58	36.30	47.70
8447	7	5-22 (7 x 30): 2-18 (16 x 30)	.246	1 0 3		9.60	42.45	85.20
1443	8	6-22 (7 x 30); 2-18 (16 x 30)	.251"	2.07	-	10.26	46.50	93.00
8448	9	7-22 (7 x 30): 2-18 (16 x 30)	.261*	2.25		10.95	50.25	100.50

#### SPECIAL INTERCOM AND SOUND CABLES

For systems requiring shielded lines eabled with unshielded control lines.

Siden He. 873 (Fig. F) — Tinned copper, viny linesuised. I white coded onductor with tinned copper braid shield. S conductors cabled in chrome viny! jackets, unshielded conductors coded Black, Red. Conductors 22 A.W.O. 7 g 30 atranded, O.D. 18 onlines, busefested day ventiles.

188 Speci. Net. 6.15 300 Speci. Net. 25.75 1880 Speci. Net. 51.50

PORTABLE CORDAGE AND MULTIPLE CONDUCTORS (Fig. 1)

Ideal for power supply cordage, flexible speaker lines and unshielded entirel cables; abrasion and impact resistant, and thus, diranded copper conductors, rubber insulated and cabled with fillers, rubber jacker; 300 voits, 60° C.

Belden		AWG and	Col-	Norts.			Not I		peal of		
Pin.	Cond.	(Stranding)	ort:	O.D.	15'	25	58'	F86.	250	00'	1000
84527 84785 84725 64537 8464 8455	22 23 4 5	18 (41 x 34) 18 (41 x 34) 16 (85 x 34) 18 (41 x 34)* 18 (41 x 34)* 3-20 (28 x 34)*	2004	.245* 299* .325* 265* .280*			5.25	B.19 11.10 9.90	19.50	34.95 45.00 46.45 52.95	78.00

2-Binck, White, Green, 3-Black, \*Tinned, †UL Type SV. †UL Type SJ. †Colors: 1—Black, White, Brown, Red. †—Brown, Green, White; Black, Red



#### TWO CONDUCTOR UNSHIELDED CABLE

All purpose cable for sound, intercom and alarm systems in a variety of sizes and insulations. Uniform quality and size for dependable service, easy installation, Fig. 0 Types: Cabled vinyl insulated copper conductors. Fig. 0 Types: Cabled vinyl insulated copper conductors in throne vinyl jacket. Fig. 0 Types: Tinned copper conductors rubber insulated and cabled lastic white cotton braid treated for weather resistance. Far other unsilated ables, see listings on Juke Sax and Portable Cortage.

Balden	L	AWG and	Col-	Nom.	Suggested		Not Eas	h, Sposi of	
No.	Fig.	(Stranding)	ors.	0.D.	Work Volts	25'	100	\$0	1000
8401	0	22 (Solid)4		.112"	350		2.28	7.35	14.70
8482	0	19 (Solid)4	1	.115"	350		2.94	10.95	21.90
1460	0	18 (7 x 26)	3	.175*	405		4.29	16.90	33.80
8461	P	18 (7 x 26)	3	226"	450		5.07	20.85	41.70
2205	P	20 (10 x 30)	4	.190°	350		3.83	14.10	28.20

Vinyl insulated for better resistance to sun and seather. Fig. 1 Type: Bare copper conductors parallel chrome vinyl insulated; a conductor tinued and insulation ribbed. Fig. 1 Types: Bare copper conductors vinyl insulated. cabled, chrome vinyl jacket: Color coded 1—Black, 2—Green, 3—Red, 4—White, 5—Yellow, 6—Orange, 7—Bluc, 8—Brown.

Beiden		No.	AWG and		1	Net	Each, Sp		
No.	Fig.	Cond.	(Stranding)	Inch	50	75	100	500	3000
8464		4	20 (7 K 28)	.070 x 390	2.61	3.51	4.50	19.50	38.25
1414	J	4	20 (7 x 28)	.180	80 W		4.70	20,55	41,10
8485	J	5	20 (7 x 28)	,190	*****		5.85	25.50	\$1.00
2488	J	8	22 (7x 30)	.205			5.75	30.30	60.60

#### MICROPHONE AND SHIELDED POWER SUPPLY CABLES

Lone flex life and high tensile arrength for microphones, hi-8 connection, shielded interconnection, power supply, ramote control and strain sauges. Color-coded: 1-White, 2-Black, 3-Red, 4-Green, 5-Black, 6-Brown, 7-Yellow, 8-Grange.

#### PLASTIC JACKET MICROPHONE CABLE

Ideal for applications where lower capacitance, lower loss, greater ozone and oil resistance, lighter weight and smaller size are desired. New 3401 and 3431 3 atrands copper, 4 strands copperpredict, tinged, ceilulose yars braid, polyethylene insulation tinned copper braid shield, chrome visyl jacket

Beldami	No.ef	AWG and	Cap.,   Nem.		Net	Each,	fe loog	_
No.	Cond.	(Stranding)	μμ1/H.* O.D.	15'	25'   50'	264	259	200, 2000
8411	A	25 ( 7 x 33) 25 ( 7 x 33)	347 .144"	1.17	1.68:2.61	4.95	10.45	20.90 41.80
8481	A 1	25 (7 x 33)	25† .200"	1.44	1.92 3.39	6.30	13.20	26.40 52 80
8481	Ĉ 2	22 (16 x 34)	32 231"	1.80	1 68 2 61 92 3 39 2 76 5 10	6.95	19.75	39.40 78

#### RUBBER JACKET MICROPHONE CABLE

Has greater abrasion and impact resistance along with cairs limpness so cable will lie flat on stag studio floor. No. 18430 3 strands copper, 4 strands Copperweid&, tinsed, reliables years braid, rul insulated, rayon braid, tinned copper braid shield cotton wrap black rubber jacket. No. 18430 Elimp mike cable: tinned copper, cotton wrap rubber jacket, cabled, conductive textile wrap abried, attanded ground wire, black rubber jacket.

copper	braid	shield	. cotton	жтар	black n	ubber 1	acket.	25	20.	100	280	500	1000
8410 8412 8428 / 8423 8424 8425 8426 8427	G	2 1 4	25 (7 x 20 (26 18 (41 20 (26 20 (26 20 (26 20 (26 20 (26	E 34)	331 68 80 85 95 80 78 75	245° 268° 295° 277° 295° 323° 349° 360°	3.00		8.00	15.70 16.70 20.80 25.50	27 450 30.60 35.25 350.70 69.00	70 50 78 75	122.40 162.00 141.00 157.60

\*Capacitance between one conductor and other conductors connected to shield. †Capacitance between

				MIHLA	7URE	BROADCA	ST AUDIO	9	CABL		100	500	1 1000"
8450	-1	D	1	22 (solid)		118'	200	L	76	1	4.50	18.70	33.45
.845	1		5	STRANDED						1	4.74	19.50	1 39.00

#### TWO AND THREE CONDUCTOR, TWISTED PAIR SHIELDED CABLE

#### TWO CONOUCTOR SHIELDED

Variety of gauges, insulations, shieldings and jacksis meet every service requirement. Uniform quality for dependable service Fig. E Types: Tinned copper, vinyl insulated, tinned copper apiral wrapped shield Chrome vinyl saket. Fig. F Types: Tinned copper polyethylene insulated. Beidolio aluminum-Mylarg wrapped shield, stranded thaned copper ground wire. Chrome vinyl saket. Fig. E Types: Tinned copper, rubber insulated, braided tinned copper shield. Chrome vinyl saket. Fig. H Types: Tinned copper, rubber insulated, braided tinned copper shield. White cotton braid treated for weather resistance. Fig. I Types Tinned copper, rubber insulated, copper, vinyl insulated. Braided tinned copper shield. Fig. J Types: Tinned copper, rubber insulated, cotton braid, lacquered, braided tinned copper shield.

Net Each. Speak of
3' 50' 100' 500' 1600'
4.56 19.35 38.70
4.80 21.25 42.50
6.00 25.00 50.00
5.33 22.10 44.25
5 85 23.80 47.60
47 3.90 6.75 26.90 57.80

Color coded: #Black, Red. | Red. White, | Black, White. Between one conductor and other conductor(s) connected to shield.



#### HI-FI, STEREO AND PHONOGRAPH CABLES

Shielded connector cords and phono pick-up arm cables are light, Scrible and small diameter with excellent dielectric strength. For maximum channel isolation in storeo phonu pickups use one cable for


Meet JAN-C-17A specifications except where otherwise indicated. Polyethylene insulating material over conductors except as otherwise indicated.

	Belden		_	G.	OL.		AWG and	Shields	Jack -					speol of	
	No.	Flq.		ia.	On I	ns	AWG end (Strending)	No. Typ	e et	0.D.	257	50	100	500	1000
	1237	L	- 8	/U	152	13	(7 x 21) b	1 b	13.5	4115*		9 70	16 30	64 80	129.60
	<b>#238</b>	L	11	/U	175	118	(7 x 26) €	1 b	B.v.	4.11.5			1 4 1 0	44 65	OF. 1111
	6240	L	58	/U	175	1 20	(Solid) e	1 6	BV	.193*	2.07	3.21	5 64	20.70	41.40
٦.	8241	L	59	/U	173	1 22	(1)	I b	BV .	240"	2.43	3.90	6.90	23.90	47.80
1	11.0	1		-	101		AWC -	1 1 0	L14-	11-	L. D.	1	Mas E	ach, Sp	20100
ı	Belden		1	K	,  U		AWG or					SITE	Idel C	acu, 2b	
	No	I Gil	a l	No			Strandin	ra Ne	. Type	19	10	D	100'	500°	1000'

No.	Fig.	No.	CENTRE	Stranding	No.	Гуре	el	O.D.	100'	500°	1000'
3213	L	75	75	14 (Solid) t	1	R	BV	-405		70.951	41.90
3221	L	59/U	75 75	22 (Solid) b	1 2	B	BV BV	. 242	7.80	26.00 101.25_2	52.00 02.50

MIL-C-17B spees, for 213/U. Bare Copperwelds: e-silver coated

TRANSMISSION LINE CABLES WELDOHM TV TWIN LEAD WIRE



brown polyethylene insuiated, Weldohmd, cable is 14 dines stronger and 24 times more fiesible than the equivalent twin lead with all copper conductors, who the stronger and 24 times more fiesible than resistance to rulling, whipping and twisting for a long lasting installatioh, Fig. 0 Type: Copperweld, state to rulling, whipping and twisting for a long lasting installatioh, Fig. 0 Type: Copperweld, state of the conductors 20 (7 x 28) parallel, tubum polyethylene jacketing with mert gas filled unfeelular polyethylene core: Cellulin & maintains uniformity of electrical characteristics by eliminating all possibilities of moisture between conductors. No emiscaling is necessary. Brown polyethylene outer jacket protects cable from abrasion and sun damage. Efficient, it maintains a stronger UHF or VEF picture

melden.		Nem. O.D.	mem. Cap.	Nem. db		760	R Each	, person	36.1	
No.	e. Ohms	Inch	µµt/tt.	@ 480 mc	25	188	75	200	100	
8275 I	300 300	.072 = .400 .300 = .400	4.6	2.7	-95	1.43	1.89	2.37 4.86	11.25 21.6 23.10 45.3	00

8

## MC GEE HAS WIRE BARGAINS OF ALL KINDS!

FIDELITY MC GEE ER CABLE



24Geuge, Easy Zip 2 Conductor Clear Plastic Cover Audio Speaker Cable 1 Timmed (Bare Copper Easy Identification.

Metal Spool

No. 1356 COL.

MINIATURE PARALLEL 100 FEET 1.39

SPOOLS

No. 1356-500, SOO ft, Spool \$12.95 No. 1356-1000, 1000ft, Spool



Polarized - 7 colors - brown, black, white, grey, clear. Super flexible-24 gauge. Low voltage application-SPEAKER CORD.

2F24--500' roll clear....\$5.10 2F24--1000' roll clear .... 9.95

2F24-Specify color 500'. 5.10 2F24-Specify color 1000' 9.95

Belden 8782

JUKE BOX SPEAKER CABLE

1001...\$1.89 500' .. \$6.30 1000' .. (5 Lbs.) \$12.60



\$695

INDOOR SPEAKER WIRE, 20 '2 GA. BLACK RUBBER ZIP CORD. No. B2-20,500 ft. spool, Price \$6.95



18 GAUGE 250 ft spool

BROWN Stock No. 1825BR

4-250 ft. spools

IVORY Stock No. 182SIV

200

95

STANDARD ZIP CORD

No. 18-2ZIP, Specify BROWN or WHITE



25 ft. coil, 75¢ 100 ft. coil, \$2.49

250 ft. 5pool \$5.95

1000 ft. Spool \$23.00

No. 18/2 parallel zip cord, Best grade extra flexible plastic insulated Unapproved zip cord with 18 ga, wire. For AC & SPE speaker extensions etc.



Assorted Sizes Size: 134" x 34" x Ve" 2Ve" x 34" x Ve", 2Ve" x Xe" x Ve"

A McGEE BARGAIN

SALE PRICE SET 3

## SPECIAL

FACTORY FRESHI



TWO CONDUCTOR AC REPAIR CORDS

Stock No. 3503-3, Brown viny! SPT-1.6 ft. 18/2 ga. cord. McGee Price 25c ea. 5 for \$1.00, 50 for 1\$9,754, 100 for \$19.25

Stock No. 3503-9, Brown vinyl SPT-1, 9f t. 18/2 ga. McGee Price 27 cea. 5 for \$1.30, 50 for \$12.50, 100 for \$21.95

#### BARGAIN REPLACEMENT CORDS.

Stock No. C5206, Chartruse vinyl SPT-2 18/2 ga. Heavy duty cord. Price 196 en.

Stock No. SWP+G White vinyl SPT-2 18/2 ge, Heavy duty cord, Price 19g ea 10 for \$1.79,

#### TELEVISION AC-CORDS FACTORY MOLDED ENDS FRESH BEST

PLASTIC BROWN 18-2

Stock Nu. 4185-2, Best brown vany! SPT-1 5 for \$1.25,50 for \$12.00, 100 for \$23.00

Stock No. 4189-1, Best Brown vinvi SPT-1 18 2 gs. 9 ft. tong with molded ends, 37c 5 for \$1.75, 50 for \$16.50, 100 for \$31.95

QUALITY T.V. CHEATER CORDS LOW BARGAIN PRICES. 19¢

Stk. No. 82C22-1



with male plug and TV connector.

Stuck S. .. 82C22-1

AC cord Black plastic insulation 8 foot 18 guage

AC cord. With copper prices going up, here is a red hot value

CII - 8 TV Cheater Cord



Stock No. OH-8 .24¢ eq. 10 for \$2.20 .26¢ eq. 10 for \$2.50



## STEREO AUDIO CABLE

Color Coded
Dual Phono Plug on One End to Stripped and Tinned on the Cother
Grey Shielded Audio Cables
Chicago Made

Differ \$3.50

Stock no. GSAC-72

10 for \$3.50

## SPECIAL FACTORY FRESH ZIP CORD

18 GAUGE 250 ft spool 495 BROWN

Stock No. 1828BR 4-250 ft. spools

IVORY \$17. Black











8 foot No. 18 black zip cord with emel! 7 watt size screw base lamp socket, with light 12 bracket attached. Stock No. EC-LSS, Sale price, 19c sech, 6 for \$1.00.



Belden


TWO CONDUCTOR SHIELDED CABLES


sound and broadcast audio cables


Belden

Trade	A # G &	Non. O I. (Inch)	Cond. Color Coding	Leaves 18 - 1 University	Vision of	Fig.	100'	et Eoch 250°	, Spool 500°	of 1000'
8450	22 (Solid)	.118	BR, Red	100	200	B	\$4.50	8.35	16.70	33, 45
8451"	22 (7=30)	.135	Oft, Red	100	200	8	4.74	9.75	19.50	39.00
8437	27 (Solid)	.200	Bit, Red	10	200	C			27.40	54.80
6441	27 [10x34]	.210	Bh, Red	8.6	200		6.90		30.75	61.50
1641	24 (7+32)	.140	Mk, Clear	100	350	D	4.29		EVEVE S	34.50
8761	22 (7:30)	.167	8th, Clear	100	350	D			17.55	35, 10
8762	20 (7.28)	.196	Blk, Clear	100	350	D	5. 33	11.05	22. 10	44, 25
8760	18 (16±30)	.222	Blk, Clear	100	450	D	1000	13.30	26.60	53, 20

## SPECIAL ANTENNA ROTOR CABLE







No. 672, 3 were round rater cattle, used were filter and anno retator and others, Each conductor, 7 strend capes with plastic resultant and singl electric justice are careful. Each conductor relativeced for identification

CO-AXIAL CABLE - 1000 FT. 3921

RG-59U 72 ohm

RG-50U 72 ohm most popular lead in wire for the new style color TV antennas Ship weight 3 lbs per 100 ft, 4/2e per ft. 1000 ft. spool \$39.95

Extra fine hook-up wire, such as used in Telephone and transsistor work. 28 ga, tint with plastic insulation, easily stripped, FHW-500, 5, 100 ft. coits Price \$2.79 Colors, Green, Black, Orange, Red & White

bare ground wire, Pleatie cover, Three color-Red Green Rrown. Stock No. GBR-150, 3 couls of 59 ft ea.

----Braided shielded wire for any application Flexable 22 ga Stock No. BSW-100. 100 ft. coti

### RECORD PLAYER BRASS AND WALNUT



SIZE: 19%" M. x 22" L. x 13%" D.
With 3" Coeters
COMES KNOCKED DOWN Easy to Assemble
Weight Ends and Walnut Pitts an Mesonite Reco
Base will mecomodate recordal avers up to m Was long

NOT MAILABLE DUE TO SIZE of CARTON

# LOW PRICES TELEVISION LEAD



Per 1000 FT. ANY QUANITY

R80-20

Price \$2.99

80 MILL-20 **GUAGE STRANDED COPPER** 

WHY PAY MORE? GUARANTEED IST QUALITY Factory Name Branded

6000 Volt insulation were for TV, high volf cable Flesable 22 ga 99¢ Stock No. TVHV 100 It. coil

RECORD PLAYER CART AND RECORD STORAGE

Black and Bross Finish Stock No. CASE SALE PRICE not over 18" long. Size Size: not over 18 long, (2)

22" Lax 14" W x 26" H Ship. Wr. 8 lbs. mailable

Stock No. CASE

500 ft, Spool \$2.59 WHITE 2x26 FLEX CORD TINSEL COPPER, VERY FLEXIBLE AS USED ON TOOTH BRUSHES AND ELECTRIC RAZORS. MAKES GOOD SPEAKER

LEADS, FINEST PLASTIC COVERING. STOCK NO 226FC





(5) BP25G-DR25G, Base Plate & 4 Drive rods. Wt. 18 lbs. Set ... (6) HB25BG, House Bracket, 15" to 24" Ext. Wt. 10 1bs. Net... \$18,55

BPC-25G, Concrete Base Plate

WORLD'S FINEST 16 GA. EXPANDED STEEL MAST TUBING Made from high-cerbon, extra-atrength steel tubing and in com-peterly givenized. Here 6' mething expanded 1610 BN 10 ft. 1/2"-16 Ga, Most.... \$3.18 Eq 10 at \$3.08 Eq. 1605 BN, 5 ft. 1/4"- 16 Ga, Most.... \$1.71 Eq 10 at \$1.61 Eq. LARGE 25 SERIES TOWERS DROP SHIPPED F.O.B. FROM FACTORY IN PEORIA, ILLINOIS

ROHN GALVANIZED TELESCOPING MASTS


Heavy 17 gauge. Hes mest brake for simpler installations. Sections 10' long hot-dipped galvanized inside and out after fabrication, includes guy rings. carbon steel. Full 10 feet per section, hot dipped gelvantzed for long life. Shipped assembled, sections do not pull spart. Ideal for the Citizens Band antennes and large T.V. antennes, where you want the best. Order McGee's linest grade. Top section 1%", 2nd. section 1%", 3rd. section 1%", 4th. section 2% diameter.

Stock No.	Height	Tubing Size	Wt. LDs.	Net Each	3 L-1., E.	
MTE-20	20 Ft.	11/211 to 11/411	15	10.85	9.85	
MTE-30	30 Ft.	13/17 to 13/17	24	17.00	16.00	
MTE-40	40 Ft.	2" to 11/4"	- 34	23.75	22.75	
MTE-50	50 Ft.	24" to 14"	48	31.70	30.70	

### ALLIANCE "TENNA-ROTORS" T-45 MANUAL

ROTOR SYSTEM





MODEL T-45 TENNA-TELLER

#### C-D R (CORNELL-DUBILIER)ROTATORS AUTOMATIC ROTOR AR-22R

AUTOMATIC ROTOR AR-22R
Completely automatic, heavy-duty rotor that will handle as much as a 150 lb. load with ease. Streamlined, weatherproof design, durable sturdy construction, heavily reinforced die cast housing. Instantaneously reversible heavy-duty motor. Magnetically released mechanical brakes bring rotor to immediate halt. Precision heavy-duty general 12 heavy duty ball bearings in two 6½ hall hearing races. Reversible clamps will handle masts from ½ no 2 0 D. Buttable for modern design control cabinet with dial that indicates direction antenna is facing.

Shpg. Wt. 15 1bs. CDR No. AR-22R

With Mahogany finish case.

Model AR-22R, Antenna turns and stops as dialed. Rotates Iuli 375 degrees at 1 rpm. \$34.95 Uses 8464, 4-Cond. flat cable 5¢ per IL.

C-225 AUTOMATIC ROTOR SYSTEM





Model C-225, Automatic Rotor \$36,50 Laes 8463 5-Cond, flat cable 49:e \$485, 5-Gada, Rd.

## U-100 AUTOMATIC ROTOR SYSTEM





MODEL U-100 TENNA-ROTOR

Combines the new completely translatorized C-225

Control unit which enables you to receive the brightest, clearest pictures possible and the rotating unit. Gives the sensitive tuning required for Color TV viewing. The C-225 provides automatically moves toward the desired location, and the dial light of Color TV viewing. The C-225 provides automatic possitive stepless synchronous antenna control ic, positive stepless synchronous antenna control throughout 360 degree rotation. Features a patented phase-sensing electronic bridge circuit. Openates at 1 pm on 115 V. 60 cycle AC, 80 watts.

Magnetic brake and sensing circuit eliminates over control box sensitives. Stepless of the control box sensitives and sensing circuit eliminates over control box sensitives and sensing circuit eliminates over control box sensitives. Stepless of the control box sensitives and sensing circuit eliminates over control box sensitives. Stepless of the control box sensitives and sensing circuit eliminates over control box sensitives and sensing circuit eliminates over control box sensitives and sensing circuit eliminates over control box sensitives and sensitive tuning control size of the control of the desired point has been reached. The rotator can be put up with "stop" in any desired position and the control box sensitives are control box sensitives and the dial light protation. The antenna stops where the pointer is est, and the dial light protation and the control of the desired point has been reached. The rotator can be put up with "stop" in any desired position and the control of the desired point has been reached. The rotator can be put up with "stop" in any desired position and the control of the desired point has been reached. The rotator can be put up with "stop" in any desired position and the control of the desired point has been reached. The rotator can be put up with "stop" in any desired position and the control of the desired point has been control of the desired point has been can defined in the desired point has been

Model U-100. Set indicator and antenna automatically moves to desired location and stops.\$27.50
Uses 8 464, 4-Cond. flat cable 5c per ft.

#### TR-2C ROTATOR SYSTEM WITH MANUAL CONTROL





Manual antenna rotor system combines the reliable bell rotse with an attractive, compact (only 6 % x 4 % x 2 %) control box designed by Raymond Loewy/William Snaith Inc. The control unit features a patterned btack vinyl-clast steel case, trimmed in allver, with exita attentioum sides Provides precise antenna direction with a touch of the control bar; illuminated compassion of the control bar; illuminated compassion rotation, for added safety, Heavy duty rotor features in-line, reacherproof construction, with built-in 6 % ball thrust heaving;

Model TR-2C, with Manual control New design. Convenient switch operation, \$30.95 Uses 8488, 8-Cond. Round cable 644 per ft.

#### NEW/ C-D-R AUTOROTOR

MODEL **AR33** 

4995



New Model! Only push-button controlled rotor made. Set antenna direction once for each of 5 channels...then return to that direction automatically by push-button selector. Also has dial controlled selector for any composs point. Completely silent all solid state. Use standard S-wire cable. With same heavy duty rotor unit as other models at left. Shpg. Wt. 15 lbs. \$49.95

## HARDWARE, PARTS AND ACCESSORIES





"SNAP-IN" WALL MOUNT 8306 PER SET

> Clearance 6" WALL MOUNT Clearance 8"



MASTER DELUXE SNAP-IN WALL MOUNT Extra Sturdy



Brackets are spaced 16" wide so as to fasten to 16 in. 2x4 spacing in homes, Made of 1½" x 1/8" steel Fits up to 1½" Dia. mast 8312 12" Clearance 3.69 8318 18" Clearance 4.95 8324 24" Clearance6,75

NEW PEAK MOUNT



Three models to fit three different pitch roofs. Made of heavy steel, to hold masts up to 130" Diameter. 18", 30" or 48" long.

8624 18" long. 8625 30" long. \$3.53 8933 48" long. \$6.50

GUY WIRE CABLE CLAMPS EACH 10 LOT


244 22¢ 8131 hold guy wires securely.

## No. 8575 ANTENNA



All purpose mount for ang-le roofs, flat roofs and also used for comer mounting. Supports mast up to 1½" diameter, Mounts masts in two positions. Heavy steel zinc plated against nist.

## NEW SNAP-IN **VENT MOUNTS**



Fasy to use. Save time — simply snap in place. Many times it is more practical to fasten an antenna mest to a vent pipe. Completely assembled, ready to use. Made of 1/8" x 1½" C.R. steel, heavily zinc plated. 8802-2" to 4"....\$2.69


## HEAVY DUTY SWING-UP MOUNTS

Best quality, heavy duty base mounts for use with telescoping masts. Heavy steel with rust resistant coating. All have hinged mounted feet and will swi ng up from horizontal to vertical position.

1-SP, for use with all 20' masts. ..... \$1.49 1-LP, for use with all 30°

1%" masts. ..... \$1.59 

## PERMA-TUBE BASE MOUNTS



Swing-up mount for masts up to 1-5/8" Diameter.
Use for 11/4" and 11/4"masts

#### 6 STRAND 20 GUAGE STEEL GUY WIRE

IN 50 FT. COILS 20 50 FT. Stock No. 65-20GW

\$6.50

## PORCELAIN EGG INSULATORS

No. J-852 10 LOT EACH 15¢ 12¢Eo.

Porcelain egg strain insulators for guy wires, et 1' long, 1/2' diameter.

## PREMAX

GROUND RODS Heavily copper plated steel ground rods with tapered and for easy driving and adjust-clamp with screw terminal.

4 Ft. 3/8" Dia. 99¢ 6 Ft. 3/8" Dia. \$1.49

#### TELEVISION GROUND WIRE



WERED OF BEEN

8051 12' COIL.....

8052 100' COIL ..... \$6.50

No. Closed Open Each Lat 8057 4" 5-5/8" .20 .18 8365 5½" 7-5/8" .29 .27 8366 6¾" 9¼" .50 .48 8367 7½" 10½" .69 .65

GROUND CLAMP

Eoch

294

GUY WIRE CLAMPS

Each

39€

Handy clamp to fasten to mast to attach guy wires. Made of heavy steel, zinc plated. Will fit masts '/'' to !//'' diameter.

3-WAY

GUY WIRE CLAMPS

Handy 3-way clamp made with acrew eyes for easy fastening of guy wires. Fits masts up to 2/2" diameter. Heavy steel,

GUY WIRE THIMBLES

Made to quickly festen and hold securely guy wires and

Prevents wird from frey ing and loosening.

80. 111

EACH 10 LOT

2/" diameter. Heavy steel, zinc plated, dichromate dip.

8120

000

8372

Popular C-type clamp will fit pipes up to 136" diameter.

Heavy Steel

10 Lot

26¢

10 Lot

36¢

8911

59¢

Makes a secure ground.

TURNBUCKLES

10

No. 8 solid aluminum best quality weather-proof ground wire. Use for grounding TV masts and enterna lead in arrestor

NGW-100, 100 ft. coil \$2.19 NGW-1000, 1000 ft. corton 19.95 HANGER STRAPPING

## Wood Screw Type

**DUPLEX STAND-OFF** 

UNIVERSAL STAND-OFF

Wood Screw Type

3 ½" 5 ½" 7 ½"

12"

8027

8028

8029

8030

Each 25 las

-05 .04

.06 .05

.07 .06

.11



8225 7 1/2".

## Each 25 lot

.19 .18 **DUPLEX MAST STAND-OFFS** 



UNIVERSAL STAND-OFF **WOOD SCREW TYPE** No. Length 31/2" 8027

TELCO 3-WAY TV CLIP Clothes Pin Type



**EACH** 20 FOR

Stock No. Made of Plastic 9015 Metal Contacts

#### MAST STAND-OFFS

Eoch 25 lot 8253 .17 .12 71/2" .20 .15 8257 THE NEW IMPROVED ADJUSTABLE MAST STAND-OFF, STRAP GALVANIZED STEEL

GUTTER STAND-OFF

No. GST350 3½" 100 GST750 7½" 14¢ Anchors twin lead-ins safely & securely against roof gutters

NAIL-IN STAND-OFF LENGTH 3½"

Eoch 8¢ No. 7¢ 8343 Lot

STEEL LAG BOLTS Tri manus 8¢ EACH 2" LONG 1/4" DIA.

1/4"diameter, steel log bolts made al corrasion proof steel. For wood, brick and concrete. Necessary for any good TV installation. NO. BR36,

OPEN TV HOOKS FOR TURNBUCKLES AND GUY WIRES

No. 8735 7 ¢ Mode of heavy guage wire, zinc ploted. This is the bass type of hook for fost-ening guy wires, turnbuckles, etc.

8735 7¢ EA. 10 FOR 65¢ SCREW EYES

No. Length Each 10 Lot 8078 .05 .045 3" 8342 .065 5" 8486 .07 .08

## No. 8610 SNAP-IN CHIMNEY MOUNT



Heavy Gauge Steel 11/4" × 1/8" \$289

No. Fits masts up to 13/11 8610 HEAVILY PLATED Complete with two 12-foot straps

& all hardware 8610-L, Mount with 1/4" x 20 Ft. strapping... \$3.69

UNIVERSAL UHF & VHF LIGHTNING ARRESTOR TAKES ALL UHF No. 9242 65¢ Each 10 For \$ 55

No. 9 242, Teleo Lightning Arrestor fits all types of lines, this VHF, Hollow Line, Oval Line, Open Line, Square Line and reg. 300 ohm twin lead. For indoor or outdoor use. Easy to install.



LIGHTNING ARRESTERS

4-Wire, 8- contoct Rotator Lightning Arrestor (With Strap)..... 20 AT1045

300 ohm Lightning Arrestor for Regular and Oval Jumbo with strap for pipe mtg.

5 Wire Lightning Arrestor for Rotor Cable (With Strap).....\$282 AT1065

AT1105 Best Buy-VHF-UHF 3-in-1 300 ohm Arrestor (With Strap) Fits all heavy duty leads \$174

24 VOLT...... 12 VOLT....... 6 VOLT



## soundolier

MODEL PS24-20 SPECIFICATIONS

117 VAC, 60 cycles. 48 waits
Nominal 24 VDC at 2 amps

12 VDC at 2 amps
6 VDC at 2 amps
Less tham 24,5% at full load
6% 1 3 % 2 amp
Cadmium pisted with gold iridescent linish

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

TAPE PLAYERS

IDEAL POWER SUPPLY FOR CARTRIDGE TYPE

TAPE PLAYERS
Shipping Weight 7.1bs.
SALE \$2.4795
It shall be capable of supplying 2 mmp at 74 vots. 12 vots as 6 vots.
It shall be capable of supplying 2 mmp at 74 vots. 12 vots as 6 vots.
It shall be fused by the primary for maximum protection for the trens.
former. The filter section shall have a chole input. The netifier shall be fused and consist of learn site and closes.

PROVIDE 110 VOLT A.C. CURRENT IN CAR-BOAT-PLANE MAKE 110 VOLT AC POWER FROM A CAR BATTERY TERADO

## TERADO

60 CYCLE CONVERTERS PROVIDE 110 VOLT AC FROM CAR BATTERY

Operate Tape Recorders

Phonographs Radios And Appliances, Etc. TERADO

AUTO-SHAVERS



AC Power Output, 42-52 water, Net ... \$21.30

peraires all circles shapers by plunging into AC, requisite provided variable in 6 v or 12 v, pure large provided variable in 6 v or 12 v, pure large relations machines and tage recorders, radio and phonographs, emergency into the contract of lightness condens and phonographs, emergency lightness contracts to the contract of lightness condens and phonographs, emergency lightness condens and the contract of lightness condens and the contract of lightness condens and the contract of lightness condens and the condens and th

Verade No. 10103 Vistage Input, 12 v. \$11.85

#### 60 CYCLE CONVERTERS

#### SENIOR

frieraies radios, lights, phonographs and so-tage recorders. Available to 6 w or 12 w into Sumple to Install into charecto uniter, Alumin, edge, Sea forces habed channel. Sau: 2 % w 44g d. a. 2 % n. shipping Weight, 3 lbs...


Versian No. 50119- Voltage input, 12 T. 518.47

#### CHIEF

Operation state reviewing area. The models avail-marking, higher, himselve, it was not considered. Con-marking, interpretable and the control. Venit-recept aric. Toggie weitels outsut control. Venit-lated steel range. Easy in mount. Size 24% w. x. 60% of x. 4. n. sulling and venit. Size 24% w. x. 60% of x. 4. n. sulling area. Venit. AC 1 Power Output. 73-608 watta. Not Tertade No. 60328. Voltage lengt. 179. \$53.90 AC 1 Power Output. 100-125 watta. Not AUTOMATIC.

Fluerares giriarias manihas radios, phosostraph, fase reconjers, managang equippenni, etc. I suo compart. Bubi weight months explained a Strape fast status of the fast of the status of the fast of the status of the fast of the status of the

#### MASITE



117 VOLTS AC TO DC- 4- AMPS \$1495 PLAY YOUR AUTO

STEREO ON HOUSE CURRENT case size 43/4 x3x61/2

NO NOTICEABLE HUM OR VOLTAGE DIP WHEN USED ON AUTO CARTRIDGE PLAY-ERS OR C.B. RADIOS.

VISTA IV

SHIP WT. 5 LBS.

sale price \$14.95 2 for 29.00

#### VISTA IV

The standard for home playing of auto tape decks. Highly filtered, quality components, fuse breaker protected, ON-OFF switch, neon indicator light, NO hum, has a 12 VDC output and is 4 Amp rated. This very attractive unit has a pastel green hammertone gover and a brushed aluminum face, has proven to be the fastest selling unit \$ 1 4 95 SUGGESTED LIST : \$24.95 in the industry.

#### VISTA V


For the hobbist who requires more power than VISTA IV. This 5 Amp rated unit will take surges to 7.5 Amps. Very low ripple and works well in areas of power dips. Will play ALL auto tape decks without hum or power fade on channel change. This unit, designed as a top sales promotor, with it's gold hammertone cover and gold brushed aluminum face. \$1995 2 for SUGGESTED LIST: \$29.95
SIZE: 5"X5\"X4"/ALL UNITS 1.A.C.I Y APPROVED /U.L.APPROVED COMPONENTS

\* | YEAR WARRANTY \*



## GENERAL & ELECTRIC VARIABLE TRANSFORMERS

Just Turn the Knob to Change the Volts




A variable Transformer for many uses, for adjusting line voltages to test equipment and other units, where certain imput voltages are required. Can be used as a light dinning control. (not over 5 Bulbs of 100 watts each. This Volt-Pac has been used on a 70.7 volt output line of a power amplifier to control the volume volt output line of a power amplifier to control the volume of the speakers used.

9T92-A1 Volt-Pac 2,5 AMPS, 120V, in 0-120/132 out Price, \$12.00

## PERMA-POWER

Voltage Regulators for Color TV and other appliances rated up to 400 Watts, 60 CPS





SALE PRICE

NEVER BEFORE SO MUCH POWER AT SO LOW A COST Copacity 140 Watts Continuous, 175 Intermittent Adjustable Frequency - 50 to 60 cycles Adjustable Output Voltage Plugs Into Cigarette Lighter or Connects directly to Battery.

WILL OPERATE ANY OF THE FOLLOWING: Tape Recorders, Ham Gear, 11" Portable TV, Dictating Machines, 1/4" Electric Hand Drill (for up to 3/4" wood bit), Soldering Irons, Sewing Machines, Test Equipment, Hedge Clippers, Hand Sanders, Radios, Emergency Lighting (6 bulbs - each 25 watts). Paint Sprayers, Saber Saws, Electric Shavers, Food Mixers, Electric Blankets, Hand Vacuum

Stock No. 50-205

Price. \$46.94



Model TH-30 Kit shipping weight 10 lbs.



VOLTAGE REGULATOR MANUALLY SET



MODEL NO.	MAX, WATTS CONT.	MAX, OUTPUT WATTS (5 MIN)	INPUT AMPS NO LOAO	BATTERY	XISTOR	FREQ. CONTROL 60 HZ 11 HZ 11-16 VDC	POLARITY PRO- TECTION	OVER- LOAD PILOT LIGHT	SIZE hxwxd	WTG. LBS.	MISC. INFO.	DUSTRIAL NET
PV-100	100	110	2%		2				3%×6%×5%	6	Cord & cigar lighter plug-in	\$ 29.96
PV-150	150	165	3		2				3%x6%x5%	7		39.95
PVR-1958	195	195	3	5 amps	4				9%x7x15	15	Use any No. 24 case 12V battery (not incl.)	69.96
PV-2008	200	220	3	5 amps	4				3%x6%x5%	7		49.96
PV-350	350	385	4%	1	8				3%x6%x9	10		74.95
PV-6008	500	550	4	10 amps	10		X	Х	5x9%x9	19	High Efficiency	104.95
PV-1000	1000	1100	8		20		х	X	5x9%x17	46	High Efficiency	199.95
PV-250FC	250	275	3%		11	Х			3½x6½x9	13		99.95
PV-500FC	500	550	416		15	X	X	X	5x9%x9	19		199.96
PV-1000FC	1000	1100	12		27	Х	X	х	5x9%x17	45		299.95
PV-500SWFC	500	500	12	7	17	X	X	X	5x9%x17	40	Sine Wave Output	299.95

CHROME REAR AND FRONT

ACGEE SPECIAL 99

SEAT SPEAKER

CONTROL KIT

EVERHOT

J.40



#### **AUTO - RADIO** VIBRATORS

STANDARD 12 VOLT 4 PRONG CORNELL - OUBILIER

G8301 WHILE 1000 LAST ! A McGEE 79¢ Each
BARGAIN 10 FOR \$7.00
Size: 1½" × 2½"

\$2,00 Value

115 CPS

MODEL PVR-195 B

### MALLORY

11/2 Meg Control **TAPPED AT 750.000** Push-Pull AC Switch Stock No. 69C 10 For 63-6829 \$6.50 6" AC wire attached witch. Shaft 5" long, 3/16" NO 40115

deluxe oven-Broiler

When Ordering by moil Please give page no. and stock no for foster order service.

MODEL PV-150 MODEL PV-200 B

These McGrow-Edison Applionce offered at about 30% below reg. dealer cost. May have slight imperfections in finish. A Real Buy.

ANOTHER

PRODUCT

oven tray may be turned over for dual purpose use . a red hot value for

the cool cook

THE COULT COOK PRODUCT

THERMOSTAT CONTROLLED

GLEAMING CHROME FINISH WITH COOL
BAKELITE END PANELS

USE RIGHT AT THE TABLE FOR BROILING
OR BAKING

TWO POSITION TRAY HAS SEE THRU GLASS
FRONT

RUGGED ENCLOSED ROD-TYPE HEATING
ELEMENT, OFFERING SAFER LONGER LIFE

Dado, Rabbet, Groove, Edge Dovetall Elc Powerful, 5 amp motor Ship 20,000 rpm spindle Uses standard 1/4" shank bits 8 16 s Micrometer type depth Ball bearing spindle NO. 77500

# RECIPROCAL SAW

MANNING

BOWMAN PRECISION ROUTER

Use for Tree Pruning, Cutting Metal, Plaster, Wood

Ship

8 1bs.

Starts its own cutting NO. 73531

2,400, %" cutting strokes per minute

Handle mounts on either side or up and down

4 amp industrial rating

# **EVERHOT** ELECTRIC GRIDDLE



TEFLON III COATED FOR NON STICK COOKING AND EASY WASHING
COMPLETELY IMMERSIBLE FOR WASHING

B 20" x 10" COOKING SUBFACE

41102 TEAN BE USED AS WARMING TRAY

OR ROLL WARMER
EXCESS GREASE DRAIMS INTO GREASE Ship wt.
CUP, KEEPING SURFACE DRY
15 | bs

Special





FINGER-TIP
HEAT CONTROL
PUSHBUTTON STEAM CONTROL
CAST ALUMINUM SOLE PLATE
BUTTON SLOTS
WASH AND WEAR SETTING Ship wt.

GUARANTEED sale price \$5.98 5 lbs.

109



Control makes you the master of your new Variable Speed Drill, Now! You can drill holes or drive screws in wood, plastic, metal, even on hard to drill curved or irregular surfaces You actually control the correct bit speed with your trigger finger. Speed increases as trigger is depressed, decreases as trigger is re-leased. Trigger Lock for full speed continuous operation. Only Variable Speed Drills have the yellow trigger. Try it today.



High torque

NO. 70548

MODEL 70578

A deluse drill with the axtro chuck capacity to aften seeded. Bright-finish, aluminum die-east housing. Geared key chuck. Capacity: 17 lie metal. 37 in wood. A full 3 amp., 113 valt, AC, 50-60 cycle motor, Industrial rating. Variable speed control Pinlack Pligger. Oiled-for-life, top-quality borace bearings. Precision ground ball thrust bearing. Gear reduction; 21,4 of 1, No load speed, 0 to 1000 R.P.M. Net weight 3½ lbs. Pocked one to a Carton, 3 to a case. Shipping weight 14½ lbs. 14% lbs

NOW AT MCGEE

ELECTRIC PLANER

MODEL 75500 -

McGRAW-EDISON

12-CUP

AUTOMATIC

ot slow speed MANNING-BOWMAN HAND TOOLS AT BARGAIN PRICES 3/8 INCH DRILL 1/2 INCH DRILL 1/4 INCH DRILL MODEL 4

REVERSABLE 70556

capacity 1/2"

61/2" INCH POWER SAW

**MODEL 73524** 

MODEL

3/8 INCH DRILL Bright fines, handle, milishy side handle, milishy side handle, for an arrival of the first transfer of the fi

4-INCH

50-60 cycle motor. Autor Precision ground bell-thr reduction. No load spe speed 500 rpm. Net wt. 7 1/4 INCH POWER SAW 2695

MODEL 73526

BELT

SANDER

MODEL 72510

7.5 amp. MODEL 72510

- BENCH

GRINDER

71107

NO. 70508

speed 1400 mm. bearings, Gear re

SABRE JIG SAW 1595

Now full 3 amps deg. cut.



MOTOR DRIVEN SANDER

MODEL 725001

75008

COFFEE MAKER STAINLESS STEEL

LUSTER

Made By Menning-Bowman Di vi sion

1129 Stock No.

Has "Peek-A-Brew" opening in back to see amount of water in percolator. Has flavor control for mild to strong. Signal light tells you when its ready. Keeps coffee hot after brewing.

This Percolator sold under other Brand names for as much as \$29.95



DOUBLE WAFFLE MAKER 154" × 154" × 7"

Model 37 100 2. Automatic Double Waffle Baker & Sandwich Grill with Teflon coated grids. Chrome finish with black plastic handles and feet. Automatic signal light, reversible grids, drain spouts. 1300 watt, 120 volt, 60 cycle AC. Weight 13 lbs. Sold under other Name Brands for 539,95

These McGraw-Edison Appliances offered at about 30% below regular dealer cost. May have slight imper-fections in finish. Real McGee Buys.

115 volt


Regular \$49.95 List Value FACTORY RE-RUNS GUARANTEED LIKE NEW PROFESSIONAL TYPE BELT MASSAGER

MODEL \$19

MODEL 511130, Professional type belt massager with adjustable belt stroke for gentle or vigorous massage. Light blue housing and base with non-slip base surface. 115 volt, 150 watts, 60 cycle, AC only. Motor provides 1000 rpm. Shipping weight opproximotely 26 lbs.

Sold For \$49.95 under other Name Brands TOASTER MODEL 345350

4-SLICE



Model 345350, 4-Slice Toaster in Gleaming chrome finish with black plastic control & handles and feet. May be shipped with One or Two controls. 120 volt, 1600 watts, 60 cycle, AC only, Weight 22% ibs. Size; 12%' x 11-7/8' x 25%'. McGee Sale Price....\$9.95

# MERCURY 1101C TUBE TESTER

BUILT-IN VACUUM TUBE VOLTMETER CIRCUITRY . CUTS RIGHT THRU WASTED MOTIONS TO THE 2 UNFAILING TESTS THAT WILL TIME AFTER TIME, PICK OUT THE BAD TURES. THE WEAK TURES THE GASSY THRES!

#### THESE TESTS ARE:

- 1. Catiode Emissi
- 2. Gas, Grid Emission and Grid Leakage

WIRED 1101 KIT 79 95



#### FEATLUSES

auced ALAN wested at Georgias Els compet works counters voting years against advant appropriated.

The speak of promote approximation and belief and sections of the

"Maximum samptivity and figures appropriate industries been to \$5.00 toler and \$6.00 Leaves test applies appropriate industries been to \$5.00 toler toler toler applies appropriate the sample applies to the imput of the fifth for industries to the industries applies applies to the industries applies appropriate industries applies to the industries applies a

Delto Mark 10 B Instant change over switch from Delta to regular ignition. CAPACITIVE DISCHARGE **IGNITION SYSTEM** 

The Mark 10 B has been designed to provide the finest and most reliable ignition system available. Characteristics of the Mark 10 B are improvements in performance and economy due to the high spark energy, along with the increase in spark firing duration. Better cold weather starting with low battery valtage. The plug firing duration decreases at high RPM but the high spark energy continues to be delivered to the spark plugs.





#### SPECIAL FEATURES

NOT A KIT WIRED ONLY

LIGHT WEIGHT

VOLTAGE RANCES
OC 0-0-25, 1-25, 10, 50, 250, 1000, 6000 volts
C 0-2 5, 1-2 5, 10, 50, 250, 1000, 5000 volts
20,0002 ber VDC --50002 per VAC
CURRENT RANCES
DC. 0-50gas, 1-ms, 10ms, 100ms, 500ms, 10A
Drop in voltage between terminals -0.28V
RESISTANCE RANOES

D.28(12()center)

est phospher bronze conflact type sechells sockets identified up to fair pin attraphteners is might suppr metric mith special Gary Grid Lisbage Arc 1 acabage and Gar Rest 1 acabage and Gar Rest 8 proof ne-plane integrate type serving code betten 3 poweron Switching System and

and linguage type a arrying code
partiest Surfactional System enduces the obsolescence of

FUBE CAREA is not only up to date that is hely up to date on a year inflyed out bases! Data for over 3000 tubes is constantly reviewed and entarged year after year!

NEW 1972 MERCURY VOM

STOCK NO 1800A PRICE \$7995

PROFESSIONAL QUALITY VOLT-OHM-MILLIAMMETER

EASY-TO-READ 5" MIRROR SCALE
13% ACCURACY ON ALL RANGES
DIODE OVERLOAD PROTECTION

IDEAL FOR CIRCUIT DESIGNERS
SERVICE AND LAB TECHNICIANS

# ± 100 0-200K Ω (1200Ω center)

G

I

I

DB SCALES 20 to in 4 ranges FREQUENCY RESPONSE 40.5 db from 1081 to 100KHz on 2.5, 10, 50 wats ranges ACCURACY OC 40 full scale Flamsware; \$2% of full scale Flamsware; \$2% of set GENERAL

#### POPULAR TUBE TESTER



WIRED

\$3495

NEW

\$7495

1972 MERCURY

AC VTVM

KIT

COMPACT

TUBE

**TESTER** 

is a Miniature-size Space-Saver BUT

u Unquestionably FULL SIZED in

PERFORMANCE!

12 circuit bide button feasier amighing systems tractument case 9 Power Requirements...
a face 615° a 715° x 3.5° # Weight 616 little.

STOCK NO 1800

PRICE

\$79.95

WIRED ONLY NOT A KIT





STOCK NO 1750

NOT A KIT WIRED ONLY

This is a high sensitivity VTVM designed by measure as chack-concurts and low-level AC voltages

PIRATUMES
Bibliotrod neuronicum una conscientate quantity di negative feedb
Bibliotrod neuronicum una conscientate quantity di negative feedb
Bibliotrod neuronicum una conscientate de la conscienta della cons

#### SPI CIFICATIONS

105\*1.2%, AC 50\*80 PM, 20VA (Appre),
12A F7, 68LB, eleann 4004 inteOrpt
10e11, 75ge
AC 300 V rinc. DC 5 1000V
Mayer Inn 7 V or Cult scale
2,0,6 db on 10 V47\*NO0 CRF at capacity load 67 less sharp, 0,01
2006 - 40, 30, 30, 40, 6, 10, 3, 1, 2, 10, 30 (so), 300 V xm
38hm = 40, 30, 30, 40, 6, 10, 30, 30, 40, 60 dbm
15% at 14h scale late 185445
15% at 1000 F18 applied \$100. Thetavoltein of little voltamp, 15

MERCURY 1750 AC VIVM \$49.95 NOT A KIT WIRED ONLY STOCK NO

> 1750 PRICE \$49.95

NEAL 6", 50 microamp \*2%, dodd protected and solated from moud Weller 6", 50 microamp \*2%, dodd protected and solated from moud Qhms 3attery 1.59 "UM62" cell for R41, R+100, 7.89 (1aU84.2 and 4-UM-39 6e R410K : D-mersi LATEST TRANSISTORIZED AUTOMOBILE IGNITION SYSTEMS

8 a 1000 0 20M121120K@conter)

# UDSON

ELECTRONIC-MAGNETO IGNITION SYSTEM

\* Enay-to-install, one place unit \* Premium Silicon translator \* Top High-Speed Performance Net Eoch

> THE ULTIMATE IN ELECTRONIC IGNITION

It's like getting & permanent engine

Stock Ho. JEM

TRANSISTOR IGNITION COIL 250 TO 1 RATIO Special FALE

10 Far \$25.00

Stock No.

TRS-10

FACTORY WIRED \$39 IGNITION SYSTEM INSTALL

McGees Best Buy in a Transistor IGNITION SYSTEM The New Mark 10 Requires only A Few Minutes to Install

Specify Positive or Negative Ground

# DELTA'S FABULOUS CAPACITIVE DISCHARGE

MORE EFFICIENTLY WITH A



You read ell about the fabulous MARK TEN in the August issue of ML. How, prove to yourself the increased performance, the remarkable fuel savings, the more complete combustion possible only with Detta's MARK TEK, Delta ploneered this electronic manual; thousands have installed it. Proven and accepted by the automotive industry for 3 years, the MARK TEN is to volume production and is offered at low, low cost! det your MARK TEN today, install in only ten minutes: build your own from all with complete seay to follow instructions and save.

A spath Plag life increased 3 to 10 times.

A lestant starts in all earther SPECIFIS

- ▲ Up to 20% feel savings ▲ Gramatic acceleration increase A installs in 10 minutes
- () Positive Ground Hegative Ground (Hid 32 V only)

NEW MODEL



Model 889 kit

Model 889W wired \$ 3 995

IGNITION SYSTEM CAPACITIVE



Boosts your gas mileage up to 25%; extends life bf points and plugs to 100,000 miles; makes tune-ups last 5-times longer; gets faster starting, better acceleration—even at sub-zero temperatures. No waste—you

use your present coil, plugs, wiring! Model

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108

# **BUI** Precision Test Equipment

#### NEW! B & K OSCILLOSCOPES WITH EXCLUSIVE CALI-BRAIN® FEATURE

#### Model 1440 with Recurrent Sweep

The 1440 is the only other scope on the market that has B&K's new, patented CALI-BRAIN feature (described in full at left, in the 1465 description), it also has 10 MHz bandwidth and front-panel Vectorscope capability. For anobication, not requiring tries.



applications not requiring trig-gered sweep, she 1440 is an out-standing scope for use in service shops, schools, labs and industry. Has the time-awing TV-H and TV-V poritions on the sweep selector, with pre-set 30 Hz and 7875 Hz sweep frequencies for synchronization of the horizontal and vertical TV signals. With dual 10.1/DIRECT probe, Mylar Vertical overlay and Ulti-stand for synchronizations. Vector overlay and tilt stand for cyc-level viewing. Size: 9 x 10 x 17 deep. For 105-125 VAC, 50-60 Hz. 3-wire line cord. Wt., 27 lbs.

B & K Modet 1440, With probe ................................ Net: \$299.95

#### Model 1460 Triggered Sweep Deluxe Scope

Fully automatic triggered sweep. View the entire composite TV signal or any



the entire composite TV signal or any portion thereof, including the VITS and "back porch" of the homzontal sync pulse-all in perfect sync. Special sync separator circult operates in all 19 triggered sweep positions, including TV-H and TV-V positions; switch back and forth from 2 horizontal lines to 2 vertical fields—with no other adjustments! DC to 10 MHz bandwidth; 10 millivoits/cm sensitivity displays smallest signal levels. DC amplifier, Has 1, 2, 5 steps on calibrated vertical attenuator, Front-panel Vectorscope capability. With dual 10:1/DIRECT probe, Mylar vector overlay and tilt stand. Size, 9x10x17". For 105-125 VAC, 50-60 Hz, WE, 27 lbs. 50-60 Hz Wt 27 lbs

#### Model 10778 Television Analyst

Analyzes any stage of color or B & W TV sets ... solid state or tube-type circuits. Greatly speeds trouble-shooting and virtually eliminates those "tough dog" problems. Outputs include: IF, video, sync. 4.5 MHz sound, high level color rainbow and bursts. B



level color rainbow and bursts. RF and IF outputs have keyed color rainbow pattern and sound channel which can be displayed with picture, UHF Channels 14-83; 8 VHF Channels. Low impedance bias supply; UHF Channels 14-83; 8 VHF Channels. Low impedance bias supply; shorted turn tester; grid, plate and solid state tweep driving signals. Pattern generator uses flying apol scanner to produce video portion of signal; pattern dides supplied include test pattern, crosshatch, dots, and R-Y, B-Y keyed color bars. Any 3x4" transparency will produce pictures for CCTC, CATV, TV paging, advertising, etc. With pattern sides, cables and dilustrated 111-page instruction manual For 105-125 VAC, 60 Hz. 3-Wire line cord. Size: 9-3/4x18x12", Wt., 31 lbs.

#### Model 177 30-Range VTVM



Highly versatile, rugged, "old-stand-by" vacuum ohms battery required Has 30 ranges:
DC/AC/RMS volts; resistance. Separate peak-topeak and RMS scales, Special calibration on low
AC ranges Large 7", mirrored, 100-microamp
meter, input resistance, 11 megohms. Accuracy
3% on DC, 5% on AC. Supplied with 8 & K
PR-43 high-impact Cycolac, DC/AC/Ohms test
B & K Model 177
AV-1A RF PROBE, Extende for

B&R Model 177 . Net: \$89.95 AV-1A RF PROBE, Extends freq, range to 250 MHz. 1 lb. Net: \$ 7.95 AV-2A HIGH-VOLTAGE PROBE, Extends DCV range to 60,000 voits. W. 1 lb.



#### Model E200D Wide-Range RF Generator

100% solid-state circultry calibrated meter monitors:
RF level and % modulation;
zener-regulated power supply, 100 KHz to 54 MHz on
fundamentals, 54-216 MHz
on harmonics, Outputs; Un-

modulated RF; modulated RF: externally modulated RF; 400 Hz audio. Accuracy of better than 0.1% possible with internal crystal calibration. For trap, bandpass coll alignment; FM/AM receiver alignment; stage-by-stage amplifier gain test; signal tracing, 110-130 VAC, 50-60 Hz, 16 lbs. B & K-Precision Model E200D. Net: \$189.95



#### Model 1465 with Triggered Sweep

screen. To read peak-to-peak voits faster and more accurately, here's all you do: (4) Get pattern on screen; (2) pull out CALI-BRAIN knob (vertical position control); this collapses the honzontal sweep and shifts the resulting vertical line to the proper scale; (3) position the compressed waveform on the base line; (4) read the peak-to-peak voits directly off the screen! The 100% solid-state 1465 also has 10 MHz bandwidth, triggered sweep, automatic sync and front-panel Vectorscope capability. With dual 10:1/DIRECT probe, tilt stand. Size, 9x10x17", For 103-125 VAC, 50-60 Hz, Wt., 27 lbs.

8.4. K. Midel 1465. With probe.

# & K Model 1465. With probe



#### NEW! Model 1470 **Dual-Trace Scope**

Features dual display of waverms, their sum or difference, for fast easy comparison, etc. Pully automatic and triggered sweep. DC to 10 MHz bandwidth; 10 millivolts/cm to 20 volts/cm verti cal sensitivity, divided into 11 culibrated ranges. Operating modes: Ch. 1 only, Ch. 2 only;

modes: Ch. 1 only, Ch. 2 only; alternate; chopping (140 KHz); Ch. 2 invert or normal (push-push-switch). TV sync Separator; SX magnification; all solid state. With Mylar Vector overlay and tilt stand. Size: 9x10x17". For 105-125 VAC, 50-60 Hz. 3-wire line cord. Wt., 28 lbs. B & K Model 1470. Less probes; see listing below ....... Net; \$499.95

MODEL PR-18 PROBE SET. Two B & K dual-purpose. 10:1/DIRECT probes for use with the Model 1470, Wt., 2 lbs. . . . . . Net: 5 29.95



#### Model 415 Sweep/ Marker Generator

With the 415, the only other equipment needed for TV alignment is a scope and VTVM. Full solid state design, with dual gate MOS-FET. Self-contained tuner. IF and chroma bias supplies

usable on tube and transistor sets. Crystal-controlled RF (Channeis 4 and 10). No curve distortion with 11 crystal-controlled, post-injected markers, all usable simultaneously. Front panel visual reproduction of lighted curves with lighted markers, for soope waveform reference. Electronic sweep for maximum linearity and dependability, Marker tilt and marker amplitude control features permit easy identification of marker position, regardless of sweep curvature—for positive alignment of traps, etc. With all leads, cables, direct and demodulator probes. Size: 9x17-5/8x10-5/8". For 105-125 VAC, 60 Hz. With 3-wire line cord.



#### Model 466 Deluxe CRT Tester-Rejuvenator

Professional-quality B&W and col-or CRT Tester with the latest advanced features Checks Trini-trons, GE 11th tubes. Separate G-2 control for each color gun; moni-tored rejuvenation - see precisely what you are doing, "Super-Rejuvenate" function for re-

storing otherwise worthless tubes 442" meter; continuously variable and metered heater, G-1, G-2 voltages monitors heaters at the CRT pins. Tests CRT's for opens, shorts, leakage checks cathode emission; evaluates color gun tracking. 13½x9½x5¼" For 105-125 VAC, 50-60 Hz. Wt., 8 lbs.

\*\*\* MPORTANT NOTICE\*\*\*\* ALL RETURN MERCHANDISE MUST BE REPACKED IN THE ORIGINAL

PACKING CARTONS USED IN THE SHIPMENT TO YOU. IF PACKAGED OTHERWISE AND DAMAGE ACURS, WE MUST MAKE A CHARGE FOR REPACK-ING AND STOCKING. \*\*\*BE SURE TO SAVE CARTONS

NEW! Model 179 F.E.T. VOM 55 Ranges, Including AC Current

CALI-BRAIN-another B&K Put it to the test! Get drift-free accuracy, wideband first! Special CRT screen has 2 AC response and all the versatility of a standard VOM scales, one on each side; selecting in the new Model 179, Reads DC volts, current; AC your vertical attenuator range au-volts, current; and ohms—for a total of \$5 ranges (plus your vertical attenuator range auvois, current; and onma-for a total of 30 ranges (high sup the correct dominance). High input importance (10 megohms),
scale and produces a digital readminimizes circuit loading. Diode-protected input,
out of full scale wolts above the Internal voltage regulation assures stable, accurate
screen. To read peak-to-peak volts readings. Large, 4W mater has sensitive 80-microamp
accurately, here's all you do: (1) Get pattern on screen; movement and mirror scale. Case has "stay-put" handle

movement and mirror scale. Case has "stay-put" handle; stays in position.

Complete with batteries and shielded test cord set. Size, 5x7-5/8x4-3/8".

Shpg. wt., 3/4 ibs.

B & K Model 179 Net; 574.95



#### Model E3108 Sine/ Square Wave Generator

Latest version of the industry standard. For service shops testing hi-fi equipment; for schools, labs, industry. Now features solid-state circuitry: F.E.T. in oscillator, all-silicon transistors. Step attenuation of both une and square wave outputs. Extended ranges.

constant-voltage output. Fully thielded. Easy-to-read 5" dial with 12:1 gear ratio drive. Size: 12-3/4 x 7\%x8". For 110-130 VAC, 50-60 Hz. Shpg. wt., 11 lbs.

B & K-Precision Model E3108 ...... Net: 5119.95



#### NEW! Model 747 **Dynamic Gm Tube Tester**

Tests all tubes with true dynamic mutual conductance test. Has (1)
"Jet-Check" section for testing
tubes most often used in radio and TV; (2) programmed section for less popular tube types. Thus, the 747 is truly obsolescentproof, extremely fast and easy to use, and offers the positive reli-

ability of the dynamic Gm test in both sections. Tests emission of non-amplifying tubes such as diodes and rectifiers; checks high-voltage regulators with effective dynamic test. Checks for shorts, leakage, grid solid state. 5-5/16x20%x11%



The color generator with broadcast station stability. Integratedflip-flop circuits for accurate countdown, 9 patterns, including Center Dot, 1x9 and 9x1 Cross-

Center Dol., v.y. and wat cross-hatches. Crystal-controlled RF. Ch. 3, 4. Also 4.5 MHz unmodulated carrier (tuning aid). Red. blue, green gun killers. In exclusive "Instant Use" carry case. 2½x7x10-3/4", 100-130 VAC, 50-60 Hz, Wt., a bs.

MODEL 1243 COLOR GENERATOR. As above, but only 6 patterns; tunable to Ch. 3, 4, 5; factory-tuned to 3. Less unmodulated carrier, gun killers, carry case. 2\%\pi\pi\_3/4\". 3 lbs. . . . . . . . Net: \$99.95



#### Model 607 High-Speed Dyna-Jet" Tube Tester

Here's the only tube tester in its price class that gives you POSI-TIVE shorts indication. Exclusive lockout pushbutions open any tube's multiple-connected puns.

UALITY check. Shape-coded symbols match panel controls to chart. Checks cathode emission under simulated load conditions. Checks orgid emission, gas, leakage. Tests latest tube types, plus old types used in Radio/TV, including Nursitors, Magnorals, 10-pin tubes and 12-pin Compactions. Phosphor bronze sockets for long life. Compact, attschetype case. Size: 1346194824", For 105-125 VAC, 50-60 Hz. Carrying wt., only 6 lbs. Shpg. wt., 7 lbs.

B & K Model 607

When Ordering by mail Please give page no. and stock no for foster order service.

GG22 WORLD'S SMALLEST COLOR HI-LO FIELD EFFECT MULTIMETERS - A New Concept



GENERATOR

8900

A pocket size color generator with a grant performance. No larger than two 5U4 tubes. Push button pattern selector switch for ease of operation. RF could be retrictable eliminating dangling cords. Built in pre-steer for colder climates. Exclusive automatic shutoff of battery power. All electronic, no more run down hatteries if you forget to turn it off, it turns it self off. Uses the same perma-lock circulary in the larger CG159 to give painted patterns and small dota. Uses two mercury batteries, Eveready E164 or equivalent, (not supplied).

OG22 Caddy Bar Jr. size 4 1/8" x 6" g 2" weight



The new King in co,or bar generators, the CCESO. New permalock circuitry makes for rock solid pat-terns and "painted" dots on the screen. Smaller dots terns and "painted" dots on the screen. Smaller dots and lines for easier convergence with licensed RCA patterns. Single dot and line pattern both movable to simplify dynamic convergence. Thermostatically controlled heater to awarn the CG159 you could day or drive out moisture in humid areas. New high styled two-toned carrying case give you that professional look, and its made in America.

CG159 Color King [II] 10" is 9" x 3 1/2" weegs the

\$169.50



Test transitors, Diodes of FETS in and out of the circuit with ease and accuracy with either the Sencore TF17 or the TF15L. Both testers use an AC beta test to dynamically test transitors in and out of the circuit for AC beta. FETs are tested dynamically for transconductance just like a tube with the Gin read out with on the meter. Leakage tests made out of circuit on both transitors and FETs. FET zero bias fets the contract of the feet meters converted that feet methods contract accurate. drain current (ldss) for matching or industrial sorting is included on both testers

TF17 in and out of execut transitor tester with 4 1/2 inch meter and all steel carrying ease with lid 9 1/2" x 7 3/4" x 3 3/4" wt. 7 lb. (not shown) . . . . \$109.50 in and out of circuit transistor tester with unch meter for the bench or lab 9 1/2" x 7 1/2" weight 9 lb.





19950 FE21

FE20

FE180

\$129<sup>50</sup>

19000

HI-LO FIELD EFFECT MULTIMETERS—A NEW CONCEPT IN FE METERS. NOW YOU CAN MEA-SURE RESISTANCES IN CIRCUIT IN SOLID STAL DEVICES WITH THESE HI-LO FIELD EFFECT MULTIMETERS LOW POWER OHMS using .66 volta to make in-circum resistance measurements accurately. use latest Howard Sams service in Allows you to use latest Howard Sams service in-formation. HIGH POWER OHMS for routine reinstance measurements and to check front-to-back ratios of diodes. Meters would not be complete with low power ohms only. ONE-TENTH VOLT FULL. low power ohms only, ONE-TENTH VOLT FULL SCALE sensitivity on both AC and DC voltage. A must when servicing in solid state directle with critical low voltage binner. PROTECTED TO 1000 TIMES OVERLOAD. A truly burnout proof multimeter Tested in production with 1,000 voltage in 1 volt range. Multimeter resistors protected by \$8 mm fuse to save these valuable and expensive components. No more than 10 forces when you excelentably measure solid. trips to factory when you accidentally measure volts on ohms rante.

FE20 Complete with high voltage probe and all steel case. Size 9" x 7" x 4". Weight 5 lbs. 46 inch meter) \$129.50

> **CR161** CRT AUTO-TRACKER WITH COMPUTER

> > MEMORY CIRCUITS. 4000

The new CR161 Auto-Tracker features automatic tracking with computer memory system. Just put a button and make the previously complicated tracking test on the go-no go scale of the meter. The computer memory sucreties store the necessary information for the tracking test. The filiament voltage is set on the meter for greater accuracy than ever before. Now you can test all the picture tubes you encounter with the same test procedure, American 8tf gun, the Sony Trinitron and black and white CRTS. Eliminates all the complexities of CRT testers of the pask. New societe assemblies are stronger and more durable than ever to list longer. Housed in a professional two toned vinyl clad steel case. The new CR161 Auto-Tracker features automa two toned vinvi clad steel case

CR161 Auto-Tracker size 10" a 9" a 3 1/2" weight 5140.00 FE20 and FE21 SPECIFICATIONS

- 9 DC Voltage ranges. 1 to 1000 volta full scale.
  3 High Voltage ranges of 3, 10, and 30 KV.
  9 DC Zero center ranges. 05 to 500 volta.
  9 AC Voltage ranges. 1 to 1000 volta full scale.
  9 AC Peak-to-Peak ranges, 28 to 2800 volta.
  9 DC Current ranges. 100 microamps to 1 amp full.
- 7 Hs Power ohms ranges, 1000 ohms to 1000 meg-
- 6 Lo Power ohm- ranges, 1000 ohms to 100 megohnts
- FE160 SPECIFICATIONS DC Voltage ranges; .3 to 3000 volts full scale Zero Center ranges; .05 to 1500 volts AC Voltage ranges; .3 to 1000 volts

- AC Peak-to-Peak ranges: "28 to 2800 volts DC current ranges. 30 microamps to 3 amps full
- AC current ranges. 30 microamps to 3 amps
- full scale 8 Hi Por wer ohms ranges. 600 ohms to 6000 meg.
- 7 Lo Power ohms ranges. 600 ohms to 600 meg-



**FE14** 169°5 **\$84** 50

Field effect meters are fact replacing the VTVMs for service and tab use. The Service FE14 and FE16 are general purpose FE meters with 4.1/2 inch meters. The input impedance is 15 megohins on DC and 10 megohins on AC for less carcuit loading and more accurate readings, instant on stability hecause FET1 are used in place of tubes. Both units are fully protected for up to 100 times AC overload to prevent meter demans. Sinceral shelded leads resemblished. netter for up to 100 times. At oversom to present meter damage. Spread sheeled teach prevent tray pick-up. 14 DC voltage ranges 1 to 1000 volts full scale, 7 negative and 7 positive, 7 zero center ranges from 5 to 600 volts full scale, 7 AC ranges, 1 to 1000 from 5 to 500 volts full scale, 7 AC ranges, 1 to 1000 volts full scale RMS, 7 peek to peak ranges from 2 80 to 2800 volts, 5 DC current ranges from 100 meroamps to 1 amp full scale and 5 resistance ranges, 1000 ohms to 100 megohns with a 100 ohm center scale, 80th meters use 8 1.5 volt "C" cell and 9 volt transistor radio battery (not supplied). Size 5" 8 7 3/16" x 3/1/16", Weight 4 lbs.

FE14 FE Meter with 2.5% DC and 4.5% AC Accessory.

FE16 FE Meter with 1,5% DC and 2,5% AC as

39A19 High voltage probe for use with the PE14 or PE18 to extend the DC voltage range up to 30,000 an on 69 95

PS148 DUAL PUR POSE SC'LLOSCOPE VICTORSCOPE \$269.50

PS148 Dual purpose Oscilloscope/Vectorscope, the first really complete service scope. Wide band as FS148 Dual purpose Oscilloscope/Vectorscope, the first really complete service supper. Wide band nesponse of 10 Hz to 5.2 MHz ± 1 db at a senativity of 17 mV R348 per inch. High imput impediance of 27 megahns shanted by 11 pf with the low cap probat Voltage rating of the probe in 7000 volta to prevent accidental damage, to the scope if the wrong point is contacted. Direct read out of the peak go peak voltage with two simple front panel controls. Convert to a vector-cope with the flip of a switch. Positive system and full vange of horizontal useeps frequenties from 5 Hz to never 500 KHz. A truly deliuse service is cope with a flat face 5 °CRT. Size only 11" a 9" x 15 1/2" Weighs only 22 lbs. Veighs only 22 lhs

PS1-18 On di

#### PM157 POWER MONITOR

The new PM157 Power Monitor is the most prac-lical tool ever devised for the electronic service to dustry dustry. Its on AC line soft meter from 65 to 135 volts calibrated at 115 volts for greater ac-Its on AC III



115 volts for greater accuracy. 10 an AC anymeter up to 10 amps for cherking flavor and consult breakens. Its an AC watte meter up to 1150 with a make your troubleshooting reaser. Its an DC amponeter up to 110 amps for power problems. There is a special fose osister scale color coded for eo no go constituint for faster service. All this and it is fully protected and sociated from the power line for operator safety. power line for operator safety PM157 Power Mondon 6" x 6" x 8" we



the cess anguly after vit. Fit the Latter with per-chimination registers to allow festing of more tubes than ever before. Magfalse thorts caused by internal connections. Now ebecks more tubes at full reduced cathode current level that have made the Mighty Mite so famous. Sensitive 100 megohin grid leshage test pichs out troublesome tubes before they can cause a all hack. Stethos opic shorts test each and every element for true-shorts. Durable, high styled two toned carrying case for that professional look that you need on your home service call. This new Mighty you need on your home service call. This Mite is still the same price as the older mo TC162. Mighty. Hite. VII size. 10" x 9.

weight 9 lbs



PS163

3495°°

Sencore PS163 Dual Trace Tragered Sweep Oscillo-scope. The most complete and venatile oscilloacope available today, Extremely stable trigered sweep with full hand width capability in both automatic and tragered modes PLUS free running capability for use as a sync sweep service scope.

Complete Dual Trace capability with pushbutton selcomplete the arms of Channel A, channel B, chopped or alternate displays PICUS Sencore exclusive sector mode with full sensitivity.

SENCORE



SPEED ALIGNER

\$27500

The SM158 Speed Aligner is designed for speed ar simplicity in television alignment. Simple took up of only four cables for full alignment. Zero baseline ma-ference for trap alignment and postnoining of carrier markers. Twelve crystal controlled markers with the timele. markers. Twelve crystal controlled markers with the cimple puts of a button. 38,75, 41,82, 41,87, 42,17, 42,67, 44,25, 45,75, 47,25, 4.6, 4.08, 3.58, and 3.08 MHz. All frequencies listed right on front panel for fast identification. Both horizontal and vertical mar-kers. Four channels of RF, two more than most gen-erators for tuner checking and overall performance checks. Full 18 Megaherts sweep width and post in-jection markers make the SM158 the true Speed Aligner.

jection markers mane to Aligner SM188 Speed Aligner Size 7" \$ 10.3/4" x 5" Weight , \$275.00

three 0 - 25 volts plus and minus and one 0 - 75 volts negative. Size 7" x 4" x 2", Weight 2 lb. . \$24.95



The MU150 Continental II is the worlds only tube analyzer. Checks the tabes for Gm with a 5000 Hertz square were for a true Gm test. Checks the tube for full load cubode essission just like the Mighty Mits. 100 megohm grid leskage test to pick out the troublesome tubes encountered in your daily routine. Trug shorts picked out with the famous Sencore stethoscopic shorts test. Only true shorts show up on the Continential II. Housed in a handsome seed stanch case.

MUJSO Continential II tube tester size 17" x 11" x 14" weight 18 lbs. \$269.50

14" weight 18 lbs.

GIVE STOCK

PAGE NUMBER ON ORDER.

SM152

SWEEP & MARKER GENERATOR

\$45000

The SM152 Sweep and Marker generator is the only generator that goes all the way. Full coverage from 10 megaherta to 920 megaherta. Covers all TV IFs, VHF channels. UHF TV channels and FM IF and RF VHF channels. UHF TV channels and FM IF and RF frequencies. Calibrated were no output and sweep width for more precise alignment. IF spot band for pre-alignment adjustments and troubleshooting Marticles for channels 4, 5, 10 and 13. Twelve IF and chroma markers, all crystal controlled, 39,78,41.25, 41.67, 42.17, 42.67, 44.25, 45.78, 47.25, 4.5, 4.08, 3.58, and 3.08 MHz. Zero baseline and simple hook up make the SM152 the most complete generator worldble.

SM152 Sweep and Marker use 14" x 10" x 6"

BE256, 7 in 1 DC Bias Supply. A must for solid state and tube receivers for alignment and AGC trouble-shooting. Three separate and isolated bias supplies:



955

Versatile ohms-volts-milliameter effectively tests both vacuum tube and semiconductor circuits. Accurate current section can be used for AC and DC measurements from 10 µA to 1 A in seven 10 dB ranges. Low i-volt scale allows accurate rerading, as low as 4.05 volt, while giving good indications down to 0.01 volt. Direct readings may be made to 1.000 volts, Single ail-purpose DC/AC/ohms/mA Uni-1-robe high input impedance using FET: position-peak measurements of VAC and mA on large 6½ meter: 7 non-skip ranges. In professional 10 dB steps; AC line or hattery operated. VAC Rangess: Peak to peak, 0-2.8, 8.5, 28, 85, 290, 850, 280, 1,000, 300, 1,000. AC and DC Current Ranges: Saine as voltage ranges the respective of the peak of the pe

Eico Model 242 Solld State FET TVOM-Wired. Net.... \$84.50 Eico Model 242K Solid State FET TVOM Kit-Net Ea... 68.95

#### MODEL 240 SOLID STATE PET TVM

Especially adaptable to semiconductor circuit testing; entirely suitable for aervicing vacuum tube equipment. Low 1-volt scale allows accurate reading, as low as 0.05 volt while giving good indications down to that volt. Direct readings may be made to 1,000 volts. Single all-purpose DC/AC/obms Uni-probe: PET extremely high impedance input amplifier: peak-to-peak AC measurements: 7 non-skip ranges, in professional 10 dB steps; AC time or baltery operated. VAC Ranges: Peak to peak, 0-2.8, 8.5, 28, 85, 280, 150, 2800. AC rms Sine Wave end VDC Ranges: 10-1, 3, 10, 30, 100, 300, 1,000. Input Impedence: DC to 1 megs; AC to 1 negs, Frequency Response: 25 Hz to 2 MHs. Ohms: 0.2 ohm to 1000 megs in 7 ranges. Meter Movements 4½, 200 gA. Power Raquired: 105-132 VAC; or three batteries, 9 V (NEDA 4600), and one 1.5 V D cell: 1.4 VA. Size: 5½, w, x 5° d. x 8½, b. Weight, 6 lbs.

Eice Model 240 Solid State FET TVM-Wired. Net Ea., \$79.95 Eico Model 240K Solid State FET TVM Kit-Net Ea.... 59.95

#### MODEL 33D SOLID STATE OF SIGNAL GENERATOR

MODEL 33D SOLID STATE RE SIGNAL GREEKATOK
For aligning all types of television sets, AM and FM fadtos and
communication gear. An excellent source of modulated or unmodulated RF and audio signals, it displays exceptionally good
waveforms. Five fundamental bands cover 100 kHz to 34 MHz.
Frequencies easily and accurately set with vernier control; calibrated front-panel, modulation-adjustment control; 409 Hz audio
output at front panel; provision for modulating RF with internsi
or external signal source RF Fundamental Frequencies: 110k kHz
to 34 MHz to 30-bands, Output: More than 300,000 gV on any
band into 50-olum load, RF Coarse Attenuation: Three steps.
RF Fine Attenuation: 0 to 100%, lenternal Modulation: Approx.
400 Hz, from 0 to 100%, Power Required: 106-132 VAC, 50/60
H3, I.7 VA, Shae: 8½° w. x 5° d. x 7½° h. Weight, 5 lbs.

Elco Model 338K Selid State RF Signal Generator Kit-

MODEL 955 IN-CIRCUIT BRIDGE-TYPE CAPACITOR TESTER MODEL 955 IN-CIRCUIT BRIDGE-TYPE CAPACITOR TESTER Provides short and open tests; includes Wien bridge for capacitance tests, with shunt resistance balancing provision that permits in-circuit measurements even when shunting resistance is low. One coax lead to rail tests; celacitable, with mike connector coupling to unit. Shorts: in or out of circuit, shunt rests, as low as 1 ohm; reliable up 10 2.000 µf; max. test. 6.3 VAC (open leads; decreasing with decreasing impedance. Deen: In or out of circuit; tests capacitors as small as 15 pF. In-circuit, shunt may be as low as 36 ohms above 250 pF. 7K ohms at 15 pF. Capacitance; 0.1-30 µf using Wien bridge with shunt balancing permitting a 10% accuracy. In or out of circuit, Power Required: 8 watts, 117 VAC, 60 Hz. Indicator Tuets: EMSA/GBGS. Size: 5½" w. x. 6" d. x 8½" h. Weight, 6 lbs. hedel 955 Capacitor Tester—Wired, Net Each......... \$44.95 Model 955 Capacitor Tester—Wired, Net Each.............. \$49.5

MODEL 1020 SOLID STATE POWER AND BIAS SUPPLY A completely translatorized, low-rippic, continuously variable DC power and bias supply. Two 2N256 power translators permit output voltages up to 30 V. Maximum load current, 300 mA. Max, rippie (120 Hs) full load, 0.005%, Size: 4" w, x 5½" d, x 5" h. Model 1820 Power and Blas Supply—Wired, Net Each... \$34.95 Model 1820 Fower and Blas Supply Rit.—Net Each... 25.95

MODEL 1030 REGULATED POWER SUPPLY
Two independent sources: Bias, with 0-150 V at 2 mA: output, with 0-400 V at 150 mA. Line change of =10 V causes less than 5 V output change. Has unregulated flament voltages of 6.3 V (12.6 total) at 3 A. DC milliammeter and voltmeter on front panel; separate test circuit/filament power switches. Ripplet 3 nV rms. Model 1030 Regulated Power Supply—Net Each. \$109.95 Model 1030 Regulated Power Supply—Net Each. \$109.95

#### MODEL 10645 BATTERY ELIMINATOR AND CHARGER

Heavy duty battery eliminator drives any auto radio, mobile and marine transceiver. Also charges 8- and 12-volt storage batteries. Continuous output voltage adjustment on both ranges; LC filter with heavy duty choke; tused primary and automatic reset nverload relay in the secondary; heavy duty silicon rectifiers. Output Voltages; 0-8 VDC, 0-16 VDC. Current Ratines; 10 amps continuous, 20 amps intermittent at 0-8 V; 6 amps continuous, 10 amps intermittent at 0-16 V. AC Rippie; 1.5% at 2 amps, 2% at 6 amps and 4.5% at 10 amps at 0-18 V; 0.3% at 2 amps, 12% at 6 amps and 4.5% at 10 amps at 0-18 V; 0.3% at 2 amps, 12% at 6 amps and 1.5% at 10 amps at 0-18 V; 0.3% at 8 amps at 0-18 V; 0.3% at 8 amps at 0-18 V; 0.3% at 9 amps, 2% at 10 amps at 0-18 V; 0.3% at 8 amps at 0-18 V; 0.3% at 8 amps at 0-18 V; 0.3% at 8 amps at 0-18 V; 0.3% at 9 amps a

MODEL 379 SOUD STATE

SINE AND SOUARE WAVE GENERATOR

1064-5

249

Eice Model 379K Solid State Sine and Square Wave Generator MIT-Net Each Solid State Sine and Square Wave Generator MODEL 232 PEAK-TO-PEAK VIVM

MODEL 232 PEAK-TO-PEAK VIVM

For its measurement up to 30,000 VDC with any VIVM of control of the peak to-beak measurement of complex voltage waveforms on separate scales. Provides dynamic rms and DC voltage measurement ments with negligible circuit leading. Exclusive Elco Uniprobe selects all measurement functions. Offers exceptional stability and cacuracy: 7 non-skip ranges on every function. 4% meter the grant burn out: circuit. Calibration without the control of the peak in the control of the

Model 515 Pertable Tube Tester Mt.—Net Each. \$74.95

Model 515 Pertable Tube Tester Mt.—Net Each. \$74.95

Model 515 Pertable Tube Tester Mt.—Net Each. \$9.95

Model 515 Regardance and capacitors of the company of the

MODEL OBO TRANSISTOR AND CIRCUIT TESTER
Cheeks germanium, alileon and selenium diodes and rectifiers.
Trensistor Measurements: Icaso and Icaso with separate ranges
for signal and power types: DC beta in two ranges 2-30 and 20300; AC beta indirectly on separate scale, using incremental
differences in collector and base currents of DC beta to find AC
beta. DC Gurrent Ranges: 50 μA, 500 μA, 5 mA, 500 mA,
500 mA.
DC Voltager 5 and 50 volts. Resistance Ranges x 1 (0-2K. 12 ohms
center), x 100 (0-200K; 12,000 ohms center), and x 10K (0-20
megs: 120K ohms center), Size: 5 K° w. x 3° d. x 6 K° h.
Model 680 Transistor and Circuit Tester—Wired and tested.

Met Each.

MODEL 150 SOLID STATE SIGNAL TRACES

379

150

1 7 01 12

330

MODEL 150 SOLID STATE SIGNAL TRACER
For convenient and rapid servicing of both solid state and vacuum tube equipment. Indispensable in troubleshooting AM, FM and Troubles are provided. Bigli frequency RF point consect crystal demodulator and direct audio. An output transformer is provided to permit the checking of a suspected defective component by substitution is any type of vacuum tube or transistor amplifier. Speaker, mounted on front panel, may be used as a substitute for a questionable one. Independent RF and audio inputs; speaker and ealthrated meter output indicators; 400 mW continuous power output; substitution amplifier, output transformer and speaker. Outputs; 400 mW. Imput for Rated Output; RF, i mV; audio, 63 mV. Mum: Better than 60 dB below 400 mV, Meter; 200 µA novement. Power Requisited: 155-132 VAC, 50/60 Hz, 5 VA. State Styl, w. 8 of d. x. 1½ h. Weight, 6 lbs.

Eico Model 150K Solid State Signal Tracer Kit-Net.... 49-95

Designed as an oscillator capable of generating frequencies required to test all sudio and supersont equipment. Low distortion signals make it especially suitable for checking high fidelity amplifiers and transducers. Ideal for sonar testing. Simultaneous sine and square wave outputs; covers 20 Hz to 2 MHz in 5 bands; low distortion Sulser feedback strettle using FET square wave rise distortion Sulser feedback strettle using FET square wave rise time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage: Sine of time better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage Sine better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage Sine better than 0.1 µsec. Fraquesecy Range: Sine wave. 20 Hz to 200 kHz. Output Voltage Sine output Curve Tracer Wite. Net. \$1.40 to 20 kHz. Output Voltage Prosse

#### HIGH VOLTAGE PROBE

For safe measurement up to 30,000 VDC with any VTVM or 20,000 ohms/voit VOM. Includes choice of high quality multiplier resistor to match nost popular instruments. Model HVP-2 High Voltage Probe—Wired. Net Each... 39.95

beta, DC Current Rangest 50 µA, 500 mA, 500 mA, 600 mA

#### "NEW LOOK" IN PANEL METERS MC GEES' 1970




# MIDLAND


## Precision WIDE-VIEW

**Panel Meters** 

New, Highly Readable and Accurate Design



An all-new fine of quality Midland panel meters. Designed for 21/2% accuracy and easy readability. High impact construction with clear aerylic faces. Missing coil permanent magnet movements in all meters except AC Voltmeters which have rectifier type movements. 4" meter faces measure a big 4-5, 16" x 3-1/4" and mount in 2-1/2" fiole. 2" meters have 2-3/8" x 1-13/16" faces, mount in 1-1/2" hole. All models mount in panels up to 1/4" thick and have zero adjustment series. Individually boxed.



#### 4" Panel Meters

23-226- 0-50 UA DC Microammeter

23-228-0-100 UA DC Microammeter 23-230-0-500 UA DC Microammeter

ABOVE \$4.95 EACH

23-320-0-1 MA DC Milkummeter 23-321-0-10 MA DC Milkummeter 23-322-0-100 MA DC Milkummeter 23-323-0-200 MA DC Milkummeter 23-324-0-300 MA DC Milkummeter 23-325-0-500 MA DC Milkummeter

ABOVE \$4.49 EACH

23-420-0-15V AC Voltmeter 23-421-0-150V AC Voltmeter

23-521-0-15V DC Valtmeter

23-523-0-100V DC Voltmeter 23-524-0-300V DC Voltmeter 23-525-0-500V DC Voltmeter

ABOVE \$4.95 EACH

23-620-0-15A DC Ammeter 23-621-0-304 DC Ammeter

ABOVE\$4.49 EACH ABOVE \$4.95 EACH

#### 2" Panel Meters

23-206-0-50 UA DC Microammeter 23-207-56-0-50 UA DC Microammeter 23-208-0-100 UA DC Microammeter

23.411-0-150v AC Voltmeter ABOVE \$3,49 EACH

23-210-0-500 UA DC Microammeter

#### ABOVE \$3.99 EACH

23-310-0-1 MA DC Milliammeler 23-311-0-10 MA DC Milliammaler 23-312-0-100 MA DC Milliammeter 23-313-0-200 MA DC Milliammeter 23-314-0-300 MA DC Milliammeter 23-316-0-500 MA DC Milliammeter

23-515-0-500V DC Voltmate ABOVE \$3.49 EACH

23-610-0-15A DC Ammeter 23-611-0-30A DC Ammeter

ABOVE \$3,49 EACH ABOVE\$3,99 EACH

Meters of this type are rapidly gaining popularity because of their accuracy, mechanical precision, and quality appearance. There are cheaper meters, but our judgement is that the quality of imported meters is well worth the little difference. Made to our rigid specifications by a leading meter manufacturer.

DC MICROAMMETER

Moving coil, permanent magnet type movement, 2/, % accuracy for entire scale, clear plastic cases, silvered dials with center zero adjustment screw. Face is unbreakable clear plastic, See illustration for dimensions.

Series	0-50	0-200	477
60-165	50-0-50	0-500	
SPECIFY	.0.100		EACH
RANGE	DC MILLIA	MMETER	
Series	DC MILLIA	ALIVE T LAK	A OF
60-158	0-1	0-200 \$	-7 43
	0-10	0-300	
SPECIFY		0-500	
RANGE	0-100	0-300	EACH

BUILDERS SPECIAL
OHMS. AC & DC VOLTS AND DB





INC-301K

Special \$4.95, Metal Cabinet 8-3/8'\*x11-1/8'\*x 6½'' deep. Removed front panel 8½x11-5/16'' serves as meter mounting and escutcheon. The American made meter is 6'' wide and 5'' tall. Visual scale area 6'' x 2½''. Meter is slightly higher than 1000 ohms per volt DC. Scale xhow Ohms, AC and DC Volts, and DB. Originally it was part of Sylvania Model 301 V.T.V.M.

This is not a VTVM Kit, only parts shown are offered. Shipping Weight 5 pounds.



AU VOLTMETER

AC meters are rectifier type, 1000 ohms/volts; otherwise same description as DC meters.

Series 60-150 0-15 0-150 \$295

Series		OLTME	rer	\$ 7 95
60-152 SPECIFY RANGE	0-30 0-200		0-300 0-500	EACH
	"DC"	AMAME	TEDS	

Series 60-171 SPECIF 0-10 amp DC

0-30 amp DC DE JUR 0-3 VOLT D.C. Stock No. DCV-03

10 For \$19.00

Dejur 2-5/8", 0-3 Volt DC, Volt Meter. Sens-itivity 1000 ohms per volt with 0-3 Volt DC Sc-ale, built-in multiplier. Add external resistor if you want this to read higher than 3 Volts. Stock No. DCV-03, Sale price \$2.00 per meter, 10 meters for \$19.00. Shipping Wt. 8 Oz. each.

CLEAR FACE METER

Cat. No. \$449 60-174 1-5/8" Square

A necessity for the amateur operator and SW listener, for giving signal reports and tuning the receivers. Meter has a basic movement of P-1 MA. Calibration is from 0 to 9 "S" units, plus 10 to alus 30 db, and full scale value of 1 MA is divided equally from 0 to 5 and -0-10 on dial face.



#### MIDLAND 4" and 2" S Meters

Model 23-710-2" \$4,95 Model 23-720-4" \$5.95

Model 23-696-2" Illuminated \$5.95

Model 23-697-4" Illuminated \$6.95

Available in illuminated and non-diluminated unders 4" meters have face measurements of 4-3 8" x 3-1 4" and fit a 2-1/2" hole in panels up to 1/4" thick 2" meters measure 2-3/8" x 1-3/4" and fit a 1-1/2" hole. Top scale, 0-19 and +10 to 30 db over 9, 2nd scale; 0-10, 3rd scale; 0-5. Easy-to-read, Clear acryllic face.



#### 4" and 2" **VU Meters**

Model 23-711-2" \$4.95

Model 23-721-4" \$5,95

Model 23-715-2" Illuminated \$5.95

Model 23-725-4" Illuminated \$6.95

Choose illuminated or non-illuminated models. Same dimensions as "S" meters above. Freq. Range: 30-7,500 Hz. Impedance: 3,900 ohms ±200 ohms across 500,600 ohm line. Time Constant: 0.3 seconds for full scale deflection. Top Scale: -20 to +3 VU. Bottom Scale: 0-100% modulation. Accuracy: 2½%.

#### 3-INCH VU METER

Model 60-176 Calrad 3" valume meter calibrated in standard -20 to 3 VU and 0 to 100% ranges. 10K ahm internol resistance. "O" VU is 1.225 valts AC across meter connected to 600 ohm source. Housed in clear plastic case 3%" x 35 Model 60-176



# CLEAR PLASTIC FACE "VU" METER



1-5/8" Square Model 60-175

Accurately calibrated and marked -20 to Plus 3 VU on the upper scale and 0-100% modulation on lower. 1½" mtg. holes. Meter is boxed.

# 11/ INCH

VU METER

5399

Upper scale range read minus 20 to + 3 VU. Lower scale reads 0 - 100% modulation. Ac-Lower scale reads 0 - 100% modulation. Accuracy within 2%. Limiting resister included. Zero set screw adjustment, 11/4" square clear plastic panel. Bakelite screw mount type case. Overall depth 11/4". Depth behind panel including screw terminals and solder lugs is 1". Mouting hole diameter required 1-1/16". Mouting hole diameter required 1-1/16". Mounting hardware included. No. VUS

Net Price\$3.99 as

11/4 INCH

"S" METER \$349



Calibrated from 0 to 9 "S" units, with the scale terminating in +10 and +30 calibrations. Zero adjustment screw on front of panel. Jewel bearing movement. Has 0-1MA movement. 1½" square clear plastic panel. Bakalite screw mount type case. Overall depth 1½". Depth behind panel including screw terminals and solder lugs is 1". Mounting hole diameter required 1-1/16". Mounting hardware included. ing herdware included.

No. SM5

Not Price\$3.49 ea



2-1/4" SQUARE DC METER PANEL

MOUNTING era, Measuring DC current flow a \$5- reliberation by the State of the

\$2,25 Ea

# MC GEE OFFERS TERRIFIC VALUES IN VOLT OHM METERS



20,000 OHMS PER VOLT SERVICEMANS MULTITESTER

VOL TS

OHMS

MILLS

DR

23-101

\$995

I tick includes

less leads and ly, volt per

gree e A2-Volts 0 to 16-50-750

Volts 0 to 5-24-123-500-750

ma-0 to 50 tis, .mp. and 0 to 250

ma-0 to 10 tis .mp. and 0 to 250

ma-0 to 10 tis .mp. and 0 to 250

ma-0 to 10 tis .mp. and 0 to 250

ma-0 to 10 tis .mp. and 0 to 250

ma-0 tis .mp. and 0 tis .mp. and 0 to 250

ma-0 tis .mp. and

MITH TEST LEADS

Model 23-094

Economical 1,000 Ohm-Volt **Vest-Pocket Multimeter** 

20,000 Ohms/Volt Multimeter EASY-READ, WIDE-SWEEP 5-7/8" DIAL

MOVEMENT GUARDIAN CIRCUIT ... BURN-OUT PROTECTED McGEE \$1395 Net Each

MIDLAND Model 23-113

DC Volts: Q.6-3-12-30-120-600 (20, AC Volts: 3-30-120-600 (8,000 ahms

000 ohms per voltil DC Current: 50uA-0.6-60-600mA per volt)
Resistance: | 10k-100k-1M-10M phms

overload design. Burnout protected, Black high-impact case with wood-tone control panel. 5-7/8" wide x 4-5/8" control panel. 5-7/8" wide x 4-5/8" high x 2-3/8" deep. Lightweight multi-meter comes with batteries, test leads and complete instructions.

100,000 Ohms/Volt VOM with 25 Ranges



fratures that pesfessionals hash lar-inadright, black stad in introceed to olingia. Movement Guardian Chroni-prevents measy overland and but givened movement, big \$5\pi^{\text{oline}}\$ or ale month-action sylon values selector. IC scale in enemath for transactor men-betton larks allows measurements.

Model 23-137

2495

dadel 23-137-100.000 Ohms/ Volt Multi



Deluxe Grand Master Model 80M Multitester

BURNOUT PROTECTED

095

ANGES: (RX1) (RX100) (RX10,000) (RX10,000) (Rxpanded low end scale "30 center" 0 00005-.01uF 001-0.2uF 20db to +63db (5 ranges)

100.000 Ohm/Volt Multimeter

CALRAD

MODEL 134.95

Full Size 4-Inch Mirror Scale RANGES: DC Volts: 0-500 MV-2.5-10-50-250-1000 100,000 ohm/volt sensitivity

AC Volts: 0-2.5-10-50-250-1000

12,500 ohm/valt sensitivity
Volume Level: -20 to +62 db in 5 ranges
7" high x 5\%" wide x 3\%" deep.

POCKET SIZE 4,000 OHM PER VOLT MULTITESTER Model TK-401

USS SPEN CELLS

a constitution

| Uen 2 P.EN. CELL 8 | DC Velns | O-5-23-125-500-2500 | (4.000 chms per voir) | O-10-50-250-1000 | (7.000 chms per voir) | O-10-50-250-1000 | (7.000 chms per voir) | O-250 MA | Resistance: O-10K - O-1 Meg. Mid-Scale: -0 O-0-5-5 K Ohm | Decibels: -20 to +22 db | O-10-5 K O-10 | O-10-25 k | O-10-5 K O-10 | O-10-5 K O-1

Decibels: -2016 722 db
An economical valicable milliammeter with
3½" scale. Features an expanded realtance scale that enables accurate low ohm
readings. Uses 250 UA D'Arianval meter
movement, Malded plastiz case 4½" H, x
3½" W, x 1" deep. Furnished with test
leads, instructions and battery.

OHMMETER MODEL 362 SALE PRICE \*24\*

BIG BUY!

HALF PRICE

\$50.00 Value

Sumpson

a 5%" x 21/2"

5-Pc. PANEL SET

Build Your Own Projects wish: 3 Poef Boards 1 Aluminum Plate 1 Bakelite Panel

31/2"X6"

Stock No. 842

NEW POCKET-SIZED MULTIMETER

Brand new pocket multimeter designed for accuracy in the field or on the technician's bench. Easy-to-read heavy black numbers earefully scaled for quick, exact heavy black numbers carefully scaled for quick, exact reading. Crystal clear high impact plastic front takes rough treatment and gives full scale view. Popular swinging-lever nylon range-selector switch allows easy selection of ranges and stands up to continuous use. Dimensions: 4-3 4" High x 3" Wide x 1-1 4" Deep. Other outstanding features include a heavy duty bakelite case, precision 250uA D'Arsonval movement, pin jacks. Each unit is supplied with batteries, test leads, leather case and instruction manual. \*\*Association\*\* ACOUNTED TO SENTING AND TO SEN MEASURES: rough tach unit is supplied with batterica, test leads, leather cease and instruction manual.

WITH LEATHER CARRYING CASE
With LEATHER CARRYING CASE
On the content of the conten

MGC

to Times better high
ohms readability over
meters using I or 2 pen
cetts.

Uses pen lie cell and 15 valt bottery
the same size as Everody 504 NET EACH FULL SIZE PROFESSIONAL



AC volts: 0.6.30-120-600-120-6 DC current: 0.50A-60MA-600MA Ohms: 0.6.000-600,000-6MEG.-60MEG.

10 TIMES BETTER HIGH OHMS
READABILITY OVER METERS
USING ONLY 1 or 2 PEN CELLS. SALE PRICE
OUR NEW MODEL 23-108 IS
EQUAL TO METERS SELLING FOR \$159

BEST BUY

r valt unit that uses only a 3 valt battery

**BIGGEST METER BUY** A deluse accurate highly sensitive instrument having many features required in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing modern electronic equipment, A 20 UA O'Arsonval meter and 1% of precision resolved in testing DELUXE VOLT-OHM MILLIAMETER EXTRA SENSITIVE 50,000 OHM PER VOLT

DC Volts AC Volts DC Currents

MIRRORED SCALE ELIMINATES PARALLAX ORED SCALE ELIMINATES 0-0.6-3-12-6-300-13-00 0-3-30-120-300-17-00 0-20 UA.-6-06-000 MA. 0-10K; 1 Meg.: 10 Meg.; 100 Meg. 60 6K 60K 60K -20 to +61 db

Reading at center of scale.

3

を

TEST LEADS INCLUDED

Clark/300

Without sacrificing performance, precision or comfort. David Clark Co, has been eminently successful in producing a budget priced stereo headset, the Clark/300 It is now possible for everyone to experience the intimate luxury of stereophonic listening. Children revel in the "just for me" performances and learn to enjoy and understand more fully the music of the masters. Ask to experience stereo in its fullest dimension at your favorite dealer. He has the full Clark line to show you and invites your interest. you and invites your interest.

SPECIFICATIONS
FERGUSHOY Range: 20 to 17,000 Hz = 10 ft. zoil cord with molded on plug no extra cheige (stendard equipment) = Impedance: 8 ohms = Weight: 15 ounces





LIDLAND MULTIMETER New 50,000 Ohms/Volt VOM-22 Ranges

> 0-0.6-3-12-300-OC Voltage: 600 (50,000 ohms/

voltì

0-3-30-300-600 AC Voltage: (8.000 ohms/volt) DC Current: Resistance:

0-20ua-6-60-60 Ma 0-10K-100K-1 M. -10M, (80 ohms cen-

ter scale)

Decihels:

-20 to +57 in 4 ranges

Accurate test instrument features exclusive new Midland "midnight" black dial . . . mirrored for pinpoint readings. Movement Guardian Circuit automatically protects meter from overload and positively prevents movement burnout. Jeweled d'Arsonval movement with big 5" scale. Smooth-action 17-position nylon range selector. Special low-voltage DC scale for transistor service work. Precision 1% resistors used throughout. Recessed zero-ohms control features "off" position to prevent accidental meter damage. Rugged black high impact case resists chipping and breakage. Size: 5-5/8" x 4-3/4" x 1-7/8". Complete with batteries, test leads, and instructions.

-50.000 Ohms/Volt Multimeter

# McGEE Special TP-5 2000 Ohm/Volt Multimeter

**Bullt-In Overload Protection** 

Priced with 2 11/2 voit pen cells and test leads, with instructions.

TP-5 \$II.95

Two for \$23.75

\$799

metal back

Sensitivity; 2 000 Ohms Volts DC and AC. Ranges; DC Volts; 0-5, 25, 100 500 and 1000 volts. AC Volts; 0-5, 25, 100, 500, and 1000 volts. Resistance; 0-20K ohms and 0-2 megohms. DC Current; 0-500 microamps, 25 ma. and 500 ma. Decibels; %timum 20, plus 16 db. Size; 5½" tall, 3-5/8" wide, only 1½" thick. Meter Scale 3½" wide. Ship wt. 2 lbs.

Model TP-5; small Voit-Ohm-Meter 54... tall, 3-5/8" wide and 14/" thick with 34/" meter face. This meter is ideal for the Radio-TV Service man and has been used extensively by various Bell Telephone companies for the past several years. Compact and very rugged construction make this meter specially suited for service calls and hard usage and at the same time it is economical emough for the "Do-It-Yourself" once-in-a while user. Sensitivity 2000 ohms per volt. DC volts; 0 to 1000 in 5 ranges. DC current; 0 to 500 ma. in 3 ranges. Resistanct; 0 to 1.5 megohms in 2 ranges. Decibels; minus 20 to plus (odb equals .777 volts). A thin comact instrument of quality import, made by one of the foremost Japanese precision meter factories, especially for "IcGee buyers. This value cannot be cuplicated in an American made instrument for less than \$25.00. Complete





REDUCED SALE PRICE SALE PRICE 100 8795.00

The RCA LG-30 Pulse Generator produces steep-front pulses whose amplitude, length and recurrence are veriable, end it will modulate an RF wave with these pulses to approximately 100%. All diata are directly calibrated, graphs and tables are unnecessary,

# Pulse Generator

REPETITION RATE: 50 to 1,000 cps; secPlus or -57. PRINCIPAL PULSE: Length
from 0.1 to 2 microseconds. Length seco
Plus or 10 microseconds. Ingith seco
Plus or 10 microseconds. Top single
Fall time; 0.01 microseconds. Top single
circuit; 20% Maximum output open circuit;
plus or 20%. Maximum output open circuit;
plus or 20%. Cutuple positive or negative,
puts siduatable by a linear calibrated sitem
to the company of the co

#### Resistance Substitution Box

Catrad resistor substitution unit in hand

some box. Dual range.
Low—15-10K ohms High—15K 10 meg Red and black insulated alligator clips 36" long. Easy to find resistance needed in most electronic circuits by rotary switches in two ranges indicated on panel of box. Fast and

accurate for trouble-shooting resistors which may have changed in value or burned out.

Stock No. \$3.95 RSB

Shipping Weight 11b.

\$\$\$ SAVE \$\$\$ LAST MINUTE PURCHASE A 1972 McGEE SPECIAL



FULL RANGE SPEAKER

> STOCK NO. CTS-15-32-8

PRICE

4.95

2 for \$29.00

2 lb. Ceramic Magnet, 11/2" voice coil 8 ohms.

Shipping Weight 11 lbs

60-INCH LUCS TEST LEADS
4 INCH PRODS anters test both the Cot Ma nor both coupling one TL-20

POMONA MEW COT TEST PROBE WITH BUILT-IN METER



MODEL 2900

Shipping Weight 11b.

POMONA ELECTRONICS CO., INC.

\$19.95



Shipping Weight 1 1b

INSULATED COLOR CODED ALLIGATOR TEST LEAD CLIP SET

the action would 99¢

FXTRA FLEXIBLE Capacitance Substitution Bax

Calrad condenser substitution box with 9 ranges from .0001 to .22 mfd. Fast selection of any one of 9 ranges is available, and all condensers are of the moisture proof tubular type rated at 600 volt.

Complete with 36 inch red and black test leads with alligator clips. CSB 2.95



50" LEADS Meter End Phone Tips

RETRACTABLE TEST LEADS

TEST LEADS



Extends to 76 inches, retracts to 16 inches. I ea. phone tip test prods Red and Black are

#### Perma Power for Better Color Television Color-BRITE COLOR-BRITE **Picture**

**Tube Briteners** 

Color-Brite brings out the tost sharpness and details of fading enginess and details of fading color picture subes it provides increased filament voltage to boost the electron emission and return full contrast and color quality to the 3 gun color picture tube.

Color-Brite is eutomatic ..., no switching or wiring. Just plug it in between Color Tube and Color Socket and picture tube brights

for an extra year or more. Model C-501 Model C-507 for round tubes (70° shell neodineprat 12-pm base) Parattel-wired filament Heeter rating: 6.3 vots. 180 amps Shipping Weight 1 tb.

Model C-511 Modef C-511
for rectangular tubes
(90' small-button diheptal
12-pin base)
Patalitel-seried filament
Heeter reting: 6.3 volts. 800 MA
Shipping Weight 1 lb.

\$5.85

Isolation **Briteners** 

The No Boost Calor-Brite Isolation Britener corrects the color problems that occur when a cathode to filament short Causes loss of the black and white. By isolating the short, it rastores the black and white information that chares to

The Brite Line.

white information that gives the color picture its quality.
Note: Color-Barie corrects for only one cathode to file
short if e second short occurs, the picture tube
be replaced. Model C-502

for round tubes (70° shell neodiheptal 12-pin base) Parallel-wired filement Heater rating 6.3 volts. 160 amps

Model C-512 (90° small-button d heptel 12-pm base) Heater rating: 6.3 volts. 800 MA Shipping We

\$7.25

Model Graze
for 110° button base sets
(RCA type)
series or parallel
any heater rating
Shipping Weight 6 og.

Model C-412 to 110' button base sets. (RCA type) swires-wired filaments. Heater ratings. 2.34 volts. 800 amp. 2.68 volts. 450 amp. 8.3 volts. 300, 450, 800 amp. B4 volts. 450 amp. Shupping Weight B oz.

\$1.80

Madel C-212

Shipping Weight 8 oz.

#### \$5.85 \$7.25 Products for Better Black and White Television Model C-202

for duodecal base sets series or parallel any heater rating Shipping Weight 8 oz.

TU-BRITES warm-up filaments reted to 2.34 and 2.67 volts. On these newer picture tubes, you cannot safely volt sets. Choose either a properly volt sets. Choose either a properly vated angle purpose Britishers, or a versarile Perma-PowerTu-Brite. Tu-Brite takes the worry out of britening.

lithe Base is Right, the Boost 👛

VU-BRITES Complete coverage . ... with single-purpose economy

vur-orites are trace encount economy veries, for all black and white picture tubes, electrostatic prefectionagnetic focus. Series or parallel models are available, with units for any base type, any heater rating.

Model C-401 for duodecal base sets paraffel-wired filaments Heeter ratings: 8.3 volts. 300,450,500 amps. Shipping Weight 8 ez.

99¢



Model C-402 Heater rating: 6.3 volts: 600 amp hipping Waight 8 oz. 99¢

Model C-411 for 110' button base sets (RCA type) parallel-wired filaments Heater ratings\* 6.3 volts .300 ,450 .600 amp \$1.49

Restores COLOR balance when one gun fades.

Lets you adjust the biss of the weakened gun. A color brightner may be added later when tube aging dulls the entire picture.

Complete with spliging con-nectors

Perma-Power

SINGLE BRITE

COLOR GUN

CONTROL

Stock No. Price Model B-150 \$4.80

Universal TV Tube **Briteners** 

Perma-Power's unique design allows operation as constem voltage transformer in parellet wired sers, constem current transformer in series wired sets For isolation applications as well ea retieving cathode-lifament shoria. Boost or No-Boost.

Model C-301 Model C-311

base sets

series or parellel

Kester rating: 6.3 volts .600 amp

Model C-301

series or parellel Heater rating: 6.3 volts .600 amp Shipping Weight 8 oz.

\$2.67 \$2.98

TALL TEST SOCKET TUBE ADAPTERS

# **Vu-Brites**

Complete coverage . . . with single-purpose economy!

Vu-Brites are the efficient economy series, for all black and white picture tubes, electrostatic or electromagnetic focus. Series or parallel models are available. with units for any base type. any heater rating.



Model 2-414

5 700

Model C-414 for miniature base tubes series-wired filaments Heater ratings: 4.2 volts .450 amp 6.3 voits .450 amp (for AC sets only)

Shipping Weight 8 oz.

#### C-Brite

The C-Brite is a britener, it offers two way performance, series or parallel, with the convenience of stocking only one unit for either application.

Model C-201 for duodecal base sets series or parallel Heater rating: 6.3 volts :600 amp Shipping Weight 8 oz.

<sup>\$</sup>1.49

B

## POMONA ELECTRONICS

# Color TV Test Accessories

Pomona Electronics

NOVAR-6JE6 CATHODE CURRENT HORIZONTAL DUTPUT COLOR TEST ADAPTER COMPACTRON - 6/56
CATHODE CURRENT HORIZONTAL
OUTPUT COLOR TEST ADAPTER



MODEL 2599A NET 3.75

1 550 Dro Din Carson

1.75



MODEL 2712A NET 3.95 COLOR-TUBE SOCKET CONVERSION ADAPTER

This bingle adapter will date you to lead both me new fortiers and ICA color tools me new fortiers and ICA color tools and your person for requirement. Provides and your person for requirement with 100 mg 2001

Because Ibyl Manistre Oriental Becket, 108 Them.

Plug Bed: Non-third Page 1844, AM.

Bang.

MODEL 2276 NET 5.95 CRT CONVERSION ADAPTERS

MODEL 1447

NET 1.95

MODEL TVS-7

NET 1.65





MDDFI 1449

MODEL TVS 8 NET 1,75



MODEL 2610

NET 2.55

MDDEL TVS.9 NET 165



MODEL 1779 1 PM NOVAE NET 2.25

MODEL 2749

NET 3.25

MODEL TVS-12

MODEL 2742 PIN COMPACTEUN NET 3.55

1.70

MODEL 1451 NET 2.25

MODEL 1710

NET 2.55 TEST SOCKET ADAPTER HOLDER

MODEL 2898 Color: Green

**NET \$2.50** 

The holder accepts up to seven socket adaptor longer adapters of the seven socker adapters of 1\%" in diameter or less, and six adapters of 1\%" in diameter or less. Holes at both ends of the rack accommodate 12 service tools, Mounting holes are provided for easy installation on any vertical surface, Fabricated from cold rolled steel with baked enamel finish.

COLOR-TEST ADAPTER



ter Center Tolorypass Picture Tubes Presented for again year MODEL 2380 NET 4.95

CATHODE RAY TUBE TEST ADAPTER



MODEL TVS-2 NET 7.45

MODEL 55-7

-33-

MODEL SS-8

MODEL 55-9

POMONA ELECTRONICS CO.,

MULTI-CORDER 8 (Model BM-2900) Features: Combination FM/FM-Multiplex stereo radio and 8-track tape playerrecorder; records stereo music from any stereo station onto a blank 8-track tape; has 16 watts output

THE UTMOST IN 8-TRACK CAR STEREOS



SPECIFICATIONS/MODEL MAXI BM-2900 FM-FM MULTIPLEX RECORDER

LESS SPEAKERS STEREO TAPE & RECORD Number of tracks—8 (plays and records

stereo ar monaural) Tape Speed-3% in. per sec. Tape Program Selector: Automatic and/or manual Bias Frequency: 60KC

Wow/Flutter-less than 0.25 % Full Tonal Control Power Output: 6 watts per channel [RMS]
Erasing: A.C. erasing: 60KHZ

FM RADIO AND TOTAL COMPLEMENT Tuning Range: MC-88-MC-108 Automatic Frequency Control man Lighted FM Tuning Dial 1117 1111 12 Transistars, 13 Diodes Integrated Circuits: 8 tuned circuits Sensitivity: 10 microvolts or better Low Battery Drain-approx. 1 amp. FM Stereo Separation: more than 20 db Dimensions: 7 1/8" W x 2 1/8" H x 8" D

Net Weight: 6 lbs. Shipping Weight: 7 1/2 fbs.

The brond new "MAXI" B-trock, allows possible you to record your own chairs of male fallows possible you to record your own chairs of male fallows possible in the built-in FALFAN Sereo Redow Which is truly the maximum in stereo elegance. Simply insert any blank b-trock tope certridge, press the button marked "it", tune in any fifth Sereo broadcast, now you are ready to record, test press in the red record button and sevent thill the musc is over before releasing the button.

BEST BUY IN AMERICA FOR

# Boman dstrosonix

SOILID STATE EIGHT TRACK CAR STEREO TAPE PLAYER Mitey Mini Car Stereo-8 PLUS

Model BM-909



4-Channel Adaptor for Car Stereo Tape Players & Stereo Radios Model OA-1 OUADSONIC PLUS



Complete Tape Player & Adaptor & 4, Stereo 5'\* Speakers in beautiful flush mounting grills

Complete Tape Player & Adaptor plus 4-5" 3 oz. Speakers m unted in beautiful perferated bright metal grills. Easy to mount in the car.

BM-909-0A-1

\$59.95 value, McGEE SPECIAL \$39.95 speakers for both radio and tape.

BOMAN BOMAN

8 TRACK CAR STEREO TAPE PLAYER & RADIO COMBINATION

BOMAN

WITH AM-FM MULTIPLEX RADIO COMPLETE

MCGEE SPECIAL PRICE AUTO SOUND LESS SPEAKERS CENTER.



dial built into cartridee door THE IN DASH GENERATION IS HERE

THE ULTIMATE SOLUTION TO THE THEFT PROBLEM

Ajusts to your dash.

AM/FM MPX & 8-TRACK -- A complete universal sound center which provides a true custom in-dash installation. BM-1100-UN offers AM/FM multiplex stereo radio with the versatility of an 8-track car slereo. Also, the BM-1100-UN incorporates a fully adjustable uni-chassis. pandable chassis adupts to any dash from 5%" to maximum adjustment of 6%." This combination unit has push-button program selector, digital culored channel indicator lights. BM-1700-UN turning dial built into cartridge door, thumbwheel tuning control, 22 transistors, 16

diodes and 12 watts peak music power per channel.

DIMENSIONS 6% Wx 6% D • 1% H.

WLIGHT, Sibs.

Stock no. RADIO SS-7 Price \$2.95 SPEAKER CONTROL

Radio/tape speaker control change over switch allows the use of same set of

We call this one our "King of the Road" for good

# LEAR JET STEREO 8

DELUXE AUTOMOTIVE 8-TRACK STEREO TAPE PLAYER with AM/FM, FM STEREO SIGNAL SEEKING RADIO

SPEAKER SET



\$200,00 VALUE McGEE SPECIAL \$13950

OVER

HAD ALL THE FEATURES OF THIS STEREO 8

NO OTHER 8 TRACK RADIO COMBO EVER AM RADIO

BY NATIONAL OF JAPAN

MADE

Sensitivity: 20 microvolts, R.F. Stage

TOTAL COMPLEMENT 34 transistors 1 F.E.T. (Field Effect Transistor)

WORLDS 24 Diodes, 3 Zener Diodes LARGEST Oimensions: 84" wide, 81/16" deep, 34" high Net Weight: 10% lbs: ELECTRONICS Shipping Weight: 12 lbs. Specifications subject to change without notice.

FM RADIO Tuning range: 535-KC-1610 KC Tuning range: 88 mc-108 mc, Automatic Frequency Control
Circuits: 6 tuned circuits

Edge Lighted FM Tuning Oial Circuits: 9 tuned circuits Sensitivity: 5.0 microvolts R.F. Stage **Automatic Signal Seeking** Multiplex-Monaural Switch Distance-Local Switch

COMPLETE WITH

BELLE WOOD REAL Deluxe HI-FI Stereo Speaker Kit. HI FI

AIR SUSPENSION CONE AND GIANT 7,2 OZ. MAGNET reason. We designed an automotive entertainment center for the discriminating person who won't settle for less than the ultimate. The Stereo 8° tape player has such premium features as cartridge eject, fast forward control, and illuminated program indicators to permit quick location of a favorite selection on an album. The built-in radios include all the most sophisticated features such as automatic signal seeking tuner with local-distant switching, multiplex-monaural switching, and stereo signal light. The absolute finest components and design make this best of all Lear Jet autoplayers truly the "King of the Road".

SPECIFICATIONS A-250 DELUXE AUTOMOTIVE 8-TRACK STEREO TAPE PLAYER with AM/FM, FM STEREO SIGNAL SEEKING RADIO

STEREO TAPE PLAYBACK

Number of tracks: 8 (plays stereo or monaural) Tape Speed: 3%" per second Program Selector: automatic and/or manual push-button Wow/Flutter: less than 0.3% total Full Variable Tone Control Full Variable Steren Balance Control

Loudness control for bass compensation Power Output: 4 watts per channel (RMS):

16 watts peak music power Cartridge Eject

119

# 8 TRACK STEREO AUTO TAPE PLAYER

MEDALLION IS AN AUTOMOTIVE NAME OF MIDLAND

**NEW! Deluxe AM/FM Stereo Radio** with Twin Big-Sound Speakers



Complete with Twin 6" x 9" Speakers and Grilles . . Outstanding Full-Range Sound!

Model 65-214

BEST BUY AM-FM MULTIPLEX

Full-Feature Listening with

#### **Pushbutton Convenience!**

- Switcheble AFC circuit assures drift-free FM Model 66-214

Medalinon's outstanding new auto radio offers great AM FM stereo insteming plus easy in-dean or under clash mounting. Powerful solid stere chassis with 17 transistors, 10 diodes, 2 integrated circuits. 4 the mistors, Signal pulling RF stage on both AM and FM, AGC circuit to stop blast and fade on AM illuminated slide rule. Turing dial with FM stereo indicator light.

Rich-sounding AM reception plus brillient FM Stereo Multiplex listening • Completely equipped for universal under-dash or custom in-dash mounting Two FM, three AM pushbuttons to preset whith leafter grain and to popular local settions systems. Complete with twin 6" a 9" speakers and FM stereo/mono awitch with stereo light grilles, mounting hardware, fused gover cord speaker cords, trim plate and inserts. Measures 1.7 8" x 6-1.2" a 6" Wt. 4-1.2 lbs.

Switchable AFC circult.

Model 65-506

Our Finest . . . Features Usually Found Only on Home Players!



LESS SPEAKERS

Our Finest Features Usually Found Only on Home Players! PRICE

Popular program "rapeet" circuit Controls for fast-forward, fine tuning

Slide controls for Volume, balance, tone

Convenient built-in map light

Full 8 watts power per chennel

Medaltion introduces the complete auto tape playar with the sound and features of a fiving room 8 track! Smooth-action slide controls for volume, balance and tone Precision rhumbwheel fine tuning Rocker switches for last forward, program repeat, mae light Automatic or manual track selection with lighted program indicator. 12-transistor chassis, full 8 wattls/charvel power. Frequency response. 30. 10,000 Mz. For 12-voll systems, positive or negative ground. With power cord, mounting bracket and screws. Black and chrome selet is 71\*22 ½1\*12.71\*
Weight 8 bis.

Model 65 506

medallion Model 65-502 Burglar alarm connects to horn

LESS SPEAKERS

Compact New 8-Track Auto Tape Player

- Burgler slavm connects to horn Motor shutoff switch for use with radio tuner cartridge
- Precision fine runing control
- watts per channel sound power Solid state 10-transistor chassis

#### Full stereo sound, priced for volume sales

- Compact cabinet mounts quickly and easily in any 12-volt car or boat
- High-power, 10-transistor circuitry de-livers up to 10 watts
- Automatic or manual program selection With mounting hardware, power cord

I ESS SPEAKERS

Model 65-500

McGEE Special ! §9N95 \$5900

Economy 8-Track Tape Player

- Compact design for car or boat
- Full stereo sound, priced for voturns sales

The basic auto stereo module, with 5 watts of sound power per channel individual thumbwheel volume controls. Automatic or manual track selection, high low tone switch, on oil indicator light. For 12 work negative systems. Frequence response: 50 10,000 RF Wring and handware induded Compact black and chrome unit is 7.0 x2 % "x65x", weighs 4 lbs.

#### 8-Track Mini Player Has **Locking Mount Bracket**

- Player key locks into the permanent theft-deterrent mounting bracket
- · Removable for safe keeping at night
- · Plays in optional home system below
- . 6 watts per channel sound power


10 000 Hz response. Black, chrome cabinet is just 7% "x2",8", weighs 7 lbs With mount ing bracket and hardware, cable and spare fuse, bracket keys 12 volt negative ground.

Model 65 505

LESS SPEAKERS

Model 65-520 Player key locks into theft

... or Play It at Home with Medallion's New Power System





- Converts model 65 505 car player to an 8 track home system
- · Headphone, auternal specker jacks

Model 65-505

\$3495

sides out, swrips up. larches with a larches with a larches plane too. But the larches plane too. But the larches with a larches with a larches plane too. But the larches with a la

Model 65 820



#### New 8-Track Player with **Built-in FM Stereo Radio**

- Powerful solid state chassis delivers 12 watts peak power
- Pushbutton tape program repeat circuit; fingertip fast-forward control
- Burglar alarm connects to car horn
- Modern, convenient slide type controls for volume, tone, balance

All the performance features and handsome styling of fine home units. High-power chassis has 20 transistors, 18 other solid state devices. Built-In AFC circuit locks in FM. Pushbutton controls for tape program selection, repeat circuit, fast-forward, tape/FM MPX. Tape program indicator lights. Fine tuning control for proper head alignment, Illuminated stide-rule FM dial with thumbwheel tuning control, stereo light, 30-10,000 Hz response. Stylish black and chrome face panel, wood-grained metal cabinet. 12-volt, negative ground. With burglar alarm mounting bracket, power cord. 8-1/2" x 9" x 3-1/4". Wt.: 7 lbs.

Model 65-508

LESS SPEAKERS

Convertible 5" Wedge Speakers

- Use as reer-deck wedge speekers or remove speeker and grille for recessed mounting
- 8ig 5" speakers with heavy-duty 5 oz. magnets

Rugged 2-piece black polystyrene cabinets for flush or surface mounting. 8-ohm speakers handle up to 8 watts each. With wire and mounting hardware in display box.

Model 60-179

NEW 1972: 4 CHANNEL QUAD AUTO STEREO

Model 65-212

A REAL MC GEE SPECIAL

LESS SPEAKERS Model No.: Description: 4 Channel Quad Auto Stereo

OME-2445

Dimensions: 7%"D x 8%"W x 2-7/8"H Engineering Features:

Instant Response" slide bar controls Tape Program Repeat Button

Fine-Tuning Control Eliminates crosstalk Channel Selector w/Program Lights

Individual four speaker balance controls Technical Specifications:

Circuitry 24 Transistors, 13 Diodes Power Supply. 12-Volt Negative Ground Tape Speed 3% i.p.s.

Tape Reproduction. 8-Track (standard), Quad-4 channel Power Output. 80 watts f.P.P. Less than 0.3% RMS Wow & Flutter

Output Impedance 4 or 8 ohm speakers Stereo Cassette Player medallion



 Instant front-loading with automatic or manual cassette ejection LESS SPEAKERS

· High-power chassis has 18 transistors, 6 other solid state devices

Trim, compact cabinet with modern thumbwheel volume, tone, balance controls

Full-fidelity stereo cassette sound for car or boat. Cassette automatically ejects at end of tape. Manual eject button doubles as a slide control for fast-forward and rewind. Power-on indicator light. Solid state amplifier delivers 12 watts total power. Frequency response: 40-10,000 Hz. 12-volt, negative ground. Attractive black and chrome face panel. With wiring, mounting hardware Measures 2-3/4" x 6-7/8" x 6-3/4" Weight: 6-1/4 lbs

## BELLE WOOD

Deluxe HI-FI Stereo Speaker Kit. AIR SUSPENSION CONE AND GIANT 7.2 OZ. MAGNET.

2 SUPER D 1/4 IN. B OHM HANG ON SPEAKERS FO UNDER DASH - FIRE WALL OR IN REAR DECK MTG, 12 FOOT OF LEAD AND SHAP ON CONNECTORS.

SHIP WT 6 LBS FOR SET OF 2 SPEAKERS

Stock No. 3820 PRICE

10 sets for

\$100.00



UNIVERSAL - MANUAL TUNED

AUTO RADIO

Mode C-51

FOR CARS - TRUCKS - BOATS

AMERICAS' BEST BUY UNIVERSAL AUTO RADIO MODEL C-51 UNIVERSAL AM MANUAL TUNED AUTO RADIO Combines trouble-free, solid-state circuitry and 7 high-gain transistors for moximum sensitivity and selectivity. Operates in ear, truck or boat with a 12-volt positive or negative ground electrical system. Mounting hardware is in-cluded for easy under-dash installation in all vehicles. Features 7 tuned circuits, environmentally stabilized circuitry, and a 4" diameter, 8 ohm internal speaker. Size: 6½"Lx5"Dx2"H.Ship. Wt. 5 Iba.

CRAIG # PIONIER CRAIG model 3126 SOLIO STATE STEREO



MOBILE STEREO TAPE PLAYER

should be your choice if you preter 8 track THE CRAIG cartridges. It gives you the finest in stereo sound and separa tion--and is a beautiful accessory for any car. "E-Z-JECT" cartridge release button, automatic program change, manual selector button, and computer-styled program indicator lamps make operation a breeze. Cartridge slot door serves as dust guard for heads and capstan. With twin-pack cartridges you

enjoy up to 80 minutes of music

Any Lear type B track 12 volt system, negati ground 1 amp play 3 amp change Cartridge Playing Time: Up to 80 minutes (been-pack) Tape Speed: 3 3/4 rps 7 3/4" W = 2-7/6" H + 9 1/2" D Wow and Flutter: Less than 0.25% rms 8 E 104 Output Power: Swatts (4 watts per channel)

CRAIG Signal / Horse Ratio Better than 40 dB model 3126

Crass-Tola Separati

SINCE 1920 AUTOMATIC he Mighty Mini MODEL Best Buy LESS SPEAKERS



10 Transistors, 1 Diade, 4 Fhamistors 25 Watti (P.S. Less Than 1.8 amp 4 or 6 ohm art Than Q.3% PMS

Universal FM/AM **Auto Radio**  For 6 or 12-volt systems, negative or positive ground Includes Separate

Convenient pushbutton controls

5" x 7" Speaker Powerful chassis has 12 transistres with A LITTLE KNOW tors, 8 diodes, 2 thermistors HOW CAN FIT MOST HOW CAN FIT MOST CARS AND TRUCKS.

Designed for custom dashboard installation or universal under-the dash mounting. Handsome trim plate includes leather-grain and walnut-tone inserts. Pushbuttons for FM, AM, sone, AFC, local/distant reception. Volume and tuning controls. Lighted stide rule dial. Complete with mounting hardware, wiring, speaker, order form for optional custom frim plates. Measures 2" x 7" x 6 1/2". Weight: 3-3/4 lbs.

# medallion FM CONVERTER



Converts present AM auto radios to FM/AM For 12-volt negative ground systems

- High-performance chas-sis with 9 transistors
- . AFC circuit locks out FM

casy, inexpensive way to add FM to cars equipped with AM radios. solid state or tube type. Lighted stide dial with thumb wheel tuning control. Pushbuttons for FM/AM, local/distant reception Black and chrome color high impact cabinet Includes leather grain and wood tone trim plate inserts, mounting hardware, antenna jumper cable, power cord. 1-5/8" x 7" x 5-7/8". Weight:

Midland 65-241 Sole Price \$24.95



 Big 10 oz. magnets Twin speakers Model 60-174

2 for \$19.50

Deluxe 51/411 Stereo Speakers

• Twin speakers have air suspension cone design

Big 10 oz. magnets . . . up to 10 watts each

Our linest stereo speaker kit. Big 8-ohm speakers have Our views server a speaker and any own to restended range response. Complete with black padded vinyl snap- on grilles, winning, mounting herdware. Display based,

CA-6393

**52**95

CARTRIDGE INTO AN & 4-THACK

Simply insert GIDGET into any 4-track stereo cartridge is slide it into the Compact Convertible stereo lape player. Presto . . . the 4-track cartridge plays. Does not necessor by fir olf arbon makes at Tape Players.

#### AMERICAS BEST SELECTION AND LOWEST PRICE LINE OF AUTO STEREO SPEAKERS

MODEL PJR-6

Pair - 5" Speakers Mounted in Deluxe Wedge Housing



WITH 6 oz., MAGNET

Great for Radio or Hanging Up

#### Description

An exclusively designed unit with deluxe 5 inch speakers perfectly matched for best stereo perform ance. Housing is made of high impact ABS plastic with a touch of chrome trim for perfect blending with any car interior. 2-piece blastic case makes set up and installation quick and easy.

#### Application

5-520

This quality designed speaker will fit neatly and compactly on rear package deck, under front car seats, on to side kick panels, For best stereo re sponse cut a 3" to 4" round hole behind speaker when mounting on rear window deck. This will bring out an even richer bass and clearer high.

> Model No., PJR-6 With heavy 6 oz., Magnet

2 FOR \$15,00 2E15P

Pair - 5" Speakers with Black Plastic Grilles



2E15P \$3.95 Pair

#### Description

A quality engineered 5" round speaker specifically designed to fit all in the door installations. This powerfully built speaker brings out the finest stered response from any model stereo tape player. With the car door acting as a baffle you will enjoy car stereo entertainment at Its finest Custom molded black plastic or metal grilles that almost conceal themselves within the car interior.

#### Application

Specifically designed for flush mounting in any car door, kick panel or rear package tray. You enjoy the ultimate in car stereo from this flush mounted speaker. Clear rich tones from bass to highs are readily reproduced

#### Specifications

- 5" Round matching stereo speakers
- · 8 OHMS Impedance
- 4 Watts of stereo power • 2 oz. ceramic magnet
- Weather resistant
- Frequency range 130 to 12,000 HZ (CPS) + or - 5 OB
- Includes wiring and mounting hardware
- · Packaged in sets of 2

DELUXE WEDGE SPEAKERS



ALL SPEAKERS PACKED IN DISPLAY BOXES

Set of 4 - 5" Speakers with Black Plastic Grilles



4E15P SAME AS 2E15P Except Packed 4- In A Box

FOR \$6.95

TWO FLUSH MOUNT 5" **SPEAKERS** Easy to mount




GRILLS 51/4 x 6"

- FEATURES
  Choice of 3 oz. 6 oz. BIG BRUTE Ceramic Magnets
- 5" Speakers 34" Voice Colls
- Wide-Range Frequency Specially Engineered Sounding Boards
- Speaker and Enclosure scientifically matched for true hi fidelity
- Prewired for easy installation Hardware included
- High Impact ABS Plastic Housing

Model No. 3-M3 \$ 5 95 with 3 oz., Magnet 5 in. SPEAKERS

Model No 3-6M \$6.95 with 6 oz., Magnet 5 in. SPEAKERS



TSPEAKERS IN AMERICA 5 %" SPEAKERS B WATTS --- 8 OHMS ASSY CHROME GRILL FASY TO INSTALL

be Ardun, Bint Model S-520

Ship. Wt. 4 lbs.

2 Pair \$13.00

10 Pairs for \$60,00

NEW POPULAR WEDGE SHAPE AUTO STEREO SPEAKERS

UNIVERSAL MOUNT

> Stock No. 885

99 PAIR

2 PAIR FOR \$9.50 10 PAIR FOR \$45,00

5 WATT - 8 OHM EASY TO MOUNT RESILIENT PLASTIC ENCLOSURE

Universal mount car stereo speakers. 9 Wafts - Heavy Ferrite Magnets, No holes to cue-mounts on the surface, Fits on rear window shelf under the dash, under front seat or on side kick plates. Tough resilient plastic enclosures protectine speakers and give exceptional balling for good bass response. With 5 watt 8 dam speakers, each 10 watts peak rating, 8 ohm volce colls, Size; 84% x 7" base, Maximum height 3-5/6". Has Approx, 15 Ft, speaker lead, Ship, Wt. 3 lbs.

BELLE WOOD STEREO SPEAKER SYSTEMS MODEL 3860 **295** PAIR 10 for \$55,00

Two 5"-8 ohm, 2.8 oz.ceramic magnet Hang-On Speakers in mot finish housing. 12 ft. of wire with clip-on leads. 5 watt rating.

Model No 3860 \$5,95 pair 10/\$55.00

FOR CUSTOM FLUSH AND SURFACE MOUNTING. ONLY & MOUNTING DEPTH REQUIRES ONLY 4 BOLTS OR SCREWS TO MOUNT ON ANY SURFACE

er handling: 5 watts peak Frequency range: 60 Hz - 20 kHz Input impedance: 8 ohms

Size: %" x 5" x 10"
THIS SPEAKER HAS MANY WAYS TO BE USEO.. WALL BAFFLES, 4 OR MORE IN A SOUND COLUMES, AUTOS, HOME INTERCOMS., BOATS, CHURCHES AND SO MANY OTHER APPLICATIONS.

STOCK NO. P.5 PRICE

\$ 5 95

STOCK HO. HAR-5 P-5 Speaker & Walnut vinyl covered Baffle.So small it will mount anywhere. Size; 9" long, 5/1/8 wide, 1% deep

122

# BIG INCH FEATURING FULL I INCH VOICE COILS PLUS 1.73 ... ALMICO V MAGNETS FINE TONE QUALITY - RUGGED CONSTRUCTION - LOWEST PRICES McGEE'S 1971



EAKERS Hove UMINUM VOICE IL FORMS.....

410-173-8

2½ X 10 4% X 1Q \$2.29

B 44210 Inch - Stock No. 410-173-5, 1" Aluminum litery Duty Voice Coll. High efficiency 1.73 Oz. Alnice V Vagnet, 5/2" desp. 40,210" Ovel with Jun 6 7/6" mountie, hales....

C 14X.0 inch - Stock No. 210-147-8, or is. Aluminum voice Cuil 147 Oz. Alnice V Magnel. Because of the "yalo dimensions the "gis" voice coll and 1,47 Oz. manel gives like bestworking speaker in this perituier madel. Maunting, holes on eggh ppd. 92. celliers.

\$2.49

D 6% inch . Stock No. 52-173-8; ... Attention Heavy Duby Voice Coal not elected by Stock No. 57-173-8; ... After V Market (tited inside the voice coal for marginum affidiency. Come has a small dust reflect hoter for rese dech auto speaker morning. Prices at low as some speakers with small voice coils and read in magnets. This is ariginate designed also decided and

69-173-6

10 OZ new: CERAMIC MAGNET

2 for \$7.70

Mod QM-69-10CR, 6X9 Speaker with 10 Ox. Ceramic Magnet. If you need a 6X9 Speaker with fyll range, for a hard to do job, this is the one for you. McGee Sale Price...

DELUXE 6X9 AUTO SPEAKER WITH HEAVY DUTY 21/2 OZ. MAGNET 1" 8 OHM VOICE COIL

Stock No. 79 69-250-8

10 FOR \$25,00 31/4" Deep

Ship. Wt. 2 lbs.

6 X 9 HI - FI FEATURING 5 OZ. CERAMIC MAGNET

HEAVY DUTY I" VOICE CON HI-FI CONSTRUCTION

WITH WIZZER CONE ... 5 Ox. MAGNET

69CTF, Model CTS Super Newsy Duty 6X9 epecker with 5 Oz. Ceramic Magnet, 1" volce cail. Another McGEE "Best Buy" in a high efficiency 6X9 with a Whizzer Conc. New low profile deeign, only 2X1" epace needed. Frequency Response 40 to 12,000 cps Net each \$2,89, 2 for \$5.58, 10 for \$25.00.

47 OZ. ALNICO V MAGNET

100 for \$180.00

8 ohm VC. K" VOICE COIL  NEW CTS 51/4", pin-cushion 10 oz ceramic magnet, 8 ohm, 1" voice coil SPEAKER Stock No. Price

6 X 9

52CT10HF \$3.99 Ship. Wt 2½ lbs 2 for \$7.50 Latest high compliance full-range; soil edge cone with a whizzer cone for highs Auto stereo speaker. 5½ pin-cushion, 10 oz. 8 ohm c.

2 Oz. Alnico V Magnet

49F-173-8

Stock No. 695-CLM

Actual size 64" x 104"

SPECIAL BUY 6 X 9 % Inch 8 Ohm V.C.

7 Ox. Ainico Magnet .69

Stock No. 69-8 Plenty of stock on hand

10 for \$15.00

31/4" 51/2 X 71/2" MOPAR Deep P.M. SPEAKER Stock No. Ship. Wt. 3.16 oz. Alnico V Magnet Heavy Duty Speak agent 57-75

8 OHM 4 X 10 Size. 1.73 Mag., 1", 8 ahm V.C.

HIN SPEAKER Price \$2.99 Stock No.

410-2-FL Only 2" thick, this type used in G.M. cars and many others requiring small space. Mounting centers 3%x?". Size: 4x10' 1.73 mag. 8 ohm, 1" voice coil. Ship Wt. 1% Iba.

AUTO SPEAKERS. Can also be

used in other instellations 4 X 6", SPEAKER 75-32 7", 1.47 oz knob magnet, 4 ohm ¼ VC.

PERFECT FOR STEREO WITH CONE COVERED WITH Price \$1.99

75-173 7", 1.73 oz bar magnet, 4 ohm 1 VC. Price \$2,19

7P2 7\*\* 2.15 oz bai magnet, 4 ohm ¾ VC. Price \$2.49

REAR DECK SPEAKER KITS



6X9 REAR DECK SPEAKER KIT EL-69A STOCK NO.

**5X7** REAR DECK SPEAKER KIT STOCK NO. EL-57 A

\$3.99

\$2.79 COMPLETE 6X9 REAR SEAT SPEAKER KIT

BRIGHT CHROME GRILL FADER CONTROL CONNECTING WIRE AND INSTRUCTIONS of warm a stall 1.73 ser. Ainter V Magnet litted inside the liveste coll. Most 1.02. Magnet litted inside the lite of the literature of the lit

Similar star year seat speaker hit sumplets with 527 2 Da Magnet Speaker and Grills, Switch and Wire.

5 1/4" VOLKSWAGEN REPLACEMENT 3 oz. Ceramic Magnet 8 OHM Stock No 1.99

SHIP. WT. 1 LB 525-316-8

Ideal replacement for most 10 for \$19.00

### GENUINE FORD 6 X 9 SPEAKER

.73 oz. Alnico V 1" Voice Coil 8 OHM

2.79 10 for \$25,00

Stock No69 FORD 1.73



PERS & HODBUP BRAGRAM (RCLUDED Face Co a Impo-Dia, dance In Lin. MET Inches (Ohms) Watts Lin. Price 6 1 \$2.99 6 1 \$2.99 7 1 5-99



AUTO REAR SPEAKER 3 FOR \$4.50



6x9 GRILL only; Same as used in above kit, 99 Stock No. 182. 6x9 CHROME GRILL, Price



6X9 GRILLES Dull Aluminum Can be painted my color

MCG-79 79¢

CLOTH SCREENING. ONLY 11/11 THICK.

Used by FORD and other car manufacturers

8 ohm V.C. 3 oz. Magne SOLD IN PAIRS ONLY







#### 2 far Top Value \$25.00 11/2", 6 ohm voice coll, will work on the 4 or 8 ahm tap an your P.A. amplifier. Good response In open or closed baffles Shipping weight 10 lbs.



MODEL SC-28-



\*FEATURES A SPECIAL WIDE RANGE CONE \*EXTRA GOOD BASS AND TREBLE TONE QUAL-ITY AT ORDINARY ROOM VOLUME ..... \*\*\*OROER TWO ALIKE FOR STEREO\*\*\*

Model EMI-8 15, a ft.,e low cost high fidality PM spesier imported from England, Features e specially designed wide range cone for full range response from 35 to 15 000 cps. Ainto magnat and 4 ohm impedance voice coll, ideal for use in stereo high fightly systems. A unique speaker in performance and design, if you want something a little difference we commend our Stock No. EMI-813. 8'\* 13'\* PM speaker made in England, Shipping weight 39s lbs. A regular \$8,00 value, Sate price, \$3.95 each, 2 for \$7,50, or buy 10 for only 35,00.

## MCGEE HAS THE LARGEST SELECTION OF REPLACEMENT SPEAKERS FOR EVERY PURPOSE

BIG BRUTE SPEAKER 5" X 7" SUPER HI-FI SPEAKERS

with WHIZZER TWEETER CONE. Price \$2.49 Stock No. COMM-57-3-8

6 OZ. CERAMIC MAGNET 8 OHM, HIGH TEMPERATURE VOICE COIL WILL HANDLE 8 WATTS AND MORE.

57-2-8-CHF WILL HANDLE 5 WATTS

57-06-HIFI BOHM, VOICE COIL WILL HANDLE 3 WATES

Price \$1.49



A 3-1-3 3 Square 1.0 3 9/16 1-3/4 ½ 9.99  C 3599654 3½ Square 1.0 3 2 9/16 1-3/4 ½ 9.99  A 3.5PX1 3½ Square 1.0 3.2 9/16 1-1/2 ½ 9.99  A 3.5PX3 3½ Square 1.68 3.2 9/16 1-1/2 ½ 9.99  A 3.5PX8 3½ Square 1.47 3.2 9/16 1-1/2 ½ 9.99  A 3.5PX8 3½ Square 1.47 3.2 9/16 1-1/2 ½ 9.99  A 3.5PX8 3½ Square 1.47 3.2 9/16 1-1/2 ½ 9.99  A 3.5PX8 3½ Square 1.68 8 9/16 1-1/2 ½ 9.99  A 4PXY 4 Square 5.3 3.2 9/16 1-5/8 ½ 1b. 99  A 4PXY 4 Square 5.3 3.2 9/16 1-5/8 ½ 1b. 99  A 4PXY 4 Square 1.0 2 9/16 1-5/8 ½ 1b. 99  A 4PX 4 Square 1.0 2 9/16 1-5/8 ½ 1b. 99  A 4PM 4 Square 1.0 2 9/16 1-5/8 ½ 1b. 99  A 4PM 4 Square 1.0 2 8 9/16 1-3/4 ½ 1b. 99  C 4PM 4 Square 1.0 2 8 9/16 1-3/4 ½ 1b. 99  C 4PM 4 Square 1.0 2 8 9/16 1-3/4 ½ 1b. 99  C 4PM 5 4 Square 1.0 2 8 9/16 1-3/4 ½ 1b. 99  C 5.5WP 5 5 Round 1.47 8 3.4 1-7/8 ½ 1b. 99  C 5.5WP 5 7 Round 5.3 4 9/16 1-3/4 ½ 1b. 99  C 5.5WP 5 8 Round 1.0 2 4 9/16 1-3/4 ½ 1b. 99  B 5-1-10 5 Pin C 1.0 4 9/16 1-3/4 3/4 1.19  A 5P2 5 Round 1.47 4 9/16 1-3/4 3/4 1.19  B 5-1-16 5 Pin C 1.0 2 4 9/16 1-3/4 3/4 1.19  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.39  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.39  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.49  B 6P2 6 Pin C 1.47 3.2 9/16 1-3/4 3/4 1.49  B 6P2 7 Pin C 2.15 8 3/4 3-1/4 1 1b. 1.39  B 6P2 7 Pin C 2.15 8 3/4 3-1/4 1 1b. 1.99  T-B 78-32 7 Pin C 2.15 8 3/4 3-1/4 1 1.99  T-B 78-32 7 Pin C 2.15 8 3/4 3-1/4 1 1.99  T-B 78-32 8 Round 3.16 4 3/4 3/4 3-1/4 2.199  B 10PX 8 ROUND 3.16 8 Pin C 1.47 8 3/4 3-1/4 2 1.99  T-B 78-38 8 Round 3.16 4 3/4 3/4 3-1/4 2 1.99  A 10PX 10 Round 4.64 1 1 4-1/2 3/4 3.99  A 12PX 12 Round 1 to 1¼ 8 3/4 3-4 3/4 3 3.49  A 12PX 12 Round 1 to 1¼ 8 3/4 3/4 3-1/4 2 1.99  A 12PX 12 Round 1 to 1¼ 8 3/4 3-4 3/4 3 3.49  A 12PX 12 Round 1 to							The state of the s	A.	1	TO	
C 35996 54 3-y Square 1.0 3.2 9/16 1-3/4 5-y 99   A 3.5PX 31/5 Square 1.68 3.2 9/16 1-3/4 5-y 99   A 3.5PX 31/5 Square 1.68 3.2 9/16 1-1/2 5-y 99   C 4PXX 4 Square 1.7 3.2 9/16 1-1/2 5-y 99   C 4PXY 4 Square 1.53 3.2 9/16 1-1/2 5-y 99   C 4PXY 4 Square 1.53 3.2 9/16 1-1/2 5-y 99   A 4PX 4 Square 1.53 3.2 9/16 1-1/2 5-y 99   A 4PX 4 Square 1.68 3.2 9/16 1-3/8 5-y 10   C 4PP 4 Square 1.68 3.2 9/16 1-3/8 5-y 10   C 4PM 4 Square 1.68 3.2 9/16 1-3/8 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   C 4PM 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   A 4PM3 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   A 4PM3 4 Square 1.0 2. 3. 9/16 1-3/4 5-y 10   A 5P3 5-y 10   C 5-SWPS 5 Round 6.8 4 9/16 1-3/4 5-y 10   A 5P2 1-1   C 5-SWPS 5 Round 6.8 4 9/16 1-3/4 3/4 1-19   B 5-10 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-10 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   A 5P2 5 Round 1.47 4 9/16 1-3/4 3/4 1-19   A 5P2 5 Round 1.47 4 9/16 1-3/4 3/4 1-19   B 5-116 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-116 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-116 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-116 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-116 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-116 6 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-116 6 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 5-117 8-32 7 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 6P2 6 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 6P2 7 Pin C 2.15 8 3/4 2-3/4 1 1 1.0 99   B 8PX1 8 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 8PX1 8 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 9PX8 8 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 9PX8 8 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 9PX8 8 Pin C 1.47 8 9/16 1-3/4 3/4 1-19   B 10P8 10 PP 10 Round 1.47 4 3/4 3-1/4 2 1-19   B 10P8 10 PP 10 Round 1.47 4 3/4 3-3/4 1-19   B 10P8 10 PP 10 Round 1.46 8 1 1 5 3/4 3-3/9   A 10P3 10 Round 1.47 4 3/4 3-3/4 1-19   B 10P3 10 Round 1.68 8 1 5 3/4 3-3/4 3-		2-1-2	2	C	10	3	0 / 16	1-2:4	1.	90	-
D 3CM7 364 Round 1.0 3.2 9/16 1-3/4 15 99 94 3 5PX8 31/5 Square 68 8 9/16 1-1/2 15 99 94 A 3.5PX8 31/5 Square 68 8 9/16 1-1/2 15 99 99 A 3.5PX8 31/5 Square 1.47 3.2 9/16 1-1/2 15 99 99 A 3.5PX8 31/5 Square 1.47 3.2 9/16 1-1/2 15 99 99 A 4 4PXY 4 Square 7.53 3.2 9/16 1-5/8 1/5 1/5 1/5 1/5 1/5 1/5 1/5 1/5 1/5 1/5											ı
A 3.5PX8 3½ Square 1.47 3.2 9/16 1-1/2 ½ 9.99   C 4PXX 4 Square .53 3.2 9/16 1-1/2 ½ 9.99   A 4PXY 4 Square .53 3.2 9/16 1-1/5/8 ½ 1b. 99   C 4PP 4 Square .68 3.2 9/16 1-3/8 ½ 1b. 99   C 4PP 4 Square .68 3.9 1/16 1-3/8 ½ 1b. 99   C 4PM 4 Square .68 3.9 1/16 1-3/8 ½ 1b. 99   C 4PM 4 Square .68 3.9 1/16 1-3/8 ½ 1b. 99   A 4PX1 4 Square .68 3.9 1/16 1-3/8 ½ 1b. 99   A 4PX1 4 Square .68 3.9 1/16 1-3/8 ½ 1b99   A 4PM1 5quare .02 3.2 9/16 1-3/8 ½ 1b99   A 4PM3 4 Square .1 0z. 8 9/16 1-3/4 ½ 1b99   A 4PN3 4 Square .1 1.47 8 3/4 1-1/8 ½ 1b99   A 4PN3 5quare .1 1.47 8 3/4 1-1/8 ½ 1b99   A 5TPX1 5 Round .68 4 9/16 1-3/4 ½ 1b99   B 5-100 5 Pin C 10z. 4 9/16 1-3/4 ½ 1b99   B 5-4-147 5 Pin C 10z. 4 9/16 1-3/4 ½ 1b99   B 5-4-147 5 Pin C 1.47 4 9/16 1-3/4 ½ 1b99   B 5-4-147 5 Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 5-147 5 Round 1.47 4 9/16 1-3/4 ½ 1.19   B 5-116 5 Pin C 1.47 4 9/16 1-3/4 ½ 1.19   B 5-116 5 Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 5-116 5 Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 5-116 5 Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 5-116 5 Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 5-127 5903 5½ Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 575903 5½ Pin C 1.47 4 9/16 1-3/4 ½ 1b19   B 6PX1 6 Pin C 1.47 3.2 3/4 2-3/8 1ib. 1.69   B 6PX 6 Pin C 1.47 3.2 3/4 2-3/8 1ib. 1.69   B 6PX 7-B 78-32 7 Pin C 1.47 3.2 3/4 2-3/8 1ib. 1.99   7-B 78-32 7 Pin C 1.47 3.2 3/4 3.1 4 1 2.49   7-B 7-B 7-250 7 Pin C 1.47 3.2 3/4 3.1 4 1 2.49   B 8PX8 8 Pin C 1.47 8 9/16 2-1/4 3/4 1.29   B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.49   A 8P28 8 Round 2.15 8 3/4 3/4 3/4 1.29   B 8PX1 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.49   A 8P28 8 Round 2.15 8 3/4 3/4 3/4 1/4 2.49   A 8P28 8 Round 3.16 4 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pin C 1.47 8 3/4 3/4 3/4 1/4 2.49   A 10PX 10 Pi										.99	L
A   3.5-1-4   3½   Square   1.47   3.2   9/16   1-1/2   ½   9.99	Α				.68	3.2			1.,	.99	ſ
C 4PXX 4 Square .53 3.2 9/16 1-3/6 1/1 1b, 99 4 A 4PXY 4 Square .68 3.2 9/16 1-5/8 1/1 1b, 99 4 A 4PX 1 4 Square .68 3.2 9/16 1-5/8 1/1 1b, 99 4 A 4PP 4 Square .68 8 9/16 1-3/8 1/1 1b, 99 4 C 4PP 4 Square .68 8 9/16 1-3/8 1/1 1b, 99 4 C 4PM 4 Square .68 8 9/16 1-3/8 1/1 1b, 99 4 C 4PM 1 4 Square .90 2. 3 9/16 1-5/8 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2			31/2								
A 4PXY 4 Square .53 3.2 9/16 1-5/8 1/10, 99 A 4PP 4 Square .68 3.2 9/16 1-3/8 1/10, 99 A 4PP 4 Square .68 3.2 9/16 1-3/8 1/10, 99 A 4PM 4 Square .68 3.2 9/16 1-3/8 1/10, 99 C 4PM 4 Square Doz. 3 9/16 1-3/8 1/10, 99 C 4PM 4 Square Doz. 3 9/16 1-3/8 1/10, 99 A 4PM 3 4 Square 1.0z, 8 9/16 1-3/4 1/10, 99 A 4PM 3 4 Square 1.47 8 3/4 1-7/8 1/10, 99 A 4PM 3 4 Square 1.47 8 3/4 1-7/8 1/10, 99 A 4-BAR-8 4 Square 1.47 8 3/4 1-7/8 1/10, 99 A 5-100 5 Pin C 1.47 8 9/16 1-3/4 3/4 1-99 B 5-100 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-19 B 5-4-147 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-19 B 5-4-147 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-19 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-49 B 5-1-16 5 Pin C 1.47 4 9/16 1-3/4 3/4 1-99 B 575903 5% Pin C 2.15 8 3/4 2-14 11b. 1.99 B 575903 5% Pin C 2.15 8 3/4 2-14 11b. 1.99 B 6PX1 6 Pin C 1.47 3.2 9/16 2-1/4 3/4 1-29 B 6P 6 Pin C 1.47 3.2 9/16 2-1/4 3/4 1-29 F-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 1-19 F-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 1-19 B 8PX8 8 Pin C 1.47 8 9/16 1-1/2 3/4 3/4 1-79 B 8PX8 8 Pin C 1.47 8 9/16 1-1/2 1/2 3/4 1-2/9 F-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 1-99 F-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 4 1 2.49 F-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 4 1 2.49 F-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 4 1 2.49 F-B 7-250 7 Pin C 2.15 8 3/4 3-1 4 1 2.49 F-B 7-250 7 Pin C 2.15 8 3/4 3-1 4 1 2.49 F-B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1/9 2.19 B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1/9 2.19 B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1/9 2.19 B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1/9 2.19 B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1/9 2.19 B 10P12 10 Pin C 1.47 3.3 3/4 3/4 3/4 3/4 2.19 A 8P38 8 Round 3.16 4 3/4 3/4 3/4 2.19 A 8P38 8 Round 3.16 4 3/4 3/4 3/4 2.19 A 10-68-8 10 Pin C 1.47 8 3/4 3/4 3/4 2.19 B 10PX8 10 Pin C 1.47 8 3/4 3/4 3/4 2.19 B 10PX8 10 Pin C 1.47 8 3/4 4-3/4 3 3.49 B 10PX8 10 Pin C 1.4	Λ	3.5-1-4	31/2	Square	1.47	3 2	9/16	1-1/2	1/2	-99	ľ
A 4PP 4 Square 68 8 9,16 1-3/8 1/15 b. 99 A 4PP 4 Square 10z, 3.2 9/16 1-3/8 1/15 b. 99 C 4PM1 4 Square 10z, 3.2 9/16 1-3/8 1/15 b. 99 C 4PM8 4 Square 10z, 3.2 9/16 1-3/4 1/15 b. 99 A 4PM3 4 Square 1.47 3.2 9/16 1-3/4 1/15 b. 99 A 4PM3 4 Square 1.47 3.2 9/16 1-3/4 1/15 b. 99 C 5-SWP5 5 Round 1.47 3.2 9/16 1-3/4 1/15 b. 99 C 5-SWP5 5 Round 68 4 9/16 1-3/4 3/4 1/19 b. 99 B 5-100 5 Pin C 1 0z, 4 9/16 1-3/4 3/4 1.19 B 5-4-147 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.19 B 5-4-147 5 Round 1.47 4 9/16 1-3/4 3/4 1.19 B 5-106 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.19 B 5-16 5 Pin C 1 0z, 4 9/16 1-3/4 3/4 1.49 A 5PM5-C45 5 Round 1.47 4 9/16 1-3/4 3/4 1.49 B 5-16 A 5PM5-C45 5 Round 1.47 4 9/16 1-3/4 3/4 1.49 B 5-16 B 6PX 6 Pin C 1 0z, 68 4 9/16 2-1/4 11b, 1.99 B 525-147 5½ Pin C 1 0z, 68 4 9/16 2-1/4 11b, 1.99 B 525-147 5½ Pin C 1.47 4 9/16 1-3/4 3/4 1.49 B 5-16 A 5PM5-C45 5 Round 1.47 4 9/16 1-3/4 3/4 1.49 B 5-16 A 5PM5-C45 5 Round 1.47 4 9/16 1-3/4 3/4 1.49 B 5-16 A 5PM5-C45 5 Round 1.47 4 9/16 2-1/4 11b, 1.99 B 6PX1 6 Pin C 1.47 8 9/16 2-1/4 11b, 1.99 B 6PX 6 Pin C 2.15 8 3/4 2-3/8 11b, 1.69 B 6PX 6 Pin C 1.47 8 9/16 2-1/4 11b, 1.99 B 6PX 7-B 7-B 7-S50 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.99 B 8PX 8 Round 1.47 8 9/16 2-1/4 3/4 1.29 B 8PX 8 Round 2.15 8 9/16 2-1/4 3/4 1.29 B 8PX 8 Round 3.16 8 9/16 2-1/4 3/4 1.29 B 8PX 8 Round 3.16 8 3/4 3/4 3-3/4 1.49 A 8P2 8 Round 3.16 8 3/4 3/4 3-3/4 2.49 A 8P3 8 Round 3.16 8 3/4 3/4 3-3/4 2.49 A 8P3 8 Round 3.16 8 3/4 3/4 3-3/4 2.49 A 8P3 8 Round 3.16 8 3/4 3/4 3-3/4 2.49 A 8P3 8 Round 3.16 8 3/4 3/4 3-3/4 2/2 2.49 B 9P16 2 10 Round 3.16 8 3/4 3/4 3-3/4 2/2 2.49 B 10PX 10 Round 3.16 8 3/4 3/4 3-3/4 2/2 2.49 A 10PX 10 Round 4.64 4 1 4-1/2 3 3.79 A 10PX 10 Round 4.64 4 1 4-1/2 3 3.79 A 10PX 10 Round 4.64 8 1 1 5 3/4 3/4 3.99 B 12PX 12 PIN C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 PIN C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 PIN C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 PIN C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 PIN C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 PIN C 3.16 8 1 5 3/4 4.39	C	4PXX	4	Square	.53	3.2	9/16	1-3/8		.99	
C 4PP 4 Square 102, 32, 9/16 1-3/4 1/5 1.99   C 4PM1 4 Square 702, 3 9/16 1-5/8 1/5 1b. 99   C 4PM8 4 Square 702, 3 9/16 1-5/8 1/5 1b. 99   A 4PM1 4 Square 1.47 8 9/16 1-3/4 1/5 1b. 99   A 4PM3 4 Square 1.47 8 3/4 1-7/8 1/5 1b. 99   C 5-SWP5 5 Round 1.47 8 3/4 1-7/8 1/5 1b. 99   C 5-SWP5 5 Round 68 4 9/16 1-3/4 3/4 1b. 99   B 5-100 5 Pin C 1 Oz. 4 9/16 1-3/4 3/4 .99   B 5-100 5 Pin C 1 Oz. 4 9/16 1-3/4 3/4 1.19   B 5-4-147 5 Round 1.47 4 9/16 1-3/4 3/4 1.39   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.39   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49   B 5-1-16 6 Pin C 1 Oz. 16 9/16 2-1/4 3/4 1 1b. 1.99   B 6PZ 6 Pin C 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Α		_							.99	
A 4PM 1 4 Square 1 Oz. 3.2 9/16 13/4 ½ 1b. 99 C 4PM8 4 Square 1 Oz. 8 9/16 15/8 ½ 1b. 99 C 4PM8 4 Square 1 Oz. 8 9/16 13/4 ½ 1b. 99 C 5SWP5 5 Round 1.47 8 3/4 17/8 ½ 1b. 99 C 5SWP5 5 Round 6.8 4 9/16 13/4 ½ 1b. 99 C 5SWP5 5 Round 6.8 4 9/16 13/4 ½ 1b. 99 C 5SWP5 5 Round 6.8 4 9/16 13/4 ⅓ 1b. 99 C 7 S-SWP5 7 Round 7 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 4 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 1 Oz. 6 9/16 13/4 ⅓ 1 19 P 1 C 2.15 8 3/4 21/4 1 1b. 19 P 1 C 2.15 8 3/4 23/8 1 1b. 169 P 1 C 147 8 9/16 21/4 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1 1b. 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 1 19 P 1 C 21/4 8 9/16 21/4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			_							.99	ı
C 4PM1 4 Square 10.2, 8 9/16 1-3/4 ½ 1b. 99 4 4 PM3 4 Square 1.47 8 3.2 9/16 1-3/4 ½ 1b. 99 27 4 PM3 4 Square 1.47 8 3.74 1-7/8 ½ 1b. 99 27 4 PM3 4 4 Square 1.47 8 3.74 1-7/8 ½ 1b. 99 27 4 PM3 4 4 Square 1.47 8 3.74 1-7/8 ½ 1b. 99 27 4 PM3 4 4 Square 1.47 8 3.74 1-7/8 ½ 1b. 99 28 28 28 28 28 28 28 28 28 28 28 28 28											
C 4PM8 4 Square 1.02, 8 9/16 1-3/4 1/2 lb. 99 4 A 4PM3 4 Square 1.47 3.2 9/16 1-3/4 1/2 lb. 99 4 A 4PM3 4 Square 1.47 3.2 9/16 1-3/4 1/2 lb. 99 5 C 5-SWP5 5 Round .68 4 9/16 1-3/4 3/4 1.19 .99 6 STPX1 5 Round .68 4 9/16 1-3/4 3/4 1.19 .99 8 5-4-147 5 Round 1.02. 4 9/16 1-3/4 3/4 1.19 8 5-4-147 5 Round 1.47 4 9/16 1-3/4 3/4 1.19 8 5-1-16 5 Pln C 1.47 4 9/16 1-3/4 3/4 1.49 A 5-147 5 Round 1.47 4 9/16 1-3/4 3/4 1.49 A 5-147 5 Round 1.47 8 9/16 1-3/4 3/4 1.49 8 5-1-16 5 Pln C 1.47 45 9/16 1-3/4 3/4 1.49 8 5-1-16 5 Pln C 1.47 45 9/16 1-3/4 3/4 1.49 1.99 8 5-5-147 5 Round 1.47 4 9/16 1-3/4 3/4 1.49 1.99 8 5-1-16 5 Pln C 1.47 45 9/16 2-1/4 11b. 1.99 1.99 8 575903 5/4 Pln C 2.15 8 3/4 2-3/8 11b. 1.69 8 6PX1 6 Pln C 1.47 8 9/16 2-1/4 11b. 1.39 1.69 8 6PX1 6 Pln C 1.47 8 9/16 2-1/4 3/4 1.29 8 6PX1 6 Pln C 1.47 8 9/16 2-1/4 3/4 1.29 8 6PX 6 Pln C 1.47 8 9/16 2-1/4 3/4 1.29 8 6PX 6 Pln C 1.47 8 9/16 2-1/4 3/4 1.29 8 6PX 6 Pln C 2.15 3.2 3/4 3 1 1.99 7-Pln C 3.16 3.2 1 3-3/8 11/4 2.49 8 PX 8 8 PIn C 1.47 8 9/16 1-7/8 11/4 2.49 8 PX 8 8 PIn C 1.47 8 9/16 1-7/8 11/4 2.49 8 PX 8 8 PIn C 1.47 8 9/16 1-7/8 11/4 2.49 8 PX 8 8 PIn C 2.15 8 3/4 3 11/4 2.49 8 PX 8 8 PIn C 1.47 8 9/16 1-7/8 11/4 2.49 8 PX 8 8 PX 8 8 PIn C 1.47 8 9/16 1-7/8 11/4 2.49 8 PX 8 8 Round 3.16 8 3/4 3/4 3/4 1.49 2.49 8 PX 8 8 PIn C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 8 PIn C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 PX 8 8 PIn C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 8 PIn C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 8 PX 8 8 PIn C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 8 PIN C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 8 PX 8 8 PIN C 2.15 8 3/4 3 11/4 2.49 2.49 8 PX 8 8 PX 8 8 PIN C 2.15 8 3/4 3 3/4 3/4 2.49 2.49 8 PX 8 8	2		1								L
A 4PM3											Γ
A 4-BAR-8 4 Square 1.47 8 3/4 1-7/8 1/5 10. 99  C 5-SWP5 5 Round 6.68 4 9/16 1-3/4 3/4 .99  B 5-100 5 Pin C 1 Oz. 4 9/16 1-3/4 3/4 1.19  B 5-100 5 Pin C 1.47 4 9/16 1-3/4 3/4 1.19  B 5-4-147 5 Round 1.47 4 9/16 1-3/4 3/4 1.19  A 5P2 5 Round 1.47 4 9/16 1-3/4 3/4 1.39  A 5-147 5 Round 1.47 8 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1.47 8 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 1 Oz. 16 9/16 1-3/4 3/4 1.49  B 5-1-16 5 Pin C 2.15 8 3/4 2-1/4 1 1b. 1.99  B 575903 5½ Pin C 2.15 8 3/4 2-1/4 1 1b. 1.39  B 6PX1 6 Pin C 1.47 4 9/16 2-1/4 1 1b. 1.39  B 6PX1 6 Pin C 1.47 4 3/4 2-1/4 1 1b. 1.39  B 6PX 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29  B 6P2 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29  B 6P2 6 Pin C 2.15 8 3/4 2-3/8 1 1b. 1.69  F-B 78-32 7 Pin C 1.47 8 9/16 2-1/4 3/4 1.29  B 6P2 6 Pin C 2.15 4 3/4 3-1 1 1.99  7-B 7-B 7-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 1 1.99  7-B 7-B 7-B 7-250 7 Pin C 2.15 3.2 3/4 3-1 1 1.99  B 8PX1 8 Pin C 3.16 3.2 1 3-3/8 1½ 2.49  A 8P2 8 Round 2.15 3.2 3/4 3 1½ 2.49  A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49  A 8P3 8 Round 2.15 4 3/4 3 1½ 2.49  A 8P3 8 Round 3.16 8 3/4 3/4 3/4 1/4 2.19  B 10P8 10 Pin C 1.47 8 3/4 3/4 3 1½ 2.49  A 8P3 8 Round 3.16 8 3/4 3/4 3/4 1/4 2.19  B 10P8 10 Pin C 1.47 8 3/4 3/4 3 1½ 2.49  A 10P3 10 Round 6.8 16 1 4-1/4 2/4 1.99  B 10P8 10 Pin C 1.47 8 3/4 3/4 3-1/4 2 1.99  B 10P8 10 Pin C 1.47 8 3/4 3/4 3-1/4 2 1.99  B 10P8 10 Pin C 1.47 8 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4						3.2					ı
A STPX1			4	Square	1.47	8	3/4	1-7/8	1/3 1b.	-99	ı
A STPX1		E WDE	5	Round	.53	A A	9/16	1-1/2	3/4	.99	L
B 5-100											
A 5P		_			1 Oz.		9/16		3/4	1.19	
A 5P2					_	4					1
A 5-147											1.
B 5-1-16							_				
A SPM5-C45 5 Round 1.47 45 9/16 2-1/4 11b. 1.99  B 525-147 5½ Pin C 1.47 4 3/4 2-1/4 11b. 1.39  B 575903 5½ Pin C 2.15 8 3/4 2-3/8 11b. 1.69  B 6PX1 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29  B 6SWP-6 6 Pin C 1.47 3.2 9/16 2-1/4 3/4 1.29  B 6P2 6 Pin C 1.47 3.2 9/16 2-1/2 3/4 1.79  B 6P2 6 Pin C 2.15 4 3/4 3-1/4 1 1.99  7-B 78-32 7 Pin C 2.15 3.2 3/4 3-1/4 1 1.99  7-B 7-B 7-S50 7 Pin C 2.50 8 1 2-1/4 1½ 2.69  7-B 7-B 7-S-HD 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.99  B 8PX1 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.99  B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.49  A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49  A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49  A 8P3 8 Round 3.16 4 3/4 3 1½ 2.49  A 8P3 8 Round 3.16 8 3/4 3/4 1½ 2.79  A 8P38 8 Round 3.16 8 3/4 3/4 1½ 2.79  A 8P38 8 Round 3.16 8 3/4 3/4 1½ 2.79  A 8P16 8 Round 3.16 8 3/4 3/4 1½ 2.79  A 8P16 8 Round 3.16 8 3/4 3/4 1½ 2.79  A 8P16 8 Round 3.16 8 3/4 3-1/4 2 1.99  B 10P2 10 Round 6.8 16 1 4-1/4 2½ 4.79  A 10PX1 10 Round 6.8 16 1 4-1/4 2½ 4.79  A 10PX1 10 Round 4.64 4 1 4-1/2 3 3.79  A 10PX1 10 Round 6.8 1 5 3/4 3.99  A 12PX1 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.99  A 12PX8 12 Round 6.8 1 5 3/4 3.99  A 12PX1 12 Round 6.8 1 5 3/4 3.99  B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99  B 12P3 12 Pin C 3.16 4 15 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 3.99  B 12P3 12 Pin C 3.16 8 1 5 3/4 4.39											ı
B 525-147 5½ Pin C 1.47 4 3/4 2-1/4 1 lb, 1.39 B 575903 5½ Pin C 2.15 8 3/4 2-1/4 1 lb, 1.69 B 6PX1 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29 B 6PX 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29 B 6P 6 Pin C 1.47 3.2 9/16 2-1/2 3/4 1.29 B 6P 6 Pin C 1.47 3.2 9/16 2-1/2 3/4 1.79 B 6P2 7-B 7-B 7-B 7-B 7-P2 7 Pin C 2.15 4 3/4 3-1/4 1 2.49 7-B											L
B 57 5903 5½ Pin C 2.15 B 3/4 2.3/8 1 lb. 1.69 B 6PX1 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29 B 6SWP-6 6 Pin C 1.47 3.2 9/16 2-1/4 3/4 1.29 B 6P 6 Pin C 1.47 3.2 9/16 2-1/4 3/4 1.79 B 6P2 6 Pin C 2.15 4 3/4 2-3/4 1 1.99 7-B 78-32 7 Pin C 1.47 3.2 3/4 3-1/4 1 2.49 7-B 7-B 7-250 7 Pin C 2.50 8 1 2-1/4 1½ 2.69 7-B 7-S-HD 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.99  B 8PX1 8 Pin C 2.50 8 1 2-1/4 1½ 2.69 7-B 7-B 7-S-HD 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.99  B 8PX1 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.19 A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49 A 8P2 8 Round 2.15 8 3/4 3 1½ 2.49 A 8P2 8 Round 3.16 4 3/4 3/4 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 A 8P3 8 Round 3.16 4 3/4 3/4 1½ 2.79 A 8P3 8 Round 3.16 4 3/4 3/4 1½ 2.79 C 8P316 8 Pin C 3.02. 16 1 2-1/2 1½ 2.79 A 8P16 8 Round 6.8 16 1 4-1/4 2½ 4.79  A 10P2 10 Round 6.8 16 1 4-1/4 2½ 1.99 B 10PX8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 12 3/4 3-3/4 2½ 2.49 A 10P3 10 Round 3.16 4 3/4 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 12 3/4 3-3/4 2½ 2.49 A 10P3 10 Round 3.16 4 3/4 3/4 3-3/4 2½ 2.49 A 10PX 10 Round 3.16 4 3/4 3/4 3-3/4 2½ 2.49 A 10PX 10 Round 3.16 4 3/4 3/4 3-3/4 2½ 2.49 A 10PX 10 Round 6.8 1 5 3/4 3-3/4 3-3/9 A 10PX 10 Round 6.8 1 5 3/4 3-3/9 A 10PX 12 Pin C 2.15 8 3/4 3-3/4 3 3.99 A 12PX 12 Pin C 2.15 8 3/8 4-3/4 3 3.99 B 12PX 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12PX 12 Pin C 3.16 8 1 5 3/4 4.39							-/-	الأناف			
B 6PX1						4		2-1/4			
B 6SWP-6 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29 B 6P2 6 Pin C 1.47 3.2 9/16 2-1/2 3/4 1.79 B 6P2 6 Pin C 2.15 4 3/4 2-3/4 1 1.99 Pin C 2.15 4 3/4 2-3/4 1 1.99 Pin C 7-B 78-32 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 Pin C 7-B 7-250 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 Pin C 3.16 3.2 1 3-3/8 1½ 2.49 Pin C 3.16 3.2 1 3-3/8 1½ 2.49 Pin C 3.16 3.2 1 3-3/8 1½ 2.49 Pin C 3.16 3/4 3 1½ 2.49 Pin C 3.16 2.15 4 3/4 3 1½ 2.49 Pin C 3.16 2.15 4 3/4 3 1½ 2.49 Pin C 3.02 Pin C 3.04 Pin Pin C 3.06 Pin C 3.06 Pin C 3.06 Pin Pin C 3.06 Pin C 3.06 Pin	В	57 59 0 3	51/4	Pin C	2.15	8	3/4	2-3/8	1 lb,	1.69	ı
B 6SWP-6 6 Pin C 1.47 8 9/16 2-1/4 3/4 1.29 B 6P 6 Pin C 1.47 3.2 9/16 2-1/2 3/4 1.79 B 6P2 6 Pin C 2.15 4 3/4 2-3/4 1 1.99 7-B 78-32 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 7-B 7-250 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 7-B 7-250 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.69 7-B 7S-HD 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 Pin C 3.16 3.2 1 3-3/8 1½ 2.49 Pin C 3.16 3.2 1 3-3/8 1½ 2.49 Pin C 3.16 3.2 1 3-3/8 1½ 2.49 Pin C 3.16 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4 3/4	В	6PX1	6	Pin C	.68	4	9/16	2-1/4	3/4	1,29	ı
B 6P 6 Pin C 1.47 3.2 9/16 2-1/2 3/4 1.79 B 6P2 6 Pin C 2.15 4 3/4 2-3/4 1 1.99  7-B 78-32 7 Pin C 2.15 3.2 3/4 3 1 2.49 7-B 7-250 7 Pin C 2.50 8 1 2-1/4 1½ 2.69 7-B 7-250 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.99  B 8PX1 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.99  B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.19 A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49 A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 A 8P3 8 Round 3.16 4 3/4 3/4 1½ 2.79 A 8P3 8 Round 3.16 8 3/4 3/4 1½ 2.79 A 8P38 8 Round 3.16 8 3/4 3/4 1½ 2.79 A 8P16 8 Round 6.8 16 1 4-1/4 2½ 4.79  A 10P2 10 Round 6.8 16 1 4-1/4 2½ 1.99 B 10P12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 8 3/4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3/4 3-1/4 2 1.99 A 10PX8 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 A 10PX8 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 A 10PX8 10 Round 3.16 4 3/4 3/4 3-1/4 2 1.99 A 10PX8 10 Round 6.8 1 1 5 3/4 3.99 A 10PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.79 A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.99 B 12P28 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P28 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39								_	1		i
7-B 78-32 7 Pin C 1.47 3.2 3/4 3 1 2.49 7-B 7P2 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 7-B 7-250 7 Pin C 2.50 8 1 2-1/4 11/4 2.69 7-B 78-HD 7 Pin C 3.16 3.2 1 3-3/8 11/4 2.99 8 8PX1 8 Pin C 1.47 8 9/16 1-7/8 11/4 2.19 A 8P2 8 Round 2.15 4 3/4 3 11/4 2.49 A 8P2 8 Round 2.15 4 3/4 3 11/4 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 11/4 2.49 A 8P3 8 Round 3.16 4 3/4 3/4 11/4 2.79 A 8P38 8 Round 3.16 4 3/4 3/4 11/4 2.79 A 8P38 8 Round 3.16 8 3/4 3/4 11/4 2.79 A 8P38 8 Round 3.16 8 3/4 3/4 11/4 2.79 A 8P38 8 Round 6.8 16 1 2-1/2 11/4 2.79 B 10P8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10P12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 2.15 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 2.15 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 2.15 8 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 8 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3-3/4 21/2 2.49 A 10PX1 10 Round 3.16 4 3/4 3-3/4 21/2 2.49 A 10PX1 10 Round 3.16 4 3/4 3-3/4 21/2 2.49 A 10PX1 10 Round 6.8 1 1 5 31/4 3.99 A 10-68-8 10 Round 6.8 8 1 5 31/4 3.99 A 10-68-8 10 Round 6.8 8 1 5 31/4 3.99 B 12PX8 12 Round 1 to 11/4 8 3/4 4-3/4 3 3.49 B 12PX8 12 Round 1 to 11/4 8 3/4 4-3/4 3 3.49 B 12PX8 12 Pin C 2.15 8 7/8 4-1/2 33/4 3.99 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 4 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pin C 3.16 8 1 5 31/4 4.39 B 12PX8 12 Pi	В		6	Pin C	1.47	3. 2	9/16	2-1/2			L
7-B 7-250 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 7-B 7-250 7 Pin C 2.50 8 1 2-1/4 11/4 2.69 7-B 7S-HD 7 Pin C 3.16 3.2 1 3-3/8 11/2 2.99 8 8 PX 1 8 PX 8 8 Pin C 1.47 8 9/16 1-7/8 11/2 2.19 8 PX 8 PX 8 Round 2.15 4 3/4 3 11/2 2.49 8 PX 8 P	В	6P2	6	Pin C	2.15	4	3/4	2-3/4	1	1.99	ı
7-B 7-250 7 Pin C 2.15 3.2 3/4 3-1/4 1 2.49 7-B 7-250 7 Pin C 2.50 8 1 2-1/4 11/4 2.69 7-B 7S-HD 7 Pin C 3.16 3.2 1 3-3/8 11/2 2.99 8 8 PX 1 8 PX 8 8 Pin C 1.47 8 9/16 1-7/8 11/2 2.19 8 PX 8 PX 8 Round 2.15 4 3/4 3 11/2 2.49 8 PX 8 P						2.0	3/4	2		1 90	ı
7-B 7-250 7 Pin C 2.50 8 1 2-1/4 1½ 2.69 7-B 7S-HD 7 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 2.99 2.99 2.99 2.99 2.99 2.12 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 2.99 2.99 2.12 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 2.99 2.99 2.12 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 2.99 2.99 2.12 Pin C 3.16 3.2 1 3-3/8 1½ 2.99 2.99 2.99 2.15 8 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.19 2.49 2.49 2.49 2.15 4 3/4 3 1½ 2.49 2.49 2.49 2.49 2.15 8 3/4 3 1½ 2.49 2.49 2.49 2.49 2.49 2.49 2.15 45 3/4 3 1½ 2.49 2.49 2.49 2.49 2.49 2.49 2.49 2.49											ı
Record   R										2.69	ı
B 8PX1 8 Pin C 1 Oz. 4 9/16 1-7/8 1½ 2.19 B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.19 A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 A 8P3 8 Round 3.16 4 3/4 3¼ 1¾ 2.49 C 8P316 8 Pin C 3 Oz. 16 1 2-1/2 1½ 2.79 B 10P16 8 Round 6.8 16 1 4-1/4 2½ 4.79  A 10P2 10 Round 6.8 16 1 4-1/4 2½ 4.79 B 10P12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10P12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 8 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 3.16 4 3/4 3-3/4 2½ 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10P3 10 Round 3.16 4 3/4 3/4 3-3/4 2½ 2.49 A 10PA1 10 Round 6.8 1 1 5 3/2 3.79 A 10PL4 10 Round 6.8 8 1 5 3/2 3.99 A 10PL4 10 Round 6.8 8 1 5 3/2 3.99 A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P28 12 Pin C 3.16 4 1 5 3/4 3.99 B 12P38 12 Pin C 3.16 4 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39						3.2	1			2.99	ı
B 8PX8 8 Pin C 1.47 8 9/16 1-7/8 1½ 2.19 A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 A 8P38 8 Round 3.16 4 3/4 3¼ 1½ 2.79 A 8P38 8 Round 3.16 8 3/4 3¼ 1½ 2.79 A 8P38 8 Round 3.16 8 3/4 3¼ 1½ 2.79 C 8P316 8 Pin C 3 Oz. 16 1 2-1/2 1¼ 2.79 A 8P16 8 Round 6.8 16 1 4-1/4 2½ 1.99 B 10P8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 4 3/4 3-3/4 2½ 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10PX1 10 Round 3.16 4 3/4 4 2½ 2.49 A 10PX1 10 Round 3.16 4 3/4 4 2½ 3.49 A 10PM10 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PM10 10 Round 6.8 8 1 5 3½ 3.99 A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39										2 10	ł
A 8P2 8 Round 2.15 4 3/4 3 1½ 2.49  A 8P28 8 Round 2.15 8 3/4 3 1½ 2.49  B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49  A 8P3 8 Round 3.16 4 3/4 3¾ 1¾ 2.79  A 8P38 8 Round 3.16 8 3/4 3¼ 1¾ 2.79  C 8P316 8 Pin C 3 Oz. 16 1 2-1/2 1½ 2.79  A 8P16 8 Round 6.8 16 1 4-1/4 2½ 1.99  B 10P2 10 Round 6.8 16 1 4-1/4 2½ 1.99  B 10P12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99  B 10PX8 10 Pin C 2.15 4 3/4 3-1/4 2 1.99  A 10PX1 10 Round 2.15 4 3/4 3-1/4 2 1.99  A 10PX1 10 Round 2.15 4 3/4 3-1/4 2 1.99  A 10PX1 10 Round 3.16 4 3/4 3-3/4 2½ 2.49  A 10P3 10 Round 3.16 4 3/4 3-3/4 2½ 2.49  A 10P4 10 Round 6.8 1 1 4-1/2 3 3.79  A 10PM10 10 Round 4.64 8 1 4-1/2 3 3.79  A 10PL4 10 Round 6.8 8 1 5 3½ 3.99  A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49  A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49  B 12P2 12 Pin C 2.15 8 3/4 3-3/4 3 3.49  B 12P2 12 Pin C 2.15 8 3/4 4-3/4 3 3.49  B 12P28 12 Pin C 2.15 8 3/4 4-3/4 3 3.49  B 12P38 12 Pin C 3.16 4 1 5 3¼ 3.99  B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39  B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39  B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39  B 12P3 12 Pin C 3.16 8 1 5 3¼ 4.39  B 12P3 12 Pin C 3.16 8 1 5 3¼ 4.39  B 12P3 12 Pin C 3.16 8 1 5 3¼ 4.39	В										ı
A 8P 28 8 Round 2.15 8 3/4 3 1½ 2.49 B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 A 8P 3 8 Round 3.16 4 3/4 3¼ 1½ 2.79 A 8P 38 8 Round 3.16 8 3/4 3¼ 1½ 2.79 A 8P 36 8 Pin C 3 Oz. 16 1 2-1/2 1½ 2.79 A 8P 16 8 Round 6.8 16 1 4-1/4 2½ 4.79 B 10P 12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10P 12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 A 10P X1 10 Round 2.15 8 3/4 3-1/4 2 1.99 A 10P X1 10 Round 3.16 4 3/4 3-1/4 2 1.99 A 10P X1 10 Round 3.16 4 3/4 3-1/4 2 1.99 A 10P X1 10 Round 3.16 4 3/4 3-3/4 2½ 2.49 A 10P X1 10 Round 3.16 4 3/4 3-3/4 2½ 2.49 A 10P X1 10 Round 4.64 4 1 4-1/2 3 3.79 A 10P X1 10 Round 6.8 3 1 5 3½ 3.79 A 10P X1 10 Round 6.8 1 1 5 3½ 3.99 B 12P X1 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 X1 12P X8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 X1 12P X8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P X8 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99 B 12P X8 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99 B 12P X8 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C 3.16 8 1 5 5 3¼ 4.39 B 12P X8 12 Pin C					N .						ı
B 8P45 8 Pin C 2.15 45 3/4 3 1½ 2.49 A 8P3 8 Round 3.16 4 3/4 3¼ 1¾ 2.79 A 8P38 8 Round 3.16 8 3/4 3¼ 1¼ 2.79 C 8P316 8 Pin C 3 Oz. 16 1 2·1/2 1¼ 2.79 A 8P16 8 Round 6.8 16 1 4·1/4 2½ 4.79 B 10P2 10 Round 1.47 4 3/4 3-1/4 2 1.99 B 10P12 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX1 10 Round 2.15 4 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10PX1 10 Round 2.15 8 3/4 3-3/4 2½ 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10PX 10 Round 3.16 4 3/4 4 2½ 3.49 A 10PM 10 Round 4.64 4 1 4-1/2 3 3.79 A 10PL4 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 8 1 5 3½ 3.99 A 12PX1 12 Round 1 to 1¼ 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P28 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99 B 12P28 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39									1		L
A 8P3 8 Round 3.16 4 3/4 3½ 1½ 2.79 A 8P38 8 Round 3.16 8 3/4 3½ 1½ 2.79 C 8P316 8 Pin C 3 Oz. 16 1 2-1/2 1½ 2.79 A 8P16 8 Round 6.8 16 1 4-1/4 2½ 4.79  A 10P2 10 Round 1.47 4 3/4 3-1/4 2 1.99 B 10P8 10 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10PX1 10 Round 2.15 4 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 4 3/4 3-1/4 2 1.99 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10P3 10 Round 3.16 4 3/4 4 2½ 2.49 A 10P3 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PM10 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 8 1 5 3½ 3.99 A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 2.15 8 3/4 4-3/4 3 3.49 B 12P28 12 Pin C 2.15 8 3/4 4-3/4 3 3.49 B 12P38 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 8 1 5 3½ 4.39											
A 8P38 8 Round 3.16 8 3/4 3½4 1½ 2.79 C 8P316 8 Pin C 3 Oz. 16 1 2-1/2 1½ 2.79 A 8P16 8 Round 6.8 16 1 4-1/4 2½ 4.79  A 10P2 10 Round 1.47 4 3/4 3-1/4 2 1.99 B 10P8 20 Pin C 1.47 8 3/4 3-1/4 2 1.99 B 10P12 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 4 3/4 3-3/4 2½ 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10PX 10 Round 3.16 4 3/4 4 2½ 3.49 A 10PM10 10 Round 4.64 4 1 4-1/2 3 3.79 A 10PM10 10 Round 6.8 3 1 5 3½ 3.99 A 12PX 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49 B 12P28 12 Pin C 2.15 8 3/4 4-3/4 3 3.49 B 12P28 12 Pin C 2.15 8 3/4 4-3/4 3 3.49 B 12P38 12 Pin C 3.16 4 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3½ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39								-		2.79	ı
C 8P316 8 Pin C 3 Oz. 16 1 2-1/2 11/4 2.79  A 10P2 10 Round 1.47 4 3/4 3-1/4 2 1.99  B 10P8 20 Pin C 1.47 8 3/4 3-1/4 2 1.99  B 10P12 10 Pin C 1.47 12 3/4 3-1/4 2 1.99  A 10PX1 10 Round 2.15 4 3/4 3-3/4 2½ 2.49  B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49  A 10PX1 10 Round 3.16 4 3/4 4 2½ 3.49  A 10PX1 10 Round 4.64 4 1 4-1/2 3 3.79  A 10PM10 10 Round 4.64 8 1 4-1/2 3 3.79  A 10PL4 10 Round 6.8 8 1 5 3½ 3.99  A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.49  A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49  B 12P18 12 Pin C 2.15 8 3/4 3-3/4 3 3.49  B 12P28 12 Pin C 2.15 8 3/4 4-3/4 3 3.49  B 12P28 12 Pin C 2.15 4 7/8 4-1/2 3/4 3.99  B 12P38 12 Pin C 3.16 4 1 5 3½ 3.99  B 12P38 12 Pin C 3.16 8 1 5 3½ 3.99  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39					Li .	8	3/4	31/4	1	2.79	ı
A 10P2 10 Round 1.47 4 3/4 3-1/4 2 1.99 B 10P12 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 4 3/4 3-3/4 2/2 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2/2 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2/2 2.49 A 10P3 10 Round 3.16 4 3/4 4 2/4 3.49 A 10P410 10 Round 4.64 4 1 4-1/2 3 3.49 A 10PL4 10 Round 6.8 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 8 1 5 3/4 3.99 A 12PX1 12 Round 1 to 1/4 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1/4 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P38 12 Pin C 3.16 4 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 4 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 4 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39											1
B 10P8 20 Pin C 1.47 8 3/4 3-1/4 2 1.99 10P12 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.95 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 1 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 1 Pin C 1.46 1 Pin C 1.95 1 Pin C 1.47 1 Pin C 1.95 1 Pin C 1.47 1 Pin C 1.49 1 Pin C 1.16 1 Pin	A	8P 16	8	Round	6.8	16	1	4-1/4	21/2	4.79	1
B 10P8 20 Pin C 1.47 8 3/4 3-1/4 2 1.99 10P12 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.47 12 3/4 3-1/4 2 1.99 1 Pin C 1.95 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 1 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 1 Pin C 1.46 1 Pin C 1.95 1 Pin C 1.47 1 Pin C 1.95 1 Pin C 1.47 1 Pin C 1.49 1 Pin C 1.16 1 Pin		10P2	20	Rose	1.47	4	3/4	3-1/4	2	1.99	-
B 10P12 10 Pin C 1.47 12 3/4 3-1/4 2 1.99 A 10PX1 10 Round 2.15 4 3/4 3-3/4 2½ 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10P3 10 Round 3.16 4 3/4 4 2½ 3.49 A 10-464 10 Round 4.64 4 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 8 1 4-1/2 3 3.79 A 10-68-8 10 Round 6.8 8 1 5 3½ 3.99 A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.99 A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3/4 3.99 B 12P28 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P38 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P38 12 Pin C 3.16 8 1 5 3½ 3.99 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39											1
A 10PX1 10 Round 2.15 4 3/4 3-3/4 2½ 2.49 B 10PX8 10 Pin C 2.15 8 3/4 3-3/4 2½ 2.49 A 10P3 10 Round 3.16 4 3/4 4 2½ 3.49 A 10P3 10 Round 4.64 4 1 4-1/2 3 3.79 A 10PM10 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 3 1 5 3½ 3.99 A 10-68-8 10 Round 6.8 8 1 5 3½ 3.99 A 12PX1 12 Round 1 to 1¼ 4 3/4 4-3/4 3 3.99 A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3¼ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39						12		3-1/4		1.99	1
A 10P3 10 Round 3.16 4 3/4 4 2½ 3.49 A 10-464 20 Round 4.64 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 3 1 5 3½ 3.99 A 10-68-8 10 Round 6.8 8 1 5 3½ 3.99 A 12PX8 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3½ 3.99 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3½ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39	A			Round							1
A 10-464 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PM10 10 Round 4.64 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 3 1 5 3½ 3.99 A 10-68-8 10 Round 6.8 8 1 5 3½ 3.99  A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.99 A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3¼ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39		1									1
A 10PM10 10 Round 4,64 8 1 4-1/2 3 3.79 A 10PL4 10 Round 6.8 8 1 5 3½ 3.99 A 10-68-8 10 Round 6.8 8 1 5 3½ 3.99 A 12PX1 12 Round 1 to 1¼ 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3¼ 3.99 B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39	10000	_					11				-
A 10PL4 10 Round 6.8 3 1 5 3½ 3.99  A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.99  A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49  B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69  B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3½ 3.99  B 12P2 12 Pin C 3.16 4 1 5 3¼ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39											1
A 10-68-8 10 Round 6.8 8 1 5 3½ 3.99  A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.49  A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49  B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.49  B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3½ 3.99  B 12P2 12 Pin C 2.15 8 7/8 4-1/2 3¼ 3.99  B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39  B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39							N .				1
A 12PX1 12 Round 1 to 1½ 4 3/4 4-3/4 3 3.49 A 12PX8 12 Round 1 to 1½ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3½ 3.99 B 12P28 12 Pin C 2.15 8 7/8 4-1/2 3½ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39											-
A 12PX8 12 Round 1 to 1¼ 8 3/4 4-3/4 3 3.49 B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3¼ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39				-			_		-		-
B 12P18 12 Pin C 1.47 8 3/4 4-3/4 3 3.69 B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3/4 3.99 B 12P3 12 Pin C 3.16 4 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39 B 12P38 12 Pin C 3.16 8 1 5 3/4 4.39							2				F
B 12P2 12 Pin C 2.15 4 7/8 4-1/2 3¼ 3.99 B 12P3 12 Pin C 3.16 4 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3¼ 4.39											1
B 12P28 12 Pin C 2.15 8 7.8 4-1/2 334 3.99 B 12P3 12 Pin C 3.16 4 1 5 334 4.39 B 12P38 12 Pin C 3.16 8 1 5 334 4.39			1						1	3.99	1
B 12P3 12 Pin C 3.16 4 1 5 3½ 4.39 B 12P38 12 Pin C 3.16 8 1 5 3½ 4.39		1								3.99	1
420			12	Pin C	3.16		1	_			1
B 12-31-32   12 Pin C 3.16   321 1 5   31/4 4.39	4				N .						E
	B	12-31-32	12	Pin C	3.16	32	1	5	1 31/4	4.39	1

Туре	Stock No.	Size	Shape	Mag. Wt. Type	VC Imp.	VC Dia.	Depth	Ship.	Price
Α	12P44	1-2	Round	4.64	4	1	5-1/2	31/2	4.69
Α	12P6	12	Round	6.8	8	1	6	5	5.59
Α	12P16	12	Round	6.8	16	1	6	5	5.59
C	12P 10	12	Pin C	10 Oz.	8	1	3-1/2	4	5,59
A	15-58 40 15 X	15	Round	6.8	8	1	7	7	5.95



	_		-						1	
	Туре	Stock No.	Size	Shape	Mag. Wt. Type	VC Imp.	VC Dia	Depth	Ship. Wt.	Price
-	A	26-147-3	21/2×61/4	Rect.	1.47	- 8	9/16	1-3/4	1/2	1.49
	A	26-100-16	21/4×61/4	Rect.	1 Oz.	16	9/16	1-3/4	1/2	1.49
	С	26-100-3	21/0861/4	Rect.	1 Oz.	4	9/16	1-1/2	1/2	1.49
1	A	210-147-8	21 2×10	Rect.	1.47	8	1"	2-1/4	1	2.29
	A	210-E3-8	21/2×10		2.16	8	9/16	2-1/2	1	2.29
	С	135 A 3-3	3×5	Rect.	.53	4	9/16	1-3/4	1/2	.99
	A	135A6	3×5	Rect.	.53	6	9/16	2	3/4	.99
Н	Â	135C3-8	3×5	Rect.	1 Oz.	8	9/16	2	3/4	.99
	A	1-49D996	3x5	Rect.	1.47	4	9/16	2	3/4	.99
	A	135D8	3×5	Rect.	1.47	8	9/16	2	3/4	.99
	A	135E8	3×5	Rect.	2.15	8	9/16	2	1	1.19
			4 X 6	100			0.446		1/2	-99
	A	46P1	4X6	Rect.	1 Oz.	4	9/16	2	1/2	.99
8	A	46P 18		Rect,	1 Oz.	8	9/16	2		
	A	46-147-3	4X6	Rect.	1.47	3	9/16	2 2	3/4	-99
3	A	46-147-8	970	Rect.	1.47	8	9/16		3/4	.99
	A	48 CMS-3	4X8	Rect.	1 Oz.	3.2	9/16	2-1/2	116,	1.69
	Α	48-173-3	4X8	Rect.	1.73	3.2	9/16	2-1/4	31/4	2.19
	A	48-173-8	4 X 8	Rect.	1 73	8	9/16	2-1/4	13/4	2,19
	A	48E3-3	4X8	Rect.	2.15	3.2	9/16	2-1/2	11/4	2.29
2	A	410-147-3	4X10	Rect.	1.47	3	9/16	3	1	1.99
	A	410-173-8	4X10	Rect.	1.73	8	7/8	2-3/4	11/4	2,49
	Α	410-244-8	4X10	Rect.	2.44	8	7/8	2-3/4	11/4	2.79
7	A	57C3-3	5X7	Rect.	1 Oz.	4	9, 16	1-1/2	1	1.49
9	A	57-3-8	5X7	Rect.	1 Oz.	8	9/16			1.49
	A	57D3-8	5X7	Rect.	1.47	3	9/16	1/ -		1.59
	A	57 E 3	5X7	Rect.	2.15	4	9/16	4/ -		1.99
	A	57 E 3-8	5X7	Rect.	2.15	В	9/16	1-1/2		1.99
	D	57FBI	5X7	Rect.	1.47	8	9/16	1-1/2	1	2.99
•		0, ==	-				0/16	2-7/8	11/2	1.49
	С	69HC69.47	6X9	Oval	.7 1 Oz.	4	9/16	2-7/8	11/2	1.69
9	С	69-8	6X9	Ovat	1.47	8		311	11/2	1.99
9	A	69P	6X9	Oval	1.47	4	9/16	311	11/2	
9	A	69SWP-147	6X9	Oval	1.73	8	117	2-3/4	11/4	2.79
ģ	A	69-173-8	6X9	Oval	1.73	20	1.00	3"	13/4	2.49
	A	69-17 20	6X9	Oval	2	-	1''	311	2	2,49
9	D	69S-CLM	6X9	Oval	3.16	8	1,00	411	1%	2,99
ģ	A	69P38	6X9	Oval	4.64	8	3/4	422	3	2.99
9	A	69HD69-4	6X9	Oval	6.8	8	127	411	3	4.95
ģ	A	69G16	OXY	Oval		16	-	1	T	4.73
ó		CLOSE OUT	TCDE	CIAL	1		1 4	a 11 C	DEA	VED

#### CLOSE OUT SPECIAL ACCOUSTICAL TILE BLOCKS Series M . types for ceilings

Reg. \$6.90 List 1.99 Standard Perfore Model 10-8 McGEE LOW PRICES

12" x 12" Ship. Wt. 31/2 lbs. Reg. \$8.02 List Full Random Model 10-8R

series M. o. coosteel tile black types for coillegt.
Despend to match and replace standard \$2^\* x \$2^\* x \$3^\* x assults the
deficit in ealths standard preferration of roll tradition tepes. Permits a
completely, buthins spender as stem;
Considerated at \$2 x x initial with performing spender girller.
The distortion have a stem; should not place that the late feeling
much press meaning have feeling and permits that the late feeling
much press meaning have feeling.



\$12.90

10 For




ONLY 150 PIECES TO SELL

24 Series — Louvered ceiling brushed eluminium beffle designed to effectively spread the high frequencies. Can be mounted to outler box (through adapter) or with 4 toggle boils.

3% Lbs. 16 5/16" 5%"

# VALUES IN IMPORTED ELECTRONIC TOOLS





Fully drop forged from fine Sneffield steet. Red baked ename! handles, Fully polished head. Precision milled jaws. Carefully sharpened cutter. An excellent promotional 

LONG NOSE CUTTING PLIER. Nickel Plated (E)



Fully drop forged from fine Sheffeeld steel. Fully polished and nickel plated to resist lust. Precision milled jaws. Carefully pened cutter. 

LONG NOSE CUTTING PLIER



Fully drop forged from fine Sheffield tool steel. Hardened and tempered. Full overal polished with knurled handles. The finish preferred by professionals. Precision milied jaws, Carfully sharpened cutter.

\_ 64 in. .....95¢

ERALD HEAVY DUTY SOLDERING PISTOL

30 WATT Stock No.





Fully drop lorged, hardened and tempered Sheffield tool steel, Prolessional finish Full polish with knurled handles. Precision milled jaws. Sharpened cutting edges.

1517 \_7 in. \_\_\_\_ \$1.19¢ WATERPUMP PLIER TO BEALL 

Drop forged from Sheffield Steel. Properly hardened and tomogred, Milled laws, Nickel plated finish. Four positions.

1029P - 9/3 III. 4------ 95 ¢

SLIP JOINT COMBINATION PLIER




Fully drop forged from Sheffield steel. Polished head and knurled handles. Nickel plated overall, Carefully hardened and tempered. Precision milled jams.

DIAGONAL CUTTING PLIER



Fully drop forged from fine Sheffield steel. Red baked enamel handles. Fully polished head. Carefully sharpened cutting edge. An excellent promotion number. 79 ¢

SPINETTE SOCKET WRENCH and SCREWDRIVER SET



Consists of five sockets, sizes
42, 5/16, 11/32, 3/8, and
7/16, strung onto hexagon
shaft which ends in a 4, screw driver. Shock-proof handle, bright finish sockets Stock No. Price

1100

99¢ Stock No. 30-705

SET. 8-1/2", 6-3/4", 5-1/4", 4-1/2", and 3-1/4" slice types and 5-3/4" Philips Better grade 5tee! lips. blades. Easy-grip, 5000V plastic-insulated handles. Polyethylene pegboard pack

Model 30-706-6-Pc. Set

996



STRIPPERS



Cuts or strips at any point along wire. Tem-pered steel, insulated handles. Pawl locks stripper for wire sizes 12 through 22, and prevents crushing or accidental cutting of

Model 30-850-Wire Stripper 69C

\*\*\*\*\*\*\*\*\*\*\* CHROME TOP QUALITY HAND TOOLS WITH PLASTIC INSULATED HANDLES Priced below import cost.

We believe these tools

Model 30-100

ore equal to domestic taals of twice the price Model 30-200

Long Nose Rodio Pliers

Made from the finest quality chrome steel. All tools are made for perfect fit . We believe these to be as fine a quality as there is on the market,

regardless of price. 100% guaranteed- Plastic insulated handles. A quality import. Your choice of these 500 quality tools for only 99e each. \*\*\*\*\*\*\*\*\*\*\*

# NEON VOLTAGE TESTER



Combination insulated blade screwdriver and high voltage-low voltage neon tester with selfcontained current limiting resistor. Transparent yellow handle contains molded banana jack and pocket clip. Overall length 43/4", blade length 134". Indicates high voltage up to 12,000 volts. By inserting a banana plug and lead into the handle you may also test AC and DC voltages from 90 to 380 volts. Tests TV and Ignition systems, live wires, fuses and B-plus, Mounted 12 to a display card, Made in West Germany,

60 ASSORTED SCREWDRIVER DISPLAY IDEAL FOR

SCHOOLS

COLOR CODED Sain-1 SCREWDRIVER SET No. 1300 \$1.99

Packaged in handy 2-piece see-thru plastic durable carrying case. Each color coded minihandle screwdriver snaps firmly into a suregrip standard size master handle.

Each blade is made of hardened steel; sizes: 1/8", 3/16" and 1/4". Phillips sizes are: miniature, standard and large. Also included are one awl and one screw starter.

#### 9 PIECE UTILITY PLIER AND SCREW DRIVER SET



#### No. TM109

\$499

The assortment of screwdrivers and awl fit firmly in a strong brass chuck that has a non-flammable amber plastic handle. The set consists of:

1-Round Nose Plier 51/2"

1-Long Nose Piler w/cutter 51/3"

1-Diagonal Cutting Nipper 5"

1-Flat Nose Plier 51/2"


1-Phillips Screwdriver No. 1

2-Standard Screwdriver Blade width 32 and 32

1-Awi

1-Plastic amber handle and brass chuck These high quality tools are packaged in a vinyl handy-bag with a built-on snap.

PRECISION SCREWDRIVER KIT



CLEAR PLASTIC CARRY CASE

6 Pieces

Blade width 0.8 to 3.8mm

6- piece Jeweler's screw-driver set for precision work, Chrome plated brass Handles, Hardened and tempered blades, 6 sizes 0-1-2-3-4-5. Packaged in a 23/x5" Clear Plastic

Stock No.

Price

90-805

\$1.99

### HIGH SPEED ROTARY FILES ggc EACH

Stock No. PTRF-1

\*File Regular 1/4" Electric Drill "Cuta Wood, Metal or Plastic I'deal for the Hobbylst, Model Bullder, or Hame Workshop......

\*The cree, rotary file-treamer, high good for use fit any 1-4" electric drill. A should be provided by the control of the control o

FACTORY RE-GROUND ROTARY FILES
SPECIAL SALE
AGE
AND TO TO TO THE SECOND FOR \$2.79

39° то 79°

to 5/32". Overall length at.".

ilius, shown), 31th spiral reamer L/S' for metal or wood, Sale price, 10g ca, star bell nose deburring tool. Jim t/4 ich.
nose deburring tool, itaa a
le wach.
ouw deburring tool, itaa 1/4"



**Nutdriver Sets** 

No. 127TB "Tray Bien" Net Each \$6.75

No. 13778 "Tray Bien" Net Each \$7.65

No. 147TB "Tray Bien" Net Euch \$8.94

Hendy, yellow nolded plastic bench tray has fold-away atand and provisions for wait incurring. Sing fock (resture holds tools securely yet permits easy reasons). Centains 7 color coded, solid shaft auditivers has size of 3/6", 3/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/2", 3/6", 1/4", 1

iodel 137TB Contains 5 color coded solld shelt suddrivers them sizes 3/10, /4", 5/10", 11/32", 5/8" and 2 hollow shaft drivers then sizes 1/2",0/16 jodel 147TB. Handy, Beige molded planur Banth Tray contains ? color coded hollow sheft nutdrivers (hes sizes 1/4", 6/32", 5/12", 11/52", 3/2, 147TB. N

ul Driver Set in Plantie Bench Tray...... No. 600. Combination Screwdover/Nutdiriver Set. Handy-4-way tool with pocket clip. 1/2" and 3/4" hes openings in handle. Stubby blade has a | Phillips and 3/4" elected set. - Net Each 7, 92





Color coded for easy identification of sizes. Finest quality nutdrivers with full size shockproof, heakproof plastic handles. Hollow shaft type fits over bolts, volume controls, etc. 7 oz. ea.

	Hollow 20411 Type					Standard Shert Type				
Stock Nu.	Depth of Hole	Nut Size	Lgth.	Net Each	Stock No.	Nut	Lgth.	Net Each		
HS8	6**	1/4	7"	1.15	6	3/16	5"	1.01		
HS10	5"	5/16	7	1.15	7	7/32	6"	1.01		
HS11	5"	11/32	7"	1.15	8	1/4	6"	1.01		
H512	5"	3/8	7"	1,15	9	9/32	6"	1.01		
HS14	5"	7/16	7%"	1.32	10	5/16	6"	1,01		
HS15	5"	1/2	7X"	1.32	11	11/32	6"	1.01		
HS18	5"	9/16	7%"	1.38	12	3/8	6"	1.01		
H\$20	5"	5/8	7%"	1.55	14	7/16	6"	1.25		
Stubby	Type	For Poc	ket Siz	e. 1-1/8	" long d	haft, Ove	rnll Leth	3-1/8		
SB	For 1/4"	"nuts					0.000	88d		
610	En- 6/2/	£ 14 1.						004		

\$10 For 3/16" nuts. COMPACT NUTDRIVER AND SCREWDRIVER SETS







Screwdriver Set. WITH SLIP-ON TORQUE HANDLES

These ests do more jobs with fewer tools, save beach space, lighten the years kit, Remarks his "highyback" torque amplifiers handle staps over top of color coded midget tools to provide larger gripping surface, gartend read increased driving power. Bim, time sentincy labetic case first pocket, has Dat beee for use as bench stand, Handlest, most often needed tools. MINIATURE NUTDRIVER SET

Complete set of ten pretation management are middly each chock-proof, breakproof pleate handless, edge coded for instant identification. Sees, 3.37°, 1.69°, 5.32°, 3.10°°, 7.32°, 3.10°°, 7.32°, 3.10°°, 7.32°, 3.10°°, 7.32°, 3.10°°, 3.12°, 3.10°°, 3.12°, 3.10°°, 3.12°, 3.10°°, 3.12°, 3.10°°, 3.12°, 3.10°°, 3.10°, 3.11°, 3.1


PRECISION SCREWDRIVER SET 

NUTDRIVER AND SCREWDRIVER SET

Includes the small popular wised tools from above setts, 2 nutdrivers 1 4".

5/16" 2 Phillips screwdriver No. 8 and No. 11 All 3-1/2" pocket size,
with teeque handle. Shed, Wt. 11h.

PS7. Nutdriver and Scrawdriver Set, Plantic Cane Each.....\$4.28





as a handy bench stand. Slipover cover fits tightly, has integral snap lock. Contains 10 color coded, hollow shaft nutdrivers thex sizes 30", 30", 30", 30", 30", 30"). Net each \$11.94


No. 99 LN = 7 Piece Allen Hea Type Scraw-driver KR. Regular size (1-1/16" x 41/8") Series 99 handle and 6 Allen liex type screw-driver blooks 41/16" thru 3/16"), Snap fasterie case, Not each S4.65

2142FEAHU

VERSATILE SOCKET WRENCH SET Model 1001 - 14 piece, 1/4" square drive socket wrench set, designed for electronic, automotive and industrial

use. Includes 6 pt. sockets 3/16" to 1/2", 10 pt. sockets 1/4" and 5/16", reversible entchet, 2" extension and 5-3/4" spinner/extension.

.....\$12.40 Net each .....



Magnetic fixed-handle nutdrivers, the ultimate in cunvenience for operations involving hea flasteners. Newly designed handle provides adequate torque and distinguishes magnetic tools from regular Xvelite nutdrivers.

Stock No.	Not Size	Length	Styler	
P-8-M	1/4	1%	Pocket Clip	1.01
P-10-M	5/16	1%	Pocket Clip	1.01
8 64	1/4	3	Regular	1,55
10-M	5/16	3	Regular	1.55
A-8-M	1/4	6	Extra Long	1.96
A-10-M	5/16	ě.	Extra Long	1.94
MBAA	1/4	16-3/4	Super Lang	4,59
AA-10-M	5/16	16-3/4	Super "Long	4.59

## KCF TE Phillips Screwdrivers





Chrome vanadium steel blades. Precision points. Shockproof, breakproof, amber plastic (ULI handles.

CATALOG NO.	POINT	BLADE	BLADE	MARIOLE DIME.	OYERALL LENGTH	REY				
	POCKEY CLIP STYLE									
P12\$	0	16"	2"	1/2" x 21/4"	4!/4"	\$ .54				
STURBY										
SX101	1	3,0"	1%,"	%" x 11/3"	213/6"	.84				
SX102	2	1/4"	13,5"	1%" x2"	33/10"	.95				
			REGULA	t						
X101	1	36"	3"	%" 13%"	6%*	.91				
X102	2	16"	4"	1" x3%"	71/4"	1,11				
X103	3	376"	6"	11/4" x 41/4"	101/4"	1.62				
X104	4	3 "	8~	11/6" x 41/2"	1215"	2.03				

#### Round Blade Screwdrivers for —— Slotted Screws

Blades are forged from tough. AtSI 615tl chrome vanadium steel.

CATALOG	BLADE	HAMPLE	OVERALL	MET				
			LENGTH	EACH				
R3322	2-	13" × 21/4"	41,"	\$ .41				
R1E1	2	35" x 234"	43,0	.41				
R183	3"	1/2" x 21/4"	514"	.44				
R1841,	4"	15" x 234"	614"	.47				
REGULAR								
R184	4*	34" x 23,"	63/4"	.54				
R186	6"	34" 1254"	B5 -	.61				
R188	8"			.71				
W1810	10"	3/4" x 23/4"		.81				
R5323	3"	3, " # 75. "		.61				
R5324	4"			.61				
R5325	5-			.64				
R5328	8"			.81				
P2162	2"			.78				
				.84				
R3166	6"	" a 3% a"	953	.95				
R3168	8"	7 x 35 "	1130"	1.05				
8144	4*	1" x 3%"	72/4	1.11				
R146	6-	1" x 3%"	9%"	1.22				
R148	8"	1" x 3%"	1136"	1.28				
R5166	6~	1%"×4%"	10%	1.45				
	R13322 R181 R183 R1841 R184 R186 R188 R1810 R5323 R5324 R5325 R5328 R3163 R3166 R3168 R144 R146 R148	POCKET CLI R3322 2" R181 2" R181 2" R181 4" RESUL R184 4" R185 6" R188 8" R1810 10" R5323 3" R5324 8" R5325 5" R5328 8" R3163 3" R3164 6" R3168 8" R144 4" R146 6" R148 8"	NO.	NO.				

## Series 99 Compact Sets

Pocket size, plastic cases pack an unusual number of tools into a small space. Blades are interchangeable in regular Series 99 handle included with each set.



99PS-40-11-Piece Allen Hax Type Screwdriver Set, 9 Allen hex type acrewdriver blades (.050" thru 3/16"), 4" extension blade.

Not each...57.43

99PS-80--14-Piece Nutdriver/Screw-driver Set. 7 Nutdriver (3/16" thru 3/8"), 3/16" and 9/32" slotted serewdriver, #1 and #2
Phillips screwdriver, 4 extension. Ne; each...\$9.15



99PS-60-11-Piece Bristol Screw driver Set. For Bristol multi-ple-spline socket screws. 9 Bristol screwdriver blades (.048"/4-flute thru .183"/6 flute). 4" extension blade. Net each .... \$7.43

#### Diagonal Pliers

Long Nose Pliers

#### DIAGONAL PLIERS

and a midder a tensulou dath tot close-dinutes Mosk'	. Net s	a, 3.07
55CG - 5" versatile plier with cushion grip.	Ner e	- 3.77
SACG - 6"- gushian min lang dir		2.00
56CG - 6"; coshion grip; long slim jaws		
66CG - 6' all-purpose plier; cushion grip.	Net a	a. 4.08
67CG - 7" heavy-duty plier; cushion grip	At	0, 4,00
er oo i meary duty prict common grip	· LAGE III	a. 4.08
LONG NOSE PLIERS		
410G - Midget 4" without side cutters; cushlon grip		- 7 20
4100 - Mitaget 4 Without side cutters; custion grip	Mat 6	a. 3.38
52CG - 64"; no side cutters; cushion grip	No.	a 3.30
Died - on with side cutter, cosmon grip,	tasr a	a. 4.16

#### MINIATURE ELECTRONIC PLIERS

Small, lightweight pliers designed for holding, bending and cutting fine wires in electronic, radio/TV, electrical and lewelry work. All

mare cosmon grip namules and polished needs and anough	
70CG - Flat Nose: 4%" long: no cutter	NET 42 3 98
71CG - Round Nose: 446": for looning fine wire "	Not az 4 44
70CG - Flat Nose; 4%" long: no cutter	Not as 4 16
Committee, 4 long, shoots jawa,	IAET 49' 4'10

#### SPECIAL TIP CUTTING PLIERS

73CG - 4%" Needle Nose, Snap cuts fine wires.

OIAGONAL FLUSH CUTTING PLIERS
74CG - 4" long for fast elean tip cutting.

Partin AND TW PLIERS Net ea. 5.69 Net es. 5.00



#### & Cutters



## Screwdriver 2

**Nutdriver** Set



#### Adjustable Wrenches

Rugged, forged alloy steel construction. Chromium plated with polished heads; cushion grip (CG) handles.

Caralog No.	Length	Opening	Net Each
44CG 46CG 48CG	4". 6". 8"	1/2" 3/4" 15/16"	\$3.44 \$3.48 - \$3.93
12		El.	ectronic




Snips

86CG - 64" Electronic Sneps with cushion grip......Net \$3.23



Service Master Kit 995.66 Z 1-Paret set (B roll) op plants stonfed catters care Kit thi lodge (i "burg niese and I "hopping plants, both self-routhings, graph, "burg-plants allgorithm serverth regular 11 1276 42 178") and stability (I 1726 in 2") plants stability (ii) inter-angretise blants V ergular (I 4/16 in inter-) 172")

IBAR 12 Parce Compact Nutsirerer/Survey/com Bat Jun-ion sate CETE | Series VP handle and following blades Outsirpers (2000) their DE | July | Society | Soc





Miniature Jewelers-type slotted & Phillips screwdriversdesigned for finest detail work.

M50 – 5 slotted screwdrivers (.040" thre 100") Net...\$1.50
M60 – 5 slotted screwdrivers (.040" thru .100"), #00 Phillips and torque amplifier handle. Net...\$2.10 Net .... \$2.10

Knife and screwdriver both. Screwdriver has sharp edge for scraping insulation. Net \$2.95 K22.....



Has tape holder, knife elip and five tool pockets. Durable 





# Weller Soldering Guns and Tools



MODEL 8200PK EXPERT OWAL HEAT SOLDERING GUM KIT Includes Welter dual heat 100/140 wate gun, magnet plantle ut by case, there sold the, the-charding wrench, flag Brush, subjection and auditor.

SERIES "D" DUAL-HEAT PROFESSIONAL GUNS

illion cumments of the distribution of the desired without damage to insuration under the grip assures full constant heat, which action of the lackers distribution set resistance and oxidation, Model 9.486 full duty gun rated 145/210 waits let 0-556; Heavy-duty gun rated 24 325 warts.







MODEL D-SBOPK NEAVY-DUTY DUAL HEAT SOLDERING GUN RIT Features 249 '425 watt dual heat gun, break-proof plantic carrying case, no amouthing and cutting light, lipschanging witersh and solder.

Weiler No.	Rating. Watts	Not Each, Lots of	Waller	Rating.	Not Each; Lots of 1 3-11
8280PM 8280PM 83448	1101 + 611 1101 F 111 1 1 5 2 11	7.45 6.70 9.15 8.25 9.95 8.95	DSSOPH	2410 H25	11.20 10.15

#### WELLER TEMPMATIC SOLDERING TOOL

FAST HEATING-trigger action LIGHTWEIGHT-weighs only 7 ozs. RELIABLE-exclusive tempature controlled POWERFUL-for light and heavy soldering Model STAINLESS STEEL-long reach barrel COMPLETE with tempature controlled POWERHEAD and quick change to other Tool with 7A700 De.F. 3, 16 th chisel point 1995

trically non-conductive, fast acting, meets every requirement for high speed soldering and all applicable Mil and Federal Specifications - it so specified

50% Tin 1 th Speed 697 12 20" BEALTH FRILE 50% Load I-lb. Spool MP (1 14" Blatters PRICE

60% Tin 992 (3 37": 014110 9 99K\$ \$2.27 lb

KESTER "44" RESIN CORE SOLDER Solder prices subject to changes.

_	The state of the s									
Weller No.	For Gun or Iron No.	Tip	Phy. 2	Wallet No.	For Gun er tron No.	Type	Net Each			
8125° 7258	8100B, 8200 8250A, 13-550	Nolder Nolder	490	61201 61401 61101	8100B, 8200, 15-440 82503, 17-550	Smoothing	490			
rais	H25HA, 13-550 H100, 13-440	Holder		61107 61307	8100B, 8200, 12-440 8250A, 12-550	C'urring C'urrinc	400			

### Ungar Interchangeable Tips...

J			
TIP TEMPERATURES	CHISEL TIP LONG TAPER	PYRAMIO TIP	CHISEL TIP SHORT TAPER
850° to 1000° F #4000 Super Hi-Heat Series 47-1/2 Watt	#4033 Tip 1-5/8" tong, 1/4" wide. New copper altoy, fron clad, silver plated. 4033 \$3.38 eq.	#4036 Tip 1-1/8" long, 3/8" diameter. Copper, iron clad, silver plated 4036 \$3.38 eq.	#4039 Tip 1-1/8" long, 3/8" diameter. Copper, iron clad, silver plated. 4039 \$3.38 eq.
750° to 800° F. #1200 Hi-Heat Series 37-1/2 Watt	#1233 Tip 1-5/8" long, 1/4" wide. Copper, unplated. 1233 \$2.35 eq.	#1236 Tip 1-1/8" long, 5/16" diameter. Pure solid Armoo iron, silver plated. 1236 \$2.35 co.	#1239 Tip 1-1/8" long, 3/8" diameter. Pure solid Armco iron, silver plated.  1239 \$2.35 eq.
650° to 750° F. #500 Standard Series 23-1/2 Watt	#533 Tip 1-5/8" long, 3/16" wide, Copper, unplated. 533 \$1.62 eq.	#536 Tip 1-1/8" long, 5/16" diameter. Copper, unplated. 536 \$1.62 eq.	#539 Tip 1-1/8" long, 5/16" dlameter. Copper, unplated. 539 \$1,62 eq.

New UNGAR HEATING UNITS AND THREAD-ON TIPS for Hi-Speed Repeat Soldering



600° to 650°F - 23½ Watts 537 \$1.88 eg. #1237 Hi-Speed Heating Unit— 750"-800"F. 374/2 Watts 1237 52.35 eq.

#4037 Hi-Speed Heating Unit -850°-900°F. 4742 Watts

4037 \$3.35 ca.

#PL 111 PENCIL TIP. 1/4" x 3/4" iron clad, Silver Plated.

#111 Plain Copper .43 ea.

#PL 113 CHISEL TIP. 16" x 34" Iron clad, Silver Plated. PL113 .85 ea. .43 ea. #113 Plain Copper.

#PL 114 Stepped Micro-Spade, fron Clad, Silver Plated .85 eq.

#116 5/16" Pyramid, Rugged Copper Alloy 43c ed 43c ea.

.85 eq. #PL 116 S/16" Pyramid, Iron .43 eq. Clad, Silver Plated 85c eq 85c ea.

# ARROW AUTOMATIC JAM-PROOF STAPLE TACKERS



SHOOTS-STAPLES WHEREVER

Kat is complete in attractive nachage with T-10 Gun, \$1 Steples in 4 sizes 7 3/8 17 and 9/16\*) and hor-rly attalled removes, Sing wt. 5 lbs. Lest Value \$15.50, Net Price

T-50K Kit complete.... \$17.25 

Les Leth, Box 5009 1/4" 522.75 3/8" 53.25 1/2" \$3.80 9/16" \$3.80 T-50-1/1 T-50-3/8 T-50-1/2 T-50-9/16 \$3.28 \$3.80 \$3.80

T-32 PRODUCTION STAPLE GUN

Morpi T-J.J. Production Stanic Cun-te Cheme Innahed Sun I with vi-ciation eengineered working parts. Etonauvel, used by danflaymen, I v. Sayvicemmen, Uphalaterers. Auto-orities of the Company of the Com-ciliant of the Company of the Com-ciliant Company of the Com-ciliant Company of the Com-tended Spirit Stanics at ories, accurage, 1916 of proving accura-te Company of the Company of the Com-tended Spirit Stanics at ories, accurage, 1916 of proving accura-

T-32-3/16 1/16" \$2.80 T-32-1/4 1/4" \$2.50 T-32-5/16 5/16" \$2.75

Designed to fill the needs of the serviceman, hi-fi installer or homeowner. A medium weight remarkably low priced Gun Tacker that will take care of 90% of all your tacking needs. Fastens ceiling tile, wall board, grille cloth, and many other uses. Durable, precision engineered, operates on double leverage principle. Works 10 times faster than hammer and nalls with powerful penetration. Solid steel construction with jem-proof mechanism. Baked enamel finish, Shpg. Wt. 1½1bs

STAPLE CON TACKER

No. T-55

Models T-50 and T-55 use the same 6 staple sizes,





\$18.00

Handy tools to gravide easily more afficient that allaten of and sables, Oriver a teples a reity into desired pration close corners, mailtone school corners, har busiting the same which eliminets Canger of damaging were estables or ver louch projection when the form custom for the 

odel T-25 for -ire up to 4" in lameter. Wt. 1 lb. 67.0.00 \$18.00

STAPLES FOR ABOVE GUNS T-75-5/8 T-75-7/8 T-25-7/16 T-25-9/16

HIGH-SPEED STAPLE DRIVER AT LOWEST PRICE EVER

A fact, rawy operating mun tather with the first property of the fact of the f 17-21 Gun Tocker ..... 56.95

STAPLES FOR MODEL JT-21 GUN JT-1/4" 1000 for...... 79 c JJ-5/16" 5000 for...... \$3.45

#778 SOLDERING HANDLE Ungar's red handle with cork grip. For all Ungar interchangeable Tips. Model 776 Price \$1.87

FULL-CONTACT
SPRING SOCKET, NO TIP WOBBLE HANDLE IN PASTEL COLOR - NEW POLYVINYL INSULATED CORD - OCTAGON
SHAPE GUARO WASHER

\$1.87 ea.

UNGAR 6010 40 wott Imperial with 3 tips. ---- Net \$9.00



f 15 V. AC cord included

Best buys in small soldering irons with most popular tips.



PENCIL TYPE SOLDERING IRON

Lightweight 30 watt iron for continuous use. Perfectly suited for industrial and hobbylist use. Welf-balanced headle, 2 oz. weight, and heat shield assures comfortable operation. Replaceable \*0. copper tip and nichrome element. For 110-120 volts ACIDC Complete with heavy duty cord and plug. Size: 9" long Weight: 2 oz. (less cord) Attractively packaged for peg-rack sales.

No. Net Price \$530 30 watt iron \$199
\$531 Replacement tip for about

30 watt iron \$1.99 Replacement tip for above .39 Replacement element for above.79

SL-SO STAPLE LIFTER \$1.00 JB-66 Plies Type HAND STAPLER

No. T-32 GUN TACKER

\$1.50 htdd: | He/d Filter Type Hand Storier has a bristle had been too be been been thought the beautiful with the beautiful wi

McGee Has Top Values in Transistors for Service Replacement and for the Builder.



GENUINE TRANSISTORS 2N-44

Jobber Boxed McGees Low prices

...FACTORY FRESH.... 2N-1970 \$2.39

\$1.29

RCA SK-3003RCA SK-3018 TRANSISTOR PACK OF 4

\$2.16

TRANSISTOR MNPN 99¢ PASK OF 4

icement or Experimenter Use in Audio Ous For Replacement or Experimenter Use in VHF TV of Battery Portable Amplifiers and Rec. Tuners, TV IF Amplifiers, FM Tuners, FM IF Amplifiers and Rec. Tuners, TV IF Amplifiers, FM Tuners, FM IF Amplifiers Operating With

Supply Voltages up to 25 Volts Output Capacitance of 1,35 pF Gain-Bandwidth Product of 800 MHz

TRANSISTOR PNP 89¢ PSS124F4

etvers Operating With:
Supply Voltages up to 9 Volts
Dissipations up to 150 mW at T<sub>A</sub> = 25°C
Typical Peak Collector Currents to 500 mA

For Replacement or Experimenter Use in Broad-ca-sciand Automobile Radios and Portable Battery Operated Receivers Operating With:

Supply Voltages up to 15 Volts.
Dissiportors up to 250 mW of T<sub>A</sub>= 250 C
Typical Collector Currents up to 5 mA
Peak Collector Currents up to 5 mA ypical Collector Currents up to 5 mA eak Callector Currents of Approx. 10 mA

TRANSISTOR

RCA SK-3008 RCA SK-3020 TRANSISTOR NPN 79 ¢ PACK OF 4 \$2.88 or Replacement or Experimenter Use in Low Level Driver, and Output al-amplifiar Stages Operating

Collector supply voltages up to 25 Volts Peak Voltages up to 40 Volts Dissipations up to 0.5 W at T = 55° C Peak Currents up to 300 mA Typical beta (hgg) of 50

GRAB BAG ASSORTMENT

FOR MADIOS HAVE PRODI IDENTIFICATION ONLY, ALL FACTORY NEWS GE - TS. ETC. AL GOOD VALUE.

stock no GB-50TR

25A15 GENUINE HITACHIN NEW GENERAL PURPOSE PNP TRANSISTOR

39¢ 3 For \$1.00

Report from Service Dealer is that this one number worked well in auto radios and other 12 volt DC circuits as RF, IF and audio gain stages, every spot except power output stages. Mc Gee sale price, 39¢ each, 3 for.....\$1.00

Automatic Rodio 6-60F GENERAL PURPOSE PNP TRANSISTOR 39¢ 3 For \$1.00

HITACHI MADE FOR AUTOMATIC AUTO RADIOS. FOR IP RF DSCLETC. SIM LAR TO 28A18 LISTED ABOVE SERVICE MEN MIGHT DO WELL TO HAVE BOTH ON HAND TO PICK THE BEST POSSIBLE ONE FOR THE AUTO RADIO PROFORMANCE.

MATSUSHITA SILICON NPN HIGH POWER TRANSISTOR Stock No \$3.95 ea

2SC687 2 tor \$7.50

Equiv. ,to HEP-707, Net \$10.90 A Transistor for equal or better replacement, Maximum 400 Vdc. up to 125 watte power. TO-3 case

SODULES ARE WITH WIRELESS IN TRANSMITTER SENSATIONAL SALE

SOLID STATE MODULES

For simple mounting plugs into socket, provided Also prevents damage to components by soldering direct to socket rather than module.

POWER SUPPLY NOT INCLUDED PHONO PELAMPLIFIE FOR AMPLIFIE FOR AMPLIFIES MAGNETIC CARTEIDGES Input impedance 100 K OHM Gelin: 26 Do on: 76 De nomina Outputs 3 V someon Bapati 30 m V tartion: 0.13% (or 1 V Level)

Numery Response: BIAA or Supply: 9 V-12 V DC No. MESO

2 TRANSISTORS (7) 258-175 \$1.95 two fer \$3.80

0:

WIRELESS COOF OSCILLATOR Here transmitter of code ugnot used with AM radio, Car used at test banch signal source for troubleshooting AM Radios. Cet No M851 \$1.95 t=o for \$3.80

MODULES ARE WITH WISELESS IM TRANSMITTSE
CASES
Can be used with microphone, telephone call and alc. to send dynal up in about 150 dee.

Input (impediame). St COMM.
Meximum Dought 3 m W.
Transmitter Frequency: 88 MMZ-108 MMZ
Power Supply 9 V OC
Cat No. M637
DUAN PLASME

An electronic switch to olies needly fleak bee minieture 6 v bulb. Idcal flex medel cur, planes, or head or needle train layout Attention disjourn and onergrency warmings upons: Flouber Tambe Is me. Currenth 150 m A \$1.95 two for Power Seegly: 6 VO Cot. No. 1865)

SOWER AND

Makes on excellent quality amplifier with law disturbus and good \$1.95 two for \$3.80

Makes on excellent quality amplifier with law disturbun on frequency responses.

Casis: 20 DS \$1.95 two for \$1 mail of the property of the pro 3 TRANSISTORS

## MODULES LOW PRICES

EMPTY CASE WITH PLUG AND SOCKET

MAKE YOUR OWN SOLID STATE MODULES



39¢ 2 for 70¢ 10 sets for \$3.00

Empty com-plus and sucket & see Inside dimension; 1-15/16" L. ; 13/16" W. a 15/16" H. Mounting centers 2:5/16".

RED HOT UHF TRANSISTOR BUY. PNP populer in UHF front ends and electronic door openers Works up to 1½ gigacycles over 1000 mega cycles.

Texas Insterment

sterment MD-TXVD 594 Two

PNP 1HITRON TRANSISTOR 2N1038

Pock of 4 for \$1.99 Watt Push-Puli, up to 3 Watts with Heat Sink JOBBER SINGLE PACKED \$1.90 each in 100 Lots

Germanium PNP, Medium Pawer Audio Output Transistors in TO-S case. Average collector current up to 3 Amps.

POWER TRANSISTOR 39¢ 3 for 1.00



A general replacement for his is, medium and low wattage types such as 2N234, 2N234A, 2N235, 2N235A, 2N36B, 2N36B, 2N36B, 2N36B, 2N36B, 2N36B, 2N398, 2N397A, 2N367A, 2N667A, 2N307A, 2N352, 2N 2N400, 2N401, 2N669.

# HANOY-PACK OF TRANSISTORS PACKED BY G.E. PACKAGE OF 4 TRANSISTORS AT NEW LOW PRICES

	TYPE	IN PKG.	DESCRIPTION	APPLICATION	SIMILAR TO	OF 4
	TRO-I	4	PMP-General Purpore	Audin, 18 Switching	2N218 CK722 GT222 2H107	69¢
111	TRB-2	4	PNP-Audia Driver	Audia Driver	29107	69¢
	TRB-4	4	NPN-Germanism IF 'RP, Audia	IF.RF Audio	2N\$70	69¢
	TRB-S	4	NPN-Miser, Oscillator, Convertor	Mixer. Oscillator Converter	2N388 2N1304 2N1302, e/c.	69¢
	TRB-6	14	NPN-Germanium (with 9V Supply)	IF IRF Audio Converter	2H170 2H297 2H293	69¢
	TR8-7		PNP-1F Ampli- fige & Convertor (with 9V Supply)	If Amplifier & Converter	2N409 <sup>2</sup> 410 2N112 2N414 2N404 2N1305, etc.	69¢
7	TRB-6	4	PNP-Audio Cade Pice Oscillator, Smell Signal Devices, etc. (with OV Supply)	Prace General Purpase Audia	2N107 CK722 GT222 2N218, etc.	69¢

	180-1		Purpore	Switching	CK722 GT222 2H107	69¢
111	TRB-2	4	PNP-Audia Driver	Audia Driver	210107	69¢
	TRB-4	4	NPN-Germaniste IF RP, Audie	IF <sub>o</sub> RF Audio	2M\$70	69¢
111	TRB-S	4	NPN-Miner, Oscillator, Convertor	Mixer. Qualifotor Converter	2N388 2N1304 2N1302, erc.	69¢
	TRB-6	4	NPN-Germanium (with 9V Supply)	IF RF Audio Converser	2H17D 2H29Z 2H293	69¢
	TR8-7	1	PNP-IF Ampli- fler & Converses (with PV Supply)	If Amplifler & Converter	2N409 /410 2N112 2N414 2N404 2N1305, atc.	69¢
7	TRB-8	4	PNP-Audio Code Practice Oscillator, Smell Signal Devices, etc. (with 8V Supply)	General Purpase Audia	2N107 CK722 GT222 2N218, etc.	69¢

McGee Special AUTO RADIO TRANSISTORS

Medium Power 2N155 DR-Hi-Power

2N176



NEW LOW PRICE

2N-3055



HIGH POWERED AUDIO NPN IN TO-3 CASE
Mounting Centers (-37)679 \$15 \$159 For Replocement in Joponese 30-40 Wort Net Each

REPLACEMENT FOR



501 / 441

9 ¢ 10 For \$7.00

Popular auto radio power transistor.

# \$.39 EACH

**NEW JERSEY** 

SEMICONDUCTOR

MADE BY FAIRCHILD

**EPOXY TRANSISTORS** 

\$3.30

WILL REPLACE 80% DF ALL TRANSISTORS EPOXY No. 1

P.N.P GENERAL PURPOSE LOW NOISE AMPLIFIER

Breakdown = 60 volts; Gain 100-300 or 150 ma.

EPOXY No. 2

39¢

P.N.P. HIGH SPEED SWITCH AMPLIFIER & OSCILLATOR

Breakdown: 20 volts; Gain 50 to 200 at 10 ma. 39 ¢

Gain 30 to 200 at 10 ma.

Fraquency: 400 mc.

Replaces: 273:10-400-410-413-43-49-500-705-711A
806-995-118-2613-909-300-3905-9906-428-439MP 2230-4-30-300-3005-3906-428-439MP 2230-4-30-300-5230-518-6519-6512-518-6512-5

EPOXY No. 3 N.P.N. R.F. and I.F. AMPLIFIER Breakdowns 70 volts; Gain 50 to 200 at 10 ma. 39¢ Frequency: 250 mc.

EPOXY No. 4 N.P.N HIGH SPEED SWITCH

EPOXY No. 5

N.P.N. GENERAL PURPOSE AMPLIFIER & SWITCH

AMPLIFIER 8 SWITCH
Breakdown: 60 volts;
Gain 100:300 or 150 ma.
Frequency: 250 mv.
Replaces: 207:79-557-357-358-358A-546-547-548
551-560-587-60 6-697-730-956-1053-1117-1360-1308
1300-134-16-18-208-2558-255-2550-27143300-34-36-45-3764-397-4-168270-7397-64-1585-1364-3704-397-4-168270-7397-64-18-553-65-3764-3764-397-4283300-TR 21-AC168

#### **EPOXY TRANSISTOR** CROSS REFERENCE GUIDE

SPECIAL OFFERING

2 Each Epoxy 1-2-3-4-5 and cross ref. guide.

Transistors total A red hot value-

stock no Epoxy ETCRG-5

**POWER TRANSISTOR 25B474** MATCHED PAIR \$249

No. 2-258474
Small Diamond shaped Small Diamond shaped case, Pins 5/16' apart. Mtg. holes 15/16 center to center. With 2 Mica insulators and 4 acrews. Ideal for many models of auto stereo output stages.

# MOTOROLA UNIVERSAL TRANSISTORS

NET

EACH

1.25

-1 Common 922 Com 56 60 Cases 100 Com 10-3 Com 10-66 TO-36 TO-5 TO-100. 10 Land Com TO-72 C200 10-93

DESCRIPTION

HEP NO.

CASE

2	TO-5	Go RF Transator PRP 100000Nz 300mW	1.25	
3	TO-72	Gas Rif Transaman - PNP 25CmEHz 100mW	1,25	
50	TO-18	So RF Transport NPN 1009MN J 300mW	.79	
51	10-5	So RF Transpirer -PNP- SOMM: 600mW	1.29	
52	TO-18	St RF Temperor-PNP-100MHz 300HW	.95	
53	TO-5	# RF Transator - RPN - \$000Hz 600mW	1.15	
54	TQ-82 (8)	So R.F. Transactor-96990-30004c 310mW	F 08	
5.5	10-83 (8)	So RF Transpare-8890-2109912 310mW	1 20	
56	TO-97 (D)	St UNF Oscillator - NPM 750MHz 210mW	1.44	
57	TO-93 (B)	Si RF Transmer-PMF-300Mite 310mile	1 20	
101	00-2	Zonor Quada-10V 400mm	-95	
102	Care 50	Zoner Dapity-3/6V TW	1 20	
103	Care 54	Zerw Dodo-62V 1W	1 20	
104	C- 59	Zoruz Diode-BLIV 198	1 20	
106	Care 50	Zenar Duals-12V 1W	1 20	
134	TO IEA	Go Osoph (19434A Subsecutor)	.26	
135	TO-16A	Ge Diode (1N60 Subsetute)	.26	
151	00-6	Si Power Recoher-Stad-90P1V ISAmp	.79	
153	DO-5	Si Passer Records - Stud - 200PIV 15Amp tu	1 24	
154	Case 59	Si Recolum-Acus Laus-10PtV 1Amp	:41	
156	Cost 59	Si Recolut Aunt Lost - 200PIV 1Amp	-45	
157	Case 50	Si Recolor-Assel Lead-400PtV TAmp	-54	
158	Com 50	\$ Recision - Asset Load - 800PtV 1Amp		
159	Case 50	Se Recordor: Asset Lead ; 800PtV (Amp	-60	
160	Carp 60	Si Receiut - Axial Lauf-1000PIV 1Amp	-76	
181	<b>Cam</b> 60	St "Top Hat" Recolor-SOPIV Sharp	1 09	
167	Case 60	Si "Top Hat" Recider - 20075V 3Ame	1 25	
165	TO 92 (F)	So Duel Goods - Convinon Cathesia	.63	
166	10-02 (G)	Sr Oual Displa-Common Areals	.60	
170	Comp 54	Si Rectifier - Autor Local - 1000PtV 2.5Amp	.59	
17%	Com 108	Full Wave Bridge Rectifier - SOPLY TAmo	1.49	
175	Cam 108	Full Wave Bridge Rectifies ~ 200P1V 1Amp	2 05	
127	Case 108	Full Wave Strates Rectified 600P1V 1Amp	2 25	
178	Case 100	Full their Bridge Rectifier (800PtV 1Amp	3 05	
200	TO-3	Ga Pause Transator-PNP-TQ 5-3Amp 90Vinti	.62	
230	TO-3	Ga Favor Transvor PNF-TD 3-8Amp 90%ett	.89	
231	TO 36	Ge Peace Yearspoor -PMP-TQ-36-15Amp 150Wat1	1 69	
732	TO-3	Gar Power Transistor -FRP-TQ-3 7Amp 90Watt	2 34	
233	TO-36	Ge Power Transactor - PRP-TO-38- (55mp (708 at)	4,20	
234	TOB	Ge High Voltage Part Transferor - PNP- 200V SA 56W	3.25	
235	TO-3	Ge Hapt Voltage Part Transator - PRP - 220V 10A 56W	4.50	
236	10-41	Ger High Corrent Por Transpor - PHP 80V 75A 106W	5.70	
740	10-66	S Fower Transition NPN-TD-85-300V 500mA 10N	2 05	
241	10.66	So High Fower Transpor-NPN 160V SA 40W	1.79	
242	TD-8"	So Maid Peacer Transactor: PNP -50V 3A GWIComp to 7431	2.40	
243	10.5"	Si Med Power Engraphy - NPN -80V 3A 6001Comp. to 2421	1 79	
344	Cam 77	S High Voltage Par Transplor-NPN - 300V 500mA 25W	2 15	
246	Cem 27	\$5 May Peace Transitor-NPTs 60V 3A 30W1Comp to 2461	1.99	
246	C== 27	Si Med Power Tegranter - PMP 60V 3A 30M Comp to 2451	2 29	
247	10.3	Settingh Pawer Transactor: NPW-70V 20A 150W(Comp. to 248)	2.80	
74B	10-3	# High Power Transition -NPN-70V TOA 1508HComp to 2481	6,49	
250	TO-5	Ger Gereral Purpose Transactor -PRP -Mad.Gash 200mW	.79	
251	TO-5	Ge General Purpose Transactor -PNP Hi-Gain 200mily	.89	
752	TQ-5	Ger General Purpose Transplor - PRP - Last Last-age - 200mb	.89	
253	TO-5"	Ge General Purpose Transactor -PMP Med Gain 225mily	.05	
254	TO-5"	Ge General Purpose Transition PNP Med Gam-205mW	.89	
300	Centr 86	Thyrator (SCR) -50V SAmp	2 29	
302	Carm Bib	Divisios (SCR) -200V SAmp	2 49	
304	Com 97	Thyrania ISCRI 50V 18Amp	4 35	
305	C= 97	Thyrater SCR: Reverse Petersty -50V 15Amo	4 60	
306	Case 92	Thyrotox (SCRI 200V 15Amp	5 90	
307	Care 92	Thyranae (SCR) Reverse Polantsy - 200V 15Amp	6 20	
310	10-87 (E)	Si Unquietion Transitior 300mW	1 49	
311	TO-92 04	So Bulgoton of Tragger Claude	.99	
320	TO-92 (A)	Thyracor (SCR) - 30V 800mA	.99	
340	Care Bis	Tries - 700V BA	€.49	
553	C= 71	Integrated Carpet - ECL - Helf Adder	1 -89	
554	C- 71	Integrated Comptt-ECL-Sim Driver	1,.49	
556	Case 71	Integrated Carpet - ECL-3 Input Gate	179	
558	Case 71	Integrand Circuit ECL-J-E Fig Flop	2.39	
570	Cam 93	Ingegrated Carcurti-RT L -Qualit Gate	2.30	
571	Case 93	Integrated Certain - RITL - Dual Buffer	2.10	

P	LA	CEME	IN I CICTIMAL THE	110
	HEP NO.	CASE	DESCRIPTION	NET
	572	C== 03	Integrated Copple WTL - Out &K Fite Flop	3.90
	580	TO 99	Incorporer Copult -RTL -Dust 2-Input Gate	.95
	587	10-86	Integrated Conset - RTL 4 Imput Gate Integrated Conset RTL Dept Buffer	.99
	583	7/2 00	Antonio and Company O'Ys LM Cam Hime	1.49
-	584	TO-RE Case 71	Torque and Carpet RTs, Qual 2-triput Gate Secretarian Carpet of amount Mark Removary Amountain	3.99
	591	Cam 71	Integrated Coput - Limbs - High Possionicy Amplifier Integrated Cocust - Limbs - Walls Band Amplifier/Discriminator	3.60
	597	Case 71	Integrated Carpat - Luxini - Store Promphilist	3.25 7.95
	593 600	Cost 71 DO-21	Integrand Const - Lating 1 West Audio Power Amphilier Silicon Press Fit Rectifier (Cathode to Case)	1.11
	601	DO-21	Periodic Lucino List Leccritain (www.nor. to rem.)	1.13
	602	Cost 59	B.B Velt Zener Dade 1 Wetr S.B Velt Zener Dade 1 Wetr	1.84
	604	Case 59 Case 59	19.5 Volt Zerer Decks I Wat1	1.84
	806	Case 50	12.8 Veit Zener Dude I Watt	1,84
	606	Case 50	M.D Volt Zarar Ouds 1 Watt 15 O Volt Zarar Crods 1 Watt	1.64
	508	Case 59 Case 59	27.0 Volt Zener Duote 1 Watt	1.64
	609	Cast 59	33.0 Volt Zover Quide 1 Watt	2.49
	810	Case 59 Case 59	55.0 Vedt Zarer Omde 1 Wett 42.6 Velt Zaner Dione 9 Wett	2,49
	812	Cast 59	628 Valv Zangr Dione 9 Watt 82,0 Volv Zangr Dione 3 West	2.49
	(113	Com 59	110 Veit Zene Diode I Watt Thyruser (Sidom Controlled Rectifies)	3,65 4,40
	620 671	Cost 87L Cast 87L	Thyrager (Salgum Controlled Rectifier)	5.25 5.10
	622	C- 90	Thyristor (Silicon Controllad Rectifier)	
	823 824	TO-3	Ge Geteral Purpose Audio Peeret Amptilias PNP Ge Germal Purpose Audio Power Amptilias - PNP	2.20
	625	TO-3	Ge General Purpose Audio Power Amptilias -PNP	7.10
	626	10-3	Ge Gersesi Purpose Audio Power Amplifes - PNP	6.35
	628	10-3	Go Consest Purpose Audio Power Amplifies - Priff Go Consest Purpose Audio Power Amplifies - Priff	2.20
	629	TO-5	Ge General Purpose Austo Amphiliar - PNP	2.10
	630	TO-5	Ge General Purpose Audio Ampletor - PNP	2,20
	632	10-5 TO-5	Go General Purpose Audio Amplifies (PNP) Go General Purpose Audio Amplifies (PNP)	2, 10
	633	104	Gir Gerege at Purpose Agailab Amphiliser - PNP	1.84
	634	TO-6	Go General Purso or Audite Amonities - PNP	2.70
	535 636	TO-5 TO 18	Go General Purpo e Alloy Junction RF -PNP Go General Purpose Alloy Junction RF -PNP	3, 12
	6.37	10-72	Ge Goraral Purpose Alloy Junction RF - PNP Ge General Purpose Alloy Junction RF - PNP	2.3
	638	TO-5	Ga General Purpose Drift Field PNP Ga General Purpose Drift Field—PNP	1.50
	640	70-1	Ge General Purpose Dritt-Fland -PMP	1.73
	641 700	TO 6 Cam 77	Ga General Purpose RF and Audio Amphilier - NPN Si General Purpose Audio Power Amphilier - NPN	2.75
	701	Com 71	Si General Purpose Audio Pesser Amelifier - NPN	2,49
	702	10 86 TO-86	Si General Purpose Audio Power Ampfilie - PNP SI General Purpose Audio Power Ampfilier - NPN	5,25
	704	10-3	Si General Purpose Audio Pesser Ameliles -NPH	3.62
	706	10.3	St Gentral Purpose Audio Fours American PNP	3.1
	706	10-5"	S) General Purpour Audio Pewer Amptiles -NPM Sileges High Voltage High Power-NPM -(400 Volts 10 Amp)	10.9
	706	TO-18	St Low Power RF America - PRP	1.2
	709 710	TO-18 TO-5°	Si UNF Oscillator, Miser, RF Amptifer—NPN Si Law Frequency RF and Audio Amptifer—Ptch	2.0
	712	105	SELow Frequency Outstoon, oliver, RF Amplifor -NPN	3,30
	713	TO-5"	Si Law Fraguercy Oppission, Misse, RF Amplifor-RPN St High Voltage Audio Amplifor NPN	3.10
	715	TO-62 (8)	III General Purpose Lipes Frequency RF and Autho Amp—Phil  III General Purpose Medium Current Amplish and Switch—Phil	.95
	716	TQ-92 (8)		1.24
	718	TQ-93 (8)	St VHEY, DE Occideror, Niver, RF Amplites—NPN Se VHEY, DEFONDER, New TREATMENT OF THE PROPERTY.	1.40
	719	10-92 (8)	Si VHF /LBHF Oscillator, Meser, R.F. Aungster-HPN	1.49
	720	TO 92 (B)	S VHE/DHF Oscillator, Music, RE Ampther—NPN Si General Purposi Auto Amether—NPN	1.55
	722	TO 97 (8)	Si General Pursuer Audio Ampilier -NPN	1.0
	723	TO 92 (8)	Si General Purcuie Audio America – NPN Si General Purpose Audio America – NPN	93
	725	TO-92 (8)	St General Purpose Audio Ampifer - NPN	1.03
	726	TO 97 (8)	Si General Purpose Audio Amprilies - NPN	1.03
	727	TO-92 (8)	Si Canarat Purpour Audio Amplifus—NPN B Canarat Purpour Audio Amplifus—NPN	1.10
	729	TO-97 (8)	Si General Purpose Audeo Amorter: NPN	1.33
	730	10 92 (8)	Se General Purpose Audio Ampi*int=8899	1.0
	731	TQ-92 (8)	Si General Purpose Audio Amplitat -NPN Si General Purpose Audio Amplitat -NPN	1.3
	733	TO-92 (8)	Si General Purpose Audio Ampiliar -NFN	1 21
	734	TO 92 (D)	Si General Pursons Audio America —NPN Si General Purpose Audio America NPN	1,3
	736	TO 92 (8)	So Geograf Purpose Applies Ampirior MPN	1.2
	737	TO 92 (8)	S. Gueste et Purmour Auden Azentinte - RPN	1.39
	739	TO-02 (81	Si General Pur pose Audio Amerite NPN SI 29404 (Germanium Reptacement—PNP Field Effect Transition - Audion—Is Channel	.63
	801	10-72	Field Effect Francisco - Audito-19 Literature	3.39
	802	TO-92 IC?	Field Effect Transcope - RF -H Channel	1.59

#### MOTOROLA HEP ADDITIONS

DESCRIPTION ASK's 

#### MOTOROLA

#### semi-conductor MANUALS



Integrated Circuit Projects Manual, Gives intro-Motorola 407, Integrated Circuit Manual.\$1.00

Field Effect Transistor projects manual gives Introduction to field effect transistors and construction techniques. Easy to construct projects with parts lists to build vibrato, audio mixer, timer, crystal oscillator, preamp., DC volumeter, 62 pages 5½ x 8½°, Wt. ½ pound.

Motorola 408, Field Effect Manual...\$1.00

Solid State projects from Motorole gives hints solid State projects from Motorola gives hints to builders and fundamental semi-conductor operation. Easy to construct projects with parts lists to build panic button, code practice oscillator, audio signal generator, hi-fi amplifier, regulated power supply, intercom, motor speed control and 6 meter converter. 62 pages 5½ x 8½°. Wt. ½ 1b. Motorola 400, Solid State Manual......50¢

Silicon Rectifier Handbook. An Engineers guide to Silicon Rectifier Applications. Gives replacement and interchangeability guide, Specifications, Assembles, Ratings as well as Circuit performance Characteristics, 210 pages 5½ x 8½° Wt. ½ 1b Motorola 410, Silicon Rectifier Handbook...\$1.50

#### MOTOROLA SEMI-CONDUCTOR CROSS REFERENCE GUIDE

Stock No. 25¢ HMA07-4 EACH

FREE ON REQUEST If ordered with Motorola HEP Tronsistors

Motorola Semi-conductor Cross Reference Guide 50 pages, 4 x 13"...Approx. 18,000 devices listed. Germanium Translators, Silicon Translators, Diodes and Silicon Rectifiers. Stock No. HM A07-4 Price 25¢, FREE on request if ordered with any Motorola HEP-Translators on this page.

#### \*\*\*\*\*\*\*\*\*\*\*\*\*\* TRANSISTOR

2 Kits For \$2,20 GRAB ( BOX

Stock No. GB-2SPNP 25 for \$1.19 Two Kits\$2.20 25 PNP transistors. Mostly small audio, Some RF-short leads 'A' or more long. This low price because they come from factory accumulation. Stock No. GB-25PNP, \$1.19

#### MALLORY SELENIUM RECTIFIERS AT REDUCED PRICES!



SHRINKABLE

AUTO

65-450

TUBING

HST 216

450 MILL

MILL SE SALE PRICE

PRICE 59 C

6S-750

QUANITY BUYERS 100. HEP-170, 1000 P.I.V

For Color T.V. and Audio Amplifiers 50 Mills, 500 Mills or up to 2½ Amps.

#### HEP ADDITIONS

LATEST MOTOROLA HANDBOOKS

HEP-413. Zener Diodo Handbook. Contains complete zener theory plus applications. HEP-413.....\$2.00

MEP-414, Semiconductor Power Circuita Mandbook. Contains over 100 semiconduct-or power circuits and many applications. HEP-414......\$2.00

silicon Rectifier for \$29.95

HEP

230

# Matarola Mounting accessories, Translator Mounting RIT—TO-5 Integrated Circuit Socket (Pike of 2) 10 Pin Integrated Circuit Socket (Pike of 2) 10 Pin Integrated Circuit Socket of Pin—Pin of 2 I.G. Socket—B Pin—Pin 1,49 1,49 ,32 ,90 1,49 ,32 ,32 ,32 2,38 ,85

HEP-803.....\$3.39 POPULAR MOTOROLA

up to 90 Watts Audio BVCBO 30 Volts IC-5 Amps 89¢ Each, Lots of 5 80¢ Each, Lots of 10 75¢ Each

Replacement for 2N-179, 2N-1529, 2N-1291, 2N-1292 TO-3 2N-2137, 2N-2138 and many other 2N numbers. Individually packed with specifications on each pkg. Case

#### Materala Bullders Kits.

Materials Buffers Experiments Rft. Inplace S 2011, Integrated Circuits 11 each HEBstudies 5 2011, Integrated Circuits 11 each HEBstudies 5 2011, Integrated Circuits 12 each HEBstudies S 2011, Integrated Circuits 12 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2 each
SSS J-IR FIRE-Rop. and 2 425 9300 feural 2

Motivate Times and the Committee Rift, Includes I N. channel Rr FET | Non-thannel Rr FET | No

HEP 570 Gate and \$5.95

MEK-4 Home Construction Projects Kit, cludes: 1 Silicon controlled Rectifies, 1 Unition, 1 Photodiode, 1 Silicon Rectifier as \$4.95





RADIO



## SAVE 50% AND MORE ON "SPECIAL BUYS" AT MCGEE



2½" long 1¼" dia. ¾" m tg. hole required.

750

399 H 200 P.LV.

195 2 for 950

377 H 400 P.I.V.

895 2 for 700

Rect, are single packed with mtg. nut.
MK-D09 Insulating mounting kit for 240 amp rect. 60¢



## Silicon 70 AMP 50 PIV.

Very popular size for chargers and power supplies stock no AASC-70 Matched Pair for.

Lenath 2 in. 1 in. dia, threaded end 3/8 in. MK-D08 insulating mounting kif for 70 amp rect. 40¢

#### 70 AMP 400 PIV \$695

Stock no. AASC70400 popular 70 cmp 400 PIV silicone rect. at a new low price of \$6.95 eo. matched pair for \$13.50 Insulating mounting kit for 70 amp rect. stock no MK-D08

40¢ extra.

SILICON RECTIFIER 750 MA No. RE-32 699

3 for \$2 SPECIFICATIONS: Mfgrs. Type: SD-500-90; RMS A.C. Input: 280 Voits; Peak In-verse Voltage: 400 Voita. Output: D.C. 500 MA @ 100° C; Current: 750 MA @

# EXTRUCED ALUMINUM HEAT SINKS OR TRANSISTORS AND RECTIFICES ORIGINA MODELS BLANK MODELS HE HE

HSQ-2BB DOUBLE FIN HEAT SINK FOR GENERAL PURPOSE APPLICATIONS—UNDEFLIED RADIATING SURFACE—46 72 SQ. UN

720

FOR USE WITH 1 IEDEC TYPE 183 TEANSISTON OR OUR TYPE 1-7 RADIATING SURFACE 4.72 SQ. IN MSD-17 SALE CT 2.7

PRICE \$127 DOUBLE FIR HEAT SINK

FOR USE WITH 1
IFDEC TYPE TO-36 TRANSISTOR
OR OUR TYPE T-0
RADIATING SURFACE—45 72 BQ. IN. 2 SALE \$127

DOUBLE FIN HEAT SINK

APPLICATIONS-UNDRILLED RADIATING SURFACE-70 08 SQ. IN PRICE \$127 HSD-3B

DOUBLE FIN HEAT SINK FOR USE WITH 2 JEDEC TYPE TO:3 TRANSISTORS OR TYPE 1:7 RADIATING SURFACE—70 OF SQ. IN.

SALE \$157 HSD-27 DOUBLE FIN HEAT SINK

PRICE \$157

TELEVISION DIODE SALE GLASS COLD BONDED

1N64 - 1N34 100 BUY EM BY THE 100 FOR \$6.95

10 FOR 89# SO FOR \$4.00 SILICON DIODE POWER RECTIFIER

Stock No. 1N-4004, For TV and radio replacement use. Medc in USA. by ...MeGee'e Sale Price, 39s ea., 10 for \$3.50, 100 for \$29.95

500 MA 400 PIV 10 FOR \$3.50

INTERNATIONAL SILICON DIODE POWER RECTIFIERS

1N2071A 750 MA 400 PIV

HSD-28

745

New Epoxy Dealgn

10 FOR \$4.50 100 FOR \$39.00 Letat Lepony design, ministure Silicon Olode Power Resulfaction of 19.007, making power resulfaction of 19.007, ideal power resulfaction of 19.007, ideal power resulfaction for redio, TV, Power Supriy circulate, ampliface etc. Will Fill mejority of your resulfaction. 19.071A replaces SYL-750, Sylvania Silicon bloods SYL-750, Sylvania Silicon bloods Power Resulfaction. 19.00 for \$4.50, 100 for ....\$39.00

## **400 MW ZENER DIODES** IN DO7 CASE PACK OF 2

When ordering specify type DZ-4 and choice of voltage. 4.7 6.8 10 15 22 and 30 volts.

## 1 Watt & 10 Watt Zener Diode Specials!

These zener diodes are suitable for applications such as voltage references, voltage regulated power supplies, transietor bias, voltage switches, transietor absorbers, etc. Buy by the handful at these low prices! Mede In U.S.A. 10 WATT

PAK OF 2

Cat. No. Normal Voltage Nat **DZ47** DZ62 **DZ90** DZ12

PAK of 2

Cat. No. Normal Voltage Not DZ147 4.7 V ..... 99¢ DZ 162 6.2V..... 99¢ 9V..... DZ190 12V..... 594 DZ112 12V..... 15V..... 59¢ DZ 118 18 V.....

#### PACK OF 2 10 Watt Zener Diode

24 VOLT With Mtg. Nut and \$109

Insulating Washer
For use in Tube Ampilifiers to
establish 24 volts Blas or for
Voltare regulation in D. C.
Power Supplies. No. 7-24VIOW

# PACK OF

10 WATT 50 VOLT **IGNITION SYSTEM** ZENER DIODES



**\$109** 

#### TOP HAT SILICON RECTIFIER S

Stock no. 10- 500400 BM. Pack. of 10 rectifiers.



DZ15

500 MIL - 400 PIV 10 FOR \$700

McGee T.V. serviceman special A pack of 10 GOLD PLATED oll purpose 500 mill 400 piv. silicon rectifiers, for only \$2.00


## HITRON SILICON RECTIFIER

1 AMP 2000 PRY

\$ |29 Ea. 2 \$250 FOR \$ 1000

Incapsulated %" x¾" x 3/16". Rated all up to 1 Amp. at 2000 P.R.V. Fine for using in replacements for tube rectifiers. Stock No. 1A2KV. McGee Sale Price \$1.29 each. 2 for \$2.50, 10 for........\$10.00

10 Germanium Diodes Similar to 1N34, 1N34A, 1N60



Equivalent in use to silicon diodes with lower forward voltage drop Wt. 1/4 lb.

10 Silicon Diode Pak

DS1-89¢

Replaces 1N137A, 1N200-209 types, eet. Long axial leads, black body with cathode band for easy identification.

# SILICON POWER RECTIFIERS

49¢ EACH two for 90 cents.

Popular silicon power recrifier similar to those used in the new auto alternators. Rated at 50 PIV at up to 18 amps. Made by Motorolo Iss Quality. Reg. 82¢ Net. McGes Price 49¢ each, 2 fee 90¢ 10 for \$4 25 Motorola No. MR322 or MR322R. The R stands for Reverse Polarity far bridge circuit. Size: 5/8"x 5/16"

# GENERAL & ELECTRIC

NEW LOOK IN 509

UNIVERSAL TV SILICON RECTIFIER

Model 509 Actual Size 1000 P.I.V

This Rectifier Features..... 1000 Voits - Both PRV and DC Rating High Surge Current Cambility Typical Applications.....

1 AMP

Hermetic Soul Low Leakage Dual Heat Sink Design

New higher rated

59¢ FOR \$4.95

LOWER PRICE

Transient Vallage Protection . Color and Manachrome T.V.

50 MILL 200 PIV SILICON

RECTIFIERS pack of 10

No. NJ-105 10

79 Pack

RAYTHEON 800 PIV 2 AMP High Voltage 890 10 FOR \$7.90

Right for that High Voltage POWER SUPPLY ...

top hat silicon rect. 750 mili at 400 piv.

39¢ 10 750500T 10 for \$3 50

MOTOROLA ALL-PURPOSE SILICON RECTIFIER Stock 1000 P.I.V

HEP-1704 9:10 FOR \$3.90 For Color T.V. and Audio Amplifiers 50 Mills, 500 Mills or un to 21/2 Amps.

## GENERAL ELECTRIC SEMICONDUCTORS

PRP UNIVERSAL REPLACEMENT TRANSISTORS						
GE Type	Application	Not Each				
GE-1	Mixer/oscillator converter, RF-IF amplifier	\$1.20				
GE-2	Air amplifier	1.02				
GE-3	Al' power amplifier	1.78				
GE-4	AP high power amplifier	2.94				
GE-5*	Mixer/oscillator converter, RF-IF simplifier	1.68				
GE-6	Mixer/oscillator converter, RF amplifier	1.83				
GE-7°	IF amplifier	1-77				
GE-8°	AF amplifier	1.29				
GE-9	Mixer/oscillator converter, RF-IF amplifier	1.683 1.779 1.226 1.220				
GE-10" GE-110	AM amplifier, driver output	1.20				
GE-12*	TV. FM. IF amplifier; UHF oscillator AF power amplifier	1.53 2.34 3.56 3.51 7.02				
GE-11	Matched pair GE-3	2.24				
GE-14 .	AF power amplifier	3.50				
GE-15.	Matched pair GE-14	7.02				
GE-16	AF high power amplifier	3.15				
GE-17°	HF FAI, RF and ose, TV circuits	1.42				
GE-18*	Audio amps, outputs and oscillators	1-46				
GE-19"	Power	206				
GE-20 .	RF-IF amplifier/oscillator	1.10				
GE-21°	RF-IF amplifier/oscillator	1,12				
GE-22	AM-FM oscillator	1:03				
GE-21°	Class A/B AF power amplifier	2.52				
GE-24 °	Matched pair GE-23	5.04				
GE-FET1		1.50				
2N107	Germanium transistor	2.45				
2N170 ·	Low voltage HF	1.102 1.052 1.052 5.04 7.52 7.52 1.02				
2N188A	Audio output amplifier	1.83				
ZN190	Driver and Class A output	-84				
2N324	Audio driver and power output	.72				
2N508	Preampilfier/amplifier	.78				
2N1415	Audio amplifier	1.02				
2N2160	Unijunction	1.65				

VAC-U-SELS MINIATURE DOUBLE DIODES For TV horizontal phase detector, replacement, etc. Wt., 2 oz. GE No. 6GC1 (Common Cathode), 6GD1 (Series Connected), or 6GX1 (Common Acode)—Net Each. 45 e GERMANIUM DIODES

GE Type	Application	Min. PRV	Mez.	Net Each
INSTANT INGO	General purpose Video detector	75 V 30 V	500 μA 67 μA	\$0.33
INSZA+	UHF mixer UHF mixer	5 V	100 µA 100 µA	.87
1N295	Video detector	50 V	200 µA	.96

Silicon, small package. †Silicon, large package

GE Type	PIV	Max	Net Each	GE Type	PIV	Max	Not Each
GE-504A	600	1	660	GE-509	1000		79¢
	COLO	TY R	ECTIFIE	RS AND	RYS7A	LS	
GE	-	-	Net I	GÉ			Net

The same of the sa	COLOR T	RECTIF	ERS AND	CRYSTALS	
GE Type GECR-1	Description Rectifier	Net Each \$2.25	Type GE-41	Description Quartz erystal	Net Each
GECR-2 GECR-3	Rectifier Rectifier	-99	ĞE-42	Quartz erystal	

ZENER DIODES							
GE Type	Net Each	GE Type	Net Each	GE Type	Net Each		
GEZO-3.6 GEZO-5.1 GEZO-5.6 GEZO-6.2	\$1.20 1.20	GEZD-9.1 GEZO-18-4 GEZO-1Z GEZD-15	\$1.20 .90 1.20	GEZD-18 GEZD-20 GEZD-27	\$1.20 1.20 1.20		

INDUSTRIAL REPLACEMENT SEMICONDUCTORS						
GE Type	1-99	1, Lats of 100-999	GE Type	Net Each	100-995	
GEMR-1 GEMR-2 GEMR-3	\$4.80 6.90 8-60	\$3.30 5.20 6.50	GEMR-4 GEMR-5 GEMR-6	\$3.80 1.40 1.42	\$2-90	

SEMICONDUCTOR REPLACEMENT KIT Contains transitions, silicon rectifiers, diodes and dual diodes. In sturdy cabinet with 15 drawers, Other kits available. GE No. K-915C-1 Replacement Mt-Net Each. \$22.38 EXPERIMENTER-NOSSYIST COMPONENTS

GE Type	Description	Net Ea.
GE-M100	Germanium Mesa transistor	\$1.20
GE-XI	Solid state switch rated at 117 V	2.60
GE-X2A	Light activated power switch	2.80
GE-X3	High current to 13 A at 50 PIV SCR	4.00
GE-X4	High current to 20 A; 200 PIV max. SCR	1.60
GE-X5	High sensitivity SCR	2.30
GE-X6	Cadmium suifide photoconductive cell	1-40
GE-X7	External magnetic actuation reed switch	-80
GE-X8	NPN medium speed germanium transistor	-70
GE-X9	PNP medium speed germanium transistor	79
GE-X10	3-terminal unifunction transistor	1.35
GE-XII	Zener diode rated 8.2 V at 1 watt	1-80
GE-X12 GE-X13	Remote control with schematic	4.50
GE-X14	Lamp dimmer, AC control with schematic Dual voltage power supply w/schematic	1.60
GE-X15		5.50
GE-X16	Adjustable temperature alarm w/schematic Battery operated fluorescent light w/schem.	3.45
SEMALCO	INDUCTOR MANUALS AVAILABLE ON DE	SHEST

Heat Sinks for TOS Case



10

KT 7189

COOL OFF ANY TRANSISTOR WITH ALLIMINUM NEAT SINKS FOR TO-OF 10 FOR ONLY 99¢

#### ELECTROLYTIC MINIATURE CONDENSERS

Law Prices



arder 10 take 10% off SMALL ELECTROLYTICS IN ALLIMINUM CASES WITH PLAS TO JACKETS AS ILLUSTRATED, POPULAR FOR THE POWER SUPPLY BUILDER OR ANY WHERE YOU NEED A SMALL CONC

CAPACITY VOLTS BIZE

29¢ UC\_500-15 500 mfd 15 V. 3/X1 UC\_1000\_15 1000 mfd 15 V 1/4X11/4 UC\_500\_35 500 mfd 35V 1/4X11/2 33¢ 39¢




49¢ each order 10 take 10% off EC-1500-25 1500 mfd 25 .V. 1 x 13/4



TUBULAR ELECTROLYTIC

EC-1000-50 1000 mfd 50 v. 21/4x1 in. net 59¢ order 10 take 10% off.

EC-1000-12 1000 mfd 12 V 13/x5/8 in net 33¢ oreder 10 take 10% aff.



Replacement for net 794 SH-prison #24-777 99¢ 2 for \$1.80 EMITTER HIGH POWER SILICON NPN TRANSISTOR
Designed for driver circults, 0 980 switching, and amplifier applications. 160 Vdc max. Power 40 watts. TO-66 case Stock No TV-109

net 794

saméras HEP-241, net \$1.79

NORKMANGO

TV DAMPER RECTIFIER



Model

SH3<sup>M</sup> 89¢ FOR COLOR TV

CONVERGENCE RECTIFIER 3 CELL

Used in RCA, Admirol, Zenith, Motorolo, etc.

Model SH4M 89¢ FOR COLOR

CONVERGENCE RECTIFIER 4 CELL

Used in RCA, Philco, Zenith, Sylvonia, etc



CONVERGENCE RECTIFIER CELL Replacement for RCA #1471858-1

GENERAL & ELECTRIC

Vac-v-5el SELENIUM Television DUAL-DIODE RECTIFIERS

		4	5 c
Cotolog No.	Туре	— 10 NET	for \$4.00
6GC1	Common Cathode	\$ .45	ACT AC
6G01	Series Connected	.45	-[4]4
6GX1	Common Anode	.45	AC AC

WESTINGHOUSE

# AMP---

# COLOR RECTIFIER

AND ALL PURPOSE POWER REC. Silicane. 1000 P.I.V.

McGees Sale Price 59¢ 10 for \$5.00 A Red Hat McGee Value

Leads are heavy silver plated for better heat disipation, Ideal for color black and white T.V. or other uses, no. WE-3-1K

## NPN Epoxy Transistors

Red Dot Case 29 for Automotive Usage

Stock no KT-7187 Pack of 10 \$ 29 McGee service dealer spècial

# DELCO

DTG-1200 Power Trans





COLOR FOCUS RECTIFIERS 14.000 VOLT 1 MA

4" long with 112" long Leade

5rock No. 13-0016106-C02 \$1.29 10 For

6500 VOLT COLOR RECTIFIER

6500 Volt Rectifier, 24" long with 2" lend out each end. Stock No. 212-85..... \$1.50 GE COLOR TV RECTIFIERS GE CR-2

MODEL B92

Control (Color)

Horiz, Free

B + BOOST

GE CR-1 FOCUS RECTIFIER 3.09

600 VOLT BOOSTER RECTIFIER



# NEW SQUARE 10 WATT RESISTORS

NEWEST FACTORY PRODUCTION

NEW LOWER PRICES

20°

19¢ LOTS OF

18¢ 100

ASSORTED

NEW TYPE HH SQUARE WIRE WOUND RESISTORS

New HH, 10 watt wire wound resistors. Latest square construction with ohms value clearly printed on each resistor. Offered in sizes from 5 ohms to 25,000 ohms. 20,e each, 19c each in lots of 100 assorted. Regular 60¢ list value. Specity Type

	TYPE H	H-10	1-	$.7/8" \times 3/$	8''
.15	75	470	1250	3500	8000
	85	500	1500	3900	8200
7.5	100	600	1600	4000	8500
10	120	680	1750	4500	9000
	125	700	1800	4700	10000
20	150	750	2000	5000	12000
25	175	800	2250	5600	12500
30	200	820	2 <b>50</b> 0	6000	15000
40	250	900	2700	6800	20000
47	300	1000	3000	7000	25000
50	400	1200	3300	7500	

# NEW SQUARE 5 WATT RESISTORS

7/8" × 3/8"

NEW LOWER PRODUCTION

NEW LOWER PRICES

18 4 1.70

16.00

100 FOR

NEW TYPE HH SQUARE WIRE WOUND 5 WATT RESISTORS

McGee offers a very wide selection of these American made, 5 watt square wire wound resistors. Popular for all new needs in resistors, such as transistor auto radios. Small in size, 3/8"x 3/8"x 7/8". Notice, 8 sizes offered are less than 1 ohm. Pricediess than carbon resistors which burn out much sooner. Buy 100 assorted and save.

TYPE HH-5 SQUARE WIRE WOUND RESISTORS

.09	1.5	18	75	220	750	27 50	6500
.11	2.7	22	80	250	820	3000	6800
.15	3.	24	82	270	850	3300	7000
.17	4.	25	85	300	900	3400	7500
.22	4.7	35	90	330	1000	3500	10000
.27	5.	40	100.	360	1200	3600	
,33	5.6	50	110	400	1500	37 50	
,27 ,33 ,47 ,51 ,68	6.4	54	120	450	1600	3900	
.51	8.	56	130	500	1750	4000 •	Are 1-3/8
.68	10.	60	150	560	1800	4500	Long
.82	13.	68	175	600	2000	5000	
1.0 ohm	17.	70	200	700	2200	6000	

# **NEW SQUARE 20 WATT RESISTORS**

NEWEST FACTORY PRODUCTIO

NEW X-63 20 WATT SQUARE WIRE WOUND RESISTORS

New style American made 20 Watt wire wound resistors. Low prices and good quality. Buy 50 assorted and Save. Specify X-63 and then select resistance values shown here.

35 ¢ 3 30

50 FOR 1/2×1/2×1-7/8

15.00

400 2000 5 Ohms 20 500 2500 7.5 25 100 3000 750 125 10 150 5000 15 7500 200 1250 Specity 20 Watt X=63 When Ordering 250 10000 1500 15000 300 1750

X-63 .370 A

LOW OHM 20 WATT KIT \$3,30 1Ea. X63 Resistor. 5 ohm, 7.5,10. 15. 20, 25, 30, 40, 50 and 75 ohms.

5tock No...20LHK MED, OHM 20 WATT KIT 53.30 1-Each X-63, 100, 125, 150, 200, 250, 300, 400, 500, 750, 1000 Ohm

Stock No.....20MHK
HIGH OHM 20 WATT KIT \$3.30
1-Each X-63, 1250 Ohms, 1500
1750, 2000, 2500, 3000, 5000,
7500, 10,000 and 15,000 nhms.

Stock No.....20HKK

# TV FILAMENT DROPPING RESISTORS

25 Wott FILAMEN'T DROPPING RESISTORS 496
HH, 25 watt tilament dropping resistars for Television sets.
Flat, sand-coated types as used in TV production. Specify
Type HH-25F when ordering, then list ohms values wanted.

Specify Type HH-25F and volue on order... Net 49¢ each

5 ohms -	25 ohms	41 ohms	54 ohms
7 11	33 ''	45 "	59 ''
7 ''	36 "		68 ''
20 **	38 "	48 "	133 "

# FUSIBILE RESISTOR

10 OHM

DUTY

FUSIBLE RESISTORS

Replacement tuse type resistors as used in every TV set in conjunction with selenium rectifiers. They respond to of averload and furthish the proper resistence at the same time

evertood and	lurflish the proper l	Peristance of Pho	same Pim
Stock No.	Description	Net	4 Lot
		Each	Each
F4.7	4.7 ohm, 5 watti	.30	.25
F5.6	5.6 ohm, 5 watts	.30	.25
F9	9 ohms, 5 watts	.30	.25
F22	22 ohm, 5 watts	.30	.25
R7	7.5 ohm, 3 umps	.35	.30
F12A	150 ohm .12 amp	p30	.25
F150	150 ohm, 5 watt	.30	.25
F4 kit cor	ntains 1 eo. 5.6,	7.5, 9, 22 ohn	fusible
	11,19 each, lots		

#### Stock 1

10 WATT
High Surge fuelble resistors made for use with 500 MII to 850 MII Top Hat rectifiers in valeage doubler and tough filter circuits. Especially good in Rurol areas with REA line fluctuations etc.

# FUSIBLE RESISTOR

5 7.5 OHM

MOST POPULAR IN USE TODAY
KIT OF 5 · 7.5 Ohm 59¢

Stock No. 5FR-7.5

7.5

20c 10 FOR \$180

# GENUINE IRC CARBON RESISTORS AT BIG SAV NGS

Genuine IRC insulated carbon resistors, All are newest production clearly color coded, Plus or minus 10%, for all close tolerance applications. If you buy 50 of one size, we will ship our handy "50 Pack" for your stocking convienence, Available in RTMA sizes as listed below. All ohms values sell for the same unit price. Quantity orices are for all of 1 size.

()hms	Ohms	Olims	Ohms	Ohms	Megohms	Megohms	
10	82	680	5600	47,000	.39	3.3	
12	100	1000	6800	56,000 68,000	.47	3.9	
18	120	1200	10.000	68,000 82,000	.47 .56 .68	4.7	
22	180	1500	12,000	100,000	.82	6.8	
27	220	1800	15,000	120,000	1.0	8.2	
33 39 47 56 68	270	2200	18,000	150.000	1.2	10.0	
39	330	2700	22,000	180,000	1.5		
47	390	3300	24.000	220,000	1.8	15.0	
50	560	4700	30,000	270,000	4.2	18.0	
VO	:00	4,00	37,000	330.000	2.7	22 N	

LOT PRICES FOR 500 and 1000 QUANTITY ARE FOR ONE SIZE ONLY. (NOT ASSORTED SIZES)

IRC Type GTB 1/2 Watt Resistors, 6¢ ea. 10 for 55¢, 50 tor 2.50 500 for \$16.00, 1000 for \$28.00. All of one size for quon, prices. IRC Type GTB, 1 Watt Resistors, 10¢ ea. 10 for 88¢, 50 for 3.50 500 for \$74,00, 1000 for \$42.50. All 1 value for quantity prices. IRC Type SR-2, 2 Watt Resistors, 15¢ each, 10 of one size \$1.30

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108

7.5 OHM HEAVY

# ORANGE DROP® DIFILM® DIPPED TUBULARS

- B Especially Made for Erect, Original Replacement
- Deal Dislectric (Polyester Film and Paper) Solidiy Inspregnated with Esclusive HCKR to Produce Rock-Hard Capacitor Section
- Outperforms Any Other Dipped Tubular Capacitor
- Double Dipped in Bright Orange Eposy Resin—

  Beats Heat and Humidilly





	Copacitance To	lerance ±10%		7
uf	D. x L.	Cat. No.	NET	10 UP
		VOLTS D-C		EACH
			-	
.022	% × %	225-520	.18	.15
.047	2 1/4 H 1/8 2 1/4 H 1/8	2PS-522 2PS-547	.18	.15
.05	15/32 × 1/8	2PS-S50	.18	.15
.1	51/4 × 13/4	2PS-P10	21	
			.21	.17
.25	% x 1%	2PS-P25 2PS-P33	.30	·25 ·32
.47	4%4 x 1 %	2PS-P47	.40	.35
.5	23/ <sub>33</sub> x 15/ <sub>4</sub>	2PS-P50	.45	.35
	_	OLTS D-C		
-				10
.01	1 1/32 × 11/14	4PS-S10	.15	.12
.022	2 7/64 × 7/8	4PS-522	.18	.15
.033	1 1/22 × 1/0	4PS-S33	.18	.15
.047	20/64 × 13/16	4PS-547	.21	.17
.1		4PS-P10	-24	.20
.25	41/64 x 1 3/6	4PS-P25	.36	.30
-	600 V	OLTS D-C		
201	-		1.	12
.001	21/64 × 11/16	6PS-D10	.15	.12
.002	31/4 × 11/16	6PS-D20	.15	.12
.0022	21/64 X 11/16	6PS-D22	.15	.12
.003	11/32 # 11/14	6PS-030	.15	.12
.0033	23/64 × 11/16 5/8 × 11/16	6PS-D33 6PS-D39	.15	.12
.004	3/8 × 11/16	6PS-D40	-15	.12
.0047	25/4 × 1/14 25/4 × 1/16	6PS-D47 6PS-D50	.15 .15	.12
.0056	2564 × 11/16	6PS-056	.15	.12
.006	13/2 × ×11/4	6PS-D60	.15	.12
.0068	7 7 7	6PS-D68		.12
.0075	13/ <sub>22</sub> × 11/ <sub>16</sub> 23/ <sub>44</sub> × 7/ <sub>4</sub>	6PS-D75	.15	.12
.008	23/64 X 7/8	6PS-D80	.15	.12
.01	2 1/4 × 1/4	6PS-51D	-15	.12
.012	2 % a 1/2	6PS-S12	15	.12
.015	2 1/64 × 1/8	6PS-S15	.18	.15
.02	31/64 X 1/8	6PS-S20	.18	.15
.022	31/44 × 7/8	6PS-522	.18	.15
.022	17/32 # 7/8	6PS-525	.18	.15
.027	1/10 x 1 1/16	6P5-S27	-18	.15
.03	7/16 × 1 1/16	6PS-\$30	.18	.15
.033	13/ <sub>20</sub> × 13/ <sub>16</sub>	6PS-S33	.18	.15
.035	14/2 × 1 1/4	6PS-535	.21	.15
			.21	-17
.039	31/64 x 13/16	6PS-S39 6PS-S40	.21	.17
.047	1/2 x 1 3/14	6PS-549	21	.17
.05	17/32 × 13/16	6P5-S50	.21	.17
		Table 1		1000
.056	3%4 x 13/4	6PS-556	.21	.17
.1	% x 1%	6PS-P10	.27	.22
.25	13/16 x 1 1/6	6PS-P25	-48	-40
.47	41/4 × 1 1/6	6PS-P47	.51	.42
		OLTS D-C		100
	.000	_	2.0	77
.001	1/2 × 3/0	16PS-D10	.18	.15
.0015	1/2 × 1/4	16PS-D15 16PS-D20	-21	.17
.002	1/2 × 1/0			.17
.0022	1/2 × 1/2	16PS-D22	.21 .21	.17
.003	1% x 1 1/32 1% x 1 1/32	16PS-D30	.21	.17
.0033	1%12 H 1 1/12	16PS-D40	.24	.20
		16PS-D47		.20
.0047	19/32 X 9/32 19/32 X 1 9/32	16PS-D50	.24	.22
,006	1%32 X 1 %32	16PS-D60	.27	.22
.0068	1 1/32 × 1 1/32	16PS-D68	.27	.22
.007	1 1/12 x 1 1/22	16PS-D70	.27	.22
.0075	1%2 × 1%2	16PS-D75	.27	.22
.008	1%12 x 1 1/22	16PS-D80	.27	.22
.D1	1 1/32 × 1 1/32	16PS-51D	•30	.25

## TYPE 279P ISOFARAD® PLASTIC FILM CAPACITORS

Isotarod Quality is a Must in Color TV Synchroguide Circuits, Harizontal and Vertical Oscillators, Bridge and Parallel T Circuits and Other Tuned Circuit Applications Requiring Close Tolerance and Zero Temperature Coefficient of Capacitance

Superior to Silvered Mica Copacitors, Yel Considerably Less Expensive

Constant Capacitance—Will Not Change More Than ±0.2% from Room Temperature to +80C

at a Maximum Rated Valtage Will Withstand Operating Temperatures to 85C (185F)

#### Capacitance Tolerance: ±5%





# WORLD'S.FINEST PLANET TWIST MOUNT ELECTROLYTICS

MULTIPLE SECTIONS—ALL 450V.V.
FRESH FACTORY PRODUCED FOR McGee
A NAME YOU KNOW— MADE IN U.S.A.
Guaroniced one year-All 1 3/8" can diameter
and shipped with fiber mounting plate.

# GENERAL ELECTRIC 10% Off in lats 4 or mare

QT1-4 8 mfd. 450 V. QT1-7 10 mfd. 600 V. . 55¢ \$1.29 net. 60¢ QT1-8 16 mfd. 450 V. QT1-10 20 mfd 475V. 70¢ MT1-12 25 mfd. 50 V. 55e QT1-12 30 mfd. 450 V. 70¢ QT1-14 40 mfd. 450 V. 80∉ QT1-16 50 mfd. 450 V. QT1-19 60 mfd. 450 V. 90€ 99€ \$1.19 QT1-21 80 mfd. 450 V, QT1-24 100 mfd. 450 V. \$1.39 QT1-25 150 mfd. 150 V. 80e QT1-26 150 mfd. 300 V. \$1.39 QT1-27 200 mfd. 200 V. \$1.29 \$1,39 QT1-29 300 mfd. 150 V.

#### DISC CERAMIC CONDENSERS

"RED-CAP" DISC CERAMIC CONDENSERS
5 mmfd(2000005) to 10,000 mmfd (.01 mfd.)

American made 600 volt Diac Ceramic condensers. Popular small physical sizes, as used in TV sets; video circuits and audio tone control circuits. These new disc ceramics are better for RF and audio circuits than old style paper condensers. Less loss, lower leakage, less resistance. Buy them from McGee at half the price you might pay. Specify Type GA when ordering.



Price 9¢ Each, Any Size 10 for 80¢, 100 for \$7.00 1000 assorted for \$60.00

Capacity in mmfd. 600 volts AC- klylar Dipped5 mmf 50 mmf 150 mmf 500 mmf 2000 mmf
10 " 56 " 160 " 680 " 2700 "
15 " 68 " 250 " 820 " 3000 "
12 " 82 " 270 " 1000" 3300 "
13 " 100" 330 " 1500" 4700 "
120 " 470 " 2000" 5000 "

.01 to .02 "Red-Cap" Disc Ceramics, 10¢ 10 for 90¢, 100 for \$8.00, 1000 for \$70.00--


.01 mfd 600V .015 mfd 600V .02 mfd 600V

50 PLANET 50-30 Mfd 150 Volt NEW JOBBER STOCK YEAR GUARANTEE 50 FOR \$2195 Cardio and Judga, was 1816 of 100 fg. in any lated Leads, Ill are now year.

All condensers on this page are name brand and factory fresh.

### PLANET-CAP TUBULAR ELECTROLYTICS


FRESH STOCK



MANIL

Popular Planet type L single section electrolytics with lead out each end.

Stack Number	CAPACITY	VOLTAGE	ICS E	10 L ot
L-100-12	100 mfd		.40	.36
L-25-25	25 mfd 100 mfd	25 volts	-35	.33
L-100-25 L-1000-50	100 mtd 1000 mld	25 volts	.40	.38
1-8-150	8 mtd	150 volts	-44	.40
E-20-150 L-40-150	20 mfd 40 mfd	150 volts	.38	434
1.50.150	50 m fd	150 valte	.52	.48
L-80-150 L-100-150	60 mfd	150 volts	.56	.52
L-100-150 L-150-150 L-200-150	150 mld	150 volts	.67	.63
L-20-250	200 m/d	150 volts 150 volts 250 volts	1.01	.96
1 -30-250	30 mfd	ZOU VOITE	.55	.51
C-40-250 L-20-350	40 mfd 20 mfd	250 volts	.54	.50
L - 30 - 350	30 mid	350 voits	.58	.54
L-40-350 L-8-450	40 mfdi 8 mld	450 volts	.03	.59
E-16-450	16 mld	450 volts	.51	.47
L-20-450 L-30-450	20 mfd	450 volts	.55	.57
L-40-450	40 m fd	450 votes	-64	.60
L-60-450 L-80-450	60 mfd 80 mfd	450 voits	1.09	.80
E-100-450	100 mfd	450 volts	1.42	1.00
L-10-500	10 mfd 20 mfd	500 volts	.56	.52
E-20-500 E-30-500	20 mfd 30 mfd	500 voles	-89	-65
	SECTION CAR			-
CT-5020-150	20-20 mfd 50-20 mfd	150 velts	.50 .54	.47
C T-5030-150	50-30 mfd	150 volts	.54	30
CT+2X\$0=150	50-50 m/4 D QUAD SECTION		TUBULA	.61 .05
CT302020-150	30-20-20/20	150/25 volt	.45	.6]
CT403020-150 CT404020-150	40-30-20 mld	150 volta	.65	-6
CI503020-250	50=30=20 mfd	250 volts	1.09	1.05
E1503020-250 E1804020-150 E1803020-150	80-30-20-725	750 volts 130 volts 150 volts 150 volts	1.09	1.05
	100			



### 5/6 x 13/4 x 45/4 225P22391 21d Earh \$1.90 1/32 x 1/4 x 4%4 225P47391 24 g Eoch \$2.20 17/32 x 21/4 x 45/4 225P10491 27 & Each \$2.50 ELECTROLYTIC MINIATURE CONDENSERS MALOUT RECTIFY TO CONTRACT Rit of 30 upright mounting miniature electrolytic condensers Excellent for all sub-miniature applica-tions such as transistor sets and most printed circuit work. 15-100 mfd 15 with

2 FOR


\$7.00

36¢ \$3.30

45¢ \$4.10

68¢ \$5.90

78 € \$6.90



\$5,50

BY-PASS MINIATURE

CONDENSER KIT

50 miniature by-pass upright-mbg. Con-denser kit for all transistor and other appli-

Five—1 Ten—.01

Tan-- 05



#### UNIVERSAL MICROPHONE REMOTE CONTROL



McGEE SALE PRICE



#### **ELECTROLYTIC** CONDENSER KIT

\$1.49 Ea. 5 For \$6.00

Furnished in aluminum tubes with viryl plastic cover. Plainly marked as to capacity and voltage All are 15 volt working size \$4.1½° [Io \$4.546"]. Call Me TCK 5 each of

10MFD-15WV 50MFD-15WV 6MFD-15WY

2 FOR



SAVE 50% OR MORE ON ALL OF THESE IMPORTED MICROPHONES NOW PRICED AT LESS THAN IMPORTERS COST



DNE OF THE LARGEST SELLING ny Thousande Sold for \$7,95 - 59,95 Of Japan

PENCIL TYPE DYNAMIC MICROPHONE \$495 2 For Cat. No. OM19

COMPLETE WITH DESK STAND AND LAVALIER LOOP

A high sensitivity unit with a specially designed law range comparisating barrel, only 3% \*\* x \*\* "diameter. Perfect for recorders, paging, ham stations, lecturers, stc.

#### SPECIFICATIONS

Supplied with cable and removable mike trand.

\$4.95, 2 for \$9.00

DYNAMIC MIKE SALE McGEE

# DYNAMIC MICROPHONE ON GOOSE NECK STAND

LAST WITH ON-OFF \$495 Cat. Na. DM-37F

response 00-10,000 No. DM-37F

DYNAMIC MICROPHONE

HAND HELD WITH ON-OFF SWITCH McGEE Special! Stock Ho. DM-3



\$19°5 LOWEST PRICED UNIDYNE ... EVER! 515-SB: Low Impedance, List Price \$35.00

BUY A

GENUINE

MICROPHONE

Output Level High -58 db per Microbar) 1.25 Wv m witch Net Price.

#### DUAL IMPEDANCE

BROADCAST CARDIOID DYNAMIC RESPONSE MIKE 35-14,500 DM57HL

MCGEE SALE PRICE

. OUTPUT LEVELS -52 db

. CHROME FINISH

. DIE CAST CASE

Features a smooth cardioid pattern for maximum reduction of extraneous noises and reverberation Permits clase talking while reducing bass occentration, ideal for P.A., archestral and voca use. Includes a 4 prong connector with 20 Ft. cable a 14-27 mike stand holder. No. DMS7NL



#### **ALUMINUM CAN TWIST MOUNT**

# ELECTROLYTICS SAVE UP TO 70%

SINGLE SECTION FP ELECTROLYTICS

	Cop. Mfd.	Volts DC	Size Inches	Stock No.	Price Each	10 Lot Price	2
	25	450	1x2	K1-25450	. 39	3.50	1
	30 30	450 450	1-1/8x3 1x2%	K 1-30450 K 1-3045	. 49	4.50	
	80	47.5	1-3/8×3	K 2-80 47 5	. 59	5.50	1
ŀ	80			K2B100150			L
	100	150 200	1-1/8 x 2 1/4 1-1/8 x 2-7	/8 K 2B 100 15 /8 K 2B 10 2	. 29	2.50 4.50	Tie
			• "	* * *		9.50	
	160 160	250 250	1-1/8×3 1/ 1/4×2-5/8		.99	9.50	L
	400	200	11/1×31/4	K3B42	.49	4.50	1
	500 500	150 200	1½x4 1½x4¼	K3-500150 K3B502	.49 .59	4.50 5.50	1
	1000	10	1×3 1-3/8×21/4	K3-10001	.39	5.50 3.50 4.50	1-
	1000	35 75	142×24	K 3- 1000 35 K 3B 1007 5	.59	5.50	5
1	1500	50	11 × 31/4 1-3/8×41/1	K 1505 K 3B 161	.69	6.50	3
4	1600 2 <b>000</b>	100	1-3/8×2	K3B215	69	6.50	П
ı	4001	15	11/2×33/4	K4-415	.79	7.50	1
	DUA	L SECTIO	NFPE	LECTROLY1	ICS .		1
	15-15	400-400	1x2	K 5- 1515	. 39	3.50	1
	30-10	400-400	1×2	K4-3010	. 39	3.50	H
	40-5 40-40	450-450 450-450	1×3 1-3/8×3	K 5A405 K 5A440	.39	3.50 3.50	1
	50- 30	150-150	1×2	K 4-503 K 4B60201	.39	3.50 3.50	1
	60-20 60-150	150-150 400-150	1×2 1×2	K 5A60 15 K 4B60 2150	.39	3.50 3.50	
	60-200 80-2	150-10 450-350	1×2 1-3/8×2½	K 51380 2	.39	4.50	
	80-40 80-160	450- 200 47:5- 250	1-3/8×3 1-3/8×4½	K 4B8U4452	.49	4.50 5.50	L
	100-10	400-300	1-3/8 x 21/6	K4B10010	.49	4.50	1
	-	-				2.27	14
	100-100	400-50	1-3/8×4	K 5- 10 1405	.59	5.50	4
	180-50	150-150	1 x 21/2	K6-18050	.39	3.50	3
	1000-50	8-150	1x3	K6-100050	.39	3.50 4.50 5.50	2
ı	1000-500 1000-1000-	16-16 50-50	1-1/8 x23/4 1-3/8 x 21/2	K 5- 10 10 50	.59	5.50	1
	2000-2000	30-30	1-3/8×3	K 6- 2020	.59	5.50	1
			ION FP	ELECTROL			1,
	10-10-10 10-10-20	450-450-25 300-50-25	Ix	2½ K6A111 2½ K6A101020	.19	1.50 1.50 2.50	-
	10-18-40	475-475-25	1-3/8×	2 K6A1084	.29	2,50	11
	15-15-20	450-450-25	1x 1x		. 29	2.50	1
	30-10-10 30-15-25	150-50-50 350-300-25	1-3/8×	2 K7 A3015	. 29	2.50 2.50	
	40-20-20 40-40-40	350-350-350 350-350-200			. 49	4,50 3,50	1
			1-3/8 x		49	4.50	1
	50-40-40 60-20-2	475-475-25 450-450-350			.59	5.50	
	80-35-50	350-300-15	1-3/8×	2 K8A803550	.59	5.50	1
ŀ	100-80-200	150-150-10	1-3/8×	21/2 K9A1082	.59	5.50	i
	100-120-5	200-350-350 150-150-150	1-3/8x 1-1/8x		, 59 . 39	5.50	ľ
	1 20-8 0- 20 1 50-5-100	200- 350-50	1-3/8 x	2½ K9-1551	.59	- 3.50 5.50	
	200-140-60	150-150-150	. 1 3 10-		0 .49	4.50	
-	250-200-10	175-150-15	1 7 /P.				1
	250-200-50 500-200-50	150-150-15 100-100-10	0 1-3/81	k3 K10A552	.59	4.50 5.50 4.50	1
	500-300-100 1000-500-20	15-15-15 16-16-16	1-1/2	K11-531 K10A10502	0 .49	4.50 4.50	1
	500-100-100	25- 25- 25	1x 2	K9-511	, 49	4.50	ı
	500-500-170 3500-1000-1000	51=50<50 25=25-25	1-3/8: 1-3/8x		.59	5, 50 6, 50	
	QUA			LECTROLY			
		475-475-150-5	0 1-3/8>	3 K11-111220	. 39	3.50	1
	16-16-16-15 20-20-20-20	450-450-450-4			.49	4.50	
	30-20-5-100 40-20-10-10	350-350-350-	200 1-3/8	x3 K 12-32510	.39	3.50 6.50	
	40-20-20-20	450-450-400- 150-150-150-	150 1-3/8	8 x 2 1/2 K 12-4222	44	4.50	1
	40-40-30-20	350-350-350- 400-400 350-	350 1-3/8 75 1-3/8	3x4 K12A4125	.59	5 50 5 50	1
	50-18-40-40	475-450-150-	50 1-3/8		.59	5.50	
	70-40-10-50	350-350-350-			.59	5.50	1
	80-4-4-200	475-475-475-	-25 1-3/8	K13-80442	59	5.50	1
	80-50-10-20	450-450-450-	25 1-3/8	3×4 K 13-8512	.79	7 50	-
	80-50-250-250 80-80-40 20	0 450-450-50-1 160-150-150	25 1-3/8	x41/2 K13A8522	.59	6 50	
	80-80-40-100	350-350-300		/x3 K13A8842 8x4 K14-8841	.59	4.50	
	100-500-500-20	350-50: 25-2	5 1-3/8	3x3 K14A1552	49	4 50	
	150 20-50-50 160-30-20-40	250-450-75-1 250-450-450	50 1-3/8	3×31/4 K14A160	89 89	8 50 8 50	
	-	230-730-430	-150 1-3/8	3×4 K14A132		8 30	1

		10-	-	
Cap.	Volts DC	Size Inches	Stock No.	Price 10 Lot Each Price
200-30-40-10 200-200-100-10 200-200-200-30	150-350-350-35 150-150-150-7	5 1-3/8×4	4 K15-22101	59 5 50 .59 5.50 4 .69 6.50 4
250-20-20-50	175-175-175-13 350-350-350-2			59 550
300-200-10-100 2000-2000-25-50	175-150-150-1			.59 5.50
25 mfd. 450 vdc,	40-40-50-40 80 mfd. 475	1-3/8 x	100 mfd, 475 vdc.	160 mfd. 250 vdč
l×2	1-3/8×3	100	1-1/8×2-2/8	1-1/8×3-1/8
K1-25450	K2-80475		K2B102 49 €	K19-1625 99¢
10 for \$3.50	10 for \$5.50		10 for \$4,50	
160 mfd, 250 vdc.	1000 mfd. 10 1×3 NP.	vdc.	60 mfd. 400 vdc. 150 mfd. 150 vdc.	80 mfd 475 vdc 160 mfd 250 vdc
1½ x 2-5/8 K19A-160	K3-1000	1	1×2 K5A6015	1-3/8×4½ K5A816
99€	29¢		39¢	59 €
// *	10 for \$2,5		10 for \$3.50	10 for \$5,50 40 mfd. 350 vdc
50 mfd. 150 vdc.	80 mfd, 450		10 mfd. 300 vdc. 10 mfd 50 vdc.	20 mfd. 350 vdc.
30 mfd.  50 vdc.	40 mfd, 200 1-3/8×3		20 mfd. 25 vdc	20 mfd. 350 vdc. 1-3/8x2
K4-503	K488044	52	K6A101020	K20-148
39¢ 10 for \$3.50	49¢	1	19¢ 10 for \$1.50	49¢
10 for \$3.50	10 for \$4		200 mfd. 150 vdc.	250 mfd, 150 vde.
-	5 mfd. 350	vdc.	140 mfd. 150 vdc.	200 mfd. 150 vdc.
	100 mfd. 50 1-3/8×23		60 mfd, 150 vdc, 1-3/8X4	50 mfd. 150 vdc. 1-3/8x3½
Callenger Co.	K9-1551		K10-201460	K10A105020
	59¢	50	59¢ 10 for \$5.50	49¢ 10 for \$4.50
40 mfd. 350 vdc.	40 mfd, 400	-	300 mfd 175 vde	80 mfd, 475 vdc
40 mfd. 350 vdc. 30 mfd. 350 vdc.	120 mfd. 400 5 mfd. 350		200 mfd 150 vdc	4 mfd. 475 vde. 4 mfd. 475 vdc.
20 mfd, 350 vdc. 1-3/8x3	60 mfd, 75 1-3/8X4		100 mfd 150 vde 1-3/8×4	200 mfd. 25 vdc. 1-3/8 × 31/4
K12A 404	K12A4125	900	K20-73B140	K13-80442
59¢	59¢	eys:	59¢	59¢ 10 for \$5.50
160 mfd 250 vdc		1	10 for \$5.50	CTION DELCO
30 mfd 450 vdc 20 mfd 450 vdc	1000 mfd. 16 500 mfd. 16	5 vdc.	CONTROLS for AL	TO, TRANSISTOR
40 mfd 150 vdc 1-3/8×4	20 mfd, 16 1½ x 2	vdc.	RADIOS. KIT of 25	ASSORTED \$5.00
K14A132	K10A105	029		
10 for \$8.50	49 ¢			44.77
ALUMINUM C.		* or m		UALS
200 mfd 150 vdc 5 mfd 150 vdc	120 mfd 1 1-1/8x31/4		11-1	P
1-1/8x3¼ K22TP200-5	K22T P-1		Contains no more	DUADS than 5 of amy type
Price .39¢	10 for \$	3.50	all have SWITCHE	ES and concentric are made by CTS,
HIGH CAPACI	TY LOW VOL	TAGE	Mallory and Stackp have tone taps. 10K & 20K, 25K &	Resistance are 25K 100K & 30K
ELEC"	ROLYTICS.		500K & 250K Som	e are TAB mounted
Hernetically sealed clean of the state of th	small sizes. These	s. Top le elec-	the price of this k	
	GEE S	40	Stock No 25DTR	
>pe	cial No		McGee E	SARGAIN
	0 mfd. • 200 vd 0 mfd. • 165 vd		CAPA	CITORS
12	50 mfd. + 180 vd	de.	SPECIAL P	50%
1.175	00 mfd 52.8 v	-	MOISTURE	

4000 mfd. - 33 vdc 12,000 mfd. - 11 vde

a MFD. 600 VGC
OIL CONDENSER

89¢ E4ch

400 Val\* Gair Falled Plager F 1rs Captionnes in in dismonship to the second of the secon

From standard manufacturers
.022 mfd. 600 vdc. .07¢ 10 for .60¢
.027 mfd. 600 vdc. .07¢ 10 for .60¢
.039 mfd. 600 vdc. .07¢ 10 for .60¢
.047 mfd. 600 vdc. .07¢ 10 for .60¢
.1 mfd. 100 vdc. .09¢ 10 for .90¢
.1 mfd. 1000 vdc. .10¢ 10 for .90¢
.2 mfd. 600 vdc. .11¢ 10 for 1.00
.22 mfd. 200 vdc. .11¢ 10 for 1.00

ALUMINUM CAN TWIST MOUNT

# ELECTROLYTICS SAVE UP TO 70%



	hes No.	Each   Price
60/150 400-150 1-3 80/40 450-200 1-3 50/40/40 47 5-47 5-25 1-3 200/140/60 150-150-150 1-3 3500/1000/1000 25-25-25 1-3 40/120/5/60 400-400-350-75 1-3 80/50/250/250 450-450-50-25 1-3 80/4/4/200 47 5-47 5-47 5-25 1-3 80/30/4/4 47 5-47 5-47 5-47 5-1-3 160/30/20/40 250-450-450-150 1-3 200/20/100/40 350-50-50-50 1-3 200/20/20/50 350-350-350-350 1-3 250/20/20/50 350-350-350-25 1-3	/8x4 OR-7 /8x3½ 554011-606 /8x3 CE9103 /8x3 22-5113 /8x4 23B733495 /8x4V; OR-15 /8x4 OR-19 /8x4½ OR-16 /8x4 OR-16 /8x4 D33579 /8x5 OR-18 /8x5 OR-17 /8x4 Z7-810	.59 \$5.50 .49 \$4.50 .49 \$4.50 .49 \$4.50 .59 \$5.50 .69 \$6.50 .69 \$6.50 .69 \$6.50 .69 \$6.50 .79 \$7.50 .79 \$7.50 .79 \$7.50 .79 \$7.50 .49 \$4.50

SYLVANIA IO WATT STEREO TRANSISTOR AMPLIFIER

Made by PHILLIPS HOLLAND for SYLVANIA.

A.C., 117 Volt input. COMPLETE WITH AC LINE CORD



Full sized Powertransformer Requires space of 111/x51/2 to mount 10 WATT, RMS OUTPUT 5 WATTS EACH CHANNEL 6- TRANSISTORS 4 NEW TYPE POWER TRANSISTORS

4- DIODES 4 CONTROLS, LOUDNESS, BASS, TREBLE and BALANCE CERAMIC PHONO INPUT.

Stock No. P530-208

Price

Chassis size 101/3 x 51/3 Here is a Solid-State Power Amplifier that can be used to upgrade your AM. FM. AM-FM Tuner. Also the Phono, (Record player) output quality. Amplifier matches any 8 ohm speaker or speaker system. Crystal or ceramic cartridge output only. A schematic and Knobs are furnished. See SAM PHOTO FACTS

AMERICA'S HEAVIEST 18 INCH INSTRUMENT SPEAKER

CAST ALUMINUM FRAME, 18" CONE, WITH WITH A 3" VOICE COIL WOUND ON A GROOVED BAKELITE FORM TO INSURE PERFECT ALIGNMENT STOCK NO. CLE-18-1250-8 McGEE

SPECIAL PRICE

This 18" Cletron Speaker is probably the best 18 ever built. Has a cast Aluminum frame, 3° bakelite voice coil. A large 12½ th. Ceramic Magnet This is not magnet STRUCTURE but weight of the magnet SINUCIONE Dut weight of speaker is 38 lbs. Has a heavy one piece Cone with 8 ohm VC Range 50 to 12,000 cycles. Ideal for Instrument use or heavy—duty public address work, PROPERLY BAFFLED THIS SPEAKER WILL STAND 100 WATTS ONLY 150 SPEAKERS AVAILABLE

Set No. 1056, folder No. 8. A big barbain at this low price \$12.95 SPECIAL 12 in. CORNER WALL BAFFLE

and a 12 in, SPEAKER

BARGAIN.

A WELL CONSTRUCTED WALNUT COLORED SPEAKER BAFFLE AND 12 in. 6.8 oz. MAGNET 8 OHM VC., SPEAKER.

THIS COMBINATION WILL SERVE ALL YOUR P.A. NEEDS

> SHIPPING WEIGHT II LBS.

STOCK NO. C12RA

10 for \$65,00



MAGNETIC PROXIMITY SWITCH

NET. 79¢ stock no 2 FOR \$1.50 MD-RD30

USED FOR

RETAIL VALUE

Circuit closes when mognet opprooches sw.

McGee Special Purchase sale Actuates from Magnetic Field No Mechanical contact required.

MINITURE PROXIMITY SWITCH 1/8 IN IN CHAMETER AND
1 IN LONG 'S IN WIRE LEADS, HERMETICALLY SEALED
CLASS TUBE HAS PRICTIOUS METAL CONTACTS FOR ABOUT
AMP 50 VOLT CIRCUITS. REED SWITCH IS NORMALLY OPEN
UNTIL MAGNET IS PLACED ALONG SIDE OF SWITCH, IDEAL
FOR ALL KINDS OF USES, A WICO BAR MAG. 1/E 1/8 INC.

Midget D.C. Reversable Motors

SAVE UP TO 80 % ON THESE

CLOSE OUT ITEMS

VU METER SALE

1/a square, Mil-M-10304, specifications. Standard aidio VUECale -20DB to Plus 3. External 3600 ohm resistors required. Made for audio use. 1.22 volts will calibrate at 0 VU. Regular government cost \$8.96 in 10,000 lots. McGee's sale pice \$1.92 of \$0.00 Stock No. \$9-1034 has build nectification for standard audio use.



DC 0-1 MILL With 0-100 DB SCALE \$1.49

No. 59-3144 is an American made 1½' square 0 to 1 mill DC meter with a Decibel scale 0 to 100. DB. Regular go verament cost was \$5.77 in 10,000 lots. McGee's sale price 1s 52.05. 2 for 65.50.

(1000 ohms per volt) with 0-100 DB scale, Must be adapted to proper circuit.

MICRO-SWITCH LEAVER OPERATED

Small size: 5/8 x 1-1/8 body, with a 2-3/8 leaver

two flat push-on terminals.

10 Amps., 1/3 HP., 125 and 250 VAC., 25 AMPS., 250 VDC. .50 Amps., at 125 VDC.

Stock No.

2TMT28-4-Y

"TERRIFIC VALUE!" ORIGINAL EQUIPMENT

TELEVISION TRANSFORMERS

T. Power Transformers no transformers no tree. It code numbers on them. It is voit 50 cycle AC, new mers and have never been inced to be too quality manuals more than 2 of a kind in any becomments guaranteed to be



DC 0-1, MILL METER
MAD I BY HONEYWELL, COST
them \$5.95 to make. Our price

\$3.95 ea. 112-050

Housed in a Beautiful Plastic case With a removable front. Meter scale easy to change for new calibrations Size: 3-1/8 wide, 2-5/8 high and 1/2 thick. Extende 3/8 from panel. Mounts thru 24/29 hole. 3 boit: mounting. Shipping weight, 1 lb.

6 & 71/2 Volt NORELCO AC ADAPTORS FOR USE AS BATTERY ELIMINATORS

FOR RADIOS AND LOW CURRENT TAPE PLAYERS AND CASSETTES

NOR-6, \$ 149 NOR-750, \$ 1

7½ VOLT



SLOT RACER MOTOR Up to 9000 R.P.M. 3 to 12 volts D.C. 8 X 1 5 /8 IN. 1 /16 SHAFT IS 7/18 LONG.

53

reversable motor os used in cossette

stock no SLRM

McGEE SALE PRICE

McGEE SPECIAL

Pack 49¢

stock no. M-3XM

Midget D.C.

# MYLAR CAPACITORS

Rectangular type, epoxy-dipped for complete humidity resistance. Ideal for printed ge transistor circuits. Rated at 100 volts, plus or minus 10% Tolerance. Capacity and voltage stamped on each Capacitor.

	CAPACIT	Y	
No.	MFD.	SIZE	Not Price
MC001	.001	%"=%"=%"	\$ .05 .0.
MC002	.002	%"= %" = Yh"	.05 ea.
MC005	.005	1/14" # 1/32" # 1/32"	.05 au.
MC01	.01	36 " = 1/4 " = 1/2"	.06 ea.
MC02	.02	%"A"4"A%"	.07 +0.
MC04	.04	7" x 4" x 1/4"	.08 ea.
M COS	.05	74" × 5/4" × 1/4".	.08 .0.
MCT	.1	1/10" = 1/6" = 1/12"	.14 .0.

#### SUB-MINIATURE ELECTROLYTIC CONDENSERS FOR PRINTED CIRCUIT



Smoll condensers ore designed pri marily for vertical mounting but leads are 14" long for any use. Mylar wrapping prevents shorting in compoct circuits. Selected high grade materials used in manufacturing. Packed 5 of one type in o stondard pockage, All are 15 V. DC working.

Cat. Na.	Capacity	Pock of 5	
UC-615	6 mfd. ,.		
UC-1015	10 mfd	85	
UC-3015		1.00	
UC-5015		1.10	
UC-10015		1.25	
10 Asst. Packs 10% Off			

#### SUB-MINIATURE ELECTROLYTIC CONDENSERS WITH COAXIAL LEAD



Tiny electrolytic condensers for transistor and all miniature applications. Furnished in aluminum tubes with vinyl plastic cover. Plainly marked as to capocity and voltage. All are 15 volt working size ¼" x ½" to 5/16" x ¾" Standard pockage 5 of one value.

Cpt. No.	Capacity	Pack of 5	
EC-615	6 mfd.	75	
EC-1015	10 mfd.	.,85	
EC-3015	30 mfd.	1.00	
EC-5015	50 mfd.	1.10	
EC-10015	100 mfd.	1.25	
10 Asst. Packs 10% Off			

MADE IN HIGH MIC. -LOW VOLT U. S. A. ELECTROLYTIC CONDENSERS

SPECIAL BUY ITEM Plastic Cased

NASH	500 Mfd15 V29€
NASH	750 Mfd20 V39e
	900 Mfd50 V79¢
NASH	1000 Mfd 35 V 59€

#### CONDENSERS MINIATURE ELECTROLYTIC

CAPACITORS

Molded plastic Insulation - hermetically sealed.

18		EACH		FOR 1,65
Cat. No.	Mfd	DC WY.	Dia.	Length
E20	3	12	3/16"	%" %" %"
E21	6	12	1/4"	46 "
E22	10	12	3/16"	34"
E23	30	12"	14"	46 °
E24	1	25	3/16"	46°
E25	3	25	3/16"	13/16"
E26	6	25	14"	46 W
£27	10	25	¼"	**
E2s	30	25	34"	7/6**

UPRIGHT MOUNTING

MINIATURE CONDENSER KIT STOCK NO. UCK

Krt contains: \$2.95 " 2 FDR \$5.50

denser left of the 30 most popular types used in 2 to 6 transistor radios, and many other applications. All are 15 voits Cal No. UCA

PLASTIC INSULATED ELECTROLYTIC CONDENSER 1000 MFD. 20 VOLTS

1%" Long, 1" Dia. Leads out one end. PLASTIC 10 For \$2.75

Stock No. K4-1000-20



1000 MFD. 25 VOLT 10 FOR \$3.50

Stack No. 13481011-7

## TUBULAR ELECTROLYTIC

INSULATED ALUMINUM CASES McGEE

SPECIAL 1000 mfd., 70 voit DC.. Size; 1 X 3% with 2% " bore .

Stock No. K 20-034, \* Price .69c, 10 6.50

### ELECTROLYTIC CONDENSERS BIG BARGAINS

2000 Mfd. 30 V: **59¢** 1-3/8" x 3" 10 For \$5.00

BATHTUB CAPACITOR 1. Mfd. 100 VDC.

No. P30M Price 49¢ Oiled filled Tweeter Cross-over conden-Terminals are insulated from the metal case.

#### GENERATOR TYPE CONDENSER



Stock No. 8A4491

.5 mfd., - 100 vdc.

29¢EACH Size: 11-16 x 1-5/8 5" Leads with lug. 4 FOR \$1.00

# SAVE OVER 50%



Table 1

IMPORTATED OIL FILLED PAPER TUBULAR CONDENSERS. Insulated

.05 mfd 400 V.DC .05ea .1 mfd 400 V.DC .05ea.

### ELECTROLYTIC 49¢ 140 MFD. 175 VOLTS

Sinch No. 16347 10 For \$4.50 INSULATED SEALED BLUMINUM CAN

## McGEE SPECIAL PURCHASE SALE PLANET TUBULAR



**ELECTROLYTIC** 25 Mfd. - 150 V

1%" Long, K" Dio. 3%" Leads INSULATED TUBE 10 For \$1.75

#### TUBULAR ELECTROLYTIC 100 MFD. 15 V.DC

Size: 5/16 X 1",3" bare leads. Stock no. 1443418-9, Price 19¢

#### TUBULAR ELECTROLYTIC

50 MFD.--50 v.de

Size 5/8 X 11/2, with 3" bare leads Stock No. 23C65808 Price 19e

#### TUBULAR ELECTROLYTI 200 V

40 MFD.\ Size: 1/4 x 11/2 with 3" bare leads.

Stock no. 31519-12 Price. 29¢ CERAMIC DISC CAPACITORS /

# **500 FOR 4.99**

Sioca No. Sup-Soosu, 500 Asserted T.V. and refito sizes of disc ceramic condensers. From 2 Imfd. thru. 92 Mid. all intended for set menufacturers production. 200 to 1000 volts. Many different sizes, lacges made so big purchase. Every servicemen needs it react one of this stoortment. Sup-3003D as

Stock NoSWP-500DS Price \$4.99

TUBULAR ELECTROLYTICS 1: 200 AMERICAN MADE

50-30 Mfdrock No. ICHE-5315 150 VOLT

FOR \$2.59

GENERAL INSTRUMENT PRINTED ELECTROLYTIC

30 Mfd. 150 VDC 20 Mfd. 25 VDC 50 Mfd. 150 VDC

10 For Size 1x2% 10 Fo Stock No. K22-67C39-8 \$2.50

PRINTED CIRCUIT F.P. 39¢ ·· 50 Mfd .- 150 VDC. 30 Mfd.- 150 VDC. Stock No. Price. . 39e

Size, 1x2 10 for \$3.50

TUBULAR ELECTROLYTIC OIL SEALED PAPER TUBULARS USED IN ALL COLOR T.V. SETS 1 MFD. 350 VDC . TELEVISION SPECIAL

Size: 3/8 X 1", with 1¾" bare leads Stock no. 322-95 Price 29¢

#### CERAMIC CASED TUBULAR CAPICATOR .1 MFD., 1009 VDC 19¢ Stock No. TU-1

Latest typestandard size mylar dielectric ceramic cased tubular capacitor widely used in T.V. Solid tinned leads AMERICAN MFG



OVER 1000 OF THESE SOLD FOR \$19.95..... Fresh Stock .. \$14.95 100 FP ELECTROLYTICS \$1495 Assorted Sizes Stock No. TV-100C

INGLES - DUALS - TRIPLES - QUAD SECTIONS

#### SUPER BUY IN A FRESH 50 ASSORTED TUBULAR CONDENSER KIT.



Super low voltage tubular condenser kit. Some of these are the latest type for transistor replacement, high mfd. and low yoltage. Some low and high mfd., at 150 volt and up, and balance of kit are dual AC-DC radio filter condensers. Late productions, 50 assorted single and dual cordboard insulated condensers.

Stock No. MA-CON-50

Price \$3.95

#### OUR BEST F-P CONDENSER KIT, 50 FRESH STOCK F-P's for only \$5.95

Use these in all of your TV, Radio Solid state amplifiers and tube equipment.



Very latest types, some low voltage for Transistor use. Same high mfds, at low voltage for voltage doubler,, balance of capacitors are singles, duals, triples and quads. Can sizes are 1-3/8 and 2" dia. and 2 to 4½° long. All are Aluminum cons, some with insulating sleeves.

Shipping Wt. 9 lbs.

Stock No. MA-50 Price \$5.95

K4-503

## MC GEE OFFERS TREMENDOUS VALUES...BUY NOW AND SAVE!

#### ALL ASSORTMENTS CONTAIN NEW AND USEABLE ITEMS

Vertical Mount Capacitors PLASTIC CASED !

Latest Types For Printed Circuit Chassis



99° KT-7000

ALL POPULAR VALUES New Y-G-FULLAR VALUES
form is an accument of glassic coan relical mount tobulars for all princip circulical mount tobulars for all princip circumount must demoke, reacting from 20 for 10
formity all pacend in clear plants base.
Thesis of the services and repair
familiars today, Order now at our loss price
file is a feat mover.

20 Vertical Capacitors 99.

OPULAR PLASTIC MOLDED CONDENSER WIT



\$1.99 POPULAR SZERIE KT-7001

48 PLASTIC MOLDERS

Printed Circuit Kit



99¢

KT-7002

TINY CAPACITOR KI KT-7003



NEEDED NOW

This correlating relected conservants of tags intent time respectively methods must require emits for PF a kinds opplications... 0 vic-variety of sites and voltages for very small lectured a site vice, it is most Philipp Ortifalti in ALL CAPACITYS... assertance on site of National Capacity of the conservance of the con-traction of the conservance of the con-traction of the contraction of the contraction of the con-traction of the contraction of the con-traction of the contraction of the contraction of the con-traction of the contraction of the contraction of the con-traction of the contraction of the contraction of the con-traction of the contraction of the contraction of the con-traction of the contraction of the contraction of the contraction of the con-traction of the contraction of the

SO TINY CAPACITORS \$1.39

DISC CERAMIC CONDENSER KIT



ALMAY'S MODEL POPULAR STEES

KT-7005 \$1.99

TUBULAR CERAMIC



POPULAR CAPACITIES KT-7006

more than three of any samaity, Nortly puler General Purpose, NPU and NY50 ten-rature booffictors—all are popular and analy sale.

T-TO SO THOULAR CENAMICS

TUBULAR CONDENSER KIT



KT-7008

SO PAPER CORDERSERS \$1.39

MICA CONDENSER KIT



POPULAR CAPACITIES

\$1.19

KT-7010 sa micas

TRIMMER CONDENSER KIT



POPULAR CAPACITIES KT-7011

.99

25 TRIMMERS

\$1.49 ALMATS STEERS

PORTAL TYPE KT-7012

IN ASSORTED CONTROLS

TAR MOUNT



\$1.49 KT-7013

10 has event will, input a to the control of the co

10 TAB MOUNT CONTROLS

DUALCONCENTP' CONTROLS



\$2.49 HERD THES EST KT-7014

10 negotian dual monements anticule und in TV ord este ratio. Elé lamiente 5 coch converte with and editions oriton. All com-maio for very large TV not annuferiorment, Dealers in pour area will go for this in a fid mystill.

IN CONCENTRIC CONTROLS

20 METAL CLAD RESISTORS KT-7015

Top quality metal clad realware summittee called condolum. A white range of remistance values and languam from 20° to v". Disaffait book rapitly when numbed to motal change.

694 TO METAL CLAD RESISTORS

INSULATED SHAFT CONTROLS

Sabelite Shafts KT-7016

10 INSUI ATED CC \$1.49

25 Precision R



20.12 POPULAR SIZES SMASATICHAL SAVINGS KT-7017

25 Precision Resistors

TUBE SHIELD



28 ASS'T THE SHELM 79

100 Ass't insulated Resistors



ALMATS STREET ALMATS POPULAR KT-7019

100 slamp oppniar value 1/2, 5 and 3 ent inculated sarben realstore, Broyr resister tendant RM is color coded and made by relan-dered minifesturer, EES includes 700-1/2, 20 2, and 100°s must resister, cholese overpo-views in the U.S. mass and over 30,000 of those 15% to their ministrict service and experimentar contamers, Pathagud Shrunt-Seely is established to the control of the resistance of the contamers of the control of the resistance of the contamers of the control of the resistance of the contamers of the contamers of the contamers of the resistance of the contamers o

100 INSULATED BESISTORS

SAMS COATED WIREWORRS RIT



KT-7020

35 very steely used values of § 1 10 mg; open centur reassers. Each value clausity merical or read there may, 16 to believe the merical or read there may, 16 to believe the merical or read to the control of the contr

25 SAND RESISTORS 994

WIREWOUND RESISTOR KIT



\$1.59

AUMATH POPULAR

IN WITEWOORD DESISTORS-

WIRE ASSORTMENT



SIX 75 FOOT COILS Pally Insulated Standard Sizes Tinned Copper

KT-7022

SIX 25 FOOT COILS

Hočkup Wire N. CUT-STRIPPED-TINNED



720E 54710 KT-7023

Vide variety of six of invalid theology in re-week lay the perimeter, service maps and sectors. He time and tengers, the substitute of tengers, the substitute of tenge langths or specific. Trained along plactic uses, iconsteadly upon these by the speak is resdy to use.

Pound Cui Wire

Matched Cable



SAVES TEN K T-7024

.69 € 10 MATCHES CABLES

MATCHED PLUG & SOCK.



ALMAYS POPULAR KT-7025

20 SOCKETS & PLUES .69 d

HIGH VOLTAGE CORRECTOR SIT



ALMAPS SEEDED KT-7026

16 ASS'T CORNECTORS \$1,29

RADIO POINTER KIT



79¢ POPULAR TIPES KT-7027

20 ASS'T BIAL POINTERS



ON 79c KT-7028

Hanty tenorages of it solver by terminal etripatall tandard types so seed daily in resistant and place or included from each of six types from each through &

Crossover Condenser Kit



For the RL FL Forest All Torted & Descriptor KT-7029

S CROSSOVER COND. .79 U. H. F TV KNOB KIT



79¢ KT-7030

ed in white study places has a close subject the for nore than a lat. Take mirortage new of this Australia. H. F. Knobs

Screw Terminal Assortment



89¢ Almare Popular

KT-7031

20 SCREW TERMINALS

Attachable AC Switches

# AC Switches KT-7032 BIG VALUE .. . 89

Set Screw Knob Kit ALL WITH SET SCREWS



KT-7033

5 PAIR SET SCREW ENDRS 996 PLUG BUTTON KIT



KT-7034

dare he a splendid assortance (a. plug hetians for covering missed delay chards or for ormanental use... Magain a clear plants beg.

14 Assorted Buttons 49¢



KT-7035

15 BATTERY PLOTS 49¢

#### TERMINAL BOARDS



POPULAR TIPES KT-7036

20 ASSORTED BOARDS .90

PILOT LIGHT SOCKETS

POPULAR. KT-7037

38 PILOT LIRHT SOCRETS . 79



KT-7038 tantaro 3/8 - 32 tareno .59

TV COIL KIT



ALMATS STREET PORGLAS TYPES KT-7039

25 TV COILS 69d



Wennished and Shielder Types

18-21 MG. TV I.F.S 59d

KIT OF 23 RADIO CLOCK KNOSS Cahad Ck-25

25 RADIO CLUCK KNOWS

3

Ratio Detector Assortment



POPULAR

I different, popular, 4.7 K T - 7042

I different, popular, 4.7 Kc. reals dedector mends of right-priced live any Fi services and will law, I balance seem momentar from 15th to 1-75 detection of circuit, edde-tilp to 15th and reals boll monation, restauge attractively in clarify placetic began.

5-4. 5 MC MATIO BETECTORS

SLUG TUNED COIL KIT



POPULAR SIZES KT-7043

29 assorts' sing tuned radio and TV units Excellent for these who destro to strip to receive, or see be seen as ting are. Tack-aged th a class playtic bug.

26 SLUG TENES COILS . 59¢

Broadcast Oscillator Coil Kit



ALMATS VENDO

KT-7045 O amounted 6 popular breatenst assillater only for all AC interminists frequency... I fluo variety of segmentional types used be work over with standard superhot some beind in a clear plantic beg.

10 Broadcast Occ Coils 69¢

TUNING SLUG KIT ALL POWDERED IRON

> \* Standard Erpon · Pecular Verlet

KT-7046

25 ASS'T TUNING SLUGS .69



KT-7096



990

59 CABLE CLAMPS 694



METAL SPACER KIT Steel, Breas And

KT-7049

SO METAL SPACERS 59e

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108

#### \* \* \* PRINTED HEADERS



KNOB ASSORTMENT

KT-7050

10 ASS'T CHANGER MIONS 89¢

TV KNOB SETS



39¢

KT-7052 TV CHANNEL SELECTOR KNOWS



\$1.09 ALL VIE

KT-7053

IN TO CHARBEL SELECTORS

LONG NECK KNOB ASS'T



20 LONG NECK KNOB\$1.19

STATION SELECTOR



Permian Types Always Santos KT-7055

10 AM SELECTOR KNOBS (94

PUSH-ON RADIO KNOB KIT



POPULAR.

to 17-7050 25 PBSH-ON KRORS-80 17-7057 50 PUSH-OR \$1.40

""INTED CIRCUIT SOCKET KIT KT-7058



H-709 25 PG BOCKET\* 99

TUBE SOCKET KIT



KT-7059

79¢ 28 TOBE SOCKETS

TEST POINT SOCKET KIT WIDE VARIETY OF 7 & 9 PIN



KT-7060

20 TEST POINT SOCKETS

SMALL SIZE ELECTROLITIC THEBLAR ASS'T IBEAL FOR TRANSISTOR EQUIPMENT



AMERICAN MADE RESH STOCK I KT-7061 \$1.29

TER SMALL ELECTROLYTICS

RECTANGULAR WIRE WOUND RESISTORS



KT-7062

28 RECTARGULAL DE \$ 1 29:

FOR SERIES STRING SETS



KT-7063

5 FILAMENT PESISTORS \$1.19

SE VOLUME CONTROLS FOR SMALL ASSEMBLIES



KT-7064 \$1.39

S MINIATURE CONTROLS

BUZZ & SENSITIVITY CONTROLS



KT-7065

S BBZZ SERSITIVITY CONTROLS

35 PIECE KNOB KIT PUSH-ON KNOBS



KK-35

Price \$1.00

Shipping weight 11b.



Push off- Push on. 3 amp 250 volts AC switch 40-638 Red. 654 40-639 Block 65¢

AUTO RADIO CONTROLS



KT-7069

10 AUTO RABIO CONTROLS

BUMPER FEET ASS'T FORR MATCHER SETS OF FORR



59¢ KT-7070

2 LB BOX

FILAMERT BROPPING RESISTORS SELF TAPPING SCREWS



\$1.19

2 LB. SELF TAPPING SCREWS

2 LB. BOX STEEL WASHER VIZIETY




¿LBS. STEEL WASHER\$129 **AUTO RADIO KNOBS** 



KT-7073 \$1.49

20 AUTO RADIO KNOBS

2 LBS. RADIO-TV HARDWARE





TV KNOB KIT



POPULAR KT-7083

\$2.39

SOLDER TERMINAL LOG KIT ₹ KT7084 9 F \$1.29

200 TOOTH & RING LUGS



imility 2 lbd packed in a strong cor-container. scortaget will save you time, somey i . Order now at great savings....... Pound Nuts & Scrows



16 CABINET PYLLS-3149



200 ASSORTED SPRINGS

Huge Hardware Ass't




2 Pounds Hardware \$1.19

Wood Screw \*

POPULAR SIZES

KT-7090

200 Wood Screws \$1.49



ore to a real terrein in a very popular contint error bit, consisting of self-ing type of self-twist and mechani-cipment total, all repair ones, later cipment total, all repair otage, later

\*75 SHEET METAL SCREWS

ESSENTIAL HARDWARE KIT CLEAR PLANTIC



PRINTED CIRCUIT BOARDS



KT-7093

10 PRINTED BOARDS 89¢



RECORD AMP-LOK

\* Universal mounting to AF B.S.R., VM and Garrard Amp-Lok with AC cord for record changer



STEREO PHONO LEADS



6 it. Twin shielded phono wires with 2 RCA phono plugs. Has many uses THE ELECTRIC MOTOR

SALE PRICE

PAIRS BALUN COILS

TELECHRON AND WESTCLOCK CLOCK MOVEMENTS

(Leat Fares)

tock No. TWEM. Price \$2.99

лист **99**е



3/4 in rubber feet with screws.




90-807 net 36¢ Pack of 2 dual RCA type pin jacks in a fiber mtg. plote. 4 mtg. hales 1/2 X



30-441 net 65¢ pack of 10 RCA type pin jacks for chasis mounting 3/4 in. mounting hole centers




90-810 net. 89¢ 5 red and 5 block 5/8 in long sub-miniture binding posts for trans board mounting.





30-440 net 65¢ pack of 10 clomp on for \$1.00 rca type pin plugs



## AUDIO and GENERAL-PURPOSE CONNECTOR CABLES

Flexible "Y" Connectors with 4" Shielded Cable

Model 14-131 496

Pin plug to one pin plug and one pin jack—all RCA type.



Pin plug to two pin plugs-all RCA type



Model 14-133

89¢

Pin plug to two pin jacks-all RCA type

## HI-FI CABLE ASSEMBLIES



89¢

and right angle RCA type phone



Right angle phone plug one end and stripped and tinned leads at


Right angle phone plug one and and straight barrel phone jack other and, 72" grey, shielded cable, Cat, No. TN-5

Right angle phone plug one and and pair of alligator clips at other and 72° gray, unshielded parallel

Cal. No. TH-7

569¢

Bight angle RGA type phono plug one end and microphone connector other east. Coupling ring can be screwed back to convert to male connector. 72° grey, shielded cable. Cst. No. TM-4




99¢





Right angle RCA type phone plug one end and streight ber rel phone jack other end, ?? grey, shielded cable Call No. TN-8

Right angle ACA type phono plug and peir of alligator clips at other end. 72" grey, unshielded parallel cable Cat. No. TN-8 Right angle phone plug one end and RCA type phone pack other end; 79 ¢ 72° grey, shielded cable Cat. Me. TN-10



WITH MINIATURE PLUGS Finest quality shielded silver-grey audio cables, plastic cov-ered. Most ends feature mould-ed plug or jacks for trouble free

connections. All cables are 72" long. Miniature moulded plugs fit Sony, Concord and 90% of the Japanese tape recorders.



movided plug, 72 with 2 alligator clips and. Cat. No. MP-3

69¢

Cat. No. MP-5

69¢

Miniature moulded plug one end to RCA type pin plug other end. Cat. No. MP-7

99¢

to standard shielded other end. Cat. Cat. No. MP-6

Ministure moulded plug one end to standard moulded phone plug other end. Cat. No. MP-6

69¢

DUAL AUDIO CONNECTOR CABLES Audio connector cable. Color coded dual pages other and - Individually packaged -

69: 89: SAB 36 36 inches long SAB 72 72 inches long **DUAL AUOIO** 

CONNECTOR CABLES SAT 36 36 inches long 89¢ SAT 72 72 inches long 1.19



#### FM EXTENSION CABLES

390 FM-36; Length: 36" 49¢ FM-48- Langth 48" 54¢ FM-80: Langth: 60" \_\_\_ 72; Length 72 ... 59¢ 69¢ FM 120; Length 120"

Connector cables, new style extension cord with insulated RCA type pin plug to RCA type firm grip insulated extension jack. Grey color available in the sizes




EACH KIT CONTAINS

1—grey cable 2—red cable 1—black cable 1—green cable \$159

10 FOR \$15.00

JUMPER CABLES Main RCA type plu plug both ends



45¢ 59¢ 39¢ IC-72: Length 72" JC-36; Length: 36" \_\_\_\_ 69¢ 44¢ IC-126; Length: 120" IC-48, Length: 48"

#### INTERCONNECTING Hi-Fi CABLES

PHONG PIN PLUG ONE END OTHER END STREPPED AND TINNED

## Cammunit. 18-36 (36" long) 29¢ Finest quality shielded, silver grey audio cable. \$72 \(\text{OZ'}\) long) 49¢ Plug molded directly with polystaplene for a more reliable, trouble-free connection. \$8-120 \((120'\)\) long) 69¢


#### STEREO EXTENSION CORD 3-WAY PLUG & 3-WAY INLINE JACK

20 ft. extension cord with 3 circuit plug and jack will permit listering to your favorite stereo program through your stereo headphones.

Grey covered three conductor plastic cable. One end has 3 circuit plug. Other \$ 9 4 9 and has 3 circuit in-line jack. Cat. No. E.C.-3

## STEREO ADAPTER KIT

Stereophonic Conversion IM for most tone arms, IM contains two shielded subles with pin plugs connected to 5 terminal tie point, 36-inch cables.



Cable



Stock No. MPJ 72" PATCH CORD

## WITH PLUGS AND CLIPS PH 10 for Stock No. PC-72 996 \$9.00

RETRACTIBLE

GUITAR CORD Stock No. \$200 PP 25 R.

Shielded calfe is covered with a rugged blesh viryl. Sweled &:"
phono plue is on one end to plue into the smaller and a right infit the smaller and a right infit %" plug is on the opposite
for to plue into guiter. 32,99



### RETRACTIBLE

GUITAR CORD 180 INCHES LONG Stock No. \$1.99 LESS THAN IMPORT COST

Right Angle Phone Plug

Patch Adapters To German Plugs



Model 841 STEREO ADAPTOR PATCH CORD

\$2.25

May be used on Phillip's type cassette recorders, Norelco, Wollensak, Bell & Howell and others using D.I.N. European plus. For universal use to record stereo/monaural from tuner-receiver or playback through stereo/monaural speakers. 5 prong D.I.N European plug to 4 RCA pin plugs, 64 feet long shielded stereo cable, Flexible molded plugs,

## AUDIO PATCH CABLE

3 Pin D.I.N. To 2 RCA Plugs \$1.95 Model 877

6 foot shielded, color coded audio patch cable 3 pin D.I.N. foreign type audio plug to 2 RCA type phono plugs. Adapts Cables for cassette, reel recorders or radios using 3 hole D.I.N. socket, for microphones, speaker, phone, etc.

#### AUDIO PATCH CABLE

3 Pin D.I.N. Model 878 To 1 RCA Plug \$1.75

3 pin D.I.N. european plug one end. RCA type phono plug other end. 6 foot shielded cable adapts foreign 3 contact socket to standard phone jack.

## ADAPTOR CABLE FOR FOREIGN RECORDERS

3 Pin D.I.N. To 2 RCA Jacks \$1.50 3 Pin D.I.N. Model 879

3 pin D.I.N plug connects to 2 jacks. Shielded ca-ble each 12°. Color coded. Adapts foreign 3 con-tact sockets in Norelco, Karting, Grundig, Sony & and Elber Recorders, and in Grundig Radios, to standard phone plugs. Use in microphone input, speaker output or phono recorder circuits.

## AUDIO PATCH CABLE

Model 862 To 4 RCA Jacks \$2.50

May be used on Phillip's type cassette recorders, Norelco, Wollensak, Bell & Howell and others using D.I.N. European plug. For universal use to record stereo/monaural from tunen-receiver or play back through stereo/monaural speakers. 5 prong D.I.N. European plug to 4 RCA jacks. 6% feet long shielded stereo cable, Flexible molded plugs

## GERMAN AUDIO PLUGS





3 PRONG D.I.N. AUDIO PLUG FOR ALL MONAURAL CONNECTIONS Model 845 3 Pin D.I.N. Audio Plug 59¢

5 PRONG D.I.N. AUDIO PLUG FOR

ALL STEREO CONNECTIONS Model 846 5 Pin D.I.N.

5 PRONG D.I.N. AUDIO PLUG & JACK FOR ALL STEREO CONNECTIONS Model 847 5 Pin D.I.N. Plug & Jack

D.I.N. Audio Plugs are completely shielded and insulated. Insulating sleeves are easily removed to expose the soldering connections

#### RETRACTABLE HI-FI CABLES Audio Cable with RCA Type Plug Each End



EASIEST AND FASTEST WAY TO CONNECT HI-FI EQUIPMENT

79¢ EACH HF-6 36 In. Cable HF-14 15 Ft. Cable \$1.49 EACH



PLATED ALLIGATOR CLIPS 100 bags for \$30.00


Strong grip jaws plain alligator clip. For use in all types of testing equipment, Designed with a long thin nose to fit close areas or hard to get at places. 2 inches long, with screws for terminals. Packed 10 Alligator Clips to a package. AC-5 (BAG OF 10)

MINIATURE PUSHBUTTON

SWITCH

A new heavy duty minature push button switch for panel mounting. Wide use in most ministure and sub-ministure applications.

S.P.S.T. - momentary contact push to make 125 wort 1 amp capacity Overall length 114 inches SP-2 (40-637)



**SWITCH** S.P.S.T.

1-1/8" x 3/4" Dia 2 Screw Tempinal Municitary Contact Normally Open

Stk. No. 19 ¢ SP-3 10 For \$1.75

A new heavy duty pushbutton switch for moment-ary contact. Mounts on panel thru 5/8" hole, Red button, black base with Chrome mig. ring.

ROCKER-TYPE SWITCH

Rocker-type a.c. switch. Neat ivory plastic arm is pivoted so that only slight thumb pressure is needed for control. Shows at a glance whether off or on. Molded plastic encased with mount ing flanges. Size 1% & 1% & 1% in Rated 3 49 c amps @ 125 V. RS-2 (40-630)

RS-6. DPDT Rocker Switch. 59¢ SPST TOGGLE SWITCH Bakelite case, but handle, with chrome On-Off plate Solder fug terminals 125V-3A. 1%" x %" x 1" deep to too of %" bushing. TS-10 (40-600) 29

DPDT TOGGLE SWITCH

Bat handle switch with chroma On-Off blate. Ballelite case, six solder terminals, 125V, 3A., 1V4"x 14" x 114" deep, 14" bushing.

TS-12 (40-601)



Bat handle center-off toggle switch with bakelite case Red and black On-Off plate. Six screw terminals. 1%" x 4" x 1%" deep. 125V — 6 amp; 250V —3 amp rating, %" bushing

TOGGLE SWITCHES MT-6 MT-6 (40-611) \$1.09 ctuol size MT-3 99¢


MT-6 Sub-minature 15 amp. 125V. DPDT Toggle switch, 1.09 ea. 10 for \$9.90

Similar to above but smaller. SPST Toggle switch, 99c ea. 10 for only \$8.90

HEAVY DUTY TOGGLE SWITCH Will handle up to 20 omps. at 125 VAC. or 10 amps, at 250 AC
//16" dia, ½" long bushing

3/16 dia., 5/8 long handle Body size: 5/8 thick x 1-1/8 wide. Requires 1" space behind the panel.6/32 screw terminals for wire connections

BITY standard package of 4 and save. Stock No. 308-7, 39¢ ea. 4 for \$1.40



79 Cot. No. N-823

Handy for Radio men and electricians for testing AC lines, polarity of AC or DC, for blown fuses, tracing ground lines in AC circuits. Can be used on voltages to 550 volts AC or DC.

#### 3-WAY AUTO SPEAKER SWITCH KIT

Cat. No AS-2

impletely wired with instructions. For switching heren dual speakers (front and rear). All dis ides wired switch, mounting plate, knob an rews. Industrually bened in plasfic box.

3-WAY AUTO SPEAKER FAOER KIT With Fader Control

olume between front and it includes wired control, ind screws Individually boo

PUSH BUTTON SWITCH KIT **99**c

Push button switch kill for any rear deck auto speaker. Push button selection of rear seat speaker, from speaker or both speakers. Comes with all necessary cable connections, mounting plate, hardware and instructions. Call. No. AS-G.

3-WAY AUTO SPEAKER SWITCH Stock No. 55-1 Rotary switch for selecting either front or rear or both suto radio speakers, positive contacts, plated solder terminals. Has split 1/4" knurled shaft. 3/8 bushing mounts through dash or panel.

ROTARY SWITCHES

1886J 1-pale, 11-position Single Deck 1887J 2-pale, 12-position Two Deck

Precision-Built rotary Wafer Switches with silver plated contacts and double ball detents, Ideal for use as selector switches in Stereo and Monaural Hi-Fi, test equipment and many more experimenter applications. Size: 1/2 round shaft x 11/2 long, mounts in 3/8 hole in panels up to 1/8 thick.



LOCKING TYPE PUSHBUTTON SWITCHES

Positive action, multi-circuit pushbution awitches with lack-in feature for push-on, push-off applications. Used by experimenters, amateurs, MLFI builders, etc. Equipped with silver plated terminals, pre-lubricated self-cleaning wiper blodes and molded plastic button. Mounting holes lapped for 4-40 screws on 25/32" centers.

Overall tength LORRE 1890J 4POT



D 1096

A.C. CHASSIS SOCKETS

AC socket 'Fifs standard plug' For use on chassis as 117 vott AC outlet, 15 amo (10 per beg) Depth to lugs
Thickness Cat. Na. ACS 10 FOR \$1,25

184

STANDARD BRAND SLIDE SWITCHES. Made in at less than manufacturers cost. USA Stk. No E 10 15 ntacts Conta SPST Mtg. 1-1/8" E 10 18 SPDT

1-1/8

PILOT LIGHT ASSEMBLIES

DP DT

FOR \$6.50

neum famps of various is mends 3 4" behind the nickel plated here! Buy mips. Both contacts are pring positive center con Model B 110B-R Same Surpnet, Red

39 M-40 81108-G 10 FOR \$3,50

10 FOR \$7.50

FUR SAU TYPE FUSES

1/2" FACETED JEWEL UNIVERSAL PILOT LIGHT ASSEM

25-311 GREEN

MUELLER CLIPS AND INSULATORS

NEW 34 SERIES MICEO-GATOR CLIPS 50 07 \$0.047 \$0.041 - 00 033 039 MINI-GATOR CLIPS

10 10 10 50.062 50

TO SERIES ALLIGATOR CLIPS 70 70-5 70-C5 70-C5 08 50

5 3. 1 03 50



60 SERIES ALLIGATOR CLIPS UNIMSULATED 60 SERIES

ter Each, Late of 0150.07 50.061 2 .082 .07 6 .126 .1 98 06 ...041 .035 INSULATED 60 SERTES 30.16\$0.115'S0.098 - 22 186 134 - 23 158 136 - 27 19 162 60-M5 60-CH5 63-C PEE-WEE CLIPS (FIG. M)

0 30 008 30 0



Will take alligator clip, benena and tip plugs, spade lug or wire 99¢ Model 25-855

## BINDING POSTS Sturdy 5-Way-

Mounts through 1/4" hole in panels up to 1/4" thick. Tops of posts have standard banans jacks and will unscrew for ellp or bare wire attachment. Stud solder connector designed for quick-tie installation.

**K(0)** Model 25-852G.

Green Binding Post. 10 for \$2.90

PLASTIC PHONO PLUGS,

390

10 FOR 53.50

ASSEMBLIES

Standard RCA type. Two piece plastic connector that does not need soldering of the shielded braid of the constitution of the content of

10¢ ea, 10 for 89¢. 100 for \$70.00

PUSH BUTTON BINDING POST KIT STANDARD FUSE HOLDER Ideal for fast connections

Supplied with hardware and insulating washers.

2, RED & 2, BLACK

"' long, ''' dis.

Strick No. 865(90-780) 69¢

VOLT PANEL LIGHT

3/8" INDICATOR
LIGHT with
a minature base, sevent type bulb.
Smooth face Jewel in 4" threaded
brass holder. Package of 2, Red
and Green.NO. 90-797, 79¢

NEON PANEL LIGHT INDICATOR

Red or Grean the line out 39¢10 For

## 250,000 RADIO-TV-HI-FI VOLUME CONTROLS - SAVE UP TO 80 %

#### MINIATURE VOLUME CONTROL LESS SWITCH

Replacement controls 14" dia., fits in Yu" hale, Shaft % Oia.45" long Supplied with mounting hardware, Specify resistance.

Cat. No. TV-100


Car. No. (4	-100	
Co1 No.	Value	45
TV-100	2K-Linear Taper	
TV-100	SK-Linear Toper	CABLL
TV-100	10K-Linear Toper	The Page
TV-100	SOK-Linear Taper	TO TALL ACT
TV-100	100K-Linear Taper	1/1/0/2
TV-100	250K-Linear Toper	70/000
TV-100	500K-Audro Taper	
TV-100	1 Meg-Audio Toper	
	-	10 For \$4 5

## **VOLUME CONTROL — LESS SWITCH**

Replacement carbon valums controls ovail-able in the 6 most popular values. High qual-ity carbon having high stallifity under most conditions. Specify Value
VI. 2K— 2,000 ahm Linear Taper
VI. 10K— 10,000 " " 10 Fo
VI. 10K— 10,000 " " 10 Fo
VI. 10K— 10,000 " " \$4.50
VI. 250K—25,000 " " \$4.50
VI. 500K—500,000 " Audio Taper
VI. 1 Meg—1 Megahm
Specifications 10 For \$4.50 Specifications:
11/1, dia., 1/16 deep, 10 inch dia.
2" flat shaft. 2" flat shaft.
""" bushing, 2" long
Supplied with lock washer and mig. nutladiv. baxed.
Cat. No. VL

## MINIATURE CONTROLS WITH SWITCH

10 For \$5.50



## UNIVERSAL VOLUME CONTROLS AT MORE THAN 50% SAVINGS!

carbon potentiometers



59¢ 49¢ =~ LOTS OF 100 EACH LOTS OF 10

OHMS **OHMS** OHMS 1 MEG 100,000 500,000 3 MEG. 250,000

## UNIVERSAL SHAFT VOLUME CONTROLS

10 ASSORTED FOR \$5.50 Description Switch Shaft Type-Lonoth No.

June 1964. Description points from the property of the large of the la

#### WIRE WOUND CONTROLS



60 OHM 4 WATT FOR USE WITH ANY TWEETER

Stock No. CTS-60W, 60 ohm 4 watt wire wound control for use with any tweeter, as described in Popular Electronics article on construction of the Sweet Sixteen Speaker System. This control is dealigned specially for this type of application. Will the through panels up to 3/8" thick.

McGEE Sale Price...852 each, 10 FOR .....\$3.20

## STANDARD SIZE CONTROL

AT BARGAIN PRICES

Stock No. 2A51

29¢ EACH

3/8" threaded bushing 500,000 ohm, 14" dia. salined push on shaft 7/8" long

## MALLORY

Stock no. 2A69

1 MEG. OHM.

oudin toper WITH PUSH-PUSH ON-OFF SWITCH

REG 1 IN. DIAMETER CONTROL WITH 3/6 IN.
THREADED MOUNTING STUD AND 3/16 DIAMETER
SHAFT 3/4 INLONG BEVOND STUD.

## NATIONAL UNION SAV-A-SHAFT CONTROLS



WITH SWITCH 19¢ AND 24¢ EACH

Audio controls with standard 1/4" diameter shaft and coupling sleeve for universal replacement and builders use. All controls have Off-On AC power switch which is engaged by pulling out a small metal tab. You can use these controls with or without the switch. Individually boxed and labeled National Union. (Made in U.S.A.) McGee has only 25,000 to sell at 19e and 24e each. No added discount for quantity purchase.

Stock Number NU-5M-A NU-10M-B NU-25M-A

250K 500K

Description
5,000 ohm w/switch
19¢
15,000 ohm w/switch
19¢
19¢

100,000 onm w/switch 19e 250 000 ohm tapped, w/sw. 24e 2 megonm tapped, w/sw. 24e

## 10,000 ohm Volume Control




39¢ EACH 10 for \$3.50

SMALL CARBON POT HAS SPST BWITCH MADE IN USA. FOR TRANSISTOR CIRCUITS. 5/6 IN. DIA. 3/16 IN SHAFT IS \$ IN LONG

**SAVE 70%** 2 Watt Hot Molded

## **POTENTIOMETERS**



MECHANICAL SPECIFICATIONS

size 1%" diameter, %" deep FMS 2 watts @ 70° C, 500 walts @ 70° C, 500
SMAFTS RC39 Series — 1/4" diameter, stain less steel, full round, screwdraver slotted 23/4" long from mounting surface.

Ohms	Taper	Catalog No	
50 100 250 500	C1 C1 C1	ACS9 500 U ACS9-101 U ACS9 251 U ACS9-501 U	
2500 5000- 10H 25K	C1 C1 C1	ACS9-252-U ACS9-502-U ACS9-103-U ACS9-253-U	

Otents	Taper	Catalog No.
1000	CZ	AC\$9 104 A
250K	(2	ACS 9 254 A
500K	C2	ACS9-504 A
3 Meg.	C2	ACS9 105 R
2.5 Meg	CZ	ACS9 255 R
104	C)	ACS9 103-B
25K	C3	ACS9 253 B
50K	C3	ACS9-503 B

## AFSS SERIES (LOCKING BUSHING)

Dhins	Taper	Catalog No
50	GI	AF\$5 500-U
100	C1	AF\$5-101-U
250	CL	AFS5-251-U
500	C1	AFS5 501-U

Centralab 5 for \$3.00 -10 for \$5.50

## SPECIAL SALE ON VOLUME CONTROLS WITH PUSH-PULL SWITCHES

Stock No. 23C220252-1 Price. 69¢

CONCENTRIC CONTROL

Front Section: 2 meg.

Shaft W' X 3/8" long. Rear Section: 1 meg. tap at 200,000 ohm. Shaft, 3/16" X 5/8" long.

3/8" Threaded bu shing. PUSH-PULL SPST SWITCH-

#### I MEG ohm CONTROL

Standard size 7/8 round. 3/16" flated shaft 3" long. 3/8" threaded bushing

Stock No 1472207-39 AUDIO TAPER

Price 59€

PUSH-PULL SWITCH, 6 Amps, 125 VAC.

## GENUINE ZENITH CONTROLS WITH PUSH-PULL SWITCHES

1 MEG CONTROL with SWITCH Tapped at 500K AUDIO TAPES 3/8° threaded bushing.
3/16" round shaft 4" long Price, 69¢ Stock No. 63-7444

## 1 MEG CONTROL with SWITCH

Tapped at 40 K ohms. ZENITH WITH PUSH PULL OFF-OH SWITCH

Price 69¢ AUDIO TAP

23/11 long shaft Stock No. 63-6955

3/8 INCH THREADED BUSHING. 3/16 DIAMETER SHAPT IS 2 3/4 IN. LONG

## 1 meg Control With Switch.

Price 69¢ Topped at 500K ohm 63-6953 PUSH PULL OFF- ON SWITCH

3/16 DIAMETER SHAFT IS T 1/4 IN LONG

## 1 Meg Control With Switch Topped of 500K ohms, price 69¢

63-6477 PUSH PULL OFF-ON SWITCH

FITS ZENTTH AUDIO TAPER TWIST TAB MOUNTING. THE 3/16 IN.

DIAMETER SHAFT IS 3 INCHES LONG. FITS ZENITH

## 1 Meg Control with switch Topped of 500K Price 69¢

24 IN LEAD ATTACHED TO SWITCH 63-6829 PUSH PULL OFF- ON SWITCH.

FITS ZENITH. 3/8 IN. THREADED MOUNTING

BUSNING. 3/16 IN. DIA. SHAFT IS 5 IN. LONG.

10 for

SPECIAL DRIVE-IN 59¢

stock no. TH8-L

quantity limited. McGee Special

4 10 4

\$5.50

control volumn of 8 ohm speakers.

5 WATT WIRE WOUND OXITA 6 OHM L PAD. 120 DEGREE ROTATION FROM MIN TO MAX. REG 3/8 IN THREADED BUSHING MOUNTING 1/4 IN SNAFT IS 3/8 IN LONG. VERY GOOD FOR COMMERCIAL WALL BAFFLES AND CETLING GRILLS.

49° Audio \$3.90 Taper 6 cmp switch \_\_\_\_

M-178J208-2 control is 1 in dio. twist tab mounting reg. oft—on ac switch 1/4 in nylon shaft is ! In long



7/8 in. diameter control is twist tab mounting shaft is nylon 3/16 in.

diameter 1 in. long

DUAL CONTROL with AC. SWITCH 500 000 ohm front 500,000 ohm rea. 79¢ 10 for \$7.50

with single throw single pole switch. Stock No 120-180 Price 79a

LINEAR TAPER

CONTROLS TAB MOUNT

" DIO. 15"INSULATED SPLINED SHAFT

McGEE 29 \$ 10 For \$2.75 Special 29 \$ 100 For \$25.00 1U For 52.75 Remetance Shell to Taper Light. Size Type

M b-J 796-2 2 SK Line aw P5 4 Rd. Sol. Tab M b-J 796-12 100K Audio 1-3,4 3 16 R P1. Tab M b-J 796-12 200K Line B 12 4 Rd. Sol. Tab M b-J 796-1 200K Line P5 4 Rd. Sol. Tab M b-J 570-2 350K Line P5 4 Rd. Sol. Tab M 2-J 519-2 12 Mea. Line P5 4 Rd. Sol. Tab M 2-J 519-2 12 Mea. Line P5 4 Rd. Sol. Tab M 2-J 797-5 2 S Mea. Line, P5 4 Rd. Sol. Tab M 2-R 797-2 S Wee, Aud. Line, 1 Rd. R. P1. Tab M 2-R 797-2 S Wee, Aud. Line, 1 Rd. Sol. Tab M 2-R 795-2 S Wee, Line, 1 Rd. Sol. Tab M 2-R 795-2 W 1 Mex. Line, 1 Rd. Sol. Tab M 2-R 795-2 W 1 Mex. Line, 1 Rd. Sol. Tab

10,000 OHM AUDIO TAPER CONTROL
With SPST SWITCH AND
Standard threaded Bushing Mig.

Stock No. 39¢ ..

1/2" long Round Flotted Shaft

200,000 OHM CONTROL With DPST Switch SNAP-IN MOUNT Stock No. 39¢ M3-1346141

1/4" Statted Shaft, 3/16" Lang

I MEG. CONTROLS WITH SPST SWITCH 3/16" Dia, Insulated Flored Shaft with 3/8" Bross Bushing Mtg.

M3-750158 39¢ ..

PRINTED CIRCUIT CONTROLS WITH SWITCH 500,000 OHM

M3A-V027-N14

1 '4" Dia. Round Shaft, Flated 3/8" Shaft Length 1"

PRINTED CIRCUIT CONTROL AUDIO TAPER 1.2 MEG.

M4-31P101 L2 Mes Ohm Audio Taper Control 5.4" Shaft 145" Icog, S.P.O Type.......29c



100 \$20.00 29 Coach for 500,000 ohm

Audio taper 390900 7/8 diameter 1 in. long 3/8 in threaded bush 1/4 in. shaft 2 1/2 in long

DUAL CONTROLS FOR HI-FI AND STEREO Dual controls for HI-Fi and stereo. 15/16" Dio. and less switch except as indicated. FPO shaft as shown.

Common shaft works both sections. Stock Front Rear Shaft Net Number Section Section Type Longth Price 973243-5 500K Tap 175K 500K Com. 175K %" Flot .69 175K 100K SPST Switch 2 Meg Com. 17/8" Fl. .49 2 Meg Com. 1" Flot .49 3 Meg Com. 1" Flot .49 100K 2 Meg 12381-1 2 Meg 2 Meg Com. 7/8" Fl. 49 120-165 2 Meg 2 Meg Com. 1" Flor 49 63-4840 3 Meg 3 Meg Com. 1" Flor 49 12468-3 3,3 Meg 3,3 Meg Com. 1-1/8 Spl. 49 Top: 1 Meg 1 Meg

304-5301 5000 5000 1/2 IN. CARBON CONTROLS LESS SWITCH 3 for 50c 20c Each

Here is a wide selection of single carbon controls for radio and TV replacement use at less than factory cost.Order a good supply now and save. Top quality, exact replacement for original equipment.

BUY 100 ASSORTED, ONLY \$15.00



Number | SOS-4 | megah | IAE-1 | ISOO | RD-1 | SOOO | RD-3 | IOO | RO-3 | IOO | IOO | RO-5 | IOO | IOO | RO-5 | IOO | IO 1/2" TAB RD RD RD RD RD Stech

KN-2 SDS-1 500 SDS-2 500,000 SDS SDS

5 Shaft Style

CARBON CONTROLS WITH SWITCH 29c EACH 4 FOR \$1.00

Single carbon controls with switch for eadle and TV replacement at less than factory cast, REFER TO CONTROLS ABOVE FOR SHAFT STYLE

\$POS-2 1 megahm SPST SPD 1-5/8"

10 ASSORTED DUAL CONTROLS less SWITCH. Kit C1....\$2.59 10 Assorted dual controls Shaft length 5/8" to 2" long. Dual 350K, 750K, 1 Meg and 5 Meg.

10 ASST. CONCENTRIC CONTROLS less SWITCH, Kit C2.....\$2,59 Shaft length 1/2 to 2" long. Many combinations of real stance values IK and 500K, and many other values

TRANSISTOR VOLUME CONTROLS SPST Switch



Model 25-775 - 5,000 ahm Control Model 25-776 - 10,000 ahm Control These controls are designed as replacements in the majority of imported transistor radios, Exact mountages, switch and remistance for small printed circuit sets. Overall dimensions: 3/8" diameter x 1/2" deep.

Comes complete with 15/16" knob. SPST SWITCH ATTACHED

27140410-1 49¢

250000 ohm control audio taper 7/8 in dia. 3/16 shaft is 4 1/2 in long. 3/8 in. threaded mounting stud

PG-24 Pressure Gauge



Light weight and occurate pressure gauge. Place gauge as terreble, rest stylus as broad end of eauge and elece counter weight as clander and to obtain believe. Read stylus pressure directly to grame. Indirect ally haved. Cat. PG=24. 89C

> 10 T.V. CONTROLS \$1.95

T.V. Concentric controls as used in many receivers. Dual controls with separate shafts for each control. About 30% of these controls have switches. Many combinations of values and shaft lengths. Stock No.

10 HI-FI CONTROLS \$1.95

Dual Controls on common shaft, For Hi-Fi-Stereos. Not more than four of any size and resistance. All Controls are less switch. Values range from 100,000 ohm to 3 egs. Shaft lengths range from 1/2" 2-3/4" tong. Stk. No. HF 10

10 HI-FI CONTROLS \$1.95

Concentris Controls for HiFi
Stereo Dual Controls with Dual
shafts, About 25% of these controls
have switches attached, Values
range from 100K to 5 Meg. Shaft
lengths range from 1/2" to 3" long.
Stock No. CCHF10

100 RADIO & TV \$6.95 CONTROLS

Kit contains 25 or more controls with switches, these alone are worth the price of this kit

the price of this At-100 Radio & TV Controls of many types. Single and dual shafts. Also concentric shafts. Not over 5 of any one kind. Resistance value ranges from 5,000 ohms to 5 meg. Stock No.CMX-100, Price\$6.95

KIT OF 100 TAB MOUNTING CONTROLS.

This kit was made up with the servicemen in mind. As most of these controls are of the latest production for Motorola, Admiral, and Magnovox

STOCK NO. PRICE 5 ZO-10T

100 tab mounting Controls as used in the latest production of T.V. and other equipment.

Control shafts are 3/16" in dia. & 1/4". The shaft length vory from 1/4 to 5" long. Resistances are from 5000 ohms to 5 meg-ohms.

STOCK NO.ZO -10T

TEST EQUIPMENT CONTINUOUSLY VARIABLE 500 WATT TRANSFORMER



Specifications Cot. No. VC-6 Output is variable 0-150V @ 5 Amp. Input 115 V. 60 Cps. \$ 19

Shipping Weight 12 lbs. (Not Mailable) Continuously variable line tendadomer in meta-cabinet with 150 volt AC meter, on and off awif-ch, Juse and pilet tight, two outlets on ricer o cobines. A highly efficient mamual operated vol-age regulator furnishing adjustable outlet to the from AC line. Current returns apply a welf ful "args of outlet voltages. Net Mail shirt. Ho., "Col-

SERVICE BENCH D.C. POWER SUPPLY



DELIVERS 6, 9 AND 12 VOLTS DC IDEAL FOR TESTING TRANSISTORIZED

EQUIPMENT, Radios, Recorders Erc. Shipping weight 5 lbs.

TELEPHONE AMPLIFIER TALK AND LISTEN



Place the phone over the speaker cradl Both parties voices are amplified through the extension speaker. Control adjusts incoming voice volume for group monitoring. Ivory only . Operates on four IV-volt pentite cells. Less batteries.

Cot. No. 868

Sale Price No. 45-739



Caired delune continuously variable line transformer. Newly styled metal cabinet with easy to read fullview meter for accurate readings and adjustments. Large easy grip type knob.

COLOR YOKE

For Motorola and others.

92De. deflection rectangle tubes

23 mh. Vert.

s O 95

Price

s **O** 95

Price

THESE COLOR FLYBACKS ARE COMMONLY USED IN MANY COLOR TV SETS. REFER TO YOUR EOUIP

95

ADMIRAL

ADMIR AL

Used in chassis TK 10-2A. 3K 10-1A 17K 10-1A/thru/1D

ADMIRAL

MENT GUIDE FOR CONVERSION.

WILL REPLACE MOST OF THE YOKES NEEDED FOR REPAIRS For 19-23-25 inch Color tubes



80-79-4L

Price

\$10.95

13,4 mh, Horiz,

21 mh. Vert.

Fits all 19,23 & 25" rectangle
Fits all new 19, 23 & 25" rectangle
Fits all new 19, 23 & 25" rectangle
color picture tubes. Exact replacement for Merit- MDF-145C, Stancor
DY-95AC., Triad- YC312-2 and
Thordarson Y-109. THIS YOKE 18
USEDBY MOST OF THE MAJOR
MANUFACTURERS OF COLOR SETS
List Pncs 358 95. Net Price \$34.95
Shipping weight 4 lbs.

Shipping weight 4 lbs.

80-79-4L

\$10.95

#### MAGNAVOX COLOR YOKE ome construction as the above picture

Simular to THORDARSON No. Y110 90 de. 11.8 mh. Horiz. 20 mh. Vert

Used in the following sets. Chassis no's are.

T 911, 01 thru 12. U 911, 01 thru 12 U 914, 01, 02, 03 U 915, 01 thru 04 T 919, 01 thru 09. U 919, 01 thru 09 T 920, 01 thru 14 U 920, 01 thru 14

361290-102

\$8.95

## MOTOROLA COLOR YOKE



Similar to stancore DY 97 AC MOTOROLA FOR 23 and 25" CTR

-PRICE \$8.95 24D68592B01-

MINIATURE POINTER KNOB

70¢

Dia, 1 V 16<sup>10</sup>, 3/8" high. With set screw to fit W' shaft.
Btock No. 1509. Black .00
Stock Np. 150W, White .00

## DEFLECTION YOKES



90, and 114 De° YOKES

All \$2,95 yokes 4 for \$10,00 All \$3,95 yokes 4 for \$14.50

ANGLE	NORIZ. VERT.	THORDARSON BY	STOCK PRICE
90 DE. 1 90 DE. 2 90 DE. 2 90 DE. 2 90 DE. 92 DE. 9		Y16 Y44 LY16 DUMONT Y60 EMERSON Y83 MAGHAVOX	Y 1943 \$2.95 Y 2041 \$2.95 Y 2103 \$2.95 2013861 \$2.95 708381 \$2.95 360980-1 \$2.95 490V 008H04 \$3.95

14 DE: 1910 MH 44.0 MH. Y-118 GENERAL ELECTRIC 29C220594-1 \$3.95

## COLOR YOKE

For Westinghouse and others



90 de. deflection. 10 mh. Horiz., 35 mh. Vert. Size: 41/4" dia. 8. 3" deep

COLOR YOKES

Stock No. 490V030D01 10 95

List value \$50.00 Regular net \$30.00

Stock No. 94-D304-8 COLOR YOKE

12 mh. Horiz.

Stock No.

24D67822A03

ADMIRAL Equiv. to THORDARSON-Y-109 STANCORE DY-93AC 90 De., 21 mh Vert., 13 mh Horiz. 90 De., 21 mh Vert., USED IN ADMIRAL, PMFRSON, MUNTZ and RCA. T.V. SE'S

Stock No. s **O** 95

94D304-2

ADMIRAL COLOR YOKE

Equiv., to STANCORE DY-95AC THORDARSON - Y108 90 De. 12 mh. Horiz. 24.5 mh. V 90 De. 12 mh. Horiz. 24.5 mh. Vert. ADMIRAL, ZENITH AND MANY MORE

110 De. TV. FLYBACK MADE FOR OLYMPIC TY Stock No. TDT-366H

RCA FLYBACK 906147-501 Equivalent to Thordarson 240 Used in over 60

Diomater 1" a ts"

MK-1140 Stock

394

RCA Chassis See Sams Photofacts No. 553, 559, 629, 734, 768, 283s 786, 789. 1" Die.. W" deep





STOCK NO

79D140-1J 95 PRICE ALTERNATE for

STOCK NO

79D140/1

79 D140-1 STOCK NO

> 79D146-3C **6**) 95 PRICE

K 1663-30 thru 35 1K 1673-16/20/22/24 2K 1663-29., 3K 1673-11/14/26

STOCK NO EMERSON 738222

1095 Price

Replaces many sets. Airline, Coronado, Emerson Curtise-Mather and allWELL-GARDINER

> STOCK NO 32-10079-1 95

PHILCO




SOLID ALUMINUM KNOBS

NEW TYPE KNOB A1 - 7

10e each 10 for 90¢ 100 for \$8.00

Tapred from 11/16" to 5/8" dia 4" deep.

Stk no. MK112B, Block,.. . 39c




10 FOR 494 Cot. No. MK-123 Network Cot. No. MK-1236 Sterk Cot. No. MK-1236 Sterk Diameny 16" x % down

6739·

10 FOR \$1.50


MK-1228 Block

Cell, No MIC-125 Natur Cell No MIC-1255 Bloc Cell, No. MIC-1250 Gol



10 For \$4 50 Cat. No. MK-119 Natural Cat. No. MK-119B Black Cat. No. MK-1190 Gold





noided plastic in two izes and cotors, with W' bras inverts and sat crews. [3 dia;6:1% dia 19 8 10 for \$1.50

Black 140' White 14' Black E5'' White 14'' Stk. No. PK-10 2B. Stk. No. PK-10 2W. Stk. No. PK-10 5R. Stk. No. PK-10 5W

One piece step knob, i'd. Single groove on back sertion. deep over

10 FOR \$4.50

Cat. No. MK-121 Natural Cat. No. MK-1218 Block Cat. No. MK-121G Gold

CALIBRATED INSTRUMENT AND AMPLIFIER KNOB 290 EACH

GREY PLASTIC 1 3/8" DIAM. BRASS INSERTS 29¢ EACH 10 FOR \$2.50



15" long, with Brass Inserts, ipped with set screw, to fit 1,11 sha

Stock No. BK-1B, Black Stock No. BK-1R, Red Stock No. BK-1W, White



## TRANSFORMER KIT TO BUILD A 70 WATT RCA HIGH FIDELITY POWER AMPLIFIER

MC GEE PRICE SALE

75.00 VALUE

Stock No. RCA-K70, Includes ; each power trans-farmer, choice and output transformer with RCA 70 west diagram. Ship, et. 30 the. htcGee's sale price \$15.95

FREQUENCY IN CYCLES PER SECOND \$21.34 LIST VALUE 70 WATT OUTPUT TRANSFORMER <sup>\$</sup>7.95

Stock No. 649/27-1 estra large 7-1,7 lb, lligh Fidelity audie estpat transformer mode for our fidelity audie estpat transformer mode for our fidelity audie estpat transformer mode for our Fully shielded upraget mounting, 8-7/8" [all 8 5:3/4" 8 4"-4"so-writing held exciter \$2/4 x 3".

Equipped with loss lifesible leads. Frequency responsed is flat from 20 to 20,000 CPS. Fringery inpartance matches Paul Poll newties 802 with any output their requiring, 4500 others pitte to piete. Total number of leads 3 for the Permary of the responsery. Secondary impedance large 4-8-16-72 and 141 others [7 2 other tap is the 70 voll line [ap]. Singerd with instructions, 4-8-16-72 and 141 others [7 2 other tap is the 70 voll line [ap]. Singerd with instructions, and this output. 2CC) replacement list value \$22,34. Highest audie stock \$2.5. teles 'n nale price \$7.95, 2 for \$15.00.



§8.95 \$34.21 LIST VALUE

POWER

Pencer transformer part as, 949,331-1 mode to pawer the RC's 70 mail audio amplifier model strict2188 wear, 13-12,70c. 1-1011 shielded upright mounting, 5-1,247 tall is 45,878 in 30 million to 100 million 1-1,247 tall is 45,878 in 30 million to 100 million 1-1,247 tall is 45,878 in 30 million 1-1,247 tall is all in 3-3,46 x 4\*-Mounting hole denotes 1-2,00 million 1-1,00 million



\$20,00 LIST VALUE FILTER CHOKE

25 Worl PUSH PULL OUT PUT

push pull out put transformer 8 000 uhm PuP to 4 obst VC, Strap mountind 2-5/8 centers. Size P<sub>4</sub> n 3 n 2-7/8. Long culor coded wires

Stock No.. A5092-3. Price 53.29

TRANSFORMER

8.000 ohm to 4 ohm VC.

Price \$3.29

P-6051-3 Push-Pull

10,000 ohm to 8 ohm V.C.

Output Trons. \$1,49

CAPITOL HI-FI

No. 120030 Capital, strop mtg.
Hidris output memidemen. 10 matil,
gaste pull, 100000 ather st of home strop
1-5/8" thus extra long columnation
1-5/8" thus e

New 20 Watt Ultra Linear High Fidelity

Output Transformer, \$2.95, 2 for \$5.50.

20 WATT PUSH-PULL

AUDIO OUTPUT

7355 or 6L6

Stock No.

50W6

## GENERAL ELECTRIC HI-FI OUTPUT TRANSFORMER SALE



Price \$3.95

MATCHED \$7.50

General Liectric 20 watt Hi-Fi output transformer Extremely good quality. Rated at 30 to 20k, cps. 8000 ohms plate to plate. Matches push-pull 6V6 EL-84, 7189A or 6D 27 tubes. Output voice coil impedances are 4, 8 and 18 ohms. Shielded upright mounting with 1-7/8 x 2½/2 centers. Only 3-166 high, 2-5/8 wide and 2-7/8" thick, Insul ated leads 5" long. Shipping Wt. 3 lbs.

Schematic furnished

#### 30 volts C.T. 1 amp. 15 volts. full wove 2 amps. Sale price \$1.99

TRANSISTOR POWER TRANS.

1 IN CORE BTACK 2 3/8 IN.
MTG. CENTERS. 117 VOLT
PRI. 30 V CT SEC. AT 1
AMP OR 15 VOLTS AT 2 AMP.
FULL WAVE RECTIFIED. SHIP W FULL WAVE RECTIFIED, SHIP WT

## 21 volts c.t.500 mills L 10 1/2 volts full wave.

TRANSISTOR POWER
TRANS, 117 VOLTS CT
AT 600 MILLS, OR 10 1
VOLTS AT 1 AMP. 2 IN
X 1 8/6 × 5/6 CORE.

STOCK NO. 6588-1

21 volts 300 mills

TRANSISTON POWER TRANS. 117 VOLT PRI. SEC. 1 INL MTG. CTR. STOCK NO. B79-121

DELUXE QUALITY HI-FI 35 WATT OUTPUT Stock No. TRANSFORMER Price \$495 M3262 2 for \$9.00

Our finest High Fidelity Output Transformer made for first quality amplitier manufacturer.

Stock No. M3262. High fidelity push-pull outer put transformer. 10,000 ohms center tapped primary. Secondary tapped at 4, 8 & 16 ohms. Fully shielded upright mounting. 2 X 3/4" mounting centers. Size: 3" high, 7/4" wide & 3/4" deep. Matches 6V6 and many other types of power tubes. All leads are colored coded and 6" long. SHIPPING WT. 5 pounds.

## OUTPUT TRANSFORMER

for 60 to 70 WATT POWER AMPLIFIER

Stock No. \$6.95 s13.50 710-2052-202 MAKE YOUR OWN HIGH POWERED

GUITAR, OR SOUND AMPLIFIER

Fully cased upright type. Push-pull 5000 ohm primary center tapped.
Secondary: Com., 4, and 16 ohm VC.
Secondary: Com., 25 volt and 70.7 V. lines Primary leads are 4" long.
Secondary are 10" long. Shipping Wt. 7 lbs.
3-7/8" High, 3\%" Wide and 4" Deep.

Mounting centers 21/2 X 21/4

25 WATT PUSH-PULL 6L6 AUDIO OUTPUT

25 watt push-pull 6L 6 output transformer for sudio amplifier. 3-1/8" tall. Mounting centers 1½" x 2". Impedance 6500 ohms plate to plate. Voice coil windings are 4, 8, 16 ohms 70.7 voit and 200 ohm line. Regular \$12.50 list value. MCGEE SALE PRICE... \$5.95, Two for \$10.00

#### SAVE ON ORIGINAL EQUIPMENT-OUTPUTS CHOKES-VERTICALS

RADIO TV FILTER CHOKES 160-72, 1.8 henry, lot me, /2 and strop mounting take, 2-t3/16" mtg, centers. Sale price, 89¢ oc. C200-130, 1.1 henry, 200 ms, 130 ehm strap mig choke, 2-1 /16" mtg, caneers, Sele price, 79g each K128G68-2, I henry, 200 Mo., 50 ehm, strap mtg. choke, 1-3 8" mtg. centers, Sale price, eoch 70: No. 502528, 7 henry, 53 Mo. 200 ehm, strap mtg. choke, 1-1/2" ntg. centers, Sale Price, eoch 49g choke, 1472 hig. centers, 30 ehm, strap mig. choke, 2-3/8" mig. centers, Sale price, each 99¢ 74A12, 8,5 henry, 225 Ma., 65 ehm, strap mrg. choke, 3-5/8" mrg. centers, Sale price, \$1.19

80-15-6, ib henry, 250 Mai, 35 ehm, strap mtg. choka, 2-3/8" mtg. centers, Sole price, each 79e 258734495, 4 honry, 375 Me., 25 ohm, strap mtg. choke, 3-1/8" mtg. centers, Sale price, each 99e

## CHOKES 79c and up

1 henry 200mill 79c Henry 200 Ma - Stock No. 568117, Strap nting 2-1/16" mounting centers. 1.1 henry, ohm of 200 Ma. A small high everent TV. e. Stock No. 568117 79g each - 2 for \$1.50

TELEVISION



## AUDIO OUTPUTS

5-Wort single plate to V.C. Output transformers for T.V. replacement.

TAO-4 TAO-5 TAO-6	3000 4000 5000 6000	TO TO TO	3.2 V.C. 3.2 V.C. 3.2 V.C. 3.2 V.C.	89¢ 89¢ 89¢
TAO-7 TAO-8	7000	TO TO	3.2 V.C. 3.2 V.C.	89 € 89 €

49c OUTPUT TRANS. 10 FOR \$4.50 afrap mounting audie output transformers to be other mounted on the speaker or radio chassis injulie vibbe output plates to 3.2 ohm vedec actil.

	at a time and save.		
Number	Description	Eoch	10 for
TO-2	2000 ahm to 3.2 v.c.	.49	\$4,50
TO-2A	2500 ohm to 3.2 v.c.	.49	4.50
AC-OT	3500 ehm to 3,2 v.c.	.49	4.50
TO-4	4000 shm to 3.2 v.c.	.49	4.50
TOWA	4500 ahm to 3,2 v.c.	.49	4.50
TO-S	\$000 ohm to 3,2 v.c.	.49	4.50
10-6	6000 ohm to 3.2 v.c.	-49	4.50
10-6	8000 ohm to 3.2 v.e.	.49	4.50
TO-10	10,000 ohm to 3.2 v.c.	.49	4.50

#### AUDIO OUTPUTS



PUSH-PULL

# SMALL SOCS OUTPUT TRANSFORMER JOBBER 49C EACH

Social imported 2000 ohm output for 50C5 50L6, 35C5 output tubes. Jobber boxed. Very good quality construction. Matches 3,2 ohm speaker voice coil.

Stock No. TNO-50

Not 49e

#### OUTPUT TRANSFORMER Stock No. CAL 6V6

49¢ ... 10 For

d Output Transformer adaptable to T.V.

Primary: 5007 Ohm for single lute. Secondary: \$ 2 min Voice Cost

FOR 6V6 PLATE 89C TO 3.2 V.C. Each

Stock No. 345,151-17, 8 mail-size, single plate to worke coil output transformer, 2 Mg ohm plate improve coil output transformer, 2 Mg ohm plate improved to 1,2 thm voice coil. Nutlable for many applications, TV. Radio and Phono they. Many mounting type, 32c 1-7/2" tall, 2-1/2" tall, 2-1/2"



RCA Single 10.000 ohm plote t c 8 ohm V.C. OUTPUT

TRANS FORMER

TRANSFURMER

16 26 28 - 2 10 wait single lube output

transformer for HL-F1 Stereo, T.V., and Radio Strap mounting 2% mounting centers

Size 2, long, 2 high, 1% usd-Stock No. 962828-7

With this transformer you can make your own 45 ohm Speaker.

Convert any 8 ohm VC speaker to 45 ohms, for intercom system.





SINGLE or PUSH-PULL 2 to 32 ohm Voice Cail 2,000 to 14,000 ohm Plate

Description 6W14 4 wort universal output \$ 1.89 \$1.79

6W15 8 watt universal autput \$1,99 \$1.89



## **10 OUTPUTS**

Price

14.95

2 For 59.00 20 watt push-pull 5000 ohm, center

ASSORTED

FROM 4 TO 15 WATT SIZES 2000 to 6606 ohms, 3.2 ohm V.C.

ansformers. You net 10 exported transformers. Some coil, some are single plate to voice coil, 2000 ohers conformers included. Buy this deal and seve. A ter- 27, 10 outputs only \$3,95



Stock No. 50WI Price

## SAVE UP TO 75 PERCENT ON TV POWER TRANSFORMERS

## TRANSFORMERS FOR

SOLID-STATE POWER SUPPLY



## TRANSFORMER

FOR PILAMENT AND OTHER USES

SOK 2

189

Primoty 117 Volt AC e0CPS " H. Sec. 2/2 VAC 2/2 AMP. Strap Sitg. 2-3/8" Mrg. Centers. Ship, Wt. 15 (b)



## TRANSFORMER

FOR FILAMENT AND OTHER USES

Stock No. LT-230 X

99¢ Primary 117 Vale AC 60CPS 6.3 VAC. 1 AMP. Steep Mrs. 3-2/8" Mrs. Centers. Ship. Wit 1-10.



## TRANSFORMER

For FIL AMENT and other uses. Stock no. CENTER TAP

169 7169

Primary 117 Vols AC 60CPS 6.3 VAC. 1.5 AMPS.
Strap 3Nd. 2-3/8" Mac Centers.
Ship. We 1. th.



## TRANSFORMER

FOR TRANSISTOR POWER SUPPLY 12.6 VOLT CENTER TAP Stock No. 229 229

Primary 117 Volt AC 60CPS 6.3 - 0 - 6.3 VAC (1 AMP. Strep Sitz. 2-3/8" Sitg. Centers. Ship, Wt. 1, 15,



#### TRANSFORMER FOR TRANSISTOR

POWER SUPPLY 12 VOLT, CENTER TAP Stock No. \$249

Primary 117 VAC., 50 CPS.

6.5 -0-6.5 VAC.

at 11/2 Amps Ship Wt. 1/2 1h. Strap Mtg. 2 3/8 Mtg. centers.



## TRANSFORMER FOR TRANSISTOR

POWER SUPPLY 20 VOLT CENTER TAP Stock. No. 269

Primary 117 Valt AC 60CPS 10-0-10 VAC 1½ AMPS. Strep Mtg. 2-7/8" Mtg. Centers. Ship. Wt. 1 16.



#### TRANSFORMER

FOR TRANSISTOR 24 Voit, center tap

Stock No \$249 7173

117 VAC primary 2 1/8 Deep Fully shielded 12-0-12 VAC. 1 AMPS.

Strap mtg. J" core

Sho Wt. 1 lb.



TRANSFORMER FOR TRANSTIOR POWER SUPPLY Stock No.

\$269 7171

IN HEGH IN LONG 24 V. AC at 11/2 Amps. IN DEEP IN MOUNTING CENTERS. 1 US.



## TRANSFORMER

99¢ AT12A1005

Heavy Duty Appliance And Many Other Usks Pri. 13 VAC, no CPS Secondary 25 VAC . As

Shipping Weight 1 lb.

TRANSFORMER \$249 2

Primery 117 VAC., 50, 00, CPS. 14-7-11 VAC. 1 Ang. 10 VAC. 15 MA. 6,3 VAC. 1 Ang. 2 1 L 10 D 2 1L lo D Supping Weight 3 lbs, tipright mounting 1 7 8X2', m unting centers



## TRANSFORMER

FOR TRANSITOR POWER SUPPLY
35 VOLT CENTER TAP \$295 1461028-5



17%-0 = (7% VAC 1% Amore.

317 VAC 60 CPs.

Shipping Weight 3 lbs., Hyncht me, King 1 5/8% Wappunting centers.



## TRANSFORMER

\$295 1461174-1

117 VAC 60 CPS. 171-0-171 VAC By Ampa

FLUSH MOUNTING 1 1 X21 CENTERS.



## HALF WAVE POWER TRANSFORMER


Stock No. 95-2110

\$395 Primary 117 Volt AC 60 CPS 120 VAC 250 Mo-

HALF WAVE POWER TRANSFORMER Designed for holf wave or bridge circuits In Preamps. Radios. Intercom's and Small Amplifiars.

Trimery | 13 Volts AC. | 150 Me. | 150 Ne. |

Stock No. 55-95





## HEAVY DUTY HALF WAVE POWER TRANSFORMER Recommented for use with Sizicon Top Hot Rectifiers in voltage doubler

Price \$4.95 STOCK NO. 55-90



## TRANSFORMER

\$3.95 TR 7-4

TRANSFORMER

Pri. 117 VAC., 60 CPS.

Primary 117 VAC, 60 CPS. 175 VAC. 1.D MA 6.2 VAC. 1.7 Amps. 6.3 VAC. 2.7 Appl.



Primary 117 VAC 60 CPS

195 VAC 125 Mm. 24 VAC .6 Amps. S.B VAC. 2 Amps. 5.J VAC. 5.5 Amps.



## TRANSFORMER

TR 12-18

Primin 117 VAC. 10 CPS. 80-0+10 VAC. 259 Mis. 6:3 VAC - € ATION.

Shipping Weight 3 this

Flush Mag. 2 12 IoX3 7 Io Mts. Centeral



## JRANSFORMER

\$2.95

70

70

70

50

0

SE

PH., 117 VAC., 60 CPS. 675-1-175 VAC. 50 Mil. 5.3 VAC. 10 Amps 6/2 VAC. 5.1 Amps

Stupping weight 3 lbs. Plat white. 2X2



## RANSFORMER

\$3.95 TR 7-6-1

UPRIGHT Ph. 117 VAC. .-4 CPS. 175-0-178 VAC #5 am. Thous 42 VAC IL I VAC &S AMPA



Per HT VAC. 10 CHS. | 221-0-281 VAC | DO MA. | | 24 VAC | 000 Mm. | 50 VAC | 2 ATH-| 0.3 VAC | 4 Angl.



## Stock No. 25C61641 POWER TRANSFORMER

POWER 1 DE TYPE FLUSH TYPE MOUNT. enters 21 X 2 M Primary 117 V.AC. 60 Cps. 500 V. Ct. at 75 Ma. 6.3 V. Ct. at 4 Amps. 6.3 V. at 2 Amps.

Size 3N., 33 sw., 24, D., Standard color code Shipping weight 3 lbs. Steck No. 25C61641 Price \$3.95

## Power Transformer



0

SE

350-0-350 VAC 70 MA. 6.3 VAC 2/2 AMP. 3" high, 2-7/8" long, 24" wide, 2"x 2" stounting Centers.

B 130-1 \$ 2. 95

#### WHEN ORDERING PLEASE GIVE STOCK NO. AND PAGE NO.

PM-90 Stoncor 90 MA. Flush mtg. \$3.95 \$ solts at 2 arros. 6.3 volts at 3.5 award 2-1/8"x 3-2"x 3-7/8". 2-5/8"x 3'4" n.tg. centers. Sale price; \$3.95, 2 for \$7.50.



2 2

70

## POWER TRANSFORMER

117 Voit primary. Power transformer 350-0-130 V.AC. 150 Ms. 5.0 V.AC. 3 Amps. 6.3 V.AC. 4 Amps.

Upright mounting standar Mountang cunters 24 X 2½ Size 3541-3 1/8W-3½D. Shipping wt.,7 10a. standard color code

Stock No. TP-0100 Price \$5.95

## **Power Transformers**





600

70

SE 90 MA. RCA Power Transformer, \$1,99 Stack No. 973861, RCA 98 ms. power transformer 740 volts C.T. 5 volts at 2 amps. 6,3 volts at

## SONALERT Audible signal device



SC-628. 2900cps., 6-28 VDC.

When the lea kettle sounds off, you know it. But the Sonalert electronic audible signal is even louder, in fact, it blasts out a penetrating 80 db with 14 milliamps of current.

And its solid-state design is compact enough to go anywhere . . . 1 1/5 " long, 1 % ounces light. production machines, computers, appliances, alarm systems. Even as a reminder on cars.

There are models for just about any use; 6 to 250 volts, ac and dc; -20 to 65°C standard wider range available; fixed temperature . pulsating or warbling tone.



Completely wired, with transistors. Will serve as a subminiature phono amp, etc. Includes leads for input, speaker, volume control/switch

## AN EXPERMINTERS KIT of 10 PORTABLE TYPE TRANSISTOR RADIO



STOCK NO. 10-PTTR \$4.95

3 SMALL CHASSIS



THIS KIT IS FOR EXPERMINTERS, SCHOOL PROJECTS, REPAIR PARTS

LL OF THE CHASSIS MAY NOT BE COMPLETE AS SOME MAY HAVE THE VOLUME CONTROL IND THE CONDENSER GANG MISSING . KNOSS AND SPEAKER ARE NOT MURNISHED.

AS REPAIR PARTS; PLENTY OF IF'S, INPUT & OUTPUT AUDIO TRANSFORMERS. AND TRANSFORDED ONE TO FIRESE CHASS IS SHOULD WORK WITH OUT TOO MUCH REPAIR.

I WATT TRANSISTOR AMPLIFIER ONLY 2000 TO SELL McGEE STS12 \$ 1.95 SPECIAL





## SAVE UP TO 75 PERCENT ON TV POWER TRANSFORMERS

Stock Number	Plate S	LA XDC	Besti	A.	Palt &	il. Mounting	Mtg. Type	H. Dimensione D.	Shpe.	Net Price
95-1242 1	320-0-320	150	5.0	1 2	5.0 2		U	4%" x 3%" x 4-8/16	11 lbs.	58,95
22E79	165-9-185 309-0-309 185-0-185	92 160 90	5.0	3			F	450° x 336° x 41/2°	13 1ba.	\$7.95
10000572	280-0-280	280	5.0	3	6.3 3	3X 3-3/8	P	4-1/6 x 3% x 4-5/8	\$1 bx.	\$ 6.95
PC 1098	380-0-380 175-0-175	195	3.0	3	6.3 ¥	3", # 3%",		4" a 35" a 95"	10 Ibe.	\$7.93
32-8276	355-D-353 220-0-220	200	5.0	3	6.3	0 3-1/8m3%	is la p	5-1/8" = 3%" x 4%"	12 lbs.	\$6.93
32-8214 D300069G2	360-0-360 225-0-225	200 250	5.0 5.0	3	5.8 8 6.3 2	3-3/8×3½° 3½°° x4-3/°		4-8/6x312x3-7/612 51/41x 41/414 41/41	9 lbs. 13 lbs.	\$5.95 \$7 <sub>4</sub> 93
25D740084G PC 10148	260-0-260 300-0-300 180-0-180	273 273 75	\$.0 \$.0	3 2	6.3 10 6.3 12		FRR	5½1's 3%1's 4-5/81' 4-5/81's 3%1's 4½1'	12 lbs. 11 lbs.	\$7.95
22E86	26 5-0-265	290	5.0	6	6.3 3.6 6.3 11.5		FRE	5%1'x 3%1'x 4551	11 lbs.	\$7.95
-	NOTE: ALL	PRIMA	RIES	ARE	17 VOLTS	. OD CYCLE A	c.	256" x 2-5/8" x 256"	2100	\$2.99
B130-1 972861	350-0-350 370-0-370 18.0	70 90 150	5.0	2	6.3 ct 2	3 1-7/8" x 2"x 2-5/8		3" x 2"/" x 2%" 3-1/8" x 2%" x 2%"	5 lbs.	\$1.95
PH-90 A7297 80B\$9-1	350-0-350 325-0-325 290-0-290	90 90 115	5.0 5.0 5.0	2 2 2	5.3 3¼ 12.6ct 3 6.3 ct 2	2"3 x 2\/2"1 2-7/8x3"1	" F	3-2/8x3-1/4x3\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	6 1bs. 5 1bs. 8 lbs.	\$3.95 \$5.49 \$4.49
TP0100	1mp 115 V 350-0-350 315-0-315	150	5.0	3	6.3 1.4 6.3 4 6.3 3	255" x 215" 210" x 3"	U	3%" x 3-1/8 x 3\%" 3\%" x 2-7/8" x 4-1/8"	7 lbs. 9 lbs.	85.95 \$6.95
949231-1	750-0-750 300-0-300	90	5.0	3	6.3 5.1	254" x 255	· · · ·	59/12 4-3/01 x 511 39/12 2-7/81239/1	15 lbs. 4 lbs.	\$8.95
50K8 50K7	6.3-0-6.3	Ida win				2-3/8 2-5/16	8	1-5/8×1-7/8**×1-5/8** 2** x 2½** x 2-7/8	% lbs.	\$1.89
Half v	wave and Ble	ment Te	enelon	mere	-				1	2
410V023H01	123	SO		F	24.0 1	15m 2-1/8	· F	2-5/81-12-8/10121/1"	2 lbs.	\$3.49
55-95 66907/3	125	130			6.3 3.1		0 "	3 x 21/4" x 3/4" 4-3/16" x3/4" x4-3/8"	5 lbs.	\$3.49
	3.6	40		1						1

PRICEO FROM \$5.95











s best offenns of a COLOR replacement wer Transformer for T.V. This transformer for T.V. This transformer like Zenikh RCA, GE andmany others. Also this maformer is ideal for Amplituse power supplies ing Sition Rectifiers in voltage doubler cre-



Stack No. Y 127J387

\$995

2 For \$19.50

Primary 1281 125 VAC, 60 CPS. Secondary 155 VAC, 430 VtA. 6.3 VAC, 2.7MIPS. 6.3 VAC, 15.5 AMPS. Upright 1/8 H 5/0 D Supping Weight 12 lbs.
Incight mounting 3X3's mounting centers.



695 SALE \$ PRICE

Stock No. 32-8376

350-0-350 VAC - 200 Mg. 220-0-220 VAC - 90 Mg. 5.0 VAC 2 Amp. 5.0 VAC 3 AMP 6.3 VAC 10 Amp. 146b Mtg. Centers 3-1/8" x 3(.\*\*



TRANSFORMER TR 13-3-2 \$5.95

1-3/8\*\*#1-11/16\*\*#1-5/16\*\* 1-5/8#1-7/8#1-5/8 3%\*\*#3%\*\*#3%\*\*

Pris 117 Volta AC 60 CPS

400-0-400 VAC 175 Me. 56 VAC 140 Me. 5.0 VAC 2 Ampa.

Shipping Weight, 7 Lbs. Flush mounting 2% X 3-1/8 Mounting centers.



11/11

TRANSFORMER

Stock No. TR 13-3-4 \$6.95 Flush

Pri. 117 Volt AC to Che 43)-0-430 VAC 175 MM 10-0-60 VAC 141 MM 5.2 VAC 2 Amps.

Weight 8 r. bs. unting centers unting centers



TRANSFORMER

POWER DESIGNED FOR SILICON RECTIFIERS. \$6.95 TR 13-8

PR. 117 VAC 60 CPS. 360 - 260 VAC 150 Me 35 - 35 VAC 370 Me

Simpling Weight & 1, bs Firsh mounting., 256 X 31 Mounting cente



POWER TRANSFORMER

TYPE FRR

SPECIAL 795 Stock No XCOT-1

Primary tapped at 110V, 115V and 120V 60 cycle

odarys, 700 V - Ct at 700 Mills 5 voit se, 6,3 Voir 10 amps. od Power Transformer and Lab, trans-

### BARGAIN BONUS! 24 VOLT HONEYWELL TRANSFORMER

Stock No. AT-1241005 79c WHILE THEY LAST!



TV TRANSFORMER Stock No. 6.95 117 Volt AC Primary

280-0-280 VAC 280 Ma. S. 7 5.0 VAC 3 Amp 4-11/8 m 6.3 VAC 3 Amp 1-1/8 m 6.3 VAC 3 Amp 12 Amp 3 Amp. 12 Amp.


nting aktouring Centers 3 h 3-5/8"
Color Coded, Shipping Wt. 8 Pounds

CRYSTAL MIKE UNIT

510CK NO 99¢ REDUCED FROM \$1.49

CRYSTAL MICROPHONE REPLACEMENT CARTRIOGE

IMPEDANCE 99¢



STOCK NO. 894

PRICE 49¢

FM DIPOLE ANTENNA

Stock No. 892 72" LONG Flexable folded dipole entenna for FM or TV Has tips on end of wires for easy attachment Price \$1.19

SOLD WITHOUT FACES

FOR PARTS ONLY



GIVE AWAY PRICES ON REPLACEMENT MIKE ELEMENTS DYNAMIC MICROPHONE ELEMENTS WITH HI IMPEDENCE TRANS.

cartridge High Impedance, extra sec lin, MC-10 Parlect for canceled location.



DIA-25 53.85 DM-15 52.85 DM-35 72.85 WORL \$4.85







NOW \$1.99 NOW \$1.99 NOW \$2.99 NOW \$2.99

TRANSFORMER FOR TRANSISTOR

95-2174 \$395 Primory 117 Volt AC 60 CPS 30-0-30 VAC 1 AMP.

ng. .. 1%<sup>10</sup> #2\*\* Mounting Geni en. g Weight 25; 1bs.

GLO-BAR RESISTOR SAVE 50% OR MORE

119.8 Ohm of 25° C Stock No. 23A-200 69\*\*

40.9 Ohm of 50° C 6.32 Ohmat 104.4° C Similar to Workman FRT-2

10 For \$6.50 ZILICON

400 P.I.V. AMP. Over \$1.00 Value

SILVER LEADS 490 Stock No. SR-3A

These can be used in Bridge Circults to make much higher wattage without use of heat sink

50 ARMY-NAVY QUALITY IN-34A DIODES

Stock Na. 50 \$1.99 50-1N34A FOR

OW IMPEDANCE RECORDING MIKE Equiped with GERMAN plug that can



DYNAMIC MICROPHONE DUAL IMPEDANCE 50,000 ohms High

50 ohms Low THOUSANOS SOLO FOR \$9.95

Cat. No. DM-16HL



BUY A PAIR FOR STEREO Improve quality of your recordings Freq. Response: 60 - 9,000

Impedance: 50K ohm

2 for \$7.50 Cat. No. DM-9


With 2 Brushes

SHOE POLISHER MODEL 56517 399 \$12.50 2 FOR \$7.50 etail Value

Charcoal grey plastic shoe polisher with 2 rotary polishing brushes. On-Off (ingertip switch, push-button brush ejector. 6 amp, 115 VAC. Shipping Weight 3 lbs...\$3.99

## Sockets and Connectors for Varied Applications

















XL	R-	3-	31	l



Contacts Not 1-24"

MICROPHONE CONNECTORS-1, 2, 3, 4 CONTACT

Description

No.	Description	Not.
2501F	Female, 1-contact, coup-	40
2501 M	Male, I-contact. (Not	.35
2591 MP	Male panel conn. (Fig.	.36
	Closed circuit male panel connector (Not Ilius.)	.45
25Y	Plus adapter (Fig. H) 2 male to 1 female (Fig. C)	1.38
2501FT	Dbl. female connects 2 cables to male (Fig. D)	.96
2501 MT	Dbl. male connects 2 cables to female, (Fig. C)	.96

XLR-3-31 XLR-3-32 XLR-3-32 XLR-3-32 XLR-3-31 XLR

Cannon	1	/ Net Each
No.	Description	1-9 120-49
		671.57
	Receptacle*	1.461.36
	Receptaring	2.352.25
	Receptacles Receptacles	1.23 1.03

Cannon		Net	Each
No.	Description	1.9	20-49
XLR-3-14N	Receptacles	2.48	2.28
XLR-3-15	Receptacles		3.6
XLR-3-11	Recentacies	2.35	2.1
XLR-3-32	Recentacle*	1.33	1.22

## MICROPHONE CONNECTORS

#### PRESSURE TYPE



		- 100	41151 0 2112 1 2			
Amphenal No.	Figure	Description	Net 1-24"			
75-PC1M	E	Non-Short	48			
75-CL-PC1M	D	Closed Circuit	74			
75-MC1P	F	Phone Flug Ad.	.58			
75-CCC1		Cap and Chain	47			
75-MC15	G	Mike Switch	2.00			
75-MC1F-A	C	Angle Plug	1.49			
75-MC1F	Å	Straight Plug	7 Q			
75-MC1M	B	Cable Jack	50			
75-1	1	Female Connector	.45			
75-2	1	Male Connector	.33			
75-3		Chassis Connector	55			

Miniature: 1:14° ig., female: 1" ig., male: 14" ig. chassis.

#### UHF 83 SERIES COAXIAL CONNECTORS

Amphenol Low-loss RF Connectors, Adapters and Terminations, have been especially designed for use with Caxial and Twin Coaxial and Twin Coaxial Cable similar to Amphenol RG-/U cable.



Amph.	Fig.	Description	1-5°
83-168 83-168 83-165 83-17 83-17 83-10 83-17 83-14 83-14 83-14 83-14 83-14	AHHABOGECOF	Plug for small and medium sized cable Reducing adapter for RG-59, 62, 71/U Reducing adapter for RG-58/U Plug for RG-5, 59, 62, 71/U Receptacle, mica filed insert, Hood for RG-5, 10, 11, 12, 13, 63, 65/U Hood, as above Adapter, Tee Right angle adapter Adapter, atraight Adapter, bulkhead	1.65

	"S" TYPE SOCKETS						
	Contacts	Riack Pi	1-49°	Mica-	Filled		
	1 1	78-51	21				
CHE CO	6 7 Sinali	78-56 78-575	.28				
OPER .	9 Lokial		.35	Nolo	nger		
	9 Octal* 11 Octal* 7 Min.	78-59 78-511 78-A7Pt	30	avail	able		
	9 Min.	78-A5P	.36				
*Octal style. †Mo	unis in stan						

#### REPLACEMENT SOCKETS

Consists of regular "8" type sockets assembled with retainer rings in styrily pickel plated steel mounting rings. Use these suckets to replace broken and noisy wafer types. Either black pienoide or low-loss mica-filled. Mounting plate has slotted holes to fit renters from 136" findlesies octal style.



	Black Ph			ca-Fi			
Contacts	Amphenol No.	Nut 1-49"	Amp	henol	No.	Net	1-49°
4	78-R54	29					
5	78-R55	.31					
6	78-RS6	.33					
7 Small	78-R576	35				1	
8 Octal	78-R58	.32					ilable
B Loktal	78-RS\$L	.44					
9 Octal*	78-RS9	.34	1	4		•	
1 Octal	76-RS11	.39			_		

# Maio Plug Femaie Cable Jack Femaie Chassis Receptacle Male Plug Femaie Cable Jack Femaie Chassis Receptacle Male Plug Femaie Chassis Receptacle Male Plug Femaie Chassis Receptacle Male Plug Femaie Cable Jack Femaie Cable Jack Femaie Cable Jack

"PHONE PLUGS" (FIG. A) Conventional design standard plugs with bakelite or metal handles. O.D. "19".

#### Two-Conductor

No.	Nandla*	Description	Not
45 70	214 Black 214 Red 214 Metal	Screw Terminal Screw Terminal Screw Terminal	56.60 96 78
160 178 180	1": Metal 2"4": Metal 2"4": Metal	Screw Terminal Screw Terminal For use in	1.23
_		3-cond, jack Screw Terminal	1.32

- sangin and material. \$2-piece handle with built-in cable clamp (14" cable). †MIL type l'J-636.

No.	Handle*	Description	Net
60 90 190 190A	214 Black 1 Metal 214 Metal 214 Metal	Solder Lug Solder Lug Bolder Lug Solder Lug	1 02 1 17 1 47

\*Length and material, 42-piece handle with built-in cable clamp ()(\* cable).

#### "LITTEL-PLUGS" (FIG. B)

Dual purpose sleeve terminal clamped over metal braid of shielded cables; B) Sleeve terminal can be clamped over outer insulation of 2-conductor cable (extra ing in terminal for wire connection); C) Screw terminal type has no cable clamp (one screw in each terminal). Tente or metal handles 1, "long x y." dis. Exterior metal bickel-plated.

No.	Hamphe	Description	Not
24.0		Screw Terminal	57
245		Serew Terminal	57
250		Clamp-lug Terminal	54
255		Clamp-lux Terminal	54
270		Serew Terminal	79
280		Clamp-lug Terminal	79
285		For use in 8-cond, jack	81
5-250	Black	Clamp-lug Term., .206"	5 7
5-280	Metal	Clamp-lug Term., .206"	.7 9
R-280	Metal	Clamp-lus Terminal*	.99

Inter-Conductor						
169 Red 190 Metal	Serew Terminal Clamp-lug Terminal Clamp-lug Terminal Screw Terminal Clamp-lug Terminal	81 81 1.05				

Phone plugs with handle and body of mini-mum disneter, yet it standard jacks. Revere Recorders; mates with No. 128 Offer various terminal combinations: A) "Extension Jax".

PHONO CONNECTORS						
No.	Flg.	Description	Not			
3501F 3501M 3501MC	D	Phono Jack, 2 cond. Phono plug, 2 cond. Phono plug, 2 cond. (cable clamp type)	90			
3501FP 3501FR		Phono Jax, 'A' O D, for back panel mtg. Phono Jax, '4" Q.D. for front panel mtg.	.30			
3502		Phono plug removable handle. Cable clamp. Shielded. N.I'.	.33			
3503	H	Phono ext. Jax. Re- movable hdie. Cable elamp. Sh'ided. N.P.	-42			

## SHIELDED "EXTENSION JAX"

Same O.D. M" as "Littel Plugs". For attachment to cable, Built-in cable clamp is cable support and steeve terminal. Solder terminal.

OCT (III III A. III.								
No.   Description						Not		
121	2-ennd 3-cond	TOT 1/4	dia.	phone	binds	1.14		
131	3-cond	for W	" ctia.	phone	DILLER	1.41		

#### PHONE JAX

"Littel-Jea" (Fig. A)—Notched washers hold springs and lugs; "V" bend in tip spring holds mating plug; minimum space requirements. %" hole, panels to 'd'.

	TENT JA		"SF-J	АХН	"LF-	IAX"	Sche-
5	No. 11	Not .33 .48 39	No. 21 51 51 C-51	.51 51 89	14a.	.5 7	matic

## MIP MOLDED-IN-PLATE SOCKETS



High delectric black baselite, steel mounting plate moided into soil body. Cannot come loose. Mount in 1½ hole. Two ½ holes on 1½ mounting centers, except 77-MIP70 and 77-MIP70 which mount in 1½ hole and Compact MIP1 which mount in 1½ holes on 1½ centers. Indicates octal style.

-	9	Cares octa	M OCTIVE	
5	77-M1P-4 77-M1P-5	24	77-MIP-IT	No
6 7 Large	77-MIP-6 77-MIP-7L	29	77-MIP-6T	longer
7 Small 8 Octal	77-MIP-75 77-MIP-8	-2 8 -2 5	77-MIP-75T	
Octal	77-MIP-9	2.8		aveilab

#### FLOATING OCTAL SOCKET



Live rubber grommers at into mounting holes for ribration-free operation. Black bakelite dielectric. Mounts in 1½ hole, 1½ holes on 1½ centers. Amphenol No. 77-MIP-8FK—Complete with 4 rubber grommerts, 2 mount-30 ing seriews. Net. 1-49 Amphenol No. 77-MIP-8F—Net. 1-49 Net. 1-



For cables up to 6 conductors. Polarized contacts make incorrect nas-riobs impossible. Shell length on shielded connectors 11/2.

Car dis mounting receptacies mount in the hole, with ring.						
Amphenel No.	Style	Contacts	Not 1-49*			
78-533	A	3				
78-545	A	4	22			
73-45	B	3	.1.5			
78-565 71-65	A B	6	.2 4			
91-MPM35 91-MPF35	D	3 3	.42			
91-MPW45 91-MPF45	D		.45			

## MINIATURE 7 AND 9 PIN SOCKETS









Type A—Ministure retainer eing type sockets mount in "D" shaped or round note. ), diameter.

Types B, D—Ministure 7- and 9-th sockets. 7-pin sockets mount in % hole; mounting centers 14". 9-pin sockets mount in 16" hole; mounting centers 14". Shielded sockets mount above chassis: unshielded sockets mount below.

Amphenol No. Type Contacts Meterial Not 1-49"

78-7P	A	7	Phenolic	- 28
59-409	n	9	Phenolie	.35
347-905	В	7	Phenolie	.35
\$9-406	В	9	Phenolle	.41
	SHIE	LDS WITH	SPRINGS	
5-401 5-402	C	For 7	1% high	-21 -22 -22
5-405	-6-	Vor 9	114° bleb	- 22

#### SHIELDED CABLE CONNECTOR Multi-wire cable connectors consist of "B" type sockets and "CP" type plugs in metal can shields.

Contacts	Amph.	Not Each in Lots of		Female Amph.	Net Each in Lots of	
Contacts	No.	1-49	50-249	No. 78-	1-49	50-249
4 6 6 7 amail 8 octal 9 keyed 11 keyed	PM4 PM5 PM5 PM7\$ PM8 PM9	.45 .47 .56 .40 .49	.38 .36 .40 .46 .40	PF4 PF5 PF6 PF75 PF8 PF8	.41 .43 .45 .47 .44	.34 .36 .38 .40 .37 .39



## HOT MCGEE SPECIAL ITEMS

## BUY A TUBE OPERATED S' AM/FM/FM-MPX Stereo Receiver System

634" X 16-3/8" Dial Plote

TUBE COMPLEMENT

1 - 6AQ8 - FM RF Amplifier & Converter
1 - 6BE6 - AM Converter
3 - 6BA6 - FM - AM IF Amplifiers
1 - 6AV6 - 19KC Amplifier
2 - 12AT7 - 19KC & 38KC Amp. & Audio Amp.
1 - 12AX7 - Audio Amplifier
2 - 6BC6 - Power Amplifier
Silicon Diode- Bridge Rectifier for Power

SCOOP 0 95

HIGH FIDELITY AT LOWER COST

Heavy Duty Power Transformer For Cool Operation.

Heavy Duty Output transformers

Easy To Install in Recreation Room Wolls or your own HI-FI Cobinet.

Service Manual Included Ship wt. 20 lbs.

KNOBS NOT SHOWN BUT INCLUDED

Motsushito (Ponosonic)

Stock no RUA-300

8 WATTS RMS PER CHANNEL ... SAVE OVER 50%

## SOUNDS GOOD WITH MOST ANY SPEAKERS YOU SELECT COMPLETE SYSTEM INCLUDING AM-FM TUNER...AMPLIFIER



11/2 x 11/2 x 21/2 14x31/2x51/2

Using the TA-1 and TA-2 Telephone Monitors, you can pick up both sides of all telephone conversations and record for permanent records of both incoming and outgoing calls. Completely Automatic, Use with any tape recorder. Connect at any point on your phone line. Phone operates normally. TA-1 uses 1, 9V. Battery. TA-2 uses 3 inexpensive pen cell batteries.

Subject to Local, State, and Federal Regulations Where Applicable



15 WATTS

11-TUBES

110 V. AC

MUSIC POWER

Although this Amplifier is tuned at the factory to receive channels 70 thru 83. With proper knowledge and care of tuning of high frequency tuners. This amplifier can be tune to lower channels by adjusting the space of between the turns of the coils.

## SOCKETS LOWEST PRICES




Fig. 1. LAMINATED OCTAL WAFER SOCKETS
Type Description Net 10 Lot
LS-10 Octal socket, 1-5/16" mtg. .06 .055

Fig. 2. LAMINATED MINIATURE 7 AND 9 PIN WAFER SOCKETS: Type Description Net 10 Lot 15-206 7 pin. 1" mounting .07 .065 LS-209 7 pin. 1-5/16" mtg. .08 .072 LS-214 9 pin. 1-1/8" mtg. .08 .072 LS-214 9 pin, 1-5/16" mtg. .08 .072

Fig. 3. MOLDED OCTAL SOCKETS:
Type Description Net MS-247, Octal socket, 1-5/16" mtg .08 MS-248, Octal, Mica. 1-5/16" mtg .10

Fig. 4. MINIATURE MOLDED SOCKETS: Type Description Net MS-223, 7 pin, 7/8'' mtg. .08 MS-235, 9 pin, 1-1/8'' mtg. .12



Pig. 5. TROMBONE SHIELD and bakefite socke Type Description Net 10 Lot MS-229, 7 pin, 1' mtg. .20 .18 MS-241, 9 pin, 1-1/8' mtg. .22 .20

Fig. 6. MOLDED PRINTED CIRCUIT SOCKETS
Type Description Net 10 Lot
PS-258, 7 pin socket .10 .08
PS-258, 9 pin socket .15 .12
PS-253, Octal WAFER socket .15 .12

No. VS-218, 3 prong wafer socket, fits 12 volt, 3 prong auto radio vibrator, 10 c ea., 10 for 75c.

RS-218-4, 4 prong wafer socket, fits 6 & 1 2 V. 4 prong auto radio vibrator. 10 c.es., 10 for 75c. AUTO ANTENNA CONNECTORS: Fig. 7. No. AA-697 with saddle flange. 12c ca.

Fig. g. No. AA-697B shell type .07 ea. No. MO-6, Male pin plug to fit above sockets .08





Fig 11



Fig. 10 MPC-1 2pin Socket(compactron) .55 ea. Fig. 11 NV-2879 pin Novar Socket Fig 12 MSN-5 5 pin Navistor Socket

10 pin minature Socket for 6 C9 or 17 C9 . 10 ea.

TRANSISTOR SOCKETS



## AUTO RADIO VIBRATORS STANDARD 12 VOLT 4 PRONG 10 for \$7.00 G8301 CPS

# OUR LEADER

GIANT 16-0Z. ECONOMY SIZE

MADE BY

AMERICAS NO. 1

MAKER

OF SPRAY

10 FOR \$7.50

S-100 GLOSS WHITE 5-101 FLAT WHITE S-110 GLOSS BLACK S-111 FLAT BLACK S-112 MEDIUM GRAY S-120 SILVER

5-121 GOLD S-122 COPPER

S-130 BRIGHT RED S-140 FOREST GREEN S-160 ROYAL BLUE

S-190 PERMA-CLEAR ACRYLIC S-191 PRIMER (GRAY) S-194 CLEANER & DEGREASER

## KRYLON SPRAY-ON ENAMELS AND CHEMICALS

No. 1302 Crystal-Clear Spray—Prevents pitting and rusting of antennae; reduces corona and arcing; sait-apray resistant, Dielectric strength, 400 to 800; delectric constant, 3.2 to 3.7 (1.000 cps); electrical resistance. 101° ohms/cm² 16 os. spray can. \$17 Net Each, 16 Oz. Spray Can.

SPRAY ENAMELS \$107
Weatherproof and waterproof. Excellent adhesion. Guaranteed non-clogging valve. Available in the following colors:

on-crostraf	ARIAC VARIABLE III	ttle tottownii	CUIQIB.
Krylon	Color	Krylon No.	Color
1401 1501 1502 1503 1601 1602 1603	Bright Silver Glossy White Flat White Antique Ivory Glossy Black Flat Black Machine Gray	1604 1701 1901 2003 2101 2201 2202	Light Gray Bright Gold Regal Blue Munter Green Cherry Red Bright Copper Brass

GLOWING PLUORESCENT SPRAY PAINT For use on paper, wood, cloth, glass, metal, styrofoam and some plastice. Dry in minutes, Just push the button and spray. No fusi or mess. Glows in daylight. 16 os. cans

Color Colar Lemon Yellow Cerise Green Red-Orange-633° Yellow Orange-634° Sunset Gold 3103 3102 3103

\*Made to MIL-P-21600 (AER) specifications.

16 Oz. Spray Can—Net Each,

5167



**FUSE HOLDERS** Kit of 3 Standard Fuse holders for chassis mounting. For

Stock No. 896 Price 99¢



3 AG size Fuses.

TUNER LEANER and lubricant

for COL OR -

NON-DRIFT COLOR TUNER SPRAY TUNER & CONTROL CLEANER AND LUBRICANT

McGee Color Tuner Cleaner and \$1.79
Lubricant, Non-Drift, Safe for all plastic material, Finest quality.
A very necessary item for the color TV servicenan. 60z. aprey can with fine whole no zeel extender, Net \$1.79, 2 cans for \$3.50
\$3.50

• FAST DRYING


McGEE

Stock No. WILL NOT DETUNE NO. 179
NOT HARMFUL TO PLASTICS

• NON FLAMMABLE

## GENERAL & ELECTRIC LONG LIFE NICKEL CADMIUM BATTERY SYSTEM

rechargeable




Hedel GC-3

53

"AA" Size Sallery Model OC-1

Note: The General Electote Nickel Cad-mium bettery must be charged before put-tings into use. The factory DOES NOT CHARGE them before delivery to us, Therefore this method incurse is longer battery life, G. E. Nickel batteries are sold only in gairs.



OPERATES ON AC ONLY 60 CYCLE

Right Battery for Specific Portable Needs

MODEL BC1 Charger Medel



#### PANASONIC SUPER POWERFUL LONGER LIFE BATTER. HI TOP BATTERIES

Major breakthrough in dry cell engineering and ingrediental Certified by a national testing loboratory to have more than double the useful life of ordinary batteries. Truly super-powerful, super-long losting. Actually have 3 full years of shelf life compared to usual 1-year meximum.

HIGHER PRICED - BETTER LIFE 210

21 ¢ 17 ¢ Each HT-UM-20 10 ET-UM-30 10 FOR Panite \$1.60 FOR \$2,00

\$2.00 dd by one If of the show coils are longer like than regular atteries. Designed by one of Japans largest factories, Aliverisaed in and approved by Good House-eping. RicTop batteries means Happower, Top erformance, Double the life of visandard batteries,

#### STANDARD QUALITY BATTERIES · From Fresh Stock

"C" cart UM2 36 € 2 for 70¢ 10 for1 .70 10 for1 .0

'D' Cell, Standard Flashlight Cell, No. UM-1 18¢ Each, for \$1.70

Top Quality Imports - Money Saving Prices

PANASONIC 9 VOLT "EVEREADY" 9 VOLT HI-TOP HI-TOP LONG LIFE BATTERY



No. 216 No. 006PD 54¢ eq. No. E146N 17 6 1.43 eq. S1.43 eq. NO. E146X

REPLACEMENT BATTERY HOLDERS

7

## McGEE SPECIAL BATTER'

FRESH STOCK 9 Volt BATTERY

150 EA. 10 for \$1.39

Stock No. 006-15



7 AND 8 CELL BATTERY HOLDERS

Cat No BH-7 7 Call Holder Cat No BH-8 8 Call Halder





Stock No BC-9 Price .09¢, 10 for 80¢

# These parented battery holders are made of stordy plastic material. Each holder is individually peckaged in a poly bag, suitable

mercineant bearages us 4 bost audi	Administr
for peg-rack sales.	
Na. Net F	rice Each
J70 For 4 regular pentite batteries	5.35
J71 For 2 reguler pentite batteries	
duel In -line.	.29
J72 For 3 regular penlife batterjes	.35
J73 For 4 regular ponlite batteries,	
duel in-line	.35
J74 For 6 segular penlite betteries,	40
175 For 8 regular peniire batteries	.59
J76 For 2 "C" cell betteries with	
red and black leads.	.39
J77 for 4 "C" cell batteries with	
red and black leads.	.47
J7# For • "D" cell batteries	.44
J79 For 3 "D" cell betteries	.50

**CHART-O-MATIC** INSTRUCTION GUIDE INPUT: 110 VOLTS AC MODEL CH-ACD

Our Best Selling Battery Charge Fedin Model Chi-ACD Defuse Battery Charger has ned Indicatof Light to show when peoperly changed Recharges 9 volt Transa ato fatteries, 13 volt "AA". "C" and "D" also batteries, Teet Indicator Light to check batteries as charge

Botteries at

Racharges up to 5

## PERMA-CELL INDUSTRIAL **BATTERY CHARGER**

Recharge D size Perma-cell batteries 1000 times or more

BC-48 charger \$189.50

Could mean as much as 400% return on investment yearly!

#### Features of the BC-48 charger

- Heavy-duty steel charger case Charges batteries to peak power in 14
- to 16 hours Charges 1 to 48 size 'D' Perma-ceil
- Batteries
- Individual battery compartments Automatic operation
- Operates on 110-120 voits 50/60 cycles a-c 25 watts
- Easy bench or wall mounting
- Lockable cover Charging indicator light for each battery Convenient size: 25% long x 18% wide x 4½ high
- Unique design prevents harmful reverse
- charging Permits Perma-cell batteries to be stored on charge indefinitely

## VIZ VOLI POWER ESLIPPLY



Replaces 5 cells, Made to operate most cassette recorders & players and other units using 7 1/2 volts 

## AC BATTERY CHARGER

AND FLIMINATOR

Converts Transistor Portable Radios, using 9-volt flat batteries, to AC operation. Also extends useable life of batteries, such as BL005P, Bargess 216. RCA VS312. Eveready 215 etc. Complete with line cord. neon indicator light and jumper cable. Individually boxed complete with instructions

No BCIOI.....\$2.99

A.C. ADAPTORS
HEAVY DUTY, BIG ENOUGH
FOR ALL TRANSISTOR RADIO:
AND MOST BATTERY OPERAT
ED TAPE RECORDERS.

A-C ADAPTOR Output 9-Vales DC

Precession-bask cracity like Model 18-10s above but delivers 9-cales of electronically regulated DC power Maximum load empority 200 ma. Allows use of howehold current for 9-wok radios, tensectivers and other electronic devices. Complete, with the encessary adaptor filtpr 80 use no any 9-vol to preferred equipment. Blister maked on a red card for pegboard display.

odel 18-109 - A.C Adepter 9-Vals DC Output

Net \$4.95 ea., Two for \$9.50



A-C ADAPTOR: Output 12-Voits DC

A companion unit to Modele 15-1160 and 18-109 above. Maximum load capacity 250 max For nae with 12-volt transistor radios, transcreare and other elements everyment where notise-free, regulated AC power source is needed. Complete with necessary adaptor clips for use on any 12-volt operated equipment. Blister packed on green eard for perposed display.

Model 18-112 - A-C Adaptor 12-Voit DC



A precision-built A-C Adapsor for convening 110-120 Volta AC to 6-Yolts DC liverany-stor circustry regulates the output to an exact 6-yolts for reliable, noise-free operation of 6-yolt translator radious transceivers and other efectronic devices. Mashman load capacity 200 ms. Saves the cent of batteries, provides a ready source of power shen batteries go stead. Comes complete with microcassary adaptor effps to use on any 6-yolt operated equipment. Blister-packed on a blue card for personal diaplay.

Model 18-106 - A-C Adapter: 6-Volr DC

## Manganese Dry Battery

	200	NET	F121
	Size "D", 1.5 V	.17	.30
UM-2G	Size "C", 1.5 V	.16	.30
UM-3G	Size "AA", 1.5 V	125	.25

Twice-Prolonged Service Life

ordinary Carbon-zinc ce


## Maxe "1000" Alkaline Dry Battery Up to Ten Times Longer Service Life Than

Carbon-Z	Cinc Cell	YOUR	LIST
AM-1	Size "D", 1.5 V	.55	.95
AM-2	Size "C", 1.5 V	.43	.75
AM-3	Size "AA", 1.5 V	.35	.60

200

Maxe

2000



LAMP

HOME

SHOP

OFFICE

SCHOOL

69¢ \$6.50

While they Last !

3/4" x 66 Ft. BLACK \$1.25 Value Stock No. 007

190

414

119-190 119-190 .25A 150 900 75A

115-195

CAR

CD1

COE

1A 100

115-180 300

115-190 190V

#### GENERAL ELECTRIC LAMPS NEON

190

WE CAN OBTAIN ANY PROJECTION LAMP MADE BY GENERAL ELECTRIC SEND US YOUR ORDER AND WE WILL GET IT FOR YOU. SEND THE NUMBER

CVS 115-198 900 Mad Pt

CWD 115-190 300

CKK

CKT

COL

CZA

DAR 190 100 484

DAR

DAS

DCA

DCH

DOM

DDY 115-198

DEA

750

115-190 300 Mad Pl

113-198 300 S.C. Say.

190 1900 4-Pa

113-190 500 Med PL

113-190 500 E Med 8

115-190 750 | Mad PL

790

115-120 750 4-Pm

150 alta

EDISON

CYC 119-198 300 S.C Say

130 300

119-190 500

PRICE

DFD

De sc

DFR

bar

51.6

113-120 1000 Index Bing 113-120 1000 Adds Bing (mining 4Pm

115-190 1000 Mad Pl

115-190 300 4-Pla

119-190 300 4-Pto

119-190 1900 Med Pl.

150

115-190 1000 Mag Pf

119-180 1000 Med. PE

100 1000 Mad. Pl 115-130 1000 Mad. Pl

115-190 1500 Mag. Pf. 113-190 500 S.C. Buy 190 489 Seemed

FCB special not.

BACK | 115-120 | 500 | Med. Pt. BPJ | 115-120 | 730 | Med. Pt.

PMS 119-190 500

190 4-Pm

150 4.Pm

500 4-Pm 115-150 1000 Index Ring

500 d.Pto

Longs man King

3.76

15 6.60 13 J. 16

25 3,57

13 3.96

15 3, 60

2 3.16

10 7.60

10 4.60

15 4.40

15 4,20

15 4.88

B 3.16

13 4.20

15 4.40

ts 4.60

10 4, 24

900 7.12

15 4,96

15 4.76

5.08

G-E PROJECTION LAMPS

PRICE 1

3, 48

1 7.88

85

Net Lamp Bulb Base Each (NE-2) (NE-2H) (NE-45) (NE-48) (NE-81) - C UNBSU. CANDA D.C. BAY. MIN. BAY. MIN. BAY. EDISON D.C! BA. 1.53 B2A J5A L5A R2A 10

IMPORTED PANEL LAMPS

10 for 49¢ Type 40, Imported Lamps,

15 3.96

10 4.92

25 5.00

10 5.40

23 4.5.7

25 4.76

15 4,40

15 5,40

15 3, 40

10 5.64

10

15

15

50

6. 20

5, 40

4. 22

3.04

15 |5.40|

B 11.60

15 4.04

Type 44 Imported PANEL LAMPS 10/ 494 Type 44, imported panel lamps, Stock No. 1-44, Nox of 10, 4 pc. 10 boxes, (100 lamps) for ta. 00 Type 47 Imported PANEL LAMPS 10/49 Type 47, imported pilot lamps, boxed 10 in a attractive carton, Stock No. -47, box of 10 No 47 panel lemps, 49c, 10 boxes (100 lemps) 14,00

# No. 44-524 Ivory High intensity plus cool low-voltage operation. Gives the ultimate in glare-free, concentrated white light for redding, typing, sewing and many other uses, 12½° brass-finish flexible goose neck is easily adjustable. High impact plastic bose and vented shade. 6-ft. cord, 110-120 volts, AC Built-in transformer. Uses No. 93 GE bulb.

-INTENSITY

Model 44-522

FOR \$7.50

SPECIAL SALE on

G.E. No. 47 Panel Lamps. 3 Boxes for 51.99. Stock No. GEL-47

## McGEE SERVICEMANS BARGAIN SIGHT-MASTER



Signe-Master is a precision optical instrument which enables anyone to do very close work and see it clearly. Has comfortable adjustable headband. Ground and polished prismatic lenses makes an ideal binocular magnifier for TV and Radio Technicians. Allows free use of both hands while working. Reduces harmful eyestrain. Select magnification and working distance desired. Magna 3 - Net \$4.95. Normal glass to object viewing distance is 14th. This is likely to be the best for viewing work on transistor radios. For more magnification and a closer viewing distance order No. 5 or No. 7

MOST POPULAR SERVICE BENCH LIGHTS IN U.S.A.

Fluorescent

MAGNIFIER-LAMP



**NEW - ATTRACTIVELY** 95

ALL-PURPOSE LAMP 45" ARM REACH ALL METAL CONSTRUCTION

AIR-VENTED SHADE

Incandescent



SOLID-TUBES

**PULL OUT** those troublesome vacuum tubes\*



PLUG IN the all new, all solid-state trouble-free SOLID-TUBES

米 High Voltage Rectifier Damper Diode. **Focus Rectifier** 

Add to your profits — GO SOLID STATE!
Pull out those three troublesome vacuum tubes and simply plug-in ED) all solid-state SOLID-TUBES . . . R-3A3 (or R-3AT2), R-2AV2 and R-DW4.

Install EOF SOLID-TUBES and you provide your customers with the same proven EDI technology used in our mass production of recitier modules for one of the largest manufacturers of color TV receivers.

SOLO-TUBE Type Number	Replaces Vecuum Test Type Number	
R-SA3 High Vort Rect	343, 1893, 362 TCA3, 3683, 3603, 3623, 2683, 183, 163, 183, 113	\$6.95
9-3622 High Voil Rec1	3AT2 3AW2, 38L2 38M2 38N2	
8-28YE Focus Rect	TAVZ. EVZ	\$3.49
H-8/84 Damper Drode	5DW4 6CM3, 6CL3, 58A3	\$4.49

The all new, all solid-state, EDI SOLID-TUBES insure high reliability and longer life, but down on troublesome call backs and dissatisfied customers.

help eliminate burn-outs and one potential source of X-radiation.

Order your EDI SOLID-TÜBES from your nearest parls distributor or call us collect

#### ONEIDA PERMABOND ADHESIVE

ONEIDA

\$1.99

SPACE ADE ADRESIVE - ONLIDA PERMASOND Unpelievable strength! One arou holds a ton! Saves 3 & Fixes things ordinary adhesives can't touch! For repairing 100's of electronic and hebby items! Belongs in every serviceman's cool kit! An absolute must for Pams, experimenters Stock PERMABOND

channel color music organ, It picks up bass, treble, and alto

from any music, "Talk To Me Lite. 24x10x6 \$29

2 For \$58,00 "LITE OF THE YEAR'

PRICE \$4.95

10x6x6 Stock No ANES-6

The 6" light is Anea' newest environmental light random blinking, yet gives the illusion of keeping time with music

trouble-free 24" voice activated unit THIS 10 TRANSISTOR, WALKIE-TALKIE 2- CHANNEL, SELLING AT LESS THAN IMPORT COST, \$12.95 ea., TWO for \$25.00

> TOL telmar MODEL - MA103 MODEL 10 TRANSISTOR MA103

CHANNEL SYSTEM **WALKIE-TALKIE** WITH 1 SET OF CRYSTALS FOR CHANNEL 8

2 for \$25.00

\* LEATHER CARRYING CASE

\* EARPHONE

\* 7 PEN CELLS INCLUDED

\* HEAVY METAL CASE

\* 45" TELESCOPING ANTENNA EXTRA SET OF CRYSTALS

WHEN ORDERED WITH WALKIE-TALKIE

WITH WALKIE-TALKIE

PROCESS OF THE P

#### UNIVERSAL 6V, 7½V, and 9V POSITIVE SELECTOR SWITCH ADAPTOR

FOR 6V, 7 1/2 and 9V

+ AND - POLARITY ROTATING CONNECTOR MAKES THIS AC ADAPTOR UNIVERSAL

STOCK NO



Here is an Adaptor that has all the combined features of our Models 8E69 (6 and 9 volt Adaptor) and BE75 (7.5 volt Adaptor) in one compact 2 1/4 x 1 1/4 x 1 1/2" case resulting in converting 110-120 volt AC. 50/60 Hz source to three DC pre-determined voltage outputs, as listed above.

# neida

## **DRIVE BELT and** "O" RING KIT

NEVFR BE WITHOUT A BELT **AGAIN** 

PRICE

\$19.95

Stock No. ORK-1 KIT

Produces instant "O" rings and drive belts of any standard or special size

Eliminates "down-time" caused by extended delivery time for 'specials'

Eliminates need for stocks of replacement rings and belts which deteriorate or are misplaced.

No molds or complicated vulcanizing procedures

No special skill required

CONTENTS OF THE ORK-1 KIT:



1 tube ONEIDA PERMABOND jig for controlling cutis single edge rezor blade eight foot lengths precision rubber cord stock

Only three simple steps to produce perfect "O" rinos or belts -

cut cord to correct length apply ONEIDA PERMABONO sparingly from dispenser tube to

3. join the ends and hold for one minute

Special User Net Price \$19.95 Stock no ORK-1

DELUXE SOUND

SPEAKER SYSTEMS

Response 35 to 13,500 cps, at 40 watts.

STOCK NO

DSC-48

MCGEE SALE PRICE

2 for \$58.00

Four of the best 8" Speakers ever designed for sound columes. They have designed for sound columes, they haw large 1/4° diameter, 8 ohm voice coils o.8 oz., Alnico V magnet, this allows higher power output of sound.

CAN BE CARRIED OR MOUNTED VERTICALLY OR HORIZON ALLY TO ANY SURFACE.

TO ANY SURFACE.

A solid constructed "" plywood case covered with the hardest covering known. FORMICA it is beautiful and colored a medium WALNUT. This sound colume is made to with stand rough handling, which is true of portable use. Our case is almost imposible to mar, or scratch. Size and weight are also important factors. The size is 48" long, 10" widw and 6" deep. Weighs only 27 lbs., SHIPPING WEIGHT 32 lbs.



IT'S A

\$10.00 list \$395

# 15 WATT STEREO AMPLIFIER

WITH REMOTE SPEAKER SELECTION

For the discriminating Mi-Fi enthusiast, who is also budget minded, this is the perfect amplifier. This compact unit features remote speaker selection, choice of phono or auxiliary input, separate channel valume controls, tone control, stereo-mono mode switch and stereo phone lock. The SA1500 is attractively pockaged in a simulated wood grain metal cabinet with extruded aluminum front panel.

No. SA1500



Made Switchess Remote or Main Speakers Stereo + Mano Selector Switchs Aux. - Phono

Power envolf switch

Stereo phone jack Operates on 105 - 125 Volts AC 50/60 Hz

SPECIFICATIONS:

Power Output: 15 Warts IHF Music Power at 8 ohms Frequency Responses 20 to 20,000 Hz Tone Response: Variable to ~15 db. Harmonic Distortions 3% at listening levels

Channel Separation: 40 db Hum and Noise Level: -50 db Input Sensitivity: 150 mV

Phono: (ceromic or crystal corttidge) Aux. (Tuner, Tope Dack, Microphone

PORTABLE RADIO RETRACTABLE TELESCOPING ANTENNAS

> PANOS ONIC and MANY OTHER MAKES CHROME PLATED

SIZE: 6½° long folded down es tends to 36° full length. 5/16° diameter shaft, requires 7/16° mounting hole

7's long folded down, extends to 47½s full length. 3/8's dismeter shaft, requires sometime of the state of th

STOCK NO. PA-67

\$2.79 PRICE PER PAIR 2 for \$5.50 TWO PAIR PRICE HEAVY-DUTY CONSTRUCTION SOLD ONLY IN PAIRS.

MA105

TANDEM TANDEM SWITCH ON 1/5° COMMON SHAFT 1-SPST 1-DPDT 1 HP, 129 /250 AC

STOCK NO TS2 PRICE 49¢

STOCK NO G-508

DRIFTLESS SILICONE BASE

CLEANS & LUBRICATES CORROSION RESISTANT SUPERIOR PRODUCT

REGULAR NET \$ 739 Lea



McGEE BIG

SPECIAL

PRICE



STOCK NO. G-508

uner Cleaner and Lube. 8 oz.aerosol nozzle adapter

8 oz. CAN

Model TK-303, The Champ and Two, RM-84 Speaker Systems.

TK-303-RM84



## SOLID STATE 10 oz. Geramic Stereo Multiplex ze: 18 long. 10 high, plenty of HI\_FI Styl deep Audio Power. Receiver CONTROLS YOUME TONI BAL TUNING AND INPUT BAL TUNING AND INPUT RECEIVER

nigh, plenty of HI-FI

deep Audio Power.

Receives and amplifies AM. FM and BELECTOR. GAIN FOR
FM stereo multiplex broadcasts. Also STEWED XTAL CART.
equipped with plug-in jacks for stereo
phono, stereo tape input and output.
Multiplex program indicator hight.
Illuminated dial with slide-rule station
selector. Handsome walnut-finish wood
cabinetry SHIPDENG WELGEN

SHIPPING WEIGHT 14 LBS

Complete MUSIC SYSTEM with two walnut vinyl covering TK 303. Stereo Receiver.

MATCHING GRILLE CLOTH. TK-303-RM84 Price \$59.95

\$995

WALNUT VINYL COVERING

8" WOOFER.

CALRAD PROFESSIONAL RECORDING LAVALIER MIKE USED IN JAPAN IN PRO USE SOLD REGULAR FOR \$5,00 1/2"x2" BRUSHED ALUM CASE.

No. 10-100

Calrad miniature dynamic microphone 200 ohm, low impedance with coil cord and lava-lier holder. For use with most cassette recorders

## FIRE MASTER

THE AEROSOL FIRE EXTINGUISHER



Puts Out Fires With the Push of a Button

So Easy a Child Can Operate It.

> For Use In Business Home Car Garage Tractor Camper Boat Trailer Plane Truek Tent Shop

or any place a Fire Might Start

FIRE MASTER Will Work on All Types of Fires (Gasoline Wood, Grease, Cloth, Oil, Paper, Coal, Electrical, Etc.)

Buy Several, They Are So In-Expensive Now Priced In The Reach of Every One

STOCK NO

FMX-CO

## WALKIE-TALKIE

**WORLDS FINEST 100 MW** 

REGULAR IMPORT COST MODEL

ruc approved - requires no license.

Deluxe 10 transistor

TRANSCEIVERS TOKAL MADE

AT FACTORY PRICE 2 CHANNEL SYSTEM WITH CALL SIGNAL

WITH 2 COMPLETE SETS OF CRYSTALS

AN **AMAZING** "WALKIE-TALKIE"

\* LEATHER CARRYING CASE \* EARPHONE

\* BATTERIES INCLUDED # 45" ANTENNA

MODEL

McGee Extra Vaius... Buy this 10 translabor, 100 Milliwett Walkies-Talkie at factory perice. Not 1, but 2 Channels crystal controlled superhet with built-in beep tone. Price includes Channel 7 and 8 CB crystal controlled superhet with built-in beep tone. Price includes Channel 7 and 8 CB crystal Channel 7 and 10 CB crystal Channel 10 CB crystal Channel 10 CB crystal Channel 10 CB crystal Channel 10 CB crystal CB cr

EQUIPPED WITH CHANNELS 788 CRYSTALS

**MA105** 

IEC SUBMINIATURE POLYESTER FILM METALIZED POLYESTER FILM CAPACITORS

EM SERIES SUB-MINIATURE POLYESTER FILM—Extremely small size for high density cir-cuits, with radial leads for easy

pacitance Range: 001 MFD to 5 MFD ODT MYO to age:
Operating Voltage:
100, 200, 400, 600 Volts D.C.
Temperature:
-40°C to +85°C,
no dersting

CM SERIES METALIZED POLV-ESTER FILM—Non-inductively wound, entended foil construc-tion. Saft-healing cheracteris-rics saure extended life in all applications. Capacitance Ranges. 0047 MFD to 10 MFD

Operating Voltage: 63, 100, 250, 400, 800 Volta D.C.

Temperatures. -40°C to +125°C


250 capacitors \$25.00 contains 18 different capacitor values EM Series (100V 10%) 1en values: from .001 to .47 MFD CM Series (250V 10%) eight values: from .01 to 2.2 MFD

S TOCK NO

PRICE.

\$25,00


IEC-250 CAPACITORS



The Most Popular of All TO WATT MONAURAL AMPLIFIER

VIDLAND

10 WATT MONAURAL



AMPLIFIER' \$49.96 LIST

SPEAKER

SYSTEM

61/2 INCH FULL RANGE

1,47 oz. Magnet SPEAKER

CLOSEOUT PRICE

Madel 13-601 Madel 13-601 \$49,95 Value -NOW only -\$1 995

The modern styling, exceptional performance, and its reasonable price make this amplifier an outside median value. The high fidelity response is derived from top quality components, experiment generated from top quality components, experiment engineering and excellent workmanship. This amplifier provides a full 10 waits of audio with 4-tube realistic tone adjustmant. The frequency response is 35-16,000 cps. Inputs are provided for a caramit cartridge and a tune with convenient switching. Overall Dimensions, Width 122-7. Depth (including 5/47 knobs) 7/47. Fin shed in light tan with the comed front plats, knobs and legs. Each set is attractively cartoned with instructions included.



apsulative verb cur-cult. (Reverb apring not furnished). This unit requires B plus and filament voite ages. A Terrifle value at \$9,95. Ship. Wt. 2 [bs. Stock Ns. CHS-1186

CHS-1186 WOR 59.95 . NOW \$4.95 5 WATT MONAURAL AMPLIFIER Mode By SYL VANIA

\$1295 AC POWERED RCA JACK INPUT

7 for \$25.00 RCA JACK IN U. Stock No. SYL-AMP5 McGeo off

## Extension Speaker BAFFLE



SPEAKER SALE PRICE FOR BOTH \$795 RUGGED CONSTRUCTION 1" - 8 Ohm mounting bracker for

output or line transformers Large 10 oz.CERAMC MAGNET Newest construction for greater preformance — 40 to 14,000 cps SPEAKER COMFS UNMOUNTED

## SPECIAL HOT MCGEE SPECIAL PAGING SPEAKER \$36,00 LIST VAILUE

for \$7.95 SAVE

STOCK NO.

FINEST LOOKING EVER BUILT

IR - 9BRUSHED ALUMINUM PRICE FINISH

2 FOR \$15.00 PAGING

IR-9

## SPEAKER MADE BY ATLAS

Atlas built for Webster Productomatic. A \$36.00 list value 12 months Atlas built for Webster Productomatic. A \$36.00 list value, 12 watts peak, 7½ watts continuous. 8 ohm VC. Spun aluminum brushed finish hom, 7°° x 14°° long. Good sound for music and speech. Swivel mounting on any wall in minutes A complete trumpet and driver for indoor or outdoor P.A. or intercom use. Dealers net value over \$20.00. McGEE sale Price\$7.95, two for \$15.00



2,95 to 39,95. A terrific b

## CAPITOL STEREO 7 TUBE AMPLIFIER

LESS CONTROLS AND PANEL

5 watts per channel, 4- 25L6 tubes in Push-pull parallel. 3- 12AX7 pre

Price

omp tubes. Stock No.



The amplifier is complete but less the AC Switch, Balance, Volume and Tone controls and case. Make your own control panel. Parts needed: 4- nto 1 leg. dual controls and an AC switch. Although these parts are not fumished they are easily obtained. Schematic only is fumished for wiring. No cables orplugs are fumished, easy to construct or wire around. The Tube complement: 1:12AX7 Phono-Preamp, 2-12AX7 Phase Inverter and Amplifier, 4-25L6 Push-Putl parallell output tubes plus sillcon rectifier. This is an exceptional buy at \$9.95 as it is less than the wholesate price (60% off List price would be \$10.46. These amplifiers are the same as our #1000 Stereo Amplifier but less stereo control panel and cables. stereo control panel and cables. CAP 10, Special Closeout Price \$9.95

## 5 WATT SPEAKER / AMPLIFIER SYSTEM

MFG. BY SYLVANIA

year term ages may be come in emersion will out unliquion but 1871 k qs for 1871 mars o 371 samp

Priced Below Manufacturers Cost ! #3 TUBE A.C. AMPLIFIER Heavy Duty Power Transformer \* EXTENDED RANGE 6" P.M. SPEAKER

\* ON-OFF SWITCH and \* VOLUME CONTROL

# TONE CONTROL

# PILOT LIGHT

McGEE 4 95

ILITIE

PHONO-AMP

00 FOR

3-WATT

STEREO

Bningen Coatral

FAMOUS

Stock No. BS. SAMP

Stock No. BS-SAMP. Attractive 5 Watt Book-Stelf Speaker/ Ambither System manufactured by Syl features book design front to their diwith books on your shell. Mooden sebinet covered with brown theretic hes my attractive grifts. Sizes 10° is not a 10° wide a 2° deep. The ETIMe, 50° lifter with heavy duty power transformer uses 6AVS, 6AQS and 6X4 tuber, line aide mounted On-Switch and Volume control, Tone control. Plots ight indicates when amplifier is turned on Idea use as 3rd, chained for Stereo Systems, for Tape Record Changers with any Crystal phone errivide, of use 2 for Stereo. Terminal on back for conting most AM-FM Tuners, Ship, Weight 9 bis, This well naise you a very structive appeaker system Stock No. BS-SAMP, Book-Shelf Speaker/Amplifier System, \$19.95 each, 2 for .......\$38.00



Boffle Cost Moker over \$5.00

\$3.99 \$7.50

Stock No.

Simulated Book Front Design

Boiffe Leatherette Covered 10" Nigh x 10" Wide x 7" Deep

g" It, a tig" H. a 2-2 '8" D. External Power Hooded & V. DC

750 2 5 19:

4 TRANSISTOR

3-WATT AMPLIFIER

PL 14-421 ANDIO AMPLIFIER Z for \$11.00 2521

DO YOU WANT TO ADD THE FINEST TONE CONTROL CENTER MP-176 \$895 SCOOP!

## Drivers

Rugged Construction Field Replaceable Diaphragms High Efficiency Dual Weather Protection DIAMETER POWER (OHICE) LENGTH \$14.95 RESPONSE MODEL \$16.95 \$23.95 80-12.000 HZ 2531 to watts 336 70-12,000 HZ


2531

TAPE HEADS & PARTS AN EXPERIMENTERS ITEM I.B.M. COMPUTER BOARDS

## SPECIAL Stock No. IBM-3-100

IBM BOARDS 9

TWENTY Boards full of Transistors Condensers and Resistors. Guaranteed 36 Transistors. SHIPPING WT. 1 LB.



## LEAR SOLID STATE PRE-AMPLIFIER.

Ideal for Servicement's replacement parts and experimental use. Matded Epox Transport or made by Fairchild.



Stock No. 2009

\$2.99 EA 2 for \$5, 50

A COMPLETE STEREO PRE-AMPLIFIER PRINTED CIRCUIT BOARD, On ginally used in Automobile tage players, This unit was made by Lear, Circuit exhausts of Eight moulded Trans-tators, Fage are used in sect. Channel, Operates on Batteries or 12 Volt DC Power supply. Can be adapted to Sound Amplifier as entre White Pre-Amp, inputs, also VR and low output Crystal carridge Phono pre-memps. This unit can be Completed by adding the final stereo stages,

Size 1% ends 5° long & b. B high, Shin W. 11b, KNOBS and CONTROLS are not included. Stock No. 1009 Parce 32.99, ca. 2 for \$5.50



CU-B2L7K REPLACEMENT FOR LEAR 8 Track
PLAYBACK CARTRIDGE PLAYER

8-Tr. Steren Stork No. \$3,59

CASSETTE TAPE RECORDER HEADS Will fit most of the imported Recorders



RECORD/PLAY & ERASE

These Tope Heads will fit most of the Japanes Tape Recorders. A two-piece set constating of one record playback and ersse head, with fwach Record Play: ', track, DC Res. 600 ohms,imped 3500 ohms, Buss current 0.2 ms. Ersse: 320 ohm Ersse current 4 ms. With instructions & hardwa Price \$2.49 Strat No. RE-2

RS-25

Real - Holders

Set price 49 Cmile.



TRANSISTOR RADIOS

Earphone, less hanger, Dynamie, Radial 29 ¢ Plug (1 \*\*\* 0 v\$ \*\*\* L shank) 46\*\* cord, 10 ohm impedance Medel 21-204 10 to: \$2.75 Dynamie Earphone Lass Hanast 294

### HEAD DEMAGNETIZERS & MOTORS

CARTRIDGE HEAD DEMAGNETIZER FOR HOME TAPE PLATERS



CARTRIDGE HEAD DEMAGNETIZER FOR 12 VOLT USE IN AUTO TAPE PLATERS

DELUXE TAPE HEAD DEMAGNETIZER



ERASER UP TO

#### ECONOMY TAPE ERASER

\$695

#### TAPE SPLICERS



\$19.65

\$10.50 \$7.88

REPLACEMENT CUTTER CARTRIDGE AND 2 UTTER PADS. NO. TZ-2 FOR TS-4A SER-ES SPLICERS. NO. TZ-3 FOR TS-45. A-75. AND -7J TAPE SPLICERS. NO. TZ-8 FOR TS-8D. NO. TZ-4 CUTTER PADS FOR TS-4A SERIES AND TS-75 AND TS-7J NO. TS-8 CUTTER PADS FOR TS-8D. 12 UTTER PADS TO A PACKAGE.

**EACH KIT \$1.39** 



GOOSE-NECK TROUBLE LIGHT

handous light to get lists hard to places. Light will stand and game can be pastioned, where having hid light Equipment with profit solich corrying clip. Game such in d'Tong, igles from § 11y Yah #1 cells, Less



10 foot CABLE & PLUG

Plugs into auto lighter socket

Two for \$1.10

CBL-10

ONLY 500 TO SELL MICROPHONES

RETRACTIBLE CABLE 4 CONDUCTORS

Ship. Wt. 1 lb.

Black Plastic Case 2-3/8" W x 3-3/4" L. CBM-299

McGEE Special!



Perfect for controlling small mutor-driven AC appliances. Foot twitch is stress connected with one side of the AC plug-socket combination. Plug the foot twitch into the AC socket and then plug your appliances into it. Ideal for drills, maxers, sewing machines, tables, saws, etc. Individually packed in pegboard display pachage. 2-7/8" sac; 6-ft cord.

Model 18:365—

Model 18-865-AC Foot Switch

ELECTRIC OUTLET CONTROL



- ADD1 6 ABOITIONAL OUTLETS

## Plas PPair PLASTIC REPAIR KIT CADDIE SIZE KIT 30cc Plastic liquid

40 grams Plastic powder Liquid despending bottle

Dropper. Instructions. \$185 Boxed

## LIGHTWEIGHT




20 ft. cord with plug

Stock No. GOLD-20 Price 39¢

DYNAMIC

10 for \$3.50 100 for \$25.00

Ideal for listening on Transistor sets, HEARING AIDS, RADIO SETS AND TELEVISION SETS





Thousands sold for \$19.95 Many Hard-Of-Hearing

carry this wish them wherever thay go

#### TELEPHONE PICKUP COIL

994

10 For \$9.00

## HEAVY DUTY INDUSTRIAL SWITCHES

Stock No. Chrome Handle.

Price Heavy duty

S.P. S.T. Toggie Switch 6 Amp. - 250 Volts Silver Contacts



HEAVY DUTY D.P.D.T. Toggle Switch.

Chrome Handle 6 Amp.-250 Volts Silver Contacts

Stock No. SUB-MINIATURE MT-7 DPDT Center Off DPDT Center Off

Toggle SWITCH \$1.29

5 Amp. at 125 volts A.C.



99¢ Standard SPST rocker switch with builtin meon bulb, 125 volts at 10 amp. Bulb

operates on 120 volts. A.C.

## E REPLACEMENT TAPE HEADS, KITS, MOUNTS, ACCESSORIES



4-Channel

4-Tr. Stereo



9000 Sector 5606 Series

1000 Series

6000 Series

#### RECORD/PLAY AND RECORD ONLY HEADS

All heads described are no-mount styles with hyperbolic face and laminated core construction. Application Notes: A—High impedance general-purpose Record/Play or Playback Only head for vacuum tube circuits. 8—Medium impedance Record/Play lical for vacuum tube or transistor circuits. C—Low impedance Record Only head for vacuum tube or transistor circuits. D—Low impedance Record Only head for vacuum tube or transistor circuits.

800	
100	\$21.50 21.50 21.50
800 400	27.25 27.20 27.28
100	33.10 33.10 33.10
800 100	17.90 17.90
800 400 800	10.60 30.60
400 100	17.90 17.99
370	94.50 94.50 94.50
	800 400 50 800 100 50 800 100 800 400 100 90 370

"COMBO" HEADS
Combination heads with all-in-one function of Record/Play and

P.FESC.	MO-INOMITE BEAL	C.		
Nort.	Head Description	Head Function	Nortrentes No. Each	•
6000 6002 6127	4-track stereo 4-track stereo 2-track mono		1400 & 1201   \$24.0 1401 & 1201   24.0 3601 & 2601   12.5	10

#### ERASE HEADS

Nortronics No.	Head Type	imped- ance	I MHX Inductance mH	Impedance Ohms	Net Each
1400	4-Track Stereo	High Medlum	80 10	30,000 2,800	5 9.58 3.50
2280 2281	2-Track Stereo	High Medium	80	25,000	13.20
3600	2-Track Minno	High Medium	80	25,000 2,000	6.80
4400	Full Track	High Medium	40 3.6	12,000	14.00

## HOME AND AUTO STEREO



FREE REPLACEMENT INFORMATION As your local Nortronics distributor, we will be glad to provide you with Nortronics Tape Head replacement information for your recorder. Compilete Replacement Guide covers over 2800 foreign and donestic machines. This is the only comprehensive listing in the industry.

QUIK-KIT MOUNTING HARDWARE Quik-Kits available for use with no-mount style heads. Kits

Nortronics C		For Nortronics Head	Net Each
QK-18 QK-20 QK-38	QK-19 QK-21 QK-66	All standard crase heads 3000, 3001, 3200-3202 All other Rec./Play, Rec. Only, and "Combo" heads	1.26

#### Other Quik-Kit Mounts:

Nortranics Quik-Kit No.	For Head	Not Each
QK-15	Bpecial Rec./Play & protessional base-mt.	\$2.00
QK-100	Pentron mounting assembly	2.00
QK-182	Sony Record/Play mount	1.75
QK-119	Adjustable Sony mount	1.25
QK-100	Pentron crass mounting assembly	2.25
QK-305	Sony crass mount	3.00

#### **BROADCAST MOUNTS**

#### HO-MOUNT HEAD BRACKET ASSEMBLIES FOR CARTRIDOE RECORDERS

	PROFESSIONAL RECO	RDER HE	AD RI	PLACE	MENTS
	For Tape Recorder	Func- tion*	Nort. Head No.	Quilt- Kit No.	Head, Net Each
	Ampex 300, 350, 351, 354, 600, 900, PR-10	RFT	9103		5 47.95
	AG380/355 300, 350, 351, 354, 600, 900, AG350/355, PR-10	RFT	9104 9102		47.75 47.75
	38191	EFT	9128		47.75
e	350, 351, 354 600, 900, 1°R-10 300, 350, 351, 354, 600, 900.	EFT	8109	QK-87	47.75 47.75 23.15
1	300, 351, 354, 600, 900, PR-10 AG350/355, PR-18 300, 600, 351, 354, 600, 900, AG350/355, PR-18 300, 600, 900 351, PR-10 355, AG350 300, 350, 351, 354, 600, 900, PR-10	R2TS	9203	Ampex	45.23
ľ	AG350/355 300, 350, 351, 354, 600, 900,	R2TS P2TS	3284 3282	PR-10;	45.25 45.05
C	AG350/355, PR-10 300, 600, 900	E2TS	8304	QK-66 for	22.75
	350, 354	F2TH	8309	600:	22.75
	355. AO350	E2T6 E2T8 E2T8 E2T8	9226 9222	QK-86	45.05 45.05
-	300, 350, 351, 354, 600, 900, PR-10	R2TM	8401	for 900:	28-26
	A COMMENT OF F	R2TM P2TM	8414	QK-76	18.10
	AGS307/353, 300, 350, 351, 354, 600, 900, AG359/355, 1:R-10 800, 600, 900, PR-10 350, 351, 354 300, 350, 351, 354, 600, 900 AG350/355			for	
	300, 600, 900, PR-10 350, 351, 354	E2TM E2TM	8504 8509	all others	16.00
-	300, 350, 351, 354, 600, 900	R4TH	8604	oth. o	27.50
	300, 350, 351, 354, 600, 900,	RATS PATS	\$614 \$600	71.7	27.50 31.40
	300, 350, 351, 354, 600, 900, AG350/355 300, 350, 351, 354, 600, 900	E4TS	8701	- 1	19.15
-	Crewn 701, 801, BX801, 1001, 1401	PFT or R/PFT	9111	QK-35	47.75
	BX801, 1001, 1401	RFT	9103	QK-35 QK-35	47.95
	Chamm 712 620	EFT P2TS or	-8102 8209	QK-35 QK-35	23.15 45.05
	Crown 712, 822, BX822, 1022,	R/P2TS R2TS			
	1422/8	R2TS E2TS	8201 8304	QK-35 QK-38	33.20 22.75
	Crewn 702, 802.	P2TM or	£403	QK-35	20.4
•	BX802, 1002, 1402/8	P2TM or R/P2TM R2TM	8404	OK-35	18.10
		EZIM	8504	QK-35 QK-38	26.00
1	Crewn A51, A314 Crewn A54, A324	P2TM P4T8	\$406 \$401	QK-68 QK-68	29.46 31.46
	Crewn 714C, 824.	P4T8 or	REOR	QK-66	31.4
5	Crewn 714C, 824, BX824, 1024, 1424	P4T8 or R/P4TS R4TS	4608	QK-66	31.40
Ð		r.41D	8781	QK-66 QK-38	19.15
9	Magnecord 1021	RFT	9111		47.9 47.7 17.9
		P2TM EFT	8484 8102		23.1
1		RATE	8203		33.20
	Magnecord 1022	P2TS E2TS	4202 8302	******	33.20 45.09 22.79
•		RATS	6602		27.50
_	Magnecord 1024	PATS EATS	8607 8702		31.4
	Magnecord P60, P76, N190	RFT	9103	QK-35	47.95
		EFT	9102 8105	QK-35 QK-35 QK-35	23.1
-	Sculty 270, 278, 280	PFT P2TS	3100 3200		72.7
	Scully 2/0, 275, 280 270-2, 275-2, 280-2 270-4 280	P4TS	8620		5 C 44
	- 2250	RFT EFT	9101 9138		72.9 72.7 70.2
	280-2 280-2	R2TS E2TS	9201 9221		70.2
		R3C	9361		210.0
	Scully 282-3	P3C E3C	9361 9360 9370		210.0
		R4C	9461		235.0
1	Scully 282-4	P4C E4C	9480 9470		235.0
1		Dec	9881		420 0

\*Function Codes R, record; P, pisy; E, erase; FY, full-track; 27, 2-track; 47, 4-track; 30, 3-channel ½; 40, 4-channel ½; 80, 8-channel 1; M, mono; 8, stereo.

Scully 284-8

AMPEX PROFESSIONAL MOUNT
Neutranics QK-76—Kit containing everything
necrosary to adapt Nortronics head to shield cup
of an Ampex head nest. Includes precision castsiuminum block, spacers, serews, connector plug
and full instructions. Other necessary parts are
utilized from the original Ampex equipment.
Net Each. \$12.00
Nert. Head

recording brekings, Ameninten.	ALL EMOI			92.01
Revere T-2200, TS-2205, -2225	R/P E	7601 E-52		32.20 6.55
Revere 5150 Revere 5200, 5250, 5280, 5300	R/P/E	6128 8985	QK-66 QK-66	12.98 24.00
Seny TC200, 250, 260	R/P	1807	QK-102 QK-306	21.50
Sony 262D, 262SL, 464CS, 464D, 464SL	R/P E	1402	QK-102 QK-305	21.50
Sony 263, 263E	R	1218	QK-102 QK-102	27.20 21.50
Seny 300, 500, \$21, TC561	E R/P	1402	QK-305 QK-119	9.50 21.50
Sony TC801A, SSA905A, TC905A	E R/P E	3001	QK-305	3.50
V-M 700, 701, R-1200 V-M 700	R/P E	3000	QK-20 QK-18	18.60
V-M 701, R-1200 V-M 720, 722, 755, 1001-15.	E R/P	1001	QK-18 QK-38	6.88 21.50
1002-1/2, 720, 722, 735, 720, 722, 755, 1001-1/2, 1002-1/2	E	1401 2001	QK-18 QK-38	9.50 33.10
V-M 710, 710A, 711, 711A, 714,	P R/P	3181	QK-38 QK-20	10.50
730, 750, 750A, 1000 V-M 714, 750A, 1000 (only)	P	2001	QK-38	33.10
All above V-M models V-M 725-1	R/P/E	3661 6127	QK-18 QK-38	12.94
				_

5	The second secon	Head	Hond,		
-	Manufacturer and Medel Number	Func-	Tape	Quik-	Net 1
٠,		R/P/E	Feed 6003	Kit	Each .
,	V-M 726, 735, 738-1, 1471-1, 1481-1, 733-1, 733AV-1	R/F/E	+003	QK-38	\$24.00
95	V-M 740, 740-1, 741	R/P/E	6002	QK-38	24.00
	V-M 735, 740, 740-1, 741	P	1009	QK-38	21.50
95	V-M 754, 744, R-600, 1482-1 Webcer 2001-1, -1A, -1B, -1C,	R/P/E	6005	QK-38	24.00
75	-5A10 2002 2003 2009	16	7500		6.30
75	-5A, -10, 2002, 2003, 2009, 2103-1, 2206-1, 2810, 2811, 2812,				
75	2816, 2819, 2892, 2897, 2910,				
15	2919, 2896 For the following include 2820,	1*	40.00		
25	2820-1C, 2821, 2822, 2827, 2897.	1	7620		40,30
25	2923, 2980, 2955				
QS	Webcer 2202, 2202-1, 2300, 2300-1, 2302, 2302-1, 1303, 2400-1, 2402, 2402-1, 2500-1,	R/H	3100		10.60
	2300-1, 2302, 2302-1, 2303,	E	7500	Acces to	6.90
75 75	ZOUU-11 ZAUG-1, ZAUG-10 Z599				- 0
òŝ	5400				
85	Webcer 2008, 2208, 2323,	R/P E	1000		21.50
10	FP-2323-1 4		7500		6.90
18	Webcer 2007, 2107, 2150, 2207, 2250, 2328, 2356, 2360, 2391,	R/P	1000	QK-18	21.50
	3392, 3393, EP-2107 1, -2150,	£	1482	QK-IB	9.50
	-2207-12208-1, -2250-1, -2328-1.				
09	-2356-1, -2356-1A, -2356-1B,				
50	-2357, -2357-1, -2360-1, -4007-1 Webcer 2456, CP-2520-1, -2522-1	Th			
50		R/P/E	6003		24.08
40	Webcor 2503-1, EP-2403, -2403-1.	R/P/E	6025		14.59
15	PB-2503-1. Viscount III	,-,-	****		24.38
75		R/P/E	RPE-23		18.05
	Wellersak T-700D, T-1400-B, -C, -D, -E, T-1500, -1570, -1600,		laces or		
95	-1700, -1800, TS-1520 and all		hure he		
15	older 2-track mono models	R/P/E	laces or		22.00
85		Nortron	ics or N	hure head	1
20	Westersalt T-1440B-, «C. »D. »E.	R/P	7601		
75	1-1010-4, -1010-4, -1015	E	7720	22-1	
40	Wellersak 1580, T-1780-B, -C, -D, -E, T-1980-B, -C, -D, -E,	R/P	7601		
		E	E-59		20.90
10	Wellersak 524, 7500, T-540	R/P/E	6125		12.30
	Waltemah 1990	R/P/E	6026		
40	Wolfensak 1280 Welfensak 5150	R/P/E	6082	QK-66	24.00
40		R/P/E	6128	QK-66	20.00
40	*Price is for head only; see Quik-	mit dati	ngs for	QK price	8.
15			1000		
95	4-545				

ADDITIONAL
REPLACEMENT AND CONVERSION DATA FOR
OVER 3000 RECORDERS.
REQUEST INFORMATION BY MANUFACTURER'S
MAME AND MODEL HUMBER OR BY HEAD HUMBER

#### TAPE RECORDER ACCESSORIES

Neutronics AT-100 azimuth and Amplifler Allignment Yapa—Full-track 7½ ips direct oscillator master recording. Has frequencies from 100 to 10,000 Hz for ehecking azimuth and NAB equalization. A 1000 Hz zero-reference level tone is included. With instructions. Net Each. \$9.90

tions. Net Each.

NetTrenics L-5 L-Eracket—For side-mount heads. Net Each. 60c NetTrenics L-5 L-Bracket—For side-mount heads. Net Each. 31.00 NetTrenics L-5 Narrow base version of L-5. Net Each. 31.00 NetTrenics L-7—Identical to L-6, but with reverse orientation to the bracket. Net Each.

\$1.00 NetTrenics TG-7 Tape Guide Peac—Vertically adjustable with tapped mounting hole in base. Chrome-plated brans for long life. Net Each.

\$1.50 NetTrenics TG-8 Tape Guide Plate—For side-mount heads and L-5. L-6 or L-7 bracket. Gives additional guiding, Net Each. 9 October 10 NetTrenics CC-70 Commenter Assembly—18" plug and shielded insulated cable assembly for all Nortronics heads except mono Combo types. Net Each.

Nottrenics CC-77—Identical to CC-70, but for Nortronics mono Combo heads. Net Each.

\$3.30

## BASIC OSCILLATOR TRANSFORMERS

T-70 Series is for printed circuit hoard mountings and T-60 Series is for chas-




T-70

For type of Circuit Met Transistor Transistor Transistor Transistor Transistor Vacuum Tube Vacuum Tube 50 120 kHz 150 200 kHz 230 500 kHz 50-110 kHz 230-500 kHz 40-70 kHz 60-100 kHz 40, 80 or 120 40 70 40, 80 or 120

_					
1		Hood	Nortre	Head.	
	Manufacturer and Model Number	Func-	Tape	Quite-	Net Each
P P P T	mtree HF-400, HT-225, P-4, B-1, PBA-2, PMC, FMD-1, F-3C, -3M, T-90, TM-56, TR-4, T-1, TM-1, CT-1, RWN, T-72, -74, -W3, NL-1, -2, -3, R-10	R/P	3844	QK-100	510.60
A	il above but PBA-2 & PB-1	E	3600	QK-300	6.88
	entron NL-4, GR-1500	R/P E	1060	QK-38 QK-18	21.58 9.58
X	P60 OR15A/B/S, AR-62,	R/P	3884	QK-20 QK-18	16.00
P	entron XP-608	R/F E	1866	QK-38 QK-18	21.50 6.88
	entren AR62S	PE	1005	QK-38 QK-18	21.50 6.80
	metron PR-65	R/P/E	6662		24.00
	ontron ST-3	R/P E	2660 1660	QK-38 QK-18	33.10
-7	28748748W3S. TM-4	R/P E	2500 1500	QK-100 QK-300	33.30
-7	1-10, -11, -100, -202, -700, 00-D, -900, -1100, -1400, -2000,		ces Shu	re head	16.05
T	R-20 thru -1200 (except R-600), TRS-25 thru -1226, S-15 thru -2025	Rep	laces or tronics	iginal	22.46
R	overe T-11-4, T-204-4	R/P E	7681 7728		32.24 16.39

## POPINS

## CASSETTE, CARTRIDGE, REEL TO REEL TAPE AND PHONO ACCESSORIES AT EXTRA SAVINGS FROM MCGEE



CASSETTE PLAYER/RECORDER HEAD DEMAGNETIZER

Removes excessive magnetic build-up from heads, a major cause of fidelity and sound loss. Recommended use by equipment manufacturers, every 15 - 20 hours of player/recorder use. Has built-in pilot light. 110 V. 50-60 Hz. A.C.

\$6.19

CARTRIDGE PLAYER/RECORDER HEAD DEMAGNETIZERS

#TD-12 for Home players. \$ 8.39 #TD-15 for Automobile units.

Direct current. Plugs into cigarette lighter. 12 V. \$10.99

(A) 8-TRACK 3-WAY COMBINATION TEST-N-CLEAN CARTRIDGE 1. Cleans player heads to improve sound fidelity. 2. Tests head for correct alignment to assure full fidelity playback without annoying cross-talk between tracks. 3. Tests Stereo balance

\$1.75 #THC-8



BEEPER HEAD CLEANER 8-TRACK CARTRIDGE

Special cleaning tape removes accumulated oxide, grime, and particles from heads. Audible beep signals times heads. cleaning cycle. \$1.25

(B) 'DOUBLE-HEADER" CARTRIDGE (B) "DOUBLE-HEADER" CARTRIDGE
ADVANCED MAINTENANCE KIT
Double ended Cartridge has specialformula non-abrasive head cleaner
tape, and player capstan drive cleaner
tape. Either end of cartridge fits
equipment. Includes bottle of head
cleaner solution, Maintains equipment performance.

\$7.99

(C) CASSETTE NON-ABRASIVE HEAD-KLEEN TAPE

Sale cleaning of Cassette player heads. Gently removes oxide, grime, and particles from heads, Improves fidelity. #THC-4 \$1.49

(C) CASSETTE MICRO-POLISHING HEAD-KLEEN TAPE Cleans and polishes player heads Removes accumulated oxide and other

particles. Improves fidelity #THC-7 \$1.25

3-WAY COMBINATION TEST-N-CLEAN CASSETTE l. Cleans player heads. 2. Tests head alignment. 3. Tests Stereo balance.

#THC -6

Patches.

"CUT-N-SPLICE"

CASSETTE TAPE SPLICER. Cuts tape at 45°

angle. Includes 25 self-stick Splicing

#TS-115 \$ 2.98

\$1.75



(D) CASSETTE AND CARTRIDGE RECORDER HEAD-KLEEN KIT 2 oz.bottles of Nead Cleaner and Head and Guide Lubricant, plus 25 extra-long Swabbies for safe, easy cleaning and lubricating of hard to reach recording heads. \$1.49 #TK-3

CASSETTE STORAGE ALBUM Holds 12 Cassettes. Built-in stops prevent tape unwinding. Decorator Walnut wood grain cover. Extra Walnut wood grain cover. Extra sturdy. Size: 10 3/8" x 9 3/8" x 1 1/4".

#TSA-IW \$2.19

(F) CASSETTE COMPACT CARRY CASE Attractive, heavy duty vinyl. Alliga-tor textured. Holds 12 Cassettes in their canisters. #TCC-5

\$2.69

(F) CARTRIDGE COMPACT CARRY CASE Attractive, heavy-duty vinyl. Alliga-tor textured. Holds 12 Cartridges.

#TCC -9 \$3.29



"GIBSON GIRL" STEREO TAPE SPLICERS

Rapid, professional tape editing and repairs. Cuts tape diagonally. Trims edges of splices to prevent adhesive of splicing tape from contacting critical parts of recorder. Replace-able cutter cartridge and pads.

\*TS-8D DELUXE SPLICER "See - thru" windows show cut and trim positions. Tape guide and fingers secure tape. Easy threading tape dispenser has roll of 1/2" x 100" Splicing Tape. Made of durable Cycolac. \$ 8.40

(H) TS-7S STANDARD SPLICER Has 3/8" Same features as above. Has 3/8" x 100" roll of Splicing Tape. Made of metal and plastic. \$ 6.29

REPLACEMENT CUTTER KITS

\*TZ-3. Cutter cartridge and two cutter pads for TS-7S and TS-7J Splicers. \$1 17

#TZ-8. Cutter cartridge and two cutter pads for TS-8D.

SPLICING TAPE Mylar base with special formula adhesive. Tackiness, thickness, strength, and cold flow carefully controlled for secure, clean splices.

#TST-235 1/4" wide x 300" #TST-376 3/8" wide x 275" .75 #TST-501 1/2" wide x 250" . 75

.75

Type Reel Size Pkg. Qty. Price .75 TR30-6 3" 6 TR50-2 2 .69 .69 TR70-2



BULK TAPE ERASERS Superior erasure of tape recordings than normal crase heads of recorders. Saves time. Reduces head and


(I) #TM-88 HAND HELD MODEL For Cassettes and 1/4" reels to 7" dia. Reduces background noise levels of tape to below normal erase head level. Size: 4" x 2 1/4" x 4 1/4". Wt. 2 lbs. 4 oz. 110 V. A.C.

\*TM-99 PROFESSIONAL UL LISTED MODEL. Reduces background noise level of tape 3 to 6 dB below normal erase head level. For tapes to 1/2" wide, reels to 1/2" dia. Size: 5 1/4" x 6 3/4" x 3 3/4". 110 V. 5 amps, 50-60 Hz A.C.

\$33.00

#TM-100 AUDIO-VIDEO BULK TAPE ERASER. For tapes to 1" wide, reels to 10 1/2" dia. Reduces background noise levels of tape from 50-90 dB below saturation minimum. Size: 3 3/4" x 6" x 8". 115 V. 50-60 Hz A.C. Duty Cycle: 5 min. On/10 min.

\$69.00



RECORDER HEAD DEMAGNETIZERS Removes signal damaging residual magnetism which cause noise build-up during operation of recorders. Maintains optimum recorder performance. 110 V. 50-60 Hz A.C.

#TD-6 PROFESSIONAL UL LISTED MODEL. Precision machined, Chrome plated probe is angled for safe contact with recorder heads. Size: 3 5/8" x 1 1/4". \$7.65

\*TD-3 Efficient low cost model. Angled probe has soft plastic shield for safe contact with heads. Size: 3 1/2" x 1 1/4" dia. Components are fully encapsulated in hi-impact

PROFESSIONAL "GIBSON GIRL" AUDIO – VIDEO TAPE SPLICERS

Heavy duty. Precision cut and trim for accurate, fast tape splices. Long life blades and cutter are replaceable.

#TS-250 for 1/4" wide tape 59.95 #TS-500 for 1/2" wide tape 59.95 #TS-1000 for 1" wide tape 59.95

COLOR-CODING LEADER TAPES Set of five 2 1/2" reels, 100 ft. each-Red, Blue, Green, Yellow, and White, 1 1/2 mil Leader Tape. Splice colorful leaders to ends of tape to reinforce and code them. #TT-16

\$2,85







(I) ADJUSTABLE STYLUS BRUSH Spring secured flexible brush adjusts to height of tone-arm, 3/4" to 2 1/4". Removes dust blob accumulation on stylus when tone-arm cycles, Selfstick base.

#PB-3

.89

(J) PROFESSIONAL RECORD SWEEP Automatically sweeps dust and other particles from delicate sound grooves of records. Deposits anti-static Cleaner and Lubricant, included. Suction cup mount to phono deck. \$3,29 # PR-10

(K) "MIRACLE" RECORD CLEANING CLOTHS AND CLIP-ON RECORD BRUSH "VALUE - PACK" Anti-Static ingredient of Cloths helps

reduce dust formation on records. Brush clips to tone-arm of phono and sweeps dust from records.

,81



'ROB-O-STAT" RECORD CLEANING KIT

Contains: super-soft velvet and foam applicator mitt, 11/2 oz. plastic bottle of Anti-Static Record Cleaner and Lubricant, polyfoam pad for cleaning mitt, and Stylus Brush.

(L) "TENDER-LOVING CARE" KIT Contains: super-soft velvet and foam Applicator Mitt. 1 1/2 oz. plastic Applicator Mitt. 11/2 oz. plastic bottle of Anti-Static Record Cleaner and Lubricant, Adjustable Stylus Brush, and Combination Tone-Arm Lift and Record Brush.

#PK-9

\$ 2.98 (M) STYLUS PRESSURE GAUGE

S 1.59

Sturdy, accurately calibrated and balanced Gauge with counter balance weight. Adjusts to measure stylus pressure to 1/2 gram. Correct stylus pressure assures proper tracking, optimum fidelity, minimum stylus and record wear. \$1.09 #PSG-3



(N) AUTOMATIC SOLID-STATE HI-FI/STEREO SHUT-OFF Automatically turns off amplifier when last record has played and auto-matic changer sto. . Prevents equipmatic changer sto. Prevents equipment burn-up. Use with all equipment. Switch permits manual operation, 110 V. A.C. Size: 61/2" L x 21/4" x 13/4" H. Mounts on wail or cabinet.

#PS-3

"DISCO-TOTE" RECORD CARRY CASE
Heavy duty vinyl, Alligator textured.
Holds 12- 12" records intheir albums.

#PRC-12 \$5.49

ANTI-STATIC RECORD CLEAN-LUBE SPRAY Silicone formula Aerosol Spray. Prevents dust accumulation. Eliminates annoying static pops and clicks. Improves fidelity, Increases record life. 8 oz.

TAPE HEAD CLEAN AND LUBE KIT CLEAR TAPE REELS 2 oz. bottles of Head Cleaner and Tape Head and Guide Lubricant. Minimizes head, guide, and capstan wear of recorder. Reduces wow and flutter. Improves sound fidelity.

\$ 1.35 #TK-6

163

\$129

\$7.49



## SONUSWITCH starts when you clap your hands!













the never touch a switch Clap your hands buce, the rights go on Clap them again, the gers are off. On stand scross the room and turn on the TV radio or move projector. MAGICE SORUSWITCHE

No doubt you can edd to link let TV, motors, lights, move and sude prosection, todays small needers, washers, dryers, dishwashers, and mules Think of the uses in brogetax, mediatries, offices and schools. Turn die the egiss from your bed, for example or control a tipe records.

Truly, its uses are limited only by the imagination

The amazing new electronic solid state Sonuswitch comes in black, gold, aque, and ivory cases,  $81/2^+$  by  $3^-$  high by  $31/2^-$  deep weighs under 2 pounds.

Just clap your hands and watch Sonuswitch start spiling! Like magics

Sonutwidth penetrates the electronic frontier — takes you into the Magic World of Sound Command being developed by Sonus Corporation

It's helpful to the hard-of-hearing, blinks a lamp on and off when the telephone rings.

It's a security device— switch on all the lights without leaving your room

Model SON-SW

SALE PRICE



#### Siren Auto Burglar Alarm \$14.95

FOR 12 VOLT AUTOS



#### Bell Auto Burglar Alarm \$14.95

MODEL 62 - 822 SIREN AUTO BURGLAR ALARM.

BLASTS A LOUD HIGH PITCHEO WHINE WHEN
CAR DOOR, HOOD, OR TRUNK IS OPENED. CONTHINGES TO SOUND UNTIL LOCK SWITCH IS TURNED OFF.
OFF. INCLUDES LOCK SWITCH Z KETS, 6 DOOR
SWITCHES WIRE AND MOUNTING SCREWS. SHIP AND MOUNTING SCREWS. (FOR 12 VOLT
WIT. 3 LBS. EASY TO FOLLOW INSTRUCTIONS.
FOR 12 VOLT AUTOS

MODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 820 BURGLAR ALARM THAT USES
ARM. LOUD, HEAVY DUTY BELL RINGS WHEN CAR PRESENT CAR HORN FOR THE SOUND. INCLUDES
TOR 10 DOOR, TRUNK OR NOOD IS OPENED. SOUNDS UNMASTER SWITCH, WORK OR NOOD IS OPENED. SOUNDS UNMASTER SWITCH IS ON ANY MOVE
SWITCHES WIRE AND MOUNTING SCREWS. (FOR 12 VOLT CARS)
MENT OF THE CARS WILL CAUSE HORN TO BLOW
FOR 12 VOLT AUTOS

MODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 820 BURGLAR ALARM THAT USES
ARM. LOUD, HEAVY DUTY BELL RINGS WHEN CAR PRESENT CAR HORN FOR THE SOUND. INCLUDES:

LOCK SWITCH IS TURNED OFF. COMPLETE WITH FAST INSTRUCTIONS. WORKS IN 6 OR 12 VOLT
AND MODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 820 BURGLAR ALARM THAT USES
ARM. LOUD, HEAVY DUTY BELL RINGS WHEN CAR PRESENT CAR HORN FOR THE SOUND. INCLUDES:

LOCK SWITCH IS TURNED OFF. COMPLETE WITH FAST INSTRUCTIONS. WORKS IN 6 OR 12 VOLT
AND MODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 820 BURGLAR ALARM THAT USES
ARM. LOUD, HEAVY DUTY BELL RINGS WHEN CAR PRESENT CAR HORN FOR THE SOUND. INCLUDES:

LOCK SWITCH IS TURNED OFF. COMPLETE WITH FAST INSTRUCTIONS. WORKS IN 6 OR 12 VOLT
AND MODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 820 BURGLAR ALMODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 826 BURGLAR ALMODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 826 BURGLAR ALMODEL 62 - 824 BELL TYPE AUTO BUGLAR ALMODEL 62 - 826 BURGLAR AL-



## Sound your Harn burglar alarm \$2.95

ON-GUARD PORTABLE HAND SPOTLIGH

Model HS-107 \$5.95

35,000 Condle Power Sealed Beam 12- Valt



BULLHORN All-Transistor

Range Up to 400 Feet. EASY TO FOLLOW INSTRUCTIONS

All Solid State Kit Eico model BH-16





#### TELEPHONE PLUG EXTENSION



## TELEPHONE

OUTLETS AND PLUGS
STANDARD WESTERN ELECTRIC
STYLE 4-WIRE LIKE USED
ON PRACTICALLY ALL
HOME TELEPHONES



PJI (70-386)

99¢ EACH

10 FOR

MCGEE SPECIAL PURCHASE TELEPHONE PLUG & JACK

SURFACE MOUNT JACK



Ideal for making plug-in connections for speakers, Etc. Has a Million Uses.

TJI (70-387 49¢

TPI (70-389)

ANY QUANTITY

49¢

G-C ASSORTED SPAGHETTI KIT



An assortment of 7½° lengths of sparhetti siceving. 26 lengths to the kit. Sires include from No. 17 wire '0 ½° I. D. A very handy bundle to have for repair John G.-C. No. 556—Kit 26 lengths.

36C

#### G-C SPAGHETTI ASSORTMENT "A Box Full of Spaghetti"



Here a buy you can't beat on a page that a sortiment a variety of size and colors are included of high trade varieth tubing. Put up in attractive box. 90 C

## TV WALL PLATE KIT FITS STANBARD OUTLET BOX AMERICAN MAGE

F.M. AND T.V. WALL PLATE WITH POLARIZED PLUGS 59¢ 10 For \$5.50

TV-FM ROTOR WALL PLATE

VP-67 79¢ 10 For (75-485) prong and one

UNIVERSAL TV-FM SOCKET AND PLUG VP-35 (75-482)

t hadt. Zonnhalte worder soch unt für sim für 1637 ar aus Zon uber ennecten fehltr seine

29¢ 10 FOR

UNIVERSAL TWIN LEAD CONNECTORS 

39¢ VP-16.83.50

POLARIZED PLUG heap more prong polarized plus for 15¢ use with most wan receptacies 10 FOR VP-25 (75-481) \$1.25

ZV\_FM WALL PLATE BUY 39c 10 FOR

\$3.50 for 300 olum twin lead-in. Allows you to put an outlet for TV lead-in wherever you wish No more unsightly wises. Comes with polarized glug and mounting hardware and complete instructions. Fits Standard outlet box. Cal. No. VP-65.

STOCK NUMBER VP-65 (75-483)

#### 4-WAY EMERGENCY BLINKER SWITCH



994

9 SECTION

\$1" EXTENDED

STOCK NO.

TA-2 (75-461)

\$1.69

Cat No. TA-2

## AMERICAN MADE UNIVERSAL

Pair of 455KC Printed Circuit I. F. Transformers Stock No.



1

53C06-09 59 Price

PAIR



Stock No. 53C06-09 Price . 59 pr.

## ERALD Intermetic LYTER



Protects our Home With Light 24 Hour Plug-In Timer Cordiess—Plugs directly into well

Outlet Turns Lights on and off Automatically for a 'Lived-In' Look That Discourages Prowlers Operation Daily Without Recet Size 234" x 334" x 11/4"

## CONVENIENT PICK-UP TOOL



892 (75-472)

Very useful to shop, home or effice: Can-reach into-inaccostable places, pet up small places; and parts with just a press of the thumb! Molds screws, both and nots for eary staring. A nodestify for every mechanic and technicism. Individually packaged for pag No. P50 Not Trice 5.75

testible folded dipale antenna for F.M. or T.Y. les tabs on and all wire for easy attachment to

MINIATURE TELESCOPING ANTENNA

FM OR TV FOLDED ANTENNA

86

## RESISTORS 39¢

52 OHM

10 For \$3.50

Very popular 52 ohm 25 watt wire-wound, filament dropping resislor used widly in TV. White ceramic case measures 19/32" dia. and 3" long. Single ended lugs. complete with mounting strap. Stock No 601487, Price 39¢

GLOBAR RESISTOR JA/81

1 epiaces Motorela Port 6A735941 also Workman FR-11 69¢ 5 FOR 10 FOR 53,00 \$5.50

-1/8"

MIRA KLEER ALL PURPOSE CLEANER 12 OZ.



CLEAR AND PROTECT TV CHASSIS PICTURE TUBES MASKS ETC. SOLD FOR MANY YEARS TO MANY REPEAT EMSTONIESS

CENERAL CELECTRIC GE 2568-01D Handy 6-OZ. Spray Can New Improved

Silicone Lubricant

Net \$1.09 \$1,00 each in lots of 2



## GENERAL ELECTRIC SILICONE SEAL

Super Clase. 100% rubber. Bonds securely to glass, ceramics, metal, wood, fabrics, mesonry, painted safeces, most plastics, and rubber. Permaneuer Caulii. Will not shrink, crack or dry out, Remains flexible and elastic and can stretch over 100%. Originally developed for sealing space wehicles. Calaranteed 10 years

101 uses around ony shop

BPECIFY COLDR
WHEN OPPERING
3 Ounce Tubes
White Seal \$1.59
Elack Seal 1.59
Abstrainem Seal 1.59

G.E. Silicone Seal in 12 oz. cartridges far reg. coulking guns.

12 oz, white seal \$3.59

12 oz. transpar.



Cet. No. TA-10 CB WALKIE TALKIE REPLACEMENT ANTENNA 27MC Phoes CB-827 (75-473) DISAPPEARING

\$1.99

TA-9 (75-467)

Cor. No TA-4

TELESCOPIC ANTENNA 90 - VERTICAL ROYATION 9 SECTION 32 INCHES EXTENDED

**\$1.79** 

ADJUSTABLE DISAPPEARING Y TELESCOPIC ANTENNA

COP No TA-3

360\* HORIZONTAL ROTATION 180" VERTICAL S SECTIONS 22% INCHES STOCK NO. TA-6 (75-465) \$1.79

50" EXTENDED STOCK NO.

11 SECTION

TA-1 (75-460)

\$1.69 Cut Ne. TA-1

TELESCOPING

TA-14 (75-469)

\$2.19

WHIP ANTENNA

TA-5 (75-464) \$1.19 TELESCOPIC ANTENNA

TA-8 (75-466)





net each. Shielded 600 ohm audio line matching transformer, lx l1 in, case size with color coded leads for easy installation, 4 pm. and 2 sec leads. Works with any background music or PA amp. Full range audio response, 5000 No. GR-250 McGee Net Price \$3.95. Two for... 57.50

BROADCAST LOOPSTICK ANTENNA

39 C EACH Stock No. 75-474



# NTERNATIONAL

SAVE 30% ON THIS BEAUTIFUL HI-FI SYSTEM

STOCK NO.

MODEL 19-650.

McGEE SPECIAL PRICE

McGEE

BEST

50-Watt AM/FM/FM Stereo Receiver with Changer

Compact stereo home entertainment with brilliant AM/FM/Multiplex plus a top-mounted B5R record changer module. Solid state receiver delivers 50 watts total power ± 1 db. Station-pulling RF stage on both AM and FM. Full complement of jacks for total base amplifier versatility. Changer features professional-quality 4-pole motor. Tubular aluminum tone arm has cue and pause lever, anti-skate device, cartridge shell with finger-lift. Shure magnetic cartridge, diamond stylus with adjustable pressure knob. Walnut-finish wood cabinetry topped by an attractive tinted dust cover.

• FM (88-108 MHz); AM (540-1600 KHz)

32 transistors, 1 F.E.T., 11 diodes, 1 thermistor, 1 rectifier
 Power output: 50 watts ± 1 db, 40 watts total music power, 12 watts/channel RMS

Frequency response: 25-30,000 Hz ± 1.5 db

Channel separation: 35 db

Distortion: Less than 1% THD

Hum and Noise: -65 db

FM sensitivity (IHF): 2 μV

 Controls: Volume, bass, treble, balance, tuning, loudness stereo/mono, high filter, power on/off, tape monitor

Changer: 4-speed, 4-pole induction motor; low mass tone arm, Shure magnetic cartridge, diamond stylus

Changer controls: Stop/start/auto, 16/33/45/78 RPM selector, 7"/10"/12" size selector
 Inputs: Magnetic phono, ceramic phono, auxiliary,

tape in, external FM and AM antennas

 Input sensitivity: 2.5 mv (mag. phono), 180 mv (aux.) Outputs: Speakers, tape out, headphones, AC outlet

 Appearance: Walnut-finish wood cabinet, die-cast control panel, black changer trimmed in silver-color.

Complete with FM antenna, changer module, dust cover Size: 163/8" x 73/4" x 91/2"

Shipping weight: 24 lbs.

Model 19-650 - 50-watt receiver with changer \$139,95

SPECIAL OFFERING OF SPEAKER SYSTEMS, WITH THIS RECEIVER AND CHANGER, MODEL DA8N3N SYSTEM AS SHOWN ON THE OPPOSITE PAGE FOR \$50.00 MORE, WHEN PURCHASED AS A UNIT.

STOCK NO.. 19-650-DA8N

\$29

CASE

#IIH

PRICE

ECIAL

SP

MCGE

CASE

3

CE W

PR

COMPLETE PRICE \$189.95

\$13995 SO WATTS MUSIC POWER.
(12 WATTS per CHANEL RMS.) COVER 

BSR, McDONALD 4 SPEED CHANGER.
With a 11" TURN -TABLE
4 POLE MOTOR.
PLASTIC DUST COVER.
SHURE, M-71 CARTRIDGE.

REGULAR \$200.00 MIDLAND STEREO RECEIVER

ONLY 100 TO SELL

SPECIAL BUY SAVE \$15.00 WHILE 100 LAST.

Lectro-Voice **Omnidirectional** Microphone MODEL 631PC 90 \$ 58. Two for WHEN ORDERED

WITH ANY

Model 631PC-One model 631 (Hi-Z) with phone plug. Microphone and cable packed in convenient carrying

"HANO AND STANO" DYNAMIC-High quality entertainer's microphone. Omnidirectional. Lightweight, rugged, and shockproof. Effective 4-stage filter allows use close up without blasting, pops, or distortion. Silent, magnetic on/off switch with removable actuator but-

Response: 80-13,000 Hz. Output: -55 db. Hi-Z

With cable and 310 stand clamp. Size: 6" long, 1-3/8" head diameter, %" shank diameter.

MOTOR STARTING CAPACITOR
CORNELL-DIBILIER 2.5 MFD. 330 VAC CRA-3025-7 PRICE 99¢ " LONG. 1/3/8 DIA. WITH MOUNTING CALIBRATED INSTRUMENT & CAMBRATED, 0 TO10 1" GOLD KNOB ON STOCK NO. 36D60203 PRICE 29¢ PILOT LIGHT ASSEMBLY

AUDIOAND PHONOSHE LOED CABLE

49¢ AUC-14 PRICE BSR, McDONALD 4 SPEED RECORD CHANGER

6 X 9 SPEAKER 6.8 oz. Alnico '5' MAGNET 8 ohm, 1" Voice Coil. THIS IS THE PEAKER THAT STANO UP ON ANY TRACTOR RADIO. HIPPING WEIGHT STOCK NO.

**HEP-69** 2 FOR \$7.50 PRICE \$3.99 10FOR\$37.50 GOOD REAR SEAT SPEAKERS

SHURE MAGNETIC CARTRIDGE M-71 VALUE SERVICEMAN'S SPECIAL FACTORY CARTON OF 4 \$10000 PER CARTON

SIZE: 1114" X 13

COLOR, BLACK with BRIGHT TRIM

4-SPEEO. 4-POLE INDUCTION MOTOR
LARGE 11" TURNTABLE
COUNTER WEIGHTED TONE ARM
MUTING CONTROL
CHANGER CONTROLS., STOP/START/AUTO.
16/33/45/78 RPM, SELECTOR. 7"/10"/12"
ALL PHONO LEADS AND A.C. CORO FURNISHED.
YOU MUST HAVE A MAGNETIC INPUT ON YOUR AMPLIFIER
TO USE THIS CARTRIDGE

THANGER BASE CA-68 BLACK PLASTIC WITH TRIM. DUST COVER, CA-75.

CHANGERS

MODEL A-70

PRICE EACH

95

SUPER HEAVY DUTY This is our hest yet to sell

THE MARQUIS

SPEAKER CABINET MADE BY ELECTRO-VOICE



THE CABINET IS MADE OF 1". 7 PLY FURNITURE PLYWOOD. MAHOGANY VENEERED, BEAUTI FUL BROWN FINISH, CANE GRILL CLOTH FRONT.

SIZE 1 OF CABINET 291 .. HIGH, 184 ... SPEAKERS:

HIGH COMPLIANCE C177A, GOODMAN 12" 24 Ib CERAMIC MAGNET WOOFER FULLY ENCLOSED IN BAFFLE 54" MID-RANGE SPEAKER JENSEN HORN TWEERER,

CONDENSER TYPE CROSS-OVER. FREQ. RES. 35 to 20,000 CPS.

Stock No. M-300-M 95

## NEW WEATHER MATIC RADIO HOTTEST ITEM FOR 1972

## AM/FM Stereocast Weather-Matic Radio

Come rain or shine, this portable radio lets you now the weather ahead of time.

know the weather ahead of time. Just push a button anytime, day or night, and you instantly get the local area weather report, provid-ed by the U.S. government weather service. The RPA10 is a high-power portable AM/FM radio. Operates both, on batteries and house cur-rent (built-in AC adapter). Slide rule tuning. Superb. sound from the advanced-design Unicone speaker

sound from the advanced-design Unicone speaker Sterao foor. Special circuitry allows you to enjoy the exciting sound of FM stereo by simply plugging in the new Sanyo Stereocasi adapter to similaritunized device that uses advanced integrated circuits (IC) to receive decode, and amplify FM multiplex broadcasts in stereo For your listening enjoyment a stareo headphone is included with this accessory. Music news sports, weather, even stereo time, anywhere



#### Model RP7410

#### Features:

- Hi-performance portable radio that receives AM. FM or FM stereo (with optional Stereocast adapter)
- Weather-Matic pushbutton funing . consisted 24 hour a dey. U.S. government weather broadcast on fixed frequency of
- Advanced-design Stereocast built in, to add FM stereo listening
- . Operales on house current or batteries
- a Unique Unicone speaker
- · Hi/Lo tone control

## AM/FM Solid State Radio EQUIPPED FOR FM STEREO

RP5310

BANYO

The powerful portable

An AM/FM radio about the size of a book Proofes volumes of vibrant rich sound from the large
divanced design, Samo Unicone sceaker. Slide
ule luning for precise station reception Operates
in penight batteries, or house current with the
principal AC adapter accessory.

The social is easily to clarge who these vibrates and

This radio is ready for stereo wherever you are

This radio is ready for stereo wherever you are Special circuitry allows you to enjoy the exciting sound of FM stereo by simply plugging in the new Sanyo Stereocast adapter (optional). The Stereocast adapter us a miniaturized device that uses advanced integrated circuits (IC) to re-ceive, decode, and amplify FM multiplax broad-casts in stereo. For your listening enjoyment a stereo headphone is included with this accessory.

- a AM, FM or FM stereo reception (with optional Stereocast adapter)
- Battery operated or house current with optional adapter
- Advanced-design Stereocast built in, to add
   FM stereo listening
- Unique Unicone speaker
- e Compact size
- a Hi/Lo tone awitch



## AM/FM/HPS 3-Band Solid State Radio



Our traveling performer.

A portable that gives you a choice of 3 bands to salisfy any listening mood. AM, FM and High Public Service for a variety of action broadcasts police, fire, weather, to restry and conservation. The 24-hour U.S. government weather service position is specially indicated on the tuning dial for instant weather.

Superb sound with its big 4 inch, advanced-deaign Unicone speaker. Operates on both DC battery power or AC house current.

All this and stereo, too. Special circuitry allows you to enjoy the exciting sound of FM stereo by simply plugging in the new Sanyo Stereocast adapter (optional). The Stereocast adapter is a ministurized device that uses advanced integrated circuits ((C) to receive, decode and amplity FM multiplex broadcasts in stereo. For your (istering enjoyment a stereo headphone is included with Mis accessory. If a one radio that has everything.

#### Features:

- e AM, FM end FM stareo reception (with optional Stereocest edapter)
- High public service band tunes you in to police, highway patrol, fire, lorestry, conservation and U.S. government wsether
- . Operates on house current or batteries
- Advenced-design Stereocast circuitry built-in to add FM stereo listening
- e Big 4 Unicone speaker
- e Farohone
- e High power amplifier

## AM/FM Digital

Clock Radio RM5410

EQUIPPED FOR FM STEREO



This is one digital clock you can see "by the

dawn's early light." Or without it.
It's big, lighted numerals come through any
drowsy fog A super quiet, flip-type digital clock
with a 24 hour alarm — music or buzzer, Auto-

matically re-sets daily. Also has a sixty minute sutomatic sleep timer. The radio has brilliant, full fidelity sound. The reason: a large advanced-design Unicone speaker. advanced-design FM circuitry and high output

Push buttons for selecting AM, FM, and auto-

matic or manual clock operation

matic or manual clock operation.

Special circuitry allows you to enjoy the exciting sound of FM stereo by simply plugging in the new Sanyo Stereocast adapter (optional).

The stereocast adapter is a miniaturized device that uses advanced integrated circuits (IC) to receive, decode, and amplify FM multiplex broadcasts in stereo. For your listening enjoyment a stereo headphone is included with this accessory. It's the soundest investment in sound steep any-

- e AM, FM and FM stereo with Stereocast
- · Pushbutton AM, FM selector
- s Super quiet, easy to read. Hip-type time numerals
- Advanced-design Stereocast circuitry to add FM stereo listening
- e Integrated circuits (IC)
- e Large Unicone speaker e Earphone Included \$3



AM/FM Stereo Radio



Stereo-to-go, Ideal for the patio and beach,

Either stereo or "mono" sounds great with this model it has twice the output power of most port-ables. You can enjoy the superb sound of FM stereo through this sets two built-in speakers...

with the stereo headphone that comes with it.
Operates on house current with an AC edapter

For in-home stereo listening, the unit may be used with external speakers or as a stereo tuner with a hi-fi system.

#### eatures:

- AM, FM and FM stereo reception
- Rich, full fidelity sound quality
- Two, built-in, advanced design Unicone speakers
- Two built-in amplifiers Stereo balance meter
- s Operates on batteries or house curren

AFC circuitry

- Jack for use with stereo headphone or extension speakers
- Stereo headphone includes

RB9000 .909

STEREO CAST

ADAPTOR

RB9000

95

Stereocast Adapti FM Stereo Adapter-Amplifier

#### HOME ENTERTAINMENT AM/FM/FM Stereo Receiver SYSTEM 2/4 Channel 8 Track Cartridge Player DXL5480 360° Bass-Wave Speaker System

25 watts

EQUIPPED FOR 4 CHANNEL STERED

This compact stereo system receives AM and FM/FM stereo broadcasts, and has a built-in 8 track cartridge player for both 2 channel and discrete 4 channel pre-

recorded cartridges

The cartridge player incorporates 2/4 channel head
and 4 pre-amplifiers, it plays back 2 channel tape
certridges through the systems's power amplifiers, and

4 channel cartridges by adding another stereo &



DXL 5480 IS A TOP QUALITY SYSTEM EQUAL TO THE VERY BEST.

Specifications: 8-TRACK TAPE PLAYER 2/4 channel

Four Pre-amps Tape speed: 336 ins 50 db 50 - 12,000 Hz Frequency response:

18%" (W) x 107 (D) x 4%" (H)

25 pounds Weight: Accessories optional: Sanvo Decoder 4

25 watts Tone controls

Frequency range AM: 540 - 1600 KHZ FM: 88 - 108 MH2

360" Bass-Wave speakers SX802 7½" (W) x 7½" (D) x 12%" (H) Power source:

120V. 60 Hz Phono or external tape player Inputs:

Tape recording output Stereo headphone jack Stereo 4 channel output for use with Sanyo Decoder 4 (optional accessory)

Speakers:





Craig 8-TRACK UNITS...

Formally sold for You're way shead of the pack with this complete 8-track stereo system. Plays up to 80 minutes without cartridge change. Electromagnetic latch releases cartridges automatically. Speaker unit Beautiful Walnut finish, 8½W x 11H x 4½D.

Separate volume, balance and tone controls, Combination program-change and eject button.14 watt watts per channel) Player size; 8-7/8 x 5H x 101/D

Stereo Eight-Track Tope Player System. This smartly styled cartindge player with separaté speakers features a simple combination program change and cartridge eject button, volume, belance, and tone controls. Has black and bringer styling and wainful grance limsh. Adds. "home" mileage to your outo tape collection, Model 3205 Ship. Wt. 26, Ibs.



AM/FM Mini-Stereo Receiver System

INCLUDED

ADAPTDR

cable at the season and the season as the season as the season at the se speaker position.
7" W x 7%" H x 3%" D (apeaker units)

Solic sittle including integrated circuitry • Automatic stereo switching with indicator lamp and AFC - Speaker, phono and tape player jacks - Convertible speaker units - ALC - Back-lighted slide rule dial with vernier tuning - Separate off/ on slide switch Walnut finished wood cabinet with matching speakers • Rotary function selection, 6 watts peak (3 per channel), 14" W x 3" H x 8" D (main unit)

THIS UNIT SELLING AT \$79-50 is the LIST PRICE IS EQUAL TO OTHERS PRICED AT \$99.50

## **NEW AUDIOVOX**

PORTABLE CASSETTE RECORDER WITH BUILT-IN-MIKE THE CONDENSER MIKE IS FANTASTIC RECORDS AND PLAYS BACK

Compact, attractive, and easy to operate, the C-748 embodies a built-in condenser microphone and a single all function control. Snap-in/Snap-out AC adaptor replaces battery compartment. DIMENSIONS: 4" W x 6-3/4" H x 1-5/8" D

STOCK NO

McGEE SPECIAL PRICE

CRAIG MODEL 1504 FM/AM/FM STEREO SYSTEM

Compact ... fits neatly in bookshelf, cobinet or on table. Sol-Id state . . .. featuring AFC, vernier tuning, rotary function se lector, volume, balance and tone controls and stereo Indiestor light.

REG. WAS \$119.95



## Wollensak



..... 40 — 18.000 Hz ± 3db @ 7½ ips 40 — 15.000 Hz ± 3db @ 3¾ ips 0.15% RMS @ 7½ ips 0.20% RMS @ 3¾ ips

Greater than 50 db @ 71/2 and 31/4 ips

7 V2 . 3% . 1% ips

Greater than 50 db 8 watts per channel EIA

Regular \$229.95 SAVE \$75.00

STOCK NO. PRICE 6340

Operates Vertically or Horizical BLACK and SILVER FIMISH All Solid State...16 watt Stereo output

Pre-amp Output 0.5 volts (each channel) Microphone Input: 1 mV, low impedance 25-50 mV

Pre-amp Input: Track Width: 16 1/2 " wide, 14 1/2 " high, 10 1/2 " deep (with speakers) Size:

22 pounds (with speakers attached) 50 watts, AC only Weight: Power Consumption:

speeds • 2 Motors • Push-Button Istereo output amplifier • Automatic

4-track stereophonic recording controls / Separate Accoustic Tape shut-off . Stereo headphone playback • 4-track monophonic suspension speakers • Open-front jack • Low impedance wide range recording/playback • 3 Tape microphones

threading . Solid state 16 watt



PORTABLE CASSETTE RECORDER RADIO **MODEL 4410** and AM/FM List price \$84.95 SAVE \$35.00

STOCK NO 4410

PRICE 5

THE " TAKE ANYWHERE" CASSETTE TAPE RECORDER

Records & Plays mono., cassettes Plays stereo cassettes mono. Autometic record level Remote control Microphone
4- Position switch controls all modes.

MENTS: 4, 1 V.'C' CELLS OR 1171 AC. SIZE: 3"X81"X10" (INCLIDING HANDLE) . WEIGHT 3; US. ESS BATTERIES, AM/FM RADIO SPECIFICATIONS: AM-535 TO 1605 KC. FM-88-108 MC. AFC ON FM.

262I CRAIG A REAL BEST BUY ITEM

#### PORTABLE CASSETTE RECORDER

- AUTOMATIC SHUT OFF SYSTEM AT BIRD OF TAPE
- AUTOMATIC LEVEL CONTROL (ALC) RECORDING
- BATTERY CONDITION INDICATOR
- BATTERY OR AC POWER, WITH DETACHABLE AC COL
- BUILT-IN AUTOMATIC BATTERY RECHARGING CIRCUITRY

The CRAIG 2621 Portable Cossette Recorder is a versatile solidstate unit utilizing pocket-sized cassettes and affording instantreplay capability. If incorporates advanced features such as natic Lavel Control recording and CRAIG'S Automatic Shut-Off System to conserve battery life when the end of the tape is reached. Convenient pieno-key controls are provided for tape notion (rewind, fast forward, play, end stop) and recording. The bettery condition indicator werns when the built-in AC power supply should be used to recharge optional rechargeable batteries. The detachable AC cord and remote-control microphone

#### TECHNICAL DATA

Recording Time: 60 min. total with C-60 Cossette, more with extended-play cossettes 60 seconds (C-60

Tape Speed 1% ins

Wow and

Less than 0.35% rms Output Powers 800 mW peak

Signal/Noise Ratio:

Better than 35 dB

Erase System: DC

Microphone, 10K ohms -70 dBm

Earphone/Ext. Speaker, Culputs

2% Inch Speaker Size: Dynamic, 200 ohms, Microphone:

oth remote control switch

Five "C"-size cells or 120V 50/60 Hz, 2 wells 514 "W x 296"H x 1014"O Weight: 3% (b) (inc. bettery)

Microphone
Accessory Pouch
AC Cord
Accessory Carrying Case

Footswitch Stathscope Earphone Recording Connector

# SOLID-STATE COMPACT

The precise sounds of frequency modulation are cap-tured in this compact and handsome receiver of both FM and FM Stereo broadcasts Solid-state engineering means dependability and years of service.

GIBBS STEREO AUTO RADIO

Dimensions: 8-1/16" x 1-3/4" x 6-13/16"

## 35 WATT HI-FI

AM/FM STEREO CAS-SETTE RECORDER AC 117V. MUSIC CENTER

all solid state all solid state \$11995 27 transistor, 14 diode 11995 USE WITH ANY SPEAKERS



For home builders who want good stereo will making a big investment the SHC-40f is ideal combines a high quality cassette section with a 2-band on an attractive malnut have Recording unto cassette steren, and from external sources. The tadio's FM sec has automatic multiplex circuitry of is by single action plano-type keys and cassettes po or the chamber at the push of a button. Included is unter, remote control mike, and left right records 8-1 4" v 1-14 16" snelers \$5 waft numbuls 50

# CSC.

and AM/FM Stereo radio. McGEE 1499



CSC-505FW, riere's the periest portable stereo combina bon! You get a stereo cassette recorder and a sensil AM/FM/FM steteo radio and two detachable stereo speak ers and two quality mikes? All solid state with 24 transistors (10-transistors fadio). Psano-key push button street consette controls for easy, accurate recording. Irom temu-control ON/OFF miles or directly from the 3-band radio Radio features new wide dial for quick luning of AM, FA and Atuitiples stations disch 15 watt output with 100-10,000 Mz response Fold-away carrying handle 11 lbs. Truly versatile, AC/battery operation Tauly portable

Deluxe AM/FM Digital Clock Radic 8 3/16 X 4 1/4 X 5 1/4 IN...

Cornegie. DCR-F8AC 10-Transistor

Sale Price

0-Transistor \$24.95 Solid State. SHIP WY. PLBS.



Wake up to AM/FM Music

Plus diarm buzzeri17 volts activery good tone dualty from this up, to the minute clock radio. You vill get hours of enjotment for years, he big 31m, speaker gives good tone the radio 15 big enough to sound good and small enough to put antwhere.

All solid state micro-compact cassette recorder/player



• 95 CTR-9001 push button AC Adaptor tape transport \$4.95

Powerful 2-V2" PM dynamic speaker

4-Band

Small Aircraft

Pilots

the neat cassette recorder takes \$3.90. C-80 or \$6.90 cas effets and plays 'em back loud and clear at the push platton. Switt (ingerij) tape transport control for Record evantd, Forward (Playback). Fast Forward. Stop, and a stra-convenient TAPE-UP button for quick cassette change thas a useful array of Jacks that will double your tun. For the microphone, remota ON-OFF control on mike, an auxiliar ack so you can record directly from other sources and a

O PERATES ON 4 C CELLS OR 117 Frequency range: Volts AC.

SALE PRICE FM 88-108 MHz

RF-800AW. A deluxe radio that offers 4-hand recep-

on, full portability and powerful delivery—it has its or irrying handle and a handsome featherette sheath. 4 transistors make it highly sensitive to ESI ASI/EW AIR se special AfR hand brings in all the specialized, weather nd easigational reports for righ, rlear delivery there's a test oval speaker with larger dimensions than usual sets. Or afteries or AC the TRI-800A\V gives equally impressive re

uits. Carries nasily at \$1 lbs and measures a compact /16" s 6-7/8" s 3".

Write For The Latest

CROWN

1972 Catalog and

Price Sheet

95 LW 150 - 400 KHz

AM 520-1605 KHz

AIR 108-140 MHz

SIG 3 X B

2016

SOLID STATE MODEL 7TV-1 VHF/UHF ALL CHANNEL 9" TV 7" (18em diagonal 33-WITH FM/AM

TRANSISTOR 2-BAND RADIO 9TV-301

AC/DC or CAR BATTERY AC/DC or CAR BATTEMY
Power source: AC, seclusively designed rechargeable battery(optional), or car battery with car cord(optional) Power output: 500 mW Speaker: 2-3/4×6-1/8 PM dynamic nensions (H x W x D): 7-1/4" x 9-5/8" x 8-1/4"

BUDGET PRICED

(ROWN SOLIO STATE

TAPE RECORDER TELEPHONE VALET
AUTOMATIC
TELEPHONE ANSWERING
AND MESSAGE TAKING
MACMINE
TOUR OWN PRIVATE ANSWERING SERVICE.
USING YOUR OWN TAPE RECORDER MODEL \$99.95

Respinore (act)

But that's not all. We also gave it a top quality powerful permanent dynamic speaker. And because it is from Crow you get all the accessories. Like an earphone patch of dynamic microphone case fine leather title of dynamic microphone case fine leather title of the Direct or Indirect 7 transistor CROWN TRF-800- Telephone Coupling

\$249,95

CTA-4450 The most versifile automatic answering sys-tem of them all: hower mas another telephone call agun CROWN's Telephone Vales instancy assess even single call

**CDM-10** CROWN

Obd-10. The period piece of other endergroups to the into-date secretary. Push in a cassembly press about on an user an hour-and-a-half of distation. It is simple to unmechanically-minded typish yet contains the rest in quality (assette technolog)

latest in quality cavette technology, and a unique took pedal lith under the desk and can stop and start the message at the tap of a time. If even has CROWN's ingenious. "Auto Repeat" function that takes comback through the last 7 seconds of the message. Cassettes slip in tast and pop-up at the push of a button start and pop-up at the push of a button case.

Works on halteries or AC Complete with stethoscope

CROWN

Fully Automatic Compact Take It Any Where

4.0 lbs

Cassette Recorder With Built in. AC or 4-C Cell Operation 9-1/2" x 6-3/4" x 1-15/16"



CTR-320W. The tirst truly portable and automatic Can ette tecorder for instant action? Hang this all new audio narvel from your shoulder and just slip a cassette in inply closing the chamber automatically staits playback other tassette unit has this spesial teature? And that in other tassette unit has this special teature? by the great beginning." Push one button and soutre re-

CTR-8750

Battery/AC operated, all solid state portable compact cassette

recorder and player.

all solid state. dynamic

microphone 2-1/2" round. PM dynamic

2-1/2"× 7-5/8"× 7-11/ 16

his compact functional set cellent recording and playing are tound in the CTR-8750 full tone and volume controls. A tape up button this is the casserte for masy removal. There's also a useful reevel indication lump and a full set of jacks for versatile if The included mike var she operated by its own remotest rol switch. Comes in a modern, slim tableet with built

## CROWN Plus Cassette Recorder

OPERATES ON 4 1 1 VOLT C CELLS AND 117 VOLTS A.C 9-1/8 " X 11-1/4" X

2-15/16

3- BAND Radio

Radio frequency range FM 88 - 108 MHz AM 520 - 1605 KHz SW 6 - 18 MHz 6 lbs

CRC-410FW. Here's an all push mbined with AM/FM/SW reception one attractively styled and eminently purtable unit ou get seculity with three different types of radio promatic tuning Indicator" which lights up when you dial the lation's dead center. Record directly from the 3-band tadio from the included mike with remote control on/oft ilt for long-lite with practical carrying handle

McGee Radio Co. 1901 McGee Street, Kansas City, Missouri 64108



MIDLAND

HIGH POWERED

2 WATT. 3 CHANNEL HAND HELD TRANSCEIVER

> 13-TRANSISTOR Model 13-724



NEW

Variable Squelch

CALL SIGNAL

8 pen-lite Cell not

included

. 13-Transistor Circuit 3-Channel Operation (CHANNEL 11 Crystals Supplied)

**Call Signating** Circuitry

95

9

- Deluxe Superhet Receiver with Tuned RF Stage
- Push-Pull Class B High Level Audio
- Full Two-Watt Input
- Variable Squelch Control
- Shoulder Strap
- Battery Meter
- AC, Charger & Earphone Jacks
- Plug-In Crystals
- AGC Circuitry
- Telescoping 60" Antenna
- All Metal Cabinet with Chrome Grille & Trim

## 11DLAND® **Finest** Base/Mobile CB Unit

WALKIE-TALKIES



5-WATT, 23-CHANNEL

Model 13-876 Ship, Wt.

Pi Type Network 8" DEEP.

An exciting new 23-channel CB communicator that is pre-equipped to operate as a 117 volt AC base or 12 volt DC mobile station unit. Frequency synthesized crystal-controlled transmit and receive on all 23 channels with no extra crystals to buy. Dual conversion receiver has mechanical filter to give high-gain sensitivity and extra selectivity. Pi-type network assures optimum RF output and perfect antenna impedance match, Full S-watts input transmitter power. Big sound power from a 5°4 x 3° PM dynamic speaker. Model 13-876

WATT 6 -MIDLAND CHANNEL TRANSCEIVERS CHANNEL WATT 11 TRANSISTORS 11 TRANSISTORS

- Including Revolutionary

Model 13-770 \$6995

TUNED RF & 7 STAGES

PUSH-PULL AUDIO BATTFRYCHARGER JACK ON BOTH MODELS

EARPHONE JACK ON BOTH MODELS

ADAPTOR JACK JACK SQUELCH

BATTERIES ARE NOT INCLUDED VARIABLE SQUELCH MODEL 13-770. 5 WATT. 6-CHANNEL TRANSCEIVER WITH CHAN. 7 PLIG-IN RYSTALS INSTALLED, SUPERMET INTEGRATED CIRCUIT WITH CALL SIGNAL AND QUELCH IN ALL METAL CASINET WITH DIE-CAST FRONT. SIZE 92 x 2-3/16 x 3 x 0 PERATES ON B "AA" CELLS, IZ-VOLT AC ADAPTOR, ON 12-V ALL ABLE (ALL EXTRA), MAS 60" ANTENNA, 2 3 SPEAKER-MIKE & CARTY CASE.

MODEL 13-700. 1-WATT, 2-CHANNEL TRANCEIVER WITH CHAN. RYSTALS INSTALLED. SUPERHET CIRCUIT WITH CALL BIGMAN SQUELCH IN ALL METAL CABINET WITH 2-5/8" W. x 2-1/8" D. OPERATES ON EXTRA) HAS 13 SECTION, 60" ANTER

## power-charge switch. External power-charger jack, earphone jack, external mike jack, PA jack, external attenna jack, 974" high x 31/2" wide x 2-3/16" deep. Included: Leather case, carry strap, instruction booklet. MIDLAND **BASE STATION**

6 Channels avoilable. Channel 7 (27.035 MC) plug-in crystals factory installed in number 1 position. Superheterodyne with RF amplifier. Sensitivity better than 1.2 uV.

Dual purpose, 6 channel, crystal-controlled ascillator system transmits call signal for establishing communication and AM vaice transmission.

5 Waits.
12-Valts DC (8 pentite batteries self-contained ar external
12-Valts DC source not included).
6-channel selector switch, full variable squetch with PA posttion, call signal switch, Off-On valume control, external
power-charge switch.
External power-charges lack, agrabane lack external mike

17 transistors, 3 diades, 1 thermister, 1 varister.

AC POWER SUPPLY **wc4** Less H264. 12-Volt A 0 0 0 D.C. Amp Model 18-805

a, 12, 23, Channel \$ 3-150,13-860,13-870

ALTERNATOR-NOISE amperes. Maximum current 25 FILTER



MAGNETIC MIKE HOLDER

ō Stock No. MH 200

verful magnet attaches to any st surface. You can hang mike up n any surface such as car dash

## MIDLAND

5 WATT, 23 CHANNELS HAND HELD TRANSCEIVER



23 Channel Operation All Crystals Included

Model 13-795

Use as CB or PA

Deluxe Superhet Receiver with Tened RF Stage . Dual Conversion Push-Pull Class B High Level Audio Variable Squelch Control . PA Switch Dupl-Purpose Motor Reads RF Output Signal Strength and Battery condition

ତିହାଁ

\* AC. Charger & Earphone Jacks BATTERIES ARE NOT INCLUDED Operates on 8 peniight batteries, 10 Nicad rechargeable cells, 12-volt AC adaptor, base station power supply, or 12-volt auto cable, (ALL Optional)


Security strap & leather case

\* Telescoping 65½" Antenna \* All Metal Cabinat with Chrome Grille & Trim

Size: 94"H x 314"W x 214" D Shipping Wt. 7 lbs.

## 23-CHANNEL CRYSTAL-CONTROL TRANSCEIVER

MIDLAND



Dual Conversion Super Het, with

Mechanical-Filter.

Call Signal.

Duel-Purpose Meter Reads RF Output and Signal Strength.

PA Switch.

Variable Squelch.

Transmitter

Transmitter All Crystals

INCLUDED \$129 None to Buy !

Bereiner

Sem. Frequency Toleronce: Transmitter

Fower: Receiver Sensitivity Secritivi Recalese Selectivity: Sawelch 23 channel single synthesized

system
12-channel dual tenversion
superheterodyne system
18 sifican transistors, 2 silicon
diodes, 6 germanium diodes,
1 tener diode

t 005 (-20°C to 50°C).

5 waits input power to final stage. 1.0 eV or better for 10 db S/N. 40 db down fi 10 KC

IuV (nominal) Automatic 12-16 Voits DC 6" widex2'h" high#815" deep.

## MIDLAND

Model 13-700

3495

TUNED RF & 3

IF STAGES

PUSH-PULL AUDIO

5 WATT, 6 CHANNEL Mobile-Base \$

Transceiver

PUSHBUTTON CHANNEL SELECTOR



13 Transistor and 3 Diades tuned RF stage and 3 IF stages.

Midland Integrated Circuit Channel 9 Crystals Installed

Single Conversion Superheterodyne · Automatic Naise Limiter

Tronsmit Indicator Light

 Audia Output over 2 Watts Speaker/Microphone - 4' cailed cable · Power Source: 12 Volts D.C.

Mounting bracket and Auto cable included Variable valume & Squelch controls

Receiver Sensitivity: 0.5 uv or better Transmitter Power: 5 watts input to final amplifier.

Handsome Design:

Metal Cobinet covered with padded Black leother-groined vinyl. Cabinet Size: 4%" Wx6½"Dx2"H Shipping Weight S lbs.

McGEE RADIO CO., 1901-07 McGEE STREET, KANSAS CITY, MISSOURI 64108

# BIG SCOOP! 10,000 YDS. GRILL CLOTH LATEST WEAVES \$199 SQUARE YD. \$379 2 SQUARE YDS.

LATEST WEAVES

36" x 36"



Stock No. 4108302 BROWN & GREY CLOTH BLACK PLASTIC CROSS WEAVE

4016104

BRIGHT GOLD

WHITE & BROWN

Plastic Background

Stack No. 4117904 WALNUT BROWN DN BROWN PLASTIC DPEN WEAVE

Stock No.

4087209

BEAUTIFUL

SOLID

BLACK



4042304 CINNAMON BROWN BLACK & WHITE



Stock No. 2-9-33

WALNUT BROWN LIGHT BROWN lastic Interweave



4100404 WALNUT BROWN DN

BACKGROUND

LIGHT BLUE WITH BLACK FLECK White Hairline

SALE OF PLASTIC GRILLE CLOTH 2000 YAROS OF THE FINEST QUALITY

4089601



Stock No. 4056004 COCOA BROWN WITH LIGHT BROWN FIGURE

BLACK PLASTIC SPECIAL 50 SQUARE ASSORTED 72" WIDE GRILL CLOTH Major American Migrs. latest Grill Cloth 6 or More different cloths, Notice amolter disen

50SQ

ATTRACTIVE WAFFLE WEAVE MATCHES DILED WALNUT CUT FROM BOLT 54" WIDE AT LESS THAN MANUFACTURERS COST SALE PRICE

RUNNING YARD 36" X 54"

Stock Na. 2036-2AC

Shipping Wt.

10 SQ. YARDS FOR \$22.50 A VERY POPULAR SELLER

New weave looks like coarse Linen and is Light Buff color with White Cross Flecks Stock No. 445-4 36" Wide



ACOUSTONE STEREO HI-FI GRILLE CLOTH

(A DIVISION OF NEWCASYLE FASRICS CORF.) A ADMITTMENT TOTAL

(No Lagging

POPULAR SARAN PLASTIC WITH CANE WEAVE TODAYS MOST POPULAR PLASTIC GRILL CLOTH



Either style 52.95 per yord.

Sold off o 36 in. bolt. 10 running yards for \$26,00

Stock No. 24 X 75

Buff crossing Buff on Black beckground. Matchee Blond or lighter
finished Bafflee or Cabinets.

Stock No. 24 X 75-3
Buff crossing dark Brown on Black
background. Makehea Weinut, Mahogany or any dark finished cabinet.

METALLIC WEAVE 36 in. wide. \$2.39 per y



Stock No. T-8 Grey on Black with Metallic Silver interweaving cross thread, is ideal for use with any cabinet finish.

for use with any cabanet linish.

Stock No. T+12

Beige on dark Brown with Metalike
Bronze interweaving cross thread,
For use with Mahogany or Walmut.

Stock No. T-28
Buff on Block with Metallic Gold
Interweaving cross thread, Matches
Mahogeny or Walnut finishes

Pagular White Black and Grev FINEST ALL PLASTIC GRILLE

> 36" WIDE Any Length WHITE Platinum Gray BLACK

Our most popular seller. Sold oil bolt 36" wide and in any length, 33 69 per running yard. Popular with sound installers. Fine accountical qualities, Available in Solid Black, Solid White or Platinum Gray, Spacify

3021 White S3.69 Sq. Yard 3072 Walnut 2005 Platinum Gray 1300 Black S35.00

59. Yds. 535.00 SQUARE

Stock No.

MCGEESPECIAL

GRILLE CLOTH ASSORTMENT 10 CUT PIECES 12" Square or Better

\$1.29 OF PACK

Manufacturers Latest Model's of Gnile Cloths Mostly Brown & Greys Stock No. SWP-10

51 99 SQUARE LATEST

Stock No. 4044600

LIGHT BUFF ( BEIGE)

4059400

SILVER AND BLACK
PLASTIC STRIPE
ON
LIGHT GREY PLASTIC

THIS ONE ONLY 52.49 Running 4d.

4373000 METALIC SILVER WHITE PLASTIC Stock No. 4524709

GOLD FLECK ON BLACK, open weave

STOCK NO 4119004

THE PARTY OF THE P

BROWN over BLACK PLASTIC BACK GROUND

STOCK NO 4133304



BROWN open weave BROWN over BLACK PLASTIC



TAN CAIN over BLACK



LIGHT and DARK BROWN with BLACK over weave



BROWN and BLACK loose weave

STOCK NO 4126309 Louis an a be an inch gin ? Het i fin in auch fiebe die met rates mit es with gen a line of the

BLACK PLASTIC open weave

NEW 1972 GRILL CLOTH

STOCK NO 4097303



BLACK PLASTIC BACK GROUND PLUS BROWN CORDS BRIGHT RED OVER LAY

> STOCK NO 4129103



**BLACK PLASTIC BACK GROUND** WITH MAROON RED FIGURE OVER LAY

> STOCK NO 4100002



DARK OLIVE & BLACK PLASTIC BACK GROUND WITH LIGHT OLIVE GREEN RAISED FIGURES

> STOCK NO 4068902



BLACK & BROWN PLASTIC BACK GROUND VERY DARK OLIVE GREEN OVER LAY

Do Not Use This Space

## McGEE RADIO CO

1901-07 McGEE STREET

## KANSAS CITY 8, MISSOURI

PHONE: VICTOR 2-5092-

ON FREIGHT OR EXPRESS ORDERS If your station has an agent do not send money for shipping charges. If there is no egent, send edvence payment for charges. They are the same either way.

FILL IN BELOW AMOUNT ENCLOSED

PART PAID \$	
SHIP CO.D. FOR BALANCE	

HOW SHALL WE SHIP PARCEL POST \_\_ FREIGHT - UP5 EXPRESS

EFD ( KANSAS & MISSOURI) MERCHANTS. SAME AS ABO \_MISTLETOE. IOKALHOMA

ALL STATES WHERE

AUTO-CHECK PAYMENT METHO

AUTO-CHECK PAYMENT METHO
We will accept your check for the amount of your order. To save tim in making refunds or remitting the balance of postage due, it is best use our "Auto Chrek Payment". It all your order and send a signed chewith the amount left blank. We will in your check for the exact amou to pay for the order and postag (You may make notation on yo check that is is not good over a cetain amount). Be sure to make limingh enough to cover sufficient postage. Invoice included with your oder will show the exact amount yo check was made for.

## **EXPRESS**

All fragile merchandise such as recechangers, large speakers and fluor cent fastures should he shipped Express whenever possible. Do include allowance for transportat wharges on express shipments. The exact amount will be collected who your order is delivered.

#### INSURANCE FEE

-01	to	15.00 20
15.0 l	(0	50.00
50.01	to	100.00
100.01	to	150.0050

## PARCEL POST

A table is provided to ticure postain on parcel post orders. Be sure to a low enough for postage and insurance on C.O.D. shipments via parcel post acharger is made for collection & the post office (C.O.D. fee) and money order fee for sending the amount to us. These are in addition to the regular rate charged for postage. Send full remittance with your order and save C.O.D. and M. (fees.

The state of the s

	Local	1 and 2	3	4	5	6_	7	. 0
	KI -	Up to 150 miles	150 to 300 miles	300 to 600 mules	600 to 1,000 miles	1,400 to 1,400 miles	1,400 to 1,800 miles	Ovey (_Brki miles
2	\$0, 50	80, 65	\$0,70	\$0, 75	\$0,80	\$0, 90	\$1,00	\$1.05
3	, 60	.75	. 90	. 85	. 95	1.10	1, 20	1.35
4		, 80	. R5	, 95	1, 10	1.30	1, 40	1.60
5	70	. 85	. 90	1. 05	1, 20	1. 45	1. 65	1, 90
6	70	. 95	1.00	1, 15	1, 35	1, 60	1.85	2.10
7		1, 05	1. 10	1. 25	1.50	1. 75	2.10	2, 35
8		1. 10	1, 15	1, 35	1, 60	1. 90	2, 30	2, 60
9		1.15	1, 20	1, 45	1, 75	2.05	2, 45	2, 85
10		1.20	1.30	1, 55	1, 90	2, 20	2, 65	3, 10
	40		1. 35	1, 60	2.00	2.30	2, 85	3, 35
11		1.25	1. 45	1, 70	2 10	2, 45	3, 05	3. 55
12	85	1. 35	1. 55	1.88	2, 20	2, 60	3, 25	3. 80
13		1. 40	1, 60	1.90	2. 35	2.75	3, 45	4, 00
15		1, 45	1. 65	2,00	2, 45	2.85	3, 60	4. 20
10.,,	1 900		*1 00	0.00				
16	. 95	1, 55	1.75	2.05	2, 55	2. 95	3, 80	4. 40
17	1.00	1, 60	1, 80	2, 15	2, 65	3, 10	3, 95	4.60
18	1.00	1, 65	1.90	2, 20	2.75	3, 20	4, 15	4. RO
19	1.05	1,70	2,00	2, 30	2.85	3. 35	4. 30	5.00
20	1, 05	1, 75	2, 05	2, 40	2, 95	3, 50	4, 50	5. 20

TERMS: Send full remittance plus ample poetage with orders up to \$5,00. Larger orders can be shipped C.O.D. when 25% remittance accompanies your order. It coets you less if you avoid C.O.D. orders by sending full remittance and ample postage and insurance with your order. Many of our customers are using the Auto Check Method of Payment as described in column at left. hills SOURI ORDERS: Include 3% Sales Tax or send State Tax Exemption Number.

STOCK

NUMBER

IOWA KANSAS MISSOURI
NEBRASKA VIRGINIA
NEW HAMPSHIRE WEST VIRGINIA
WISCONSIN

UPS, BLUE LINE AIR SERVICE TO CALIFORNIA,
OREGON AND WASHINGTON. RATES ARE MUCH
HIGHER THAN PARCEL POST, BUT CHEAPER
THAN EXPRESS OR TRUCK ON SMALL ORDERS.
EI: 5 lbs, 52.10. 10lbs, 53.70, 15 lbs, 5.30.
25 lbs, \$8.50, 35 lbs, \$10.10, 50 lbs, \$16.50

PAGE

QUANTITY

NAME STREET ADDRESS R.F D BOX NO POST OFFICE STATE ZIP CODE DATE...., PLEASE GIVE SHIPPING POINT IF DIFFERENT FROM POST OFFICE SHIPPING POINT STATE

PLEASE USE A LINE FOR EACH ITEM ORDERED

MAY WE SUBSTITUTE EQUAL VALUE? YES NO Put Total Price Here and Add This Column

MONEY ORDER

CASH TOTAL Price

Each

TYPE OR PRINT CLEARLY YOUR NAME AND COMPLETE ADDRESS

VE									
E N.									
OD			1000						
the ime the					100				
To-									
will									
age. /our cer-									
umit ost- ot-						-			
your							-		
cord	_							-	
via not							- 1		
The then						(8)	4		
*11011					EASE				
20 30					00 8	-	8-10		
40 50				ORDERS					
age				WEIGHTON MAST OF DERES \$5	1	7.9			
al- nce, post		The same		MANIMUM			- 54		
by d a the		1	100						
tion ost-									
O.						11/2012			
Y. N	Be s	ure to incl	ide enough U	PS or Parcel charges with this order.	=				
JDE	RANCI	2	ON PACKAGE	RE GIVING EXCELLENT PACKAGE SERVI S FROM 20 lbs. to 100 lbs YOU PICK UP A		4	المساج		
5	6		BUS STATION DO NOT REMIT	S. I CHARGES FOR EXPRESS, TRUCK of BU	Missouri custo Missouri SALE				
1,000	1,000 to 1,400 mules	1,400 to Over 1,810 1,800 miles miles	PHONE NUMBER	AREA CODE EXCHANGE PHONE NO.	PACKING FI	EE		30¢	
50, 80	\$0.90	\$1,00 \$1.08	COTTY NO	RCEL SERVICE is available from KANSAS to the following states; NEW YORK	P.P. Insuran	ce	1.54		
1. 10 1. 20	1. 10 1. 30 1. 45	1, 20 1, 35 1, 40 1, 60 1, 65 1, 90	1	NORTH CAROLINA KENTUCKY NORTH DAKOTA MAINE OHIO	PARCEL POS U.P.S. CH	ARGES	2172VS		
1. 35	1. 60 1. 75 1. 90	1. 85 2, 10 2, 10 2, 33 2, 30 2, 60	CONNECTIC	UT MARYLAND PENNSYLVANIA MASSACHUSETTS RHODE ISLAND	C.O.D. DEPO	SIT	4		
1. 60 1. 75 1. 80	2. 05 2. 20	2, 30 2, 60 2, 45 2, 80 2, 65 3, 10	COLUMBIA	MINNESOTA SOUTH DAKOTA MISSISSIPPI TENNESSEE	C.O.D. Bala		7 =		
2.00	2.30	2, 85 3, 3,	GEORGIA	MISSOURI VERMONT NEBRASKA VIRGINIA	HONEY ORD	ED			

DESCRIPTION OF ARTICLE

## BUILD YOUR SELF ONE OF THE GREATEST SPEAKER SYSTEMS OF EURUP WITH THE NEW PHILLIPS-NORELCO SPEAKERS IMPORTED IN U.S.A. BY AMPEREX 7



NORELCO SYSTEM No. 23 THE KING OF SPEAKER SYSTEMS

4.....AD5060/W8, for MID-RANGE USES: 4....AD0160/T8, 1....AD1256/W8 TWEETERS SEE INDEX FOR MORE NORELCO WOOFER SPEAKERS 1.....3 WAY CROSS-OVER NETWORK

SYSTEM COMPLETE WITH ABOVE SPEAKERS AND NORELCO SPEAKER MANUAL, \$84,95

Build your own speaker system and enclosure. Complete instructions 40 are given in the manual for building the enclosure and assembly of speakers When finished you will have a top quality system 20 12" High Fidelity Woofer second to none other.

Power handling capacity 40 wotts. Impedance 8 ohms. Shipping Wt. 27 lbs.

200 SYSTEM -23 COMPLETE


Frequency response curve for System 23 measured with speakers mounted in the enclosure.

\*\*\*NOTICE\*\*\*\*

ONLY ONE MANUAL IS SUPPLIED WITH SINGLE OR DOUBLE SPEAKER

1000 2000

SYSTEM ORDERS.



27

AD5060/W8

AD1055/W8

50 100 200 500Hz1 2 345 10 20kHz

AD1256/W

SYSTEM No. 17 -- WITH THE WORLDS BEST 10 inch SPEAKER USES:

1.....AD0160/T8,

For those who want the best and economy too! This is the system. It uses the best 10' woofer and components made. Also the enclosure is smaller in size. Cross-over frequency 7001iz and 3000 liz. Voice coll impedance is 8 ohms.


TWEETER MID-RANGE 1.....AD5060/W8, SEE OTHER PAGES
OF THIS CATALOGUE
FOR MANY OTHER
HORELCO SPEAKERS
1....AD5060/W8, MID-RANGE
WOOFER
1....3-WAY CROSS-OVER NETWORK
NORELCO SPEAKER MANUAL

All for \$44.95

Frequency response curva for System 17 measured with speakers mounted in the enclosure.



10" High Fidelity Woofer



POWER HANDLING CAPACITY IS

40 WATTS in the PROPER ENCLOSURE Shipping weight 15 lbs.

SYSTEM 17 COMPLETE

5000 16000 2000 AD 5060/ W8

AD8065/W8 SYSTEM 13 THE BEST 8" TWO WAY SYSTEM THAT WE CAN OFFER

1...AD0160/T8, TWEETER

1...2-WAY CROSS-OVER N.W.



8" High Fidelity Woofer

I...NORELCO SPEAKER MANUAL Impedance 8 ohms.

20 WATTS Power Ideal system for intermediate size baffle Shippina wt. 6 lbs.

SYSTEM-13



AD 0160/T 8

Cross-over frequency - 1500 Hz.



1...AD0160/T8

SYSTEM 3. THE BEST SMALL

TWEETER

AD5060/W8

AD-0160XT 8

MANUAL 100 PAGE NORELCO

TOLING 20

2 3 4 5



For building Hi-Fi speaker system enclosures.

Step by step con-struction of the enelosures.

Room acousties. Speaker dimentions and response curves.

PRICE \$1.95



3 WAY CROSS-OVER

Designed to use with 3 Speaker Designed to use with 3 Speakes.
TWEETER, MID-RANGE & WOOF
with 3 ohm voice coils. Cross-over
frequency at 700 and 3000 Hz. All
components are mounted on a printed elreuit
board. Inductance &
capacitor type. Size:
4" x 5½" long. Ship
weight ilb. Hook-up
schematic furnished.

schematic furnished. Stock No. Price 4304-07X \$7.95



## NORELCO 2 WAY CROSS-OVER

Capacitor and inductance type cross-over net work Can be used with any 2 Woofer and TWEETER speakers. Small size 2% x 4" long. Cross-over frequency 1000 Hz. Ship wt. 1 1b.

Stock No-3W999

Price \$4.95

