




LAFAYETTE RADIO

Sensational Winter Breakthrough!



NEW! TruTest STEREO/5 AMPLIFIER



- Individual Stereo Volume-Balance Controls
- For Both Stereo and Monaural
- Fully Wired — Ready For Stereo

Never
Before Such
Quality At This Price!

1095

One of the finest stereo values we have ever offered. This rugged, precision made dual channel stereo amplifier will amaze you with its fine quality. . . . Ideal for that low cost stereo system you're planning for your home or business. Perfect for converting your present console or portable to stereo. Provision for crystal or ceramic cartridges, 4 ohm output terminals accept most speakers. Size: 4 1/4" H x 5 1/2" W x 4 1/2" D. 115 volt 60 cycles. Shpg. wt., 5 lbs. PK-441 Net 10.95

LAFAYETTE BRINGS YOU A COMPLETE STEREO PHONO SYSTEM
AT A PRICE YOU CAN AFFORD




Now you can have genuine component stereophonic sound at the lowest price ever. Complete in every detail this system consists of: the TruTest Stereo/5 Amplifier (as described above), Lafayette ML-24 4-speed Turntable for 16-2/3, 33-1/3, 45 and 78 rpm records, easy to install pre-cut mounting board, Lafayette PK-171 Stereo Tone Arm with wide-range Plug-In Crystal Stereo Cartridge and .75 mil sapphire stylus

for stereo and monaural records. Completing the system are 2 of Lafayette's amazing 5K-109 miniature speaker systems. Housed in attractive mahogany veneer enclosures each speaker is supplied with 25 feet of hook-up cable and measures only 9 1/2" W x 7 3/4" H x 3 1/2" D. Shpg. wt., 20 lbs. PK-443WX 2.00 Down Net 33.50

3350

only 2.00 Down

LAFAYETTE MINIATURE DUO-REMOTE T.V. SPEAKER Remote Control Sound At Your Side!



450

- Not Only An Excellent Extension Speaker—Also Provides Remote Control Volume Of Your TV, Radio, Phono or Hi-Fi
- Adjust The Volume Of Your Favorite Program From Your Bed or Chair
- Mount On Wall or Use On Desk or Table
- May Be Used With Any Set — Only Minutes To Install

You will be amazed at the number of uses you'll find for this unit. The fine quality of the built-in speaker makes it perfect for use as an extension speaker anywhere in your home or office. It's small size makes it an ideal personal speaker when watching TV or listening to your phonograph . . . The dual volume controls provide independent volume control of the main speaker from your listening or viewing position or the remote's own self contained speaker. Attractive molded cabinet measures 4" W x 2 7/8" H x 1 3/4" D. Complete with 20 ft. of 4-conductor cable. Shpg. wt., 1 1/2 lbs. SK-145 Net 4.50

BSR MONARCH BSR 4-SPEED STEREO RECORD CHANGER COMPLETE WITH RONETTE STEREO TURNOVER CARTRIDGE

SPECIAL SALE! **22.50**

WITH EXTRA DIAMOND NEEDLE **24.50**



• FULL INTERMIX IN ANY ORDER • PLAYS BOTH STEREO AND MONAURAL RECORDS
The newest British made BSR Monarch featuring heavy duty 4-pole induction motor, with rumble-free, wow-less, low hum, automatic operation. Design and construction assure trouble-free operation and long life. Complete with Ronette's famous compatible stereo turnover cartridge with dual sapphire stylus. Dimensions: 12 1/2" W x 10 3/4" D — 2 3/4" below mounting board, 5 1/2" above mounting board.

PK-285W Monarch Changer with Ronette Stereo Cartridge . . . 2.00 Down . . . Net 22.50
PK-293W Same as PK-285W but with extra Diamond LP Needle . . . 2.00 . . . Net 24.50
PK-289 MONARCH 45 RPM Spindle . . . Down . . . Net 1.88
WOOD MOUNTING BASE cut to fit PK-372W Blonde, PK-371W Mahogany . . . Net 3.95
PK-373W Walnut . . . Net 4.50

NEW! 20,000 OHMS PER VOLT MULTITESTER

- 20,000 OHMS PER VOLT DC—10,000 OHMS PER VOLT AC
- 40 MICROAMPERE 3" D'ARSONVAL METER MOVEMENT
- HIGH INPUT RESISTANCE ON ALL DC AND AC RANGES



1350

This new multitester incorporates the extra luxury features found in the most costly instruments. Easy visibility is provided by the large 3" meter with two color scales. The 40 micro-ampere meter movement permits a high input resistance on all ranges: 20,000 ohms per volt on DC; 10,000 ohms per volt on AC. This plus 1% tolerance resistors allow the measuring of voltages without unduly loading the circuit, thus preserving the accuracy of the readings. Besides the extreme sensitivity and versatility of this instrument, it features ranges not found on other, competitively priced VOM's. Measures 0-10-50-250-500-1000 DC volts, 0-10-50-250-500-1000 AC volts, 0-10K-100K-1 meg ohms, 0-500 microamperes, 0-10-250 milliamperes, -20 to +36 decibels, PLUS two special ranges 0-3000 henrys inductance and 250 mfd to .02 mfd capacity. Employs one standard 1 1/2 volt penlight battery. Size 3 3/4" x 5 3/4" x 1 1/8". Shpg. wt., 3 lbs. Model RW-60 Multi-Tester . . . Net 13.50

Lafayette
Radio

165-08 LIBERTY AVE.
JAMAICA 33, N. Y.
AXtel 1-7000
OPEN MON. AND FRI.
TILL 8:45 P.M.

CATALOG
**6
0
2**

NEW YORK 13, N.Y.
100 6th Ave.
WOrth 6 300
Open THUR.
'til 8:45 P.M.


BOSTON 10, Mass.
110 Federal St.
HUBbard 2-7850
Open MON.-WED.
'til 8:45 P.M.

OTHER LOCATIONS
BRONX 58, N.Y.
542 E. Fordham Rd.
FOrdham 7-8813
Open THUR.
'til 8:45 P.M.

NEWARK 2, N. J.
24 Central Ave.
MARket 2-1661
Open WED.
'til 8:45 P.M.

PLAINFIELD, N.J.
139 W. 2nd St.
Plainfield 6-4718
Open THUR.
'til 8:45 P.M.

Scott



NEW SCOTT 299


COMPLETE STEREO AMPLIFIER

Features dual 20 watt amplifiers and dual preamplifiers on one chassis. Includes a 3rd channel output for the ultimate in stereo reproduction. Has separate Bass and Treble controls for each channel; low level stereo cartridge inputs for cartridges with exceptionally low outputs; Balance Control for precisely balancing both channels; Master Volume Control with loudness switch for tonal balance; Phase Reversal Switch; corrects reversed phasing on improperly made recordings; Master Function Selector switches for stereo records (a-level or hi-level cartridges, stereo FM/AM broadcasts, use of stereo cartridge for monaural records, for a monaural source through both amplifiers. Unit is also used as a monaural electric crossover. Inputs: 2 low-level, 2 high channel. Outputs: Tape recorder output; center channel output, and speaker impedance of 4, 8, and 16 ohms/ for each channel. Freq. Response: 20-30,000 cps. Power output per section 20 watts, 40 watts peak; Harmonic Distortion: 0.8% 1M 0.3%. 11 tubes Size: 4 1/2" x 15" x 12". Shpg. wt., 35 lbs.

- G-135WX 299—Less Case 5.00 Down Net 199.95
- G-147W C Steel Case Net 9.95
- G-149W CW Mahogany Case Net 19.95
- G-151W CWB Blonde Case Net 19.95
- G-150W CWW Walnut Case Net 19.95

NEW SCOTT 222

24 WATT STEREO AMPLIFIER



This is a new 24 watt Stereo Amplifier (12 watts per channel) with numerous features found only on more expensive amplifiers. Dual preamps and control facilities provide complete flexibility in the control and reproduction of all stereo or monaural sources. Outputs are available for stereo tape recording plus a third channel output for connection to another amplifier to provide the ultimate in stereo realism. Loudspeaker output impedances are 4, 8 and 16 ohms for each channel. Inputs: 4 dual (3 high level, 1 low level) Mag High, Mag Low, Tuner, Tape Playback. Outputs: Tape Out (dual) Center Channel (single). Specifications: Frequency response: 20 to 20,000 cps; Harmonic Distortion: less than 0.8% at 12 watts output; IM 0.3% (CCIF method); all aluminum chassis and DC on preamplifier tube heaters result in a hum level of 80 db below full output; Phono sensitivity 3 mv for full output; Size: 13 1/2" wide x 5" high x 9 1/2" deep. Shpg. wt., 24 lbs.

- G-137WX 222—Less Case 5.00 Down Net 139.95
- G-147W C Steel Case Net 9.95

NEW BOGEN DB212

24 WATT STEREO AMPLIFIER




With this "Stereo-Control Center" you can precisely control all stereo sources and feed them through the self contained dual amplifiers to your speaker systems. When you use monaural program sources you have 24 watts of power available to the speaker system. You can also feed one channel monaurally through the tweeter and mid-range speakers, and the other monaurally through the low range speaker. Output Power: 24 watts (two 12 watt channels) peak power 48 watts. Harmonic Distortion: 0.5% at rated output. Frequency Response: 20 to 20,000 cycles \pm 1 db. Speaker Output: 4, 8, and 16 ohms. Tone Controls: Bass \pm 10 db at 60 cycles; Treble \pm 10 db at 10,000 cycles. Controls: 4 position selector switch (tape, phono, radio, aux.); Function switch (Monaural: Channel 1, Channel 2, Channels 1 and 2; Stereophonic; normal, Inverted). Volume; Bass; Treble; Hi-filter (flat, 4 kc). Lo-filter (flat, 100 cps); Speaker (2 position). Power on-off switch. Tubes: (9) two 12AX7/7025, two 6U8, four 6V6GT, one EZ81. Dimensions: 15" W x 4 1/2" H x 12 1/2" D. For 110-120 V. 60 cycles AC. Shpg. wt., 20 lbs.

- G-185WX DB212—Less Cabinet...5.00 Down...Net 119.95
- G-186W BEG Cabinet with legsNet 7.50

NEW BOGEN DB230A


60-WATT STEREO AMPLIFIER

- SEPARATE BASS AND TREBLE FOR EACH CHANNEL
- DUAL VOLUME CONTROLS



The ultimate in a stereo amplifier for top quality and design. With this system you can control all types of stereo and monaural program sources, and feed them through the dual 30-watt amplifiers. When you use it monaurally you have the combined 60 watts available, with a special switching arrangement for monaural phono cartridges. Features are CPF output circuit, Phasing Switch which eliminates hole in middle effect, a provision for remote balance control. Specifications: Power Output: 30 watts (60 watts peak) each channel for stereo. 60 watts (120-watts peak) for monaural. Harmonic Distortion: less than 1% at rated output. Frequency Response: 20 to 20,000 cps. \pm 0.5 db. IM Distortion: less than 2% of rated output; Hum and Noise: (below rated output) fundamental -85 db. Inputs: (3) 0 inputs—5 channel 1, 5 channel 2) magnetic cartridge, crystal cartridge, tape, tuner, auxiliary. Outputs: channel 1 speaker, channel 2 speaker, channel 1 tape, channel 2 tape. Dimensions: 15" W x 5 1/2" H x 13 1/2" D. Shpg. wt., 39 lbs.


- G-187WX DB230A—Less Cabinet—5.00 Down Net 189.50
- G-188W CEG Cabinet with LegsNet 8.00



NEW! Lafayette 50-WATT STEREO AMPLIFIER MODEL LA-250

Impressive Performance... Handsome Styling... Another Unbeatable Lafayette


Value!




- 50 WATTS MONAURAL—25 WATTS EACH STEREO CHANNEL ● RESPONSE 17-21,000 CPS \pm 1 DB (at normal listening level) ● UNIQUE "BLEND" CONTROL ● PREMIUM EL86 OUTPUT TUBES ● SEPARATE BASS & TREBLE CONTROLS ● CLUTCH-TYPE VOLUME-BALANCE CONTROL ● 3RD CHANNEL OUTPUT

COMPLETE STEREO AMPLIFIER
89.50

COMPARABLE TO AMPLIFIERS COSTING UP TO **179.50**



The Stereo 250



The Stereo 250... a completely new stereo high fidelity amplifier with a high quality of reproduction, remarkable versatility and new distinctive styling—worthy of a place in the finest stereo hi-fi music system. A full range of controls enables you to enjoy the utmost in listening pleasure in any situation. A unique "blend" control which provides continuously variable channel separation—from full monaural to full stereo—may be used to eliminate the exaggerated channel separation found in some stereo source material. Included is a clutch-type Volume Balance control for independent or simultaneous control of both channels, concentric Bass and Treble controls which provide independent tonal control of each channel and a 4-position switch which selects phono, tuner, auxiliary or tape head stereo inputs. Simple slide switches provide channel reversal and phase reversal—or you can reproduce either channel through both amplifiers. A loudness switch permits the volume balance control to function as a compensated loudness control. The LA-250 also features a 3rd channel output which may be used to feed a 3rd single channel amplifier and speaker to provide a wider sound spread, a

Tape Output jack for recording purposes, plus dual terminations for 4, 8 or 16 ohm speakers. Advanced circuitry includes DC operated preamp and tone control tube filaments for hum-free operation, premium 6CW5/EL86 push-pull output tubes, individual bias and balance adjustments on each channel and a hum balance control.

SPECIFICATIONS: POWER OUTPUT: 50 Watts—25 per channel Institute of High Fidelity Manufacturers Rating (100 Watts peak). FREQUENCY RESPONSE: 17-21,000 Cps \pm 1 db (at normal listening level). HARMONIC DISTORTION: Less than 1%. HUM and NOISE: 75 db below rated output at full volume (high level inputs). CHANNEL SEPARATION: Greater than 50 db. OUTPUT IMPEDANCE: 4, 8, and 16 ohms per channel.

Attractive beige vinyl laminated steel case. Handsomely designed brass anodized aluminum front panel. Sienna brown milled legs and matching knobs with polished brass inserts. Dimensions with legs and knobs, 14 1/2" w x 12 1/2" d x 5 1/2" h. Shpg. Wt., 26 lbs.

- LA-250WX 5.00 Down Net 89.50

MARANTZ QUALITY HI-FI COMPONENTS

MODEL 7C STEREO CONSOLE PREAMPLIFIER



This new self-powered stereo preamplifier combines Marantz's remarkable quality construction with complete versatility and ease of operation. Front Panel Controls feature: 8-pos. Selector (Mic, Phono 1, Phono 2, Tape-head, FM-AM, FM Multiplex, TV, Auxiliary, 5-pos. Mode (Stereo, Stereo Reverse, Ch A, Ch B, Ch A+B) Volume, Balance, 4-Independent Bass and Treble Tone Controls, Record Equalizer, Tape Playback on Monitor, High Filter, Rumble Filter and Power Switch. Rear Controls feature: Output Level-set, 3 Pairs of Outputs, Tape-head Equalizer Adjustments, 9 Pairs of Inputs, 6 AC Convenience Outlets and System Grounding Point. Frequency Response: 1/2 db 20-20,000 cps 1M. Distortion: 0.1%. Total Noise: in 20-20,000 cps audio range, 80 db below 10 mv phono input with RIAA curve. Tubes: 6-ECC83 12AX7. Dimensions: 14 1/2" WX 5 1/2" HX 8 1/2" D. Panel 15 1/2" WX 5 1/2" H. For 110-120V. 50-60 cycle AC. Shpg. wt., 16 lbs.

- G-231WX Marantz Model 7C—Less Cabinet 10.00 Down Net 249.00
- WOOD CABINET FOR ABOVE: Specify Mahogany, Blonde, Walnut, Oiled Walnut. Shpg. wt., 4 lbs.
- G-233W Net 24.00


MODEL 8A DUAL 30-WATT STEREOPHONIC POWER AMPLIFIER



Professional in every respect the Model 8 Stereo Amplifier furnishes performance and workmanship found in high quality Broadcast or Laboratory equipment. Optimum performance is insured by built-in metered test instruments which provide simple, accurate adjustments. Power Output is 30 Watts per channel (60 watts peak) "Ultra-Linear" operation. 18-watts of Triode operation is possible by altering two connections. Response: 0.1 db from 20-20,000 cps at 30-watts. Distortion: harmonic, less than 0.1% .1M., less than 0.5%. Hum: 90 db. Input Sensitivity 1.3 volts. Power Supply employs 3 heavy duty telephone quality electrolytics and choke. Output impedance: 4, 8 and 16 ohms. Tubes: 2-6BN6, 2-6CH7, 4-EL34/6CA7. Overall size: 13 1/2" wx 7 1/4" H 10 1/2" D. For 117 volts 60 cycles AC. Shpg. wt., 55 lbs.

- G-250WX Marantz Model 8A Less Cabinet 10.00 Down Net 237.00
- Model 8G Gold Finish Perforated Snap on Grille for above. Shpg. wt., 1 lb.
- G-257W Net 9.00

MODEL 5A 40-WATT POWER AMPLIFIER



The highest standards of workmanship, components and design guarantee unexcelled performance from this new Marantz basic power amplifier. Power Output in 30 watts (60 Watts Peak) "Ultra-Linear" operation. 18 Watts of excellent Triode operation can be obtained by alternating two connections. Response at 30-watts is 0.1 db from 20-20,000 cps. Distortion: harmonic, less than 0.1% .1M., less than 0.5%. Hum is better than 90 db below 30 watts. Power Supply employs transmitting-type oil input condenser, choke, telephone quality electrolytic and GZ-34 heater-cathode rectifier. A built-in meter and test switch provide accurate adjustment of each output tube bias. Tubes: 1-6BM6, 1-6CG7, 2-EL34/6CA7, 1-GZ-34. For 117 volts, 60 cycles AC. Overall size: 7 3/4" HX 6" W x 15 1/2" D. Shpg. wt., 35 lbs.

- G-252WX Marantz Model 5A Less Cabinet 10.00 Down Net 147.00
- Model 5C Gold Finish Perforated Grille for above. Shpg. wt., 11 lbs.
- G-258W Net 7.50

LAFAYETTE RADIO

Pioneers in HI-FI!


"Let Your Own Ears be the Judge"

The best "independent testing laboratory" in the whole world is your own living room — because it represents the actual conditions under which you will listen to your hi-fi system.

The best instruments for you to judge sound quality are your own ears — because sound is a very personal thing.

So, if you wish, read the so-called "Best Buy Reports," remembering that they do not consider your desires, your ears, the characteristics of your home and your pocket book.

We at Lafayette are conscious of all these factors and invite you to either visit our sound salons if you are able to do so, or to avail yourself of Lafayette's "LISTEN AT HOME GUARANTEE" described on the right.



LAFAYETTE CONTROL PANEL FOR COMPARATIVE LISTENING — INSTANTANEOUSLY DEMONSTRATES HUNDREDS OF HI-FI COMBINATIONS.



The Smart Way To Buy HI-FI

Lafayette's

"LISTEN AT HOME GUARANTEE"

Prove to yourself in your own living room, that the hi-fi system you select sounds as good at home as it does in our showroom.

LISTEN AT HOME AND BE SURE!

With Lafayette's Famous 15 Day FREE Trial if not completely satisfied with your purchase once you get it home, you can return it within 15 days and get your Full Purchase Price returned to you, less only transportation charges.

LAFAYETTE FOR LEADING STEREO COMPONENTS

NEW! Lafayette 50-WATT COMPLETE STEREO PHONO SYSTEM

The Excitement and Realism of The Concert Hall!

LA-250




LAFAYETTE LA-250 50-WATT STEREO AMPLIFIER



SELECT YOUR OWN CARTRIDGE



NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE



PICKERING 371.70 (.7 MIL) DIAMOND STEREO CARTRIDGE



SHURE M7D (.7 MIL) DIAMOND STEREO CARTRIDGE



NEW ELECTRO-VOICE 31MD7 (.7 MIL) DIAMOND STEREO CARTRIDGE

You may substitute any of the above cartridges at no additional cost.

COMPLETE STEREO SYSTEM

174.50

YOUR GUARANTEED BEST STEREO SYSTEM BUY!




LAFAYETTE SK-58 FAMOUS FREE EDGE 12" COAXIAL SPEAKER



GARRARD RC121/11

WOOD BASE



LAFAYETTE ELIOFLEX SERIES BOOKSHELF ENCLOSURE

- LAFAYETTE LA-250 50-WATT STEREO AMPLIFIER 89.50
- GARRARD RC121/11 STEREO CHANGER 41.65
- NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE 24.45
- LAFAYETTE WOOD CHANGER BASE (Specify Finish.) 3.95
- 2-LAFAYETTE SK-58 FAMOUS FREE EDGE 12" COAXIAL SPEAKERS at 29.50 59.00


Regular Catalog Price 218.55

You Save 44.05

This superb system will add a new dimension in living to your home with all the excitement and realism of a live concert. The new Lafayette LA-250 50-watt stereo amplifier (25 watts each channel) forms the heart of this outstanding stereo hi-fi phonograph music system—the features, versatility and advanced circuitry of this unit are second to none—all the necessary inputs and outputs are provided if you wish to add stereo tape and stereo FM/AM later. A unique blend control allows continuously variable channel separation—from full monoaural to full stereo. Also included is the famous Garrard RC121/11 intermix 4-speed automatic record changer with full manual or automatic operation supplied with your choice of stereo cartridges—the new GE VR-22 (.7 mil) diamond stereo cartridge, Pickering 371.70 (.7 mil) diamond stereo cartridge, Shure M7D (.7 mil) diamond stereo cartridge or the new Electro-Voice 31MD7 (.7 mil) diamond stereo cartridge. Supplied with the Lafayette PK-111 wood base cut for the RC121 in your choice of finishes. These outstanding components are coupled with the 2-famous free-edge Lafayette SK-58 12" Coaxial speakers with built-in crossover network and brilliance level control. System supplied with plugs, cables and simple instructions. Shpg. Wt., 67 lbs.

- MF-681WX HI-FI STEREO PHONO SYSTEM with choice of cartridge and mahogany, walnut or blond changer base (please specify). Net 174.50
5.00 Down
- MF-683WX Same as MF-681, but with choice of 2-Lafayette Eliofoflex Series Bookshelf Enclosures or 2-Lafayette Cab-16 Series Resonator Enclosures (please specify cabinet model and finish.) Shpg. Wt., 143 lbs. Net 229.95
10.00 Down
- MF-684WX Same as MF-681, except speakers furnished are 2-University 312. 12" 3-way speakers. Shpg. Wt., 67 lbs. Net 237.50
10.00 Down
- MF-685WX Same as MF-684, but with choice of 2-Lafayette Eliofoflex Series Bookshelf Enclosures or 2-Lafayette Cab-16 Series Resonator Enclosures (please specify cabinet model and finish.) Shpg. Wt., 143 lbs. Net 294.50
10.00 Down
- MF-682WX STEREO AM-FM-PHONO SYSTEM: Same as MF-681 but including the new Lafayette LT-50 stereo tuner. Shpg. Wt., 85 lbs. Net 287.50
10.00 Down

ALTERNATE ENCLOSURES



LAFAYETTE CAB-16 SERIES RESONATOR ENCLOSURE

McIntosh


McINTOSH C20 STEREO COMPENSATOR



Full stereo flexibility is provided plus built-in protection for your investment in monophonic records. Mode Selector has 6 positions. Internally decouples stereo phono cartridge to offer best-quality reproduction from monophonic records. Separate treble and bass tone controls. Has separate channel back panel controls to balance the frequency response of the system independent of front panel controls. Equalization: Individual bass and treble 6 position switches, including NAB tape and flat for any low level flat source. Provides Fletcher-Munson compensation, continuously variable. Rumble filter and 2-position (9KC and 5KC) high frequency cutoff to suppress hiss and noise. 180° phase reversal control. Tape: Front panel jacks, push button switch controlled, to permit the addition of portable recorder, Tape Monitor. Freq. Response: ± 0.5 db 20 to 20 KC. Distortion less than 0.2% at rated output. Hum and noise inaudible. Outputs: Main—2.5V with rated input, tape—0.25V with rated input. Power requirements: 117VAC, 35 watts. A.C. Aux. Outlets: 1 unswitched and 3 switched. Less Case. Size 14 1/2" x 12" x 4". Shpg. wt., 19 lbs.

- G-170WX 10.00 Down Net 225.00
- Model L-55. Cabinet for C20 in mahogany or walnut. Shpg. wt., 5 lbs. Specify finish.
- G-174W 2.00 Down Net 25.00


McINTOSH MC-30 30-WATT AMPLIFIER



Superlative Amplification with 1M distortion at 1/2% and Harmonic Distortion at less than 1/2%. Input sensitivity 0.5 volt with gain control. Frequency Response ± 1 db between 15-50,000 cps. Hum and noise are .90 db. Amplifier outputs of 4, 8, 16 and 600 ohms (balanced). Tubes are 2-12AX7, 12-AU7, 12-BH7, 2-1614, 5 U4GA (Rectifier). Chrome and black finish. Dimensions 13 1/2" x 8" x 8". Power consumption 155 watts, 117/125v, 50/60 cycles AC. Shpg. wt., 34 lbs.

- G-171WX 5.00 Down Net 143.50

McINTOSH MC-60 60-WATT AMPLIFIER




The ultimate in quality with 60 watts of power at less than .3% distortion from 20-20,000 cps. Two inputs: one of low level sensitivity of .5 volt with volume control and one high level 2.5v input. Frequency response is ± .1 db from 20-30,000 cps. with hum and noise level of .90 db. Outputs of 4, 8, 16 and 600 ohms (balanced). Tubes are 2-12AX7, 12AU7, 12BH7, 2-6650, 2-5U4GA (Rectifiers). Chrome and black finish. Power consumption 280 watts, 117/125 volts, 50/60 cps. AC. Dimensions 14 1/2" x 10" x 8". Shpg. wt., 48 lbs.

- G-172WX 5.00 Down Net 198.50

NOW Lafayette COMBINES THE INCOMPARABLE QUALITY of COMPONENT STEREO HI-FI with the ELEGANCE of Custom Cabinetry.

Custom Crafted Cabinets Individually Tailored For YOUR HOME • YOUR TASTE and YOUR BUDGET

319.50 10.00 Down
COMPLETE STEREO ENSEMBLE



49.95

52.50

49.95



LA-250 STEREO AMPLIFIER



GARRARD RC121



SK-58 COAXIAL SPEAKER



GE VR-227



OPTIONAL TUNER

LT-50


LAFAYETTE HAS REFUSED TO COMPROMISE . . . you need not sacrifice your taste in fine furniture in order to achieve component sound quality, nor compromise beautiful music for fine cabinetry. The performance of these brilliant cabinet systems is in every respect the equal of Component Quality. Until now, such perfection has been enjoyed, only by the Hi-Fi enthusiast who reproduced stereo music with a combination of separate components — Lafayette's audio experts have integrated these very same components into a series of acoustically correct decorator styled cabinets. Bring the full beauty and realism of stereo into your home with these luxurious custom crafted cabinets and matched components integrated into a superb STEREO ENSEMBLE.

► The new Lafayette LA-250 50-Watt stereo amplifier (25 watts each channel) provides every outstanding feature you could ask for in an amplifier. Response 17-21,000 cps; less than 1% distortion.

► The famous Garrard RC121/11 4 speed Automatic record changer is supplied with the new GE VR-227 stereo cartridge for perfect reproduction.

► System is supplied with 2-renowned Lafayette SK-58 Coaxial Speakers. 1 1/4 lbs. magnet, built-in crossover network and "sheepskin" free edge cone mounting make this one of the finest speakers available today. Supplied with easy to follow instructions. (Refer to HF-681, Pg. 3 for complete information on these components.) Stereo Ensemble consisting of above components plus complete set of custom crafted cabinets. Shpg. wt., 222 lbs. Equipment is separately and securely packaged to insure safe shipment. (Specify cabinet finish.) HF-746WX . . . 10.00 Down . . . Net 319.50

Stereo Ensemble — same as above but with the addition of Lafayette LT-50 FM-AM Stereo Tuner featuring 1- μ v sensitivity, AFC and multiplex output. Shpg. wt., 240 lbs. Equipment is separately and securely packaged to insure safe shipment. HF-747WX . . . 10.00 Down . . . Net 439.50



DESIGN FLEXIBILITY . . . place cabinets together as a complete Home Entertainment Center or utilize separately to suit your own room arrangement. Modular concept permits the addition of more units at any time.



Each individual unit is a complete beautifully finished cabinet in itself. Due to their modular concept extreme flexibility has been achieved. The equipment-speaker units fit together perfectly or may be placed separately in the room to suit your own arrangement for stereophonic or monophonic reproduction. The speaker enclosure is acoustically designed to house up to a 12" speaker or speaker system. The equipment cabinet is built to house pre-amplifier and/or amplifier, tuner, or tape recorder-player and transcription table or record changer. A removable shelf is provided which is adjustable in height for mounting separate components.

Equipment Cabinets: Inside Dimensions are 18 1/2"W x 13 1/8"H. Overall size: 20"W x 32 1/2"H x 18"D. Shpg. wt., 55 lbs.

CAB-87WX Walnut, CAB-88WX Mahogany, CAB-89WX Blonde, CAB-90WX Ebony. (Specify Finish.) 5.00 Down . . . Net 52.50

T Adapter Board — Converts equipment cabinet for use with 12" transcription turntable. (Specify Finish.) CAB-91W . . . Net 1.50

Speaker Enclosure: Dimensions 20"W x 32 1/2"H x 10"D. Shpg. wt., 50 lbs.

CAB-115WX Walnut, CAB-116WX Mahogany, CAB-117WX Blonde, CAB-118WX Ebony. (Specify Finish.) 2.00 Down . . . Net 49.95

STEREO CLASSIC CONSOLE SYSTEM A Lafayette Special Stereo Value!



GE G-506 SPEAKER SYSTEM




GE G-7600



GARRARD RC121



GE VR-227



GE FA-17

COMPONENTS	
GE G-7600 40-WATT STEREO AMPLIFIER	139.95
GARRARD RC-121/11 STEREO RECORD CHANGER	41.65
GE VR-227 (.7 MIL) DIAMOND STEREO CARTRIDGE	24.45
2-GE G-506 SPEAKER SYSTEMS @ 127.35	254.70
WOODBASE CUT FOR RC-121	3.95
	Regular Catalog Price 464.70

LAFAYETTE SYSTEM PRICE 372.56 10.00 Down
You save 92.14

Complete stereo phono system as listed above. Shpg. wt., 145 lbs. (Specify Walnut, Mahogany, Cherry or Blonde Speaker Finish.) HF-751WX . . . 10.00 Down . . . Net 372.56
Recommended Tuner — GE FA-17 FM-AM Tuner. . . 5.00 Down . . . Net 129.95
Above system with GE FA-17 Tuner. Shpg. wt., 160 lbs. HF-752WX . . . 10.00 Down . . . Net 476.56


Complete your stereo system with this new GE EQ Series Equipment Cabinet: Room for all your components plus two large sliding panel record storage sections. This attractive acoustically designed cabinet features matched wood graining, recessed door pulls and brass ferruled legs. Dimensions: 31"H x 39 3/4"W x 17 3/4"D. Shpg. wt., 60 lbs. CAB-119WX (Mahogany), CAB-120WX (Blonde), CAB-121WX (Cherry), CAB-122WX (Walnut) . . . 5.00 Down . . . Net 107.75

Lafayette BRINGS YOU A COMPLETE CUSTOM STEREOPHONIC MUSIC CENTER


329.50
10.00 Down



LA-250 STEREO AMPLIFIER



SK-58 COAXIAL SPEAKER



GARRARD RC121



LT-50

A triumph of custom cabinet design and imaginative engineering . . . for this is no ordinary commercial console. Speaker enclosures are acoustically isolated, in effect they are literally cushioned and floated on live rubber inside the main enclosure. Thus all resonance created by the speaker is prevented from reaching the sensitive elements of the rest of the system. Stereophonic Music Center includes these famous Lafayette Components: new Lafayette LA-250 50 Watt Stereo Amplifier, Garrard RC 121/11 4-Speed Record Changer with new GE VR-227 stereo cartridge and two famous Lafayette SK-58 12" Coaxial Speakers. (Refer to HF-681, pg. 3 for complete information on these components.) Furniture crafted of selected woods, this compact, integrated all-in-one console utilizing these individual stereo components will provide a beautiful addition to your home. Size 54"W x 32 1/2"H x 18"D. Specify Walnut, Mahogany, Blonde or Ebony finish. Supplied with complete instructions. (Cabinets and equipment are separately packaged to insure safe shipment) Shpg. wt., 243 lbs. HF-749WX . . . 10.00 Down . . . Net 329.50


Same as HF-749WX, but with addition of Lafayette LT-50 FM-AM Stereo Tuner, Shpg. wt., 261 lbs. HF-750WX . . . 10.00 Down . . . Net 449.50

This superbly styled cabinet will easily accommodate all components of the stereo music system. The twin speaker enclosures provide true stereophonic listening pleasure — each houses a 12" loudspeaker or separate multi-way speaker system with provision for any size tweeter. Center equipment section houses amplifier and/or pre-amplifier, tuner or tape recorder player. Has drop front to keep open or closed. Inside dimensions: 18 1/2"W x 13 1/8"H. Overall size: 54"W x 32 1/2"H x 18"D. Shpg. wt., 176 lbs. CAB-111WX Walnut, CAB-112WX Mahogany, CAB-113WX Blonde, CAB-114WX Ebony. (Specify finish.) 5.00 Down . . . Net 159.50

Lafayette presents THE LONG, LOW LOOK IN HIGH FIDELITY CABINETRY... As a One-Piece System or in Separate Units, The Finest in Cabinets for Fine Music Systems.



Create Your Own Custom Stereophonic Grouping. These versatile cabinets adapt to any room arrangement, acoustic requirement or personal preference.



NEW GENERAL ELECTRIC 56-WATT STEREO PHONO SYSTEM



- COMPONENTS**
- GE 56-WATT STEREO AMPLIFIER 186.15
 - GLASER STEERS GS-77 DELUXE CHANGER (LESS BASE) 59.50
 - NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE 24.45
 - 2-GE G-506 SPEAKER SYSTEMS @ 127.35 254.70
- (Specify Mahogany, Blonde, Cherry or Walnut)

LAFAYETTE SYSTEM PRICE 419.84

Only 10.00 Down

- Complete stereo system as listed Shpg. wt., 143 lbs. Net 419.84
- HF-771WX 10.00 Down Net 419.84
 - Same as HF-771WX, but with 2-Lafayette Eliptaflex Bookshelf Speaker systems employing 2-Lafayette SK-58 12" coaxial speakers (Specify Finish) Shpg. wt., 117 lbs. Net 345.08
 - HF-772WX 10.00 Down Net 345.08
 - Same as HF-771WX, plus GE FA-17 FM-AM Tuner finished in saddle brown, FA-15 finished in beige or FA-14 finished in white. Shpg. wt., 158 lbs. Net 523.79
 - HF-773WX 10.00 Down Net 523.79
 - Model G5B Woodbase for GS-77 in ebony with satin brass trim. Shpg. wt., 5 lbs. Net 9.60
 - PK-350W


- ▶ Constructed of 3/4" Selected Walnut Veneers
- ▶ Meets the Highest Engineering Standards
- ▶ Superlative Contemporary Styling — Adapts To Any Room Arrangement

MAGNIFICENT CUSTOM CABINETS . . . Incorporating the highest standards of wood-working craftsmanship and engineering design. These fine cabinets meet the most rigid engineering requirements of stereophonic sound. The equipment cabinet is constructed to assure continuous air circulation and removal of heat generated by components. Ample space has been provided for record changer, turntable or tape transport, tuner and amplifier. Control panel may be either cut for components or used as a shelf for supporting components. Specially designed slides are employed on the record changer platform, providing an absolute level, even when fully extended. Additional custom features are concealed furniture hinges with built in stops and magnetic door catches. Speaker enclosures are constructed of a special 3/4" high pressure core plywood and feature adjustable ports for precise tuning of the port opening to the individual speaker. The enclosure accepts either an 8" or 12" speaker. Cabinets feature solid legs and trim, with brass leg ferrules.

Equipment Cabinet — Overall dimensions: 20" W x 18 1/2" D x 32 3/4" H. Control panel 18 3/4" W x 12" H with clearance 15" in back, 2" in front. Changer section: 18 3/4" W x 17 1/4" D x 11 1/4" H. Height of motor board is adjustable to clear all popular changers and turntables.

CAB-107WX Walnut Only 5.00 Down Net 52.50
 Speaker Enclosure — Overall Dimensions: 20" W x 18 1/2" D x 32 3/4" H.
 CAB-123WX Walnut Only 2.00 Down Net 44.95

COMPLETE FISHER FM-AM STEREO PHONO SYSTEM



- COMPONENTS**
- FISHER TA-600 STEREO TUNER AND AMPLIFIER (Less Cabinet) 349.50
 - GLASER STEERS GS-77 DELUXE CHANGER (LESS BASE) 59.50
 - NEW G. E. VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE 24.45
 - 2-LAFAYETTE SK-58 FAMOUS FREE EDGE 12" COAXIAL SPEAKERS @ 29.50 ea. 59.00


Complete system as listed above. Shpg. wt., 75 lbs. Net 396.75

- HF-768WX 10.00 Down Net 396.75
- Same as above but with 2-Lafayette Eliptaflex Bookshelf Enclosure finished on 4-sides (Specify Finish) Shpg. wt., 123 lbs. Net 468.25
- HF-769WX 10.00 Down Net 468.25
- Same as HF-768WX, but with 2 University 312 12" Triaxial Speakers. Shpg. wt., 75 lbs. Net 461.21
- HF-770WX 10.00 Down Net 461.21
- Model G5B Woodbase for GS-77 in ebony with satin brass trim. Shpg. wt., 5 lbs. Net 9.60
- PK-350W

LAFAYETTE SYSTEM PRICE 396.75

Only 10.00 Down

COMPLETE HARMAN-KARDON FM-AM STEREO PHONO SYSTEM



- COMPONENTS**
- H-K TA230 STEREO FESTIVAL (Less Cage) 259.95
 - GLASER STEERS GS-400 STEREO RECORD CHANGER (LESS BASE) 46.55
 - NEW G. E. VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE 24.45
 - 2-LAFAYETTE SK-58 FAMOUS FREE EDGE 12" COAXIAL SPEAKERS @ 29.50 ea. 59.00

LAFAYETTE SYSTEM PRICE 293.50

Only 10.00 Down

- Complete stereo system as listed above. Shpg. wt., 70 lbs. Net 293.50
- HF-765WX 10.00 Down Net 293.50
 - Same as above, but with 2-Lafayette Eliptaflex Bookshelf Enclosures finished on 4 sides (Specify Finish) Shpg. wt., 118 lbs. Net 365.00
 - HF-766WX 10.00 Down Net 365.00
 - Same as HF-765WX, but with 2-University 312 12" Triaxial Speakers. Shpg. wt., 70 lbs. Net 357.00
 - HF-767WX 10.00 Down Net 357.00
 - Model G5B Woodbase for GS-400 in ebony with satin brass trim. Shpg. wt., 5 lbs. Net 9.60
 - PK-350W

WRITE FOR LAFAYETTE'S SYSTEM-PLAN PRICES

If you wish to assemble a music system made up of components of your own choice, let Lafayette "price" the high-fidelity system you select. Just send us a list of the components you desire, and a special, money-saving package price will be sent to you promptly. Fill out the coupon below, specifying the makes and models of the components you want priced, and mail it today to our Audio Division. No charge or obligation, of course.

STOCK NO.	QUANTITY DESIRED	DESCRIPTION	PRICE EACH


Lafayette's System-Plan Price →

Name _____

Address _____

City _____ Zone _____ State _____

FANTASTIC VALUES in PHONOGRAPHS and RECORD CHANGERS



LAFAYETTE'S FINEST PORTABLE PHONOGRAPH

- PLAYS BOTH STEREO AND MONAURAL
- FULLY AUTOMATIC GARRARD CHANGER
- TWO POWERFUL 10 WATT AMPLIFIERS
- SECOND SPEAKER EASILY DETACHED

A complete portable and compact stereo phonograph in one convenient case. System uses the well-known Garrard RC-121/II 4-speed stereo changer which features true intermix of 12" and 10" records in any order with instant selection of either automatic or full manual operation. Uses a stereo turnover cartridge to play all your records—whether monaural or stereo. Two powerful 10 watt amplifiers provide a frequency response of 50 to 12,000 cps. Controls included: Master Volume, Remote speaker volume, Master treble, Master Bass, Detachable front speaker cabinet houses a 6" x 9" speaker with 19 ft. extension cord. Main unit houses two speakers—one 6" x 9" woofer and one 4" tweeter. Phonograph has easy-grip handle on attractive smart-looking Pyroxylin covered case. Size: 18 1/2" long, 15 1/2" wide, 9" high. Shpg. wt., 36 1/2 lbs. Complete Stereo phonograph with remote speaker.

89.50

PH-128WX 5.00 Down Net 89.50

LAFAYETTE PORTABLE 4-SPEED MANUAL PHONOGRAPH

- Turnover Cartridge For All Monaural Records
- Provision For Extension Speaker
- Attractive 2-Tone Case

With this portable phonograph you can play any record up to 12" size at 33-1/3, 45 or 78 rpm, or at the new "Talking Book" speed of 16-2/3 rpm. A single lever selects any speed. The lightweight pick-up arm is equipped with a turnover cartridge with dual sapphire stylus. Has both tone control and volume control with on-off switch. Has jack for adding extension speaker. Fine quality Alnico 5 pm speaker. Attractive 2-tone leatherette covered case. For 117 volts, 60 cps AC. Dimensions 14 1/2" x 10 1/4" x 5 1/4". Shpg. wt., 10 lbs.



PH-130W

Net 18.25

18.25

Nationally Advertised

4-SPEED AUTOMATIC RECORD CHANGER

COMPLETE WITH THE BRAND NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE



Regular ~~68.00~~
Special **39.95**
Only \$2.00 Down



ANOTHER FABULOUS BUY at Lafayette! This is a brand new current changer made by a famous manufacturer, plus the new General Electric VR-22 (.7 MIL) Diamond Stereo Cartridge, offering the finest reproduction from both stereo and monaural records. This cartridge features 20-17,000 cps response, -30 db channel separation, tracks at 5 to 7 grams. This deluxe changer features what we DARE NOT mention the manufacturer's name. This deluxe changer features automatic intermix of different size records, a mulling switch, click filter, and automatic intermix of different size records. The heavy rim-weight system, all table, the heavy duty 4 pole shaded pole motor and a rugged drive system, all combine to produce even, smooth torque with no speed variations; there is practically no wow, no flutter, no rumble. And don't forget Lafayette's MONEY BACK GUARANTEE if you don't agree that you have received an exceptional value. Size: 12 1/4" x 13 1/2" requiring 5" clearance above and 2-11/16" below motor board. Shpg. wt., 21 lbs. less base.

RECORD CHANGER WITH NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE. 2.00 Down Net **39.95**

PK-330WX RECORD CHANGER WITH FAMOUS GE 4G-052 (1 MIL) DIAMOND MONAURAL CARTRIDGE. 2.00 Down Net **39.95**

PK-250WX RECORD CHANGER WITH GE GC-7 (.7 MIL) DIAMOND STEREO CARTRIDGE. 2.00 Down Net **34.95**

PK-251WX RECORD CHANGER WITH PICKERING 371C (.7 MIL) DIAMOND STEREO CARTRIDGE. 2.00 Down Net **42.50**

PK-252WX WOOD BASES FOR ABOVE 3.95

PK-359W MAHOGANY BASE 3.95

PK-360W BLONDE BASE 4.50

PK-361W Walnut Base 4.50

NATIONALLY ADVERTISED CHANGER

Tremendous Buy for Stereo!!



Regular ~~38.50~~
Special **24.50**
Only \$2.00 Down



FOR STEREO AND MONAURAL CARTRIDGES

A superb value for the "stereophile"—Top name brand, 4-speed stereo changer with tone arm which will accept all standard stereo cartridges. Automatic intermix handling of records, mulling switch for soundless change cycle, automatic shut-off after last record. Rim-weighted turntable, heavy-duty shaded 4 pole motor for top quality reproduction. If you don't agree that this changer is a top buy—your money will be refunded. Changer measures 12 1/4" x 13 1/2" with 5" clearance above and 2-11/16" below motorboard. Shpg. wt., 21 lbs. less base.

RECORD CHANGER (less cartridge) 2.00 Down Net **24.50**

PK-275WX RECORD CHANGER COMPLETE WITH RONNETTE'S FAMOUS COMPATIBLE STEREO TURNOVER CARTRIDGE WITH TWO SAPPHIRE STYLI (.75 & 2.5 MIL) 2.00 Down Net **29.95**

PK-276WX RECORD CHANGER COMPLETE WITH ELECTRO-VOICE MAGNORAMIC STEREO CARTRIDGE (31MD-7) WITH .7 MIL DIAMOND STYLUS. FOR MAGNETIC INPUT. 2.00 Down Net **35.50**

PK-337WX RECORD CHANGER COMPLETE WITH ELECTRO-VOICE 31D-7 CERAMIC STEREO CARTRIDGE WITH .7 MIL DIAMOND STYLUS. FOR CERAMIC OR CRYSTAL INPUT. 2.00 Down Net **35.50**

PK-338WX RECORD CHANGER COMPLETE WITH RONNETTE MONAURAL TURNOVER CARTRIDGE WITH 1 MIL AND 3 MIL SAPPHIRE STYLI. 2.00 Down Net **27.45**

PK-339WX WOOD BASES FOR ABOVE 3.95

PK-374W MAHOGANY BASE 3.95

PK-375W BLONDE BASE 4.50

PK-376W WALNUT BASE 4.50

Lafayette is First Again!

NEW! GLASER-STEERS GS-400 STEREO RECORD CHANGER


Complete With Cartridge: GE VR-22 (.7 MIL) Diamond Stereo Cartridge

(Less Base)

Regular ~~71.95~~

Special **52.50**

Only 5.00 Down




AN UNBEATABLE STEREO VALUE from Lafayette. This new Glaser-Steers 4-speed stereo record changer is provided with the new GE VR-227 Diamond Stylus Stereo Cartridge for perfect stereo and manual reproduction. Check these Glaser-Steers features... automatic intermix and play of all size records of any selected speed without regard to sequence; acoustically isolated and dynamically balanced transcription type tone arm; automatic and manual operation at all 4 speeds; 16, 33-1/3, 45 and 78 rpm; idler automatically disengages in off position preventing flat spots; mulling switch and RC network maintain silence for both stereo channels. Finished in Gray and Silver trim with Oyster White turntable pad. For 105-130 volts 60 cycle AC. Dimensions 13 1/2" x 12" x 3" below and 5 1/2" above mounting board. Shpg. wt., 14 lbs.

GS-400 Record Changer with GE VR-227 Diamond Stereo Cartridge. 5.00 Down Net **52.50**

PK-350W Ebony woodbase with gold trim \$ lbs. Net **9.60**

PK-352 Automatic 45 rpm spindle 1 1/2 lbs. Net **2.95**

SPECIAL LAFAYETTE PK-168 **1.25**



REPLACEMENT CARTRIDGES FOR RCA 74067

• Replacement for cartridges in many thousands of RCA45 and many LP record changers.

• 1 MIL SAPPHIRE STYLUS • 2.3V OUTPUT

• HIGH IMPEDANCE CRYSTAL • TAKES 7-10 GMS PRESSURE • 3/8" MTG CENTERS


EXACT REPLACEMENT FOR

RCA		SHURE	
74067	75575	W31AR	P73AR
74425	76318	P73	P73R
75476		P73A	

PK-168 Net **1.25**

PS-555-Sapphire replacement stylus Net **.99**

GENUINE MAGNAVOX CARTRIDGES



Genuine Magnavox exact replacement cartridges complete with indicated stylus. Shpg. wt., 12 oz.

STOCK NO.	MAG. NO.	FIG.	STYLI	NET
D-75	560133-4	A	Use 560170-1	8.80
D-76	560170-1	C	Dual Sapphire	9.80
	560151-9	B	Sapphire	
	560151-5	B	Use 560151-9	
	560151-6	B	Use 560151-9	
D-77	560158-2	B	Diam/Sapphire	11.52
D-78	560169-1	C	Diam/Sapphire	10.52


GENUINE ZENITH COBRA CARTRIDGES



All Zenith cartridges are identified by color. Just match color to obtain exact replacement. *For diamond cartridges listed below gold will replace green and blue; white replaces blue; gray replaces brown. wt., .5oz.

STOCK NO.	ZENITH NO.	COLOR	COBRAMATIC MODEL	STYLUS	NET
D-10	S11473	Red	All to "L"	3 Mil Os	2.34
D-11	S15780	Red & Green	All to "L"	2 Mil Sapp	2.34
		Green	All to "L"	1 Mil Dia	10.00
D-12	S15222	Gold	"L" & "M"	3 Mil Sapp	3.34
D-13	*S21458	Purple	"L" & "M"	2 Mil Sapp	3.34
D-14	142-73	Yellow	"L" & "M"	1 Mil Dia	10.00
D-15	142-72	Blue	"L" & "M"	1 Mil Dia	10.00
D-16	142-71	White	"L" & "M"	1 Mil Dia	10.00
D-17	*142-74	Brown	"L" & "M"	1 Mil Dia	10.00
D-18	142-77	Brown	"L" & "M"	1 Mil Dia	10.00
D-19	*142-76	Gray	Turnover "R" & "L"	3 Mil Sapp	5.00
			Turnover	1 Mil Dia	11.00
			Turnover	3 Mil Sapp	11.00

PK-11 **1.29**



PHONO CARTRIDGES 3.5 VOLT OUTPUT (PK 11)

Guaranteed high quality exact duplicates for direct replacement of all standard cartridges such as L70, L82, L92, W608, N10, and many others. Pin plug connectors for all 78 r.p.m. Shpg. wt., 6 oz.

PK-11 each **1.29**

HI-FI TURNOVER CARTRIDGE 40-14,000 CYCLES (PK-79)

Never before has a turnover cartridge of this quality been offered at such a price. Frequency response from 40-14,000 cycles \pm 2 db! Has 2 sapphire styli to play all speeds and types of records. Needle pressure required is only 5 grams on LP and 12-15 grams on 78 RPM. Output is .5 volts. Comes complete with turnover mechanism and knob. Fits Webster, Garrard, VM, Callara and tone arms of other leading manufacturers of record changers and players. Shpg. wt., 8 oz.

PK-79—Singly, each \$2.75.....in lots of 3, each 2.50

PK-84—Sapphire LP Replacement Needle..... .69

PK-85—Sapphire STD (78) Replacement Needle..... .69

PK-79 **2.75**



PK-80 **2.50**



3 VOLT TURNOVER CARTRIDGES

• High Output: 3 volts • Turnover Mechanism • Dual Sapphire Styli • Excellent Frequency Response


Lafayette has gone all out to provide for the serviceman a replacement turnover phono cartridge at a price never before attained. Here is a crystal cartridge complete with 2 sapphire styli, turnover mechanism, mounting bracket and knob—with sufficient output to use in any record player—and yet of fine quality. All at a price that enables you to use it on any repair job. Length, (less knob) 2 1/8". Ease of mounting assured by two sets of mounting holes each set with 1/2" centers. Shpg. wt., 8 oz.

PK-80—Singly, each 2.50 in lots of 3, each 2.25

PK-86—Sapphire LP Replacement Needle..... .69

PK-87—Sapphire STD (78) Replacement Needle..... .69

2.75



NEW! STEREO CRYSTAL TURNOVER CARTRIDGE

• EXCELLENT FREQUENCY RESPONSE

• HIGH OUTPUT • LOW TRACKING FORCE

• DUAL SAPPHIRE STYLI

Another instance of Lafayette special value for you: a stereo crystal turnover cartridge at such a low price. Frequency response 40-14,000 cps. Tracks with low stylus pressure and high output voltage. Excellent channel separations for stereo effect. Supplied with turnover mechanism, knob and dual sapphire styli to play records of all speeds. Completely compatible. Fits all standard arms. Shpg. wt., 6 oz.

PK-258 Net **2.75**

REPLACEMENT STYLI


PK-281—Sapphire Stereo LP Net **.69**

PK-282—Sapphire STD (78) Net **.69**

PS-86—DIAMOND Stereo LP Net **2.59**

A LAFAYETTE SPECIAL!

STEREO TONE ARM COMPLETE WITH CRYSTAL STEREO CARTRIDGE



only **2.95**

An exceptional value! A transcription-type stereo tone arm ready for use with all stereo and monaural LP records at an amazingly low price. Modern, plastic, straight line design with offset plug-in head which has a wide-range ceramic stereo cartridge with single sapphire stylus. Output is 1 volt per channel—high enough to connect directly to basic amplifier. Stylus pressure adjustable by variable spring tension. Has finger-lift for ease in handling. Mounts easily—requires only one 7/16" hole and is secured by single locknut. May be mounted on turntable base of up to 1/2" thickness. Easy height adjustment at base of arm. Overall length 10". Finished in gleaming black with gold trim. Shpg. wt., 1 lb.

PK-171 Stereo Tone Arm with ceramic cartridge Net **2.95**

PK-172 Replacement cartridge Net **1.95**

PS 576 Replacement needle Net **.69**

DIAMOND STYLI AT LOWEST PRICES ANYWHERE

LAFAYETTE DIAMOND and DIAMOND-SAPPHIRE STYLI

MADE FOR LAFAYETTE BY THE FOREMOST AMERICAN MANUFACTURERS

KEY TO POINT CODES HOW TO ORDER

The symbols in the column headed "PT SIZE" are explained in the table below.

LP = SINGLE 1 MIL MICROGROOVE FOR 33 1/2 AND 45 RPM

AG = SINGLE 2 MIL ALL GROOVE FOR ALL SPEEDS

ST = SINGLE 3 MIL STANDARD FOR 78 RPM

COMB = DUAL 1 MIL DIAMOND AND 3 MIL SAPPHIRE

Identify your needle by cartridge number and illustration and order by stock no. Note that all our needles listed here are for monaural cartridges.

ALL DIAMOND STYLI ARE NOT ALIKE

Only Lafayette's Superior Diamond Styli are


- MADE FROM WHOLE DIAMONDS
- PRECISION GROUND AND POLISHED
- VERTICALLY AND EDGEWISE GRAIN ORIENTED
- SHADOWGRAPHED



Each Lafayette's diamond stylus is made from individual diamond, properly oriented and ground to close tolerance; shadowgraph tested to give you less wear per play and long service life.

FULL 1 YEAR GUARANTEE ANY DIAMOND or DIAMOND-SAPPHIRE NEEDLE IN THIS LISTING

2.59



STOCK NO.	SIZE PT.	FIG.	CARTRIDGE	REPLACES JENSEN NO.	STOCK NO.	SIZE PT.	FIG.	CARTRIDGE	REPLACES JENSEN NO.	STOCK NO.	SIZE PT.	FIG.	CARTRIDGE	REPLACES JENSEN NO.
DIAMOND NEEDLES														
FOR ADMIRAL CARTRIDGES					FOR MAGNAVOX CARTRIDGES					FOR SONOTONE CARTRIDGES				
PS-10	LP	1	409A11, 409A300, 98A54-1	JPS-30LPD	PS-35	LP	54	560176, 560180	CRA-55LPD	PS-35	LP	53	TO-200, TO-222, TO-284, or TO-400 series, RA284, DT60 series, TX88, A	CRA-55LPD
PS-16	COMB	6	409B21	JPS-35SD	PS-70	COMB	51	560161	S-66SD	PS-69	LP	38		CRA-56LPD
PS-17	LP	7	409A30	AB1LPD	FOR PHILCO CARTRIDGES					FOR SHURE CARTRIDGES				
FOR ASTATIC CARTRIDGES					PS-56	COMB	43	45-9612, 76-4449, 425-0016	PH-13SD	PS-16	COMB	6	WC10, WC100, PC2 series, PC3 series, PC4 series, PCS series	JPS-35SD
PS-20	LP	3	AC Series, 40T, 41T, 40-1, 41-1, 42-1, 90T series, 10L-3, 11L-3	A-75LPD	PS-56	COMB	43	45-0009, 425-0011, 425-0014	PH-13SD	PS-10	LP	1	P-72, P-73, P-73R, P-75, P-76, P-77, P-80, W-21, W-21AR, W-22A, WC-24, WC-25 Series	JPS-30LPD
PS-23	LP	12	408	M-70LPD	FOR PERPETUUM EBNER CARTRIDGES					FOR SONOTONE CARTRIDGES				
PS-25	COMB	14	GCO, 409, SS-T, SST, SSTM	A-71SD	PS-64	COMB	47	P12/RG	RX550SD	PS-70	COMB	51	1P-LB-10, 2T0, 2T5, 2T-5D, 2T-LB-0, 2T-LB-5, 2T-LB-5D, 9980-5, 9980-5D, 99800, ST, ST-LB-5, ST-LB-5D	S-66SD
PS-23	LP	12	410	M-70LPD	PS-65	COMB	48	PE-8, PE10	RX551SD	PS-32	COMB	51	3T, 3T5, 3TD	S-61SD
PS-17	LP	7	CAC, CO, CO-1, L00, L00-1, QT, QT-33, 44-T, 46-1, 48-1, 106T Series	A-81LPD	PS-66	LP	22	P7000 (MJ, MD) (LP only)	RX552LPD	FOR WEBSTER ELECTRIC CARTRIDGES				
PS-35	LP	54	110, 120, 124 series, 310T, 312T, 420, 422, 424TS series, 310-1, 310-TB, TS, 312-TB, TS, 414-1	CRA-55LPD	FOR R.C.A. CARTRIDGES									
FOR MAGNAVOX CARTRIDGES					PS-23	LP	12	74067	M-70LPD	PS-17	LP	7	BX	A-81LPD
PS-51	COMB	37	560176, 560180, 560133, 560151, 560169-1, 560170	M-50SD	PS-10	LP	1	55652, 76257, (988370-1), 75044	JPS-30LPD	PS-10	LP	1	F11	JPS-30LPD
REPLACEMENT STYLI FOR GE CARTRIDGES					STYLI FOR OLD TYPE GE CARTRIDGES (FIG. 32)					DIAMOND STYLI FOR				
FOR GE VR II CARTRIDGES (FIG. 35)					Exact replacement for all old type single needle GE cartridges. Avg. wt., 2 oz.					AS LOW AS <h1>2.59</h1>				
Direct replacements for clip-in styli in GE VR II series models 4G-050, 4G-052, 4G-053, 4G-040, 4G-041, 4G-063, 4G-061 cartridges. Avg. shpg. wt., 2 oz.														
PS-48-1 mil diamond LP clip-in stylus. Replaces GE 4G-01D Net 2.59					PS-45-Diamond 1 mil (LP) replaces GE RPJ-004 Net 2.59									
PS-546-1 mil sapphire LP clip-in stylus. Replaces GE 4G-01S Net 1.15					PS-541-Sapphire 1 mil (LP) replaces GE RPJ-005 Net .99									
PS-548-3 mil sapphire 78 clip-in stylus. Replaces GE 4G-03S Net 1.15					PS-540-Sapphire 3 mil (78) replaces GE RPJ-001 Net .99									
MODERNIZATION ASSEMBLIES (FIG. 33)					FOR GE SERIES A CARTRIDGES (FIG. 34)									
Modernize your old triple-play cartridge. These assemblies replace both the old and new series "A." Once installed, you can replace one point at a time.					Individual styli replacements that clip in to all GE "A" series. Avg. wt., 2 oz.									
DIAMOND SAPPHIRE. Replaces old RPJ-013 and new RPJ-013A. Avg. wt., 2 oz. Net 2.59					PS-47-Diamond 1 mil (LP) replaces GE RPJ-010 Net 2.59									
DUAL DIAMOND. Replaces old GE RPJ-012 and new RPJ-012A. Net 7.95					PS-543-Sapphire 1 mil (LP) replaces GE RPJ-015 Net 1.15									
DUAL SAPPHIRE. Replaces old GE RPJ-010 and new RPJ-019A. Net 2.10					PS-542-Sapphire 3 mil (78) replaces GE RPJ-035 Net 1.15									

STEREO DIAMOND STYLI 2.59 AT LAFAYETTE'S LOW PRICES!

- FOR GE GC-7**
(A) .7 mil diamond for G.E. GC-7 cartridge. PS-87 \$2.59
- FOR RONNETTE**
(B) .7 mil diamond for Ronnette turnover cartridges OV, OVI, T1 and single BF40. PS-81 \$2.59
- FOR ELECTRO VOICE**
(C) .7 mil diamond for Electro Voice series 26 stereo turnover and series 21 single needle. PS-80 \$2.59
- FOR SONOTONE**
(D) Combination .7 mil (stereo) diamond and 3 mil (78 RPM) sapphire for Sonotone 8T and 8TA PS-82 \$2.59
(D) Same as above but with .7 mil (stereo) diamond and 1 mil (monaural LP) sapphire. PS-83 \$2.59
- FOR RCA**
(E) .7 mil diamond for RCA 106770 or 106771. PS-85 \$2.59
- FOR MONARCH (BSR)**
(F) .7 mil diamond for TC85 Cartridge. PS-86 \$2.59

CONVERSAPHONE LANGUAGE COURSES

Learning languages is fun by the amazing new Conversaphone method. In minutes, you'll be understanding and speaking a new language. Expert instructor teaches you perfect pronunciation as you follow each phrase in the lesson manual. Contains 1-10"-33 1/3 RPM record and manual. Shpg. wt., 1/4 lb.

- PR-28 French Net 2.79
- PR-29 Spanish Net 2.79
- PR-30 Italian Net 2.79
- PR-31 German Net 2.79
- PR-32 Hebrew Net 2.79
- PR-33 Russian Net 2.79
- PR-34 Japanese Net 2.79
- PR-35 Portuguese Net 2.79
- PR-36 Swedish Net 2.79
- PR-37 Finnish Net 2.79
- PR-38 Norwegian Net 2.79
- PR-39 Mod. Greek Net 2.79

MULTILINGUA LANGUAGE COURSE

- FRENCH Net 6.95
- ITALIAN
- GERMAN
- SPANISH

You can now learn to speak French, Italian, German or Spanish easily and pleasantly in your own home and progress at your own speed. Features the new simplified participation method that helps you to learn the lessons faster and retain them longer. It is a complete language course with 48 lessons on two 12" hi-fi long playing records. You learn with native speakers! The recorded lessons are printed in an illustrated conversation manual. Also included is a combination of grammar and dictionary book. When ordering, please specify the language desired. Shpg. wt., 4 lbs.

- PR-15 List 9.95 Net 6.95
- 4-LANGUAGE COMBINATION COURSE All 4 languages, French, Italian, German and Spanish, on 8-12" LP records, 192 lessons, 2 books.
- PR-16 Net 10.95

NEW! EXCLUSIVE LAFAYETTE STYLOCHRON

- PROTECT YOUR PRECIOUS RECORDINGS.
 - NO MORE GUESS WORK - KEEPS AN ACCURATE RECORD OF NEEDLE USE.
- # 4.95

More precious recordings are ruined by tardy replacement of the needle than by any other cause. Now, there is no need to let this happen, especially to your doubly precious stereo recordings. Lafayette Stylochron lets you know just how long your needle has been in use so that you can replace the worn needle at the proper time, before it can do damage to your records. The Stylochron is quickly and easily mounted on your motor board or other convenient place. The moment your record changer or turntable starts, the Stylochron begins to register. It stops when the turntable stops. The 1000 hour dial will tell you at any time how long you have been using the needle. Dial is marked off in 50 hour units. You can remove your stylus for inspection at any predetermined number of hours. Diameter of the face plate is 2 1/4". Extends 1 1/2" below or behind panel. Complete with instructions. Shpg. wt., 2 lbs.



2.95 LAFAYETTE HIGH FIDELITY STEREO-MONAUROAL TEST RECORD

- TESTS RUMBLE EACH CHANNEL
- TESTS LEVEL EACH CHANNEL
- TESTS BALANCE
- TESTS EQUALIZATION
- STYLUS WEAR TEST
- TESTS RESONANCE
- INCORPORATES PHASE CHECK

A Lafayette exclusive to help you check both stereo and monaural systems. For stereo testing this two-sided 12" LP stereo record has on its stereo side two 1000 cycle bands to check the level of each channel separately; balance check to set the level of each channel using special metronome recording; rumble test. There are stylus wear test grooves on both outer and inner edges of each side to check both stereo and monaural styli. Incorporates phase adjusting check to simplify phasing of speakers. For monaural testing it provides an RIAA equalization test

4 SPEED PHONO MOTOR WITH TURNTABLE

Quiet, dependable A-C operation assured by rubber shock-mounted friction drive motor. Speed change control through idler driving on 8" turntable. Mounting centers 4 1/2" x 3 3/8"; 2 1/2" depth below base plate. Shpg. wt., 3 1/2 lbs.

ML-24 Phono and turntable Net 5.35
PK-149 Mounting board for motor Net 95c

5.35

WIRELESS BROADCASTER

Play your phonograph through any radio in the house without connecting wires. Talk through your radio by microphone.

Lafayette's new wireless broadcaster will extend your enjoyment of your phono-player to every room that has a radio. Connect phono to wireless broadcaster, tune in any radio to the wireless broadcaster, which broadcasts on an adjustable frequency between 700KC - 1700KC. Pick your spot. Will take crystal or magnetic cartridges and also microphones for voice broadcast. Has volume control with "on-off" switch. Size 4 1/2" x 5 1/2" x 1 1/2". Completely wired and assembled with all tubes and operating instructions. 110V AC/DC operation. Shpg. wt., 4 lbs.

LA-14 Wireless broadcaster Net 9.75
PA-24 Crystal microphone Net 4.25

9.75

2-TUBE PHONO AMPLIFIER

4.50 with Tubes

A two tube phono amplifier using a 50L6 and 35Z5 tube as rectifier. Well-built, good tone and volume. Contains volume control with switch. AT A BIG SAVING! Shpg. wt., 3 lbs.

PK-24-Two tube amplifier 4.50

COMPLETE WITH TUBES

TR-10 OUTPUT TRANSFORMER - matches output of either PK-23 or PK-24 to 3-4 ohm voice coil. Shpg. wt. 1/2 lb.

TR-10 singly, ea. .49 in lots of 5, ea. .45

AC-DC Phono Amplifier

2.95

Equipped with a variable tone control and a separate volume control. Delivers two watts output. Phonograph motor connects to the amplifier. Uses 12AT6, 50B5, and 35W4 rectifier. For 110-120V, 60 cycles AC or 110-120 V. DC. Supplied with line cord and plug, but less tubes. Shpg. wt. 2 lbs.

KI-59 Net 2.75
PK-23 2.95

KIT OF TUBES

Complete set of 3 tubes for above. Shpg. wt., 1 lb.

99c LAFAYETTE SPECIAL VALUE STYLUS PRESSURE GAUGE

With the advent of stereo records, correct stylus pressure becomes all important in obtaining the best reproduction and least stylus and record wear. Lafayette's stylus pressure gauge is an accurate device that allows you to read gm. No spring and minimum moving parts. Shpg. wt., 1 lb.

PK-223 Net 99c

NEW! AUTOMATIC CUT-OFF

- Automatically Turns Off Hi-Fi System
- Plugs In—No Special Wiring
- May Be Used With Record Changer Employing Automatic Shut-Off

SPECIAL PRICE 3.45

Automatically shuts off complete Hi-Fi system after last record has been played. May be used with record changer employing an automatic shut-off. Components are plugged into unit which in turn plugs into AC power outlet. Provision for automatic or manual operation. Mounts externally or internally. Size 5 1/2" x 2" x 1 1/2"

PK-284 Net 3.45

Lafayette

LEADS IN TAPE RECORDING VALUES!



ALL LAFAYETTE TAPES SOLD ON MONEY-BACK GUARANTEE
GUARANTEED FIRST QUALITY SPICE-FREE

You Be The Judge!

NEW! MYLAR BASE RECORDING TAPE

Lafayette's huge purchasing power makes it possible to provide you with first-quality tape at about half the price you would pay for the same tape with the manufacturer's own labels. WE GUARANTEE ABSOLUTE SATISFACTION OR YOUR MONEY BACK. These splice-free mylar base recording tapes are quality manufactured to assure uniformity of frequency response and complete absence of drop-outs. In addition, they are extremely durable and break-resistant and are capable of withstanding temperature and humidity changes. The wide frequency response characteristics combined with low noise level and long playing time opens new horizons of recording possibilities for the high fidelity enthusiasts as well as professional sound engineers. Av. Shpg. wt., 12 oz.

RT-12 1800 ft. on 1 mil Mylar base, 7" reel diameter. Lots of 5, Ea. 2.25 Singly, Ea. **2.50**
RT-13 2400 ft. on 1/2 mil Mylar base, 7" reel diameter. Lots of 5, Ea. 3.39 Singly, Ea. **3.69**

ACETATE BASE RECORDING TAPE

These popular high quality tapes are coated uniformly with red oxide on plastic base with high output and uniform frequency response covering the entire audio spectrum, 40-15,000 cps, completely splice-free. Another Lafayette outstanding value for all hi-fi recordists, backed up by our Money Back Guarantee. Using 7 1/2 cps dual track, 1200 ft. reel provides 1 hr. of recording time while 1800 ft. reel provides 1 1/2 hr. of recording time. Avg. Shpg. wt., 14 oz.


RT-10 1200 ft. on 1 1/2 mil acetate base, 7" reel. Lots of 5, Ea. 1.49 Singly, Ea. **1.59**
RT-11 1800 ft. on 1 mil acetate base, 7" reel. Lots of 5, Ea. 1.88 Singly, Ea. **1.98**

NEW! LAFAYETTE TENSILIZED MYLAR RECORDING TAPE

Strong and durable because it has been pre-stretched. Shipping weight 1 lb.

RT-16 2400' on tensilized mylar base. Lots of 5, Ea. 4.45 Singly, Ea. **4.95**

NEW! TELEPHONE PICKUP COIL



1.89

This telephone pick-up coil is designed to feed into the microphone input of either a tape recorder or any high gain amplifier. The pick up can be easily attached to the telephone by the use of a rubber suction type attachment. The coil is electrostatically shielded to minimize hum pick-up. When properly positioned on a telephone handset, the output of this device is more than adequate for a fully modulated tape recording. Complete with 5' shielded cable. Shpg. wt., 6 ozs.

MS-693 Net 1.89



TAPE SPLICER WITH WAIST-TYPE SPLICE




QUANTITY LIMITED! **98c**

Over **70% off!**

Here's a terrific value! The famous RCA Autosplicer cuts a diagonal flap joint in the tape and trims the splicing tape and tape edges with an indented trim cut. The slight "waists" formed prevent adhesive from contacting recorder mechanism and prevent layer-to-layer adhesion. No more "wow", "flutter", or erratic performance due to adhesive deposited on tape guides, etc. Consists of a tape alignment guide with self-adhesive back for fastening to any surface, cutting unit with diagonal cutter on one side and waist-type cutters on other, and protective cover for blades. Shpg. wt., 6 oz. SP-144 Net .98

TELEPHONE PICKUP FOR RECORDING TELEPHONE CONVERSATIONS



Induction telephone pickup. Telephone conversations can now be picked up with no tapping of wires or special telephone circuits. Simply place the phone base, either cradle or upright type, on the pickup platform and connect the leads to the high impedance input of any medium gain audio amplifier, or directly to any tape, disc or wire recorder. Shpg. wt. 8 ozs. MS-16 Net 1.95 **1.95**

ROBINS TAPE THREADER

No more awkward fumbling while threading a reel. A few turns on the crank and you're ready to play or record. Saves time and tape. Shpg. wt., 2 oz. MS-22279

EMPTY PLASTIC REELS



Individually boxed plastic reels for recording tape. Avg. Shpg. wt., 4 oz. singly.

MS-692. 5" reel. In lots of 6, Ea. .26 Singly, Ea. .29
MS-267. 7" reel. In lots of 6, Ea. .38 Singly, Ea. .45

METAL STORAGE CANS

Your best protection for valuable recorded tapes and movie film. Cans are ribbed for easy storage. Precision fit makes opening and closing easy. Attractively finished in grey. 3 sizes to choose from to fit any size reel. Av. shpg. wt., 8 ozs.

ML-154 3" Can. lots of 6, Ea. .18 Singly, Ea. .20
ML-155 5" Can. lots of 6, Ea. .27 Singly, Ea. .30
ML-61 7" Can. lots of 6, Ea. .36 Singly, Ea. .39



METAL TAPE STORAGE CHEST


STANDARD CASE Sturdy all steel carrying case. Holds 12 7" or 5" reels and cans. Twin snap locks for positive closure; perfect portability. Guards against exposure and accidental erase. Platinum gray hammerloid finish. Metal separators between reels. Includes index cards. Shpg. wt., 5 lbs. ML-60 Net 2.99

NEW! Lafayette BULK TAPE ERASER AND DEMAGNETIZER

PROFESSIONAL MODEL

- Completely Erases Tape
- Two Erasing Coils
- Erases up to 1" Tapes
- Erases 1/2" Tapes in One Operation
- No Reversing
- For 3", 5", 7" or 10 1/2" Reels

18.95



A carefully designed and precisely manufactured professional tape "degusser" for complete erasing of tapes. Just place the tape reel on spindle of demagnetizer, slowly rotate 2 or 3 turns, take off, and that's all. Reduce tape hiss to the level of new "virgin" tape. Two completely separate coils are used for doubly-effective erasures, even of large, 10 1/2" reels. Will erase 1" wide tape. An extra powerful unit for heavy-duty use—draws over 9 amperes. Can be used to demagnetize tape, magnetically stripped film, plus tools and watches. Has a heavy, custom finished case, a rugged non-magnetic top, heavy duty on-off switch and power cord. Has built-in fuse. Pilot light prevents accidentally leaving it turned on. Size 6 1/4" x 7 1/8" x 3 1/2". For 117 volts, 60 cps. Shpg. wt., 14 lbs. ML-120—Regularly 49.95 Net 18.95

STANDARD MODEL

- Top Value
- Reduces Noise Level
- Takes Reels Up To 10 1/2"

12.50



A bulk tape demagnetizer that erases existing recorded signals and noise from magnetic tapes quickly and efficiently. Also capable of demagnetizing metal parts and work tools. Ideal for the recording enthusiast desiring clean, noise-free tones. Simply rotate reel of tape several turns over unit, turn over and repeat once. Has two spindle positions: inner position for tape reel sizes up to 7" in diameter, and the outer one for 10 1/2" reels. Push button energizes the coil, and a pilot light installed on top of the unit indicates unit in operation. Non-magnetic bakelite plate for tape reel rest. One powerful coil is used for effective erasure of all quarter-inch tapes. Current consumption—5 amps. Heavy duty, rugged gauge metal case. Attractive finish. For 105-125 volts, 60 cycles. Size 7 1/2" x 4 3/4" x 3 1/2". Shpg. wt., 9 lbs. ML-176 Net 12.50



3.95

LAFAYETTE TAPE HEAD DEMAGNETIZER

- REMOVABLE POLEPIECES
- EXTRA CONVENIENT

Lafayette Tape Head Demagnetizer uses removable polepieces. Three complete sets are furnished: straight, 45°, and 90° (right angle), permitting quick and easy use with any tape head. Far from being a luxury, a tape head demagnetizer is necessary for best tape recorder performance. Although unmagnetized when new, tape heads gradually become magnetized by sharp switching pulses occurring while switching the recorder from play to record or vice versa. The solution is to use a demagnetizer to re-

move this permanent magnetism from the head, thus reducing the noise level. Periodic head demagnetization is required for all tape recorders to insure optimum signal-to-noise ratio. Now Lafayette enables anyone with even the most modest budget to perform this necessary demagnetization with a minimum of effort. For 110 volts, 60 cycles. Shpg. wt., 1 lb. PK-238—Tape Head Demagnetizer 3.95

LAFAYETTE SCOOPS the TAPE RECORDER INDUSTRY!

Never Before Such Exceptional QUALITY and VALUE!

54.50 ONLY 5.00 DOWN

- Completely Portable—Carry it Anywhere!
- Two Speeds—3 3/4 or 7 1/2" Per Second
- Uses Standard 5" Reel • Frequency Response 60-8,500 C.P.S.

LAFAYETTE LEADS THE AUDIO WORLD WITH THIS FANTASTIC TAPE RECORDER BUY. Indeed we can honestly say there has never been a tape recorder value that compares to this remarkable instrument. Perfect for home, school or office. At home, the RK-400 proves ideal for parties or recording your favorite musical performance. Use it at school for lectures, notes or voice training. In the office its small size lends itself ideally for dictation or sales presentations. Handy fool-proof operation has been provided by a single rugged function control (reverse, stop, play and record) and separate on/off volume control. Speeds are adjustable from 3 3/4" to 7 1/2" per second by a simple




DELIVERY APPROXIMATELY JANUARY 25, 1960

capstan adjustment. At 3 3/4 ips the RK-400 provides up to one hour of recording time on a standard 600 ft. 5" reel of tape. Special 5" heavy duty permanent magnet speaker furnishes an exceptionally fine tonal quality. Record level indicator light facilitates recording by showing you when volume control is correctly set. Jacks are provided for microphone, phono and extension speaker (special alligator clip card is supplied.) Complete with sensitive crystal microphone. Finished in attractive scuff resistant pyroxylin material. Dimensions: 11 3/4" x 9 7/8" x 7 1/8". For 110 volts 50-60 cycles. Shpg. wt., 20 lbs. RK-400 5.00 Down Net 54.50

ACOUSTIC BAND EXTENDER

Converts Any 12" Hi-Fi Speaker To A Complete 4-Way System

- MOUNTS AXIALLY ON 12" SPEAKER
- ELIMINATES EXTRA CARPENTRY
- 3-WAY INTEGRATED SPEAKER
- FROM 1,000 TO 18,000 CPS
- 25 WATTS RATING
- BUILT-IN CROSSOVER



10.95

A real boon to the hi-fi enthusiast who has a single speaker and wants to extend the upper tonal range of his system and at the same time improve the vital middle ranges for better realism and fuller enjoyment. The Acoustic Band Extender includes 3 acoustic channels in one housing. One channel, 1-3.5 kc, is a rear loading exponential dual flared horn energized by the rear of the driver diaphragm. The second channel, 3.5 to 5.5 kc, is a front-loading dual horn, while the third channel, 5.5 to 18 kc, is direct free aperture loaded. Wide-angle sound radiation is assured by the design for thorough distribution of the added brilliance and presence supplied by this unit. The driver unit has a highly efficient 3.2 oz. Alnico 5 slug magnet and a custom-molded linen phenolic diaphragm for minimal distortion. Built-in 1000 cps high-pass filter. Universal mounting-rests within a 12" speaker—or may be mounted separately with a 10 1/4" x 3 1/4" rectangular cutout. Impedance 9 ohms; power handling 25 watts. Shpg. wt., 2 1/2 lbs. SK-120 Net 10.95

SENSATIONAL VALUES in Stereo Turntables and Changers

WHAT THE TECHNICAL PRESS* IS SAYING ABOUT THE PK-245

high fidelity

HiFi REVIEW

High Fidelity

"... an excellent buy at a much higher price."

"The workmanship in the entire assembly is excellent — all parts are snugly assembled...
"Speed regulation was excellent. No wow or flutter was audible on any kind of musical material. Checks with a stroboscope disc indicated that, at all speed selector settings... was precisely on speed, and maintained this speed under the heaviest loads that would be imposed by a playback pickup."

Hi-Fi Review

"... of the highest caliber..."

"A good gage of a turntable is the freedom after the motor has been stopped. Freedom of movement permits the turntable to revolve under its own momentum. The model revolves about as long as any top-quality turntable we've tested — 135 seconds."

*The technical staff of the publication carefully inspects and tests the unit. Their evaluation as to what the unit does, how it does it, and how it sounds, is based upon use in their laboratories.

LAFAYETTE PROFESSIONAL TURNTABLE WITH AUTHENTIC HYSTERESIS SYNCHRONOUS MOTOR PERFECT FOR NEW STEREO & MONAURAL RECORDS

PROFESSIONAL 4-SPEED TURNTABLE WITH HYSTERESIS-SYNCHRONOUS MOTOR

The LAFAYETTE TRUE HYSTERESIS-SYNCHRONOUS MOTOR. Since many so-called "hysteresis" motors have appeared and will continue to appear on the market, it is important that you know the difference between the real thing, as provided by Lafayette, and the imitators, with partial hysteresis motors.

THE LAFAYETTE TRUE HYSTERESIS SYNCHRONOUS MOTOR IS PERFECT FOR THE NEW STEREO AND MONAURAL RECORDS. THE FACT THAT THE NEW STEREO RECORDS CONTAIN VERTICAL MODULATION IMPOSES STRINGENT REQUIREMENTS ON TURNTABLES. THEY HAVE TO BE FREE FROM RUMBLE, FLUTTER, WOW AND SPEED VARIATION. THE LAFAYETTE TRUE HYSTERESIS SYNCHRONOUS MOTOR MEETS ALL THESE REQUIREMENTS WITH EFFORTLESS EASE, RESULTING IN SUPERIOR REPRODUCTION OF STEREO DISCS, AS WELL AS TREMENDOUS REDUCTION IN RECORD WEAR.

ONLY LAFAYETTE'S HYSTERESIS-SYNCHRONOUS MOTOR, in its price class, is made to extremely fine tolerances (on the order of .00001 inches!) Only Lafayette's motor has 16 cores, a high permeability rotor magnet, ball thrust bearings, oilite sleeve bearings plus felt oil reservoir, cooling fins as an integral part of the rotor and a hollow rotor core for maximum efficiency and minimum heat. Only Lafayette's motor can be oiled from above, without disassembly, through a unique oil feed system. Only Lafayette's motor has a self-aligning armature.

ONLY LAFAYETTE CAN GIVE YOU A REALLY PROFESSIONAL TURNTABLE WITH TRUE HYSTERESIS-SYNCHRONOUS MOTOR AT SUCH AMAZINGLY LOW PRICES!

Here's THE turntable—the last word in professional high-fidelity performance! A fine precision instrument in every sense. Just look at some of these OUTSTANDING FEATURES—WOW AND FLUTTER: Less than 0.2% • TURNTABLE: Heavy, diecast aluminum. Lath-turned for perfect balance and concentricity, 12" diameter—weighs approx. 4 lbs. and provides amazingly constant speed; the extra-heavy rim acts just like a flywheel to prevent speed variations • TRUE HYSTERESIS-SYNCHRONOUS MOTOR: For smooth, low-noise, wow- and flutter-free operation • RUMBLE AND NOISE: 50 db below average recorded level • INTEGRATED SPEED CONTROL: For all 4 speeds—78, 45, 33 1/3 and 16 2/3 rpm • 2 OVERSIZE, HEAVY DUTY IDLERS: Precision-ground, provide positive constant-speed rim drive • SINGLE BALL THRUST BEARING: Turntable rides smoothly over ball bearing floating on thin film of oil • FREE-FLOATING, SHOCK-MOUNTED MOTOR • RUBBER CUSHION SHOCKMOUNTS • AUTOMATIC IDLER DISENGAGEMENT • RUBBER MAT • STAINLESS STEEL PRECISION SPINDLE • POWER REQUIREMENTS: For 105-130 volts, 60 cps AC; draws 16 V.A. • ACCESSORIES SUPPLIED: 45 RPM adapter, Strobe disc • SIZE: 2 1/8" above and 4" below motor board; 14 3/4" deep x 12 1/4" wide • SHIPPING WEIGHT: 16 lbs.

LAFAYETTE MODEL PK-245W 5.00 Down Net 64.50

LAFAYETTE MONEY-SAVER COMBINATIONS

(Base not included—see above for selection of woodbases)

COMBINATION WITH 16" ARM				COMBINATION WITH 12" ARM			
COMB. NO.	TURNTABLE	TONE ARM	SPECIAL NET	COMB. NO.	TURNTABLE	TONE ARM	SPECIAL NET
PK-424WX	PK-245	PK-280	GE VR 225 87.95	PK-425WX	PK-245	PK-270	GE VR 225 85.99
PK-427WX	PK-245	PK-280	E-V 31MDS 87.95	PK-429WX	PK-245	PK-270	Pickering 371A 85.95
PK-428WX	PK-245	PK-280	Pickering 371A 87.95	PK-431WX	PK-245	PK-270	E-V 31MDS 85.95

Average Shipping Weight of these combinations is 18 lbs. 5.00 Down


VALUE ~~129.50~~ ONLY 64.50
SAVE OVER 50%
5.00 DOWN



FOR COMBINATION OFFER
SEE TABLE AT LEFT

DELUXE WOODBASES AND MOUNTING BOARDS FOR TRANSCRIPTION TURNTABLES

NET
14.95



- FINEST SELECTED HARDWOOD VENEERS
- CHOICE OF FIVE CABINETMAKER FINISHES
- FREE-FLOATING FOAM RUBBER MOUNTED MOTOR BOARD
- INDIVIDUALLY ADJUSTABLE FEET FOR ACCURATE LEVELING

These substantial woodbases are deluxe units made from the finest selected hardwood veneers by skilled craftsmen. All four sides are 3/4" thick and the top is 1/2". All have firmly secured mitered corners. The four bumper feet are individually adjustable for accurate leveling. The free floating mounting board is foam rubber mounted and the top has a finish matching the woodbase. Available in five attractive cabinetmaker finishes: mahogany, blonde, ebony, walnut and fruitwood; please specify when ordering. The elegant styling and finish add beauty to any high fidelity installation. Accommodates a turntable and a 12" or 16" tone arm. Size, 21 1/2" x 16 1/2" x 4 3/4". Shpg. wt., 15 lbs. Base and board cut for Lafayette PK-245 turntable. Net 14.95

PK-265W Net 14.95
Base and board cut for Lafayette PK-240 turntable. Net 14.95
PK-266W Net 14.95
Base and board uncut for mounting other makes of turntables. Net 14.95
PK-267W Net 14.95
Base and board for Lafayette PK-331 turntable. Net 14.95
PK-335W Net 14.95

Pre-cut, unfinished, smoothly sanded mounting boards for Lafayette turntables. Ready for easy finishing. Size 13 1/2" x 20 1/2" x 3/4". Shpg. wt., 3 lbs.

PK-268W. Cut for Laf. PK-245 turntable Net 3.75
PK-269W. Cut for Laf. PK-240 turntable Net 3.75

NEW! Lafayette VISCIOUS-DAMPED STEREO TONE ARM

—THE PROFESSIONAL 12" PK-90S



12.95

- JEWEL BEARING SUPPORT
- INSTANT PLUG-IN CARTRIDGE CHANGE
- AUTOMATIC FLUID CONTROL
- PERFECT RECORD TRACKING
- ACCOMMODATES MOST STEREO & MONAURAL HIGH FIDELITY CARTRIDGES

This Stereo/Monaural transcription arm assures dependable and stable operation, utilizing the floating-action principle of viscous-damping. The arm is supported at a single point by a pivot and level bearing having negligible friction. Damping is accomplished by a silicone fluid occupying the gap between a ball and socket. This damping control permits high compliance and negligible tracking error and prevents damage to either record or stylus should the tone arm be accidentally dropped. Low frequency resonance, skidding and groove-jumping are likewise minimized. The tone arm accepts all records up to 12" and accommodates virtually all Stereo or Monaural hi-fi cartridges by means of precisely engineered adapters which simplify installation and provide proper stylus pressure. The arm has a decorative glossy-black finish. Overall length is 12"; height adjustable from 1/2" to 2 1/4" above motorboard; round mounting base is 2 1/4" in diameter. Shpg. wt., 2 1/2 lbs.

PK-90S—12" VISCIOUS-DAMPED STEREO TONE ARM
Net 12.50

PK-240 ONLY
37.50



FOR COMBINATION OFFER
SEE TABLE AT RIGHT

LAFAYETTE 4-SPEED PROFESSIONAL TRANSCRIPTION PLAYER WITH 3 LB. 12" ALUMINUM TURNTABLE

- IDEALLY SUITED FOR STEREO! • BETTER THAN -50 DB RUMBLE & NOISE • VIBRATIONLESS MOTOR SUSPENSION • BELOW 0.2% WOW & FLUTTER • MAGNETIC EDDY-CURRENT BRAKE
- 3 LB. 12" BALANCED & MACHINED ALUMINUM TURNTABLE • SPEED CONTROL FOR ± 7% VARIATION OF EACH SPEED

An amazing low price for the superior quality embodied in this fine instrument. Features include heavy, rim-weighted, 3 lb. machined-aluminum 12" turntable, magnetic brake with speed control for ± 7% variation of each speed; the extremely low noise and rumble figure of -50 db below average recorded level; wow and flutter (speed variations) of less than 0.2%; new-type oversize precision-ground idler with special lubrication features; positive-locking detents on 4-speed single-knob speed selector; ("off" positions between all speed positions; free-floating shock-mounted motor; automatic idler disengagement in "off" positions; precision spindle turns on single ball bearing; heavy duty 4-pole induction motor. Heavy rubber turntable mat. For 105-120 volts, 60 cps AC; draws 0.13 amperes. Size of motor plate 11" x 10" x 1 1/2"; requires 4" below motor board, 1 1/2" above. Complete with stroboscope disc, 45 rpm adapter, AC line cord. Shpg. wt., 14 lbs.

PK-240 w 12" TRANSCRIPTION TURNTABLE 2.00 Down Net 37.50

LAFAYETTE SUPER-VALUE COMBINATIONS

Save on these combinations of Lafayette turntables, arms and nationally famous stereo diamond cartridges. For selection of wood bases see above

COMB. NO.	TURNTABLE	TONE ARM	CARTRIDGE	SPECIAL NET
PK-411W	PK-240	PK-270	GE VR-225	61.50
PK-412W	PK-240	PK-270	Pickering 371A	61.50
PK-413W	PK-240	PK-270	E-V 31MDS	61.50
PK-415W	PK-240	PK-280	GE VR-225	63.50
PK-416W	PK-240	PK-280	Pickering 371A	63.50
PK-417W	PK-240	PK-280	E-V 31MDS	63.50

Average shipping weight of these combinations is 16 lbs. 5.00 Down

THE REVOLUTIONARY NEW LAFAYETTE VERTICAL-LATERAL KNIFE-EDGE 12" & 16" STEREO TONE ARMS!

- 4 HARDENED-STEEL KNIFE-EDGE PIVOTS & BEARINGS FOR COMPLETE, PRACTICALLY FRICTIONLESS, FREEDOM OF MOTION
- LIGHTWEIGHT, DIE-CAST ALUMINUM TONE ARM
- EQUIPPED WITH UNIVERSAL PLUG-IN SHELL FOR ALL POPULAR STEREO CARTRIDGES
- SELF-CONTAINED BUBBLE LEVEL FOR PERFECT, GUESS-FREE LEVELLING
- PRECISELY-ADJUSTABLE COUNTERBALANCE WEIGHT
- NON-RESONANT WITHIN THE AUDIBLE FREQUENCY RANGE
- PERFECT TRACKING WITH THE LIGHTEST STYLUS FORCE

RUGGED CONSTRUCTION — FOOLPROOF — TROUBLE FREE


A remarkable advance in tone arm design is presented in these new Lafayette tone arms. An unusual new principle, utilizing 2 vertical and 2 lateral hardened-steel knife-edge pivots supported by hardened steel bearings, provides extremely low horizontal and vertical friction. This unusual type of bearing provides minimum waveform distortion and no undesirable motion or loose-jointed action as viewed from the stylus end. Groove tracing is smooth, with excellent tracking even with very light pickup weight, due to the absence of frictional losses. Friction in horizontal and vertical directions is low, but mechanical impedance is high at 45°, providing maximum effectiveness with 45-45 stereo cartridges. The unique knife edge bearing construction makes it possible to draw out the shielded cable from the center of the support column, eliminating "stiffness friction" due to the cable. A highly precise bubble level is provided at the top of the support column; the bubble plus 3 adjustments on the base, provide perfect leveling. Height of the arm is adjustable from 1 1/2" to 2 1/4" above motorboard. Overall length of the PK-270 12" arm is 13". Linear distance from support column to stylus tip is 10-5/16"; the PK-280 16" arm is 14 1/4" overall, effective length is 11-13/16".

PK-270 Lafayette 12" Tone Arm. Shpg. wt., 1 1/2 lbs. Net 17.50
PK-280 Lafayette 16" Tone Arm. Shpg. wt., 2 lbs. Net 19.50

PK-270
12" STEREO
TONE ARM 17.50

PK-280
16" STEREO
TONE ARM 19.50

PLUG-IN HEADS
FOR POPULAR
STEREO CARTRIDGES



REVOLUTIONARY NEW
VERTICAL-LATERAL
KNIFE-EDGE BEARINGS
FOR COMPLETE FREEDOM
OF STEREO MOTION

LAFAYETTE COMPLETE STEREO TRANSCRIPTION PLAYER



26.95
(LESS BASE)

- 5-CONTACT PLUG IN HEAD FOR ALL STEREO CARTRIDGES • 4-SPEED, HEAVY DUTY 4-POLE TRANSCRIPTION TYPE INDUCTION MOTOR • MAGNETIC BRAKE FOR ± 7% SPEED ADJUSTMENT • STYLUS WEIGHT ADJUSTMENT SCREW ON TONE ARM • RUMBLE AND NOISE — 40 DB • LESS THAN 0.3% WOW

This top quality manual player features a 5-contact plug in head to accommodate the latest stereo as well as monaural cartridges. The lightweight tone arm is an integral part of the mounting plate and requires no installation. The new 4-speed turntable assembly is equipped with a quiet, heavy duty 4-pole motor, with an exclusive magnetic brake for instantaneous fine adjustment of each speed. Stroboscope disc also included. Smooth operation is assured further by the 10" heavy turntable, fitted with rubber mat. Provision for easy adjustment of stylus pressure is available. Dimensions of mounting plate 12-15/16" left to right, and 10 1/2" front to rear. Requires 2 1/4" below and 3" above motor board. For 105-120V, 60 cps. Accessories included: 45 rpm adaptor, output cable and plug in heads. Shpg. wt., 14 lbs.


PK-1605W—Complete stereo transcription player, less cartridge 2.00 Down Net 26.95
PK-438W—Same as above, but with new GE VR 225 stereo cartridge with diamond stylus. 2.00 Down 39.95
PK-162W—Wood base for above, in mahogany or blonde (Please Specify). Shpg. wt., 5 lbs. Net 3.95
PK-163W—Unfinished mounting board for above. Strong durable 3/4" gumwood. (Shpg. wt., 1 lb.) Net .95

Announcing THE FABULOUS NEW Lafayette

Brought To You By Lafayette Research — Engineered To Set A New Standard Of Speaker System Excellence



PATENTS APPLIED FOR IN UNITED STATES, ENGLAND AND CANADA




ELIPTOFLEX

64.50
ONLY 5.00 DOWN


FINISHED ON 4 SIDES

Adapts to any room arrangement. Place horizontally on shelves or vertically on the floor.



PERFORMANCE EXPLANATION

The loudspeaker is mounted on a baffle recessed in the cabinet shell with the front plate extending partially across the front surface of the baffle forming ducts or tubes from the port openings to the outside air. The elliptical cutout changes the effective length of the duct as the frequency changes. This variation in path lengths provide an extremely smooth transition from duct to free air; broadens the frequency response and provide better transient response. A triangular shaped diffracting ring mounted on the front of the baffle board virtually eliminates undesirable cancellation effects normally produced by close coupling of front and rear cone radiation. This results in a "lens" effect, changing relative particle velocities and consequently, phase relationships so as to produce a smooth transition from front to rear radiation. Comparative laboratory and listening tests indicate that "Eliptoflex" performance is demonstratively superior throughout the audio spectrum.



▶ NOW IT IS POSSIBLE TO HAVE ALL THE ADVANTAGES OF A HIGH EFFICIENCY 12" SPEAKER IN A BOOKSHELF SIZE ENCLOSURE.

▶ SPECIALLY DESIGNED 12" COAXIAL SPEAKER WITH SHEEPSKIN CONE EDGE SUSPENSION AND 1 1/4 LB. MAGNET PROVIDE A RESPONSE FROM BELOW 30 TO 15,000 CPS.

▶ ENCLOSURE BEAUTIFULLY FINISHED ON FOUR SIDES IN HAND RUBBED VENEERS.

The "Eliptoflex" is the result of an intensive research program whose 3-fold purpose was to:

- 1 Develop a speaker system that would meet the space requirements of stereo.
- 2 Utilize the full advantages of efficient 12" speaker performance.
- 3 Provide optimum performance without the use of large wattage expensive amplifiers.

The Results Were Remarkable... The Eliptoflex utilizes a unique elliptical port which broadens frequency response and provides better transient response. A specially engineered diffracting ring eliminates cancellation effects between front and rear radiation. These engineering advances are coupled with the famous Lafayette free edge SK-58 12" coaxial speaker with 3" cone type tweeter, 1 1/4 lb. TSK-5 high-flux density magnet special 3/8" wide sheepskin cone-edge suspension and built-in and crossover network level control.

ortion and rich robust bass hitherto found only in large enclosure speaker systems or inefficient bookshelf speakers many times its price requiring high powered amplifiers. Due to its highly efficient design characteristics the "Eliptoflex" does not require costly high wattage amplification.

The "Eliptoflex" speaker system is beautifully finished on 4 sides in a variety of hardwood veneers for attractive room placement either horizontally or vertically. Dimensions are 14"H x 23-7/16"W x 13-5/16"D. Shpg. wt., 35 lbs.

Set of attractive Wood Runner Feet attaches on horizontal or vertical sides. Adds 1" height. Shpg. wt., 1 lb.

SY-381WX "Eliptoflex" Speaker System (Mahogany).....	Net 64.50
SY-382WX "Eliptoflex" Speaker System (Walnut).....	Net 64.50
SY-383WX "Eliptoflex" Speaker System (Blande).....	Net 64.50
SY-384WX "Eliptoflex" Speaker System (Oiled Walnut).....	Net 64.50
SY-392WX "Eliptoflex" Speaker System (Unfinished furniture grade birch).....	Net 59.50
CAB-44W (Mahogany).....	Net 1.45
CAB-45W (Walnut).....	Net 1.45
CAB-46W (Blande).....	Net 1.45



NEW! LAFAYETTE SK-125 HI-COMPLIANCE 3-WAY SPEAKER SYSTEM

8" Woofer - 6 1/2" Mid-Range - 2 1/2" Tweeter



COMPLETELY ASSEMBLED INCLUDES 3-WAY CROSSOVER NETWORK

- VARIABLE BALANCING CONTROL
- FREQUENCY RESPONSE FROM BELOW 35 TO 18,000 CPS
- SOLID VENTED, DUCTED-PORT TYPE ENCLOSURE
- FINISHED ON 4-SIDES FOR SHELF OR FLOOR PLACEMENT
- PERFECT FOR STEREO

Lafayette has succeeded in achieving a standard of performance formerly associated only with very large speaker systems. This complete 3-way speaker system, incorporates advanced Hi-Compliance speaker design in an extra rigid vented, ducted-port type enclosure, lined throughout with acoustic material. The natural, full bass, faithful mid-range and clear sparkling highs are startling from a speaker system of such small proportions. Employing a 3-way LC crossover network with a variable 10-position balancing control, it is possible to match the speaker system to individual room acoustics and listening tastes. Frequency response is from below 35 to 18,000 cps. with a power handling capacity of 25 watts. Impedance 8-16 ohms. Finished on all 4 sides in attractive hand-rubbed mahogany or walnut veneers (please specify). Dimensions are 24"W x 11"H x 10 1/4"D. Shpg. wt., 26 lbs.



SK-125WX HI-COMPLIANCE 3-WAY SPEAKER SYSTEM.....	2.00 Down	Net 49.50
SET OF 2-SK-125WX SPEAKER SYSTEMS FOR STEREO.....	5.00 Down	Net 98.00


New LAFAYETTE ULTRA-COMPLIANCE MECHANICAL 2-WAY SPEAKER SYSTEM

- ESPECIALLY DESIGNED VENTED, TUNED, DUCT TYPE ENCLOSURE
- UNIQUE MECHANICAL 2-WAY SPEAKER WITH EXTRA HEAVY MAGNET
- BEAUTIFULLY FINISHED ON 4 SIDES
- EXCELLENT FOR STEREO
- ONLY 10 1/2" H x 18 1/8" L x 8 1/8" D

\$17.50 OUTPERFORMS SPEAKERS DOUBLE LAFAYETTE'S LOW PRICE



COMPLETELY ASSEMBLED



SK-124WX MECHANICAL 2-WAY SPEAKER SYSTEM.....	Specify Finish	Net 17.50
SET OF TWO SK-124 WX SPEAKER SYSTEMS FOR STEREO.....	2.00 Down	Net 34.00

Lafayette has indeed wrought a small miracle in engineering such acoustic excellence into so small a package. Smooth, distortion free response with a deep fundamental bass and clean pure highs that give no indication of its small size and price. The perfect speaker for that high quality installation in your home, office or restaurant—two are ideal for stereo. The speaker features unique dual cone construction with extra heavy magnets. Both tweeter and woofer "float" on flexible, corrugated edges with the outer edge of the tweeter cone attached to the mid-section of the woofer cone. This results in a mechanical crossover so that both cones operate in phase at low frequencies, but only the tweeter cone operates at high frequencies. The same type of wide-range frequency response normally found only in true coaxial or multiple speaker systems is provided. Frequency response of 40-16,000 cps. Impedance 8-16 ohms. Cabinet is finished on 4-sides in hand-rubbed mahogany and walnut for attractive horizontal or vertical placement anywhere in the room. Dimensions are 10 1/2" H x 18-7/16"L x 8-7/16"D. Shpg. wt., 15 lbs.

AN EXCITING NEW SPEAKER DEVELOPMENT



New! Lafayette COMPRESSION-HORN TWEETER

- RESPONSE 1500-16,000 CPS
- 20 WATTS • EXPONENTIAL HORN
- FOR 2-WAY, 3-WAY OR 4-WAY SPEAKER SYSTEMS
- WIDE-ANGLE DISPERSION OF HIGHS
- FOR TOP OR IN-CABINET MOUNTING

ONLY **8.95**

A high quality compression-driver tweeter with a frequency response of 1500-16,000 cps and a continuous duty rating of 20 watts. Vertical positioning of the mouth of the exponential horn provides widest dispersion of high frequencies at ear-height. With chrome-plated fork-type swivel base. Flux density is a high 13,500 gauss for greatest efficiency; crossover range is 2800 cps or higher, with 4000-5000 cps recommended for 3-way systems; the wide, smooth response range permits it to be used with 2-, 3-, or 4-way speaker systems. The exponential horn is a heavy, one-piece casting non-resonant within the audible frequency range. Voice coil impedance is 8-16 ohms. Chrome-plated screw terminals for easy connections. Overall height with swivel stand is 4 1/4"; width 2 1/4"; behind-panel mounting requires a rectangular cutout (lang axis vertical) 1 1/2" x 4-3/16". Shpg. wt., 3 lbs. SK-105 Compression-driver Horn TweeterNet 8.95

2 OR 3 WAY CROSSOVER NETWORK



- 4 CROSSOVER FREQUENCIES
- L PAD BALANCE CONTROLS
- EASY TO USE
- IMPEDANCE 16-OHMS

8.75

The LN-7 Crossover Network combines quality performance, beauty and versatility at an unbeatable price. It can be used in a two-way system by crossing over at 500 cps or 3300 cps, and in a three-way system by utilizing the two simultaneously. The change from a 2-way to a 3-way 6 db per octave network may be accomplished easily. Complete with two level balance controls. Size: 5 1/2" x 2 1/2" x 2 1/2". Shpg. wt., 2 1/2 lbs. LN-7Net 8.75

SPECIAL COMBINATION



FAMOUS LAFAYETTE-GOODMAN 15" 3-WAY SPEAKER WITH HIGHBOY OR LOWBOY CABINET

AS LOW AS **79.50**

5.00 DOWN

Now you can obtain what is conceded to be the greatest performance value on the hi-fi market—and save up to 29.50. Available with either SK-111 15" 3-way speaker with 1 1/2 lb. magnet or SK-113 3-way with 3 1/2 lb. magnet. These are both highly efficient integrated 3-way speakers made by world renowned Goodmans of England. Supplied complete with genuine 12 db/octave crossover network with L-pad high frequency level control.

The enclosure is the renowned Lafayette bass reflex in either highboy or lowboy styling and in a choice of mahogany, walnut or blonde. Solidly constructed of 1/2" stock, these units have picture frame moldings, attractive plastic grilles, tapered legs, brass ferrules, internal acoustic linings, and are finished in genuine wood veneers. Size of lowboy (less legs) 28 1/2" w x 23 1/2" h x 16 1/2" d. Same size for highboy with height and width interchanged.

WHEN ORDERING, SPECIFY CHOICE OF BOTH: STYLE — HIGHBOY OR LOWBOY FINISH—MAHOGANY, BLONDE, WALNUT

8Y-281WX SK-111 15" with 1 1/2 lb. magnet 3-WAY SPEAKER & ENCLOSURE COMBINATION—Net 79.50 Only 5.00 Down
8Y-338WX SK-113 15" with 3 1/2 lb. magnet 3-WAY SPEAKER & ENCLOSURE COMBINATION—Net 89.50 Only 5.00 Down

COMPRESSION HORN TWEETER WITH 2 OR 3 WAY CROSSOVER



Versatility is the byword in this combination of the famous Lafayette SK-105 tweeter and LN-7 crossover. The Lafayette LN-7 6 db per octave crossover may be utilized as a 2-way at 500 cps or 3300 cps now—and in the future, by the addition of a mid-range speaker, it will become a 3-way, crossing over at 500 cps and 3300 cps. Rated at 20 watts of continuous power the Lafayette SK-105 tweeter will extend system response up to 16,000 cps. The very high flux density of 13,500 gauss guarantees excellent efficiency and essentially flat frequency response. Ruggedly built from a one-piece casting and carefully designed to eliminate unwanted resonance in the audio range, its attractive styling permits mounting on top of the speaker enclosure or, optionally, within the enclosure. Impedance 8-16 ohms. Shpg. wt., 3 1/2 lbs.

8Y-344—Combination Tweeter and Crossover System Net 16.50

Lafayette Presents

THE NEW ULTRA-LINEAR SK-128

19.50

FULL RANGE 8-INCH BIAXIAL SPEAKER WITH NEWLY




DEVELOPED TWEETER BAFFLE DESIGN.

- 40 TO 16,000 CPS—FLAT WITHIN 3 DB
- HIGH EFFICIENCY
- HIGH EXCURSION WOOFER WITH UNIQUE "CONICAL STIFFENER"
- HANDLES HEAVY BASS PASSAGES WITHOUT "DOUBLING"

Eccentric Tweeter Mounting & Unique Elliptical Baffle Completely Eliminates Interaction Between Woofer & Tweeter

The SK-128 combines the best features of a multiple speaker system in one compact and economical unit. It offers full, even coverage of the entire audible range, with no distortion or coloration to mar your listening pleasure. The specially treated woofer cone has a unique "Conical Stiffener" at the apex which, coupled with its high compliance, enables the cone to operate in a piston-like manner—delivering a clean, powerful bass response. The 2-inch tweeter has its own voice coil and magnetic field. Special treatment of cone and cone edge provides even distribution of the high frequencies, with no peaks or resonances. The unusual off-center mounting of the tweeter and its elliptical baffle minimizes interaction between tweeter and woofer and insures an overall response free of intermodulation distortion. Electrical crossover from the woofer cone to the tweeter unit is provided by a

built-in network. An adjustable brilliance control permits matching of sound to room acoustics. Efficiency of the speaker is such that it will operate from any amplifier with an output of 1 watt or more. Installed in a bass-reflex type of enclosure, it performs outstandingly, and is recommended for all high-quality music systems—whether monaural or stereophonic. SPECIFICATIONS: Overall Response: 20-20,000 cps (40-16,000 cps ± 3 db). Free air Resonance: 45-65 cps. Impedance: 8 ohms. Power Rating: 20 watts Integrated Program Material. Crossover: 2,500 cps. Overall Diam. 8-5/32". Overall Depth: 5-17/32". Baffle cut-out: 7-1/32". Rugged, vibration-free speaker frame with color-coded screw-type terminals for quick, easy connection of amplifier leads. Shpg. wt., 5 lbs. SK-128 Full Range 8" Biaxial SpeakerNet 19.50



Tweeter with baffle Polyester resin treated tweeter edge

LAFAYETTE MINI-DUCT BOOKSHELF ENCLOSURE WITH SK-128 8" ULTRA-LINEAR SPEAKER

The perfect answer for those who demand realistic sound reproduction even where space is limited. Two of these systems are ideal for stereo. Shpg. wt., 28 lbs. 2.00 Down

- 8Y-343WX Speaker System in WalnutNet 39.50
- 8Y-344WX Speaker System in MahoganyNet 39.50
- 8Y-345WX Speaker System in BlondeNet 39.50
- 8Y-346WX Speaker System in Oiled WalnutNet 39.50
- 8Y-347WX Speaker system in unfinished birchNet 37.50



THE WIDELY ACCLAIMED SK-58 12" COAXIAL SPEAKER

Now Offered Exclusively By Lafayette At **Tremendous Savings**


SUPERB PERFORMANCE GUARANTEED —OR YOUR MONEY BACK!

THE WORLD-RENOWNED Lafayette SK-58

- RESPONSE 30-15,000 CPS
- SHEEPSKIN "FREE EDGE" CONE MOUNTING
- 1 1/4 LB MAGNET WEIGHT
- 3" COAXIALLY MOUNTED TWEETER
- BUILT-IN LC NETWORK
- RATED AT 20 WATTS CONTINUOUS POWER

COMPARABLE VALUE **44.50**

29.50



Lafayette's exclusive 12" coaxial is a precision-made high fidelity loudspeaker, universally acclaimed by music lovers, hi-fi enthusiasts and professional experts alike as the greatest performance-value on the hi-fi market. It provides a truly faithful reproduction of sound without any "coloration" or distortion, its excellence being responsible for its use in innumerable high fidelity music systems today. The SK-58 incorporates such features as heavy, high flux density TSK-5 magnets for high efficiency; 1/4" wide sheepskin cone-edge suspension and special composition fibre cone material, specially treated for ultra-linear, distortion-free response; heavy rugged cast metal frame for freedom from resonances and for greater rigidity.

The coaxially-mounted 3" cone-type tweeter has a bell shaped mounting for maximum dispersion of high frequencies with no back radiation. With the built-in 3000 cps crossover network it contributes its share to the smooth delivery of the overall wide range response of 30-15,000 cps. Woofer resonance in free air is 40 cps. Speaker power handling capacity is 20 watts continuous sine wave, 35 watts peak program material. Impedance of the voice coil is 8 ohms, connections being made to chrome-plated screw terminals. Finished in gray-brown apolent enamel, the speaker is supplied complete with "brilliance" level control. Shpg. wt., 11 lbs. SK-58 12" COAXIAL SPEAKER 2.00 DownNet 29.50


NEW! REVOLUTIONARY HIGH-FREQUENCY SPEAKER

THE NEW LAFAYETTE HIGH FREQUENCY SUPER TWEETER



THE MOST SIGNIFICANT ADVANCE IN TWEETER DESIGN OF THE STEREO AGE

SK-131



19.50

At long last the breakthrough in High-Frequency Speaker design. Here is a tweeter with unequalled performance, engineered for today's high compliance stereo speaker systems. The Lafayette Sphericon represents a complete departure from Electrostatic tweeters, which are extremely inefficient — indeed so much so that it is often necessary to utilize an L-pad on the woofer in order to hear the tweeter properly, thereby lowering the efficiency of the woofer to the same level as that of the Electrostatic tweeter. In the case of many high compliance low effi-

ciency units this is disastrous, as an already inefficient speaker is made even less efficient. The Lafayette Sphericon, due to its high sensitivity may be coupled to any speaker system with no loss in speaker efficiency. As a result less amplification is needed assuring lower distortion. Equipped with a built-in 3000 cycle crossover network the Sphericon produces a smooth linear response from 3,000 cps to beyond 40,000 cps; within plus or minus 1 db from 3000 cps to supersonic frequencies. A specially designed domed phenolic diaphragm delivers

SPHERICON DESIGNED SPECIFICALLY FOR MEDIUM AND LOW EFFICIENCY SPEAKER SYSTEMS: This is essentially the same as the SK-131 (listed above),


but supplied with a built-in attenuator. This attenuator will not lower the efficiency of the woofer, yet provides precise matching of the "Sphericon" with today's popular

phenomenally smooth, silky, faithful high radiating a pattern of 120° in all directions, vertically as well as horizontally—with no trace of stridency or harshness. Power capacity is 30 watts. May be used with any 4-16 ohm speaker. Beautifully styled with an acoustically designed gold anodized aluminum grill set in a sturdy satin black plastic case. Shpg. wt., 3 1/2 lbs. LAFAYETTE SPHERICON SUPER TWEETER — For High Efficiency Speaker Systems. Net 19.50

low and medium efficiency speakers and speaker systems. Shpg. wt., 4 lbs. SK-146 2.00 Down Net 22.50

ELECTROSTATIC 3 ELEMENT TWEETER

WAS ~~27.50~~ NOW ONLY 17.50



SK-150 Mahogany Finish
SK-151 Walnut Finish
SK-152 Blende Finish
(Please specify finish) Shpg. wt., 7 lb. Net 17.50

RECOMMENDED INSTALLATION ACCESSORIES

Select crossover networks and L pads to match impedance CROSSOVER NETWORK KITS

Consists of coils and condensers and detailed assembly instructions. Shpg. wt., 2 lbs.

KT-128—8 ohm crossover kit (for AR-1, AR-2 & KLM-6) Net 2.75

KT-129—16 ohm crossover kit (for KLM-4) Net 2.75

LAFAYETTE "L" PAD ATTENUATORS

VC-49—8 ohm (for AR-2 & KLM-6) Shpg. wt., 6 oz. Net 1.49


VC-50—16 ohm. Shpg. wt., 6 oz. Net 1.49

LAFAYETTE Sphericon TWEETER AND ACOUSTIC RESEARCH AR-2 SPEAKER SYSTEM COMBINATIONS AT MONEY SAVING PRICES


SPHERICON EXTENDS THE RESPONSE OF YOUR AR SPEAKER TO BEYOND 40,000 CPS

AR-2 10" Acoustic suspension speaker and tweeter assembly; 42-14,000 cps. ±3 db; Size 13 1/2" x 11" x 24" Shpg. wt., 52 lbs.
SY-296 WX — Consists of Lafayette SK-146 Sphericon Tweeter and AR-2 Mahogany Finish 5.00 Down Net 101.60
SY-297 WX — Consists of Lafayette SK-146 Sphericon

Tweeter and AR-2 Walnut Finish 5.00 Down Net 106.00
SY-298 WX — Consists of Lafayette 146 Sphericon Tweeter and AR-2 Korina (Blond) Finish 5.00 Down Net 116.00
SY-299 WX — Consists of unfinished AR-2 speaker system and Lafayette SK-146 Sphericon Tweeter 5.00 Down Net 95.65



High Compliance Dual-Voice Coil Stereo Woofers



THE VERY SAME STUDIO QUALITY WOOFERS EMPLOYED IN THE LAFAYETTE CELESTIAL-SATELLITE STEREO SPEAKER SYSTEMS

Acoustical studies have shown that low frequency response is not directional... Indeed the stereo effect we hear is determined by frequencies above 350 cps. This dual voice coil woofer features two electrically separate voice coils on a single woofer chassis. Each voice coil receives low frequencies from its respective stereo channel. Both of these signals are blended through the single woofer cone. This advance in woofer design now makes possible 3-channel stereo without the need of complicated costly control filters or adaptor networks.

Now Lafayette offers these advanced design dual voice coil woofers for the high-fidelity enthusiast who wishes to build his own 3-channel stereo speaker system—or use it as the basis of a monaural system now and eventually work into a 3-channel stereo system.

12" DUAL VOICE COIL WOOFER

● FREQUENCY RESPONSE 20-2500 CPS ● 2 LB. ALNICO V MAGNET ● 2" VOICE COIL ● HIGH COMPLIANCE CONE FLOATS ON ROLLED CLOTH EDGES ● IMPEDANCE—EACH VOICE COIL 8-OHMS ● POWER HANDLING CAPACITY 30-WATTS
SK-133 Shpg. wt., 10 1/2 lbs. 2.00 Down Net 25.50

8" DUAL VOICE COIL WOOFER

● FREQUENCY RESPONSE 25-3000 CPS ● 2 LB. ALNICO V MAGNET ● 2" VOICE COIL ● HIGH COMPLIANCE CONE FLOATS ON ROLLED CLOTH EDGES ● IMPEDANCE—EACH VOICE COIL 8-OHMS ● POWER HANDLING CAPACITY 30-WATTS
SK-139 Shpg. wt., 8 1/2 lbs. 2.00 Down Net 20.95

Lafayette DELUXE CELESTIAL — SATELLITE SPEAKER SYSTEM A DYNAMIC NEW DIMENSION IN STEREO

● FREQUENCY RESPONSE 20-20,000 CPS ● 12" HIGH COMPLIANCE DUAL VOICE COIL WOOFER WITH 2 LB. ALNICO V MAGNET AND EXCLUSIVE LAFAYETTE ELIPTOFLEX CABINET ● SPECIAL CROSSOVER NETWORK KIT ● 3-CHANNEL WIDE PANORAMIC SOUND ENDS "HOLE IN THE MIDDLE" OR "PING PONG" EFFECT

Lafayette research and engineering facilities have evolved a new concept in stereo speaker systems. Research has proven that the low bass frequencies are nondirectional. By employing a newly designed high compliance 12" dual voice coil woofer with 2 lb. Alnico V magnet, Lafayette engineers have utilized this phenomenon. Bass frequencies below 350 cps are directed from their respective stereo channels to two electrically separate voice coils. In this manner both bass signals are blended through the single woofer cone assembly, which combined with the revolutionary Lafayette Eliptoflex bookshelf enclosure produces a robust, extremely smooth, balanced low frequency response down to 20 cps. Extensive laboratory and listening tests confirm this combination of 12" dual voice coil woofer with Lafayette Eliptoflex Bookshelf Enclosure, the equal or superior to anything yet conceived. The two Satellite speaker systems consisting of 2-Lafayette SK-128 Ultra-Linear 8" Dual voice speakers in specially designed 1/2" wood enclosures, reproduce all the bass overtones, middle and high frequencies.

In this manner use of a normal standard 2-channel amplifier, 3-channel wide panoramic stereo sound is achieved without the annoying "hole in the middle" or "ping pong" effect so often found in conventional stereo speaker systems. A large symphony orchestra spreads across the entire area, while a soloist or small musical group is properly located near the center. Conventional stereo speaker systems require large areas of space with the distance between speaker and location of the listening area in relation to these speakers extremely critical—Not so the Lafayette Celestial-Satellite Stereo system. Complete balance controls are provided for balancing low, middle and high frequency contours to individual listening tastes and room acoustics. Satellites may be placed in any position along the room (high or low) and may be separated by as much as 20 feet, with the Celestial low frequency bookshelf unit located any distance between Satellites as room decor permits—indeed, now you can welcome stereo into your home without the need of rearranging furniture. Available in Mahogany or Walnut—finished on 4 sides for attractive horizontal or vertical placement. Dimensions are: 14" H x 23-7/16" W x 13-5/16" D for Celestial low frequency unit. 14" W x 10 1/2" H x 7 1/2" W for Satellite midrange and tweeter units. Power Handling Capacity 30 watts. Impedance 8 ohms. Shpg. wt., 74 lbs. Supplied complete with necessary instructions and hook up cable.

LAFAYETTE DELUXE CELESTIAL-SATELLITE FINISHED IN MAHOGANY

SY-373WX Only 5.00 Down Net 109.50

ENCLOSURES FINISHED IN WALNUT

SY-374WX Only 5.00 Down Net 109.50

DELUXE CELESTIAL — SATELLITE SPEAKER SYSTEM LESS CABINETS

Consists of 2 — SK-128 ultra-linear 8" bixial speakers, 1 — SK-133 12" dual voice coil woofer, 2 — VC-49 attenuators and 1 — KT-161 crossover network. Shpg. wt., 23 lbs.

SY-300WX 5.00 Down Net 72.50



SK-128 ULTRA-LINEAR 8" DUAXIAL SPEAKERS IN SLOPING FRONT SATELLITE ENCLOSURES. ALLOW AIMING FOR BEST STEREO EFFECT

SPECIAL CROSSOVER NETWORK KIT

ELIPTOFLEX SERIES BOOKSHELF ENCLOSURE WITH SK-133 12" DUAL VOICE COIL WOOFER

NEW! 6 1/2" COAXIAL SPEAKER


● FOR EXCELLENT HI-FI SOUND ● ECONOMICAL & A SPACE-SAVER FOR STEREO ● RESPONSE 50-16,000 CPS! ● BUILT-IN CROSSOVER NETWORK ● LARGE, HEAVY MAGNETS

An excellent speaker, with all the best features of coaxial design, especially recommended for use in stereo high fidelity systems where space and/or cost are factors. The 6 1/2" woofer is provided with extra-heavy large magnets for good power sensitivity and low distortion; the 2" tweeter is a separate speaker coaxially mounted in a housing which completely seals off back radiation and with a mesh dispersion screen to provide smooth, wide-angle dispersion high frequency response. The built-in electrical crossover


contributes to the overall smooth tonal response of 50-16,000 cps. Woofer resonance is 70 cps; voice coil impedance is 8 ohms. Color-coded, screw-type terminals. Requires 5/8" diameter cutout. Mounts with 4 equally-spaced holes. Size is 6 1/2" diam., 3 1/4" deep. Shpg. wt., 3 1/2 lbs.

SK-97 6 1/2" COAXIAL SPEAKER Net 6.95
GET 2 FOR STEREO Only 12.95 Net

ONLY 6.95 BUY 2 FOR STEREO 12.95



CROSSOVER NETWORK KIT



Designed for use with Lafayette Dual Voice Coil Woofer (listed above). Crossover at 350 cycles. Employs finest quality components. Complete with detailed pictorial instructions. Shpg. wt., 3 1/2 lbs.

KT-161 7.26

LATEST SHERWOOD-HI-FI COMPONENTS

S-5000 STEREO 40W. AMPLIFIER



189.50

This brand new stereo central amplifier features the most versatile controls available. Dual loudness, bass and treble controls; one knob varies both channels simultaneously—yet, pull out on the knob, and you can vary each channel independent of the other! Features presence, rumble and scratch filters, DC filaments, indicator lights to indicate mode of operation used. For playing manual records with stereo cartridges, ingenious phasing system balances out all vertical (rumble and noise) pickup! SPECIFICATIONS: POWER: 20 watts each channel, 40 watts on monoaural. RESPONSE: 20-20,000 cps \pm 1/2 db at full power. INPUTS: Phono (RIAA), tape head (NARTB), 6 High level. NOISE: -80 db (-60 db for phono). OUTPUTS: dual 4, 8, 16 ohms, dual cathode followers for tape recorder. 12 TUBES: 4-6BQ5/EL84, 2-7199, 5-12AX7/ECC83, GZ34. sel. rect. 14" x 14" x 4". Shpg. wt., 29 lbs. G-265WX less case 5.00 Down Net 189.50

S-3000 II BASIC FM TUNER



105.50

FEATURES: One of the most sensitive FM circuits ever developed—only .95 microvolt for 20 db quieting. 1.8 microvolt for 30 db. "Feather-Ray" tuning indicator. Logging dial permits split-second tuning. Special sensitivity control for local or distant stations. SPECIFICATIONS: SENSITIVITY—.95 microvolts for 20 db quieting, 1.8 microvolts for 30 db. FREQUENCY RESPONSE: 20-20,000 cps \pm 1/2 db. DISTORTION AT 100% MODULATION—1.3% 1M, 1/4% harmonic, HUM AND NOISE—60 db below 100% modulation. DRIFT \pm 2 kc. with AFC, \pm 15 kc without AFC. OUTPUTS—Cathode follower audio, FM multiplex, AUDIO OUTPUT—2 volts. TUBES—9 tubes and rectifier. POWER CONSUMPTION—40 watts, 110-120 V 50-60 cycles. SIZE: 14" x 10 1/2" x 4". Shpg. Wt., 16 lbs. G-275WX less case 5.00 Down Net 105.50

CASES FOR SHERWOOD COMPONENTS

STOCK NO.	MFR. NO.	COLOR	FOR	NET
G-281W	A	Brown Flexstone	SMX-S 5W x 10W	4.00
G-282W	B	Black Flexstone	x 4 1/2" x 4 lbs.	4.00
G-283W	A	Brown Flexstone		5.00
G-284W	B	Black Flexstone	S-2200S, S-5000S	5.00
G-285W	C	Mahog. Leatherette	14 x 13 x 4 1/2"	10.00
G-286W	J	Black Leatherette	Shpg. Wt., 8 lbs.	13.00
G-287W	T	Tan Leatherette	Large Case	13.00
G-288W	W	White Leatherette		15.00
G-289W	A	Brown Flexstone	S-100011S, S-1060S	5.00
G-290W	B	Black Flexstone	S-200011S, S-300011S	5.00
G-291W	C	Mahog. Leatherette	S-4400S	10.00
G-292W	J	Black Leatherette	14 x 10 1/2" x 4 1/2"	15.00
G-293W	T	Tan Leatherette	Shpg. Wt., 6 lbs.	15.00
G-294W	W	White Leatherette	Standard Case	15.00

NEW Scott 399 STEREO TUNER-AMPLIFIER COMBINATION



399.95

The new Scott 399 combines the famous Scott 330D FM-AM stereo tuner and 299 40-watt stereo amplifier (20-watts each channel) on one compact chassis. The Tuner section features separate silver-sensitive FM front end and highly sensitive AM front-end with individual tuning controls for precise station selection. Tuner has switching provisions for FM multiplex stereo or FM-AM stereo. Amplifier section employs separate Bass and Treble controls on each channel, phase reverse switch, third channel output and DC filament supply for preamp. Complete switching facilities have been provided. Frequency response is 20-30,000 cps. Harmonic Distortion: 0.8% at full power output. Hum better than 80 db below full power output. 4, 8 and 16 ohm speaker outputs for each channel. FM sensitivity 2 microvolts for 20 db of quieting. Dimensions: 16 1/2" W x 6" H x 14 1/2" D. Shpg. wt., 35 lbs. G-159WX less case 10.00 Down Net 399.95 Scott FWW Walnut Case for 399 Tuner-Amplifier. Shpg. wt., 8 lbs. G-160W 2.00 Down Net 29.95

AMAZING VALUES!

Lafayette

FM-AM STEREO TUNER


MODEL LT 77

Truly a triumph of engineering skill

Simplicity, flexibility and superb styling have been carefully integrated in this quality instrument. Offering tremendous versatility, the LT-77 will receive the new simultaneous FM-AM stereophonic broadcasts or since the FM and AM sections are completely independent, the tuner may also be employed for FM or AM reception separately. Designed with the future in mind, a multiplex output has been included for the new stereo FM. Each unit has been hand wired and individually laboratory tested. Controls provide for every tuner function. On-off power switch; Separate AM/FM flywheel tuning; Individual AM/FM volume controls; Choice of AM, FM, FMAFC or stereo reception. FM circuitry features Armstrong grounded grid low noise front end and triode mixer coupled with tuned dual limiters, Foster-Seeley discriminator with AFC and AFC defeat. FM Sensitivity of 1.5 uv for 20 db quieting insures long range reception. Superhet AM circuit with 3 stages AVC and ferrite loopstick antenna. Individual 3-gang tuning condenser and tuned RF stages for both AM & FM sections. Selectivity: FM 200 KC band width; 6 db down, AM 8 KC BW; 6 db down. Frequency Response: FM 20-20,000 cps \pm 1/2 db, AM 20-5,000 cps \pm 3 db; Harmonic Distortion under 1% on FM; under 1% on AM for up to 80% modulation. Hum Level—60 db. Image Rejection: FM, better than 40 db AM 70 db. I.F. Rejection: FM 70 db, AM 50 db Radiation meets FCC requirements. Tubes: 2-6AQ8, 4-6BA6, 2-AU6, 1 each 6BE6, 6AL5 and 6X4 plus diode detector. Antenna Input: 300 ohms. Superbly styled low silhouette enclosure finished in gold and white with easy to read black dial face. Complete with cage and legs. Dimensions: 14 1/2" W x 4 1/2" H x 10 1/2" D Feet add 1/2" to height. Shpg. wt., 16 lbs. LT 77 AM-FM STEREO TUNER ... 5.00 Down NET 74.50

- 14 TUBE PERFORMANCE—10 TUBES (2-DUAL PURPOSE)
- RECTIFIER + DIODE & 2-TUNING METERS ● ARMSTRONG CIRCUIT WITH DUAL TUNED LIMITERS AND FOSTER-SEELEY DISCRIMINATOR
- FM AFC AND AFC DEFEAT ● EXTREME SENSITIVITY AND WIDE FREQUENCY RESPONSE ● TUNED GROUNDED GRID R.F. STAGE ON AM & FM ● MULTIPLEX OUTPUT ● FLY WHEEL TUNING ● AM FEATURES BROADBAND TUNED I.F. STAGE ● 2-3 GANG CONDENSERS
- INDIVIDUAL VOLUME-BALANCE CONTROLS FOR AM & FM

WEAK SIGNAL—
STRONG SIGNAL . . .
Lafayette's separate,
precision twin-tuning
meters for FM and AM
insure pin-point tuning
accuracy every time



74⁵⁰
COMPARABLE VALUE 139.50

Due to the avalanche of orders for these Tuners, delivery will be delayed until approximately January 25, 1960. However we are filling all orders in strict chronological sequence . . . Order now for earliest possible delivery.


49⁵⁰
COMPARABLE VALUE 89.50



Lafayette FM TUNER

MODEL LT 80


Remarkable . . . quality, performance and styling that is in every respect the equal and in many instances superior to tuners priced far above the modest cost of this instrument. The same sensitive FM circuit employed in the LT-77 AM-FM Stereo Tuner (Specifications as listed above) has been incorporated in the LT-80 . . . designed and constructed of the finest components, with jewel like precision (each unit is hand wired) in order to insure that each tuner will maintain its excellence year after year with a minimum of maintenance. Making every attempt to anticipate the requirements of the future, Lafayette designers have included a multiplex output for the new stereo F.M. broadcasts. Controls consist of On-Off; FM; FM AFC and FM MEX. Flywheel action tuning control provides velvet-smooth tuning action. Tube complement consists of 2-6AQ8, 2-6BA6, 2-6AP6, 1 each 6AL5 and 6X4. Handsome low silhouette enclosure will do justice to any decor. Beautifully finished in gold and white with contrasting black dial face. Complete with cage and legs. Dimensions: 11 1/2" W x 8" D x 4 1/2" H Legs add 1/2" to height. Shpg. wt., 11 lbs. LT 80 FM STEREO TUNER . . . 2.00 Down NET 49.50



Pin-point tuning accuracy is provided by this precision tuning meter; evaluates relative strength of the incoming signal . . . invaluable when tuning weak stations.

- ARMSTRONG CIRCUIT FOSTER-SEELEY DISCRIMINATOR AND DUAL TUNED LIMITERS
- EXTREMELY SENSITIVE—1.5 UV FOR 20DB QUIETING
- 10-TUBE PERFORMANCE—8 TUBES (2-DUAL PURPOSE)
- 20-20,000 CYCLES \pm 1/2 DB ● AFC
- AFC DEFEAT ● SUPERB LOW SILHOUETTE STYLING

Lafayette COMPLETE STEREO PHONO SYSTEM




Bring the full beauty, and realism of stereo sound into your home with these matched Lafayette components—Carefully selected and matched by experts, rigidly engineered and manufactured to the most exacting specifications . . . each component has been completely evaluated by comparative laboratory and listening tests in order to provide the utmost in flexibility, quality and value.

● Heart of the system is the new LA-235 35 watt stereo amplifier which acts as a complete stereo control center. Designed with the future in mind all necessary inputs are provided if you wish to add stereo tape and/or stereo FM/AM later.

● The famous Garrard RC 121 4-speed automatic record changer is supplied with an attractive wood base in your choice of finisher.

● The new GE VR-227 stereo cartridge insures perfect reproduction throughout the full audio range from 20-17,000 cps.

● Two of Lafayette's new SK-128 Ultra-Linear full range 8-inch coaxial speakers featuring the most advanced speaker design available, complete this excellent system.



COMPONENTS

- LAFAYETTE LA-235 35 WATT STEREO AMPLIFIER . . . 69.50
 - GARRARD RC 121 4-SPEED RECORD CHANGER . . . 41.65
 - NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE . . . 24.45
 - WOOD BASE FOR RC121 (SPECIFY FINISH) . . . 3.95
 - 2-LAFAYETTE SK-128 FULL RANGE 8" DUAXIAL SPEAKERS 39.00
- Regular Catalog Price 178.55

ALL MATCHED COMPONENTS

139⁹⁵
5.00 Down

Complete Stereo phono system as listed above. Shpg. wt., 46 lbs.

- HF-725WX . . . 5.00 Down Net 139.95
- Same as HF-725 WX, with the addition of 2-Lafayette amazing "Mini-Duct" Bookshelf Enclosures (Specify Enclosure Finish) Shpg. wt. 92 lbs.
- HF-726WX . . . 5.00 Down Net 182.45
- Same as HF-725WX, but with 2-Lafayette Famous SK-58 Free Edge 12" 2-way speakers. Shpg. wt., 58 lbs.
- HF-727 WX . . . 5.00 Down Net 158.50
- Same as HF-727WX, with the addition of 2-Eliptoflex Bookshelf Enclosures (Specify Enclosure Finish) Shpg. wt., 106 lbs.
- HF-728WX . . . 10.00 Down Net 212.95



● SELECT YOUR OWN CARTRIDGE ● You may substitute the Shure M7D, Pickering 371C, or the new Electro-Voice 31MD7 in any system shown with the GE VR-22 at no additional cost. The Shure M3D may be substituted at an additional cost of \$24.00.

New! LAFAYETTE LA-55 15 WATT MONAURAL AMPLIFIER

- FREQUENCY RESPONSE: 15-30,000 CPS
- POWER OUTPUT 15 WATTS
- SENSITIVITY: 3 MV MAG. PHONO
- HUM 65 DB BELOW RATED OUTPUT
- HARMONIC DISTORTION LESS THAN .3%



- 5 INPUT CHANNELS
- RUMBLE FILTER
- EL84 OUTPUT TUBES IN PUSH-PULL
- BEAUTIFULLY STYLED



The Most Extraordinary Hi-Fi Value Ever Offered

Outstanding Performance and Engineering + Beautiful Styling + Unbeatable Price—add up to make the Lafayette LA-55 truly the finest Hi-Fi monaural amplifier value today. Beautifully styled in gold and white, the LA-55 easily adapts to any room decor. Perfect for that music system in your living room, finished basement, store or office. Ruggedly constructed, this fully integrated amplifier-preamplifier employs premium quality EL84 tubes in push-pull and advanced circuitry for faithful reproduction of all monophonic sources. Perfect for use as a second amplifier for stereo or for starting out monophonically and adding stereo at a later date. Engineered to include every practical feature making a worthwhile contribution to hi-fi reproduction. SPECIFICATIONS: Power Output 15 watts Institute of High Fidelity Manufacturers Rating (30 watts peak) Frequency Response 15-30,000 cps ± 1 db (at normal listening

39.50

COMPARABLE
VALUE ~~69.50~~
2.00 DOWN

level); Sensitivity: For full power, High level inputs 0.5v. Mag. phono 3 mv. Hum and Noise: Volume control at max. High level inputs 65 db below rated output. Mag. Phono 55 db below rated output; Harmonic Distortion less than .3%. Inputs: Total 5—Aux, Tuner, Mag. Phono, Crystal Phono, Tape Head. Outputs: Tape Out, 4, 8 and 16 ohm speaker terminals; Tubes: Total of 5 plus rectifier—2-EL84, 1-6BL8, 1-AU6, 1-12AX7, and 1-6CA4/WZ81. Controls: Monitor/On-Off; Volume/Power On-Off; Bass; Treble; Rumble Filter. Hum balance control. Selector; 4-position, Aux, Tuner, Phono, Tape Head. Complete with removable case and legs. AC receptacle on rear of chassis. Dimensions: 13 1/2" W x 4" H x 8 3/4" D. Knobs extend 1/4" in front of panel. Shpg. wt., 20 lbs.

LA-55WX 2.00 Down Net 39.50

LAFAYETTE SUPER-VALUE HIGH-FIDELITY PHONO SYSTEM



PLAY STEREO & MONAURAL RECORDS MONAURALLY NOW — ADD COMPLETE STEREO LATER

This economical high-fidelity system is the performance value of the year. Designed for ruggedness as well as beauty, these components will satisfy even the most critical music listener.

- COMPONENTS
- LAFAYETTE LA-55 15 WATT COMPLETE AMPLIFIER 39.50
 - NEW GE VR-22 (.7 MIL) DIAMOND CARTRIDGE FOR BOTH STEREO AND MONAURAL RECORDS 24.45
 - GARRARD RC-121 4-SPEED RECORD CHANGER 41.65
 - WOODBASE FOR RC121 (Specify Finish) 3.95
 - LAFAYETTE SK-124 BOOKSHELF SPEAKER SYSTEM (Finished on 4 sides in Mahogany or Walnut) 17.50


LAFAYETTE SYSTEM PRICE **99.50** YOU SAVE 27.55

Complete phono system as listed above featuring Lafayette's famous LA-55 Amplifier and SK-124 Bookshelf Speaker System. Finished on 4 sides for horizontal or vertical placement anywhere in the room—provides a smooth distortion free response with a deep fundamental base and clean pure highs normally found only in multiple speaker systems. Shpg. wt., 53 lbs.

HF-763WX 5.00 Down Net 99.50
Some system as HF 763 WX, with the addition of the Lafayette LT-80 FM Tuner. Shpg. wt., 64 lbs.

HF-764WX 5.00 Down Net 147.00


NEW GE MODEL G-7700 56 WATT STEREO AMPLIFIER



Engineered to fulfill the need for a top quality unit at a modest cost. Dual concentric controls permit individual bass and treble adjustment. Controls: Input selector (tape head, monaural phono, stereo phono, tuner, auxiliary); speaker mode selector; loudness; contour; balance; bass; treble; rumble filter; scratch filter; speaker phasing switch. Inputs: 2 stereo cartridge, 2 stereo tape head, 1 mon. phono, 2 tuner, 2 auxiliary stereo. Outputs: Dual speaker (4, 8, 16 ohm), dual output jacks, 2 AC outlets. Power output: 56 watts (28 watts per channel), music power. Freq. response: 20-20,000 cps. ± 0.5 db. Harmonic distortion below 1% at full rated power. Hum and noise inaudible. Channel separation: 40 db minimum. For 117V, 60 cycles, AC. Cabinet finished in beige vinyl. Size 15 x 12 x 5 1/2". Shpg. wt., 31 lbs.

G-326WX 5.00 down Net 186.15
Model G-7710. Same as G-7700, but white vinyl finish.
G-327WX 5.00 down Net 186.15


NEW GE MODEL 7600 40 WATT STEREO AMPLIFIER



This integrated stereo amplifier combines 2 power amplifiers and 2 preamp control units on a single chassis. Features concentric bass and treble control to permit individual channel adjustment. Power output 20 watts per channel or 40 watts total. Front panel controls include: input selector, speaker mode selector; loudness; contour; balance (continuously variable); bass; treble; rumble filter on-off. Inputs: 2 stereo cartridge, 2 tuner, 2 auxiliary stereo. Outputs: Dual speaker (4, 8, 16 ohm), dual output jacks, 2 AC outlets. Hum and noise 65 db below 20 watts on phono input. Freq. response: 20-20,000 cps ± 0.5 db. Harmonic distortion: below 1% at full rated power. For 117V., 60 cycle AC. 11 tubes. Cabinet finished in saddle brown vinyl. Size 15 x 12 x 5 1/2". Shpg. wt., 30 lbs.

G-325WX 5.00 down Net 137.15

NEW GENERAL ELECTRIC FM-AM TUNER MODEL FA-17



This new GE FM-AM Tuner features high sensitivity, and ability to receive weak signals with minimum distortion. Specifications: AM sensitivity—200 μ v per meter for 20 db signal-to-noise ratio; FM—25 microvolts on 300 ohm input for 20 db quieting. FM Distortion—less than 1.5% harmonic at rated output—less than 2% IM. Noise—FM 55 db below 100% modulation—AM built-in ferrite rod antenna. AFC eliminates FM drift. Dual-purpose FM-AM tuning meter. Saddle brown finish. Dimensions: 15-1/32" W x 5 3/4" H x 10" D. Shpg. wt., 15 lbs. For 110-120 Volts, 60 cycles AC.

G-329WX 5.00 down Net 127.35
FA-15 Same as FA-17, but finished in beige
G-330WX 5.00 down Net 127.35
FA-16 same as FA-17, but finished in white
G-331WX 5.00 down Net 127.35

Lafayette

STEREO 235 GIVES NEW DIMENSION TO MUSIC

UNCOMPROMISING QUALITY!



35 WATT STEREO AMPLIFIER
17 1/2 WATTS PER CHANNEL

- FREQUENCY RESPONSE: 20-20,000 CPS ± 1 DB
- HARMONIC DISTORTION LESS THAN 1% AT RATED OUTPUT
- IM DISTORTION LESS THAN 2%
- 4 EL84 TUBES IN PUSH-PULL
- DUAL CONCENTRIC SEPARATE BASS AND TREBLE CONTROLS
- CLUTCH-OPERATED VOLUME-BALANCE CONTROLS
- HIGH SENSITIVITY FOR USE WITH NEW STEREO CARTRIDGES
- VARIABLE BLEND CONTROL ELIMINATES EXAGGERATED CHANNEL SEPARATION

SUPER VALUE
\$ **69.50** 5.00 Down
COMPARABLE VALUE **109.50**

Superior in concept, design and performance, the new Lafayette LA-235 represents a new standard in stereophonic amplifiers. Every outstanding feature you could ask for in an amplifier has been provided—Completely versatile, this instrument may be used as a dual 17 1/2 watt stereo amplifier or as a single monophonic 35 watt amplifier . . . perfect for those on a limited budget who wish to start out with a monaural system and eventually build into stereo.

Engineered to deliver the finest performance under all conditions; an exclusive blend control has been incorporated, providing continuously variable channel separation from full monophonic to full stereo, thus insuring the correct degree of stereo separation for individual listening tastes and room acoustics. Concentric clutch-operated volume-balance controls provides individual or simultaneous level control for both channels. Bass and treble are adjusted by means of separate dual-concentric controls for independent tonal control of each channel. Function switch provides Aux, Tape (high level) Tuner and Phono. Simple slide switches are provided for Power on-off, Phase Reverse, Channel Reverse.

SPECIFICATIONS: 35 watts—17 1/2 watts per channel ± 1 db. Institute of High Fidelity Manufacturers Rating (70 watts peak) Harmonic Distortion: Less than 1% at rated output; IM Distortion: Less than 2%. Frequency Response: 20 to 20,000 cps ± 1 DB (at normal listening level); Tone Control Range: Treble ± 10 db at 10 kc; Bass ± 10 db at 50 cps. Sensitivity: For full power-High level inputs 0.5v. Mag. phono 4 mv at 1 kc. Hum and Noise: Volume control at max.—High level inputs 65 db below rated output. Mag. phono 55 db below rated output. Channel Separation: Greater than 40 db. Total: 10 inputs 2 Aux, 2 Tape (high level) 2 Tuner, 2 Mag. Phono, 2 Crystal Phono; Total 4 outputs 2 Tape Out, AC convenience outlet located on rear. Dual 8 and 16 ohms speaker outputs. Total of 9 tubes consisting of 4-EL84, 2-7199, 2-12AX7 and 1-GZ34. For 117 volts, 50/60 cps AC. Attractively styled in a rich brown vinyl cage with brass plated escutcheon and ivory and gold knobs. Dimensions: 14" W x 4 3/4" H x 9" D. Cover and legs may be removed for panel mounting. Shpg. wt., 22 lbs.


LA-235WX 5.00 Down Net 69.50

LAFAYETTE

EXTRA
LOW
COST

AUDIO & PHONO ACCESSORIES

LAFAYETTE SPECIAL VALUES IN T PADS, FADERS AND SPEAKER SWITCHES.



Multiple Speaker Switch (A). Constant impedance device for controlling any 6 remote speakers; up to 63 different combinations. Wall mounting with brass plate. With instructions and hardware. Shpg. wt., 10 oz. MS-459..... Net 2.10

Multiple Speaker Switch (H). Identical to above but mounted on flat, gold-embossed plate for mounting on flat panel. 3 1/2" x 2 1/4". Shpg. wt., 10 oz. MS-544..... Net 1.19

Speaker Selector Switch (B). Selects 3 speakers in any combination, with up to 60 watts of audio power. A constant impedance device. On gold finished steel electric outlet plate, 2 1/4 x 4 1/2". MS-458 Shpg. wt., 1 lb. Net 1.39

Remote Speaker Switch (C). Connects remote speaker to any existing set. Turns both on or either speaker on or off. With gold embossed plate for front panel mounting. Shpg. wt., 6 oz. MS-469 With all parts and instructions. Net .95

Remote Speaker Switch (F). Same as MS-469 except for wall mounting. Shpg. wt., 6 oz. MS-470..... Net 1.50


Remote Speaker Fader (E). Provides adjustable volume level for Radio, TV, Hi-Fi and remote speaker. Gradually increases volume on one speaker while diminishing volume on the other. May also be used to adjust volume for 1 speaker. Gold plate for front panel mounting. With instructions. Shpg. wt., 6 oz. VC-53..... Net 1.10

Remote Speaker Fader (G). Same as VC-53 except for wall mounting. Shpg. wt., 6 oz. VC-54..... Net 1.55

T Pads (D). Constant impedance control to adjust speaker volume. With brass satin plate for wall mounting. With all parts and instructions. Shpg. wt., 10 oz. VC-51 8 ohm T Pad..... Net 3.85

VC-52 16 ohm T Pad..... Net 3.85

NEW LAFAYETTE L PADS




New L pads for use as "brilliance" controls to vary tweeter level, or as "presence" controls to vary mid-range speaker level. Both wirewound elements are concentrically mounted within one plastic housing. With gold-finished metal escutcheon plate, mtg screws, and attractive black knob. Size: 1-9/16" dia., 3/8" deep (less shaft), 2 1/2" deep overall. Shpg. wt., 6 oz. VC-49-L pad for 8 ohm circuits..... Net 1.49

VC-50-L pad for 16 ohm circuits..... Net 1.49

LAFAYETTE COMPLETE CABLE ASSEMBLIES FOR HI-FI AND P. A.

High quality extension cables "tailor made" for users of recorders, hi-fi equipment, etc. All plugs molded directly to various cable combinations. Shielded cable for high impedance (mike, etc.) connections; parallel wire for low impedance (speaker, etc.) connections. Average shpg. wt., 8 oz.



90° PHONE PLUG (A) TO VARIOUS CONNECTIONS. Std. 1/4" sleeve; completely shielded. All cables shielded except * unshielded parallel cable. Avg. shpg. wt., 9 oz.

RCA TYPE PHONO PLUG (B) TO VARIOUS CONNECTIONS. All cables shielded except * unshielded parallel cable. Avg. shpg. wt., 9 oz.

Stock No.	One Termination	Cable Length	Other Termination	Net
MS-345	90° phone plug (A)	72 in.	Straight RCA phono plug (B)	.72
MS-346	90° phone plug (A)	72 in.	Straight RCA phono jack (D)	.85
MS-347	90° phone plug (A)	72 in.	Straight barrel phone jack (C)	.93
MS-348	90° phone plug (A)	72 in.	Mike connector (F)	.93
MS-349	90° phone plug (A)	120 in.	Mike connector (F)	1.26
MS-350	90° phone plug (A)	72 in.	90° RCA phono plug (E)	.72
MS-351*	90° phone plug (A)	72 in.	Stripped and tinned ends (J)	.51
MS-352*	90° phone plug (A)	72 in.	Alligator clips (I)	.68

Stock No.	One Termination	Cable Length	Other Termination	Net
MS-486	Straight RCA phono plug (B)	36 in.	Straight RCA phono plug (B)	.39
MS-480	Straight RCA phono plug (B)	60 in.	Straight RCA phono plug (B)	.47
MS-481	Straight RCA phono plug (B)	72 in.	Straight phone plug (G)	.69
MS-487	Straight RCA phono plug (B)	48 in.	RCA-type phono jack (D)	.54
MS-483	Straight RCA phono plug (B)	60 in.	RCA-type phono jack (D)	.59
MS-484	Straight RCA phono plug (B)	72 in.	Barrel-type phone jack (C)	.60
MS-555	Straight RCA phono plug (B)	72 in.	Mike connector (F)	.88
MS-556*	Straight RCA phono plug (B)	120 in.	Alligator clips (I)	.81
MS-573	Straight RCA phono plug (B)	36 in.	Stripped & tinned ends (K)	.34
MS-574	Straight RCA phono plug (B)	48 in.	Stripped & tinned ends (K)	.36
MS-575	Straight RCA phono plug (B)	60 in.	Stripped & tinned ends (K)	.39
MS-576	Straight RCA phono plug (B)	72 in.	Stripped & tinned ends (K)	.41
MS-577	Straight RCA phono plug (B)	144 in.	Stripped & tinned ends (K)	.69

PHONE PLUG (G) TO VARIOUS CONNECTIONS. Std. 1/4" diam. sleeve; completely shielded. All cables shielded. Avg. shpg. wt., 9 oz.

Stock No.	One Termination	Cable Length	Other Termination	Net
MS-482	Straight phone plug (G)	72 in.	RCA-type phono jack (D)	.79
MS-485	Straight phone plug (G)	72 in.	Barrel-type phone jack (C)	.79
MS-553	Straight phone plug (G)	72 in.	Mike connector (F)	.93
MS-554	Straight phone plug (G)	120 in.	Mike connector (F)	1.26

90° RCA PHONO PLUG (E) TO VARIOUS CONNECTIONS. All cables shielded except * unshielded parallel cable. Avg. shpg. wt., 9 oz.

Stock No.	One Termination	Cable Length	Other Termination	Net
MS-557	90° RCA phono plug (E)	72 in.	Barrel-type phone jack (C)	.72
MS-558	90° RCA phono plug (E)	72 in.	Mike connector (F)	.88
MS-559*	90° RCA phono plug (E)	36 in.	Stripped and tinned ends (J)	.32
MS-560*	90° RCA phono plug (E)	72 in.	Alligator clips (I)	.63

SPECIAL 10 FT. JUMPER CABLE. Unshielded parallel cable, 10 ft. long, with alligator clips (I) at both ends. MS-561..... Net .60

SPECIAL LAFAYETTE HI-FI AND PA ACCESSORIES

SPEAKER PHASING CONTROL


Allows you to reverse speaker connection to obtain correct phasing without disconnecting leads from speakers. A must for stereo. Complete with screw terminals and all mounting hardware. Shpg. wt., 1 lb. MS-756 Speaker Phasing Control..... Net .98

STEREO-MONAUERAL-REVERSE SWITCH

Lets you switch instantly from stereo to monaural or reverses stereo channels. 2 phono jacks input... 2 phono jacks output. Completely shielded, ready to mount with all hardware. Shpg. wt., 1 lb. MS-757 Stereo-Monaural-Reverse Switch..... Net 1.29

MULTI-INPUT SELECTOR CONTROL

Connects any one of 5 inputs to 1 output AM, FM, phono, tape, aux. Completely shielded to prevent hum. Complete with mounting hardware. 5 phono jacks input, 1 phono jack output. Shpg. wt., 1 lb. MS-758 Multi Input Selector..... Net 1.76



STEREO PHASER SELECTOR



1.03

This specially designed switch offers a simple and smooth method for changing over from monaural to stereo operation or to "rephase" the speakers if they should happen to be in electrical opposition. In monaural operation the monaural signal is fed to two amplifiers and two speaker systems; in stereo operation each of the two channels is fed to its own amplifier and speaker. Has polished brass embossed plate for mounting on speaker enclosure or Hi-Fi panel. All hardware and instructions are included. Shpg. wt., 10 oz. PK-228..... Net 1.03

3 SPEAKER SELECTOR SWITCH

1.89



Convenient rotary switch permits selection of any speaker or combination of 2 or 3 speakers from a remote location. Attractively finished in gold metal with black and ivory rotary switch. Dimensions are 3 1/2" x 4 1/2" x 2 1/4". MS-567..... 1.89

PHONO PIN JACK SINGLE HOLE MOUNTING

15c ea. 10 for \$1.35

RCA type female input jack. Mounts securely in single 1/4" hole by means of locknut on jack. Screws, nuts and washers unnecessary. MS-568..... 10 for 1.35 singly ea. .15

With this handy, small mixer you can announce titles before playing records, mix two high impedance microphone inputs or perform any other mixing operation where 2 high impedance input channels are converted to a single mixed high impedance input channel. Each input channel has its own easy acting level control for quiet mixing; all mounted in shielded, chrome plated housing. Has 2 RCA type female input jacks and one male RCA plug on output side. Overall size 2 1/4" x 1 1/4" x 1/2". Shpg. wt., 1/2 lb. PK-239 AUDIO MIXER..... Net 1.75

MINIATURE HI-FI AUDIO MIXER

1.75

1.75

1.75

MINIATURE RCA METAL INSULATED EXTENSION PLUGS & JACKS

(A) Sturdy, heavy brass, nickel-plated RCA phone plugs. Provide excellent shielding. Ideal to use in high fidelity music systems. Length—1-5/16". Shpg. wt., 4 oz. MS-593..... Net .19

(B) Extension cable jack that matches MS-593 plug or any RCA phone plug. Shpg. wt., 4 oz. MS-594..... Net .19

STEREO LINE BALANCE

(L) Volume Control Adapter. Single channel, high impedance circuits only. Phono jack input to phono plug output. Designed for use in unbalanced stereo channels, in pairs for dual stereo channel control. Completely shielded; nickel plated. Shpg. wt., 12 oz. MS-689..... Net 2.32

(M) Dual Volume Control Adapter Twin channel, high impedance circuits only. 2 phono jack inputs and 2 phono plug outputs with separate recessed volume controls. Tan finished. Completely shielded. Shpg. wt., 1 1/2 lbs. MS-690..... Net 4.41

KOSS STEREO HEADSETS AND ACCESSORIES



Model SP-3 Stereophones (Fig. A)

The Koss SP-3 Stereophones are a specially constructed headset that provide a wide frequency range of 30-15000 cycles by means of unusual 3 1/2" dynamic reproducers incorporated into each earphone. They are extremely comfortable to wear, light and rugged. Ideal for Stereo, they can also be used for monaural sound. Since they have an impedance of 4 ohms, they can be connected directly to amplifier outputs or across speaker voice coil leads. Shipping weight 2 lbs. G-600..... Net 24.95

MODEL T-5 JUNCTION BOX (Fig. B)

Junction Box for connecting stereophones to existing stereo or monaural system. Impedance 4-16 ohms. Contains 2 Volume controls for changing the Volume of each side of the headset independently. Has 2 output jacks for stereo or monaural use. Equipped with speaker on-off switch for personalized listening. Shipping weight 1 1/4 lbs. G-605..... Net 5.95

RECORDER PATCH CORD




IDEAL FOR MAKING CONNECTIONS FROM RADIO, PHONO OR TV TO TAPE RECORDER.

Handy 6 ft. lead has insulated alligator clips at one end and RCA phono plug at the other. Supplied with shielded phono plug adapter to adapt the RCA phono plug to standard phono plug if necessary. Attach alligator clips to speaker terminals and simply plug other end into tape recorder. Ideal for recording from Radio, Phono or TV. Shpg. wt., 8 oz. MS-565..... .67

.67

FLEXIBLE AUDIO Y CONNECTORS



For converting Stereo Player to Monaural. Can be used for a Top-In-Meter Monitor connection. Also required on some Tape Recorders. Shpg. wt., 4 oz.


(A) Phono Plug connected to 2 Phono Jacks by 4" shielded cable. Net .59

MS-672 (B) Phono Jack connected to 2 Phono Plugs. NET .59

MS-673 (C) 3 Phono Plugs connected together by 4" shielded cable. Net .59

MS-674

SHIELDED "Y" ADAPTERS



Completely shielded Y-Adapters with choice of connectors and terminations.

(A) Two phono jacks connectors in parallel to a standard 2-conductor phono plug. Avg. shpg. wt., 7 oz. MS-595..... Net .69

(B) Two phono jacks connectors in parallel to a standard phono plug. MS-596..... Net .69

(C) 3 phono jacks connectors in parallel. MS-597..... Net .69

(D) Two male microphone connectors in parallel to a standard two-conductor phono plug. MS-598..... Net .69


REEL LOCKS Set of Two 59c

Holds tape recorder reel in place by locking spindle to reel. Especially useful if recorder is in vertical position. Will not interfere with normal operation of reels. Easily removable. Shpg. wt., 6 oz. MS-564 Set of two..... .59

BUILD-YOUR-OWN LAFAYETTE SPEAKER ENCLOSURES

EASY-TO-ASSEMBLE HI-FI ENCLOSURE KITS and COMPLETE SPEAKER SYSTEMS

AT TREMENDOUS SAVINGS TO YOU!



A LAFAYETTE BEST BUY AT ONLY 29.50

LAFAYETTE UNIVERSAL HI-FI BASS REFLEX ENCLOSURE KITS

• EASIEST TO ASSEMBLE - ALL YOU NEED IS A SCREWDRIVER! • 3/4" WHITE BIRCH • PRECISION-CUT - FITS TOGETHER SMOOTHLY • PERFECT FOR SINGLE WIDE RANGE, 2-WAY OR 3-WAY SPEAKER SYSTEMS • HIGHBOY OR LOWBOY STYLE

All pieces of these carefully designed bass reflex high fidelity speaker enclosures are accurately pre-cut of 3/4" veneers to fit snugly together and eliminate spurious resonances. Front panels are handsomely detailed with picture-frame moulding and covered with pleasingly decorative plastic acoustic grilles to blend with any finish and room decor. Attractively tapered offset legs are protected by good-looking brass ferrules. Acoustic lining material is provided to prevent reverberation and cabinet resonance. Cutouts are provided for 15" speaker plus adapter for 12"; 8 1/2" or 8" midrange plus adapter for 5" and blank wood block if no midrange speaker is used; Jensen compression horn tweeter plus adapter for Lafayette HK-3, HW-7 or Lafayette-Goodmans SK-104 tweeters plus blank wood block if no tweeter is used. Thus, any single wide-range 12" or 15" speaker may be used, or any Lafayette 2- or 3-way speaker system, or almost any other combination of speakers. Kits are supplied unfinished, smoothly sanded and ready for finishing. The lowboy-style cabinet dimensions are (less legs) 28 3/4" w x 23 1/4" h x 16 3/4" d; legs are 7" high. Highboy has same dimensions with height and width interchanged. Instructions, all parts, hardware, and grille are included with each kit. Shpg. wt., 54 lbs.

- CK-10WX Unfinished Highboy Enclosure Kit 2.00 Down Net 29.50
 - CK-11WX Unfinished Lowboy Enclosure Kit 2.00 Down Net 29.50
- FINISHING KITS**
- To obtain professional-like furniture finishes. Includes Varnish, Filler-stain, Sealer, Solvent, Brush, Sandpaper and detailed instructions. Shpg. Wt., 6 lbs.
- | | | |
|----------------------|------------------|-------------------|
| MS-584 Walnut | MS-586 Fruitwood | MS-588 Golden Oak |
| MS-585 Mahogany | MS-587 Cherry | MS-589 Maple |
| MS-697 Harvest Wheat | MS-589 Ebony | |
- Net each 3.87

- Factory-Assembled Bass Reflex Enclosures**
- Same as the Lafayette kits above but factory-assembled and finished in lustrous, hand-rubbed mahogany or blonde to measure up to the finest standards of high quality fine-furniture finishes. Also available assembled but unfinished. Shpg. wt., 54 lbs.
- | | | |
|--|-----------|-----------|
| CAB-13WX Assembled Unfinished Highboy | 2.00 Down | Net 39.50 |
| CAB-19WX Highboy, Assembled, finished in Mahogany or Blonde (please specify) | 2.00 Down | Net 49.50 |
| CAB-21WX Highboy Assembled in Walnut | 5.00 Down | Net 52.50 |
| CAB-14WX Assembled, Unfinished Lowboy | 2.00 Down | Net 39.50 |
| CAB-20WX Mahogany or Blonde Lowboy, completely assembled (please specify finish) | 2.00 Down | Net 49.50 |
| CAB-22WX Lowboy Assembled in Walnut | 5.00 Down | Net 52.50 |


HIGH FREQUENCY TWEETER WITH ACOUSTIC LENS

DIRECT IMPORTATION MAKES THIS PRICE POSSIBLE!

- FREQUENCY RESPONSE FROM 2000 CPS TO BEYOND AUDIBILITY
- LOUVERED ACOUSTIC LENS FOR UNIFORM SOUND DISPERSION
- HANDLES 25 WATTS OF POWER
- PRICED EXCEPTIONALLY LOW

14.95

New high frequency tweeter featuring a louvered acoustic lens for uniform sound dispersion and capable of handling up to 25 watts of distortion-free power. The directional tendency of high frequency notes is overcome by the natural wide dispersion angle of the short horn and the acoustic lens which disperses and radiates the high notes smoothly throughout the entire listening area. The lens is detachable for panel mounting, with a separate base for the tweeter furnished for external mounting where desired. Aluminum voice coil has 16 ohms impedance. Size: 4 1/4" long x 3" diameter, lens extends 2 1/2". Requires a crossover network, preferably one with a level control, such as the LN-2. With full instructions. Shpg. wt., 5 lbs.



FAMOUS LAFAYETTE HK-3 METAL-CASED CONE TYPE HI-FI TWEETER

OUTPERFORMS TWEETERS COSTING MANY TIMES THE PRICE

FREQUENCY RESPONSE 2000-16,000 CPS HANDLES 20 WATTS OF POWER

Highest quality cone type high frequency tweeter having a range from 2000 to 16,000 cycles. Especially efficient at higher end of audio spectrum where other cone type tweeters tend to lose clarity and volume. Entirely closed in a metal case with a base so that it can stand by itself or be mounted on a flat surface with mounting bracket supplied. Rated to handle 20 watts of power. A crossover network is required; the Lafayette LN-2 is ideal. Voice coil impedance 8-16 ohms. Size: 3 1/2" x 2 1/2" x 3" Diam. Shpg. wt., 3 lbs.

Net 5.95

NEW! METAL CASED TWEETER SPECIAL PRICE ONLY

2.95


- FREQUENCY RESPONSE 3,000-16,000 CPS
- HANDLES 20 WATTS OF POWER
- CHOICE OF 8 OR 16 OHM IMPEDANCE

The modest price of this tweeter gives no indication as to its high quality. Smooth, silky reproduction of the high frequencies along with an even sound dispersion is insured by the use of the round cone. The tweeter assembly is protected by a heavy wire mesh screen and completely enclosed in an attractive Satin Gold metal. As a result of the rear casing on the tweeter, speaker interaction between speakers has been eliminated allowing for the placement of the tweeter in the same enclosure with the woofer and mid-range speakers. Supplied with sturdy attached mounting stand and 2 1/2 ft. hook-up cord. Size 2 1/2" diam. x 2" deep. Shpg. wt., 2 1/2 lbs.

SK-121 8 ohm Tweeter Net 2.95
SK-122 16 ohm Tweeter Net 2.95

Famous 3-WAY SYSTEM

with 15" WOOFER... 8" MID-RANGE SPEAKER... HORN TWEETER... CROSSOVER NETWORK



55.50
ONLY \$5.00 DOWN

- 15-INCH WOOFER WITH 31.5 OZ. MAGNET (SK-67)
 - 8-INCH MID-RANGE SPEAKER (SK-74)
 - NEW HIGH-FREQUENCY ACOUSTICAL LENS TWEETER (HW-7)
 - 3-WAY CROSSOVER NETWORK (LN-5)
- Lafayette presents this outstanding 3-way speaker system designed for the high fidelity enthusiast who desires performance formerly possible in multi-speaker systems costing many times this price. You won't believe your ears when you hear the superb reproduction throughout the entire audio spectrum. The SK-67 15" woofer provides phenomenal bass response, the SK-74 8" speaker delivers full bodied, mid-range frequencies, and the HW-7 high frequency acoustical lens tweeter faithfully reproduces the highest audible frequencies. Crossover points at 350 and 5000 cycles are provided by the LN-5 3-way inductance-capacitance network with continuously variable presence and brilliance controls that adjust tone balance to personal taste. Shpg. wt., 25 lbs.

SY 93WX-Complete System as listed above. 5.00 Down Net 55.50

NEW! LAFAYETTE-GOODMANS High Fidelity Speakers

FROM ONE OF ENGLAND'S LEADING SPEAKER MFR'S!

LAFAYETTE-GOODMANS 3-way SPEAKER SYSTEM

ONLY 49.50 A REAL BUY

PERFECT for LAFAYETTE BASS REFLEX CABINETS (CABINET NOT INCLUDED)

- HANDLES 30 WATTS • FAMOUS ENGLISH GOODMANS MADE 12" WOOFER, 8 1/2" MIDRANGE, COMPRESSION-DRIVER HORN TWEETER • LAFAYETTE LC CROSSOVER NETWORK • SYSTEM RESPONSE 30-16,000 cps

Here is an outstanding 3-way high fidelity speaker system which we are indeed proud to be able to offer. It includes a group of speakers custom-made for Lafayette by Goodmans, famous English manufacturer of some of the world's best high fidelity speakers. The system is ideal for installation in Lafayette bass reflex speaker enclosures, and provides the extremely wide range of 30 to 16,000 cps (8 db down at 20,000 cps) smoothly and without unpleasant peaks. Power handling capacity of the system is 30 watts of integrated program material. Included in the system are the Lafayette-Goodmans SK-102 12" woofer covering the range from 30 to 700 cps, the Lafayette-Goodmans SK-103 8 1/2" mid-range speaker covering 700 to 5,000 cps, and the Lafayette-Goodmans SK-104 compression-driver tweeter operating at from 5,000 cps to over 16,000 cps. Also included is the Lafayette LN-5 inductance-capacitance (L/C) crossover network with attached Brilliance (high-frequency) and Presence (mid-range) controls. System impedance is 16 ohms. This is a really great system at an unusually low price! Shpg. wt., 25 lbs.

SY-163WX Lafayette-Goodman 3-Way Speaker System 2.00 Down Net 49.50

LAFAYETTE-GOODMANS 12" WOOFER

A highly-efficient low-frequency transducer for faithful reproduction of the lowest audible frequencies without tone coloration or distortion. Incorporates high flux Alcomax magnets for smooth response and good power sensitivity. Frequency response is 30-7,000 cps, with recommended crossover at 700 to 1000 cps. Total flux is 89,500 maxwells; voice coil diameter is 1 3/4". Rated at 30 watts power handling capacity for integrated program material in a multiple speaker system with an LC crossover network. Voice coil impedance 16 ohms. Size 12 1/4" diam. x 6" deep. Shpg. wt., 9 lbs.

SK-102 12" Lafayette-Goodman Woofer. 2.00 Down. Net 23.50

LAFAYETTE-GOODMANS high frequency DRIVER and HORN

A highly efficient compression-type wide-angle radiator for the higher audio frequencies. With high flux Alcomax magnets. Rigid plastic horn with circular mouth and special design acoustic chamber with phasing plug achieves smooth wide-angle distribution to extremely high frequencies. Horn diameter 2 1/2", mouth opening 1 3/4" diam. Pot diameter 2 3/4". Overall depth 3". Frequency response 2500 to 16,000 cps; 8 db down at 20,000 cps. Magnet flux is 25,400 maxwells. Voice coil diameter is 1". Recommended crossover is 5,000 cps. Power rating is 30 watts program material in a 3-way system. Voice coil is 16 ohms. Shpg. wt., 3 lbs.

SK-104 Lafayette-Goodmans Tweeter Net 10.95

LAFAYETTE-GOODMANS 8 1/2" MIDRANGE SPEAKER

• Alcomax Core and Self-Centering Aluminum Voice Coil

A sweet-sounding high-fidelity reproducer capable of doing full justice to the most important range of musical reproduction—the mid-frequency range from 500 to 5,000 cps. Incorporates high-efficiency Alcomax magnets, a specially-constructed cone with an "accordion fold" half-way down for smooth sound reproduction free from peaks and distortion; plus a completely sealed rear housing to prevent back radiation and interaction with other speakers. Response is 500 to 8,000 cps. Recommended crossovers are 700-1000 cps at the low end, 5,000 cps at the high end in a 3-way system. Magnet total flux is 32,900 maxwells. Voice coil diameter is 1". Power rating is 30 watts program material in a 3-way system. Voice coil is 16 ohms. Size is 8 1/2" diam. x 3 3/4" deep. Shpg. wt., 4 lbs.

SK-103 8 1/2" Lafayette-Goodmans Midrange Net 5.95

LAFAYETTE 2-WAY CROSSOVER NETWORK ADJUSTS TO EITHER 2500 OR 5000 CPS CROSSOVER FREQUENCY

7.95

A carefully designed capacitive-inductive 2-way crossover network with crossover frequency easily set to either 2500 or 5000 cycles. Has a built-in continuously variable high-frequency "Brilliance" level control to match room acoustics perfectly. Control has a 2 1/2 ft. cable to mount on rear or side of speaker cabinet, and a long shaft for thick wood panels. Has an attractive brushed-gold finish escutcheon plate. For use with 8-16 ohm speakers. Easily accessible screw terminals. Metal case 5 1/2" L x 2 1/4" H x 2 1/4" D. Complete with simplified instructions. Shpg. wt., 5 lbs.

LN-2B 2-Way Crossover Network With Control. Net 7.95

NEW! 2- and 3-way L/C CROSSOVER NETWORK

14.95


- 2- OR 3-WAY CHOICE OF 4 CROSSOVER FREQUENCIES
- 6 CROSSOVER COMBINATIONS
- METAL CABINET
- BUILT-IN BRILLIANCE AND PRESENCE CONTROLS

This versatile unit can be used either as a 2-way or 3-way 6 db. per octave network, simply by loosening a few screws on the rear terminal panel and shifting several wires. You can use this network for a 2-way system now, easily and quickly convert to 3-way later. Six crossover combinations are available—2-way crossover with 2000-3000 cycle or 5000 cycle crossover, and 3-way with crossover frequencies of 350 and 5000, 350 and 2000-3000, 700 and 2000-3000 or 700 and 5000 cycles—a total of four different crossover frequencies! Suitable for 8-16 ohm speakers. The network is housed in an attractive metal case, suitable for mounting inside enclosure or leaving out in the open. Two level controls—Brilliance and Presence controls—are mounted on the front panel. If desired, these level controls may be removed, along with the beautiful gleaming copper escutcheon plate, for external mounting; controls are wired with 3-foot long leads. High quality components are used for long life and top performance.

LN-5 Lafayette L/C Crossover Net 14.95



RCA 202W1—Two Circuit Selector Switch



- Switches 2 phono—or phono & tuner—to single input!
- Saves your precious HI FI record player!
- Switches Car Radio and Citizens Band Equipment to Single Antenna!

.99

Reg. List 5.65 Special at

RCA's famous two circuit selector switch—with a raft of uses in any audio or electronic rig. Switches 2 phono—or phono and tuner—or 2 tuners—or tape recorders—any program source to one input. Can switch speaker output to either of 2 speakers. Can be adapted to switching auto radio and citizens band rig to one antenna. Heavy shielding makes it a natural for R/F and audio switching problems. Or use it to switch the "kids" record player through your Hi-Fi set to protect your record player. Or switch your TV output to a head set to protect your nerves when the "shoot in" starts! Complete with 36" lead, adapter, mtg. screws and Instructions for use as record player selector. Shpg. wt., 8 ozs.

SP-161 Net .99

Mercury STEREO GIFT RECORDS! LESS THAN HALF-PRICE!



★ CLASSICALS ★ POPS ★ NOVELTIES
★ INSTRUMENTALS ★ SHOW TUNES

IN
LOTS
OF 5
13.49
Reg. Value
29.90

Reg. 5.98
2.89
EACH

Leave it to Lafayette to solve your ticklish gift problems — and to stock your own personal record collection with these much-wanted Mercury 12" Stereo LP's — AT LESS THAN HALF-PRICE — and right in time for the gift-giving season. The LARGEST and BEST assortment of Mercury stereo discs to satisfy every musical taste. These are BRAND NEW FACTORY-FRESH wanted recordings by TOP NAME ARTISTS. Lowest priced at \$2.89 each, you can SAVE STILL FURTHER by selecting FIVE for \$13.49. Get your order in fast while stocks are complete. Please indicate second choices. Include postage with your order — allowing 1 lb. per disc.

- SR60000 — RICHARD HAYMAN CUBAN FAVORITES — 9 selections include Tropical Merengue, Love and the World Loves With You, Caminito, Rhapsodero, Lo Compara. STOCK NO. PR-110.
- SR60001 — LET'S DANCE, DAVID CARROLL & ORCH. — A dozen delightful tunes including Cuddle Up a Little Closer, The Trouble With Merry, Let's Dance, The Glow Worm, Armen's Theme, Puerto Rican Paddler. STOCK NO. PR-111
- SR60021 — WE COULD HAVE DANCED ALL NIGHT — Dance treats by Griff Williams and his orchestra, includes I Get A Kick Out of You, I Know That You Know, Isn't This A Lovely Day, Let's Fly Away. STOCK NO. PR-112
- SR60055 — POLKA TIME — 40 minutes of accordionist Dick Cantino in Pennsylvania Polka, Beer Barrel Polka, Mond Clap Polka, Hot Pretzels and Liechtensteiner Polka. STOCK NO. PR-113
- SR60056 — JOHN CALI, THE BANJO MINSTREL MAN — Banjo, barbershop quartet, trombones and tuba accompany this artist in By The Light of The Silvery Moon, Somebody Stole My Gal, Waiting For The Robert E. Lee, and others. STOCK NO. PR-114
- SR60065 — SONGS FROM GREAT SHOWS — Clebonoff Strings play 12 favorites including I've Grown Accustomed to Her Face (My Fair Lady), Balli Hai (South Pacific), They Say It's Wonder (Annie Get Your Gun) and others. STOCK NO. PR-115
- SR60068 — OLDIES BUT GOODIES — Griff Williams plays old and new favorites — Teo For Two, Moonlight Serenade, Oh You Beautiful Doll, Brazil, Three Little Words, and many others. STOCK NO. PR-116
- SR60082 — JAN AUGUST — A dozen piano Cha-Cha selections including You're The Cream In My Coffee, Boogie Woogie Cho Cha, etc. STOCK NO. PR-117
- SR90001 — CARMEN SUITE—Music from Carmen and the L'Arlesienne Suites No. 1 and 2 with Paul Paray conducting the Detroit Symphony Orchestra. STOCK NO. PR-118
- SR90002 — RHAPSODY IN BLUE — Eugene List in Gershwin's Immortal Rhapsody and Concerto in F. Eastman-Rochester Symphony Orchestra under direction of Howard Hanson. STOCK NO. PR-119
- SR90005 — BOLERO — The famous Ravel Work plus Ravel's Mother Goose Suite and Chabrier's Bourree Fantastique, directed by Paul Paray. STOCK NO. PR-120
- SR90009 — MUSIC OF LEROY ANDERSON, VOL. 1 — Frederick Fennell arranges and conducts the Eastman-Rochester POPS orchestra in Sleigh Ride and Bugler's Holiday, Sandpaper Ballet, Irish Suite, Serenade, Forgotten Dreams and many others. STOCK NO. PR-121
- SR90016 — GAITE PARISIENNE — Antal Dorati and Minneapolis Symphony Orchestra in Offenbach's Ballet and the ballet from Strauss' Graduation Ball. STOCK NO. PR-122
- SR90049 — GRAND CANYON AND MISSISSIPPI SUITES — Symphonic tone poems by Ferde Grofe played by Eastman-Rochester Orchestra, conducted by Howard Hanson. STOCK NO. PR-123
- SR90105 — MARCHING ALONG — Stirring rendition of a dozen famous marches, including The Stars and Stripes Forever, The U. S. Field Artillery, El Capitan, On The Mall, Washington Post, American Patrol and others. STOCK NO. PR-124
- SR90109 — BOARDWALK PIPES — Robert Elmore of the world-famous Atlantic City Convention Hall organ. Numbers include Stars and Stripes Forever, Liebesfreud, Squirrel, Coprice Viennois, Marche Champetre, Stars In My EYES, Old Refrain, Fantasy on Nursery Themes and many others. STOCK NO. PR-125
- SR90122 — BORODIN — Polovetzian Music from "Prince Igor" performed by Minneapolis Symphony Orchestra and large chorus under direction of Antal Dorati Paired with Rimsky-Korsakov's Le Coq D'Or Suite. STOCK NO. PR-126
- SR90156 — VERDI — Five overtures and preludes played by London Symphony Orchestra, conducted by Antal Dorati. Forza del Destino, Vespri Siciliano, Nebucco, Traviato. STOCK NO. PR-127
- SR90170 — MARCH TIME—Eleven Marches played by Eastman Symphonic Wind Ensemble conducted by Frederick Fennell including Guadalcanal March, Illinois March, March Grandioso, Americans We, The Mad Major. STOCK NO. PR-128
- SR90195 — RIMSKY-KORSAKOFF—Scherzade, Symphonic Suite Op. 35 played by Minneapolis Symphony Orchestra with Rafael Drujan violin interpretations and conducted by Antal Dorati. STOCK NO. PR-129

RECORDS ARE NOT AVAILABLE ON LAFAYETTE'S EASY PAY PLAN
ADD 35¢ PER ORDER FOR PACKING AND HANDLING

RCA VICTOR
LM-6074

60 YEARS OF "MUSIC AMERICA LOVES BEST"

This special 2 record monophonic set contains a fabulous cavalcade, featuring outstanding performances by these musical immortals:

CARUSO	TOSCANINI	ARTIE SHAW
RUBINSTEIN	JAN PEECE	TOMMY DORSEY
MARIO LANZA	HEIFETZ	PERRY COMO
PADEREWSKI	STOKOWSKI	AMES BROTHERS
JOSE ITURBI	BENNY GOODMAN	DUKE ELLINGTON
PAUL WHITEMAN	GLENN MILLER	HARRY BELAFONTE
	AND OTHERS	

List 9.96
3.38
2 RECORDS

AMAZING OFFER OF RCA VICTOR RECORDS

1812 OVERTURE AND BOLERO
STEREO RCA VICTOR LSC-2345
ORCHESTRA AND BAND WITH CANNON AND BELLS
CONDUCTED BY MORTON GOULD

A new exciting stereo recording rich in sonic splendor. The record surface contains a new, revolutionary antistatic ingredient which repels dust.

PR-102 2 Record Set — Shpg. wt., 2 lbs. Net **3.38**

PR-101 1812 Shpg. Wt., 1 lb. Net **1.69**

RECORDS ARE NOT AVAILABLE ON LAFAYETTE'S EASY PAY PLAN
ADD 35¢ PER ORDER FOR PACKING AND HANDLING

1.69 5.98 Value

RCA VICTOR
LSC-2345

NOW! Lafayette Gives You Tremendous Savings On AUDIO FIDELITY Records INCLUDING THE LATEST RELEASES

DISCOUNTS OVER 45% • SAVINGS AS HIGH AS \$3.17

\$6.95 STEREO
3.78 each
Shpg. wt., 1 lb. each disc


\$5.95 MONAURAL
3.25 each



- THE BRAVE BULLS**—Step right into the bull ring with the original Banda Taurina of the Plaza Mexico, Genaro Nunez, conductor. Includes the famous Bullfighter's Entry Music (La Virgen De La Macarena), and a musical description and picture story of the fight. (Monaural, AFLP-1801) 5.95 value. **3.25**
PR-130 (Stereo, AFSD-5801) 6.95 value. **3.78**
PR-131 **3.78**
- ROME WITH LOVE**—Jo Basile, with his accordion and orchestra, give you an intimate tour of the Italian capital in his rich, warm and dynamic style. Nostalgic and beautiful Italian melodies include Arrivederci Rama, Anima E. Core, O Sole Mio, Santa Lucia. (Monaural, AFLP-1822) 5.95 value. **3.25**
PR-132 (Stereo, AFSD-5822) 6.95 value. **3.78**
PR-133 **3.78**
- MALLET MAGIC**—Harry Brewer and his Quintet play old favorites in a new style of music-making. You'll appreciate Bumble Bee Bolero, Tulip Polka, and others. (Monaural, AFLP-1825) 5.95 value. **3.25**
PR-134 (Stereo, AFSD-5825) 6.95 value. **3.78**
PR-135 **3.78**
- JOHNNY PULEO**—The little rascal with his mischievous grin display their artistic talent on the mouth organs. You'll remember Peg O' My Heart, Rates of Picardy, Peanut Vendor, Twelfth Street Rag, etc. (Monaural, AFLP-1830) 5.95 value. **3.25**
PR-136 (Stereo, AFSD-5830) 6.95 value. **3.78**
PR-137 **3.78**
- RAILROAD SOUNDS**—The sounds of a vanishing era captured in all its glory and transformed into a pageantry of sounds for the high-fidelity enthusiasts. (Monaural, AFLP-1843) 5.95 value. **3.25**
PR-138 (Stereo, AFSD-5843) 6.95 value. **3.78**
PR-139 **3.78**
- HAWAII**—Johnny Pineapple and his Islanders bid you aloha to woffing, sensuous Hawaii. You'll recognize the familiar Lovely Hula Hands, Hawaiian War Chant, My Little Grass Shack, Kui Lei, and more. (Monaural, AFLP-1850) 5.95 value. **3.25**
PR-140 (Stereo, AFSD-5850) 6.95 value. **3.78**
PR-141 **3.78**
- VIENNESE WALTZES**—The charm of old Vienna is recreated for you by Joe Basile, his accordion and orchestra. You're invited to dance to such captivating tunes as Waltz Time in Vienna, Waltz Dream, Cafe Mazarin. (Monaural, AFLP-1868) 5.95 value. **3.25**
PR-142 (Stereo, AFSD-5868) 6.95 value. **3.78**
PR-143 **3.78**
- VIENNESE WALTZES**—The charm of old Vienna is recreated for you by Joe Basile, his accordion and orchestra. You're invited to dance to such captivating tunes as Waltz Time in Vienna, Waltz Dream, Cafe Mazarin. (Monaural, AFLP-1868) 5.95 value. **3.25**
PR-142 (Stereo, AFSD-5868) 6.95 value. **3.78**
PR-143 **3.78**
- AL MELGARD AT THE CHICAGO STADIUM ORGAN**—The brilliant highs and dynamic lows of the theatre pipe organ—the world's largest with 40,000 pipes. Versatile Al Melgard plays Parade of the Wooden Soldiers, Battle Hymn of the Republic, and many more. (Monaural, AFLP-1886) 5.95 value. **3.25**
PR-146 (Stereo, AFSD-5886) 6.95 value. **3.78**
PR-147 **3.78**
- CHA CHA . . . CHA CHA CHA**—Played by the Morimba Chiapas, the foremost Morimba group of Mexico. Dance, or listen, to the infectious beat of Cosita Linda, Dancero, Tarera, El Manicera, and many more. (Monaural, AFLP-1900) 5.95 value. **3.25**
PR-148 (Stereo, AFSD-5900) 6.95 value. **3.78**
PR-149 **3.78**
- ITALIAN STREET SINGER**—Featuring the vibrant voice of Val Valenti. You'll thrill to the warmth and enthusiasm of the Italian Street Singer through such selections as Core 'ngrata, Mattinata, Tiritamba. (Monaural, AFLP-1902) 5.95 value. **3.25**
PR-150 (Stereo, AFSD-5902) 6.95 value. **3.78**
PR-151 **3.78**
- LARRY ADLER**—Outstanding artistry . . . unequalled virtuosity in a display of talent never heard before. The most renowned harmonic master playing such selections as Summer Time, Blues in the Night, Genevieve. (Monaural, AFLP-1909) 5.95 value. **3.25**
PR-154 (Stereo, AFSD-5909) 6.95 value. **3.78**
PR-155 **3.78**
- DIXIELAND BANJO**—Featuring Dave Wierbach and his Dixieland band. Hear the exciting banjo of the minstrel era, backed by the band, swing in the true dixieland manner. Limehouse Blues, Chinatown, etc. (Monaural, AFLP-1910) 5.95 value. **3.25**
PR-156 (Stereo, AFSD-5910) 6.95 value. **3.78**
PR-157 **3.78**
- HAMP'S BIG BAND**—None other than Lionel Hampton of the vibes . . . at his greatest. Hamp is fantastic with his big band in such outstanding jazz numbers as Air Mail Special, Night Train, Hamp's Boogie, Hey Ba Ba Re Bop. (Monaural, AFLP-1913) 5.95 value. **3.25**
PR-158 (Stereo, AFSD-5913) 6.95 value. **3.78**
PR-159 **3.78**
- DUKES OF DIXIELAND: CARNEGIE HALL CONCERT**—Join the enthusiastic and sellout audience at New York's Carnegie Hall for the "in-person" concert of the phenomenal Dukes. You too will acclaim their Muskrat Ramble, Royal Garden Blues, Maritot, etc. (Monaural, AFLP-1918) 5.95 value. **3.25**
PR-162 (Stereo, AFSD-5918) 6.95 value. **3.78**
PR-163 **3.78**
- JOHNNY PULEO: WESTERN SONGS**—Go west with Johnny Puleo and his Harmonica Gang. Hear the amazing talent of the mouth organ as the whole gang plays the all-time hits including Red River Valley, Yellow Rose of Texas, On Top of Old Smokey, and many more. (Monaural, AFLP-1919) 5.95 value. **3.25**
PR-164 (Stereo, AFSD-5919) 6.95 value. **3.78**
PR-165 **3.78**
- DEMONSTRATION AND SOUND EFFECTS RECORD**—An informative and fascinating demonstration of stereophonic reproduction of sounds including cannons, fire engines, subway trains, etc. Also includes a lecture and demonstration of stereo sound depth. (Stereo Only, AFSD-5890) 6.95 value. **3.78**
PR-166 **3.78**
- FIRST COMPONENT SERIES: STEREO TEST RECORD**—A must for all stereophiles, present and future. Special tests of separate bands for checking of speaker and amplifier, 30-15,000 cps frequency response, tone arm and stylus tracking, and others. Also has choice musical selection; reproduced in stereo. (Stereo Only, FCS-50,000) 6.95 value. **3.78**
PR-167 **3.78**

RECORDS ARE NOT AVAILABLE ON LAFAYETTE'S EASY PAY PLAN
ADD 35¢ PER ORDER FOR PACKING AND HANDLING

SAVE UP TO 75% on **RCA** GOLD LABEL SPEAKERS



RCA 12" WIDE RANGE HI-FI SPEAKER

6.95
QUANTITY LIMITED

USED IN RCA \$600 CONSOLES—FREQUENCY RANGE 50-15,000 CYCLES

These are the same speakers used by RCA in their fine sets selling in the \$600.00 price range. This fine 12" wide range speaker covers from 50 to 15,000 Cycles and has a heavy 6.8 oz. Alnico 5 magnet. Voice Coil 8 ohms. Shpg. Wt., 6 lbs.

SK-168 6.95

RCA "GOLD LABEL" PM REPLACEMENT SPEAKERS

SAVE UP TO 75% QUANTITIES LIMITED

Fine replacement speakers — all with 3.2 ohm voice coil

STOCK NO.	RCA NO.	SIZE	WATTS	MAG (oz.)	LBS.	LIST	NET
SK-165	2693-1	4"x6"	3	.53	1 1/2	3.75	1.19
SK-172	24652	4"x6"	3	.68	1 1/2	4.20	1.29
SK-173	44652	4"x6"	3	1.47	1 1/2	4.75	1.75
SK-170	2688-9	5"x7"	4	.76	2	4.25	1.40
SK-166	22951	4 1/2"	4	1.0	2	4.90	1.59
SK-167	2673-7	6 1/2"	5	2.15	2	5.75	1.79

Lafayette EXCLUSIVE SCOOP!


THE STANDARD "NEUTRODE" CASCODE TUNER

13.75

Each
In lots of 3
13.25
Each

This is the latest design of the famous Standard Coil 12-channel tuners that have been used in more TV sets than any other. The "Neutrode" is an exact physical and electrical replacement for all previous Standard Coil cascode tuners, but is far superior in sensitivity and performance. Shaft is 6" long and can be cut easily to desired length—a perfect universal replacement. Supplied complete with 6CG8 and 6BN4 tubes and schematic diagram. Shpg. wt., 4 lbs.

TL-52—For 21 Mc. only Net 13.75
In Lots of 3 Each 13.25



1.28

SOUND TAKE-OFF COIL



Designed for use with Cascode Tuner for T.V. Sets having separate video and sound I.F.'s Standard Coil No. XM752. Shpg. wt., 2 oz.

TS-309 Net 1.28

SAVE FREE!

UP TO 56% ON YOUR RECEIVING TUBE PURCHASES

RCA GE PLUS SYLVANIA

VALUABLE FREE GIFTS ON PURCHASE OF 15 OR MORE TUBES

30 WATT SOLDERING PENCIL

Reg. Price **1.79**

FREE with Purchase of 15 Receiving Tubes

TECHNICIAN'S ELECTRIC TOOL KIT

Reg. Price **7.95**

FREE with Purchase of 50 Receiving Tubes

20,000 Ohms-Per-Volt VOM

Reg. Price **13.50**

FREE with Purchase of 100 Receiving Tubes

ALL BRAND NEW — FRESH STOCK — ORIGINAL BOXED TUBES • FULL 12 MONTH GUARANTEE • YOU MAY ASSORT FOR QUANTITY — PRICE SAVINGS!

TUBE TYPE	List Price	NET EACH IN QUANTITIES OF:				TUBE TYPE	List Price	NET EACH IN QUANTITIES OF:				TUBE TYPE	List Price	NET EACH IN QUANTITIES OF:					
		1 to 5	6 to 49	50 or more				1 to 5	6 to 49	50 or more				1 to 5	6 to 49	50 or more			
OZ4	2.15	1.14	1.05	.94	6AW8A	3.55	1.88	1.74	1.57	6S4A	2.05	1.09	1.00	.90	12BY7A	3.05	1.62	1.49	1.34
1B3GT	2.90	1.54	1.42	1.28	6AX4GT	2.65	1.40	1.30	1.17	6S4A	3.40	1.80	1.66	1.49	12SA7	3.70	1.96	1.81	1.63
1R5	2.55	1.35	1.25	1.12	6BA6	2.00	1.06	.98	.88	6SN7GTB	2.60	1.37	1.27	1.14	12SA7GT	3.25	1.71	1.59	1.43
1U4	2.35	1.24	1.15	1.03	6BC5	2.30	1.22	1.13	1.02	6SQ7	3.15	1.67	1.54	1.39	12SK7	3.40	1.80	1.66	1.49
1U5	2.05	1.09	1.00	.90	6BE6	2.20	1.17	1.08	.97	6T8A	3.35	1.77	1.64	1.48	12SQ7	3.15	1.67	1.54	1.39
1X2A/B	3.05	1.62	1.49	1.34	6BG6GA	6.50	3.44	3.18	2.86	6U8A	3.30	1.74	1.62	1.46	25L6GT	2.25	1.19	1.10	.99
3BZ6	2.30	1.22	1.13	1.02	6BK7B	3.35	1.77	1.64	1.48	6V6GT	2.15	1.14	1.05	.94	35C5	2.15	1.14	1.05	.94
3CB6	2.25	1.19	1.10	.99	6BL7GTA	3.95	2.09	1.93	1.74	6W4GT	2.40	1.27	1.18	1.06	35L6GT	2.40	1.27	1.18	1.06
3V4	2.35	1.24	1.15	1.03	6BQ6GT/6CU6	4.35	2.30	2.13	1.92	6W6GT	2.85	1.51	1.40	1.26	35W4	1.40	.74	.69	.62
5U4GB	2.10	1.11	1.03	.93	6BQ7A	3.95	2.09	1.93	1.74	6X4	1.65	.87	.80	.72	35Z5GT	1.85	.98	.91	.82
5U8	3.30	1.74	1.62	1.46	6BZ7	4.00	2.12	1.96	1.76	6X5GT	2.05	1.09	1.00	.90	50C5	2.15	1.14	1.05	.94
5V4GA	3.30	1.74	1.62	1.46	6C4	1.85	.98	.91	.82	6X8	3.15	1.67	1.54	1.39	50L6GT	2.40	1.27	1.18	1.06
5Y3GT	1.75	.93	.86	.79	6CB6	2.25	1.19	1.10	.99	12AT6	1.85	.98	.91	.82	117Z3	2.50	1.32	1.22	1.10
6AC7	4.65	2.46	2.27	2.04	6CB6A	2.25	1.19	1.10	.99	12AT7	3.05	1.62	1.49	1.34					
6AF4A	4.00	2.12	1.96	1.76	6CG6A	5.80	3.06	2.84	2.56	12AU7A	2.45	1.29	1.20	1.08					
6AG5	2.60	1.37	1.27	1.14	6CG7	2.45	1.29	1.20	1.08	12AV6	1.65	.87	.80	.72					
6AL5	1.85	.98	.91	.82	6DQ6A	4.15	2.20	2.03	1.83	12AX7	2.55	1.35	1.25	1.12					
6AN8	3.50	1.85	1.71	1.54	6E6	2.80	1.48	1.37	1.23	12BA6	2.00	1.06	.98	.88					
6AQ5A	2.15	1.14	1.05	.94	6E6GT	2.35	1.24	1.15	1.03	12BE6	2.15	1.14	1.05	.94					
6AU6A	2.10	1.11	1.03	.93	6L6GB	4.20	2.22	2.06	1.85	12BH7A	3.05	1.62	1.49	1.34					

NOTE: This is a partial listing. This gift offer also applies to your selection from our complete receiving tube listing on Pages 106 and 107, Catalog 600. Your order is shipped at current prices. You benefit from any price reductions during life of this catalog.

LAFAYETTE BUDGET-PRICED TV PICTURE TUBES

• GUARANTEED ONE FULL YEAR

TOP QUALITY PICTURE TUBES IN FACTORY-SEALED CARTON — REBUILT BY TOP TV PICTURE TUBE MANUFACTURER AT LAFAYETTE ECONOMY PRICES!

STOCK NO.	TYPE	SHPG. WT. LBS.	NET PRICE LESS DUD	NET PRICE WITH DUD
PT-350X	12LP4A	17	12.75	11.75
PT-351X	14EP4/CP4	14	12.95	11.95
PT-352X	14EP4B/CP4B*	14	14.85	13.85
PT-353X	16AP4/AP4A	22	18.50	15.00
PT-354X	16GP4†	22	18.50	16.50
PT-355X	16KP4/RP4	21	12.75	11.75
PT-356X	16KP4A/RP4A*	21	15.00	14.00
PT-357X	17BP4/BP4A	21	15.50	12.00
PT-358X	17BP4B*	21	18.00	14.50
PT-359X	17CP4†	16	21.95	17.45
PT-360X	17GP4/TP4†	24	25.75	21.25
PT-361X	17HP4/RP4	24	19.75	16.25
PT-362X	17HP4B/RP4C*	24	21.40	17.90
PT-363X	17LP4/VP4	23	17.25	15.00
PT-364X	17LP4A/VP4B*	23	18.25	16.00
PT-365X	19AP4A†	24	22.50	21.50
PT-366X	19AP4B†	24	22.50	21.50
PT-367X	20CP4A/DP4A	29	18.50	16.00
PT-368X	20CP4D/DP4C*	29	20.25	17.75
PT-369X	21AP4	25	29.00	23.00
PT-370X	21ACP4A/AMP4A/BSP4*	35	21.50	16.50
PT-371X	21ALP4	35	21.50	16.50
PT-372X	21ALP4A*	35	26.25	21.25
PT-373X	21AUP4/AVP4A	35	23.25	18.25
PT-374X	21AUP4B/AVP4B*	35	26.25	21.25
PT-375X	21CBP4A*	35	26.25	21.25

STOCK NO.	TYPE	SHPG. WT. LBS.	NET PRICE LESS DUD	NET PRICE WITH DUD	STOCK NO.	TYPE	SHPG. WT. LBS.	NET PRICE LESS DUD	NET PRICE WITH DUD
PT-376X	21EP4A	35	19.50	17.00	PT-380X	21WP4	31	22.00	19.50
PT-377X	21EP4B*	35	21.00	18.50	PT-381X	21WP4A*	35	24.75	22.25
PT-378X	21FP4A/KP4A	35	20.75	18.25	PT-382X	21YP4	35	21.50	16.50
PT-379X	21FP4C/KP4C*	35	23.00	20.50	PT-383X	21YP4A*	35	24.00	19.00

Net price "with DUD" based on your prepaid shipment or delivery of old picture tube (Dud). Returned tubes must be intact and without scratches. When ordering give stock number and type. * indicates tubes with aluminized screens. † indicates metal tubes.



Lafayette BATTERIES

AT TREMENDOUS SAVINGS
These popular batteries are for Portable and Transistor radios, R/C equipment, experimenters, labs, and hobbyists, etc.

FRESH STOCK — BRAND NEW — GUARANTEED
Here are six of the most popular types used and at RIDICULOUSLY LOW PRICES

Stock No.	Voltage	Net Each	Lots 10	RCA	Burgess	Eveready	Others
BA-1	67 1/2	1.59	1.49	VS215	P45	477	BL-M145
				VS216	P45M		
				VS218			
BA-2	9	.59	.53	VS312	7U6	216	BL-006P
				VS323			
BA-3	9	.59	.53	VS300A	P6		
				VS314	P6M	226	BL-M10A
BA-5	67 1/2	1.29	1.19	VS318	UX45	416	BL-045
BA-6	67 1/2	1.45	1.35	VS016	XX45	467	BL-145
BA-7	9	.59	.53	V5-309A	3-177	Mol	TR-177

UNEQUALED QUALITY AND SAVINGS IN LAFAYETTE HI-FI KITS

KT-310 36 WATT (18 WATTS PER CHANNEL) STEREO BASIC POWER AMPLIFIER KIT

- 36-WATT STEREO AMPLIFIER - 18-WATTS EACH CHANNEL
- EMPLOY'S 4 NEW PREMIUM-TYPE 7189 OUTPUT TUBES
- 2 PRINTED CIRCUIT BOARDS FOR NEAT, SIMPLIFIED WIRING
- RESPONSE BETTER THAN 35-30,000 CPS \pm 1/2 DB AT 18 WATTS
- LESS THAN 1% HARMONIC OR INTERMODULATION DISTORTION




2.00 down
47.50

Save lots of money without sacrificing high-fidelity performance by assembling this carefully engineered basic amplifier kit. Designed for both stereo and monaural applications—circuit provides 18 watts on each stereo channel or can deliver a hefty 36 watts when operated monaurally. TRUE HIGH-FIDELITY RESPONSE with coverage from 35 to 30,000 cps \pm 1/2 db at 18 watts. Four premium-type 7189 output tubes are your assurance of true, undistorted reproduction of all program material. Less than 1% IM or harmonic distortion. CONTROLS include two input volume controls, a channel-reverse switch (AB-BA), and a monaural/sterео mode switch. DUAL OUTPUT IMPEDANCES of 4, 8, 16 and 32 ohms, the latter tap permitting

the parallel (monaural) operation of two speaker systems of up to 16 ohms impedance. INPUT SENSITIVITY is 0.45 volt per channel for full output. PRINTED CIRCUIT BOARDS make it easy for even the beginner to assemble his own amplifier. The illustrated instruction manual which comes with the kit outlines each step clearly and completely. The kit includes all parts, the perforated metal cage shown in the photograph, tubes, and instruction manual. Overall measurements are: 9-3/16" deep (10-9/16" with control knobs), 5 1/4" high, and 13 1/4" wide. Shipping weight is 22 lbs. KT-310WX 2.00 Down Net 47.50 LA-310WX Same as above, but completely wired and tested 5.00 Down Net 72.50

70-WATT DELUXE BASIC AMPLIFIER KIT

- Frequency Response 10-100,000 cps +1db at 1 watt
- Power Response 20-20,000 cps +1db at 70 watts with less than 2%
- Inverse Feedback
- Variable Damping
- Metered Balance and Bias Adjust Controls
- Famed Chicago Wide-Range Linear Output & Power Transformers.



KT-400
5.00 down
69.50

Here's ultra-stability in a 70 watt basic power amplifier employing highest quality components conservatively rated to insure performance and long life. Features matched pair KT 88's and wire range linear Chicago output transformer, variable damping control, meter for bias and balance and gold finish chassis. Frequency response 10-100,000 cps \pm 1 db. Hum and noise 90 db below full output. IM distortion less than 1 1/2% at 70 watts, less than 0.3% below 30 watts. Harmonic distortion less than 2% at 70 watts from

20 to 20,000 cps \pm 1 db. Output impedance 4, 8 and 16 ohms. Handsome decorative cage perforated for proper ventilation. Size 14 1/2" x 10 x 7 1/8" including cage and knobs. Shpg. wt., 40 lbs. KT400WX — Lafayette 70 watt Deluxe Basic Amplifier Kit complete with cage and detailed assembly instructions. 5.00 Down Net 69.50 LA-70WX — Same as above completely wired and tested with cage and instruction manual 5.00 Down Net 94.50

KT-300 MASTER AUDIO CONTROL CENTER KIT

- HIGHLY FLEXIBLE — CANNOT BECOME OBSOLETE ● SELF-POWERED
- DC ON ALL FILAMENTS ● 24 POSITIONS OF EQUALIZATION
- TAPE HEAD INPUT, HIGH IMPEDANCE
- DUAL CATHODE FOLLOWER OUTPUT STAGES
- PERFECT FOR CONVERTING TO STEREO



2.00 down
29.50


The KT-300 is not only an outstanding monaural preamp, but it has been functionally designed to keep pace with the conversion of your present HI-FI system to stereo. A special dual volume control provides for the output adjustment of a second preamplifier. Features include DC on all tube filaments, negative feedback in every stage, dual cathode follower output stages and latest printed circuit construction. Less than 0.09% IM distortion and less than 0.07 harmonic distortion at 1 volt. Hum and noise level better than 80 db below 3 volts. Uniformly flat

frequency response over entire audible spectrum. 7 inputs for every type of phono, tuner or tape. Size 12 3/4" x 9 1/8" x 3 3/4". Shpg. wt. 10 1/2 lbs. Lafayette Master Audio Control Kit. Complete with cage and detailed assembly instructions. KT-300 2.00 Down Net 29.50

Same as above, but completely wired and tested with cage and instruction manual. LT-30 2.00 Down Net 49.50

KT-315 STEREO CONTROL CENTER KIT

- TWO LOW NOISE 7025 DUAL-TRIODES
- POSITIVE CONTROL 50 FEET OR MORE
- BRIDGE BALANCING CIRCUIT
- OUTPUT FOR "THIRD CHANNEL"
- CLUTCH-TYPE VOLUME CONTROL



2.00 down
27.50

This self-powered electronic adapter offers exciting features unique even in the fast moving stereo field. Inclusion of low-impedance "plate follower" outputs permits remote operation 50 feet or more from the controlled amplifier. Unusual bridge circuit assures precise balancing of the stereo system by means of audible "null." Objectionable "hole-in-the-middle" effect can be eliminated by cross-feeding variable amounts of audio from each channel. Includes controlled third-channel output for driving third amplifier and speaker, if desired. Individual or simultaneous control of each channel. Phase reversal with or

without channel reversal. Selective monaural operation. Frequency response 10 to 25,000 cps \pm 0.5 db; gain 6 db; cross channel rejection better than 50 db.

Premium type 7025 dual triodes. Printed circuit boards for easy error-free assembly. Complete, profusely illustrated manual included. Adapter with cage measures 6 1/2" wide x 4 1/2" high x 7" deep (not including knobs and projections). Shipping weight 7 1/2 lbs. KT-315 Electronic Stereo Adapter Kit (with cage) 2.00 Down Net 27.50

DO-IT-YOURSELF PROFESSIONAL STEREO HI-FI SYSTEMS

Build it yourself... enjoy the finest in stereophonic sound by assembling these Lafayette components in kit form. Lafayette's crystal clear instruction manuals and pictorial diagrams insure easy assembly even if you have no previous technical experience. Best of all — Lafayette kit systems offer you the best in stereo equipment at tremendous savings.

COMPONENTS

LAFAYETTE KT-600WX STEREO PREAMP KIT	79.50
LAFAYETTE KT-310WX 36 WATT STEREO POWER AMP. KIT	47.50
GLASER-STEERS GS-77 DELUXE CHANGER	59.50
NEW GE VR-22 (.7 MIL) DIAMOND STEREO CARTRIDGE	24.45
2-LAFAYETTE-GOODMANS SK-113WX 3-WAY 15" SPEAKERS @ 79.50	159.00
Regular Catalog Price — 349.95	

You Save 55.05

LAFAYETTE SYSTEM PRICE **314.90**

Only 10.00 Down

Complete stereo system as described above. Shpg. wt., 112 lbs. MF-660WX 10.00 Down Net 314.90

Same as MF-660WX but with the addition of 2 — Lafayette Highboy speaker enclosures. Choice of CAB-19 in Mahogany or Blonde and CAB-21 in Walnut (Please Specify). Shpg. wt., 188 lbs. Dimensions 20"W x 23"H x 16"D. MF-661WX 10.00 Down Net 404.90

Model GSB Woodbase for GS-77 in ebony with satin brass trim. Shpg. wt., 5 lbs. PK-350W Net 9.60



● SELECT YOUR OWN CARTRIDGE ● You may substitute the Shure M7D, Pickering 371C, or the new Electro-Voice 31MD7 in any system shown with the GE VR-22 at no additional cost. The Shure M3D may be substituted at an additional cost of \$24.00.

COMPONENTS

LAFAYETTE KT-600WX STEREO PREAMP KIT	79.50
2-LAFAYETTE KT-400WX 70-WATT AMPLIFIER KITS @ 69.50	139.00
LAFAYETTE PK-245WX PROFESSIONAL TURNTABLE (Less Base)	64.50
LAFAYETTE PK-270W 12" TONE ARM	17.50
NEW GE VR-22 (.5 MIL) STEREO	27.39
2-LAFAYETTE-GOODMANS SK-115WX 3-WAY 15" SPEAKERS @ 82.00	164.00
Regular Catalog Price — 491.89	

You Save 52.39
LAFAYETTE SYSTEM PRICE 439.50


Only 10.00 Down

Complete stereo system as listed above. Shpg. wt., 195 lbs. MF-716WX 10.00 Down Net 439.50

Wood base for Lafayette PK-245WX. Specify finish. PK-265W Net 14.95

Same as MF-716WX, but with Lafayette PK-280W 16" Tone Arm instead of PK-270 Tone Arm. Shpg. wt., 196 lbs. MF-717WX 10.00 Down Net 441.50

Same as MF-716WX, but with the addition of 2 Lafayette Highboy speaker enclosures. Choice of CAB-19 in Mahogany or Blonde and CAB-21 in Walnut (Please Specify). Shpg. wt., 271 lbs. Dimensions 20"W x 23"H x 16"D. MF-715WX 10.00 Down Net 529.50



NEW!

The OUTSTANDING "Stereo 250" KIT

LAFAYETTE'S 50 WATT STEREO AMPLIFIER


For Those Who Want, and Expect, the Finest!

- ✓ DELUXE FEATURES YOU'LL FIND IN UNITS COSTING 189.50
- ✓ UNSURPASSED PERFORMANCE FOR SUPERLATIVE STEREO
- ✓ ADVANCED AUDIO CIRCUITRY
- ✓ TREMENDOUS RESERVE POWER



Model KT-250

IN
EASY-TO-BUILD
KIT FORM
64.50
ONLY 5.00 DOWN



50 WATT INTEGRATED STEREO AMPLIFIER

- Two 25 Watt Channels, 50 Watt Monophonic Output
- Response 17 to 21,000 cycles
- Third Channel Output
- New 6CW5/EL86 Output tubes
- Full Range of Controls and Inputs
- New Distinctive Styling
- Individual Bias and Balance Adjustments

The new Lafayette KT-250 offers remarkable versatility, high quality of reproduction and new distinctive styling in one convenient low-cost unit — another example of Lafayette's constant effort to provide the audio enthusiast and music lover with audio components that represent the finest quality value in their class.

Designed and engineered for ease of assembly, the KT-250 is a fine stereo preamplifier and 50 watt stereo amplifier combined — with all the controls and features to enable you to enjoy the utmost in listening pleasure in any situation. Whether you use it as a stereo amplifier delivering 25 watts per channel or as a powerful 50 watt monophonic amplifier, you are assured of true high fidelity reproduction — free from hum, noise and distortion. Check the features below — see why the KT-250 is worthy of a place in your stereo music system.

DELUXE FEATURES

Unique Separation Control—A new stereo control which provides continuously variable channel separation—from full monophonic to full stereo. Lets you select the amount of separation you want.

Clutch-Operated Volume Balance Control—Gives you a choice of independent or simultaneous control of both channels—you can use it as a master volume control without disturbing previously selected settings on each channel.

4 Independent Tone Controls—Independent Bass and Treble adjustment for each channel. Concentric mounting for convenience—inner knob controls one channel, outer the other channel.

Mode Switching—Two slide switches provide Normal Stereo—Reverse Channel—Mon A (Channel A reproduced through both channels)—Mon B (Channel B reproduced through both channels).

Input Selector—4-position switch lets you select instantly any one of your connected monophonic or stereo sources—special non-shortening arrangement on one position permits recording and playback using a permanently connected tape recorder.

Loudness Switch—Provides the frequency response changes required by the ear at low listening levels and permits the Volume-Balance control to function as a compensated loudness control.

Phase Switch—Reverses the phase of one channel electrically—corrects for speakers connected out of phase or for reversed phase recordings sometimes found commercially.

3 Pairs of High Level Inputs—For connection of Crystal or Ceramic phono, Tuner, and auxiliary equipment.

2 Pairs of Low Level Inputs—For connection of magnetic phono and Tape Head.

Main Speaker Outputs—Dual 4, 8 and 16 ohm terminals may be paralleled for 4 or 8 ohm operation at 50 watts.

Tape Output—Provides an output for Tape recording—unaffected by Volume and Tone Controls.

Bridged Output—A monophonic blend of both channels which can be fed to a third single channel power amplifier and speaker for a greater sound spread in stereo. May also be used for listening in another room.

ADVANCED AUDIO CIRCUITRY INCLUDES:

- DC applied to all preamplifier and tone control tube heaters for hum-free operation
- RIAA equalization on phono inputs
- MARTB tape equalization on tape head inputs
- Individual bias and balance controls
- Hum balance Control
- Excellent OC power supply regulation provided by silicon diodes
- Total of 9 tubes, plus 3 silicon diodes—uses premium 6CW5/EL86 output tubes.

SPECIFICATIONS

CONTROLS: Total of 12 individual controls (3 dual concentric and 6 single); **SELECTOR SWITCH:** 4 position—Phono-Aux-Tuner-Tape Head. **SEPARATION CONTROL:** Continuously variable with power on-off switch. **BASS CONTROL:** Dual concentric, 14 db boost or cut at 50 cps. **TREBLE CONTROL:** Dual concentric, 14 db boost or cut at 10 Kc. **VOLUME-BALANCE CONTROL:** Dual concentric, clutch-Operated for independent or simultaneous level control of both channels. **MODE SWITCHES:** 2 slide switches, provide Normal Stereo—Reverse Channel—Mon A—Mon B. **LOUDNESS SWITCH:** On-Off. Provides loudness contour compensation for volume control. **PHASE SWITCH:** Provides electronic phase reversal.

POWER OUTPUT: 50 watts-25 watts per channel. Institute of High Fidelity Manufacturers Rating (100 watts peak).

FREQUENCY RESPONSE: 17-21,000 cps ± 1 db (at normal listening level). **DISTORTION:** Harmonic, less than 0.25% at normal listening level; IM, less than 1%. **HUM AND NOISE:** (At full volume) High Level—74 db below rated output. Low Level—54 db below rated output. **CHANNEL SEPARATION:** Better than 50 db. **SPEAKER OUTPUT IMPEDANCE:** Dual 4, 8 and 16 ohms. **AUXILIARY OUTLET:** 1, switched. **TUBE COMPLEMENT:** 4-6CW5/EL86, 2-7199, 3-12AX7, 3 silicon diodes. Attractive beige vinyl laminated steel cabinet. Handsomely designed brass anodized aluminum front panel. Sienna brown molded legs, matching knobs with polished brass inserts. 14 1/2" w x 12 3/4" d x 5 1/2" h (with legs and knobs). Shpg. wt., 26 lbs.

MODEL KT-250WX—50 Watt Integrated Stereo Amplifier Kit, complete with deluxe cabinet and legs, all necessary parts and detailed assembly manual 5.00 Down Net 64.50

NO TECHNICAL SKILL REQUIRED

Designed for ease of construction, the KT-250 can be assembled in a minimum of time. Assembly manual contains detailed step-by-step instructions ... guides you every step of the way. Large full-scale pictorials show you where every wire and component goes — eliminate any chance of error or confusion. You build an amplifier comparable in every way to a factory-wired unit — and save real money too!

TOP QUALITY STEREO-PHONO SYSTEM With the Outstanding "Stereo 250" Kit

LAFAYETTE SYSTEM PRICE 212.50




Lafayette KT-250



Glaser-Steers GS-77



New GE VR-22 (.7 Mil) Stereo Cartridge With Diamond Stylus



2-Lafayette Elioatflex Series Bookshelf Enclosures



2-Lafayette-Goodmans SK-110WX

COMPONENTS


- Lafayette KT-250 50 Watt Integrated Stereo Amplifier Kit
- Glaser-Steers GS-77 4 Speed Stereo Record Changer (Less Base)
- New GE VR-22 (.7 MIL) Stereo Cartridge with Diamond Stylus
- 2-Lafayette-Goodmans SK-110WX 12" 3-Way Speakers with 1 1/4 lb. Magnets.

Enjoy the latest stereo records with superb high fidelity system. Truly breathtaking sound reproduced realistically in your home. And you enjoy tremendous savings by buying these components as a system and assembling the amplifier. You can also add, at any later date, a stereo tape deck and/or stereo FM/AM tuner to complete your music center. The new Lafayette KT-250 50 watt integrated stereo amplifier kit offers 25 watts per stereo channel, or 50 watts if used monophonically. Advanced features such as separate bass and treble controls for each channel and concentric clutch-operated control for individual or simultaneous level adjustment are incorporated. Full flexibility and smart styling keynote this new integrated stereo amplifier. The Glaser-Steers GS-77 stereo changer is featured because of its proven quality. The new GE VR-22 stereo cartridge with diamond stylus provides low tracking force and wide frequency range. The speakers for this outstanding system are the widely acclaimed Lafayette-Goodmans SK-110WX 12" 3-way speakers with 1 1/4 lb. magnets.

System supplied with all interconnecting cables and simplified instructions for easy assembly.

Complete stereo system as described above. Shpg. wt., 79 lbs.

HF-692WX	10.00 Down	Net 212.50
PK-350W Model GSB Woodbase for GS-77	Shpg. wt., 5 lbs.	Net 9.60
Some as HF-692WX, plus choice of either 2 Lafayette Elioatflex Series Bookshelf Enclosures or 2 Lafayette CAB-16WX Series Resonator Enclosures (specify enclosure and finish).	Shpg. wt., 150 lbs.	
HF-708WX	10.00 Down	Net 270.00
Some as HF-692WX, but with 2 Lafayette-Goodmans SK-115WX 15" speakers with 6 1/2 lb. magnets instead of Lafayette-Goodmans SK-110WX speakers.	Shpg. wt., 119 lbs.	
HF-693WX	10.00 Down	Net 287.50
Some as HF-693WX, plus 2 Lafayette CAB-19WX Series Universal Bass Reflex Enclosures (specify finish).	Shpg. wt., 227 lbs.	
HF-709WX	10.00 Down	Net 377.50



LAFAYETTE STEREO KITS

and ACCLAIMED by ENGINEERS, MAGAZINES,

Lafayette . . . STEREO TUNER KIT



KT-500

**THIS LAFAYETTE STEREO-TUNER IS
UNIQUE AND INCOMPARABLE**


- Use it as a Stereophonic FM-AM Tuner
- Use it as separate Monaural FM & AM Tuners
- Use it as straight Monaural FM or AM Tuner

THIS STEREO-TUNER IS YEARS AHEAD



**KT-500
74.50
IN KIT FORM**

**LT-50
124.50
COMPLETELY WIRED
AND TESTED**

**ONLY \$5.00 DOWN
• THE MOST FLEXIBLE TUNER
EVER DESIGNED!**



Use it as a Stereophonic FM-AM Tuner



Use it as simultaneous Monaural FM & AM Tuners

Use it as separate Monaural FM or AM Tuner

More than a year of research, planning and engineering went into the making of the Lafayette Stereophonic Tuner. Designed against obscurity, it incorporates every practical and worthwhile feature that is considered necessary for your complete satisfaction of all present and future types of broadcasting. Already, breathtaking stereophonic programs are being transmitted via FM and AM. It will certainly become more and more the popular method of high fidelity broadcasting. The tuner also provides an output for multiplex FM stereophonic reception, enabling you to enjoy the ultimate in high-fidelity sound reproduction. Since the FM and AM sections are completely independent of each other, this tuner can be used furthermore as a dual-monaural tuner. In this way, the music lovers are able to listen to concert programs on the FM channel in one room, while the younger-set can listen to a different program on AM in another room. In addition, on a monaural program which is broadcasted simultaneously via FM and AM, this tuner will enable you to tune in both channels and reproduce them through individual amplifier-speaker systems. The improvement of quality will be immediately noticeable because the sound source is now distributed and at the same time, the hole-in-the-wall point source effect is completely eliminated. Of course, the unit can also be used as an ordinary type of FM-AM tuner, providing you with unsurpassed quality of reception.

Apart from its unique flexibility, this is, before all else, a superior high-fidelity tuner, employing many features found only in the highest priced units. An inspection of the tubes and parts used will reveal that this tuner is engineered without compromise of any kind. With the Lafayette Stereo-Tuner you are assured of noise-free, drift-free, distortion-free performance. You will not only hear this quality, but also sense it even in the mechanical details; in the "feel" on the velvet-smooth easy flywheel tuning, in the professional appearance of the tastefully selected colors that will blend with any decor. The just-right shade of gold-brass escutcheon contrasts just enough with the dark maroon background, and is set off by matching maroon knobs with gold inserts. The design of the cabinet has the simplicity of modern styling, touched by a stroke of traditional elegance. Carefully designed for easy installation in console if desired. Deluxe features include separate FM and AM sections, each tuned with its own 3-gang tuning capacitor, and each has its individual low impedance cathode follower output. This means that long output cables can be used to connect tuner to amplifier or control center without fear of high frequency loss. Also, separate volume controls are provided for each channel so that, when used for stereophonic reception, a proper balance between channels can be achieved. Without this important feature, the wonderful realism of stereophonic sound would be destroyed. Convenient front panel switch changes from stereo to monaural use. Simplified accurate knife-edge tuning is provided by magic eye which operates independently on FM and AM. Automatic frequency control "locks in" FM signal permanently. Ferrite rod antenna with loading ring is supplied to bring in weak AM stations for quality reproduction. Designed for easy assembly, the kit is built around two printed circuit boards and prealigned IF's, making construction and wiring simple, even for such a complex unit.

THE MOST FLEXIBLE TUNER EVER DESIGNED!

- MULTIPLEX OUTPUT FOR NEW STEREO FM
- TWO PRINTED CIRCUIT BOARDS AND IF'S PREALIGNED
- FM AFC AND AFC DEFEAT
- 17 TUBE PERFORMANCE — 11 Tubes (4 dual-purpose) + Tuning Eye & Selenium Rectifier
- ARMSTRONG CIRCUIT WITH DUAL LIMITERS AND FOSTER-SEELEY DISCRIMINATOR
- 12 TUNED CIRCUITS AND DUAL CATHODE FOLLOWER OUTPUTS
- EXTREME SENSITIVITY AND WIDE FREQUENCY RESPONSE

SPECIFICATIONS: RANGE: FM 88-108MC, AM 530-1650KC. FM CIRCUIT: Armstrong, low noise front end with triode grounded grid amplifier and triode mixer. Double tuned dual limiters, Foster-Seeley discriminator, AFC and AFC defeat. AM CIRCUIT: Superhet with 3 stages AVC, 10kc whistle filter, ferrite antenna. **DISTORTION:** Under 1% harmonic on FM; under 1% on AM for up to 80% modulation. **HUM LEVEL:** 60 db below 100% modulation. **SENSITIVITY:** FM—full limiting on signals as low as 1 μ v, 2 μ v for 30 db quieting; AM Terminal Sensitivity 5 μ v. **SELECTIVITY:** FM 200kc bandwidth; 6 db down, AM 8kc BW; 6 db down. **FREQUENCY RESPONSE:** FM 20-20,000 cps \pm 1/2 db, AM 20-5,000 \pm 3 db. **FM DRIFT:** \pm 5kc Maximum. **IMAGE REJECTION:** FM 40 db; AM 30 db. **I.F. REJECTION:** FM 70 db, AM 50 db. **RADIATION:** MEETS FCC REQUIREMENTS. **OUTPUT LEVEL:** FM 2 1/2V for 100% modulation, 1V for 30%; AM average 1V. **CONTROLS:** 5 controls; FM VOL, AM VOL, FM Tuning, AM Tuning, and five position function selector switch. **TUBES:** 3-6BA6, 2-6AU6, 1 each 6BK7B, ECC85, 6AL5, 6BE6, 12AU7 and 6U5 tuning eye. Selenium rectifier. **OUTPUT IMPEDANCE:** Low impedances cathode follower. Output jacks for FM, AM or Stereo. **ANTENNA INPUT:** 300 ohms. Size, 13 3/4" W x 10 1/2" D x 4 1/2" H. Shpg. wt., 18 lbs. Kit comes complete with all parts and metal cover, a step-by-step instruction manual, schematic and pictorial diagrams.

MODEL KT-500WX Stereo Tuner Kit 5.00 Down Net 74.50
LT-50WX Same as above, completely factory wired and tested 5.00 Down Net 124.50

COMMENTS of the TECHNICAL and PROFESSIONAL CRITICS!

hi-fi music

AT HOME

"The assurance of success lies in the excellent design of this tuner, the thoughtful manner in which it was planned for assembly from a kit of parts, the use of RF and IF printed-circuit boards in the FM sections, and the very complete illustrations and instructions. You will have reason to be proud and pleased with the results."

July-Aug. 1958

Radio-Electronics

TELEVISION - SERVICING - HIGH FIDELITY

"The KT-500 tuner has a number of interesting construction and design features not usually found in moderately priced tuner construction kits."

Oct., 1958

audiocraft

for the HI-FI hobbyist

"... low distortion on the FM channel and excellent sensitivity of the tuner as a whole combines with simplicity of construction to make the KT-500 a pleasure to build and use."

July, 1958

CONSUMERS' REMARKS concerning the KT-500

"Instructions good . . . the kit's tops.
Dominic Grande
Cambridge, Mass.

"This kit was a well engineered model and your instructions made it easy to construct."
Edwin Lambert, Jr.
Quincy, Mass.

"Worked fine!"

John Ricketts
Honolulu, Hawaii

"Instructions and diagrams were very good. AM is tremendous, very good tuner."

F. Hathaway
Pompey, New York

"... this kit is excellent all the way around. It would be difficult to improve upon."

Robert Meier
Washington, D.C.

"Instructions were very good. Performance is wonderful. Best all around design..."

S. B. Heberlig
Glendora, New Jersey

"I thoroughly enjoyed building this kit. It proved to be worthy of all my expectations. I am very pleased with its performance. Keep up the good work!"

John Kinney
Santa Monica, Calif.

"I am enjoying my KT-500 more and more each day. It works beautifully and meets, if not exceeds, all your specifications. A friend of mine, after seeing and hearing my KT-500, has decided to order one for his Hi-Fi unit. It didn't take much convincing on my part, the KT-500 spoke for itself."

Charles Bell St. Louis, Mo.

TRIED, TESTED, APPROVED

STEREOPHILES, and KIT-BUILDERS




Lafayette PROFESSIONAL

STEREO PRE-AMPLIFIER MASTER CONTROL CENTER

KT-600

THE LAFAYETTE KT-600 SOLVES EVERY STEREO/MONAUROUS CONTROL PROBLEM

With All The Versatility Of A Broadcast Studio Control Console



Patents applied for on Bridge and Null Balance circuitry.

MODEL KT-600
IN EASY-TO-BUILD KIT FORM
79.50
\$5.00 DOWN

LA-600
COMPLETELY WIRED AND TESTED
134.50
\$5.00 DOWN

- A GIANT FORWARD STEP IN PREAMPLIFIER DESIGN!
- UNIQUE STEREO & MONAUROUS CONTROL CENTER FACILITIES & OUTSTANDING PERFORMANCE SUPERIORITY!
- WITH AMAZING NEW BRIDGE CIRCUITRY & CONTROL FOR VARIABLE 3d-CHANNEL OUTPUT FOR 3-SPEAKER STEREO SYSTEMS!
- VARIABLE CROSS-CHANNEL SIGNAL FEED FOR ELIMINATION OF "HOLE-IN-THE-MIDDLE" EFFECTS WITH STANDARD 2-SPEAKER STEREO!
- HIGHLY PRECISE "NULL" BALANCING & CALIBRATING SYSTEM PROVIDES MORE ACCURATE STEREO BALANCE THAN METERS!

PERFORMANCE SPECIFICATIONS FOR SUPER-STEREO

- RESPONSE 5-40,000 CPS \pm 1 DB
- TAPE HEAD PLAYBACK EQUALIZATION FOR NEW 4-TRACK STEREO
- LOW LEVEL SENSITIVITY 2.2 MILLIVOLTS FOR 1 VOLT OUT
- HIGH LEVEL SENSITIVITY 94 MILLIVOLTS FOR 1 VOLT
- SWITCHED 12 DB/OCTAVE RUMBLE & SCRATCH FILTERS
- LESS THAN .03% IM DISTORTION
- DUAL TAPE MONITOR JACKS & SWITCH FOR RECORD & PLAYBACK
- DUAL INPUTS FOR STEREO/MONAUROUS CERAMIC, CRYSTAL OR CAPACITIVE PICKUPS WITH FULL USE OF EQUALIZATION SELECTORS
- SIGNAL-TO-NOISE BETTER THAN -80 DB AT HIGH LEVEL & -62 DB AT LOW LEVEL INPUTS FOR 2 VOLTS OUT
- "PRESENCE" SWITCH SOLO PROJECTION
- BASIC CONTROLS ALL CONCENTRIC
- "PLATE FOLLOWER" OUTPUTS FOR LOW IMPEDANCE WITH LOWEST DISTORTION
- 7-TYPE 7025 LOW-NOISE DUAL TRIODES
- 4-AUXILIARY AC OUTLETS

The KT-600 represents one of the most brilliant audio achievements since the advent of stereo. This "no compromise" stereo preamplifier and control unit offers unlimited versatility... includes every feature necessary for the very finest reproduction — truly a masterpiece of audio design. Already in use professionally, the LA-600 has been overwhelmingly acclaimed by those who own it as the finest stereo preamplifier available — at any price! It has a total of 12 input jacks (6 stereo pairs) for program sources of any type and any level — all of which may be selected by a front panel control. Separate Turnover and Roll-Off switches provide 24 positions of correct equalization — independently adjustable on each channel. A dual concentric Stereo Function selector provides extreme flexibility in the control of your selected program sources — there is practically no mode of operation which cannot be provided by these two switches. A unique Bridge Control provides continuously variable channel separation from full monaural to full stereo, or it can optionally be used to regulate the 3rd channel output. A clutch-operated Volume Balance control pro-

vides independent or simultaneous level adjustment of channels. Additionally, this control may be used to balance channels by means of an audible "null" — far more accurate than meters! Low impedance cathode follower outputs are provided for connection to two basic amplifiers (or stereo amplifier) and in addition to the 3rd channel output, there are two tape output jacks for recording purposes. Other features include: 4 dual concentric input level controls, Presence Rise switch, Individual Bass and Treble controls for each channel; Rumble Filter; Scratch Filter; Loudness switch; Tape Play-Monitor switch.

Tape Head inputs 1.8 mv for 1 volt out. HUM AND NOISE: High level inputs better than 80 db below 2.0 volts; low level inputs better than 62 db below 2.0 volts. INPUT IMPEDANCES: High level—250K ohms; Mag—96K ohms; Ceramic—96K ohms in series with 48 μ mf; Tape Head—470K ohms. OUTPUT IMPEDANCES: Main Outputs—1500 ohms; Tape Outputs—2700 ohms; Bridged Output—1100 ohms. TONE CONTROL RANGE: Bass \pm 15 db at 30 cps; Treble \pm 15 db at 10 Kc. RUMBLE FILTER: 12 db octave slope, down 15 db at 30 cps. SCRATCH FILTER: 12 db octave slope, down 15 db at 15 Kc. CROSSTALK: Greater than 55 db separation between channels. AUXILIARY AC OUTLETS: 4, 1 unswitched. TUBES: 7-7025, 2-Selenium Rectifiers. POWER REQUIREMENTS: 35 Watts, 105-125 volts AC, 50/60 cycles. SIZE: 14" W x 4-13/16" H x 11 1/2" D, not including projections. Shpg. wt., 16 lbs.

SPECIFICATIONS

FREQUENCY RESPONSE: 5-40,000 cps \pm db. DISTORTION: Less than 0.05% 1M at 2 volts out; Less than 0.1% Harmonic, nt 2 volts out. SENSITIVITY: Low level 2.2 mv for 1 volt out; high level 94 mv for 1 volt out;

Stereo Preamplifier Kit		
KT-600 WX	5.00 Down	Net 79.50
Stereo Preamplifier, wired and tested		
LA-600 WX	5.00 Down	Net 134.50

COMMENTS of the TECHNICAL and PROFESSIONAL CRITICS!



"The Lafayette KT-600 is unquestionably one of the most flexible stereo control units available today. Its flexibility is complemented by overall performance comparable to manufactured units selling for far more than its modest price."
 Oct., 1959



"This is a skillfully engineered unit incorporating almost every mono and stereo function of value that has yet appeared."
 May, 1959



"... so complete and detailed, there's little chance of making a mistake in putting the unit together."
 Nov., 1959



"It incorporates just about all the features one could hope to find on a single chassis."
 May, 1959

CONSUMERS' REMARKS concerning the KT-600

"As an Electrical Engineer by profession, my sincere admiration goes to the engineers who performed the background work in developing the layout and assembly instructions for this kit assemble."
 H. C. Pendergast
 Boise, Idaho

"The KT-600 is the most remarkable electronic instrument I have ever seen..."
 Howard Kindig
 Akron, Ohio

"I wish to commend the staff who designed this kit. I think it is one of the best planned, best organized kits I have ever seen."
 Robert Fitz
 Columbus, Ohio

"... one of the finest stereo preamps available... I congratulate you on the fine achievement..."
 Bill Mitchell
 Santa Rosa, Calif.

"... the instructions were terrific! I am convinced that Lafayette has the best..."
 Peter Leyden
 Brooklyn, New York

"Everything excellent!!"
 Carl Jensen
 Randolph, Mass.

"The KT-600 is simply wonderful."
 Felipe Reyes
 New York, New York

"It was a real pleasure putting the KT-600 together. Your etched circuit board set-up is finest I have seen."
 I. E. Ricketts
 Glendale, Calif.

Lafayette POPULAR TRANSISTOR KITS

New 6 TRANSISTOR SUPERHET RECEIVER


WITH LATEST NPN-PNP TRANSISTORS

- GE 2N188A AUDIO OUTPUT TRANSISTORS
- 100% SUBMINIATURE PARTS — NO COMPROMISES!
- LABORATORY DESIGNED — SENSITIVE, SELECTIVE, STABLE!
- CLASS B PUSH-PULL AMPLIFICATION — PLENTY OF POWER.
- FOR GROUP AND PRIVATE LISTENING
- NEW 28 PAGE INSTRUCTION MANUAL

Superb Performance! Incomparable Value!

FOR GROUP AND PRIVATE LISTENING

Transistor-wise Lafayette proudly presents its newly revised 6 Transistor Superhet Receiver Kit KT-119A. This improved model uses the latest GE NPN-PNP Transistors in an ingeniously engineered, laboratory tested circuit providing superb performance and an amazing superior commercial quality. The circuit features a specially matched set of 3 IF transformers, Oscillator Coil, High-Q Loop, Class B Push-Pull Audio Amplification and optimum Transformer Coupling in audio and output stages. Has efficient 2 1/2" speaker for exemplary reproduction and earphone jack for private listening. Complete with all parts, transistors, pre-punched chassis, but less battery and leather case. New 28 page easy-to-follow step-by-step instruction book. Size 6 x 3 1/2 x 1 1/2". Shpg. wt., 3 lbs.




26.50 LESS CASE AND BATTERY

- KT-119A — Complete Kit—Less Case and Battery.....Net 26.50
 BA-180 Battery 9 V Burgess 2N6.....Net 1.30
 MS-339A — Sturdy attractive brown leather case with carrying strap for KT-119A. 6 x 3 1/2 x 1 1/2". Shpg. wt., 1 lb.....Net 2.95
 MS-391 — Sensitive matching earphone.....Net .79

5 TRANSISTOR AUDIO AMPLIFIER KIT KT-104

13.95

- CLASS "B" Push-Pull
- Bass and Treble Controls with Preamplifier for Cartridge and Microphone Input
- Excellent as second amplifier



for stereo phono conversion

An advanced 5-transistor audio amplifier with a well-designed pre-amplifier stage. Has more than enough volume for average sized room. 3 inputs: Crystal, ceramic and most hi-output magnetic phono cartridges, AM, FM and Transistor Radio Tuners; most magnetic microphones, and crystal microphones when used with a matching input transformer. Employs circuitry for minimum distortion. Has Bass and Treble controls for more enjoyable listening. Transformer coupled in driver and class "B" push-pull output stages, for clean output and optimum performance. Complete with all parts, pre-punched chassis, attractive front panel, knobs, and easy-to-follow step-by-step instructions. 5 1/2" x 4" x 1". Shpg. wt., 3 lbs.

- KT-104 For 3.2 ohm speaker, less battery.....Net 13.95
 KT-105 for 8 ohm speaker, less battery.....Net 13.95
 BATTERY FOR ABOVE
 BA-180 BURG. 2N6 or eq. 9 v. Shpg. wt., 5 oz.....Net 1.30

3 TRANSISTOR SUPER-HET POCKET RADIO KIT KT-116

• CONVERTER, 2 IF STAGES, DIODE AND AUDIO OUTPUT DESIGNER'S DREAM IN A TRUE POCKET SUPERHET RECEIVER! NO EXTERNAL ANTENNA! NO EXTERNAL GROUND!

A highly sensitive, super-selective true pocket superhet receiver that will surprise you with its performance over the complete broadcast band. Just place it in your shirt pocket, place the earphone to your ear, and you're in for a treat! Best of all! No pesky external antenna and ground leads to worry about! The circuit uses 2 high frequency converter and IF Transistors, 2 specially matched IF transformers for maximum power transfer, an efficient crystal diode for detection and a dependable Audio Transistor in a single-ended audio output stage. The components are housed in an attractive professional-looking plastic case. Comes complete with ON-OFF knob and stylish station dial that adds considerable class to the receiver's appearance. Complete with all parts, transistors, case, dial and easy-to-follow step-by-step instructions. Less Battery 4 1/2" x 2 3/4" x 1-1/16". Shpg. wt., 1 lb.

- KT-116 — Complete Kit—Less Battery.....Net 13.95
 MS-260 — Super power dynamic Earphone.....Net 2.95
 or MS-368 — SENSITIVE ECONOMY DYNAMIC EARPHONE.....Net 1.44
 BA-400 Battery 9 V. RCA VS309A.....Net 1.53



13.95

1 AND 2 TRANSISTOR POCKET RADIO KITS

ONE TRANSISTOR POCKET RADIO KIT — KT-97

An ideal, neat and low-cost transistor pocket radio kit for students, hobbyists and experimenters interested in a practical and basic knowledge of transistor circuits. Employs the new tapped variable Ferris-Loop and a specially designed miniaturized 365 uF variable capacitor for super selective tuning. Includes a Crystal Diode detector and a reliable transistor in a grounded emitter amplifier stage for maximum output. Will give good reception up to 50 mile radius with approx. 50 ft. antenna and a good ground. Complete with transistor, crystal diode, plastic case, variable capacitor, tapped Ferris-Loop, resistor, cap adjuster, a neat pre-punched metal chassis that makes advancement to the 2 Transistor Kit easy-as-pie. With simple, detailed How-To-Do-It Instructions. Size: 3 3/4" x 2 1/2" x 1". Shpg. wt., 1 lb.

- KT-97 — Complete Kit (less earphone and less battery).....Net 3.95
 BA-154 Battery 1 1/2 V. BURGESS #7.....Net .10

TWO TRANSISTOR POCKET RADIO KIT — KT-98

The 1 Transistor Pocket Radio Kit plus an additional resistance coupled transistor stage for increased sensitivity and greater output. Can receive even the weaker stations with an approx. 50 ft. antenna and ground. Includes all the KT-97 parts plus one transistor, 2 resistors, one capacitor and transistor socket. Complete with simple, detailed instructions. Size: 3 3/4" x 2 1/2" x 1-3/16". Shpg. wt., 1 lb.

- KT-98 — Complete 2 Transistor Kit (less earphone and less battery).....Net 4.95
 MS-111 Crystal Earphone for KT-97 and KT-98.....Net .89
 BA-154 Battery 1 1/2 V. BURGESS #7.....Net .10




KT-97

TRANSISTOR CODE PRACTICE PRACTICE OSCILLATOR KIT

COMPLETE WITH TELEGRAPH KEY & TRANSISTOR

2.99



For those interested in mastering the international code, an audio tone oscillator is essential. The circuit of this transistorized feedback oscillator has the simplicity of the neon glow, the signal strength of the vacuum tube, and requires only two penlite cells for weeks of service. It may be used for solo practice, or two may send and receive with the same unit. Kit comes complete with Transistor, Telegraph Key, Resistor, Condenser, Masonite Board, etc., and Schematic Diagram. Net 1.18
 KT-72 LESS BATTERY.....Net 1.18
 ME-33 Cannon AM-15-1 Single headset.....Net 1.18
 BA-154 Battery Burg. #7 or eq. (2 required) wt., ea. 1/2 oz.....Net .10

4 TRANSISTOR TELEPHONE PICK-UP AMPLIFIER KIT

- FOR FAMILY AND BUSINESS GROUP LISTENING
- HI-GAIN AMPLIFIER FOR PHONO AND MIKE

17.95




Lafayette's new Super-Sensitive 4 Transistor Telephone Pick-up Amplifier with class "B" push-pull output for efficient speaker operation. Permits the whole family to enjoy phone conversations. Invaluable on long distance calls, as well as for group listening on business calls and conferences. No need for extension phones! Just place the pickup coil under the telephone cradle base, or in case of metallic base, near phone receiver and you'll marvel at how loudly and clearly the two-way conversation comes through the speaker. Uses transformer coupling for optimum performance. The kit comes complete with all parts including 4 transistors, 3 transistor audio transformers, speaker, volume control, an attractive ripple-finish metallic cabinet, a pre-cut metallic chassis that makes mounting and wiring of parts a "snap", wire and solder, less battery and pickup coil. Includes easy-to-follow illustrated instructions. Size 4 1/2" H x 4 1/4" W x 4 1/4" D. Shpg. wt., 3 lbs.

- KT-131 Complete Kit Less Battery & Pickup Coil.....Net 17.95
 BA-180 Battery 9 v. Burg. 2N6 or eq. wt., 5 oz.....Net 1.30
 MS-16 Telephone Pickup Coil Shpg. wt., 4 oz.....Net 1.95

3 TRANSISTOR HI-FI PREAMPLIFIER KIT With Volume, Bass and Treble Controls

16.95



Lafayette 3 Transistor Hi-Fi Preamplifier Kit KT-117 provides the voltage gain necessary for the operation of even the lowest level magnetic cartridges and microphones. It may be used with Hi-Fi equipment to provide stable, low noise preamplification with extremely low power consumption, zero hum and without any microphonics inherent in vacuum tube preamplifiers. It is ideal as a remote preamplifier since it is battery operated and can be connected by cable up to 175 ft. from associated equipment. It has its own Bass and Treble controls for improved quality of reproduction, and uses 3 quality audio transistors. Frequency Response is 20 to 20,000 cycles. 40 db maximum gain. Zero hum level; Noise level—approx. 48 db below 10 millivolts input for high impedance cartridge, better than 52 db below 2 millivolts for low impedance cartridges. Four inputs: Three phono inputs—high output cartridges, high impedance variable reluctance cartridges and low impedance law output cartridges; Microphone Input. From 0.5 to 1 volt output; Controls—Phono—Microphone, Hi-Low Level, Power-Volume, Bass and Treble. Complete with all parts, transistors, pre-punched chassis, and detailed step-by-step instructions. 1/2" x 3 3/4" x 1 1/2".

- KT-117—Complete Kit Less Battery.....Net 16.95
 BA-178 Battery 9V BURGESS 2U6.....Net .95


LAFAYETTE 10-IN-1 LAB KIT

• EDUCATIONAL • PRACTICAL

You Build:

1. RADIO RECEIVER
2. PHONO-MICROPHONE AMPLIFIER
3. PHONO OSCILLATOR
4. BROADCAST STATION
5. CODE PRACTICE OSCILLATOR
6. SIGNAL TRACER
7. CAPACITY OPERATED RELAY
8. ELECTRONIC TIMER
9. ELECTRONIC SWITCH
10. PHOTOCELL RELAY

12.95




Here is a new laboratory tested experimenters kit designed to provide maximum instruction and entertainment and which is ideal for both the beginner and advanced experimenter. Features practical and interesting circuits which enable you to do many novel and interesting things while learning how these circuits function. You can broadcast your voice or play a phonograph through your radio from anywhere in the house, send code through a head-phone or radio, or use light or body capacitance to activate electrical circuits. Safe, low voltage is utilized. Kit is complete with perforated mounting board, 3 vacuum tubes, microphone and all parts necessary for construction. A detailed 12 page instruction manual contains simple-to-follow pictorial and schematic diagrams for each project. Less headphone, photoelectric cell and socket, wire and solder. Shpg. wt., 5 lbs.

- KT-36A.....Net 12.95
 PHOTOELECTRIC CELL TYPE 848 TUBE Shpg. wt., 8 oz.....3.75
 AMPHENOL 77MIP4 SOCKET FOR ABOVE Shpg. wt., 1 oz......08
 ME-33 CANNON AM-15-1 1000 OHM SINGLE HEADPHONE Shpg. wt., 1 lb.....1.18

NEW! "SUNFLEX" 2 TRANSISTOR REFLEX RADIO RECEIVER KIT

- FOR SOLAR OR FLASHLIGHT BATTERY OPERATION
- NPN-PNP COMPLEMENTARY SYMMETRY CIRCUIT SUPER-REFLEXED FOR 3 TRANSISTOR PERFORMANCE
- BUILT-IN "HI-Q" FERRITE ANTENNA

An efficient and economical miniature receiver kit for earphone operation. Uses one NPN transistor and one PNP transistor and a crystal diode in an ingenious reflexed complementary symmetry circuit for 3 transistor performance. Gives surprisingly good reception of local stations in most locations without external antenna or ground connections. Antenna plug-in lead supplied for reception of distant stations. Current drain is less than 1 millamp. Operates on 2 inexpensive penlight flashlight batteries (3 volts) or will give new lifetime performance in sunlight or under artificial light with use of amazing new silicon solar battery (not supplied). Ideal for the beach, ball games and other outdoor uses as well as for indoors. Complete with all parts, transistors, diode, perforated chassis, two-tone plastic case, wire, solder and easy to follow instructions. Size 4 1/4" x 3-5/8" x 1-5/8". Shpg. wt., 1 lb. KT-132—KIT (less earphone).....Net 11.95
 MS-260 — Super power dynamic earphone? Shpg. wt., 3 oz.....Net 2.95
 MS-420 Solar battery wt. 2 oz.....Net 2.95
 BA-155 Penlight cells (2) wt., ea. 1 oz.....Net .75



MIGHTY SUBMINIATURE "HELIODYNE" SOLAR SILICON BATTERY


- LATEST, MOST EFFICIENT TYPE OF SUN BATTERY
- USED BY ARMED SERVICES TO POWER ELECTRONIC EQUIPMENT

The most efficient type of solar battery yet developed to generate electrical energy from sunlight or from light rays from other sources. Rated 3.2 volts at 2 milliamperes. Ideal for operating Lafayette "Sunflex" Radio Receiver Kit or any other receiver drawing up to 2 ma at 3 volts. 1-1/16" L x 3/32" W. Shpg. wt., 2 oz.



7.75

- MS-420—"HELIODYNE" SILICON SOLAR BATTERY.....Net 7.75



BUILD YOUR OWN!

LAFAYETTE Quality KITS

NEW! LAFAYETTE 15-IN-1 TRANSISTOR EXPERIMENTERS KIT

A TRULY REMARKABLE VALUE

Practical-Educational-Entertaining
EXCITING PROJECTS BUILD ALL OF THESE



14.95

- ELECTRONIC TIMER
- BURGLAR ALARM
- 2-STAGE AUDIO AMPLIFIER
- PHOTO-ELECTRIC RELAY
- CODE PRACTICE OSCILLATOR
- AUDIO PREAMPLIFIER
- ELECTRONIC FLASHER
- TV COMMERCIAL KILLER
- RAIN ALARM
- SIGNAL INJECTOR
- INTERCOM
- 2-STAGE BROADCAST RECEIVER
- WIRELESS BROADCASTER
- WIRELESS CODE TRANSMITTER
- REGENERATIVE RADIO RECEIVER

ASSEMBLE THE BASIC COMPONENTS — THEN WIRE EACH CLEARLY EXPLAINED CIRCUIT BY SIMPLY CONNECTING THE PROPER LEADS.

AN IDEAL LABORATORY KIT WHICH HELPS TEACH YOU HOW TRANSISTORS WORK IN A PRACTICAL WAY.

THE MOST EXTENSIVE TRANSISTOR LAB KIT IDEAL FOR STUDENT — HOBBYIST — EXPERIMENTER

Lafayette's new 15-in-1 transistor experimenters kit is the most practical introduction to the understanding of the operation of transistors — since it utilizes basic transistor principles and circuitry. Its unexcelled simplicity of construction provides a fascinating and educational program of instruction. You build practical, useful operating transistor devices that teach you transistor fundamentals and applications.

This versatile kit is supplied complete with transistors, relay, photocell, dual headphones and all necessary items including lead wire, solder. You also receive an easily understood instruction manual which explains just how each of the 15 circuits works. Battery powered, the kit is shockproof and safe — ideal for beginners. Shpg. wt., 4 lbs.

KT-134A 15-in-1 Transistor Experimenters Kit (Less batteries).....Net 14.95

BATTERIES
BA-155 Burgess Z or RCA VS034 (8 required).....Shpg. wt., 4 oz. EA.....each 10¢

NEW! EXCITING "EXPLOR-AIR" RECEIVER KIT 4 BAND



18.50



- 4 Bands for total coverage:
- 550-1600 Kc broadcast band
- 1.7-5.0 Mc., 5.0-14 Mc., 14-30 Mc. shortwave bands
- Complete bandswitching from front panel
- Built-in Big 4" PM Loud-speaker

The most sensational shortwave economy receiver kit ever offered. A complete shortwave and standard broadcast set which covers the entire region from 550 kilocycles to 30 megacycles. Four whole bands of fascinating programming unavailable elsewhere. Perfect for students of languages, radio amateurs and casual listeners. Only a regenerative circuit can offer such amazing performance and yet be so simple to build. Building this fine kit is an absolute pleasure — it's so well designed you can't go wrong. Kit includes all the parts you need, and the detailed step-by-step instruction book with its giant pictorial drawings shows you just how to put them together.


One front panel knob does all the bandswitching at the flick of the wrist, immediately taking you from band to band. All coils are prewound for greater accuracy. This kit is so easy to build a child who can read could do it (and many already have!) The chassis is completely isolated from the circuit, so there is no shock hazard.

This precision radio kit is just full of extra features. Complete 4 band coverage of broadcast stations, international broadcast bands, amateur, marine, fire and police services, yes, even satellite signals! Big 4" speaker and sensitive circuit with 50C5 output stage and 12AX7 regenerative detector and amplifier stages give you all the volume you want. Phone jack for privacy automatically disconnects speaker. All controls are on the front panel: On-Off Volume, Main Tuning, Band Spread, Bandswitch, Antenna Tuning, and Regeneration. 110 Volt 50-60 cycle AC-DC power supply lets you use this fine set anywhere. Size: 10" x 7" x 5". Everything needed for unexcelled reception is combined in a compact, economical package.

KT-135 EXPLOR-AIR RECEIVER KIT (Less Cabinet) wt., 5 lbs. 18.50

ML-150 — Leathertette covered Wooden Cabinet for above 1 lb.Net 2.75

5-WATT PUSH-PULL AC-DC HI-FI Amplifier Kit




10.95

- SEPARATE VOLUME, BASS & TREBLE CONTROLS
- PUSH-PULL AUDIO OUTPUT STAGE
- INVERSE FEEDBACK CIRCUIT
- AC OR DC OPERATION

Here in kit form is an AC-DC hi-fi amplifier that presents unusual features despite its amazingly low price. The separate bass and treble controls permit adjustment of both low and high frequency response and balance. Works equally well with both crystal or ceramic cartridges. Has a 4-tube line-up—a 12AX7 amplifier and phase inverter, a 35W4 rectifier and a pair of 35C5's in push-pull, having a power-packed low distortion output. The circuit utilizes an inverse feedback loop to reduce the level of hum and distortion. Kit is complete containing all essential parts, tubes and detailed instruction manual showing pictorial and schematic diagrams. Shpg. wt., 4 lbs.

KT-92Net 10.95

SUPER-SENSITIVE PHOTOCELL ELECTRONIC RELAY KIT



12.95


- WITH CLAIREX CADMIUM SULPHIDE PHOTOCELL
- ADJUSTABLE SUPER SENSITIVITY—WORKS WITH JUST A FLASHLIGHT AT 250 FEET!
- NEEDS NO SPECIAL HIGH-INTENSITY LIGHTS
- INSTANTANEOUS OR SUSTAINED OPERATION ON THE FLIP OF A SWITCH!

Lafayette's latest achievement in a super-sensitive photocell relay kit. Ideal for sustained operation required for burglar alarms, door buzzers, for turning on porch and home lights at night to discourage prowlers when away in the evening. Excellent for instantaneously on-off operation required for counters, packaging, door opening, motor activation and countless industrial applications. A flip of the switch converts unit from instantaneous "on-off" to sustained "on" operation. A simple push on the "RESET" switch opens the external circuit and turns off the alarm. The unit operates on 110 volt AC and incorporates the efficient 5823 cold cathode tube, permitting longer life since there are no filaments to burn out. The controlled circuit is plugged into a convenient 110V AC output socket. A simple change in wiring (in instructions), as well as convenient input terminals, enable you to supply the external circuit with any desired voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on voltage. Size: 3" x 4" x 5". Shpg. wt., 3 lbs. cabinet and easy-to-follow illustrated instructions. Net 12.95

KT-133—Kit, Complete

CAN BE USED AS BURGLAR ALARM

NEW! SEMI-AUTOMATIC "BUG"



SUPER SPEED TELEGRAPH KEY

9.95

Value 20.00


Fully the equal of keys selling at almost twice the price! 7 adjustments for speed and comfort, so important in developing the right timing when using a "bug." Heavily weighted with solid steel block in base. Speed adjustable 10 wpm to as high as desired. 1/2" silver contacts; weight scale for reproducible speed settings. A real bargain for radio amateurs and professional CW operators! 6 1/2" long x 3" wide x 2 1/4" high, exclusive of knobs and feet. Shpg. wt., 3 1/2 lbs. MS-435 Semi-Automatic "Bug"Net 9.95

NEW! CODE PRACTICE SET

Economical and practical code practice key and buzzer unit for learning code. Telegraph key chrome and nickel plated with both adjustable spring tension and contact clearance. The high frequency buzzer has frequency adjustment with locknut to keep tone constant. Screw type pin jack terminals for headphone connection. Works with inexpensive 1 1/2 volt battery. Heavy black molded phenolic base and buzzer housing. Base 6 1/2" x 2 1/2" x 1 1/8", overall length 8 1/2". Shpg. wt., 2 lbs. MS-438 Code Practice Set (less battery) 1.79

BATTERY BA-157 Burgess 21.13
MS-369 Stethoscope Headset1.39

NEW! LAFAYETTE STEREO PHONO AMPLIFIER KIT



ONLY 18.95

- GANGED TONE CONTROLS
- STEREO-MONAUROUS SWITCH
- .04 VOLT SENSITIVITY
- 4 WATTS STEREO OUTPUT
- ISOLATION TRANSFORMER
- SEPARATE VOLUME CONTROLS

This is a complete 4-watt hi-fi stereo amplifier having 2 watts output per channel. Features separate volume control for each channel; ganged tone controls; Stereo-monaural switch to feed one channel to both speakers and to reverse the channels. Just right for any use where a small stereo amplifier is required—ideal for custom mounting in even the tightest locations; specially designed for small apartment sized stereo systems.

An isolation transformer makes this circuit extra safe. Other circuit features for better performance include application of negative feedback to driver and output stages for wide-range response and extra low distortion. Dual-triode 12AX7 tubes function as voltage amplifier and driver, providing very high gain; 40 millivolts drives this unit to full output. This tremendous gain, plus an extremely high input impedance, make this amplifier perform exceptionally well with all types of ceramic and crystal pickups, as well as tuners, tape recorders, etc. Selenium rectifier power supply has extremely good regulation. Logical layout, high quality parts, plus complete instructions for assembly, make this kit a pleasure to build and use. For 3.2 or 8 ohm speakers. Tubes: 2-50C5, 2-12AX7 plus selenium rectifier. Size: 9 1/2" x 5" x 4 1/2". Complete with all parts. For 110-120 volts, 60 cycle AC. Shpg. wt., 7 lbs. KT-126—Kit, Complete Net 18.95

NEW! LAFAYETTE "BRASS-POUNDER'S" KEY



1.95

LAFAYETTE SPECIAL

• With Ball-Bearing Pivots
• Solid Polished-Brass Base
A better quality precision-made key designed for hard usage. Polished brass base; spring tension and contact clearance adjustments; 3/16" silver contacts. Base 3" x 2" overall size 5" long x 2 1/2" wide x 1-1/16" high. Shpg. wt., 1 1/2 lbs. MS-428 Telegraph KeyNet 1.95

COMPLETE STEREO PHONO SYSTEM KIT

- ASSEMBLE THE STEREO AMPLIFIER AND SAVE REAL MONEY
- PLAYS STEREO AND MONAUROUS RECORDS

REGULAR 26.55 ONLY 59.95

Enjoy fine stereo performance with this "easy-to-assemble" exclusive Lafayette package. The complete system consists of Lafayette KT-126 basic stereo phono amplifier kit, the renowned Collaro TSC-640 4-speed automatic record changer, the new Bonette "OV" Turnover Stereo cartridge with dual sapphire styl for stereo and monaural records, and two Lafayette SK-109 Miniature Hi-Fi separate volume control, "stereo-reversal-monaural operation" switch, and isolation transformer to work from either 4 or 8 ohm outputs and are supplied with 25 ft. of cable for hookup. You save 16.58 over regular catalog prices! Shpg. wt., 33 lbs. PK-299WX Stereo Phono Kit System Less changer base 5.00 DownNet 59.95

Wood base for Collaro TSC-640, Mahogany finish. Shpg. wt., 5 lbs. PK-374W


PK-375W Above base, blond finish. Shpg. wt., 5 lbs.

Net 3.95

Net 3.95



Lafayette KT-126



Two Lafayette SK-109



Collaro TSC-640



Bonette "OV" Turnover Stereo cartridge



79¢

LAFAYETTE SPECIAL

SAVE ON NEW TELEGRAPH KEY

Economical and practical code practice key. Solid, heavily chrome and nickel plated metal parts, molded phenolic base. Adjustable spring tension and adjustable contact clearance. A real buy! Base 3 1/4" long x 1-13/16" wide. Overall length 5"; height 1 3/8". Shpg. wt., 12 oz. MS-319 Telegraph KeyNet .79

NEW! high frequency CODE PRACTICE BUZZER




79¢

Reg. Value 2.50
Adjustable frequency buzzer ideal for individual or group code practice. Black molded phenolic housing — Works with 1 1/2 volt battery. Screw adjustment for changing tone. 1 1/8" diam. x 1-1/16" high. Shpg. wt., 6 oz. MS-436 BuzzerNet .79

Save 33 1/3 to 50% on MINIATURE-TRANSISTOR & R/C Equipment

NEW! Lafayette's SUPER-TROL R/C EQUIPMENT



(A) **RADIO CONTROL TRANSMITTER:** Assembled-tested-guaranteed. No license examination required for operation. Crystal controlled for stability and to meet F.C.C. regulations. Uses powerful 3A5 tube for range of approximately one mile. Will operate any 27.255 mc R/C receiver. Overall dimensions only 8 1/2" x 2 3/4" x 1 1/2" — just a handful! Includes antenna — tube — crystal — and instructions. Less Batteries. Shpg. wt., 2 1/2 lbs. Just fill out enclosed FCC forms for station license. **Net 14.95**

(B) **RADIO CONTROL RECEIVER:** Completely wired and tested receiver — extremely sensitive and stable. Completely enclosed — ideal in boats — or case may be removed if desired. Ingeniously constructed to withstand vibration and shock. Features external fine tuning — antenna "snap" lead — plug for power and actuator connections. Ideal Companion for F-249 Transmitter and F-327 Servo shown elsewhere on this page. Requires one 1.5V battery and one 67.5 Volt battery. Size determined by use. Measures only 3" x 2 3/4" x 1 1/2". Complete with tube and instructions. Less batteries. Shpg. wt., 8 oz. **Net 8.95**

SPECIAL COMBINATION OFFER
F-259 — Combination Consists of R/C Transmitter (F-249), and R/C Receiver (F-208) 2.00 Down **Net 22.90**

NEW! LAFAYETTE 27.255 MC CITIZEN BAND REMOTE CONTROL TRANSMITTER KIT KT-127

- WAY OVER 1 MILE LINE OF SIGHT TRANSMISSION!
- SUPER STABILITY FOR FOOLPROOF CONTROL OF MODEL PLANES, BOATS AND CARS.

Once again Lafayette spurts into the lead with its new amazing RC CITIZEN BAND TRANSMITTER. You'll marvel at the neatness and simplicity of its layout and at the dependability of its crystal controlled circuit. Fits comfortably in the palm of your hand — yet is so stable that it is unaffected by hand capacitance or motion. Has new attractive wide-scale meter for visually tuning transmitter for optimum foalproof performance. Has wide, non-critical tuning. Uses one B & W prewound coil — no tedious winding of coils! Tuning for maximum output and antenna loading adjustment easily performed from exterior of cabinet. Complete with approved telescoping antenna, meter, cabinet, chassis, tube, crystal, alignment tool, all parts and easy step-by-step instructions. Just fill out enclosed FCC forms for station license. 5 lbs.

KT-127, Less Batteries..... Net 15.95
 1 BA-157 Burgess No. 2 (RCA VS036) Battery Net .13
 2 BA-133 Burgess P45 (RCA VS218) Battery @ 2.17 Net 4.34



DYNAMIC EARPHONES

- FOR TRANSISTOR AND SUBMINIATURE RECEIVERS
- FOR SILENT RADIO AND TV LISTENING.

A sensitive all-purpose earphone designed with both your listening pleasure and pocketbook in mind. Extensive range and excellent tone combine, to provide excellent reproduction. Lightweight, equipped with a practically invisible ear support, that slips comfortably over either ear, from which the earphone can't slip out or fall. Ideal for use with TV and radio sets, amplifiers, miniature and transistor receivers, etc. Attractive unit with shiny chrome finish. Complete with a 3 ft. cord. A super value at this price. Shpg. wt., 5 oz.
MS-591 6 ohm impedance with subminiature phone plug Net .79
MS-365 6 ohm impedance, with phone tip plugs. For silent radio or TV listening Net .98
MS-367 2000 ohm impedance, with phone tip plugs Net 1.15
MS-368 3000 ohm impedance with subminiature phone plug and matching phone jack Net 1.05



As Low As **.79**

SERVICEMAN'S SPECIAL! MINIATURE REPLACEMENTS FOR JAPANESE 6 TRANSISTOR RADIOS

FIG. A IF TRANSFORMERS — Specially constructed for extra efficient performance in Japanese 6 transistor printed circuit superheterodyne radios. Adjustable core easily accessible from top. Size: 31/64" x 13/32" x 13/32" less terminals. Shpg. wt., 3 oz.
MS-764 1st IF Transformer Net .59
MS-751 2nd IF Transformer Net .59
MS-752 3rd IF Transformer Net .59
FIG. B OSCILLATOR COIL — Excellent for above transformers as well as for most Japanese superhet receivers. 31/64" x 13/32" x 13/32" less terminals. Shpg. wt., 3 oz.
MS-753 Net .59
FIG. C ANTENNA COIL — Highly efficient ferrite antenna coil for Japanese superhet receivers. 437 microhenris, Q is 200 at 1000 kc. 2 3/4" x 1/2" x 3/16". Shpg. wt., 4 oz.
MS-754 Net .59



REMOTE CONTROL ESCAPEMENT

- AT THE LOWEST PRICE ANYWHERE!



A sturdy 2 arm self-neutralizing escapement. Completely wired (not a kit). Converts electrical impulses from remote control receiver to mechanical motion for varying movement of plane, boat, or car. Four 90° rotations — two by armature activation, two by neutralization. Has ratchet governor for maintaining foolproof rotating speed. Weighs only 7/8 oz. Size: 1-3/8" L x 2" W overall. Shpg. wt., 5 oz.
F-255 Net 2.45

REMOTE ENGINE CONTROL ESCAPEMENT

Lafayette's exciting new air-bleed self-neutralizing remote engine control. Varies engine speed of your model. Neutral position of one arm is low speed, neutral position of 2nd arm is high speed, and maintained activated position of either arm (armature activated) stops motor. Perfect mate for Lafayette F-256. Compact and weighs only 3/4 oz. Requires 1-1/2 volt battery. Low current drain. Size: 1-5/8" x 1" x 3/4". Shpg. wt., 5 oz.
F-257 Net 3.45



3.45
3.95

COMPOUND REMOTE CONTROL ESCAPEMENT

- LAFAYETTE'S AMAZING VALUE IN A 4-ARM SELF-NEUTRALIZING COMPOUND ESCAPEMENT!
- NO NEED TO WORRY ABOUT LOSING YOUR MODEL!

You have no sequence of operation to worry about! Simple as A B C! One pulse always gives right turn; two pulses always gives left turn. Three pulses closes the circuit for the supplementary control such as motor (F-257) or elevator, if used. The rudder always returns to neutral position after any turn as soon as transmitter keying button is released. With ratchet governor for foolproof operation. Sturdy construction — low current drain. Uses 1-1/2 volt battery. Weighs 1-1/8 oz. Size: 2-7/8" L x 1-9/16" overall. Shpg. wt., 6 oz.
F-256 Net 3.95


NEW! COMPLETE TRANSISTOR BROADCAST RECEIVER COIL KIT

- MINIATURE 2-GANG POLY-VARI-CON TUNING CONDENSER
- 3-45SKC IF'S ● OSCILLATOR ● FERRITE LOOP ANTENNA
- MATCHED MICRO-MINIATURE COILS



A complete set of matched micro-miniature coils for use in subminiature transistorized radio receiver circuits. Shielded IF and Oscillator coils measure only 7/16" high above chassis and are 3/8" in diameter! Correct impedances are provided for maximum gain in transistor circuits; high "Q" coil design and impregnation for maximum stability make these units hard to beat at any price!

The oscillator coil has an inductance of 261 µh, variable ± 20% by means of a tuning slug. The 1st IF coil (converter output) primary impedance 15,000 ohms; secondary 350 ohms; center frequency 455KC. The 2nd IF (interstage) the same but secondary 500 ohms. The 3rd IF (detector) also the same except secondary 5,000 ohms. The ferrite loop antenna is flat type, 2 3/4" long x 9/16" w x 1/4" thick. Includes famous Poly-Vari-Con 2-gang tuning condenser. Shpg. wt. of kit is 1 lb.
MS-450 Net 3.95



3.95

SUBMINIATURE TRANSISTOR RECEIVER COIL KIT

Includes same set of high "Q" miniature components as MS-450 except for the tuning condenser.
MS-440 Same as above, less tuning capacitor Net 2.49

POWER TRANSISTORS EACH UNIT FACTORY TESTED TO MEET SPECIFICATIONS



EQUIVALENT TO:
 CBS 2N256
 SYLVANIA 2N307
 MOTOROLA 2N554
 Net .77

Reg. Value ~~1.35~~
77¢

SP-147 Power Transistor

GENERAL PURPOSE DIODES




EXCELLENT DETECTOR FOR TRANSISTOR AND VACUUM TUBE RADIO RECEIVERS

29¢ 10 for **2.59**
 Each

EQUIVALENT TO:
 1N34 1N34A 1N38A
 1N48 1N56 1N69

SP-148 General Purpose Diode Net .29 each 10 for 2.59


"JEWEL" REMOTE CONTROL RELAY



2.75

A natural for remote control receivers, it is highly sensitive, and built to withstand severe crashes. The smallest commercial job available, it weighs less than 1/2 oz. Factory adjusted to pull in at 1.4 MA. drop out at 1.2 MA D.C. Single pole, double throw. Used in outstanding R/C receivers. 5,000 ohm coil. IMPORTED TO SAVE YOU MONEY.
F-260 — Relay Net 2.75

27.255 R/C CRYSTAL



Reg. 2.95
1.95

Specially manufactured for Lafayette. Designed specifically for use in R/C model planes, boats, cars, etc. Low-drift — high output — dependable frequency control. Tolerance .04%. 13/16" wide x 7/16" deep x 1 1/8" high above pins. Pins on 1/2" centers.
MS-446 Net ea. 1.95



MATCHING CRYSTAL SOCKET: Made of special low loss phenolic. Easily mounts flush or stand-off. Small — light — rugged.
MS-447 Net ea. .15

miniature TELESCOPING ANTENNA




.59
 RETRACTS to 9 INCHES with PLASTIC CASE

5-section antenna of chrome-plated brass. Plugs into jack supplied. 38" fully extended and retracts to 9". Comes in a flexible plastic case with slip-under protecting flap.
F-343 Telescoping Antenna Net 59¢

LAFAYETTE PNP AUDIO TRANSISTOR

SPECIAL!
 AS LOW AS **37¢**



General audio type PNP transistor for experimenters and hobbyists, for code practice oscillators and similar small signal devices. In new JETC 30 welded case.
SP-146 Net, singly, each 59¢
 10 for 4.50, 50 for 19.50, 100 for 37.00

ANOTHER LAFAYETTE FIRST!

TOSHIBA, HITACHI AND NEC HIGH QUALITY REPLACEMENT TRANSISTORS FOR POPULAR JAPANESE TRANSISTOR RADIOS.

SERVICEMEN'S SPECIALS!



AS LOW AS **1.19**

EACH TRANSISTOR MEETS TOP SPECIFICATIONS

STOCK NO.	USE	TOSHIBA	HITACHI	NEC	NET
SP-151	Conv.	2N52	HJ23	ST371	1.39
SP-152	1st IF	2N48	HJ22	ST24C	1.39
SP-153	2nd IF	2N45	a	ST24C	1.39
SP-154	Driver	2N44	HJ15	ST303	1.39
SP-155	Output	2N56	HJ17	ST342	1.39

Average shpg. wt., 2 oz.

*Same as 1st IF. Use SP-152.
 †2 Units used in Push-Pull output.
 NEC — Nippon Electric Co.
 All 3 MFR's Types within each use category completely interchangeable. HITACHI 2N213, 2N217, 2N218 and 2N219 equivalents of HITACHI HJ15, HJ17, HJ22 and HJ23 respectively.

COPPER CLAD LAMINATE AT LAFAYETTE'S LOW PRICES!

Finest quality XXXP bakelite base, copper clad boards for printed circuit work.

NO.	DESCRIPTION	NET
MS-510	XXXX Copper Lam.—1 side—9"x12"	1.30
MS-511	XXXX Copper Lam.—1 side—6"x4 1/2"	.45
MS-512	XXXX Copper Lam.—1 side—3"x4 1/2"	.30
MS-513	XXXX Copper Lam.—1 side—2"x4 1/2"	.25
MS-514	XXXX Copper Lam.—1 side—3"x2 1/2"	.24
MS-515	XXXX Copper Lam.—2 sides—9"x12"	1.95
MS-516	XXXX Copper Lam.—2 sides—6"x4 1/2"	.60
MS-517	XXXX Copper Lam.—2 sides—3"x4 1/2"	.40
MS-518	XXXX Copper Lam.—2 sides—2"x4 1/2"	.30
MS-519	XXXX Copper Lam.—2 sides—3"x2 1/2"	.27

PLASTIC CASE FOR MINIATURE EQUIPMENT

Beautiful pocket sized modern streamlined case with rounded corners and removable snap-on cover. This is an ideal case for that transistorized receiver—or other miniature of subminiature preamplifier, amplifier, oscillator or transmitter. Two pre-drilled apertures, a 2 1/2" diameter opening ideal for Poly-Vari-Con tuning capacitor and a 5/16" opening ideal for volume control and switch. In addition, there are two small openings on the slide for such internal leads as antenna or earphone. Experimenters, builders and hobbyists will want to stock up on several of these cases at this low bargain price. Size: 4 1/4" x 2 3/4" x 1 1/4". Shpg. wt., 6 oz.
MS-302 Net 95¢

NEW! Lafayette Super-Value Sun Battery QUANTITY LIMITED!

Sensational buy enables Lafayette to offer this famous selenium photocell at a small fraction of its normal price! Approx. 8 MA current output at 100 ft. candles with 55 ohms load! .5 volts open circuit voltage in av. sunlight. 30 MW power output at 100 ft. candles with 1000 ohm load! Truly a super buy for the experimenter, kit builder, etc. With colored pigtail leads. 1 1/4" diam.
MS-343 Net 1.47

TRANSISTOR OUTPUT TRANSFORMER



Only 5/8" x 3/4" x 1-1/16". 2000 ohm primary to 10 ohm voice coil. Matches most transistor outputs. Shpg. wt., 8 ozs.
TR-93 Net 69¢

SUPER MICRO-MOTORS

- HALF THE WEIGHT—TWICE THE POWER!
- HIGHER SPEED—LOWER DRAIN!
- PERMANENTLY LUBRICATED!
- DOUBLE PERMANENT FERRITE MAGNETS!



Expertly designed, miniature, D.C. permanent magnet motors. Ruggedized construction for industrial use. Highest power and speed to weight ratio of any miniature motor makes these a "natural" for models and remote control applications. Ferrite magnets preclude possibility of demagnetization and offer minimum weight. Unique, precision formed device permanently centers commutator in precise position. Utilizes phosphor-bronze brushes and brass sleeve bearings. May be mounted by means of motor mount supplied or by means of tapped hole in motor case. Avg. Shpg. wt., 4 oz. Complete with leads. Shaft diameter 3/32"

Stock No.	Voh. Range	Drain Ma.	RPM	H.	W.	L.	Wt.	NET EA.	LOTS 3 EA.
F-403	1.5-4.5	200-300	5000-6000	1"	1 1/8"	1 1/2"	1 1/2 oz.	.69	.62
F-404	3-6	250-300	6000-7000	1 1/8"	1 1/8"	1 3/4"	2 1/2 oz.	1.10	.98
F-405	1.2-16	90-140	8000-9000	1 1/4"	1 3/8"	1 3/4"	2 1/2 oz.	1.39	1.25

Eico • Dynakit • Acrosound • Paco • Harman-Kardon HI-FI Kits

NEW! EICO STEREO PHONIC DUAL PREAMP KIT

Self-powered preamp-control center offering complete switching and control facilities for any stereo program source.

SPECIFICATIONS (both channels):
 Frequency response 5-200,000 cps \pm 0.3 db; IM distortion (60 & 7000 cps) .03% @ 1 v. RMS output; Harmonic distortion (20-20,000 cps) .1% @ 3 v. RMS output; Tone-control range \pm 15 db @ 50 and 10,000 cps; RIAA phono and NARTB tape head (15, 7.5, and 3.75 ips) equalization; Output-to-main amplifier impedance, 8000 ohms. Tubes: 5-12AX7/ECC83's, 1-6X4. Size: 3 1/2" high, 12" wide, 8 1/2" deep. Shpg. wt., 10 lbs. Cover supplied.

HF85K Stereo Dual Preamp Kit.
 G-492 2.00 Down Net 39.95
 HF85 Same, Factory wired and tested
 G-493 5.00 Down Net 64.95

EICO Model HF-81K STEREO PHONIC DUAL AMPLIFIER-PREAMP

A handsome complete hi-fi stereophonic control center with 2 matched Williamson type push-pull EL84 power amplifiers, all on one chassis. Output Power - rated 28 watts (continuous) for monaural, 14 watts for stereo. Freq. Response - \pm 5 db, 10 to 100 kc at 2 w out. IM Distortion (60 and 6000 cps at 4i) - 0.5% at 10 watts input. Harmonic Distortion - less than 1% from 40-10 kc at 20 w output. Sensitivity for rated output - mag phono: 4 mv; tape head: 2 mv; mic: 6 mv; tuner and auxiliaries: 0.5 v. Hum and Noise Level (below 14W): - 56 db on low level input, - 75 db on high level inputs. Boss - \pm 15 db at 50 cps. Treble - \pm 15 db at 10 kc. Speaker Connections - 4, 8, & 16 ohms. Tubes - 4 ECC83/12AX7, 2 ECC82/12AU7, 4 EL84, 2 EZ81. Size 15 x 10 1/2 x 4 1/4". Shpg. wt., 24 lbs.

Model HF-81K. Kit complete with cover
 G-490WX 5.00 Down Net 69.95
 Model HF-81 as above, but factory wired.
 G-491WX 5.00 Down Net 109.95

EICO FM TUNER HFT-90

newly-designed, extremely sensitive, low-noise "front end" supplied in a cast housing completely pre-wired, pre-aligned, ready to use. Employs the broad-band deflector circuit used in \$169 FM tuners now on the market. Also features new DM-70 traveling tuning eye. Input 300 ohms, IF bandwidth 260 kc, detector separation of 600 kc. Freq. resp. 20-20,000 cps \pm 1 db. Audio output 1 V for 10 uv input with 75 kc deviation. Hum 60 db below 1 V. Cathode follower and multiplex outputs. Flywheel slide-rule tuning, AGC, stabilized low limiting threshold for excellent performance from weaker signals, broad-band ratio detector for improved capture ratio and easier tuning, full-wave rectifier and heavy filtering, very low distortion. Uses 1-ECC85/6AQ8, 3-6AU6, 1-6AL5, 1-6CA, 1-DM70, 1-6X4. Flexible "low silhouette" design adaptable to any panel thickness for console installation; optional cabinet. MWD: 3 1/2" x 12" x 8 1/4". Operates from 110-125 VAC. 60 cps line. Shpg. wt., 10 lbs.

HFT 90K FM TUNER KIT (less cover)
 G-422 2.00 Down Net 39.95
 HFT 90 Factory wired and tested tuner.
 G-423 5.00 Down Net 65.95
 E-5 Cover for above
 G-431 2.00 Down Net 3.95

EICO 12-WATT WILLIAMSON-TYPE HI-FI AMPLIFIER . . . PREAMP . . . CONTROL SECTION

Compact, attractively styled amplifier with complete front end facilities and true high fidelity performance. Direct tape head and magnetic phono inputs with NARTB (tape) and RIAA (phono) feedback equalizations. Dual triode circuit for variable turnover bass and treble feedback-type controls. Power output: 12 watts continuous, 25 watts peak. Intermodulation distortion 1.5% at 12 watts, 0.55% at 6 watts, 60 to 6000 cps. Frequency response: 12-50,000 cps \pm 0.5 db at 1 watt; 25-20,000 cps \pm 0.5 db at 12 watts. 4 Controls: Selector switch, level control, bass and treble controls. Speaker connections for 16, 8, and 4 ohms. Tubes: (2) ECC83/12AX7, ECC82/12AU7, (2) EL84, EZ81. Size: 3 1/2" H, 12" W, 8 1/4" D. Shpg. wt. 13 lbs. With instructions.

HF 12K-Complete Kit.
 G-424 2.00 Down Net 34.95
 HF 12-As above, factory wired.
 G-425 5.00 Down Net 57.95

NEW EICO MODEL HF87K 70-WATT STEREO HIGH FIDELITY DUAL POWER AMPLIFIER KIT

This superb dual 35 watt amplifier kit utilizes a cathode-coupled phase inverter-driver circuit. Frequency response: \pm 0.5 db 5 cps 100 kc. Harmonic distortion less than 1%. From 20 to 20,000 cps within 1 db at 70 watts. Damping factor: above 11. Sensitivity: 0.38v for full output. Channel separation: 55 db. Controls-Level Ch. 1, Level Ch. 2, "Service Selector" switch, On-Off switch. Speaker connections: 4, 8, 16, 32 ohms. Tubes 1-ECC83/12AX7, 2-6SN7GTB, 4-EL34, 2 silicon diode rectifiers-215 watts, 117v, 60 cps. Size 13x11x6". Shpg. wt., 32 lbs.

G-496WX Kit 5.00 Down Net 74.95
 HF87 Same as above, but factory wired
 G-497WX 5.00 Down Net 114.95

EICO 20 WATT HIGH FIDELITY AMPLIFIER KIT MODEL HF20K

High quality equalizer and control section plus 20 watt Ultra-Linear Williamson-type power amplifier. Low distortion feedback equalization; 5 equalizations provided for LP's and 78's including RIAA. Variable turnover, low distortion feedback tone controls.

Six inputs: 4 high level switched inputs-Tuner, TV, Tape, Auxiliary (crystal/ceramic phono or second tuner); 2 low level inputs (not switched)-provides proper pick-up loading and attenuation for all leading magnetic, FM and high quality crystal cartridges without changing resistors. Hum balance control for balancing out 60 cycle residual hum. Power Consumption: 110-120 volts, 60 cps, 100 watts. Tubes: 2-12AX7, 2-12AU7A, 2-6L6GB, 1-5U4GB. Handsomely styled to eliminate the necessity for cabinet. Size: 8 1/2" H, 15" W, 10" D. Shpg. wt., 24 lbs.

G-502WX HF-20-KIT 2.00 Down Net 49.95
 G-503WX Factory Wired 5.00 Down Net 79.95
 G-428W ENCLOSURE FOR HF20 2.00 Down Net 4.50

EICO 30-WATT HI-FI INTEGRATED AMPLIFIER KIT with PREAMPLIFIER EQUALIZER AND CONTROL SECTION

Combines exceptional power supply reliability of the power amplifier section with an extremely versatile preamplifier control section. Has 3 low level inputs for magnetic phono tape head and microphone and 3 high level inputs for TV or tuner, crystal or ceramic cartridge or tape; 4 phono equalizations and NARTB tape head equalization with equalization circuit of extremely low distortion. IM DISTORTION: 2% at 30 watts, 0.5% at 10 watts. HARMONIC DISTORTION: Below 1% 20 cps-20KC 1 db below 30 watts. FREQUENCY RESPONSE: At 30 w \pm 0.5 db 15 cps - 50KC, \pm 1.5 db 15 cps - 100KC; \pm 0.1 db 15 cps - 30KC at any level from 1 mw to 30 w. SQUARE WAVE RESPONSE: 20 cps to 30 KC essentially undistorted. SPEAKER CONNECTIONS: 4, 8 and 16 ohms. SENSITIVITY (input for rated output): Mag Phono-5 mv, Tape Head - 2 mv, Mic - 4 mv, High level - 2 mv. TUBES: 2 - ECC83/12AX7, 2 - EC90/6CA, 4 - EL84, 2 - EZ81. POWER REQUIREMENTS: 117v, 60 cps; 140 watts consumption. Size: 15" x 4 1/4" x 10 1/2". Shpg. wt., 28 lbs.

G-420WX HF32K KIT 5.00 Down Net 57.95
 G-421WX HF32 Factory Wired 5.00 Down Net 89.95
 G-504 HF30K basic power amplifier Kit, less cover. Shpg. wt., 17 lbs. 2.00 Down Net 39.95
 G-505 HF30 Factory Wired. 5.00 Down Net 62.95
 G-506 E-4 Matching Cover 2.00 Down Net 3.95

NEW! EICO BASIC AMPLIFIER KITS

35-watt "Ultra-Linear" power amplifier (70 watts peak) featuring EL34 tapped-screen output stage, low-noise EF86 voltage amplifier, 6SN7GTB, plus GZ34 rectifier. Frequency response 5-100,000 cps \pm 1.5 db @ 35 watts. IM Distortion (60 & 7000 cps) 1.5%, and harmonic distortion below 1%. 20-20,000 cps \pm 1 db both at 35 watts. Hum 90 db below rated output. Damping factor above 10 (20-20,000 cps), 15 @ 1 kc. Speaker taps 4, 8, 16 ohms. Power consumption 130 watts @ 117 volts 60 cps. Size: 7" high x 14" wide x 8" deep. Shpg. wt., 25 lbs.

G-412WX HF-35K Amp. Kit 2.00 Down Net 47.95
 G-413WX HF-35 Factory Wired. 5.00 Down Net 72.95
 G-414 E-2 Matching Enclosure 2.00 Down Net 4.50

Five-tube "Ultra-Linear" hi-fi amplifier rated 22 watts continuous, 44 watts peak. Low-noise EF86 direct-coupled to 6SN7GTB drives push-pull 6L6GB tapped-screen output stage. Will handle 4, 8, 16 ohm speakers, including electrostatics. Frequency response \pm 1.5 db, 5-100,000 cps @ 22 watts. IM distortion (60 & 7000 cps) 1%, harmonic distortion below 1%. From 20-20,000 cps \pm 1 db, both at 22 watts. Hum 85 db below rated output. Sensitivity 0.6 volt for 22 watt output. Damping factor above 12 (20-20,000 cps), 21 @ 1 kc. Power consumption 90 watts from 117 v, 60 cycle source. Size: 7" high x 14" wide x 8" deep. Shpg. wt., 25 lbs.

G-415WX HF-22K Amp. Kit 2.00 Down Net 38.95
 G-416WX HF-22 Factory wired. 5.00 Down Net 61.95
 G-414 E-2 Matching Enclosure 2.00 Down Net 4.50

Williamson-type 14 watt (28 watts peak) power amplifier at low cost for both stereo and monaural installations. Frequency response \pm 0.5 db, 10-100,000 cps @ 1 watt. Harmonic distortion less than 1% (50-10,000 cps) and IM distortion (60 & 7000 cps) 2%—both @ 14 watts, 20 db inverse feedback. Damping factor above 8 (20-15,000 cps). Hum 90 db below rated output. Tubes: 1-ECC83/12AX7, 2-EL84, 1-EZ81. Speaker taps 4, 8, 16 ohms. Size: 3 1/2" high x 12" wide x 4" deep. Shpg. wt., 10 lbs.

G-417 HF14K Amp. Kit. 2.00 Down Net 23.50
 G-418 HF14 Factory wired. 2.00 Down Net 41.50
 G-419 E-6 Matching Enclosure 2.00 Down Net 4.50

EICO HIGH FIDELITY AM TUNER KIT HFT94K

The new HFT94K is a basic AM tuner kit designed for hi-fi applications. The DM-70 traveling eye indicator is pre-wired. Sensitivity: 3 mv. at 30% mod. for 1 v. output. Selectivity: Frequency response: 20-9000 cps (wide), 20-5000 cps (narrow). Output: low impedance plate follower. Extra recording output. Controls: Bandwidth Selector, Level/Power, Tuning. For 110-125 V., 60 cps. Size: 3 1/2" x 12 x 8 1/4". Shpg. wt., 12 lbs.

G-500 Kit 2.00 Down Net 39.95
 HFT94 Same as above, but factory wired.
 G-501 5.00 Down Net 65.95

EICO MODEL AF-4K COMPLETE STEREO PHONIC DUAL AMPLIFIER KIT

The Model AF-4K kit consists of two highly fed-back, four watt amplifiers preceded by complete facilities for stereo/monophonic operation. Controls Include: Selector (AM, FM, FM Multiplex; Aux., high-level Phono), Mode (Amp 1, Amp 2, Norm., Reverse, Mon. Phono, Mon. Aux.), Independent, concentric level and tone controls, On-Off switch. Frequency response: \pm 0.5 db 30-20,000 cps. Harmonic distortion, less than 1% at 4 watts. Sensitivity (for 4 W. output/channel): 26 V. (phono), .113V (other inputs). Hum: - 74 db below full output. Speaker connections: 4, 8, 16, 32 ohms. Tubes: 2 - 12DW7, 2-EL84, 1-EZ81. Size: 3 1/2" x 12 x 8 1/4". Shpg. wt., 13 lbs.

G-498 Kit 2.00 Down Net 38.95
 AF-4 Same as above, but factory wired.
 G-499 5.00 Down Net 64.95

PACO MODEL SA-40 STEREO PREAMP AMPLIFIER KIT

SA-40 combines a dual 20 watt amplifier and versatile preamplifier in an easy-to-build kit. PERFORMANCE SPECIFICATIONS - RESPONSE: 30-90,000 cps, \pm 1 db. DISTORTION: Less 0.2% harmonic and 1% intermodulation per channel. INPUTS: 14 total. OUTPUTS: Dual tape, Separate Preamp, Dual Speaker. HUM AND NOISE LEVEL: Up to 80 db below rated output. SPEAKER TAPS: 4, 8, 16, 32 ohms. SENSITIVITY: Tuner and Aux. 0.75 v., Mag. Phono-1.5 mv., Mag. Phono-2 5 mv., or 0.3 v. Ceramic TAPE OUTPUT LEVEL: 2 v., unaffected by Loudness or Tone settings. 9 tubes plus 2 silicon and 1 selenium rectifier. For 117 v. 50-60 cycles AC. 15 1/2" W x 11 1/2" D x 5 1/2" H. Shpg. wt., 23 lbs. Complete with case and step-by-step assembly-operation manual.

G-590WX 5.00 Down Net 79.95
 G-591WX SA-40, Factory Wired 5.00 Down Net 129.95

DYNAKIT PAS-2 STEREO PREAMPLIFIER KIT

The PAS-2 stereo preamplifier includes two independent preamplifier-control channels with complete stereo facilities. Inputs: 3 stereo low level and 4 stereo high level. Outputs: low impedance audio output and tape output. Frequency response: \pm 0.5 db 6-60,000 cps. Distortion: less than 0.5%. Noise: less than 3 μ v. equivalent noise input on RIAA. Gain: 60 db at 1000 cps on RIAA, 20 db on high level. Tubes: 4 12AX7/ECC-83, 6X4, selenium rectifier. Size: 13x8x4". Shpg. wt., 11 lbs.

G-453WX Kit 5.00 Down Net 59.95
 Dynakit PAS-2 Stereo Preamp. Same as above, but completely wired. Shpg. wt., 11 lbs.
 G-454WX 5.00 Down Net 99.95

NEW DYNAKIT STEREO 70 70-WATT STEREO AMPLIFIER KIT

The stereo 70 has 2 independent power amplifiers capable of 35 watts for each channel or 70 watts of power for monophonic use. Frequency response: \pm 0.5 db 10-40,000 cps. IM distortion: less than 1% at 35 watts. Sensitivity: 1.3 volts rms input for 35 watts output. Output impedance: 4, 8, 16 ohms. Minimum channel separation: 55 db. Size: 13x9 1/2x6 1/2". Shpg. wt., 32 lbs.

G-455WX Kit 5.00 Down Net 99.95
 Dynakit Stereo 70 Stereo Amplifier. Same as above, but completely wired.
 G-456WX 5.00 Down Net 129.95

DYNAKIT PAM-1 HI-FI PRE-AMPLIFIER KIT

A quality preamp-control unit incorporating factory-wired printed-circuit module for easy assembly. Inputs: Low-level magnetic input, tape head, or mike. Outputs: Tape and audio output. Controls: Selector-equalization, bass, treble, volume, tape monitor, loudness, hum-balance. Phono Equalization: RIAA, 78 rpm. IM Distortion: Less than .05%. Response: \pm 0.5 db 6-60,000 cps. Tubes: 2-ECC/12AX7 plus selenium stack. Power Requirements: 200-400 volts d.c. @ 3-4 ma.; 6 volts a.c. @ .75 amps. Size: 2 1/2" high x 12" wide x 6" deep. Shpg. wt., 7 lbs. Choice of bone white or charcoal brown vinyl finish.

G-465 Kit 2.00 Down Net 34.95
 G-466 As above, but wired, 5.00 Down Net 59.95

NEW DYNAKIT MARK III 60 WATT POWER AMPLIFIER KIT

Compact 60 watt basic amplifier. Accurate and simple bias setting independent of meter accuracy. Frequency response better than \pm .5 db from below 6 cps to above 60 kc. IM distortion less than 1% at 60 watts, .5% below 50 watts and .04% at average listening levels. Less than 1% harmonic distortion within 1 db of 60 watts from 30 cps to 20 kc. 4, 8, and 16 ohm outputs. Utilizes 1-6AN8, 2 KT88 (or 6550), 1 GZ34 and selenium rectifier. All parts, tubes and protective cover included in kit. Shpg. wt., 28 lbs.

G-457WX Kit 5.00 Down Net 79.95
 G-458W As above, but wired 5.00 Down Net 99.95
 G-459WX Kit with 70.7 watt output for P.A. use 5.00 Down Net 84.95

DYNAKIT MARK IV 40 WATT POWER AMPLIFIER KIT

The Mark IV is a 40 watt basic power amplifier. Power output: 40 watts continuous, 80 watts peak. Frequency response: \pm 0.5 db 10-40,000 cps. IM distortion: less than 1% at 40 watts, less than .05% at 1 watt. Hum and noise: better than 90 db below 40 watts. Output impedance: 4, 8, 16 ohms. Sensitivity: 1.3 volts rms input for 40 watts output. Tubes: 2 EL-34, 7199, GZ-34, selenium rectifier. Finish with nickel chassis, and vinyl coated charcoal brown cover. Power consumption: 115 watts. Size: 5 x 14 x 6 1/2". Shpg. wt., 20 lbs.

G-449WX Kit 5.00 Down Net 59.95
 Mark IV 40 Watt Amplifier. Same as above, but completely wired. Shpg. wt., 20 lbs.
 G-450WX 5.00 Down Net 79.95

DYNAKIT ACCESSORIES

PS-1 Dual Power Supply Kit. Shpg. wt., 4 lbs.
 G-460 Kit 5.00 Down Net 8.95
 G-461 As above, but wired 5.00 Down Net 14.95
 PM-1 Panel Mounting Kit for Preamp PAM-1.
 Shpg. wt., 2 lbs.
 G-462 Kit 2.00 Down Net 2.95
 PM-25 Panel Mounting Kit (2 PAM-1 & 1 DSC-1).
 Shpg. wt., 3 lbs.
 G-463 2.00 Down Net 1.95
 CM-25 Walnut Cabinet Mount (2 PAM-1 & 1 DSC-1).
 Shpg. wt., 4 lbs.
 G-464 5.00 Down Net 17.95

ACROSOUND S1001 STEREO PREAMP KIT

Printed circuit board and modular design make construction simple and enjoyable. Unique features include Mike Dub Switch, balance control, and panel Light Matrix. SPECIFICATIONS - INPUTS: 2-MAG. Carl., 2-Tape Head, 2-Tuner (FM-AM, FM-FM Multiplex), Tape Input, Micro phono. OUTPUTS: 2-Main, 2-Tape, 3rd Channel. CONTROLS AND SWITCHES: Tape Monitor, Mike Dub, Input Selector (78, LP, RIAA-1, RIAA-2, Tape Head, FM-AM, FM-FM Multiplex, Aux.), 2-Bass, 2-Treble, Balance, Ganged Volume/Loudness, Output Selector (Check A, Check B, Stereo, Stereo Rev., Mon. AB, Mon. A, Mon. B), 1-Scratch, 1-Rumble, Phasing, Loudness In-Out, 4 A.C. outlets (2-switched). Input Sensitivity: 5 mv. low level, 30 mv. high level, 2 mv. tape head. 4 1/2" h x 12 1/2" w x 6 1/2" d. Supplied with ribbed aluminum cover in black satin finish, with sand-colored front panel. Shpg. wt., 10 lbs.

G-578WX 5.00 Down Net 69.50

ACROSOUND STEREO 20-20 DUAL BASIC AMPLIFIER KIT

A two-channel basic amplifier kit with common power supply. 18 watts per channel at 2% Harm., 1.5% IM distortion; 36 watts monaural. Individual level controls, stereo-monoaural switch. Dual speaker outputs: 4, 8, 16, 32 ohms. Response: 10-70,000 cps \pm 1 db. A.C. 7 x 10 x 5 1/2" h. Shpg. wt., 18 lbs.

G-570WX 5.00 Down Net 69.50
 Stereo 20-20, Factory wired
 G-571WX 5.00 Down Net 99.50
 Stereo 20. Single channel amplifier Kit; specs equal to one channel of 20-20. 7 x 7 x 5 1/2". Shpg. wt., 13 lbs.
 G-574 2.00 Down Net 44.50
 G-575 Stereo 20, factory wired. 5.00 Down Net 64.50
 Stereo 20A. Stereo 20 Kit, requires power supply, from Stereo 20 or other source. Shpg. wt., 6 lbs. 7" x 5 1/2" x 5 1/2".
 G-572 2.00 Down Net 29.50
 G-573. Stereo 20A, factory wired 2.00 Down Net 39.50
 ULTRA-LINEAR II, (not illustrated). 60 watt power amplifier Kit Size 7" x 15" x 8" h. Shpg. wt., 30 lbs.
 G-576WX 5.00 Down Net 79.50
 G-577WX As above, factory wired 5.00 Down Net 109.50

NEW! HARMAN-KARDON CITATION I KIT

A high quality stereo-monoaural preamp-control unit. Inputs: 12 (six pairs) - Aux, Tape Amp, Tuner, low-level phono, high-level phono. Outputs: 5-Two main preamp outputs plus a third channel output, two tape outputs for recording. Made selector chooses output types stereo, Blend, A + B, Channel A, Channel B, Stereo Reverse Switch provides proper orchestra orientation by reversing channel A + B. ON-OFF switch, IM DISTORTION: Less than 0.05% at 2 watts, Response: \pm .5 db 5-80,000 cps. Tubes: 9-ECC83/12AX7 plus silicon rect., Power Requirements: 110V AC, Size: 14 1/2" W x 12 1/2" D x 6" H. Shipping wt., 20 lbs. Gold & Charcoal brown finish.

G-230WX Kit 5.00 Down Net 139.95
 G-231WX Wired 10.00 Down Net 239.95
 G-232W Walnut Enclosure 5.00 Down Net 29.95

NEW! HARMAN-KARDON CITATION II KIT

The perfect companion piece to the Citation I. Two ultra-linear type amplifiers deliver 60 watts each channel or a total of 120 monaural. Bias meter allows complete accurate balancing of output tubes. Frequency Response: 18-40,000 cps \pm 0.5 db - 1.0 db @ 60 watts, 2-80,000 cps \pm 0 - 1.0 db @ 1 watt; IM Distortion: Less than .5% @ 60 watts, unmeasurable at normal listening levels. Harmonic Distortion: Less than 0.5%, 20-20,000 cps @ 60 watts. Unmeasurable at normal listening level. Output 4, 8, 16 ohms. Tubes: 6 - 12B7Z, 4 - KT88, plus 4-Silicon Diodes & 1 Selenium rect., Dimensions: 16 1/2" W x 9" H x 11 1/2" D. Charcoal Brown & Gold finish. Shpg. wt., 60 lbs.

G-233WX Kit 5.00 Down Net 159.95
 G-234WX Wired 10.00 Down Net 219.95
 G-237WX Charcoal Brown Metal Enclosure Net 7.95

Lafayette's 39th Annual Winter Tool Sale

Breaking Records for Savings




FLEXIBLE SHAFT ATTACHMENT FOR ELECTRIC DRILLS

- DRILL WHEREVER YOU WILL
- TAKES UP TO 1/8" SIZE DRILLS

2.39

Operates off any fixed or portable 1/4" power drill; enables you to drill at any angle anywhere. Capacity up to 1/8" size drills; 36" overall length, with chuck. Comes in box with complete instructions. Shpg. wt., 1 lb. **MD-389** Net 2.39



"EVER-LEVEL"

- MEASURES PITCH IN DEGREES.
- MEASURES INCH RISE PER FOOT.
- FLOATING POINTER FOR HAIRLINE ACCURACY.

The first new leveling device in over one hundred years. Floating pointer gives true level or inclination at a glance. Only 2" square by 1" thick. Molded case of specially selected plastic. Pointer bob floats in oil. Reads any angle instantly. Case design allows leveling from top-bottom or sides. Nothing to break or get out of order. Levels any job—large or small. Shpg. Wt., 4 ozs. **MD-185** Net 98

RECHARGEABLE FLASHLIGHT

- NEEDS NO BATTERY
- ATTRACTIVE & DURABLE
- EASY FLIP-ON SWITCH



This small light weight flashlight fits easily into the palm of your hand. Two-tone (orange and white) color makes an attractive appearance. New concave glass lens spreads out light. This unit can be used in many household applications. Ideal for use in the car. The detachable end covers a pair of male plugs by which the flashlight can be recharged. This feature allows the unit to be used for benchwork or where single light source is required in dark surroundings. Smooth flip-on switch permits easy action. Complete with one replaceable lightbulb. Measures 4 1/2" in length and 1 1/2" diameter. Shpg. wt., 4 oz. **F-435** Net 2.95

NEW CHASSIS PUNCH SET

- EASY-SMOOTH-HOLES IN SHEET METAL
- 5 SIZES: 1/2", 3/8", 3/4", 1", 1 1/2"



5.49

Five most often needed round hole punches. Do the job in minutes—save hours of tedious hand labor. Cuts smooth accurate holes for sockets—plugs—controls—panel lights—switches—terminals—most radio parts. Works equally well with sheet metal—sheet plastics—composition board etc. Drive with any wrench—or with T handle included. Punch sizes included are 1/2", 3/8", 3/4", 1", and 1 1/2". Supplied complete with punches, dies, T drive handle, tapered reamer, fitted wooden case and instructions. Shpg. wt., 2 1/2 lbs. **MD-471** Net ea., 5.49, Net ea., in lots of 3 4.94

NEW! SQUARE PUNCH SET

- 3 NEEDED SIZES—1/2" — 5/8" — 1"
- SMOOTH, ACCURATE, EASY TO USE.



6.95

Save time—save effort—cutting square holes in chassis—panels—sheet metal up to 1/8". Most often needed sizes for square chassis components. Multiple cuts allow any size square hole. Drive punches with any wrench or with T handle included. Cuts smooth, accurate square holes in metal—bakelite—plastic—composition board etc. Complete with 1/2", 5/8", 1" punches—dies—drive screw, T handle and wooden case. Shpg. wt., 2 lbs. **MD-480** Net 6.95

2.98

JACOBS TYPE DRILL CHUCK

Comparable to Jacobs 18. Key type geared tooth chuck. Capacity 0-1/2". Thread 1/8" x 24. Ruggedly constructed.



Polished finish. Used as standard equipment on most electric drills. Made to rigid specifications. Compare our really low price. You'll find this same chuck selling for twice as much! Shpg. wt., 1 lb. **MD-186** Net 2.98


1.20

TUBING CUTTER

A quality cutter for copper, brass, or aluminum tubing. Provides up to 1" capacity. Equipped with alloy steel cutting wheel and slide-lock reamer. Ideal for light plumbing etc. Shpg. wt., 8 oz. **MD-346** Net 1.20



Vinyl Insulated "PROFESSIONAL" Pliers



- 10 Kilovolt Insulation
- Chrome Plated
- Tested Beyond Professional Specifications

Professional quality—heavy duty—forged from special heat treated, alloy steel. Chrome plated to resist rust. Insulated with fitted, vinyl, non-slit handle grips—protects up to 10,000 volts. Hand honed cutting edges. Machine milled teeth. Handles shaped for easy grip and maximum leverage. Short fulcrum distance for greater gripping power. Unconditionally guaranteed by Lafayette. Average Shpg. wt., 10 oz.


HD-350 Diagonal cutter-wire stripper
HD-351 Long nose-side cutter-wire stripper
HD-352 Electronic ablique cutter-wire gripper
HD-353 Long chain nose-side cutter-gripper
HD-354 7" Linesman's side cutters-beveled nose

1.29
YOUR CHOICE ea.



1.69 7 in 1 HOLE SAW

Fits any electric drill, drill press, motor arbor, rotary sander or lathe. Cylindrical saw blades cut holes from 1" to 2 1/2" diameter in any 1/2" stock. Hole sizes are 1", 1 1/4", 1 1/2", 1 3/4", 2", 2 1/4", 2 1/2". True size carbon steel saw blades fit into deep machined grooves in tool head and are locked into place by a full length lock screw. Cuts wood, plastics, metals, sheet-rock, wall-board, masonry, formico, etc. Has guide bit and automatic slug ejector. Shipping wt., 1 1/2 lbs. **MD-225** Net 1.69




NEW! RAM HI-TORQUE 1/4" DRILL

- Full 2.9 amperes
- Multiple Thrust ball bearings
- 1/4" Geared Chuck and Key

Powerful, cool-running drill for all medium-duty applications. Uses a heavy-duty universal type series wound motor for extra efficient performance. Motor works well on both AC and DC, 110-120 volts, permitting operation almost everywhere. Multiple heavy duty thrust ball bearings are used for smooth running even with large loads. Drill has a no-load speed of 2000 R.P.M., full load speed of 1200 R.P.M. Uses trigger-type on-off switch with locking pin for continuous operation, and automatic release feature. 1/2" capacity in hardwood, 1/4" in steel. Uses an extra rugged geared Jacobs chuck with 1/4" jaw. With 6 foot, 2 conductor UL approved cord. Overall length 9" Shpg. wt., 5 lbs. **MD-365** List 23.50 Net 13.95


SCREW-MATIC 3.97

- SCREWDRIVER ATTACHMENT FOR ELECTRIC DRILLS



Can be fitted to any fixed or portable drill, to drive up to 1/4" diameter wood screws quickly and easily. Bit idles until pressure is applied, powerful "non-slip" industrial-type clutch disengages itself when screw is driven home. Special bit holder prevents bit from slipping out of screw slot. Includes two hardened tool steel 1/4" hex bits for No. 2 Phillips head and for No. 6 to No. 14 slotted screws. Shpg. wt., 1 1/2 lbs. **MD-463** Net 3.97

ARCO JIG SAW 6.63




Cuts perfect circles any size up to 20" diameter; rips accurate widths any size up to 10" wide. An especially desirable home workshop tool because of its versatility. Does work at Jig, Keyhole, Coping, Rip, Crosscut, Band and Macksaw for intricate patterns, the Jig Saw is simply guided over the cutting line while the Automatic Air-Blower blows sawdust away from blade. Cuts plywood, plastics, wallboard, metals—even lumber up to 2 x 4's! Starts inside holes without boring. Has Right Angle Drive, strong Safety-Yoke and Worm Drive Clamp, Self-Lubricating Lifetime Bearings. Blades are easily changed in seconds with ordinary screwdriver. Shpg. wt., 3 lbs. **MD-56** Net 6.63

Same as above—with circle cutter and rip guide. **MD-196** Shpg. wt., 4 lbs. Net 7.30

Replacement Blades—Package of 6 Assid. **MD-157** Net 1.30

NEW! Knicknack CABINET


- 18 Drawers—each one 5 3/4" x 2 1/4" x 1 1/4"




COMPARABLE VALUE 6.98

Perfect storage for articles up to 6" long! Holds thread, pins, bolts, screws, nails, stamps, jewelry, cosmetics, fishing lures—hundreds of other items used in home, office or shop. Crystal clear transparent plastic drawers for "quick picking," cannot spill, yet instantly removable to carry to work area. Heavily molded of shatter-proof plastic maximum strength. Smooth sliding ribs molded into bottom assure easy opening and extra rigidity. Removable dividers make one drawer into three compartments. Welded steel cabinet stands, stacks or hangs on wall. Includes index labels, crosswise dividers. Cabinet measures 9" H x 10" W x 6" D. Shpg. wt. 8 lbs. **MC-32** Net 3.49

13 PC. TWIST DRILL SET 1.29




Set of 13 high quality chrome vanadium twist drills, complete with metal index. Sizes: 1/16" to 1/4" by 64ths. Shpg. wt., 8 oz. **MD-113** Net 1.29



1.66 ROTARY RASP

For use with any 1/4" electric drill or drill press. Made of hardened steel, it is ideal for shaping of wood, plastic, fibre etc.—planing of floors and boards—mixing of paints, oils and other heavy liquids. Extremely handy for the home craftsman, hobbyist, handyman etc. 2 1/4" in diameter. 13/16" wide. Shpg. wt., 1/2 lb. **MD-458** Net 1.66

BENCH AND WOODWORK VISES



SWIVEL CLAMP-ON VISE (A)

Sturdy, practical and efficiently constructed. 2 1/2" wide jaws—open to a maximum 2 1/2". Twin guide rods and precision drive screw assure smooth action—rigid grip. Jaws accurately machined, polished and lacquered. Unexcelled for ordinary jobs in shop, home or garage. Shpg. wt., 3 1/2 lbs. **MD-107** Net 1.99

NEW BENCH VISE (B)

Sturdy, practical and efficient. Twin 5/16" die bars assure versatile smooth action. A large "T" free action tightening bar is connected to drive screw. Set screw on vise permits removal of drive screw from vise body. Knurled tightening knob on clamp permits speedy clamping of vise. Screw parts are nickel plated, vise body is finished in baked enamel. Jaws are 1 1/2" wide and open to a maximum 1 1/2". Shpg. wt., 3 1/2 lbs. **MD-356** Net each 1.10

WOODWORKERS VISE (C)

- 6 1/2" x 3 1/2" JAWS
- OPENS TO 4 1/2"

A fine, practical tool for the small shop-home-form or garage. Guides are of finely machined cold rolled steel. Gray iron jaws—face ground and finished. 1/2" diameter screw—6 thread per inch. Shpg. wt., 6 lbs. **MD-182** Net 1.99

VINYL PLASTIC ELECTRICAL TAPE

- GUARANTEED FIRST GRADE 54¢
- 60 FT. x 3/4" in lots of 24
- .008 in. THICK
- 10,900 V. BREAKDOWN

First quality, pressure sensitive polyvinyl chloride tape. Extremely high dielectric strength of 10,900V breakdown. Insulation resistance of one million megohms. Over 150% elongation at break. Excellent resistance against acids, alkalis, oils, salt water, etc. Tensile strength of 15 lbs. per in. High conformability; forms tight, smooth protective wrap. Shpg. wt., 6 oz.

MD-216—Plastic electrical tape, 70¢ per roll; in lots of 6, 60¢ per roll; in lots of 24, 54¢ per roll.

LOCKING PLI-RENCH

Super power locking combination pliers, wrench, clamp and vise. Exerts over 1,000 lbs. of pressure. Heat treated, drop forged jaws. Machine milled teeth. Length 10". Shpg. wt., 1 lb. **MD-126** Net 1.20

"Little Smith" Anvil .98

"Little Smith" is the perfect companion for the hobbyist-tinkerer-model maker-or just plain faalin' arounder. Measures only 4 1/2" x 2 1/2" x 2 1/2" overall. Rugged enough for heavy pounding-sized right for home or hobby. Makes a perfect paper weight for the craftsman's bench or desk. Shpg. wt., 2 lbs. **MD-460** Net .98

TWINWELD EPOXY ADHESIVE



- Attach Anything to Anything—Anywhere
- Steel-hard permanent repairs in minutes
- Won't shrink—can't expand
- Can be shaped—cast—drilled—sawed—sanded

An advanced, flexible epoxy formulation. Engineered for permanent adhesive use for metal-wood-glass-ceramics-concrete-hard rubber-fiberglass-brick-and many other materials. Quick, easy, professional repairs. Mends anything. Ideal production line "filler." Can be molded to any shape—no sagging or draping—perfect for duplicating and shape-making. Use as a "roof-holder"—as coating or filler—as a gasket—as caulking—as a dielectric. Chemically and dimensionally stable. Safe—no solvents. Non-toxic, non-allergenic. Shpg. wt., 1 lb. **MD-685** Net 1.49

SAW DRILL

.39

- Starts own hole
- Saws in any direction
- Any shape hole

Quickly and easily saws any shape hole in wood, plastic, plaster, wall board, plywood, etc. Gimlet tip starts hole—"teeth" cut quickly in any direction. Drills—roots—enlarges holes. Does the work of a drill and a keyhole saw on many jobs. Shpg. wt., 4 ozs. **MD-679** Net .39

Ratchet Head SOCKETOOL 2.25



Amazingly versatile! Handles carriage bolts, machine bolts, lag screws, sheet metal screws, machine screws, wood screws, cap screws—any style of head—slotted, recessed, square or hex. Operates in straight or offset position—handy for hard-to-reach places. Universal ratched head works right, left or locks—speeds and simplifies any job! Contains Shelton suregrip ratchet handle; straight hex adapter; offset hex adapter; 5 hex sockets—7/16", 3/8", 11/32", 5/16", 1/4"; 3 square sockets—7/16", 3/8", 5/16"; tool steel screwdriver bit for slotted screws; tool steel screwdriver bit for recessed head (Phillips) screws. A fine small tool set, ruggedly constructed for hard usage. Complete in durable plastic case. Shpg. wt., 1 lb. **MD-451** Net 2.25

20 PC. AUTO SOCKET SET 2.79

Ideal for auto or home. Contains 8 regular 12-point sockets—7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 7/8", and 15/16"; 1/2" drive hex. L handle, 1 ratchet handle, 1 screwdriver adapter; also 7 ignition sockets—1/4", 5/16", 11/32", 3/8", 7/16", 1/2", and 5/8" internal knurled socket; 1/2" drive hex. L handle. All parts are properly heat treated and nickel-plated. Mounted in red wall bracket. Shpg. wt., 3 lbs. **MD-446** Net 2.79

20-PIECE TAP AND DIE SET

- NATIONAL COARSE SIZES

Twenty of the most often needed taps and dies. Sizes popularly used in radio, hobby, home, shop and light industry. Contains one tap and one die in each of the following sizes: 6-32, 8-32, 10-24, 12-24, 1/4"-20, 5/16"-18, 3/8"-16, 7/16"-14, and 1/2"-13. Includes die stock and adjustable tap wrench. Entire set contained in a fitted metal case. Shpg. wt. 4 lbs. **MD-252** Net 5.59

RAM "88" 7" POWER SAW 27.95



- 1 1/4" HP MOTOR
- 8 AMPS
- 4500 RPM
- FREE SPEED
- CUTS 2 1/8" DEEP
- 7" BLADE

Top value for the home craftsman with features hitherto unheard of at this price. Newly designed model features a powerful 1 1/4 horse-power motor with self lubricating Moly Sulphite bearings. 7" blade diameter, 3/8" round arbor hole. Cuts to a depth of 2-7/16". Angle of cut can be adjusted from 0° to 45°, with depth of cut of 2 1/8" at 45°. No load motor speed 4500 R.P.M. This rugged but lightweight saw is designed for effortless one-handed operation. For 110-120 volts DC or 50-60 cycle AC. Lustrous mirror finish. Combination rip and cross-cut blade and rip-guide included. UL approved. 3 conductor cord. Shpg. wt., 15 lbs. **MD-359** Saw—List 49.98 2.00 Down Net 27.95

SAW TABLE. Perfect complement to the "88" Saw. Allows cutting at any angle between 45° and 90°. Complete with miter gauge and rip fence. Shpg. wt., 12 lbs. **MD-360** Saw table, List 17.50 Net 11.65

COMBINATION OFFER. Consists of the MD-359 saw and MD-360 saw table, at a further saving in price. **MD-364** Saw and Table 2.00 Down Net 36.90

COMBINATION BLADE for up or crosscut work. **MD-361** Shpg. wt., 1 1/2 lbs. Net 1.69

FLOORING CUT-OFF BLADE for smoother crosscut than combination blade. **MD-362** Shpg. wt., 1 1/2 lbs. Net 1.69

PLANER BLADE will cut off, mitre, and rip smooth enough to eliminate sanding. **MD-363** Shpg. wt., 1 1/2 lbs. Net 4.13

SAVE UP TO 75% ON LAFAYETTE RADIO PARTS

PORCELAIN CASED TUBULAR CAPACITORS

New

Greatest Condenser Value Ever Offered!

KIT OF 100 600V W V DC			KIT OF 50 600V W V DC		
QTY	MFD	NET	QTY	MFD	NET
10	.001	.001	5	.001	.001
10	.002	.002	5	.002	.002
10	.005	.005	5	.005	.005
10	.01	.01	5	.01	.01
10	.02	.02	5	.02	.02
10	.05	.05	5	.05	.05
10	.1	.1	5	.1	.1

KIT NO. KI-52 KIT NO. KI-51
List Value \$2.00 List Value \$1.00
4.95 **2.75**
SPECIAL NET SPECIAL NET

• TESTED AT 3 TIMES WORKING VOLTAGE
• EXCEPTIONALLY RESISTANT TO HIGH TEMPERATURES AND MOISTURE
• SURPASSES PERFORMANCE OF MOLDED PLASTIC TUBULARS

They're new, they're different, and they're better! New, at a price for less than that of ordinary plastic molded tubulars, Lafayette brings you, for every day service work, a condenser that was designed for critical industrial applications. The case is of durable gleaming porcelain, a ceramic known for its high degree of imperviousness to moisture and resistance to heat. The capacitor is of finest quality, tested at 3 times the rated voltage with much closer capacity tolerance. It maintains its characteristics under extreme conditions of heat and humidity. Its mechanical construction is excellent, the leads are firmly attached and sealed — they won't twist or break off. We've selected the most popular values and put them up in two service-man designed kits. Each condenser is plainly marked. Each value is mounted on separate handy strips. All are conservatively rated at 600 DC working volts. See chart for contents of each kit.

KI-51 ... Kit of 50 2.75
KI-52 ... Kit of 100 4.95

HEAVY DUTY 10 AMP DPDT MOTOR SWITCH

• MOLDED PHENOLIC CASE **79¢**
• METAL FACE PLATE

Workmanship on this switch is of the best quality. Terminals are oversized, flow-free solder type which makes for neat, no-arc connections. Rated 10 Amps at 125 Volts, contacts easily take the current surges of motor starting. Size 1 1/2" x 1 1/2" x 1". Bushing 7/16" dia., 3/8" long, bot handle 3/4" long. Shpg. wt., 6 oz. Net .79
SW-26 DPDT Toggle Switch In lots of 10, Each .75

MIDGET-BAKELITE KNIFE SWITCHES

Compact switches mounted on a black bakelite base with insulated knob handle of black bakelite. Plated brass contacts provide positive low-resistance connection.

SPDT KNIFE SWITCH
Overall size 1 1/2" x 2 3/4". Shpg. wt., 6 oz. Net .12 ea. — 10 for .99
SW-23

DPDT KNIFE SWITCH
Overall size 1 1/2" x 2 3/4". Shpg. wt., 4 oz. Net .19 ea. — 10 for 1.75
SW-24

INSULATED ALLIGATOR CLIP

7c **20 for 1.17**

Sturdy nickel-plated brass jaws with plastic insulated thumb rest and insulated barrel. Strong spring with hard bite. Solder lug connection. Overall length 2 1/4". Shpg. wt., 4 oz. Supplied in Red and Black.

MS-451—Red Alligator Clip Net Ea. .07
MS-452—Black Alligator Clip 20 for 1.17

A FABULOUS BUY! GENUINE 100 and ALLEN-BRADLEY Resistor Kit

100 INSULATED RESISTORS
with **PLASTIC HINGED BOX!**

10% TOLERANCE
1/2 Watt RMA Color Coded

QUANT.	OHMS
3	100
4	470
4	1,000
3	2,200
4	4,700
5	10,000
4	22,000
4	27,000
4	33,000
4	47,000
10	1 meg
4	15 meg
4	27 meg
10	47 meg
10	1 meg
4	2 meg
20	Other popular values

Lafayette leads the field with a genuine Allen Bradley and IRC 1/2 watt, 10% tolerance, molded resistor kit with a Transparent Plastic Utility Box (built in partitions) size: 8 1/2" x 4 1/2" x 1-3/16". The finest resistors on the market. Molded insulated composition resistors. Meet JAN-R-11 specifications, including salt water, immersion and high humidity tests.

Stock No. KI-23—Total 100 molded resistors with Transparent Plastic Case. **NET 4.50 100 TOTAL**

\$4.50

LONG SHAFT CONTROL WITH SWITCH

Famous Brand Each .49
Lots of 10 Each .39

VC-10, 1 Meg. } AUDIO TAPER
VC-11, 1/2 Meg. }

LAFAYETTE METAL CASED OIL FILLED TUBULAR CAPACITORS

New!

• Exceptional capacitance stability
• 10% Tolerance
• High insulation resistance
• Wide temperature range

These oil-filled and oil impregnated paper capacitors are manufactured to high standards. Features 10% tolerance. Operates efficiently from -40°C to +100°C. Ruggedly constructed in metal case with plastic insulating outer sleeve to withstand shock, voltage surge, moisture, and other adverse operating conditions. Has low dielectric leakage, low power factor and exceptional capacitance stability. Lightweight compact, made to render long servicing life. Ideal for replacement and original applications in radio, TV and other electronic equipment. Outside foil is clearly printed. Doubly tinned copper-weld type leads are firmly attached to the case. Conservatively rated at 600 WVDC. Ave. shpg. wt., 5 oz. each.

TYPE	CAP MFD	SIZE D X L	NET		EACH	
			SINGLE	Lots of 10	Lots of 100	
C-800	.001	9/32 x 26/32"	.09	.81	7.00	
C-801	.002	9/32 x 26/32"	.09	.81	7.00	
C-802	.005	9/32 x 27/32"	.09	.81	7.00	
C-803	.01	9/32 x 27/32"	.10	.90	7.90	
C-804	.02	10/32 x 27/32"	.11	.99	8.50	
C-805	.05	13/32 x 1"	.12	1.08	9.50	
C-806	.1	15/32 x 1 1/16"	.14	1.26	11.40	

HEAVY SHIELDED PHONE PLUGS AND JACKS

(A) Sturdy, heavy brass, nickel-plated phone plugs with screw terminal connections. Threaded insulated cable outlet may be removed for larger cables to pass through. Body dia. 3/4", overall length 3 1/4". Shpg. wt., 4 oz. Net ea. .59 10 for 5.30
MS-534 Plug

(B) Matching in-line phone jack, same construction as plug. Overall length 2". Net ea. .55 10 for 4.95
MS-533 Jack

INSULATED ALLIGATOR TEST CLIPS WITH 6 FT. LEAD

Handy for quick connections. Plated brass alligator clip with insulated handles and 6 ft. of No. 22 stranded wire attached. Clip is 1 1/2" overall. 50 for 3.25 10 for .72
MS-536 Red MS-537 Black

PHONE PLUG TO PHONO JACK ADAPTER

Brass, nickel-plated adapter. Has standard phone jack on one end to take regular phone plug, and RCA-type phono plug on other end. Has threaded bushing with nut and washer to can be panel mounted if desired. Shpg. wt., 4 oz. Net .52
MS-535

LAFAYETTE SPECIAL 2-CONDUCTOR PHONE PLUGS

Phone plugs for a wide variety of applications with choice of handle sizes and materials. All sleeves fit standard 1/4" phone jacks.

FIG. A. SLIM PHONE PLUG Smooth bakelite handle. Solder terminals with cable clamp. Net .25 ea. — 10 for 2.15
MS-453

FIG. B. BARREL PHONE PLUG Ribbed plastic barrel handle. Screw terminals. Net .24 ea. — 10 for 2.10
MS-455

FIG. C. SHIELDED SLIM PLUG Ribbed chromed metal handle. Solder terminal with cable clamp. Net .33 ea. — 10 for 2.95
MS-443

FIG. D. PHONE TO PHONO PLUG ADAPTER Adapts from standard phone plug to RCA type phono plug. Overall length 2 1/2" x 1/2" diam. Net .39 ea. — 10 for 3.25
MS-444

STANDARD PHONE JACKS FOR 1/4" PLUGS

FIG. E. OPEN CIRCUIT JACK Standard open circuit phone jack, 1/4" bushing, 1/2" long. Complete with mounting hardware. Net .19 ea. — 10 for 1.75
MS-441

FIG. F. CLOSED CIRCUIT JACK Same as above but closed circuit phone jack. Net .19 ea. — 10 for 1.75
MS-454

FIG. G. OPEN CIRCUIT JACK Open circuit jack for 3 conductors. Net .29 ea. — 10 for 2.90
MS-318

FIG. H. EXTENSION CABLE JACK Fit standard 1/4" phone plug. Screw terminals. Barrel plastic handle matches MS-455 barrel plug. Net .22 ea. — 10 for 1.90
MS-442

NEW! sub-miniature TRANSISTOR AUDIO TRANSFORMERS

ONLY 79¢

• Input, Output and Driver Transformers
• Only 1/2" x 1/2" x 1/2"

A new series of miniature transformers for transistor and experimental miniature circuits. Ideal for miniature radio receivers, amplifiers, hearing aids, etc., using standard transistors. Incorporate special heat-treated high permeability magnetic cores and treated to resist corrosion. Designed for improved frequency response with low distortion. 3" color-coded leads. Average shpg. wt., 4 oz.

TR-97 INPUT TRANSFORMER—Primary impedance 100,000 ohms; secondary 1000 ohms; DC resistance primary 1000 ohms; secondary 100 ohms. Net .79

TR-98 DRIVER TRANSFORMER—Primary impedance 10,000 ohms; secondary 2000 ohms, center-tapped; DC resistance of primary 240 ohms; secondary 60 ohms, center-tapped. Net .79

TR-99 OUTPUT TRANSFORMER—Primary impedance 500 ohms center-tapped; secondary 3.2 ohms. Primary DC resistance 42 ohms, center-tapped; secondary 0.7 ohms. Net .79

Precision VERNIER DIALS

NEW!

Precision planetary drive vernier dials with approximately 8 to 1 ratio. Mounts on panel surface and has accurately centered metal inserts for 1/4" shafts. Metal dials are brushed silver finish with deeply etched and black filled engraving to provide maximum legibility even under poor lighting conditions. Reads counter-clockwise 0 to 100 in 180°. Uses tough scratch resistant for sure grip fluted molded knob and housing. Phosphor bronze and brass utilized for internal parts. Shpg. wt., 8 oz.

F-346 36MM (1 1/2") Diameter Vernier Dial, 13/16" from front to back Net .95
F-347 50 MM (2") Diameter Vernier Dial, 1" from front to back Net 1.25
F-348 70MM (2 3/4") Diameter Vernier Dial 1 1/4" from front to back Net 1.49

LAFAYETTE SPECIAL BARGAINS

BUDGET UNIVERSAL TEST LEAD KIT IN PLASTIC CASE

This kit consists of color coded 4 1/2" long x 3/8" dia. red and black plastic handle pin prods with heavy duty 37" knittless rubber leads with 5000 v breakdown insulation terminating in coded 2" long x 3/8" dia. plastic grip banana plugs. 3 sets of interchangeable terminals are included. They all slip directly on to the banana plugs. They are spade lug terminals, phone tips and red and black insulated alligator clips. These items have their own handsome and handy compartmentalized flexible plastic case which snaps shut. Shpg. wt., 1 1/2 lbs. Net .77
F-373

TEST LEADS

Standard test leads furnished with plastic prods and pin plugs which withstands chipping or breaking. Extra flexible knittless vinyl covered 60" red and black leads. Prods are red and black. 4" long x 3/8" diameter. Supplied in pair of one red and one black. Shpg. wt., 8 oz.

F-344 Test Leads With Banana Plugs Net .39
F-345 Test Leads With Pin Plugs Net .39

SINGLE POLE SINGLE THROW TOGGLE SWITCH

22¢ • BALL HANDLE

Ball handle S.P.S.T. toggle switch in molded bakelite case. Rated 3A-125 Volts. Supplied with chrome metal on-off indicator plate and two mounting nuts. Body size 1 1/2" x 3/4" x 1/2" behind panel. Bushing 7/16" diam., 7/16" long. Ball handle 1/2" long. Shpg. wt., 4 oz. Net .22
SW-21 SPST Toggle Switch In lots of 10, Each .19

Miniature PUSH BUTTON SWITCH

19¢

Momentary contact push button switch ideal for all miniaturized applications. Single pole two circuit push-to-make type. Beryllium copper leaf contacts. Overall diameter 1/2", overall depth 11/16", protrudes 3/8" behind panel. Bushing 1/4" dia., 3/16" long. Supplied with washer and mounting nut. Shpg. wt., 3 oz. Net .19
MS-449 Miniature Push Button Switch

LAFAYETTE JUMBO 5-WAY BINDING POST

25¢

Accepts phone tip plug, a spade lug, a banana plug, an alligator clip and a strand of wire. Head non-removable from stand. Molded plastic construction. For panels 1 1/2" to 1/4" thick. In either red or black color; specify. Net Ea. 25¢
PJ-37—Shpg. wt., 8 oz.

HEAVY DUTY 6 AMP DPDT SWITCH

32¢ A TERRIFIC BUY!

Heavy duty bot handle toggle switch in enclosed bakelite case — ideal for hundreds of applications. Rated 250V-3 amps or 125V-6 amps. Six solder lug terminals. Comes with chrome metal on-off indicator plate and mounting nuts. Switch body 1 1/2" x 3/4" x 3/8" behind panel. Including terminals. Bushing 15/32" dia., 7/16" long. Bot handle 1/2" long. Shpg. wt., 6 oz. Net .32
SW-22 DPDT Toggle Switch In lots of 10, Each .29

HEAVY DUTY 6 AMP DPDT CENTER OFF TOGGLE SWITCH

49¢ SPECIAL!

Heavy-duty double-pole double-throw for control of lighting circuits, high power p.a. horns, electrical appliances and motors. Rated at 6 amps 125 volts AC or 3 amps 250 v. AC. Metal on-off indicator plate and mounting nuts. Switch body 1-5/16" x 1 1/4" x 1" behind panel. Including terminals. 7/16" bushing, 7/16" diam. 3/8" bot handle. Shpg. wt., 8 oz. Net .49
SW-19 In lots of 10, Ea. .45

HEAVY DUTY 10 AMP SPDT CENTER OFF TOGGLE

This heavy duty switch is ideal for small size equipment. Heavy silvered lugs for low-loss connections. Rated 10 amps at 125 volts. Body size 1 1/2" x 9/16" x 3/8" depth behind panel. Bushing 3/8" dia., 7/16" long. Bot handle 1/2" long. Shpg. wt., 4 oz. Net .39
SW-27 SPDT Toggle Switch In lots of 10, Each .35

RUGGED TELEPHONE TYPE 4PDT LEVER SWITCH

ANOTHER LAFAYETTE BUY! 69¢ EA.

Small 3-position lever action telephone type switch of rugged non-inductive construction, perfect for large intercom switching panels, test equipment, model railroad control panels, communications systems, etc. Has 4 sets of single-pole, double-throw contacts. Chrome-plated actuating cam has 3 locking positions and stays put in each position. (Switching action is shown in accompanying schematic diagram.) Black insulated lever handle. Heavy All contacts easily demountable for making connections. If necessary. Mounts to panel with 2 screws (furnished). 15/16" mounting centers. Size 2 1/2" long behind panel, 3/4" wide, 1-5/16" high. Shpg. wt., 6 oz. Net .69 Ea.
SW-20 3-Position Telephone-Type Switch In lots of 10, .69 Ea.

SERVICEMEN AND DEALERS! LOOK AT THESE PRICES!

LAFAYETTE COMPLETELY WIRED TEST EQUIPMENT

SENSATIONAL VALUES AT LESS THAN THE PRICE OF KITS!

NEW! POCKET AC-DC VOM

5.45

• EXTREMELY COMPACT, MEASURES ONLY 3 7/8" x 2 1/8" x 1". WEIGHS 5 OZS. • 1,000 OHMS PER VOLT SENSITIVITY • COMPLETELY WIRED (NOT A KIT) • 1% PRECISION RESISTORS • READS 0-1000 VOLTS AC-DC 0-100KΩ, 0-150 MA

Here's the best test equipment buy in America. Lafayette's new, pocket multimeter features an unbeatable combination of small physical size, and a wide selection of useful ranges. It can be used for troubleshooting any type of electronic circuit or electrical appliances such as irons, lamps, radios, television, hi-fi equipment etc. It is also useful for testing complex electrical circuits, such as those found in automobiles, and around the home shack. Extreme portability allows unlimited usage either at home or in the field.

1000 ohms per volt sensitivity, and 1% precision resistor components assure accurate, precise readings. Operation is extremely easy, simply plug the leads into the desired scale, and you are ready to go, no switching or fiddling required. Ranges: Volts, 0-15-150-1000 AC and DC, Ohms, 0-1000K MA, 0-150. The VOM comes completely wired and tested, and is enclosed in durable plastic case. All accessories including battery and rubber insulated, color coded, flexible test leads are supplied. Shpg. wt., 1 lb.

TE-13 AC POCKET VOM Net 5.45

New! MINIATURE POCKET MULTITESTER

ONLY 17.50

- 20,000 Ω/v DC SENSITIVITY
- 10,000 Ω/v AC SENSITIVITY
- 1% RESISTORS
- WEIGHS ONLY 10 oz.
- 38 μA MOVEMENT
- 23 RANGES
- COMPLETELY WIRED



A terrific bargain in an all-round extra sensitive multimeter. Here is the ideal all-purpose multimeter for troubleshooting anything electrical or electronic — can be used for repairing automobile wiring, checking ordinary household appliances, such as irons, heaters, and motors; troubleshooting complex electronic equipment in the home, in the shop or in the field. Ideal for TV sets, home radios, high-fidelity sets, amateur gear, commercial communications equipment — wherever a truly portable unit is required. This is a completely wired precision instrument, NOT A KIT. Uses a sensitive, rugged 38 microampere basic meter, a d'Arsonval movement with jewelled bearings providing easy, accurate read-off from its large, clear scales. 2 1/2" meter face. 1% precision resistors guarantee top-notch accuracy. This unit weighs only 10 oz., measures only 4 3/4" x 2 1/4" x 1 1/4" — fits into pocket without bulging, without weighing down. The entire front is protected by a thick, clear sheet of plastic, preventing scratching

and eradicating of switch markings, protecting your meter and preserving its appearance. Single selector switch with positive detents and clearly marked positions permits one-handed operation. Recessed, break-proof zero-ohms knob permits easy adjustment, yet cannot be broken even under rough handling.

Has 23 ranges at the unusually high sensitivities of 20,000 ohms per volt DC, 10,000 ohms per volt AC; DC Volts, 0-5-25-100-500-1000; AC Volts, 0-5-25-100-500-1000; OHMS, 0-6K-600K-6 Meg-60 Meg; DC MILLIAMPERES, 0-.05 (50 microamps) -.5-50-500; DECIBELS, -20 to +64 in 5 ranges.

Truly a superb instrument for any application. Complete with 1.5 volt and 15 volt batteries, and vinyl insulated flexible test leads. Shpg. wt. 1 lb.

AR-660 MINIATURE POCKET VOM Net 17.50


20,000 OHM PER VOLT MULTITESTER SEMI-KIT

A New Kind of Kit

THE DIFFICULT WORK IS ALREADY DONE

- 20,000 OHMS PER VOLT DC
- 10,000 OHMS PER VOLT AC
- 40 MICROAMPERE 3" D'ARSONVAL METER MOVEMENT

ONLY 11.95



The semi-kit is a new concept in test equipment kits. All the important or difficult parts are already mounted. All that remains to be done is to mount and wire in a few small parts — a job so simple you'll finish before you realize it, and best of all, you'll have one of the finest high sensitivity multimeters on the market. When used in a circuit, the high input resistance on all DC and AC ranges does away with the highly inaccurate readings

common to low resistance testers which load the circuit. Ranges: DC Volts, 0-10-50-250-500-1000; AC Volts, 0-10-50-250-500-1000; DC CURRENT, 0-500 μa, 0-10-250 ma; OHMS, 0-10K-100K-1 meg, DECIBELS, -20 to +36; PLUS 0-5000 henries and 250 mhf. to .02 mfd. Block case 5 3/4" x 3 3/4" x 1 3/4". Complete with test leads, all parts, and instructions and battery. Shpg. wt. 3 lbs.

TK-10 KIT Net 11.95

A LAFAYETTE SPECIAL TUBE TESTER!

COMPLETELY WIRED — NOT A KIT
• MOST ADVANCED ENGINEERING TO FIT SERVICEMAN'S NEEDS



26.95

A new streamlined tube tester with a realistic approach to the problem of quickly testing the ever increasing number of tube types. It incorporates new and advanced engineering features and all at a price of about half of even the most ordinary tube tester. Read these Specifications.

"FREE POINT" ELEMENT SELECTOR SWITCHING: Newly designed, it reduces possibility of obsolescence to a minimum because any pin may be used as a filament pin and voltage applied between it and any other pin, or even the "top cap." Tubes with topped filaments or with filaments terminating in more than 1 pin are truly tested.

MULTIPURPOSE TUBES: Special isolating circuit allow each section of multi-purpose tubes to be tested individually as if it were in a separate envelope.

SHORTS AND LEAKAGES: Supersensitive method checks shorts and leakages up to 5 megohm between any and ALL elements; continuity between various sections individually indicated.

SIMPLICITY: Fast simple operation. The 4 position fast action snap switches are all numbered in exact accord with RMA standards. Thus when testing element terminating in pin No. 7 of a tube — you use button No. 7. You can't insert a tube in the wrong socket — there's one for each type of tube base.

TUBE TYPES: Tests all octal, loctal, 7 pin miniatures, 9 pin miniatures as well as the new novel and Sub-Minor types. Old type sockets used for testing obsolete types — that you rarely see anymore — have been eliminated.

SIZE: A practical size to carry with you as well as for use in the shop — only 8 3/4" x 6 3/4" x 2 1/4" deep. Shpg. Wt. 5 lbs.

MODEL TD-55 — complete with carrying case and instructions. 2.00 Down 26.95

NEW! 20,000 OHMS PER VOLT MULTITESTER

20,000 OHMS PER VOLT DC
10,000 OHMS PER VOLT AC
40 μA MOVEMENT
1% RESISTORS 17.95



A new high-quality, low-priced multimeter. Its light weight makes it a perfect portable instrument for technicians, servicemen, etc. Rugged design withstands hard use. Features large easy-to-read meter and sensitive 40 microampere meter movement. 1% tolerance resistors provide extreme accuracy of measurements. Housed in rugged bakelite case. Single knob selector and clearly marked positions permit easy operation. Recessed zero-ohms knob adjustment provided.


Features sensitivity of 20,000 ohms/volt DC, and 10,000 ohms/volt AC. Ranges — DC volts: 0-0.6, 0-6, 0-30, 0-120, 0-600, 0-1200, 0-3000, 0-6000 volts. AC volts: 0-6, 0-30, 0-120, 0-600, 0-1200 volts. Resistances: RX1, RX10K, RX1K, RX10K. DC currents: 0-0.06, 0-6, 0-60, 0-600 ma. Decibels: -20 to +17 (0 db = 0.774 V). Capacity: .0001-.01, .005-.20 mfd. Output ranges: 0-6, 0-30, 0-120, 0-600, 0-1200 volts.

Complete with color-coded heavy duty test probes and battery. Size: 6 x 3 3/4" x 1 1/4". Shpg. Wt., 1 1/4 lbs.

TE-12 Net 17.95

EDGE-WISE PANEL METERS

- 2% FULL SCALE ACCURACY
- PRECISION D'ARSONVAL MOVEMENTS
- FRONT PANEL AREA ONLY 3 3/4" x 1"



Precision D'Arsonval meters with 2% or better full scale accuracy. Front panel dimension is 3 3/4" x 1". Overall depth is 3 3/4" behind panel including terminals. Zero adjust screw. Shpg. wt., 1/4 lbs.

VU METER — Calibrated and damped in accordance with standard VU meter practice. Upper scale reads -20 to +3 VU. Lower scale reads 0-100% modulation. Accuracy to ±0.5 VU from 30-15,000 cps.

TM-23 Net 5.95

0-150 AC VOLTMETER — Full-wave bridge rectifier type. 1000 ohms per volt. 5 volts per division, linear scale.

TM-22 Net 5.69

0-1 DC MILLIAMMETER — CALIBRATED from 0-1 m to 0.02 ma. divisions. Black scale, red pointer.

TM-21 Net 5.69

NEW! LAFAYETTE PANEL METERS

• HIGH QUALITY D'ARSONVAL MOVEMENTS • ACCURACY 2% OF FULL SCALE • BAKELITE CASES • JEWELLED BEARINGS • UNUSUALLY LOW PRICED FOR SUCH EXCELLENT QUALITY. High Quality, precision-built meters with better than 2% of full scale accuracy. Screw terminals with polarity on DC Models clearly marked. Zero adjustment screw on front of panel.

SQUARE PANEL METERS

3 3/4" square meters with overall depth of 1-11/16", including terminals. Requires 2-9/16" diameter mounting hole, 4 threaded mounting studs in corners. Shpg. wt., 1 lb.

ILLUMINATED SCALE VU METER

CLEAR PLASTIC FRONT METER — Standard 3900 ohm "B" scale volume indicator calibrated and damped in accordance with standard VU meter practice. Upper scale reads 0-100% modulation, lower scale reads -20 to +3 VU (0 VU corresponds to 100%) Accurate to ±0.2 VU from 35-1000 cps, ±0.5 VU from 30-15,000 cps. With suddenly applied sine wave signal, meter will reach 99% of correct reading within 0.3 seconds; overshoot beyond correct reading is 1 to 1 1/2%. A root-mean-square instrument with full wave bridge rectifier. Includes built-in 6-8 volt bulb. Complete with instructions.

TM-80 Net 7.50

0-50 DC MICROAMMETER

0-50 DC MICROAMMETER — Highly damped, sensitive movement, calibrated in 50 one-microamp linear scale divisions. Cushioned ceramic bumpers protect pointer against overtravel and damage with moderate overloads. Red pointer.

TM-70 Net 7.50

0-1 DC MILLIAMETER

0-1 DC MILLIAMETER — Sensitive, quick-acting basic movement. Linear calibrations in .02 ma. divisions. Black scale, red pointer.

TM-60 Net 3.95

0-150 AC VOLTMETER

0-150 AC VOLTMETER — Full-wave bridge rectifier type. 1000 ohms per volt. With precision carbon-film multiplier resistor. 5 volts per division, linear scale.

TM-50 Net 3.95

METER RECTIFIER

A brand new, economical meter rectifier of exceptionally linear characteristics. This full wave rectifier is specially designed as a universal replacement for all modern multimeters, such as Lafayette's miniature V.O.M.'s. Simple to install, mounts with single screw. Long terminals facilitate easy connection.

RE-22 Net .45

MINIATURE PANEL METERS

Rugged miniature panel meters, 1-9/16" square faces, 1 1/2" deep overall. Require 1 1/2" diameter mounting hole, 4 corner mounting holes. Silvered dials and black numerals and pointer. Shpg. wt., 8 oz.

VU METER

VU METER — Volume level indicator, calibrated in standard -20 to +3 VU and 0-100% ranges. Uses precision carbon film multiplier resistor and full wave rectifier. Damped in accordance with standard VU meter requirements. Reference level 1 mw in 600 ohm line. 10,000 ohms internal resistance. "0" VU is 1.225 volts sine wave AC across meter connected to 600 ohm source with 600 ohm load. May be used with T-pad attenuator. 0-100% scale used to indicate percent use of transmitter output.

TM-10 Net 3.95

"S" METER

"S" METER — Standard "ham" signal strength indicator. Calibrated in "S" units from 0-9, with the scale terminating in +10 and +30 db calibrations. Additional full scale calibrations of 0-5 and 0-10 in linear scale divisions. A "must" for radio amateurs for conversion of any communications receiver with AVC action to give calibrated signal strength indications. Use of "S" meter fully described in 1958 "Radio Amateur's Handbook" (Lafayette stock No. BK-1000), pages 206-207 Catalog 600.

TM-11 Net 3.95

DC MILLIAMMETERS

TM-400	0-1 DC	MILLIAMPERES	Net 3.75
TM-401	0-5 DC	MILLIAMPERES	Net 3.75
TM-402	0-50 DC	MILLIAMPERES	Net 3.75
TM-403	0-100 DC	MILLIAMPERES	Net 3.75

DC MICROAMMETER

TM-200	0-50 DC	MICROAMPERES	Net 4.95
--------	---------	--------------	----------

AMMETERS

TM-510	50-0-50 DC	AMPERES	Net 3.95
TM-511	0-10 DC	AMPERES	Net 3.95

R.F. AMMETER


TM-500	0-5 RF	AMPERES	Net 3.95
--------	--------	---------	----------

VOLTMETERS

TM-100	0-15 DC	VOLTS	Net 3.75
TM-101	0-200 DC	VOLTS	Net 3.75
TM-300	0-150 AC	VOLTS	Net 3.75
TM-301	0-300 AC	VOLTS	Net 3.75

FAMOUS RCA VOLTOHMYST IN KIT FORM

NEW!



ONLY 29.95!

49.95
Wired

ONLY 2.00 Down

- BURNOUT-PROOF!
- 28 RANGES
- FAMED WV-77E VOLTOHMYST VTVM
- ± 3% ACCURACY ON DC
- RESPONSE ± 5%, 40 CPS to 5 MC.
- DC INPUT 11 MEG.

This new kit makes possible substantial savings in a high quality vacuum-tube voltmeter. Its 28 ranges include 7 DC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with ± 3% of full scale accuracy and input resistance of 11 megohms; 7 rms AC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with ± 5% of full scale accuracy; 7 peak-to-peak AC voltages: 0-4, 14, 40, 140, 400, 1400, 4000 volts, with 5% accuracy; 7 overlapping ohms ranges from 0.2 ohms to 1000 megohms with center-scale values of 10, 100, 1000, 10K, 100K, 1 meg, and 10 meg. ohms. Other important features include zero-center for discriminator alignment; frequency response of 40 cps to 5 mc. flat to within ± 5% on the 1.5 to 15 volt rms and 4 to 40 volt p-p ranges; 1% deposited-carbon resistors; meter electronically protected against burnout and ohms ranges fused; cables can be stored in sleeve on handle; meter scales color coded to match range switch; shielded by metal case; and etched front-panel lettering. Tubes are 6AL5 and 12AU7. Power requirement is 5 watts at 105-125 v., 50-60 cps AC and VS035 battery. Supplied complete with DC and AC/ohms probes and cables and ground leads, battery, and instruction book. Shpg. wt., 5 1/2 lbs.

TE-141 RCA WV-77E(K) KIT 2.00 Down Net 29.95

WV-77E Same, completely wired and factory-calibrated

TE-142 2.00 Down Net 49.95

NEW!




NEW!



A GALAXY OF LAFAYETTE'S SUPER VALUES

PRECISION PLIER SET



- Jewelers Types
- Full polished chrome plated
- Insulated handles


3.89

Matched set of precision pliers for the technician-hobbyist-model maker-craftsman. Particularly suited to miniature electronic work. Size and handle shape matched for accuracy, exacting work. Overall length approximately 4 1/2". Set includes combination side cutters—flat nose—horn nose—round nose—round/flat nose—diagonal cutters—and cutting nippers. All have insulated, cushioned handles. Drop forged from tool steel. Preselected types for a diversity of use. Extra heavy, poly-vinyl, roll up case. Clear view pockets. Can be rolled for easy carry—or hang above bench. Shpg. wt., 1 lb. 6 ozs. **HD-681**

Net 3.89

2 in 1 EYELET TOOL

- PUNCHES HOLE — SETS EYELET AT SAME TIME
- COMPLETE WITH 300 EYELETS



.99

Neatly — easily — punches holes and sets eyelets in fabric — canvas — plastic — leather — paper — cardboard. Does a professional looking job every time. Use it on belts, shoes, sneakers, tarpaulin, luggage, sports equipment, flags, banners, shower curtains. Prevents tearing of materials — actually strengthens them. Hundreds of uses for everyone — everywhere. Complete with 300 assorted eyelets and instructions. Shpg. wt., 1 lb. **HD-668 EYELET TOOL** Net .99
HD-669 EXTRA EYELETS—Pkg. of 300 Net .29

NOVATRON NEW! A SCIENTIFIC INSTRUMENT FOR THE EXPERIMENTERS...

- MINIATURE ATOM SMASHER
- PRODUCES 75,000 VOLTS
- ABSOLUTELY SAFE

11.95



COMPLETELY WIRED (NOT A KIT)

In no sense of the word a toy or gadget. This machine is a scientific instrument capable of producing 75,000 volts — makes sparks up to 2" long — yet it is absolutely safe because the current is infinitesimal. The science teacher — science lover — or hobbyist can perform experiments to astound students — friends — family. Makes smoke disappear — defy gravity — turns propellers at a distance — transforms atomic energy into light — makes artificial lightning — smashes atoms — demonstrates ionic space ship drive — and many other experiments. Constructed of the finest materials. Will do exactly — for instruction purposes — what generators that cost 3 to 10 times more will do. The perfect device to teach the secrets of atomic physics and electricity. Will hold an audience spellbound as it performs trick after amazing trick. Includes an experiment kit and illustrated experiment manual. Manual explains the "how" and "why". You will invent many new experiments of your own. A fine research tool that will give years of beneficial service to the institution or individual who owns one 110 V. AC or DC. **F-371 Assembled—Shpg. wt., 4 lbs.** Net 11.95

8.22

EL-78



6.72

EL-79

NEW! Cordomatic Mobile-Lite Reel

- Completely Portable • Light & power anywhere!

New Mobile-Lite Reel throws a wide, bright beam of light wherever it's needed, while a built in electrical outlet provides power for tools or appliances. Completely portable for use all around the house. Ideal for attic, basement or garage... and perfect for outdoor illumination of patio, lawn or garden. Cord locks and releases at any desired length... automatically retracts when not in use. Phenolic pistol-grip handle on universal swivel permits light to be adjusted in any position. The new Mobile-Lite Reel accommodates a 150-watt reflector flood spotlight of incandescent bulb. 20 ft. cord, 7 amp rating. Hanging hook on back of case permits wall mounting. Less bulb. Shpg. wt., 5 lbs. **EL-78** Net 8.22

Portable Outlet: Similar to above, except does not include lamp fixture. 3 way outlet operates several tools or appliances at once. Eliminates forever the inconvenience and hazard of tangled cords. 15 ft. cord, 10 amp rating. Shpg. wt., 2 1/2 lbs. **EL-79** Net 6.72

S.O.S. Magnetic WARNING SIGNAL

1.79




- 4" TWOFACED PARABOLIC REFLECTOR
- NEW SUPER REFLECTIVE SURFACE
- NO MOVING PARTS — BULBS — WIRES

The S.O.S. Emergency Warning Signal is the simplest, most dependable and practical safety device ever offered to help protect you in all emergencies. No moving parts — no wires or bulbs. May be used on or off the car. — Holds magnetically to car in any position at any angle! — Powerful, permanent magnets grip tight to steel surfaces! — Warns traffic in both directions! Parabolic reflector faces! Warns traffic from front or rear! Reflective power exceeds ICC specifications! Ideal for hand signalling! — Makes a perfect road "flare"! Stand it on the metal plate furnished and position it on a curved road! It can't slide! — Perfect parking protection on dark roads or tip or slide! Perfect protection in case of tail-light failure! — Protection for hiking or working on dark roads. The sway of the arm keeps it in continuous motion to insure pedestrian protection. Shpg. wt., 1 lb. **HD-677** Net 1.59

24 Hour Electric WORLD CLOCK

- Adjustable for Various Time Zones
- South Polar Projection
- 8" Overall diameter

Net 8.47



Tells world time at a glance. Self starting, accurate electric clock. Tells world-wide as well as local time. Calibrated in hours—1 to 24, minutes and seconds—1 to 60. Reads universal, military time in any zone. Quickly, easily and accurately. Polar projection dial adjusts for various time zones. Black dial with white graduations. Chrome plated case. U.L. approved. 110-120 V. 60 cyc. AC. Shpg. wt., 1 1/2 lbs. **ML-210 including excise tax** Net 8.47

NEW! Easy-Heat Automatic Heat Band

- Sure-Safe-Freeze Protection
- Protect Water pipes, Downspouts, Gutters
- Home-Farm-Mobile Plumbing
- Built in thermostat




Here is low-cost, winter-long, automatic protection against winter freeze-up. It's safe, simple, easy to install. Completely moisture-proof vinyl band holds properly spaced Heater Wire in separate channels. Thermostat and connections hermetically sealed—durably built. 12 extra inches of cold lead wire and mated plug are UL-approved. For any 110 or 120-volt AC outlet: Best of all, built-in Thermostat operates only when surface temperatures approach freezing—saves when surface temperatures approach 50° below zero! Freezes ice jams in down spouts and gutters. Protects water supply to livestock. Safe and sure indoors or out. Includes heating cable, thermostat, insulating outer wrap, tape, and instructions.

Stock No.	Length	Watts	Shpg. wt.	Net
EL-80	6 ft.	30	8 oz.	4.85
EL-81	12 ft.	60	1 lb.	5.57
EL-82	18 ft.	90	1 1/2 lbs.	6.24
EL-83	24 ft.	120	2 lbs.	6.84

Goodyear VAC-ETTE! with Attachments

- Light — ONLY 4 LBS. COMPLETE
- Quiet — AC/DC UNIVERSAL MOTOR
- Sturdy — ALL METAL CONSTRUCTION



Reg. 21.95
16.50

- Guaranteed for 1 full year!
- Designed for easier cleaning!
- Super Suction Power!

Power packed—all purpose—hand vacuum cleaner. Designed for every cleaning job in the home—car—workshop. Light for complete portability. All metal (NOT plastic) construction for years of hard use. Throwaway paper bag—no dust bags to empty. Positive locking accessories—crevice tool, dusting brush, upholstery nozzle, throwaway bags. Powerful, universal AC/DC motor. Fingertip push button switch. Includes storage container, instructions and guarantee. Shpg. wt., 4 lbs. **AP-41** Net 16.50

LAFAYETTE'S "READ-EASE"

- READ WITH EASE — WHILE RECLINING

4.59



Read-or write-or watch television while lying down — with all the vision ease of sitting upright. Ingenious, optically correct, prismatic readers give you "right-angle" vision to any object you care to view. Even bedridden patients can read — while lying flat — for hours without tiring. The prismatic system — working like a pair of tiny periscopes — angles your vision but adds no correction or aberration. Can even be used in conjunction with ordinary glasses. The light gathering power of the prisms actually gives a brighter image than normal. No fitting problems — prism plane is fully adjustable — locks in at angle of your choosing. The crown glass prisms are precisely aligned and ground to the closest tolerance. Specially suited for the avid reader—invalid—traveler. Shpg. wt., 6 ozs. **F-439** Net 4.59

NEW AMPHIBIOUS FLASHLIGHT


2.95



Outstanding new all purpose flashlight which is water-proof and gas tight. Can be used under water or in the rain. Ideal for use in camping and working outside at night. On-Off Switch is of back handle type. Powerful light beam provided by two cells. Complete with nylon shoulder band. Shpg. wt., 1 lb. **F-434** Net 2.95

Musical Door Chime

- Replace or supplement ordinary door bells!
- Different! Delightful!
- Installs in minutes!




4.49

Full scale musical door chime plays one chorus of a pleasant melody. Just a press of the button activates the musical unit to play a 15 second chorus. No need to hold the button down. Play and stop is automatic once button is pressed. Easily installed. Requires no special tools. Use as door bell — announcer — page, etc. Includes pushbutton, chime unit and 15 ft. of wire. Powered by 1 1/2 V. flashlight battery. Battery not included. Shpg. wt., 1 lb. **BA-157** Battery for Above. 1 required Net 4.49 Net .13

MARKING PEN SET

- Marks any Surface
- Posters — Packages — Prices — Signs



(Set of 3)
Red, Black, and Blue pens.

.69

Felt tip pens for writing on paper, wood, metal, glass, rubber, plastic, practically any surface. Instant drying, waterproof ink. Excellent for poster work, hobby, store-keeper, stock clerk, ad man. Address packages, mark frozen foods. Permanent on painted and porous surfaces. Combination tip for fine and broad line marking. Can be refilled. Set includes one each Red, Black, and Blue pens. Shpg. wt., 8 ozs. **HD-682** Net .69

Shear Magic


- Cuts EVERYTHING!
- From Metal to paper!



High grade, compound leverage, multi-purpose shears. Cuts just about everything that needs cutting. Paper—cloth—asphalt tile—rubber tile—wallboard—wire—sheet metal—cable—shingles — flowers — vines — shrubs — plastic — liguleum — canvas — carpet — metal foil — fibre board — coral — shingles — and hundreds more. A basic tool for indoors or outdoors—necessary as a screwdriver, hammer or pliers. 8 1/2" long, chrome plated handles, tool steel blades with black oxide finish. Shpg. wt., 1 lb. **HD-678** Net 1.29

"LEVEL-UP" Universal Surface Leveler

- Fast, Accurate
- Level Anything
- Keep your Equipment on the level.



.49

3 for 1.20

Level anything — anywhere — anytime! Shelves record changers — shop tools — cameras — stoves — refrigerators build-up projects — cabinets — trailers — and many more items. Simply center the bubble in the ring. The "Level-Up" may be mounted on a larger base, or trued up board, for spanning large areas. A professional tool—a home craftsman necessity. Shpg. wt., 4 ozs. **HD-680** Net .49 3 for 1.20

MINIATURE MUSIC BOX MOVEMENTS

- PRECISION MOVING PARTS
- MORE THAN 3-MINUTES PLAYING TIME
- RUGGEDLY BUILT
- BEAUTIFUL TONE

These miniature music box movements have an infinite number of applications for the ingenious home builder. Can be mounted in cigarette boxes, perfume cases, etc. The unit is so delicately balanced that a slight touch on the flywheel is sufficient to start or stop the movement. Has full 18 note scale. Precision-built drum and moving parts are made to last a lifetime. Components are mounted on a die-cast chassis. Complete with threaded mounting holes and winding key. Size: 1 1/2" x 2 1/4" x 1/4" Shpg. wt., 6 oz.

MS-578	AULD LANG SYNE	Net 1.88
MS-579	HAPPY BIRTHDAY	Net 1.88
MS-580	HERE COMES THE BRIDE	Net 1.88
MS-581	BLUE DANUBE WALTZ	Net 1.88

NEW! ELECTRIC MUSIC BOX MOVEMENTS

SPECIAL — ALL 4 for 6.95

- Operates on a single flashlight cell • Full 18 note scales • Maintains perfect pitch
- Uses limited only by your imagination! Battery operation opens a whole new field of applications. No springs to run down—no keys to wind! Precision built miniature motor and moving parts are designed to last a lifetime. Can be used anywhere ordinary movements are used—plus many more places. You can have a musical door "bell"! Musical electric toys work into model train layouts! store displays! annunciators. Measures only 3" by 1 1/2" by 7/8". Operates from any 1 1/2 volt battery of your choice. Shpg. wt., 6 oz.
- | | | |
|--------|-----------------------------|------|
| MS-760 | Moonlight Serenade | 1.88 |
| MS-761 | Smoke Gets in Your Eyes | 1.88 |
| MS-762 | How Dry I Am | 1.88 |
| MS-763 | Around the World in 80 Days | 1.88 |

New! The GIZMO

- 10 way Combination tool!
- A tool box in your pocket!
- 3 for 1.50



The perfect "traveling companion" for the service-man-mechanic-electrician-handyman or gadgeteer. As useful as a fish hook in the tackle box—more necessary than bullets in the hunters kit. Keep one in your car. Another in the kitchen—workshop—tool room. 8 handy tools packed into a single 4" x 1" package. It's a **plier—cutter—wrench—small screw driver—large screwdriver—awl—scraper—tack hammer—tack lifter**. Screwdrivers can be additional length. Complete with vinyl case and instructions. **HD-666** Net, ea. 59¢ 3 for 1.50

Lafayette

IMPORTED SLIDE RULES

ENGINEERING & DRAFTING SUPPLIES

NEW! DELUXE LOG LOG DUPLEX DECI-TRIG SLIDE RULE

- 25 Scales with 8 Log Log Scales ● 40" Log Log Dec. Fractions Scale ● Extended Range Avoids "Going Off Scale"
- Extra P Scale Simplifies Computations

This brand new 10" log log duplex trig slide rule is built for the most exacting demands and is a truly universal calculating instrument. Contains 25 scales in total. Has 8 Log Log Scales—40" Log Log Decimal fraction scale. The need for the troublesome end-to-end resetting of the slide is eliminated by the extensions of the C and D scales. Other scale arrangements also allow easier calculation of problems involving the value of trigonometric functions. The twin set of Log Log scales in four sections each runs from 1.001 to 100,000 and .999 to .00001, thereby enlarging the scale by one scale length each compared with ordinary log log slide rules. Extra features include the P scale which enables easy computations of vector problems involving two sides of a right triangle. Scales include L101, L102, L103, DF, CF, C1F, C1, C, D, L13, L12, and L11, L100, L, K, A, B, S, ST, T, C, D, D1, P, and L10. Complete with instruction book and saddle leather case. Overall length is 14". Shpg. wt., 1 1/2 lbs.



LIST 30.00

15.95

F-428

F-428 LIST 30.00 Net 15.95

10" LOG LOG DUPLEX TRIG SLIDE RULE

LIST 26.00

10.45



F-341

10" Log Log Slide Rule: Constructed of specially selected, laminated, non-hygroscopic bamboo. All scales are machine engraved on white plastic in permanently accurate calibrations. Adjusting screws permit varying the tension on the slide. 21 scales in all including the more frequently used C, D and CI scales on both sides of the rule. Evaluates trigonometric, algebraic and exponential problems. L10 and L100 scales refer to 8 scale. All other scales coordinate and refer to D scale. Scales are L, L11, DF, CF, C1F, C1, C, D, L13, L12, L10, L100, A, B, K, C1, C, D, S, ST and T. Scale characteristics permit multiplication, division, proportion, inverse proportion, reciprocals, cotangents, squares, square roots, cubes, cube roots, logarithms, tangents, sines, PI factor multiplication and division, powers and roots of numbers less than 1, powers and roots of numbers greater than 1, logarithms to base "e". The most often used slide rule in all basic fields science, engineering, production and economics. Shpg. wt., 1 1/2 lbs.

F-341 LIST 25.00 Net 10.45

5" POCKET SLIDE RULE

5" Pocket Slide Rule: Convenient pocket sized slide rule of specially selected and treated bamboo. Will not warp, shrink or lengthen under varying atmospheric conditions. A, B, C1, C, D and K scales engraved on white plastic surface. Reverse side of slide has standard S, L and T scales. The upper, beveled edge of the rule is graduated in m/m to 13 cm. Other edge is divided into 5 inches by 32nds. Only 5-13/16" long over all. Carried easily in any pocket. Shpg. wt., 8 oz.

F-340 LIST 6.00 Net 2.89




F-340

2.89

F-340 LIST 6.00 Net 2.89

DIRECT VISION PRECISION SPECTROSCOPE



- 400-800 MILLIMICRON SCALE
- ADJUSTABLE SLIT WIDTH; DRAWTUBE SLIT FOCUSING
- HORIZONTALLY SPLIT FIELD

76.50



A prismatic type, hand-held instrument that has most features of the finest standard laboratory instruments. The millimicron scale is adjustable for sharp focus and for position [with "lock-in" feature to fix scale with relation to known spectral lines]. Highest grade optics yields a broad dispersion field of high intensity obtained from best quality glass dispersing prisms, while excellent lens system resolves the closest spectral lines into 2 distinct lines. By a twist of the collar, a horizontally split field is obtained by which a comparison can be made of two light sources simultaneously. Tubes and collars are constructed of highly polished corrosion proof steel. Equally suited to laboratory or field work, the spectroscope has a wide array of applications: emission spectrum analysis of light sources; qualitative chemical analysis and metallurgical analysis by emission spectra; qualitative analysis of absorption spectra by examining aqueous or other solutions contained in the small test tubes provided. Absorption spectrum analysis has application in many branches of technology—color and dye chemistry, blood chemistry, clinical medicine, criminology. Complete with plush-lined case, shipping wt., 1 1/2 lbs.

F-361 5.00 Down Net 76.50

SUGAR REFRACTOMETER

- MODIFIED ABBE DESIGN — READS % SUGAR DIRECT
- NO MOVING PARTS TO WEAR OUT
- CAN BE USED TO DETERMINE REFRACTIVE INDEX



Here is a beautifully constructed scientific tool of simple design, easy to operate, with no moving parts, except for the focusing eye piece.

Operation is very simple. A few drops of the sample are placed on the prism, the cover is closed and observation is made by means of tungsten illumination or daylight. A perfectly clear field, completely color corrected, shows a reticle graduated in percent from 0-32%. With the sample in place as described above the field will show a sharp dividing line between a bright and dark portion; where the dividing line falls determines the reading, which can be estimated to 0.1% accuracy. The instrument can be converted to a universal laboratory type by changing % readings to "index of refraction" readings. (Consult Chemical Handbook or literature.) This instrument is an essential tool in the fields of sugar refining, agricultural, food technology, medicine, theoretical chemistry, etc. Comes in a convenient portable leather case. Shipping wt., 1 1/2 lbs.

F-358 2.00 Down Net 29.50
 F-431. Same as F-358, but range from 30 to 60%. 2.00 Down Net 33.95
 F-430. Same as F-358, but range from 50 to 80%. 2.00 Down Net 41.90
 F-432. Same as F-358, but range from 60 to 90%. 2.00 Down Net 41.90

ILLUMINATED MAGNIFIER

- 5X MAGNIFICATION — 2" FIELD
- ONLY 2.95



A fine, fixed-focus illuminated magnifier—magnifies work 5 times. Field of vision is 2" at 1 1/2" working distance. Unlimited usage in industry—shop—hobbies. For checking tools and dies—castings—forgings—welds—etc. Inspection of meter movements—fine soldering electronic repairs. Magnified area easily accessible through cut out invaluable in hobbies such as stamp or coin collecting, photography, entomology—mineralogy—etc. Excellent map reader. Completely portable—uses two No. 2 cells for power. Weight 3/4 lbs., length 8 1/2" overall. Shpg. wt., 1 1/2 lbs.

F-193 Net 2.95

Direct Vision Spectroscope

- SIMPLEST WAY TO OBSERVE SPECTRA
- BETTER THAN ANY GRATING SCOPE OF EQUAL COST
- HIGHEST GRADE OPTICS IN DIRECT VISION FIELD




19.50

Every physics, chemistry, science class, or hobbyist can afford to own this superb instrument. It is the simplest means by which one can observe emission spectra from light sources and vaporized chemical salts, and the Solar Spectrum.

A broad dispersion field of high intensity is obtained from several dispersing prisms of matched glass, while a high grade optical system yields good resolution, sufficient to separate 5789.6A from 5790.6A in the spectrum of a fluorescent lamp. The slit has adjustable width and can be focused sharply by means of an eye piece draw-tube, assuring easy viewing and establishment of Fraunhofer lines of the Solar spectrum or bright lines of the emission spectra. Metal parts are made of highly polished corrosion-proof steel. Comes in plush-lined case. Shipping wt., 9 oz.

F-359 Net 19.50

ALCOMAX MAGNETS



POWER MAGNET

● LIFTS 50 TIMES ITS OWN WEIGHT
 Made of Alcomax—a material with 12 times the magnetic energy of tungsten steel. Designed for most efficient performance/weight ratio—will lift up to 50 times its own weight. Horseshoe shape with plated keeper. Ideal for such applications as magnetic clutch, lifting, work holding, etc. relays, etc. Size 1 1/2" H x 1 1/4" D x 1 1/4" W. Distance between poles is 1/2". Shpg. wt., 1/2 lb.

F-55 Net 2.40

POCKET MAGNET

An Alnico magnet useful for inspection of hardware to sort steel from brass, as a retriever of small parts. Highly efficient. Size 1" H x 1/2" x 5/16" D. 1/4" between poles. Shpg. wt., 3 oz. With plated keeper.

F-54 Net .45

LABORATORY SET

This set has been specially designed for schools, laboratories, and technicians, for testing and demonstrating the magnetic properties of permanent magnets. Fine hardware case contains a pair of bar magnets 2" x 1/2" diam., a horseshoe magnet 1 3/4" high x 1-5/16" D x 1/2" deep with 5/16" spacing between poles, and a bridge magnet 7/16" high x 28/32" x 5/16" deep with 1/4" space between poles. Shpg. wt., 1 1/2 lbs.

F-58 Net 3.45

TECHNICAL DRAFTING SET

- Center Wheel Adjustment
- Professional Quality
- German Craftsmanship
- A \$15.00 Value

5.95



A fine set of imported nickel plated brass instruments priced far below the usual price for this quality. Contains 1/2" self-centering compass, one leg knuckle joint with divider, pencil, pen parts and lengthening bar; 6/16" self-centering divider; spring bow divider 4/16", center wheel adjustment with interchangeable needle points; spring bow pencil and spring bow pen, both 4/16" with center wheel adjustment and interchangeable needle point; two 5/16" ruling pens; extra handle for pen and pencil parts; adjustment tool; lead case and leads; and spare parts kit, all in velvet lined snap closing case. Shpg. wt. 1 1/2 lbs.

F-48 Net 5.95

2.59

UTILITY DRAFTING SET

- EXCEPTIONAL VALUE



Made in Germany of hard rolled, nickel plated brass. All instruments are nested in a fitted, velvet lined case. Contains three side wheel 3/4" bow instruments—one a pencil and one a pen. All have reversible needle point. 5/16" compass with pen and pencil parts—and lengthening bar. 5/16" divider with straightening device. 5" ruling pen. Extra handle for use with pen and pencil parts. Capsule with extra leads. Perfect for schools, labs, industrials or wherever precision drawing sets are used.

F-137 Net 2.59

8" PROPORTIONAL DIVIDER

Extremely accurate finely made proportional dividers. Basic equipment for draftsmen—architects—engineers—students. Replaceable steel points—in hard, leather covered, felt lined case. Used for proportional reductions and enlargements, copying drawings in enlarged or reduced scale, dividing lines or circles into equal parts, quick solving of difficult measuring problems, finding distances on maps without scales, etc. Flat form—replaceable steel points. Pressure setting. Graduated for lines from 1/4" to 10" — Circles from 6" to 20". Excellent, accurate utility model. Shpg. wt. 8 ozs.

- IMPORTED FROM GERMANY



3.95

F-167 Net 3.95

Professional GIANT BOW



- 6" Size with Center Wheel Adjustment
- Finely Balanced—Professional Type

2.95

Professional quality utility set in a fitted, velvet lined case. Made in Western Germany of nickel plated, hard-rolled brass. 6" giant bow has preferred center wheel adjustment. Makes circles from 1/8" to over 10" in diameter. Set includes 6" giant bow, interchangeable pen and pencil parts, extra needle for using bow as divider, handle for use with pen and pencil parts, lead, lead box and repair parts. Shpg. wt. 1 lb.

F-44 Net 2.95

NEW "Micro-Lab" Kit

COMPLETE HOME LABORATORY ALL THE MOST NEEDED ACCESSORIES

7.79



A carefully preselected assortment of the most often used lab items for biology, botany, anatomy, zoology, microscopy, etc. Perfectly complements the many inexpensive microscopes already in use. The instruments and accessories are of professional quality. The cabinet will accommodate any microscope of no more than 8 1/2" x 5 1/2" overall (such as our F-334 "BI-OCULAR" and F-357 "Micro-Mech" and contains the following accessories: 15 slides, slide labels, slide covers, viol of balsam, dissecting scissors, probe, scalpel tweezers, spatula, applicator rod, eyedropper, magnifier, 5 test tubes with stoppers, 6 laboratory jars, alcohol burner, polishing cloth. All in fitted drawers. Shpg. wt., 7 1/2 lbs.

F-434 Net 7.79

GENIAC CYLINDRICAL SLIDE RULE




The GENIAC cylindrical slide rule uses a new concept in slide rule design to achieve the graduations and accuracy of a 66 inch slide rule. This rule may be used to give answers with up to 5 digit accuracy, and quickly solve problems involving multiplication, division, roots, powers, logarithms, proportions, and percentages. Cylindrical construction features all-metal construction with plastic coated spiral scales. 1 1/2" diameter and 10" long, the rule collapses to 6", small enough to be easily carried in a pocket. Almost indestructible, cannot warp. Shpg. wt., 1 lb.

F-387 GENIAC Cylindrical Slide Rule Net 13.95

HARD MAPLE PANTOGRAPH

- ENLARGES — REDUCES REPRODUCES! ● PRECISION SUSPENDED!




3.75

21" adjustable pantograph—21 different ratios from 1 1/4" to 8. Enlarges, reduces or reproduces drawings—sketches—diagrams—maps etc. Most rapid, accurate means of reducing or enlarging to scale. Lacquered highly finished bars are 21" long and 3/4" wide. Heavy metal standard, with bearing eliminates all friction. Chrome plated hardware—ratio thumb screws and nuts. Complete with lead, accessories and detailed instructions. Shpg. wt. 2 lbs.

F-158 Net 3.75

"draftette" DRAFTING MACHINE



Full 180° protractor scale, finest aircraft aluminum with black satin finish. Engraved, white filled numbers and markings are machine calibrated to ± .0005 of an inch. Folds like a jackknife... slips into drawer or briefcase, eliminates clutter of T-square, ruler, protractor, triangles. Clamps to drawing board or sketch pad. Layout chassis, diagrams, sketches, design detail, surveys etc.

F-287 Draftette with 3 x 5" scale, attached to 11" x 17" drawing board. Shpg. wt., 3 lbs. List 4.95 Net 3.95
 F-289 Draftette with 3 x 5" scale, attached to 11" x 17" drawing board. Shpg. wt., 3 lbs. List 6.50 Net 5.20
 F-401 Draftette with 4 x 6" scale, List 6.95 Net 5.56
 F-402 4 x 6" Draftette mounted on 11" x 17" drawing board. List 8.50 Net 6.80

SUPER DRAWING KIT

- REGULAR 15.50

9.00



● COMPARE OUR PRICE!
 Lafayette has designed this set with the professional draftsman and advanced student in mind. Contains all the necessary equipment for drafting mechanical drawing—designing—engineering. Sturdy accurate components. Includes 20" x 24 1/2" drawing board 24" T square, 10" 30°/60° triangle, 8" 45° triangle, french curve, 12" triangular rule, 6" 180° protractor, 4 pencils pencil pointer, erasing shield, thumb locks, and art gum eraser. If purchased separately these components would cost many times our low price. An unbeatable value! Shpg. wt., 10 lbs.


F-180 Net 9.00

SPECIAL COMBINATION OFFER

Consists of F-65 Technical Drafting Set and F-180 Super drawing outfit. Shpg. wt., 12 lbs.

F-181 Net 13.75

OPTICAL MICROMETER



7.95

- Pocket sized Comparator
- Direct measurement to .005"
- Measures Diameters Radii—Angles
- Linear scale in Inches

High quality optical micrometer using a triplet lens system of approximately 7 power. Triplet system affords a wide flat field of view. Extremely accurate reticle of etched glass. Unaffected by changes in temperature and humidity—impervious to oil, solvents and scratches. 0.5 inch linear scale calibrated to .005 inch. 10 mm scale calibrated to .2 mm. Hole diameters from 1/64" to 1/16" and from .005" to .05". Thickness scales from 1/64" to 1/4". Radii from 1/16" to 1/8" and angles from 0° to 90°. Measures instantly—without adjustments. Accurate to edge of 1" field. Adjustable focus. Reticle removable for use as high power magnifier. Infinite uses in lab and industry. Complete with leather case. Shpg. wt., 6 oz.

F-376 Net 7.95

SPECIAL MICROMETER RETICLES

Extremely accurate, etched glass reticles for use with F-376 Optical Micrometer or other comparators of equal quality. Unaffected by changes in humidity and temperature—resistant to scratching—oils—and solvents. All reticles measure 1-1/16" (27mm).

(B) Particle measuring grid 0.4" x 0.3" subdivided to .005". Hole diameters from 0.1mm to 3.0mm. Radii from 1mm to 10mm. Angles from 0° to 90°. 10mm linear scale calibrated to .2mm. Shpg. wt., 4 ozs.

F-456 Net 2.75

Radii and angle scales. 180° protractor scale, 0 to 90° in 1° increments. Radius scale, concentric 0.5mm to 10mm with .5mm subdivisions. Shpg. wt., 4 ozs.

F-457 Net 2.75

Thickness gauge. 15 scales consisting of parallel lines—measures from .002 to .016 inches. Shpg. wt., 4 ozs.

F-458 Net 2.75

Particle measuring grid and diameters. 10mm square grid of 0.5mm squares. Subdivided with 0.1 increment. Diameters from 0.1mm to 2.5mm in 0.1mm increments. Shpg. wt., 4 ozs.

F-459 Net 2.75

Complete comparator. All five reticles and magnifier. With leather case. Shpg. wt., 8 ozs.

F-460 Net 16.95

Lafayette

"WINDICATOR" ANEMOMETER

WIND VELOCITY AND DIRECTION INDICATOR



59.95

PRODUCED BY THE SCIENCE MINDED FOR THE SCIENCE MINDED

- Direction and Velocity on One Dial
- Indicates Velocity from 0 to 100 m.p.h.
- New "Gyra" Design
- Starting Speed: 5 m.p.h.
- Accuracy for Speed $\pm 5\%$


Registers wind velocity and direction on a single dial. Modern, compact design. Completely self contained — no outside power source is required. A precision velocity/direction system designed to fill the needs of serious weather students, pilots, colleges, broadcast stations, mariners, airports, farms, testing labs, drilling rigs, forestry stations, yacht clubs, motels as well as private homes and executive offices. The transmitter assembly may be mounted on a roof or any suitable elevated position. Utilizes any 1 1/4" O.D. pipe or mast. Indicating unit can be wall mounted or set on a desk, table, mantle or shelf. Bracket permits tilted mounting. The indicator is housed in a handsome wooden cabinet, 5 1/2" x 2 1/2" x 7 7/8", finished in black and gold. Highly legible dial face 4 1/2" x 3 1/2". Two scales for speed, 0 to 25 m.p.h. and 0 to 100 m.p.h. plus third scale for direction. Outdoor parts of aluminum and specially coated and treated steel for maximum corrosion resistance. Self contained battery — no drain except when reading wind direction. Simple installation — similar to TV antenna installation. New "Gyra" design for maximum stability and minimum wind loading. Complete with 60 ft. of 5 conductor, color coded cable, 1 1/2 volt battery and instructions. Shpg. wt., 15 lbs. Net 59.95

"WINDICATOR" Mounting Kit

- Guyless Universal Mounting Assembly

Consists of mini-tower for mounting on any peaked or flat roof or surface. 5 ft., 18 gauge, 1 1/4" O.D. aluminum mast. Special, hardened screw-nails for rigid fastening. Self sealing, adjustable feet. Five standoff insulators. Set up height 9 ft. Shpg. wt., 8 1/2 lbs. Net 7.17

Wire for extended runs, 5 cond., color coded. WR-121 Shpg. wt., 2 1/2 lbs. Net, per 100 ft. 4.70



6.95

NEW! LAFAYETTE AUTOMATIC PHOTO-ELECTRIC "LAMPLIGHTER"

- Automatic Light Switch
- Lights on at sunset—off at sunrise

New photo-electronic, light sensitive switch turns lights on and off at dusk and dawn. Better than a clock—no setting and resetting of timer. Variance in "on-off" cycle adds extra protection when away from home. You need never come home to a darkened house. The controlled lamps go on as darkness falls—stay on until sufficient day light returns or until manually turned off. Just plug it in for protection from prowlers—to turn on night lights—illuminate outdoor areas—light up brooders—green houses—displays—show windows—any place you require automatic illumination. Mounts most anywhere on a rubber suction cup feet. Unobtrusive—measures only 4" x 2 1/2" x 1 1/4". Use on 117 volt AC only. Maximum 300 watts lamp load. Instructions included. Shpg. wt., 1 lb. MS-759 Net 6.95

UNIQUE HANDI-MIXER

- Economical—runs on 3 flashlight batteries
- Convenient—use it anywhere, home or away
- Safe—perfectly balanced, will not mar bowl
- Useful—mixes, whips, stirs, beats
- Trouble free—powerful, quiet motor requires no oil




3.49

Just flip the switch and the Handi-Mixer is ready for use anywhere—at the table, the stove, the sink, at home or away. It takes only 3 ordinary flashlight batteries to operate the powerful, quiet motor for months and months. You get a colorful case, 2 beaters, 1 egg beater, 1 brush. For all your mixing, whipping, stirring and beating chores. 10" long. Shpg. wt., 2 lbs. F-509 Handi-Mixer Net 3.49

HUMIDICATOR- "Slide Rule" HYGROMETER

- Slide Rule Readings
- No Computing —
- No Conversion
- Exceptional Ease and Accuracy

The most recent innovation in weather instruments. Fastest—easiest method of determining relative humidity. With the cursor (slide) set on the temperature, the relating humidity is read directly off the humidity indicator graph. Does away completely with tables, charts and time consuming calculations. The "sliderule" calculator correlates wet and dry bulb readings and "calls-out" percent of relative humidity. The "Humidicator" graph is calibrated in increments of 2%. Lesser figures may be readily estimated. Both thermometers are calibrated in increments of 2° from 20° F. to 120° F. Background colors chosen for easy readability and instant reference to "Humidicator" graph. Specially treated gauge for wet thermometer has increased "wetting" capacity. Overall size, including cistern, is 13 1/2" x 3 1/4". All mounted on a mahogany board with provision for hanging. Shpg. wt., 1 lb. F-496 Net 4.95



RAIN GAUGE 1.59

Farmers, gardeners, weather hobbyists. All need this sturdy, milled plastic rain gauge, precision manufactured to give accurate rainfall records. Unique "chisel" shape permits recording of minute quantities of precipitation. Exclusive easily-operated Cumiprecipitation Indicator. The gauge has large numerals on an easy-to-read scale graduated up to 5 1/2 inches. Scales in opaque numerals on a transparent shell with opaque numerals for easy readability. With complete instructions back for mounting and use, to obtain weather-station accuracy to 1/10th of an inch. Overall length 10 3/4", width 2 1/2". Shpg. wt., 8 ozs. Net 1.59



INDOOR-OUTDOOR THERMOMETER 2.29

Tell inside and outside temperature — instantly — from the comfort of your room. Inside location — ideal for quick, easy reading. Dual tubes single scale for instant, visual comparison. Plastic case with modern tapered lines. 8" x 2 1/2" x 4 1/2" long copper capillary tube and bulb. Large scale numeral for ease of reading. No moving parts to become worn. Shpg. Wt. 1 lb. F-321 Net 2.29



MAXIMUM-MINIMUM THERMOMETER 4.70

For weather enthusiasts—gardeners—farmers, etc. Gives three readings at a glance — maximum, minimum and present temperatures. Self-registering — no knobs — magnets — or push buttons needed for reset. Magnifying lens case for ease of reading. Maintains automatic check on temperature variations. Makes you the local weather expert. Shpg. wt., 1 lb. F-372 List 6.95 Net 4.70



STEREO SELECTOR SWITCH

- Now have stereo in every room in your home
- Permits remote selection of any of 3 pairs of speakers



A constant impedance speaker selector switch for multiple-speaker Stereo Hi-Fi. Selects 3 sets of speakers in any combination, with up to 60 watts of audio power. Mounted on an attractive, gold-finished, steel, electric outlet plate. 2 3/4" x 4 1/2". Shpg. wt., 1 lb. MS-765 Stereo Speaker Selector Switch Net 1.79

2 INSULATED ALLIGATOR CLIPS WITH BANANA PLUGS .49

- With banana jack
- Solid copper clips




Handy for all types of connections. Accurately matching, sturdy jaws for a tight grip. Convenient thumb grips equipped with soldering lug. Complete with banana plugs. 1 red, 1 black. Overall 4" long. Shpg. wt., 4 ozs. MS-768 2 Alligator Clips with Plugs Net .49

ADJUSTABLE CURVE 1.69

1.69

Enables anyone to draw curved designs with ease. The rule is easily bent to any desired curve with the fingers. Once bent, the rule stays curved without being held. White plastic frame encloses a lead bar and a steel sheet support. Overall length is 23 1/2". Shpg. wt., 8 ozs. F-441 Net 1.69


RUGGED LEVER SWITCHES FOR AUDIO APPLICATIONS AND INTERCOMS



4PDT lever action switch has 4 sets of single-pole, double-throw contacts. Switch has three positions with positive and spring returns. Front panel mounting is especially suited for audio applications and intercoms. Mounts to panel with 2 screws, mounting centers 1" apart. Size 2 1/4" long behind panel, 1 3/16" wide, 1" high. Shpg. wt., 4 ozs. Net .95 SW-68 4PDT Lever Switch

SPST lever action switch similar to SW-68 above. Has 2 positions with spring return. Size 1 1/4" long behind panel, 3/4" high. Shpg. wt., 4 ozs. Net .39 SW-69 SPST Lever Switch

PROFESSIONAL STYLE OIL PAINT SET



18.75 value

8.44


- Eleven 2" x 3/4" tubes of oil paint
- Jumbo 3" x 1" tube of zinc white
- 5 bristle brushes
- 2 bottles linseed oil and turpentine
- steel palette knife and cup
- 12 1/4" x 9" wood paint palette
- 12" x 8 1/2" mounted canvas panel

Imported by Lafayette to give you more fun and better results... AND TO SAVE YOU MONEY. Here is an 18.75 value for only 8.44, and that's a saving of 10.31. This complete set is in a sturdy 13" x 10" wood box. Shpg. wt. 4 1/2 lbs. F-532 Oil Paint Set Net 8.44

MINIATURE DYNAMIC MIKE 1.95

- Designed for transistor equipment
- Only 1-1/16" x 5/16" overall
- Perfect for "hidden" applications—Hearing Aids—Dictating Equipment—Transmitters

Specially designed for use in miniaturized equipment. Ideally suited for applications wherein size, weight and portability are important. 600 ohm impedance matches most transistor circuitry calling for dynamic microphones. Rugged — metal enclosed — to resist mechanical shock and variations in heat and humidity. Measures only 1-1/16" dia. x 5/16" thick. High sensitivity in the voice range. Frequency response 300 to 5000 cps. Output .73 db. Includes 4" flexible lead terminals. Shpg. wt., 4 ozs. PA-74 Net 1.95






Lafayette CAMERA DIVISION

WE INVITE COMPARISON!
WE DEFY COMPETITION!!!
ALL MERCHANDISE SOLD ON A MONEY
BACK GUARANTEE—YOU BE THE JUDGE.

LAFAYETTE CAMERA DIVISION presents the
'RANGEFINDER II' SYSTEM versatility at low cost

• 5 ELEMENT F2.8 COATED LENS! • COUPLED RANGEFINDER
only 29.95 less case



Exposure meter illustrated not included.

✓ BRILLIANT COMBINED VIEW-RANGE FINDER! ✓ SINGLE STROKE RAPID FILM TRANSPORT! ✓ NINE SHUTTER SPEEDS TO 1/300! ✓ MXF SYN-ALL SPEEDS — ALL BULBS — PLUS STROBE! ✓ F2.8 45mm COATED LENS! ✓ HI-SPEED REWIND! ✓ STANDARD PC FLASH TERMINAL! ✓ DOUBLE EXPOSURE PREVENTION! ✓ BUILT-IN SELF TIMER!


Lafayette's outstanding camera value Precision-made to order for the camera fan who is a wise buyer. Check the features — then compare Lafayette's price with any other brand. Fast F2.8 coated anastigmat lens and extra-wide lens aperture for brilliant, sharper full color or black and white even in poor light. Sight and focus through combined range-view finder. Fully synchronized at all speeds for class F, M and electronic flash. Speeds from 1 sec to 1/300th. Rapid advance sets shutter, counts exposure and transports film. Built-in delayed action timer — automatic exposure counter and film stop. Hi-speed rewind with folding lever. Standard accessory shoe on top-film type indicator. All metal body with brushed chrome trim-black leatherette covering. 20 or 36 exposures on black and white or color 35mm film. PG flash terminal. Shpg. wt., 3 lbs. Use series 6 accessories.

F-485 Less Case and Exposure Meter 2.00 Down Net 29.95
F-486 Leather Eveready Case. Shpg. wt., 1/2 lb. Net 3.95
F-351 Clip-on Exposure Meter Shpg. wt., 8 ozs. Net 5.95
Special Combination Offer: Includes camera above—Eveready case—folding BC flash gun—and clip-on exposure meter. Shpg. wt., 4 lbs. Net 39.95
F-487 2.00 Down Net 39.95

NEW! "SUPER-VUE" SLIDE VIEWER

- For all 2 x 2 slides—35mm, super slides, 828
- Large Screen—3" x 3"—Viewing
- Battery Illuminated

5.95




Extra brilliant viewing of all 2 x 2 slides 35mm, Bantam (828) and super-slides. Paper, metal, plastic or glass. Highly corrected 3" x 3" lens allows small group viewing. May be hand-held or placed on table. Built-in "tilt" for best viewing angle. Lens system gives amazing depth to carriers provide semi automatic action. "Battery Saver" feature—lights only when slide is in viewing position. Bright—sharp images with no "cut" corners. Lightweight—sturdy—compact. Complete with 2 carriers—2 color corrected bulbs—instructions. Shpg. wt., 3 1/2 lbs.

F-497 Net 5.95

"35" CLIP-ON EXPOSURE METER

5.95



- Fits camera accessory shoe
- ASA scale 6 to 3200
- Measures reflected and incident light


Exceptionally convenient exposure meter. Clips right on camera—quick easy reading. Gives better, more accurately exposed pictures with a minimum of effort. Speeds 1/1000 to 30 sec. Lens aperture f/1 to f/22. Light value scale (LVS) from 1 to 18. Cine settings from 8 to 64 frames per sec. Measures reflected and incident light. Mounts on camera or may be hand held. Complete with leather case and instructions. Shpg. wt., 1/2 lb.

F-351—Reg. 9.00 Net 5.95

NEW!

AUXILIARY LENSES

- TELEPHOTO — TWICE AS CLOSE!
- WIDE ANGLE — 75% MORE
- CLOSE UP — DOWN TO 6 1/2"



Telephoto shots — wide angle shots or extreme close ups. Easy as 1-2-3 with the new auxiliary lenses. Each lens is hard coated for maximum light transmission. Prefocused and color corrected. No increase in exposure setting is necessary. Wide angle and telephoto lenses screw into Bring your subject twice as close with Telephoto — add 75% more area with the Wide-angle. Indispensable for panoramic shots. Close up lens kit consists of +1, +2, and +3 Praxar lenses—allows focussing down to 6 1/2" for amazing close-up results. All auxiliary lenses are supplied in cowhide cases. Use with any color or black and white film. The close up lenses require an adapter ring for mounting on your camera. Shpg. wt. of each auxiliary lens approx. 6 ozs.

F-488-AUX. TELEPHOTO LENS (A) Net 9.90
F-489 AUX. WIDE ANGLE LENS (A) Net 9.90
F-294 CLOSE UP SET (B) Net 8.91
F-408 VIEW FINDER FOR TELEPHOTO AND W-A LENS (C) Net 1.69
F-490 Adapter ring for close up set, filters and auxiliary lenses. (D) Shpg. wt., 6 ozs. Net 1.95
PACKAGE DEAL: One each of the auxiliary lenses, close up set, adapter, and view finder. Shpg. wt., 1 1/2 lbs. Net 29.95
F-491 2.00 Down

NEW-BOOSTER EXPOSURE METER

6.95

WITH BOOSTER

- ASA Scale—LVS Scale • Stills or Movies
- Includes booster—Leather cases—neck cord

Extremely versatile — extremely simple. Highly legible direct reading dial. Speeds from 4 sec. to 1/1000 sec. Lens aperture settings from f/1 to f/32. ASA scale 6 to 800. LVS scale 1 to 18. Cine scale 8, 16, 24 and 32 frames per second. Booster cell makes possible readings at extremely low light levels. Small-rugged-lightweight. Includes booster cell, leather cases, neck cord and instructions. Shpg. wt., 1 lb.

F-349 List 11.95 Net 6.95



FOLDING BC FLASH GUN

- FOLDS LIKE A FAN TO 4" x 2"
- EFFICIENT B-C OPERATION!



Brand new—unique—pocket size—completely folding flash unit at Lafayette's famous low-cost! Efficient 4 1/2" diameter metal reflector has pebbled finish to eliminate hot spots. B-C combination for surefire and hi voltage. Heavy molded battery case with built in test lamp—bulb ejector—extension socket. Standard shoe with pressure adjust fits accessory clips. Uses standard bayonet base flash bulbs. Novel, useful exposure guide built in on rear of case. Complete with cord for PC fitting and condenser. Shpg. wt., 1 lb.

F-209 Complete with case Net 3.99
8A117 Battery for above Net 1.05

ELEVATOR TRIPOD

8.59



- Folds to 16" including Panhead!
 - Extends to 47" PLUS 7" Elevator!
 - Tri-Tilt head — Moves in 3 planes!
- For any small camera — 35mm — reflex — or movie. Professional quality for professional results. Strong — steady — lightweight. Pencil slim, chrome plated, brass legs. Lock securely in place — fold down readily. Single action tilt-pan — and swing over for taking pictures in vertical or horizontal format. Geared elevator centerpost with positive lock and folding crank. Weighs only 31 ozs. All the most wanted features in one tripod. Shpg. wt., 2 1/2 lbs.

F-339 List 19.95 Net 8.59

New "SPEEDLITE" Electronic Photoflash system
110V AC or Midget Battery Pack


- FEATHERWEIGHT • SUPER POWERED • 4 SECOND RECYCLE • 50 WATT SEC. OUTPUT • COLOR BALANCED LIGHT • BUILT IN DIFFUSER

(A) Designed by one of the foremost electronic flash engineers. More power—more practical features than any other unit in its price class. Thousands of flashes from one lifetime tube—pays for itself in savings on flash-bulbs—less than 1/2 cent per flash. Featherweight flash head weighs only 16 ozs. Entire unit—including battery—only 2 lbs. 4 ozs. Battery pack measures 5 1/2" x 3" x 1 1/2"—fits gadget bag or pocket. Coiled cord extends 5 ft. for off-camera or bounce flash. 15 ft. AC cord gives practically unlimited movement when operating an AC. Universal bracket fits any camera with a tripod socket. Gun also mounts on side of portable pack. Light is color balanced (6500° Kelvin) for color pictures without filters. Kodachrome guide 25—Tri-X guide 120. Recycles in 3 to 4 seconds. Speed 1/700 sec. flash duration. Gives soft, even, wide angle illumination. "Ready" light on head indicates flash is ready to fire. "Easy-off" clamp permits rapid off camera use. Socket on head for extension or multiple flash use. For any camera having X (zero delay) synchronization. Complete with battery, portable pack, 5 ft. coiled cord, shutter cord, 15 ft. A.C. cord, mounting bracket, clamp and instruction book. Shpg. wt., 4 lbs.

F-370 2.00 Down Net 25.95
Replacement battery for above. Shpg. wt., 1 lb.
BA-306 List 7.95 Net 5.56

"Speedlite" Accessories

(B) "Bio-lite". Ring type strobe flash attachment. For perfectly flat, shadowless photos. Mounts on lens for close ups. For studies in medicine, biology, botany, numismatics, philately. Same guide numbers as F-370. Fits series 6 adapter ring. Shpg. wt. 2 lbs. Net 22.50
F-501 2.00 Down
(C) "Booster" Capacitor. Fits on the bottom of F-370 Speedlite. Easy clamp-on attachment. Furnishes double the normal light output. Shpg. wt., Net 10.39
F-502
(D) EXTRA HEAD. Complete, second lamp head for extension use with the Booster. Shpg. wt., Net 12.95
F-503



PAN-HEAD TRIPOD

4.49 • LIGHTWEIGHT — STURDY — LOW COST

Five section, chrome plated, brass tripod. Extends to 45" telescopes down to 12 1/2". Weighs only 20 ozs. Tension adjust screws for each leg. Camera retaining screw on panhead rotates — makes turning camera unnecessary. Pans and tilts with a single motion. Handle is detachable. Pans 360° — tilts 145°. A "must" to take the "jiggle" out of those special shots. Shpg. wt., 2 1/2 lbs.

F-295 Net 4.49

35 mm Slide File

1.69 HOLDS UP TO 300 SLIDES



Portable all steel 35mm slide file. Store 150 2x2 glass slides or 300 2x2 cardboard slides. Includes index card, and numbered strips for quick, easy identification. Metal handle and 2 snap catches. Finished in platinum gray enamel. F-161 Net 1.69

MOBILGRIP HANDLE FOR EASY PICTURE TAKING


1.88

Eliminate fuzzy pictures with a Mobilgrip handle. Contoured all-metal construction with pre-set rubber platform-tripod socket in base. Baked hammerstone finish. Fits all standard movie cameras and light bars. F-549—Handle Shpg. wt., 10 ozs. Net 1.88



NEW "mini-pro" 2" x 2" MM SLIDE PROJECTOR

- COMPACT — ONLY 8 1/2" x 6" x 4 1/2" OVERALL
- BRIGHTER — SHARPER — EVEN IN LIGHTED ROOMS
- 80 mm f/3.5 COATED 3 ELEMENT LENS



19.95

A new, portable projector for showing mounted 2" x 2" 35 mm transparencies. An unusually fine, compound lens system develops a brilliance seldom found in projectors of far higher wattage. Projection lens in a fully coated, 80 mm f/3.5, three element, triplet type, anastigmat, extremely fine, aspheric, multi-condenser system multiplies the lamp output giving the maximum illumination possible. Exceptionally bright-sharp images—even in lighted rooms. Highly efficient double tube venturi cooling plus hardened, heat absorbing filter. Slides will not "pop" out of focus—eliminates constant refocusing. Flat field projection eliminates the usual distortion. Projection distance ranges from 3 feet to 26 feet. Fill a 40" x 40" screen at 10 feet. At 26 feet you get a giant 8 ft. by 15 ft. picture. Elevating knobs tilt projector to desired angle. Weighs less than 3 1/2 lbs. Includes 150 watt projection lamp, attractive, sturdy carrying case, standard two slide carrier, six foot cord and protective lens cap. Shpg. wt., 5 lbs.

F-356—List 37.50 Net 19.95

YASHICA Y-16 ULTRAMINIATURE CAMERA

- Foolproof "Clip" loading
- Speeds 1/25th to 1/200th Sec.
- Only 4" x 2" x 1" overall
- "Synched" for flash

Load and shoot in a second. Exclusive "clip-load" magazine-fast-foolproof. Permits changing from color to black and white film anytime-anyplace. Even if roll is only partially exposed—you "waste" only one frame! Combined "rip-action" film advance and shutter wind for truly rapid shooting. Fixed focus f/3.5 coated lens with stops to f/16. Click stop shutter speeds from 1/25th to 1/200th plus unique "slow" setting. The "S" setting permits variable slow shutter speeds and "Time" exposures. Built-in flash terminal (PC) and "X" synchronizations. Accurate exposure counter with automatic "zero" reset. Cable release socket and tripod socket. Film clip loads 24 B&W or color shots, 10 x 14mm negative. Magazines may be bulk loaded with either perforated or non-perforated 16mm film. Makes full size prints. All metal body. Includes leather case and wrist strap. Shpg. wt., 1 lb.

F-528 2.00 Down Net 27.95

Accessories and Film for Yashica Y-16



F-25




F-545

Clipload Magazine: Black and White, Plus X; ASA 80. 24 exposures. Shpg. wt., 4 ozs. Net 1.13

F-543 24 exposures, Shpg. wt., 4 ozs. Net 1.13

F-542 24 exposures, Shpg. wt., 4 ozs. Net 1.35

F-541 24 exposures, Shpg. wt., 4 ozs. Net .79



Reg. 34.95

27.95

Self Timer: Fits cable release socket of Y16 (F-528). 15 seconds delay—automatically retracts. Net 1.98

F-25 Net 1.98

Flash Unit: Fanyte BC flashgun, folds down to 4" x 2". Includes clip to adapt to Y16 (F-528) camera. With card and leather case. Less Battery. Shpg. wt., 1 lb. Net 5.25

F-545 Net 5.25

COMPARE!

YOU CAN'T BEAT LAFAYETTES' WHOLESALE PRICES



900X "MICROBE HUNTER"

- The only Microscope in its class featuring GRADE A optics!
- Power Range 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 900X
- Full Range Fine Adjustment
- Safety Stop on Coarse Adjustment

Made to rigid design specifications—has wide usage in schools, laboratories and law enforcement agencies. All of the most needed features for diversified micro-studies. Power range from 25X to 900X in 12 possible combinations. Gearing rack and pinion coarse focusing. Micro-motion fine focusing—12 complete revolutions. 36mm (plano/concave) mirror. Fixed square stage, 70mm x 80mm.

Rotating 5-hole, disc diaphragm. Three Huygenian eyepieces of 5X, 10X and 15X. Four achromatic objectives of 5X, 10X, 40X and 60X. Oversize base insures stability. Body perfectly balanced at any angle. Complete with upright, wooden carrying case. Shpg. wt., 8 lbs.

F-338—List 69.95 2.00 Down Net **34.50**




1200X "RESEARCHER"

- MAGNIFICATION RANGE 25X - 1200X
- 4 OBJECTIVES, 4 EYEPIECES,
- FULL RANGE FINE FOCUS ADJUSTMENT
- FULLY CONTROLLED, INTEGRAL MECHANICAL MOVEABLE STAGE

This superb instrument closely parallels the "Society" grade microscope in every desirable detail and yet is available at very low cost. Provides heavy, stable horseshoe base, smooth acting joint, enabling the body to turn through 60°, perfectly balanced at any angle. Tube length is 140 mm. Four Huygen's eyepieces and four achromatic objectives yield 16 combinations of power from 25X to 1200X. By means of two knurled micro-motion screws of the rear of the stage, it is possible for the operator to move the stage (and the slide) a distance of 3/16" - 1/4". In any direction, while looking through the eyepiece. Hardware is of the finest quality. Tubes are of the highest grade chrome-plated brass. All fittings are expertly machined and threaded, making this scope suitable for the most exacting work. Scope comes with a set of 5 basic dissecting instruments, made of high-grade instrument steel. 10 slides, a pack of cover slips and a tube of mounting fluid. Includes dovetailed wooden carrying case. Shipping wt., 10 lbs. F-369 2.00 Down Net **44.50**

44.50

PREPARED MICRO SLIDES



- SPECIALLY SELECTED MICRO-SUBJECTS.
- ADD TO THE ENJOYMENT OF YOUR MICROSCOPE.
- PROFESSIONALLY PREPARED.

AS LOW AS **79¢** PER SET

Specially selected slides of universal interest. Carefully prepared—cleaned, dissected, embalmed, stained, mounted and covered. Slides are professional size. Set includes 12 prepared slides and slatted, covered box for filing and storing. Shpg. wt., 8 ozs.

Stock No.	Description	Net ea.
F-123	Parts of Insects	1.39
F-124	Spiders and Disease Carriers	1.39
F-125	Tiny Creatures found around House	1.39
F-126	Sea Life	1.39
F-128	Structure of Blood	1.15
F-130	Life cycle of Insects	1.39
F-131	Bacteria	1.79
F-132	Pond, Marsh and Sea Life, Plankton	1.59
F-134	Micro-Animals	1.29
F-261	Textile Fibres	.79
F-262	Starch Grains—silver stained	.79
F-263	Structure of Leaves	.79
F-264	Plant Reproduction	.79
F-266	Honey Bee Organs	.79
F-135	Micro-Organisms	1.29
F-136	Substance of Cells	.89

*—Set of 6 slides



900 X "MICRO-PREP" KIT

- 100X to 900X IN 7 RANGES
- BUILT-IN SUB-STAGE LIGHT
- 2 MATCHED EYE PIECES
- INCLUDES DISSECTING SET, SPECIMEN, SLIDES

Monocular tube design made to educational standard. Uses geared rack and pinion for focusing. Coaxial knob adjustment permits smooth action. Fixed square stage is 70 mm. x 80 mm. with click-stop sub-stage diaphragm. Sub-stage is illuminated by built-in battery lamp, giving brilliant, color corrected field. Light is supported by a 35 mm. adjustable plano-concave reflex mirror. Huygenian eye pieces of 10X and 15X. 4 achromatic objectives—10X, 20X, 40X, and 60X. Combination of the two yields 100X, 150X, 200X, 300X, 400X, 600X, and 900X. Include 12 slides of which 8 are blank and four prepared. Dissecting kit consists of 1 spatula, 1 tweezers, 1 probe, 1 scalpel, 1 scissors and 1 magnifying glass. Overall height 11". Grey satin finished with chrome trim. Provided with handsome fitted cabinet with carrying handle. Shpg. wt., 6 lbs. F-433 Net **15.95**

15.95



Brinnell Microscope

- Reads direct to 0.0005 inch
- Magnification 100X
- Self Illuminated

Directly measures the size of Brinnell hardness impressions, or any object, down to .0005 in. Built in eye piece reticle is .05" long divided into 100 parts. Each 200th inch is numbered for direct read-out. Helicoid focusing of eye-piece corrects for diopter variations. Focusing of main tube by extremely fine rack and pinion. Illuminated by a pen light attached to an adjustable arm. Portability, rugged construction and high light efficiency make this an excellent general purpose industrial unit. Suitable for field work as well as lab and shop. Eye relief of approximately one inch permits use while wearing glasses. Complete with adjustable arm, penlight and fitted case. Shpg. wt. 2 1/2 lbs. F-508 2.00 Down Net **32.50**

Net **32.50**

PHOTOMICROGRAPHY MICRO' DAPTER

- INEXPENSIVE — ACCURATE — EASY TO USE
- USE ANY CAMERA/MICROSCOPE SETUP
- RECORD ANY MICRO-OBSERVATION




Net **24.95**

The MICRO'DAPTER permits the use of any camera—even movie cameras—with practically all microscopes. May be used with all color and black & white film. No need to remove the camera lens. All exposures are made with the camera set at infinity. You view the specimen—choose the field of view—and focus while sighting through the MICRO'DAPTER's viewing telescope. Cross hairs are superimposed on the image for centering. The telescope is focusable for diopter variations. The image is automatically in focus for the camera when viewed in focus through the MICRO'DAPTER. An internal shutter shuts all the light to the telescope for viewing or to the camera when ready for exposure. The camera shutter is operated in the normal fashion. Accessory sleeves permit the MICRO'DAPTER to be used with other than Society size microscopes. The MICRO'DAPTER will also couple a camera to a telescope and may be used in the same manner as with a microscope. Complete with lateral viewing telescope, accessory sleeves and fitted case. Shpg. wt. 1 1/2 lbs. F-506 2.00 Down Net **24.95**

F-506 2.00 Down Net **24.95**

SIMPLEX CYLINDER MICROTOME

Small, accurate microtome for freehand sectioning. Suitable for school use as well as lab applications where a hand operated feed is sufficient. Extremely well made to very close tolerances. Micrometer feed screw is graduated in 10 micron intervals. The ground glass stage is 75 mm in diameter. The microtome knife is of surgical steel, ground and tempered to produce and retain a keen cutting edge. Complete with knife and wooden storage case. Shpg. wt., 2 lbs. F-442 Net **16.95**



NEW! 30X-70X STEREO-SCOPE

- STEREOSCOPIC Binocular Dissecting Microscope
- Wide Field 3-Dimension View
- Two Models to Choose from

SEMI-PRO "STEREO-SCOPE": An especially engineered instrument featuring the stereopsis and wide view field needed in biology — petrography — archeology — mineralogy — criminology — industry — agriculture — etc. Indispensable for inspection of large specimens — small parts — surface features of gross objects — dissection — etc. Fixed objective lenses and interchangeable eyepieces for a choice of either 30X or 50X. Prismatic binocular head with full interpupillary adjustment. Ground glass stage 3-3/16" x 3-5/16". Oversize modified horseshoe base. Rack and pinion focusing. Automatic stop prevents over rise. Overall height 9 1/2". Complete with fitted wooden carrying case. Shpg. wt., 6 lbs. F-337 Net **21.50**




Net **17.95**

Net **21.50**

STUDENT "STEREO-SCOPE": A 30X stereoscopic binocular microscope—designed primarily for the student and serious hobbyist. Includes most of the features of our "Semi-Pro" model shown on this page. Fixed objective lenses and non-interchangeable eyepieces. All optics are achromatic. Ground glass stage measures 2 7/8" x 2-13/16". Overall height 7 3/4". Complete with fitted woden carrying case. Shpg. wt., 3 lbs. F-335 Net **17.95**

F-335 Net **17.95**

MICROSCOPE STAGE MICROMETER




3.95

Measures microscope field sizes—used for calibrating and standardizing micrometer eyepieces. Fine polished glass slide, 75 mm x 25 mm, has a 1.0 mm scale with 100 graduations (0.01mm) ruled directly on it. Each fifth and tenth calibration is a larger line to aid in measurement. The lines are stained black and protected by a cover glass. Complete in hinged case. Shpg. wt., 6 ozs. F-448 Net **3.95**

F-448 Net **3.95**

SLIDE PREPARATION KIT



• 30 Large Blank Slides **.98**

30 glass slides, 3" x 1", in a fitted, sturdy cardboard container. Slatted guides hold slides upright for easy indexing. Includes slide covers and vial of mounting fluid. Shpg. wt. 1 lb. F-533 Net **.98**

F-533 Net **.98**

COLLAPSIBLE ILLUMINATED MAGNIFIER



.98

Collapsible lens pulls out, automatically lighting flashlight. Magnifies work 5 times. Ideal for examination of coins, stamps, etc. Size 4 1/4" x 1 3/4". F-426 ea. **.85**


Lot of 3 BA-155 Burgess 2 battery (2 required for above) ea. **1.00**

HUNTING WITH THE MICROSCOPE

NEW EDITION
Guide for beginners and advanced users of microscopes. How the microscope works. How to prepare and study cultures—set up a microscopic zoo and garden—grow micro organisms—perform micro surgery. Profusely illustrated with photographs and drawings. 14 chapters of easy-to-read, highly informative text. BK-1440 136 PAGES 5 1/2" x 8" Net **.89**

BK-1440 136 PAGES 5 1/2" x 8" Net **.89**

NEW! Achromatic BARLOW LENS




- Makes Any Good Telescope Better!
- Doubles Your Telescope's Power!
- Improves Definition!
- Provides Greater Eye Relief!
- Greater Illumination—Wider Field!

4.95

The Barlow Lens is a negative (diverging) lens which can increase the range of magnification of any given set of eyepieces. Greater eye relief is provided—even on short focal length eyepieces. Sharpens definition and reduces image deterioration by permitting use of low-power eyepieces to achieve high magnification. This also provides for greater illumination and a wider field. By increasing the effective focal length of the objective—and reducing its relative aperture—it greatly reduces aberrations present in poorly corrected eyepieces. Lafayette's Barlow lens will make any good telescope perform like a much larger one. Fits all Lafayette telescopes except F-330 Explorer. Accepts eyepieces of 24.5mm (.97") O.D. and fits draw tubes of that size. Shpg. wt., 1 lb.

Net 4.95

ACCESSORY EYEPIECES



- Highly Corrected
- Hard Coated
- 24.5 mm O.D.
- Finest Quality

Manufactured to extremely close tolerances by one of world's leading manufacturers of optical accessories. These oculars allow you to obtain maximum performance from your refractor or reflector. You can determine the magnification possible by dividing the focal length of the eyepiece into the focal length of the telescope objective lens. All are hard coated. The 24.5 mm O.D., (.97") fits most telescopes currently available.

Stock #	Description	Net, ea.	Stock #	Description	Net, ea.
F-391	4mm Orthoscopic	8.95	F-396	24-32 mm Combination	
F-392	6mm Huygenian-Mittenzwey	5.45		Kellner-Achromatic Huygenian	9.45
F-393	9mm Huygenian-Mittenzwey	5.45	F-397	22 mm Kellner	7.95
F-394	12.5 mm Huygenian-Mittenzwey	5.45	F-398	Sunglass—for above oculars	1.25
F-395	20 mm Huygens	5.75	F-399	Moonglass—for above oculars	1.25

30x, 60mm SPOTTING SCOPE

- Binocular Type
- Complete With Focus
- Complete With Leather Case



A prismatic telescope using the same fine features as expensive binoculars! Field of view is 85 feet at 1000 yds.! Both front and rear optics are coated. High relative brilliance due to great 60mm objective lens. Exceptionally small and light—weighs only 1 1/2 lbs. Including metal tripod! The perfect companion for shooting—hunting—viewing—naturalists—and hobbyists. Comes equipped with 1 1/2" tripod and mount and zippered leather carrying case for both scope and tripod. Shpg. wt., 2 1/2 lbs.

17.95

- Coated Optics
- Isamatic Lens System

"MAGNI-SCOPE" PROJECTION MICROSCOPE

Produced for the Science Minded—by the Science Minded

- TWO PROFESSIONAL INSTRUMENTS IN ONE.
- ACCEPTS SOCIETY SIZE OBJECTIVES AND EYE PIECES
- SIMPLE—COMPACT—INEXPENSIVE

49.50



Professionally designed and produced to conform to the standards set by Lafayette's Instrument Division. The "Magni-Scope" is not merely a converted microscope—nor a converted projector. It is a true micro-projector instantly adaptable to use as an extremely fine microscope capable of delivering high magnification (up to 1500x) and excellent definition. The "Magni-Scope" will project every type of prepared slide. Heat absorbing filter glasses also permit the projection of living material. These filters, built into the condensing system, protect valuable slides from damage by heat. The highly efficient 100 watt light source—coupled with a first class optical train, assures projected images of exceptional clarity and brightness. The highly corrected optics permit extremes of magnification without distortion or color aberrations. The "Magni-Scope" has also been designed for use as a shadow graph, making it invaluable in industrial and testing laboratories. All standard (society size) microscope objectives and eyepieces are standard and can be used in the "Magni-Scope". Hence the "Magni-Scope" offers all advantages of the most expensive microscopes. Magnifications up to 1500x are possible by using a 15x eyepiece and 100x oil immersion objective. Polarizing filters and an iris diaphragm are mounted subsstage for light control. The "Magni-Scope" finned housing and the large stable base are cast aluminum alloy, finished in black crackle enamel. The focusing mechanism is a dovetailed chromed brass slide with a spring-loaded micro-drive for fine focus. Stage is 90mm by 80mm. Supplied complete with a 10x eyepiece, 10x objective, 100 watt projection lamp, instructions and a fitted hardwood carrying case. Shpg. wt., 10 1/2 lbs.

F-484 2.00 Down Net 49.50

Lafayette's DIRECT IMPORTS

Make These Prices Possible

THE NEW Professionally Designed and Produced

Polaris 2.4" EQUATORIAL REFRACTOR

- 800-mm. Focal Length
- 62-mm. Objective
- Micromotion adjustments on both axes
- Coated optics throughout
- Equatorial mount

160x—88x—40x—22x with eyepieces included 200x* by use of optional eyepiece

79.50 Only 5.00 Down

Latest in a long line of Lafayette refractors at reasonable prices. The unusual value of the Polaris is recognizable in the following specifications. Objective: Fraunhofer-type achromat, hard coated, 62.5 mm., 800-mm. focal length. Collects about 75 times as much light as the naked eye, resolving power 2 seconds, faintest discernible star 10.7 magnitude. All eyepieces are hard-coated Huygenians. Eyepieces included: 160x (5-mm), 88x (9-mm), 40x (20-mm), 22x (35-mm).

Finder scope is 6x, 30 mm. Equatorial mount with slow-motion controls in right ascension and declination. Tripod head with latitude adjustment. Clamp lever for declination and inclination. Accessories include sunglass, star diagonal, erecting prism, sun projection screen, field tripod, and wooden case. Magnifications of 160x, 88x, and 40x. Rack-and-pinion focusing. Heavy plating used throughout to prevent rusting. Shipping wt. 30 lbs.

F342 WX Net 79.50
F391 *200x obtainable by use of optional 4-mm Orthoscopic Eyepiece Net 8.95



Galactic 3" Equatorial Refractor

RESEARCH QUALITY

- 910mm FOCAL LENGTH
- 76.2mm CLEAR APERTURE
- MICROMOTION CONTROLS FOR DECLINATION AND RIGHT ASCENSION
- RESOLVING POWER 1.6
- 1.6" FINDER SCOPE — 500 MM. FOCAL LENGTH

Truly superior quality—advanced design—optically and mechanically suitable for serious research. The objective lens is a 79mm, hard coated, air spaced Fraunhofer achromat with a clear aperture of 76.2mm (3"). Focal length 910 mm, focal ratio f/12, resolving power 1.6". Seven coated eyepieces provide magnifications of 227X, 152X, 101X, 73X, 45X, 35X plus 25X through the viewfinder. Focusing by means of micro-precision rack and pinion drive. The viewfinder scope has a 42mm (1.6 in. clear aperture) objective—500mm focal length—rack and pinion focusing—and will accommodate various eyepieces. The equatorial mount is oversized—insuring stability and smooth action. Finely calibrated hour and declination circles for rapid finding and setting. Micro-motion and rapid motion controls are provided for both declination and right ascension. Micro-motion controls are fitted with flexible shafts and oversized knobs for ease of positioning while viewing. Body tube of white enameled aluminum for maximum strength with minimum weight. Accessories include three sunlasses, moonglass, two star diagonals, sun diagonal, erecting prism, sun projecting screen, extensible field tripod, chain brace, accessory shelf and wooden cabinet. Shpg. wt., 60 lbs.

F-384 WX 5.00 Down Net 189.00

Sale! 189.00

5.00 Down



Regular Value \$300.00

LAFAYETTE EXCLUSIVE ASTROGRAPHIC PLANETARIUM

12.50

- ★ HOLD THE UNIVERSE IN YOUR HAND!
- ★ COMPLETELY PORTABLE!
- ★ SELF ILLUMINATED!
- ★ LOCATES AND IDENTIFIES ALL IMPORTANT CONSTELLATIONS IN OUR LATITUDES!

Produced for the Science Minded—by the Science Minded.



A totally new, portable, astronomical instrument. Based on the centuries old principle of the Astrographic Star Finder. The Astrographic Portable Planetarium simplifies the study of the basic elements of astronomy. Indoors—it teaches the names—locations—appearance—and relative positions of all the major constellations in our latitudes. Outdoors—it becomes a "star-finder" without peer. Locates and identifies all the major constellations—stars from the 1st to 5th magnitude—clusters—nebulae—Milky Way. Observable from

30° to 40°N. Latitude. Adjusts for any hour of any day of any month. The "Sky"—as view through the Astrographic Planetarium—includes the mythical constellation configurations. Properly placed and named and precisely executed in all their intimacy and beauty. Super imposed celestial equator and ecliptic—Month/Day and Hour Dial—cardinal compass points for viewing direction—"soft-lite" bulb. Includes batteries and instructions. Shpg. wt., 1 1/2 lbs.

Net 12.50

LAFAYETTE 14" TRANSPARENT CELESTIAL GLOBE

Basic Aid for Students and Teachers of Astronomy

- Navigators
- Aeronautics
- Astronautics.

FIRST TIME UNDER \$100.00
AVAILABLE ONLY THROUGH LAFAYETTE IN THE UNITED STATES, CANADA & MEXICO

Designed by Dr. N. Hirase and Mr. Manabe of the Tokyo Astronomical Observatory

- ★ Adjustable Satellite Orbits
- ★ Satellites Travel around Earth Automatically
- ★ Adjustable Sun and Moon
- ★ Adjustable Lunar orbital inclination
- ★ 80 Constellations—including all stars of 1st, 2nd, 3rd and 4th Magnitude.
- ★ Similar devices used by the Navy—Air Force—and Marines.



59.50

A true "mechanical universe." Designed for and dedicated to those who recognize the challenge and adventure that lie on the frontiers of space. The concept of the celestial sphere is the most convenient means of illustrating and discussing the common motions of the stars and the individual motions of the members of the solar system. It offers an easily used and easily understood working model of our universe. An invaluable aid in visualizing and identifying the stars and constellations and their relationship to each other, to terrestrial positions and to times and dates. Permits comprehensive explorations in time and space beyond the earth atmosphere. The Lafayette celestial sphere will illustrate times and dates. Permits comprehensive explorations in time and space beyond the earth atmosphere. This system of geocentric coordinates will illustrate as this defined at a sphere of infinite radius with its center located at the center of the earth. This system of astronomical spherical coordinates, such as the true geographic zeniths of the sun and stars at any time on any day. All systems of astronomical spherical coordinates, such as the equatorial, galactic, ecliptic, etc., which are based on the celestial sphere, rotate with the sphere. The apparent contra-rotation of the stars, actually due to the earth rotating about an axis is clearly demonstrated. The sphere will illustrate how the sky will appear at any hour—on any date—from any point on earth. With it you can tell time by the stars—learn to tell time by the sky—clearly illustrate and help solve navigational problems. Traces the orbits of man made satellites and finds their overhead positions. Serves as a superb star chart. Sun and moon positioned by external controls. Artificial satellites automatically circle around the celestial sphere. The celestial globe is 14" in diameter with the terrestrial globe centered within. Equipped with horizon ring—time ring—fixed meridian ring—swinging meridian ring—sun and moon pointers—fixed ecliptic—detachable "planet"—indications—universal base—and complete instructions. Shpg. wt., 15 lbs.

F-400WX 5.00 Down Net 59.50



LOW LAFAYETTE PRICES

AUTO ACCESSORIES-AMERICAN & FOREIGN!



MOTOROLA

FOREIGN CAR RADIOS • SAVE 50%

- TRANSISTOR POWERED
- CUSTOM DESIGN

\$39⁹⁵
\$2 Down



COMPLETE NOTHING ELSE TO BUY. ONLY 2.00 DOWN

- Perfect For Sports Cars, Boats And Trucks
- Special Transistor Powered Circuit Eliminates Noise And Provides Low Battery Drain.
- Extremely Compact — Will Mount In-Dash, Under Dash Or In Specially Positioned Installations
- Automatic Volume Control
- Self Contained 5" Golden Voice Speaker
- Measures 6 1/2" W x 2 1/2" H x 7 1/4" D

Available for 6 or 12 Volt — Specify Make and Model of Car
CR-18 Shpg. wt., 6 Lbs. 2.00 Down Net 39.95

CONSULT THIS CHART FOR YOUR FOREIGN OR SPORTS CAR

ALFA-ROMEO 1956-59	DKW 1956-59	HILLMAN MINX 1957-58	PEUGEOT 1958-59*	SUNBEAM RAPIER 1955-59
ARNOLT BRISTOL 1955-59	ENGLISH FORD ANGLIA, ESCORT PREFECT, SQUIRE 1958-59	JAGUAR (ALL) 1950-59	RENAULT DAUPHINE 4CY-1955-58*	TANAUS 1959
AUSTIN 1956-59	ENGLISH FORD CONSUL-ZEPHYR ZODIAC 1957-59	LLOYD 1957-59	RENAULT DAUPHINE 4CY-1959*	TRIUMPH (ALL) 1955-59
BMW (ISETTA 300) 1957-59	ENGLISH FORD CONSUL-ZEPHYR ZODIAC 1957-59	MERCEDES BENZ 1955-59*	RILEY 1957-59	VAUXHALL 1958-59
BMW (ISETTA 600) 1958-59	FIAT ROADSTER 1957-59	MGA 1958-59	ROVER 1958-59	VOLKSWAGEN 1952-57*
BORGWARD 1957-59*	FIAT ROADSTER 1957-59	MORRIS MINOR 1956-59	SAAB 1958-59	VOLKSWAGEN 1958-59*
BRISTOL 1957-59	FIAT (600-1100) 1957-59	NSU PRINZ OPEL 1958-59	SIMCA ARONDE 1958-59	VOLKSWAGEN GHIA 1955-59
CITROEN (ID-19) 1956-59	GOGOMOBIL 1958-59*	PANHARD 1957-59*	SIMCA VERSAILLES 1958-59*	VOLKSWAGEN BUS 1955-59*
CITROEN (DS-19) 1958-59*		PORSCHE (ALL) 1957-59*	SIMCA CPE. DE VILLE 1958-59	VOLVO 1957-59*

*Radio is Available For Sports And Foreign Cars Noted In Above Chart.

NEW! MOTOROLA TRANSISTOR-POWERED MANUAL TUNING CAR RADIO

Also Available for Sports Cars

\$45²⁰

ONLY 2.00 DOWN

Specify make and year of your car

BUICK 1954 thru 59	NASH RAMBLER 1957 thru 59
CHEVROLET 1953 thru 60	OLDSMOBILE 1954 thru 59
GMC TRUCK 1953 thru 60	PLYMOUTH 1953 thru 59
EDSEL 1958 thru 59	PONTIAC 1957 thru 59
FORD 1953 thru 60	STUDEBAKER 1955 thru 60



This transistor powered car radio installs easily on the dash of most cars. Features 7 tuned circuits with 5 tubes plus transistor, noise eliminator-circuit, automatic volume control, tone control and 6 x 9" external speaker. Size 7 1/2" W x 2 1/2" H x 5 3/4" D. For 12 volt cars. Shpg. w., 7 lbs.
CR-10 5.00 Down Net 50.20
For 6 volt cars: Similar to above, but with 5 tubes and rectifier, no transistor, and 5" x 7" external speaker. Shpg. wt., 9 lbs.
CR-11 2.00 Down Net 45.20

ALSO Available for SPORTS CARS with * in this Chart




NEW! SCHAUER KAR-START

6 & 12 VOLT
STARTS WET OR COLD ENGINES INSTANTLY!

ONLY **5.15**

If you park your car outside in wet or wintry weather, you need Kar-Start. At instant of starting, Kar-Start sends five times the normal amount of spark from your plugs for sure-fire starts. Used for starting only. It is automatically disconnected when engine is running. Will not damage plugs or distributor. Simply, easily installed with just 3 quick connections. Save your battery, time and temper. Shipping weight 1 lb.
MS-710 for 6 and 12 Volt cars List 7.95 Net \$5.15

REAR SEAT AUTO SPEAKER KITS



6" x 9" KIT WITH CHROME OR GOLD GRILLE

Complete kit for adding second speaker in rear of your car. Includes a 6" x 9" PM speaker; 3-position selector switch for cutting in front, rear, or both speakers; dial plate with mounting bracket, knob, and hardware; chrome or gold grille; wire; and wiring instructions. Simple to install. Shpg. wt., 5 lbs.
SK-94 Speaker kit (specify chrome or gold grille) Net 3.45

DELUXE 6" x 9" KIT with 2.15 oz. ALNICO V MAGNET

Same as above but with deluxe speaker with extra-heavy Alnico V magnet (2.15 oz.). This is same speaker used in kits selling at twice the price. Shpg. wt., 5 lbs.
SK-37 Speaker kit (specify chrome or gold grille) Net 4.65

5" x 7" KIT

Same as SK-94 but with 5" x 7" speaker and grille (specify chrome or gold), 5 lbs.
SK-42 Net 3.05

FADER TYPE AUTO KITS

Rear-seat speaker kits identical to those above except with fader-type controls to cut either speaker in or out or balance both. Shpg. wt., 5 lbs. Specify chrome or gold grille.

SK-55 5" x 7" kit. Same as SK-42 but with fader control. Net 3.29

SK-95 6" x 9" kit. Same as SK-94 but with fader control. Net 3.69

DELUXE 6" x 9" FADER KIT

Deluxe kit with extra-heavy magnet 6" x 9" speaker, plus fader control. Specify chrome or gold grille. Shpg. wt., 5 lbs.
SK-56 6" x 9" kit. Same as SK-37 but with fader. Net 4.89


3 SECTION 59" AUTO ANTENNA



- Easy to Mount
- Pulls In Those Long Distance Stations
- Rust Proof Construction

\$7.89

Measures 23" collapsed and extends to 59". Employs polyethylene insulator — easy mounts on fender or trunk. Shpg. wt., 1 1/4 lb.
AA-21 Net 1.89



NEW! ALL TRANSISTOR CAR RADIO

- Needs No External Antenna
- Easily Installed — No Holes To Drill
- Built In Map Reading Light
- Non-Glare 2 Way Mirror
- No Dial Plate Necessary
- 12 Volt Operation Only

74.50
5.00 DOWN


Standard external antenna not needed—unit has built-in non-directional ferrite antenna—radio plays with constant volume regardless of car's direction.
Fully transistorized — Extremely low power drain
Interference reduced to an absolute minimum
Extremely powerful fringe area reception and true Hi-Fi reproduction
Uniquely constructed and mounted to withstand any shock or vibration
A revolutionary new concept in the design and placement of a car radio. The entire receiving unit of this unique all transistor radio has been engineered into a 2 way rear view mirror which easily replaced the standard mirror of any car.
CR-17 5.00 Down Net 74.50

NEW! "Spring Back" REPLACEMENT ANTENNA STAFF

ONLY **.99**

Stainless steel replacement staff easily replaces antennas lost through vandalism or accident. Powerful coil spring in the antenna base prevents deliberate or accidental "snap-off". Simple set screw mount on stub of broken antenna. Stainless steel for maximum strength and corrosion resistance. Overall length 28". Shpg. Wt. 1 lb.
AA-40 Net .99

8 ft. BATTERY BOOSTER CABLES



MS-766

1.78 set of 2

- A MUST FOR ALL CARS WITH AUTOMATIC TRANSMISSIONS

A life saver in case of battery failure. These heavy duty rubber covered cables are perfect for starting stalled cars, charging batteries, etc.—Rugged copper-clad positive active grips identified by Black and Red heavy vinyl covered handles. Shpg. wt., 3 lbs.
MS-766 8 ft. long, set of 2 Net 1.78
MS-767 12 ft. long, set of 2 Net 2.25

"Zippy" Drain Auger



3.89

• 15 ft. Super flexible cleaner
"Zippy" quickly cleans obstructions in drains, sinks, waste lines, tubs, eaves and gutters. Scaled down version of the professional tool. Designed for home, shop, garage and light industrial use. Flexible 15 ft. by 1/4" in. spring steel rod coils neatly in the canister when not in use. Only the length of rod required for the job is withdrawn from the canister. Reams out obstructions quickly, cleanly, easily. Cork-screw head allows tip to pass through crossbars without dismantling traps or drains. Entire rod retracts into the baked enamel finished, self starting steel container. Will not damage pipes as chemical cleaners do. Shpg. Wt. 4 lbs.
HD-683 Net 3.89
Giant "Zippy": Same as HD-683, but with 26 ft. rod. Shpg. Wt., 6 lbs.
HD-684 Net 5.99

MITYMITE BATTERY CHARGER



- KEEPS BATTERIES AT PEAK POWER
- RECHARGES RUN-DOWN BATTERIES
- AUTOMATICALLY CUTS OFF


FOR 6 & 12 VOLT BATTERIES

5.95

Keep your battery at peak power; prevent battery destruction caused by infrequent use or over use. Safe 1/2 Amp charging rate automatically cuts off when battery is fully charged. Operates on regular household current. For 6 or 12 Volt batteries. Trouble light indicates proper connection to battery. Will also recharge run-down batteries. Guaranteed for one full year. Size 4 1/2 x 1/2 x 2 1/2". Shpg. wt., 2 lbs.
MS-720 List 9.95 Net 5.95

LAFAYETTE is your HEADQUARTERS for TV ANTENNAS AND ACCESSORIES!

try to BEAT these ANTENNA PRICES!



REGULAR LIST 13.45
OVER 60% OFF!

- ALL ALUMINUM
- NO LOOSE PARTS
- FASTEST INSTALLATIONS

FULL 20 ELEMENT STACKED Snap Open Conical

in lots of 3
4.95 EACH

SINGLY EACH 5.25

Best antenna deal yet for servicemen-dealer-and installation specialists. All the most wanted features. Quickest-easiest installation possible. No loose hardware. All elements snap open and lock in without tools. Most efficient conical design for all reception areas. Two complete boys with Q bars, less most. Shpg. wt., 8 lbs. Via Express only. **4.95**

• "U-INSTALL-IT" KIT With All Angle Roof Mounts. Includes AN-28 antenna and installation Kit as shown with two 5 ft. masts. **5.25**

• "U-INSTALL-IT" KIT With Chimney Mount. Same antenna and accessories but includes chimney mount instead of roof mount. **Net 7.95**


• AN-32-WX Via Express only. Shpg. wt., 18 lbs. **Net 8.75**

• AN-43-WX Via Express only. Shpg. wt., 18 lbs. **Net 13.95**

FAMOUS BRAND Color 'Tenna

PRICE BREAK - Over 50% Off!

LIST 29.95
SALE 13.95!



Gold Anodized

- High Gain On All VHF Channels
- Completely Factory Preassembled
- Electronic Lens Design
- Highly Directional - Yagi Performance

Lafayette is the FIRST to offer this nationally tried and proven antenna at close to 25% off the regular dealer price. This is the same fine antenna with all its exclusive features—that sells for dollars more than our record-breaking price. Check these features: Electronic Focusing—High Gain—all VHF channel coverage—gold anodized quality construction—highly balanced—outstanding fringe area reception—compact design dynamically stallation—All-aluminum construction—automatic hardware. Shpg. wt., 8 lbs. Via Express only. **List 29.95**

Complete Kit of AN-51 antenna plus AM-12 mtg. kit as shown. Shpg. wt., 15 lbs. **Net 13.95**


• AN-51 WX—List 29.95 **Net 13.95**

• AN-52 WX—List 29.95 **Net 16.30**

NEW! SUPER FRINGE AREA ANTENNA

- THE MAXIMUM ANTENNA FOR YOUR AREA.
- MAXIMUM CONSTRUCTION.
- PERFECT 300Ω MATCH ON EACH CHANNEL.

The most recent advance in antenna design and construction. Extremely high gain and front to back ratio. Phasing relationship assures equal gain on all VHF channels. Eliminates channel interference. Elements are double locked in high impact Styrene plastic insulators. Automatic brackets lock and secure all elements. Completely preassembled. Entire antenna snaps open and locks in. Dual insulators prevent waver, slip and twist of elements. All aluminum construction. Single boy. Less most. Shpg. wt., 12 lbs.



14.55

• AN-37WX List 33.19 **Net 14.55**

• AN-38WX 2 boys stacked **Net 29.58**

• "U Install It" Kit. Includes AN-37WX and roof mount kit AM-10 with one 5 ft. mast. Shpg. wt., 20 lbs. **2.00 Down**

• AN-40WX Stacked Kit. Includes AN-38 and roof-mount kit with AM-11. Shpg. wt., 32 lbs. **2.00 Down**

• AN-41WX **Net 16.95**

• AN-42WX **Net 32.69**

TV PICTURE TUBE SHORT ELIMINATOR

- Burns off Picture Tube shorts
- Lengthens Picture Tube life




.99

Eliminates expensive picture tube repairs. No elaborate equipment needed. Repairs grid and cathode shorts in two minutes—without pulling the chassis! Easy to use—decontaminates cathodes—restores operation of brightness control. Can be used as often as needed. Simple "plug-in, switch-on" operation. Works with any TV picture tube. Shpg. wt., 1/2 lb. **Net .99**

TS-282

Famous Brand SUPER Color 'Tenna

20 Elements—Up to 125 miles
OVER 50% OFF



- ELECTRONIC LENS DESIGN
- HIGHLY DIRECTIONAL-YAGI ENGINEERED
- COMPLETELY PREASSEMBLED
- MORE GAIN ON ALL VHF CHANNELS

Well known, field proven, deep fringe antenna—at dollars below the regular dealer price. All the exclusive features that have made this antenna a national favorite for "problem area" reception. Electronic focusing—20 elements for more gain—quality construction—1" square crossarm—1" round driven elements—1" tubing boom brace—easy installation—automatic hardware—all aluminum construction. Dynamically balanced design—outstanding fringe area performance. Shpg. wt., 10 lbs. **Net 16.98**

• AN-63WX Kit AK-34. Includes AN-63WX SUPER color 'tenna; 20 ft. telescoping mast and accessories. Shpg. wt., 30 lbs. **Net 23.95**

• AN-64WX Kit AK-35. As above, including Alliance K-22 rotator and additional accessories. Shpg. wt., 52 lbs. **Net 51.40**

• AN-65WX **Net 16.98**

• AN-66WX **Net 16.98**

• AN-67WX **Net 16.98**

• AN-68WX **Net 16.98**

• AN-69WX **Net 16.98**

• AN-70WX **Net 16.98**

• AN-71WX **Net 16.98**

• AN-72WX **Net 16.98**

• AN-73WX **Net 16.98**

• AN-74WX **Net 16.98**

• AN-75WX **Net 16.98**

• AN-76WX **Net 16.98**

• AN-77WX **Net 16.98**

• AN-78WX **Net 16.98**

• AN-79WX **Net 16.98**

• AN-80WX **Net 16.98**

• AN-81WX **Net 16.98**

• AN-82WX **Net 16.98**

• AN-83WX **Net 16.98**

• AN-84WX **Net 16.98**

• AN-85WX **Net 16.98**

• AN-86WX **Net 16.98**

• AN-87WX **Net 16.98**

• AN-88WX **Net 16.98**

• AN-89WX **Net 16.98**

• AN-90WX **Net 16.98**

• AN-91WX **Net 16.98**

• AN-92WX **Net 16.98**

• AN-93WX **Net 16.98**

• AN-94WX **Net 16.98**

• AN-95WX **Net 16.98**

• AN-96WX **Net 16.98**


• AN-97WX **Net 16.98**

• AN-98WX **Net 16.98**

• AN-99WX **Net 16.98**

• AN-100WX **Net 16.98**

"U-INSTALL-IT" KITS!



All aluminum 8 element conical. Full sized. Rugged insulator block. Designed for rapid assembly. Fan front of 6 full length elements. Real value. Shpg. wt., 4 lbs.

• AN-11W **Net 2.40**

• AN-21W **Net 2.29**

• AN-20W 2 boys stacked **Net 4.39**

• "U Install It" Kit. Includes AN-11 and roof-mount kit with one 5 ft. mast. Shpg. wt., 11 lbs. **Net 4.95**

• "U Install It" Kit. With chimney mount instead of roof mount. Shpg. wt., 11 lbs. **Net 5.29**

• "U Install It" Kit. Includes AN-21W and roof-mount kit, with one 5 ft. mast. Shpg. wt., 11 lbs. **Net 4.70**

• "U Install It" Kit. With chimney mount instead of roof mount. Shpg. wt., 11 lbs. **Net 5.29**

TV TUBE BRITENER

.79 EACH

in lots of 10

Absolutely no tools or soldering needed for installing this handy inexpensive tube rejuvenator. You simply attach two plugs as directed on the instructions. For magnetic tubes and PARALLEL CIRCUITS only. Restores brightness contrast. MS-12 in lots of 10, each .79—singly .89

UNIVERSAL TV TUBE "BRITENER"

\$1.29 EACH

SINGLY

Restores brightness to dim TV picture tubes. Operates on all types—magnetic or electrostatic—and in oh circuits—parallel or series.

TS-170—in lots of 6 **each 1.29**

Singly **each 1.39**

300 OHM TWIN-LEAD

1.39

COPPER CONDUCTORS

per 100 ft. LO-LOSS POLYETHYLENE

High quality low-loss lead-in for all TV and FM installations. Polyethylene dielectric—standard copper leads. Shpg. wt., 2 lbs. per 100 ft. **1.39**

Stock No. WR-25—100 ft. **1.39**

500 ft. **5.75**

1,000 ft. **10.95**

TV ANTENNA MASTS

STEEL MASTS. New corrosion-resistant 5 ft. steel mast made to fit all antennas. One end is tapered. "Jam Fit" construction with locking key. 1 1/2" O.D.

TL-12W 5 ft. Wt., 2 1/2 lbs. **.69**

TL-13WX 5 ft. Wt., 4 1/2 lbs. **1.29**

TL-14WX 10 ft., 16 gauge. Wt., 8 lbs. **1.89**

ALUMINUM MASTS. 18 gauge-heavy wall-high tensile strength. Rust and corrosion proof. Swaged for stacking.

TL-60W 5 ft. Wt., 1 1/2 lbs. **1.20**

TL-17WX 10 ft. Wt., 2 1/2 lbs. **2.30**

10 Ft. Mast shipped via express only.

ECONOMY MOUNT

99¢

Can be erected in minutes; without special tools or drilling. Adjustable, two-section design permits unlimited spacing between brackets for maximum support of masts 1/2" to 1 1/2" O.D. Complete with two 12-ft. lengths of 1/4" galvanized steel bands and hardware. Shpg. wt. 3 lbs. **TS-82. Net Each .99**

GOLD ANODIZED ALUMINUM MASTING

IDEAL MAST FOR GOLDEN ANODIZED ANTENNA

This Golden Anodized aluminum mast will outlast any antenna. Made of a tough, extra strong, drawn aluminum alloy. This .050" wall mast is stronger than a 20 gauge steel mast. Permanently eliminates corrosion problems. Ends are swaged for "jam-fit" so that two or more masts may be telescoped together.

TL-11SW 5 ft. Wt. 1 1/2 lbs. **Net 1.70**

TL-116WX 10 ft. Wt. 2 1/2 lbs. **Net 3.26**

ALL CHANNEL'S "RIVIERA" WORLD'S MOST POWERFUL ULTRAFRINGE VHF—UHF—FM ANTENNA



GUARANTEED 200 MILE VHF RECEPTION OR YOUR MONEY BACK

- Receives channel 2-83 from all directions without a rotor
- Broadband UHF-VHF and FM, motorless all direction reception
- All aluminum flip-out assembly

Field tests reception on VHF of up to 200 miles has made possible this unprecedented guarantee. Here is an antenna with one transmission line for all UHF, VHF and FM stations in all directions without the use of a rotator. The nine position selector switch connected at the set electronically rotates antenna beam instantly without physically moving the antenna. Gain on channels 2-4 comparable to 4-bay conicals; on channels 7-13 comparable to stacked 10-element single channel yagis; on 14-83 comparable to bow-tie reflector, 16 1/2" doweled aluminum elements are 40 inches long. Complete with switch, coupler, 45" stacking bars and 2 7/2" angle type mast insulators for Polymicelene line listed below. Shpg. Wt. 10 lbs. **AN-135WX Less Most Net 19.85**

THE RIVIERA MUST BE USED WITH THE LOW LOSS LEAD IN WIRE LISTED BELOW

"U-Install-It" kit: Includes Riviera antenna, chimney mount, two five ft. masts, 100 ft. of Polymicelene 4 conductor lead-in wire, 8 stand off insulators and complete instructions. Shipping wt., 16 lbs. **AN-42WX 2.00 Down Net 29.95**


ALL CHANNEL LEAD-IN WIRE FOR USE WITH RIVIERA ANTENNA

Special 4 conductors, matched impedance transmission line. Low loss, micro-filled Polymicelene copperweld conductors.

WR-8—50 ft. length **Net 5.00** WR-18—100 ft. length **Net 8.90**

WR-9 75 ft. length **Net 7.50** over 100 ft., per 100 ft. **Net 8.90**

INSTALLATION ACCESSORY KITS



All the accessory items necessary to do a quick, easy installation from roof to receiver! You get an all angle roof mount—lightning arrester—75 feet of 300 ohm twin lead—6 insulated screw eyes—2 insulated mast standoffs and a 5 ft., 1 1/4" OD steel mast. Shpg. wt., 7 lbs.

AM-10W. eo. 2.95 Lots of 3, eo. 2.85

AM-11W with 2—5 ft. masts. Shpg. wt., 10 lbs. Singly, 3.55 Lots of 3, eo. 3.35

AM-12W Same as AM-10 but with chimney mount. Eo. 3.25 Lots of 3, eo. 3.15

AM-13W Same as AM-11 but with chimney mount. Eo. 3.85 Lots of 3, eo. 3.75

NEW! TV TUBE RESTORER

FOR ALL PICTURE TUBES EXCEPT 110" TYPES

LOCATES AND CORRECTS FOR

- OPEN CATHODE
- HEATER TO CATHODE SHORT
- OPEN CONTROL GRID
- CONTROL GRID TO CATHODE SHORT
- LOW EMISSION
- COMBINATIONS OF ABOVE

One simple unit provides the cure to any defective picture tube in any TV set. Works on electrostatic or electromagnetic focus picture tubes in series or parallel-wired filament TV sets. Corrects for dozens of picture tube faults.

TS-268 **3.23** Shpg. wt., 1 lb. **Net 3.23**

AMPHENOL

INDOOR TV ANTENNA WITH TRUE "VIDEO FIDELITY"

- Slender Line Styling With Foldaway Elements
- Slide Rule Tuning
- Transformer Coupling
- Power Packed Performance

Only Lafayette can bring you this sort of bargain—a truly acceptable indoor antenna at but a small fraction of its regular price. This is not just another indoor TV antenna, but designed for true video fidelity—featuring "slide rule" tuning with inductive reactance network for fine picture adjustment and transformer coupling for strict impedance matching. Elements fold from sight when not in use. You can look for and wide but nowhere will you find another antenna comparable to this AMPHENOL unit in beauty and performance or of this LAFAYETTE price! Get yours while they last—a word to the wise is sufficient!

AN-65 Indoor TV Antenna **Net 2.79**

UNBELIEVABLY PRICED AT

2.79

"TOP BUY" WHEN SOLD AT 4.95



TUNER CLEANER

- Infector Type
- Cleans & Lubricates
- Eliminates Noise
- Long Lasting Protection

New, wax-free lubricant. Contains no carbon tet. Non-toxic, non-inflammable. Hypo-style injector needle prevents drift and drip. Retards Corrosion—keeps tuners cleaner longer. Easily reaches hard-to-get at spots. Does not affect electrical properties—harmless to insulation and soldered joints. Easy-to-use—long lasting. Shpg. wt., 12 oz. **TS-324 Net .90**

TWO SET COUPLER

.55

in lots of 6

Uses one antenna for two sets. Compact electronic set coupler assures performance of two TV sets on one installation. Easy to connect. Nothing to go wrong. Shpg. Wt. 1 lb.

TS-326 **Each .59**

In lots of 6 **Each .55**

IT'S LAFAYETTE for POPULAR CITIZENS BAND TRANSCEIVERS


FOR: BUSINESS, INDUSTRY, BOATS, FARM, SPORTS, ETC.



22 recently assigned radio channels within the 26.965 to 27.225 megacycle range (11 meters) make possible 2-way communications in a great number of business and personal applications. Station license is easy to obtain — merely fill out single FCC form (supplied) . . . no exam or special skill is required.

GONSET G-12 MULTI-CHANNEL 2-WAY CITIZENS BAND RADIO

- 4 Crystal Controlled Transmit And Receive Channels
- Transmitter Tuning Indicator
- Adjustable Squelch



4 quartz crystal controlled channels (any 4 of the 22 authorized) provide fullest operational versatility—permit instant switch to other channels if voice traffic is especially heavy or interference is present on channel in use. Also allows various stations in system, such as cars, trucks, boats to be assigned different channel frequencies. Features press-to-talk switch on microphone, noise limiter, built-in speaker and adjustable squelch, resistant to moisture and impervious. Universal power supply for 117 VAC and 12 VDC. Tube complement: 6CX8 (Osc-Doubler-Final), 6AU6 (RF), 6UBA (Osc-Mixer), 6BM6 (1st IF), 6BA6 (2nd IF), 6AV6 (Det-1st Audio), 6AL5 (ANL-Gated Squelch), 6BQ5 (Audio Output/Mod). Complete with push-to-talk ceramic microphone, universal desk stand/mobile mounting bracket, and transmit and receive crystals for one channel. 4 1/2" H x 7" W x 10" deep. Shpg. wt., 13 lbs. HE-537WX Model 3316 5.00 Down Net 149.95

GONSET G-11 SINGLE CHANNEL CRYSTAL CONTROLLED TRANSCEIVER

Complete with press-to-talk microphone and set of transmit-receive crystals. Shpg. wt., 10 lbs.
HE-527WX Model 3303 For 115 VAC 5.00 Down Net 124.50
HE-528WX Model 3304 For 12 VDC 5.00 Down Net 124.50
HE-529WX Model 3305 For 6 VDC 5.00 Down Net 124.50
Model 3297 Mobile Antenna Cowl loaded whip. Shpg. wt., 2 lbs. HE-531 Net 13.50

INTERNATIONAL CRYSTAL "EXECUTIVE" CITIZEN BANDER


- 3 Crystal Controlled Transmitting Positions
- 2 Crystal Controlled Receive Positions
- Dual Conversion Superhet Receiver Tuning All 22 Channels



The International Crystal "Executive" class D Citizen band transceiver features push-to-talk operation, 3 crystal controlled transmitting positions, 2 crystal controlled receive positions, dual conversion superhet receiver tuning of all 22 channels, and crisp and clear full modulation. Has 11 tubes, 4 of which are multi-purpose, and one diode, resulting in 16 tube performance. High Impedance push-to-talk crystal microphone or carbon microphone input. Normally supplied with one transmit crystal for channel 9; 2 additional transmitting crystals and 2 receiving crystals available for any of the 22 channels. Operates on 115 VAC, 6VDC and 12 VDC. Supplied with power cord for 115 Volt operation, power cords for 6 VDC and 12 VDC available separately. Has attractive case for easy fixed station and mobile installation. Size 6" x 9" x 10" deep. Shpg. wt., 15 lbs.

HE-460WX 5.00 Down Net 169.50
HE-461 Power Cable for 6 Volt Operation Net 7.50
HE-462 Power Cable for 12 Volt Operation Net 7.50
HE-463 Transmit Crystal (Specify Channel or Frequency) Net 6.00
HE-464 Receive Crystal (Specify Channel or Frequency) Net 6.00
HE-465 Mobile Mounting Rock Net 12.50
HE-466 Hi-Impedance Push-to-Talk Microphone Net 9.50

JOHNSON VIKING MESSENGER FULLY ENGINEERED "INDUSTRIAL-TYPE" CITIZENS BAND TRANSCEIVER



Choice of 5 Channels at the flip of a switch. "More than just 2-way Citizen's Radio equipment" — the Viking Messenger is one of the very finest personal communications equipment available. Designed for reliability and easy installation in your home, business location, car, truck, or boat. Excellent receiver sensitivity and selectivity. Built-in Squelch, Automatic Volume Control, and Automatic Noise Limiter. Compact modern styling. Complete with tubes, push-to-talk high impedance ceramic microphone, and set of crystals for one channel. Crystals supplied will be for channel 1, 5, 7, 18 or 22 unless otherwise specified. 5 1/2" x 7" x 11 1/2" deep. Shpg. wt. 15 1/2 lbs.

HE-447WX Model 242-128 For 115 VAC and 12 VDC 5.00 Down Net 139.75
HE-448WX Model 242-127 For 115 VAC and 6 VDC 5.00 Down Net 139.75
Crystals in Matched Pairs For Channels 1 thru 23 (Specify Channel)
HE-449 250-901 thru 250-923 Per Pair Net 7.95

GLOBE CB-100 COMPLETE TWO-WAY CITIZEN BAND STATION



5 watts input power to the final amplifier. Full AM modulation. Crystal tolerance .005%. The unit meets all FCC requirements. Same model operates on either 115V AC or 12V DC. Extremely compact and light weight. Size: 3 1/2" x 13" x 10". Shpg. wt., 11 lbs.

MODEL CB-100. Complete with crystals and push-to-talk microphone. HE-600WX 5.00 Down Net 129.95

Optional Accessories for CB-100

External speaker with 15 ft. cord and plug. Shpg. wt., 5 lbs. HE-601 Net 6.95
12 Volt cable and plug, for mobile operation. HE-602 Net 2.75
Whip antenna, ADM Door mount HE-603 Net 3.95
Matched Crystals (specify frequency). HE-604 Net 5.90

The receiver section contains a 7-tube crystal controlled superheterodyne circuit with 3-channel selectivity. No tuning is necessary, channel selection with simple switch and illuminated jewel indicates channel in use. Highest receiver sensitivity and highest transmitter efficiency as no RF circuits are common to both receiver and transmitter. Rectifier circuit utilizes choke/capacitor high voltage filter system for extremely low AC hum level—such circuits found only in highest quality equipment. Very high image rejection due to 1680KC intermediate frequency. Excellent squelch circuit for quiet operation. Built-in limiter circuit permits mobile operation. The transmitter operates at the maximum allowable power.

ELECTRO-VOICE RME MODEL 4303 CITIZENS PORTABLE TRANSCEIVER


Hand-held completely transistorized "walkie-talkie" type radio transmitter and superheterodyne receiver for short range communication in the 11 meter citizens band. Complies with Part 15 FCC Rules and Regulations and requires no license or permit. Excellent for sportsman, surveyors, short-range industrial applications, etc. Employs 7 transistors and one diode. Complete with whip antenna and 2-6 volt batteries. 9 1/2" x 3 1/4" x 1 1/2". Shpg. wt., 2 lbs. HE-620WX 5.00 Down Net 99.50
BA-109 Extra Burgess Z4 Battery (2 required) Shpg. wt., 4 oz. Net Ea. .63

No License or Permit Needed

99.50



PHILMORE 11-METER CITIZEN'S BAND CLASS "D" TWO WAY RADIO KIT




3 CRYSTAL CONTROLLED TRANSMIT-RECEIVE CHANNELS FOR BUSINESS/HOME, COMMERCIAL, FARMS, BOATING. NO TESTS NOR SKILL REQUIRED FOR LICENSE; JUST FILL OUT FCC FORM ENCLOSED WITH KIT

for mobile operation taken from automobile cigarette lighter socket. Complete with 5 tubes, one crystal for any of the 3 channels incorporated, microphone, cabinet and operator's power supply and power cord. Size 10" W x 4 1/2" H x 10 1/2" Deep. Shpg. wt., 12 lbs.

Model TC11 For 115 Volt AC, less antenna HE-580 2.00 Down Net 39.95
Model TC612 For 6 and 12 Volt DC, less antenna HE-581 2.00 Down Net 44.49
Model TC15 7-Section Whip Antenna with base loading coil, for short range communication. HE-582 Shpg. wt., 2 lbs. Net 4.50

VOCALINE

THE COMMAIRE ED-27 is a compact, highly efficient transceiver. The receiver section employs a double conversion superheterodyne circuit and emphasizes excellent sensitivity and selectivity. The transmitter section features of full 5 watt input and a high quality modulator. SPECIFICATIONS: Selectivity: ± 5 kc at points 6 db down. Sensitivity: 0.1 microvolts. Noise immune. Patented squelch. Audio Output: 4.5 watts. Uses 10 tubes. Power Supply is transistorized. Power 115V AC and 6V DC or 115 V AC and 12V DC. Size: 5" x 9" x 7 1/2". Shpg. wt., 11 1/2 lbs. Complete with push-button microphone, short range antenna, crystals to operate on 27.105 mc. AC and DC line cords and mobile mounting brackets. HE-250WX 115 VAC/6 VDC 5.00 Down Net 143.60
HE-251WX 115 VAC/12 VDC 5.00 Down Net 143.60



REGENCY

The CB-27 was designed to give complete flexibility at operation on the class D Citizens Band. TRANSMITTER section provides choice of two channels for interference-free transmission. Unit comes equipped with crystal for one channel. Unit is factory aligned on an additional channel. Other features: Double conversion, superheterodyne design, adjustable squelch, noise limiter, illuminated slide rule dial, AVC and crystal controlled first oscillator.

Receiver
Tuneable chon. 1-22. Sens. 2uv or better. Selectivity: — 6 kc @ 6 db down and 14 kc @ 60 db down. Image rejection: 40 db or better. Double conversion superheterodyne. 1st osc. xtal controlled-1st IF 10.7 mc—2nd osc. tuneable-2nd IF 455 kc. Adjustable carrier-operated squelch operates reliably at 5 uv or less. Adjustable carrier-controlled series-gate noise limiter AVC 2 watts audio output-4" Alnico V speaker
Easy to read calibrated slide rule dial

Controls: Tuning, squelch, on-off/vol.
Transmitter
Hand-held microphone with push-to-talk button
Automatic modulation control
5 watts input power
Two switch-selected transmit channels available. One channel factory aligned and crystal furnished—additional channel factory aligned for easy crystal installation if desired.
Antenna matching over a range of 20-100 ohms.

General
Power Supply: 115 V AC (CB-27) or 12 V DC (CBM-27). Power Consumption 30 watts (standby) 50 watts (transmit) Size: 4 1/2" x 6 1/2" x 8 1/2". Shpg. wt., 11 lbs.
MODEL CB-27 Operates on 115 V AC. HE-488WX 5.00 Down Net 124.95
MODEL CBM-27. Operates on 12 V DC. HE-489WX 5.00 Down Net 124.95

ANOTHER LAFAYETTE SCOOP!

A TERRIFIC BUY FOR THE 24-50MC MOBILE AMATEUR AND FOR THE 27 MC (11 METER) CITIZEN BANDER. COMPLETE — ALL IN ONE —

- PROFESSIONAL-SIZE ALUMINUM SWIVEL BASE PERFORMANCE PLUS
- SPECIALLY STYLED CADMIUM PLATED PROOF SPRING PLUS
- 96" STAINLESS STEEL WHIP WITH REMOVABLE PLATED STEEL ADAPTOR

Regularly Priced at 14.95

ALL THREE YOUR PRICE **8.55**

Swivel ball mount base designed to be mounted on any surface. Spring holds rod in properly adjusted position and prevents rod damage from shocks and blows. Stainless steel whip made of special alloy for maximum resiliency and strength. Shpg. wt., 5 lbs. SP-156WX Net 8.55



FREE!

LIMITED TIME ONLY!

FREE 11 METER CITIZEN BAND ANTENNA WITH PURCHASE OF CITIZEN BAND TRANSCEIVER

(Does Not Apply To Kits HE15 Nor RME4303)

ANY ONE OF THE FOLLOWING:

HE-670WX Ground Plane Antenna Regular Price 15.63
HE-674WX Mobile Rear Mount Antenna Regular Price 18.52
HE-678WX Rear Bumper Mount Antenna Regular Price 17.25

48" CITIZEN BAND TELESCOPING ANTENNA

Ideal for mobile or fixed transceivers, miniature portable and pocket transistor radios, and a host of similar applications. The 4 section antenna is made of chrome-plated brass and plugs into a jack. Measures 48" fully extended and retracted is 11" to facilitate carrying in pocket. Complete with a flexible plastic case with slip-under protecting flap. Shpg. wt., 8 oz. F-440 Net .79

INTERNATIONAL CRYSTAL NEW 1960 CLASS "D" CITIZEN BAND CALL AND HANDBOOK

Approximately 50,000 up-to-date names, addresses and call numbers by districts. Also includes FCC rules and regulations, Radio District Map, Radio messages and call code, and valuable authoritative construction articles for citizen banders. BK-1320 Postpaid in USA Net 3.95

RETAIL INSTALLMENT CONTRACT

FOR OFFICE USE ONLY
Account Number _____

Buyer's Copy Mailed—Date _____
By _____

MINIMUM ORDER \$20.00 TOTAL CASH PRICE —
DOWN PAYMENTS
\$2.00 on Orders from \$20 to \$50
\$5.00 on Orders from \$50 to \$200
\$10.00 on Orders Above \$200

ADDITIONAL PURCHASES: Once you establish credit, you can "add-on" to your account with purchases of \$20.00 or more. No down payment required on "add-ons" or reopened accounts for less than \$100.00. Just list the items you want on the order blank, write "add to my account" and give your account number. Make certain you sign the Easy Payment Agreement.

Before filling out amounts see EASY PAY PLAN SCHEDULE and example. Figure your sums first on separate paper to avoid errors. USE INK. DO NOT ERASE OR CROSS OUT.

NOTICE TO THE BUYER: 1. Do not sign this agreement before you read it or if it contains any blank space. 2. You are entitled to a completely filled in copy of this agreement. 3. Under the law, you have the right to pay off in advance the full amount due and under certain conditions to obtain a partial refund of the credit service charge.

LAFAYETTE RADIO ELECTRONICS CORPORATION (SELLER)
165-08 LIBERTY AVE., JAMAICA 33, N. Y.

sells and buyer purchases merchandise as described on reverse side hereof to be kept in good repair and unencumbered at buyer's stated address. Seller shall retain title to and right to possession of merchandise until fully paid. Upon default of any payment or payments seller may declare entire unpaid balance due at once and may also repossess merchandise retaining previous payments as compensation for the use thereof. If proceeds of resale of merchandise are insufficient to cover buyer's obligation, buyer will pay the deficiency to seller; if proceeds result in overage, seller will pay such overage to buyer. Payments will be made to the place and/or to any party designated by the seller in writing.

LAFAYETTE RADIO ELECTRONICS CORPORATION (SELLER)

By _____ **BUYER SIGN HERE** Signed _____ (LS) DATE _____

RETAIL INSTALLMENT CONTRACT

(Please Print)
Name _____
Present Home Address _____
City _____ Zone _____ State _____
How Long At This Address _____ Telephone _____

To fill in spaces below correctly refer to EASY PAY PLAN Schedule on this sheet and note example.

1. Total Cash Price*			
2. Sales Tax (if any)			
3. Total (items 1+2)			
4. Down Payment See Down Payment Schedule			
5. Unpaid Balance (item 3 minus item 4)			
6. Credit Service Charge (See EASY PAY Schedule)			
7. EASY PAY BALANCE (Add items 5+6)			
Total EASY PAY Price (Add items 3+6)			

EXAMPLE—(Standard Terms)

If Item (5) Unpaid Balance	= 106.50
Item (6) Credit Service Charge	= 11.00
Item (7) EASY PAY Balance	= 117.50
Your Monthly Payment (See Schedule) is	10.00
You will pay \$10.00 for 11 months or	110.00
And your FINAL Monthly payment will be	7.50

Buyer agrees to pay \$ _____ each month beginning one month after shipment for _____ months and a FINAL Monthly payment of \$ _____

EASY PAY ORDERS SENT SHIPPING CHARGES COLLECT. DO NOT INCLUDE SHIPPING CHARGES.

NEW "EASY PAY PLAN" PAYMENT SCHEDULE

If Unpaid Balance Is	Standard Terms		Extended Terms		If Unpaid Balance Is	Standard Terms		Extended Terms	
	Credit Service Charge	Monthly Payment	Credit Service Charge	Monthly Payment		Credit Service Charge	Monthly Payment	Credit Service Charge	Monthly Payment
UP to 20.00	2.00	5.00	AVAILABLE ONLY		100.01 — 110.00	11.00	10.00	15.00	6.00
20.01 — 30.00	3.00	5.00	ON ORDERS WITH UNPAID BALANCES OVER \$50.00		110.01 — 120.00	12.00	10.00	17.00	6.00
30.01 — 40.00	4.00	5.00			120.01 — 130.00	13.00	10.00	19.00	7.00
40.01 — 50.00	5.00	5.00			130.01 — 140.00	14.00	11.00	21.00	7.00
50.01 — 60.00	6.00	6.00	7.00	5.00	140.01 — 150.00	15.00	12.00	23.00	8.00
60.01 — 70.00	7.00	7.00	8.00	5.00	150.01 — 160.00	16.00	12.00	24.00	8.00
70.01 — 80.00	8.00	7.00	9.00	5.00	160.01 — 180.00	18.00	13.00	27.00	9.00
80.01 — 90.00	9.00	8.00	11.00	5.00	180.01 — 200.00	20.00	14.00	30.00	10.00
90.01 — 100.00	10.00	9.00	13.00	5.00	200.01 — 225.00	22.50	15.00	34.00	11.00

For purpose of receiving credit for above EASY PAY PLAN purchase, the buyer makes the following representation

With Whom Living: Parents Spouse Alone Landlord's Name and Address: _____

Name Address: _____ Permanent Previous (Check which)

Age (Must Be Over 21): _____ Single Married Divorced Name of Spouse: _____

Spouse Employed By: _____ (Address) _____ Salary _____

Draft Classification: _____ Reserve Status: _____ Have you bought from Lafayette before? Yes No

On Time Payment? Yes No If yes, please give your Lafayette Time Payment Account Number. No. _____

Real Estate Holdings—Address: _____ City _____ State _____

Recorded In Name of: _____ Present Value \$ _____ Mortgage \$ _____

Name Present Employer: _____ If self-employed, so state _____ Tel. No. _____ Position Badge No. _____ Salary _____ How Long (Years) _____ (Months) _____

Business Address: _____ Any Other Income Source \$ _____

Name Farmer Employer: _____ How Long (Years) _____ (Months) _____

Bank Account With: _____ Savings Checking (Address) _____

First Trade Reference: _____ (Address) _____ Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____

Second Trade Reference: _____ (Name) _____ (Address) _____ (City and State) _____ Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____

Third Trade Reference: _____ (Name) _____ (Address) _____ (City and State) _____ Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____

Nearest Relative: _____ (Name) _____ (Address) _____ (City and State) _____ Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____

Name (DO NOT LIST THOSE WITH WHOM YOU RESIDE) _____ Address _____ Relationship _____

CUT ALONG DOTTED LINE

To order the merchandise you want to buy on Easy Terms, use your Lafayette order blank. The amounts shown in the EASY PAY PLAN SCHEDULE for either the STANDARD or the EXTENDED terms, depending upon which terms you are choosing. Do not fill in the space indicating sales tax unless delivery is to be made in New York City. Supply the answers to all the questions below the contract, which must be filled in correctly and signed before we can process your order. Be sure to give complete names and addresses of all references you list. Attach the remittance covering your down payment, and mail your order. As soon as your credit is approved, your order will be shipped. Your first payment is not due until 30 days after shipment. Lafayette has made this plan as simple and confidential as possible.

— NO RED TAPE: Any responsible person over 21 with a steady source of income can get credit. Lafayette's Easy Pay Plan is available to all residents of the United States. It cannot be applied to shipment to U.S. possessions or territories, to A.P.O. or F.P.O. addresses, or to foreign countries.

HOW TO BUY ON NEW EASY TERMS

- ★ **New Lowest Down Payments**
Only \$2.00 Down on orders from \$20 to \$50
Only \$5.00 Down on orders from \$50.01 to \$200
Only \$10.00 Down on orders over \$200
- ★ **Longer Repayment Period**
New Optional Extended Easy Pay Terms permit payments up to 24 months.
- ★ **It's Easy To Open A Lafayette Account**
Fast — Economical — Confidential
- ★ **Immediate Handling**
Orders shipped immediately upon approval of credit
- ★ **Simplified "Add-On" Purchases**
No Down Payment For "Add-On" Purchases of less than 100.00

Take Advantage of these new EASY PAY Features TODAY

Lafayette **NEW! EASY PAY PLAN TERMS...**
Makes it Even Easier for YOU to BUY NOW

IT'S SIMPLE TO OPEN AN ACCOUNT — CHOOSE EITHER STANDARD OR EXTENDED TERMS
Lafayette's Easy Pay Plan enables you to order on new easier terms the equipment you want now even if you are short of ready cash. This sensible plan permits you to pay out of future earnings — and at the lowest carrying charges! You can buy whatever you please under this plan, including High Fidelity Systems; individual Hi-Fi units and accessories; Test Equipment; Kits; Public Address and Intercom Equipment; Amateur Gear; Power and Hand Tools; Photographs and Record Changers; Telescopes; Binoculars and Photographic Equipment; Books and Manuals; etc.

TERMS OF LAFAYETTE'S NEW EASY PAY PLAN

Minimum Order Orders must have a total cash value of \$20.00 or more.
Down Payment Only \$2.00 down on orders from \$20 to \$50.
Only \$5.00 down on orders over \$200 \$50.01 to \$200.
(larger down payments reduce the service charges and monthly payments)

Service Charge: You may choose either the Standard or the Extended plan to obtain the lowest service charges for the greatest length of time.
Monthly Payments: You can make your monthly payments under standard or Extended terms shown in the new easy payment table. The extended terms permit smaller monthly payments over a longer period, up to 24 months. When ordering, please indicate in the space provided on the order blank, your choice of standard or extended terms.

REFUND OF SERVICE CHARGES FOR ADVANCED PAYMENT

All credit service charges will be refunded if payment is completed within 60 days of shipment. Take the full time to pay if you wish. However, you may pay off your account at any time and obtain a partial refund of the credit service charge.

ADDITIONAL PURCHASES

Once you have established credit with Lafayette you can "add-on" to your account with any purchase of \$20.00 or more. No down payment is required on either "add-on" or reopened accounts for purchases of less than \$100.00. You simply list the items wanted on the order blank, write "add to my account," and give your account number. Make certain that you sign the Easy Payment Agreement below.

ON ORDERS AS LOW AS \$20!

OUTSTANDING HAM and SHORT WAVE EQUIPMENT



NEW NATIONAL NC-60 SPECIAL

National's new all-wave low-priced receiver which features continuous coverage of AM Broadcast, Amateur and World Wide Short Wave Bands; brilliantly styled by Peter Quay Yang for easy operation, ready reading and attractive decor. Features Include: 4 separate bands — 540 Kc-1600 Kc; 1.6-4.5 Mc; 4-12 Mc; 10.5-31 Mc with police, CD, marine, aircraft, amateur, etc. stations clearly marked; plus 0-100 logging and bandspread scale. Bands spread operative, on all bands. Audio section drives built-in speaker for front panel phone jack. Has AM, CW switch, standby-receive switch, 2 degrees of selectivity, complement of 4 tubes plus rectifier superheterodyne circuit. Finish is two tone black and gray enamel. Size: 7 1/2" x 8 1/2" x 13 1/2". Shpg. wt., 15 lbs.

HE-200WX 5.00 Down Net 59.95

FREE WITH PURCHASE OF NC-60!

SHORTWAVE ANTENNA KIT — Complete antenna kit for 50 ft. installation. Shpg. wt., 2 lbs.


Plus

MATCHING EARPHONES — for efficient private listening. Shpg. wt., 1 lbs.

(This Offer Good for Life of This Catalog)

NC-60 receiver, ant. kit and earphones, shpg. wt., 18 lbs.

SP-157WX 5.00 Down Net 59.95



NATIONAL NC-109 RECEIVER

National's general coverage receiver for CW, AM and SSB reception that incorporates many features of their most expensive types but still sells at a low price. These exclusive features are "Microtone" crystal filter in IF section for 5 different degrees of selectivity; sharp phasing notch over 60 db deep for interference rejection; separate product detector for CW and SSB reception; mode selector switch includes accessory position for crystal calibrator or phono input. Coverage is from 540 Kc-40 Mc on 4 bands, with bandspread scales for special amateur bands all clearly marked; logging scale included. Conelrad (CD) points clearly marked. Size 16-13/16" x 10" x 10 1/2". Shpg. wt., 35 lbs.

HE-205WX 5.00 Down Net 169.95

NC-109XCU. Plug-in crystal calibrator. Shpg. wt., 2 lbs.

HE-206 2.00 Down Net 20.95

NFM-83-60 N.F.M. Adaptor. Shpg. Wt., 5 lbs.

HE-207 2.00 Down Net 33.95

FREE WITH NC-109 RECEIVER!

NATIONAL NTS-1 MATCHING SPEAKER — Regular 17.50 Value!

(This Offer Good For Life of This Catalog)

SP-158 WX — NC-109 and NTS-1 5.00 Down 169.95

LAFAYETTE BREAKS PRICE on FAMOUS



NATIONAL VFO-62
Regularly 69.95
Now ONLY 49.95!

• THE FIRST SELF-POWERED VFO FOR 6 and 2 METERS

Highly versatile Variable Frequency Oscillator with full coverage of both 6 and 2 meter amateur bands. Completely self-powered plugs into 117 VAC and transmitter crystal socket. Has front panel crystal socket for instant selection of favorite crystal, controlled internal crystal socket for use with 1 mc calibrating crystal, and front panel mode switch and band switch. Built-in phone jack for direct detection of calibrating markers, and vernier drive for precise tuning control. Complete internal shielding. Size 5 1/2" D x 6 1/2" W x 5 1/4" H. Shpg. wt., 6 lbs.

HE-213 2.00 Down Net 49.95

TRANSISTOR-DIODE CHECKER KIT

ANOTHER LAFAYETTE FIRST


- QUALITATIVE CHECK OF P-N-P and N-P-N TRANSISTORS FOR LEAKAGE AND GAIN
- CHECKS DIODES
- CHECKS SELENIUM RECTIFIERS

7.95

Lafayette's tried and proven transistor checker is indispensable for ultra fast, reliable transistor testing. It checks P-N-P and N-P-N transistors for leakage and shorts on a multi-colored scale and indicates at once whether transistor is good or bad. Selector switch permits direct GAIN reading on a calibrated GAIN scale without needle deflecting off scale. Permits rapid check of diode and selenium rectifier quality by indicating forward and reverse current characteristics. Sturdy black bakelite case and attractive black baked enamel aluminum panel with white lettering. Complete with detailed instructions and up-to-date manufacturers GAIN standards. 6 1/4" x 3 3/4" x 2". Shpg. wt., 2 lbs.

KT-84A—Transistor-Diode Checker Kit Net 7.95

Lafayette PROFESSIONAL QUALITY AMATEUR COMMUNICATION RECEIVER




KT-200
IN KIT FORM
64.50
5.00 DOWN

HE-10
WIRED AND TESTED
79.95
5.00 DOWN

Superheterodyne Circuit Utilizing 8 Tubes & Rectifier Tube

- BAND SPREAD FOR EASY TUNING
- BUILT-IN "S" METER WITH ADJUSTMENT CONTROL
- EXCELLENT SELECTIVITY
- ACCESSORY POWER SOCKET PROVIDED
- ALL TRIMMERS PRE-ALIGNED
- COVERS 455KC. to 31MC. IN FOUR BANDS
- VARIABLE BFO AND RF GAIN CONTROLS
- BUILT IN PRE-CALIBRATED "S" METER
- SWITCHABLE AVC AND AUTOMATIC NOISE LIMITER
- ALL MAJOR COMPONENTS PRE-MOUNTED
- DUAL 4 AND 8 OHM OUTPUT-IMPEDANCES



High sensitivity superheterodyne circuit utilizes 8 miniature tubes plus rectifier tube and transformer input, full wave rectifier. The 80-40-20-15 and 10 meter amateur bands are clearly indicated on the illuminated dial face, and can be easily tuned with the pre-calibrated band spread. The receiver has complete band switching, thus eliminating the need for bothersome plug-in coils. Band spread is laid out on easy-to-read 0-100 scale, and features a weighted control knob which offers smooth, precise tuning. Coverage of from 455 KC to 31 MC is obtained through the use of four switchable ranges (455-1600 KC/1.6-4.8 MC/4.8-14.5 MC/10.5-31 MC). All controls, switches and phone jack are located on the front panel. Receiver sensitivity is 1.25 microvolts for 10 DB signal to noise ratio. Selectivity is -60DB at 10KC image rejection is -40DB at 3MC. Panel is gray metal with white lettering, and controls are back with aluminum trim. Hinged top makes inside of receiver readily accessible to operator. 7 1/2" H x 15" W x 9" D. Tubes: 3-6BD6, 2-6BE6, 2-6AV6, 1-6AR5, 1-5Y3. Shpg. wt., 22 lbs.

KT-200 WX 5.00 Down Net 64.50
HE-10 WX Same as above, factory wired & tested. 5.00 Down Net 79.95

MOSLEY CITIZENS BAND 27MC ANTENNA



- BEAM TYPE
- CONSTRUCTED OF DURABLE LIGHTWEIGHT ALUMINUM

MODEL A-311 3 ELEMENT BEAM 9.3 db gain over dipole means effective radiated power is multiplied by 8. A five watt rig with an A-311 delivers the equivalent power of a 40 watt transmitter on a dipole. Boom is 12" long, tuning radius is 9.5 ft. Shpg. wt., 20 lbs.

AN-57WX 2.00 Down Net 37.50

TRANSISTORIZED CODE PRACTICE OSCILLATOR



2.29

- MINIATURE-PORTABLE
- SELF CONTAINED BATTERY POWER SUPPLY
- PRODUCES CLEAR, CRISP, CW NOTE

Here is an ideal, inexpensive code practice oscillator for the amateur radio enthusiast. Long 38 inch wire from oscillator to earpiece, allows two persons to practice without interference. The unit is completely portable, and weighs only 6 oz. Tone produced is clear and crisp, similar to that received during F.C.C. licensing examinations. Low voltage transistorized circuit utilized 1.5 volt penlight type battery which completely eliminates any possible shock hazard. Earpiece is crystal type, and housed in sanitary plastic. Shpg. wt., 5 oz.

F-429 Oscillator only Net 2.29

Above oscillator plus adjustable telegraph key (MS-319). Key has spade lug connectors, making it possible to disconnect the key from the oscillator and use it separately if desired. Shpg. wt., 9 oz.

F-479 MS-319 Key and Oscillator Net 2.95

10 WATT PUSH PULL HI-FI AMPLIFIER KIT

24.50




- BUILT-IN PREAMPLIFIER FOR GE RELUCTANCE CARTRIDGE
- SELECTOR SWITCHES PERMIT CHOICE OF THREE INPUTS
- 4, 8 AND 16 OHM OUTPUTS
- EASY-TO-FOLLOW INSTRUCTIONS

This new, economy hi-fi amplifier has many deluxe features for exceptional performance. The three inputs are radio/crystal phono pickup, magnetic phono pickup and microphone. A selector switches the input from radio/crystal to microphone or magnetic pickup, depending upon the position of a rear apron slide switch. OUTPUT—Rated 10 watts, peak 18. FREQUENCY RESPONSE—±1 db 30-15,000 cps. DISTORTION—1.5% harmonic, 4% intermodulation of 8 watts. 4 CONTROLS—Input Selector; Volume; Treble; Power-On-Off-Bass. TREBLE CONTROL—Flat response up to 15 db boost. BASS CONTROL—Flat response up to 18 db attenuation. OUTPUT IMPEDANCES—4, 8 and 16 ohms. TUBES—6SC7, 6SL7GT, 2-6V6GT and 5Y3GT rectifiers. AUXILIARY AC OUTLET—Distinctive Hammett finish. SIZE—10 1/2" x 6 1/2" x 5 1/2". WEIGHT—8 1/2 lbs. For 110-120 Volts. Complete kit with coded wire, highest grade solder and detailed instruction manual.

KT-91 2.00 Down Net 24.50

HALLICRAFTERS



MODEL S-38E
NEW LOW COST RECEIVER

Hallcrafters' economy model SWL receiver pulls in everything on its highly sensitive AC-DC superhet circuit: 4 tubes plus one rectifier, with 5" P.M. speaker delivering 2 watts audio. Has tip jacks for phones, standby-receive switch AM-CW switch for talk or code. COVERAGE: 4-BANDS: Standard Broadcast and 3-SW bands ranging from 1650 Kc-32MC. Features large Overseas Dial, with specific foreign stations dotted 0-100 separate bandspread dial. Also covers police, aircraft, ship-to-shore and all amateur bands. Operates on 105-125 DC or 60 cycle AC. Size 12 1/2" x 7 1/2". Comes in attractive gray steel cabinet with silver frame trim. Shpg. wt., 14 lbs.

HE-100 5.00 Down Net 59.95

MODEL S-38EM Receiver with mahogany over metal finish.

HE-101 5.00 Down Net 59.95

MODEL S-38EB Receiver, with blond over metal finish.

HE-102 5.00 Down Net 59.95



MODEL SX-110
AMATEUR-SWL RECEIVER

Superheterodyne receiver covers 540 KC (broadcast band) to 34 MC in four bands. Features slide rule type dial and electrical bandspread over the 10, 15, 20, 40 and 80 meter amateur bands. Separate bandspread tuning condenser. Switchable crystal filter and built-in "S" meter. All controls are on front panel, and include main and band spread tuning, AM-CW switch, sensitivity, BFO pitch, on/off/line, volume, receiver-standby, selectivity, crystal filter-phasing, noise limiter, and headphone jacks. Receiver uses either 3.2 or 500 ohm speaker. Antenna may be doublet, single wire, ground plane or beam type. Utilizes seven tubes plus one rectifier 6SG7, first IF amp, 6SK7 second IF amp, 6SC7 BFO and audio amp, 6K6GT, audio output, 6H6 AN L-AVC-detector, 5Y3 rectifier. Output: 2 watts. Gray steel cabinet with chrome trim. Size: 18 1/4" W x 8" H x 10 1/4" D. 117 AC. Shpg. wt., 32 lbs.

HE-108WX 5.00 Down Net 159.95

HAMMARLUND RECEIVER HQ-100



Sensitivity and selectivity place this receiver in the really "hot" class. Continuously tunable from 540 Kc to 30 Mc in four bands. Electrical bandspread tuning with dial markings every 10 Kcs on 80, 40 and 20 meter bands; every 20 Kcs on 15 meter band, and every 50 Kcs on 10 meter band. Q-multiplier permits continuously variable selectivity. Sensitivity of 1.75 microvolt produces 10-1 signal-to-noise ratio. Voltage regulated and temperature compensated. AVC on RF and IF stages. 10 tube circuit with automatic noise limiter. Antenna compensation for variable loading effects. For 105-125 volts, 50-60 cps. With "S" meter; combination clock and automatic timer optional, 1 1/2" L x 9 7/16" H x 9 1/4" D. Shpg. wt., 33 lbs.

HQ-100 Receiver less clock-timer.

HE-150WX 5.00 Down Net 189.00

MODEL HQ-100C. Receiver with clock. Shpg. Wt., 34 lbs.

HE-151WX 5.00 Down Net 199.00

MODEL S-100. Matching speaker in cabinet. Shpg. Wt., 10 lbs.

HE-152 3 lbs. Shpg. Wt., 14.95

MODEL XC-100. 100 KC crystal calibrator. Shpg. Wt., 3 lbs.

HE-153 Net 15.95

E. F. JOHNSON



"ADVENTURER" CW-TRANSMITTER

Loaded with features for both novice and experienced amateur, the new Viking "Adventurer" kit is a completely self-contained, single-knob bandswitching and effectively TVI suppressed transmitter. The "Adventurer" operates crystal or external VFO control. The RF lineup consists of a 6AG7 oscillator/multiplier and an 807 power output tube. Front panel meter switching monitors final grid or plate currents—clean and crisp break-in keying is accomplished by breaking both oscillator and final amplifier circuits simultaneously. Size: 10 1/2" x 8 1/2" x 7 1/2". Shpg. wt., 19 lbs.


MODEL 240-181-1 Above in kit form. With tubes.

HE-423WX 5.00 Down Net 54.95

MODEL 250-40 Speech amplifier/Modulator kit for Adventurer. With tubes. Shpg. wt., 1 lb.

HE-444 Net 12.25

PHILMORE COMMUNICATIONS RECEIVER KIT



Here is a high quality superheterodyne receiver offered at an unbelievable low price. It contains features usually found only in receivers costing many times the price. The CR-SAC employs a highly sensitive, 4 tube & rectifier superheterodyne circuit. Covers all ham bands, 80 through 10 meters. FEATURES: Continuous coverage from 455 kc (broadcast band) to 30 mc. Receives fire police, ship-to-shore etc. Full electrical bandspread on each band. Adjustable B.F.O. Built-in noise limiter. Built-in "S" meter. Provisions for use with any type of antenna. Input jack for insertion of external Q multiplier. Built-in speakers with heavy magnet. Shpg. wt., 13 lbs.

CR-SAC Receiver kit less cabinet.

HE-583 2.00 Down Net 39.95

MODEL CR. metal cabinet for CR-SAC. Shpg. wt., 8 lbs.


HE-584 Net 7.95



HERE IT IS!

The Greatest Value In The Citizens Band Field!

FOR INDUSTRY, FOR FARM, FOR BOATS, FOR PERSONAL COMMUNICATION




LAFAYETTE 11 METER CITIZENS BAND 2-WAY SUPERHETERODYNE RADIO TRANSCEIVER

COMPLETELY WIRED NOT A KIT

At Sensational, Low Price of

59.95

Delivery, Approximately Feb. 15, 1960



Not Superregenerative but **SUPERHET**

- 5 Crystal Controlled Transmitting Channels
- Superheterodyne Tuneable Receiver Over Full 22 Channel Band
- 4 Dual Function Tubes, plus 2 Single Function Tubes, Plus 2 Rectifiers For 12 Tube Performance
- Surprising Reception on Land and at Sea . . . Compares Favorably With Transceivers Costing 3 Times As Much

Transceiver features 5 watts input fully modulated, RF stage in transmitter and receiver, RF transmitting indicator and Transmit-Listen spring return switch; 3 watts audio output; planetary vernier tuning; noise limiting, squelch ON-OFF switch; all coils ferrite tuned. Output impedance matches 52 and 72 ohm antenna, and has Amphenol type coax connector for operating into dipole, ground plane or rod antenna. Has large 4" PM speaker; input jack for crystal or ceramic microphone; power receptacle in rear for AC line and 6 or 12 volt external power supply. Complete with one transmitting crystal, microphone that can be hung on cabinet, and brackets for easy mounting of unit in car, boat, etc. Operates on 115 volts AC. Addition of 6 or 12 volt power supply (separately supplied) adapts transceiver for mobile operation. Attractive slate gray chip-proof cabinet has holder for call letters card and microphone. No examination is required for your license; just fill out and submit enclosed FCC application. Size 10 1/2" W x 5 1/2" H x 6 3/4" D. Shpg. wt., 11 lbs.

ME-15 5.00 Down Net 59.95

POWER SUPPLY Adapts ME-15 for mobile operation. Complete with cable, 6 or 12 volt vibrator and mounting flanges. Completely enclosed. Size: 4 1/2" D x 6" W x 4" H. Shpg. wt., 4 lbs.

ME-16 For 12 volts Net 9.95
ME-18 For 6 volts Net 9.95

ANTENNA: Base loaded telescoping whip antenna with PL259 coax connector. Mounts directly on rear of cabinet. Ideal for indoor use. Extends to 45" and telescopes to only 15". Shpg. wt., 2 lbs.



ME-17 Net 6.95

CRYSTALS, TRANSMITTING For any of the 22 channels. Specify channel or frequency.

ME-830 Net 2.95

EICO TEST EQUIPMENT KITS

SUPERIOR-PACO



NEW! MODEL 666K DYNAMIC CONDUCTANCE TUBE AND TRANSISTOR TESTER

An ideal tube tester for color and monochrome TV servicing. Tests all receiving tubes, including 4, 5, 6, 7-pin, octal, loctal, miniature 7 and 9-pin, sub-miniature, 5, 6, 7-pin (in-line base) and 8-pin (circular base) receiving tubes, transmitting and special-purpose tubes, VR, cold-cathode rectifiers, magic eye and ballast tubes. Tests color and black-and-white TV picture tubes with accessory adaptor. Measures transistor collector current and shows current amplification factor. Individual test of multi-section tubes. Measures Gp, Gm and also leakage in ohms. 4 1/2" 200 μ A D'Arsonval meter movement, in clear lucite case; For 105-130 volts, AC 50/60 cps. 12" x 15" x 4 1/4". Shpg. wt., 18 lbs.

TE-151WX Kit 5.00 Down Net 69.95
Model 666. As above, but factory wired and tested.
TE-152WX 5.00 Down Net 109.95

MODEL 625K TUBE TESTER

Cathode Conductance type of tube tester features 10 individual level-action switches for testing each tube element. Tests all std. tubes including 9-pin miniature, VR, magic eye and pilot bulbs. Provides knock-out for addition of new socket. Illuminated roll chart gives instant test setting. Provides 2 grid-cap connections. Tests shorts and open elements. Protective over-load bulb also acts as fuse. 4 1/2" meter. All components and instruction manual supplied complete. For 115V 60 cycles. 12 1/2" x 9 1/2" x 4 1/4". Shpg. wt., 12 lbs.

TE-153 Kit 2.00 Down Net 34.95
Model 625. As above, but factory wired and tested.
TE-154 2.00 Down Net 49.95
Model L-1 Lid (cover) for 625K or 625 Shpg. wt., 3 lbs.
TE-155 Net 3.98
Model 625CK. Same as 625K but with Counter Display Case. Shpg. wt., 17 lbs.
TE-156 KIT 2.00 Down Net 44.95
Model 625C. As above, but factory wired and tested.
TE-157 5.00 Down Net 59.95

MODEL CRA PICTURE TUBE ADAPTER

Model CRA. Adapts #625 and #666 or similar Tube Testers for checking all sizes of TV picture tubes. Measures cathode emission; tests for filament continuity; shorts between elements. Complete with standard 12-pin socket, octal plug-in connector and 4-ft. cable to permit testing tube without removal from set. Shpg. wt., 2 lbs.

TE-160 Net 4.50

MODEL 950K R.C. BRIDGE & R-C-L COMPARATOR

Latest bridge-type professional instrument featuring the valuable Comparator Range for measuring unknown capacitance, resistance and inductance with a complementary component as a standard. Transformer operated assures safe operation. Direct scale on panel reads 0.5 ohms - 500 megohms resistance (4 ranges), 10 mfd - 5000 mfd capacitance (4 ranges), and power factor. Kit includes precision calibrating resistor. Unique comparator range has ratio from 0.05 to 20 (400 to 1). Leakage testing of all capacitors at rated dc working voltage with internal (variable) 0-500 vdc source. Electron-ray tube as both bridge balance and capacitor indicator. Attractive, durable case, neat easy-to-read characters. Size: 8" x 10" x 4 1/4". Shpg. wt., 8 lbs.

TE-214 Kit 2.00 Down Net 19.95
Model 950. As above, but factory wired and tested.
TE-215 2.00 Down Net 29.95

MODEL 232K PEAK-TO-PEAK VACUUM TUBE VOLTMETER

A precision unit with advanced engineering features. 11M Ω input impedance. 1% precision ceramic multiplier resistors used. Measures directly peak-to-peak voltage: 0-4, 14, 42, 140, 420, 1400, 4200. DC/RMS sine volts: 0-1.5, 5, 15, 50, 150, 500, 1500 (up to 30,000 volts with MYP probe, and 250 mc with PRF probe). Ohms: 0.2 ohms to 1000 megohms in 7 ranges. Easy calibration. 4 1/2" meter, can't burn-out circuit. Zero center. With new AC/DC Uni-Probe - half turn to select DC or AC/ohms. Exceptional stability and accuracy. All components and instructions supplied. For operation of 105-125 50/60 cps AC. Size: 8 1/2" x 5" x 5". Shpg. wt., 7 lbs.

TE-176 Kit 2.00 Down Net 29.95
Model 232. As above, but factory wired and tested.
TE-177 2.00 Down Net 49.95

MODEL 221K VTVM

A precision VTVM for fast operation and lifetime dependable service. 4 1/2" meter, can't burn out circuit. New zero center. Totals 15 ranges - AC/DC volts: 0-5-10-100-500-1000 v. (30,000 volts and 200 MC with MYP-1 and P-75 probes). Ohms: 0-1K ohms, 0-1-10-100-1000 megohm. DB: -20 to +55 in 5 ranges. New stable double triode balanced bridge circuit - 25 megohm DC input impedance. 115v., 60 cycle. 9-1/16" x 6" x 5". Includes all parts and tubes and instructions. Shpg. wt., 10 lbs.

TE-180 Kit 2.00 Down Net 25.95
Model 221. As above, but factory wired and tested.
TE-181 2.00 Down Net 39.95

MODEL 324K RF SIGNAL GENERATOR

For IF-RF alignment, signal tracing and trouble-shooting of TV, FM, AM sets all the fundamentals; marker generator for alignment of new h-f and older i-f TV IF's. Range: 150 kc-145 mc on fundamental; 111-435 mc on calibrated harmonics $\pm 1.5\%$ frequency accuracy. Internal 400 cps sine-wave modulation variable from 0-50%. Colpitts oscillator. Variable gain external modulation amplifier; Turret-mounted, slug-tuned coils. RF output 100,000 microwatts. AF output up to 10 volts. Output impedance is 50 ohms. For 105-125V. AC 50/60 cps. Size: 8 x 10 x 4 3/4". Shpg. wt., 10 lbs.

TE-242 Kit 2.00 Down Net 26.95
Model 324. As above, but factory wired and tested.
TE-243 2.00 Down Net 39.95

MODEL 460K NEW WIDE BAND SCOPE

Excellent Lab precision scope featuring Push-pull direct coupled vertical amplifier with high sensitivity; 25 mv/in. Response flat from DC to 4.5 mc, useful to 10 MC. Ideal for reproduction of 3.58 mc color TV sync. burst. 4 step freq.-compensated attenuator in both AC, DC positions. Also internal voltage calibration. Automatic sync limiter and amplifier. 2X-full screen horizontal positioning. Sweep-freq: 10 to 100 Kcps with external capacitor for la-freq. sweeps. Pre-set TV V & H sweep positions (30 and 7875 cps). Variably lit graphed 5" screen. Very high input impedance. Complete with all components and instructions for easy assembly. 13 x 8 1/2 x 16". For 105-125 vac, 50-60 cycles. Shpg. wt., 30 lbs.

TE-222WX Kit 5.00 Down Net 79.95
Model 460. As above, but factory wired and tested.
TE-223WX 5.00 Down Net 129.50

MODEL 425K 5" OSCILLOSCOPE

New, professional oscilloscope kit, for precise servicing of TV, FM and AM. Push-pull deflection and .05 to .1 Rms volt/inch sensitivity. Response, flat from 5 cps to 500 kc, useful to 2.5 mc. Wide range sweep from 15 to 75,000 cps. External sync input. Direct connection to CRT plates. 6.3V line test signal output. 1 meg input impedance. Intensity modulation. Tubes: 3-6SN7, 2-6J5, 2-5Y3, 58P1 CRT. For 110-120V, 60 cycles AC. All components supplied with portable steel case, schematic and pictorial diagrams. Size 8 1/2" x 17" x 13". Shpg. wt., 29 lbs.

TE-226WX Kit 2.00 Down Net 44.95
Model 425. As above, but factory wired and tested.
TE-227WX 5.00 Down Net 79.95

NEW! MODEL 540K UTILITY TESTER

An all-in-one Multi-Range ac/dc voltmeter, ammeter, ohmmeter, wattmeter and leakage checker. Indispensable in home repairs of electrical appliances, and in automotive trouble-shooting of batteries, generators, distributors, etc. 3 1/2" meter ranges: Volts AC/DC 0-7.5-15-30-300. AC/DC currents: 0-15 amps. Ohms 0-100 ohms. Capacitor leakage test. All components and instructions supplied. 3 1/2" x 6 1/2" x 3 1/2". Shpg. wt., 3 lbs.

TE-173 Kit Net 12.95
Model 540. As above, but factory wired and tested.
TE-174 Net 15.95

MODEL 1120K RETMA CAPACITANCE SUBSTITUTION BOX

Ideal equipment for development, designing, servicing work. Enables rapid substitution of wide range of RETMA capacitance values from 0.0001 to 0.22 MFD in an operating circuit to determine value needed for best performance and to find value of badly damaged or illegible capacitors. Minimum accuracy $\pm 10\%$. Uses silver-mica and malded plastic (or sealed in plastic) capacitors, rated approx. 600 volts. Size: 3 1/2" x 6 1/2" x 3 1/2". Shpg. wt., 2 lbs.

TE-218 Kit Net 5.95
Model 1120. As above, but factory wired and tested.
TE-219 Net 9.95

MODEL 1140K SERIES/PARALLEL R-C COMBINATIONS BOX

An extremely valuable combination of the model 1100K Resistance Box and the Model 1120K capacitance box with additional switching facilities that permit selection of any resistance alone, any capacitance alone, or any combination of resistance and capacitance in either series or parallel. Also open circuit and short circuit positions. Same specs as #1100 and #1120. With convenient jack-top binding posts. Shpg. wt., 4 lbs.

TE-212 Kit Net 13.95
Model 1140. As above, but factory wired and tested.
TE-213 2.00 Down Net 19.95

MODEL 147AK DELUXE SIGNAL TRACER

A deluxe instrument with unsurpassed testing facilities, engineered for high sensitivity as well as good audio quality. Features high gain RF and low gain audio channels. Both visual and aural monitors. With shielded RF crystal demodulator, valuable noise locator circuit, built in calibrated wattmeter, substitute test speaker, amplifier and output transformer. Output for VTVM or scope. Triode input circuit for extreme low noise. Hum free operation. Complete with all components and instructions with probes. For 105-125 vac 50/60 cycles. 8 x 10 x 4 3/4" Shpg. wt., 11 lbs.

TE-216 Kit 2.00 Down Net 24.95
Model 147A. As above, but factory wired and tested.
TE-217 2.00 Down Net 39.95

SUPERIOR TW-11 TUBE TESTER

Tests all tubes including 4, 5, 6, 7, octal, lock-in, peanut, banam, hearing aid, Thyratron, miniature, sub-miniature, neon, sub-miniature, proximity fuse type, etc. Will test for "shorts" and "leakages" up to 5 megohms. Uses the new self-cleaning lever action switches for individual element testing. The user can instantly identify which element is under test. Truly tests tubes with tapped filaments as any of the pins may be placed in the neutral position when necessary. Individual sockets for each type of tube. No combination sockets used. Built-in roll chart provides complete data. Line voltage control compensates for variations between 105 and 130 volts. Jack on front panel for plugging in phones or amplifier in detect mode.

Operates on 105-130 volts, 60 cycles AC. Housed in an oak cabinet complete with cover. 11 1/4" x 13" x 6" Shpg. wt., 15 lbs.

TE-506 2.00 Down Net 46.55

SUPERIOR MODEL 70 UTILITY TESTER

Specifically designed as an appliance and utility tester, it performs testing operations while units are in operation, in many cases. Will test toasters, irons, broilers, clocks, fans, fluorescent lamps, auto systems. Also has scales for measuring AC and DC voltages, AC and DC current, resistance, leakage (ohms scale from 0.5 Megohms). Voltage scales 0-150; 0-300. Amps Scales 0-15 amp. Comes with instructions and leads. Shpg. wt., 3 lbs.

TE-513 Net 15.53

SUPERIOR MODEL TV-50A GENO METER

Superior's new Model Genometer is a versatile all-inclusive generator which provides all the outputs needed for servicing AM and FM. Amplifiers, and Black and White or color TV. It is really 7 signal generators housed in one unit, producing these necessary signals: R.F. Signal generator for AM and FM - for all kinds of AM and FM RF circuits. Generates from 100KC to 60MC on fundamentals and from 60MC to 180MC on powerful harmonics, separate or modulated RF available. Variable Audio Frequency Generator - with 400 cycle sine wave or 300-20,000 cycle peaked wave audio signal available for checking distortion in amplifiers, amplifier gain, etc. Bar Generator - to place 4-16 horizontal or 7-20 vertical bars on TV screen for adjusting linearity controls. Cross Hatch Generator - Creates interlocked pattern for correct- ing ion trap adjust; Dot Pattern - dot pattern helps adjust for color convergence; Marker Generator - 13 marker points provided. Size 10" x 16" x 14 1/2". wt., 13 lbs.

TE-510 2.00 Down Net 46.55

KINGSTON PROBLEMMASTER

A unique test instrument combining the features of a highly versatile probe with a neon checker. Its built-in capacitive network permits bypassing stages, checking open capacitors, isolating defective stages without external signal generator, and elimination of time consuming capacitor substitution. Shpg. wt., 1 lb.

TE-497 Net 4.95

PACO MODEL V-70 VACUUM TUBE VOLTMETER KIT

7 DC and RMS AC voltage ranges to 1500 volts. 7 peak-to-peak voltage ranges to 4000 Volts. 7 ohmmeter ranges to 1000 megohms. Special PACE 5" acrylic, cased meter. Attractive, easy-reading two color panel. Rugged ripple-finished steel cabinet, size 7 1/2" x 5 1/2" x 4 1/2". Complete with all parts and instructions. Shpg. wt., 6 lbs.

TE-455 Kit 2.00 Down Net 31.50
Model V-70W, as above, but factory wired.
TE-456 Shpg. wt., 8 lbs. 2.00 Down Net 47.50

TE-457. AV-1 HF Crystal Probe far above 1 ta. Net 5.95
AV-2 High Voltage Safety Probe. Permits reading up to 60,000 V. Shpg. wt., 1 lb.
TE-458 Net 5.95

MODEL C-20 RATIO BRIDGE KIT

Capacity Ranges from 10 mmd to 2000 mfd. Resistance Ranges from .5 ohms to 200 megohms. Radio test ranges from .05 to .20. Tests leakage of mica, paper, and electrolytic capacitors. In attractive, ripple finished steel cabinet and easy-reading 2 color panel. Dimensions: 7" x 11 1/2" x 5". Complete with all parts and step-by-step instructions. Shpg. wt., 9 lbs.

TE-459 Kit 2.00 Down Net 20.95
Model C-20W. As above but factory wired.
TE-460 2.00 Down Net 31.50

MORE LAFAYETTE SPECIAL VALUES!

NEW! The "ULTRA" Electro-Tool Kit

7.95



- Designed with the Technician in mind
- Professional Quality Throughout
- All the most often needed tools

The finest-most compact carefully selected tool kit we have ever offered. Each component tool chosen to offer utility and quality. The "ULTRA" kit contains the following: 3 1/2" Insulated side cutters, 5" Insulated chrome plated diagonal, 6" offset open-end wrenches, 5" long nose, 30 watt soldering iron, 3 offset tweezers, 3/32nd screwdriver handle, 3/32nd screwdriver blade, punch-wrenches covering from 1/4" to 1/2", 5" chrome screw driver blade, shockproof amberoid chuck handle, #1 recessed screwdriver blade, 5/32nd nut driver blade, solder and flux. Pliers insulated with 10,000 volts, hand honed cutting edges. Side cutters have beveled nose, diagonals have provision for wire stripping, long nose has "wrench" grip jaws and cutters. The entire set is nested in a zippered, fitted, lined book type carrying case with handle. Measures a scant 9" x 5" x 2". Shpg. wt., 2 1/2 lbs. Net 7.95 HD-345

LAFAYETTE'S AMAZING NEW 4-TRANSISTOR RADIO



16.95

Quite frankly, the exceptional tonal quality and precision workmanship of this radio make it one of the finest transistor radio values Lafayette has yet offered. Highly sensitive and selective, this radio will surprise you with its performance over the complete broadcast band. A perfect gift for the whole family—use it for baseball and football games, picnics, beaches or as a handy radio in the home. Printed circuit construction insures trouble free performance and extra long life. Extraordinary indoor or outdoor reception is provided by the built-in ferrite loop-stick antenna and PM speaker. The plug-in earphone cuts out built-in speaker for completely private listening. Only one small battery, crystal earphone with 3' flexible cord with separate leather carrying case. Size: 2 1/2" W x 4" H x 1 1/4" D. Shpg. wt., 1 1/4 lbs. Net 16.95 FS-204

Extra Battery for Above Net 9.95 Burgess 2U6 type (1 required) Shpg. wt., 2 oz. BA-178

FAMOUS BRAND 2-STATION INTERCOM



Specially Priced 12.50

- ALL-METAL UNBREAKABLE CABINETS
- VERY SMART STYLING
- FOR 117 VOLTS AC OR DC
- SENSITIVE—PICKS UP SLIGHTEST SOUNDS AT A DISTANCE
- FOR HOME OR OFFICE
- IDEAL BABY SITTER OR SICK ROOM WATCHER

COMPLETE WITH 50' CABLE Here is a FAMOUS-MAKE 2-station electronic Intercom PRICED SO LOW WE DARE NOT MENTION THE MANUFACTURER'S NAME. Sensitive—picks up sounds from across the room. Beautifully styled to grace any home or office. Master station has volume control and talk-listen switch. Remote is always "open," making it ideal for listening to baby, sick room, invalids, children at play—or for store to stock-room, restaurant to kitchen, etc. Alineo 5 pm speakers. Costs less than a penny a day to operate. Complete system includes Master, Remote and 50' cable. Simple to operate, easy to install—virtually foolproof. Size of each station approximately 8" x 4" x 4". Shpg. wt., 6 lbs. PA-12 2 Station Intercom System Complete Net 12.50



NEW! THE AUTO BARO-ALTIMETER

6.95

- SHOWS CHANGES IN ALTITUDE WHILE DRIVING
- FORECASTS WEATHER
- INVALUABLE FOR THE AUTO TRAVELER

Here's an instrument which is as important to every driver as a compass is to a ship's captain. It accurately forecasts tomorrow's weather today (by barometric pressure) and indicates your exact altitude while you drive along. Meter reads altitude from -400 to 10,000 feet above sea level, and is housed in durable, vibration-proof plastic case. The Auto Altimeter comes complete with mounting bracket, and step-by-step installation and operation instructions. Also included is a handy chart which converts all numerical barometric changes, into the coming day's weather forecast. F-483 Net 6.95

Wollensak

TAPE RECORDERS AT PRICES YOU CAN AFFORD!



SPECIAL PRICE 139.50



SPECIAL PRICE 237.50

MODEL T-1500 HI-FI TAPE RECORDER—POPULAR SALES RECORD SMASHER!
 • 10 WATTS PUSH-PULL OUTPUT • 40-15,000 CPS
 • 0.8% I • SIMPLIFIED KEYBOARD CONTROL • INGENUOUS PORTABLE DESIGN — WEIGHS ONLY 18 lbs.
 A truly reliable and superbly designed tape recorder. Supplied complete with ceramic wide-range microphone, 1 reel of tape, 1 empty takeup reel, range microphone, 1 reel of tape, 1 empty takeup reel, radio-TV attachment card and Hi-Fi cable. 6 1/2" x 10 1/2" x 1 1/2". Shpg. wt., 21 lbs. For 110-120 volts 60 cycles AC. Also available in 50 cycle units; please specify. RK-405WX Reg. 199.50 5.00 Down Net 139.50


NEW! MODEL T-1515-4 FOUR TRACK STEREO HI-FI TAPE RECORDER
 • Doubles Stereo Playing Time And Quadruples Monaural Playing Time Per Roll Of Tape
 Reg. Price 229.50 OUR SPECIAL PRICE 167.50 5.00 DOWN
 The Hi-Fi enthusiasts dream in a compact portable tape recorder for true stereo performance. Has all the styling and superb features of the famous monaural T-1500, plus stereo head and built-in second preamplifier. Plays 2 and 4 track monaural and 2 and 4 track stereo. Records up to 4 separate monaural tracks on a single roll of tape. 6 1/2" x 10 1/2" x 1 1/2". Shpg. wt., 24 lbs. RK-417WX Reg. 229.50 5.00 Down Net 167.50

NEW! MODEL T-1600 ELECTRONICALLY CONTROLLED RECORDER—SENSATIONAL FOR: DICTATION... HI-FI • Automatic Stop, Rewind, Replay and Turn Off
 New Rack Space Bar provides instant and immediate replay of any part of the tape. PUSH-TALK control in microphone permits operation from remote location. All other features and specifications similar to Model T-1500 plus added function indicator lamps. With remote control, ceramic microphone, 2 reels, tape and cards. Shpg. wt. 23 lbs. RK-407WX Reg. 299.50 10.00 Down Net 237.50

NEW MODEL T-1616 STEREO RECORDER SPECIAL PRICE 261.25
 Same features as Model T-1600 plus IN-LINE stereo phone playback head and built-in second preamplifier. Shpg. wt., 26 lbs. RK-408WX Reg. 329.50 10.00 Down Net 261.25

SPECIAL! TABLE TENNIS SET

Complete PING PONG SET FOR 4 at 1/2 USUAL PRICE REG 8.95 3.95



- Play Singles or Doubles
- "Buffalo" Pebbled Rubber Face
- American Style Paddles
- Regulation Balls

Four 3 ply latex wood paddles. Maximum strength with minimum weight. "Buffalo" pebbled rubber faces for the most in ball control. Lacquered, standard American style handles. 6 1/2" x 6" taped net. Heavy duty offset clamps—will not bend—net can't sag. Net extends past table edge for regulation play. Six regulation balls—touch celluloid—uniformly sized. Includes rule book. Shpg. wt., 3 1/2 lbs. SE-10 Net 3.95



IT'S A WINNER!

NEW LAFAYETTE "tiny" 6 Transistor Radio!



SENSATIONAL PERFORMANCE in a Small Package!

- 6 ULTRA-MODERN TRANSISTORS PLUS GERMANIUM DIODE
- VEST POCKET SIZE—ONLY 4" H X 2 1/2" W X 1 1/4" D
- EARPHONE JACK BUILT IN FOR PRIVATE LISTENING
- FULL TONE DYNAMIC SPEAKER • TROUBLE-FREE PRINTED CIRCUIT
- BUILT-IN FERRITE BAR ANTENNA • SUPERHETERODYNE CIRCUIT
- RUGGED PLASTIC CASE • ECONOMICAL—USES ONLY ONE BATTERY

Engineered and constructed with the jewel like precision of a fine watch . . . true superhet circuit with push-pull audio output powers either the built-in dynamic speaker or the personal-type earphone. The trouble-free printed circuit utilizes six ultra modern transistors plus germanium diode. Super sensitive . . . built-in ferrite-rod antenna brings in distant stations like locals. High on power, low on battery drain . . . employs single long-life standard 9 volt battery for economical service. Housed in smartly designed black and gold case of rugged, durable plastic. Soft leather carrying case with attached earphone pouch. "On-off" volume control plus large easy to read tuning dial. Covers 550-1600Kc. Just 4" H x 2 1/2" W x 1 1/4" Thick and weighing a mere 10 ounces—a true purse/pocket portable. Lafayette "Tiny" 6-Transistor Radio—including battery, carrying case, and earphone for personal listening . . . all at an unbelievably low price! Shpg. wt., 2 lbs. FS-206 "Tiny" 6-Transistor Radio . . . Net 24.95



USE YOUR "TINY" TRANSISTOR RADIO AS A CORDLESS HOME TABLE RADIO

Just think . . . simply by combining this handsome speaker unit with your FS-206 "Tiny" Transistor Radio, you have an attractive Cordless Transistor Table Radio. The large 4" speaker provides a sound quality that is equal or superior to the best table radios. Beautifully styled and finished in an attractive cherry mahogany wood, this unit is perfect for use anywhere in your home . . . an excellent table radio or simply by unplugging the FS-206 you have a pocket size portable. Size: 8" H x 10 1/2" L x 4" D. Shipping weight 4 lbs. SK-144 Cordless Radio Enclosure . . . Net \$6.95



REGULAR ~~\$48.50~~ **24.95** 2.00 Down INCLUDING EARPHONE BATTERY AND CARRYING CASE

ENCLOSURE ONLY **6.95**

THE PERFECT COMBINATION Lafayette FS-206 "Tiny" Transistor Radio and SK-144 Cordless Radio Enclosure. Shipping weight 6 pounds. FS-206 2.00 Down \$28.95 **29.95**


LAFAYETTE "B" BATTERY ELIMINATOR and CHARGER for TRANSISTOR RADIOS



2.95

This simple "B" battery and eliminator has provision for replacing snap terminals on all 9-volt transistor batteries. Now when indoors you can operate your portable transistor set on regular 110V AC house current without using up your expensive "B" battery. . . . Best of all you may also recharge your used battery for many extra hours of use. Complete with AC cord and assorted snap terminals to fit all 9-volt transistor batteries. Size: 3 1/2" W x 3 3/4" H x 2 1/2" D. Shpg. wt., 1 lb. F-481 . . . Net 2.95

DUAL Wide Angle Tweeter LAFAYETTE SCOOP! Quantity Limited



SPECIAL WAS 5.95 NOW **3.95**

ADD TO YOUR PRESENT SPEAKER FOR A 2- OR 3-WAY SPEAKER SYSTEM

Modernize your high fidelity listening by adding this wide-angle dual-tweeter to extend treble range in a 2-way or 3-way speaker system. Mounts directly on any 12" speaker and converts it to a coaxial type. Response 1500 to 16,000 cps. Recommended crossover 2500 to 4000 cps. Heavy magnets for high efficiency with 18,000 gauss flux density. Dispersion angle approx. 125° horizontally. Impedance 16 ohms (2-8 ohm units in series). Will handle up to 20 watts program in 2 or 3-way system. Incorporates specially designed chrome-plated steel bracket of rigid construction to prevent resonances. Measures 12" L x 2" D x 2 1/8" H overall. Shpg. wt., 2 lbs. SK-100—Dual Tweeter . . . Net 3.95

Sensational LAFAYETTE f1.8 TRIPLE TURRET 8mm MOVIE CAMERA

MORE CAMERA for the Money than any Other



- ✓ CHECK the features!
- ✓ Then CHECK the PRICE!

29.95
Comparable Value 59.50

- 3 Fast f 1.8 Lenses. • 4 Speeds—including Slow Motion. • Single Frame Exposure. • "Combo-View" finder—for normal, wide angle and telephoto areas. • "Drop in" Spool Loading. • Built-in Exposure Guide. • Die Cast Aluminum Body. • Slide Rule Footage Indicator.

Truly modern—truly versatile—and truly inexpensive! Lafayette's "8-T3" puts movie-making in the snap-shot class. Fast f 1.8 lenses—normal wide angle and telephoto for fine color movies even in dim light. Fixed focus on all three—never needs "fumble-focusing." Single dial exposure setting—for all three lenses. Positive lock turret switch from normal to telephoto to wide angle—in an instant. Even beginners get perfect movies every time. The lensatic optical viewfinder frames

the area for each separate lens. "Drop-in" spool loading—easy and economical—makes reverse loading an impossibility. All lenses recessed in their own sun-shades. Four operating speeds plus single frame exposure for trick effects. Heavy duty—governor controlled—spring wind motor. The "8-T3" offers more for less money—than any other 8mm movie camera. Shpg. wt., 3 lbs. F-470 Camera only . . . 2.00 Down . . . Net 29.95 F-469 Leather Case for "8-T3" 8 oz. . . . Net 2.95

NEW! Cine "X" Meter

- Mounts on Turret!
- Fast! Easy! Direct Reading!
- Accurate - Versatile - Compact



7.75

Designed specifically for movie camera owners. Direct reading—nothing to remember—correct exposure shown in "f" stops. Any "turret" camera becomes a camera with "built-in" exposure meter. Just remove a lens not in use and attach the Cine "X" Meter. Aim your camera—read exposure—and shoot! Calibrated for exposure from f:1 to f:32. ASA index from 8 to 200. Eliminates "mental conversion" when using filters. Just phase filter in Cine "X" Meter for reading to use when filter is on lens. Perfect color temperature sensitivity—accurate exposures—even in poor light. Can be hand held or hung on chain. Includes sun shade, dust cap, adaptor and instructions. Shpg. wt., 8 oz. F-499 . . . Net 7.75

Matched MOVIE OUTFIT

- Matched to Take MOVIES—Show MOVIES
- Unmatched in PRICE and VALUE!
- Dollars below the regular price! • Includes New Cine "X" Meter!

86.99



Everything you need for movie making and showing fun. No need to "shop" for unmatched equipment—no need to pay more for fine home movies. You get all this: Lafayettes f1.8 Triple Turret 8mm Movie camera . . . Hallday M-1000 500 watt projector . . . 30 "X40" glass beaded folding tripod screen . . . 2 light bar . . . camera case . . . 2 400' reel cans . . . Cine "X" Electric Eye light meter. Unbeatable for foolproof shooting and showing of indoor and outdoor movies. Shpg. wt., 30 lbs. F-540 . . . 5.00 DOWN . . . Net 86.99

- 30 "X40" glass beaded folding tripod screen. Shpg. wt., 10 lbs. F-536 . . . Net 9.75
- 2 light bar—holds still or movie cameras. 6 ft. cord. Shpg. wt., 1 1/2 lbs. F-537 . . . Net 2.50
- 300 watt Reflector type photoflood bulbs. Shpg. wt., 1 lb. F-539 . . . Net, ea. .95
- 400' 8mm Reel and Can. Shpg. wt., 14 oz. F-538 . . . Net .95

LAFAYETTE RADIO

165-08 LIBERTY AVENUE, JAMAICA 33, N. Y.

BULK RATE U. S. POSTAGE PAID New York, N. Y. Permit No. 8486

ABCDE 12345