

LAFAYETTE

RADIO ELECTRONICS


Spring Catalog No. 653



PA SYSTEMS



MUSICAL INSTRUMENTS



PORTABLE RADIOS



HI-FI COMPONENTS

**OUR NEWEST
STORE...
WASH., D.C.
AREA
See Page 3**




TAPE RECORDERS



PHOTOGRAPHY EQUIPMENT



CB EQUIPMENT



LIVE BETTER ELECTRONICALLY WITH LAFAYETTE

LAFAYETTE

MAIL ORDER & L. I., SALES CENTER

111 JERICHO TURNPIKE
(West of So. Oyster Bay Rd.)

SYOSSET,

L. I., N. Y. 11791

Shop-by-Phone Dept. Other Departments
516 WALnut 1-7500 5 6 WALnut 1-7700

OTHER STORES

NEW YORK

BRONX
BROOKLYN
JAMAICA
MANHATTAN
SCARSDALE

MASS.

BOSTON
NATICK

NEW JERSEY

NEWARK
PARAMUS
PLAINFIELD

MARYLAND
MT. RAINIER

FOR COMPLETE ADDRESSES AND
STORE HOURS See Page 3

FOR LAFAYETTE "ASSOCIATE
STORE" LOCATIONS See Page 125

FOR EASY PAY INFORMATION

See Center Insert A

FOR INDEX See Center Insert B



MODEL HB-500

139⁵⁰

\$7.00 Monthly

LAFAYETTE Deluxe Solid-State 5-Watt Dual Conversion Citizens Band Transceiver

The Perfect Unit For Mobile

- Full 5-Watt Performance
- 12 Crystal Transmit and Receive Positions
- 23 Channel Tunable Receiver With Spotting Switch
- Multi-Stage Automatic Noise Limiting Circuit
- Dual Conversion Receiver with 5/10 μ V Sensitivity
- Mechanical Filter For Razor Sharp Selectivity
- "S" Meter and 5x3" front-mounted Speaker
- 15 Transistors, 4 Diodes, plus 1 Thermistor
- Dependable Sealed Relay Switching
- Panel-controlled Variable Squelch
- $\pm .003\%$ Crystals Exceed FCC Spec.

QUALITY MECHANICAL FILTER



Advanced circuit features include a costly mechanical filter that provides razor-sharp selectivity . . . virtually eliminates interference from stations on adjacent channels—a quality exclusive feature not generally found on other CB units!

It's Small . . . Quiet . . . Powerful!

- ✓ Only 3" high—fits easily in any car
- ✓ Special multi-stage noise-limiting circuit ends problem of mobile noise
- ✓ The same output as the most powerful tube unit —yet uses only 1/50th of the battery power



If you're looking for a high-performance CB transceiver in a small, compact size, you'll want the HB-500! Using advanced solid-state circuitry, this transceiver offers full 5-watt performance, yet is small enough to fit conveniently into the most compact car. And, battery drain is so low as to be negligible—the transceiver draws as little as .12 amps on receive, .85 amps on transmit. As a result, you need neither heavy-duty battery nor generator—an important advantage in mobile applications! The transmitter features full crystal control on any 12 of the 23 CB channels. Dual conversion receiver with better than .5 μ v sensitivity offers 12 crystal-controlled channels, plus full 23 channel tuning. A 455 Kc mechanical filter provides ultra-sharp receiver selectivity—virtually eliminates adjacent channel interference! Full fidelity voice reception is assured by the use of a powerful push-pull circuit that supplies up to 2.7 watts of audio into a big 5x3" front-mounted speaker. A powerful 3-stage transmitter offers full modulation capability and delivers a signal that's all audio—you can lower your voice to a whisper and still hit 100% modulation! And you get built-in reliability, 9 rugged, heat-resistant silicon mesa transistors (superior to conventional germanium) are used in critical areas to assure dependable, failure-

free operation. Other features include an efficient multi-stage automatic noise limiter, variable Squelch for silencing the receiver on standby, spotting switch for exact frequency location on tunable receiver, "S" meter, earphone jack, and illuminated channel dials. Supplied complete with special easy-mount mobile bracket with exclusive "quick-release" feature, push-to-talk dynamic microphone and .003% tolerance transmit and receive crystals for channel 12. For operation on 12V DC negative or positive ground with DC cable supplied. Size: 3Hx1 1/4"Wx6 1/4"D. Shpg. wt., 12 lbs.

99 N 3027WX Model HB-500 (12v DC)	Net 139.50
99 N 3043C Receive crystal (specify channel) $\pm .003\%$	Net 2.50
99 N 3042C Transmit crystal (specify channel) $\pm .003\%$	Net 2.50
Direct plug-in antenna (shpg. wt., 1 lb.)	
99 N 3015	Net 3.95

Model HB-501 Solid State AC Power Supply

Matching solid state AC power supply for HB-500 for fixed station operation (at home, business, office). Transceiver rests on power supply to form an attractive integrated unit. Size: 1 1/4"x6"x2 1/2". Shpg. wt., 10 lbs.

99 N 3028W	Net 16.95
------------	-----------

LAFAYETTE — Foremost Supplier Of Electronics

MAIL ORDER DIVISION

Our modern Mail Order Headquarters, located on over 8 acres of land, includes expanded warehouse facilities plus the most modern handling equipment to give you quicker service. Within 24 hours after receipt, most orders are processed, picked, wrapped and shipped on their way.

RETAIL STORE DIVISION

Visit any Lafayette store and see a wide assortment of merchandise from this catalog as well as many non-catalog items. Also be sure to see the custom-designed Sound Studios and Lafayette's Ham Shack. Trained, courteous sales personnel will help you with your selections. For Associate Store Locations See Page 125

NOW IN WASHINGTON D. C. Area

Just Northeast — Adjoining D.C. Line

Another new interesting Lafayette Store has opened adjoining Northeast Washington D.C. providing everything in electronics for the Home, Industry and Laboratory. Trained, courteous sales personnel will be happy to show you the latest Stereo Hi-Fi in the famous Lafayette Sound Studio; CB and Ham Equipment, Tools, Cameras, TV and Radios and much more. Be sure to stop in and let Lafayette help you "Live Better Electronically".

MT. RAINIER/HYATTSVILLE MD.

3191 Queens Chapel Rd. (Rt. 500)
(Corner Queens Chapel & Chillum Rds. — Rt. 501)
"Queenstown Shopping Center"
Phone: 301 779-7020

Open Mon., Thurs., Fri., — 9:30 — 9:30 PM
Tues., Wed. — 9:30 — 6:30 PM
Sat., — 9:00 6:00 PM

Mail Order and Sales Center SYOSSET, L. I., N. Y. 111 Jericho Turnpike (West of So. Oyster Bay Rd.) Shop By Phone Dept 516 WALnut 1-7500 All Departments 516 WALnut 1-7700 Open Mon., Thurs. & Fri. 'til 9:30 P.M.	NEW YORK—45th St. 71 West 45 St. (between 5-6 Aves.) Phone 212 757-3121 Open Thurs. 'til 9:00 P.M.		BROOKLYN, N. Y. 2265 Bedford Avenue (cor. Snyder Ave.) 212 IN 9-8900 Open Mon., Wed., Thurs., Fri. 'til 9:30 P.M.	
	NEW YORK, N.Y. 100 Sixth Avenue (1 block north of Canal St.) 212 WO 6-5300 Open Thurs. 'til 8:45 P.M.	JAMAICA, N.Y. 165-08 Liberty Avenue (off Merrick Rd.) 212 AX 1-7000 Open Mon., Thurs., Fri. 'til 8:45 P.M.	BRONX, N.Y. 542 E. Fordham Road (3 blocks east of Webster Ave.) 212 FO 7-8813 Open Thurs. 'til 8:45 P.M.	SCARSDALE, N.Y. 691 Central (Park) Ave. (½ mile north of Ardsley Rd.) 914 GR 2-2700 Open Mon., Thurs., Fri. 'til 9:30 P.M.
BOSTON, MASS. 584 Commonwealth Ave. (½ block above Kenmore Sq.) Phone: 617 267-8900 Open Mon. thru Fri. 'til 9:00 P.M.	NATICK, MASS. 1400 Worcester Street (Rt. 9 opposite Shopper's World) Phone: 617 875-6146 Open Wed., Thurs., Fri. 'til 9:30 P.M.	NEWARK, N.J. 24 Central Avenue (just west of Broad St.) 201 MA 2-1661 Open Wed. 'til 8:45 P.M.	PLAINFIELD, N.J. 139 W. 2nd Street (1 block E. of Front St.) 201 PL 6-5100 Open Thurs. 'til 8:45 P.M.	PARAMUS, N.J. 182 Route 17 (1 mile north of Garden State Plaza) 201 CO 1-8800 Open Mon., Wed., Fri. 'til 9:30 P.M.

Industrial Electronics Division

Industrial, Institutional and Government Agency Buyers

NEW ENGLAND 1400 Worcester St., Natick, Mass. Phone: 617 875-1358	NEW JERSEY 24 Central Ave., Newark 2, N.J. 201 Mitchell 3-6868	METROPOLITAN NEW YORK—LONG ISLAND 165-08 Liberty Ave., Jamaica 33, N. Y. 212 Olympia 8-5050
--	---	--

INTERNATIONAL SALES DIVISION

SERVICES BUYERS WORLDWIDE.

WRITE TO:
International Sales Division
 Lafayette Radio Electronics Corporation
 P.O. Box P
 Syosset, L.I., N.Y., U.S.A.

EXPORT TERMS

Full payment must accompany the order. Enclose check or draft; or remit international Postal Money Order or confirmed, irrevocable Letter of Credit. All payments should be in U.S. Dollars payable at U.S. Bank. Include 20% above merchandise value to cover international postage, insurance, consular fees and other export shipping costs. Overpayments are promptly refunded. All prices F.O.B. our warehouses and subject to change without notice.

LAFAYETTE GUARANTEES

When you buy from Lafayette, you buy with confidence. Lafayette's pledge to you, of "Satisfaction Guaranteed or Money Refunded," is

your assurance that we mean what we say. For 44 years we have kept this pledge . . . and shall continue to do so in the future.

SATISFACTION GUARANTEED OR MONEY REFUNDED

See your purchase at home. If for any reason you are not satisfied return it to us at once in the original factory carton and we will exchange it or return your money (less transportation charges). Merchandise returned must be in good condition and not soldered or abused—no holes drilled or changes made in any other way. This policy does not apply to kits (kit guarantee listed below), nor to pre-recorded tape, records, books, repair parts, or merchandise not regularly stocked that has been ordered especially for you.

SERVICE AND REPLACEMENT GUARANTEES

All merchandise is guaranteed to be free of defects in material and workmanship for the period of time specified in the listing of the product. Where no time is specified the guarantee is for 90 days. Wherever so indicated in our listing of the product we will replace it. Wherever our listing does not specify we will either replace it or repair it at our option. Item must be returned prepaid for our inspection.

LAFAYETTE KITS

All parts in kits are guaranteed to be free from defects in material or workmanship, and if properly wired, to meet the published specifications for performance. Parts are guaranteed for the time specified in the listing. Where no time is specified guarantee is for 90 days. During this period we will replace or repair at our option any defective part returned to us.

If your kit does not function properly when fully wired it may be returned to us prepaid for inspection. If failure to function is due to improper wiring or handling, we will make the necessary corrections or repairs at modest charges. These charges vary with each kit and are shown in a price sheet enclosed with each kit.

OTHER KITS

Kits of manufacturers other than Lafayette carry the same guarantee as above, except that Lafayette does not repair or rewire them. They may be returned to us and we will forward them to the manufacturer who will determine the charges, where applicable.

Our Finest Pocket Transistor Radios


NEW "GREAT 8" -- SUPER SENSITIVE 8-TRANSISTOR POCKET RADIO

only **7⁹⁵**

- Slim, Compact Shirt-Pocket Size
- Big Sound Reception on Full AM Band
- With Earphone, Battery and Carrying Case

Here is an 8-transistor radio you've wanted, at a price you've waited for—the "Great 8." A miniature marvel with outstanding performance, the supersensitive superheterodyne circuit employs eight transistors with a built-in ferrite antenna to pull in all stations loud and clear. High efficiency speaker produces rich, clear sound. Easy-to-use thumbwheel controls. Compactly styled to fit in the palm of the hand, a woman's purse, and even a shirt pocket. Complete with earphone for private listening, battery, and carrying case with convenient wrist strap. Only 2½ x 4¼ x 1½". Shpg. wt., 1 lb. Imported.

17 N 4200L Net 7.95
Extra 9-Volt Battery. Shpg. wt., 2 oz. Net .21
99 N 6021



LAFAYETTE "MIGHTY 9" 9-TRANSISTOR RADIO

New
Low
Price **8⁹⁵**

was 9.95 Jan. Catalog 652

- Compact, Shirt-Pocket Size
- Powerful Superheterodyne Circuit
- Clear, Crisp Tone
- Includes Leather Case, Earphone and Battery

Precision-made and handsomely styled, this feature-packed transistor radio uses 9 transistors in a powerful superheterodyne circuit with built-in ferrite antenna to really pull in those AM Stations. Push-pull audio output circuit with 2¼" speaker assures exceptionally clear, crisp tonal quality. Automatic volume control circuit minimizes fadeout and sudden blasts of volume. Slim & compact, it can easily be slipped into pocket or purse—it's an ideal traveling companion wherever you go. Has handy thumbwheel controls, easy-view dial window, earphone jack, and operates on a single low-cost 9-volt battery. Comes complete with leather case, earphone (for private listening), and 9-volt battery. Shpg. wt., 1 lb. Imported.

99 N 3513L Net 8.95
99 N 6021 Extra Battery. Shpg. wt., 2 oz. Net .21



NEW "TOP 10" -- POWERFUL 10-TRANSISTOR POCKET RADIO

9⁹⁵

- A Pocketful of Power
- Outstanding Tonal Quality
- Carry it in Your Shirt Pocket Everywhere
- Complete with Earphone, Carrying Case, Battery

Smaller than your hand . . . yet powerful enough to provide years of listening enjoyment no matter where you are. The 10-transistor, 1-diode superheterodyne circuit provides plenty of pulling power up and down the AM dial. The full-fidelity speaker is your assurance of outstanding sound quality. Built-in long-range ferrite antenna. Powered by an inexpensive 9-volt battery—plays instantly without warm-up. Compact, modern-designed case makes it a "take-it-along-everywhere" radio with true voice and music pleasure too. The "Top 10" comes complete with carrying case with a wrist strap, earphone for private listening, and 9-volt battery for hours of enjoyment. Overall size ½ x 4¼ x 1½". Shpg. wt., 1 lb. Imported.

17 N 4201L Net 9.95
Extra 9-Volt Battery. Shpg. wt., 2 oz. Net .21
99 N 6021



LAFAYETTE 10 TRANSISTOR AM/FM PORTABLE

MAGNIFICENT TONE QUALITY

- Big Set Performance
- Telescoping FM antenna
- 2 Band Slide Rule Dial
- Adjustable tone control

24⁹⁵

Tubeless, cordless static-free FM are yours with this thrilling performer. High efficiency "twe-tone" 2½x3½" oval dynamic speaker and push-pull audio output deliver a full range of sound on FM or AM to enhance your radio listening pleasure. FM drift is virtually eliminated. Super-powered circuit employs 10 transistors, 1 thermistor and 3 diodes, AVC. Only 4½x8¼x2", it offers undreamed-of convenience—take it anywhere. Features: precision vernier dial tuning, built-in ferrite AM antenna, chrome plated telescoping 27" FM whip antenna, earphone jack for private listening. Operates on 4 inexpensive penlite cells. Low current drain gives long battery life. Complete with batteries, leather case and earphone. Imported. Shpg. wt., 3½ lbs. **17 N 6902L** Net 24.95
32 N 4802 Extra batteries. Uses 4. Wt., 2 oz. Net ea. .13



Complete with batteries and earphone.



DELUXE MINIATURE AM-FM PORTABLE RADIO

- With Automatic Frequency Control
- Brilliant, Full Tone 3" Speaker
- 10 Transistors, 4 Diodes
- 2 Earphone Jacks • Handsome Styling
- Includes Earphone, Batteries

29⁹⁵

A quality portable for listeners who enjoy the added tonal quality of FM sound. Practical miniature, its leather-like plastic case has a built-in retractable handle — does not require an external case for outdoor use. 10-transistor 4-diode superheterodyne circuit and rich tone 3" speaker provide plenty of pulling power and magnificent sound quality on both AM and FM bands. AFC locks in FM for listening with virtually no drift. Large easy-to-read slide rule dial and vernier tuning make selecting stations simple. Telescoping Antenna For FM, Ferrite core for AM. Two jacks for personal-earphone listening . . . one shuts off speaker. Only 4¾x5¾x2¼"D. Chrome front panel. Operates on 4 inexpensive penlight cells. Complete with earphone, batteries. Shpg. wt., 2 lbs. Imported.

17 N 2101L Net 29.95
32 N 4802 Extra Battery For Above. (4 req.) Net ea. .13

Complete with batteries and earphone.



14-TRANSISTOR 3-BAND FM/AM/SW PORTABLE RADIO

TWIN TUNING DIALS -- FOR USE AS A PORTABLE OR TABLE RADIO

- Tunes 540-1600 KC, 4-12 MC, 88-108 MC

New functional design creates a fully flexible AM/FM/SW portable. 2 large slide rule dials allow either vertical or horizontal positioning. Enjoy great reception both outdoors and in the home. Advanced engineering features a superheterodyne AM and ratio detector FM circuit assembled on 2 separate chassis for low drift and good sensitivity. An adjustable tone control and 5" PM dynamic speaker insure faithful audio reproduction. 14 transistors, 6 diodes, and 2 thermistors for superior performance. Frequency Range: AM 540-1600KC, 4-12mc and FM 88-108 mc. Automatic gain and frequency control. Telescopic whip antenna extends 31". External antenna jack can be used to connect to auto antenna for mobile use. Operates on 4, 1½ volt standard "D" cells. Low current drain. Complete with batteries, earphone and external antenna wire. Shpg. wt., 8 lbs. Imported.

17 N 6904L Net 48.88
32 N 4804 Batteries for above (4 required) Net ea. .13

LOW LOW PRICE

48⁸⁸

\$5 monthly



Complete with batteries and earphone.

NEW DELUXE 15-TRANSISTOR 4-BAND FM/AM/SW/MB PORTABLE RADIO

**BANDS: AM = 540KC-1600KC; SW = 4.6MC-12MC
 FM = 88MC-108MC; MB = 1.6MC-4.6MC**

- AFC Lock Minimizes Drift On FM
- Large 4x6" Speaker Delivers Superb Tone
- Ferrite Core And 2 Telescopic Antennas On Ball Bearings
- Big Slide Rule Dial With Dial Light

57⁹⁵

\$5 Monthly

A distinctive portable radio you'll be proud to take along on a boat, to a beach, picnic or listen to at home. Expertly engineered with four bands and 15-transistors. It provides fine FM broadcast reproduction, sensitive AM broadcast reception, exciting worldwide shortwave listening (4.6-12 MC) and valuable sea and weather data broadcasts on the (1.6-4.6 MC) marine band. Deluxe features include: large easy-to-read slide rule dial with push-button dial illumination for night viewing, AFC lock for stable FM performance, 4x6" speaker gives faithful sound, tone control, 2 earphone jacks for private listening and external phono jack. Has dual rotating telescopic whip antennas and ferrite bar antenna. Complete with 4 standard "D" cells, earphone. In handsome black vinyl cabinet with chrome grille. Size: 10¾x9 9½x3 3½"D. Shpg. wt., 7 lbs. Imported.

17 N 0106L Net 57.95
32 N 4804 Extra Battery For Above. (4 req.) Net ea. .13




Complete with batteries

DELUXE LAFAYETTE 9-TRANSISTOR VHF AIRCRAFT AND BROADCAST PORTABLE RECEIVER



- Tunes: 535-1605KC and 108-135MC
- Powerful 9-Transistor Superheterodyne Circuitry
- Separate VHF RF Amplifier Stage
- Thermistor to Compensate for Temperature Changes



39⁹⁵

\$5 monthly

Complete with Earphone and Batteries

Hear thrilling plane-to-plane, plane-to-tower communications which give flight patterns, vital landing instructions, exacting weather forecasts, plus standard broadcast band on one superbly engineered and crafted portable receiver.

A must for aviation enthusiasts! Take it with you wherever you go — it plays anywhere on its self contained battery operated power supply. Now you can hear thrilling plane-to-plane and plane-to-tower communications which give exacting weather forecasts, flight patterns, and vital landing instructions. Features advanced transistor circuitry (9 transistors, 3 diodes) and a varistor as a temperature compensating device. Super Sensitive; has an extra VHF RF amplifier. Tunes the important VHF band from 108-135MC in addition to the standard broadcast band (535 — 1.60MC). Has its own telescoping VHF antenna which may be folded over when not in use. Provisions are made to couple an external antenna to the receiver to obtain a stronger signal in areas of weak reception. Instant band switching is accomplished through use of a band selecting lever. Audio output is through a powerful 3" speaker. A separate tone control is provided to "custom blend" the highs and lows for ones own listening pleasure. Slide rule type tuning indicator for ease of station selection. Comes complete with earphone, carrying case, and 6 penlite batteries. Size: 4 $\frac{1}{2}$ x7 $\frac{1}{2}$ x2". Shpg. wt., 2 $\frac{1}{2}$ lbs.

99 N 3514L Net 39.95
32 N 4802 Extra batteries, 6 req. Net .13.



THE TRANSCONTINENTAL "SOLID STATE" 11 BAND AM-FM SHORTWAVE PORTABLE SUPERB PERFORMANCE MAGNIFICENT TONE

- 16 Transistors
- 8 Diodes
- Super Sensitive Tuner
- Variable Selectivity
- Automatic Frequency Control

only **99⁵⁰**
\$5 monthly

Complete with Earphone and Batteries

11 BANDS:

MW 540-1600Kc	SW 20.5-22.5Mc
LW 150-400Kc	FM 66.5-72.5Mc
SW 2-4Mc	FM 78-88Mc
SW 4-9Mc	FM 88-108Mc
SW 9-12Mc	FM 118-132Mc
SW 14.5-18.5Mc	

The TRANSCONTINENTAL is an extremely versatile multiband portable radio receiver and offers 11 reception bands making it useful anywhere in the world. Besides the standard Medium and Long Wave bands, the four FM bands can be used for standard FM broadcast and as a monitor for airdrome control towers. The five short wave bands include ship-to-ship, marine, weather, amateur and international broadcasts. Features special module components which can be easily replaced in the event of set failure. Three major circuit boards are designed for easy, immediate replacement. A single tuner is used in the LW, MW, and FM bands to eliminate duplication and simplify service. FM circuit can be locked for stable operation with switchable AFC. Selectivity can be

switched for improved audio reproduction and extended side band reception. Large ferrite bar antenna for LW and MW bands, and 5.6 foot multi-section whip antenna for SW and FM broadcasts. A 2-Way speaker system consisting of a 4" woofer and 1 $\frac{1}{2}$ " tweeter offers excellent reproduction. Separate jacks for external antenna, earphone, speaker, and microphone/phonograph. Uses six 1.5 volt batteries. Shpg. wt., 12 lbs. Imported.

17 N 6903WX

Net 99.50

32 N 4801 Extra Size "C" Batteries. (6 required)

Net ea. .13

QUALITY 8-TRANSISTOR AM-MARINE BAND PORTABLE RADIO

- Covers AM and Marine Bands
- Highly Sensitive Rod-Antenna Plus Built-In Ferrite Core Antenna

19⁹⁵



Complete with Leather case, earphones, and battery

This fine transistorized portable covers both the general broadcast band plus the 1.6-4.6 MC marine band. Your perfect listening companion even when at sea. A built-in antenna is used for the broadcast band and a telescoping antenna for the marine band. The receiver circuitry utilizes 8 transistors, 1-diode, and 1-varistor. Superheterodyne system with A.G.C. The built-in speaker can be shut off by inserting an external earphone (supplied) for personal listening. Operates on 4 inexpensive Z cells giving up to 3 times longer life than ordinary 6-volt batteries. Comes complete with telescoping antenna, carrying case and earphone. Measures: 6 $\frac{1}{2}$ x3 $\frac{1}{4}$ x1 $\frac{1}{4}$ ". Shpg. wt., 2 lbs Imported.

17 N 3401L

Net 19.95

32 N 4802 Extra Z cells for above

Net ea. .13

AM-SW 8-TRANSISTOR PORTABLE RADIO

Same deluxe circuitry as above but covers AM (530-1600 KC) and the 3.9-12MC band for short-wave listening.

17 N 3402L

Net 19.95

Top Quality LAFAYETTE Table Radios


POWERFUL 9-TRANSISTOR AM PORTABLE AND TABLE RADIO WITH GENUINE TOP GRADE COWHIDE CABINET

- 9 Transistors, 1 Diode, 1 Thermistor
- Big Tone 3½" PM Speaker
- Precision Vernier Tuning
- Complete with Batteries and Earphone

24⁵⁰

Receive top performance indoors and out from this highly attractive AM portable and table radio. Entire cabinet is made of handsome saddle-stitched top grain cowhide. A 3½" PM speaker give "big-set" tone even in noisy outdoor areas. Powerful 9-transistor circuit pulls in distant stations. The impressive tone and leather carrying case make this set ideal for use anywhere in the home. Operates on six readily obtainable flashlight batteries. Smooth vernier tuning makes station selections easy. Has built-in Ferrite-rod antenna, earphone for private listening, built-in carrying handle.

With batteries. Dimensions: 7¾Wx5¼Hx2½"D. Shpg. wt., 5 lbs. Imported.
99 N 3504 Net **24.50**
32 N 4801 Extra "C" batteries (uses 6) Wt., 2 oz. Net ea. .13




FULL RICH TONE

QUALITY FM/AM TABLE RADIO

- Distinctive Styling
- Rich Tone 4" Speaker
- Effective AFC For Stable FM Reception

Smartly styled table-top or shelf radio which receives rich, static-free FM and quality AM broadcasts. Completely self-contained, requires no external FM or AM antennas. These are built-in for superb reception. Powerful 4" speaker offers full-bodied FM sound and clear AM broadcasts. Effective AFC circuit keeps FM stations tuned-in with low drift. AVC prevents blasting, keeps sound level relatively even. Handsome, easy-to-read slide rule dial has precision vernier control for simpler tuning. Superheterodyne circuit has 6 tubes, 2 diodes. Stylish hi-impact plastic cabinet finished in ivory and gold. Imported. Size: 9¼Wx6¼Hx5½"D. For 110-120 volts 50/60 cycles AC. Shpg. wt., 5 lbs. Imported.

17 N 3002 Net **29.95**



29⁹⁵

DELUXE LAFAYETTE FM/AM DUAL SPEAKER TABLE RADIO

- Two 4-inch PM Speakers for Full Dynamic Range
- External 300-Ohm Antenna Input Terminals
- Greater Sensitivity—AFC
- Provision for Extension Speaker

High Fidelity FM/AM table radio. Fine furniture styling. Dual 4-inch PM speakers, in an acoustically correct cabinet, produce rich full-frequency sound on both FM and AM. Features improved AFC action which "locks-in" FM stations. A supersensitive AM antenna brings in distant stations clearly while reducing unwanted noise. An FM wire antenna is provided to assure clear FM reception. An external 300-ohm FM antenna can be attached to built-in input terminals for improved reception of distant stations. Beautifully finished Dield Walnut cabinet and easy-to-read slide rule dial with an on-off neon indicator light. Handy jack allows easy, quick addition of an extension speaker. For 110-120 volts, 60 cps AC or DC. Size: 17½Wx7¾Hx5¾"D. Shpg. wt., 8 lbs. Imported.

99 N 3502 Net **39.50**

Beautifully Styled Oil Walnut Cabinet



Magnificent Rich Tone!

39⁵⁰

\$5 monthly

MAGNIFICENT FM/AM CLOCK RADIO

- Automatic Telechron Clock
- Wake-to-Music Plus Alarm
- Sleep-Switch—Lulls you to Sleep
- Powerful Alnico V PM Speaker


39⁹⁵

\$5 monthly

Combines a fully automatic Telechron clock with luminous hands and a superb FM/AM radio. Handy sleep-switch permits you to slowly drift-off to dreamland while the radio shuts itself off at a preset time. Beautiful AM or FM music awakens you pleasantly. Optional buzzer alarm also included. In addition to a standard AM broadcast radio, a quality FM radio, with AFC will expand your listening pleasure. FM antenna is built into line cord. External FM antenna terminals built-in for fringe area use. Slide rule dial for easier tuning. Beautiful molded plastic cabinet in antique white and gray with silver trim. Size: 13½Wx7Hx5½"D. For 110-120 volts, 60 cps AC only. Imported.

Net **39.95**

Take Advantage of Lafayette's Low Radio Prices



New LAFAYETTE 30-Watt AM-FM Stereo Receiver Model LR-400



Only
169⁵⁰
\$8 Monthly

JUST ADD SPEAKERS FOR A COMPLETE FM/AM STEREO SYSTEM


- Sensitive Nuvistor Front End
- 16 Tubes plus 9 Diodes
- 30-Watt Fully Integrated Stereo Amplifier
- Tone Stereo "Searcher" For Locating Stereo Stations Easily and Positively
- FM Stereo Noise Filter
- Front Panel Stereo Headphone Jack
- Bar-Type "Magic-Eye" For Precise Tuning
- Complete Stereo Controls

Make the LR-400 the heart of your stereo system. Combines on one compact chassis a sensitive stereo FM-AM tuner, a powerful 30-watt stereo amplifier and complete control facilities for extraordinary performance. Highly sensitive nuvistor provides an additional RF stage to a wide-band tuner circuit to bring in fringe signals with ease. The tuner also utilizes Lafayette's famous stereo "Search" circuit which takes the guesswork out of finding FM stereo stations. During tuning for stereo, a continuous tone is heard through your loudspeakers when a stereo station is on the air. Switchable filter reduces hiss and background noise during reception of weak stereo signals. A superb 30-watt stereo push-pull amplifier brings out the rich sound present in FM and modern stereo records. Annoying Hum and noise are virtually reduced to the vanishing point. A complete complement of operating controls provide optimum flexibility. As added conveniences, a front panel stereo headphone jack and speaker on-off switch for your private listening pleasure, and phono and aux., indicator lights are provided. Controls include: Variable AFC, Tuning, Power on/off, Concentric friction lock Volume, Base and Treble; Selector (AM, FM Stereo Search, Stereo FM, Phono Aux.); Mode

Switch (Left, Right, Mix, Stereo, Rev.) and switches for loudness and MPX Noise Filter. Rear panel controls are: Impedance selector switch, speaker phone switch and hum balance. AC Convenience receptacle. Handsome tilted gold extruded aluminum panel for easier view and contrasting case harmonize with any decor. 17¼Wx 5½Hx12¼"D. For 117V, 50/60 cycles AC. Shpg. wt., 36 lbs. Imported
99 N 0004WX Net **169.50**

SPECIFICATIONS

TUNER: FM 88-108MC. AM 550-1600KC; SENSITIVITY: 2½ UV For 20 db S/N ratio; FM SEPARATION: 25 db @ 400 cps; FREQUENCY RESPONSE: 20-20,000 cps ± 2 db. AFC, MPX, Noise Filter. AMPLIFIER: Output: 15 watts per channel (music Power); TONE CONTROLS ± 10 db boost & cut; EQUALIZATION: RIAA; HUM & NOISE: Mag. Phono—55 db; Aux.—68 db. INPUTS: 4 Pair, SPEAKER IMPEDANCE: 8-16 ohms. TUBES: 16 Tubes, 9 diodes, plus EM84 Tuning eye.



2—SK-300



Garrard Model 50

CHOICE OF STEREO CARTRIDGE



Pickering V15/AT-1




Empire 880



Shure M7/N210



2—SK-180



2—ElioTflex Enclosures



Garrard Changer AT-60

Matched Stereophonic Systems Featuring Model LR-400 30-Watt AM-FM Stereo Receiver

AS
LOW
AS **234⁹⁵**
\$11.50 Monthly

LAFAYETTE LR-400 30 WATT AM-FM STEREO Tuner-Amplifier
Garrard Model 50 4-Speed Record Changer
Pickering Model V15/AT-1 Diamond Needle Cartridge*
Wood Base for Changer (Specify Oiled Walnut or Mahogany)
2 LAFAYETTE SK-300 "Decor-ette V" 5-Speaker Slim Speaker Systems (Oiled Walnut)

Above Hi-Fi Stereophonic system with * choice of Pickering V15/AT-1, Shure M7/N210, or Empire 880 diamond needle cartridge complete with all necessary cables and instructions. Shpg. wt., 86 lbs.

21 N 9521CWXM 11.50 Monthly Net 249.95

Same as above except with Garrard Model AT-60 record changer instead of Garrard Model 50. Shpg. wt. 88 lbs.

21 N 9522CWXM 12.50 Monthly Net 264.95

Same as 21 N 9521WXM system except with 2 Lafayette Model SK-180 10" Trihelix® 3-way speakers instead of 2 SK-300 speaker systems. Shpg. wt. 68 lbs.

21 N 9523CWXM 11.00 Monthly Net 234.95


Same as 21 N 9523WXM stereo system plus 2 Lafayette famous patented ElioTflex speaker enclosures (specify oiled walnut, walnut, or mahogany). Shpr. wt. 116 lbs.

21 N 9524CWXM 15.00 Monthly Net 294.95

Prices On This Page May Be Raised April 1st Due-To New Excise Tax

LAFAYETTE Complete AM-FM Stereophonic Receiver Model LA-215A

Only
109⁵⁰
\$9.00 Monthly



- AM/FM Tuning Meter
- 15 Tubes plus 6 Diodes
- Front Panel Stereo Headphone Jack
- Complete Stereo Preamp Facilities

A Fine AM-FM Tune with Built-in-Multiplex plus
a 12-WATT COMPLETELY INTEGRATED STEREO AMPLIFIER

A complete stereo control center with AM/FM tuner with built-in multiplex and a 12-watt stereo amplifier. FM section features advanced stereo "Search" circuit which introduces a tone when a multiplex signal is tuned in. Changing the selector switch from stereo search to FM stereo permits normal MPX reception. AFC assures low drift FM reception. MPX noise filter eliminates unwanted station noise. AM section features superhet circuit and a built-in antenna. Convenient tuning meter provides precise station tuning on AM or FM. Front panel controls; power on/off; concentric volume/balance; master bass; master treble; 6-position selector switch (AM, FM, Stereo Search, Stereo FM, Phono, Aux.); tuning, stereo-mono mode switch; MPX noise filter on/off; AFC

- 11 Front Panel Controls
- Just Add Speakers for Complete Stereo System

on/off; speakers on/off. Rear panel has speaker phase switch and 8 & 16 ohm impedance selector; stereo inputs for mag phono, crystal phono, auxiliary; stereo outputs for tape recorder; AC receptacle. Illuminated, easy-to-read slide rule dial and flywheel tuning. Finished in gold and brown, with metal cabinet, 117 volts, 50/60 cps AC. 16 1/2" x 5 1/2" x 11 1/2" D. Imported. Shpg. wt., 27 lbs. 99 N 0013WX Net 109.05

SPECIFICATIONS

TUNER FM Sensitivity: 3µV for 20 db S/N ratio—Frequency Response: FM, 20-20,000 cps ±2 db; FM Stereo, 50-15,000 cps ±2 db—Harmonic Distortion: FM, less than 1% @ 400 cps; FM Stereo, less than 2% @ 400 cps—FM Stereo Separation: 25 db @ 400 cps.
AMPLIFIER Power Output: 6 watts music power per channel—Sensitivity: Mag. Phono, 3.5 mv @ 4.5 watts output Crystal, 30 mv @ 4.5 watts output—Hum and Noise—55 db for low level input—75 db for high level input—Output Impedance: 8 & 16 ohms switched—Phono Equalization: RIAA.

LAFAYETTE Complete Stereo Hi-Fi Systems

Featuring the LA-215A 12-Watt AM-FM Stereo Receiver

Only **172⁹⁵**
\$9 Monthly

Lafayette LA-215A 12-watt AM-FM Stereo Tuner-Amplifier.

Lafayette-Webcor Model PK-770 4 Speed Automatic Record Changer with Asatic Turnover Cartridge and Diamond LP Stylus.

Wood Base for Changer (Oiled Walnut).

2 Lafayette SK-265 "Slenderette III" 2-Speaker Slim Speaker Systems with all necessary cables and instructions.

Complete system as above. Shpg. wt., 75 lbs.
21 N 9539WXM Net 172.95


Same as above except with Garrard Model 50 4 speed changer with choice of Pickering V15/AT-1, Shure M7/N21D or Empire 880 diamond stylus cartridge instead of Lafayette-Webcor Model PK-770 changer. Shpg. wt., 75 lbs.
21 N 9540WXM Net 167.95

Same as 21 N 9539WXM except with 2 Lafayette SK-123A Ultra-Compliance speaker system (oiled walnut finish) instead of SK-265 speaker systems. Shpg. wt., 75 lbs.
21 N 9542WXM Net 179.95

Same as 21 N 9540WXM except with 2 Lafayette SK-123A Ultra-Compliance speaker system (oiled walnut finish) instead of SK-265 speaker systems. Shpg. wt., 75 lbs.
21 N 9541WXM Net 193.95

Same as 21 N 9540WXM except with 2 Lafayette famous SK-58 12" free-edge coaxial speakers instead of SK-265 "Slenderette III" speaker systems. Shpg. wt., 65 lbs.
21 N 9543WXM Net 204.95

Same as 21 N 9543WXM plus 2 Lafayette famous patented Eliptoflex speaker enclosures (specify oiled walnut, walnut, or mahogany). Shpg. wt., 112 lbs.
21 N 4544WXM Net 267.95




2 SK-265
SLENDERETTE III



GARRARD MODEL 50


2 SK-123A



2 SK-58




LAFAYETTE-
WEBCOR
PK-770



2 ELIPTOFLEX




LAFAYETTE 44-Watt All-Transistor Stereo Amplifier Model LA-200



- Complete Stereophonic Control Facilities
- Modern Styling, Compact Size
- Cool Running, Reliable Transistor Circuitry
- 20-20,000 cycles \pm 1db
- Smooth, Fast Transient Response
- Freedom From Hum and Noise
- Instantaneous Warmup

109⁵⁰
\$5 Monthly

19 Transistors
5 Silicon Diodes



YEARS AHEAD FEATURES

- 1 Smooth Positive Action Controls and Switches
- 2 Front Panel Stereo Phone Jack
- 3 Oversize Electrolytic Capacitors for Better Power Supply Filtering, and Longer Life
- 4 Military-type Terminal Boards Give Greater Reliability
- 5 Heat Shield for extra component protection
- 6 Massive Heat Sink to Insure Cool operation of Power Transistors
- 7 Speaker Phase Switch
- 8 2 AC Convenience Outlets, One Switched
- 9 Fused AC Line
- 10 Massive Power Transformer
- 11 Complete Overload or Short Circuit Protection
- 12 19 Transistors, 5 Silicon Diodes

SPECIFICATIONS

IHFM Music Power: 44 watts; 22 watts per channel; 18 watts continuous sine wave power per channel. Frequency Response \pm 1 db, 20-20,000 cps. Harmonic Dist.: 1%. Hum & Noise: Tuner, —74 db; Mag. Phono, —54 db. Tone Controls: \pm 10 db. Inputs: (5 pairs): Tape Head; Mag. Phono; Cer. Phono; Tuner; Aux. Outputs: Tape Recorder, 4 ohms (also for 8 and 16 ohm speakers).

The LA-200 combines a complete stereophonic preamplifier and a dual channel 44-watt power amplifier on one compact chassis. All-transistor circuit offers advantages not found in tube sets . . . The initial performance level is maintained for years without adjustments when operated properly, features include: Front panel stereo headphone receptacle, scratch and rumble filters, separate on-off power switch, bass and treble controls for each channel, 4-position mode switch, volume, balance and 5-position input selector switch, speaker on/off switch. Phase switch on rear panel; 4 AC convenience receptacles, one switched; pilot light. Operates with 4, 8 or 16-ohm speakers. Brown textured finish case, gold finish aluminum panel and knobs. For 105-125V 50/60 cycles AC. Size: 13Wx 4 1/2 Hx 9" D (with legs). Shpg. wt., 15 lbs. Imported.

99 N 0012WX Model LA-200

Net 109.50

44-Watt Hi-Fi Stereo Systems with LAFAYETTE Model LA-200 All-Transistor Stereo Amplifier

As Low As

207⁵⁰
\$10 monthly

CHOICE OF STEREO CARTRIDGE



Lafayette LA-200 44-Watt All-Transistor Stereo Amplifier

Garrard Model 50 4-Speed Stereo Changer
Pickering V15/AT-1 Diamond Needle Cartridge*
Wood Base for Changer (Oiled Walnut or Mahogany)
2-Lafayette SK-300 "Decor-ette V" 5-Speaker Slim Speaker System (Oiled Walnut)

Complete system as above plus all necessary cables and instructions. Shpg. wt., 64 lbs.

21 N 9701CWXM \$10 Monthly Net 208.50

Same system as 21 K 9701CWXM except with Garrard Model AT60 record changer instead of model 50. Shpg. wt., 66 lbs.

21 N 9702CWXM . . . \$11 Monthly Net 219.50


Same as 21 K 9701CWXM except with 2 Lafayette SK-180 10" Trihelix® three way speakers instead of Decor-ette V speaker systems. Shpg. wt., 46 lbs.

21 N 9707CWXM . . . \$10 Monthly Net 207.50

Same as 21 K 9707CWXM plus 2 Lafayette famous patented Eliptoflex speaker enclosures (specify oiled walnut, walnut, or mahogany). Shpg. wt., 94 lbs.

21 N 9710CWXM . . . \$12.50 Monthly Net 265.25

* Specify your choice of Pickering V15/AT-1, Shure M7/N21D or Empire 880 diamond needle cartridge.




2 SK-300

Garrard Model 50



2 SK-180



2-Eliptoflex Enclosures



Garrard Model AT60

LAFAYETTE 40-Watt All-Transistor Stereo Amplifier Model LA-340

- Big 40 Watts of Music Power (IHFM)
- Extremely Cool Running
- Instant Warm Up—Plays Immediately
- Tape Recording Outputs
- Transformerless Output Circuit For Lower Distortion
- 19 Transistors, 4 Diodes
- Slim-Modern Styling



79⁹⁵
\$5 Monthly

Low in cost, high in performance! If you wanted the thrilling sound of transistor amplification but found it too expensive—the Lafayette LA-340 is your answer. New slim styling with virtually no heat production lets you place it anywhere in the room. Full range sound is achieved with a frequency response of 30-20,000 cycles. Five pairs of stereo inputs accommodate a tuner, phono using magnetic or ceramic cartridges, tape recorder and auxiliary sources. Accept: 4, 8 or 16 ohm speakers. Terminal board wiring assures mechanical stability. Other features include, front panel stereo headphone jack and switch to silence loudspeakers, and concentric volume control, 2 AC receptacles for convenience in connecting other components. Beautiful gold panel and matching knobs. Size: 11¾Wx3¾Hx10½" deep inclu. knobs and dark brown metal case. For 117V 50/60 cycles AC. Shpg. wt., 10 lbs. Imported
99 N 0011WX Model LA-340

Net 79.95

SPECIFICATIONS

Power Output: 40 Watts IHFM; 20 watts IHFM music power per channel. 12 watts continuous sine wave power per channel. **Frequency Response:** ±1 db 30-20,000 cps. **Harmonic Distortion:** 1% **Hum and Noise:** —70db on Tuner, Aux. —56 db Magnetic Phono, Tape Head. **Cross talk:** 52 db @ 100 cps. **Sensitivity:** Tuner 0.25 volts, .75 volts Aux. **Inputs:** 5 pairs—Tape Head, Magnetic Phono, Ceramic Phono, Tuner, Auxiliary. **Outputs:** 4, 8, 16 ohm, two high impedance for tape recording; Front panel stereo headphone jack. **Equalization:** NAB; RIAA. **Controls:** Switches — Power on/off, spkr./Phone, Bass, Treble, Mode (Left, Right, Stereo, Rev). 2 AC receptacles, one switched.

LAFAYETTE 40-Watt Stereo Systems with Model LA-340 All-Transistor Stereo Amplifier

Lafayette LA-340 40-Watt All-Transistor Stereo Amplifier
Garrard Model 50 4-Speed Record Changer
Wood Base for Changer (Specify oiled walnut or Mahogany)
Pickering V15/AT-1 Diamond Needle Cartridge*
2 Lafayette SK-300 "Decor-ette V" 5 Speaker Slim Speaker System (oiled walnut)

Complete 40 watt stereo system as above with choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge; and with all necessary cables and instructions. Shpg. wt., 64 lbs.
21 N 9785CWXM Net 186.50

Same as above except with Garrard AT60 4 speed record changer instead of Garrard Model 50 record changer. Shpg. wt., 66 lbs.
21 N 9786CWXM Net 197.50

Same as 21 N 9785CWXM except with 2 Lafayette famous SK-5B 12" free edge coaxial speakers in 2 Lafayette patented Eliptoflex speaker enclosures. (Specify oiled walnut, walnut or mahogany) instead of 2 Decor-ette V speaker systems. Shpg. wt., 100 lbs.
21 N 9790CWXM Net 234.95

Same as 21 N 9790CWXM except with Garrard AT60 instead of Garrard Model 50 record changer. Shpg. wt., 102 lbs.
21 N 9792CWXM Net 245.50

GARRARD MODEL 50
ON BASE

As Low As
186⁵⁰
\$9 monthly

CHOICE OF
STEREO
CARTRIDGE



Pickering
V-15/AT-1




Empire
880



Shure
M7/N21D




2 SK-300
DECOR-ETTE V



2 SK-5B



2 ELIPTOFLEX
ENCLOSURES



GARRARD AT60
ON BASE



Prices On This Page May Be Raised April 1st Due To New Excise Tax

LAFAYETTE 30-Watt Stereo Amplifier

Model LA-224A



59⁹⁵
\$5 Monthly

- Stereo Headphone Jack
- Independent Concentric Bass & Treble Controls For Each Channel
- Concentric Volume/Balance Control

FIRST RATE—a Brilliant Stereo Performer... an amplifier with wide-range frequency response, low distortion, low hum and noise characteristics you can expect of a quality hi-fi amplifier designed for placement anywhere in your home. A full range of control facilities have been provided to assure complete Stereo capability and flexibility. Two dual concentric Bass and Treble controls provide separate and individual tone controls for each channel. A dual concentric volume control acts as an independent level control for each channel and allows precise channel balancing. Fast, easy operation between Stereo, Reverse Stereo, Monophonic Left channel and Monophonic Right channel is furnished by a Mode switch. A selector Switch furnishes switching from Aux, Tuner or Phono music sources. In addition slide switches are included for: Rumble Filter (off-on) Phase (normal-reverse) and to take full advantage of the front panel Headphone jack a switch is provided for speaker or phone operation. Paired inputs located on the rear panel accommodate any of the ordinary stereo sound sources—inputs are included for magnetic, crystal or ceramic cartridges; Tuner, tape or auxiliary (high output) plus Tape Out jacks for recording through

- Frequency Response: 25-25,000 CPS ± 1.5 db Average at Rated Output
- Hum & Noise—75 db Below Rated Output
- High Sensitivity Allows Use With Most Stereo Cartridges

your tape recorder. Beautifully styled in a low silhouette enclosure, color keyed to do justice to any decor. Ivory and gold front panel is contrasted by gold metal knobs and enclosure. Complete with cage and legs. Size: $5\frac{1}{2} \times 13\frac{3}{4} \times 8\frac{1}{2}$ " D. For 115V 60 cycle AC operation. Shpg. wt., 20 lbs. Imported.
99 N 0026WX Net 59.95

SPECIFICATIONS

Power Output: 15 watts rms per channel stereo, 30-watts rms monaural operation. Frequency Response: 25-25,000 CPS ± 1.5 db average at rated output. Hum and Noise: Mag. Phone —56db below rated output. Tuner —75db below rated output. Distortion: 1.25% total harmonic distortion at 15 watts (1KC), less than .25% total harmonic distortion at 1 watt (1KC). Sensitivity: Low Level (Mag Input) 5.5mv at full output, High Level .6v at full output. Tone Controls: ± 11 db. Outputs: Dual 8 and 16-ohm impedance speaker outputs. Dual Tape outputs. Tube Complement: Total of 10, 5-12AX7, 4-6BQ5, 1-5AR4.

LAFAYETTE 30-Watt Matched Stereo Phono Systems with LA-224A Stereo Amplifier

137⁵⁰
\$7.00 Monthly



GARRARD 50

CHOICE OF STEREO CARTRIDGE




Pickering V15/AT-1




Empire 880




Shure M7/N21D




2 SK-265



2 SK-300



2 SK-58



2 ELIPTOFLEX

Lafayette Model LA-224A 30-watt Stereo Amplifier, Garrard Model 50 4-speed Record Changer, Pickering V15/AT-1 Diamond Needle Cartridge*, Wood Base for Changer (Specify Oiled Walnut or Mahogany).

2 Lafayette Model SK-265 "Slenderette III" 2-Speaker Slim Speaker Systems. (Oiled Walnut).

Above stereophonic hi-fi system complete with necessary cables and instruction. Shpg. wt., 65 lbs.
21 N 9665WXM Net 137.50

Same as 21 N 9665WXM except with 2 Lafayette Model SK-300 "Decor-ette V" 5 speaker slim speaker systems (oiled walnut) instead of 2 Model SK-265 speaker systems. Shpg. wt., 69 lbs.
21 N 9666WXM Net 157.50

Same system as 21 N 9665WXM except with 2 Lafayette famous SK-58 12" free-edge coaxial speakers instead of Slenderette III speaker systems. Shpg. wt., 57 lbs.
21 N 9667WXM Net 156.50

Same as 21 N 9667WXM plus 2 Lafayette patented ELIPTOFLEX speaker enclosures (Specify oiled walnut, walnut, or mahogany). Shpg. wt., 105 lbs.
21 N 9668WXM Net 214.50

* Specify choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 Cartridge.

LAFAYETTE 40-Watt Stereo Amplifier Model LA-260



79⁹⁵

\$5 Monthly

If you are interested in owning an outstanding high fidelity system, then the heart of it should be the Model LA-260. 40 big watts of output gives you full bass, solid midrange and brilliant treble response — even with popular low efficiency speakers. Complete master control facilities include concentric bass, treble and volume controls to customize the sound to suit your taste and listening area. Low cut rumble filter eliminates possible annoying rumble from record players; selector switch gives choice of phono, tuner, tape head and auxiliary program sources. Mode switch (Left, Right, Stereo & Rev) positions. Panel Speaker-Phonesswitch for choice of headphone or loudspeaker listening. Phase switch corrects speaker phasing without changing wires. In addition tape recorder outputs are provided on front and rear panels for your convenience. Tape head inputs permit direct playback from your recorders tape heads. AC outlet. Ivory and Gold front panel with case. For 115V 60 cycle AC. Size: 14 $\frac{1}{4}$ Wx5 $\frac{1}{4}$ Hx11"D. Shpg. wt., 30 $\frac{1}{2}$ lbs. Imported.

99 N 0016WX

Net 79.95

- Concentric Volume, Bass & Treble Controls
- Less Than 1% Harmonic Distortion At Rated Output
- Frequency Response: ± 1 db 40-20,000 @ Rated Output
- Front Panel Stereo Headphone and Tape Output Jacks
- High Sensitivity — Will Accept Majority of Stereo Cartridges

SPECIFICATIONS

Music Power Output: 40 watts, 20 watts each channel. Harmonic Distortion: Less than 1% at rated output. Frequency Response: ± 1 db 40-20,000 cps. Hum and Noise: Tuner — 75 db; Magnetic phono — 58 db. Sensitivity: For full output—Mag Phono 4.5 mv; High level: .5 v. Inputs (5 pairs): Tape Head, Mag Phono, ceramic phono, Tuner, Aux. Outputs: 2-pair tape recorder, stereo headphone jack, 8 and 16-ohm per channel speaker impedance. Tubes: (3) 12AX7, (2) 6BL8, (4) 6BQ5, 5AR4, GZ34, rectifier.

LAFAYETTE 40-Watt Matched Stereo Phono Systems with Model LA-260 Stereo Amplifier

- Lafayette LA-260 40-Watt Stereo Amplifier
- Garrard Model 50 4-Speed Record Changer
- Wood Base for Changer (Specify oiled walnut or mahogany)
- Pickering V-15/AT-1, Diamond Needle Cartridge*
- 2 Lafayette SK-265 Slenderette III 2-Way Slim Speaker System: (oiled walnut)

Complete featured stereo system above with all necessary cables and instructions plus * choice of Pickering V-15/AT-1, Shure M7/N210, or Empire 880 diamond needle cartridge. Shpg. tw., 76 lbs.

21 N 9798CWXM Net 154.50

Same as above but with Garrard Model AT60 4 speed record changer instead of Garrard Model 50 changer. Shpg. wt., 78 lbs.

21 N 9799CWXM Net 169.50

Same as 21 N 9799CWXM except with 2 Lafayette SK-180 16" Trihelix 3 way speakers instead of SK-265 speaker systems. Shpg. wt., 62 lbs.

21 N 9737CWXM Net 167.50

Same as 21 N 9737CWXM plus 2 Lafayette patented Elio-plex speaker enclosures. (specify oiled walnut, walnut, or mahogany) Shpg. wt., 110 lbs.

21 N 9738CWXM Net 224.75

Same as 21 N 9738CWXM except with Garrard Model AT-60 4 speed record changer instead of Garrard Model 50 changer. Shpg. wt., 112 lbs.

21 N 9740CWXM Net 239.50

GARRARD MODEL 50
ON BASE



2 SK-265
Slenderette III




154⁵⁰

\$8 monthly


CHOICE OF STEREO CARTRIDGE



GARRARD AT 60
ON BASE



2 SK-180



2 Elio-plex

Prices On This Page May Be Raised April 1st Due To New Excise Tax

Lafayette Cat. No. 653 13

LAFAYETTE 70-Watt Stereo Amplifier Model LA-350



- Six Pairs of Stereo Inputs For All Sources
- Handsome Extruded Aluminum Front Panel
- DC On Preamp Filaments For Minimum Hum
- Tape Monitor Switch
- Stereo Headphone Jack On Front Panel
- Separate Channel Tone Controls

Only
99⁵⁰
\$5 Monthly

The deluxe Lafayette LA-350 is packed with power, features and handsome styling. 70 watts of sonic power produces tonal beauty to match its good looks. Delivers plenty of reserve power to drive even inefficient speakers to full listening levels. Eleven comprehensive front panel controls provide utmost flexibility—assures "custom" sound reproduction in your home. Six position program selector enables instant selection of music sources including tape head inputs for direct playback of tapes from a stereo tape recorder. Mode switch provides choice of left or right channels, mix, stereo and reverse channels. Separate bass and treble controls are friction-locked and are adjustable independently or simultaneously. Friction-locked balance controls adjusts each stereo channel for perfect separation. Separate volume control and power switch makes possible undisturbed control settings — simplicity of operation. Also features: tape monitor switch which lets you listen to tapes while recording, rumble filter, loudness switch and a convenient front panel stereo headphone jack with a switch to silence speakers for real private listening. Rugged construction and quality components will provide years of dependable performance.

DC on preamplifier filaments and hum adjust controls on both DC and AC filament lines minimizes hum to extremely low levels. Two AC convenience outlets on rear panel apron permits simple connection of tuner and phono AC line. Handsome brushed gold extruded aluminum front panel and knobs with contrasting case fits in any decor. 14 $\frac{1}{2}$ "x5 $\frac{1}{4}$ "x10"D. For 117V. 60 cycles AC. Imported. Shpg. wt., 30 lbs.

99 N 0007WX

Net 99.50

SPECIFICATIONS

Power Output: 70 watts Music Power: 28 watts per channel continuous. **Frequency Response:** ± 1 db 15 to 30,000 cps at normal listening level. **Harmonic Distortion:** Less than 1%. **Hum and Noise:** 55 db down and Phono inputs, 76 db down on auxiliary inputs. **Channel Separation:** 50 db at 1KC. **Inputs and Sensitivity:** Tape Head and Phono 1, 1.5 mv; Phono 2, 6 mv; Tuner, 200 mv; Auxiliary 1, 10 mv; Aux. 2, 750 mv. **Output Impedances:** 8 and 16 ohms. **Tape Outputs:** 2 pair. **Tubes:** (3) 12AX7/EGC83, (2) 6AN8, (4) 7198A; 5 diodes. 2 AC Outlets, 1 switched.

LAFAYETTE 70-Watt Matched Stereo Systems with Model LA-350 Stereo Amplifier


AS LOW AS
184⁵⁰
\$9 Monthly



GARRARD MODEL 50 ON BASE




2 SK-300 Decor-ette V



2 SK-58

GARRARD MODEL AT 60 ON BASE



2 Eliptoflex®

Lafayette LA-350 70 Watt Stereo Amplifier
Garrard Model 50 4-Speed Record Changer
Wood Base for Changer (Specify oiled walnut or mahogany)
Pickering V15/AT-1 Diamond Needle Cartridge*
2 Lafayette SK-300 "Decor-ette V" 5 Speaker Slim Speaker Systems (Oiled Walnut)

Complete featured system as above with your * choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge, and with all necessary cables and instructions. Shpg. wt., 30 lbs.
21 N 9601CWXM..... Net 194.50

ALTERNATE SYSTEMS

System	Amp	Garrard Changer Base	Cartridge	Speaker/ Speaker System	Speaker Cabinet	Wt. Lbs.	Net
21 N 9602CWXM	LA-350	AT60	†	Choice of 2 SK-300	Decor-ette V*	81	204.50
21 N 9604CWXM	LA-350	50	†	Pickering 2 SK-58	-----	67	184.50
21 N 9605CWXM	LA-350	50	†	V15/AT-1	2 SK-58	115	242.25
21 N 9606CWXM	LA-350	AT60	†	or Shure	2 SK-58	69	194.50
21 N 9607CWXM	LA-350	AT60	†	M7/N21D	2 SK-58	117	252.95

† Specified oiled walnut or mahogany. ‡ Oiled Walnut, walnut or mahogany. * Oiled walnut only.

Any of above systems with addition of Lafayette MODEL LT-250 FM Multiplex Stereo Tuner add \$74.25 to price of system and 13 lbs to shpg. wt.

Any of above systems with addition of Lafayette MODEL LT-325 AM-FM Multiplex Stereo Tuner add \$82.50 to system price and 17 lbs. to shpg. wt.

Prices On This Page May Be Raised April 1st Due To New Excise Tax

LAFAYETTE 10-Watt Stereo Amplifier Model LA-214



39⁵⁰
\$5 Monthly

- 5 Watts of Power Each Channel
- Frequency Response 50 to 20,000 cps ± 1 db
- Front Panel Stereo Phone Jack
- Dual Concentric Bass and Treble Controls
- Rumble Filter
- Inputs for Ceramic and Crystal Phono, Tuner, High Level Tape
- Beautifully Styled

The Lafayette model LA-214 is a complete amplifier/preamplifier in a highly styled metal cabinet. It will faithfully reproduce such program sources as stereo or monophonic record changers, tuners, and stereo tape player. Features concentric bass and treble controls, rumble filter and front panel jack for stereo headphones. Other controls include Power/on; Volume, Mode selector (4 positions); 3-position program selector and Speaker/Phone switch. On rear panel 8 or 16 ohm speaker impedances may be selected and there is a handy speaker phase switch. Also included are a hum adjust and AC convenience outlet. Rugged hand wired circuit is fused for maximum component protection. Power output: 5 watts music power each stereo channel or 10 watts if used monophonically. The amplifier is compact enough to fit in any convenient location such as a shelf, table or bookcase. For 105-125 volts 50/60 cycles AC only. Tube complement: 2-6BQ5, 12AX7, 6CA4. Imported. Size 12½Wx5Hx7¾"D. (with legs). Shpg. wt., 15 lbs.

99 N 0023W Net 39.50

10-Watt Matched Stereo Phono Systems with LA-214 Amplifier

COMPLETE SYSTEM



88⁵⁰
\$5 Monthly

Lafayette LA-214 10 Watt Stereo Amplifier
Lafayette-Webcor 4-Speed Record Changer with Wide-Range Ceramic Turnover Cartridge with Synthetic Sapphire Stylus and LP Diamond Stylus Wood Base for Changer (Specify Mahogany or Walnut)

Two Lafayette SK-181 "Minuette" Speaker Systems (Walnut)



LAFAYETTE WEBCOR RECORD CHANGER



LAFAYETTE SK-181 "MINUETTE" SPEAKER SYSTEM

SK-265 SLENDERETTE III SPEAKER SYSTEM

Complete system above with all necessary cables and interconnecting instructions. Shpg. wt., 43 lbs.
21 N 9927CWXM Net 88.50

Same system as above except with two Lafayette oiled walnut finished Minuette speaker systems instead of walnut Minuette systems. Shpg. wt., 43 lbs.
21 N 9928CWXM Net 90.50

Same as above except with two Lafayette SK-265 SLENDERETTE III oiled walnut 2-speaker 2-way slim speaker systems instead of Minuette speaker systems. Shpg. wt., 62 lbs.
21 N 9929CWXM Net 96.50

Prices On This Page May Be Raised April 1st Due To New Excise Tax

LAFAYETTE 15-Watt Monaural Hi-Fi Amplifier Model LA-218



Only
44⁵⁰
\$5 Monthly

- Hum & Noise 75 db Below Rated Output
- Power Output 15-Watts
- Sensitivity: 3 mv. Magnetic Phono
- 5 Input Selections
- Frequency Response: 30-20,000 cps ± 1.5 db At Normal Listening Level

The Lafayette LA-218 is a perfect combination of outstanding performance, beautiful styling, and low price. It can easily be integrated into a fully equipped hi-fi system utilizing the 5 input selections. Because of its high input sensitivity, either magnetic or ceramic cartridges may be used, achieving full power output. A tape deck, even without playback preamplifiers, may be used in direct recording through tape output jack and in playing back through tape-head input. Also may be used with AM, FM or TV tuner music sources. A loudness control compensates for the loss of low frequencies when listening at low levels—you do not have to listen at high volume level to achieve full tonal quality. A scratch filter is useful in reducing noise of dusty or damaged records. Headphone jack is provided for private listening. Individual bass and treble controls each provide a boost of 10 db and cut of 14 db for adjusting to individual listening areas and tastes. Full 15 watts is sufficient power to adequately drive most speaker systems. Perfect for use as a second amplifier for converting to stereo or for starting out monophonically and adding stereo at a later date. Engineered to include every practical feature at a low, low price. Beautifully styled in popular low silhouette enclosure and will add beauty to any room decor. Size: 12 $\frac{1}{2}$ Wx5 $\frac{1}{4}$ Hx8 $\frac{1}{4}$ "O. Shpg. wt., 18 lbs. Imported.

99 N 0043WX

Net 44.50

SPECIFICATIONS:

Power Output: 15-watts; Frequency response: 30-20,000 cps ± 1.5 db (at normal listening level). Input Sensitivity: High level .23V, Magnetic phono 3 mv. Hum and Noise Level: Volume control at maximum—High level inputs 75 db below rated output, Magnetic phono and tape head inputs 58 db below rated output. Harmonic distortion: less than 1% at full power output. Outputs: 8 and 16 ohm impedance speaker outputs; tape output. Tube complement: 2-12AX7, 2-6BQ5, 1-12AU7, 1-6CA4.

LAFAYETTE 15-Watt Matched Hi-Fi Phono Systems



SK-265
Slenderette III

AS LOW AS
99⁹⁵
\$5 Monthly



GARRARD
MODEL 50

CHOICE OF STEREO CARTRIDGE

		
Pickering V15/AT-1	Empire 880	Shure M7/N210

Lafayette LA-218 15-Watt Complete Integrated Monaural Amplifier.

Garrard Model 50 4-Speed Record Changer.

Wood Base for Changer (Specify Mahogany or Oiled Walnut).

Pickering V-15/AT-1 Diamond Needle Cartridge

Lafayette SK-265 SLENDERETTE III, 2-Speaker 2-Way Slim Speaker System (oiled walnut).

Above system complete with choice of Pickering V15/AT-1, Shure M7/N210, or Empire 880 diamond needle cartridge plus interconnecting cables and necessary instructions. Shpg. wt.; 50 lbs.

21 N 9930CWX Net 99.95

Same as 21 N 9930CWX system except with Lafayette SK-300 Decorette V 5-Speaker Slim Speaker System (oiled walnut) instead of SK-265 speaker system. Shpg. wt., 52 lbs.


21 N 9931CWX Net 114.95

Same as 21 N 9931CWX except with Lafayette famous 12" Free-Edge Coaxial Speaker SK-58 instead of SK-300 speaker system. Shpg. wt., 46 lbs.

21 N 9932CWX Net 109.95

Same as 21 N 9932CWX system above plus Lafayette patented Eliptoflex speaker enclosure (specify oiled walnut, walnut, or mahogany). Shpg. wt., 70 lbs.


21 N 9933CWX Net 130.95



SK-300
Decor-ette V



SK-58



ELIPTOFLEX®

LAFAYETTE AM/FM Stereo Tuner Model LT-325



93⁹⁵
\$5 Monthly

- 20-Tube Performance—12 Tubes plus Tuning Eye and Rectifier and 9 Diodes
- MPX Separation 38 DB @ 400 CPS
- Less than 1% Distortion
- Dual Tuned Cascade Limiters and Wide Band Ratio Detector
- Grounded Grid R-F Front End for Low Noise
- Variable AFC Control
- Flywheel Tuning
- Stereo Noise Filter Switch
- Automatic Stereo Mode Indicator

Simplicity, Flexibility and Superb Styling have been carefully integrated in this quality tuner. Offering unlimited versatility, the LT-325 features new Automatic Stereo Monitor which shows automatically when you are tuned to a stereo broadcast. Tuning eye helps to tune all stations accurately. New "Stereo Search" circuitry provides an audible signal through both left and right channel speakers to let you know when you have tuned to a station broadcasting in FM stereo multiplex. Its new low silhouette enclosure can be placed proudly on an open bookshelf or custom installation anywhere in your home. On the front panel there is a mode selection switch with a choice of AM, FM, FM Stereo, and Stereo Search; power on/off Multiplex noise filter see-saw switches; a variable Automatic Frequency Control; and the main tuning control Flywheel tuning for smooth rapid station selection. Plate follower output permits using the tuner up to 50 ft. from an amplifier. FM circuitry features a grounded grid low noise front end and wide-band ratio


Features New Audible Tone Stereo Search System. Two 3-Gang Tuning Condensers With added Tuned RF Stage For Superb Sensitivity and Selectivity.

detector; superheterodyne AM circuit with 3 stages. AVC and ferrite loopstick antenna. Decorator finished extruded aluminum front panel with complementary case and metal knobs. Imported.
99 N 0001WX Shpg. wt., 17½ lbs. Net 93.95

SPECIFICATIONS

Frequency Response: FM and FM stereo 15-15,000 cps ± 1 db. FM Stereo Separation: more than 38 db @ 400 cps. Harmonic Distortion: FM and FM Stereo less than 1% @ 400 cps; MPX Noise Filter: -7db @ 10KC. SCA Rejection: better than 50 db. Tuner Sensitivity: FM 2 μv for 20 db of S/N. Variable FM AFC lock control, stereo tone search. Tubes: 6BE6, (3) 6BA6, (3) 6AU6, EM84, 6AV6, 6X4, 6BL8/ECF80, (2) 6AQ8/ECC85, 12AX7/ECC83. Power: 117V 50/60 cps AC, 60 watts. Dimensions: 14¾Wx4½Hx9½"D. Legs add ¾" to height. Shpg. wt., 17½ lbs.

LAFAYETTE FM Stereo Tuner Model LT-250



83⁹⁵
\$5 Monthly

- MPX Noise Filter
- Built-in Multiplex Circuit with 38 DB Separation @ 400 CPS
- Ratio Detector and Dual Tuned Limiters
- AFC Switch
- Stereo Mode Indicator
- Frequency Response 20-20,000 CPS ± 1 DB
- Low Silhouette Styling


- New Audible Stereo Search System To Locate Stations Broadcasting In FM Multiplex Stereo
- 3-Gang Tuning Condenser Provides A Tuned RF Stage For Excellent Sensitivity and Selectivity.

TRULY remarkable, quality performance and styling that will delight both your eye and your ear. Features the new stereo search control. When this circuit is energized by a station broadcasting in FM multiplex stereo, it sends an audible signal through both the left and the right channels. Tuning eye facilitates accurate tuning of all signals with pin point sharpness. Automatic stereo indicator lights when control is set to the "FM stereo" position. Engineered to provide high-quality FM and FM stereo reception, the LT-250 has a grounded grid low noise front end. The multiplex circuit provides a stereo separation of 38 db at 400 cps. with less than 1% distortion. Front panel controls consist of the Mode selector: (mono, stereo search,

FM stereo, FM stereo noise filter); see-saw AFC and power switches; and main tuning. Stereo dimension control to custom blend stereo reception (in-rear). Flywheel tuning control gives velvet smooth tuning action. Two stereo output jacks on rear panel. Tube complement: (2) 6BA6, (3) 6AU6, EM84, 6AV6, 6BL8/ECF80, (2) 6AQ8/ECC85, 12AX7/ECC83 and 6X4. Seven Germanium diodes and one Silicon diode. Extruded aluminum front panel with complementary case and metal knobs. Complete with cage and legs. Dimensions: 12¾Wx4½Hx9½"D. For 117V 50/60 cps AC. Imported. Shpg. wt., 13 lbs.
99 N 0002WX Net 83.95

NEW LAFAYETTE AM/FM TUNER MODEL LT-100A

A BUDGET PRICED AM-FM TUNER
PACKED WITH FEATURES



59⁹⁵
\$5 monthly


- FM Ratio Detector Plus Limiter
- Grounded Grid RF Stage
- AFC for Simplicity of Tuning-Locks in Stations

- Transformer Power Supply
- AFC Defeat for Tuning Weaker Stations
- FM Multiplex Output Jack
- 10 Tube Performance — 7 Tubes (3 Dual Purpose)


The LT-100A offers many fine features because of careful engineering and fine design. A powerful grounded grid RF stage allows clear reception of "hard to get" stations. This AM/FM tuner includes the convenience of a FM multiplex output jack—which allows easy connection to a multiplex adapter. Flywheel tuning is coupled to a large, illuminated side rule dial to insure real tuning ease. Built-in AM ferrite loop antenna and rear apron terminals for external AM and FM antenna are provided. Front Controls: 4

position selector switch including FM and AFC. FM Specifications: Sensitivity, 3-uv, Frequency Response, 20-20,000 cps \pm 1 db; Harmonic Distortion, less than 1% @ 400 cps. Attractively styled low silhouette metal enclosure has a brown finish to contract with the golden extruded aluminum front panel. Overall Dimensions: 12 $\frac{1}{2}$ "x4 $\frac{7}{8}$ "x9 $\frac{1}{2}$ "D. For 110-125 volts, 50-60 cps AC. Power consumption 40 watts. Shpg. wt., 15 lbs. Imported.
99 N 0006WX AM-FM Tuner Net 59.95

LAFAYETTE MATCHED TUNER-AMPLIFIER SYSTEM WITH MODEL LT-100A AM/FM TUNER



only
138⁵⁰
\$7.50 monthly




LA-214 Amplifier

LT-100A AM/FM Tuner



Laf/Webcor Record Changer



SK-265

LAFAYETTE Model LT-100A AM/FM Tuner
LAFAYETTE Model LA-214 10 Watt Stereo Amplifier
LAFAYETTE Webcor 4 Speed Record Changer
With Wide-Range Ceramic Turnover Cartridge
With Synthetic Sapphire Stylus and LP Diamond Stylus
Wood Base for Changer (Oiled Walnut)
LAFAYETTE Model SK-265 SLENDERETTE III
Oiled Walnut 2 Speaker 2-Way Slim Speaker System
Complete Monaural System as above with all necessary cables and instructions. Shpg. wt., 62 lbs. Net 138.50
21 N 9672WXM
FOR COMPLETE STEREO SYSTEM ADD
DNE Model SK-265 Speaker System plus Model KT-220 Multiplex Adapter Kit below.

LAFAYETTE MULTIPLEX ADAPTER KIT MODEL KT-220



QUALITY STEREO
FM MULTIPLEX
AT MINIMUM COST

19⁵⁰
\$5.00 Monthly

MADE IN
U.S.A.

- Separation 30db at 400 cycles
- self-powered • Ideal for Lafayette tuners equipment with MPX output jacks

Enjoy thrilling FM Stereophonic sound from any recent Lafayette Tuner or any other quality wide-band FM or FM-AM tuner equipped with Multiplex jacks by simply adding this low-cost Lafayette Multiplex adapter kit. Engineered for anyone to build and operate, the KT-220 is easily connected to your tuners built-in multiplex output and special instructions are provided for connection to tuners without MPX output jacks. Coils are pre-aligned and only minimum adjustments are necessary. Self-powered, the unit may be hidden out of sight or installed remotely from your tuner.

Specifications: Separation—30db at 400 CPS. Distortion—below 1%. Controls: Noise filter on-off, power on-off with pilot light, separation control (rear). Front panel is finished in beige and ivory trim with contrasting beige and brown cabinet. Size: 8 $\frac{1}{2}$ "x4 $\frac{3}{4}$ "x4 $\frac{3}{4}$ "H for 110-125 volts, 60 cycle AC. 19 N 0907 Shpg. wt., 4 lbs. Net 19.50

New Deluxe LAFAYETTE Hi-Fi Cabinetry TO DECORATE YOUR HOME WITH MUSIC

LAFAYETTE'S CRITERION MARK/II LINE

The standard of construction and design by which all others are judged.

TAMBOUR
EQUIPMENT
CABINET ONLY

89⁵⁰

\$5 monthly

Speaker Cabinet

59⁵⁰

\$5 monthly




Criterion[®]
MARK/II

THE TAMBOUR EQUIPMENT CABINET

Classic simplicity and elegance together with truly functional design characterize this new equipment cabinet. "Component Engineered" by Lafayette's audio experts to provide ample, convenient, well-ventilated accommodations for all of your components. When matched with its companion CRITERION MARK/II Eliptoflex speaker enclosure (described below) it forms a complete music center and perfectly matched furniture ensemble. The construction and design reflect the quality contained in these units: cabinets employ rigid tongue and groove construction of $\frac{3}{4}$ " lumber core woods throughout, with matched veneers inside as well as out. Smartly styled with tambour sliding doors and tapered legs for graceful, decorative harmony, as well as for room space saving. Four compartments provide space for housing turntable or changer, amplifier, tuner, etc., with room for record storage. Each upper compartment is 10Hx19 $\frac{1}{2}$ Wx15 $\frac{1}{2}$ "D; each lower compartment is 12 $\frac{1}{4}$ Hx19 $\frac{1}{2}$ Wx16 $\frac{3}{4}$ "D. Available in your choice of three finishes. Overall Dimensions: 41Wx18Dx32 $\frac{1}{2}$ H including legs. Shpg. wt., 70 lbs.

20 N 0133WX Walnut Net **89.50**
20 N 0134WX Oiled Walnut Net **89.50**
20 N 0135WX Mahogany Net **89.50**



Interior Dimensions
of Tambour Equipment Cabinet

each upper compartment
10"Hx19 $\frac{1}{2}$ "Wx15 $\frac{1}{2}$ "D

each lower compartment
12 $\frac{1}{4}$ "Hx19 $\frac{1}{2}$ "Wx16 $\frac{3}{4}$ "D



THE ELIPTOFLEX SPEAKER CABINET

The same graceful, timeless styling and fine construction as the CRITERION MARK/II equipment cabinet, which it matches. Designed to accommodate any 12" speaker, this enclosure incorporates the inner construction and acoustic principles of the famous Lafayette "Eliptoflex" enclosure. A specially designed elliptical port with diffracting ring broadens frequency response, increases transient response and eliminates cancellation effects between front and rear radiation. This results in low distortion, natural smoothness and unequal performance in the low ranges. Constructed of $\frac{3}{4}$ " lumber core woods with hand-rubbed natural wood veneers. Smartly styled with matching grille cloth, decorative tambour borders, and tapered legs. Overall Dimensions: 32 $\frac{1}{2}$ Hx18Dx16"W. Shpg. wt., 50 lb.

20 N 0136WX Walnut Net **59.50**
20 M 0137WX Oiled Walnut Net **59.50**
20 N 0138WX Mahogany Net **59.50**

Elegant Multi-Purpose Equipment Cabinet

ONLY
99⁵⁰
\$5 monthly



LUXURIOUS
STYLING

Add elegant charm to your decor with this beautiful "American Contemporary" multipurpose equipment cabinet crafted in fine woods, and finished beautifully in walnut. It is spacious cabinet will hold all of your Hi-Fi equipment in an ideal arrangement for your pleasure and convenience. The cabinet has 6 roomy compartments. The top three are 9 $\frac{1}{4}$ Hx15 $\frac{1}{2}$ "D. Each lower side compartment is 19 $\frac{1}{4}$ Wx13 $\frac{1}{4}$ "H. The lower center compartment is 18 $\frac{1}{4}$ Wx13 $\frac{1}{4}$ "D. Overall dimensions: 60Wx29Hx18"D. Three sculptured sliding doors make access to components easy without taking up space in your room. Shpg. wt., 110 lbs.
20 N 3809WX Walnut Finish Net **99.50**

Hi-Fi Components Are Available on Easy Pay Plan

Deluxe LAFAYETTE/WEBCOR Automatic Record Changer



A Superb Automatic 4-Speed Record Changer Made for Lafayette by Webcor

- Automatic 4-Speed Changer Plays 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 RPM Records Automatically or Manually
- Outstanding For Either Stereo or Monaural Use
- Intermixes Records of the Same Speed
- Heavy Duty 4-Pole 4-Coil Motor
- Ribbed Rubber Turntable Mat Prevents Slippage, Cushions Records
- Jam-Proof Tone Arm Mechanism
- Die-Cast Aluminum One-Piece Tone Arm
- Automatic Shut-off After the Last Record has Been Played
- Astatic Turnover Cartridge with .7 Mil Diamond Stylus for Microgroove Records, 3 mil Synthetic Sapphire Stylus For 78 RPM Records

29⁹⁵



COMPLETE WITH .7 MIL DIAMOND NEEDLE

A superb 4-speed automatic record changer made for Lafayette by Webcor, an outstanding leader in the development and manufacturing of top quality record changers in the United States. This Lafayette/Webcor automatic record changer has been designed to give a very high standard of performance and dependability. Plays stereo or monaural records superbly. Plays 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 RPM records automatically or manually. Intermixes a one-inch stack of 78 rpm 10 and/or 12-inch records, or a one-inch stack of 7 and/or 12-inch standard hole records of the same speed. Utilizes dynamically balanced 4-pole 4-coil motor. Mainplate has scientifically constructed ribs that absorb vibration, reducing rumble. The heavy turntable has an extra long turntable bearing that also virtually eliminates rumble and wow. Spindle prevents double record drop; enlarging of record hole. On-off reject switch permits manual record play without causing an automatic change cycle. Changer

automatically shuts off after last record has played. Jam-proof tone-arm. "Torsion Spring" action permits moving tone-arm at any time without damaging changer. Adjustable stylus set-down comes equipped with Astatic turnover stereo cartridge with .7 mil diamond stylus for microgroove records, and 3 mil synthetic sapphire tip for 78 RPM records. Minimum mounting dimensions: 14 $\frac{3}{4}$ " wide, 13 $\frac{1}{2}$ " deep, 5 $\frac{1}{2}$ " above and 4 $\frac{1}{4}$ " below mounting board. With 2" - 36" connector cables. Attractive finish in charcoal gray, aluminum and black. For 110-120 V., 60 cycles AC. Shpg. wt., 11 lbs.

21N0102W	Less base	Net 29.95
21N0103	45 RPM spindle—for above	Net 2.50
24N0112W	Oil walnut recessed base for above	Net 3.95
24N0113W	Mahogany recessed base for above	Net 3.95
24N0114W	Unfinished mtg. board for above	Net 1.10

Made By ADMIRAL for LAFAYETTE The Admiral ENSIGN



- 4-Speed—16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 RPM
- Plays Stereo or Monaural Records
- Quality Ceramic Turnover Stereo Cartridge
- Single Knob Speed/Function Control
- Automatic 3-Way Shut-Off
- Intermixes Records of Same Speed
- Heavy-Duty, Constant-Speed Motor

The Admiral "Ensign" is a fine 4-speed automatic record changer made by Admiral for Lafayette offering outstanding performance at a low, low price. Built for compatibility with both stereophonic and monaural records. The balanced featherweight tone arm operates at only 5.7 grams of needle pressure to minimize record wear. Arm is equipped with Flip-type Ronette ceramic stereo cartridge. Heavy precision turntable delivers no noticeable hum, rumble, or wow. Drive wheel disengages in neutral position, thus preventing rumble producing flat spots. Plays 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 RPM records. Intermixes 10" & 12" records of the same speed. Plays records manually if desired. Single knob speed/function control. Automatic 3-way shut-off after last record. 117VAC, 60 cycles. Compact and exceptionally functional, only 13 $\frac{1}{2}$ "x12x7 $\frac{1}{2}$ ". 3" below and 5 $\frac{1}{2}$ " above mounting board. Beautiful brown & gold finish. Shpg. wt., 12 lbs.

ONLY
19⁹⁵

21N0104W	Admiral "Ensign" less base	Net 19.95
24N0107W	Walnut Base for above	Net 3.95
24N0108W	Mahogany Base for above	Net 3.95
24N0109W	Mounting Board for above	Net 1.10
21N0105	45 RPM Spindle for above	Net 1.65

Boston, Mass. 584 Commonwealth Avenue

Garrard AUTOMATIC TURNTABLES

PLUS Your Choice Of Famous Stereo Cartridges For Only **1¢** MORE

CHOICE OF STEREO CARTRIDGE

 Pickering V-15/AT-1	 Empire 880	 Shure M7/N21D
---	---	---

GARRARD LAB 80 AUTOMATIC TURNTABLE

Precision automatic transcription turntable for professional reproduction of 33 $\frac{1}{3}$ and 45 rpm LP records only. Dynamically balanced tone arm is of low resonant afrormosia wood. Tracking force adjustable with audible/visual guide. Bias compensator cancels out tone arm skating force. Features integral cueing device, automatic shut off, heavy 12" balanced cast non-magnetic turntable, and advanced Garrard Lab series 4-pole shaded motor. Stereo wired. For 110-130V—17x14 $\frac{1}{4}$ " less base. Shpg. wt., 22 lbs. Imported from England.

21 N 3715WXM Lab 80 with Pickering V15/AT-1	Net 99.51
21 N 3716WXM Lab 80 with Empire 880P Cartridge	Net 99.51
21 N 3717WXM Lab 80 with Shure M7/N21D Cartridge	Net 99.51
21 N 3705WX Lab 80 less cartridge	Net 99.50

plus choice of PICKERING, SHURE, OR EMPIRE CARTRIDGE

99⁵¹



GARRARD TYPE A70 AUTOMATIC TURNTABLE

Successor to the world-famous "A" the 4-speed A70 automatic turntable features a completely new dynamically balanced tone arm. Built-in bias compensator—enables arm to track even the lightest and most compliant cartridges accurately, without distortion. Other outstanding features include: double shielded Lab Series 4-pole shaded motor, full-sized heavy balanced cast "sandwich" turntable. Stereo wired. Size: 16 $\frac{3}{4}$ "x14 $\frac{1}{4}$ ". For 110-130V, 60 cycles AC. Less base. Shpg. wt., 20 lbs. Imported from England.

21 N 3718WXM A70 with Pickering V-15/AT-1 Cart.	Net 84.51
21 N 3719WXM A70 with Empire 880 Cartridge	Net 84.51
21 N 3720WXM A70 with Shure M7/N21D Cartridge	Net 84.51
21 N 3706WX A70 Less Cartridge	Net 84.50

plus choice of PICKERING, SHURE, OR EMPIRE CARTRIDGE

84⁵¹



GARRARD TYPE AT60 AUTOMATIC TURNTABLE

The AT60 combines turntable performance with record changer convenience. Plays all 4-speeds: 16 $\frac{2}{3}$; 33 $\frac{1}{3}$; 45 and 78 rpm. Automatic intermix operation when desired. Features a heavy cast, oversized turntable (formally exclusive to the type A) . . . dynamically balanced and non-magnetic. The tone arm is the tubular, counter-weight adjusted, dynamically balanced design with built-in stylus pressure gauge legible from the top. Stereo wired. Size 15 $\frac{3}{4}$ "x13 $\frac{1}{4}$ "x4". For 110-130V, 60 cycles AC. Less base. Shpg. wt., 13 lbs. Imported from England.

21 N 3721WM AT60 with Pickering V-15/AT-1 cartridge	Net 59.51
21 N 3722WM AT60 with Empire 880 cartridge	Net 59.51
21 N 3723WM AT60 with Shure M7/N21D cartridge	Net 59.51
21 N 3707W AT60 less cartridge	Net 59.50

plus choice of PICKERING, SHURE, OR EMPIRE CARTRIDGE

59⁵¹



GARRARD MODEL 50 AUTOMATIC TURNTABLE

Quality in the Garrard tradition at a modest price. Features the same oversized turntable and handsome mat styling of the renowned AT-6. New counter-weighted cast aluminum tone arm with finger-touch stylus pressure adjustment. Convenient plug-in head. 4-pole shaded motor provides 4 accurate speeds: 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 rpm. Smooth changer mechanism offers automatic intermix operation. Size: 14 $\frac{1}{2}$ "x12 $\frac{1}{2}$ "x4". Stereo wired. Less base and 45 rpm spindle. For 110-130 volts, 60 cycles AC. Shpg. wt., 11 lbs. Imported from England.

21 N 3724WM Model 50 with Pickering V-15/AT-1 cart.	Net 44.51
21 N 3725WM Model 50 with Empire 880 cartridge	Net 44.51
21 N 3726WM Model 50 with Shure M7/N21D cartridge	Net 44.51
21 N 3708W Model 50 less cartridge	Net 44.50

plus choice of PICKERING, SHURE, OR EMPIRE CARTRIDGE

44⁵¹



LAFAYETTE ACCESSORIES FOR GARRARD TURNTABLES

RECESSED WOOD BASES. Sturdy, recessed, finely finished. Shpg. wt., 4 lbs. (not illus.)

Stock No.	Finish	For Models	Net
24 N 1201W	Oil Walnut	A70 and A	3.95
24 N 1202W	Mahogany	A70 and A	3.95
24 N 1203W	Oil Walnut	Lab 80	3.95
24 N 1204W	Mahogany	Lab 80	3.95
24 N 1205W	Oil Walnut	AT50, 50, AT6 and Autoslim	3.95
24 N 1206W	Mahogany	AT60, 50, AT6 and Autoslim	3.95


MOUNTING BOARDS. Unfinished, smooth sanded. Shpg. wt., 1 $\frac{1}{2}$ lbs. (not illus.)

24 N 1207W	For LAB 80	1.10
24 N 1208W	For A70 and A	1.10
For AT60, 50, AT6; Autoslim		
24 N 1209W		1.10

DELUXE GARRARD TURNTABLES PLUS YOUR CHOICE OF FAMOUS ELLIPTICAL STEREO CARTRIDGE AT LAFAYETTE'S LOW LOW PRICES



Pickering V15/AME-1



Empire 880PE

Now buy the deluxe Garrard Lab 80 or the Type A70 Automatic Turntable plus your choice of the Famous Pickering V15/AME-1 or Empire 880PE Elliptical Stereo cartridge at Lafayette's Low, Low combination prices. Elliptical Diamond Stylus reduces tracking, IM and harmonic distortion. Elliptical cartridge should not be utilized at a tracking force of over 3 grams.

Stock No.	Turntable/Elliptical Cartridge Combination	Net
21 N 9535WXM	Garrard Lab 80 plus Pickering V15/AME-1	109.50
21 N 9536WXM	Garrard Lab 80 Plus Empire 880PE	109.50
21 N 9537WXM	Garrard A70 Plus Pickering V15/AME-1	94.50
21 N 9538WXM	Garrard A70 Plus Empire 880PE	94.50

Stereo Integrated Turntables

WEATHERS "TOWNSEND 82" STEREO TURNTABLE



Only
59⁹⁶
\$5 Monthly

WITH CHOICE OF STEREO CARTRIDGE



Empire 880P



PICKERING
V15/AM-1

- Complete With Precision Tone Arm And Oil Walnut Base

Encased in walnut, the slim and compact Weathers "Townsend 82" is a low contour 33 $\frac{1}{3}$ rpm stereo turntable, 17 $\frac{1}{2}$ " wide by 14 $\frac{1}{2}$ " deep by 5 $\frac{1}{4}$ " high, including oil walnut tone arm. The arm will accept any standard cartridge and is adjustable to the stylus pressure and tracking angle recommended for each cartridge. Incorporates a 12 pole synchronous motor to achieve wow and flutter of less than 0.065%. Rumble is -50 db. "Delta shaped platform"

suspension system isolates the turntable from floor-bounce shocks or acoustic feedback. Aluminum turntable platter. Shpg. wt., 12 lbs.
21 N 6904WX Model 82 Turntable Net 59.95
Model 82 Turntable plus Empire 880P Stereo Cartridge
21 N 6908WX Net 59.96
Model 82 Turntable plus Pickering V15/AM-1 Stereo Cartridge
21 N 6909WX Net 59.96

RENOWNED AR 2-SPEED STEREO TURNTABLE

- Complete With Precision Tone Arm, Oiled Walnut Base, and Transparent Dust Cover

An outstanding turntable featuring a precision arm, oil walnut base and transparent dust cover in one compact unit. The rugged 3.3 lb. balanced aluminum platter is belt driven from synchronous motors operating at 33 $\frac{1}{3}$ and 45 RPM. Turntable and arm are shock-mounted from the top plate eliminating vibration. Meets NAB specifications for broadcast equipment on wow, flutter and speed accuracy. Also includes cables, overhang adjustment device and needle force gauge. Size with cover—12 $\frac{3}{4}$ x16 $\frac{3}{4}$ x5 $\frac{1}{4}$ ". Shpg. wt., 18 lbs.

21 N 7201WX Net 78.00
21 N 7202WX AR Turntable plus Empire 880P Net 78.01
21 N 7203WX AR Turntable plus Pickering V15/AM-1 Net 78.01

Only
78⁰¹

\$5 Monthly

WITH CHOICE
OF STEREO
CARTRIDGE



Empire 880P Pickering V15/AM-1



DUAL 1009 AUTOMATIC TURNTABLE

Only
99⁵⁰

\$5 monthly

WITH OIL WALNUT
BASE AND CHOICE
OF STEREO CAR-
TRIDGE



Empire 880P PICKERING
V15/AM-1


A deluxe automatic turntable which features a seven pound plus dynamically balanced non-ferrous platter. Precision, high torque, 4-pole motor resists variations in line voltage up to $\pm 10\%$. A unique three point suspension system provides acoustic isolation that is virtually impervious to mechanical vibration or acoustic feedback. Dynamically balanced professional tone arm. Dimensions: 12 $\frac{1}{2}$ " + $\frac{1}{2}$ " width, depth 10 $\frac{3}{4}$ " + $\frac{1}{2}$ ", above top of motor board 6 $\frac{1}{2}$ " below top of motor board 3 $\frac{1}{4}$ ". Shpg. wt., 19 $\frac{1}{4}$ lbs. Imported. *Additional $\frac{1}{2}$ " allows for counterweight clearance in cabinet installation.

Dual 1009 with oil walnut base plus Empire 880P stereo cartridge.
21-6527WX Net 99.50
Dual 1009 with oil walnut base plus Pickering V15 AT-1 stereo cartridge.
21-6528WX Net 99.50
21 N 6525 45 RPM spindle for 1009 4.80

Newark, N. J. 24 Central Avenue

**BENJAMIN
MIRACORD**

STUDIO 10H AUTOMATIC TURNTABLE



Only
99⁵¹
\$5 monthly

WITH CHOICE OF STEREO CARTRIDGE



Empire 880P Pickering V15/AM-1

The Miracord Studio 10H features a hysteresis motor, the famous "magic wand" spindle and a rectangular mass-suspended tone arm with interchangeable plug in cartridge head. Tracks and trips as low as 1 gram. Push-buttons select automatic or manual operation at any speeds playing all records including the new 33 $\frac{1}{3}$ 7" type. Satin chrome finish. Imported from W. Germany.

21 N 1601WX Model 10H less base and cartridge Net 99.50
21 N 1606WX Model 10H plus Empire 880P Net 99.51
21 N 1620WX Model 10H plus Pickering V15/AM-1 Net 99.51


ACCESSORIES for MIRACORD TURNTABLES

21 N 1603W Oiled Walnut Wood Base. Shpg. wt., 4 lbs. Net 8.95
21 N 1604W Unfinished Wood Base. Shpg. wt., 4 lbs. Net 8.95
21 N 1626 Automatic 45 RPM Spindle. Shpg. wt., 1 lb. Net 5.00
21 N 1628W Oil Wal. Integrated Base w/Plas. Dust Cover Net 19.95

22 Lafayette Cat. No. 653

Famous LAFAYETTE F-767 Stereo Headphones

Widely Acclaimed Headphones For The Hi-Fi Enthusiast



11⁸⁸

CONTROL BOX
4⁵⁹

- Air-Cushioned Headband
- Soft Foam Rubber Ear Cushions for Maximum Comfort and Bass Response
- High Sensitivity

Lafayette's Famous F-767 stereo headphone offers outstanding sound reproduction to the listener. Extremely comfortable, the F-767 headband is covered with an air-filled vinyl bag which serves as a gentle air cushion. Soft foam rubber ear pads keep out external noise, provide maximum bass response. Sensitivity is very high—a signal power of 1 to 2 mw will produce adequate listening volume. Frequency response, 30-15,000 cycles. Impedance, 8 ohms per phone. Supplied with cylindrical overload control box for connection of the head phones to equipment that does not have stereo headphone jacks. Phones plug into box and two pairs of leads from the box connect to speaker output terminals; may also be attached to two separate 2-conductor phone plugs for connection to units having two separate extension speaker jacks for stereo. This headphone and control box not recommended for transistor amplifiers that do not have a stereo headphone jack—use Model FA-60 headphone set (below) in such cases. F-767 supplied complete with attached stereo phone plug, overload junction box and instructions. Imported.
99 N 0035 Shpg. wt., 2½ lbs. Net 11.88

MODEL FA-60 STEREO HEADPHONES

- For Use With Transistor Amplifiers That Do Not Have A Stereo Headphone Jack

Same quality headphones as above, but comes with 4 separate leads terminated in spade lugs, plus over-load junction box with 4 screw-type input terminals and 4 output leads (all 4 leads isolated). Designed for connection to speaker terminals of transistor amplifiers or whenever complete isolation of all four wires is desired. Imported.
99 N 0048 Shpg. wt., 2½ lbs. Net 11.88

STEREO HEADPHONE CONTROL BOX

F-641 stereo control box is designed to connect F-767 stereo headphones to an existing system without the need of continually disconnecting speakers (cannot be used with FA-60). Impedance 4-16 ohms. Has separate earphone jacks for stereo or monaural, separate volume controls for each side of the headset, and a speaker on-off switch. 4¼x1¼x1½" D. Imported.
99 N 0036 Shpg. wt., 1¼ lbs. Net 4.59

DELUXE LAFAYETTE F-770 STEREO-PHONES

- Private Listening
- No Space Problem
- Exceptionally Fine Quality
- Stereo and Monaural
- Actually 2 High Fidelity Dynamic Speakers
- Soft Foam Rubber Ear Pads
- Frequency Response 25 to 15,000 Cycles

19⁹⁵



The Lafayette F-770 combines broad frequency response and faithful reproduction with a comfort-oriented design to make listening with them a real pleasure. The Stereophones are actually two 2½" high fidelity dynamic speakers with a frequency response range of 25 to 15,000 cycles. Perfect for stereo and monaural operation, the headphones are rated at ½ watt maximum input; impedance, 8 ohms per phone. The soft foam rubber ear pads provide extremely comfortable listening, help to keep out noise and maintain an excellent bass response. Imported.
99 N 0034 Shpg. wt., 2 lbs. Net 19.95

Control Box for F-770

Permits flexible one-switch change-over from speakers to Stereo phones. Imported.
99 N 0037 Net 4.95
"Y" connector for connecting 2 or more sets of headphones to a single source.
99 N 0044 Net 2.45

UP DATE YOUR HI FI SYSTEM WITH THESE FINE PREMIUM HI FI STEREO CARTRIDGES COMPLETE WITH DIAMOND STYLUS



Pickering V15/AT-1 21 N 5315L	1795	Pickering Mark IIC 21 N 5339L	688	ADC-660 21 N 1307L	1995	Empire 880P 21 N 3402L	1995
Pickering V15/AM-1 21 N 5316L	2195	Pickering U38/AT 21 N 5301L	1275	ADC-770 21 N 1308L	1795	Empire 880 21 N 3401L	1795
Pickering V15/AME-1 Elliptical 21 N 5344L	2995	GE Model VR1000-7 21 N 3803L	1049	Ortofon Sup/T 21 N 3208L	5000	Empire 880PE 21 N 3412L	2995

Elliptical Hand Polished Diamond Stylus replacement for EMPIRE 880P
21 N 3413L

14.95



25 FT. UNIVERSAL STEREO HEADPHONE EXTENSION CORD ONLY 2²⁹

Listen to stereo through your favorite stereo headphone anywhere in the room. Ideal for use with Lafayette, Koss, Superex, Jensen, Sharpe and many other headsets. Flexible 3-conductor cable, grey vinyl jacket. 25 ft. in length. With ¼" 3-circuit plug on one end and a 3-circuit jack on the other end. Shpg. wt., 1 lb. Imported.
99 N 0116 Net 2.29

FAMOUS SHURE STEREO CARTRIDGES WITH DIAMOND STYLUS



M7/N21-D

M-44-5

1200

M-3D
21 N 6201L

1795

M7/N21-D
21 N 6206L

2195

M-44-5
21 N 6215L

1995

M-44-7
21 N 6216L

3550

M-55E*
21 N 6221L

*Elliptical Diamond Stylus

Selected Trutest® Stereo Amplifiers

Trutest® STEREO/8 AMPLIFIER **Trutest® STEREO/5 AMPLIFIER**



Compact Low Silhouette Styling!


17⁹⁵

- Separate Stereo Volume-Balance Controls
- Variable Tone Control With On-Off Switch
- Front-Panel Phono-Tuner Switch for Selection of Phono or Tuner
- Selector Switch for Monaural or Stereo Operation

Ideal for that low cost stereo system you are planning for your living room, den, bedroom or business. It's petite size lends itself easily to any location—it's attractive low silhouette styling will blend beautifully with the furniture decor in any room of your home or business. Excellent for converting your present monaural console or portable to stereo.

Controls include separate Left Channel and Right Channel Volume-Balance Controls, Stereo/Monaural Mode switch, Variable Tone control with On-Off switch, Phono/Tuner Selector switch; 4 jacks in rear for stereo tuners and stereo crystal or ceramic phono cartridges; 2 pair of 4-ohm output terminals accept most speakers. Tubes and components mounted horizontally for compactness. Complete with case. Tube complement: 1-12AX7, 2-85C5, and 1-35W4. Size: 7¼" W x 2¼" H x 5½" D. Imported.

99 N 0047 Shpg. wt., 6 lbs. Net 17.95



10⁹⁵

- Individual Stereo Volume-Balance Controls
- For Both Stereo and Monaural
- Fully Wired—Ready For Stereo

A stereo amplifier priced to fit everyone's purse. This rugged, precision made dual channel stereo amplifier will amaze you with its fine quality . . . Ideal for that low cost stereo system you're planning for your home or business. Perfect for converting your present console or portable to stereo. Controls include separate left channel and right channel volume controls, stereo-monaural mode switch, tone control switch and on-off switch. Provision for crystal or ceramic cartridge. 4-ohm output terminals accept most speakers. Tube complement: 2-35C5, 1-35W4 and 1-12AX4. Size: 4½" H x 5½" W x 4½" D. 115 volt 60 cycles. Shpg. wt., 5 lbs. Imported.

99 N 0048 Net 10.95

COMPLETE STEREO PHONO SYSTEMS

- Featuring Lafayette/Webcor 4-Speed 4-Pole Automatic Changer

AS LOW AS 57⁵⁰

\$5 monthly

Complete system consists of Trutest Stereo/8 Stereo Amplifier, Lafayette—Webcor Automatic 4-speed Record Changer with wide-range stereo turnover cartridge, with diamond stylus, 2 Lafayette SK-109 Miniature Speaker Systems in Attractive Mahogany veneer finish. Above system supplied complete with 25' speaker cable for each speaker, less changer base. Shpg. wt., 26 lbs.

99 N 9902WXM Net 82.50

Same system as above except with Stereo/5 stereo amplifier instead of Stereo/8 stereo amplifier.

99 N 9903WXM Shpg. wt., 25 lbs. Net 57.50

24 N 0113W Mahogany base for changer Net 3.95

NEW Lafayette® STEREO VU BALANCE METER



11⁹⁵

- Two Meters in One
- Balances Stereo Systems

Ends the problem of balancing your stereo system. Two precisely damped loudness meters provide a continuous comparison of speaker levels. Scales calibrated in "Volume Units" and percent. 1.2 volts input sensitivity for 0 VU or 100 percent indication. The special calibrating switch and 20 db attenuation controls permit exact matching of channels. Greater than 8,000 ohm impedance permits connecting to output circuits without loading. The entire unit is housed in an attractive plastic case 6 W x 3¼ H x 2¾ D. Imported.

99 N 5038 Shpg. wt., 3 lbs. Stereo Balance Meter Net 11.95




Trutest Stereo/8



Lafayette—Webcor Record Changer On Base




Diamond Stylus



2 Lafayette SK-109



Stereo/5 (Alternate)



ROTRON WHISPER FAN

- Super Silent, Compact
- Reduces Service Costs
- Ideal For Cooling Hi-Fi Equipment

14⁸⁵

The ideal fan for cooling hi-fi equipment. Extremely quiet, introduces no distortion, yet it moves 60 cubic feet of cool air per minute. Lets your equipment last up to 40% longer! Compact in design, easily installed in any position. Airflow is reversible. Advanced heavy system; slow speed, and prelubrication will provide years of maintenance-free operation. For 115VAC, 60 cps, 7 watts. Size: 1½" deep and 4¼" square.

24 N 7501 Shpg. wt., 1 lb. Net 14.85

BALL BEARING HEAVY DUTY SLIDES



AS LOW AS 150

Drawer slides made of 16 gauge steel. Supports 50 lbs. Ball bearing, double-extension type, drawer slides. Length 15" travel length 11". extended 22". Shpg. wt., 5 lbs.

20 N 5201 per pair Net 1.75


SHORT TYPE. Same construction as above but 13" long; travels 9"; extends to 22".

20 N 5202 per pair Net 1.50


Plus Phono and Hi-Fidelity Accessories

GARRARD ACCESSORIES

RADIO BROADCASTER/PHONO OSCILLATOR



- 45 RPM AUTOMATIC SPINDLES (FIG. A)**
Avg. wt., 10 oz.
- 21 N 3709 For Lab 80 3.80
 - 21 N 3710 For A70 and A 3.80
 - 21 N 3711 For AT60 and 50 3.80
 - 21 N 3712 For AT6 3.80
 - 21 N 3713 For Autoslim 3.80
- PLUG-IN HEADS (FIG. B)**
With mtg. accessories. Shpg. wt., 6 oz.
- 21 N 3727 For LAB 80 and A70 2.50
 - 21 N 3728 For AT60 and 50 1.75
 - 21 N 3729 For A 1.75
 - 21 N 3730 For AT6 and Autoslim 1.75
- GARRARD PRESSURE GAUGE (FIG. C)**
Model SPG3. Insures correct pressure. Large, legible scale with widely spaced, easy-reading 1/2-gram markings. Swiveling balance scale pan. With 5-gram brass weight "standards" to check accuracy. Shpg. wt., 6 oz.
- 21 N 3731 Net 2.95
- DUST COVERS (FIG. D)**
Molded of clear sparkling vinyl to fit contours of Garrard changers. Shpg. wt., 1 1/2 lbs.
- 21 N 3733 For Lab 80 A70 and A Net 4.95
 - For AT-60, 50, Autoslim and AT-6 Net 4.95
 - 21 N 3734 Net 4.95



- 475**
Have fun making announcements and broadcasting music through your own radio — with this broadcaster. Simply connect high impedance microphone or phono pickup to broadcaster and tune in broadcaster on radio. No wiring between the broadcaster and radio set. Pretuned to 1600 on radio dial but easily retuned. With 12BE6 and 35W4 tubes, phono jack, 2 feet of antenna, schematic and line cord. Completely wired. Chassis size: 4x2". For 110-125V AC/DC operation. Shpg. wt., 2 lbs.
- 24 N 1301 Net 4.75
- 2 TUBE AMPLIFIER WITH TUBES**
(Fig. A) Uses a 50L6 and 35Z5 rectifier tube. Has volume control with switch and tone control. Chassis size: 2 1/2 x 3 1/2". For 110 125V, AC or DC. With cord and plug, tubes, diagram but less output transformer. Shpg. wt., 3 lbs.
- 24 N 1302 Net 4.90

THREE TUBE AC-DC PHONO AMPLIFIER

- (Fig. B) Equipped with a variable tone control and a separate volume control with off position. Delivers up to two watts output. Phonograph motor connects to the amplifier. Uses 3 tubes: 12AV6, 50C5, and 35W4 rectifier. For 110-125V AC or DC. 2 1/2 x 4 1/2" steel chassis. With cord and plug, schematic, but less tubes and output transformer. Shpg. wt., 2 lbs.
- 24 N 1303 Net 3.75
- (Fig. C) OUTPUT TRANSFORMER matches output tube to 3-4 ohm voice coil. Shpg. wt., 1/2 lb.
- 33 N 3701 Singly ea. .49
 - In lots of 5 ea. .45

STEREO/MONAUROAL PICKUP



- 195**
Employs a high-output crystal turnover cartridge for either stereo or monaural operation. Frequency response, 20-18,000 cycles; output, 1 volt per channel. Crosstalk between channels is 15 db or more down. Each channel has a separate shielded output cable. Travel lock arm rest prevents accidental damage to records. The pickup arm is designed to be mounted in a single, circular hole, 3/4" in diameter. Equipped with side attachment for easy lifting and setting down. Durable plastic construction. Shpg. wt., 7 oz. Imported.
- 99 N 1024 Net 1.95
 - Synthetic Sapphire LP replacement needle for above. Net .49
 - 99 N 1027 Net .49
 - Synthetic Sapphire STD replacement needle for above. Net .49
 - 99 N 1028 Net .49

THE "DUST BUG"



- Automatically removes dirt and dust on each playing. Light plastic arm mounts by suction cup. Can be permanently mounted by rubber cement. The bottle of antistatic cleaning fluid has a built-in wick for application to a brush and pad at the end of arm. Shpg. wt., 6 oz.
- 24 N 2501 Standard model (A) Imported Net 5.95
 - CHANGER DUST BUG (B). The tuft and pad assembly clips onto arm of changer. Performs the same as the standard model. Shpg. wt., 4 oz.
 - 24-N 2502 Changer model (B) Imported Net 4.95
 - DISPENSER OF ACTIVATING FLUID. For Dust Bugs. Net 1.25
 - 24 N 2504 Net 1.25
 - 24 N 2503 Replacement Plush Pad and Nylon Brush Net 1.50

HI-FI-TV ADAPTOR

- Hear True Hi-Fi From Your TV Set



- Enjoy your favorite TV programs in the true high fidelity sound as it is broadcast with this HI-FI TV adaptor. Simply incorporate the Adaptor with your present hi-fi system and TV set by connecting it to your TV and amplifier or receiver. The Adaptor picks up the hi-fi signal in the TV set and feeds it to the amplifier or receiver, after which the hi-fi sound is faithfully reproduced through the speaker system of the hi-fi system. Tape recording enthusiasts can also tape programs of their choice with full fidelity. Just connect the adaptor to the TV set and to the recording input of the tape machine. The Adaptor may be placed at the TV set or at the amplifier or tape recorder. The unit has been precisely pre-set at the factory and no other adjustment is required. Easy to install—all you need is a screwdriver. Supplied with a 6-ft. insulated wire with a tube clamp for connection to the TV receiver, plus a 6-ft. patchcord for connection to the amplifier or tape recorder. Overall 9 1/2 x 6 1/2 x 3" H. Shpg. wt., 5 lbs.
- 24 N 2400 Net 32.95

LAFAYETTE STEREO AUDIO CABLES



- Two shielded insulated cables, of different color tones, for easy identification of channels) inside a common chrome grey plastic jacket, providing two completely isolated channels. Avg. shpg. wt., 6 oz. Imported.
- | Type | Length | Net |
|-----------|--------|----------------|
| 99 N 0113 | 36" | Phono pin 1.17 |
| 99 N 0114 | 6' | plugs at 1.35 |
| 99 N 0115 | 10' | all ends 1.62 |

RECORD CLEANING KIT



- 129**
Deep clean your records the modern way. Specially prepared detergent anti-static record cleaning fluid protects your valuable records as it cleans. Just a few drops on new velvet-foam rubber applicator mitt will give your records a professional cleaning job. Supplied with anti-static fluid, velvet applicator mitt and polyurethane pad.
- 24 N 8502 Shpg. wt., 10 oz. Net 1.29
- Lafayette Cat. No. 653 25

LAFAYETTE Professional 4-Track Stereo Record & Playback Tape Deck




Optional
Dynamic Mikes

Model RK-650

109⁹⁵
\$6 monthly

- Deluxe Pushbutton Operation
- Complete with Built-in Transistorized Record & Playback Preamps
- Automatic Cut-off Switch Stops Recorder at End of Tape or When Tape Breaks
- Separate Record/Play and Erase Heads
- Smooth, 4-Pole Capacitor—Start Motor
- 2 Level Indicator Meters

The RK-650 abounds in professional-type features making it suitable to meet every stereo and monophonic recording situation. Tape transport and electronic components are integrated into one lightweight unit, for use in either a portable carrying case or a handsome built-in home installation. Has an ultra quiet 4-pole heavy duty, low sllp capacitor-start motor and belt-drive for double flutter filtering. Automatic tape and machine stop at end of the tape or during a break in the tape. The Pause control assists in making "pro" recordings by stopping the tape momentarily for editing. Separate channel recording permits sound-with-sound. Clear FM multiplex recording is assured by high (80 KC) bias operation.



PROFESSIONAL OPERATING FEATURES

- A. TAPE REELS—TAKE UP TO 7" SIZE
- B. AUTOMATIC TAPE CUT-OFF SWITCH
- C. HEADS—SEPARATE RECORD/PLAY & ERASE
- D. TAPE POSITION INDICATOR
- E. INPUT SELECTOR SWITCH
- F. SPEED SELECTOR/POWER ON-OFF
- G. RECORD LEVEL METERS
- H. INDIVIDUAL VOLUME CONTROLS
- I. MASTER VOLUME CONTROL
- J. SEPARATE CHANNEL RECORD BUTTONS
- K. PAUSE CONTROL
- L. 4 PUSHBUTTON TAPE MOTION CONTROLS
- M. ON-OFF PILOT LIGHT

All tape transport and electronic controls are located on the top panel for easy access. Has positive action pushbutton motor control. For 117V, 60 cycles AC. Tape Deck is complete with preamps, 4 connecting cables and empty reel. Shpg. wt., 20 lbs. Less Case and Microphones. Size: 15¼Wx6¼Hx11¼"D. Imported.

99 N 1502WX Model RK-650	Net 109.95
Model RK-650 with deluxe carrying case	
99 N 1503WX	Net 124.95
99 N 1510W Oiled Walnut base for RK-650	Net 6.95
99 N 4502 Dynamic Microphone for RK-650	Net ea. 4.75
	2 for 8.95

SPECIFICATIONS

Frequency Response, Record/Playback: 40-18,000 cps @ 7½: 40-12,000 cps @ 3% ips. 4 transistors, 4 tubes; 1 full-wave bridge rectifier. Audio Output: .8 volts per channel. Signal-to-Noise Ratio:

—45 db. Interchannel Separation: 45 db or better; Wow & Flutter: 0.2% @ 7½ ips, 0.25% @ 3% ips. Bias & Erase: 80KC; Outputs: 2 audio, 2 monitor. Inputs: 4.

LAFAYETTE 2-Speed Stereo Playback Tape Deck with 6-Transistor Dual Stereo Preamps



Model RK-141

ONLY
59⁵⁰
\$5 monthly

SPECIFICATIONS

Frequency Response: @ 7½ IPS, 50-15,000 CPS ± 1.5 db; @ 3% IPS, 50-9,000 CPS ± 2 db. Wow & Flutter: .15% @ 7½ IPS, 0.2% @ 3% IPS. Cross Talk & Stereo Channel Separation: 50 db. Signal To Noise Ratio: 50 db. Playback Output: with Built-in Stereo Playback Preamplifiers 0.5V. Power: 110-120V 60 cycles AC operation.

PLAYS BACK

- Stereo ¼-Track; ½-Track
- Monaural ½-Track; Full-Track
- Dual NAB Equalized Transistorized Stereo Playback Preamps Allows Use With Virtually Any Stereo Amplifier
- Frequency Response: 50-15,000 cps @ 7½ ips
- Accepts Full-Size 7-inch Reels
- Automatic Shut-Off At End Of Tape

Precision engineered to satisfy the most discriminating music listener, the RK-141 will playback with uncompromising fidelity ¼-track and ½-track stereo tapes plus ½-track and full-track monaural tapes. The RK-141 is equipped with its own built-in 6-transistor dual stereo playback preamplifiers equalized for the NAB tape curve . . . allows use with virtually any stereo amplifier by merely connecting to the auxiliary, tuner, or hi-level tape inputs. Precision laminated playback head. Automatic shut-off at the end of the tape. The 4-pole, heavy-duty, constant speed induction motor has front panel speed selector switch. In addition, two rugged lever-action controls provide for Rewind, Off, Play and Fast Forward functions. Accepts all size tape reels up to and including 7". Measures 10¾Dx14¾Wx5"H. Complete with shielded hook-up cables. Shpg. wt., 17 lbs. Imported.

99 N 1513WX Model RK-141 Stereo Playback Tape deck	Net 59.50
Furniture Grade Walnut Base for RK-141. Shpg. wt., 4 lbs.	
99 N 1514W	Net 6.95
Portable Carrying Case for RK-141. Shpg. wt., 5 lbs.	
99 N 1515W	Net 9.95

LAFAYETTE'S Top-Rated Model RK-137A Tape Recorder

FEATURING 4-TRACK STEREO PLAYBACK* 4-TRACK MONAURAL RECORD PLAYBACK

With **ELECTRONIC TRACK SELECTOR SWITCH**, **VU RECORDING LEVEL METER** and **PAUSE SWITCH** FOR INSTANT EDITING

- Two Speeds—3¾ & 7½ ips
- Pause Lever Provides Instant Stop for Editing
- Record—Erase Safety Switch
- Fast, Rugged Shift Lever Control
- Extension Speaker Jack
- High Impedance Monitoring Jack
- VU Meter Recording Level Indicator
- Electronic Track Selector Switch
- Specially Designed Heavy Duty 6x4" PM Speaker
- Separate Erase and Record Heads

The RK-137A Tape Recorder contains a fine, quality constructed, smooth performing tape mechanism. Engineered to provide virtually every wanted tape recorder feature, the RK-137A performs brilliantly, with facilities for 4-track monaural record/playback and 4-track stereo playback *(when used with a second channel containing a tape head input such as found in a component HI-FI system). Controls are completely functional and are designed and arranged to make the RK-137A a genuine pleasure to use. Features include: a rugged, easy to use shift lever for fast rewind, fast forward, play and record functions; a special push-button safety record switch assures against accidental erasure of tapes; velvet-smooth volume and on-off tone controls; a pause lever instantly stops tape in motion, especially useful for editing; track switch provides fast, dependable electronic switching between tape tracks 1-4 and 3-2. In addition a VU recording level meter has been incorporated to indicate correct volume setting for recording. Speeds are adjustable from 3¾ to 7½ inches per second by means of a simple capstan adjustment. From a standard 7" 1200 ft. reel the RK-137A provides over 2 hours monaural record/playback time at 7½ ips and over 4 hours at 3¾ ips. Jacks are furnished for microphone input, High Impedance Radio-Phono Input, Extension Speaker Output Monitor Output and Stereo Head Output for playback of 2nd stereo channel. Shpg. wt., 22 lbs. Imported.

99 N 1511WX Model RK-137A Tape Recorder Net 89.50
7" reel of 1200 ft. Lafayette Recording Tape Net 1.59
28 N 0101 Net 1.59



EMPTY 7" REEL

**TAKES FULL 7"
REEL OF
TAPE**



only
89.50
\$8 monthly

COMPLETE with
MICROPHONE
SHIELDED PATCH CORDS
EMPTY 7" REEL

Includes Lightweight
Carrying Case

SPECIFICATIONS:

RESPONSE: 40-15,000 cps at 7½ ips, 40-9,000 cps at 3¾ ips.
S/N RATIO: 40 db. WOW/FLUTTER: less than 0.3%. CHANNEL
SEPARATION: 46 db. INPUTS: Radio, Mic. OUTPUTS: Stereo Tape
Head, External Spkr., Monitor. AMPLIFIERS: Single Channel,
tube-type preamp and power amp. TAPE HEADS: 4-Track Stereo
record/playback and erase heads.

Deluxe LAFAYETTE Portable Tape Recorder

- With Recording Level Indicator
- ½-Track Doubles Play and Record Time
- Two Speeds—3¾ or 7½ ips.
- 4x6" Speaker for Fine Tonal Reproduction
- Provision for External Speaker
- Permits Direct Recording from Radio or Phono

Model RK-142

59.95

\$6 monthly

COMPLETE with
MICROPHONE
SHIELDED PATCH CORDS

Perfect for home, school or office. At home, the RK-142 proves ideal for parties or recording your favorite musical performance. Handy fool-proof operation has been provided by a specially designed lever type record switch which completely eliminates the chance of accidental erasure. At 3¾ ips, the RK-142 provides more than 4 hours recording on long play ½ mil 2400 ft. tape reel. A special 4x6-inch heavy duty permanent magnet speaker furnishes an exceptionally fine tonal quality. Record level indicator facilitates recording by showing you when the volume control is correctly set. Jacks provide for microphone, phono and extension speaker (special alligator clip cord is supplied). Complete with sensitive dynamic microphone. Finished in attractive scuff-resistant material. Dimensions: 11¾x9¾x7½". For 117 volts, 60 cycles. Shpg. wt., 22 lbs. Imported.

99 N 1512WX Model RK-142 Deluxe Tape Recorder Net 59.95



**TAKES REELS
UP TO 7"**

SPECIFICATIONS—Tape speed: 7.5 and 3.75 ips in two speeds. S/N ratio: —42 db or better at 7.5 ips tape speed. Rewind time: 3 min. for 7" reel. Fast Take-up Time: 3 min. for 7" reel. Response: Record-playback response essentially flat with tone at max. treble. Wow-Flutter: 0.2% or better at 7.5 ips; 0.3% at 3.75 ips. Power Output: 2 watts.

LAFAYETTE Compact 4-Track Stereo Recorder

- PLAYS—4-Track Stereo Tapes, 2-Track Stereo Tapes, Monaural 2-Track Tapes, Monaural Full Track Tapes
- RECORDS—4-Track Stereo, 4-Track Monaural.
- Two Speeds: 3¾ & 7½ ips
- 2 6x4" Hi-Fi Speakers

SOUND-WITH-SOUND

**MODEL
RK-600A
129⁵⁰**


As little As \$6 Monthly

**COMPLETELY
SELF-CONTAINED**

**LIGHTWEIGHT AND
COMPACT—
MAKE STEREO
RECORDINGS
ANYWHERE!**



7" Empty Reel



2 Dynamic Microphones



Patch Cords

SPECIFICATIONS

Frequency Response: 40-15,000 cps at 7½ ips. Stereo Separation: 45 db. Wow & Flutter: As low as 0.25%. S/N Ratio: 45 db. Reel Capacity 7" reel. Speakers, (2) built-in 4" x 6" oval. Audio Output: 1.5 watts per channel. Erase Frequency: 80 kc. Heads: 4 track—separate record/playback and erase heads, mu-metal shielded.

The RK-600A is a complete 4-track, 2-speed stereo tape recorder . . . needs no extra amplifiers or speakers. Plug in the microphones supplied and make "live" stereo recordings anywhere . . . play the tape back and hear your recording in full-dimension stereo—you'll be amazed how wonderfully easy it is! RK-600A also has inputs for recording from radios, FM tuners, Hi-Fi amplifiers, etc. Simply connect the patch cords supplied to your program source and follow the simple recording procedure, either in stereo or monaural . . . lets you keep a permanent recording of your favorite musical programs, etc. The recorder also makes "sound-with-sound" recordings—a feature that allows you to accompany yourself in a duet, add your voice to pre-recorded music, etc. And, "sound-with-sound" allows you to re-record one track if you are dissatisfied with it—without removing the recording on the other track!

Other features include fast-forward and fast-rewind facilities, simple tape threading arrangement, individual neon recording level indicators, a hi-lo tone switch, speaker muting switch, plus extension speaker outputs. The RK-600A is housed in a smart vinyl covered case with handle and is supplied complete with 2 dynamic microphones, patch cords and empty 7" reel. For 117V, 60 cycles AC. Dimensions: 16½Wx11Dx7½"H. Imported. Shpg. wt., 31 lbs. Model RK-600A Stereo Tape Recorder . . . Net 129.50
99 N 1506WX . . . Net 1.59
7" reel of 1200 ft. Lafayette Recording Tape
28 N 0101 . . . Net 1.59


SUPERBLY STYLED . . . WITH THESE DELUXE FEATURES



- 1 Heads—Separate record/playback and erase heads, mu-metal shielded.
- 2 INDIVIDUAL CHANNEL RECORD BUTTONS—Permit sound-with-sound recording.
- 3 INDIVIDUAL CHANNEL VOLUME CONTROLS—Provide volume adjustment on playback, act as input level controls during recording.
- 4 POSITIVE-ACTION CONTROL LEVER—Assures easy control of rewind, fast forward and record/playback functions.
- 5 2 SPEEDS—Choice of 7½ ips or 3¾ ips by means of simple capstan adjustment.
- 6 PAUSE CONTROL—Provides safe, instant stop for editing. Control is self-holding.
- 7 SOUND DEFLECTOR SIDE PANELS—Let you deflect speaker sound for best stereo effect.
- 8 HI and LO LEVEL INPUTS—Stereo inputs for recording from microphones, FM stereo tuners, stereo amplifiers, radios, etc.
- 9 MONITOR OUTPUTS—For playback through stereo amplifier, or headphone monitoring during recording.
- 10 INDIVIDUAL RECORDING LEVEL INDICATORS—Provide indication of correct volume adjustment on record.

LAFAYETTE Deluxe Pushbutton 4-Track Stereo Tape Recorder

DESIGNED TO RECORD FM STEREO BROADCASTS



- Records 4-Track Stereo, 4 Track Monaural
- Plays 4 and 2-Track Stereo and 4-Track Monaural
- 6 Pushbutton Controls
- Sound-with-Sound
- Automatic Shut-off of Tape Transport
- Wide Frequency Response for "Life-Like" Reproduction
- Heavy duty 4-Pole Capacitor Start Motor

COMPLETE WITH CARRYING CASE
2 DYNAMIC MIKES, OUTPUT CABLES
AND 7" EMPTY TAPE REEL

MODEL
RK-675
179⁹⁵

\$9.00 MONTHLY




An extraordinary self-contained portable tape recorder with professional quality features. Records and plays back 4-track stereo and monophonic tapes at 2 speeds, 7½ and 3¾ ips. Records from any source—radios, FM tuners, Hi-Fi stereo amplifiers or "live" from the quality dynamic microphones supplied. Make sound-with-sound tapes . . . accompany yourself in a duet or add your voice to prerecorded music. The rugged tape mechanism features a heavy duty 4-pole capacitor-start motor. Gives smooth tape run low flutter and wow. Automatic shut-off of entire transport at end of tape . . . disengages controls to neutral position . . . prevents tape spillage. Easy-to-use push-buttons provide positive control of tape motion. Has separate interlocking record buttons. Magnificent tone is assured with 2 big 6x4" full tone speakers and side flaps for better stereo separation. Other features include digital tape counter, pause control for editing, 2 record level meters, and individual channel volume controls. Complete with luxurious simulated leather case, 2 dynamic microphones, cables and take-up reel. For 105-125V 60 cycles AC. Size: 16¼Wx7Hx12¼"D. Shpg. wt., 35 lbs. Imported.

99 N 1504WX Model RK-675 Net 179.95
28 N 0101 7" Reel of Lafayette Recording Tape Net 1.59

SPECIFICATIONS

Frequency Response, Record/Playback: 40-18,000 cps @ 7½ ips; 40-12,000 cps @ 3¾ ips. Amplifiers: 4 transistors, 6 tubes; 1 full-wave bridge rectifier. Audio Output: 3-watts per channel. Signal-to-Noise Ratio: —45 db. Interchannel Separation: 45 db or better; Wow & Flutter: 0.2% @ 7½ ips, 0.25% @ 3¾ ips. Bias & Erase: 80KC; Rewind Time: Less than 4 minutes for 1200 ft. of tape. Speed Accuracy: 98%. Controls: Power/Speed Selector; Individual Volume for each channel; Variable Tone Control; Separate Channel Record buttons with safety interlock, Self-holding pause lever; Rewind, Play, Fast Forward and stop buttons, Input Selector Switch (Mike, Radio, Mix), Output selector switch (Mono, Stereo, Mute). Counter: 3 digit; 2 Record Level Meters; Outputs: (4) 2 audio, 2 monitor; Inputs: (4) 2 Mike, 2 Phono/tuner.



CHECK THESE DELUXE PROFESSIONAL FEATURES

1. Tape Reels—Takes up to 7" Size
2. Heads—Separate Record/Play & Erase
3. Matched Full tone, Speakers
4. Automatic Tape Cut-off Switch
5. Input Selector Switch
6. Tape Position Indicator
7. Record Level Meters
8. Speed Selector/Power ON-OFF
9. Individual Volume Controls
10. Variable Tone Control
11. Separate Channel Record Buttons
12. Pause Control
13. 4 Push button Tape Motion Controls
14. On-Off Pilot Light
15. Mono-Stereo Out-Mute Switch

THE PROFESSIONAL LAFAYETTE Criterion 1000

4-TRACK STEREO SELF-CONTAINED TAPE RECORDER

featuring
**MAGNIFICENT
TEAK CABINETRY**



**2 DYNAMIC
MICROPHONES**


only

199⁵⁰

\$10 monthly

ENGINEERED TO RECORD FM STEREO

- Plays: 2 & 4-Track Stereophonic and 4-Track Monophonic Tapes
- Records: 4-Track Stereo and Mono
- Transistorized Stereo Preamplifiers
- Push Pull Power Amplifiers
- Sound With Sound
- Six Pushbutton Tape Motion Controls
- Automatic Shut-off Electrically and Mechanically Returns Recorder to Stop Position
- 3-Speeds: 7½, 3¾, 1½ ips



OPERATING FEATURES

- (A) Supply Reel up to 7" Size
- (B) Automatic Tape Stop Switch
- (C) Heads-Separate Record/Play & Erase
- (D) Tape Position Indicator
- (E) Power Switch-Speed Selector
- (F) Stereo-Mono-Mute Output Selector
- (G) Left Channel Volume Control & Tone Controls
- (H) Individual Channel Record Push-Buttons
- (I) Positive Stop Switch
- (J) Fast Forward, Play/Record, Fast Rewind Push Buttons
- (K) Instant Pause Control
- (L) Right Channel Tone & Volume Controls
- (M) Record Level Meters
- (N) Mike, Radio, M/R Mixer Input Selector

SPECIFICATIONS

Speeds: 1½, 3¾, 7½ ips. Frequency Response: ±3 db 50-15,000 cps @ 7½ ips, ±3 db 50-10,000 cps @ 3¾ ips, ±3 db 55-5,000 cps @ 1½ ips. Motor: 4-pole capacitor-start, Signal-to-Noise ratio: 50 db. Wow & Flutter: 0.2% @ 7½ ips. Rewind Time: 1200 ft. reel, 130 sec. Inputs: 2 microphone, 2 high level. Speakers: 2 6x4" oval; Two external speaker outputs. Power output: 6 watts per channel. Bias & Erase: 80 kc. Reel Size: 7" maximum.

Another outstanding achievement by Lafayette engineers in tape recorder design. The Criterion 1000 records and plays 4-track stereophonic tapes with "ultra" realism through its own transistorized, preamplifiers, push-pull power amplifiers and matched self-contained high fidelity speakers. Speaker wing panels deflect the sound into the room with the proper stereo separation. Three finger-tip selected speeds of 7½, 3¾ and 1½ give you up to 8 hours playing time on a single 7" reel. Positive pushbutton controls coupled to a husky, heavy duty, low slip capacitor-start motor enable smooth tape control. Has 4 inputs for microphones and radio connections plus mike/radio mixer control and two output jacks for external speakers. Cabinet is genuine teakwood—a modern classic! With 2 dynamic microphones, cables and 7" take up reel. For 117 volts, 60 cycles AC. 17¼Wx7¼Hx12¾"D. Shpg. wt., 43½ lbs. Imported

99 N 1501WX Criterion 1000 Stereo Recorder Net 199.50
28 N 0101 7" reel of 1200 ft. Lafayette recording tape Net 1.59

Solid State Portable Tape Recorders

NEW! DELUXE SOLID-STATE BATTERY AND AC OPERATED PUSHBUTTON TAPE RECORDER



79⁹⁵
\$5 Monthly

- Takes 5" reels — up to 1200 ft. of tape
- 2 Switch-selected Speeds — 1 7/8 and 3 3/4 ips
- Dual track — records up to 4 1/2 hours
- Record level & Battery strength meter
- Remote control start-stop mike
- Easy-to-use keyboard controls

Includes Remote Control Mike 5" reel of tape, take-up reel batteries, earphone, AC line cord, accessory case

A deluxe solid-state (all-transistor) portable tape recorder that operates on 4 low-cost 1 1/2V "D" batteries or AC house current. Completely portable . . . records or plays back anywhere — up to 4 1/2 hours on a 5" reel containing 1200 ft. of tape (both tracks) at 1 7/8 ips. 2 switch-selected speeds — 1 7/8 ips for voice recording, 3 3/4 ips for quality music recording. Deluxe dynamic microphone has switch that lets you start or stop reels remotely — ideal for dictating, etc. Easy-to-use keyboard controls for stop, rewind, forward and fast-forward functions. Equipped with a recording level/battery strength meter, record-safety button and AC-On indicator light. Has inputs for recording from

mike, or directly from high level sources — radio, TV, phono. Push-pull audio circuit and 4x2 1/2" built-in speaker for superior tonal quality. Also has output for earphone or external speaker. Uses built-in power transformer when operated on 110-120V 60 cycles AC. Rugged die-cast aluminum-zinc frame with high-impact plastic case. Size: 12x10 3/8x3 3/8". Supplied with 5" reel of tape, take-up reel, remote control mike, batteries, earphone, AC line cord, instructions, and zippered case for mike & accessories. Imported. Shpg. wt., 14 lbs.
27 N 1007WX
Extra batteries (uses 4)
32 N 4804

Net 79.95
Net ea. .13

6 TRANSISTOR PUSHBUTTON TAPE RECORDER



39⁹⁵
\$5 Monthly


- 6 Transistors: 1 Diode, 1 Thermistor
- 3 3/4 & 1 7/8 ips • Up to One Hour Recording Time Without Turning Tape Over
- Takes 3 1/4" Reels

6-transistor tape recorder features capstan drive with governed motor for accurate speed. 3 3/4 or 1 7/8 ips, allows recording time of up to two hours on 600 foot tape — one hour without stopping to turn tape over. Equipped with record level meter and battery strength indicator. Features sensitive dynamic microphone with remote control switch for dictation and speech practicing purposes. Records directly from radio, TV, phono, telephone. Specially designed "dashboard type" push-buttons give speedy operation. Complete with remote-control dynamic microphone, magnetic earphone, tape, empty reel and batteries. Size: 9 3/8x8 3/8x2 1/2"H. 27 N 1001L wt., 5 lbs. Imported. Net 39.95
AC Power Pack for above recorder
27 N 1002
Extra "C" Cell Battery (4 req.)
32 N 4801

Net 12.95
Net ea. .13

MINIATURE SOLID STATE PORTABLE TAPE RECORDER

TAKE IT ANYWHERE!
Outstanding
For Dictation



Only
17⁹⁵

- Compact—only 3 3/8x7 1/2x2 1/2"H
- Makes Direct Telephone Recordings
- Complete with Lapel Microphone, Earphone, Batteries and 3" Take-up Reel

Take this recorder anywhere! Offers reliable solid-state circuitry, compact size, and low cost battery operation to make it a true personal portable. It is ideal for oral note taking, homework, dictation and all-around family fun. Can record and play back in any position — even with the lid closed. Positive action controls (Rev., Stop, Play, Rec.) and Volume are up Front where you can operate them easily. Crystal mike has lapel clip for inconspicuous use. Motor is powered by 2 "C" type cells; amplifier by one 9-volt battery. Handy telephone pickup makes possible direct telephone recording for your permanent records. Housed in rugged metal case with carrying handle. Total recording time approximately 24 minutes. Complete with built-in speaker, earphone for personal listening, batteries and 3" empty take-up reel. Shpg. wt., 3 lbs. Imported.
27 N 1005L
32 N 4801 Extra "C" cell battery (2 required) Net 17.95
99 N 6021 Extra 9-volt battery (1 required) Net .21

5 TRANSISTOR PORTABLE PUSHBUTTON TAPE RECORDER

Features Remote
Control Microphone



19⁹⁵

Includes:
Mike, Batteries
and 3" Tape
Reel

- Small, Compact—weighs only 2 lbs.
- Uses 2-Track System—Doubles Recording Time
- Battery Operated
- Takes 3" Reels

A deluxe, miniature 2-track tape recorder measuring only 7 1/2x6 1/4x 2 1/2" and weighing a mere 2 lbs. Records and plays up to 20 minutes (both tracks) on a 300 ft. 3" reel. Special switch on the sensitive microphone lets you stop or start reels remotely — makes the unit ideal for dictating purposes. Has simple push-button operation for Record, Play, Rewind and Stop functions. Circuit is completely transistorized and has push-pull audio output with built-in speaker . . . offers clear, crisp sound reproduction. Special earphone receptacle for monitoring during recording or for private listening during playback. Special design allows recorder to be operated with cover closed . . . lets you record or play with the unit in any position — even while walking! Housed in a high-impact plastic cabinet in black and gray with silver trim, push-buttons, volume control, carrying handle. Supplied complete with remote control microphone, 3" reel of tape, empty reel, batteries. Imported.
27 N 1006L Shpg. wt., 3 lbs. Net 19.95
32 N 4801 Extra "C" cell battery (3 required) Net ea. .13
99 N 6021 Extra 9-Volt Battery Net .21

Deluxe Professional Quality Tape Recorders

NEW CONCORD 994 DELUXE TRANSISTORIZED STEREO AUTOMATIC TAPE RECORDER



For:
Automatic Stereo Recording
Automatic Continuous Playback

- Automatic Programming
- Automatic Threading
- Automatic Reverse
- Automatic Sound-On-Sound

349⁵⁰

\$17 Monthly

A completely automatic 4-track stereo recorder with a "magnetic memory." Automatic Features include: **AUTOMATIC STEREO RECORDING** — Record continuously up to 12 hours on a single reel of tape without touching the recorder. **AUTOMATIC CONTINUOUS PLAYBACK** — Plays continuously, 1 hour — 2 hours — or all day. Plays both sides of pre-recorded stereo tapes without changing reels. **AUTOMATIC PROGRAMMING** — Four modes of operation — automatic reverse, single play, continuous play, or manual operation. **AUTOMATIC THREADING**, Lighted indicators show tape direction at a glance. Also features automatic sound-on-sound, three speeds — 7½, 3¾, and 1½ ips, automatically equalized. Push-button motor functions. 15-watt solid-state stereo amplifier drives four speakers in separate, removable enclosures. Four tape heads. Frequency response: 40-16,000 cps ±2db @ 7½ ips, 40-12,000 cps ±3db @ 3¾ ips, 50-10,000 cps ±3db @ 1½ ips. Signal-to-noise ratio 55db. Wow and flutter: .15% @ 7½ ips. Complete with two dynamic microphones, hi-fi outputs. For 110 volts, 60 cycles AC. Shpg. wt., 50 lbs. Imported

27 N 3503WX

Net 349.50

DELUXE CONCERTONE MODEL 801 STEREO TAPE RECORDER



featuring

- 6 Heads
- Automatic Reversing for Playback or Recording
- Solid State Circuitry
- 3 Motors
- Push Button Controls

397⁴⁶

\$19 monthly

The Concertone 801 is an advanced stereo recorder. Six heads—two play, two record, two erase. This ¼ track stereo Bi-Directional recorder allows continuous playback or recording in either direction without reel turnover thus permitting an entire evening of uninterrupted music. **SPECIFICATIONS:** Two Speeds: 3¾ and 7½ ips. Frequency Response: 30-18,000 cps @ 7½ ips and 40-12,000 cps @ 3¾ ips. Wow and Flutter: Less than .2% at 7½ ips. Signal to Noise Ratio: 50 db. Three Motors. Rewind time: 1200 feet in 45 sec. Output level 1.0 volt. Completely self contained portable with integrated speakers, monitor amplifiers, dynamic microphones, and handsome two-tone carrying case. Size 19¼Hx14¼Wx 8¾"D. Shpg. wt., 49 lbs. Imported

27 N 1405WX

Net 397.46

MODEL 802—Stereophonic Tape Deck version of famous Model 801. Shpg. wt., 30 lbs. Imported

27 N 1406WX

Net 334.36

FAMOUS Wollensak T-524 4-SPEED TAPE RECORDER



ONLY **99⁰⁰**

\$5.00 MONTHLY

- 4-Speeds; 7½, 3¾, 1½, ¾ ips
- Push-button Operation
- Instant Pause Control
- Tone Control
- Neon Record Level Indicators
- Records/Plays—2-Track Mono

A terrific performer, ideal for students. Slowest speed (¾ ips) is perfect for dictation, homework, lectures etc. Records 2 track mono. Big 5x7" speaker gives true voice and music reproduction. Other features include, easy-to-use push button tape drive control, instant pause and tone controls, external speaker outputs, 2 record indicators (normal and distort) and safety record interlock to prevent accidental tape erasure. Frequency response: 80-12,000 cps; signal-to-noise ratio, 45 db; wow and flutter, less than .3% at 7½ ips; 3 watts audio output at 5% distortion. Handsome, lightweight black and grey vinyl clad steel case 7x13x10". Complete with mike, 7" reel of recording tape. 7" take-up reel and power cord. For 110-120 V, 60 cycle AC. Shpg. wt., 28 lbs.

27 N 7003WX \$5.00 monthly Net 99.00

32 Lafayette Cat. No. 653

NORELCO DELUXE CARRY-CORDER™ "150"



COMPLETE WITH:
Mike,
Deluxe Carrying Case and Mike Pouch,
4 Tape Cartridges and Patch cord

Only **119⁵⁰**

\$6 Monthly

- All Transistor—Cordless
- Uses Tape Cartridges
- Compact—Take It Anywhere

A marvel of tape recorder engineering. Extremely lightweight—weighs less than 3 lbs. Including batteries. Carry it everywhere... ideal for students, salesman, busy executives. Records voice and music on 2 tracks at 1½ ips with perfect fidelity. Fully transistorized for instant record/playback. No warmup. Easy to use. Single master control starts, stops, winds and rewinds tape. Microphone has remote switch for start-stop. 300 ft. triple-play tape cartridge provides up to 1 hour play/record time, can be removed at any time—no need to wind or rewind tape. Uses 5 "C" size flashlight cells. Has recording level/battery life meter. Can be used with external amplifier, headphones. Complete with mike, patch cord, vinyl carrying case, 4 tape cartridges and separate microphone pouch. Size: 7¾x4½x2¼". Shpg. wt., 4 lbs. Imported.

27 N 4804XL Model 150 Net 119.50

Extra Blank Tape Cartridge Net 3.65

27 N 4805 Net 3.65

"C" Type Battery, 5 required

32 N 4801 Net ea. .13

CONCORD 330 VOICE OPERATED PORTABLE RECORDER



only **149⁵⁰**

\$8.00 monthly

- Automatic Voice Operation — Sound Starts It — Sound Stops It
- Automatic Slide Advance for Unattended Slide Projector Operation
- Automatic Movie Sync—Synchronizes Sound with Movie Projector
- Automatic Tape Threading
- Fully Transistorized—Runs on Flashlight Batteries

The New Concord Model 330 is a fully automatic voice operated portable tape recorder incorporating many deluxe features. Automatic-voice operation provides almost unlimited recording applications — the 330 starts recording whenever a sound is present and stops during silent periods. Frequency response is 50 to 10,000 cps for excellent musical reproduction. Takes up to 5 inch reels and operates at both 1½ and 3¾ ips. Complete with dynamic microphone, earphone, empty reel, sensing tape, and slide projector plug. Uses 6 size "D" cells. Dimensions: 12Wx8¾Dx3¾"H. Shpg. wt., 6 lbs. 27 N 3502WX Model 330 Imp. Net 149.50

27 N 3501 AC Adaptor for 330 Net 12.95

"D" Size Batteries for 330 (6 req.)

32 N 4804 Net .13

New York — 45th St. 71 West 45 St.

LAFAYETTE RECORDING TAPES

LAFAYETTE'S FAMOUS MONEY-BACK GUARANTEE

YOU BE THE JUDGE!



Lafayette's tape is made by outstanding nationally known manufacturers. It is first quality, splice free, red oxide coated, with full frequency response, uniform output and no "drop-outs." Resistant to moisture, heat, cold and abrasion.

We guarantee absolute satisfaction or your money back. If for any reason you are dissatisfied, return the tape at once and we will refund your money less only transportation charges. You are the sole judge.

LAFAYETTE ACETATE BASE RECORDING TAPE

Acetate base magnetic recording tape with uniform standard red oxide coating provides wide range high fidelity response over the audio spectrum. Features precise true reproduction, low abrasion and uniform output. In 1 mil and 1 1/2 mil thickness.

Stock No.	Feet	Reel	Mils	Wt. Lbs.	Net Per Reel		
					1-4	5-24	25 Up
28 N 0102	600	5"	1 1/2	1/2	.99	.90	.85
28 N 0103	900	5"	1	3/4	1.20	1.10	.99
28 N 0101	1200	7"	1 1/2	1	1.59	1.49	1.35
28 N 0104	1800	7"	1	1 1/4	1.98	1.88	1.79

LAFAYETTE MYLAR BASE RECORDING TAPE

Mylar base is especially strong, durable and break resistant, and is virtually impervious to heat, cold or humidity. All in clear plastic reels, individually boxed.

Stock No.	Feet	Reel	Mils	Wt. Lbs.	Net Per Reel		
					1-4	5-24	25 Up
28 N 0105	1200	5"	1/2	3/4	1.75	1.58	1.42
28 N 0106	1800	7"	1	1 1/4	2.49	2.25	2.13
28 N 0107	2400	7"	1/2	1 1/4	3.10	2.79	2.51

LAFAYETTE TENSILIZED MYLAR TAPES

These tapes are of the same high quality as the standard acetate and mylar Lafayette tapes with the added advantages of the tensilized mylar base. Super-strong mylar is prestretched and is highly resistant to breakage, moisture, heat, cold, and humidity. Highly polished, splice-free, quiet, non-abrasive finish. Smooth output throughout the entire audio spectrum. Tensilized mylar gives you the most permanent type of base and is therefore ideal for your most treasured recordings. All are 1/2 mil, thus permitting the maximum amount of footage per reel. Individually boxed.

Stock No.	Feet	Reel Size	Wt. Lbs.	Net Per Reel		
				1-4	5-24	25-Up
28 N 0109	300	3"	1/2	.69	.63	.59
28 N 0110	600	3 1/4"	1	1.00	.90	.80
28 N 0111	1200	5"	1/2	2.25	2.03	1.83
28 N 0108	2400	7"	1/2	3.69	3.39	3.05



4-TRACK STEREO CONVERSION KITS



Converts head mechanisms to play 2 and 4-track stereo tapes. Shpg. wt., 12 oz.

FOR WOLLENSAK AND REVERE

TYPE WR-35. Four-track R/P head kit for all 2-track stereo recorders. Includes head shifter.

28 N 5754 Net 25.50

TYPE WR-40. Four-track erase/record/playback head kit for all monaural units. With head shifter.

28 N 5755 Net 32.50

TYPE WR-60. Four-track mono or stereo erase-record/playback head kit for all mono and 2-track stereo recorders. With 3 position head shifter and cable assembly.

28 N 5756 Net 49.50

FOR WEBCOR

Type W-6. Four-track stereo R/P head and bracket assembly with shifter for 2800, 2900 and 2000 series recorders (except 2020).

REPLACEMENTS FOR SHURE "COMBO" HEADS



Features 2 separately cased heads in a single housing. Shpg. wt., 12 oz.

Type RPE-23. Replaces Shure 815, TR5, TR5B, TR5B-J, TR5D, TR5H.

28 N 5742 Net 15.60

Type RPE-24. Replaces Shure 315H, TR5C, TR5E, TR5L, TR5Z-1, TR5Z-2J.

28 N 5770 Net 15.60

KINEMATIX "VOICE-MATIC" VOICE ACTUATED CONTROLS

- Converts your Battery operated Tape Recorder to a Voice-Actuated Tape Recorder
- Sound Starts your Tape Recorder—Absence of Sound stops your tape Recorder
- No tools needed—no soldering required

As low as **19⁹⁵**



Model KX5000

Model KX4000—A new concept in a tape recording accessory. Contact board of KX4000 is inserted between contacts and battery of your present battery operated tape recorder. No soldering required—no tools needed. Now your tape recorder will start whenever a sound is present. The recorder will stop when sound source stops. Has .5 amp switching capacity. Complete with sensitivity control which permits you to operate a recorder from as far away as 15 feet. Requires 2 standard 9 volt batteries (not supplied with KX4000). Dim. 3 1/2"x1"x2 1/4". Shpg. wt., 1 lb.

28 N 3101L Net 19.95

Model KX5000—Deluxe Version of Model KX4000—Switching capacity—2 amp. 2 controls—Sensitivity control and adjustable Pause control which keeps recorder from turning off immediately during pauses between sentences. Includes input jack for external mike—and accessory input jack for use with various household appliances enabling you to turn the appliances on and off.


28 N 3102L Net 29.95
Standard 9 Volt battery for KX4000 and KX5000. 2 req.

99 N 6021 Net .21
Miniature phone plug—fits input jack of Model KX4000 and KX5000.

99 N 6210 Net .17


Tape Recording Accessories

MAGNETIC TAPE SPLICER



An excellent accessory that splices tapes accurately and eliminates joint noise. Both ends cut simultaneously. Nicked brass finish. Shpg. wt., 1 lb.
28 N 3910 Net 1.47

ROBINS® SPLICER



ROBINS TS-8D GIBSON GIRL® "STEREO 4" TAPE SPLICERS produce precise splicing of 4 track tapes without loss of program material on the outside tracks. Works equally well on single and 2 track tapes. Unit has blade centering adjustment for lifetime accuracy, and replaceable cartridge. "See thru" windows indicating "Cut" and "Trim" positions for easy operation. Tape guide and fingers secure tape during splicing. Easy threading integral tape dispenser with roll of 1/2"x100" splicing tape. Safety lock protects blades when not in use. With Instructions. Wt., 1 lb.
28 N 6009 Net 7.65

COLOR-CODED TAPE SPLICING KIT



Everything you need for fast, professional tape editing and repairing. Easy-to-use gold anodized aluminum splicing block has special slide-out plastic storage compartment. Complete with blade and full assortment of color coded Quik Splice Mylar splicing and editing strips—will not shrink or become brittle with age. Shpg. wt., 8 oz.
28 N 3601 Net 1.49

TWIST-LOCK STYRENE CANS




• Buy the set—save and GET THE CHEST FREE!

12 dust-free, moisture-proof unbreakable styrene tape cans in storage chest. Can has foolproof twist lock feature and is ribbed for convenient stacking. Center locking stud prevents reel movement on all 7" reels and most 3" and 5" reels. Shpg. wt., 6 lbs.
28 N 6510 Net 4.75

28 N 6511 Lots of 6 ea. .40 Single ea. .45

34 Lafayette Cat. No. 653

REEL LOCKS



45¢
Set of Two

Holds tape recorder reel in place by locking spindle to reel. Especially useful if recorder is in vertical position. Will not interfere with normal operation of reels. Easily removable. Shpg. wt., 6 oz. Imported.
99 N 1519 Set of two Net .45



23¢
IN LOTS OF 6
CLEAR PLASTIC REELS

Individually boxed plastic reels for recording tape. Av. shpg. wt., 4 oz. singly.

28 N 2903 3/4" reel lots of 6, Ea. .23
Singly, Ea. .26
28 N 2904 5" reel lots of 6, Ea. .26
Singly, Ea. .29
28 N 2905 7" reel lots of 6, Ea. .38
Singly, Ea. .45

FILMAGIC TAPE MAINTENANCE KIT



Adds life and performance to tape and tape recorders. The Kit contains all the elements needed for cleaning and conditioning both tapes and critical recorder parts. Consists of: Either Flange or Suction cup type Pylon with sleeve; Tape conditioner fluid; and head condenser fluid. Can be used to clean capstans, rubber idler rollers also. Shpg. wt., 3 1/2 oz.

Kit with suction cup Pylon. Net 3.45
28 N 4005
Kit with flange-type Pylon. Net 3.45
28 N 4006

REPLACEMENT PARTS

28 N 4007 2 oz. Head Cleaner Net .98
28 N 4008 2 oz. Tape Conditioner Net .98
28 N 4009 Pkg. of 6 sleeves Net .75
28 N 4010 Wick-Tip Applicator Net .39

METAL TAPE STORAGE CHEST



2.99

STANDARD CASE: Sturdy all steel carrying case. Holds 12 7" or 5" reels and cans. Twin snap locks. Platinum grey hammerloid finish. Metal separators. Includes index cards. Shpg. wt., 5 lbs.
28 N 1501 Net 2.99

TAPE ACCESSORY KITS WITH CARRYING CASE



As Low As 6.95

Each kit contains actual recording tape and is loaded with needed accessories. Packed in a beautiful, functional carrying case.

TK7—7" TAPE KIT. Contains: Two 3" reels, two 3 1/4" reels, two 5" reels, two 7" reels, Two reels Tape 1200'A, 1 Splicer, 1 Splicing Tape, 2 Leader Tapes, 1 Strobe Tape, 6 Tape Clips, 1 Book—"How To Make Better Tape Recordings." 1 Marking Pencil.
28 N 2901 7" Tape Kit. Shpg. wt., 6 lbs. Net 9.95

TK3—3" TAPE KIT. Contains: Three 3" reels, two 3 1/4" reels, one 3" reel tape, 1-3 1/4" reel Tape, 1 Splicer, 1 Splicing Tape, 2 Leader Tapes, 1 Strobe Tape, 6 Tape Clips, 1 Book "How To Make Better Tape Recordings." 1 Marking Pencil.
28 N 2902 3" Tape Kit. Shpg. wt., 3 1/2 lbs. Net 6.95

RECORDER PATCH CORD



67¢

Ideal For Making Connections From Radio, Phono or TV To Tape Recorder

Handy 6 ft. lead has insulated alligator clips at one end and RCA phono plug at the other. Supplied with shielded phono plug adapter to adapt the RCA phono plug to standard phono plug if necessary. Attach alligator clips to speaker terminals and simply plug other end into tape recorder. Ideal for recording from Radio, Phono or TV. Shpg. wt., 8 oz. Imported.
99 N 1517 Net .67



7" TAPE CHEST 95¢

Durable chipboard storage cases covered in simulated leather. Holds 5 7" reels, in separate compartments. Size: 8x7x 4 1/2". Shpg. wt., 1/2 lb.
28 N 6512 Net .95



METAL STORAGE CANS 18¢ lots of 6

Cans are ribbed for easy storage. Precision fit. Finished in grey. Av. shpg. wt., 8 ozs.
28 N 6305 3" Can lots of 6, Ea. .18
Singly, Ea. .20
28 N 6306 5" Can lots of 6, Ea. .27
Singly, Ea. .30
28 N 6307 7" Can lots of 6, Ea. .36
Singly, Ea. .39

LAFAYETTE Recording Accessories


LAFAYETTE BULK TAPE ERASER AND DEMAGNETIZERS

PROFESSIONAL MODEL

- Completely Erases Tape
- Two Erasing Coils
- Erases up to 1" Tapes
- Erases 1/4" Tapes in One Operation—No Reversing
- For 3", 5", 7" or 10 1/2" Reels

12⁵⁰ Standard Model

18⁹⁵ Professional Model



A carefully designed and precisely manufactured tape "degausser" for complete erasing of tapes. Just place the tape reel on spindle of demagnetizer, slowly rotate 2 or 3 turns, take off, and that's all. Reduce tape hiss to the level of new "virgin" tape. Two completely separate coils are used for doubly-effective erasures, even of large, 10 1/2" reels. Will erase 1" wide tape. An extra powerful unit for heavy-duty use—draws over 9 amperes. Can be used to demagnetize tape, magnetically stripped film, plus tools and watches. Has a heavy, custom finished case, a rugged non-magnetic top, heavy duty on-off switch and power cord. Has built-in fuse. Pilot light prevents accidentally leaving it turned on. Size 6 1/4 x 7 7/8 x 3 1/2". 105-125V, 60 cycle. Shpg. wt., 14 lbs. Imported.

99 N 1516 Professional Model

Net 18.95

STANDARD MODEL

Similar to professional model for all size reels but handles only standard size 1/4" tapes or smaller and reel must be turned over once. Has separate spindle positions for 10 1/2" and 3, 5, and 7" reels; non-magnetic bakelite plate for reel rest. One powerful coil consumes 5 amps. Metal case 7 1/2 x 4 3/4 x 3 1/2". Shpg. wt., 9 lbs. Imported.

99 N 1518

Net 12.50

LAFAYETTE TAPE HEAD DEMAGNETIZERS

3⁹⁵ DELUXE MODEL WITH 3 REMOVABLE POLE PIECES

Has 3 complete sets of removable pole pieces: straight, 45° and 90° for quick easy use with any tape head. Removes magnetism that accumulates in every tape head insuring optimum signal-to-noise ratio. For 110 Volt 60 cycle. Shpg. wt., 1 lb.

24 N 0901


Net 3.95

2⁸⁸ ECONOMY MODEL

Features very strong field with a single probe. Its thin cross-sectional size allows it to be used on all heads. For 110V 60 cycle. Shpg. wt., 12 oz. Imported.

99 N 6198

Net 2.89



EDITALL TAPE EDITING KIT

All you need for a complete professional editing job. The cutting block is made of duraluminum precisely machined and polished (makes straight or diagonal cut). All accessories such as grease pencil, blades, splicing tape (66 ft. roll of 3/2") supplied. Comes with instruction booklet—in a smart metal case. Shpg. wt., 1 lb.

28 N 3005 EDITALL KIT

Net 8.82



TAPE CLEANER

149

Tape is impregnated with special formula cleaner. Simply run through like regular roll of tape. Entire job done in 2 minutes. Can be reused many times. 100' roll on 5" reel. Shpg. wt., 8 oz.

28 N 2001

Net 1.49

28 N 2002 3" Reel

Net .99

LAFAYETTE-Recording Heads

EACH SET CONTAINS 2 HEADS FOR RECORD-PLAYBACK AND ERASE

FOR MINIATURE TRANSISTORIZED TAPE RECORDERS

A two-piece set consisting of one record/playback and one erase tape head. Designed for use in dual track miniature tape recorder. Will replace the heads in most Japanese-built recorders. Record/playback head specifications: impedance: 5.5K at 1 KC; DC resistance; 1K ohm; reproduction level: -52 db (recording at +2 db); bias frequency: 35KC; bias current: 1ma; voice current: 0.03ma; response: 100-7000 cps ±5 db; S/N ratio: better than 45 db; bias system: AC & DC reproducer; gap: .0024 in. (.006mm); dimensions: approx. 1/2" x 3/4" H x 1/4" D. Erase head same dimensions. Total shpg. wt., 3 oz. Imported.

99 N 8194

Net 3.95

1/4 TRACK STEREO SET 7⁹⁵



A complete 2 piece set. Consists of one 1/4 track record-playback head and one erase head, both with mounting brackets. RECORD HEAD SPECS: Impedance, 3.3K @ 1 KC; DC resistance: 700 ohms; Sensitivity: -55db; Cross talk -45db; bias current 0.5MA; voice current: 37.5µA @ 1 KC; response: 100-12,000 cps.

Inductance 0.5H. CAP: .0002 in. ERASE HEAD: DC resistance .65 ohms; GAP: .0024 in; erase current .18A; bias freq.: 30-65KC; Erasure -60 db. Size: 1/4" H x 3/4" cent. to cent. hole mounting. Shpg. wt., 4 oz. Imported.

99 N 6195

Net 7.95

TELEPHONE PICKUP FOR RECORDING TELEPHONE CONVERSATIONS



195

Induction telephone pickup. Telephone conversations can now be picked up with no tapping of wires or special telephone circuits. Simply place the phone base, either cradle or upright type, on the pickup platform and connect the leads to the high impedance input of any medium gain audio amplifier, or directly to any tape, disc or wire recorder. Shpg. wt., 8 ozs.

28 N 0901

Net 1.95

TELEPHONE PICKUP COIL



189

Designed to feed into the microphone input of either a tape recorder or any high gain amplifier. Easily attached to the telephone by suction rubber type attachment. The coil is electrostatically shielded to minimize hum pick-up. When properly positioned on telephone handset, the output of this device is more than adequate for a fully modulated tape recording. Complete with 5' shielded cable. Shpg. wt., 6 ozs.

99 N 6197 Imported

Net 1.89

SCRIBER ELECTRO TELEPHONE PICKUP



Electro Scriber telephone pickup will enable you to amplify, record and make a permanent record of any telephone conversation. Simply place phone base on phono Scriber and plug Scriber into amplifier or tape recorder input. Amplifies cleanly. Shpg. wt., 1 lb.

For standard cradle phone.

28 N 2501

Net 7.35

For push-button phone

28 N 2502

Net 8.53



LAFAYETTE RECORD-PLAYBACK & ERASE HEADS



445

Recording head: 4K ohm impedance @ 1000 cps; recording current, 20 microamps ± 20%; bias current 500 microamps; bias frequency, 45 to 50 KC; Playback output. -48DB +2 db; Response to 10KC ± 3db. Erase head: Erasing current 150 milliamps; Impedance, 30 ohms ± 25% @ 10KC, DC resistance 0.5 ohms ± 20%. Size 3/4" H x 1/4" H x 3/4" D. Mounting flange, hole-to-hole, 1 1/4". Shpg. wt., 5 oz. Imported.

99 N 6196

Net 4.45

FISHER X-101-C 60 Watt Stereo Amplifier



A Deluxe 60 Watt
Stereophonic Master
Audio Control -
Amplifier at only

139⁵⁰

\$7 monthly

OUTSTANDING FEATURES

- 60 Watts Power Output
- Beautiful Styling
- Direct Connection of Center Channel or Extension Speaker

This deluxe 60 watt Stereophonic Master Audio Control Amplifier features the exclusive "New Look" by Fisher, an elegantly styled, functional, operational, panel. Only the Program Selector, Mode Selector and Volume control are in view. The other infrequently used controls are hidden behind a pull-down panel. Offers 30 Watts of music power output per channel, center channel, output, 14 inputs (2 phonos), output selector switch, front panel jack, loudness control, jack for "SpaceXpander." Exclusive Fisher Direct-Tape-Monitor, 10 tubes, 2 silicon rectifiers. Response 20-20,000 cps ± 1 db. Hum and noise 88 db below rated output. Harmonic distortion .5% at rated output. 1% intermodulation @ rated power. Size 15 $\frac{1}{2}$ Wx4 $\frac{1}{4}$ Hx12 $\frac{1}{2}$ "D. Less cabinet. Shpg. wt., 28 lbs.

21 N 3603WX \$7 monthly Net 139.50
 21 N 3609W MC-2 Metal Cabinet for X-101-C. Shpg. wt., 9 lbs. Net 14.36
 21 N 3610W Walnut Cabinet for X-101-C. Shpg. wt., 7 lbs. Net 22.46

60 WATT STEREO-PHONO SYSTEMS FEATURING FISHER X-101-C

SHELF SYSTEMS—As Low As 206.50

X-101-C (less case)

GARRARD 50

SLENDERETTE III

CHOICE OF STEREO CARTRIDGE

Pickering V15/AT-1 Empire 880 Shure M7/N21D

OPTIONAL COMPONENTS

Garrard Model AT60

MODEL SK270 DECORETTE II

CUSTOM SYSTEMS—as low as 232.50

X-101-C (less case)

SK58

CHOICE OF STEREO CARTRIDGE

Pickering V15/AT-1 Empire 880 Shure M7/N21D

Garrard Model AT60

OPTIONAL COMPONENTS

GARRARD A70

2 ELIPTOFLEX

System I—A moderately priced 60 watt Stereo-Phono system enhanced by the elegant styling of the Fisher X-101-C 60 watt stereo amplifier. The other fine components which complete this system are: Garrard Model 50 4-speed automatic turntable with oil walnut base, choice of Pickering V-15/AT-1, Shure M7/N21-D, or Empire 880 stereo cartridge, and a pair of Lafayette Slenderette III slim-type, 2-speaker—2-way systems with oil coat finish. wt., 55 lbs.

21 N 9634CWX \$10 monthly Net 206.50

System II—Same as above except with Garrard AT60 4-speed automatic turntable in place of Garrard 50. Shpg. wt., 57 lbs.

21 N 9635CWX \$11 monthly Net 219.50

System III—Same as 21 N 9634CWX except with a pair of Lafayette Decorette II, 5-speaker—3-way systems with oil walnut finish in place of Lafayette Slenderette III speaker system. Shpg. wt., 63 lbs.

21 N 9636CWX \$13.50 monthly Net 286.50

System IV—Same as 21 N 9636CWX except with Garrard AT60, 4-speed, automatic turntable in place of Garrard 50. Shpg. wt., 64 lbs.

21 N 9637CWX \$15 monthly Net 299.50

System I—A superb custom 60 watt stereophonic system featuring the Fisher X-101-C 60 watt stereo amplifier, Garrard Model AT60 4-speed automatic turntable with oil walnut base, choice of Pickering V-15/AT-1, Shure M7/N21-D, or Empire 880 stereo cartridge, and lastly, a pair of world-famous Lafayette SK-58 12" coaxial speakers with 1 $\frac{1}{4}$ lb. magnet. Shpg. wt., 63 lbs.

21 N 9638CWX \$11.50 monthly Net 232.50

System II—Same as above except with deluxe Garrard type A70 4-speed automatic turntable in place of Garrard AT60. Shpg. wt., 70 lbs.

21 N 9639CWX \$12.50 monthly Net 252.50

System III—Same as 21 N 9638CWX but with SK-58 speakers mounted in a pair of patented Lafayette Eliptoflex enclosures with oil walnut finish. Shpg. wt., 111 lbs.

21 N 9640CWX \$15 monthly Net 292.50

System IV—Same as 21 N 9640CWX except with deluxe Garrard type A70 4-speed automatic turntable in place of Garrard AT60. Shpg. wt., 118 lbs.


21 N 9641CWX \$17 monthly Net 312.50

FISHER 500B 65 Watt FM Stereo Receiver

Lafayette Offers This Famous
FM Stereo Receiver At Only

249⁵⁰

Check These Outstanding Features
and Technical Specifications.



This magnificent FM Stereo Receiver has complete facilities for handling every possible stereo and monophonic program source through its stereophonic master control center, powerful 65 watt stereo amplifier, and super sensitive FM Stereo Multiplex Tuner. Features Stereo Beam, an exclusive Fisher invention that tells you instantly whether or not an FM Station is broadcasting in stereo multiplex. Completely eliminates the "try and find" stereo multiplex broadcast problem. A switchable filter reduces hiss and background noise on stereo programs without affecting the frequency response. SPECIFICATIONS: Amplifier distortion less than 0.5%. Frequency response 25-25,000 cps \pm 1.5 db; FM sensitivity 0.7 μ v into 72 ohm load; IHF sensitivity 2.2 μ v. S/N & hum 70 db. IF bandwidth 190 Kc; channel selectivity 52 db; FM response 30-15,000 cps; Tubes: 4-ECC85, 6-6AU6, 4-12AX7, 2-7591, 2-EMB4A, 1N-542, plus multiplex tubes. Size: 17 $\frac{1}{2}$ Wx5 $\frac{1}{4}$ Hx13 $\frac{1}{4}$ "D. Shpg. wt., 35 lbs.

21 N 3651WX

Walnut Wood Cabinet for Model 500B. Shpg. wt., 6 lbs.

21 N 3615W

Net 249.50

Net 22.45

• Exclusive Stereo Beam • Tuning Indicator • Linear Logging Scale • CONTROLS: MPX Filter, Station Selector, Dual Bass and Treble, Six-Position Selector (Tape Head, Phono, MPX Stereo, FM, Aux, Tape). Balance, Volume. SWITCHES: High Filter, Low Filter, Tape Monitor, Mono-Stereo, Channel Reverse, Loudness Contour • Low-level audio tube filaments heated by a separate DC supply • Magnificent architectural brass-finish control panel. FM TUNER Wide-band design. Sensitivity: 0.7 microvolts (72 ohms, 20 db. quieting), 2.2 microvolt (IHF Standard.) Four IF Stages. FM-Stereo separation, 35 db. AMPLIFIER: Power output, 65 Watts. Harmonic Distortion, 0.5%. Hum and Noise, —85 db. RIAA sensitivity, 3.3 mv. Aux. Sensitivity, 230 mv. Output Impedances: 4, 8 and 16 ohms.

65 Watt FM Stereo Phono Systems Featuring "FISHER 500B"

FAMOUS SELLING STEREO SYSTEM

Now everybody can enjoy the thrill of beautiful music reproduction at only a moderate cost with this outstanding FM Stereo Phono System. System includes: Fisher 500B 65 watt FM Stereo Receiver less case, Garrard Model 50 4 speed automatic Turntable with oil walnut wood base, choice of Pickering V15/AT-1, Empire 880 or Shure M7/N21D stereo cartridge, and lastly, 2 of Lafayette's best selling speaker systems—the Decorette V—featuring 5 specially engineered speakers designed to achieve optimum performance in a thin type enclosure only 4 $\frac{1}{2}$ inches in thickness.

21 N 9625CWX Shpg. wt., 82 lbs.

Net 324.50

Same system as above but with Garrard AT60 4 speed Automatic Turntable in place of Garrard Model 50. Shpg. wt., 85 lbs.

21 N 9626CWX

Net 339.50

CUSTOM STEREO SYSTEM

Now for the audio enthusiast who desires to mount his components in a custom cabinet—Lafayette offers this exciting FM Stereo System. System includes Fisher 500B 65 watt FM Stereo Receiver less case, Garrard Model AT60 4 speed automatic Turntable with oil walnut wood base, choice of Pickering V15/AT-1 Empire 880, or Shure M7/N21D stereo cartridge, and 2 famous Lafayette SK 210 3 way speakers with 2 $\frac{1}{4}$ lb. magnet.

21 N 9627CWX Shpg. wt., 78 lbs.

Net 358.50

Same system as above but with SK210 speakers mounted in patented Lafayette Eliptoflex Enclosures (oil wal. finish). Shpg. wt., 126 lbs.

21 N 9628CWX

Net 418.50

DELUXE STEREO SYSTEM

For the audio enthusiast who wants a deluxe FM Stereo-Phono System. System includes Fisher 500B-65 watt FM Stereo Receiver, Superb Garrard Model A70 4 speed automatic Turntable with oil walnut wood base, choice of new Pickering V15/AM-1 or Empire 880P Stereo cartridge and 2 of Lafayette's finest Bookshelf speaker systems—the Decorette III which features a 12" poly-foam woofer with 1 lb magnet, 6" mid range, and 3 $\frac{1}{2}$ super tweeter mounted in a specially engineered "Tuned" enclosure with Tube-Type Duct. Enclosures are finished in oil walnut.

21 N 9629CWX

Net 427.50

FAMOUS SELLING STEREO SYSTEM

AS LOW AS


324⁵⁰

CHOICE OF STEREO CARTRIDGE



GARRARD 50

DECOR-ETTE V



CUSTOM STEREO SYSTEM


AS LOW AS

358⁵⁰

CHOICE OF STEREO CARTRIDGE



GARRARD AT60



ELIPTOFLEX

DELUXE STEREO SYSTEM


only

427⁵⁰

CHOICE OF STEREO CARTRIDGE



GARRARD A70



Decorette III

NEW Improved

FISHER

Model X100 40 Watt Stereo Amplifier



LOOK AT OUR LOW, LOW, PRICE

99⁵⁰
\$5 monthly

OUTSTANDING FEATURES

- 40-Watt Power Output
- Full Control Flexibility
- Deluxe Styling

Combines famous Fisher quality and performance with a modest price. Offers 40-watts of clean, undistorted power. Features switched stereo headphone jack on front panel for private listening. Front panel controls include 4-position selector switch (Tape Head, Phono, Tuner, Aux); Stereo-Mono mode switch, separate bass and treble for each channel; balance; volume/AC off; tape monitor switch; scratch filter switch; speaker output switch and loudness

contour switch. Specifications: Frequency response: ± 1.5 db, 20-20,000 cps. IM distortion: 0.8%. Harmonic distortion: 0.5%. Sensitivity: 3.5 mv Phono; 2 mv, Tape Hd. Hum and Noise: — 80 db. Size: 4 $\frac{1}{2}$ "x15 $\frac{1}{2}$ "x17 $\frac{1}{2}$ ". Less optional wood case below. For 105-125V., 50-60 cycle AC. Shpg. wt., 29 lbs.
21 N 3653WX Net 99.50
Oil Walnut Wood Cabinet For X-100
21 N 3641W Net 22.48


40 Watt Stereo Phono System Featuring the Fisher X100

SHELF SYSTEMS as low as **164⁵⁰**

CUSTOM SYSTEMS as low as **184⁵⁰**



Slenderette III



Garrard 50




Garrard 50



SK-58

\$9 monthly



OPTIONAL COMPONENTS

X100 (less cabinet)




OPTIONAL COMPONENTS

X100 (less cabinet)




Garrard AT-60



2 Decar-ette V



Garrard AT-60



Eliptoflex

SYSTEM I—A complete 40 watt stereo phono system for the music lover at so little in price—System includes Fisher X100 40 watt stereo integrated amplifier, Garrard Model 50 4 speed automatic turntable with oil walnut wood base, choice of Pickering V15/AT-1 Empire 880, or Shure M7N21D Stereo cartridge, and lastly, a pair of famous Lafayette "Slenderette" III Slim 2-speaker 2 way speakers systems with oil walnut finish on 4 sides.

21 N 9511CWX Shpg. wt., 66 lbs. \$8 monthly Net 164.50

SYSTEM II—same as above except with Garrard Model AT60 automatic Turntable in place of Garrard Model 50.

21 N 9512CWX Shpg. wt., 68 lbs. \$9 monthly Net 179.50

SYSTEM III—same as 21 N 9511CWX except with a pair of Lafayette Decorette V speaker systems in place of Lafayette Slenderette III Speaker Systems.

21 N 9513CWX Shpg. wt., 78 lbs. \$10 monthly Net 194.50

SYSTEM IV—same as 21 N 9513CWX except with Garrard Model AT60 automatic Turntable in place of Garrard Model 50.

21 N 9514CWX Shpg. wt., 80 lbs. \$10 monthly Net 209.50

SYSTEM I—A popular priced 40 watt stereo phono system for custom installations features the Fisher X100 40 watt stereo integrated amplifier, Garrard Model 50 4 speed automatic turntable with oil walnut wood base, choice of Pickering V15/AT-1, Empire 880, or Shure M7N21D stereo cartridge, and lastly a pair of the world famous Lafayette SK58 12" coaxial speakers with 1 $\frac{1}{4}$ " magnets.

21 N 9515CWX Shpg. wt., 61 lbs. \$9 monthly Net 184.50

SYSTEM II—same as above except with Garrard Model AT60 automatic Turntable in place of Garrard Model 50.

21 N 9516CWX Shpg. wt., 63 lbs. \$10 monthly Net 199.50

SYSTEM III—same as 21 N 9515CWX but with SK58 speakers mounted in a pair of 2 famous Lafayette patented Eliptoflex Enclosures with Oil Walnut finish.

21 N 9517CWX Shpg. wt., 131 lbs. \$11.50 monthly Net 244.50

SYSTEM IV—same as 21 N 9516CWX but with SK58 speakers mounted in a pair of 2 famous Lafayette patented Eliptoflex Enclosures with Oil Walnut finish.

21 N 9518CWX Shpg. wt., 133 lbs. \$12.50 monthly Net 259.50

Deluxe 70-Watt FM Stereo Phono System

Featuring World Famous Scott 340B Receiver

Deluxe group of components, specially selected to provide stereo listening enjoyment. Consists of:

- Scott 340 B 70-Watt tuner/amplifier, less case.
- Garrard Model 50 4-Speed automatic stereo changer on an oiled walnut finished wood base.
- Choice of Pickering V-15/AT-1, Empire 880, Shure M7/N21-D stereo cartridge.
- 2 Superb Lafayette Decorette V Slim 5-Speaker System with four 6½" low resonance speakers and one 2½" cone type tweeter in enclosure of oil walnut veneers and walnut picture frame molding.

21 N 9502CWXM Shpg. wt. 90 lbs. Net 376.50

Scott 340B 70-Watt FM Stereo Receiver

Famous Scott 340B 70-Watt FM Stereo Receiver. Combines 70-watt power amplifier with FM Stereo Tuner on a single compact chassis. Response: ± 1 db 20-20,000 cps. Harmonic distortion: 0.8% at rated output. FM Sensitivity: 2.2 Mv. Separation: over 30 db. Stereo headset jack. 5½x16¼x16"0. Less Case Shpg. wt., 36 lbs. 21 N 6010WX Net 299.95

340B
DECORETTE V
Garrard Model 50


CHOICE OF STEREO CARTRIDGE

Pickering V-15/AT-1	Empire 880	Shure M7/N21D
---------------------	------------	---------------

Complete System
Only **376⁵⁰**
\$19 Monthly

Sherwood

Stereo Hi-Fi Components



NEW MODEL S-9500S 50-WATT SILICON SOLID STATE STEREO AMPLIFIER

179⁵⁰

\$9 Monthly


- 20 Silicon Transistors, 4 Silicon Rectifiers
- Transformerless Output
- Completely Non-Microphonic

A deluxe solid-state stereo amplifier for the discriminating music listener. Engineered into this compact unit are military-type silicon transistors with less heat sensitivity than low cost germanium types; transistor short-circuit protection and an extremely low harmonic distortion of ½% at rated output. Hefty 50-watts of music power. Also features phono input noise less than -70db with no microphonics or hum; professional taxandall tone controls, tape monitoring and tape head playback, stereo headphone, jack and 4-position selector switch. Response: 12-15,000 cps. Outputs 4, 8 and 16 ohms. Compact 14Wx4½Hx10"0. For 115-125V. 60 cycles AC. Shpg. wt., 20 lbs. Less Case.

21 N 6120WX Model S-9500S Net 179.50

Walnut tone Leatherette Case for Model S-9500S.

21 N 6113W Net 7.50



S-3000V FM STEREO TUNER

165⁰⁰

\$8 Monthly

- Stereo Indicator Light Gives Instant Identification of FM Stereo Broadcasts
- FM Interchannel Hush
- Wide-Band 3-MC Gated Beam Limiter and 1 MC Balanced Ratio Detector

This deluxe FM stereo tuner provides top quality FM and FM multiplex reception. Features zero-center tuning meter, stereo indicator light which shows when you are tuned to a stereo broadcast, interchannel hush to quiet noise between FM stations and expanded slide-rule tuning scale. Wide-band 3-MC gated beam limiter and 1 MC balanced ratio detector combine to create a capture ratio of 2.4 db. Sensitivity: 1.8 µv for 30 db quieting (IHFM). Response ± ½ db 20-20,000 cps. IM distortion: below ½% @ 100% mod. 11 tubes plus rectifier. Size: 14Wx4Hx10½"0. Less case. For 115-125V 60 cycles AC. Shpg. wt., 15 lbs.

21 N 6104WX Net 165.00

Walnut Tone Leatherette Case for Model S-3000 V.

21 N 6113W Net 7.50

50-WATT SHERWOOD STEREO PHONO SYSTEM

Featuring Model S9500S



Sherwood S9500S

CHOICE OF STEREO CARTRIDGE

Pickering V15 AT-1	Empire 880	Shure M7 N21D
--------------------	------------	---------------




Garrard AT-60

Complete System as low as

273⁹⁵

Optional Eliptoflex Enclosures



SK-58

A quality custom stereo system for the audio enthusiast featuring: Sherwood S9500S 50-watt Silicon Solid State Stereo amplifier (less case), Garrard Model AT60 4-speed automatic turntable with oiled wal. wood base; choice of Pickering V15/AT-1, Empire 880, or Shure M7/N210 stereo cartridge; and 2 famous Lafayette SK-58 12" Coaxial speakers. 21 N 9533WX Shpg. wt., 60 lbs. Net 273.95

Same system as above but with SK-58 speakers mounted in patented Lafayette Eliptoflex Enclosures (oiled wal. finish). Shpg. wt., 130 lbs.

21 N 9534WX Net 324.95

Famous Name Hi Fidelity Kits




62⁹⁵ **93⁴⁵**
KIT WIRED

DYNAKIT "PAS-3" STEREO PREAMPLIFIER KIT

Top-performing stereo preamp for use with high quality basic amplifiers. Includes two independent high gain, low noise preamplifier-control channels. All critical circuitry is pre-assembled on 2 printed circuit boards. Features "Dyna-Blend" for variable channel separation, DC heated tube filaments. Inputs: 3 stereo low level and 4 stereo high level. Frequency response: ± 0.5 db 10-40,000 cps. Distortion: less than .05%. Noise: less than 2 μ v. Gain, 60 db at 1000 cps on RIAA, 20 db on high level. For 110-120V., 50/60 cycles AC. Deluxe gold panel. Size: 13x8x4". Shpg. wt., 11 lbs.

21 N 2301WX PAS-3 Kit. \$5 Monthly Net 62.95
21 N 2302WX PAS-3A Wired. \$5 Monthly Net 93.45



89⁹⁵ **110⁴⁵**
KIT WIRED

DYNAKIT "STEREO 70" 70-WATT STEREO BASIC AMPLIFIER KIT

The stereo 70 provides outstanding reproduction, firm bass, and smooth natural highs. Delivers 35-watts per channel. Frequency response: ± 0.5 db from 10 cps to 40,000 cycles. IM distortion: less than 1% at 35 watts. Sensitivity 1.3 volts rms input for 35 watts output. Hum and Noise: better than 90 db below rated output. Output impedance: 4, 8 and 16 ohms. Nickel-finished chassis; vinyl-coated charcoal brown cover. For 110-120V 50/60 cycles AC. Size 9Wx6 1/2 Hx 13"D. Shpg. wt., 32 lbs.

21 N 2303WX Stereo 70/A Kit. \$5 Monthly Net 89.95
21 N 2304WX Stereo 70/A Wired. \$5 Monthly Net 110.45



98⁹⁵ **144⁴⁵**
KIT WIRED

DYNAKIT FM-3 FM STEREO TUNER KIT

A deluxe FM Stereo tuner designed for flawless FM mono or Multiplex reception. Offers high sensitivity, selectivity, and separation. Uses 4 IF limiters, wideband balance bridge discriminator, and time-switching multiplex system. Features Dyna's "stereomatic" tuning system that automatically switches to stereo and signals when multiplex is being received. Kit version offers rapid, foolproof assembly; unique circuit design permits simple, yet precise home alignment using the tuning eye alone. Sensitivity: 4uv. Frequency Response: 10-40,000 cps \pm 0.5db (before de-emphasis). Separation: 30 db. For 110-120v 50/60 cycles AC. With deluxe gold panel and brown vinyl coated cover. Size 13 1/2 W x 4 1/2 H x 8"D. Shpg. wt., 15 lbs.

21 N 2322WX FM-3 Kit. \$5 Monthly Net 98.95
21 N 2308WX FM-3 Wired. \$7.50 Monthly Net 144.45



124⁹⁵
KIT

SCOTT MODEL LT-110B WIDE BAND FM STEREO TUNER KIT

This popular FM stereo tuner kit boasts beautiful new styling, refined Scott performance, and extremely easy to follow building methods. Critical multiplex section and silverplated front end are wired and pre-tested at the factory. You need only align the tuner's wide-bandpass IF's and detector stage using the meter on the tuner itself. SCOTT's sonic monitor eliminates guesswork in identifying FM Stereo broadcasts. Features also include precision front panel tape output, stereo subchannel filter, stereo noise filter and precision tuning meter. Newly restyled to match all Scott amplifiers and amplifier kits. SPECIFICATIONS: Sensitivity: 2.2 microvolts. Frequency response: 30-15,000 cps. Signal-to-Noise Ratio 60 db. Separation: better than 30 db. Uses 8 tubes, 11 diodes plus rectifier. Size: 15Wx4 1/2 Hx 10"D. Shpg. wt., 20 lbs. Less case.

21 N 6036WX \$6.50 Monthly Net 124.95
Leatherette metal case for LT-110B. Shpg. wt., 2 lbs. Net 12.50
21 N 6009W Net 12.50
Wooden Walnut Case for LT-110B. Shpg. wt., 7 lbs. Net 22.50
21 N 6024W Net 22.50



79⁹⁵ **129⁹⁵**
KIT WIRED

EICO ST-40K 40-WATT STEREO INTEGRATED AMPLIFIER KIT

The ST-40 contains 2 twenty watt amplifiers and a complete stereophonic hi-fi control center on one chassis. FEATURES: Switched sets of stereo inputs including magnetic phono (2), tape head, preamplified tape, FM-AM stereo tuner, FM-FM Multiplex, and Auxiliary Balance Check Switch. Loudness/level switch. Bass and treble controls. Other controls include: Six position mode selector, tape monitor, scratch and rumble. Output 4, 8, and 16 ohm. Third channel speaker connection. Specifications: IM distortion—2% at 40 watts; Harmonic Distortion—1/2% at 40 watts; Frequency response— \pm 1/2 db. 20-20,000 cps. Shpg. wt., 27 lbs.

21 N 2506WX \$5 Monthly Net 79.95
21 N 2507WX Same as above, but wired \$6.50 Monthly Net 129.95



99⁹⁵ **149⁹⁵**
KIT WIRED

EICO ST-70K 70 WATT STEREO INTEGRATED AMPLIFIER KIT


Consists of 2-35 watt amplifiers and a complete stereophonic hi-fi control center on one chassis. Stereo inputs in switched sets including: 2 magnetic phono (one for turntable, one for changer); tape head, preamplified tape, FM-AM stereo tuner, FM-FM Multiplex, and Auxiliary. Controls: Level with balance check switch and loudness/level switch; bass, treble, six-position mode selector, blend, tape speed, tape monitor, scratch, and rumble. Output: 4, 8, and 16 ohm speaker. Third channel output available. Specifications: IM distortion—2% at 70-watts. Harmonic Distortion—1/2% at 70 watts. Frequency response— \pm 1/2% db. 20-20,000 cps. Shpg. wt., 35 lbs.

21 N 2508WX Model ST-70K \$5 Monthly Net 99.95
21 N 2509WX As above, but factory wired \$7.50 Monthly Net 149.95

Deluxe LAFAYETTE Speaker Systems

NEW LAFAYETTE "CRITERION XL-360" MULTI-DIMENSIONAL 5-SPEAKER SYSTEM

- Full 360° sound dispersion of all frequencies
- Sit anywhere . . . hear everything
- Glorious, true-to-life sound
- Four 6x3" Mid Range speakers with ultra-high frequency metallic cone tweeter
- One 8" high compliance woofer
- Slim upright design offers elegant styling
- Unlimited placement possibilities in the home




Four 6x3-inch speakers for reproduction above 3000 cycles. Main cone handles frequencies up to 8,000 cycles. Supplementary metallic cone handles frequencies from 6,000 to 20,000 cycles.

Acoustic "chamber" at rear of woofer filled (not just lined) with acoustic dampening material.

High compliance 8-inch woofer handles frequencies from 32 to 3,000 cycles.

Sound diffuser deflects low frequencies through "ports" in all four sides.



SPECIFICATIONS
 Max. Freq. Range: 32-20,000 cycles; Power Handling Capacity: 20 watts; Nominal Impedance: 8 ohms; Crossover: Electrical at 3000—Mechanical at 8000.

Enjoy the thrilling experience of multi-dimensional, "all-around" sound with the Criterion XL-360. This remarkable system offers full 360-degree sound dispersion over its entire range—from 32 cycles all the way up to 20,000 cycles. Gone is the "beaming" effect of conventional speaker systems—you get full-range sound from every side! And, reproduction has to be heard to be believed—the XL-360 delivers deep, powerful bass . . . clear, natural mid-range . . . smooth, unexaggerated highs. With two of these systems, stereo comes through with dramatic realism . . . virtually surrounds you with glorious, living sound—in any room and with almost any arrangement! And the superb sound quality is not all! The slender upright design offers unlimited placement possibilities in the home. Genuine walnut veneer with rich oiled finish assures fine furniture appearance—blends in with the most elegant decor. Truly, a perfect combination of slender, good looks and "big-system" sound. Dimensions: 32½"Hx11½"Dx11½"W. Shpg. wt., 30 lbs. Imported
 99 N 0124WX Criterion XL-360 Net 69.95


69⁹⁵

\$5 Monthly

LAFAYETTE "DECORETTE III" 3 SPEAKER 3-WAY SYSTEM

Designed by Lafayette engineers—built by the foremost English Hi-Fi Speaker manufacturer to Lafayette's rigid specifications.

- Newly Developed 12" Poly-Foam Woofer with 1 lb. magnet and A Free-Air Response of 35 cps.
- 6" Closed-Back Mid-Range Speaker
- 3½" Sealed Cone-Type "Super" Tweeter
- Specially Engineered "Tuned" Enclosure with Tube-Type Duct For Superior Bass Response
- Smooth Overall Response From 30 to 30,000 cps.
- Power Rating—Up To 25 Watts Continuous, 50 Watts Instantaneous Peak
- Nominal 8 ohms Impedance



79⁹⁵

Decorette III Model SK-275

\$5 Monthly

Designed by Lafayette engineers—built by the foremost English Hi-Fi Speaker manufacturer to Lafayette's rigid specifications, the Decorette III employs three speakers to provide smooth, realistic musical reproduction over the entire audible range—you'll hear deep effortless bass . . . clear precise mid-range . . . shimmering highs.


The enclosure is a bass reflex design using a ducted port of the tube type which is proportioned to provide correct acoustic "tuning" of the enclosure. Solid ¾" wood construction, internally braced, plus the liberal use of sound absorbent material, ensures an extremely rigid enclosure, free of undesirable resonances. The particularly low bass response of this bookshelf system is aided by the use of

a newly-developed 12" low-resonance woofer which covers the range of 30 to 2000 cycles. The 6" mid-range Speaker and the 3½" "Super" tweeter act as direct radiators and provide smooth reproduction from 2,000 cps to beyond audibility. The enclosure is finished on all four sides in a hand rubbed oiled walnut veneer, tastefully framed in an ebony and gold picture frame molding with white and gold acoustic grill material. Designed for either horizontal or vertical placement, the "Decorette III" is a handsome addition to any listening room. For 10-watt amplifiers or larger. Dimensions: 14x24x12"D. Shpg. wt., 35 lbs.
 21 N 0107WX Model SK275 Decorette III Net 79.95

Net 79.95
 Two for 158.95

Decor-ette Speaker Systems


LAFAYETTE'S "decor-ette V"™ SLIM 5-SPEAKER SYSTEM



Model SK300
Decorette V

Lafayette is proud to offer a dazzling 5-speaker system—magnificently styled and engineered. The "Decorette V" incorporates a specially designed audio panel speaker system consisting of four 6½" low resonance speakers, and one 2½" cone tweeter mounted in a flat enclosure of only 4¼ inches thickness. The results achieved are remarkable; clean natural bass response, smooth midrange and pure, rich highs. These are mounted in a superbly styled oil walnut veneer enclosure with magnificent walnut picture frame molding,

Only
39⁹⁵
\$5 monthly
78⁵⁰
PAIR
\$5 monthly




- Four Specially Engineered 6½-inch Low Resonance Speakers—One 2½-inch Cone Type Tweeter Designed to achieve optimum performance in a new type audio-panel enclosure of only 4¼ inches in thickness.
- A superbly styled oil walnut veneer enclosure with magnificent walnut picture frame molding, bordering a fine decorative Cane Grille.
- Freq. response 50-18,000 cps
- Power handling Capacity continuous 15 watts, peak level power—30 watts.
- Crossover Electrical 2,500 Cycles
- Impedance—8 ohms

bordering a fine decorative cane grille. Ideal for floor mounting, bookshelf mounting, or wall mounting. Can even be used as a room divider. Overall frequency response 50-18,000 cps. Power handling capacity 15 watts, peak load power—30 watts. Complete with decorator styled legs. Impedance 8 ohms—size 21¾Hx4¼Dx17¾"W. Shpg. wt., 17 lbs. Imported.

99 N 0008WX Model SK-300 Decorette V Speaker System Net 39.95
2 for 78.50

DELUXE LAFAYETTE "decor-ette II"™ SLIM 5-SPEAKER 3-WAY SYSTEM



SK-270
DECORETTE II
59⁹⁵
Only
\$5.00 Monthly

Designed by Lafayette engineers—built by the foremost English Hi-Fi Speaker manufacturer to Lafayette's rigid specifications.

Designed by Lafayette engineers—built by the foremost English Hi-Fi Speaker manufacturer to Lafayette's rigid specifications. The genuine, hand-rubbed oiled walnut veneer cabinet with smart ebony black and gold picture frame molding, has been designed and styled for either vertical or horizontal placement. A real space-saver, it is slim in appearance and can be placed on a bookshelf, mounted on the floor, used as a room divider or hung on the wall. The "decor-ette II" is a 5-speaker 3-way system utilizing the latest advanced acoustic designs. Two 8" woofers with ½-lb. magnets incorporate a "Rigidflex" Floating Piston Hyperbolic Cone resulting in a free floating cone rim and a completely rigid cone center to provide maximum distortionless bass from 500 cycles down to 40 cycles. The



- Custom Assembled in a Genuine Hand-Rubbed Oiled Walnut Veneer Cabinet of Extra Heavy ¾" Stock
- Frequency Response, 40-20,000 cps
- Power Handling Capacity, Continuous 30 Watts; Instantaneous Peak Load Power, 60 Watts
- Impedance 8 Ohms

specially designed 6" mid-range open back driver provides uniform response from 500 to 7500 cycles. The 3½" cone type tweeter gives wide dispersion of the mid-highs smoothly from 1000 to 10,000 cycles. The dome lens type compression tweeter response is from 5000 to 35,000 cycles. Omni-directional, this tweeter gives 360° sound dispersion to add overall brilliance to the system. RC electrical crossover frequency is 5000 cps. Instantaneous peak load power, 60 watts. Impedance, 8 ohms. Size: 25"Hx17"Lx4¾"W. Supplied with 4 1" round walnut decorator legs which can be mounted on the cabinet for either vertical or horizontal placement. Shpg. wt., 24 lbs.

21 N 0106WX SK-270 Decorette II Net 59.95

Prices On This Page May Be Raised April 1st Due To New Excise Tax

Slenderette Speaker Systems

FAMOUS LAFAYETTE "SLENDERETTE III" SLIM 2-SPEAKER 2-WAY SYSTEM

*Fine Speaker Performance Offering Rich
Clean Sound At Lafayette's Low, Low Price*

- Ideal Choice for Floor, Shelf or Wall Mounting
- Perfect for low cost Stereophonic or Monophonic Systems
- Improves Fidelity of Phonographs, TV Sets, AM and FM Radios
- Room-Filling Music Everywhere In Your Home


17⁹⁵

2 FOR 34.95

The Lafayette Slenderette III is the ideal choice as a floor, shelf, or wall type speaker system for low-cost stereo or monophonic systems, and for top quality extension speaker use. Can be used for improving fidelity of existing TV sets, AM and FM radios, tape recorders, and phonographs. Enjoy smooth, wide-range sound in every room of your house. The slim styling enhances the decor of your room. Contains a special 6½" high compliance woofer and a matched 2½" cone tweeter with crossover network. Offers fine speaker performance — clear natural bass, full midrange reproduction, and wide-dispersion of high frequencies. The speakers are mounted in 3 superbly constructed and finished oil walnut cabinet. Oil walnut finish is on all four sides. With walnut picture frame molding. Measures 12x18 inches with a depth of 5¼ inches. Freq. response—50-10,000 cps. Impedance 8 ohms. Shpg. wt., 15 lbs. Imported.

99 N 0009WX Model SK-265 Slenderette III

Net 17.95
2 for 34.95



Model
SK-265

SELECT "SLENDERETTE II" SLIM 3-WAY 3-SPEAKER SYSTEM

*Featuring Jensen Speakers
and Universal Woodcrafters
Cabinet at Lafayette's Low, Low Price*

- 3-Speaker 3-Way System
- Utilizes Jensen 8" High Compliance Woofer, Jensen 6" Mid-Range Driver and Jensen 3" Tweeter
- For Shelf, Floor or Wall
- Beautifully Styled Cabinet Finished on all 4 Sides In Finest Genuine Walnut Veneer With Cane Grille and White Enamel Border


29⁹⁵

Made in U.S.A.

The "Slenderette II" is an outstanding system offering superb styling and rich, deep sound. Incorporates the latest advanced acoustic design at Lafayette's low, low, price. Contains a 3-speaker 3-way system engineered by Jensen with newly developed Jensen components. Utilizes a Jensen 8" high compliance woofer with rubber suspension for extra wide excursion, a Jensen six-inch midrange driver in rubber suspension, and a special Jensen 3-inch tweeter. Woofer electric crossover at 400 cycles, mid-range electric crossover at 2000 cycles. Response 50 to 15,000 cycles. Power capacity: 18 watts continuously, 36 watts peak. Superbly styled cabinet finished on all 4 sides in finest genuine walnut veneer with protruding cane grille & white enamel border. Ideal for shelf, floor or wall mounting. Includes wall bracket. Impedance 8 ohms. 21¼Wx14¼Hx4¼"D. Shpg. wt., 22 lbs.

21 N 0101WX

Net 29.95



LAFAYETTE ULTRA-COMPLIANCE 2-WAY SPEAKER SYSTEMS

VERY SMALL IN SPACE — LESS THAN 1 CU. FT.

- Frequency Response 40-16,000 cps
- Especially Designed Vented, Tuned Duct Type Enclosures
- Unique Mechanical 2-Way Speaker With Heavy Magnet
- Enclosure Finished on 4 Sides
- Excellent For Stereo

19⁹⁵

FULL SIZE PERFORMANCE — These outstanding Lafayette Ultra-Compliance 2-way speaker Systems achieves a purity of sound and musical quality that is astounding from a speaker system occupying less than one cu. ft. of space. A perfect speaker for use anywhere in your home or office . . . makes ideal extension units or use in pairs for stereo.

These Ultra-Compliance 2 Way Systems feature a unique dual cone speaker with heavy magnet structure, employed in a specially designed tuned ducted port enclosure. Both tweeter and woofer "float" on flexible, corrugated edges, with the outer edge of the tweeter cone attached to the mid-section of the woofer. This results in a mechanical crossover so that both cones operate in phase at low frequencies, but only the tweeter cone radiates high frequencies. The same type of wide-range frequency response as found in true coaxial or multiple speaker systems is achieved in these unique "Ultra-Compliance" Speaker Systems. Frequency response is 40-

16,000 cps—Impedance: 8-16 ohms.


Available in rich mahogany or oiled walnut. Finished on four sides —place it horizontally on its side or vertically on its base. Easily adapts to bookshelf placement or modular use. Dimensions are only 10¾Hx18¼Lx8¾"D. Shpg. wt., 15 lbs. Imported.

99 N 0122WX Model SK-124A Mahogany
Set of Two Speaker Systems

Net 19.95
Net 38.90

99 N 0118WX Model SK-123A Oiled Walnut
Set of Two Speaker Systems

Net 19.95
Net 38.90



Prices On This Page May Be Raised April 1st Due To New Excise Tax

Lafayette Cat. No. 653 43

Deluxe LAFAYETTE ELIPTOFLEX® Enclosure




FINISHED ON 4 SIDES
Adapts to any room arrangement. Place horizontally on shelves or vertically on the floor.

As Low As
29⁵⁰

The "Eliptoflex"....

PHENOMENAL ELIPTOFLEX PERFORMANCE



U. S. Patent No. 3,089,562

The loudspeaker is mounted on a baffle recessed in the cabinet shell with the front-plate extending partially across the front surface of the baffle forming ducts or tubes from the port openings to the outside air. The elliptical cutout changes the effective length of the duct across its area. This variation in path lengths provide an extremely smooth transition from duct to free air; broadens the frequency response and provide better transient response. A triangular shaped diffracting ring mounted on the front of the baffle board virtually eliminates undesirable cancellation effects normally produced by close coupling of front and rear cone radiation. This results in a "lens" effect, changing relative particle velocities and consequently, phase relationships so as to produce a smooth transition from front to rear radiation. Comparative laboratory and listening tests indicate that "Eliptoflex" performance is demonstratively superior throughout the audio spectrum.

- 1 Meets space requirements of stereo.
- 2 Utilizes the full advantages of efficient 12" speaker performance.
- 3 Provides optimum performance without use of large wattage, expensive amplifiers.

The "Eliptoflex" utilizes a unique elliptical port which broadens frequency response and provides better transient response. A specially engineered diffracting ring eliminates cancellation effects between front and rear radiation. These engineering advances when coupled with the famous Lafayette free-edge SK-58 12" coaxial speaker with 3" cone type tweeter, 1 1/4 lb. TSK-5 high flux density magnet, — special 3/4" wide sheepskin cone-edge suspension and built-in crossover network level control offer a magnificent speaker system. (See listing below).


"Eliptoflex" achieves a degree of natural smoothness, low-distortion and rich robust bass hitherto found only in large enclosure speaker systems or inefficient bookshelf speakers requiring high powered amplifiers. Due to its highly efficient design characteristics the "Eliptoflex" does not require costly high wattage amplification.

The "Eliptoflex" speaker system is beautifully finished on 4 sides in a variety of hardwood veneers for attractive room placement either horizontally or vertically. Dimensions are 14Hx23 3/4Wx13 3/4"D. Shpg. wt., 35 lbs.

ELIPTOFLEX ENCLOSURE LESS SPEAKER — FINISHED ON 4 SIDES	
20 N 0127WX "Eliptoflex" Enclosure—Mahogany	Net 36.50
20 N 0128WX "Eliptoflex" Enclosure—Walnut	Net 36.50
20 N 0129WX "Eliptoflex" Enclosure—Oiled Walnut	Net 36.50
20 N 0130WX "Eliptoflex" Enclosure—Unfinished Birch	Net 29.50

LAFAYETTE ELIPTOFLEX with FAMOUS SK-58 12" COAXIAL SPEAKER with 1 LB. MAGNET

AS LOW AS **59⁵⁰**




Superb performance from a speaker system featuring the famous Lafayette SK-58 12" coaxial speaker with 2-3" cone type tweeters and 1 1/4 lb. magnet mounted in the patented Lafayette Eliptoflex enclosure. Enclosure comes finished on 4 sides.

Eliptoflex/SK58 Speaker System	
21 N 0115WX Mahogany	Net 64.50
21 N 0116WX Walnut	Net 64.50
21 N 0112WX Oil Walnut	Net 64.50
21 N 0117WX Unfinished Birch	Net 59.50

See Page 45 For Full description of SK-58

LAFAYETTE ELIPTOFLEX with SK-180 10" TRIHELIX 3-WAY SPEAKER

AS LOW AS **61⁵⁰**



An ideal combination of speaker and enclosure that furnishes optimum 3-way speaker performance. Eliptoflex enclosures are finished on all four sides for vertical or horizontal placement. Shpg. wt., 32 lbs.

Eliptoflex/SK180 Speaker System	
21 N 0118WX Mahogany	Net 66.50
21 N 0119WX Walnut	Net 66.50
21 N 0120WX Oiled Walnut	Net 66.50
21 N 0114WX Unfinished Birch	Net 61.50

See Page 45 For Full description of SK-180

The Widely Acclaimed LAFAYETTE® SK-58® 12" Coaxial Speaker

**SUPERB PERFORMANCE GUARANTEED*—
OR YOUR MONEY BACK!**

- 1½ Lb. Magnet Weight
- Response 30-15,000 CPS
- Sheepskin "Free Edge" Cone Mounting
- 3" Coaxially Mounted Tweeter
- Built-In LC Network
- Rated At 20 Watts Continuous Power

29⁵⁰



The World Renowned Original Lafayette SK-58

Lafayette's exclusive 12" coaxial is a precision-made high fidelity loudspeaker, universally acclaimed by music lovers, hi-fi enthusiasts and professional experts alike. It provides a truly faithful reproduction of sound without any "coloration" or distortion, its excellence being responsible for its use in innumerable high fidelity music systems today. The SK-58 incorporates such features as heavy, high flux density TSk-5 magnets for high efficiency; ¾" wide sheepskin cone-edge suspension and special composition fibre cone material, specially treated for ultra-linear, distortion-free response; heavy rugged cast metal frame for freedom from resonances and for greater rigidity. The coaxially-mounted 3" cone-type tweeter has a bell shaped mounting for maximum dispersion of high frequencies with no back radiation. With the built-in

3000 cps crossover network it contributes its share to the smooth delivery of the overall wide range response of 30-15,000 cps. Woofer resonance in free air is 40 cps. Speaker power handling capacity is 20 watts continuous sine wave, 35 watts peak program material. Impedance of the voice coil is 8 ohms, connections being made to chrome plated screw terminals. Finished in gray-brown opalescent enamel, the speaker is supplied complete with "brilliance" level control. Shpg. wt., 11 lbs. Imported.

99 N 0019W SK-58 12" Coaxial Speaker Net 29.50

*Try your SK-58 at home. If for any reason you are dissatisfied, you may return it at once and your money will be refunded (less transportation charges).


LAFAYETTE TRIHELIX®

3 Completely Independent Speakers With 3 Separate Voice Coils In A Single 10" Compact Unit

- Frequency Response 20 to 20,000 cps (30-18,000 cps ± 3 db)
- Revolutionary Conical Stiffener
- Eccentric Baffle Mounting of Midrange & Tweeter Eliminates Interaction Between Speaker Cones
- Built-in Crossover Network and Brilliance Control
- Extremely Efficient
- High Excursion Woofer
- Ideal For Stereo

32⁵⁰

\$5.00 Monthly



Recreates The Entire Audio Spectrum With Concert Hall Faithfulness—The Lafayette "Trihelix." Fresh engineering concepts have resulted in a single 10-inch speaker designed expressly for use in bookshelf size enclosures. The "Trihelix" is in effect a complete three-way high-fidelity speaker system, with three mechanically and electronically independent speakers mounted within a single 10-inch frame.

Although they are individual units the 2-inch tweeter and 5-inch midrange speakers have been especially designed to compliment the woofer. Special treatment of the cones and cone edges with polyester resins provides an even distribution of mid and high frequencies without peaks or resonances. To minimize interaction between the three cones both the midrange and tweeter units are mounted eccentrically or off-center in relation to the woofer and are completely enclosed by a specially designed baffle. These unusual design features result in effectively eliminating intermodulation distortion—a common fault in conventionally designed 3-way speakers. The specially treated woofer cone employs a revolutionary "conical stiffener" located at the apex of the cone in order to stiffen the diaphragm and eliminate "breakup," thus

providing a true piston action. This carefully designed cone-stiffening procedure, in addition to its very high compliance, enables the woofer to deliver a smooth, crisp, solid bass that balances naturally against a crystal clear midrange and natural treble. A built-in electrical crossover network with crossover points at 1500 cps and 5000 cps, allows each speaker to reproduce its portion of the audio range smoothly and efficiently. An adjustable brilliance control permits matching of sound to room acoustics. SPECIFICATIONS: Overall Response 20-20,000 cps (30 to 18,000 cps ± 3 db). Free Air Resonance 35-55 cps. Impedance 16 ohms. Power Rating: 20 watts Average Program Material. Crossover Points: 1500 & 5000 cps. Overall Diam: 10". Overall Depth: 7". Baffle cut-out: 8¾". Screw type terminals are color coded for quick easy connection of amplifier leads. Shpg. wt., 8 lbs. Imported.

99 N 0020W SK-180 10" Trihelix Speaker Net 32.50

20 N 0109W Adaptor Board To Fit above to 12" cutout Net .88

Lafayette Cat. No. 653 45

Prices On This Page May Be Raised April 1st Due To New Excise Tax

The LAFAYETTE Sovereign 12 3-Way High Performance Hi-Fi Speaker Model SK-210



**CUSTOM-BUILT IN ENGLAND TO
LAFAYETTE'S RIGID SPECIFICA-
TIONS 2¼-LB. CERAMIC MAG-
NET—3" VOICE COIL**

42⁵⁰
\$5.00 Monthly

- 2¼ lb. Ceramic Magnet
- "Rigidflex" Free-Edge Cone Suspension—No Standing Waves Or Surround Resonances
- 3-Way Axial Design Provides Exceptional Smooth Low, Mid & High Frequency Coverage
- Special Low-Resonance Woofer Cone, Stiff Mid-Range Radiator
- Compression-Driver Tweeter
- Frequency Response: 30-20,000 C.P.S.
- Fundamental Resonance: 35 Cycles
- Power Handling Capacity: 30 Watts
- Voice Coil: 3 Inches
- Wide Dispersion Tweeter, Self Aligning Aluminum Voice Coil & Diaphragm
- Impedance: 16 ohms
- Unitized Die-Cast Frame

Engineered to satisfy the most discriminating listener, the 210 achieves full 3 speaker performance through its advanced 3-way design. Woofer, midrange radiator and tweeter are all axially mounted within a single rigid, unitized die cast frame to provide an integrated, efficient wide range speaker system. Construction features incorporate a 3 inch voice coil with an exclusive "Rigidflex" cone-bonding and cone-edge treatment process to form a virtually free-edged cone suspension. All irregularities of the audible frequency spectrum are smoothed out with standing waves and surround resonances eliminated. High efficiency and low distortion are further assured by use of a specially designed 2¼ lb. ceramic magnet.


Frequency response is 30-20,000 cps with a free-air woofer cone

resonance of 35 cps. Bass response is tight and solid without boom or hangover to achieve phenomenal realism. At 2000 cps, frequencies are channeled into a stiff-coned midfrequency radiator by means of a smooth mechanical crossover. High frequencies are reproduced with a silkiness and naturalness to beyond the limits of human hearing by means of a compression driver tweeter. This superb new tweeter incorporates a rigid, die-cast, flared, hyper-elliptical horn, a 1" diameter aluminum voice coil and diaphragm in a self-aligning assembly with air chamber and phase equalizer. A built in crossover allows the tweeter to take over at 5,000 cps and is provided with a high-frequency L-pad level control with attractive escutcheon and knob. Shpg. wt., 15 lbs.

21 N 0121W

Net 42.50

LAFAYETTE ELIPTOFLX® with SK-210 SOVEREIGN 12" 3-WAY SPEAKER




AS LOW AS **67⁵⁰**
\$7 monthly

PERFORMANCE MATCHED—Lafayette's famous Eliptoflex bookshelf enclosure matched with the exceptional SK-210 Sovereign 12" 3-way speaker with 2¼ lb. ceramic magnet. The unique Eliptoflex design, featuring an elliptical port for broader frequency response, plus the famous Lafayette SK-210 3-way speaker combine to provide today's discriminating stereo enthusiast with superb performance throughout the audio spectrum. See above for individual component description. Size: 14Hx23¾Wx13¼"D. Shpg. wt., 39 lbs.

21 N 0122WX SK-210 & Eliptoflex Mahogany	Net 74.50
21 N 0123WX SK-210 & Eliptoflex Walnut	Net 74.50
21 N 0124WX SK-210 & Eliptoflex Oiled Walnut	Net 74.50
21 N 0125WX SK-210 & Eliptoflex in Unfinished Birch	Net 67.50

LAFAYETTE Criterion®/MARK II ELIPTOFLX® SPEAKER CABINET with the SK-210 SOVEREIGN 12" SPEAKER



only **98⁵⁰**
\$8 monthly


Now Lafayette's renowned Eliptoflex enclosure in a new decorator inspired form. Incorporates the same inner construction and acoustic principles that have made Eliptoflex performance famous. The SK-210 is packaged separately, and can easily be mounted in the Criterion enclosure in a matter of minutes. Size: 32½Hx18Dx16"W. Wt. 65 lbs. Criterion Eliptoflex Walnut finish with SK-210.

21 N 0133WX	Net 98.50
Criterion Eliptoflex Oiled Walnut finish with SK-210.	
21 N 0134WX	Net 98.50
Criterion Eliptoflex Mahogany finish with SK-210.	
21 N 0132WX	Net 98.50

Deluxe LAFAYETTE 3-Way 15" High Fidelity Speaker Model SK-215

- Free-Edged Cone Suspension
- 12 DB/Octave Cross-over Network with High Frequency Level Control
- Precision Pressure-Drive Horn-Loaded Tweeter with Aluminum Diaphragm & Coil
- Massive 5-lb. Ceramic Magnet
- 3-inch Main Voice Coil • Overall Frequency Response: 20-20,000cps
- Cone Resonance Frequency: 25 cps • Impedance—16 Ohms
- Power Capacity—50 Watts

Lafayette combined the finest British craftsmanship and advanced acoustic design to bring you this outstanding 3-way 15" speaker. The SK-215 utilizes a patented concentric twin-gap magnetic system with a massive 5 lb. super efficient double duty cylindrical ceramic magnet. Woofer, mid-range radiator and compression tweeter are axially mounted to achieve outstanding, efficient wide-range speaker performance. With a cone resonance of 25 cps, the woofer section features a virtually free-edged cone suspension. Automatic mechanical crossover at 2000 cps. A 12 db per octave LC crossover network provides smooth transition at 5000 cps from mid-range to a horn-loaded tweeter with an aluminum diaphragm. L-pad level control for matching of sound to room acoustics and individual listening tastes. SPECIFICATIONS: Cone Resonance, 25 cps; Overall Frequency Response, 20-20,000 cps; Magnet Weight, 5 lbs.; Magnetic Flux Density, over 250,000 Maxwells; Crossover Frequencies, 2000 and 5000 cps; Power Capacity, 50 watts; Woofer Voice Coil Diameter, 3 inches Tweeter Voice Coil Diameter, 1 inch; Impedance, 16 Ohms. Dimensions: 6½" overall depth: 15¼" diameter. Shpg. wt., 30 lbs. 21 N 0130WX Net 64.50



ONLY
64⁵⁰
\$6 monthly

Features Massive 5-lb. Ceramic Magnet, 3-in. Main Voice Coil


Lafayette Model SK-216 3-way 12" Hi-Fi Speaker

Same as SK-215 except has cone resistance of 35 cps. Dimensions: 5½" overall depth; 12¼" diameter. Shpg. wt., 25 lbs. 21 N 0129WX Net 54.50

Deluxe LAFAYETTE Speaker System featuring Lafayette "Universal" Bass Reflex Enclosure and Lafayette SK-215 3-Way 15" Speaker

A superb speaker system featuring the Lafayette SK-215 3-way speaker (see description above) and the beautifully styled Lafayette "Universal" Bass Reflex Enclosure. Solidly constructed of ¾" stock, this fine enclosure is designed to achieve optimum performance from a separate 12" or 15" full range, 3-way speaker. Provides rich, robust bass. The enclosure comes with a cutout for the SK-215, and is lined internally with acoustical material. Finished walnut and mahogany models are of genuine veneer and acoustically correct flakecore. Dim. 28" x 23½" x 16" D. Note: The SK-215 is packed separately and can easily be mounted in the "Universal" Enclosure in a matter of minutes. Shpg. wt., 84 lbs.

- | | |
|---|------------|
| 21 N 9618WX Walnut Enclosure and SK-215 Speaker | Net 117.00 |
| 21 N 9619WX Mahogany Enclosure and SK-215 Speaker | Net 117.00 |
| 20 N 0131WX Walnut Enclosure only. Shpg. wt., 54 lbs. | Net 52.50 |
| 20 N 0132WX Mahogany Enclosure only. Shpg. wt., 54 lbs. | Net 52.50 |
- LAFAYETTE "UNIVERSAL" BASS REFLEX ENCLOSURE AND LAFAYETTE SK-215 3-WAY SPEAKER.** Outstanding Lafayette Speaker System featuring same Lafayette "Universal" Bass Reflex Enclosure listed above with Lafayette SK-216 3-Way 12" Speaker. Shpg. wt., 79 lbs.
- | | |
|---|------------|
| 21 N 9616WX Walnut Enclosure and SK-216 Speaker | Net 107.00 |
| 21 N 9617WX Mahogany Enclosure and SK-216 Speaker | Net 107.00 |



Enclosure with SK-215 Speaker

117⁰⁰

Enclosure Only

52⁵⁰

Maximus I Speaker System by GOODMANS

IMPORTED FROM ENGLAND

One Of The Smallest, True High Fidelity Speaker Systems In The World! Actual Size 10½x5½x7¼"

- Sufficient Handling Capacity—With Ease
- Crisp Voice Articulation—Natural Presence
- Real Treble, Solid Bass
- Unusual Compactness—Fits Anywhere

MAXIMUS I
A Speaker System Developed by the UTC Sound Division, Garden City, New York

The MAXIMUS I is only 10½x5½x7¼" and fits everywhere—book shelf, end table, or wall. Inside each miniature mastercrafted oiled walnut enclosure are precision direct-radiator drive units with specially designed crossover networks to give uniform response from 45 to 20,000 cps. Exceptionally smooth bass is achieved by the utilization of a massive magnet in the woofer section. Power handling capacity is 15 watts, making it compatible with most amplifiers. A uniquely designed L-C crossover network transfers power at 900 cps to a newly developed backloaded mid-range/high frequency unit. Shpg. wt., 11 lbs. 21 N 8301WX Walnut Finish Net 59.50



59⁵⁰
\$6 monthly



LAFAYETTE

Ultra-Linear SK-128[®]


Full-Range 8-Inch Biaxial Speaker with Acoustic Tweeter Baffle Design

The SK-128 combines the best features of a multiple speaker system in one compact and economical unit. It offers full, even coverage of the entire audible range, with no distortion or coloration to mar your listening pleasure. The specially treated woofer cone has a unique "Conical Stiffener" at the apex which, coupled with its high compliance, enables the cone to operate in a piston-like manner—delivering a clean, powerful bass response. The 2-inch tweeter has its own voice coil and magnetic field. Special treatment of cone and cone edge provides even distribution of the high frequencies, with no peaks or resonances. The unusual off-center mounting of the tweeter and its elliptical baffle minimizes interaction between tweeter and woofer and insures an overall response free of intermodulation distortion. Electrical crossover from the woofer cone to the tweeter unit is provided by a built-in network. An adjustable brilliance control permits matching of sound to room acoustics. Efficiency of the speaker is such that it will operate from any amplifier with an output of 1 watt or more. Installed in a bass-reflex type of enclosure, it performs outstandingly, and is recommended for all high-quality music systems—whether monaural or stereophonic. SPECIFICATIONS: Overall Response: 20-20,000 cps (40-16,000 cps \pm 3 db). Free air Resonance: 45-65 cps. Impedance: 8 ohms. Power Rating: 20 watts Integrated Program Material. Crossover: 2,500 cps. Overall Diam. 8 $\frac{3}{4}$ ". Overall Depth: 5 $\frac{1}{2}$ ". Baffle cut-out: 7 $\frac{1}{2}$ ". Rugged, vibration-free speaker frame with color-coded screw-type terminals for quick, easy connection of amplifier leads. Shpg. wt., 5 lbs. Imported. 99 N 0032 Full Range 8" Biaxial Speaker . . . Net 19.50

ONLY
19⁵⁰
2 for 38.95



Eccentric Tweeter Mounting & Unique Elliptical Baffle Completely Eliminates Interaction Between Woofer & Tweeter



■ 20 TO 20,000 CPS (40 TO 16,000 CPS \pm 3 DB) ■ HIGH EFFICIENCY ■ HIGH EXCURSION WOOFER WITH UNIQUE "CONICAL STIFFENER" ■ HANDLES HEAVY BASS PASSAGES WITHOUT "DOUBLING"



LAFAYETTE MINI-DUCT[®] BOOKSHELF ENCLOSURE WITH SK-128[®] 8" ULTRA-LINEAR SPEAKER

The perfect answer for those who demand realistic sound reproduction even where space is limited. Two of these systems are ideal for stereo. Beautifully finished on all 4 sides for horizontal or vertical placement. Shpg. wt., 28 lbs.

21 N 0108WX	Speaker System in Walnut	Net 39.50
21 N 0109WX	Speaker System in Oiled Walnut	Net 39.50
21 N 0110WX	Speaker System in Mahogany	Net 39.50
21 N 0111WX	Speaker System in Unfinished Birch	Net 37.50




LAFAYETTE'S Popular



AS LOW AS
21⁵⁰

Mounting boards accept all types of tweeters

LAFAYETTE SK-98® 8" DUO-CONE HI-FI SPEAKER



9⁹⁵

- Mechanical 2-Way Design
- Overall Response 40-16,000 Cps.
- Large Magnet Structure
- Patented Cone Construction and Material High Excursion Woofer


The dual-cone construction used in these high quality 8" speakers, provides the same type of wide-range response normally found in true coaxial speakers or multiple speaker systems. The woofer and tweeter cones "float" on flexible corrugated edges. This mounting results in true mechanical crossover, so that both cones operate at low frequencies, but only the tweeter cone operates at high frequencies. This gives improved high frequency directional characteristics and minimum distortion. Patented cone materials provide extremely smooth response over the range of 40-16,000 cps. Magnets are large and heavy, with a flux density of 10,500 gauss and total flux of 56,000 maxwells. Terminals are screw-type for solderless connections. Sensitivity is 99.5 db/watt; free air resonance is 55-70 cps; voice coil impedance is 8 ohms. Size is 8" diam., 4 1/4" deep and requires 6 3/4" diam. baffle opening. Shpg. wt., 5 1/2 lbs. Imported.

99 N 0027 8" 2-WAY SPEAKER Net 9.95
2 FOR STEREO Net 18.95

MINIDUCT® SPEAKER ENCLOSURE WITH LAFAYETTE SK-98 8" PATENTED DUAL CONE SPEAKER

As Low As

31²⁵



A PERFECT COMBINATION: The "Mini-Duct" enclosure and the famous Lafayette SK-98 8" mechanical 2-way speaker with patented dual cone construction. This speaker combined with the Lafayette "Mini-Duct" enclosure will give the wide-range frequency response (40-16,000 cps) normally found in the coaxial speakers or multiple speaker systems. Shpg. wt., 29 1/2 lbs.

Combination unfinished "Mini-Duct" enclosure with SK-98 Speaker 21 N 9990WXM Net 31.25
Combination mahogany "Mini-Duct" enclosure with SK-98 Speaker 21 N 9991WXM Net 34.25
Combination walnut "Mini-Duct" enclosure with SK-98 Speaker 21 N 9992WXM Net 34.25
Combination oiled walnut "Mini-Duct" enclosure with SK-98 Speaker 21 N 9993WXM Net 34.25

Prices On This Page May Be Raised April 1st Due To New Excise Tax

MINI-DUCT®

SPEAKER ENCLOSURE

A universal ducted-port bookshelf enclosure engineered for use with 1, 2 or 3-way speaker systems.

- SOLIDLY CONSTRUCTED OF 3/4" WOODS
- START WITH A SINGLE SPEAKER AND BUILD INTO 2- OR 3-WAY SYSTEM LATER
- ACOUSTICALLY LINED THROUGHOUT
- AVAILABLE IN A VARIETY OF 4-SIDED FINISHES

Now limited space need not necessarily mean limited sound. The Lafayette Mini-Duct is acoustically designed to achieve smooth, distortion-free reproduction with a remarkably full, clean extended bass response that gives no indication as to its small size. Reducing boards are supplied so that the Mini-Duct will accept an 8" Woofer, 6" Mid-Range and a variety of tweeters. This versatility makes it possible to start with an 8" speaker and eventually build into a 2-way or 3-way speaker system. Solidly constructed of 3/4" woods the Mini-Duct is beautifully finished in a variety of fine veneers on 4 sides. Designed for attractive horizontal or vertical placement anywhere in your home with dimensions 23Wx11 1/2"Hx 11 1/4"D. Shpg. wt., 23 3/4 lbs.

20 N 0123WX Walnut Net 24.95
20 N 0124WX Mahogany Net 24.95
20 N 0125WX Oiled Walnut Net 24.95
20 N 0126WX Unfinished Birch Net 21.50

LAFAYETTE SK-130 8" WIDE-RANGE HI-FI SPEAKER



12.95

Made in England To Our Own Rigid Specifications

CHECK THESE PHENOMENAL SPECIFICATIONS

- Frequency Response: 40-18,000 cps
- Flux Density: 13,500 Maxwells
- Power Handling Capacity: 15 Watts
- Magnet Weight: 1 lb. High Efficiency
- Cone Resonance: 55 cps
- Voice Coil: 1-Inch
- Impedance: 16 Ohms
- Alcomax Magnet

ASTONISHING FIDELITY from a speaker of this size and modest price. Designed and finished with typical British craftsmanship, the SK-130 features an especially designed hyperbolic cone with a plastic surround suspension for wide compliance performance. Bass response is robust and full bodied, while the midrange and highs are virtually transparent, with never a trace of shrillness or harshness. The excellent wide-range response of the SK-130 make it ideal for stereo when used in pairs or perfect for use as a high quality extension speaker. Overall Diam. 8 1/4"x4" Deep. Baffle cut-out 7 1/4". Rigid vibration-free frame is equipped with screw type terminals. Imported.

21 N 0113 Shpg. wt., 3 lbs. Net 12.95

FAMOUS LAFAYETTE MINI-DUCT® BOOKSHELF ENCLOSURE WITH SK-130 8" WIDE-RANGE SPEAKER

As low as

33⁹⁵



A combination that rivals the performance of much larger speaker systems. This fine enclosure assures optimum performance from the SK-130. Only 23Wx11 1/2"Hx11 1/4"D—ideal for mounting in a bookcase or record shelf. Finished on 4 sides in a variety of fine furniture finishes. Shpg. wt., 27 lbs.

21 N 9994WXM Mahogany Net 36.95
21 N 9995WXM Walnut Net 36.95
21 N 9996WXM Oiled Walnut Net 36.95
21 N 9997WXM Unfinished Net 33.95

Lafayette Cat. No. 653 49

LAFAYETTE World Famous

15" COAXIAL HI-FI SPEAKER



17⁹⁵

- 30-20,000 Cps—35 Watts Peak
- Large 13 oz. Ceramic Magnet

A high quality, budget priced speaker system consisting of specially designed 15" woofer with a full 5" high-frequency tweeter coaxially mounted with a 1 1/2" voice coil. SPECIFICATIONS: Frequency response, 30-20,000 cps. Crossover frequency, 3500 cps. Cone resonance, 45 cps. Power handling capacity, 20 watts continuous and 35 watts peak. Impedance, 8 ohms. Rugged, lasting seamless cone. Has 4-way binding posts for easy installation. Shpg. wt., 12 lbs.

21 N 4711W

Net 17.95

12" WIDE-RANGE HI-POWER HI-FI SPEAKER



14⁹⁵

- 1 1/4 lb. Ceramic Magnet • Rated at 30 Watts
- Response CPS 20-14,000
- Seamless Cone
- Special Heavy-Duty Construction
- Ideal for P.A.

This wide-range 12" FM high fidelity speaker is rated at 30 watts and is excellent for use with any hi-fi system. Voice coil impedance 8 ohms. Outside diameter 12 1/4", mounting diameter 11 1/4", depth 6 3/4". Color-coded 4-way binding-post terminals. Shpg. wt., 8 lbs.

21 N 4712

Net 14.95

12" THREE-WAY HI-FI SPEAKER



11⁹⁵


- 10 oz. Ceramic Magnet
- 20 Watts Power Capacity
- Frequency Response 35-17,000 cps

Features a 10 oz. ceramic magnet, and when correctly baffled, will reproduce bass notes down to 35 cps. A special elliptical tweeter extends response to 17,500 cps and gives improved sound dispersion over the usual cylindrical types. Voice coil diameter is 1 1/4". Impedance is 8 ohms. Power Capacity is 20 watts. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 8 lbs.

21 N 4714

Net 11.95

ECONOMY 12" COAXIAL SPEAKER



8⁷⁵


- Frequency Response 40-15,000 cps
- Voice Coil Diameter 1"

An economical way to improve the sound of existing inexpensive hi-fi consoles or portables or as the main speaker system of a budget priced high-fidelity system. A built-in filter correctly divides the frequency spectrum and distributes the different frequencies to the woofer and tweeter. Power rating: 12 watts. Impedance: 8 ohms. Shpg. wt., 5 1/2 lbs.

21 N 4715

Net 8.75

15" HI-FI WOOFER



23⁹⁵

- Heavy 2 lb. Alnico Magnet
- Peak watts—35 Watts
- 20 to 5000 Cycles

Efficient 15" woofer with 2 lb. Alnico V magnet. Ideal for 2- and 3-way speaker systems. Handles 35 watts of audio power. Frequency response ± 2 db 20 CPS to 1000 CPS, and ± 5 db from 20 CPS to 5,000 CPS with proper baffling. Voice coil dia. 2"; impedance 8 ohms. Finished in beautiful brown enamel. Has 4-way binding posts. Shpg. wt., 13 1/4 lbs. Cone resonance 45 cycles.

21 N 4719W

Net 23.95

12" HI-FI WOOFER WITH 2 LB. MAGNET



22⁹⁵

- 30 Watts
- 20-2500 Cps
- 2" Voice Coil Diameter
- Cone Resonance at 30 Cps

This sturdily constructed 12" Woofer is rated at a full 30 watts audio power. Frequency response from 20 to 2500 cps with the speaker resonant frequency at 30 cps. Heavy 2 lb. Alnico V magnet and 2" diameter voice coil. Plated steel frame finished in brown baked enamel. Has 4 way binding posts. 8 ohm impedance. Shpg. wt., 10 1/2 lbs.

21 N 4720

Net 22.95

12" HI-FI WOOFER WITH 1 1/4 LB. MAGNET



15⁵⁰

- 25 Watt Power Capacity
- Response 30-9,000 Cps
- 1 1/2" Voice Coil Diameter
- Resonance 50 Cps

Ideal for assembling 2- and 3-way speaker systems at a budget price. Enclosed magnet structure — completely dust-proof. Compliance of outer cone and inner spider carefully calculated for best bass response. 1 1/4 lb. ceramic magnet, 8 ohm impedance. Has 4-Way binding posts. Cone Resonance 50 cycles. Shpg. wt., 8 lbs.

21 N 4716

Net 15.50

8 INCH WOOFER



10⁶⁵

- Rated 25 Watts
- 1 1/4 lb. Ceramic Magnet
- 35 to 7500 cps
- Free Edge Cone
- High Compliance

This 8" woofer is an ideal choice for use in 2 or 3 way speaker systems where space is of great importance. The 1 1/4 lb. ceramic magnet insures clean, boom-free response in the low end. A free-edge, high compliance cone is utilized for high efficiency. Power handling capacity is 25 watts peak. Voice coil diameter 1 1/2". Cone resonance is 50 cycles. 8 ohm impedance. Has 4-way binding posts for simple installation. Shpg. wt., 6 lbs.

21 N 4721

Net 10.65

8" MID-RANGE SPEAKER



6⁵⁰

- 25 Watts Capacity
- Response 350-14,000 cps
- Enclosed Back

Capable of reproducing virtually undistorted sound from 350 to 14,000 cps, the recommended crossover frequencies are at 350 cps and 5,000 cps. Power handling capacity: 25 watts. Cone Resonance: 150 cps. Impedance: 8 ohms. 10 oz. ceramic magnet. Voice coil diameter: 1". Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 4 1/2 lbs.

21 N 4718

Net 6.50

Prices On This Page May Be Raised April 1st Due To New Excise Tax

Budget Priced Hi-Fi Speakers

ROYAL DANISH 12" DUAL CONE SPEAKER

795

- Frequency Response 45 to 14,000 cps
- 1" Diameter Voice Coil
- High Flux Density



You will be pleasantly surprised at the quality of this fine speaker which Lafayette brings you at this low price. An exclusive, special formula cone rim treatment eliminates cone rim resonance and distortion. Overall depth, 5 3/4". Completely enclosed. 1" diameter voice coil with an impedance of 8 ohms. Shpg. wt., 6 lbs. Imported.

21 N 7101 Net 7.95

LAFAYETTE 6"x9" WIDE RANGE SPEAKER

495


- High Sensitivity Magnetic Circuit
- 55 to 14,000 cps
- Space Saver Construction



This hi-fi extended range speaker is definitely a must for add-on stereo application and lends itself to many new applications such as adding hi-fi to autos, TV, radio sets, and also where space limitations are paramount. It has an outside diameter of 6 1/2 x 9 3/4"; Mtg. hole dimensions are 4 5/8 x 6 3/8"; Depth is 3 1/2". Has 4-way binding posts. 21 N 4709 Shpg. wt., 2 lbs Net 4.95

LAFAYETTE LOW COST HI-FI TWEETER

225



- Frequency Response 3,000-16,000 Cps.

Reproduces high frequencies without losing clarity and volume. Even sound dispersion is insured by use of a round cone. Metal cased with completely sealed rear housing. Frequency response 3,000-16,000 cps. Diameter 2 3/4 inches. Depth 1 3/4 inches. Voice coil impedance 8 ohms. Shpg. wt., 1 lb. Imported.

99 N 0117 Net 2.25

6 1/2" COAXIAL HI-FI SPEAKER

- Overall Response 50-16,000 Cps.
- Space Saving & Economical For Stereo
- Built-in L C Network
- Large, Heavy Magnets

695

An excellent speaker with all the best features of coaxial design. 6 1/2" woofer is equipped with large, heavy magnet for maximum efficiency and low distortion. 2" tweeter is a separate speaker coaxially mounted in a housing which completely seals off back radiation. Voice coil impedance, 8 ohms. Requires 5 1/2" diam. cutout. Size is 6 1/2" diam., 3 3/4" deep. Shpg. wt., 3 1/2 lbs. Imported.

99 N 0028 6 1/2" Coaxial Speaker Net 6.95
2 for Stereo Net 12.95



6 1/2" LAFAYETTE THINLINE SPEAKER

495

- Rigid Die-Cast Frame
- Ideal for Economy Music Systems or Extension Speaker Use



Low-cost, 3-way, full-range speaker with 3 diaphragms performing as woofer, mid-range and tweeter. Its small size, only 2" deep, makes it excellent for use in a wide variety of space-saving applications. Frequency response, 75-12,000 cps. Power handling capacity, 3 watts of program material. Impedance, 8 ohms. Shpg. wt., 2 1/2 lbs. Imported.

99 N 0031 Net 4.95

6" MID-RANGE SPEAKER

525

- 4.8 oz. Ceramic Magnet
- Freq. Response 700-7000 cps

An excellent mid-range direct-radiator type speaker for installation in 3-way or 4-way speaker systems. Gives clean, distortion-free reproduction at rated power. Features closed back to eliminate interaction with sound waves generated from other speakers in the same enclosure. Rated power handling capacity: 10 watts. Frequency response from 700 to 7000 cps. 4.8 oz. Ceramic Magnet. Voice coil diameter 3/4". Impedance: 8 ohms. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 3 lbs.

21 N 4706 Net 5.25



LAFAYETTE COMPRESSION TWEETER

995

- 1500 to 20,000 Cycles Response
- Handles 20 Watts of Power
- Phasing Plug for Uniform Sound Dispersion
- Die-Cast Aluminum Construction
- High Efficiency



This unit offers amazing clarity and brilliance of sound. Built-in basing plug insures uniform sound output. Low end cut-off 1500 cycles; high range extends to 20,000 cycles. Handles up to 20 watts of power. Recommended crossover frequency 2500 cycles or higher. Dimensions: 5 1/4" long, mounts in 3 1/8" dia. hole. Impedance 16 ohms. Imported. Shpg. wt., 2 lbs.

99 N 6250 Net 9.95

2 AND 3-WAY L/C CROSSOVER NETWORK

1495

- 4 crossover frequencies: 350, 700, 2000, 3000, 5000 cycles
- 6 crossover combinations
- Built-in brilliance and presence controls

This versatile unit can be used either as a 2-way or 3-way 6 db per octave network. For 8-16 ohm speakers. Suitable for mounting inside enclosure or leaving out in the open. Brilliance and Presence controls — are mounted on the front panel. If desired, these level controls may be removed, escutcheon plate, for external mounting; controls are wired with 3-foot long leads. Shpg. wt., 6 lbs. Imported.

99 N 0022 Net 14.95



LAFAYETTE 2-WAY CROSSOVER NETWORK

795

- Adjusts to Either 2500 or 5000 cps Crossover Frequency


Has a built-in continuously variable high-frequency "Brilliance" level control. Control has a 2 1/2 ft. cable to mount on rear or side of speaker cabinet, and a long shaft for thick wood panels. For use with 8-16 ohm speakers. Easily accessible screw terminals. Metal case 5 1/8 x 2 3/8 x 2 3/8" D. Shpg. wt., 5 lbs. Imported.

99 N 0021 Net 7.95



Popular-Priced LAFAYETTE Speakers,

LAFAYETTE 3-WAY 12 INCH "SLENDER-LINE" HI-FI SPEAKER



ONLY
19⁹⁵
2 for 38.95


- Only 3 1/2" depth—can be mounted in virtually any "thin-type" cabinet
- Special low-resonance woofer cone
- Independent horn type super tweeter for wide dispersion of highs
- Frequency response 30-18,000 cps
- Heavy duty die cast frame
- Complete with brilliance level control.

This new superb 3-way "slender-line" 12" high fidelity speaker incorporates the latest advanced techniques in speaker design. Constructed to Lafayette rigid specifications, the Lafayette SK-260 is an unbelievable value offering rich, brilliant sound reproduction. Engineered to faithfully reproduce the complete audio spectrum from 30 to 18,000 cps, this fine speaker is but 3 1/2" in depth, can be mounted in virtually any thin-type cabinet or shelf type enclosure. Incorporates a special low-resonance woofer cone, for clean natural bass response without boom, mechanical; mid-range, and independent horn-type tweeter for wide dispersion of highs. Offers full-bodied mid-range and quality high frequency response enabling you to hear all the fine transients and high notes of the higher frequencies. Features heavy duty die-cast frame. Built-in mechanical crossover at 1,800 cps and electrical crossover at 5,000 cps. Power handling capacity 20 watts, peak 40 watts. Complete with brilliance level control. Impedance 8 ohms. Shpg. wt., 10 lbs. Imported.

99 N 0029

Net 19.95 2 for 38.95

LAFAYETTE 2-WAY 12-INCH "SLENDER-LINE" HI-FI SPEAKER



ONLY
13⁹⁵
2 for 26.95

- Dual Cone Construction
- Heavy Duty Magnet
- 2" Edge-wound "Voice Coil"
- Frequency Response: 20-13,000 cps
- Shallow Depth for Custom Mounting

Here is a high quality, low cost, dual-cone speaker featuring outstanding sound and a heavy-duty die cast frame to permanently center the sound reproducing elements. This insures low distortion for the life time of the speaker. The shallow frame design of the SK-255 permits simple custom installation in walls, "thin-type" enclosures, ready-made consoles or wall baffle extension speaker use.

The big 12" high compliance woofer delivers plenty of solid bass while the separate high frequency whizzer cone handles the middle and high frequencies clearly to the upper audio spectrum. Other features are 2" edgewound voice coil assembly and a built-in mechanical crossover at 1800 cycles. Has convenient binding post terminals for fast, easy connections to any amplifier.

SPECIFICATIONS—Frequency Response: 20-13,000 cycles. Power Handling Capacity: 20 watts, 40 watts peak. Voice Coil Impedance: 8 ohms. Cone resonance: 45 cps \pm 10 cps. Voice Coil Diameter: 2 inches. Size: 12 1/4" diameter x 3 1/2" deep. Shpg. wt., 7 lbs. Imported.

99 N 0030

Net 13.95 2 for 26.95

ECONOMY 8" COAXIAL HI-FI SPEAKER



- Perfect For Stereo
- Response 70-12,000 cps
- Built-in Crossover
- 10 Watt Rating


5⁹⁵

A fine high fidelity speaker for budget-minded hi-fi enthusiasts. Ideal in economy system or as extension speaker for music in other rooms. Can also be used to improve sound of inexpensive hi-fi sets. Features a built-in electrical crossover to distribute the high and low frequencies to the two elements. It is rated at 10 watts with a frequency response of 70-12,000 cps. Utilizes a gasket sealed 3 oz. ceramic magnet. Rigid, non-resonant frame and highly efficient, specially-treated cone contribute to its fine performance and long life. Voice coil diameter: 3/4". Impedance: 8 ohms. Shpg. wt., 3 lbs.

21 N 4717

Net 5.95

NEW LAFAYETTE COMPRESSION HORN TWEETER



7⁸⁸

- Built-in 2,000 cps Electrical Crossover
- Frequency Range 2,000 to 18,000 cps
- Handles 30 Watts of Power
- Die Cast Aluminum Construction

This high-efficiency, wide-angle compression horn-type tweeter offers outstanding high-frequency response for superb music reproduction. Features a built-in, pre-wired electrical crossover at 2,000 cps that adds "brilliance" to your present system. Low end cut-off 2,000 cycles; high range extends to 18,000 cycles. Handles up to 30 watts of power and, in conjunction with any 8", 12" or 15" speaker, gives a full range speaker system. Engineered for continuous duty operation; constructed of aluminum, die-cast under high pressure for lasting alignment with baked-on lacquer finish. Voice coil diameter, 3/4"; magnet weight, 1.4 oz.; impedance 8 ohms. Overall size: 7 1/4"L, 3"W, 6 1/4"D. Shpg. wt., 1 3/4 lbs.

21 N 4723

Net 7.88

LAFAYETTE-GOODMAN "DOME LENS" ULTRA HIGH FREQUENCY COMPRESSION TWEETER



8⁹⁵

- Omni-directional compression tweeter for 2, 3, and 4 way systems
- Handles up to 30 watts of power.

Offers 360° sound dispersion, quality high frequency response of sharp transients. Capable of handling frequencies from 5000 cps. to beyond the limits of human audibility. Has built in crossover at 5000 cps. Voice coil impedance 8-16 ohms. Dimensions: 4x2 1/2" length. Shpg. wt., 1 1/2 lbs. Imported from England.

21 N 0131


Net 8.95

Tweeters and Speaker Systems

LAFAYETTE "MINUETTE"® HIGH-FIDELITY SPEAKER SYSTEM



12⁵⁰
23⁵⁰
TWO FOR
STEREO




Room Filling Music
Everywhere in Your Home!

- Shelf Size—8¼Dx15¼Lx5¾"H
- Genuine Walnut Finish on 4 Sides
- Complete with 6' Extension Cable and Phone Plug

The Lafayette "Minuette" Hi-Fi Speaker System will bring music to any room in your home — and for a remarkably low cost. Designed for use where space is at a premium — ideal for the small apartment or listening area. Expand your stereo system to other areas of your home . . . easily used in the den, kitchen, patio or bedroom. Employs a specially designed 5x7" speaker in a rear loaded reflex type enclosure. Provides an exceptionally fine musical quality yet measures only 8¼Dx15¼Hx5¾"—small enough to fit anywhere. Superb Walnut finish on 4 sides allows placing speaker horizontally or vertically. Frequency Response 100-12,000 cps. Impedance 8 ohms. Rated at 10 watts. Supplied with 6 ft. of extension cable and phone plug. Shpg. wt., 5½ lbs. Imported

99 N 0042 Walnut	Net 12.50
Set of two for Stereo—Save 1.50	Net 23.50
99 N 0038 Oiled Walnut	Net 13.95
Set of two for Stereo—Save 1.40	Net 26.50

DELUXE LAFAYETTE REVERBERATION AMPLIFIER/SPEAKER SYSTEM



59⁵⁰
\$5 monthly
WORKS WITH



- Excellent for Mono or Stereo Systems
- Adds a Delightful Dimension to Sound Without Affecting Fidelity
- Completely Self-Contained System with Amplifier and Speaker.

A self-contained reverberation amplifier/speaker system with built-in power supply, that hooks into any existing stereophonic or monaural component sound system, FM or AM radio, TV set, tape recorder or electric organ to add acoustic dimension to your listening area. Controls: 3-position selector switch for reverb, stereo center channel, crystal phono functions plus push-pull on-off/volume. Output power is 3 watts into an 8" PM speaker. Inputs: stereo high level, stereo low level, mono crystal phono. For 110-117 volts, 50-60 cps AC. Oiled walnut finished cabinet measures 21½Wx11½Hx 8¼"D. Shpg. wt., 23 lbs. Imported.

99 N 0041WX Net 59.50

ECONOMY 3-WAY SPEAKER SYSTEM KIT

- Ideal for the "do-it-yourself" audio Enthusiast
- Features: Matched 8" woofer, 5" mid range, and 2" Tweeter.

32⁷⁵
\$5 Monthly

A 3-way speaker system, consisting of an 8" Woofer, with 10.7 oz. magnet, 5" mid-range, 2" tweeter, and crossover network completely wired and mounted on a front panel and covered with attractive grey grill cloth. Specifications: Frequency range—35-18,000 cps. Crossover frequency 4,000 cps. Impedance 8 ohms. Front panel. Size: 20x8½" Power rating 15 watts. Shpg. wt., 10 lbs.

21 N 7102W Net 32.75

FIBRE GLASS INSULATION




Excellent sound absorbing material. For lining interiors of speaker cabinets, consoles, phonos, TV's, etc. 9 sq. ft., 1" thick with glue and applicator. Shpg. wt., 1 lb.

20 N 8001 Net 1.49

DELUXE BASS REFLEX KIT: 20 square feet, 16x16x 1" Bonded fibre-glass. Shpg. wt., 2 lbs. Net 2.70
20 N 8002

JENSEN speakers + UNIVERSAL WOODCRAFTERS cabinet + LAFAYETTE low prices



38⁹⁵
\$5.00 Monthly



- Heavy 7-Ply Furniture Veneer Cabinet
- Fiberglass-loaded Cabinet for Better Bass Response
- Jensen 12" Woofer, 8" Midrange Driver, 3½" Enclosed Tweeter

Now you can get outstanding speaker performance at a low, low Lafayette price—The Uni-Voice hi-fi speaker system is a thrilling blend of fully integrated, unified 3-speaker systems engineered by Jensen with specially developed Jensen components, with cabinetry by Universal Woodcrafters. Contains special 12" woofer; 8" midrange driver independently pneumatically damped in its own hermetically enclosed acoustic surroundings, completely separated from woofer cavity; 3½" fully enclosed, independently baffled tweeter. Woofer electric crossover at 600 cycles, midrange electric crossover at 2000 cycles. Impedance 8 ohms. Response: 35-18,000 cycles. Walnut finish on 4 sides. Speaker grille completely framed with brass inlay. 24Wx14½Hx13"D.

21 N 8401WX Walnut finish. Shpg. wt., 32 lbs. Net 38.95



SONOCASTER PORTABLE OUTDOOR HI-FI SPEAKER



28²²



- Rugged All-Weather Housing
- Produces Fine, Full Range Sound
- Compact—Lightweight

An outdoor speaker with full-sized sound—connects to any portable radio, TV, console or component hi-fi system. Small and light enough to go anywhere—Uses special, high-efficiency 8 inch coaxial speaker for true hi-fi sound. Attractive housing is made of unbreakable plastic and fully weatherproofed—Response: 70-13,000 cps. Power Handling: 30 watts, peak. Impedance: 8 ohms. Color: Dune Beige. Size 16¾Hx 17Wx5¾"D. Shpg. wt., 10 lbs.

21 N 3021 Net 28.22

The Famous LAFAYETTE ELIPTOFLEX® Speaker Cabinet

Ready-To-Finish, Easy-To-Assemble Kit Form



HERE IS THE
U.S. PATENT NO. 3089562
ELIPTOFLEX
COMPLETELY
ASSEMBLED



EASY
TO ASSEMBLE!

A Bookshelf-Size Enclosure Engineered by Lafayette Research—ASSEMBLE IT, FINISH IT, and SAVE!

- The Same Speaker Cabinet That Set A New Standard of Excellence
- Utilizes the Full Advantages of Efficient 12" Speaker Performance
- Provides Optimum Performance Without Use of Expensive Large Wattage Amplifiers
- 3 Sides Prepared for Finishing
- For Horizontal Placement

This is the same Lafayette Eliptoflex Speaker Cabinet that set a new standard of speaker enclosure excellence—now available in ready-to-finish easy-to-assemble kit form. The easy-to-follow instruction sheet, with large pictures, guide you step-by-step for easy assembling. When completely assembled and highlighted with your favorite finish—you'll be amazed at the professional looking results.

You'll also appreciate the engineering excellence of this speaker cabinet. The Eliptoflex utilizes a unique elliptical port which broadens frequency response and provides better transient response. A specially engineered diffracting ring eliminates cancel-

lation effects between front and rear radiation. The "Eliptoflex" achieves a degree of natural smoothness, low distortion and rich robust bass. Due to its highly efficient design characteristics, costly high wattage amplification not required. The Kit is available in either ready-to-finish birch or in ready-to-finish genuine walnut veneer. Assembled the "Eliptoflex" measures 14Hx23⁷/₈Wx13¹/₄"D. Shpg. wt., 24 lbs.

20 N 0110WX Ready-To-Finish Kit in Birch Net 21.50
Ready-To-Finish Kit with Walnut Veneered Acoustically Correct Flake Core Net 24.50
20 N 0111WX Net 24.50

AS LOW AS
21⁵⁰

LAFAYETTE HI-FI COMPONENT SHELF/CONSOLE

Decorator Inspired!!



DIMENSIONS

Top Shelf 11"Hx16"Dx31¹/₂"W
Lower Shelf 15¹/₄"Hx15¹/₂"Dx31¹/₂"W

Speaker Compartments 27"Hx16"Dx14³/₄"W
Overall Dimensions 33³/₄"Hx16"Dx62¹/₂"W (including 5" legs)



47⁵⁰

\$5 monthly
OILED
WALNUT FINISH

28⁹⁵

UNFINISHED

- Room for All Your Components
- Sturdy 3/4" Wood Non-Warp Construction
- Holds Over 150 Records
- An Attractive Addition to Any Home—Place Along A Wall or Use As A Room Divider

The ideal answer to your Hi-Fi Stereo component placement problems—measures 62¹/₂" long, yet holds over 150 records with more than enough room for your amplifier, turntable or record changer, tape deck and stereo speakers. Veneered rear panel, finished on both sides, permits its use as a room divider. Speaker compartments spaced to achieve proper separation for stereo. Shipped knocked down—Assembles in minutes. Shpg. wt., 65 lbs.



Oiled Walnut Finish on Genuine Walnut Veneered Flake Core
20 N 0114WX Net 47.50
20 N 0115WX Unfinished Flake Board Net 28.95

See Page 3 for Lafayette Addresses and Store Hours

LAFAYETTE Universal Hi-Fi Bass Reflex Enclosure Kits

Easy-To-Assemble Hi-Fi Enclosure Kits

- Easy to Assemble
- ¾" White Birch
- Precision-Cut — Fits Together Smoothly
- Ideal for Single Wide Range, 2-Way or 3-Way Speaker Systems
- Highboy or Lowboy Style



LAFAYETTE OILED WALNUT FINISHING KIT



Use this professional walnut oiling kit to achieve a beautiful oil finish on all unfinished walnut furniture. Materials are identical to those used by professional finishers; kit contains walnut oiling mixture, walnut paste wax, sandpaper and instructions. Shpg. wt., 2 lbs. 13 N 1801 Net 2.69
DILEO WALNUT STAIN FOR LIGHT WOODS. To be used with above for an attractive walnut-colored finish on light-colored woods, such as birch, etc. 13 N 1802 Shpg. wt., 1 lb. Net .89

29⁹⁵

All pieces of these carefully designed bass reflex high fidelity speaker enclosures are accurately precut of ¾" Plywood to fit snugly together and eliminate spurious resonances. Surface is white birch veneer. Front panels have picture-frame moulding and plastic acoustic grilles to blend with any finish and room decor. Tapered offset legs are protected by brass ferrules. Acoustic lining material prevents reverberation and cabinet resonance. Cutouts are provided for 15" speaker plus adapter for 12", 8½" or 8" midrange plus adapter for 5" and blank wood block if no midrange speaker is used; cutout with adapter boards for 2 sizes of rectangular and 3 sizes of round compression horn tweeters plus blank block if no tweeter used. Kits are supplied unfinished, smoothly sanded and ready for finishing. The lowboy-style cabinet dimensions are (less legs) 28½"Wx23½"Hx16¾"D; legs are 7" high. Highboy has same dimensions with height and width interchanged. Instructions, all parts, hardware, and grille are included. Shpg. wt., 54 lbs.

20 N 0121WX Unfinished Highboy Enclosure Kit Net 29.95
 20 N 0122WX Unfinished Lowboy Enclosure Kit Net 29.95

LAFAYETTE BASS REFLEX SPEAKER BOOKSHELF ENCLOSURE KIT FOR 8" OR 6" SPEAKERS

AS LOW AS

10⁹⁵


Assembles In Less Than 30 Minutes!

- Precision Cut — Fits Together Smoothly
- Adapts for 8" or 6" Speakers
- Easy to Follow Pictorial Instructions
- Versatile — Use as Floor or Bookshelf Enclosure

BUILD IT YOURSELF . . . Expensive woodworking equipment isn't needed—each cabinet component has been precision cut and fits together perfectly. There's nothing else to buy . . . acoustic padding, grill cloth and hardware are provided. Use any 8" or 6" speaker; the mounting board has been precut for 8" speakers and an adapter is supplied for 6" speakers.

Designed for horizontal placement in a bookshelf, along a wall, etc. Constructed of veneers on 3 sides with handsome picture frame moulding. (See Lafayette's professional finishing kits). Dimensions: 23x9½x11". Available in either birch or walnut unfinished veneers.

20 N 0112WX Birch Kit, Shpg. wt., 15 lbs. Net 10.95
 20 N 0113WX Walnut Kit Net 13.95
 Speakers for Lafayette Cabinet Kit (above), Lafayette 8" Duo-Cone Speaker; 40-16,000 cps response. 99 N 0027 Shpg. wt., 5½ lbs. Net 9.95
 Lafayette 6½" Coaxial Speaker; 50-16,000 cps response. 99 N 0028 Shpg. wt., 3½ lbs. Net 6.95



Not ½" But ¾" Furniture Grade White Birch Plywood or Walnut Veneer on Flaked Core Plywood

LAFAYETTE Selected Electric Guitars

"VALUE" ELECTRIC GUITAR

34⁵⁰

- Magnetic Pick-up
- Individual Adjusting Screws
- Individual Tone and Volume Controls



The perfect instrument for the budget-minded musician be he beginner or advanced. Features double cut-away solid body construction for that true "twangy" electric guitar sound and rugged dependability. Other features are a sensitive magnetic pick-up with individual adjusting screws, individual tone and volume controls, 20 frets with 6 marked positions. Comes complete with connecting cord with standard plugs on each end. Deep mahogany color with sunburst. Shpg. wt., 12 lbs. Imported
99 N 9022WX Net 34.50

GUITAR OUTFIT: Includes 99 N 9022WX guitar, 13 N 8718 amplifier, and 13 N 8712WX case. Shpg. wt., 35 lbs.


13 N 9003WX Net 65.50
CARRYING CASE ONLY. Shpg. wt., 3 lbs.
13 N 8712WX Net 8.95

LAFAYETTE® SOLID DOUBLE CUTAWAY — DUAL PICKUP ELECTRIC GUITAR

49⁹⁵

with Tremolo Tailpiece

- 2 Adjustable Pickups
- Individual Tone Controls
 - Individual Volume Controls
 - Individual Rocker Switches
- Solid Mahogany Body—3 Piece Laminated Neck



Treat yourself to this high quality guitar. A real beauty to both eye and ear. Elegant double cutaway design features tremolo tailpiece and detachable steel reinforced warp-proof neck. Solid Mahogany Gleaming hand rubbed finish body. Rosewood fingerboard with 8 white inlaid markers and 20 frets. 2 microphone pickups each adjustable for tone and volume balance. Separate tone and volume controls. Sensitive pickups have individual adjustment screws for each string. Chrome plated guard plate. Highly polished shaded mahogany finish. Size 39Lx12Wx 11¼"D. Less case. Shpg. wt., 10 lbs. Imported.
99 N 9060WX Net 49.95

Carrying case
13 N 8713WX Shpg. wt., 3 lbs. Net 8.95

GUITAR—AMPLIFIER OUTFIT

Consists of above Guitar, 5 watt amplifier with 8" speaker, tone and volume controls and carrying case. Shpg. wt., 35 lbs.
13 N 9004WX Net 79.95

LAFAYETTE PROFESSIONAL CUTAWAY ELECTRIC GUITAR

59⁹⁵

- Auditorium Size—42½"x17½"
- Dual Adjustable Pickups
- Five Controls—including Solo/Rhythm Switch
- Laminated Arched Top and Back



Grand auditorium size—true professional design—engineered for professional performance. Laminated maple neck with oval rosewood fingerboard. Six large inlaid position markers and nickel silver frets. White, pin-stripped celluloid binding on top and back edges. Nickel plated hardware, deluxe machine heads, two sensitive pickups with individually adjustable pole pieces. Permits full range of individual emphasis and overall balanced response. Five controls permit choice of units, vary tone and volume, select between bridge pick-up for solo and forward pick-up for rhythm work. Arched laminated top and back in a shaded walnut finish with golden sunburst. Size 42½x17½x3½". Less case. Shpg. wt., 18 lbs. Imported.
99 N 9058WX Net 59.95

GUITAR—AMPLIFIER COMBINATION

Consists of 99 N 9058WX guitar, 13-0130WX 20-watt amplifier with Tremolo foot switch. Shpg. wt., 50 lbs.
13 N 9009WX Net 129.95

NEW! The "BIG BEAT".

79⁹⁵

Fabulous Tone • Fabulous Quality • Fast Action

- Double Cut Away Solid Mahogany Body
- 3 Piece Laminated Neck with Adjustable Truss Rods
- Rosewood Fingerboard With 10 Position Markers
- Individual Machines With White Markers
- Precision Fretted-Uniform "FEEL"

**Exclusive with Lafayette,
 Built-in — Completely
 Transistorized Amplifier
 and Speaker!**



An Exceptionally fine guitar with a "Show-Stopper" finish. PLUS a built in specially designed and engineered miniature transistorized amplifier and speaker! A new concept incorporating all the fine professional features: lucid, sparkling tone; easy action; up to date styling; sleek, slim, double cut-away design; powerful magnetic pick-up; separate tone and volume controls; sparkling hand rubbed finish; blonde maple neck, hand rubbed and polished; auditorium size, 40¼"x13½". The self contained amplifier affords perfect portability with the tone range and volume of "stationary" amplifier units. May also be used with any external guitar amplifier. Equipped with external jack and cord. Shpg. wt., 15 lbs.

99 N 8087WX 79.95
 Batteries for above (2 required)
99 N 6021 Net ea. .21


LAFAYETTE Offers Outstanding Musical Instruments

LAFAYETTE 20-WATT TREMOLO MUSIC AMPLIFIER

89⁵⁰

\$5 Monthly

- 20-Watt High-Fidelity Amplifier
- Built-in Heavy-Duty 12" Jensen Speaker
- 2 Separate Channels with Separate Volume and Tone Controls
- Complete With Tremelo Foot Switch



This Lafayette amplifier gives faithful reproduction of every note and tone played with minimum hum for undistorted sound. The built-in, heavy-duty efficient 12" Jensen speaker plus the 20-watts of music power gives full "big tone" performance. Dynamic 6-tube circuit offers outstanding dependability. Features a remote control foot switch for colorful tremelo — tremelo has 2 controls for added flexibility. Two separate channels with separate volume and tone controls for each channel. Other outstanding features include four inputs (two inputs per channel); on/off standby switch. Convenient carrying handle lets you 'tote' the amplifier most anywhere. Overall cabinet size measures 20³/₄" wide, 18" high, 10¹/₂" deep.

13 N 0130WX Shpg. wt., 30 lbs.

Net 89.50

AMPLIVOX™ ALL-TRANSISTOR SPEAKER-AMPLIFIER

- Cabinet Coupled Bass Driver
- 2 Speakers For Full Instrument Range
- Molded Royalite Case

A new 5-watt all transistorized audio amplifier. Features 2 Hi-Fi speakers with cabinet coupled bass driver for full instrument range. Three instrument inputs allows use with bass as well as standard guitar or accordion. Features advanced, up-to-date solid state circuitry which assures utmost reliability. No warmup necessary; ready to use instantly. Custom designed cabinet. Separate volume and tone controls. Acoustical case of handsome molded Royalite (used in finest luggage) for durability. Controls are located at the top for convenient adjustment. 117V AC powered. Size: 10x14x5". Shpg. wt., 8 lbs.

13 N 8201WX

Net 34.00



34⁰⁰ \$5 Monthly

5-WATT SPEAKER-AMPLIFIER WITH TREMOLO

- Front-Mounted Controls
- UL Approved

39⁹⁵

\$5 Monthly

A complete 5-watt amplifier with exciting tremelo control. UL approved. Has Hi-Fi speaker for faithful sound reproduction. One speed and one strength control for tremelo. Case covered with silver and tan tweed keratol. Control panel in black and gold with large matching black and gold control knobs. For 115V 60 cps, AC. Size: 19x16x6". Shpg. wt., 18 lbs.


13 N 8719WX

Net 39.95

FOOT SWITCH to remotely control the tremelo in the amplifier. Equipped with cable terminated in standard phone plug to fit corresponding jack on amplifier. Shpg. wt., 1¹/₂ lbs. Imported

99 N 9043

Net 5.95



5-WATT SPEAKER AMPLIFIER


29⁹⁵

- Our Lowest-Priced Music Amplifier
- Big 8" Speaker
- Attractive 2-Tone Cabinet

Features 8" speaker for faithful reproduction. Top-mounted control panel has tone and volume control and inputs for three instruments. Three-tube chassis. Housed in 2-tone cabinet with attractive lattice-work grille cloth. Case size: 16Wx6Dx13"H. AC-DC 60-cycle operation. Shpg. wt., 18 lbs.

13 N 8718WX


Net 29.95



CLASSIC SPANISH GUITAR

24⁵⁰

- Mirror-Bright Violin Finish on Sides and Back
- Traditional Fan-Braced Craftsmanship
- Three-Piece Laminated Neck



Enjoy the warmth of the rich vibrant tone that only a true classic guitar can inspire. Crafted with a fan-braced top of selected white spruce; back, sides and neck of exquisite mahogany brought to a gleaming violin finish. Protective celluloid binding on top edge, back and along neck. Ebony fingerboard with 18 frets and inlaid position markers on side for easier fingering. White button engraved machines; three-piece laminated neck. Overall size 39x14". Shpg. wt., 11 lbs. Imported.

99 N 9086WX

Net 24.50

ROUND HOLE GUITAR MIKE



5⁵⁰

Convert your Spanish guitar or Ukulele into an electric. Single pickup with separate tone and volume controls. Detachable cord 8 ft. long. Shpg. wt., 1 lb. Imported

99 N 4537

Net 5.50

Selected Guitar Valves

TRIPLE PICK-UP DOUBLE-CUTAWAY ELECTRIC GUITAR COMBINATION



GUITAR ONLY
109⁹⁵
\$5 MONTHLY

A 3-piece outfit with Triple-pickup professional guitar in double-cutaway style with solid mahogany body and Contour cut-back. Maple reinforced neck with adjustable steel rod and 2 parallel truss rods. Oval shaped white celluloid bound rosewood fingerboard, 20 frets and 7 inlaid pearl markers. Adjustable bridge; chrome plated tremolo tailpiece. 3 magnetic pickups, individual adjustments, 3 volume, 1 tone control, selector switch. 39x13 1/2" with case. Lafayette 20-watt music amplifier with heavy-duty 12" Jensen speaker, 4 inputs, separate tone & volume controls, tremolo foot switch. Shpg. wt., 48 lbs. Imported.

Guitar, case & Amplifier
13 N 9011WXM Net 184.50

Guitar only, Shpg. wt., 15 lbs.
13 N 8716WX Net 109.95

Case only, Shpg. wt., 3 lbs.
13 N 8717WX Net 9.95

4 PICK-UP GUITAR. Same as Triple Pick-up Guitar above except has 4 pick-ups and separate control panel with 6 selector switches. Shpg. wt., 16 lbs.

13 N 8732WX Net 129.95


Case for 4 Pick-up Guitar.

13 N 8733WX Shpg. wt., 3 1/2 lbs. Net 9.95

4 Pick-up Guitar, Case and Amplifier.

13 N 9012WXM Shpg. wt., 45 lbs Net 199.95

DELUXE DUAL PICKUP GUITAR/AMPLIFIER COMBINATION



SAVE \$23.90
ON COMBINATION

89⁹⁵
\$5 monthly
Guitar
only

An outstanding professional double cutaway guitar in selected mahogany solid body with polished hand rubbed finish. Features reinforced steel neck, oval rosewood fingerboard, 20 frets, inlaid pearl markers. Dual magnetic pickups with individual string adjustment. Controls: 2 volume, 1 tone, 2 selector switches. Chrome plated tremolo tailpiece. 38 1/2 x 12" With guitar carrying case. Also Lafayette 20-watt music amplifier with heavy-duty 12" Jensen speaker, adjustable tremolo, separate volume and tone controls, tremolo foot switch. Shpg. wt., 45 lbs. Imported.

Guitar, Case and Amplifier
13 N 9010WXM Net 164.50

Deluxe Guitar only, Wt. 15 lbs. Net 89.95

13 N 8714WX Net 89.95

Carrying case only, Wt., 3 lbs. Net 8.95

13 N 8715WX Net 8.95

NEW "ARTISTRY" CLASSIC GUITAR



57⁵⁰
\$5 monthly

- Violin Finish Maple
- True Classic Design
- Superior Materials Used Throughout

The "Artistry" classic guitar features two-piece violin finish maple back and sides with narrow grained spruce top. Excellent tonal qualities meet the critical demands of the most discriminating classic guitarist. Fan braced with steel reinforced maple neck. All edges bound with heavy black celluloid. Sound hole is inlaid and bound. Nylon strings are used for ease of positioning and excellence of tone. Utilizes slotted head-piece. Has 19 frets for full coverage. Shpg. wt., 11 lbs.
13 N 8722WX Net 57.50

JUMBO COUNTRY & WESTERN STYLE FOLK GUITAR



49⁹⁵
\$5 monthly

Get full, rich guitar tone for western, country and hootenanny fun. Genuine dark mahogany back and sides; white spruce top. Hardwood 1 3/4" neck. Top and back edges bound with heavy white celluloid. Celluloid bound rosewood fingerboard inlaid with eight pearl position dots. Guard plate, pin bridge; steel reinforced neck. Overall 41"x16". Shpg. wt., 11 lbs.
13 N 8734WX Net 49.95

Carrying case. Shpg. wt., 3 1/2 lbs.

13 N 8735W Net 8.95

ARCHED TOP GUITAR



19⁹⁵

A grand concert size, F hole guitar with glossy shaded mahogany finish on top, back and sides. Shaded mahogany finish neck with steel truss rod. White celluloid-bound ebony finish fingerboard. Has adjustable bridge and nickel-plated adjustable tail-piece. Equipped with heavy gauge shell celluloid pick guard and nickel-plated machines with white buttons. Shpg. wt., 7 lbs.
13 N 8720WX Net 19.95

7 PIECE "ECONOMY" OUTFIT



21⁹⁵

6-piece special guitar outfit with beginner's record course. You get: guitar, guitar bag, record course, 3 guitar picks, extra set of strings, neck cord. Guitar has hardwood body with shaded sunburst finish and steel reinforced neck. White striping around top edge and sound hole. Imported.

Complete Outfit. Shpg. wt., 9 lbs. Net 21.95

13 N 8723WX Net 21.95

Guitar Only, Shpg. wt., 7 lbs. Net 16.88

13 N 8724WX Net 16.88

LAFAYETTE's Outstanding Musical Instruments

14 x 20" single-tension bass drum with permanent-type tom-tom and cymbal holders. 14x5½" snare drum with separate tension flanged hoop, metal snare, professional throw-off. 12x 8" tom-tom with separate tension, flanged hoops. 12" cymbal, drum pedal with adjustable beater and springs, disappearing spurs, snare-drum stand, holder for tom-tom, sticks. Metal parts are highly nickel plated. Bright sparkle finish. Imported. Shpg. wt., 45 lbs.
13 N 8701WX Net 119.95

DRUM COMBO OUTFIT



119⁹⁵
\$6.00 Monthly

Contour-cut solid body and 30-piece adjustable steel reinforced neck. Rosewood fingerboard with 20 frets. Fingerboard is bound with white celluloid. Heavy duty pick-up with individual tuning screw for each string. Guitar has chrome plated individual covered machine heads; heavy chrome plated covered tailpiece hand rest; tone and volume controls and input jack. 45" long 12¾" wide. Polished, hand-rubbed finish. Shpg. wt., 15 lbs. Imported.
Guitar only
13 N 8702WX Net 79.95
Case for above
13 N 8703WX Net 9.95

ELECTRIC BASS



79⁹⁵
\$5 monthly

BARITONE UKULELE



14⁹⁵

Highly polished mahogany back, sides and neck. Top edge bound with white celluloid. Inlaid pearl position markers. White patent pegs, white bone nut. Strings are carefully gauged nylon. Sound hole bound with black and white celluloid and decorated with inlaid purfling. Gives the warmth of tone and ease of response to satisfy any player. Shpg. wt., 4 lbs. Imported.
13 N 8730WX Net 14.95

LONG NECK 5-STRING FOLK BANJO



69⁹⁵
\$5 monthly

Enjoy the bouncing snaps of the traditional folk banjo. Features a heavy aluminum rim with 30 sparkling brackets, and nickel-plated arm rest. The hardwood neck is steel reinforced and has a 25-fret, white celluloid-bound rosewood fingerboard. Has individual tuning pegs, sturdy plastic head, and a bright, nickel-plated tailpiece. The banjo comes complete with a heavy nylon fabric bag with a zippered accessory pocket and zipper closure. Shpg. wt., 10 lbs.
13 N 8736WX Net 69.95

"RENE DUVAL" CLARINET OUTFIT



SALE!
7250

- The Clarinets That Have Contributed to the Building of Bigger Woodwind Sections

Complete outfit consists of the "Rene Duval", quality clarinet made entirely of selected grenadilla wood. Tuned for the key of B_♭, Boehm system, 17 keys, 6 rings. Mouthpiece, cap, ligature, reed, music lyre, swab, grease cup and quality case of plush-lined fabric covered veneer. Shpg. wt., 8 lbs. Imported.
13 N 8710WX Net 72.50

METHOD FOR GUITAR by JOE FAVA

A contemporary approach towards comprehensive mastery of the guitar written in a clear concise manner by a professional. The strings are learned in order of their difficulty with musical arrangements for study. Profusely illustrated.

13 N 8706 Book I (1st position) 40 pages Net 1.49
13 N 8707 Book II (2nd position) 40 pages Net 1.49
13 N 8708 Book III (Higher positions) 48 pgs Net 1.98



HOW TO PLAY THE GUITAR

Famous "Music Minus One" Records!

The easy way to learn all the chords and rhythms on your guitar. Has vocal accompaniment; ballad styles; folk, country and western; rhythm and blues; shuffle beats. Features guitar demonstration and text by George Barnes, spoken commentary by Bob Mersey. Shpg. wt., 1 lb.
24 N 4506 Net 3.50



PROFESSIONAL TUNABLE BONGOS




15⁹⁵

- Calfskin Heads
- Four Tuning Lugs on Each Head

Pure white perfect calfskin heads for best rhythm effect. Sparkling color finish. Sturdy construction with heavy plated hardware. Four tuning-lugs on each bongo. Head sizes: 7¾" and 6½". Overall 7" deep. Complete with Tuning Key. Shpg. wt., 5 lbs. Imported.
13 N 8704 Net 15.95

ELECTRONIC METRONOME



14⁹⁵

- Flashing Baton
- Battery Operated

A smart, modern electronic metronome that uses transistors and is battery operated. Contains no motors or gears, has no tubes to replace, and does not have to be plugged in. Starts operation at the turn of a dial. Features a bright neon light which flashes in synchronization with an audible beat. Dial also provides adjustment for suitable tempo (40-208). Draws so little current that battery lasts almost indefinitely. 6" high and 7" wide at base. Shpg. wt., 2 lbs. Imported.
99 N 9083 Net 14.95

SNARE DRUM



34⁹⁵

\$5 monthly

An exciting snare drum at a low Lafayette price. 14x5½" separate tension snare drum with metal snares, tone modulator, heavy duty throw-off, flanged hoops, rolled rims, nickel plated hardware. Bright sparkle finish. Complete with norwood metal stand, 10" cymbal, sticks, brushes, instruction book. Shpg. wt., 15 lbs. Imported.
13 N 8705WX Net 34.95

LAFAYETTE Public Address Amplifiers And Systems

LAFAYETTE AMPLIFIERS ARE GUARANTEED "FOR ONE FULL YEAR" SEE PAGE 61



11 WATT PA AMPLIFIER MODEL PA-420

31⁵⁰
\$5.00 Monthly

- Separate Volume Controls for Mixing Microphone and Phono
- Two Speaker Output


FEATURES: Provides extensive coverage for store demonstrations, clubs, churches, offices, classrooms, auction sales, entertainment. Separate volume controls permit mixing microphone and phono. 2 speaker output sockets. Housed in attractive rugged cabinet with four rubber bumper feet.

SPECIFICATIONS, TUBES: 12AX7A, 6L6-GC, 6V4/EZ80 (Rect). Power Output: 11 watts (22 watts peak). **FREQUENCY RESPONSE:** 30-20,000 cps \pm 2 db. **OUTPUT IMPEDANCES:** 4, 8, 16 ohms, 25v & 70V lines, Low impedance output for Booster and tape recorder. **CONTROLS:**

Microphone, Phono-Radio (fader) Tone, Power on-off with indicator light. **MISCELLANEOUS:** Fused AC input, AC convenience outlet, 2 speaker sockets, plug supplied for 70 volt outlet and for 4, 8, 16 ohm, 25 volt outlet. Takes Amphenol #75MCIF MIC plug. **POWER CONSUMPTION:** 60 watts at 117 volts, 60 cycles AC. Size: 13 $\frac{1}{2}$ "x 5 $\frac{3}{4}$ "x 9 $\frac{1}{2}$ " D. Shpg. wt., 15 lbs.

44 N 0107WX Net 31.50

44 N 0106W Net 17.95



11 WATT FIXED P.A. SYSTEMS

- Complete Permanent System
- Choice of Crystal or Dynamic Mike

High quality, low cost system engineered for smaller permanent installations. For areas up to 5500 sq. ft. For office, store, garage, small factory paging and music systems. **THE COMPLETE SYSTEMS INCLUDE:** The new Lafayette Model PA-420, 11-watt amplifier complete; your choice of either the Electro-Voice 727 crystal microphone complete with detachable desk stand and 5' cable—or the new Lafayette Model PA-29 weatherproof, blast-proof slim dynamic mike complete with high or low impedance selector switch and detachable swivel-type stand adaptor; 8" heavy duty PM speaker; 35" speaker cable and plug; and attractive polished walnut finish speaker wall baffle. For 110-120 volts, 60 cps AC operation. Shpg. wt., 25 lbs. (Any other microphone may be substituted in all systems, at additional cost. See microphones in index.)

Complete 11-watt Permanent System as described with E-V 727 Crystal Microphone.

44 N 9009WX Shpg. wt., 24 lbs. Net 46.50

Same as above, with Lafayette PA-29 dual impedance dynamic microphone.

44 N 9010WX Shpg. wt., 24 lbs. Net 45.50




Electro-Voice 727

AS LOW AS
45⁵⁰
\$5 monthly

PA-29

LAFAYETTE 27-WATT TRANSISTORIZED PA AMPLIFIER MODEL PA-424 AND SYSTEMS



- Designed for 12V Mobile Operation
- No Warm-up—Instantaneous Operation

57⁵⁰
\$5 monthly

A compact transistorized mobile PA amplifier operating from 12 volt DC. Ideal for Sound trucks, cars, boats or any place where AC power is not available. Small size permits simple installation under dash or in glove compartment. Mounting fixtures supplied. Can also be used with AC power supply (below) for operation on 117 volts, 60 cycles AC.

SPECIFICATIONS

POWER OUTPUT: 27 watts. **FREQUENCY RESPONSE:** 100-10,000 cps. —3 db. **OUTPUT IMPEDANCES:** 4, 8, 16 ohms. **CONTROLS:** Mic volume, Aux-Radio volume, Tone, Power, on-off switch. **TRANSISTORS:** (2) 2N408, (3) 2N669. **POWER CONSUMPTION:** 3.5 amps at 12 volts DC. **INPUTS:** Mic-takes amphenol plug #91-MC4M, Radio-screw terminals, Aux-takes RCA-type phono plug. Size: 6 $\frac{1}{2}$ "x 3 $\frac{1}{2}$ "x 4 $\frac{3}{4}$ " D (less knobs). Supplied with power plug and 7 ft. cable with battery clamps.

44 N 0108WX Shpg. wt., 4 lbs. Net 57.50

AC POWER SUPPLY FOR PA-424

Enables operation of PA-424 on 117 Volts AC, 60 cycles. 12.6 volts output. Shpg. wt., 3 $\frac{1}{4}$ lbs.

44 N 0109W Net 36.95

PHONO TOP FOR DC AMPLIFIER PA-424

With 12 VDC motor for use with transistorized mobile amplifiers (See illustration at right). 4 speeds 16, 33 $\frac{1}{3}$, 45 and 78 RPM. Quality ceramic cartridge with dual stylus. 12x9 $\frac{1}{4}$ x4 $\frac{1}{2}$ ".

44 N 0110W Shpg. wt., 8 lbs. Net 32.40



ELECTRO-VOICE
844 TRUMPET



PA-31



2 UNIVERSITY
PH TRUMPETS
WITH 2 PA-57 DRIVERS

As
Low
As **77⁵⁰**
\$5 monthly



PHONO TOP

27-WATT MOBILE OUTDOOR SYSTEMS with PA-424

Complete 27-watt mobile outdoor system with PA-424 transistor mobile amplifier less phono top; with DC battery cable, plus Electro-Voice 844 trumpet, Lafayette PA-31 dynamic mike, 1-35" speaker cable and necessary connector. Shpg. wt., 19 lbs.

44 N 9011WX Net 77.50

Same as 44 G 9011WX except with 2 Lafayette PA-57 driver units and 2-University PH trumpets, instead of E-V 844, with 2-35" speaker cables. Shpg. wt., 69 lbs.

44 N 9012WX Net 119.50

Same as 44 N 9011WX plus 12 volt phono top. Shpg. wt., 27 lbs.

44 N 9013WX Net 109.90

Same as 44 N 9012WX plus 12 volt phono top. Shpg. wt., 77 lbs.

44 N 9014WX Net 151.90

LAFAYETTE Public Address Amplifiers And Systems

LAFAYETTE GUARANTEE

If you are not satisfied with your Lafayette Sound System you may return it within 30 days for full refund less only transportation charges.

1 YR. AMPLIFIER GUARANTEE. All parts guaranteed against defects in material and workmanship for 1 year. Ship defective part to us prepaid for prompt replacement.

20-WATT PA AMPLIFIER MODEL PA-421



MODEL PA-421

- Capable of Covering 50,000 square feet
- Five Output Impedances
- Two Hi-Fi 7189A Output Tubes
- Wide Range Response
- Attractive Rugged Cabinet

41⁴⁵

\$5 monthly

FEATURES: New improved circuit features ensure top performance. Uses 7189A hi-fi output tubes and designed to give wide-range response. Meets power requirements of chapels, clubs, schools, restaurants and industrial plants. Covers up to 50,000 square feet when used with trumpet type speakers. Chassis equipped with 2-speaker output sockets. Housed in attractive rugged cabinet with four rubber bumper feet.

SPECIFICATIONS. TUBES: (1) 12AX7A, (1) 6AV6, (2) 7189A, (1) 6CA4/EZ81, plus silicon rectifier. **POWER OUTPUT:** 20 watts (40 watts peak). **FREQUENCY RESPONSE:** 30-20,000 ± 1 db. **OUTPUT IMPEDANCES:** 4, 8, 16 ohms, 25V and 70V lines. High impedance output for coupling booster amplifier. Output for tape recorder. **CONTROLS:** Microphone, Phono-Radio (fader), Tone, Power on-off plus indicator light, plus internal bias adjust. **MISCELLANEOUS:** Fused AC input, AC convenience outlet, 2 speaker sockets, Plug supplied for 70 volt outlet and for 4, 8, 16 ohm, 25 volt outlet. Takes Amphenol #75MCF Mic plug. **POWER CONSUMPTION:** 70 watts at 117 volts, 60 cycles AC. Size: 13⁷/₈Wx9¹/₂Dx5³/₄"H. Shpg. wt., 15 lbs.

44 N 0105WX Net 41.45

44 N 0106W 4-SPEED PHONO TOP FOR AMPLIFIER ABOVE Net 17.95

20-WATT PERMANENT SYSTEMS WITH DUAL SPEAKERS

E-V727SR



ATLAS MS-106

PA-31


- Choice of Crystal 3-Way Lavalier or Desk-Stand Mikes
- Two Heavy-Duty 12" Speakers
- Two Polished Walnut Wall Baffles

Excellent for a great many public address, paging and sound reinforcement applications. Speakers and paging horns may be added for wider area coverage. Excellent coverage for audiences up to 2000.

THE COMPLETE PERMANENT SYSTEMS INCLUDE: One 20-watt Model PA-421 amplifier, 2-12" heavy-duty PM 15-watt speakers; 2-35 ft. speaker cables and plugs; 2 polished walnut wooden wall baffles; your choice of either the Electro-Voice 727SR Crystal microphone complete with detachable desk stand for desk, table top or hand use, and with on-off switch or the Lafayette Model PA-31 slim crystal mike with on-off switch, lavalier cord and bracket and complete with 7' cable and connector and removable swivel-type stand adaptor; you also get the popular Atlas MS-10C mike floor stand for a complete, convenient public address "package." For 110-130 volts, 60 cps AC use. Shpg. wt., 57 lbs.

20-watt Permanent System, less Phono Top, complete as described with E-V 727SR microphone
44 N 9001WX Net 75.50
Same as above with Lafayette PA-31 microphone instead of E-V 727SR
44 N 9002WX Net 69.50
Same as 44 N 9002WX, with 4-speed phono top. Shpg. wt., 65 lbs.
44 N 9003WX Net 93.45
Same as 44 N 9002WX with 4-speed phono top. Shpg. wt., 65 lbs.
44 N 9004WX Net 87.45

20-WATT PORTABLE SYSTEMS WITH DUAL SPEAKERS



PA-421



E-V 727SR CRYSTAL MIKE

PA-31 SLIM CRYSTAL 3-WAY MIKE

ATLAS MS-10C MIKE FLOOR STAND

AS LOW AS **78⁵⁰**

\$5 monthly

- Choice of 3-way Lavalier or Desk-Stand Crystal Mikes
- Heavy-Duty 12" Speakers
- Available With 4-Speed Phono Top

A complete 20-watt Dual Speaker (heavy-duty 12" PM Speakers) Portable System, packed with features. Ideal for lectures, auctions, taverns, orchestras; excellent as a rental system. **COMPLETE PORTABLE SYSTEMS, READY TO OPERATE, INCLUDE:** 2-12" heavy-duty PM Speakers rated at 15 watts each; the feature-packed 20-watt Model PA-421 amplifier; your choice of the popular Electro-Voice Model 727SR crystal mike complete with desk stand and 5' cable, detachable from stand for use as a hand mike, with floor-stand coupler and on-off switch or the Lafayette Model PA-31 high impedance slim crystal microphone with 7' cable and connector, removable swivel-type stand adaptor, lavalier cord and bracket, and on-off switch; 2-35' speaker cables and plugs; plus the Atlas MS-10C mike floor stand. Portable carrying case mounts the system conveniently for carrying and for use; covered with high quality dark blue leatherette; size 22¹/₂Hx16¹/₂Wx15"D. For 110-130 volts, 60 cps AC operation. Shpg. wt., 65 lbs. (All systems available with any other microphone at additional cost. For other mikes, see mike pages in index).

20-watt Portable System, less Phono Top, complete as described with E-V 727SR microphone.

44 N 9005WX Net 83.50
Same as above with Lafayette PA-31 lavalier mike instead of E-V 727SR
44 N 9006WX Net 78.50
Same as 44 N 9005WX with 4-speed phono top. Wt., 75 lbs.
44 N 9007WX Net 101.45
Same as 44 G 9006WX with 4-speed phono top. Wt., 75 lbs.
44 N 9008WX Net 96.45

PHONO TOP FOR AMPLIFIERS



AS LOW AS **69⁵⁰**

\$5 monthly

17⁹⁵

4-speed (16, 33¹/₃, 45 and 78 RPM) phono-graph turntable is designed to fit on top of the amplifier and is easily mounted with 2 thumb screws. Takes records up to 12". High quality ceramic pickup-turnover type with dual synthetic sapphire stylus. Power requirements: 15 watts, 117 volts, 60 cps. Durable finish. Size 12x9¹/₄x4¹/₂". Shpg. wt., 8 lbs.

FOR PA-420, PA-421, PA-422 AND PA-423.
44 N 0106W Net 17.95

LAFAYETTE Public Address Amplifiers And Systems

OUR PA AMPLIFIERS ARE GUARANTEED FOR ONE FULL YEAR SEE PAGE 61
LAFAYETTE 35-WATT PA AMPLIFIER MODEL PA-422



52⁴⁵
 \$5 Monthly

The leader of Lafayette's popular new public address line, the PA-422 35 watt PA amplifier performs outstandingly in areas measuring up to 100,000 square feet. Ideal for churches, schools, small theatres, lecture halls, industrial plants, etc. Complete with individual bass and treble controls, and 25 and 70 volt output taps for simple connection up to 70 speakers, and output for coupling booster amplifier.

FEATURES:

POWER OUTPUT: 35 Watts (70 Watts Peak)
 FREQUENCY RESPONSE: 30-20,000 cps.
 INPUTS: 2 Microphone inputs (high impedance);
 1 Microphone input convertible for phono-magnetic cartridge;

1 Phono and 1 Radio on fader control.
CONTROLS: Front: 2 Microphone Volume,
 1 Phono-Radio (fader), 1 Bass;
 1 Treble; 1 Power On-Off switch, indicator light
 Chassis: 1 Phono-Magnetic switch;
 1 Bias Adjust; 1 Hum Adjust;
 1 AC convenience outlet,
 2 speaker sockets

SPEAKER OUTPUTS: 4, 8, 16 ohms, 25 volt line, 70 volt line
BOOSTER and TAPE RECORDER OUTPUT: 1 volt — low impedance
TUBES: 2-12AX7A; 1-12AV6; 2-6L6-GC; 1-5AR4; 1-Silicon rectifier. Complete with 2 speaker plugs. AC Power Consumption: 115 watts at 117 volts, 60 cycles AC.

Size: 17½" Wx6¼" Hx10½" D. Shpg. wt., 25 lbs.
 44 N 0111WX Net 52.45
 4-SPEED PHONO TOP FOR ABOVE
 44 N 0106WX Net 17.95

35-WATT PORTABLE SYSTEMS with DUAL SPEAKERS



112⁵⁰

As little as \$6 Monthly

ATLAS MS-10C FLOOR STAND

ARGONNE AR-3 DUAL IMPEDANCE DYNAMIC MIKE

ELECTRO-VOICE 664 DELUXE CARDIOID DYNAMIC MIKE

- Choice Of Deluxe Dynamic Mikes
- Two 25-Watt Speakers

Large enough for the majority of sound system applications — used in thousands of school auditoriums, churches, theatres, dance halls, dance studios and lecture halls. DUAL SPEAKER 35-WATT PORTABLE SYSTEMS INCLUDE: Lafayette Model PA-422 35-watt amplifier; 2—25-watt PM speakers; 2—35' speaker cables and plugs; choice of Argonne AR-3 All-Purpose Dynamic dual-impedance microphone for hand-held, desk stand or floor stand use, with removable ball-joint desk stand and floor stand adapter and 8' cable; or the deluxe dual-impedance Electro-Voice 664 Cardioid dynamic microphone for use where high-feedback problems exist, on-off switch and 18' cable; the Atlas MS-10C floor mike stand; and the handsomely designed split-type portable carrying case covered in high quality dark blue leatherette. Size: approx. 25½" Hx17½" Wx15" D — provides a secure place for the system components. For 110-130 volts, 60 cps AC operation. Shpg. wt., 75 lbs. less phono; with phono 85 lbs. 35-watt Portable System, Less Phono Top and less MS-10C floor stand, complete with Argonne AR-3 dynamic mike

44 N 9015WXM Net 112.50
 Same as above, with E-V 664 dynamic microphone and MS-10C floor mike stand instead of AR-3 dynamic mike.
 44 N 9016WXM Net 142.50
 44 N 9017WXM Same as 44N9015WXM with 4-speed phono Net 130.45
 44 N 9018WXM Same as 44N9016WXM with 4-speed phono Net 160.45

35-WATT PERMANENT SYSTEMS with DUAL SPEAKERS



AS LOW AS
108⁵⁰
 \$9 Monthly

LAFAYETTE WOOD WALL BAFFLES AND 25-WATT 12" SPEAKERS

E-V 664 CARDIOID DYNAMIC MICROPHONE

ARGONNE AR-3 DYNAMIC MIKE

ATLAS MS-10C FLOOR STAND

- Choice of Deluxe Dynamic Mikes
- 70-ft. of Speaker Cable
- 2—25-Watt Speakers & Wall Baffles for Indoor Systems
- 2—Electro-Voice or University Horns for Outdoor Systems

Designed for large halls, airports, loading platforms, department store music and paging systems, restaurant music, railroad stations, etc. For 110-130 volts, 60 cycles AC. Shpg. wt., 65 lbs. less phono; with phono 73 lbs.

35-WATT PERMANENT INDOOR SYSTEMS

Consists of PA-422, 35-watt amplifier less phono top, 2-12" PM speakers, 2 walnut wood baffles, 2-35' speaker cables and plugs, MS-10C floor mike stand and Argonne AR-3 microphone

44 N 9019WXM Net 108.50
 Same as 44 N 9019WXM except with EV-664 mike
 44 N 9020WXM Net 132.50
 44 N 9021WXM Same as 44N9019WXM plus 4-speed phono Net 126.45
 44 N 9022WXM Same as 44N9020WXM plus 4-speed phono Net 150.45

35-WATT OUTDOOR SYSTEMS

Consists of PA-422 35-watt amplifier less phono top, 2-Lafayette PA-57 driver units and 2 University PH trumpets, 2-35' speaker cables and plugs, and Argonne AR-3 dynamic mike with desk stand. 65 lbs. less phono, 73 lbs. with phono.

44 N 9023WXM Net 122.00
 Same as 44 N 9023WXM except with EV-664 mike and MS-10C floor stand; instead of Argonne AR-3 mike.
 44 N 9024WXM Net 151.00
 Same as 44 N 9023WXM except with 2 EV-848 CDP 30-watt projectors
 44 N 9025WXM Net 140.50
 Same as 44 N 9025WXM except with 2 EV-664 mike and MS-10C floor stand; instead of Argonne AR-3 mike.
 44 N 9026WXM Net 169.50
 44 N 9027WXM Same as 44 N 9023WXM plus 4-speed phono Net 139.95
 44 N 9028WXM Same as 44 N 9024WXM plus 4-speed phono Net 168.95
 44 N 9029WXM Same as 44 N 9025WXM plus 4-speed phono Net 158.45
 44 N 9030WXM Same as 44 N 9026WXM plus 4-speed phono Net 187.45

LAFAYETTE PA Amplifiers And Systems

LAFAYETTE 100-WATT PA AMPLIFIER MODEL PA-423



89⁵⁰


\$8 monthly



PA-43 Mike



Electrovoice 848 CDP Projectors with 30 watt Drivers



University PH Projectors with Lafayette PA-57 Drivers



EV-641 Mike

FEATURES: Conservatively rated for long life in continuous operation. Uses popular high fidelity high power tubes type 6L6-GC and has extremely wide range response. 1-phono, 1 radio and 2-mike inputs with 1 mic input convertible for phono magnetic cartridge. Separate bass and treble tone controls. 25 volt and 70 volt outputs permit easy connection to up to 70 speakers. For groups of up to 10,000 persons or areas up to 200,000 square feet. Moused in attractive, rugged cabinet with four rubber bumper feet. **SPECIFICATIONS:** TUBES: (2) 12AX7A, (1) 12AU7, (4) 6L6-GC, (1) 6CY6, (1) NE-51H plus full-wave bridge silicon rectifier and single diode silicon rectifier. **POWER OUTPUT:** 100 watts (200 watts peak). **FREQUENCY RESPONSE:** 30-20,000 cps ± 2 db. **INPUTS:** 2 mic inputs (high impedance); 1 mic input convertible for phono magnetic cartridge; 1 phono and 1 radio on fader control **OUTPUT IMPEDANCES:** 4, 8, 16 ohms, 25V and 70V lines. **CONTROLS:** MIC-1, MIC-2, Phono-Radio (Fader), Bass, Treble, Power-on-off plus indicator light. Magnetic-Ceramic phono switch (rear). Bias and screen voltage adjust (internal). Takes Amphenol #75MCF Mic plug. **MISCELLANEOUS:** Fused AC input, AC convenience outlet, 2 speaker sockets, plug supplied for 70 volt outlet and for 4, 8, 16 ohm, 25 volt outlet. **POWER CONSUMPTION:** 290 watts at 117 volts, 60 cycles. AC. Size: 17½Wx6½Hx10½"D.

44 N 0112WX Shpg. wt., 35 lbs. Net 89.50
4-SPEED PHONO TOP FOR AMPLIFIER ABOVE Net 17.95
14 N 0106W

100 WATT HI-POWER OUTDOOR SYSTEMS

Lafayette PA-423 100 watt PA amplifier, 3 university PH trumpets with 3 Lafayette PA-57 driver units and Lafayette PA-43 high impedance dynamic microphone with stand adapter, talk switch and 7' cable & plug. Shpg. wt., 100 lbs.

As Low As **179⁵⁰** As

44 N 9031WXM Above with phono top. Shpg. wt., 110 lbs. Net 179.50

44 N 9032WXM Net 197.45

Same as 44 N 9031WXM except with Electro Voice 641 dynamic microphone with 18' cable and E-V 428 "touch-to-talk" desk stand with a DPDT switch instead of PA-43 microphone. Shpg. wt., 100 lbs. Net 197.50

44 N 9033WXM Same as 44 N 9033WXM plus phono top. Shpg. wt., 110 lbs. Net 215.45

44 N 9034WXM Same as 44 N 9031WXM except with 3 E-V 848 CDP projectors with 30-watt drivers instead of University PH trumpets. Shpg. wt., 100 lbs. Net 206.50


44 N 9035WX Same as 44 N 9035WX plus phono top. Shpg. wt., 110 lbs. Net 224.45

44 N 9036WX Same as 44 N 9035WX except with E-V 641 dynamic microphone plus E-V 428 desk stand. Shpg. wt., 100 lbs. Net 225.50

44 N 9037WX Same as 44 N 9037WX plus phono top. Shpg. wt., 110 lbs. Net 243.45

44 N 9038WX

LAFAYETTE 100-WATT INDOOR PAGING SYSTEMS



LAFAYETTE PA-423 100-WATT AMPLIFIER

COMPLETE SYSTEM

AS LOW AS **178⁵⁰**


CHOICE OF MICROPHONES



LAFAYETTE PA-43 DYNAMIC MIKE



E-V 641 DYNAMIC MIKE ON EV-428 TOUCH-TO-TALK STAND



LAFAYETTE 8" 10-WATT SPEAKER BAFFLE COMBINATIONS PRE-WIRED WITH TRANSFORMER & VOLUME CONTROL

An ideal system for heavy duty, high powered continuous performance; for paging or industrial music distribution, and for extra-large auditoriums, schools, churches, department stores, airports, etc. Included in these systems are 6 of the Lafayette pre-wired speaker-baffle combinations with 8" heavy duty speakers rated at 10 watts each, pre-wired matching transformer for 70-volt line with taps for 10, 5, 2.5, 1.25 and .625 watts per speaker, and individual volume controls. A screwdriver is all you need to connect speaker lines. You can add more speakers, if you wish, at any time — up to 80 for a 1¼-watt-per-speaker department store or school installation, etc. In addition you get the Lafayette PA-423 conservatively-rated 100-watt amplifier; your choice of either the Electro-Voice Model 641 high output dynamic microphone with 18' cable and with E-V 428 touch-to-talk desk stand with dpdt switch or the well-known Lafayette PA-43 "Dyna-Slim" high output dynamic microphone with on-off switch, omni-directional head, "quick-slip" swivel-type stand adapter, and plug-in cable. For 117 volts. 60 cps AC. Shpg. wt., 95 lbs. Complete 100-watt indoor system as described, less phono top, with E-V 641 microphone and 428 stand.

44 N 9039WXM Net 197.50

Same, with Lafayette PA-43 "Dyna-Slim" microphone, less stand. 44 N 9040WXM Net 178.50

Additional Speaker Baffle Units. Imported. Shpg. wt., 7 lbs. 99 N 4552W Net ea. 14.95

PHONO TOP SYSTEMS

These systems are identical to the above but include a 4-speed phono top which mounts easily on top of the amplifier.

Same as 44 N 9039WXM with 4-speed phono top. Shpg. wt., 105 lbs. 44 N 9041WXM Net 215.45

Same as 44 N 9040 with 4 speed phonograph top. 44 N 9042WXM Net 196.45


Prices on This Page May Be Raised April 1st Due To New Excise Tax

PA Speakers and Megaphones

LAFAYETTE 8" 10-WATT PRE-WIRED SPEAKER Baffle Combination



14⁹⁵



- For Public Address, Paging, Music Distribution Use
- Built In 70-Volt Line Matching Transformer with Taps for 10, 5, 2.5, 1.25 and .625 Watts
- Built-In Individual Volume Controls
- Only A Screwdriver Needed to Connect Speaker Lines

An 8-ohm speaker baffle combination for any type of indoor sound system. Perfect for schools, stores, offices, churches. Each unit is completely pre-wired. The heavy-duty 8" speaker with 4.64 oz. Alnico V Magnet rated at 10 watts, is installed in the beautifully styled acoustically-designed plywood baffle; the matching transformer is mounted directly on the sturdy warp-free speaker frame. Transformer taps are 10, 5, 2½, 1¼ or ¾ watts, for connection to 70-volt amplifier output, and any individual speaker taps can be changed without the need to change transformer connections on remaining speakers of the PA system. A terminal board with screw terminals is provided at the rear of each baffle for easy connections. Each speaker has its own volume control for setting volume levels as desired. Size: 11Wx9½Hx6½"D. Shpg. wt., 7 lbs. Imported.
99 N 4552W Speaker Baffle Combination Net 14.95

DELUXE LAFAYETTE PISTOL-GRIP POWER MEGAPHONE 29⁵⁰



- Weighs only 4¼ lbs. complete with batteries
- Ideal for lifeguards, coaches, construction gangs, sporting events - plus hundreds of other applications!

A lightweight megaphone notable for its extreme economy in battery power despite its high sound volume output. Uses 4 large size D flashlight batteries and has a patented non-linear current-limiting device to give maximum possible battery life. The reflexed air column in the horn plus its special shape serve to concentrate and direct the amplified sound and throw it for a considerable distance! The rubber-rimmed horn is of lightweight spun aluminum and construction is extremely sturdy throughout. Microphone is built into the base of the horn. Unit measures 12½" long; mouth diameter is 8¼". Shpg. wt., 6 lbs. Imported.
99 N 4504 Power Megaphone Net 29.50
BATTERIES FOR ABOVE—Burg. No. 2 or equiv. (4 required.) Shpg. wt., 1 oz. ea.
32 N 4804 Net ea. .13

ALL-TRANSISTOR BULL HORN



Only 6⁸⁵

Made in U.S.A.

- Weighs only 2½ lbs.
- Range up to 400 feet
- For Hunting, Camping, Boating Sports

A fully transistorized directional megaphone at Lafayette's low price. Lightweight, it carries your voice hundreds of yards or above noise. Just press the trigger and talk. Features variable volume control and carrying strap. Uses 4-standard "D" cells (not supplied with unit). 11 inches long. Shpg. wt., 3 lbs.
44 N 1509 Net 6.85
1½-volt D batteries, 4 required
32 N 4804 Net ea. .13

LAFAYETTE MINIATURE HORN PAGING SPEAKER

- Mounts Easily
- 90° Dispersion
- Weatherproof

7⁹⁵



An excellent general purpose paging speaker of amazingly compact size. Ideal for portable PA systems, patios, etc. Long throw projection of 90° dispersion offers maximum speech intelligibility in high noise areas. Compact size enables it to be mounted anywhere in almost any position. Frequency response 400-12,000 CPS. Impedance 8 ohms. Power handling capacity 5 watts, 8 watts maximum. Complete with mounting bracket, 2-conductor cable. Horn diameter 5 1/8". Depth 4 1/4". Imported. Shpg. wt., 11 lbs. 4 oz.
99 N 4508 Net 7.95

LAFAYETTE 25-WATT DRIVER UNIT FITS ALL TRUMPETS and PROJECTORS 9⁸⁵

Hermetically sealed weatherproof driver unit. Delivers 25 watts of power. Perfect for any location where high volume with low distortion is desired. Will fit any trumpet or projector of your choice without modification. The widerange frequency response of 120-7,100 cps assures excellent reproduction of music and speech. 16 Ohm impedance. Size 4" Diameter 3-5/8" depth Shpg. wt., 3 3/4 lbs. Imported.
99 N 4507 Net 9.85



OUTDOOR WEATHER-PROOF SPEAKER 4⁷⁹

- Frequency Response: 100 to 10,000 CPS
- Compact—3¾Wx3¾Hx2½"D
- Enclosed in a Cadmium Plated 20-Gauge Steel Case
- Specifically Designed Plastic Impregnated Cloth Speaker Cone



Compact. Weatherproof, Dustproof. Will withstand immersion in boiling water, and is impervious to salt spray. Utilizes a plastic impregnated cloth cone, spider and dust cap material with an aluminum voice coil and zinc plated frame. Constructed of 20-gauge cadmium plated steel with 2 coats of baked electrostatic enamel. Equipped with an RCA type phone jack, key slot mounting hole plus a mounting cutout to accept a volume control, on-off or push-to-talk switch. Shock Test: withstands up to 50 G's. Voltage: withstands up to 100 volts RMS. Temperature Extremes: from -80°F to 160°F. 3-4 ohm impedance. Shpg. wt., 5 lbs.
44 N 5201 Net 4.79

OUTDOOR 8" PATIO SPEAKER

- WEATHER PROOF—WATERPROOF
- CLEAR Hi-Fi Sound



9⁹⁵

- Mounts anywhere—Indoors or Out
- Use Two for Stereo

The perfect outdoor hi-fi speaker to let you enjoy records and music while relaxing outdoors on your patio; in your yard; at your barbecue. Handsome enough for recreation rooms and dens. Completely wired, ready to install to the radio, phono or intercom system. Unaffected by dampness, humidity, rain or snow; the metal baffle finished in golden-bronze enamel. 3.16 oz. Alnico V magnet, 8 ohm impedance, L pad for perfect matching. Peak power 8-10 watts. Size: 10½x11x5¼". Shpg. wt., 5 lbs.
44 N 3305 Net 9.95
Similar to above but with 8" coaxial speaker with built-in tweeter and electronic crossover. For extended range coverage of 70-12,000 cps. Shpg. wt., 7 lbs.
44 N 3306 Net 13.75

Patio Speakers—Baffles—Mike Stands—Mixers

LAFAYETTE HI-FI "THIN LINE" Baffle Speaker

- Measures Only 2 1/4" Deep
- Perfect for Hi-Fi Extension Speaker or PA Use

The perfect speaker to furnish music or paging throughout your home, office or factory, this unique ceiling and wall baffle speaker offers dazzling audio reproduction. Advanced design employs an inverted magnet, placing the 12 oz. magnetic structure in front of the speaker rather than behind as in conventional speakers. Only 2 1/4" deep with its own metal baffle plate, it easily mounts in any wall, ceiling, closet or ordinary wood enclosure. Two are perfect for stereo. Voice coil is 1" Diam. Frequency Response: 90-9,000 cps. Impedance: 8 ohms. Overall size including metal baffle is 9 1/2". Requires 6 5/8" wall cutout. Shpg. wt., 3 lbs. Imported. **99 N 4505** Net 5.95



FOURJAY-OUTDOOR PATIO SPEAKERS

MELODY BELL



THE PATIO PAIR

The Patio Pair consists of a separate loudspeaker baffle with weatherproof speaker, and a separate patio lamp. Identical in styling in green and white fiberglass with pipe fitting for 1" pipe. Speaker provides even dispersion of sound. Accepts up to 100-watt bulb.

Model S-0F1 8 WG Speaker Baffle. Includes 10-watt, 8" weatherproof speaker with 40-11,000 cycle range, 8-ohm voice coil. **44 N 2801 Shpg. wt., 6 lbs. Net 17.05**
 Model LMP 60/100WG attractive Patio Lamp less bulb. **44 N 2802 Shpg. wt., 4 lbs. Not Illustrated Net 10.05**

LOWELL CEILING AND WALL BAFFLES



SURFACE MOUNTING BAFFLES



AL

RS and AL Wall and Ceiling Baffles — Aluminum baffles with 1/2" mtg. flange finished in satin for installations in offices, restaurants, etc. RS types for recessed wall mtg., AL for recessed ceiling mtg. Require flush-mounting baffle enclosures, Type CP & XCP.

Stock No.	Type	Description	Lbs.	Net
44 N 5001	RS-6A	For 6" spkr. 10 3/4 x 7 3/4"	1	2.25
44 N 5002	RS-8A	For 8" spkr. 12 3/4 x 1 1/2"	1	2.50
44 N 5003	RS-8A	Same as PE-131, wh. enam.	1	2.50
44 N 5004	RS-12A	For 12" spkr. 16 1/2 x 1 1/2"	1 3/4	3.40
44 N 5005	AL6A	For 6" spkr. 10 1/2" Dia.	1 1/2	3.35
44 N 5006	AL8A	For 8" spkr. 12 3/4" Dia.	1 3/4	5.45
44 N 5007	AL12A	For 12" spkr. 16 3/4" Dia.	3 1/2	6.90

FLUSH-MOUNTING Baffle Enclosures



CP & XPS Series — Designed for mounting AL and RS baffles. CP for new constructions. XCP for existing ones. All have steel can, plastic ring and sufficient speaker back pressure. Shpg. wt., CP6 and XCP6, 3 1/2 lbs. each: CP8 and XCP8, 4 1/4 lbs. each: CP1012 and XCP1012; 7 1/2 lbs. each.

Stock No.	Mfr. Type	For	Size	I.D.	O.O.	Depth	Net
44 N 5008	CP6	AL6A, RS6A	7"	11 1/4"	4"	3.28	
44 N 5009	CP8	AL8A, RS8A	8 1/2"	13"	4 1/2"	4.05	
44 N 5010	CP1012	AL12A, RS12A	12 1/2"	17 1/8"	7"	5.54	
44 N 5011	XCP6	AL6A, RS6A	—	7"	4"	3.33	
44 N 5012	XCP8	AL8A, RS8A	—	8"	4 1/4"	3.62	
44 N 5013	XCP1012	AL12A, RS12A	—	12 1/2"	7"	4.89	

KINEMATIX "IMP II" FM WIRELESS MIKE

- Transmits Clearly Up To 200 Ft.
- Can Be Used With Any 88 — 108 Mc FM Tuner, FM Radio, FM Portable, FM Auto Radio
- Compact—Fits Into Shirt Pocket

As Low As **39.95**



FCC Type-Approval Number: WM 101

A transistorized FM transmitter and microphone, so small it can be concealed in shirt pocket or cigarette box, yet transmits up to 200 feet with perfect clarity to any 88-108 MC FM receiver. Has hundreds of practical uses — for theatrical and TV productions, PA systems, security & surveillance work, plant inventory, baby-sitter, guard against prowlers, survey work and many other applications requiring remote sound pick-up (Concealed or otherwise) without bothersome wires. Approved by FCC. Comes complete with leather case and built-in super-sensitive pin-head mike. Also has input for any low impedance (1000 ohms) mike. Tunable between 88-108 MC, freq. response 30-20,000 cps. Size: 3x1 1/4x2 3/4". Requires 1 battery (listed below). Shpg. wt., 1 lb.

44 N 4301 Model IMP11/M-222	Net 49.95
44 N 4302 Model IMP11-221, less built-in mike	Net 39.95
33 N 1428 Battery for above units. Shpg. wt., 1 oz.	Net 1.05


Hang it from trees, overhangs, wires, posts, etc. All fiberglass construction and design assures even dispersion of sound as well as fine tonal quality. Includes efficient 10 watt 8" weatherproof speaker with 40-11,000 cycle range, 8-ohm voice coil. **44 N 2803 White and green finish—Shpg. wt., 5 lbs. Net 14.26**

MELODY BELL

FOR OUTDOORS — FOR INDOORS

ATLAS MICROPHONE STANDS

As Low As **1.91**



Model MS-10C Full Grip Mike Stand. Economical mike stand featuring "Full-Grip" clutch mechanism for fast quiet adjustments without slipping and wear. Functionally designed base assures maximum stability and includes self-leveling, shock-absorbing pads plus 3 "anti-tip" points. Full chrome plated tube assembly. Terminates in a 3/8"-27 thread. Base dia. 10". finished in gray shrivel. Height adj., 35 to 64". Shpg. wt., 9 lbs. **44 N 1003 Net 5.88**

Model MS-12S "Sleeve Action" Mike Stand. New mike stand featuring a fully automatic means of height adjustment. To lower the stand, just press on the "Sleeve Action" control. To raise the stand, any point on the tube can be grasped. Quiet and smooth action. Ht. 35 to 65". Base dia. 10". Standard thread. Shpg. wt., 12 lbs. **44 N 1006 Net 13.23**

Model CS-32 Demountable Stand. Revolutionary in design, this mike stand is fully collapsible to fit in amplifier or speaker carrying case. No tools needed. Self-leveling legs are skid-proof. Features "Full-Grip" and "Velvet Action." Adjustable from 36 to 64 in. Fully chrome plated. 3/8"-27 thread. Shpg. wt., 5 lbs. **44 N 1007 Net 7.35**

Model DS-5, "Velvet Action" Desk Stand. Same quality as floor models. Base dia. 6". Finished in gun metal shrivel. Fixed ht., 4". Shpg. wt., 2 lbs. **44 N 1009 Net 1.91**

LAFAYETTE TRANSISTORIZED MIKE MIXER

4.85

- Up to 4 Channels
- Matches Hi Impedance Microphones



A compact microphone mixer capable of providing professional results. Mixer controls from one to four signals from hi-impedance microphones, tuner, phonograph and/or recorder. Permits amplifying or fading of any channel while holding the volume of other channels. Inputs accept standard 2-circuit phone plugs—output jack accepts standard circuit phone pin plugs. Requires single 9-volt battery (not supplied). Size 6Wx2 1/4x3 1/2"D. Shpg. wt., 1 1/4 lbs. Imported. **99 N 4535 Net 4.85**
99 N 6021 Battery for above Net .21

LAFAYETTE General Purpose



LAFAYETTE STUDIO CRYSTAL MICROPHONE

4⁹⁵

- DUAL CRYSTAL CARTRIDGES
- ALL DIRECTIONAL
- HIGH OUTPUT



Here is a microphone with a 360° pickup, and the added power and sensitivity of two individually shock mounted and phased crystal cartridges. This arrangement assures you of maximum pickup from all sides. Swivel mounted to give fuller flexibility. Case is chrome plated. Standard 3/8"-27 thread. Overall size 7Hx3"W complete with 4 ft. cable. Shpg. wt., 2lbs. Imported
99 N 4511 Net 4.95

LAFAYETTE GENERAL PURPOSE CRYSTAL MIKE



- For Desk-Top, Hand-Held Use
- Full —55 DB Output Level
- Excellent Frequency Response


1⁹⁵

An attractive, specially engineered general purpose crystal mike for desk-top or hand-held use. Excellent frequency response. Output level —55db. Only 1 3/8" in diameter. Includes 5-ft. of shielded cable for connection to tape recorders, public address amplifiers and radios. Chrome plated stand. Imported.
99 N 4543 Shpg. wt., 1 1/4 lbs. Net 1.95



3⁹⁵

LAFAYETTE DIE CAST CRYSTAL MICROPHONE



Easily Attaches to All String Instruments

1⁹⁵

This high quality contact microphone is ideal for amplification of single stringed instruments such as guitars, banjos, mandolins, cellos, ukuleles, etc. Provides rich, natural reproduction of the actual tone with sufficient amplification to be heard in a large hall. The clamp bar on the mike slides directly under the sounding board cutout to give a secure fit. Comes equipped with 8 ft. cable for connection to public address amplifiers, tape recorders or radios. Frequency response 40-9,000 cps. High impedance. Size: 1 1/2 L x 1 3/4 W x 3/4 D. Shpg. wt., 12 ozs.
99 N 4519 Imported Net 1.95



LAPEL MICROPHONE

1⁹⁵

- Full —55 db. Output Level!
- Ideal General Purpose Mike

Ideal general purpose mike. Specially engineered crystal Microphone. Attaches to lapel. Only 1 3/8" in diameter. Excellent frequency response. Output level —55 db. Chrome plated case and clip for attaching to lapel. Includes 5 ft. of shielded cable. Shpg. wt., 1 lb.
99 N 4510 Imported Net 1.95

Excellent for PA systems, home recorders and general applications. Frequency response 50 to 10,000 cycles. Output level —52 db provides ample output for use with low gain amplifiers. Uses quality moisture sealed crystal; Die cast case in rich green baked enamel finish, with chrome grill. Completely equipped with 5 feet of shielded cable. Mike may be used on any stand with 3/8"-27 thread. Grill diameter 2 3/4", depth 4 1/4", height 4 1/2". Shpg. wt., 3 1/2 lbs. Imported.
99 N 4512 Net 3.95

ROUND HOLE GUITAR MIKE

5⁵⁰



Convert your Spanish guitar or Ukulele into an electric. Single pickup with separate tone and volume controls. Detachable cord 8 ft. long. Shpg. wt., 1 lb. Imported.
99 N 4537 Net 5.50

GUITAR MICROPHONE

- FOR F HOLES

6⁹⁵

Add brilliant rich tone to your present guitar. Features controlled output power for each string, separate tone and volume controls and removable amplifier cord. Complete with mounting accessories. 10 1/2" long. Shpg. wt., 10 ozs. Imported.
99 N 4536 Net 6.95



MINIATURE CRYSTAL MICROPHONE

1⁴⁹

- Only 1 1/8" x 3/8"

For the experimenter, student or dealer. An extremely sensitive and small crystal microphone used in hearing aids and other small apparatus. Can be used as lapel mike—miniature transmitter mike—for concealed locations, etc. Its size and performance gives it versatility. Size only 1 1/8" x 3/8" deep. Shpg. wt., 6 ozs. Imported
99 N 4509 Net 1.49

HIGH IMPEDANCE DYNAMIC MIKE

Our Low, Low Price

4⁷⁵



MIKE FOR HOME RECORDING

- Ideal Mike for Home Recording Use
- Frequency Response: 60-10,000 CPS

An outstanding Lafayette microphone for home use. Frequency Response: 60-10,000 CPS ± 10db. Output Level: —57db @ 1000 CPS. Impedance: 50,000 ohms. Complete with 6 1/2' shielded cable with plug. Size 1 3/8" x 2 1/4" H x 7/8" D. Shpg. wt., 8 oz. Imported.
99 N 4553 Net ea. 4.75
2 for 8.95



CRYSTAL MICROPHONE CARTRIDGE


1⁴⁹

- Replacement for Astatic Shure, and Many Other Popular Microphones

Crystal microphone cartridge with heavy flexible rubber cushioned rim designed for speedy, economical repair. Fits tens of thousands of the most popular microphones such as the Astatic J130 etc. Overall diameter 2 1/8", depth 1/2". Output —52 db. Excellent frequency response. Shpg. wt., 8 oz. Imported
99 N 4513 Net 1.49

REMOTE CONTROL HAND DYNAMIC MIKE

Now, you may control your tape recorder by a handy, built-in push-to-talk switch that also features a slide-to-record position. Press to record for on-the-spot recordings or slide switch for more lengthy material. Case is of high-impact plastic. Perfect for either home or field use. Specs: 200-9,000 cps; Impedance 600, 50KΩ; sensitivity —77 db @ 600 Ω —57 db @ 50KΩ; Size: 1 1/2 x 5 1/2 x 1 3/4". Imported
99 N 4554 Shpg. wt., 1 1/4 lbs. Net 4.95



Low Price

4⁹⁵

Top Quality Microphones

LAFAYETTE DUAL IMPEDANCE SLIM DYNAMIC MICROPHONE



11⁹⁵

- 600 & 50,000 Ohm Impedances Selected By Simple Rotation of Plug
- Ruggedly Constructed
- On-Off Switch

Beautiful, professional-looking dynamic with solidly-cast, tapered, slim case with satin-chrome finish. Heavy duty slide-type on-off switch. Built-in transformer supplies dual unbalanced impedances—low Z is 600 ohms, high Z is 50,000 Ohms. Swivel mount fits all standard $\frac{3}{8}$ "-27 threaded stands. Blast filter eliminates unpleasant "pops" with voice use. Omnidirectional when used vertically—cardioid pattern when tilted. Engineering design and finish are of the highest quality, making this microphone excellent for any application. Complete with 5 ft. plug-in cable. Shpg. wt., 2½ lbs. Imported.

99 N 4523

Net 11.95

ARGONNE ALL-PURPOSE DYNAMIC MICROPHONE

- Ideal For Tape Recording, Paging, Communications
- Dual Impedance—250 & 50,000 Ohms
- Usable Response 50-18,000 CPS
- For Hand-Held, Desk Or Floor Stand Use



Here is a flexible dynamic microphone with characteristics suitable for almost any application. Ruggedly constructed, with tapered cast-metal body and removable base for desk use. Mounts to the base by means of a 360° swivel adjustable ball joint and fitted with an adapter for standard $\frac{3}{8}$ "-27 floor stand. SPECIFICATIONS: FREQUENCY RESPONSE—Practically flat 80-10,000 cps; ± 5 db 70-13,000 cps. OUTPUT—70 db below 1 volt/microbar at 1,000 cps. DUAL IMPEDANCE: Low (250 ohms), High (50,000 ohms) unbalanced. Size 9" high (with base), 2" diam. at head, tapering down to $\frac{3}{4}$ ". Base diam. 4 $\frac{1}{2}$ " x 1 $\frac{3}{4}$ " high. Shpg. wt., 6 lbs.

Dynamic microphone, complete with base, floor stand adapter, and 8" cable. Imported.

99 N 4501

Net 13.95

COMPLETE WITH BALL-JOINT DESK STAND

13⁹⁵

LAFAYETTE STUDIO DYNAMIC MICROPHONE ONLY

11⁹⁵

- Frequency Response 50-11,000 cps.
- High Impedance 50,000 Ohms
- High Output




Omni-directional microphone has a swirl ridged aluminum diaphragm completely sealed and gasketed against high humidity and temperature conditions, for a wide variety of applications. The 360° stirred-up shaped bracket provides for mounting with any $\frac{3}{8}$ "-27 thread stand. Finished in an attractive gunmetal grey with 4 $\frac{1}{2}$ " shielded cable. Shpg. wt., 1 lb. Imported

99 N 4525

Net 11.95

3 WAY SLIM CRYSTAL MICROPHONE



3⁹⁵



- May be hand-held, stand mounted or suspended by lavalier cord!
- RESPONSE 60-10,000 CPS
- On-Off Switch

Here is a fine slim-line design, only 4 $\frac{1}{2}$ " L x 1 $\frac{1}{8}$ " diam. Comes complete with swivel adapter to fit all standard mike stands, and lavalier cord and bracket which leaves both hands free. Smooth wide range response. Locking type on-off side switch. Detachable 7 ft. cable and connector. Shpg. wt., 2 lbs. Imported.

99 N 4515

Net 3.95

LAFAYETTE DUAL IMPEDANCE UNIDIRECTIONAL DYNAMIC MIKE

- Hi or Low Impedance
- Unidirectional Pick up Pattern
- Hand-held or Stand Mounted

Highly desirable cardioid pattern provides a significant front-to-back signal ratio to suppress noise, reverberations, and feedback. Impedance output (Hi—50K, low 600!). Comfortable hand-held design or may be mounted on any standard thread stand ($\frac{3}{8}$ "—27 thread). Frequency response is from 90 to 10,000 cps. Comes complete with 10 feet of 2-conductor shielded wire (balance type). Attractively finished in contrasting black and silver. Equipped with on-off switch. Shpg. wt., 2½ lbs. Imported.

99 N 4641

Net 21.50




ONLY

21⁵⁰

LAFAYETTE DUAL IMPEDANCE OMNI-DIRECTIONAL DYNAMIC MIKE

- Designed Specifically for High Quality PA Applications
- Omni-directional Pattern at all Frequencies



A superb dual impedance, omni-directional Dynamic microphone. Designed for high quality PA applications. Superior anti-feedback properties. Allows close talking without boom or bass accentuation. Features pop-proof wire mesh grille. Special filter minimizes wind effect. Attractive chrome plated frame of modern design. Equipped with on-off switch. Freq. Response 100-10,000 cps. Sensitivity—30K at —60 db. Mylar diaphragm for "pop" and "blast" proofing. Dual impedance: may be shifted from high impedance to 250 ohm low impedance by means of a cable connection. Shpg. wt., 2 lbs. Imported.

99 N 4546

Net 11.95

LAFAYETTE GENERAL PURPOSE DYNAMIC MICROPHONE

- A Hi-Fidelity Omni-directional Microphone For Recording, Radio Broadcasting, and PA Applications

A high quality omni-directional dynamic microphone at such an unusually low price. Beautifully styled in a chrome-plated diecast frame that is equipped with an on-off switch. Specifically designed for recording, radio broadcasting, and public address applications. Features a "pop-proof" and "blast-proof" mylar diaphragm, and superior anti-feedback properties. Frequency response 100-10,000 cps. Sensitivity 30K at 60 db, 600 ohms at —70 db. Shpg. wt., 2 lbs. Imported.

99 N 4545

Net 10.95

10⁹⁵



"DYNA-SLIM" MICROPHONE

- High Impedance—50,000 Ohms
- On-Off Switch
- Omnidirectional
- Tiltable For Multi-Angle Use
- "Quick-Slip" Adapter

Dynamic, high output microphone with streamlined styling. Output level —55db. Smooth response from 60 to 10,000 cycles. Omnidirectional head. External on-off switch. Slips on or off stand adapter in a wink. Standard $\frac{3}{8}$ "—27 adapter permits tilting mike for multi-angle use. Satin black and chrome finish. Complete with detachable cable and connector. 8" long, 1 $\frac{1}{4}$ " max. dia. tapered barrel 7". Shpg. wt., 2 lbs. Imported.

99 N 4521


Net 6.95



Take Advantage of Lafayette's Low Microphone Prices

Famous LAFAYETTE Intercoms

LAFAYETTE 2-STATION SOLID STATE INTERCOM



A Thousand Uses For
The Entire Family!


- Inter-Unit Tone Calling
- Beautifully Styled
- Battery Operated
- Simple Plug-in Connecting cord
- Push-Button Operation

9⁹⁵
2 UNITS
COMPLETE

A beautifully styled, miniature 2-station intercom that is fully transistorized and operates from one inexpensive 9-volt battery. The system consists of one master and one remote with 66 feet of lightweight interconnecting cord. Plug at each end of cord lets you hook-up system fast — no tools or wiring connection required. Master unit has power on/off/volume control and listen-talk to the master without has push-button for calling only — you can listen or talk to the master without operating any buttons. Master and remote can call each other even when master is switched off—pressing any of the push buttons signals the person at the other end by means of a tone. Each unit is housed in a high-impact plastic case and supplied complete with interconnecting cord and 9-volt battery. Dimensions (each unit): 3Wx1 3/4Hx4"D. Shpg. wt., 1 1/2 lbs. Imported.

99 N 4526 2-Station Transistorized intercom	Net 9.95
99 N 6021 Extra 9-volt battery	Net .21
AC power supply and battery charger for above.	
44 N 3001 Shpg. wt., 2 lbs.	Net 3.20

NEW LAFAYETTE 4-STATION SOLID STATE INTERCOM SYSTEM



Complete System Includes:
1 Master Control Unit
3 Remote units
3—60 Ft. lengths of hook-up wire
1—9 volt battery


- Instant Communications—No Warm up, Heat or Hum
- 4-Way Selector Switch—3 Remote Stations
- Remote Tone Call
- 2-Wire Distribution System
- Battery Powered

19⁹⁵

Deluxe solid state 4-station intercom system that combines smart styling, and portability with high quality performance. All interstation calling is accomplished with one 4-way selector switch. Push-button listen-call switch on all units. Call signal operates even when master switch is "off". Simple coded interruption of buzzer signal lets master operator know which remote is calling. Cool, efficient solid state master unit runs on a single, economical 9-volt battery. With selector switch in "wait" position battery life is further extended. Master unit has its own volume control with "on-off" switch. Easy hook-up is facilitated by inclusion of three 60 foot lengths of 2-conductor wire with jacks at each end. Just plug in and talk. Additional wire is available at extra cost. See below. Complete set consists of, master control unit, 3-remote units, 9-volt battery and wire. Size: Master: 4 1/2 Wx3 1/2"D; Remotes: 2Wx4"D. Imported, Shpg. wt., 2 1/2 lbs.

99 N 4555 Complete 4-station System	Net 19.95
99 N 6021 Replacement 9-volt Battery (1 Req.)	Net .21
32 N 3052 Additional wire, 100 Ft. Coil	Net .94

DELUXE LAFAYETTE WIRELESS INTERCOM



2-Station Wireless Intercom System

32⁵⁰
2 UNITS COMPLETE

- Operates from any 117V AC/DC Outlet
- No Wires to Connect
- Ideal for Home or Office
- Add as Many Extra Stations as Desired

Lafayette offers a high quality 2-station wireless intercom. Handsomely styled, these units offer quality performance for home or business use. Each unit features a 3-position bar-control lever: Dictate (for use as "baby sitter," lengthy talking), Talk (has spring return to Listen position), and Listen. No wires to connect—simply plug into any 117V AC/DC outlet, front panel volume control and pilot light; adjustable squelch control at rear reduces interference during quiet periods. Dependable 3" speaker. Add as many remotes as needed. Shpg. wt., 10 lbs. Imported.

99 N 4547M 2-Station System	Net 32.50
Extra Station. Shpg. wt., 5 lbs. Imported.	
99 N 4544	Net 16.75

Intercoms and Telephones for Private Systems

New LAFAYETTE 2 Channel Solid-State Wireless Intercom

- No wires to Connect—just plug into AC outlet
- Each unit a "Master"—use as many as needed
- Squelch Circuit for noise-free operation

The latest in wireless intercoms—small, compact and fully transistorized. Each unit is a "master"—you can use 2, 3, 4, or as many units as required. No wires to connect—just plug each unit into a regular AC outlet. 5 transistors, 5 diodes and 1 thermistor assure clear, powerful output. Units draw so little electrical current, you can leave them on all day! Perfect anywhere in the home—can even be used between adjacent homes or buildings on the same electric company power line transformer. Two channels (160 & 200 KC) for maximum flexibility. Ideal when 2 pairs are used—each pair can be used for simultaneous but independent communication using separate channels, or for communication between all units using the same channel. Controls; Volume/on-off. Press-to-talk bar with "lock-talk" feature, and channel selector (A-B). Circuit includes Squelch for noise-free operation. Transformer power supply and pilot light. Ivory high-impact plastic case. 5x6 1/4x3". For 117V. 60 cycles AC. Imported.

99 N 4556 2 Intercom Stations. Shpg. wt., 4 lbs. Net 39.95
 Additional Intercom Stations. Shpg. wt., 2 lbs.
 99 N 4557 ea. Net 21.00



2-Stations
only

39⁹⁵
\$5 monthly

TELEPHONE OPERATORS HEADSET



1995

- Ideal for Hobbyists, Marine Radio-Telephone Operators, Hams, etc.
- Leaves Both Hands Free for Operation of Equipment

Headset is lightweight and manufactured to the most exacting standards. All Parts are interchangeable. The Headset consists of the body (Cycloc), ear and mouthpiece, adjustable headband, for proper fit and maximum comfort, receiver unit, transmitter unit, cord and plug. Shpg. wt., 1 lb.

44 N 6001 Net 19.95

30 FT. TELEPHONE EXTENSION CORD

- Ideal Extension Cord for Use With Phones Listed on This Page



Add flexibility to your telephone intercom. Now be able to move your telephone intercom from room to room. 30 feet of telephone extension cord with standard 4-pin plug and jack. Color-coded cord to match screw terminals on plug and socket.

99 N 4539 Imported Net 2.85

99 N 4540 Extra Phone Jack Net 1.25

Combination male & female telephone plug & phone jack only.

99 N 4538 Net ea. 1.95

100-Ft. 2-Cond. twisted pair—unshielded telephone wire

32 N 1303 Net 1.95

3 CONDUCTOR COILED CORD



Low, low price for a tough, 3-conductor coiled cord with strain relief. Excellent for phones in private phone systems, intercoms, etc. Extends to 6'. Shpg. wt., 1/2 lb.

44 N 1806 Net .89

DIAL PHONE

Have your own Private Intercom

- For Intercoms, Extensions, Private Systems

6⁹⁵

Popular modern dial phone. Can be used to make complete private systems. Equipment taken from service, reconditioned and ready to work. Simple 3-wire hook-up. Complete with handset, dial, bell, induction coil and connecting cable. General appearance may vary slightly from catalog illustration. Shpg. wt., 8 lbs.

44 N 1801 Net 6.95



WALL-TYPE DIAL PHONE

11⁹⁹

Popular, self-contained wall-type telephone taken from service and reconditioned. Ideal for intercom and private phone systems. Simple 3-wire hook-up. Includes bell, induction coil and dial. Size and appearance may vary slightly. Shpg. wt., 7 lbs.

44 N 1807 Net 11.99



AUTHENTIC DANISH ANTIQUE TELEPHONE

- Not A Reproduction
- Ideal for the Antique lovers
- Add Elegant Continental charm to your decor
- For Private Phone Systems, Extension or intercoms

Lafayette's
low, low
price

34⁹⁵


\$5 monthly



Add continental charm to your home with this authentic Danish antique telephone. Not a reproduction. These imported phones have been rebuilt like new to include modern transmitting and receiving elements, and are ready to work. Complete with handset, dial, bell, induction coil, and 4 ft. cord with 4-pin telephone plug. Phone comes in black with nickel handset. Shpg. wt., 10 lbs. Imported.

44 N 4401W Net 34.95

Deluxe Telephone Intercoms And Accessories



LAFAYETTE EASY-PHONE TELEPHONE AMPLIFIER

17⁵⁰

- Amplifies Telephone To Room Volume
- 4 Transistors + Varistor
- No Dangling Wires, Pickups To Connect
- No Warm-Up, Instant Operation


The Easy-Phone amplifier is ideal for group conversation with one telephone in the room. Easy to operate: simply place the telephone on the amplifier, adjust the volume and everyone can listen, leaving both hands free for writing or typing. The Easy-Phone is a 4-transistor battery powered amplifier and inductive pick-up, in an attractive plastic case. 5" dynamic speaker; volume control; on/off switch activated by telephone's weight. Sturdy chrome plated runners. 8 1/4 Lx3 1/4 Wx2 1/4 H. With miniature plug and jack for recorder input. Shpg. wt., 3 lbs. Imported.

99 N 9020 With batteries Net 17.50
32 N 4802 Extra Penlight Battery Net .13

LAFAYETTE TELEPHONE AMPLIFIER

9⁹⁵

- 4-Transistor Circuit
- 2 1/4" PM Speaker
- Several People Can Listen in on Conversation Simultaneously
- Battery Operated



An efficient battery operated telephone amplifier which can be applied to and used with any type of telephone. Amplifies incoming voice and projects it through a 2 1/4" PM speaker. Suction cup on pickup coil attaches easily to telephone and makes permanent installation unnecessary. Volume control (with on-off switch) permits adjustment of volume to appropriate level for up to several people to listen in on conversation at the same time. 4-transistor amplifier is powered by inexpensive, long-lasting 9-volt battery (supplied). Unit is housed in a two-tone ivory and grey high-impact plastic case measuring 3 1/4 Wx3 3/8 Hx2 1/4 D. Shpg. wt., 1 lb. Imported.


99 N 9085 Net 9.95
99 N 6021 Replacement 9V Battery Net .21

LAFAYETTE TELEPHONE INTERCOM

- Handy As A Telephone To Use
- Full Solid State Circuitry

19⁹⁵


PAIR



Designed for real utility in the home and in business. Powerful, solid state circuitry transmits your voice over amazingly long ranges. No current drain between transmission due to separate push buttons for transmit and receive. Handy location of push buttons facilitate ease of hand-held operation. May be used wherever private telephone communications are desired. Ideal for applications for the home—between rooms, upstairs and downstairs, kitchen, workshop, etc. For industry between offices and warehouse, receptionist and offices, or for interdepartmental needs, etc. Beautifully finished in grey to match any decor. Shpg. wt., 1 1/2 lbs. Imported. Requires 2 batteries listed below.

99 N 9079 Set of two Net 19.95
99 N 9080 Singly Net ea. 10.95
32 N 4802 Battery for above, 2 req. Net ea. .13
32 N 3002 Additional 100 ft. roll of 2-cond. wire Net 1.88

ELECTRONIC 5-POSITION SWITCHBOARD!



AS LOW AS

9⁸⁸


- Real Switchboard Action-Lights, Buzzer, Dial
- Hold Calls—Switch Calls—Call to or From All Phones
- Great Play Value . . . Use As An Intercom

Great fun for the entire family, practical too. Perfect for play or adult use between living room, kitchen, bedroom, sickroom. Functions like real unit, with 4 plug-ins and 4 signal switches, which ring bell. Operator has own master phone. Call in-switchboard lights up, rings. Operator can receive all incoming calls, can connect phone to phone. Operates on two inexpensive 'D' size flashlight batteries. Complete set includes regular operations dial, message pad, one operators phone and one extension phone. Takes 3 additional extension phones (optional at extra cost). Molded of high impact plastic. Shpg. wt., 4 lbs.

13 N 8401 Net 9.88
32 N 4804 "D" cells for above; 2 req. Net ea. .13
EXTRA PHONES with hanger and wire for above.
13 N 8402 Net 2.25
"C" Battery for Extension Phones, 1 each.
32 N 4801 Net ea. .13

BOGEN TSL TELEPHONES

SELECTIVE RING— SELECTIVE TALK SYSTEMS



100% Trunkage (Multi-Conversation) Fast Operating; No Dialing; No Relays; No Central Exchange.

These new Bogen-Phones will permit you to reach other individuals in their offices without depending upon an over-burdened telephone switchboard. 100% trunkage permits as many as 8 conversations to take place at the same time, making these phones an ideal choice for busy applications. Select the station with which you wish to converse, press the ring button. When the called party lifts his handset, he is in direct communication with you. Phones may be desk or wall mounted. Each phone is furnished with snarl-proof handset cord, 6' master cable and junction box. PRS-16 Power supply required to power each system.


44 N 1201 TSL-8 8-station phone, less wire Net 34.25
44 N 1202 TSL-16 16-station phone, less wire Net 39.95
44 N 1203 PRS-16 Power supply (1 req. per system) Net 36.60

WIRE REQUIREMENTS: Use 3 more unshielded conductors than the total number of phones in the system. Those listed below may be used "between phones."

32 N 3004 7 conductor unshielded cable/100 ft. 5.51
32 N 1301 12 conductor unshielded cable/100 ft. 5.88
32 N 1305 22 conductor unshielded cable/100 ft. 10.73
Connect PRS-16 power supply to any junction box with a short 3 conductor cable.
32 N 3003 3 conductor unshielded cable/100 ft. Net 2.13

Hearing Aids-Headsets-Silent Listeners

SUB-MINIATURE HEARING AIDS



- $2\frac{3}{8}$ Lx $1\frac{1}{8}$ Wx $\frac{3}{8}$ " D
Only 2 ounces!
- $2\frac{3}{8}$ Lx $\frac{7}{8}$ Wx $\frac{3}{8}$ " D
Only One ounce!

(1) A high quality, completely adjustable, hearing aid which weighs only 2 ounces. Features an advanced 4 transistor circuit, wide range volume control, crystal microphone, magnetic earphone, and a 4 position tone converter control. Three tiny ear plugs and a 3 ft. flexible cord are included. Supplied with leather carrying case, earphone, and battery. Shpg. wt., 1 lb. Imported.

99 N 9068L	Net	24.95
32 N 4812 Extra Battery, Burgess Net type	Net	.08
99 N 9069 Extra Plug in Cord	Net	.55
99 N 9070 Extra Earphone	Net	1.59

(2) Good sound intensity and fine tonal reproduction make this an ideal hearing aid. The tiny unit is only $2\frac{3}{8}$ x $\frac{7}{8}$ x $\frac{3}{8}$ inches and weighs less than 1 ounce! Powered by a tiny, long life, mercury cell. A three transistor circuit provides the amount of amplification necessary for many different sound conditions. The large hold down spring clip keeps the hearing aid comfortably in place. A special telephone circuit provides for clear reception of telephone calls. Supplied with three interchangeable ear plugs, 3-feet of flesh-tinted cord, velvet-lined leather case, and instructions. Shpg. wt., 1 lb. Imported.

99 N 9071L	Net	22.95
33 N 1101 Extra Battery, Mallory RM625R	Net	.42



"PRIVATE EAR"

- Remote Control Radio-TV/Earphone Adapter
- Operates Up To 2 Speakers and/or Earphones



Relax in the most comfortable spot in the room and enjoy the benefits of private listening to your radio or phonograph. Connect one or two extension speakers or earphones and control the volume of each separately. 25 foot, flat, flexible extension cord on control unit. Includes earphone control unit and instructions.

99 N 9074 Imported	Net	3.29
99 N 2548 Extra Earphone for "Private Ear"	Net	.79
99 N 2549 10 ft. Earphone Extension Cord	Net	.39

"WHISPER" BONE-CONDUCTION PILLOW SPEAKER

- "Sonic Transducer" cannot be heard at a distance

A unique pillow speaker which assures the radio or TV listener absolute privacy. This patented device produces sound vibrations which are heard best when conducted to the inner ear by a solid pathway rather than air. Cannot disturb the sleep of others—only you can hear it. Round Ivory plastic case, only $2\frac{1}{2}$ " diameter and $\frac{5}{8}$ " thick. Complete with cord and jack for simple plug-in connection for radio or TV. Shpg. wt., 8 oz. Imported.

99 N 9073	Net	2.25
-----------	-----	------



DYNAMIC STEREOPHONIC HEADPHONES

- True Binaural Reproduction
- Frequency Response 40-16,000 cps
- Magnetic Elements
- Lightweight—only 2 ozs. Imported

BINAURAL HEADPHONES

Binaural-Magnetic-6 ohms impedance	2.35
99 N 1001	
Binaural-Magnetic-5000 ohms impedance	2.45
99 N 1002	

MONAURAL-MAGNETIC HEADPHONES

Monaural-Magnetic-6 ohms impedance	1.75
99 N 2546	
Monaural-Magnetic-5000 ohms impedance	1.95
99 N 2547	



BEHIND-THE-EAR HEARING AID

- Flesh Colored Plastic
- Self-Contained Miniature Unit —No Cords
- Complete with Battery Charger, 2 Rechargeable Batteries and Case




A fine unit combining good performance and very small size. Designed as a light and compact "ear-lobe" hearing aid. All components are contained in the flesh-colored high impact case, which is worn behind the ear. Weighs only $\frac{1}{2}$ of one ounce! Sound travels to the ear through a clear tube. Independent on-off switch and volume control. Operates 8-10 hours on a rechargeable alkali battery and 80-100 hours with a mercury cell. Complete with a handy battery charger capable of charging cells overnight. Shpg. wt., 1 lb. Imported.

99 N 9072	Net	62.95
33 N 1448 Mercury cell for above	Net	.32

REMOTE CONTROL FOR SILENT TV VIEWING

- Simple to Attach to any TV set or Radio

6⁵⁰



FOR LATE LISTENERS. One or two people can both see and hear the program with the loudspeaker cut off. Tops for enjoying the late-late show

without disturbing the rest of the household or the neighbors. FOR HARD-DF-HEARING. Hear without turning the set volume so high that others can't stand the noise. It is possible to listen either with the loudspeaker cut off or, if everyone wants to hear, with the speaker on.

FOR NOISY PROGRAMS view with the speaker off.

FOR NORMAL OPERATION it does not affect the regular use of the TV set. It does not have to be disconnected.

REMOTE CONTROL comes complete with 20 ft. of cable so it can be operated comfortably from a distance. Has its own volume control, speaker on-off switch, and two sets of jacks so either 1 or 2 earphones can be connected. Supplied with a miniature dynamic earphone. Highly sensitive and efficient. Complete with 1 earphone with 3 ft. of cord and plug and control box with 20 feet of cable. Only $3\frac{7}{8}$ x $2\frac{1}{2}$ ". Instructions included. Shpg. wt., 3 lbs.

13 N 0901	Net	6.50
EXTRA EARPHONE. Shpg. wt., 8 oz. Imported		
99 N 2548	Net	.79
10' EXTENSION CORD for above. Imported		
99 N 2549	Net	.39

LAFAYETTE HEAD SET

- 4000 ohm DC Resistance
- Double Permanent Magnet




A real bargain—the convenience and advantages of earphone listening at an especially low price. This is an extremely efficient, double headset with adjustable headband, for private listening or for greater intelligibility when there are distracting sounds and external noise. 4,000 ohms DC resistance. Has durable permanent magnets, removable earpiece and $3\frac{1}{2}$ feet of extension cord terminated with standard headphone tips. Shpg. wt., 12 oz. Imported.

99 N 2504	Net	1.59
-----------	-----	------

SUPER POWER DYNAMIC EARPHONE FOR TRANSISTOR CIRCUITS

- Powerful Efficient Magnet
- Includes 3 Ft. Cord



Not to be confused with run-of-the-mill earphones. Extra efficient construction and a powerful magnet provides exceptional performance. Ideal solution to the problem of low output in transistor circuits.—it will give delightful performance wherever a high impedance dynamic earphone is required. AC impedance 7000 ohms, DC resistance 1500 ohms. Snap on earpiece. Complete with 3 ft. detachable plug-in cord. Shpg. wt., 4 oz. Imported.

40 N 7801	Net	2.95
-----------	-----	------

Lamps for Industry-Lab-Office-Home

NEW LAFAYETTE CLAMP-TYPE "DRAFTING LAMP"

For Factory, Office, Studying, Drafting, Home, Kitchen


only
7⁹⁹



A deluxe new lamp from Lafayette for perfect illumination wherever you require it. Ideal for benches, tables, and drafting boards. Clamps securely to any surface up to 3" thick. Spring controlled swivel joints and double arm action moves light in any direction. Protects your eyes. Arm extends to 30". Comes in neutral color to blend with all decor. For 110-125V, 60 cycles AC. Shpg. wt., 9 lbs. Comes less bulb. Imported. **99 N 0077 Net 7.99**

NEW LAFAYETTE "DAY LIGHT" • High Intensity Miniature Lamp

12⁸⁸



Portable daylight lamp enables you to carry a high intensity concentrated light source in a briefcase. Glare free light equal to daylight (150 ft. candles at average working distances and up to 5000 foot candles for close up work.) Compact only 2½x2½x10", when collapsed. Reflector swivels in all directions and arm extends out to 15". 3 Friction joints on arm provides for many different positions. Hi-lo intensity switch. All metal with nylon feet. G.E. bulbs supplied (#1133). Shpg. wt., 6 lbs. **13 N 0100 Net 12.88**

ALL PURPOSE LAMP

14³⁸



Ideal for factory benches, tables and drafting boards. Two bolts clamp base securely to any surface up to 3" thick. Spring-controlled swivel joints and double arm action give you light in any desired position. Arm extends 36". Uses two T8, 15-W lamps. For 110-125V., 60 cycles AC. Bronze finish. Less lamps. Shpg. wt., 10 lbs. **12 N 1001 Net 14.38**
T8, 15-watt, cool white lamp Net 14.38
12 N 1002 Net ea. .92




NEW HIGH INTENSITY POWER LITE

5⁹⁹

Perfect desk and reading lamp, but has dozens of other uses—crafts, hobbies, sewing, reading in bed, piano light, etc. All metal construction with a brass finished metal gooseneck which swivels and turns to any position provides pure white, concentrated light with an intensity of 40 ft. candles. Lamp is complete with full length cord and plug, and comes equipped with G.E. #1156 12 volt bulb, guaranteed for 600 hrs. Available everywhere for replacement. Shpg. wt., 4 lbs. **12 N 1200 Net 5.99**

MAGNIFYING INSPECTION LAMP


19⁹⁵



Designed for precision work, features a 5" diameter magnifying glass with a powerful 13" focus, surrounded by a 22 watt shadow-free fluorescent tube. A custom-engineered arm permits complete directional mobility—special adjustment knobs insure the proper tension and steadiness for any desired position. 45" arm reach. Ideal for assembly, laboratory, quality control and other detail work. In kit or assembled form. Shpg. wt., 8 lbs. **12 N 8901 Kit, less lamp Net 19.95**
12 N 1003 Assembled less lamp Net 24.99
T9, 22-watt, cool white lamp Net 2.90
12 N 7501 Net ea. 2.90

NEW! HIGH INTENSITY LAMP WITH MAGNIFIED LENS

ONLY
13⁹⁵



- Magnified For Concentrated Light
- Beautifully Styled
- Neutral Color to Match Furniture

A beautifully styled high intensity lamp featuring a magnified lens for concentrated and increased light brightness. Fully adjustable—telescopes up to 17". Folds down to a compact 5½". Shade swivels a full 360°. Extremely versatile for reading, hobbies, sewing, piano light, etc. Can be hung on wall with built-in clip. Unbreakable phenolic shade and base. Bulb included. Neutral tan color. Shpg. wt., 2 lbs. **12 N 1601 Net 13.95**
32 N 6084 Replacement Bulb Net .25

ALL-PURPOSE LAMP

5⁵⁹



Smart and versatile . . . ideal for use in shop, office, home—wherever positioned lighting is needed for close work or reading. Flexible gooseneck and swivel shade permit positioning light exactly where it's wanted. Streamlined flair shade and louvers for air cooling. Concentric louver gives diffused, glare-free light. Spring clip mounting for easy insertion and removal of bulb. **12 N 1605 Less Lamp. Shpg. wt. 3 lbs. Net 5.59**

ELECTRIC LAMP LIGHT DIMMER

3⁷⁵



Set the mood with a light level that's right for you—off-dim-bright. Use dimmer with your table, floor, or pole lamps up to 300 watts incandescent only. Can be placed anywhere. Just plug into wall outlet and plug lamp into control socket. Remote control unit may be up to 8' away. Satin brass styling with ivory cord. Shpg. wt., 1 lb. 8 oz. **12 N 4201 Net 3.75**

EXTENSION WALL LAMP

8⁵⁰



• Extends 15 to 24"

A smartly styled wall-lamp for use in the den, office, shop, even the living room. Wall bracket swivels 180° horizontally and the arm extends to 24"—enough light in any direction over a large area. Arm closed is 15". Adjustable shade. Arm, wall mounting brackets and screws are brass-plated. Uses a 22-watt Circline fluorescent tube. Shpg. wt., 4 lbs. **12 N 1006 Less Lamp Net 6.40**
12 N 7501 T9, 22-watt, Cool White Lamp Net 2.80

LAFAYETTE Electrical Specialties

LAFAYETTE AUTOMATIC PHOTO-ELECTRIC 'LUMINATOR

- Automatic Light Switch
- Lights on at sunset—off at sunrise



Photo-electronic, light-sensitive switch turns lights on and off at dusk and dawn. You need never come home to a darkened house. Just plug it in for protection from prowlers—illuminate outdoor areas—any place you require automatic illumination. Measures only 3 3/4 x 2 1/2 x 2 1/4". Use on 117-volt AC only. Maximum 300 watts lamp load. Instructions included. Shpg. wt., 1 lb. Imported
99 N 9084

Net 4.95

ONLY 4.95

HOMELIGHTER AUTOMATIC LIGHT CONTROL

- Turns lights on and off Automatically
- Handles up to 1000 watts




750



A automatic light-sensitive photo-electric switch which will turn lights on and off at dusk and dawn. Never needs setting and requires no wiring or installation. Plug it in and it works. Has a 1000-watt lamp load rating which permits it to control not just one, but several fixtures. A multiple connection extension cord may be used if desired. Prowlers are discouraged, and your property is protected. Housed in decorative clear plastic case measuring 3 3/4 x 1 1/2 x 1 3/4". Complete with 6-ft. flexible 3-wire cord with adapter plug. For 110-130 volts, 50/60 cps AC. Shpg. wt., 1 lb.
12 N 3801

Net 7.50

LAFAYETTE HOME FIRE ALARM



29.95



- Loud — Clear Alarm
- Complete Signal Unit — 6 Detectors


Sensitive thermostatic detectors—located in every potential fire area, react to heat instantly. The alarm alerts you and your family before flames spread. The system does not depend on house current for operation. Long life, heavy duty battery will last at least one year. System is readily checked by means of a heat button. The push button kept within easy reach of bed, serves as an intruder alarm. Provision is made in the signal unit for attaching another alarm (6 volt bell, buzzer or horn) for outside or remote locations. The signal unit is completely enclosed in a chrome plated steel housing. Measuring only 4 1/2 x 5 1/2 x 3 1/2" overall—can be located in any convenient area. Detectors, only 2" in diameter, are unobtrusive and cover areas up to 400 sq. ft. System includes signal unit with 2 horns and provision for a 3rd, 6 thermostatic detector switches (five 135°, one 200°) 150 ft. of 18 gauge twisted pair control wire, test button, 2 boxes of staples, battery and instruction book. Shpg. wt., 8 lbs.

- 14 N 8201 Net 29.95
 14 N 8202 135° Detector Switches. Shpg. wt., 3 ozs. Net ea. 1.95
 14 N 8203 200° Detector Switches. Shpg. wt., 3 ozs. Net ea. 1.95
 13 N 8101 Test Button, Shpg. wt, 3 ozs Net .16
 18 Gauge, twisted pair control wire. Shpg. wt., 3 lbs. per 100 ft. Net 1.85
 34 N 4615 100 ft. Net 7.50
 34 N 4616 500 ft. Net .79
 32 N 4689 Replacement battery, Eveready 509. Shpg. wt., 1 1/4 lbs. Net .79

"ADJUST-A-LITE" ELECTRONIC LIGHT DIMMER CONTROL


- Replaces Ordinary Wall Switch for Variable Dimming Control

825



Complete variable control from off to 50% (normal dimming range), then instant switch-over to full bright. Fits into standard single gang wall box and uses same two wires as regular wall switch. Any standard wall plate can be used because knob is large enough to cover slot. Furnished with ivory plastic knob having brass-finish insert. For 120 volts, 60 cps AC with incandescent bulbs only, up to 600 watts. Size: 1 1/2" W x 2 1/2" H x 1 1/2" D. Shpg. wt., 1 lb.
12 N 3205 Net 8.25

ELECTRIC OUTLET CONTROL CENTER



ONLY 4.99

- Adds 6 Extra Outlets Wherever Needed
- For use in Home, Office, Industry
- Mount on Bench or Wall, or Keep Portable

If you need extra outlets, you need this Electric Outlet Control Center. Has six individual outlets with its own built-in fuse box. Fingertouch control on-off rocker switch with jeweled on-off indicator panel light. Heavy duty line cord for use in the home, office and industry too. Complete with mounting screws for permanent installation on wall or bench, or use it as a portable control center. For 110/120 V AC/DC, 1500 watts, 15 amps. Less fuse. Shpg. wt., 1 lb. Imported.
14 N 2103 Net 4.99
 13 N 1170 Box of 5 10-amp fuses Net .28
 13 N 1171 Box of 5 15-amp fuses Net .28

3-WAY POWER CONTROL

- Individually Switched Outlets With Indicator Lights

2.49



Switchable power outlet box for wall or bench mounting. Three individually controlled outlets, each with its own indicator light. Measures 4 x 2 1/4 x 1 1/4". Equipped with 3 polarized receptacles, 3 toggle switches, 3 indicator lights, 6 ft. line cord. Rated 5 amps at 125 volts AC/DC. Shpg. wt., 1 lb. Imported
99 N 8607 Net 2.49

EXTENSION CORDS INDOORS-OUTDOORS

- 2-Wire and 3-Wire, 16 Gauge
- Molded Connectors



Use indoors and out, with power tools, refrigerators, mowers, fans, etc. All are 16-gauge, 3 cond. cords have 3 prong plug.
* 2-conductor + 3-conductor.

Stock No.	Feet	Amp.	Shpg. Wt.	Net
12 N 2301*	25 ft.	7 amp.	2 lbs.	1.35
12 N 1501*	50 ft.	5 amp.	3 lbs.	2.43
12 N 3402*	100 ft.	5 amp.	3 lbs.	4.49
12 N 3403†	25 ft.	10 amp.	1 1/2 lbs.	2.13
12 N 2502†	50 ft.	7 amp.	2 1/4 lbs.	3.51
12 N 3404†	100 ft.	5 amp.	3 1/2 lbs.	6.41

SWITCH OPERATED LAMPHOLDER AND OUTLET BOX

- Portable, Unbreakable, Weatherproof
- Provides Light and Current where Needed

6.95

Weatherproof power source with a built-in lampholder. Designed to provide power and illumination outdoors. Fills the need for garden and patio lighting. Built-in AC receptacle can supply power to electric tools, barbecues, etc., and control switch. All plastic unbreakable construction insures no metal corrosion. Has individual "stay-open" hinged switch/outlet covers. Attached stake allows easy installation. Complete with 20' of #18 three wire cord. Shpg. wt., 2 1/2 lbs.
12 N 4800 Net 6.95



OUTDOOR DUPLEX PLATE

- Weatherproofs any duplex receptacle

For outdoor AC outlets and switches. Individual "snap" covers. Rust proof brass plate with aluminum finish, rubber gasket and rubber "undercoat" mat. Shpg. wt., 8 oz.
13 N 8117 Net 1.42




WEATHERPROOF BAKELITE WALL BOX

Necessary for terminating lines in old or new work. Sturdy construction with plastic ears. Standard size: UL approved.
13 N 7001 Shpg. wt., 6 ozs. Net .75



Automotive Tools And Accessories

100 PC. TOOL KIT



- 13 piece 1/2" Drive Socket Set
- 15 piece 3/8" Drive Socket Set
- 17 piece 1/4" Drive Socket Set

Professional quality tool kit. Rugged chrome alloy withstands tough use. Kit contains 15 pc. 3/8" drive socket set, 13 pc. 1/2" drive socket set, 17 pc. 1/4" drive socket set, 18 piece Hex Key Wrench set, Tubular Hack saw, 24 Hack saw blades (10"), 8 piece midget box and open end wrench set, 1 Ignition point file, guaranteed to file any tungsten or platinum contact point, keeps ignition points clean for easy starting, ratchet sets each come packed in individual heavy gauge metal box with handle. Box wrenches also serve as

- Chrome Alloy Steel Sockets
- Over 100 carefully chosen pieces
- Steel carrying case with liftout tray

ignition wrench set. Entire kit comes packed in steel tool box (18x6x3 1/4") with lift out tote tray. Actually 7 different sets packed into one fabulous package. Not a toy kit, these are precision tools that will delight the most competent mechanic. A terrific value for homeowners, craftsmen, do-it-yourselfers, hobbyists etc. Shpg. wt., 23 lbs.

13 N 5554

29.95


ELECTRONIC CRUISE CONTROL

- Maintains Any Selected Highway Speed
- Does Not Affect Braking or Instant Acceleration
- Increases Gas Mileage by Eliminating Wasteful Speed Variance
- Helps You To Adhere To Posted Speed Limits
- Sets Fast Idle for Quick Cold-Weather Warm-Up

New Electronic Cruise Control enables you to drive at a constant speed by automatically holding the throttle steady. Eliminates the need to keep foot glued to accelerator on long trips. Once you reach desired speed, simply pull out knob and Cruise Control will automatically hold that speed. Allows instant acceleration for passing but takes over again when the foot is taken off the gas pedal. Ceases to function the moment the brake is depressed and completely disengages in the event of any malfunction. Designed to fit all cars and trucks. Shpg. wt., 1 1/2 lbs.

11 N 5901

Net 19.95



EASY TO INSTALL

2 WAY CHOKE CONVERSION KIT



- Stops Costly Gas Waste and Engine Stalling
- Converts Automatic Choke to Manual Control

Gives you finger tip control of your carburetor choke for faster starts, maximum gas savings. Dual choke never interferes with normal operation of your automatic choke. No carburetor adjustment necessary. Control bracket screws easily to lip of dash panel. You'll get proper gas mixture, improved starting and gas mileage in any kind of weather.

11 N 2301

Net 1.79

NEW! UTILITY AND TOW CHAIN



A tow chain with many useful applications other than towing around the home, farm and factory. Made of strong welded 1/4" steel links—14 ft. long, with drop forge grab hooks on each end, not ordinary S hooks. Rust resistant electro-galvanized finish for long life. Shpg. wt., 8 lbs.

11 N 5401 14 ft. Tow Chain Net 2.00

DELAY ACTION HEADLIGHT SWITCH

- Automatic Headlight Control For Safe Departure
- Fits All Cars



A true night time safety device. The delayed action switch permits your cars headlights to remain on for up to a minute after you leave, then shuts-off automatically. No more tripping around in the dark. Easy to install—fits all cars, 6 or 12 V. and does not interfere with operation of regular light switch. Shpg. wt., 6 oz.

34 N 4601 Net 2.19

WARN-O-SIGN



- Visible Day or Night
- Warns Oncoming Motorists
- No Batteries to Replace
- Attaches Easily—Always Ready

Warning sign for stalled motorists helps to prevent highway accidents. Warn-o-Sign is easily attached to hood, trunk or any metal surface by means of a rubberized metallic strip on back. Won't scratch or mar body finish. Warning message printed in luminous paint on beaded reflective screen for extreme visibility. Attaches quickly, no batteries, nothing to burn out, always ready for emergencies regardless of weather. Different messages available. Shpg. wt., 2 lbs.


11 N 8501 Caution 14x36" Net 2.95
11 N 8502 Danger 18x24" Net 2.20
11 N 8503 Send Help 12x24" Net 2.20

TWIN-DICATOR

- Warns cars left and right you wish to turn
- Simple to attach to existing electrical wiring

Chrome plated twin-dicators can be installed almost anyplace on the front fenders of your car. Gives drivers on both sides of you warning of turns and eliminates turn indicator blind spots. Three feet of wire is supplied on each indicator to allow quick and easy installation. Units are also useful as fender guides. Shpg. wt., 1 lb.



11 N 4701 Pair 6.98



LAFAYETTE ELECTRONIC TUNE-UP LAB

- Compact, Self-Contained Units
- Checks Dwell Angle, Points, Coils, Alternators, Generators, Regulators
- Completely Portable Testers
- Large, Easy-To-Read Meters
- Accurate, Do-It-Yourself Engine Testing

Complete **59⁹⁵**



Precise, compact hand-held testers with easy-to-read 2½" meter scales. Rugged phenolic case with long alligator clip leads. Complete instructions included. Overall dimensions approx. 4x2½x1½". **COIL TESTER.** Tests coils on or off engine. Also checks shorted condensers. Shpg. wt., 1.5 lbs.

11 N 5502 Net 14.95

REGULATOR-GENERATOR TESTER. 0-8, 0-16 V. DC ranges for 6 & 12 volt systems with external ¼ ohm resistor. Shpg. wt., 1.5 lbs.

11 N 5503 Net 10.00

TACHMETER. Checks engine rpm, cylinder balance. 2 ranges: 0-1200 rpm, 0-1600 rpm. For 4, 6 and 8 cylinder cars. No jitter. Color coded scale. Shpg. wt., 1.5 lbs.

11 N 5504 Net 21.00

DWELL METER. Accurately measures cam angle at all engine speeds. 2 scales. For 4, 6, 8 cylinder engines; 6 or 12 volt. Uses solid state circuitry. Shpg. wt., 1.5 lbs.

11 N 5505 Net 14.95

ALTERNATOR DIODE AND IGNITION WIRE TESTER. Tests diodes in and out of alternator. Checks windings and ignition wire. Simple to use. Shpg. wt., 1.5 lbs.

11 N 5506 Net 11.50

Complete Tune-up Lab plus case. Includes all 5 Testers.

11 N 5501 Shpg. wt., 8 lbs. Net 59.95

11 N 5507 Case only. Shpg. wt., ½ lb. Net 3.95

LAFAYETTE DWELL TACHOMETER

- Tunes up electronically, any car ever made
- Three Dwell Scales
- Giant, Easy-to-Read Scale
- Use to Adjust Carburetors

A complete ready-to-use Dwell Meter and Tachometer which will operate on any car ever made. Tests cam Dwell angle and engine RPM on 4, 6 or 8 cylinder cars, 6 or 12 volt right on the engine. Giant, 6½" easy-to-read meter makes it simple for anyone to adjust points which are slightly worn or pitted. Adjusts carburetors to insure maximum gas economy and quiet engine running. RPM readings are also essential to properly service automatic transmissions. Three dwell angle scales are provided: 0 to 45 degrees, 0-60 degrees, and 0 to 90 degrees. This instrument is suitable for dwell angle adjustment on all foreign and domestic cars. Dual range tachometer 0 to 1000 rpm for precise carburetor adjustments, 0 to 5000 rpm. suitable for making all other tests at high engine speeds.

Shpg. wt., 4 lbs.


11 N 0101

Net 20.50

Completely Wired—
Not a Kit!


28⁵⁰

Made in
U.S.A.



AUTOMOTIVE TESTING EQUIPMENT

198



15⁹⁵

(A) MOTOR ANALYZER

All the advantages of a well-equipped service shop in a light, hand-held package. Ideal for do-it-yourselfers, sports car Rallyers, etc. The Analyzer enables you to test ignition coil output, spark plugs, insulation breakdowns; locate poorly adjusted carburetor, sticky or burnt valves, weak valve springs; checks valve timing, choke, muffler vacuum tank, manifold, fuel pump vacuum and pressure and vacuum operated equipment. 14Wx7¾Hx3½"D. Shpg. wt., 5½ lbs.

11 N 1701 Net 15.95

(B) REMOTE STARTER SWITCH

Eliminates the need of a second man when making compression, fuel pump, generator, starter, and electrical tests. Permits the mechanic to crank the engine from any position. Shpg. wt., ½ lb.

11 N 1702 Net 1.00



279

295

(C) MOTOR GUIDE-VACUUM FUEL PUMP TESTER


Combination motor guide, vacuum and fuel pump tester. 4 color zones: Economy Driving, Fast Pick-up, Coasting and Idle. Promotes good driving habits and economical gas mileage. Warns when tuneups are necessary. Shpg. wt., 12 oz.

11 N 1703 Net 2.95

(D) COMPRESSION TESTER

Gives quick, accurate readings of compression pressure. Merely unscrew the spark plug, plug tester into spark plug hole and read pressure. 2½" dial reads to 300 lbs. Stem is offset 15° for reaching back cylinders. Complete with instructions. Shpg. wt., 12 oz.

11 N 1704 Net 2.79



269

28⁵⁰

(E) STANDARD TIMING LIGHT

Employs the stroboscopic principle of light synchronized with motion for adjustment and setting of ignition timing under actual operating conditions. Shpg. wt., 1 lb.

11 N 1705 Net 2.60

(F) TACHOMETER

Here's the instrument for the most important check of an engine's performance: the RPM test. Tests 4, 6 and 8 cylinder engines with both 6 and 12 volt systems. Operated by two inexpensive penlight batteries which last about a year. Large dial read 0-1000 and 0-5000 RPM. Shpg. wt., 2½ lbs.

11 N 1706 Net 20.50



3⁹⁵ CAM-DWELL INDICATOR



A high quality instrument for solving all CAM-DWELL problems. Checks the number of degrees a distributor can rotate while the breaker points remain closed. Too much

rotation means points are set too close, too little means breaker points are not closed long enough for adequate build up of the magnetic field in primary coil, permitting arcing across points. Requires no electrical outlet. Distributor need not be removed. Compact, portable. Complete with case and includes chart showing specifications for all popular cars.

11 N 1009 Shpg. wt., 2 lbs. Net 3.95

TIMING & OCTANE SELECTOR

- Advances or Retards Spark As You Drive
- Spark Indicator Light Shows Engine Load

Recover the gas mileage and power your car is now wasting with this Timing and Octane Selector. Enables you to dial-in the most effective spark timing from the dash, as you drive. Harmful ping and spark knock are eliminated—you get premium performance from regular gas. Will not interfere with your distributor's advance mechanism. Mounts on your dash. Simple, do-it-yourself installation instructions—no tools needed.

11 N-3601 Shpg. wt., 1¼ lbs. Net 4.54



4⁵⁴

LAFAYETTE Values in Auto Accessories

warns of radar traffic zones

DRIVER ALERT *



• Dual Band Circuit Detects Radar Beams on Both "S" and "X" Frequencies • Gives Advance Warning Within 1/2 Mile Range • Miniature and Completely Transistorized • No Wires or Antennas Needed

29⁹⁵

Driver Alert, the miniature electronic detector, warns you of radar traffic zones in advance—up to 1/2 mile away. The Dual-Band circuit detects all commonly used police radar speed meters and traffic control devices to promote safer driving. Miniaturized and completely transistorized. Driver Alert does not require wires or antennas. Constructed of top quality components; printed wiring; 8 transistors; two 1,000 hour mercury cell, self-testing batteries (equivalent to 35,000 miles of driving at 35 M.P.H.) Magnesium case eliminates radio, TV and other interference. Weighs only 13 ozs., measures 3 1/2" x 2 1/4" x 3 1/4" D; clips to sunvisor. Complete with batteries, sunvisor clip. Instructions included.

11 N 4201 Shpg. wt., 1 1/2 lbs. Net 29.95

*This item not intended for resale in States where its use is forbidden in motor vehicles by public regulation.

NEW GAS MASTER INDICATOR



12⁸⁸


- Automatically Gives The Exact Miles Per Gallon AT A Glance
- Reads Manifold Pressure
- All Chromium Die Cast Case
- Illuminated Dial
- Fits All Cars

Now you can drive with real gas economy. The Gas Master shows you clearly and instantly your actual miles per gallon, at all cruising speeds. Big easy-to-read dial indicates both mph and engine manifold pressure. Three Color Zone (Power-Economy) indicates fuel economy and engine power at a glance. Fully illuminated for good night

visibility. Can be mounted in minutes, in, on or under your dash, on steering column or in center console. Highly polished chromium case. Fits all cars. Shpg. wt., 2 1/2 lbs.

11 N 4400 Net 12.88

AUTO SEAT BELTS



- Positive Latching
- Exceeds SAE and GSA Standards

Fig. (A) A new engineering concept in auto seat belts. Slide-lock, metal to metal buckle mechanism for positive safe action. Simple to unlock even if buckle turns over. Slide lock and dual grip buckle are formed of aircraft steel—custom chromed with a gold emblem insert. A full 90" belt made of quality, wrinkle-proof material. Pebble weave webbing comes in 8 colors. Shpg. wt., 2 lbs.

Fig. (B) A quality belt designed of heavy duty aircraft steel and triple stitched webbing. Conventional flip buckle with positive latching and release. Don't let the price fool you. These belts exceed all state, SAE and GSA standards. 8 colors. All hardware provided. Shpg. wt., 2 lbs.

Stock No. (A)	Color	Stock No. (B)
11 N 5701	Black	11 N 5709
11 N 5702	Grey	11 N 5710
11 N 5703	Beige	11 N 5711
11 N 5704	Flame Red	11 N 5712
11 N 5705	Naroon	11 N 5713
11 N 5706	Powder Blue	11 N 5714
11 N 5707	Royal Blue	11 N 5715
11 N 5708	Turquoise	11 N 5719

Net ea. 4.75 Net ea. 2.99

AUTO SEAT BELT RETRACTORS




- Rolls Up Seat Belts Automatically When Not in Use
- No Belts Caught in Doors
- Keeps Seats Neat

Auto seat belt retractors fit any car seat belt — installs quickly on belts without removing them from car. Belts roll up automatically when not in use — cannot catch in doors. Lightweight, stainless steel and aluminum construction. Installs in seconds — no tools necessary. Shpg. wt., 1/2 lb. 11 N 2403 Net pair 1.49



1⁴⁹

AH-OO-GAH! HORN



10²⁹


- Chrome Plated Bell

A real joy for the sports car enthusiast. An authentic meter driven horn approved as an exact reproduction in sound and appearance by members of antique car, hot rod, and horseless carriage clubs the world over. Chrome plated bell with black wrinkle painted housing.

11 N 3001 6-volt Net 10.29
11 N 3002 12-volt Net 10.29

CHILD'S SEAT BELT HARNESS

6⁸⁹



"Sit and Stand" Model for Maximum Freedom of movement. Safety-Tested to Exceed 2,000 lbs. Easily Installed in Any Car.

Scientifically designed seat belt harness for children up to 6 years of age. Complies with Society of Automotive Engineers' standards. Shoulder harness supports upper torso; leg straps give pelvic support to child whether sitting or standing — offers complete protection to active children. Has quick-release aircraft-type metal-to-metal buckles, strong all-nylon webbing. Fully adjustable for size to give child maximum freedom and comfort. Complete with patented floor hardware for firm anchoring. Shpg. wt., 1 1/2 lbs. 11 N 2404 Net 6.89

Plainfield, N. J. 139 W. 2nd Street

CUSTOM-FIT HEADREST



Makes Any Car Seat A Contour Chair

6⁹⁵

Now you can make your car seat really comfortable with this advanced design headrest. Helps prevent whiplash too. Dorsal contilever design keeps headrest snug against back of neck and head. Locks to seat automatically. 3 Knobs, finely calibrated gives 4-way adjustment to custom fit any individual, chair or car seat. Full 5" vertical adjustment; 4" forward and back. Looks like original equipment. Made of soft vinyl plastic with molded wing rests. Shpg. wt., 2 lbs. 11 N 1201 Black only Net 6.95

TRANSISTORIZED ILLUMINATED TACHOMETER



- 4-6-8 cylinder, 6 or 12 Volt, Neg. or Pos. Ground!
- Accurate 0-8,000 RPM Scale
- Regular or Transistor Ignition
- Heavy Chrome Die Cast Case
- 360 Degree Mounting Adjustment

only

19⁹⁵

Here is the modern electronic guide to make your driving more efficient and more fun. Illuminated 3" dial face and electro magnetic meter movement, accurately measures engine speed from 0 to 8000 RPM. Helps reduce gas, oil bills, prevents over speeding and eliminates costly repairs due to improper engine operation. Factory calibrated, no adjustments required. Separate sending unit is a transistorized magnetic amplifier for constant accuracy; easy installation. Universal mounting for above, or below dash or steering column. For regular or transistorized, 6 or 12 volt and negative or positive ground ignition systems. Works with 4, 6 or 8 cylinder cars. Chrome tach head. With clamp. Shpg. wt., 2 lbs. 11 N 4202 Net 19.95

LAFAYETTE Values in Auto Accessories

MOTOROLA TRANSISTOR IGNITION SYSTEM

37⁵⁰



Automatic ignition systems long have been responsible for a large share of car and truck maintenance, as well as emergency servicing. Deterioration of breaker-points, condenser and spark plugs are the most frequent causes as trouble. As plugs become fouled, it takes more voltage to fire them — voltage that conventional systems do not provide because the breaker points would have even shorter life. With this transistorized system, only a small amount of current is needed to "trigger" the much larger coil current and the condenser is eliminated. Circuits are separated so only the triggering current passes through the points. An advanced high turns ratio coil is incorporated. Voltage does not roll off at higher engine speeds. Points do not burn. Gas mileage increases as does the acceleration "snap." Transistor amplifier is protected by 2 Zener diodes and sealed to prevent dust and dirt build-up. For 12-volt negative ground ignition systems. Complete with simple installation instructions. Shpg. wt., 5 lbs.

11 N 7504 Net 37.50
Hi-Power Switching Relay for above. Insures "cold" starting. Bypass relay provides maximum current flow. Shpg. wt., ½ lb.
11 N 7505 Net 5.65

LAFAYETTE ILLUMINATED AMMETER & OIL PRESSURE GAUGES

4⁹⁹


- Complete with Cable and All Standard Fittings



Keep a constant check on the condition and performance of your car's electrical and oil pressure systems. The ammeter calibrated in 60-0-60 scale measures the actual rate of current flow . . . helps prevent generators from burning out and overcharging or discharging the battery. Exact oil pressure from 0 to 80 lbs. is indicated. Easily installs in any 6 or 12 volt car below the dash, without drilling or can be mounted right in the dash. Both meters are mounted in an attractive chrome panel. Easy to read meters feature 1¾" diam. black dial faces with calibrations in white. Size: 5¼Wx2¾Hx2¼"D. Supplied with 6 and 12 volt bulbs and wire, all necessary fittings plus full instructions.
99 N 8501 Imported. Shpg. wt., 1½ lbs. Net 4.99
11 N 8004 Tee Fitting Net .49

MOTOROLA ALL-ELECTRONIC ALTERNATOR SYSTEM

35-Amp System 50.63
40-Amp System 57.38
55-Amp System 60.75



- All-Transistor Voltage Regulator and 7-Diode Alternator
- Extends Battery Life
- **Guaranteed For 3 Years (or 30,000 Miles)***

Low cost solution to the heavy demands made by your car on its electrical system . . . Unlike D.C. generators, it supplies a charge at idle speeds and keeps the battery at a uniform high level of charge. The all-transistor voltage regulator has no contact points to stick or burn. Fits all domestic cars with 12-volt, negative ground electrical systems. The complete system includes: Alternator (with standard-size pulley); all-transistor regulator (with all connecting wires); universal mounting bracket; instructions for installation.
11 N 7501 35-Amp (wt., 12 lbs.) Net 50.83
11 N 7502 40-Amp (wt., 13 lbs.) Net 57.38
11 N 7503 55-Amp (wt., 15 lbs.) Net 60.75
*Manufacturer's guarantee covers repair or replacement of parts proven defective in normal use within 3 years or 30,000 miles, (whichever occurs first).

LAFAYETTE 2-TRANSISTOR ELECTRONIC IGNITION SYSTEM

24⁹⁵



- FULL POWER AT HIGH RPM • ELIMINATES POINT PITTING AND CONDENSER
- EASIER STARTING ESPECIALLY IN WINTER
- INCLUDES RELAY FOR HIGH CURRENT SWITCHING

This 2-transistor ign. system will take the needless burden of high current off of your points and deliver a constant high power spark even at speeds exceeding 10,000 RPM. Modern 2-transistor circuit switches and controls the coil primary circuit through a combination amplifier-electronic switch action. Reduces point current to a low value and with proper use extends their life to the life of the car. Carries 100% primary current to over 20,000 RPM. A special low-inductance design coil delivers constant full voltage at all speeds. Full high spark voltage to over 10,000 RPM. Spark plugs last longer due to complete burning of fuel. Condenser replacement and problems are eliminated because the circuit eliminates the condenser altogether. Switching relay relieves ignition switch drain and loss of power due to long wires. High gas mileage and low timing drift make use very efficient. Transistors are removable and unit is serviceable! System includes double insulated coil, epoxy potted amplifier, ballast, and relay. Shpg. wt., 5 lbs.

11 N 0103 For Negative Ground Systems Net 24.95
POINT INSULATION KIT: adapts transistor ign. kits to permit uses with positive ground systems.
11 N 0104 Shpg. wt., 3 oz. Net 2.50

ILLUMINATED VOLTMETER KIT

6⁴⁹

- Indicates Battery Voltage
- Large 2" Illuminated Meter



Designed for the car owner who desires more than a red light to indicate electrical system performance. May be installed on any generator equipped auto having either a 12-volt positive or negative ground system. Complete with bracket, 6/12-volt illuminating kit, hardware and instructions.

11 N 8002 Shpg. wt., 1 lb. Net 6.49

ILLUMINATED WATER TEMPERATURE GAUGE KIT

- Range 100-220°F
- 2" Diameter Dial
- Hermetically Sealed

4⁸⁸



Heavy-duty vapor tension thermometer which indicates from 100 to 220 degrees fahrenheit on a 2" diameter dial. Has 72" of armored capillary tubing with ½" male pipe thread adapter plus hose adapter for installation direct to radiator hose or motor block. Includes mounting bracket, 6/12-volt illuminating kit, hardware and instructions. Shpg. wt., 2 lbs. Imported.

99 N 8506 Net 4.88

Lafayette HOT CAR-GO Starts Your Car INSTANTLY

- Starts Wet or Cold Motors Instantly
- Saves Battery and Gasoline
- Installs Easily and Quickly
- 6 and 12 Volt Cars

2⁹⁵



Avoid excess wear and tear on your motor and battery—install Lafayette's Hot Car-Go. Provides 5 times the normal spark for fast starting in any weather, and automatically disconnects when engine is running. Will not damage plugs or distributor. Simple to install—instructions included. Shpg. wt., 1 lb. Imported.

99 N 8511 Net 2.95



MOTOROLA ALL NEW SOLID STATE AUTOMOBILE RADIOS

MOTOROLA GUARANTEE
Full 2-year warranty on all parts and labor. Manufacturer's guarantee covers free exchange or repair of any component proven defective in normal use.



39⁹⁵

\$5 Monthly
For Under Dash Mounting



59⁹⁵

\$5 Monthly
Plus Free Mounting Kit. Specify Make, Model, Year of Car.



39⁹⁵

\$5 Monthly
For Under Dash Mounting



51⁹⁵

\$5 Monthly
Plus Free Custom Mounting Kit. Specify Make, Model, Year of Car.



59⁹⁵

\$5 Monthly
Plus Free Custom Mounting Kit. Specify Make, Model, Year of Car.

NEW MOTOROLA FM/AM CAR RADIO Model FMA200



- FM Response 50-15,000 cycles
- Special Acoustinator Circuit
- 14 Transistors, 7 Diodes
- Push-Pull 8 Watt Audio System
- FM/AM Indicator Light

For 12 Volt-Negative Ground Systems

129⁹⁵

Fine FM/AM entertainment is combined in one car radio to bring you enjoyable listening on both broadcast bands. Powerful circuitry incorporates 14-transistors plus 7 diodes and 1 thermistor. FM section delivers full frequency response of 50-15,000 cycles through a powerful 8-watt push-pull audio circuit. Push button activated acoustinator circuit minimizes interference in primary signal areas. Low battery drain (.5 amp), instant warm-up and FM/AM indicator light are extra features. Includes full variable tone control, 5x7" Golden Voice Speaker. For 12 Volt-negative ground systems. 7 $\frac{1}{4}$ "x2 $\frac{1}{2}$ "x6 $\frac{3}{4}$ "D. Shpg. wt., 13 $\frac{1}{2}$ lbs.

17 N 1011X Model FMA200 \$6.50 monthly Net 129.95

78 Lafayette Cat. No. 653

7-TRANSISTOR MANUAL CAR RADIO

- For 6-Volt Systems
- 8 Tuned Circuits

Compact, universal set designed to fit 6-volt sports cars, trucks, boats and older cars under dash or with optional in-dash installation. Solid state circuitry with 7 transistors, 2 diodes and 1 thermistor has advantage of low battery drain, cool operating chassis and "instant play"—no warmup necessary. Also features 8-tuned circuits for improved selectivity, built-in 5" Golden-Voice™ speaker, thumbscrew antenna trimmer, rear speaker jack and black "leather texture" front panel. For 6-volt cars—reverse polarity. Size 6 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "x7 $\frac{1}{4}$ "D. Shpg. wt., 6 lbs.

17 N 1018 Model TM 415M Net 39.95
Custom Mounting Kit for In-dash installation, Specify Make, Model, Year of Car, Shpg. wt., 1/2 lb.
17 N 1019CY Net 2.95

DELUXE 7-TRANSISTOR PUSHBUTTON CAR RADIO

- For 6-Volt Systems
- 8 Tuned Circuits

Custom deluxe, solid-state radio delivers standard AM broadcasts with rich tone through an external 5" Golden Voice Speaker. 7 transistors, 2 diodes and 1 thermistor operate with low battery drain and cool chassis for long life. With Solid-state circuitry radio plays instantly—no waiting for warmup. Features 8 tuned circuits for improved selectivity. 5 fingertip push buttons, thumbscrew antenna adjustment and variable tune control for more enjoyment of musical programs. For 6-volt cars, reversible polarity. Size: 6 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "x7 $\frac{1}{4}$ "D. Shpg. wt., 7 lbs.

17 N 1020CM Model TM 625A Net 59.95

5-TRANSISTOR MANUAL CAR RADIO

- For 12-Volt Systems
- 8 Tuned Circuits

Compact universal set designed to fit 12-volt cars—under dash or with optional in-dash installation. Solid state electronics provides low battery drain, cool operation, instant-play—no waiting for warmup. Features 5-transistors, 2 diodes, 1 thermistor, 8 tuned circuits for improved selectivity and interference rejection, variable tune control and built-in 5" Golden Voice Speaker. Beautiful panel has "leather texture" look. For 12-volt cars reverse polarity. Size: 6 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "x7 $\frac{1}{4}$ "D. Shpg. wt., 7 lbs.

17 N 1021 Model TM 325M Net 39.95
CUSTOM MOUNTING KIT for In-Dash Installations. Specify Make, Model, Year of Car. Wt. 1/2 lb.
17 N 1022CY Net 2.95

DELUXE 6-TRANSISTOR MANUAL CAR RADIO

- For 12-Volt Systems
- Push-Pull Audio For Hi-Fi Sound

Custom universal AM radio featuring push-pull audio for full power hi-fi sound. Adjustable shafts fits most cars. LumaAlert warning device which signals through cars speaker when headlights are left on. Cool running solid state circuit has 6 transistors, 2 diodes and 1 thermistor. 8-tuned circuits for improved selectivity, variable tone control for sound balancing and thumbscrew antenna trimmer. 5x7" Golden voice external speaker. For 12 volt negative ground systems only. Size 7 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "x5 $\frac{1}{4}$ "D. Shpg. wt., 7 $\frac{1}{2}$ lbs.

17 N 1023CM Model TM5M Net 51.95

DELUXE 6-TRANSISTOR PUSHBUTTON CAR RADIO

- For 12-Volt Systems
- Push-Pull Audio For Hi-Fi Sound
- Unique LumaAlert Warning Device

High quality custom AM radio featuring cool operating, reliable solid state circuitry, push-button tuning push-pull audio output for greater power less distortion, and unique LumaAlert warning device which signals through cars speaker when headlights are left on. 8 tuned circuits 7 transistors, 2 diodes, 1 thermistor. Adjustable shaft fits most cars. With 5x7" Golden Voice Speaker, variable tone control, thumbscrew antenna trimmer. For 12-volt negative ground electrical systems only. Size: 7 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "x5 $\frac{1}{4}$ "D. Shpg. wt., 8 lbs.

17 N 1024 CM Model TM5A Net 59.95

MODEL FMC62 AUTO FM TUNER



- Quick underdash Installation
- For 12-volt negative ground installations

64⁹⁵

The model FMC62 is available for those who prefer an FM tuner which operates through the AM radio. Compact underdash installation made quickly. Specs: 7 tubes; battery drain is 1.4 amps; tuning range is 88-108 MC; sensitivity—3 μ v (avg); for 12 volt negative ground. Automatic gain and Frequency controls for "one setting" listening pleasure. Size: 6 $\frac{3}{4}$ " wide, 2 $\frac{1}{4}$ " high, 8 $\frac{3}{8}$ " deep. Shpg. wt., 8 lbs.

17 N 1012 \$5 monthly Net 64.95


Paramus, N. J. 182 Route 17

LAFAYETTE — for your Auto Radio Pleasure

LAFAYETTE SOLID STATE AUTOMOBILE REVERBERATION SOUND SYSTEM

FROM LAFAYETTE . . . AUTO REVERBERATION —

A 3rd DIMENSION IN SOUND



23⁹⁵

Made in U.S.A.

- For all 12-volt Negative Ground AM&FM Auto Radios
- Simple—Easy installation

The Lafayette solid state Automobile Reverberation sound system consists of the transistorized amplifier chassis with the reverberation unit, under dash control plate with on-off switch, fader control, and interconnecting cables. Includes simple instructions for connecting the reverb unit to your regular under dash auto speaker, and to a separate rear seat speaker (if your auto does not have a rear seat speaker, see listing of rear seat speakers on page 81. Reverberation is an entirely different approach to sound reproduction. Normal sound reproduction from a single source has a flat, one dimensional effect; with proper sound delay through "REVERBERATION," tones are created with a truly third dimension for concert hall originality. Mounts conveniently in the trunk of your car. For all 12-volt negative ground AM or FM auto radios. Dim: 10½x1x6". Shpg. wt., 3 lbs.

17 N 0105

Net 23.95

NEW BLAUPUNKT DERBY FM/AM, SW and MB PORTABLE CAR RADIO


ALL TRANSISTOR FM-AM AUTO RADIO

Only

84⁹⁵

\$5 monthly

2 Quality Car Radios in One



- Use It As a Portable—Install it in your Car
- 4 Bands—FM, AM, Shortwave and Marine Band
- 11 Transistors

Carry it as a portable or install it in your car using an optional easy-to-install adapter that disappears under the dash when not in use. Plays for approx. 300 hours on 6 inexpensive 1½-volt flashlight batteries (not supplied). A built-in ferrite antenna is used for AM reception; a retractable, pivoting telescopic antenna for shortwave/FM reception. Has push/pull output stage and sockets for earphone, tape recorder and record player. Also has a variable tone control for true hi-fi music reproduction. Attractively housed in a black featherette case. Size: 9¾x7¾x3½". Shpg. wt., 7 lbs. Made in West Germany.

17 N 1517XL Net 84.95

Universal Mounting Bracket, with lock, for auto use (6 or 12 volts—reverse polarity)

17 N 1518 Net 19.00

"D" size flashlight battery (6 req.) for portable use. Net ea. .13


32 N 4804

only

79⁹⁵

\$5 Monthly

MADE IN U.S.A.



- Push-pull Hi-Fi Output
- Convenient Under-Dash Installation
- 12-volt, Negative Ground Operation
- AFC for FM Drift-Free Performance
- High Sensitivity for Super Distant Reception on Both AM and FM
- 11 Transistors, 6 Diodes, 1 Thermistor
- Four Stages of I.F. Amplification on FM for Maximum Noise Limiting

A fully transistorized AM-FM radio with many HI-FI features. Instant play—just turn it on and immediately enjoy either AM or FM listening pleasure. Extremely sensitive for "pulling in" distant stations. A push-pull Hi-Fi output provides 10 watts of peak power which is more than enough to fill your auto with sound. Low battery drain—1 amp @ 8 watts output. Specs: 11 transistors, 6 diodes, 1 thermistor; tuned circuits—7 on FM, 5 on AM; Sensitivity: 3 µv for 20 db quieting; Speaker—external 3.16 oz. Alnico magnet; for 12-volt; negative ground installations. Dimensions: 6¼x2¼x6¼"D. Shg. wt., 8 lbs.

17 N 7701

Net 79.95

ALL-TRANSISTOR MANUAL AUTO RADIO COMPLETE with FREE ANTENNA

DELUXE PUSH-BUTTON VOLKSWAGEN RADIO with FREE VW ANTENNA



29⁹⁵

MADE IN U.S.A.


- 5 transistors and 2 diodes
- Large easy to read illuminated dial
- Convenient underdash mounting
- For 12-volt negative ground installations

A fine quality AM radio that utilizes "solid state" construction in a Superheterodyne circuit for trouble-free operation. Finger-tip control to adjust tone as you desire. Also contained is an electronic automatic volume control to keep signals strong and steady. This unit is exclusively hand wired for ruggedness—no printed circuitry. Fits under-dash or in-dash utilizing standard trim plates. Available for 12-volt negative ground installations. Neutral gray-tan baked enamel finish. Overall size: 5½x2x6½x2"H. Shpg. wt., 4½ lbs.

17 N 7405M Net 29.95

44⁹⁵

- 5 Watts Superb Audio Power
- Easy Installation
- Transistorized Circuitry



Now, the Volkswagen owner can enjoy music in his auto with this deluxe push-button radio that was especially designed to compliment the Volkswagen. Features an all-transistor circuit which gives a full 5 watts of superb audio power. Automatic volume control provides constant, even, comfort-level listening. Continuously variable tone control allows precision adjustment of both high and low frequencies so that bass and treble may easily and effectively be adjusted to the individual taste of the listener. Five quick-set push buttons mean instantaneous, fluid, finger-tip station tuning. Seven tuned circuits, including RF stage, give maximum sensitivity and selectivity in station choice. May be installed in the instrument panel in a matter of minutes. Lastly, to complete the package, includes a free antenna which is designed for the Volkswagen. Shpg. wt. 7½ lbs.

17 N 7408

\$5 Monthly Net 44.95

World's Foremost Supplier of Electronic Components

Lafayette Cat. No. 653 79


Auto Tape Player, Radio and Antennas

DELUXE TRANSISTORIZED CAR STEREO TAPE PLAYER

- Hear the Music You Want, When You Want It
- Easier To Operate Than a Car Radio
- Up to TWO HOURS of Listening Pleasure

149⁹⁵

\$7.50 Monthly



PRE-RECORDED TAPES FOR CAR STEREO TAPE PLAYER

"On A Visit To Spain" O'Artega conducts Symphony of the Air. 20 N 6101 Shpg. wt., 1 lb. Net 6.95
 Lerner & Loewe's "My Fair Lady." Shpg. wt., 1 lb. Net 6.95
 20 N 6102 Familiar Favorites from the World's Greatest Music. Net 6.95
 The Fabulous Pied Pipers serenade Tommy Dorsey. 20 N 6107 Shpg. wt., 1 lb. Net 6.95
 20 N 6108 The Fabulous Pied Pipers serenade Tommy Dorsey. Net 6.95
 20 N 6109 Shpg. wt., 1 lb. Net 6.95
 The Fabulous Frank Loesser "In Percussion." 20 N 6110 Shpg. wt., 1 lb. Net 6.95

You can now forget about tuning problems, fading, static and other annoying features that you have come to expect with the auto radio. The quality of the stereo music has the same undistorted timbre and brilliance no matter where you drive. Easier and more simple to operate than a car radio! The completely self-contained prerecorded plastic cartridge has been standardized by all manufacturers. Simply slip the cartridge onto the deck. Push the starting lever and that's all. The endless loop tape will give you up to 2 hours of music of your choice. Tape player and cartridges are shock proof. The roughest roads will not affect the performance. Installation is simple and fool proof. Electrical connections consist of one power lead, when the unit is well grounded to the vehicle, and one lead each to each speaker. Specifications: Tape speed 3 3/4 ips; Controls—volume, balance, tone controls, starting lever and track selector. Amplifier—10 transistors. Output 2 watts per stereo channel. Size 9 5/8x9Dx3 1/2"H. Shpg. wt., 20 lbs.

17 N 6501WX Net 149.95
 Switch and Wiring Harness. Can be used with any car stereo tape player when using front and rear speakers in car for stereo. Shpg. wt., 1 lb. Net 6.95
 17 N 6502

RANGER PLAY-MATE 8-TRANSISTOR AUTO/PORTABLE AM RADIO



47⁵⁰


5.00 monthly

- The Auto Radio You Can Enjoy Wherever You Go, Whatever You Do
- A Deluxe Car Radio as well as a Powerful Portable Radio
- Operates on Auto or Boat's 12-Volt Power Supply, or 4 Penlite Batteries
- Locks in Place in Car or Boat—Prevents Theft

The Ranger Play-Mate plays everywhere, goes anywhere. Insert it in its mounting case and it operates on car or boat 12 volt power supply like any other permanently-installed radio... slip it out and you have a powerful lightweight portable with a metallic gold finish, powered by its own penlight batteries (not included). Radio locks in place in car or boat, prevents theft. 8 transistors, plus diode plus thermistor super-het circuit with H.F. amplifier. 3 1/2" speaker. For 12V negative ground, positive ground cars. Shpg. wt., 6 lbs.

17 N 7407 Net 47.50
 32 N 4802 Battery For Portable Operation (4 required) Net .13

AUTO RADIO ANTENNAS



CONTINENTAL SINGLE SIDE MOUNT (1)
 Continental single side mount for foreign car. The only aerial that fits a Volkswagen Flexible adjustment with unique vertical locking. 3 section. Extends to 56". Shpg. wt., 1 lb. Net 1.98
 11 N 8801

"FLEX-O-MATIC UNIVERSAL ANTENNA (2)
 Heavy-duty, bounce-back, spring mount. Fully adjustable—mounts anywhere. 3 sections. 54" extended, 27" collapsed. 48" detachable lead. Shpg. wt., 2 lbs. Net 2.79
 11 N 7407

UNIVERSAL MOUNT AERIAL (3)
 Can be mounted anywhere on car. Adjusts to any angle. 3 section, measures 20" collapsed, extends to 57". Complete with 48" lead. Shpg. wt., 1 1/4 lbs. Net 2.49
 11 N 7411

SPRING BACK REPLACEMENT STAFF (4)
 One piece, stainless steel, spring mounted replacement staff. 28 1/2" long overall. Mounts over stub of old antenna. Fits all cars. Simple set screw installation. Shpg. wt., 8 oz. Net .99
 11 N 7406

DISAPPEARING ANTENNA (5)
 For concealed installations. Extends to 50". Fully collapsible—only mounting protrudes. 48" lead. Shpg. wt., 2 lbs. Net 2.95
 11 N 7402

LO-BOY DISAPPEARING ANTENNA (6)
 For shallow installations, foreign and sports cars. Takes only 9 1/2" below fender or deck. Extends to 25" collapses to 3 1/2". 36" permanent lead. Shpg. wt., 1 lb. Net 2.29
 11 N 7403

KEY-TENNA (7)
 Slides completely into mounting base. Locks with key rendering the antenna theft proof. 16 1/2" below fender, ext. 43". Shpg. wt., 1 lb. Net 2.59
 11 N 7404

REPLACEMENT ANTENNA STAFF (8)
 3 section 50" replacement staff. Telescoping staff replaces antenna lost through accident or vandalism. Mounts on stub of broken antenna. Simple lock on mount. Shpg. wt., 8 oz. Net 1.10
 11 N 7405

TOP COWL MOUNT (9)
 3 section antenna measures 20" collapsed, and extends to 56". Mounts on polyethylene insulator. Shpg. wt., 1 1/4 lbs. Net 1.89
 11 N 7401

"TENNAMATIC" ELECTRIC AUTO ANTENNA

- Electrically Raises & Lowers Automatically
 - Eliminates Vandalism
- As Low As **19⁸⁸**



Operate the antenna at the flip of a switch. Designed to fit most 12 volt cars. Mast extends to 35" and retracts to 1 1/4". Antenna cable is copper shielded. External parts are plated with chrome. Positive 15 lbs. thrust insures "free action" even in sub zero temperatures. Complete with cable, clips, brackets switch and plate, screws, wiring harness and instructions. Shpg. wt., 6 lbs.
REAR MOUNT—18 feet of antenna lead and 20 feet electric harness. Net 20.50
 11 N 7102
FRONT MOUNT—54" of antenna lead and 27" electric harness. Net 19.88
 11 N 7101

DYNAMIC AUTO TENNA BOOSTER

- For New Transistor Auto Radios
- Increases Radio Range and Reception
- Electronically Equivalent to 110-ft. Antenna



Increases the signal strength and range of your auto radio with the new Dynamic Auto Antenna Booster. Brings in distant and weak stations stops station-fade. Installs easily in 4 simple steps. Fits all except 4 sect. Antennas. Shpg. wt., 1/2 lb. Net 1.99
 11 N 8902

Auto Speaker Kits-Accessories

REAR SEAT SPEAKER KITS FOR TRANSISTORIZED RADIOS



- Features Multi-impedance Match For 40, 20, 8 ohms or less
- New Slim Line Construction

Complete 6x9" rear seat kit featuring new multi-impedance Slim line 6x9" speaker; chrome grill, 100 ohm Fader control, 40 ohm adaptor for Motorola Radios, and a 20 ohm adaptor for Automatic radios. Shpg. wt., 6 lbs.

32 N 2202 Net 4.69

Special Custom Rear Speaker Kit. Same as above but for the following cars: Impala, Bonneville, Invicta, and 2 door Custom Autos equipped with 40 ohm Motorola or 20 ohm Automatic radios—less grill 5 lbs.

32 N 2203 Net 3.99

MULTI IMPEDANCE SPEAKERS IN NEW SLIMLINE CONSTRUCTION

Stock No.	Size	Shpg. wt.	Net
32 N 2204	6x9" w. jumper wires	2 1/2 lbs.	3.25
32 N 2205	6" Rd. w. jumper wires	2 lbs.	2.75
32 N 2206	4x6" w. jumper wires	1 1/2 lbs.	2.46

LAFAYETTE REAR SEAT SPEAKER KIT



275

- Fits Compacts, Station Wagons
- Fits Foreign Cars, Sports Cars
- Prewired—Self Contained
- 3-Position Switch

Easy to install, it will fit any auto radio in any domestic or foreign car. Finished in a gleaming chrome shock resistant case, it can be hung up or clipped on almost anywhere. Includes all necessary wire, instructions and 3-position switch for front, rear or 2-speaker operation. Shpg. wt., 12 oz.

99 N 6122 Net 2.75

REAR SEAT AUTO SPEAKER KITS



AS LOW AS 2.98

6" x 9" Kit With Chrome Grille
Complete kit for adding second speaker in rear of your car. Includes a 6x9" PM speaker, 3-position selector switch for cutting in front, rear, or both speakers; dial plate with mounting bracket, knob, and hardware; chrome grille; wire; and wiring instructions. Simple to install. Shpg. wt., 5 lbs.

32 N 2207 Speaker kit Net 3.45

Deluxe 6" x 9" Kit with 2.15 oz. Alnico V Magnet

Same as above but with deluxe speaker with extra-heavy Alnico V magnet (2.15 oz.). This is same speaker used in kits selling at twice the price. Shpg. wt., 5 lbs.

32 N 2208 Speaker kit chrome grille Net 4.65

5" x 7" Kit

Same as 32 G 2207 but with 5x7" speaker and grille. 5 lbs.

32 N 2209 Chrome grille Net 2.88

Fader Type Auto Kits

Rear-seat speaker kits identical to those above except with fader-type controls to cut either speaker in or out or balance both. Shpg. wt., 5 lbs.

6x9" Kit. Same as 32 N 2207 but with fader

32 N 2210 Control Chrome grille Net 3.69

Deluxe 6" x 9" Fader Kit

Deluxe kit with extra-heavy-magnet 6x9" speaker, plus fader control. Shpg. wt., 5 lbs.

6x9" Kit. Same as 32 N 2208 but with fader.

32 N 2211 Chrome grilla Net 4.89

SPEAKER GRILLS



Handsome perforated metal grilles for rear-seat speaker use or other installations. Avg. Shpg. wt., 1 lb.

CHROME GRILLES

32 N 3401 5x7" Fig. A Net .79


32 N 3402 6x9" Fig. B Net .99

GOLD GRILLES

32 N 3403 5x7" Fig. A Net .79

32 N 3404 6x9" Fig. B Net .99

DUAL HI-FI REAR-SEAT SPEAKER KIT



- **Woofer-Tweeter-Crossover**
"Universal" speaker kit includes two Alnico V units—a 5 1/2" woofer and 3" tweeter with electronic crossover network; chrome grille and baffle which fits regular 6x9" cut-out; plus pre-wired, pre-soldered, 3-position switch. Shpg. wt., 4 lbs.

32 N 2212 Net 5.95

STATION WAGON REAR-SEAT KITS



- **Fully Assembled—Self Contained**
A fully assembled, easy-to-install auxiliary speaker for all station wagons. Single 4x6" Alnico V speaker, chrome grille, swivel bracket, 3-position switch with dial plate and knob. Comes complete with installation instructions and wiring diagram. Shpg. wt., 3 lbs.

32 N 2201 Net 6.88

3-WAY PUSH-BUTTON SWITCH



89¢

Just push a button to select either front speaker alone, rear speaker alone or both together. Comes completely assembled on black & silver metal plate with cable, hardware and simple instructions. Imported. Shpg. wt., 1/2 lb.

99 N 8510 Lots of 3, ea. .75 singly, ea. .89

DUAL-SPEAKER FADER CONTROL



64¢

Controls the volume of both front and rear speakers. Gradually reduces volume on one speaker while increasing volume on the other. Control comes completely mounted on black and silver metal plate with ivory pointer knob plus attached wiring for connections to both speakers. With mtg. hardware and instructions. Shpg. wt., 1/2 lb.

99 N 8507 Imported Net .84

3-WAY SPEAKER SWITCH



49¢

For use with two speakers. Three-position switch gives choice of front speaker alone, rear speaker alone, or both together. Comes completely assembled on black and silver metal plate with ivory indicator knob and attached wiring for connection to both speakers. With hardware and simple instructions. Shpg. wt., 1/2 lb.

99 N 8508 Imported Net .49

CARDIO-MASTER




- Convert your Transistor Radio into a Car Radio
- For all Makes of Cars, Cabs, Trucks

298

Cardio master is a magnetic device designed to hold a portable transistor radio in the area of a car's windshield to make it operate as an auto radio. Car's owner can remove a radio from the Cardio master for use as portable or to avoid theft while the car is parked. Fits any "pocket" transistor radio. Will not come loose in the bumpiest roads. Includes magnetic base, brackets, hardware, adjustable band and complete, illustrated instructions. Shpg. wt., 2 lbs.

11 N 1303 Net 2.98

INSTA MOUNT SPEAKER



795

- New Design Concept
- Remarkable Versatility
- Exceptional Sound Quality
- Mounts Anywhere—House, Car, Boat, Patio

Insta-mount is a unique speaker concept which allows you to flush mount this slim unit anywhere. Only the handsome triple chrome plated grill shows. Mounts in walls, doors, ceilings, desk top, cars, (perfect for station wagons), moisture resistant for outdoor and marine installations. The powerful

5 1/4" hi-fi speaker needs no baffling. Insta-Mount provides its own infinite baffling systems. Quality sound reproduction for AM FM Radio, Hi-Fi Phonograph, T.V., Tape recorder. Use 2 for stereo. Mounts quickly and easily in minutes. Enclosure is included for use on tables, bookshelves or portable use. All hardware included. Easy to follow instructions included. Shpg. wt., 3 lbs.

32 N 3405 Net 7.95

LAFAYETTE Auto Accessories

4-LITE EMERGENCY FLASHER



- Converts Front and Rear Lights to Emergency Flashers

3⁵⁹

Easy to install — It may save your life. Commands instant attention by flashing front parking light and rear brake tails on and off. For use during emergency road stops, flats, double parking. Helps bring emergency repair truck or police when needed, prevents collisions. Only minutes to install. Complete with instructions

11 N 2701 Net 3.59

REVOLVING BEACON



- Rotates Like a Light-house Beacon
- Signals Help for Miles Around
- Suction Mounts in Seconds

6⁸⁵

A red warning light that rotates 360 degrees and flashes in all directions. Suction mount holds the beacon firmly in place. Signals for help for miles around; creates a safety zone during a traffic emergency. For use on autos, boats, trucks, docks, etc. For 12 volt use; complete with cigarette lighter adapter plug. Shpg. wt., 2 lbs.

11 N 1304 Net 6.85

BLUE TURRET LENS

Converts Revolving Beacon for use by emergency vehicles, volunteer fire depts., CD units, etc.


11 N 1305 Shpg. wt., 1 lb. Net .90

"TRAVELITE" TRAVEL BAG

As Low As

1⁷⁹

- Bright Scotch Plaid
- Full Length Zipper
- Metal Hanger Slot



Perfect for travel and home storage designed to hold three (3") wooden hangers or 6 wire hangers. Protects garments from moisture, insects, dirt, rough handling. Keeps them wrinkle free. Made of heavy duty vinyl, zipper is rust-proof with long pull tab for easy operation. Reinforced at points of heavy wear. Every home can use several "Travelite" bags. Shpg. wt., 1 lb.

2 Suiter 42" long Net 1.79
11 N 8301
Coat Bag 54" long Net 2.29
11 N 8302

MAGNA-CLOCK with ALARM ONLY

4^{95*}



- Powerful Magnet in Base for Sure-Grip Attachment To Dash
- Clock Pivoted to Swing to Any Position Even on A 90° Surface
- Accurate, Dependable 30-Hour Movement with Alarm

A beautifully styled car clock with powerful magnet in the base for sure-grip attachment to any steel surface. Contour-molded plastic case has a convex glass front framed in a beveled, gold-finish metal band. All hands and numerals are luminous. Imported 30-hour movement with alarm is precision-made and is not affected by magnet in the base. Easily removed and used whenever you go. Choice of 3 colors. Shpg. wt., 1/2 lb.

11 N 2205 (Silver) Net 4.95*
11 N 2206 (Blue) Net 4.95*
11 N 2207 (Red) Net 4.95*
*Plus 10% F.E.T.

PRIMETTA "FOGGLES"



- FOR SAFER DRIVING:
- AT NIGHT
 - IN SNOW • IN FOG • IN RAIN
- A Zeiss Formulation Newly Developed Insures True Color Contrast

Night driving is safer and easier with Primetta Radar Night Glasses. Scientifically designed to protect the eye from the glare of headlights, street lights, etc. without materially reducing vision. Ideal while driving at right the rain, fog and snow. The filter lens exclude all ultra violet rays. Designed for 20-20 vision. With heavy, suede-lined leather case. Shpg. wt., 6 oz.

11 N 3201 Net 1.98
Clip-on "Foggles," with case, for use over existing glasses. Net 1.50
11 N 3202

10N-X Electronically Ionizes Gasoline Boosts Power!




- Changes Electron Balance of Fuel
- No Carbon Build-Up
- More Horse Power from Your Engine
- Increased Gas Mileage
- Fits All Cars

Sale Reg. 10.95

12⁹⁵

A revolutionary new component which when added to your existing fuel system actually changes the molecular structure of the gasoline before it enters the carburetor. This allows for a greater combustion intensity which assures more power and less carbon build up. Provides for a more closely added air/fuel mixture. Extremely easy to install. Shpg. wt., 1 lb. Imported.

11 N 1505 Net 12.95




WINDOW DEFROSTING FAN

- Defrosts, Demists, Cools
 - Plugs in Cigarette Lighter
 - Harmless 6" Rubber Blades
 - Choice of 6 or 12-volt Models
- A practical automotive accessory which keeps windshield free from frost or fog while you drive. High speed 3,000 rpm motor controlled from drivers seat by 2-speed switch. Plugs into cigarette lighter socket for quick easy installation, no wires to attach. Complete with cord; universal swivel joint on sturdy base. 2 1/2 lbs.

11 N 3401 for 6 volt cars Net 7.95
11 N 3402 for 12 volt cars Net 7.95

SIT-RITE AUTO BACK REST 5³⁷




- Cool and Comfortable Driving
- Pillows No Longer Needed

Scientifically designed to give drivers proper back support. Constructed with a spring steel frame covered with a sturdy washable woven fabric. Fits all cars — no tool installation. Neutral beige. Shpg. wt., 3 lbs.

11 N 1801 Net 5.37

AUTO-BOAT COMPASS AS LOW AS 3⁷⁵




Mounts anywhere on cars-boats-trucks-tractors-motor-cycles. Non-glare, universal mounting bracket. Most easily compensated compass available. Just a twist of the bottom or top knob. Large viewing window and figures for ease of reading. Includes mounting accessories and instructions. Illuminated model includes both 6 and 12-volt bulbs. Shpg. wt., 1 lb.

11 N 5801 Non-illuminated Net 3.75
11 N 5802 Illuminated Model Net 4.49

GLARE GUARD VISOR

- Moulded from Acrylic Plexiglass®
- Built in "Diffusion Band"
- Fits All Cars and Trucks



First major improvement in sun visors in 30 years! Scientifically designed to filter out 87% of the sun's rays. Optically clear, "Dawn Blue" filter lets you see road signs, signal lights and traffic hazards in their natural color and clarity. Simultaneously protects your eyes from glare, squint, fatigue and eye strain. Provides eye ease and comfort—safe, clear vision. Fits all cars and trucks. Non-slip, heavy duty spring clips, snap on regular visor. A "flick" of the finger positions it. Adaptable to sports cars with no original visor. A year 'round necessity. Overall size 16x4 3/4".

11 N 5101 Shpg. wt., 1 lb. Net 2.69


Battery Chargers, Converters and Inverters

TRANSISTORIZED POWER CONVERTER

- Small Enough To Mount In Any 12-Volt Car Or Boat
- Converts 12 VDC To 117 VAC
- Supplies Voltage For Any Equipment Requiring From 10 to 125 Watts

29⁹⁵

Rated at 125 watts continuous duty, this fully transistorized, highly efficient converter plugs into your car's cigarette lighter socket to supply 117 volts AC to operate any equipment requiring 10 to 125 watts including electric shavers, recorders, record players, radio, TV and many others. Has "Power to Spare" for extra years of dependable service. Shpg. wt., 5 lbs. 11 N 7301 Net 29.95



COLD-START BOOSTER-CHARGER



23⁹⁵

Our First Combination Battery Charger and Booster.

- 50 Amp Booster (6 volt)
- 25 Amp Booster (12 volt)
- 10 Amp Charger (6/12 v)

Perfect for starting 6V, 8V, 12V cars. Works as a booster—as a charger. Supplied with heavy copper cables; thermal switch prevents overheating; works up to 200-ft. away from AC power source. Power output: 12V Boost, 25 amps maximum; 6V Boost, 50 amps max.; 6/12V Charge, 10 amps tapering to 5 amps max.; Power Input: 5 amps max. at 117V AC, 60 cycles. Shpg. wt., 9½ lbs. 11 N 4001 Net 23.95

2-IN-1 BATTERY CHARGER

4²⁵ UL Approved

End dead battery trouble in your car, boat, truck or tractor. This powerhouse battery charger keeps all 6 and 12 volt batteries fully charged for peak performance even at 40° below freezing. Full 1 amp. "safe" charge rate prevents flaking and plate buckling—same method used by storage battery dealers. Easy to use—plug the line cord into any 110V outlet, connect the two terminals and forget it. Can't overcharge—automatically tapers off. Welded constructed steel. Shpg. wt., 3½ lbs. 11 N 7802 Net 4.25



3-AMP. BATTERY CHARGER WITH BUILT-IN METER FOR BOTH 6 AND 12 VOLT BATTERIES

8²⁵ U.L. Approved

Edge view meter shows actual rate of charge and indicates battery condition. Reset circuit breaker gives automatic overload protection. Has 6 and 12 volt selector switch. Delivers tapering charge. Vented steel case. 6 ft. battery leads with 50 amp clips. Size 6"x5"x5". For operation from 105-125 Volt, 50-60 cycle A.C. Shpg. wt., 5 lbs. 11 N 7684 Net 8.25



TRANSISTORIZED 40-50 WATT INVERTER


- Ideal for Salesman, Sportsman, Executive
- For Dictating Machines, Razors, Port. Tape Recorders, Etc.
- Use in Car, Boat or Private Airplane

19⁶³

2 power transistor inverter supplies 40 watts continuous, 50 watts intermittent from 12.6 volt storage battery. Silent operation. Attractively finished green Hammerloid steel case. Epoxy filled to insure longer life. Supplied complete with 3 foot cord and plug for immediate insertion into cigarette lighter receptacle. Dim: 4¾"x2½"x2¾"D. Shpg. wt., 3½ lbs. 34 N 4001 Net 19.63



INVERT O-CHARGE



- Combination Power Inverter and 8 Amp Battery Charger

This dual purpose unit will operate 120 volt equipment from a 12 volt battery or charge a 12 volt battery from a 120 volt source! 175 watts cont., 225 watt intermittent operation; metered input and output; Push button solid state operation; Protective circuit breaker; Operates any AC device within its power limitations. Shpg. wt., 10 lbs. 11 N 3701 Net 44.50

CORNELL DUBILIER 12TV12

DC TO AC INVERTER

32³⁵

- Especially Designed to Power Portable TV Sets with Power Requirements up to 120 watts
- Ideal for Automotive, Marine, House Trailers, Campers, etc., as a Source of AC Power Independent of Power Lines



The Model 12TV12 converts 12 volt DC from any 12V storage battery, to 110-120 volt AC at 60 cycles.

Designed primarily for television receivers, tape recorders, phonographs and other frequency sensitive devices, the 12TV12 employs a resonant reed tuning component to assure frequency stability. No loss of B+ in TV brilliance. Will power any TV, ham rig, CB station, or Hi-Fi unit within the 120/140 watt power requirement rating. Perfect for car or boat.

SPECIFICATIONS

Input: 12 volts @ 12 amperes (full load); Output 120 watts continuous, 140 watts intermittent; RE filtering on both input and output; Finish: Zinc Chromate corrosion resistant undercoat, crinkle paint black bottom and smokerise grey top. 8¾"Lx7½"Wx3¾"H. Wt., 13¾ lbs. Shpg. wt., 16 lbs.

34 N 5501 Net 32.35

Model MK-3544-5 Mounting Kit for 12TV12—Provides safe, secure mounting to bulkhead, wall, or floor. Supplied with all necessary mounting hardware. Shpg. wt., 2 lbs.

34 N 5502 Net 3.60

12-VOLT BATTERY CHARGER


3⁹⁹

- For Autos, Boats, Trucks
- No Messy Hook-Up
- Plugs Into Lighter Socket

Keeps any 12-volt battery at full charge. Perfect for any car, truck, boat. Simply plug into cigarette lighter socket and connect to any regular electrical outlet. Boosts battery overnight... keeps battery warm... provides added power for faster starting. Delivers 1 amp maximum — automatically tapers off while battery is being charged. Compact design... for easy, permanent installation under dash. For negative ground, easily converted to positive ground. Handsome satin chrome finish. Shpg. wt., 1½ lbs. 11 N 4803 Net 3.99



LAFAYETTE Budget-Priced TV Picture Tubes



Net price "with Dud" based on your prepaid shipment or delivery of old picture tube (Dud). Returned tubes must be intact, under vacuum and without scratches. Green glass duds not accepted. When ordering give stock number and type. Every Lafayette picture tube is top quality-made of entirely new materials except the glass, which is tested and inspected to meet new-glass standards. *Indicates aluminized screens. †Indicates metal tubes.

FULL ONE-YEAR GUARANTEE

Tubes which fail in normal use within one year will be replaced upon receipt of your returned tube. You pay only transportation.

AVERAGE SHIPPING WEIGHTS: 10" Tubes, 14 lbs.; 12"- 17 lbs.; 14" - 14 lbs.; 16" - 22 lbs.; 17" - 24 lbs.; 19" - 26 lbs.; 20" - 30 lbs.; 21" - 35 lbs.; 24" - 44 lbs.

Stock No.	Type No.	Net Less Dud	Net With Dud	Stock No.	Type No.	Net Less Dud	Net With Dud
36 N 0106X	10BP4/10BP4A	7.50	7.50	—	19AGP4	Use 19AVP4	—
—	12JP4	Use 12KP4A	—	36 N 0145X	19AP4A/B†	18.85	15.95
36 N 0107X	12KP4A*	11.25	11.25	—	19ARP4	Use 19AFP4	—
—	12LP4	Use 12LP4A	—	—	19AUP4	Use 19AFP4	—
36 N 0108X	12LP4A	9.00	9.00	36 N 0146X	19AVP4*	20.95	16.50
36 N 0109X	14AJP4*	19.25	16.25	36 N 0147X	19AXP4*	20.95	16.50
—	14ASP4	Use 14AJP4	—	—	19AYP4	Use 19AXP4	—
36 N 0110X	14ATP4*	17.50	14.50	—	19AZP4	Use 19AVP4	—
—	14AVP4	Use 14AJP4	—	—	19BVP4	Use 19AVP4	—
—	14BP4	Use 14BP4/CP4	—	36 N 0150X	19DP4	18.75	16.75
36 N 0111X	14BP4/CP4	13.50	10.50	—	19XP4	Use 19AVP4	—
36 N 0112X	14C/B/EP4B*	15.00	12.00	—	20CP4	Use 20CP4A/DP4A	—
—	14EP4/B	Use 14C/B/EP4B	—	36 N 0148X	20CP4A/DP4A*	14.00	12.50
—	14HP4	Use 14QP4A	—	36 N 0149X	20CP4B/DP4B*	17.50	15.50
—	14NP4A	Use 14WP4	—	—	20DP4	Use 20CP4B/DP4B	—
—	14QP4	Use 14QP4A	—	—	20HP4/A/B/C	Use 20HP4D	—
36 N 0113X	14QP4A*	18.50	13.50	36 N 0151X	20HP4D*	16.90	14.90
—	14RP4A	Use 14WP4	—	—	20LP4/MP4	Use 20HP4D	—
—	14SP4	Use 14WP4	—	—	21ACP4	Use 21ACP4A/AMP4A	—
36 N 0114X	14WP4*	16.50	14.50	36 N 0152X	21ACP4A/AMP4A*	13.95	10.95
—	14ZP4	Use 14WP4	—	—	21AFP4	Use 21YP4A	—
36 N 0115X	16AP4	11.95	11.95	—	21ALP4/A/B	Use 21FLP4/CBP4A	—
36 N 0116X	16CP4/LP4A	12.50	12.50	—	21ALP4A/FLP4*	Use 21FLP4/CBP4A	—
36 N 0117X	16EP4†	14.75	14.75	—	21AMP4	Use 21ACP4A/AMP4A	—
36 N 0118X	16FP4	11.75	9.95	—	21AMP4A/B	Use 21ACP4A/AMP4A	—
36 N 0119X	16GP4†	14.85	13.85	—	21ANP4/A	Use 21FLP4/CBP4A	—
36 N 0120X	16JP4	13.50	13.50	36 N 0154X	21AP4†	21.75	17.75
36 N 0121X	16KP4A/RP4A*	11.75	11.75	—	21AQ4/A	Use 21ACP4A/AMP4A	—
—	16KP4/RP4	Use 16KP4A/RP4A	—	—	21ATP4/A/B	Use 21FLP4/CBP4A	—
—	16LP4/A	Use 16CP4/LP4A	—	36 N 0155X	21AUP4/AVP4	15.50	13.50
—	16QP4	Use 16KP4A/RP4A	—	36 N 0156X	21AUP4A/AVP4B*	17.95	15.95
—	16RP4	Use 16KP4/RP4	—	36 N 0157X	21AWP4	16.25	13.25
—	16TP4	Use 16KB4/RP4	—	36 N 0158X	21AWP4A*	18.75	16.50
36 N 0123X	16UP4	Use 16KP4A/RP4A	—	—	21AYP4	Use 21XP4A	—
—	16WP4	Use 16KP4A/RP4A	15.50	—	21BAP4	Use 21FLP4/CBP4A	—
—	16XP4	Use 16RP4A/RP4A	—	—	21BCP4	Use 21YP4A	—
—	16ZP4	Use 16CP4/LP4A	—	—	21BDP4	Use 21AUP4/VP4B	—
—	17AP4	Use 17BP4 or 17BP4B	—	—	21BSP4	Use 21FLP4/CBP4A	—
36 N 0124X	17ATP4A/BJP4*	Use 17BJP4	—	—	21BSP4	Use 21ACP4A/AMP4A	—
—	17AVP4A/BJP4*	17.25	14.25	—	21BTP4	Use 21FLP4/CBP4A	—
—	17BJP4*	Use 17AVP4A/BJP4	—	—	21CBP4A/B	Use 21FLP4/CBP4A	—
—	17BP4	Use 17BP4B	—	—	21CEP4	Use 21DEP4A	—
36 N 0126X	17BP4A*	Use 17BP4B	—	36 N 0161X	21CMP4	Use 21FLP4/CBP4A	—
—	17BP4B*	13.75	12.75	—	21CQP4*	21.25	15.25
—	17BP4C/D	Use 17BP4B	—	—	21CUP4	Use 21ACP4A/AMP4A	—
36 N 0127X	17BRP4*	18.90	13.90	—	21CVP4	Use 21FLP4/CBP4A	—
36 N 0128X	17BWP4*	20.50	15.50	—	21CWP4	Use 21FLP4/CBP4A	—
36 N 0129X	17BWP4*	20.50	15.50	—	21CZP4	Use 21DEP4A	—
36 N 0130X	17BZP4*	18.90	13.90	—	21DAP4	Use 21DEP4A	—
—	17CAP4	Use 17DSP4	—	36 N 0162X	21DEP4A*	19.95	14.95
—	17CBP4	Use 17AVP4A/BJP4	—	—	21DFP4	Use 21DEP4A	—
36 N 0131X	17CDP4*	22.25	17.25	—	21DNP4	Use 21FLP4/CBP4A	—
36 N 0132X	17CFP4*	15.90	14.90	—	21EP4A	Use 21EP4B	—
—	17CKP4*	Use 17DSP4	—	36 N 0163X	21EP4B*	17.45	15.95
—	17CLP4	Use 17AVP4A/BJP4	—	36 N 0164X	21FLP4/CBP4A*	17.45	10.95
36 N 0133X	17CP4†	17.40	15.90	—	21FP4A	Use 21FP4C	—
—	17CSP4	Use 17BWP4	—	36 N 0165X	21FP4C*	17.50	16.50
—	17CWP4	Use 17DSP4	—	36 N 0166X	21MP4†	26.50	21.50
36 N 0134X	17DAP4*	22.50	17.50	36 N 0167X	21WP4/21WP4A	15.25	13.75
—	17DKP4/DLP4	Use 17DSP4	—	—	21XP4	Use 21XP4A	—
36 N 0135X	17DSP4*	16.90	13.90	36 N 0168X	21XP4A*	18.50	16.50
36 N 0136X	17DXP4/ZP4*	18.95	14.95	36 N 0169X	21YP4	14.25	9.85
—	17DZP4	Use 17DXP4/ZP4	—	36 N 0170X	21YP4A/21YP4B*	16.40	11.40
—	17DTP4	Use 17DSP4	—	—	21ZP4/A	Use 21ZP4B	—
36 N 0137X	17GP4	18.25	18.75	36 N 0171X	21ZP4B*	15.95	11.45
36 N 0138X	17HP4/RP4	11.90	10.90	—	24ADP4	Use 24CP4A	—
36 N 0139X	17HP4B/RP4C*	15.25	14.25	—	24AEP4*	Use 24DP4A/AEP4	—
—	17JP4	Use 17BP4B	—	36 N 0172X	24AHP4/ALP4*	29.25	22.50
36 N 0140X	17LP4/VP4	13.75	12.75	—	24ALP4	Use 24AHP4/ALP4	—
36 N 0141X	17LP4A/VP4B*	15.95	14.95	—	24ANP4	Use 24DP4A/AEP4	—
—	17LP4B	Use 17LP4K/VP4B	—	36 N 0173X	24AUP4*	29.25	22.50
36 N 0142X	17QP4	13.75	12.75	36 N 0174X	24CP4A*	25.00	19.00
36 N 0143X	17QP4A/B*	15.95	14.95	—	24CP4B	Use 24CP4A	—
—	17RP4	Use 17HP4/RP4	—	—	24DP4	Use 24DP4A/AEP4	—
—	17UP4	Use 17QP4	—	36 N 0175X	24DP4A/AEP4*	26.75	20.00
—	17VP4	Use 17LP4/VP4	—	—	24QP4	Use 24CP4A	—
—	17VP4B	Use 17LP4A/VP4B	—	—	24TP4	Use 24CP4A	—
—	17YP4	Use 17QP4	—	—	24VP4/A	Use 24CP4A	—
—	19ADP4	Use 19AVP4	—	—	24XP4	Use 24CP4A	—
36 N 0144X	19AFP4*	27.50	24.50	—	24YP4	Use 24DP4A/AEP4	—
—	—	—	—	—	24ZP4	Use 24DP4A/AEP4	—

Dry Chargers – Inverters – Eliminators – Batteries



"STORAGE CELL"
for TRANSISTOR RADIOS!
ONE CHARGEABLE BATTERY OUTLASTS
DOZENS OF CONVENTIONAL BATTERIES

269



- Replaces 2U8, BL-006P and 99 G 9021
- Fluid Storage Type
- Plays About 18 Hours on One Charging
- Battery Recharges Overnight
- Battery Can Be Used Over and Over Again
- Complete—Battery Plus Charger

9V Battery complete with charger. Battery 1 7/8x1 1/4"; charger 3 3/4x 1 1/4x7/8". Imported.
99 N 9018 Battery and Charger. Shpg. wt., 6 oz. Net 2.99
99 N 6026 Battery Replacement for above, wt., 3 oz. Net 1.29

9-VOLT TRANSISTOR RADIO BATTERY

20¢

Replaces RCA VS323, Burgess 2U6, Eveready 216, Zenith Z216, Ray-O-VAC 1604, NEDA 1604. Shpg. wt., 2 oz. Imported.
99 N 6021 Net ea. .21
Net. ea., Lots of 10 .20



LAFAYETTE 9-VOLT TRANSISTOR RADIO BATTERY CHARGER AND ELIMINATOR


- Charge Battery, Operate Set on AC, or Both
- Isolated Transformer—Shock-Proof



345

Just plug into any 117-volt AC receptacle and recharge your old 9-volt battery for many hours of extra use; or operate your set indoors without using the battery at all; or you can both charge battery and operate set at the same time. Has 4-position switch for above functions plus off position and pilot light. Size: 4Wx1 1/4"Hx 2 5/8"D. Imported.
99 N 9021 Shpg. wt., 1 lb. Net 3.45


LAFAYETTE BATTERIES POPULAR SIZES AT POPULAR PRICES



Popular batteries for portable radio and transistor sets.
*For hearing aids and transistor sets. Imported.

Stock No.	Volt-age	Lots of 10		Fig-ure	RCA	Bur-gess	Ever-ready	Shpg. Wt.
		Singly	10					
99 N 6020	67 1/2	1.49	1.38	A	VS215 VS216 VS218	P45 P45M	477	12 oz.
99 N 6022	9	.34	.29	B	VS300A VS314	P6 P6M	226	3 oz.
99 N 6023	67 1/2	1.29	1.19	C	VS318	UX45	416	8 oz.
99 N 6024	67 1/2	1.45	1.35	D	VS016	XX45	467	3 oz.
99 N 6025	9	.53	.45	E	VS309A	YL-6	E177	2 oz.
99 N 6027*	22 1/2	.58	.53	F	VS084	U15	412	3 oz.

BATTERY RECHARGER and ELIMINATOR




4 95

The new dry cell battery recharger and eliminator will replenish your supply of flashlight batteries. Recharges "C," "D" and "Z" cell batteries in 2 to 4 hours — keeps battery-operated toys always on the go. It's a battery eliminator too — simply plug into any 110V AC outlet. Delivers 4 to 6 V. DC for "recharge" or "eliminate."
33 N 7701 Shpg. wt., 1 1/2 lbs. Net 4.95

NEW CHART CHARGE NICKEL-CADMIUM BATTERY CHARGER

- Charges 1 to 10 Cells in Series Up to 250 MA

Designed to meet the demands for Nickel - Cadmium Cells in the industrial and hobby fields. Charges 1 to 10 cells in series and is continuously variable from 10 to 250 MA. No meter required for accurate calibration. Use of isolation transformer eliminates shock hazard. Full wave silicon diode rectification. Visual red on-off indicator lamp and UL approved line cord. 6 1/4x3 3/4x2". Shpg. wt., 2 lbs.
34 N 4101 Net 9.95



SHURITE BATTERY TESTER

Pocket tester with bright plated case, metal dial, and prods. Sturdily built. Test batteries without load. Ideal for testing batteries used in transistor circuits, model railroads, hearing aids, portable radios, etc. Shpg. wt., 8 oz.



HEARING AID BATTERY TESTER

Ideal for checking 1.5, 15, 22.5, 30, 33, and 45 volt batteries.
38 N 6164 Net 3.77

3 77

RADIO TRANSVERTER Converts Transistor Radio to Car Radio

- Fits all Cars
- For all 9-Volt Transistor Radios
- Plugs into Cigarette Lighter

Now you can avoid the expense of buying a car radio with this new radio transverter. Simple to operate—remove 9-volt battery from your transistor radio, connect contacts from transverter to battery contacts in the radio, and then plug into the cigarette lighter. Fits all cars. Shpg. wt., 6 oz.



11 N 4801 For 12-Volt Cars Net 1.47
11 N 4802 For 6-Volt Cars Net 1.47

1 47

RECHARGEABLE FLASHLIGHT

Always ready for use—no more batteries to buy. Simply plug into the nearest 110V. A.C. wall outlet—leave overnight—for a complete recharge. Self contained charger and cells need no service or replacement in normal use. 4x1 3/4" overall. Shpg. wt., 6 ozs. Imported.
14 N 2102 Net 2.50



TERADO "DYNAMO" DC TO AC INVERTER

Convert Your Table Model Radio to a Car or Boat Radio

Operate any small radio in any 12 volt car, truck, boat or trailer. No installation—just plug into cigar lighter. Needs no outside antenna—table radios will operate on their own built-in antenna. Will also operate your electric shaver or any electric appliance up to 20 watts. Complete with generator condenser and ignition noise suppressor. Measures only 2x2x3 3/4". Shpg. wt., 2 lbs.
33 N 5302 Net 9.58




TERADO "QUIK-SHAVE" AC TO DC INVERTER

Any shaver, new or old, gives super performance with QUIK-SHAVE, which changes household AC electricity into jet powered DC. Lengthens shaver life. Up to 88% more cutting power for faster, closer, more comfortable shaves. Plug QUIK-SHAVE into wall outlet, attach shaver cord, and shave twice as fast!
33 N 5301 Shpg. wt., 8 ozs. U.L. Approved Net 4.16



Quality Parts For The Serviceman

KIT OF 100 ALLEN BRADLEY AND IRC 1/2 WATT-10% RESISTORS




450

Quant.	Ohms
3	100
3	470
4	1,000
3	2,200
4	4,700
5	10,000
4	22,000
4	27,000
4	33,000
4	47,000
10	.1 meg
4	.15 meg
4	.27 meg
10	.47 meg
10	.1 meg
4	2.2 meg
20	Other popular values
100 TOTAL	

Designed especially for the serviceman. Here is a selection of 100 resistors of the most popular values used in general service work. All brand-new 1/2 watt 10%, full lead length Allen Bradley and IRC. Color coded. This is no random assortment. You get exactly the values in the list at right. Comes complete with hinged, plastic box. Shpg. wt., 2 lbs.

32 N 9901 Net 4.50

PORCELAIN CASED TUBULAR CAPACITORS VALUE PACKED KITS




Rated 600 W.V.D.C.
Tested At 3 Times Working Voltage
Exceptionally Resistant To High
Temperatures and Moisture

AS LOW AS **275**

KIT OF 100 600V W V OC QTY.	MFD.	KIT OF 50 600V W V DC QTY.	MFD.
10	.001	5	.001
10	.002	5	.002
10	.003	5	.003
20	.01	10	.01
20	.02	10	.02
20	.05	10	.05
10	.1	5	.1


99 N 6112 Kit of 50. Shpg. wt., 3/4 lbs. Net 2.75
99 N 6113 Kit of 100. Shpg. wt., 1 1/2 lbs. Net 4.95

LAFAYETTE TUBULAR ELECTROLYTICS



Lafayette electrolytic capacitors are specifically designed for service replacement applications. All are sealed in aluminum cans. All have wax impregnated cardboard outer insulating sleeves, have solid tinned copper wire leads with negative terminal grounded to can. For operations as high as 85°C. Avg. shpg. wt., 4 oz. ea.

Stock No.	Mfd.	W.V.	Net Each	Net Each In Lots of 10
32 N 0110	10	25	.29	.27
32 N 0111	25	25	.31	.28
32 N 0112	20	150	.30	.27
32 N 0113	40	150	.35	.32
32 N 0114	8	450	.35	.32
32 N 0115	20	450	.48	.45
32 N 0116	40	450	.59	.56
Dual Section Tubular Electrolytic				
32 N 0117	20-20	150	.37	.33
32 N 0118	30-30	150	.39	.34
32 N 0119	40-40	150	.41	.37
32 N 0120	50-30	150	.41	.37
32 N 0121	50-50	150	.44	.40




LAFAYETTE ECONOMY-LINE PM SPEAKERS

Top Quality replacement speakers. Selected for universal application—rugged construction—standard configurations. All have 3.2 ohm voice coils.

STOCK NO.	SIZE	SHAPE	MAG. WT.	PEAK WATTS	SHPG. WT.	NET EA.
32 N 0101	4"	Square	.68 oz	3.0	1	1.11
32 N 0102	5"	P.C.	.68 oz	4.0	1	1.29
32 N 0105	6"	Round	1.0 oz	8.0	1 1/2	1.75
32 N 0108	8"	P.C.	2.15 oz	10.0	2 1/2	2.29
32 N 0103	10"	Round	1.47 oz	10.0	3 3/4	3.60
32 N 0108	12"	Round	3.16 oz	12.0	5	3.85

AUTO PM SPEAKERS						
STOCK NO.	SIZE	SHAPE	MAG. WT.	PEAK WATTS	SHPG. WT.	NET EA.
32 N 0109	5X7"	Oval	1.0	5	1 1/2	1.59
32 N 0107	6X9"	Oval	1.47	7	2	2.15
32 N 0104	6X9"	Oval	2.15	8	2 1/2	2.95

LAFAYETTE MINIATURE SPEAKER AND ENCLOSURE



695

- Attractive Mahogany Finished Wood Cabinet
- Complete With 25 Feet of Cable

Enjoy music everywhere in your home with this amazing Lafayette miniature speaker system. Ideal as an extension speaker for your den, basement, kitchen or bedroom. Use two for stereo or with your TV and Radio. Housed in a beautiful mahogany—finished wood cabinet, the 5-watt 4x6" speaker is designed to work from either 4 or 8 ohm outputs. System is supplied with 25 feet of cable. Overall size: 9 1/2 W x 7 3/4 H (incl. feet) x 3 1/2" D. Imported.

99 N 4550 Miniature Speaker System. Shpg. wt., 5 lbs. Net 6.85

LAFAYETTE MINIATURE DUO-REMOTE T.V. SPEAKER




You will be amazed at the number of uses you'll find for this unit. The fine quality of the built-in speaker makes it perfect for use as an extension speaker anywhere in your home or office. It's small size makes it an ideal personal speaker when watching TV or listening to your phonograph. . . . The dual volume controls provide independent volume control of the main speaker from your listening or viewing position or the remote's own self contained speaker. Attractive molded cabinet measures 4Wx2 1/2 H x 1 3/4" D. Complete with 20 ft. of 4-conductor cable. Shpg. wt., 1 1/2 lbs. Imported

99 N 4548 Net 3.88

Popular Servicemen's Parts

POWER TRANSFORMER FOR SELENIUM RECTIFIER CIRCUITS



Most popular replacement power transformer for circuits using selenium rectifiers or rectifier tubes such as 6AX5, 6X4, 6X5. Primary is 117V 60 Cycles A.C. Plate supply is 125 VAC 1/2 wave at 15 ma with 6.3V 0.6 amp filament winding. Size: 2x2 3/4 x 1 3/4"; mounting centers 2". Shpg. wt., 1 lb. 33 N 3405 Net 1.59

LAFAYETTE SPECIAL

70.7 VOLT LINE-TO-VOICE COIL TRANSFORMER




- 10 watts max.
- 5-8-16 ohms

70 volt line-to-voice coil matching transformer. Primary tapped 10, 5, 2.5, 1.25 and .625 watts. Secondary tapped 5, 8 and 16 ohms. Size: 2x1 1/2". Mtg. Centers 2 3/8". Shpg. wt., 1 lb.

33 N 3709 Lot of 10 each 1.70
Singly ea. 1.98

SPECIAL LAFAYETTE TRANSFORMERS



AS LOW AS
41c
EACH

50L6 OUTPUT (FIG. B)

Matches 50L6, 35L6, 25L6, etc. to 3-4 ohm voice coil. Shpg. wt., 1/2 lb.

33 N 3701—Singly, each .49
Lots of 5, Ea. .45 Lots of 10, Ea. .41

6.3 VOLT FILAMENT TRANSFORMER

Primary 115V. Secondary 6.3V at 1 amp. Shpg. wt., 3/4 lb.

33 N 3702—Singly, each .89
Lots of 5, Ea. .81

UNIVERSAL OUTPUTS (FIG A)

Match any single or push-pull output tubes to any voice coil. Shpg. wt., 3/4 lb.

33 N 7503—4 watt—Singly, each 1.39
In lots of 5, each 1.26

33 N 7504—8 watt—Singly, each 1.53
In lots of 5, each 1.38

#47 PILOT LAMPS

10 for **45c**

Most often used pilot light. Replaces pilot in most electronic entertainment equipment. Shpg. wt., 5 oz. Imported.

99 N 6304 pkg. of 10 .45
10 pkgs. 4.00



LAFAYETTE SPECIAL NEON ASSEMBLY

For operation on 110 volts AC. Requires 100k resistor in series. When used with 200 v. use 250k resistor in series. AC starting voltage 60v. Servicing life. 5000 to 10,000 operating hours. Chrome finish. Shpg. wt., 2 oz. Imported

Stock No.	Color	Net. ea.	Lots of 10 ea.
99 N 6224	Yellow	.39	.35
99 N 6225	Amber	.39	.35
99 N 6226	Red	.39	.35
32 N 0944	Red, Brass	.39	.35

When Ordering Always Use Lafayette Stock Numbers

455 KC UNIVERSAL I.F. TRANSFORMER FOR BROADCAST AND CITIZENS BAND

59c

• Only 3/4" Square

The most popular replacement I.F. Ideal for experimenters. Exceptionally high gain powdered iron core, compression tuned 455 KC midget I.F.—only 3/4" square by 1 7/8" high. For both input and output circuits. Supplied with mounting clip and adapter plate to replace both midget and larger size cans. Used in Lafayette HE-15B CB Transceiver. Shpg. wt., 4 oz.


32 N 0946 Singly, each .59
Lots of 10 each .49



5-TUBE AC-DC KIT

Low Price!

1.98



Used in most popular AC-DC Superheterodyne Radio Receivers. Kit Consists of 1 each: 50C5, 35W4, 12AV6, 12BA6 and 12BE6. Imported.

36 N 8201 Net 1.98

SERVICEMAN'S UNIVERSAL CONTROLS WITH SWITCH-AUDIO TAPER



MOST POPULAR REPLACEMENT CONTROLS


2 1/2" Long Round Shaft 1/4" Dia.

3/8" Bushing. Shpg. wt., 3 ozs.

32 N 7287 1 meg. lots of 10 ea. .39
Singly .49

32 N 7288 1/2 meg. lots of 10 ea. .39
Singly .49


POPULAR MIKE CONNECTORS



Standard single contact, cord mounted, nickel plated brass, knurl grips, 3/8"-27 thread. Shpg. wt., 3 oz.

32 N 6417 Female connector Fig. A Net .22
32 N 6418 Male connector Fig. B Net .21

STANDARD LAFAYETTE 2-CONDUCTOR PHONE PLUGS



Phone plugs for a wide variety of applications with choice of handle sizes and materials. All sleeves fit standard 1/4" phone jacks. Avg. shpg. wt., 8 oz.

FIG. A. SLIM PHONE PLUG Smooth bakelite handle. Solder terminals with cable clamp. Imported.

99 N 6221 Net .25 ea.—10 for 2.15
FIG. B. BARREL PHONE PLUG Rubbed plastic barrel handle. Screw terminals. Imported.

99 N 6223 Net .22 ea.—10 for 1.90
FIG. C. SHIELDED SLIM PLUG Ribbed chromed metal handle. Solder terminals with cable clamp. Imported.

99 N 6215 Net .29 ea.—10 for 2.50
FIG. D. PHONE TO PHONO PLUG ADAPTER. Adapts from standard phone plug to RCA type phono plug. Overall length 2 7/8 x 1/2" diam. Imported.

99 N 6216 Net .39 ea.—10 for 3.25

STANDARD LAFAYETTE PHONE JACKS FOR 1/4" PLUGS



FIG. E. OPEN CIRCUIT JACK Standard open circuit phone jack, 3/8" bushing, 1/2" long. Complete with mounting hardware. Imported.

99 N 6213 Net .19 ea.—10 for 1.75
FIG. F. CLOSED CIRCUIT JACK Same as above but closed-circuit phone jack. Imported.

99 N 6222 Net .19 ea.—10 for 1.75
FIG. F. EXTENSION CABLE JACK Fit standard 1/4" phone plug. Screw terminals. Barrel plastic handle matches Barrel plug above. Imported. Shpg. wt., 10 oz.

99 N 6214 Net .22 ea.—10 for 1.90

50 PIECE TV KNOB KIT



1.95

- A Great Value
- Less Than 4c Each

Selection contains 50 assorted TV knobs including such types as channel selector, fine tuning, volume, etc. Useful and attractive. Many with gold lettering or gold inserts. Shpg. wt., 3 lbs.

32 N 9902 1.95

LAFAYETTE CERAMIC DISCS



RATED
1000
DCWV

These Lafayette ceramic discs are ideal for bypassing, blocking and coupling applications, replacements for paper and mica capacitors. Capacity, leakage resistance and breakdown to assure dependable performance. Available in the following values. Shpg. wt., 2 oz.

μF	μF	μF	μF	μF	μF	μF
5	22	50	150	330	.001	.0027
6.8	25	56	180	390	.0012	.003
10	27	68	200	470	.0015	.0033
12	30	75	220	500	.0018	.004
15	33	82	250	560	.002	.0047
18	39	100	270	680	.0022	.005
20	47	120	300	750	.0025	.01

Assort any of above for quantity price.
32 N 0943C 10 for .72, Singly, Ea. .08

HIGH CAPACITY DISCS

.015 μf. Shpg. wt., 2 oz. 10 for .99
34 N 5628 Singly, Ea. .11

.02 μf. Shpg. wt., 2 oz. 10 for 1.08
34 N 5629 Singly, Ea. .12

Switches For Service-Industry-Experimenters

SINGLE POLE SINGLE THROW TOGGLE SWITCH




22¢

• Standard Replacement

SPST Bat Handle: Rated 3 amps—125V. Body size $1\frac{1}{2} \times \frac{3}{4} \times \frac{1}{2}$ " behind panel. Bushing $\frac{3}{16}$ " diam., $\frac{1}{8}$ " long. Bat handle $\frac{1}{2}$ " long. Shpg. wt., 3 oz. Imported
99 N 6150

Net ea. .22
In lots of 10, ea. .19

RUGGED LEVER SWITCH FOR AUDIO AND INTERCOMS



85¢

4 PDT Audio Lever Switch: Has 4 sets of single pole, double throw contacts. Switch has three position with positive & spring return. Panel mounting, mtg. centers 1" apart. Size $2\frac{1}{4}$ " long behind panel. $1\frac{1}{8}$ " W 1" H. Shpg. wt., 3 oz. Imported
99 N 6158

Net ea. .85

RUGGED TELEPHONE TYPE 4POT LEVER SWITCH




CHROME PLATED CAM 69¢

Telephone Type 4 PDT. Lever switch: 3 position lever action switch of non induction construction. Has 4 sets of SPDT contacts — Has 3 locking positions — Heavy insulated rollers. Panel mount, $\frac{3}{16}$ " mounting centers. Size: $2\frac{1}{8}$ " long behind panel. $\frac{5}{8} \times \frac{1}{2} \times \frac{1}{4}$ " H. Shpg. wt., 3 oz. Imported.
99 N 6149

Net ea. .69
In lots of 10, ea. .65

HEAVY DUTY 6 AMP OPOT SWITCH



AS LOW AS 29¢

Heavy Duty 6 Amp DPOT: Rated 250V at 3 Amps or 125V at 6 amps. Switch body $1\frac{1}{4} \times \frac{3}{4} \times \frac{7}{8}$ " behind panel including terminals. Bushings $\frac{1}{8}$ " Dia., $\frac{1}{8}$ " long. Bat handle $\frac{1}{2}$ " long. Shpg. wt., 3 oz. Imported
99 N 6151

Net ea. .32
In lots of 10, ea. .29

SUB MINIATURE PUSH BUTTON SWITCH



18¢ ea. in lots of 10

Momentary contact push button switch. SPST, non-snap action. Rated 115V AC at 100 ma. Overall dimensions $\frac{3}{8} \times \frac{3}{4} \times \frac{1}{8}$ ". Bushing $\frac{1}{4}$ " long. Shpg. wt., 1 oz. Imported.
99 N 6159

Net ea. .20
In lots of 10, ea. .18

SPST "SEE SAW" SWITCH



39¢

• Rocker Arm actuated Flush Mounting

"Touch" action rocker arm type, equipment switch. Mounts flush in panel up to $\frac{1}{8}$ " thick. Requires rectangular mounting hole $\frac{5}{8}$ " wide by 1" long. Mtg. centers $1\frac{3}{8}$ ". Mtg. holes tapped for 4-36 machine screws. Overall behind panel dimensions $\frac{5}{8} \times \frac{3}{4} \times \frac{1}{4}$ ". Rated 3 amps at 125V AC. Shpg. wt., 2 oz.
99 N 6208 Imported

Net ea. .39
Lots of 10, ea. .35

HEAVY DUTY 10 AMP SPOT CENTER OFF TOGGLE SWITCH



39¢

Heavy Duty 10 Amp. SPDT center off: Rated 10 amps at 125V. Silvered lugs for low loss connections. Body size $1\frac{1}{2} \times \frac{3}{4} \times \frac{5}{8}$ " depth behind panel. Imported. Bushings $\frac{3}{8}$ " Dia., $\frac{1}{8}$ " long. Bat handle $\frac{1}{2}$ " long.
99 N 6155

Net ea. .39
In lots of 10, ea. .35

MINIATURE PUSH BUTTON SWITCH




19¢

Momentary contact push-button switch ideal for all miniaturized applications. Single pole two circuit push-to-make type. Beryllium copper leaf contacts. Overall diameter $\frac{1}{2}$ ", overall depth $\frac{1}{8}$ ", protrudes $\frac{3}{8}$ " behind panel. Bushing $\frac{1}{4}$ " dia., $\frac{1}{8}$ " long. Supplied with washer and mounting nut. Shpg. wt., 3 oz. Imported
99 N 6218

Net .19

MAGNETIC PROXIMITY SWITCH



17¢

Magnet Switch

- Circuit Closes When Magnet Approaches Switch
- For Industry and Business
- Hermetically Sealed

An ingenious little device that has untold uses in the home—in a burglar alarm system, electric trains, "magic tricks," and many more. As the magnet approaches the switch, the circuit closes. Hermetically sealed; precious metal contacts; 1 milli-second actuation. 15 watts resistive max. up to 1 amp to 250 volts. Size: $2\frac{1}{8}$ " with leads. 34 N 4401 Shpg. wt., 3 oz. Net 1.74

HEAVY DUTY 6 AMP OPOT CENTER OFF TOGGLE SWITCH




AS LOW AS 45¢

6 Amp DPOT Center Off: For P.A. lighting circuits, etc. Rated 6 amps 125 V.A.C. $1\frac{3}{4} \times \frac{3}{4} \times 1$ " behind panel including screw terminals. Bushings $\frac{3}{8} \times \frac{1}{8}$ ". $\frac{3}{8}$ " bat handle. Shpg. wt., 3 oz. Imported
99 N 6148

Net ea. .49
In lots of 10, ea. .45

ILLUMINATED PUSH-BUTTON SWITCH



175¢

A compact illuminated switch which will indicate mode of operation at a glance. Button lights in "IN" position takes no more space than conventional switches. Lamp is built into push handle. SPST Type. Current capacity, 10 Amps @ 125V AC, 6A @ 250V AC; insulation resistance, 100 meg ohms or more at 500V DC. Solder terminals. Single-hole mtg. Mount in $\frac{1}{8}$ " hole, $1\frac{1}{2}$ " behind panel.
99 N 6192 Imported

Net 1.75

MIDGET-BAKELITE KNIFE SWITCHES



AS LOW AS 12¢

Complete switches mounted on black bakelite base with insulated knob handle of black bakelite. Plated brass contacts provide positive low-resistance connection. Imported.


SPDT KNIFE SWITCH

Overall size $1\frac{1}{2} \times 2\frac{3}{8}$ ". Shpg. wt., 6 oz.
99 N 6152 Net .12 ea. — 10 for .99

DPDT KNIFE SWITCH

Overall size $1\frac{1}{2} \times 2\frac{3}{8}$ ". Shpg. wt., 4 oz.
99 N 6153 Net .19 ea. — 10 for 1.75

6 PDT SLIDE SWITCH



79¢

60PT SLIDE SWITCH: Panel mount. Current capacity 500 ma at 125V AC. Contact resistance 500 milliohms. DC insulation resistance 20 megohms. Measures $1\frac{1}{4} \times \frac{1}{2} \times \frac{1}{4}$ " $\frac{3}{4}$ " D. Mounting center $1\frac{1}{4}$ ". Shpg. wt., 3 oz. Imported.
99 N 6181

Net ea. .79
In lots of 10, ea. .75

ROTARY SWITCHES




4 POLE-3 POSITION 39¢

Four pole rotary selector switch, 3 positions per pole. Useful in hi-fi preamps and stereo applications. Spring loaded, positive detent action. Shorting type. Over-all diameter $1\frac{1}{4}$ ". Depth behind panel, including lugs, $\frac{3}{4}$ ". Bushing $\frac{3}{8} \times \frac{3}{8}$ ". $\frac{1}{4}$ " knurled shaft, $1\frac{1}{4}$ " long. Shpg. wt., 3 ozs. Imported.
99 N 6156 Net ea. .39

Lots of 10, ea. .35

SLIDE SWITCHES AT LOW PRICES!



Compact slide switches in cadmium steel housings. All rated 125V AC. $1\frac{1}{2}$ " mounting centers. Shpg. wt., 3 oz.

Stock No.	Circuit	Ea.	Lots 10 Ea.
34 N 3703	SPST	.09	.08
34 N 3704	SPDT	.10	.09
34 N 3911	DPST	.20	.18
34 N 3912	DPDT	.22	.20

All Channel Electronic Rotating TV Antennas

ALL CHANNEL'S "RIVIERA" WORLD'S MOST POWERFUL ULTRA-FRINGE VHF-UHF-FM ANTENNA

- Guaranteed 200 Mile VHF Reception or Your Money Back
- Broadband UHF-VHF and FM, motorless all direction reception
- Receives channel 2-83 from all directions without a rotor
- All aluminum flip-out assembly

Field tests reception on VHF of up to 200 miles has made possible this unprecedented guarantee. This most powerful ultrafringe antenna may be used for receiving TV channels 2-83 and the FM broadcast frequencies. Perfect for application where color TV or FM multiplex signals are extremely weak due to distance from transmitting antenna and to other receiving conditions. Here is an antenna with only one transmission line for all UHF, VHF, and FM stations in all directions within a 200 mile radius without the use of a motorized rotor. The nine position selector switch conveniently connected at the set electronically rotates the antenna beam pattern instantly without physically moving the antenna. Superb gain on channels 2-6 comparable to stacked 10-element single channel yagis, on channels 14-83 comparable to bow-tie reflector. 16 1/2" doweled aluminum elements are 60 inches long. Complete with switch, coupler, 45" stacking bars and 2-7 1/2" angle type mast insulators for Polymacalene line listed below. Shpg. wt., 10 lbs.

18 N 1201WX Less Mast

Net 19.85

"U-Install-It" kit: Includes Riviera antenna, chimney mount, two five ft. masts, 100 ft. of Polymacalene 4-conductor lead-in wire, 8 stand off insulators and complete instructions.

18 N 1202WX Shpg. wt., 16 lbs.

Net 27.32

ALL CHANNEL'S "ATLAS KIT" Everything Included For Complete Installation

- Money Back Guarantee
- Offers All the Advantages of An Expensive Rotor Motor
- Directional Tuning 12-Position Electronic Rotating Switch
- Eliminates Ghosts and External Interference

12-position Electronic Orientation Switch instantly and automatically beams TV set to the best possible signal, does more than a rotor motor without the large expense and headaches. Very simple to install. The antenna is of preassembled flip out construction with

THE RIVIERA MUST BE USED WITH THE LOW LOSS LEAD IN WIRE LISTED BELOW

Special 4 conductors, matched impedance transmission line. Low loss, mica-filled Polymacalene copperweld conductors.

32 N 1001W 50 ft. length	Net 5.00
32 N 1002W 75 ft. length	Net 7.50
32 N 1003W 100 ft. length	Net 8.90

the center of gravity on the mast itself. Picture quality is improved by eliminating ghosts, reflections and interference in difficult reception areas. Has no moving parts, requires no filters, uses no electric current and no motor control wire. Diamond embossed 45" elements. Complete kit includes stacked "Atlas," electronic rotating switch, switch to set coupler, 70 ft. 4-conductor polymacalene flat lead in wire, 4 stand-off insulators, mounting bracket, two 5-ft. mast sections, instructions. Completely pre-assembled, and pre-wired.

18 N 1203WX Shpg. wt., 14 lbs. Net 22.45

ALL CHANNEL COMPONENT PARTS

18 N 1204 12-Position Switch	Net 5.93 Ea.
18 N 1205 Stacking Harness	Net 2.87 Ea.

REMBRANDT

REMBRANDT TV DIRECTION FINDER



5.95

- Receives From All Directions
- Boosts The Pick-up Power!
- Filters Out Interference
- No Installation Problem

Electrically rotates the polar-receiving pattern of your existing antenna and phases the ground wave picked up by the electrical wiring system with the sky wave picked up by the antenna. Improves any existing antenna—indoor, outdoor, master or built-in. Boosts pick-up power of any antenna—old or new. Just a flick of the selector control tunes out ghosts—filters out interference—tunes in those "hard-to-get" problem channels. Automatically amplifies TV signal strength for "snow" free, brighter, clearer pictures. Works on every channel—in any location—with any antenna for any TV set. No installation problem—simply attach to antenna terminals in back of TV set—and plug into 110V AC/DC socket. Complete satisfaction guaranteed or your money back.

18 N 1206 Shpg. wt., 2 lbs.

Net, ea. 5.95

in lots of 6 ea. 5.00

REMBRANDT "DELUXE"

Ideal for FM Stereo/Multiplex reception



9.95

The only indoor TV antenna with telescoping arms that extend to 97", and using adjustable radar loop principles. Field tests prove efficient operation beyond the range of any other indoor antenna, and in difficult reception areas. New 12-position dual control switch is electronically engineered

to reject ghosts and orient antenna to direction of strongest signal. Brass tip balls on telescoping arms eliminate signal losses and static discharge interference. Adjustable radar loops coupled to arms make clearer, sharper pictures on all channels possible. Durable plastic base. Available in Mahogany, Ivory and Walnut. Shpg. wt., 4 lbs.

18 N 1207 Mahogany

Net 9.95

18 N 1208 Walnut


Net 9.95

18 N 1209 Ivory

Net 9.95

REMBRANDT "880" TV/FM OUTDOOR ANTENNA

- Operates Both FM Stereo and TV
- 12-Position Station Direction Control
- Gold Permadized



9.95

Comparable to 9 Powerful Full Wave Length FM Antennas Plus 9 Highly Directional TV Antennas

Now an outdoor antenna for both FM stereo and TV. Eight 60" long, 1/2" dia. quilted aluminum elements can be compared to 9 powerful full wave length FM antennas plus 9 TV antennas all facing in different directions. 12-position station direction control electronically offers all the advantages of a rotomotor unit without moving parts. It's the only antenna that compensates for changing signal directions caused by changing weather conditions. Also ideal for color TV reception. Elements are preassembled for fast flip-out installation.

18 N 1210WX Shpg. wt., 8 1/2 lbs.

Net 9.95

Special 4-cond. lead-in wire, tinned and plugged.

18 N 1004 70-ft. length

Net 2.10

REMBRANDT FM INDOOR ANTENNA

Up to 10 Times More Effective Than Built-In Antennas 6.95

The Model FM1000 features 1/4-wave 4-section precision arms; 3/4-wave induction coil; 12-position station direction control and a special noise filtering circuit for extremely effective performance. Weak stations are strengthened and reflected signals and background noise are blocked out. Low silhouette slim-line styling. Shpg. wt., 3 lbs.

18 N 1217 Mahogany

Net 6.95

18 N 1218 Ivory


Net 6.95

18 N 1219 Walnut

Net 6.95



LAFAYETTE'S Revolutionary LVL*



NEW HIGH GAIN ALL CHANNEL* LAFAYETTE VECTOR LOG EXCEPTIONALLY EFFICIENT LOG-PERIODIC VEE DESIGN


As Low as **879**

- Extremely High Gain and Front-to-Back Ratio
- For Reception of Black and White or Color TV, FM and FM Multiplex
- Great Selectivity and Sharpness in Any Location
- Flat Response From Lowest to Highest TV Channel

Your choice of six Lafayette LVL models gives you the ideal antenna for your particular needs. Built to last longer and pre-assembled for fast, easy installation. Receives black and white or color TV and FM and FM Multiplex stations with outstanding clarity. Simply select the antenna that will cover your range (up to 175 miles).

18 N 0108	50 mile range.	4 elements.	Shpg. wt., 4 lbs.	Net 8.79
18 N 0109	75 mile range.	6 elements.	Shpg. wt., 6 lbs.	Net 12.91
18 N 0110	100 mile range.	8 elements.	Shpg. wt., 8 lbs.	Net 17.61
18 N 0111	125 mile range.	11 elements.	Shpg. wt., 11 lbs.	Net 23.45
18 N 0112	150 mile range.	15 elements.	Shpg. wt., 13 lbs.	Net 29.37
18 N 0113	175 mile range.	18 elements.	Shpg. wt., 16 lbs.	Net 35.25

FAMOUS COLOR 'TENNA



1395


UP TO 125 MILES OF POWER FRINGE RECEPTION

- 19 Electrical Elements
- Engineered for Superior Color & Black and White Reception
- High Gain on All VHF Channels

Twin-driven elements work with carefully tuned, phased and spaced directors and reflectors to extend flat high gain response across entire VHF band. Cuts out ghosts and unwanted signals. Rugged reinforced aluminum elements and brackets stand up under most severe wind and ice loading. 100% pre-assembled for easy installation. Less mast, lead-in. Shpg. wt., 7 lbs.

18 N 0101WX Net 13.95
Select a complete antenna installation kit from listing below.

POWER BEAM VHF ANTENNA



764

- For Local And Suburban Reception
- Fast Installation
- No Loose Parts
- Time Proven Design


The ideal metropolitan and suburban VHF TV antenna. Broad-band, sharply directive. Full length elements, all aluminum construction, famous in-line design. 300-ohm impedance match reduces stray reflections and ghosts. Fiberglass insulators for maximum strength and weather protection. Less mount and lead-in. Shpg. wt., 6 lbs.

18 N 0102WX Net 7.64
Select a complete antenna installation kit from listing below.

FAMOUS COLOR 'TENNA

UP TO 150 MILES OF EXTRA POWER FRINGE RECEPTION

- 27 Electrical Elements
- Inline Twin-Driver, Yagi Design
- Deep Fringe Gain on All VHF Channels
- Completely Pre-assembled



1798

Delivers the extra picture power needed for crisp, clear pictures in remote areas. Inline twin driven yagi design provides more gain and higher front-to-back ratio. Result: More TV stations, more picture power. Factory preassembled for snap-out assembly. Reinforced gold anodized aluminum construction. Less mast and twin lead. Shpg. wt., 10 lbs.

18 N 0103WX Net 17.98
Select a complete antenna installation kit from listing below.

MAXIMUM PERFORMANCE FRINGE ANTENNA

1188


Range to 100 Miles

- 21 Active Elements
- Snap Open Design
- Fiberglass Insulators
- Compound Yagi Array


GOLD ANODIZED

Field proven design for fringe reception. Gold anodized to combat corrosion. Compound yagi array to "suck-in" signals where other designs fail. "Tension-lok" hardware. Heavy wall tubing throughout. Less Mast. Shpg. wt., 8 1/2 lbs.

18 N 0104WX Net 11.88
Select a complete antenna installation kit from listing below.



Select A Complete Antenna Installation Kit From Listing Below.




"U-INSTALL-IT" KITS

All the items for simple installation. Your choice of an all angle roof mount or chimney mount—lightning arrester—75 feet of 300 ohm twin lead—screw eyes—mast stand offs and 5 ft. 1 1/4 D.D. steel mast. Shpg. wt., 7 lbs.

18 N 0118W	With roof mount	Net 2.95
18 N 0106W	With 2-5 ft. masts.	Shpg. wt., 10 lbs. Net 3.55
18 N 0119W	Same as 18 N 0118W with chimney mount	Net 3.25
18 N 0127W	Same as 18 N 0106W with chimney mount	Net 3.05
18 N 0120WM	Same as 18 N 0119W with alum wall bracket	Net 2.95
18 N 0121WM	Same as 18 N 0106W with alum wall bracket	Net 3.55

New LAFAYETTE Super Color 'Tenna



Revolutionary Perma-Grip Mast Clamps

Massive Element Brackets

Rugged Maximum Transfer Insulators

Protected Lead Wire Terminals

As Low as **9⁹⁵**


- Designed for Color
- Goldenized Finish

Extraordinarily well built antennas with up to 31 working elements for top quality color or black and white TV reception. Features high gain and flat response for excellent color rendition; high front to back ratio to minimize ghosts and corrosion resistant goldenized finish. Preassembled, flip-open construction. Massive double-locking brackets hold elements in perfect alignment. Positive strain loop guards against lead wire breakage. Heavy duty 1" sq. boom, insulators and mounting hardware. Select a complete antenna installation kit listed on page 90.

18 N 0152WX 175 Mile Range. 31 Elements. 17 lbs.	Net 32.50
18 N 0153WX 150 Mile Range. 22 Elements. 14 lbs.	Net 24.50
18 N 0154WX 125 Mile Range. 16 Elements. 12 lbs.	Net 19.95
18 N 0155WX 100 Mile Range. 12 Elements. 9 lbs.	Net 13.39
18 N 0156WX 75 Mile Range. 8 Elements. 8 lbs.	Net 9.95

LAFAYETTE UNI-TENNA

- One Array for FM & TV
- Range to 75 Miles




585 **1055**

Excellent pattern and high gain provide top reception of color and black-white TV and is ideal for FM multiplex stereo. Uses combination TV and FM antenna on one boom with separate transmission lines. 4 Element yagi is used for TV, 3 elements yagi for FM, 10 Elements operating on high band as patented colinear yagi.

18 N 0114WX Shpg. wt., 6 lbs.	Net 10.55
18 N 0115WX Shpg. wt., 3½ lbs.	Net 5.85

Select a complete antenna installation kit from listing on page 90.

"TECHNI-POWER" DEEP FRINGE ANTENNA



- 22 Active Elements
- Range to 140 Miles
- Broadband (VHF Channels)

TV antenna obtains maximum front-to-back ratio without sacrifice of gain on either low or high band! 18 active elements on high band and 4 on low band. Multiple reflectors and directors, combined with the colinear elements sharply increase the directivity. Broadbanded for all VHF Channels 2 through 13. All aluminum screws and nuts to eliminate rusting at vital contacts; tagged connection points; "molded-in" lead line connection screw, and lifetime high impact polystyrene insulators and end caps to prevent whistling and icing.

Shpg. wt., 9½ lbs.	
18 N 0116WX Silver Aluminum	Net 17.11
18 N 0117WX Goldenized	Net 19.05

Select a complete antenna installation kit from listing on page 90.

LAFAYETTE "SUPER HELIX"



- For Deep Fringe Areas Up To 150 Miles
- 26 Working Elements for Extra Sensitivity
- "Goldenized"


1795

Extra-high sensitivity for crisp, clear, snow-free picture in B/W or color, out in deep fringes. Triple-driven collector system combines straight and folded dipole sections into single co-active antenna for Yagi-quality performance. High front-to-back ratios of up to 22 db on low band and up to 28 db on high band screen out ghosts. Entire 1" square boom rigidized by two 1" tubular supports. Less mast and 300-ohm twin line. Shpg. wt., 10 lbs.

18 N 0126W	Net 17.95
------------	-----------

Select a complete antenna installation kit from listing on page 90.

20 ELEMENT STACKED SNAP OPEN CONICAL ANTENNA



- All Aluminum
- No Loose Parts
- Fastest Installations

525

GOLDENIZED

All elements snap open and lock in without tools. Efficient conical design for all reception areas. Two complete bays with Q bars, less mast. Shpg. wt., 8 lbs.

18 N 0105WX Singly, ea.	5.25
Lots of 3, ea.	4.95


Select a complete antenna installation kit from listing on page 90.

ALLIANCE ANTENNA ROTATORS

Model U100 (1 & 2) —Fully automatic, just set control knob and antenna rotates to desired position and stops automatically. Indicator shows position of antenna. Has positive mechanical stop at the end of rotation. Size: Rotator 7¾x5¼x8". Control Case 7x4½x4" 110V, 60 cps AC at 65 watts.	Model K-22 (1 & 4) —Economy model—Provides instant finger tip control of rotation. Automatic signal light indicates when limit of travel in either direction has been reached. Size: Rotator 7¾x5¼x8". Case 5x5x4". Shpg. wt., 12 lbs.	18 N 1404W	Net 18.98
18 N 1403W Shpg. wt., 12 lbs.	4 & 5-Conductor Rotator Cable —4-cond. flat cable. Shpg. wt., 3 lbs. per 100 ft.		
Net 28.20	32 N 8911K per ft.		.03
Model T-45 (1 & 3) —Slight pressure on the control bar rotates antenna through its full 360° cycle and stops at any point by releasing the bar. 5-wire bridge type circuit provides a precision system that is unaffected by motor current, cable length and line voltage variations. Factory lubricated for life. Completely moisture sealed. Uses 5-conductor wire listed at right	32 N 8910 per c ft.		2.50
18 N 1402 Shpg. wt., 12 lbs.	5 cond. Cable. Shpg. wt., 4 lbs. per 100 ft.		.027
Net 23.55	34 N 4628K per c ft.		2.40
	34 N 4629 per c ft.		
	TBB THRUST BEARING BRACKET increases stress capacity to 300 lbs. Wt., 3 lbs.		
	18 N 1405 (not illus.)		Net 2.91



LAFAYETTE All-Channel UHF Converter



15⁹⁵

- Makes Your TV Set a Modern 82-Channel Receiver
- For Use with Any VHF Set
- Easy to Install—Easier to Operate
- Vernier Tuning


The compact Lafayette low-noise UHF converter will add all UHF channels 14-83 to channel 5 or 6 of your present TV set. Precise tuning with dual-knob Vernier selector. UHF/OFF knob for instant selection of UHF or VHF reception. UHF signal light. Maximum signal power with precision 300-ohm input and output impedance. Highly styled, durable metal cabinet. Overall size: 8Wx4Hx4½"D. For 110-120 volts, 60 cps AC. Shpg. wt., 6 lbs. **18 N 0145** Net 15.95

SPECIAL HIGH-GAIN UHF RECEPTION PACKAGE

Consists of Lafayette Converter; completely pre-assembled, 18-0142WX 4-bay UHF antenna; UHF/VHF antenna coupler. Shpg. wt., 11 lbs. **18 N 9000WX** Net 22.95

POWRSCOPE UHF ANTENNA

True Parabolic Focal Design
The Most Powerful UHF Fringe Antenna



- Positive Big Screen Ghost Rejection
- 18 db Gain at Translator Frequencies
- 13 db Gain over UHF Spectrum
- Quick, Strong Installation

The most powerful UHF fringe antenna—proven by performance in the toughest fringe and translator UHF areas. Unique parabolic design exceeds the capture area of 12 and 16 bay car's whisker type arrays. Single dipole provides maximum signal without phasing harness. All metal construction reduces signal loss due to weather deterioration. Pre-assembled screen and dipole are installed in minutes for maximum performance and reliability. Shpg. wt., 10 lbs. **18 N 2401WX** Net 12.99

12⁹⁹

ECONOMY UHF ANTENNA


4⁵⁰

- Highest Gain on 70 UHF Channels
- Completely Preassembled
- Excellent Directivity
- Flat Response Across Each Channel

Four bay, UHF bowtie antenna. Exceptionally high (12db) gain — relatively flat across the entire spectrum . . . Fully factory assembled. Quickest and easiest to install. High efficiency screen grid reflector boosts front to back ratio. Unique "cross-over" phasing bars — open V elements, Rugged—rigid — corrosion resistant construction. Shpg. wt., 5 lbs. **18 N 0142WX** Net 4.50

UHF "TRANSLATOR" 4-BAY ANTENNA

Four bay bow-tie and screen reflector—tuned to the UHF translator frequencies. Average 16db gain on channels 70-83. Completely preassembled. Shpg. wt., 5 lbs. **18 N 0143WX** Net 4.50



SOUTH RIVER SUPER MOUNT

A super-heavy pair of chimney mounts made of aluminum alloy.

Extra strong and durable. Will withstand the most severe weather conditions. Two 12 ft. stainless steel straps and stainless steel seals. Six aluminum corner brackets to protect chimney bricks. The most ideal and permanent installation for those who want quality and durability. Will hold masts up to 2" O.D. Shpg. wt., 5 lbs. **18 N 5601** Each 5.88

Lots of 3, Each 5.29



JFD "LITTLE GIANT" TWIN LEAD LIGHTNING ARRESTER

For Regular or Oval Jumbo Twin Lead. Underwriters Laboratories Approved. No wire stripping or spreading of line necessary. Small size permits easy mounting anywhere—inside or outside. Complete with ground lug and screws for wall or window sill mounting. Special high dielectric, flame-retarding plastic construction does not vary line impedance. Insures maximum signal transfer. **18 N 3802** Singly. Shpg. wt., 9 oz. Each .88



NO RUST BARGAIN MOUNT

1⁹⁸ Singly Each

The ideal chimney mount for life-long satisfactory service under the most severe conditions. Hot dip galvanized steel "Y" mount. Two 10 ft. stainless steel straps and stainless steel seals. And at Lafayette's bargain prices. Shoz. wt., 4 lbs. **18 N 6303** Net Each 1.98

Lots of 3, Each 1.80



GOLD ANODIZED ALUMINUM MAST

- Lightweight
- Strong and corrosion proof

This Golden Anodized aluminum mast will outlast any antenna. Made of a tough, extra strong, drawn aluminum alloy. Two or more masts may be telescoped together.

18 N 3817W 5' wt. 1½ lbs. Net 1.25
18 N 5614WX 10' wt. 2½ lbs. Net 2.39

ALUMINUM MASTS. 19 gauge-heavy wall-high tensile strength. Rust and corrosion proof. Swaged for stacking.

18 N 3818W 5 ft. Wt., 1½ lbs. .89
18 N 3819WX 10 ft. Wt., 2½ lbs. 1.69
10 ft. Mast shipped via express only.

STEEL MASTS. New corrosion-resistant 5 ft. steel mast made to fit all antennas. One end is tapered. "Jam Fit" construction with locking key. 1¼" O.D.

18 N 5615W 5 ft. Wt., 2½ lbs. .68
18 N 5616WX 10 ft. Wt., 4½ lbs. 1.25
18 N 5617WX 10 ft., 16 gauge Wt., 8 lbs. 1.89



ALUMINUM TENNA TOWER

Extremely light (weighs only 1/3 as much as steel) yet incredibly strong. Made completely of aluminum. Roof-mounts are designed to fit any pitch roof for easy house or store top mounting. House brackets may be used for ground installations and are available in two sizes: adjusts to 18" and to 36". Roof-mount is hinged so that the need to "climb the tower" is eliminated for servicing. Will support itself or may be guyed for added strength. May be used with any rotator. 10 ft. Top section. Shpg. wt., 10 lbs.

18 N 8901WX Net 19.87
10 ft. Center or bottom section. Shpg. wt., 10 lbs.

18 N 8902WX Net 19.87
18" House bracket. Shpg. wt., 4 lbs.

18 N 8903 Net 6.54
36" House bracket. Shpg. wt., 7 lbs.

18 N 8904 Net 7.90
Roof Mounts. Shpg. wt., 3 lbs.

18 N 8905 Net 4.62



TELESCOPING TV MASTS

Heavy-duty telescoping masts, ideal for any TV antenna array. Hot-dip zinc galvanizing inside and outside provides unusual ruggedness and impenetrable corrosion resistance. Designed for easy installation and assembly. Husky bolts lock sections automatically. No slipping, no twisting. Precision fitting assures lasting service. 18 and 20 gauge walls. Supplied complete with all guy rings, clamps and necessary hardware. Total 5 10-ft. sections for height up to 50 ft. O.D.: #1 (1¼"). #2 (1½"). #3 (1¾"). #4 (2"). #5 (2¼"). Shipping express only.

50-FT. MAST—Consists of all 5 sections listed above: Nos. 1, 2, 3, 4 and 5. Height 50 feet. Shpg. wt., 39 lbs.

18 N 5609WX Net 12.99
40-FT. MAST. Consists of 4 sections: Nos. 1, 2, 3 and 4. Height 40 feet. Shpg. wt., 28 lbs.

18 N 5610WX Net 9.49
30-FT. MAST. Consists of 3 section. Nos. 1, 2 and 3. Height 30 feet. Shpg. wt., 21 lbs.

18 N 5611WX Net 6.98
20-FT. MAST. Consists of 2 sections. Nos. 1 and 2. Height 20 feet. Shpg. wt., 14 lbs.

18 N 5612WX Net 4.29

LAFAYETTE FM Antennas and Accessories

LAFAYETTE "MULTIPLEX 10" EXTENDED RANGE FM ANTENNA GOLD ANODIZED 9⁸⁸



Ideally suited to Multiplex FM reception. This 10-element, double-driven, yagi array has the necessary added gain, sensitivity and directivity to compensate for the lack of signal strength. All-aluminum gold anodized construction. Fiberglass insulators. Torsion lock hardware, sure-lock mast clamp. Shpg. wt., 7 lbs.
18 N 0128WX Net 9.88

ALL-PURPOSE MOUNT



Mounts on all positions—on the roof, wall or chimney. The perfect all-purpose unit for any type of installation. As a complete roof mount, use only one assembly and three easily installed guy wires. For wall mounting, use two brackets for a rugged free-standing system. Also may be used as a chimney mount with supplied guy wire acting as chimney straps. Shpg. wt., 2 lbs.
18 N 6601 Net 1.39

VHF-UHF-FM COUPLER/SPLITTER

only
3²³



For maximum performance from any VHF-VHF-FM antenna using a single downlead. Signal is "split" by unit permitting 3 independent leads to 3 separate receiver terminals. VHF, VHF, TV and FM. Conjugate Filter network gives high isolation and low signal loss. Includes instructions and mounting hardware for back of set or antenna mast. Wt. 6 oz.
18 N 3021 Net 3.23

MODEL 3007 FM BAND PASS FILTER

3⁹⁸



- Engineered To Mount Anywhere
- Eliminates Interference to FM Reception

Eliminates interference from citizen band, amateur operators, electric motors, aircraft, fluorescent lamps and auto ignition. Provides up to 40 db attenuation of all interfering signals outside the FM band. Less than 1 db insertion loss in 88 to 108 mc band. Recommended to be mounted at FM radio set for maximum effectiveness but may be mounted anywhere in line for less serious applications. Shpg. wt., 8 oz.
18 N 3016 Net 3.98

TRI-SET COUPLER

2²⁹



Highly efficient 3 set coupler. For coupling 2 or 3 TV or FM sets to one antenna of any type. No Interaction—less than 60db insertion loss. 40 to 50 db rejection ratio. Shpg. wt., 1 lb. Imported.
99 N 4010 Net 2.29

TV-FM HI-PASS FILTER

2³⁹



- Eliminates Interference in Antenna Circuits

Hi-pass filter passes all frequencies above 40 mc. Rejects all frequencies below 40 mc. Automatically eliminates electrical disturbances in the antenna circuit. Clears disturbances caused by neon, X-Ray, ignition, appliances, diathermy, short wave, etc. Shpg. wt., 1 lb. Imported.
99 N 4009 Net 2.39

TV TUBE RESTORER

- Corrects Open Cathode — Heater to Cathode Short — Open Control Grid — Control Grid to Cathode Short — Low Emission



One simple unit provides the cure for most ailing picture tubes. Latest model features slide switches — not pin plugs as older units do. Rugged, well made socket — compact, single unit design. Works on electrostatic or electromagnetic focusing tubes, in series or parallel circuits. Includes instructions. Shpg. wt., 1 lb. 4 ozs.
18 N 4604 Net 3.23
18 N 4605 For RCA Type 110° Tubes Net 4.88
For Sylvania Type 110° Tubes
18 N 4606 Net 4.88

TWO SET COUPLER

39¢ In lots of 3




Use one antenna for two sets. Compact electronic set coupler assures performance of two TV sets on one installation. Easy to connect. Nothing to go wrong. Shpg. wt., 1 lb. Imported.
99 N 4004 Ea. .43
In lots of 3, Ea. .39

LAFAYETTE "HI-5" YAGI GOLD ANODIZED

- DESIGNED EXPRESSLY FOR FM

5⁹⁵



High gain antenna design for the audiophile who seeks perfection in FM reception. Extra elements on this antenna serve to pull in stations where others fail. Trouble free operation even under severe weather conditions. The fully automatic snap-lock brackets insure easy, rapid and secure installation.
18 N 0149WX Shpg. wt., 3 lbs. Net 5.95

SUPER ALL-POSITION MOUNT

A strong self-supporting mount which adjusts to any position on peak, slope, flat, corner, or sidewall of building. Positive locking braces eliminate need for guy wires in most installations. Two plane adjustment for true vertical alignment of mast. Made of heavy gauge steel—zinc plated. Standard size takes masts up to 1 1/2" O.D. Large size takes mast up to 2" O.D.
18 N 6504W Small size. Shpg. wt., 4 1/2 lbs. Net 3.00
18 N 6505W Large size. Shpg. wt., 8 1/2 lbs. Net 4.45



LAFAYETTE TRANSISTORIZED 4-SET TV/FM BOOSTER

14⁹⁸

- Amplifies Signals for Top Reception on Up to 4 Sets
- Easy to Connect and Economical to Operate
- Can be Mounted in any Location, in any Position



If your antenna isn't pulling in signals of sufficient strength then this Lafayette Booster Amplifier is just what you need. Screw-on terminals make wire connections easy, no cutting is necessary. Transistor circuit runs cool, draws little current. Signal strength is boosted 3 to 5 times. Will operate up to 4 TV and or FM sets on the same antenna. Input impedance is matched to antenna impedance. Needs no adjustment. Isolated outputs insure maximum set separation. Can be mounted in any convenient location where adequate ventilation is provided. Size: 4 3/4x1 1/4x3 1/2"D. For 117 volts, 60 cps AC. Shpg. wt., 1 lb. Imported.
99 N 4011 Net 14.98

LIFELINE COPPERWELD TWIN LEAD



Guarantee: if this deluxe 300 ohm line fails to last the life of your antenna we will replace it at no charge. 20 Gauge Copperweld (steel clad copper) conductors with finest brown polyethylene insulation. Chemically protected against deterioration. Special "waste free" dispenser package. Shpg. wt., 3 3/4 lbs. Minimum length 100 ft.
34 N 4613 100 ft. package Net 1.98
34 N 4614K Bulk per ft. (over 100 ft.) Net .018

ECONOMY 300-ohm TWIN LEAD




★ 100 FT. 90¢

High quality — heavy gauge — all purpose twin lead. Perfect FM/TV transmission line. Polyethylene insulation. Shpg. wt., 2 lbs.
32 N 8912 Net .90

LAFAYETTE® Super Power Tools Equipped with GE Motors

New LAFAYETTE 1/4" Heavy Duty Power Drill



only
12⁶⁶

- Burn-out Proof Armatures
- Dynamically Balanced G.E. Motor
- Ball-Thrust Bearings

A heavy duty power tool for wood, masonry or even steel. 2.75 amp. motor does the job smoothly and quickly. Use it for a buffer, grinder, polisher, sander. Other top quality features include, ball-thrust bearings, Jacobs geared key chuck and automatic trigger release switch. Capacity—1/4" in steel, 1" in hardwood; Speed—2200 RPM; Motor 1/4 H.P., 2.75 amps, 115V, 60 cycles AC-DC. 3 conductor, 6 ft. rubber covered cord. UL and CSA approved. Die-cast aluminum housing. Shpg. wt., 4 lbs.

13 N 0101

Net 12.66

New LAFAYETTE 3/8" Heavy Duty Power Drill



only
18⁴⁴


- Burn-out Proof Armatures
- Dynamically Balanced G.E. Motor
- Ball-Thrust Bearings
- 1250 RPM

A rugged, heavy duty tool that's loaded with power for smooth performance. Can go through practically any material—cement, plaster brick, hardwood—even tough 3/8" steel! Precision built motor is cool running, trouble-free and stall-proof. Jacobs geared keyed chuck, hand pistol grip, 3 conductor, 6 ft. rubber covered cord. Capacity: 3/8" in steel, 1 1/2" in hardwood; Motor: 1/2 HP AC-DC, 115 V. 60 cycles. Durable mirror finish. Diecast aluminum housing. UL and CSL approved. Shpg. wt., 4 1/4 lbs.

13 N 0102

Net 18.44

NEW LAFAYETTE 1/2" HEAVY DUTY POWER DRILL



22⁵⁰


- Burn-out Proof Armature
- New Compact Design.
- Dynamically Balanced G.E. Motor
- Ball Thrust Bearing
- 550 RPM

Packed with extra hi-torque power for really tough jobs... yet compact and easy to handle. 3.5 amp motor for drilling in heavy lumber and metal. Can be used with hole saws and extra large wood augers. Dynamically balanced and equipped with ball thrust bearings and micro-machined alloy gears. Jacobs geared keyed chuck, top handle and rear spade grip for greater control. Capacity 1/2" in steel, 2" in hardwood; Motor—1/2 HP, 3-5 amp AC-DC, 115V 60 cycles; length 12". Mirror-finished polished aluminum casing. UL and CSA approved. Shpg. wt., 5 1/2 lbs.

13 N 0103

Net 22.50

NEW LAFAYETTE 7" HEAVY DUTY POWER SAW



27⁹⁵


- Ball Bearing Slip Clutch
- Dynamically Balanced G.E. Motor
- Oversize, Heavy Gauge Base Plate
- Multiple Ball Thrust Bearing

A big 7" chrome nickel hardened steel combination blade—cuts through the hardest woods... masonite, plywood, plastic, wall board and dozens of other materials. Easily cuts finished 2x4 at 45°. Heavy duty universal motor, safety slip-clutch to eliminate kickbacks, spring-back blade guard, and calibrated adjustable rip, guide. Motor develops 2 HP @ 10.25 amps; No load speed 5000 RPM. Complete with auxiliary side knob, 3 conductor 6 ft. rubber-covered cord. UL and CSA approved. Shpg. wt., 14 lbs.

13 N 0104

Net 27.95

NEW LAFAYETTE HEAVY DUTY SABRE SAW



- Oversize 45° Tilt Base
 - Dynamically Balanced G.E. Motor
 - Cuts 6" Lumber at 90°
 - Compact and Lightweight,
- 19⁴⁹**

Capable of handling dozens of cutting jobs with ease. Use as rip, crosscut, coping or keyhole saw. Powerful, precision 3.5 amp motor—for greater accuracy with less work. Cuts up to 6" in woods! Also cuts plastics, metals and most other materials. Extra large adjustable base enables accurate bevel cuts up to 45° angle. Sawdust blower removes sawdust as you cut. Makes its own starting hole. 4800 strokes per minute. Complete with 5 blade assortment and 3 wire 6 ft. rubber covered cord. For 115 V; 60 cycles AC-DC. Shpg. wt., 4 1/4 lbs. UL and CSA approved.

13 N 0105

Net 19.49

10-INCH ELECTRIC 1 3/4 h.p. CHAIN SAW



54⁹⁵
\$5 Monthly

- Bores Cuts in Walls
- Pruning-Trimming-Felling Small Trees
- Cuts Cord Wood-Joists-Heavy Beams
- Draws 8 Amps

A powerful, top-quality portable chain saw designed for professional or industrial use. This rugged, multi-purpose tool will also do dozens of jobs for the home craftsman, carpenter, contractor or on the farm. Positive chain adjustment eliminates slack. Chain travels at 1300 feet per minute for fast, true cuts up to 10 inches deep. Cool-running, quiet helical cut gears in a sealed grease chamber. Self lubricating bearings. Beautifully balanced, weighs only 12 lbs. Motor develops 1 3/4 hp., 8.0 amps. 115V. 25-60 cy., AC/DC. 3-wire, 6-ft. cord. Shpg. wt., 14 lbs.

13 N 0106

Net 54.95



SPRAYIT 600 PROFESSIONAL-STYLE SPRAY UNIT

- Integral Compressor-Motor
- All-Aluminum Spray Gun
- Sprays Oil, Paints; Stains



All-purpose spray unit that gives professional results from the start. Adjusts pattern from small-as-a-dime to a fan 10" wide—4 times faster than a brush, and cleans easier too. Easy-to-use 2-finger trigger gun. Never needs lubrication. Air delivery: 1.5-2.0 CFM @ 15-20 lbs. Complete with 6 ft. cord with plug. 8-ft. hose with connections.

14 N 8401 Shpg. wt., 11 lbs.

Net 29.95

MULTI-COLOR KITS: For best results in spraying multi-color paints.

14 N 8402 Shpg. wt., 4 oz.

Net 2.10

AIR TOOLS KIT: For inflation and dusting. Includes chuck for all tires—footballs, basketballs, toys, air mattresses "dusting" attachment.

14 N 8403 Shpg. wt., 4 oz.

Net 1.70

LAFAYETTE Drill Kits and Accessories

54-PIECE SUPER DUTY 3/8" DRILL KIT

- Super Powered 3.0 Amp. 3/8" Drill with Multiple Ball Thrust Bearing, Jacobs Chuck & Key, Micro-Machined Gears, Gleaming Mirror finish
- Drill and Practical Accessories Selected for Power and Performance

A drill kit deliberately designed to make the tough jobs easy. Big 3.0 amp 3/8" drill packed with power to spare when you need it! A husky right angle gear drive—can halve or double drill speed! Increase torque or speed to suit your needs. A powerful 12-piece, screw and nut driver set with screw driver bits, Phillips head bit, eight sockets for hex and square nuts and bolts, powerful non-slip clutch. 36" flexible shaft for all your intricate drilling, grinding, buffing or hobby work. 5-pc. Carbide drill set for boring concrete, masonry, tile, plastic from 3/16" to 3/8" dia. holes. Plus 29 full jobbers length twist drills from 1/16" to 1/2" by 64th in a metal index. All the really needed tools left out of most drill kits. Shpg. wt., 12 lbs.

13 N 9006
14 N 4802 3/8" Super Power Drill only

Net 29.95
Net 13.20

only
29⁹⁵



72-PIECE "POWER SHOP" 3/8" DRILL KIT


- A Complete Workshop For Do-It-Yourself Joos
- Drill, Sand, Grinds, Buffs, Saws
- Home, Garage, Shop

A complete electric power workshop at Lafayette's typically low price. You can do almost every at-home job with this versatile 72-piece set. Look at what you get: Powerful 2.5 amp. 3/8" electric drill; 6-pc. power boring set with bits from 3/8" to 1"; 14-pc. twist drill set with metal index; 29-pc. sanding and polishing set; 7-pc. grind and buff set; 9-pc. 7-size hole saw; 7-pc. countersink and drill saw set; 3-pc. power screwdriver attachment. The 3/8" drill has 2.6 amp, 110 VAC motor. No-load speed, 1750 rpm; full load speed, 1150 rpm. Special alloy bearings throughout. U.L. approved. Shpg. wt., 10 lbs.

13 N 9005

Net 19.95

ONLY
19⁹⁵



"JIFFY" JIG SAW




488

- Automatically Blows away Sawdust
- Self-lubricating Lifetime Bearings
- Blade Easily Changed

For home craftsman, carpenters, plumbers, electricians, cabinet makers. Cuts straight lines, intricate patterns, or circles — no matter how large — in wood, wallboard, plastics, metals. It even cuts 2x4's! Use for cutting openings for plumbing, switchboxes, etc., without boring starting hole. Actually does the work of a jig, keyhole, coping, rip, crosscut, band or hacksaw. Blades easily changed with ordinary screw driver. Complete with 1 jig-saw blade, instructions and 1-year factory guarantee. Shpg. wt., 1 1/2 lbs.

14 N 1407 Net 4.88
Replacement Blades—Package of 6 Ass'd. Net 1.30
14 N 1408

SHOP-KING SAW WITH DADO ATTACHMENT



798

- Cuts 2 x 4's in one cut

"SHOP KING" with Adjustable "Dado-Arbor" cuts any groove up to 1/2" wide x 1" deep on ONE CUT! Arbor swivels sawblade to cut large grooves with little power—no heavy duty drill needed. "Dado-Arbor" easily removed for straight and angle cuts with precision Depth-Bevel-Rip Gages. Has 5" Safe-cut blade. Fits any 1/4" drill in 1 minute. With instructions and factory guarantee. Shpg. wt., 4 lbs.

14 N 1402 Net 7.98
14 N 1403 Safecut Blade 1.23
14 N 1404 Hycarbon Crosscut Blade 1.23
14 N 1405 Hycarbon Combination Blade 1.23

REVERS-A-DRIVE MODEL W-300L



950

- TAPPING
- DRILLING
- NUT DRIVING
- REVERSIBLE SCREWDRIVER
- INCREASES TORQUE

Can be fitted to any electric drill or drill press quickly and easily. Heavy duty industrial type for instant 11 to 1 speed reduction. Develops high torque when more power is required for oversize drilling. Easy stop-start action with hand clutch control. Accessories include yankee type — 3/16" standard bit — 3/16" phillips bit — socket adaptor—adaptable for 1/2" chuck plus a 3/8" female adaptor to fit drill chuck onto unit. Shpg. wt., 1 1/2 lbs.

14 N 7901 Net 9.50

PISTOL GRIP FLEXIBLE SHAFT

With 1/4" Chuck!



- 36" Long Flex. Shaft
- Comfortable Pistol Grip
- Like Owning A Flexible 1/4" Drill

With this attachment any electric motor becomes a tough work horse. No need to hold a heavy or hot motor. Sturdy metal pistol grip will allow accurate and comfortable work when using this handy item. Operates at speeds up to 6000 R.P.M. Will accommodate shanks up to 1/4" dia. and accepts all 1/4" drill attachments. Includes 1/4" chuck. Long flexible 36" shaft will allow you to "walk around" your work. Perfect for grinding — polishing — buffing — drilling — sawing — routing or carving. For use on wood — metals — glass and plastic. Shpg. wt., 3 lbs.

14 N 7006 Net 2.75

STANLEY "SWIRLWAY" 2-WAY SANDING ATTACHMENT



294

- Flexible Ball-Joint Action
- Rigid Sanding Plate

Drill attachment uses new principle in dis sanding. Has flexible ball-joint action—disc always lies flat on work. Complete control—won't gouge or score. Adjusts to standard plate in seconds. Complete with 3 abrasive discs (coarse, medium, fine). Shpg. wt., 1 lb.

13 N 3360 Net 2.94

UNIVERSAL DRILL PRESS STAND



1044


- Adjustable Depth Stop
- Spring Return Tension
- Adjustable Cradle
- Adjustable Depth Gauge Dial

Can be used for any 1/4" pistol grip electric drill. Features rack and pinion gear feed, and adjustable depth stage. 15 to 1 leverage. Drill press head is clamped in rigid position. 2 1/4" stroke. Square base is provided with slots for drill bit and for bolting work to base. Other features include spring return tension, fast hand-action, head clamps and adjustable depth gauge dial. Shpg. wt., 6 lbs.

14 N 3604 Net 10.44

LAFAYETTE Leading Tool Values

New! Wen 950 Multi-Speed
1/2" Reversible Drill




32⁸⁸

- Multiple speeds From 340 to 2400 RPM
- Powerful 6 Amp., 1/2 HP Burnout-Proof Motor
- Double Reduction Gears for Super Torque
- UL Industrially Rated

A versatile heavy duty 1/2" drill to handle big jobs — where great power is required. Quick, easy two-lever control of electronic and gear reduction speed changes permit efficient use of drill for any type of material or size of hole. All 4 speeds are reversible too with extra safety double switch. 6 amp. 1/2 horsepower motor, 120V AC/DC, 6 ft. 3-wire cord. UL and CSA approved. Size: 11x 8 1/2 x 3 1/2" (LWH). Die Cast aluminum housing, balanced for continuous operation. Shpg. wt., 9 lbs.
13 N 6533 Net 32.88

WEN ELECTRIC HAND
PLANE MODEL 930




29³⁷

- Souped-up 1.2 H.P. Burnout-Proof Motor
- Balanced, Lightweight Polished Aluminum Housing
- Industrially Rated for Heavy-Duty Use

Built for years of precision work. Separately adjustable twin cutters; welded burn-out-proof armature; finger control trigger switch. Cutter speed 14,500 R.P.M. Mitre guide plate angle adjusts up to 45°. Guide plate is removable for surface planing. Cutting width 2 1/4"; depth adjustable to 1/8". Polished aluminum housing with air stream chip ejector. Shoe length 16". 3-wire 8-ft. cord.
13 N 6503 Shpg. wt., 9 lbs. Net each 29.37

WEN 'SOUPED UP' SABRE
SAW MODEL 909



- Heavy Duty, Full 6 Amp.
- 6" 90° Cut
- 1/2 H. P. Motor, 1 inch Stroke
- 4" 45° Cut
- Largest Cutting Capacity

29³⁷

Super-long blade easily cuts through 6x6" lumber. Cuts 4x4" at a 45° angle! Power enough to cut steel plate up to 1/2" thick—iron pipe up to 2" in diameter. Saw tilts 45°—sole plate always remains flat. Air stream blows dust from line of cut. Includes seven blades for cutting wood—steel—hardboard—sheet metal—pipe—leather—rubber—formica, etc. Equipped with rip guide and circle cutter guide. 8 ft. 3 cond cord and adapter. 110 watts. 6 amp., AC-DC. 8Lx7Wx7 1/2"H. Shpg. wt., 8 1/4 lbs.
13 N 6501 Net 29.37



WELLER D550PK HEAVY-DUTY SOLDERING KIT

8⁵⁹

A Professional Heavy Duty soldering Kit featuring the dual-heat 240/325 watt Weller gun. Everything needed for hundreds of applications in Hobbies, Shopwork, Household repairs.

Kit contains D-550 Solder gun, All purpose solder, Cutting Tip, Soldering Tip, Smoothing Tip, Tip Changing Wrench and Instruction Booklet. Entire kit is enclosed in a high impact plastic case with carrying handle.
13 N 3918 Shpg. wt., 5 lbs. Net ea. 8.59

AUTOMATIC SOLDERING IRON



- Only
- Feeds Solder Automatically
 - Easy, One-Hand Operation
 - Lightweight and Durable

4⁹⁹

Features automatic feeding of solder — gives you a "3rd hand." Tip AND solder are placed at exact spot needed. Any required quantity of solder can be automatically fed to the soldering tip by adjusting the feed roller. Tip is made of special alloy for longer service life. Use with standard solder or with special spool listed below. Rated at 30 watts. Operates on 117 volts AC. Shpg. wt., 2 lbs. Imported.
99 N 8062 Net 4.99
99 N 8063 Extra Tip for above Net .35

NEW! DURO LABEL-MATE

5⁸⁸



- Wide 3/8" Self-Stick Plastic Tape
- Large Easy to Read Letters
- Easy to Use—For Home—Office—Industry

Precision built Label-Mate prints large easy-to-read raised letters instantly. Features wide 3/8" tape with self-stick backing. Tape addresses permanently to all smooth, clean surfaces — indoors or outdoors. Full-view 44 character wheel permits fast, easy operation. See each character as you emboss. Instant start—no back up, no unnecessary waste of tape. Tough durable shock-resistant plastic housing for long service.
12 N 3504 Shpg. wt., 1 lb. Net 5.88
Embossing Tape Magazines—3/8" wide, 144" long. Shpg. wt., 1/4 lb. Net ea. .98

Stock No.	Color	Stock No.	Color
12 N 3505	Red	12 N 3501	Clear
12 N 3502	Blue	12 N 3500	Black
12 N 3503	Green		




1-LB. ROSIN CORE SOLDER

Coiled on metal spool. Standard 60/40 quality — Ideal for home or shop use. Shpg. wt., 1 1/2 lbs.
13 N 6401 Net 1.29

NEW RIVET-ALL RIVET KIT

3⁹⁹



A professional tool which joins virtually anything, metal to metal, plastic to wood, fabric to fabric. Easy to operate, just insert rivet into tool, place in pre-drilled hole and squeeze gun and you have a strong rivet joint. KLIK rivets are strong, neat and permanent. Ideal for Hobbyists, Electronics, Household and Auto repairs. Kit includes Riveter, supply of rivets of various sizes. Extra rivets available at low cost. Shpg. wt., 2 lb.
13 N 5401 Net 3.99
25 Rivets for Work to 1/8" Thick 13 N 5402 Net .44
20 Rivets for Work to 1/4" Thick 13 N 5403 Net .44
15 Rivets for Work to 1/2" Thick 13 N 5404 Net .44
40 Back-up (Reinforcing) Plates 13 N 5405 Net .44



M-4 HOME LABEL MAKER 6⁶⁴

A precision tool designed especially for home use. Just dial letters, numbers, symbols—squeeze the embossing handle—pull the cut-off trigger and that's it. Embossing wheel has 44 characters. Prints a crisp white message on durable moisture-resistant tape. Made of heavy duty plastic. Size 6 1/2" x 6" H. Shpg. wt., 2 lbs.
14 N 4101 Net 6.64

Embossing tape Magazine for Model M-4. Each contains 144" of 1/4" glossy vinyl tape with adhesive backing. Shpg. wt., 1/4 lb. Net ea. .98

14 N 4102	Blue	14 N 4106	Brown
14 N 4103	Green	14 N 4107	Black
14 N 4104	Red	14 N 4130	Orange
14 N 4105	Clear	14 N 4131	Yellow
		14 N 4132	Gold

Cloth Printer Kit. Provides a clean, fast and easy way to mark all clothing when used with your Dymo Home Labelmaker. Use directly on clothing or use the iron-on label provided. Shpg. wt., 1/2 lb.
14 N 4108 Net 4.75
72 Assort. Iron-On Tapes for above Net .95
14 N 4109 Net .95

RAM "Fury"—Skil—Speedway Power Tools

RAM "FURY" 1/4" DRILL
OUR TOP DRILL VALUE




- 2 Amp. Motor
- U/L Approved
- Jacobs Geared Chuck and Key
- Multiple Thrust Ball Bearings

788

Lafayette's top drill value. 1/4" geared chuck drill rated at a full 2.0 amps. U/L approved. 1/4" capacity in steel, 1/2" capacity in steel, 1/2" capacity in hardwood. 1200 rpm speed under full load, 2000 rpm no load speed. Precision anti-friction bearings. Automatic trigger switch. Specially designed gear train for maximum torque transfer. Overall length 8". For 115 volts, 25-60 cps AC. Shpg. wt., 4 lbs.
13 N 7101 Net 7.88

SPEEDWAY HUSKY 3/8" DRILL




- "Thermoweld" 3-Amp Motor—that Won't Burn Out!

1188

Get the balance and feel of a 1/4" drill—with the power and work capacity of a husky 3/8th. Industrially rated to handle really rugged work. Special bronze alloy bearings. Precision-geared chuck and key. Noload speed 1750 rpm, full-load about 1150 rpm. Locking trigger switch. Cast aluminum alloy housing. 6-ft. 3-wire cord and plug. UL and CSA approved. 115V., 25-60 cps AC. Shpg. wt., 5 lbs.
13 N 5302 Net 11.88

RAM 2-WAY ELECTRIC SANDER
MODEL R-120




- 3/4" Stroke Orbital or Straight
- Positive Slide Switch

Orbital or Straight Line

A heavy-duty electric sander with 3/4" stroke in orbital or straight line. Features 2.4 amp universal series wound motor. Heavy-duty ball bearing and self-lubricating sleeve bearings. Pad size: 3 1/2 x 7 1/2"; sandpaper size: 3 1/2 x 9". Industrial mirror finish. 6-ft., UL approved cord. 115V, 60 cycles, AC-OC. Shpg. wt., 5 lbs.
13 N 7102 Net 16.88

RAM "FURY" 7" HEAVY-DUTY POWER SAW

Only **1988**




- 7-Inch Combination Blade
- Universal 1 1/2 hp Motor
- Safety Retracting Handle
- Heavy Duty 3 Conductor Cord
- Approved by UL and CSA

A powerful 8 ampere motor provides this big 7" circular saw plenty of reserve power to zip through straight or angle cuts. Cuts vertically to 2 1/4" at 90°, to 2 1/4" at 45°. Features self-lubricating bronze bearings, floating blade guard, safety retracting handle, combination rip and cross-cut blade and 3-wire cord and plug. No load speed, 5000 rpm. Motor is a universal 1 1/2 hp AC-DC 115 volts. UL Approved. Shpg. wt., 15 lbs.
13 N 7103 Net 19.88

SAW TABLE. Perfect complement to the above Saw. Allows cutting at any angle between 45° and 90°. Complete with miter gauge and rip fence. Shpg. wt., 12 lbs.
13 N 7104 Saw table Net 11.65

SPEEDWAY 4 1/2" BENCH GRINDER



1499

Ideal for sharpening all workshop, hobby and garden tools—drill bits, planes, knives, chisels, hoes, etc. Base equipped with rubber feet; drilled for bolting to bench or truck. Heavy-duty steel wheel guards; adjustable tool rests; built-in front water cooling tray; castin top parts tray; rear duct exhaust. Bronze alloy bearings. Two 4 1/2 x 1/2" wheels (one 40-grit, one 70-grit). 2.5 amp. 115V, 60-cycle AC motor; no-load speed 3450 rpm. 6-ft. 3-wire cord. Shpg. wt., 10 lbs.
13 N 5309 Less eyeshields Net 14.99

NEW! SKIL VARIABLE SPEED DRILLS

- Trigger Speed Control
- Speed from 0 to 2,000 RPM
- Complete with Carrying Case
- No Dials—No Buttons—No Rheostats

As Low As **2548**



EXCLUSIVE TRIGGER SPEED CONTROL 0 to 2,000 RPM



Absolute speed control at your fingertips. No dial or buttons. No rheostats. You get the exact speed you need for every conceivable task. You actually sense the correct bit speed with your "trigger finger." Make holes in steel, accurately, without center punching. Use as a precision driver. All that is required is a driver bit. The variable speed feature lets you start a screw at low speed, run it down fast at a higher speed and finally set it snug by slowing to a stop. "Super Burnout Protected Motor" rated at a full 2.5 amps., 115 V AC. Equipped with geared chuck and key, 3 wire cord and 3 prong-plug with 2 prong adapter. 9 inches long. Complete with carrying case.
13 N 6901 Shpg. wt., 4 lbs. Net 25.48
Model 569 TSC 3/8" Drill 13 N 6917 Shpg. wt., 4 1/2 lbs. (less case) Net 33.95
Model 545 TSC 1/2" Drill 13 N 6919 Shpg. wt., 5 lbs. (less case) Net 36.50

SKIL RECIPRO SAW with 3 Blades

- Cuts anything from Thinnest Plastic Sheeting to 6" Logs
- Exclusive 3-Position Foot—Flush, Stationary, Rocking
- Exclusive 4-Position Blade

3695

\$5 monthly



It's the brand new Skil Model 577 Recipro Saw—the amazing tool with a virtually unlimited cutting capacity . . . from 6" logs to the thinnest plastic sheeting. Cuts any material from soft wood to steel or plaster. Makes tough rip cuts, intricate scroll work, miter and bevel cuts, flush cuts without attachments, pocket cuts with its own starting hole, cross-cuts. Features Universal 3-amp motor with self-lubricating bearings; no load speed of 2000 strokes per minute. Stroke 3/4"; overall length 1 1/4". 3-wire cord with 3-prong and 2-prong adapter. Double reduction gears; 3-position side handle, automatic blower, canted blade, etc. Complete with 3 blades (13-6906, 13-6907, 13-6908). UL approved, 115V, 60 cycle AC.
13 N 6903 Shpg. wt., 6 1/2 lbs. Net 36.95

ACCESSORY BLADES

STOCK NO.	TEETH PER IN.	LENGTH (IN.)	USE	NET EA.
13 N 6904	10	4	Metal cutting—ferrous 1/4" or thicker	.40
13 N 6905	10	8	Non-ferrous 1/8" or thicker	.80
13 N 6906	6	4	Fast scroll cutting in wood	.60
13 N 6907	8	4	Hollow ground for smooth wood cutting	.67
13 N 6908	10	4	Multi-purpose—rough-in cuts in wood w/nails	.20
13 N 6909	10	12	Soft metals, under 1/2" thick	.47
13 N 6910	6	6	Plastic cutting or wood, building tile	.27

Stanley Heavy-Duty Router



- High Speed Production Router
- $\frac{7}{8}$ Horsepower
- 23,000 RPM Motor
- Built-In Spotlight
- Micrometer Depth Adjust To 4/1000"
- Automatic Shaft Lock—Needs Only 1 Wrench

An advanced router design which features excellent balance and control. This tool provides both outstanding safety and fine performance. Cuts dovetails—dadoes—tenons—mortises—rabbits—beading—molding—joints—grooves—decorative cuts—inlays—cuts soft metals. Built-in spotlight increases brightness as work load increases. Recessed switch automatically locks shaft when changing bits. Precision micro-depth adjustment as fine as .004 inch. Cantilevered base and advanced design grips for stability and balance. Clamping lever holds or releases motor with a flip. 6 amp., 23,000 RPM, 115v AC/DC. Shpg. wt., 9 $\frac{1}{2}$ lbs. **13 N 3358 Net 48.97**

48⁹⁷ \$5 monthly

Basic Bit Kit: Includes three most useful router bits $\frac{1}{4}$ " straight, $\frac{3}{8}$ " rounding over, $\frac{3}{8}$ " V grooving. Also includes a Silicon Carbide hone to keep cutting edges keen. Shpg. wt., $\frac{1}{2}$ lb. **13 N 3359 Net 6.97**

RAM BUFF-'N-SAND



23⁷³

- Two Tools in One—A Combination Polisher, Buffer and Sander

A rugged all-purpose polishing and sanding tool half the weight of similar units. Perfect for sanding or polishing furniture, cars, floors and walls. Engineered to operate at 500 rpm to avoid hi-speed heat and friction on working surfaces. Universal AC-DC motor employs thrust ball bearings for smooth rotary action. Supplied with heavy duty 3-conductor cord, $\frac{7}{16}$ " O.D. lambswool bonnet and 24 sanding discs. Overall length 13 $\frac{1}{2}$ ". Shpg. wt., 5 $\frac{1}{2}$ lbs. **13 N 7111 Net 23.73**

The "ULTRA" Electro-Tool Kit



8⁹⁵

- Professional Quality Throughout
- All the most often needed tools
- Designed with the Technician in mind

Each component tool chosen to offer utility and quality. The "ULTRA" kit contains the following: 6 $\frac{1}{2}$ " insulated side cutters, 5" insulated chrome plated diagonals, 6" insulated chrome plated long nose, 30-watt soldering iron. 3 offset open-end wrenches covering from $\frac{1}{4}$ " to $\frac{1}{2}$ ", 5" chrome plated tweezers, shockproof amberoid chuck handle, $\frac{1}{2}$ " screw driver blade, $\frac{3}{32}$ " screwdriver blade, #1 recessed screwdriver blade, punch-awl blades, $\frac{1}{4}$ " nut driver blade, solder and flux. Pliers insulated for 10,000 volts, hand honed cutting edges. Side cutters have beveled nose, diagonals have provisions for wire stripping, long nose has "wrench" grip jaws and cutters. The entire set is nested in a zippered, fitted, lined book type carrying case with handle. Measures a scant 9x5x2". Shpg. wt., 2 $\frac{1}{2}$ lbs. Imported. **99 N 8017 Net 8.95**

NEW CHASSIS PUNCH SET



5⁴⁹

- Easy-smooth holes in sheet metal
- 5 sizes: $\frac{1}{2}$ ", $\frac{3}{8}$ ", $\frac{3}{4}$ ", 1", 1 $\frac{1}{8}$ "

Five most often needed round hole punches. Easily cuts smooth accurate holes for sockets, plugs, controls, panel lights, switches, terminals, and most radio parts. Drive with any wrench or with included T-handle. Punch sizes included are $\frac{1}{2}$ ", $\frac{3}{8}$ ", $\frac{3}{4}$ ", 1", 1 $\frac{1}{8}$ ". Complete with punches, dies, T drive handle, tapered reamer, fitted case, and instructions. Shpg. wt., 2 $\frac{1}{2}$ lbs. Imported. **99 N 8024 Net 5.49. Lots of 3 ea. 4.94**

20-PIECE TAP AND DIE SET

- NATIONAL COARSE SIZES



5⁵⁹

Twenty of the most often needed taps and dies. Sizes popularly used in radio, hobby, home, shop and light industry. Contains one tap and one die in each of the following sizes: 6-32, 8-32, 10-24, 12-24, $\frac{1}{4}$ -20, $\frac{3}{8}$ -18, $\frac{1}{2}$ -16, $\frac{3}{4}$ -14, and $\frac{1}{2}$ -13. Includes die stock and adjustable tap wrench. Entire set contained in a fitted metal case. Shpg. wt., 4 lbs. Imported. **13 N 5510 Net 5.99**

6-PC. MOUNTED STONE SET



1²⁰

Six assorted grinding stones and wheels. Set of mounted grinding points, stones, and wheels. Mounted on $\frac{1}{8}$ " and $\frac{3}{32}$ " OO shafts. An ideal accessory for the flexi-shaft tool. Shpg. wt., 8 oz. **13 N 5001 Net 1.20**

FLEXI-SHAFT HOBBY TOOL



- Powerful-versatile
- Hi speed-hi torque

Flexible shaft and motor combination for all grinding, polishing, drilling, buffing, and engraving. 1 amp. motor delivers power for continuous use. Light weight finger tip control. 36" flexible shaft is a sealed unit. Chuck accommodates $\frac{3}{32}$ " and $\frac{1}{8}$ " in. tool shanks. 110/120V AC or DC. Shpg. wt., 3 lbs. **13 N 9008M Net 6.60**

AS LOW AS 2⁹⁸




"ADJUST-A-BOX WRENCH"

- A full set of box wrenches in one tool
- Narrow Head: Gets into tight places
- Non-Slip Jaw Grip, Prevents Slipping, Saves Knuckles
- Fits Metric Sizes as well as U.S. Standard

Covers range of eight or more double-end box wrenches—a complete box wrench set in just one tool. Off-set and upward slanted handle provides excellent knuckle clearance and full hand grip at all times. A perfect holding tool behind wall and other obstructions. Made of drop-forged alloy steel, heat treated and nickel—chromium plated. Long bolts extend through opening in jaws. Presents no problem as encountered with sockets. $\frac{1}{2}$ lb. 8" Cap. $\frac{1}{4}$ "x1". **14 N 4501 Net 2.98**

12" Cap. $\frac{3}{8}$ "x1 $\frac{1}{4}$ " **14 N 4502 Net 5.95**



COMPASS CIRCLE CUTTER

2⁹⁸

- Uses special bit with side-cutting Action
- Simple and safe to use

Simple and safe to use, makes perfect circles in wood in seconds. Use with any electric drill to cut speaker holes, vents, pipes, ceiling lights, etc. Can also be used to make discs, rings and fancy shapes. Cuts circles $\frac{1}{2}$ " to 12" in diameter. Shpg. wt., 1 lb. **12 N 4100 Net 2.98**

VARI-SPEED



8⁹⁵

- Continuous Regulation of Lights & Motors
- Regulates Speed of Power Tools

Full range solid state speed control with built in automatic circuit breaker. Allows continuous varying speed from max. RPM to min. Also controls light intensity. Fingertip speed control for power tools, home appliances and lighting. Handles up to 900 watts. Can be mounted permanently or remain portable. 3 wire receptacle and 6 ft. 3 wire power cord provides maximum safety. Shpg. wt., 2 lbs. **12 N 1301 Net 8.95**

Do-It-Yourself with Slotted Erect Angle Steel Units



Under Stairs Rack



Machine Stand



Outboard Motor Stand



Soap Box Racer

Only
944

Hundreds Of Applications

- Workshop
- Garage
- Playroom
- Basement
- Attic
- Office

Now it's easy to custom build the equipment you need in steel. Hundreds of uses in the workshop, garage, attic, playroom, basement and office. All you do is measure, cut and bolt together using only a hacksaw and wrench. Made of strong cold-rolled gray-enameled steel. Corner plates provide added structural strength and rigidity—eliminate need for crossbracing. Angles are conveniently marked-off for measuring. 50-Ft. outfit consists of 10 5-ft. lengths of angle steel, 20 corner plates and 75 nuts and bolts. Shpg. wt., 16 lbs. **12 N 7700** Net 9.44

Plastic Feet for professional look. Pkg. of 12 **12 N 7701** Shpg. wt., 6 oz. Net .77

LOOK WHAT YOU GET!

50 Ft. of angle, 75 nuts and bolts and 20 corner plates.



ZEUS PORTABLE GENERATORS

- Permanent Magnet Alternator
- Compact and Portable
- 2½ H.P. Briggs and Stratton Engine
- 1000 Watt Continuous Duty Rating

As Low As **148¹³** \$7.50 Monthly

A compact, portable electric power plant for on-the-spot electricity anytime, anywhere. Features a permanent magnet alternator that gives you more power and trouble-free operation—no brushes, armature windings, belts, slip rings or commutators. Dependable Briggs and Stratton 2.5 H.P. 4-cycle engine gives easy-to-start, long-life service hour after hour. 1-qt. capacity fuel tank. Recoil starter. Integral receptacle: rubber shock-absorbing feet. Instruction book. Portable—only 63 lbs. Compact—15Hx13½Wx13"D. 115 V, AC, 1000-watt rating. Shpg. wt., 70 lbs. **13 N 4901WX** Net 148.13

1250 AND 3000 WATT UNITS


A light weight small size, portable gasoline powered electric generator that features a permanent magnet alternator for maintenance-free operation. Trouble factors such as brushes, windings, belts, slip rings and commutators have been eliminated because there is only one moving part, the permanent magnet alternator. A Briggs and Stratton 3 horsepower, 4-cycle engine gives easy-to-start, long-life dependable service hour after hour. All units deliver 115 VAC. **13 N 4902WX** (1250 watts). Shpg. wt., 82 lbs. Net 190.88
13 N 4903WX (3,000 watts). Shpg. wt., 195 lbs. Net 431.25



"HOPPY" SPLIT-IMAGE TRANSIT

Low Cost, Precision Level and Incline Measure


459



- Prism-Like Optical System
- Plate Glass Mirrors
- External Sights

Amazingly accurate instrument that will indicate level and measure a minimum of ¼" rise or fall at 25'. Makes present day bubble and string type levels obsolete. It not only indicates level but shows exactly how much correction is needed. One man can perform any leveling or incline measuring job quickly, easily, and accurately. Makes any complicated measuring/leveling job simple. Use it for patio layout, bricklaying, flooring, surveying, terracing, fencing, plumbing, shelving, gutting, drainage, irrigation. Indispensable as a leveling and grading tool for model railway pike. Shpg. wt., 6 lbs. **14 N 1801** Net 4.59
14 N 1802 case—Shpg. wt., 1½ lbs. Net 3.20

18 COMPACT DRAWERS




MODEL 18HBA **399**

Both cabinets are 9" High and 6" Deep

Stock No.	Model	No. of Drawers	W	Wt.	Net ea.
13 N 7616	18HBA	18	10"	4½"	3.99
13 N 7617	24HBA	24	13"	6½"	4.99

INTERMATIC 3 CIRCUIT SPRINKLER TIMERS

16²²



The Intermatic lawn sprinkling system time controls permit completely automatic pre-programmed watering of up to 3 zones. A 24 hour time dial can be set to initiate sprinkling any time during the day while skipper wheels serve to eliminate watering on selected days. Time durations per area are adjustable from 5 to 60 minutes. May be manually operated. Both models are rated at 120 volts, 60 cycle, 5 amps. Gray hammertone cast measuring 7¼x5x3". Shpg. wt., 3 lbs. **13 N 2725** 7 day Net 16.22
13 N 2726 12 day Lots of 6, ea. 14.97

Net 16.22
Lots of 6, ea. 14.97
Net 16.22
Lots of 6, ea. 14.97

NEW WATER FLOW METER

- Automatic Shut-off For Any Sprinkler
- Non-Corroding
- Up to 750 Gallons per Setting

395



Set it, then forget it. The automatic water meter does the rest, shutting-off automatically when sprinkling is completed. Set dial for the degree of sprinkling needed up to 750 gallons. Quickly attached to any standard faucet or sprinkler. Operates under low or high pressure and compensates for variations in pressure. Non-corroding heavy duty zinc construction gives years of dependable service. Size: 8x7x3". Shpg. wt., 2 lbs. **12 N 7000** Net 3.95



NEW! WONDER-WORKING "GARDEN GENIE SPRAYER"

Now Everyone Can Have A "Green Thumb"

5⁹⁵

- ★ Does Most Everything But Mow the Lawn
- ★ Effective, Handy Garden Servant
- ★ You Walk — Garden Genie Does the Work

- Fertilizes Lawns, Flowers, Shrubs and Trees
- Safe, Easy Sprayer for Insect/Disease Control
- Cleans Driveways, Walk and Patio

The Garden Genie Sprayer makes spraying lawns and gardens as simple as turning on the water. Combines versatility and efficiency with simplicity and ease — you just walk and the Garden Genie does the work. It can fertilize the lawn, flowers, shrubs and trees quickly and safely. It pre-mixes plant food solutions and covers a wide area. Also used for safe, easy and effective control of destructive insects and plant diseases. The sprayer works in front of you, keeping unpleasant insecticide spray away from you; sprayer also tilts back and gets those garden pests up in bushes and trees. A single jugful gives 60 gallons of solution—plant food or insecticide. Features fingertip control for switching from wide-angle high-pitched spray for fertilizing and pest control, to powerful, ground-sweeping jet for cleaning walks, driveway, patio, even the family car. Lightweight, sturdily constructed, on wheels for easy maneuverability. Shpg. wt., 9 lbs.

13 N 6701W

5.95

ELECTRIC CULTIVATOR ATTACHMENT

- Attaches to any 1/4", 3/8" or 1/2" Electric Drill
- Weeds and Tills Soil Easily
- Digs Furrows and Plots Quickly

10⁸⁸



Gardening can be fun with this electric cultivator attachment. Just attach it to any 1/4", 3/8" or 1/2" electric drill and you can weed, till or dig. Six tiller blades are of long-lasting spring steel. Interchangeable handle for right or left-handers. Powerful gear reduction. Absolutely safe. Lightweight, it saves time and energy. Shpg. wt., 7 lbs

13 N 7110

10.88

KING-SIZE STEEL "STOR-SHED"



69⁹⁵

144 Cubic Feet

- Weatherproof, Fireproof, Rustproof
- Room Enough for Your Garden and Lawn Equipment and Tools Too!

Sturdy all-steel utility storage shed holds everything. Completely weatherproofed. Sloped roof with rain gutter. All-steel floor. Locks securely, safety handle prevents "lock-ins". Pegboard for tools. Shed has prime coat of green paint, white doors. Ventilated for air circulation. All complete with hardware, steel floor pegboards, shelf and instructions for assembly. Shipped F.O.B. Altoona, Pa. warehouse. No C.O.D.

13 N 6805WXY 6x6x4'D. wt., 220 lbs. 69.95

13 N 6806WXY 6x6x6'D. wt., 275 lbs. 93.30

100 Lafayette Cat. No. 653

"SHOP KING" HEDGE TRIMMER

6⁹⁹

● 14" BLADE



Converts any 1/4" drill into an easily handled hedge trimmer. Cuts, trims and shapes hedges and shrubbery. Extra long 14" blade of hardened tool steel. Keen edges for fast shearing action. Steel drive gear—permanently lubricated. Long, comfortable handle. Locks in any of 10 different positions. Light weight—compact. Shpg. wt., 3 lbs.

13 N 5015

6.99

ELECTRA-SPRAY



- Foolproof Spray Painting
- Includes New Viscometer


7⁴⁶

Sprays every kind of sprayable paint or liquid—adjustable, jeweled nozzle provides fine, medium or coarse spray. Completely rust-proof construction. Brass and stainless steel parts. High impact plastic housing. 22 ounce interchangeable mason-type jar. Electromagnetic motor never needs oiling or adjustment. Comfortable pistol grip handle with self-releasing trigger switch. The new VISCOMETER insures perfect paint consistency—regardless of brand—every time. Complete with 8 ft. heavy duty cord, 22 ounce jar, viscometer, wrench and instructions. For 115 V.A.C. only. Shpg. wt., 5 lbs.

13 N 3712

7.46

"STOR-ALL" LAWN LOCKER



18⁹⁵

- For Toys, Lawn & Pool Equipment, etc.

Sturdy steel construction, steel floor. Roof folds back for easy access, doors have spring latch. 24 cu. ft. of storage space. Finished in gloss green. Overall 4"Wx2'Dx3'H. With instructions for easy assembly. Shpg. wt., 60 lbs.

13 N 6807WX

18.95

RAM 1/4 HORSE POWER ELECTRIC HEDGE TRIMMER

24⁰³



- 14" Tempered Steel Blade
 - 1800 Cutting Strokes Per Minute
- A full 1/4 horsepower hedge trimmer ideal for straight or angle shrub trimming. A 14-inch tempered steel blade with "variation" design delivers 1800 cutting strokes per minute. Handle is adjustable for right or left hand use. Mirror finish housing contains a powerful, air-cooled 115V AC-DC stall-proof motor. Complete with heavy-duty 50-foot 3-conductor cord. Shpg. wt., 10 lbs.


13 N 7112

Net 24.03

SUBMERSIBLE PUMP

- Will Not Corrode or Rust
- Hermetically Sealed Motor
- For Circulating and Dispensing Water

12⁷⁵



It's the all-new Delron aluminum pump for underwater use. Guaranteed not to corrode or rust; hermetically sealed motor. Circulates and dispenses water and mild acid solutions for use in fountains, beverage dispensers, aquariums, photo developing, air conditioning, etc. Gallons per hour delivery: 240 @ 1 ft.; 180 @ 3 ft.; 125 @ 5 ft.; shut off @ 12 ft. Outlet 3/4"; inlet 1/2" pipe O.D.; height 4 1/2"; depth 4 1/4". 6 ft. safety cord. 115 V, 60 cy, AC, 49 watts load; 67 amps load. Shpg. wt., 3 1/4 lbs.

13 N 8901

Net 12.75

WATERFALL KIT



Enchanting waterfall of cascading water constantly recirculated by electric pump. Gallons per hour delivery: 180 @ 1 ft., 140 @ 3 ft.; 100 @ 5 ft.; shut off @ 10 ft. Outlet 3/4"; inlet 1/2" pipe O. D. Load: amps 65; watts 43. No concrete needed; complete with instructions. Kit consists of pump, 8-ft. plastic hose, 7-ft. sealing poly, pump filter. Shpg. wt., 4 lbs.

13 N 8902

Net 15.88

Newark, N. J. 24 Central Avenue

LAFAYETTE Binoculars and Scopes



21⁹⁵

- All Lenses Are Coated!
- Sealed Against Dust & Moisture

Precise design, quality material and expert workmanship. All center focus; adjustable right eye-piece. Leather case, neckstraps included. Imported.

7x35 Popular, versatile, all-purpose binoculars.

99 N 7018 Shpg. wt., 3 lbs. Net 21.95*

7x50 Navy style night glasses. Favored for marine use.

99 N 7016 Shpg. wt., 3½ lbs. Net 26.75*

20x50 King of the long range.

99 N 7020 Shpg. wt., 4½ lbs. Net 29.95*

*Add 10% F.E.T.



29⁹⁵

- Wide angle view
- Fully adjustable

A multi-purpose 7x35 mm binocular which is especially useful in field studies. Wide angle view allows brilliant and close-up views of sporting events without cutting the image as regular narrow angle binoculars do. Field of view at 1000 yards. is 525 feet! Center focus and right eye adjustment insures perfect focus. All optics are coated. Lined leather case provides protection when not in use. Imported.

99 N 7019 Net 29.95*

*Add 10% F.E.T.



41⁹⁵

TRU-ZOOM™


- Not a "Vari-Power," One Control Zooms both barrels! • Center Focus, Adjustable Right Eyepiece, plus Single Synchronous Zoom Control!

Sight in subject at 7 power—then Zoom up to 12 power (or any four in between) for closeup viewing power. 40 mm objective lenses are hard coated achromats. Field of view is 290 feet at 1000 yards at 12 power (5.5"). Prisms in shock-resistant mounts. Lightweight alloy frame and body. Includes lined hard leather case and straps. Shpg. wt., 5 lbs. Imported.

99 N 7108 Net 41.95*

*Add 10% F.E.T.

ZOOM SPOTTING SCOPE



39⁹⁵

- Any Power from 15X to 30X

Any power from 15X to 30X! Ideal for any "Spotting" Need. Pan-head, elevator tripod mount included. Perfect all round scope. Powerful, small lightweight, brilliant viewing. All aluminum and chromed brass. Imported. Shpg. wt., 5 lbs.

99 N 7101

39.95

10X30mm TELESCOPE with TRIPOD



6⁵⁰

- Full 10 Power
- Portable-Compact-Lightweight

A 10 power, 30mm internal (front) focus telescope that is compact, lightweight and portable—ideal for taking it everywhere you go. Features coated achromatic lenses. Has built-in camera tripod socket. Complete with tripod with rubber-tipped legs that prevent scratching. Imported.

99 N 7071 Shpg. wt., 2 lbs. Net 6.50

30X, 60mm SPOTTING SCOPE



16⁹⁵

The perfect companion for shooting, hunting and nature fans. Field of view is 85 feet at 1000 yds.! High relative brilliance due to 60mm objective lens. All optics are coated. Equipped with a 11½" tripod and zippered leather carrying case. Exceptionally small and light. Shpg. wt., 3 lbs. Imported.

99 N 7015

Net 16.95

4X RIFLESCOPE

- Lightweight—only 6½ ozs.
- Hard Coated Lenses
- Internal Adjustments
- Cross Hair Reticule

Popular, all-around scope for the small game hunter. Bright field, approx. 30 feet at 100 yards. Eye relief distance from 3½ to 4½ inches. Eyepiece diameter, 1" tube diameter ¾". Hard coated, achromatic lenses reduce glare. Internal windage and elevation adjustments for positive "zero-in." Fine, cross hair reticule pinpoints target. Featherweight, weather-resistant, precision built. Easy, fast installation with all .22's with grooved receivers, some air rifles. Imported. Shpg. wt., 1 lb.

99 N 7160

Net 5.88



5⁸⁸

MARINE COMPASS

only 2⁵⁹

Entirely non-magnetic and corrosion resistant. Direct-reading 360° dial. All cardinal points are over-sized. Compass is easily removed from gimbal for safe keeping. May be mounted as a permanent binnacle or used as a portable unit. Dimensions are 4½x4½x3¾". Shpg. wt., 1½ lbs. Imported.

99 N 9009

Net 2.59



NEW! PEDOMETER

Shows You How Far You Walk!

Do you walk a lot? Want to know how far? This easy to use pedometer is the answer. A precision instrument, no larger than a wristwatch, accurately registers up to 24 miles. Easily reset. Complete with ankle strap and instructions. Weighs 2½ oz. Made in West Germany. Shpg. wt., 8 oz.

12 N 5100

Net 4.49

4⁴⁹



"TINY" MINIATURE IMPROVED HOIST

With just one hand, plus an extra 15 oz., you can lift up to 2000 lbs. The unique "Tiny" hoist weighs only 15 oz., is small enough to fit in your pocket, yet is so strong that you can lift up to one ton with it. Ideal for anyone who does heavy lifting—in home, factory, farm, etc. Of highgrade aluminum with steel axles, prelubricated for life. Two lifting slings with heavy steel welded steel rings. With 100-ft. Nylon cable, 7-1 ratio, 2,000 lbs. test. Carrying bag; instructions. Shpg. wt., 2 lbs.

13 N 1901


Net 6.99

6⁹⁹



When Ordering Always Use Lafayette Stock Numbers

LAFAYETTE Engine Divided Slide Rules



NEW! LAFAYETTE® VECTORLOG™ SLIDE RULE

The Slide Rule for Communications Engineers and Physicists

- Laminated Bamboo Construction • P, P', and Q Scales—For Direct Vector Addition • Hyperbolic Sine and Tangent Scales • Two Sine Scales—One Marked in Degrees, One Marked in Radians • 5 Log Log Scales Plus a Voltage DB Scale • Complete with Belt Carrying Loop and Leather Case

The Lafayette VECTORLOG Slide Rule provides a new concept in scientific calculation, incorporating scales and arrangement designed for quick-easy-manipulation. Twenty-seven (27) scales incorporate the many problems encountered in Electrical Engineering and Physics. The unique P, P', and Q scales allow direct right angle vector addition. No longer are several settings required to obtain right angle vector sums—these scales work in the same manner as the C and D for multiplication. The two Hyperbolic Sine and one Hyperbolic Tangent Scale, the voltage db scale, and the five Log Log scales, provide maximum coverage of these dynamic fields. VECTORLOG is the result of extensive tests for ease of manipulation. Several of these features are: C and D scales on both the front and back of the rule; Sine scales in both degrees and radians, removing the necessity of bothersome conversion of units; A problem-tested location of scales; and adjustment screws to allow variable tension on the slide. Scales include: (FRONT) TR-1, TR-2, P', P, Q, ST, S-1, S-0, C, D, LLO1, LLO2, LLO3, LL1'; (REAR) Sh-1, Sh-2, DF, A, B, CI, CF, Th, C, D, LL3, LL2, db. With instruction book, leather carrying case, and belt carrying loop. Imported.

99 N 7102 Shpg. wt., 1½ lbs. Net 16.88

DELUXE LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE

- 25 Scales with 8 Log Log Scales
- Extended Range Avoids "Going Off Scale"
- Extra P Scale Simplifies Computations
- Two Color Scales

10" log log dupli decimal trigonometric slide rule contains 25 scales including 8 Log Log Scales. Troublesome end-for-end resetting is eliminated by extensions of C and D scales. Twin set of Log Log scales run from 1.001 to 100,000 and .999 to .00001, enlarging the scale by one scale length each compared with ordinary log log slide rules. Extra features include P scale which enables direct "readout" of cosine value. Scales include LLO1, LLO2, LL03, DF, CF, CIF, CI, C, D, LL3, LL2, LL1, LLO0, L K, A, B, S, ST, T, C, D, D1, P, and LLO. With instruction book, saddle leather case. Overall length is 14". Imported.

99 N 7055 Shpg. wt., 1½ lbs. Net 15.95

NEW! DECIMA-DYNE™ SLIDE RULE

• A Dynamic Reactance Slide Rule

- Automatic TT Multiplication on DF Scale
- Continuous Resonant Frequency Scale—
- Direct Power Factor Read-out
- Simplifies and Speeds Up CRL Calculations

Specially designed to speed up calculations for radio and electrical communication engineering, for decibel, inductive reactance, capacitive reactance, resonance frequency, surge impedance, etc. Feature scales include: DB—for computation of electric communication circuit; DF and CF—same as D and C scales, except that they are "folded" at π ; Xc—for computation of capacitive reactance; XL—for computation of inductive reactance; F₁ and F₂—for calculating resonance frequency. The 17 scales are: DB, DF, CF, CIF, CI, C, D, A, XC, XL, K, KI, S, T, F₁, F₂, DI. With instruction book, leather carrying case, belt carrying loop. Imported. Shpg. wt., 1 lb.

99 N 7128 Net 13.95

DECIMA-LOG™ DELUXE 5" LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE

- P Scale (Pythagorean) permits direct "readout" of Cosine Values
- 24 Scales including 8 Log Log Scales

A pocket version of our 10" Log Log Dupli Decimal Trigonometric slide rule. Contains all the scales of the 10" rule except the "ST" scale. Two color scales—positioned for ease in use and rapid calculations. "C" and "D" scales on both sides of the rule. "P" scale for direct cursor line reading of cosines of angles. Scales—front face: LL1, LL2, LL3, DF, CF, CIF, CI, C, D, LL3, LL2, LL1. Back face: LLO, L K, A, B, S, T, C, D, DI, LLO. Engine divided rule of laminated, non-hygroscopic bamboo. Complete with instruction book and leather case with pocket clip. Imported.

99 N 7099 Shpg. wt., 8 oz. Net 6.88

Using The Slide Rule In Electronic Technology



USING THE SLIDE RULE IN ELECTRONIC TECHNOLOGY by Charles Alvarez is written for electronic students, both beginners and advanced. It can also serve as auxiliary text in math theory. All scales are discussed separately with detailed examples, graded in difficulty to develop speed and accuracy in use of the slide rule. 120 pp. 5½x8½ paperback. 10 N 1162 Shpg. wt., 8 oz. Net 2.45




MAGNA-SIGHTER® 3-D BINOCULAR MAGNIFIER

- Leaves Hands Free
- Reduces Eyestrain
- 3-Dimensional!

A precision optical instrument enabling anyone to do very close work and see it clearly in 3 dimensions. Adjusts to any head size comfortably. No moving parts to replace. Ideal for hobbyists, repairmen, inspectors and technicians. Available in 4 sizes. Shpg. wt., ¾ lb.

15 N 2001 1.75X, 14" Working Distance	Net 7.88
15 N 2002 2.25X, 10" Working Distance	Net 7.88
15 N 2003 2.75X, 8" Working Distance	Net 7.88
15 N 2004 3.5X, 4" Working Distance	Net 9.38



Graphos

"COLLEGE" SET


- Simple As Using A Pencil
- Professional Results

A complete college assortment for ruling, technical drawing, and sketching. Drawing ink flows freely and uniformly—producing a well covered and sharply defined line. Lines of over 1000 yards can be accurately drawn with one filling of the pen. No smudges or blots! Set includes pen, black ink cartridge, 6 assorted nibs, and instructions. Housed in a plastic case. Shpg. wt., 8 oz. Net 5.98

LAFAYETTE Drafting & Drawing Essentials

PROFESSIONAL GIANT BOW

3⁵⁰



- 6" Size with Center Wheel Adjustment
- Finely Balanced—Professional Type

Professional quality utility set in a fitted, velvet lined case. Made in Western Germany of nickel plated brass. 6" giant bow has preferred center wheel adjustment. Makes circles from 1/8" to over 10" in diameter. Set includes 6" giant bow, interchangeable pen and pencil parts, extra needle for using bow as divider, handle for use with pen and pencil parts, lead, lead box and repair parts. Shpg. wt., 1 lb. Imported.

Net 3.50

SUPER DRAWING KIT

7⁹⁵



Contains all the necessary equipment for drafting, mechanical drawing, designing. Sturdy accurate components. Includes — 18x24" drawing board, 24" T square, 10" 30/60 triangle, 8" 45° triangle, french curve, 12" triangular rule, 6" 180° protractor, 4 pencils, pencil pointer, erasing shield, thumb tacks, and art gum.

Net 7.95

ACRYLIC T SQUARE



WITH ADJUSTABLE PROTRACTOR HEAD 2¹⁰


Adjustable protractor head clearly marked to 180°—easily set and fastened. Transparent arm gives clear full view of subject matter. All plastic—light weight. Adapted for ink ruling. Head fits snugly against board. Shpg. wt., 1/2 lb.

15 N 1426—18" long
15 N 1427—24" long

Net 2.10
Net 2.35

UTILITY DRAFTING SET

3³⁵




- Exceptional Value

Made in Germany of hard rolled, nickel plated brass. All instruments are nested in a fitted, velvet lined case. Contains three side wheel 3/4" bow instruments—on a divider, one a pencil and one a pen. All have reversible needle point. 5/4" compass with pen and pencil parts—and lengthening bar. 5/4" divider with straightening device. 5" ruling pen. Extra handle for use with pen and pencil parts. Capsule with extra leads. Perfect for schools, labs, industrials. Shpg. wt., 1 lb. Imported.

Net 3.35

TECHNICAL DRAFTING SET

6⁸⁵




- Center Wheel Adjustment
- Professional Quality
- Made in Germany of nickel plated brass

Contains 6 1/4" self-centering compass, one leg knuckle joint with divider, pencil, pen parts and lengthening bar; 6 1/4" self-centering divider; spring bow divider 4 1/4", center wheel adjustment with interchangeable needle points; spring bow pencil and spring bow pen, both 4 1/4" with center wheel adjustment and interchangeable needle point; two 5 3/4" ruling pens; extra handle for pen and pencil parts; adjustment tool; lead-case and leads; and spare parts kit, all in velvet lined snap closing case. Imported

Net 6.85

draftette PORTABLE DRAFTING MACHINE



- Precision Instrument

Sketch, design, draw diagrams and schematics like a professional. The new Draftette gives you all the advantages of a portable drafting instrument. One piece aluminum scale features, 2 graduations—top in 16ths and bottom in eighths and fourths, a 360° protractor mounted on a 16x21" drawing board. Draftette can be removed from its board and folded like a jack-knife, to be stored. It is easily attached, to any stiff-backed pad of paper without screws. Finest satin black anodized aluminum construction. Assembled and ready for use as a T square, triangle or protractor. Perfect for students. Clear vinyl plastic carrying case.

15 N 7401 Shpg. wt., 2 1/2 lbs. Net 13.98
Draftette =12-B Senior with 6x9" scale, 360° protractor on 20x26" drafting board. 15 N 7403 Shpg. wt., 6 lbs. Net 19.95
Draftette =12 Senior less board. 15 N 7404 Shpg. wt., 2 lbs. Net 15.30


LETTERING GUIDE SET



Made of transparent plastic. Simple to use with either sharp pencil or ink. Each has complete alphabet, all numbers plus commonly used signs. Most letters formed with one operation. Set consists of six guides. Sizes 1/8, 1/4, 3/8, 1/2, 5/8, and 3/4". Shpg. wt., 1/2 lb.

15 N 1432—Complete Set Net 6.79

HARD MAPLE PANTOGRAPH




- Enlarges • Reproduces!

A 21" adjustable pantograph with 21 different ratios from 1 1/4 to 8. Enlarges, reduces or reproduces drawings, etc. Most rapid, accurate means of reducing or enlarging to scale. Lacquered highly finished bars are 21" long and 3/4" wide. Heavy ball bearing standard. Chrome plated hardware, ratio thumb screws and nuts. Complete with lead, accessories and detailed instructions. Shpg. wt., 2 lbs.

15 N 5602 Net 3.75

"draftette" SKETCH KIT



A completely portable drafting drawing machine permanently mounted in a Vinyl binder (self-locking). A weather protected unit, it can be used for sketching, designing, drawing, and drafting. Great for traveling. Contains a precision portable drafting instrument with a 4x6" scale, 180 degree protractor, pad of 50 sheets, drawing-tracing paper 8 1/2x11", all in one compact binder. Does not require tape or tacks to hold paper in place for use. Only 9 1/2x13x1".

15 N 7402 Net 7.80

NEW RUBBER TYPE SET

- Easily Changed • Simple to Operate

An easy to use printing kit that comes complete with 14-point (1/5") rubber type, 22 numerals, over 100 capital letters, punctuation marks, ink pad and tweezers. Print anything from one to four lines long. Special "base-lock" type for perfect alignment. Neat, clean, and clear results. Many printing uses in the home or business. Instructions included. Shpg. wt., 1 1/2 lbs.


15 N 6001

Net 2.25

Extra set of (1/5") rubber type, 22 numerals, over 100 capital letters, punctuation marks.

15 N 6000

Net 1.49



2²⁵

LAFAYETTE Automatic Electric Eye Zoom Movie Camera



CAMERA ONLY
59⁹⁵

- Fast f/1.9 Zoom Lens
- Fully Automatic Exposure

- Viewfinder Zooms with Lens
- Trigger Action Pistol Grip

Precision-made 8mm movie camera has built-in electric eye which automatically sets correct exposure for any film (color or black and white) from ASA 10 to ASA 40. Fast, f/1.9 lens zooms from wide-angle, through normal, to telephoto. Big picture-window viewfinder gives sharp, clear field of view... zooms with lens if light is not enough for a good movie, signal in viewfinder tells you. Other outstanding camera features include manual exposure control, single-frame exposure (for animated titles, etc.), film counter, cable release socket, sturdy pistol-grip handle for easy trigger action, and fast drop-in spool loading. Shpg. wt., 5 lbs. Imported.

99 N 7179L

Net 59.95

ZOOM MOVIE OUTFIT



A complete zoom movie outfit with matched components to assure success in taking and showing home movies. The Camera is Lafayette's Zoom f1.9 Auto 8, "Ultra" 500 projector, 30"x40" folding screen, 500 watt Hi-Lite movie gun, 2 sets of 400' reels & cans, zoom camera case. Shpg. wt., 40 lbs.

15-9003WXM

Net 119.95



Minolta Zoom 8 **119⁹⁵**

As Little As
\$6.50 Monthly

- CdS Electric Eye Automatic Exposure
- 10-Element f/1.8 Rokkor Lens
- Micromotor Electric Drive

A fine, battery powered 8mm camera featuring a sensitive cadmium sulfide light meter that automatically sets the right exposure for any film (ASA 10-400), color or black and white. Just sight and shoot... that's all. Zoom 8 does the rest. A warning signal shows in the viewfinder in case of insufficient light for perfect exposures. Rokkor f/1.8 lens zooms from wide-angle to telephoto (10-30mm) with the touch of a finger. Filming Speeds: 12, 16 and 24 fps. High-efficiency micro-motor is powered by four inexpensive penlight batteries (included). Has manual control for special effects, single lens reflex viewfinder for through-the-lens focusing and viewing, built-in battery level indicator. Spool loading. Shpg. wt., 4 lbs. Imported.

15 N 3401L

Net 119.95

32 N 4802 Repl. Penlight Batteries (4 req.)

Net ea. .13

15 N 3405L Minolta Zoom 8 Case, Shpg. wt., 2 lbs.

Net 12.95

15 N 3407 Remote Control Switch and Cord, Shpg. wt., 4 oz.

Net 3.98

YASHICA "UL" Deluxe Power Zoom 8



- Automatic Film Loading
- Built-in Type "A" Filter
- CdS Photo Cell Electric Eye
- f/1.8 Electro-Zoom Lens

Now, your film finds its own way to trouble-free loading! A new patented mechanism now takes the frustrating work out of film threading. Simply place film on feed spindle, insert leader into film gate, engage automatic mechanism and the film threads itself. Fully coupled automatic CdS exposure system computes and sets diaphragm for perfect color or black & white film. Completely driven by a tiny yet powerful electric battery-operated motor with Power zoom control. Focuses from 3.5 feet to infinity. Zoom reflex system viewfinder with split-image focusing plus dioptically adjustable eyepiece. Has shutter release safety lock, remote control, battery tester, quick access plastic battery compartment, film rewind and film counter, manual exposure possible, cable release socket. Comes complete with batteries and pistol grip. Shpg. wt., 6 lbs. Imported.

149⁹⁵

15 N 3603L

Net 149.95

32 N 4802 Extra penlight batteries (4 req.)

Net ea. .13

Deluxe Zoom Movie Case



- 10 1/2 x 9 x 3 1/2"
- Black Vinyl Covering
- Aluminum Trim

6⁹⁵

Takes all 8mm zoom movie cameras (including those with pistol grip attached) plus supply of extra film. Case is covered with attractive black vinyl and is reinforced with aluminum trim. Has handy "Presto" lock. Overall Size: 10 1/2 W x 9 H x 3 1/2" D. Shpg. wt., 1 1/2 lbs.

15 N 1602

Net 6.95

SPORTPOD



2⁹⁸

The Sportpod is a 3-section leg with tripod screw on top, protected with a removable cap. Offers rigid camera support with least possible weight and bulk. Supplied with suspension strap. Total extended length is 58"; telescopes to 21 1/2". Sections measure 7/8", 3/4" and 3/8" in diameter. Shpg. wt., 1 1/2 lbs.

15 N 3601

Net 2.98



DIAL-A-BOUNCE MOVIE LIGHT

with camera
mounting Bracket

7⁴⁹

A versatile lamp that is a must for indoor movie making. Features long life sealed beam super-flood lamp. Calibrated knob on handle adjusts lamp to desired angle up or down for indirect "bounce" or direct lighting. Telescoping handle fits all movie cameras; keeps light from affecting electric eye when in extended position. Air vented shield cools unit, protects lamp from shock. Camera bracket mounts left or right for user convenience. Average lamp life 8 hours. UL and CSA approved. Shpg. wt., 4 lbs.

15 N 2801

Net 7.49


LAFAYETTE Triple Turret f/1.8 Electric Eye Movie Camera

- Automatic, Cross-Coupled Electric Eye
- 3 Quick Change, Turret-Mounted f/1.8 Lens
- Built-in "A" Conversion and UV Haze Filters
- Pistol Grip with Trigger Release
- "Combo-View" Finder for Normal, Wide-Angle and Telephoto Shooting

You get perfectly exposed movies automatically simply by aligning the needle in the viewfinder. Film speed selector dial adjusts for speeds of ASA 10-40. A quick twist of the turret dials the effect you want; from Normal to Wide-angle or Telephoto for thrilling close ups of distant subjects. The fast f/1.8, fixed-focus lenses are color-corrected and coated. Etched optical view finder shows exact field for each lens. Full-sized pistol grip with trigger release provides easy one hand operation. Economical drop-in spool loading. Includes instructions and pistol grip handle. Imported.

99 N 7178L Shpg. wt., 5 lbs.
15 N 1601 Holster case

Net 29.95
Net 2.95



CAMERA ONLY
29⁹⁵


Everything you need for movie-making and showing fun. No need to "shop" for unmatched equipment. No need to pay more. You get all this: triple turret—f/1.8 Electric Eye Movie Camera, camera case, 500 watt projector, 30"x40" screen, 500 watt Hi-lite movie gun, two 400' reels with storage cans. Unbeatable for foolproof shooting and showing of indoor and outdoor movies. Shpg. wt., 30 lbs.

15 N 9002WXM

Net 79.95

8mm Projector Scope

- Previews Films
- Fits Most 8mm Projectors



The projectionists friend . . . The HPI Projector-Scope attachment lets you preview films as soon as you get them. Can be attached easily to most 8mm projectors by simply removing the original lens. Large 4 5/8 x 3 1/2" screen with a 6-element lens lets you see or show sharp movies without darkening room or setting up a screen. Edit films right on the projector. Can not be used with Basken and Kodak Brownie models A10 and A15. Includes handy frame marker for easier editing. Shpg. wt., 1 lb.

15 N 3427

Net 5.33

Vernon 18/28 Automatic 8mm Movie Camera

An outstanding value in automatic 8mm movie cameras. Completely new design of rugged die-cast construction houses a fully automatic camera. Fast, sharp f/1.8 13mm lens does not require focusing. Built-in automatic electric eye adjusts lens opening from f/1.8 to f/16 according to light conditions. Adjustable for film speeds ASA 10 to 50. Perfect shots every time. Lens opening visible on side window. No rewinding causing you to miss precious "once-in-a-life-time" shots. All-electric drive runs on 4 inexpensive penlight cells. Shoots up to 20 rolls without a battery change. Run, lock or continuous run release trigger lets you get into your own movies. "And best of all, a remote control (10-ft cable) is available at extra cost . . . It lets you obtain true candid, natural shots of children and wild life. Imported.

15 N 3402L Shpg. wt., 5 lbs.

Remote control Switch and Cable

Net 29.95


15 N 3403

Penlight cells (4 req.)

Net 3.98

32 N 4802

Net ea. .13



29⁹⁵

- Fully Automatic Electric Eye
- Electric Drive
- No Winding
- Sharp f/1.8 Lens
- Built-in Handle
- Remote Control*

New! DeJURETTE Slimline Automatic Movie Camera

This simple-to-operate, fully-automatic movie camera is so small that you can carry it anywhere, yet so versatile that it compares with units costing much more. Specifications: Completely automatic exposure, ASA range 10-400; Fast Chromtar f/1.8 13mm prime lens; Built-in conversion (A) filter; remote control operation. Comes complete with carrying case, strap and mercury cell for CdS meter. Dimensions: 6x3 3/4 x 1 1/4". Shpg. wt., 4 lbs. Imported.

15 N 5201L

Net 49.98

Remote control switch and cable


Net 3.98

15 N 3403

Penlight cells (2 req.)

32 N 4802

Net ea. .13



- Electric Drive
- Exposure Indicator
- Built-in Conversion Filter

REVIEWER-EDITOR 1488

- Single Sprocket Drive
- 3x2 1/4" Viewing Screen
- 400-Ft. Film Capacity
- Ultra Compact—Only 7x5x3 1/2"

Action viewer with prismatic shutter magnifies picture more than 300 times on 3x2 1/4" screen. Features slip-in film loading that eliminates threading. Single sprocket drive to assure no skipping, flickering of film or wear. Features automatic framing and focusing, fold-away built-type 1-step splicer, folding 400' capacity rewinds and a convenient frame marker. Complete with a supply of Mylar splice tape. Shpg. wt., 4 lbs.

15 N 3620

Net 14.88

MANSFIELD "ULTRA" 8mm MOVIE PROJECTOR


53⁹⁵ Only \$5.00 monthly

- Fast, Easy Loading
- Forward, Still & Reverse
- Self-Contained Carrying Case

The "Ultra" 8 mm projector features several unusual conveniences to uncomplicate movie showing. Has swing-out gate for fast threading. Forward, Still and Reverse positions. Brilliant, new DFA lamp gives uniformly bright picture. Cinepar f/1.6 lens. Self-contained carrying case. Shpg. wt., 10 lbs.

15 N 8201WX

Net 53.95




De Jur "DUO-VISTA" 8mm Projector 129⁹⁵

- Brilliant f/1.2 15-25 zoom lens
- 2 slow-motion speeds
- Built in Viewing Screen

A new concept in 8mm projection — the UNIMATIC-DRIVE. Eliminates home movie flicker and light fall-off in slow motion. Professional movie quality. Features 8 position controls — forward, reverse, still, off, normal, fast, very slow and slow speeds — built-in viewing screen (or regular projection at the twist of a knob), automatic reel to reel threading, sharp f/1.2 zoom lens with 15-25mm range. Separate cooling motor for longer lamp and film life. Positive chain and gear drive. Room light control and film trimmer. Shpg. wt., 20 lbs.

15 N 5202WX \$6.50 Monthly

Net 129.95



Take Advantage of Lafayette's Low Camera Prices

Deluxe Single Lens Reflex 35mm Cameras

KOWA "H" AUTOMATIC SLR



- Fully Automatic Programmed Shutter
- Brilliantly Clear 48 mm f2.8 Lens
- Manual Over-ride
- Trigger Type Film Device

7950

Here is a fully automatic single lens reflex 35mm camera. No need to fuss with F stops, shutter settings or meter readings. Just set the film speed on the easy to read dial, focus and shoot perfect pictures. Everything is automatic. Provides easy focusing, even in dimly lit surroundings. Manual over-ride allows you to set lens and shutter for different exposures. New minimal movement, trigger film advance. 48mm coated, prominent-type lens gives excellent resolution and color reproduction. 8 shutter speeds to 1/300 sec. with case. M and X flash synch. Shpg. wt., 3 lbs. Imported
 15 N 6301L \$5 monthly Net 79.50

MIRANDA "F" 35 MM SLR



- Speed to 1/1000th Second
- Internally Coupled f/1.9 Lens

15995

A deluxe 35 mm single lens reflex camera which features a sharp, fast f/1.9 lens internally coupled and interchangeable with every other lens in the extensive Miranda system, plus lens of most other 35's. Pentaprism is interchangeable too with other types of finders and the new brilliant viewfinder brings out details even in the dimmest light. Shutter speed ranges from 1/1000 to 1 sec. Multigrad center spot permits precise focusing to as close as 17". The "F" also has instant return mirror, depth-of-field preview button, single-action rapid advance lever and many other features. Complete with case. Shpg. wt., 5 lbs. Imported.
 15 N 3704L \$8 monthly Net 159.95

MIRANDA AUTOMEX II



New Low Price 19995

- Fully Automated 35mm SLR
- Focal Plane Shutter-Speeds to 1/1000th
- 50mm Cross Coupled f1.9 Lens

The new automex II is an automated single lens reflex featuring increased range selenium cell exposure meter, with ASA index of 25-1000, coupled to shutter speed dial and diaphragm selector lever. The lens, diaphragm and meter are operated by moving one lever. Viewfinder is of the groundglass type, with split image rangefinder in the center to insure needlesharp shots. Choice of manual or automatic use with lens mounted switch. Rubberized cloth focal plane shutter gives quick, silent operation, with speeds of 1 to 1/1000 sec. Comes with case. 5 lbs. 15 N 3702L Imported Net 199.95

KALIMAR CdS-430 EXPOSURE METER



- ON/OFF Push-Button to Conserve Battery
- ASA Scale 6 to 12,000 (0IN Scale 9-42)
- f/1 to f/32 Lens Aperture Scale

1188

An extremely sensitive Cadmium Sulfide photoelectric exposure meter. Perfect for still or movie photography either indoors or outdoors. Designed to be used either as a hand meter or can be mounted to the accessory shoe of still cameras. Has EV indicator for Polaroid and other cameras equipped with LVS numbers. Uses readily obtainable mercury battery. Measures reflected or incident light; supplied with incident light attachment. Lightweight and very compact. Measures only 1x1 1/4x1 1/2". Complete with mercury battery and leather carrying case. Shpg. wt., 1/2 lb. Imported.
 15 N 4920 Net 11.88

BOOSTER EXPOSURE METER



645
 WITH BOOSTER

- Includes booster, leather cases, neck cord
- Stills or Movies
- ASA Scale—LVS Scale

Extremely versatile — extremely simple. Highly legible direct reading dial. Speeds from 4 sec. to 1/1000 sec. Lens aperture settings from f:1 to f:32. ASA scale 6 to 800. LVS scale 1 to 18. Cine scale 8, 16, 24 and 32 frames per second. Booster cell makes possible readings at extremely low light levels. Small-rugged-lightweight. Includes booster cell, leather cases, neck cord and instructions. Shpg. wt., 1 lb. Imported.
 99 N 7033 Net 6.45

NEW-COMBO-GRIP & FLASH BRACKET

- Firm Grip for Any Camera
- Provides Mount for Accessories
- Pistol Quick Use of Camera



This new combination grip and utility bracket is better than a third hand. Molded pistol grip provides solid grip for any camera. Particularly useful for SLR's and twin lens reflex. Accessory bracket provides mount for flash guns, meters and strobe lights. Affords ultra safe carry for valuable cameras and accessories. Imported.
 99 N 7162 Shpg. wt., 1 lb. Net 2.98

REMOTE SHUTTER RELEASE



• 20 Ft. Long

Designed to permit the camera to be used from distances up to 20 feet from the photographer. Simplifies nature shots. Excellent for candid shots of children. Has a professional rubber bulb. Shpg. wt., 8 ozs.
 15 N 4902L Net 3.98

Front Photo Focus Monocular

AS LOW AS **1495**



ENLARGES THIS TO THIS

MAKES YOUR CAMERA TELEPHOTO
 —Bring Distant Object from 6 to 8 Times Nearer

Take-super-telephoto pictures with your single lens or twin-lens reflex camera. The front focus system is specially made for on-camera operation. There is no need to miss those once-in-a-lifetime shots. Increases focal length of your camera lens 6X, 7X or 8X depending on model selected (i.e. 50mm lens plus 8X monocular equals 400mm telephoto). Rugged, lightweight construction — weight only 7 1/2 ounces; is only 5 inches long. Includes series VI adapter ring and leather case. Shpg. wt., 1 lb. Imported.
 99 N 7072 6x30 mm Net 14.95
 99 N 7073 7x35 mm Net 16.95
 99 N 7074 8x30 mm Net 18.95

LENS SET FOR POLAROID CAMERAS



- Wide Angle and Telephoto Lens
- View Finder for Accurate Composition

An ideal companion to the Polaroid Camera. Telephoto lens increases the focal length of the lens and results in a 3 times magnification. Wide Angle lens provides a 75% increase of subject area. Each lens has a "conversion band scale." Supplied with slip-on ring adapter, special electric-type bracket for viewfinder and flash, filter retaining ring, view finder and genuine leather case with shoulder strap. Shpg. wt., 2 lbs. Imported.
 15 N 4922 For J-66 Net 32.50
 15 N 4923 For 100 Net 32.50

Fine Cameras—For Every Budget

LYNX—5000 35mm



- All-in-one Finder
- Sharp, Super-fast f/1.8 lens
- Shutter Speeds to 1/1000 Sec.
- Two-Stage Cds Meter

79⁸⁸

Set the needle in the finder and SHOOT! To assure you of fine 35mm prints or slides every time the LYNX-5000 combines an easy-to-operate match needle Cds exposure meter with a super-speed f/1.8 lens and a high speed up to 1/1000 sec. shutter. Features a split-image focus rangefinder, sensitive two-stage Cds meter with on-off switch and ASA range 10-800. Viewfinder lets you set perfect exposure without removing eye from finder as you compose and focus. Shpg. wt. 3 lbs. With case. Imported. **15 N 3613L \$7 monthly** **Net 79.88**

MINIMATIC—C AUTO "35"




- Automatic Exposure, ASA 10 to 400
- 45mm YASHINON f/2.8 Lens
- View rangefinder—Automatic Parallax Correction

59⁹⁸

A point-it and shoot-it camera that programs pictures automatically. Will not let you make an error. Automatically compensates for parallax errors. Resets film exposure counter automatically. Has X flash synchronization and self-timer. Single stroke lever-type action advances film, cocks shutter and sets exposure counter. Load it, wind the film, point it and shoot, the camera does everything else. With handsome dark grey case. Shpg. wt. 3 1/2 lbs. Imported. **15 N 3614L \$6 monthly** **Net 59.98**

MIMY "72" AUTOMATIC



- Automatic 35mm Half-Frame!

37⁹⁵

Another point and shoot camera, the MIMY 72 half-frame 35mm returns up to 72 sparkling color slides or B&W prints per load. Although far smaller, slimmer and lighter than ordinary 35mm cameras the MIMY 72 includes automatic electric eye exposure and knurled wheel to advance film, cock shutter and prevent double exposure. Contains universal focus f/2.8 28mm lens; ASA 10-200; bright line viewfinder with parallax compensation mark; bulb and flash synchronous terminal, uses standard 20 or 36 exposure 35mm cartridge. With case. Shpg. wt., 3 lbs. **15 N 3615L Imported. \$5 monthly Net 37.95**

FOLDING BC FLASH GUN

- Capacitor-Type for Sure Fire Flashes
- Includes: Built-in Bulb Tester, Exposure Guide, Case.
- Weighs only 4 oz.!

2⁹⁹

Efficient 4 1/2" diameter metal reflector folds down for easy carrying, storage. Slip-on shoe with lock fits all cameras with standard accessory clip and PC type fitting. BC power for sure fire and hi-voltage. Features built-in circuit tester, exposure calculator, bulb ejector and coiled cord. Dual socket takes M base, bayonet base and AG bulbs. With plastic carrying case. Imported. Shpg. wt., 1 lb. **15 N 3621 Flash Gun, less battery** **Net 2.99**
32 N 4835 15V Battery For above **Net .81**



TRANSISTORIZED

ELECTRONIC STROBE FLASH

Operates from Batteries and AC

- Lightweight & Compact
- No Power Pack Needed
- Fully Transistorized
- Operates on 4 Economical "Z" Cell Batteries
- Fits any Camera Shoe


19⁹⁵



Now you can have a high-powered transistorized electronic flash that operates from standard AC house-current or 4 economical "Z" cell batteries. Compact and featherweight — no power pack is required. Flash duration of 1/2000 sec. for fast pictures. Recycling time: 6-10 seconds; color temperature: 6000° Kelvin. Guide number dial for F top on back. Complete with AC cord. Less batteries. Shpg. wt., 2 lbs. **99 N 7168 Imported. Net 19.95**
32 N 4802 Batteries for above (4 required). Net ea. .13

DROPFONT "PRO" BAG

A heavy-duty professional bag. Zippered for easy access. Styled for easy hand or over-the-shoulder carrying. Removable, adjustable straps. Chrome plated snap-lock, feet and hardware. Handsome, heavy black simulated cowhide with leather and corduroy lining. Front tripod carrying straps. Measures 13" long x 7" wide and 9 1/2" high. Shpg. wt., 3 lbs. All Imported. **15 N 3413** **Net 9.95**



"PRO" 11 Same as above except measures 11x6 1/4 x 8 3/4". Shpg. wt., 3 lbs. **15 N 3412** **Net 8.80**
SUPER-PRO 16". Same as above measures 16x7 3/4 x 11". Shpg. wt., 4 lbs. **15 N 4924** **Net 13.95**

"PRO" ELEVATOR TRIPOD

- Holds Heaviest Equipment
- Velvet Smooth Panning Action
- Extends to 46 1/2"—Elevator Adds 10"—Closes to 22"

All aluminum construction. Gear drive elevator with positive lock. Large, cushioned pan head fits any camera. Head pans 360°—tilts 180°. Legs lock at any height. Lock and unlock with a half twist. Completely rigid, even when fully extended. Long section construction for maximum stability. Oversize thumb locks and handle for ease of use. Velvet smooth action in all planes of motion. Positive leg stops prevent overspread. Rubber tipped feet for solid footing on any surface. Satin black and aluminum finish—chrome trimmed. Shpg. wt., 4 lbs. Imported. **99 N 7202** **Net 11.95**



PRE-VIEWER 8MM MOVIE VIEWER

Ideal for on-the-spot viewing of 8mm home movies. Lightweight, only 14 oz. Just insert movie film in viewer and turn crank. Eye level viewing lens provides 20X magnification. Built-in illumination using inexpensive night cells. Film winds forward or backward or stills. Accepts standard 50 ft. reel of 8mm movie film. Hi-impact case. Shpg. wt., 1 lb. **15 N 3408** **Net 6.95**
1.5 volt batteries for above ea. **32 N 4802** **Net .13**



DELUXE LENTICULAR SCREEN

- Greater Brilliance
- Durable Vinyl Fabric


11⁸⁸

Specially-designed, optically-correct lenticular screen is free of glare, sheen and hot spots. Amazing sharpness and color rendition. Durable vinyl fabric resists fire and fungus. Sturdy chrome tripod legs. Screen is 40x40". Shpg. wt., 12 lbs. **15 N 5005W** **Net 11.88**



Lafayette Cat., No. 653 107

LAFAYETTE Offers Value—Variety—Versatility



MINOLTA "16 II" SUBMINIATURE CAMERA

29⁹⁵

- Rokkor 3-Element f/2.8 lens
- Automatic Film Advance & Shutter Cocking
- Direct Viewfinder

An extremely easy-to-operate, palm-size camera that you can carry with you always. No need to miss those once-in-a-lifetime shots. Sliding camera in and out of built-in case advances film, clocks shutter, counts exposure and prevents double exposure—all automatically. 6 shutter speeds from 1/30 to 1/500 sec. plus B. Click-stop settings. Internally synchronized for electronic flash and bulb. Takes regular black and white pictures or color slides that fit any 35 mm projector. Direct viewfinder shows picture exactly as it will appear on film. Lens opening from f/2.8 to f/16. Click-stop settings. Complete with case. Shpg. wt., 1 lb. Imported.

15 N 3416L	Net	29.95
MINOLTA 16 II Accessories. Avg. Shpg. wt., 6 oz.		
15 N 3421 Baby BC Flash with Capacitor and Case	Net	4.95
15 N 3422 Bracket for Flash and Tripod Mtg.	Net	1.95
15 N 3423 Aux. Lens Set—2 closeup, 1 distance, 1 Y filter	Net	3.95
15 N 3424 Color Filter Set—1 ea. 1A, 80A, 81B	Net	3.95

FILM FOR "16 II" and 16 Gds—All are 20-exposure magazines. Shpg. wt., 3 oz.		
15 N 3417 Kodak Panatomic X	Net	.98
15 N 3416 Kodak Tri-X	Net	.98
15 N 3419 Kodachrome II	Net	1.25
15 N 3418 Kodak Tri-X	Net	.98



MINOLTA 16 Cds SUBMINIATURE CAMERA


69⁹⁵ \$5 monthly

- Automatic Cds Electric Eye
- Rokkor 25 mm F/2.8 lens
- Just 4½x1½x2"

A compact, completely automatic camera which makes picture taking more enjoyable and virtually foolproof. Sensitive, accurate Cds electric eye sets lens automatically for perfect exposures under different light conditions. Takes 16mm film with speeds of 25-320 ASA. Sharp Rokkor F/2.8 lens has built-in sunshade. 3-way shutter dial sets correct shutter/diaphragm combination for bright or normal light and flash. Also has bright-frame viewfinder with warning signal, rapid film advance, 2-position zone focusing and instant drop-in loading. Only 4½x1½x2". With case. Shpg. wt., 1½ lbs.

15 N 3438 Imported	Net	69.95
MINOLTA 16 Cds ACCESSORIES Av. Shpg. wt., 6 oz.		
15 N 3421 Baby BC Flash with capacitor and case	Net	4.95
15 N 3439 Bracket for Flash and Tripod Mounting	Net	1.95
15 N 3437 Filter Set—2 close-up, 1 Y-48 Yellow Filter	Net	3.49
15 N 3436 Color Filter Set—1 ea. 1A, 80A, 81B	Net	2.49

FILM FOR 16 CDS—See film listing under Model 16 II



ONLY **29⁹⁵**

MINI-"16" COLOR SLIDE PROJECTOR

- For All 16 mm Sub-Miniature Slides
- Projects Brilliant Image
- Includes Deluxe Carry Case


Compact, lightweight projector to match Minolta and other 16 mm sub-miniature cameras. Fold compactly for storage. Sharp 40 mm Rokkor F/2.5 lens projects brilliant images equal in size to a 35 mm slide in a 35 mm projector at the same distance. Can be used on table or tripod. Includes deluxe vinyl carrying case, standard slide carrier and 75 watt projector lamp. For 110-120 volts AC-DC. Shpg. wt. 3½ lbs. Imported.

15 N 3435	Net	29.95
-----------	-----	-------

KODAK FILM with PROCESSING INCLUDED

- Slides Returned Mounted, Ready for Viewing or Showing!
- Convenient, direct-mail "mailers" in every roll
- A full number of Prints guaranteed for Kodacolor and black and white.

After the complete roll has been filmed, put it into the mailer, drop into a mailbox and in a few days your finished films are delivered postpaid to your door. You get 3½" square or 3½x5" giant prints with Kodacolor and Black and White. Should you get less than the full number of prints or printable negatives per roll, you will receive coupons for additional FREE prints. DO NOT MAIL FILM TO LAFAYETTE RADIO.



Factory Fresh in Original Cartons

KODACHROME MOVIE FILM—TYPE II

15 N 2611L	KR459	8mm, 25 ft. Double roll, Daylight	3.15
15 N 2626L	KRA459	8mm, 25 ft. Double roll, "A" Indoor	3.15

KODACHROME 35MM, TYPE II AND X

Stk. No.	Mfr. No.	Description	Net Each
15 N 2627L	KR135-20	35mm, Type II, 20 Exp.	2.80
15 N 2612L	KR-135-36	35mm, Type II, 36 Exp.	4.25
15 N 9004L	KX135-20	35mm, Type X, 20 Exp.	2.99
15 N 9005L	KX135-36	35mm, Type X, 36 Exp.	4.65
15 N 9006L	KX126	Instamatic Cartridge, 20 Exp.	2.95

KODACOLOR-COLOR SNAPSHOTS

Stock No.	Film Size	Description	Net Each
15 N 2616L	C127	127 indoor/outdoor, 12 Exp.	3.40
15 N 2617L	C120	120 indoor/outdoor, 12 Exp.	3.40
15 N 2618L	C620	620 indoor/outdoor, 12 Exp.	3.40
15 N 9007L	CX126	Instamatic cartridge, 12 Exp.	3.69

KODAK BLACK & WHITE ROLL FILM

15 N 9008L	VP-126	Instamatic Cartridge	12 Exp.	1.39
15 N 2621L	VP-127	127 Verichrome Pan	12 Exp.	1.20
15 N 2622L	VP-120	120 Verichrome Pan	12 Exp.	1.20
15 N 2623L	VP-620	620 Verichrome Pan	12 Exp.	1.20
15 N 2624L	PX135-20	35mm, Plus X	20 Exp.	2.35
15 N 2625L	PX135-36	35mm, Plus X	36 Exp.	3.45

New Dynachrome II

COLOR FILM WITH PROCESSING



- Beats the High Cost of Color Film
- Same Fine Pictures
- Processing Included Direct To Your Home

New Dynachrome II film is the newer, faster color film now in demand. Same reversal type, same natural colors, same superb quality. Only the price is different—it's almost like getting the processing free. And the low price includes processing direct to your home

15 N 1808	8mm, 25 ft. Daylite ASA 25	Net 2.49
15 N 1809	8mm, 25 ft. Indoor ASA 40	Net 2.49
15 N 1810	35mm 20 Exp. Daylite ASA 25	Net 2.19
15 N 1811	35mm 36 Exp. Daylite ASA 25	Net 3.11

NEW! DYNAPAN—BLACK & WHITE ROLL FILM

High quality black & white film for all your snap shot requirements. 2 Rolls of fine grain, fast black & white film per pkg.

15 N 1812	120, 2 rolls per pkg.	Net .59
15 N 1813	127, 2 rolls per pkg.	Net .59
15 N 1814	620, 2 rolls per pkg.	Net .59

PHOTOFASH BULBS

BUY IN QUANTITY AND SAVE



Stock No.	Lamp Type	Pkg. Quan.	Per Pkg.	in Lots of 3	Ea. Pkg.
15 N 1001	AG-1	12	1.03		.96
15 N 1002	AG-1B	12	1.20		1.12
15 N 1003	M2	12	1.11		1.04
15 N 1004	M2B	12	1.30		1.20
15 N 4701	M3	12	1.30		1.20
15 N 4702	M3B	12	1.54		1.44
15 N 1005	5	8	1.30		1.20
15 N 1008	5B	8	1.54		1.44

- "My-T-Myte" and "Synchro Sure"
- Photoflash Bulbs
- Standard Sizes—Highest Quality—Pre-Tested

Low Cost Cameras and Projector

Our Lowest Cost 35 mm Camera Kit

- Lens Apertures From F/8 to F/22
- Pre-Focused Lens System
- Produces Sharp Black & White Or Color Pictures

16⁹⁵



Everything you need for perfect black & white or color pictures, plus "Perfect Picture" simplicity in use. There's no focusing or shutter speed to worry about—you simply set the correct lens opening, aim through the view finder and shoot! Equipped with a 50 mm pre-focused F/8 lens with high resolving power to provide sharp, brilliant pictures or slides. Kit includes a compact flash gun with fan-type reflector that lets you take perfect pictures under any light conditions. It features a computer dial for determining correct F stop plus a testlight and bulb ejector. The complete kit includes a handsome carrying case with strap, plus everything you need to take pictures at once. You get the 35 mm camera, a roll of black & white film, flash gun, flash bulbs, 15-volt flash battery, and instruction book. Shpg. wt., 2½ lbs. Imported.

15 N 3440L Complete 35 mm Camera Kit Net 16.95
15 N 1810L 35 mm, 20 exp. color film with processing Net 2.19

LAFAYETTE "BUDGET PRICED" MOVIE CAMERA

- Fast f/1.9 4-element lens
- Electric drive—no winding
- Enclosed optical viewfinder
- No focusing necessary

16⁹⁸



A truly modern, versatile, and inexpensive movie camera. Fast f/1.9 4-element lens captures all the exciting action in brilliant color or black and white. Fixed focus lens never needs adjustment because of a change in the distance between camera and subject. Electric motor drive with built-in standard "C" batteries eliminates bothersome hand winding. Just aim and shoot—even beginners get perfect movies every time. Automatic reset footage meter is easily readable. Variable, click-stop, lens aperture opens from f/16 to f/1.9 "Drop-in" spool loading is easy and economical. Exposure guide on side of case. Shpg. wt., 4 lbs. Imported.

99 N 7180L Net 16.98
Batteries for above (2 required)
32 N 4801 Net .13
15 N 1601 Carrying case Net 2.95
15 N 3406 Pistol grip handle Net 1.83

SNAPSHOT CAMERA FOR COLOR OR BLACK AND WHITE

- For Indoor and Outdoor Use
- Takes up to 16 Color or Black/White Pictures
- Priced Low Enough For Kids
- Good Enough For Adults

99¢



An amazing camera offer from Lafayette—a snapshot camera that looks like an expensive 35mm camera, yet sells for a sensational low price. Has three adjustments for sunny, cloudy or overcast conditions plus 3 adjustments for close-up to infinity. Takes 16 color or black/white pictures on standard roll of 120 film. With lens cover and strap. Shpg. wt., 1 lb. Imported.

15 N 2501 Net .99
FILM FOR ABOVE
Pkg. of 2 rolls, 16 exposures each. 120 B & W. Wt., 2 oz. Net .59
15 N 1812

NEW! KODAK INSTAMATIC 150 OUTFIT

- Quick Loading
- For Indoor and Outdoor Use



This complete foto outfit is perfect for the casual photographer who desires professional quality pictures. Spring wound auto-advance winds film; instant no-thread loading; built in pop up flash holder are among the features of this versatile camera. Preset, fixed-focus lens with choice of 2 shutter speeds allow simple operation. Uses popular AG-1 bulbs and size "126" film. Outfit comes with carrying case for camera and accessories. Shpg. wt., 5 lbs.

15 N 2628L Net 22.95

22⁹⁵

Take Advantage of Lafayette's Low Camera Prices

500 WATT SLIDE PROJECTOR

- Automatic Slide Changer
- Color Corrected 4" f/3.5 lens
- Holds up to 40 Slides
- 500 Watt



29⁹⁵


Designed and engineered for simplicity of operation, ease of maintenance, and long life. 4" color corrected, hard coated f/3.5 lens. Sharp, brilliant pictures assured by 500 watt lamp. No slide trays required. Project any 35mm, Bantam, 127, or Instamatic slides. Loads up to 36 slides. Different size slides can be loaded together. Unit is completely self contained and requires no tools for a bulb change. Uses standard projection lamp. Compact 5¾Hx14Lx8½"W. For 105-120 volt 50/60 cycle operation. Shpg. wt., 7½ lbs.

15 N 8401 Net 29.95

Lafayette Cat. No. 653 109

LAFAYETTE Easy To Build Educational Kits

20-IN-1 TRANSISTOR EXPERIMENTERS KIT



MADE IN U.S.A.

FUN TO BUILD—EDUCATIONAL—
and ALL 20 projects result in
a useful working instrument!

16⁹⁵

PROJECTS YOU BUILD


1. TRANSISTOR TESTER
2. VOICE ACTUATED ALARM
3. PHOTO TIMER
4. AUDIO AMPLIFIER
5. CRYSTAL SET
6. SOLAR RADIO
7. RAIN ALARM
8. TIMER
9. ONE TRANSISTOR RECEIVER
10. CODE PRACTICE OSCILLATOR

11. METROPHONE
12. TWO TRANSISTOR RECEIVER
13. ELECTRONIC RELAY
14. HOME BROADCASTER
15. PHOTO ELECTRIC RELAY
16. BURGLAR ALARM
17. WIRELESS TRANSMITTER
18. HEGENERATIVE RECEIVER
19. CITIZENS BAND MONITOR
20. AUDIO OSCILLATOR

Excellent for beginners as well as advanced experimenters, this kit enables you to build and learn about 20 interesting and useful transistor circuits. By utilizing "Breadboard" construction, each project can be simply wired and traced. After building the basic circuit, any of the 20 projects can be built by simply inserting a few preassembled component blocks and interconnecting leads between them. A soldering iron is only required for the basic wiring and not for subsequent projects. All wiring is covered in a step-by-step manner by the instruction manual. Each of the 20 projects is clearly presented with step-by-step instructions, large easy-to-read pictorial wiring diagrams, schematic diagrams, and an explanation of the circuit behavior. The kit is complete with perforated mounting board, 2-transistors, 1-diode, earphone, and all other parts required for construction. The detailed 28-page instruction manual contains a wealth of information about each project. Less batteries and tools.

19 N 0902 Complete. Shpg. wt., 6 lbs.	Net 16.95
32 N 4802 Z Cell Battery for Kit projects	Net .13
32 N 4723 22½ Volt Battery for Kit projects	Net 1.61

SHORTWAVE AND SUPERHET BROADCAST RADIO KIT



17⁹⁵

2 bands cover both standard broadcast 540-1700 KC and shortwave 5.8-18 MC which includes international broadcast, 40 and 20-meter ham bands and some of the aeronautical and marine bands. Superheterodyne circuit has high gain IF's, built-in broadcast band loop antenna. Comes complete with walnut cabinet, 4" PM speaker, tubes (12SA7, 12SK7, 12SQ7, 50L6 plus 35Z5 rectifier) and all parts. Easy to follow step-by-step instructions. Shortwave band requires external antenna (not supplied). Size 9¾x6x5½"D. For 110V AC or DC. Shpg. wt., 6 lbs.

19 N 4001 Net 17.95

LAFAYETTE WIRELESS BROADCAST/AMPLIFIER KIT



12²⁵

Use it either as a
Wireless Broadcaster or AM Audio Amplifier!

- CLEAN, MODERN STYLING • POWERFUL SIGNAL
- WORKS WITH ALL CRYSTAL AND MAGNETIC MIKES AND PHONO CARTRIDGES
- PLAYS THROUGH ALL AM RADIOS

Treat yourself and your family to hours of fun with this Lafayette Kit. Make your own radio programs, announcements, etc., through AM radios anywhere in the house, without wires or extra gadgets. Designed for easy construction by youngsters or adults, it combines in one compact unit a powerful 3-tube wireless broadcaster and an audio amplifier. Clearly written instruction manual makes it a cinch to build. Operates on any frequency between 900 and 1600 kilocycles on your radio dial. It will accept any crystal or magnetic microphone. In addition, it may be used directly as a phono or microphone amplifier. No external preamp is required. Simple slide switch permits either form of operation. Just connect it to a PM speaker (4-16 ohms). Conforms to FCC regulations and is designed to provide high quality voice or record broadcasts.

No license or permit is necessary. Complete with crystal clear instruction manual. Less Mike. For 105-125V AC or DC. Attractively styled metal cabinet. Size 4Hx8Wx4¾"D. Shpg.

19 N 0903 Net 12.25

Same as above, but factory wired & tested
19 N 0908 Net 14.95

Crystal microphone for above. Desk or hand held. 8 ft. cable. Shpg. wt., 1 lb.
99 N 4503 Net 2.95



Made in U.S.A.

12⁹⁵

LAFAYETTE SUPER-SENSITIVE PHOTOCELL ELECTRONIC RELAY KIT

- WITH CLAIREX CADMIUM SULPHIDE PHOTOCELL • ADJUSTABLE SUPER SENSITIVITY—WORKS WITH JUST A FLASHLIGHT AT 250 FEET!
- NEEDS NO SPECIAL HIGH-INTENSITY LIGHTS • INSTANTANEOUS OR SUSTAINED OPERATION ON THE FLIP OF A SWITCH!

Ideal for sustained operation required for burglar alarms, door buzzers and for instantaneous on-off operation required for counters, packaging, door opening, motor activation plus countless industrial applications. Switch converts unit from instantaneous "on-off" to sustained "on" operation. "RESET" switch opens the external circuit and turns off the alarm. The unit operates on 110 volts AC and incorporates the efficient 5823 cold cathode tube. A simple change in wiring (in instructions), as well as convenient input terminals, enables you to supply the external circuit with any desired voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on 110 Volts AC. Complete with all parts, photocell, tube chassis, silkscreened metal cabinet and easy-to-follow illustrated instructions. Size: 3x4x5". Shpg. wt., 3 lbs.

19 N 0904 Complete Kit Net 12.95

ACCESSORIES FOR ABOVE

99 N 9023 Electric Bell, 110V AC. Shpg. wt., 2 oz.	Net 1.49
99 N 9024 Electric Buzzer, 110V AC. Shpg. wt., 10 oz.	Net 1.29
99 N 9011 6-Digit Electric Counter. Shpg. wt., 1½ lbs.	Net 9.95

LIGHT SOURCE FOR ELECTRONIC RELAY KIT



- COMPLETELY WIRED
- INCLUDES RED FILTER

7⁵⁰

Completely wired and assembled light source with AC line cord and plug. Will actuate the relay at 70 feet w/o red filter, up to 30 feet with red filter. Removable red filter makes light beam invisible by day and very difficult to detect at night. Metal case. Size: 5¼x3x4". For 110V 60 cycle AC. Shpg. wt., 4 lbs. Imported.

99 N 9026 Net 7.50

Replacement Bulb for above. Net .21

99 N 9027 Net .21

Interested in Electronics?
The Ideal Gift For Young and Old!

LAFAYETTE "EXPLOR-AIR"TM 4-BAND RECEIVER KIT

• 4 Bands for Total Coverage

22⁹⁵

550KC—1600KC 1650KC—5.5MC
5.5MC—16MC 16MC—30MC
• Covers 10, 15, 20, 40, 80, 160
Meter Amateur Bands • Tunes
International Broadcast, Citizens
Band, Maritime, Aeronautical and
WWV Time Signals • Complete
Band Switching from Front Panel
• Bandsread Tuning • Built-
in 4" Speaker.



MADE IN U.S.A. TUNE IN THE WORLD!

Lafayette's sensational shortwave receiver kit is a complete shortwave and standard broadcast set which covers the entire region from 550 kilocycles to 30 megacycles. Four whole bands of fascinating programming. Perfect for language students and shortwave listeners.

Only a regenerative circuit can offer such amazing performance and yet be so simple to build. Building this fine kit is an absolute pleasure—it's so well designed you can't go wrong. Kit includes all the parts you need, and the detailed step-by-step instruction book with its giant pictorial drawings shows you just how to put them together. One front panel knob does all the bandswitching, immediately taking you from band to band. All

coils are prewound for greater accuracy. Complete 4 band coverage of broadcast stations, international broadcast bands, amateur, maritime, and WWV time signals. Big 4" speaker and sensitive circuit with 50C5 output stage and 12AT7 regenerative detector and amplifier stages give you all the volume you want. Phone jack for privacy automatically disconnects speaker. All controls are on the front panel: On-Off Volume, Main Tuning, Band Spread, Bandswitch, Antenna Tuning, and Regeneration. 110 volt 50-60 cycle AC-DC power supply. Size: 10x7x5".

19 N 0905 (Less Cabinet) wt., 5 lbs. 22.95
Leatherette covered Wooden Cabinet for above. 1 lb.
19 N 0906 Net 2.85

ANALOG COMPUTER KIT




9⁹⁵

- Ideal Introduction to Basic Elements of Analog Computers
- Work Over 50 Experiments
- Easy-to-Assemble with Screwdriver and Pliers
- Learn the Way to Sound Scientific Knowledge

The latest Analog Computer Kit offering a basic introduction to computer theory—gives accurate answers to practical problems. Perform over 50 experiments—multiplication, division, powers, square roots, rocketry, interest, radioactive decay, light, kinetic energy, etc. Level of accuracy better than 5%. The computer consists of a masonite, solid instrument panel, kits, potentiometers, meter, specially calibrated scales, guide and operating booklet. Easy-to-assemble. 19 N 3805 Shpg. wt., 6 lbs. Net 9.95

Basic Educational Computer Kits

GENIAC PORTABLE MEMORY CARD FILE



How to file a card in 25 places simultaneously.

only 17⁹⁶

For the busy scientist, engineer, teacher, businessman or student who must keep basic information on file. NOW the Geniac Portable Memory Unit, (PMU), a low cost information retrieval system can conservatively sort 400 cards per minute—using no electrical parts or gadgets. Sorting is by rods. Information is coded into the cards by matching prepunched holes around the edge of the card. No previous knowledge is necessary. Once coded the card is filed at random and will automatically appear during sorts for the various categories. Serves as a useful adjunct to company integrated information systems. The basic PMU contains a matching hand punch, sorting rods and 300 cards.

19 N 3801 Shpg. wt., 6 lbs. Net 17.96
Additional Cards, pkg. of 100
19 N 3802 Net 3.92

GENIAC[®] COMPUTER KITS



Over 800 Parts For Schools,
For Science Fairs, For
Advanced Experimenters

- COMPUTES, REASONS, PLAYS GAMES
- COMPOSES MUSIC, FORECASTS WEATHER
- DESIGN YOUR OWN COMPUTERS
- OVER 400 PARTS AND COMPONENTS

DOUBLE GENIAC

The newest kit in famous Geniac[®] series! The "Double" Geniac contains over 800 parts. Two of everything in the Standard model. Offers the advanced experimenter a far wider range of activities. Perfect for school demonstration. Multiple setup is ideal for Science Fair projects—submit one or more designs. Build "electric trains" that test intelligence—code and decode—add,

subtract, multiply and divide—solve puzzles—play games—forecast weather—reason in syllogisms—information and logic circuits. No soldering required. Easily assembled and operated. 64 page guide and reference book, beginners manual, wiring diagrams and many extra pamphlets outlining projects and methods. Complete with mounting rack and batteries. Shpg. wt., 12 lbs.

19 N 3803 Net 15.95

STANDARD GENIAC


You build up to 125 exciting "electric brain" machines. Has special circuits for forecasting weather. No soldering required. Comes complete with extra pamphlets including 64-page "Simple Electronic Brains and How To

Make Them," "Symbolic Analysis of Relay and Switching Circuits," "Beginner's Manual. Machine to Compose Music. Wiring Diagrams, etc. Complete with battery. 16 1/2 x 11 3/4". Shpg. wt., 6 lbs.

19 N 3804 Net 9.95

LAFAYETTE Kits Easy-To-Build-Enjoyable-To-Use

LAFAYETTE KT-92 5-WATT PUSH-PULL AMPLIFIER KIT



1095

Made in U.S.A.


- Push-Pull Audio Output Stage • Inverse Feedback Circuit
- Separate Volume, Bass & Treble Controls • AC or DC Operation

Here in kit form is an AC-DC hi-fi amplifier that presents deluxe features despite its amazingly low price. The separate bass and treble controls permit adjustment of both low and high frequency response and balance. Works equally well with both crystal or ceramic cartridges. Tube line-up consists of a 12AX7 amplifier and phase inverter, a pair of 35C5's in push-pull, having a power-packed low-distortion output plus a 35W4 rectifier. The circuit utilizes an inverse feedback loop to reduce the level of hum and distortion. Kit is complete containing all essential parts, tubes and detailed instruction manual showing pictorial and schematic diagrams. Shpg. wt., 4 lbs.

19 N 0101

Net 10.95

COMPLETE MONAURAL PHONO SYSTEM KIT



LAFAYETTE
ENSIGN

SK-124

4750

\$5 monthly

For those who prefer a monaural system, this package consists of the Lafayette KT-92 push-pull amplifier kit, the Lafayette-Ensign 4-speed automatic record changer complete with stereo-monoaural cartridge and the Lafayette SK-124 2-way speaker system. When ordering specify mahogany or walnut finish, less base. Shpg. wt., 28 lbs.

21 N 979WX

Net 47.50


24 N 0107 Walnut Base for changer

Net 3.95

24 N 0108 Mahogany Base for changer

Net 3.95

12-WATT HI-FI AMPLIFIER KIT with BUILT-IN PRE-AMPLIFIER



ONLY
1950

FEATURES: Separate full-range bass boost and controls. 4, 8 and 16 ohms speaker output. Amplifier, pre-amplifier and power supply on single open pre-punched chassis for the easiest construction. 4 input connections located at rear of chassis for magnetic phono or tape, crystal phono, tuner/radio, and mike or auxiliary. Self-balance phase inverter system and full range tone control amplifier. Inverse feedback circuit. Removable front panel for professional appearance in custom installations. Amplifier can be used with electric guitar, etc., or in a Public Address System. Frequency Response: 1 db 20 to 20,000 cycles; Distortion: 1% at rated output; Hum: Tuner/Crystal Phono 80 db below 12 watts; Magnetic Phono/Tape 60 db below 12 watts. Sensitivity: Magnetic Phono/Tape 3mv. Crystal Phono 0.5 volt. Tuner/Radio 0.5 volt. 4 Controls: Function, Loudness, Bass, Treble/Power Switch; Tube Complement: 12AX7/ECC83 Preamp; 12AT7 Phase Inverter; Tone Control Amplifier; 2-6V6 Push-pull Beam Power Amplifier; 1 Rectifier. Complete with 24-page instruction book complete with diagrams, illustrations and step-by-step construction details. Baked Hammertone. Golden Brown Finish Chassis. 11Wx7Dx 5"H. Power Consumption 55 watts; 117 VAC; 50-60 cycles.


19 N 0102 Shpg. wt., 11 lbs.

Net 19.50

19 N 4004 Cover for above. Shpg. wt., 3 lbs.

Net 3.95

STEREO 30-WATT WILLIAMSON TYPE DUAL AMPLIFIER/PREAMPLIFIER KIT



- A Complete Stereo Control Center
- 15 Watts Each Channel, 30 Watts Monaural
- Easy To Build

only 3650

\$5 Monthly

A Stereophonic 30-Watt Williamson Type Dual Amplifier/Preamplifier Kit. FEATURES: Stereo Inputs for Tape/Low Level Phono, High Level Phono, FM/AM Tuner, High Level Tape/Auxiliary. Dual tape outputs. Output Impedances: 4, 8 and 16 ohms. 3rd channel output. Equalization: (Tape) NAB; (Phono) RIAA. Separate full-range bass boost and treble controls for each channel. Frequency Response: ± 1 db 20 to 20,000 cps. Distortion: Less than 1% harmonic distortion. Hum: Tuner/Hi Phono/Aux. 70 db below 15 watts; Low Phono 60 db below 15 watts; Tape 55 db below 15 watts. 9 Front Panel Controls: Function, Loudness, Balance, Treble A/Off, Treble B, Bass A, Bass B, Equalization, Mode. Tubes: 2-12AX7/ECC83, 2-12AT7/ECC81, 4-7408, 1-5U4. Operates on 117 volts, 50-60 cps AC. Baked Hammertone, Golden Brown Finish Chassis. Complete with "Foolproof" instruction book having diagrams, illustrations and step-by-step construction details. Size: 15Wx6Hx8"D.

19 N 0103

Net 36.50

19 N 4005 Cover for above. Shpg. wt., 3 lbs.

Net 3.95

Features smooth counter-weight tuning with advanced circuitry that prevents drift after station selection, and special temperature-compensated oscillator circuit as additional aid in preventing drift. The powerful 5 tube circuit plus rectifier has an Armstrong FM Circuit with a low noise FM pre-wired and pre-aligned front end, and offers a 20-20,000 cps. response. The AM section features a Superheterodyne Circuit with AVC and a powerful Ferrite Loopstick Antenna with multiplex stereo output jack. SPECIFICATIONS: Frequency response: FM $\pm 1/2$ db. 20-20,000 cps. FM drift ± 15 KC Maximum. Sensitivity: FM 3 μ v for 20 db. Quietening: AM 25 μ v. Distortion: Less than 1% on FM. Hum Level: 60 db. Controls (2): Off-AM-FM, tuning with AFC incorporated. Power Drain: 30 watts at 105-125 volts AC. Size: 12" wide - 6" deep. Shpg. wt., 8 lbs. Front panel finish: Mahogany, Ivory, and Gold.

19 N 4002W

Net 36.95

19 N 4006 Cover for AM-FM Tuner. Shpg. wt., 3 lbs.

Net 5.95

FM TUNER KIT

Same as FM-AM Tuner Kit less AM circuitry and less 6BE6. Shpg. wt., 10 lbs.

19 N 4003W

Net 29.95

19 N 4006 Cover for FM Tuner Kit. Shpg. wt., 3 lbs.

Net 5.95

FM-AM TUNER KIT

- Pre-wired and Pre-aligned Front End
- Automatic Frequency Control




3695

\$5 monthly

Automatic Timers And Counters

**INTERMATIC
MODEL A211-4 TIME-ALL**

797



Makes practically everything electrical completely automatic. Will handle loads up to 1875 watts. Turns radio on and off—does not have to be reset each night. Defrosts refrigerator—turns lights on and off—controls roaster, electric blanket, washing machine, coffee makers, vaporizers, etc. 30 min. minimum on time—23 hours maximum. As easy to set as an electric clock. Stands on any surface—can be hung on wall. Easy-to-read 24 hour "day and night" dial. Operates day after day without attention. Special alloy "T". Can be controlled manually without automatic reset. Plug-in receptacle for equipment to be controlled. For 110 volt 60 cycle AC only. Complete with 6 ft. cord and plug. Instructions included. 5x4x2½". Shpg. wt., 2 lbs.

13 N 2715 Net 7.97
MODEL A221-4 TIME-ALL. Similar to A211 except has capacity of 875 watts. Shpg. wt., 2 lbs.
13 N 2716 Net 7.29

TELECHRON TIMER SWITCH

Turn on any Appliance up to 1650 watts.



395



Genuine Telechron mechanism. Complete 12 hour movement. Can be set to turn on any radio, TV or similar electrical appliance at any preset time. Gold finish dial—black lettering. Timer sets from rear. On-off-auto switch in front. Size 3½" square, 1¾" deep. Set shaft extends 5½" to rear. SPST switch, rated 15 amps at 115 volts. For 110-120V, 60 cy. AC only. Shpg. wt., 2 lbs.

*Plus 10% F.E.T.

13 N 4408 Net 3.95

TELECHRON TIMER SWITCH



- Radio — TV — Appliance Timer
- 60 Minute Sleep Switch
- Simple Installation
- 1650 Watts



Automatically turns on radios—TV sets—etc.—at any preset time in a 12 hour period. "Sleep-Switch" allows up to 60 minutes of continuous run prior to "shut-off." Built in signal alarm. All controls on front. On-off-auto, 0 to 60 sleep switch, alarm set and time set. Gold finish dial—black lettering. 3½" square bezel, 1¾" deep. SPST rated 15 amps at 115 volts; 1650 watt load capacity. For 110-120V. 60 cy. AC only. Shpg. wt., 2 lbs.
 *Plus 10% F.E.T.
13 N 4409 Net 4.98

**INTERMATIC
MODEL A401-4
CLOCK TIMER**

877



Not only tells time, but turns appliances both on and off automatically for periods of 15 minutes to 5½ hours. Cooks dinner while you're away, wakes you to music, controls electric fans, heaters, radios, TV sets, etc. No installation problem—just plug it in and set. Capacity 1875 watts. 4¾Wx4½Hx2¼"D. 6 ft. cord. For 110V 60 cycle AC. Guaranteed for 1 year. Shpg. wt., 3 lbs.

13 N 2717 Includes F.E.T. Net 8.77

**INTERMATIC
TYPE T101
TIME SWITCH**

842




Turns equipment "on" and "off" once in 24 hours, or from 1-12 "on" and "off" operations a day can be obtained by use of extra trippers—can be added without removing dial. Min. on or off time 1 hr., max. 23 hours. Can be turned on or off manually with reset SPST switch rated at 40 amps. 4375 watt capacity. Mounting holes and knockouts. Gray steel case. UL approved. Operates on 110 volt 60 cycle AC. 7¾Lx5Wx3"D. Shpg. wt., 4 lbs.

13 N 2702 Net 8.42

**5-DIGIT STROKE-ACTUATED
RESET
COUNTER**

269




- Registers up to 99,999
- For Machine Mounting
- Complete with Arm and Spring

Easy-to-mount rugged counter for counting machine operations. One count per stroke. Drilled mounting flange; actuating arm and spring. May be manually or solenoid actuated. Reads up to 99,999; side knob easily resets to zero from any number. Overall size: 2½x1½x1¾". Shpg. wt., ½ lb. Imported

99 N 9029 Net 2.69

TIMED EXTENSION CORD



511

**MODEL TE C-4
Set It and Forget It**

- Automatic Time Switch & Extension Cord + 3-Way Outlet
- Controls up to 3 Appliances at Same Time
- Reduces Electric Bills


A 3-way combination for every home—an automatic time switch, extension cord, convenient outlet. 0-4 hour time cycle. Easy to operate—plug it into any wall outlet, connect one, two or three devices to be controlled, and turn the knob to the time period desired. At the end of this time period, the electricity is turned off automatically. 6-foot cord. Shpg. wt., 1 lb.

13 N 8501 Net 5.11

HAND TALLY REGISTER

- 4 Digit Capacity
- Counts 0-9999
- Single Turn Reset Knob

229



Registers 0 to 9999. Highly polished chromium plated brass case. Attached finger-ring and compact shape for comfort in holding. Plunger operated for smooth, easy action. Large, clearly read numerals. Knurled reset knob sets register to zero in one turn. Precision accuracy for lab, school and industrial users. Invaluable for inventory control — gate checking — traffic, etc. Small Size, approximately 1¾x1¾", permits concealed operation. Shpg. wt., ½ lb. Imported

99 N 9030 Net 2.29

**1/10 SECOND
TIMER**

690

- Accurate



Designed for close timing. Large hand registers 1/10 of a second, up to 30 seconds; small hand reads minutes, up to 15. Start, stop, and continue from crown; instant zero. 1 jewel movement. Chromium plated case. Shpg. wt., 8 oz. Imported.

13 N 3102L Net 6.90

Same as 13 N 3102 (above) except 7 jewels.

13 N 3103L Net 9.33

**1/5 SECOND
TIMER**

As Low As
749

- Ideal for Sports



Second hand registers 1/5 of a second and completes turn in 60 seconds. Small hand indicates up to 30 minutes. Side slide starts and stops hands. Fast resetting dependable 7-jewel movement. Shpg. wt., 8 oz. Imported.

13 N 3104L Net 9.75

Same as 13 N 3104 (above) except 1 jewel.

13 N 3105L Net 7.49

Citizen-Ship R/C Equipment and Accessories

MODEL SL-6 SIX CHANNEL ALL-TRANSISTORIZED HIGH POWER TONE TRANSMITTER



(27.145MC)

62⁵⁰

\$5 monthly

Operates RL-6 Reed Receiver, and all single channel receivers on this page. Features RF output from silicon transistor and center loaded antenna; "contest type" lever switches, 4-transistor temperature-compensated circuit for tone stability. Six adjustable tone frequencies from 350-650 cps. Battery drain 50 MA. Anodized aluminum case with rubber feet. 6 7/8"x5 1/2"x2 3/4". Weight 2 3/4 lbs. with battery. Complete with antenna, less battery. Available in 26.995, 27.045, 27.095, 27.195 and 27.255 on special order (4 weeks delivery).

42 N 1901 Net 62.50
32 N 4808 9 volt battery for above Net 1.26

MODEL TCA TRANSISTORIZED CAM ACTION SERVO



- First Servo to Give Variable Ratio
- Ideal for Contest Work

Designed for use up to 140°F, this servo operates directly from any standard reed bank. In addition it features a variable push and pull ratio. Results in slow start for smooth flying and fast finish for quick recovery. Completely reliable and foolproof. Weighs 3 oz. Uses 6 volts (4 pencils). Shpg. wt., 1 lb.

42 N 1909 less batteries Net 20.75
32 N 4802 1 1/2 Volt Batteries (4 required) ea. Net .13

MODEL TNA TRANSISTORIZED SERVO 21⁹⁵

For Tone Actuated Receivers

Operates directly and efficiently from any standard reed bank. Transistors protected against danger from closing 2 or more reeds simultaneously or from servo being stalled by locked control. Designed for use up to 140°F. Completely reliable and foolproof. Uses 6 volts (4 pencils). Shpg. wt., 1 lb.

42 N 1902 Less batteries Net 21.95
32 N 4802 1 1/2 Volt Batteries (Burgess "Z") 4 required ea. Net .13

R/C PACK WITH SE-2 ESCAPEMENT



29⁹⁵

Single Channel
— 27.255 mc

Completely wired R/C unit for INSTANT model plane or boat installation. No soldering or connections of any kind is required. INCLUDES: Model LT "3" relayless receiver, escapement, battery holder, off-on switch, push rod, hook and bearing. Especially designed for small R/C planes 1 3/4"x2 1/4"x 1/4". Weight—complete with batteries, 5 oz. Shpg. wt., 1 lb. Operates with TTX transmitter above.


42 N 1903 Less Batteries Net 29.95
32 N 4802 1 1/2-Volt "Z" Batteries (2 required) ea. Net .13

MODEL MDL SINGLE CHANNEL RELAYLESS TONE RECEIVER

Smaller Than A Postage Stamp

Subminiature, super-regenerative relayless tone receiver that operates from any tone transmitter. Designed for perfect unit operation with powerful SE-2 escapement. Virtually crash proof. Requires 3 volts (2 pencil batteries). Size with plastic cover: 7/8"x1 1/4". Weighs 1/2 oz. Shpg. wt., 4 oz.

42 N 1904 less batteries Net 19.95
32 N 4802 1 1/2-Volt "Z" Batteries (2 required) ea. Net .13



MODEL RL-6 SIX-CHANNEL ALL-TRANSISTORIZED RELAYLESS SUPERHET REED RECEIVER



(27.145MC)

45⁷⁵

\$5 monthly

Especially designed for use with the Citizen-Ship SL-6 transmitter, the combination is ideal for Rudder (class I), Intermediate (class II), and Pylon racing. Receiver operates 3 separate servos (rt., left; up, down; high and low motor). 6 transistors, crystal controlled. Change frequency by changing crystals. High selectivity permits flying up to 5 different models simultaneously without interference. Current drain: 5 MA signal off, 15MA signal on. Weighs only 3 1/2 oz. Size: 2 7/8"x1 3/4"x1 1/4". Less battery. Available in 26.995, 27.045, 27.095, 27.195 and 27.255MC on special order (4 weeks delivery).

42 N 1905 Net 45.75
32 N 4807 9-volt battery for above Net .48

MODEL TTX TRANSISTORIZED TONE TRANSMITTER

SINGLE CHANNEL
27.255 mc



26⁵⁰


This popular, efficient single channel tone transmitter measures 3 1/4"x5 1/2"x1 7/8" and weighs only 12-oz. with battery. It is 100% collector modulated (no reduction of RF signal with modulation). In addition it features a high efficiency externally loaded antenna and printed circuit chassis. It operates on 9 volts; requires no license. Operates R/C pack with SE-2 Escapement below. Shpg. wt., 2 lbs.

42 N 1906 Less Battery Net 26.50
32 N 4808 9-Volt Battery (Burgess 2N6) Net 1.30

5-CHANNEL RESONANT REED HOBBY RELAY

7⁹⁵ TUNED TO FREQUENCIES:

266.0 CPS,
280.8 CPS, 313.0 CPS,
349.0 CPS, 389.0 CPS



A compact, reliable, 5 channel resonant reed frequency selective relay. Frequency tolerance ± 1%. Especially adaptable to 5 channel remote control hobby tone receivers and Citizens Band tone signaling receivers. Can also be used as high stability, resonant reed oscillator control. Features low tuning error, good temperature stability, and low driving requirements. Reed response approx. 75 milliseconds; contact rating 100-ma at 48 VDC, 15 ma at 100 VDC, 1 ma at 150 VDC. Drive power varies from 1-milliwatt at 100 cps to 50 milliwatts at 800 cps. Weight 1 oz. 1 3/4"x1 3/8"x1 1/4". Mounts by two 6/32" tapped holes on back and bottom. Shpg. wt., 8 oz.

42 N 1908 Net 7.95

MODEL SE-2 ESCAPEMENT

- Smallest Size Compound or Selective Type Sensitive Escapement

Select right or left at will. Always starts from same neutral. One pulse gives right rudder, two pulses left rudder. Will operate directly from a transistor. Weighs less than one ounce. Voltage required, 3 Volts (2 pen cells).

42 N 1907 Net 6.75
32 N 4802 1 1/2-V Pen Cells (2 req.) Net ea. .13




LAFAYETTE R/C Equipment and Accessories

LAFAYETTE Super-Trol™ R/C Transmitter

*MEETS FCC REGULATIONS

Assembled-tested-guaranteed.

Crystal controlled with .01% tolerance crystal as per FCC regulations. Range approximately one mile. Will operate any 27.255 MC R/C receiver. Only 8½x2¾x1¾". Includes antenna, tube, crystal, and instructions. FCC license applications enclosed — no examination required. Less batteries. Shpg. wt., 2½ lbs. Imported
99 N 9025 Net 14.95
32 N 4805 Batteries Burgess U30 (3 Needed) 1.75 ea.
32 N 4804 #2 Batteries (1 Needed)13 ea.



Super-Trol™ R/C Receiver

Completely wired and tested receiver—extremely sensitive and stable. Completely enclosed—ideal in boats —or case may be removed if desired. Ingeniously constructed to withstand vibration and shock. Features external fine tuning—antenna "snap" lead—plug for power and actuator connections. Requires one 1.5V battery and one 67.5 Volt battery. Size determined by use. Measures only 3x2¼x1½". Complete with tube and instructions. Less batteries. Shpg. wt., 8 oz. Imported
99 N 9028 Net 8.95

BATTERIES REQUIRED:

99 N 6023 (1 needed) Imported 1.29
32 N 4804 Burgess No. 2 (1 needed)13 ea.

SPECIAL COMBINATION OFFER

99 N 9032M Consists of R/C Transmitter and R/C Receiver —Combination 22.90

MULTI-PURPOSE ELECTRO SERVO MECHANISM

4⁹⁵



Operates with any single channel R/C receiver and transmitter. Requires 3 volts. Provides for steering and automatic return to neutral. Single pulse operation. Only 2½x2x1¾" overall. Includes instructions and linkage to extend actuator arm. Shpg. wt., 8 oz. Imported
99 N 9033 Net 4.95

"THE BIG EAR"

12⁹⁵



- Big 18" Reflector Disk Concentrates Sound Waves Into Transistor Unit Which Amplifies Them Loud and Clear

Powerful new transistorized listening device. Not just a toy—works on the same principle as the fabulous Missile Tracking Antennas. Pick up sounds too distant for you to hear. Make your own wildlife recordings or carry on long range 2-way communications (using a "Bull Horn"). Ideal for experimenters, etc. Complete with sturdy tripod and stethoscope-type earphones. Uses one 9V Battery (not supplied). Shpg. wt., 5 lbs.
13 N 2510W Net 12.95
99 N 6021 9V Battery for above Net .21

MINIATURE TELESCOPING ANTENNA

59¢



Ideal for transceivers, miniature portable and transistor radios, wireless broadcasters. 5-section antenna of chrome-plated brass screws jack supplied. Measures 38" fully extended, 9" closed with plastic case. Imported
99 N 4001 Net .59

LITTLE "JEWEL" REMOTE CONTROL RELAY

1⁹⁵




A natural for remote control receivers, it is highly sensitive, and built to withstand severe crashes. The smallest commercial job available, it weighs less than ½ oz. Factory adjusted to pull in at 1.4 MA drop out at 1.2 MA D.C. Single pole, double throw. Used in outstanding R/C receivers. 5,000 ohm coil. Imported
99 N 6091 Net 1.95

- The Mighty Mite of the R/C Field
- Weighs less than ½ oz.!
- Size: ¾"H, 17/32"W, 1-1/16"L

27.255 CRYSTAL .005% TOLERANCE!

2²⁵



Designed for use in R/C model planes, boats, cars, etc., as well as on channel 23 of class "D" Citizens Band Equipment. Type HC-6/U holder; Pin spacing .493; Pin dia. .050".
42 N 4206 Net 2.25

CRYSTAL SOCKET

For above and all HC-6/U Citizen band and R/C crystals.
42 N 0901 Net .20

R/C ESCAPEMENT

A sturdy 2 arm self neutralizing escapement. Converts electrical impulses from remote control receiver to mechanical motion. Four 90° rotations—two by armature activation, two by neutralization. Has ratchet governor. Weighs only 7/8 oz. Size: 1½Lx2"W overall. Shpg. wt., 5 oz. Imported
99 N 9034 Net 1.95



R/C ENGINE ESCAPEMENT

Self-neutralizing remote engine control. Varies engine speed of your model. Neutral position of one arm is low speed, neutral position of 2nd arm is high speed. Activated position of either arm (armature activated) stops motor. Or ¾ oz. Requires ½ volt battery. Size: 1½x1¾". Shpg. wt., 5 oz. Imported
99 N 9035 Net 2.45



COMPOUND R/C ESCAPEMENT

One pulse, right turn; two pulses, left turn. Three pulses closes circuit for supplementary control. The rudder returns to neutral position when transmitter keying button is released. With ratchet governor. Uses 1½ volt battery. Weighs 1½ oz. Size: 2½Lx1¾" overall. Shpg. wt., 6 oz. Imported
99 N 9036 Net 3.45



NOVATRON

A SCIENTIFIC INSTRUMENT FOR THE EXPERIMENTERS

- Powerful 110 Volt AC/DC Motor
- Miniature Atom Smasher
- Produces 75,000 Volts
- Absolutely Safe


COMPLETELY WIRED (NOT A KIT)



A scientific instrument capable of producing 75,000 volts—makes sparks up to 2" long—yet it is absolutely safe because the current is infinitesimal. The science-teacher — science lover — or hobbyist can perform experiments to astound students — friends — family. Makes smoke disappear — defy gravity — turns propellers at a distance — transforms atomic energy into light — makes artificial lightning — smashes atoms — demonstrates ionic space ship drive — and many other experiments. Includes an experimental kit and illustrated experiment manual. A fine research tool that will give years of beneficial service to the institution or individual who owns one. 110 V. AC or DC. Imported.
 Assembled — Shpg. wt., 4 lbs.
99 N 9008 Net 12.95

Experimenter's And Hobbyist's Specialties

5-TRANSISTOR PUSH-PULL AUDIO AMPLIFIER



- 360 MW Output
- Completely Wired
- Direct Wiring

6⁹⁵

ONLY 3¹⁵/₁₆" x 1¹⁵/₁₆" x 1¹/₁₆"

A more powerful and more sensitive version of the 4-transistor amplifier on right, this amplifier employs 3 stages of audio driving a push-pull output stage. Power output is 360 mw, designed for speakers with a voice coil impedance of 8-11 ohms. Low impedance input has sensitivity of 300 microvolts. Input transformer for matching high impedance to the amplifier input available as an accessory (see below). Comes with leads for low impedance input, speaker, volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Shpg. wt., 5 oz. Imported.


99 N 9037

Net 6.95

ACCESSORIES FOR ABOVE

- | | |
|--|----------|
| 99 N 6021 9 volt battery. Shpg. wt., 2 oz. | Net .21 |
| 10,000 ohm volume control w/switch. Shpg. wt., 2 oz. | |
| 32 N 7364 | Net .69 |
| 99 N 6032 8 ohm 3" speaker. Shpg. wt., 10 oz. | Net 1.49 |
| 99 N 6036 8 ohm 2" speaker. Shpg. wt., 8 oz. | Net 1.49 |
| Input transformer for matching high impedance (mike, etc.) to amplifier. | |
| 99 N 6034 | Net .89 |

4 TRANSISTOR SUBMINIATURE PUSH-PULL AUDIO AMPLIFIER



4⁹⁵

OUTPUT 100-MW

- Terrific for the Experimenter, Hobbyist and Kit Builder!
- Completely Wired, Not A Kit!
- Printed Circuit Board
- Complete With Transistors

A tiny, transistorized push-pull audio amplifier with a multitude of applications. Only 3" x 1¹/₄" x 1¹/₄", it can be mounted inside other equipment to serve as a subminiature phono amplifier, tape recorder, amplifier, etc. Can be the complement of a homebuilt project which needs only an audio amplifier to make it complete and self-contained. Two stages of audio are followed by a push-pull output stage designed to deliver 100 mw to an 8-11 ohm impedance. Low impedances input, with a sensitivity of 0.9 mv. Input transformer for matching high impedances to the amplifier available as an accessory (see below). Includes leads for input, speaker, and volume control/on-off switch. Battery clips and leads supplied for 9-volt miniature battery (one required). Shpg. wt., 5 oz. Imported.


99 N 9042

Net 4.95

ACCESSORIES FOR ABOVE

- | | |
|--|----------|
| 99 N 6021 9-volt battery. Shpg. wt., 2 oz. | Net .21 |
| 50K ohm volume control w/switch. Shpg. wt., 2 oz. | |
| 32 N 7367 | Net .69 |
| 99 N 6032 8 ohm voice coil speaker. Shpg. wt., 10 oz. | Net 1.49 |
| 99 N 6036 8 ohm voice coil speaker. Shpg. wt., 8 oz. | Net 1.49 |
| Input transformer for matching high impedance (mike, etc.) to amplifier. | |
| 99 N 6034 | Net .89 |

4-TRANSISTOR SUBMINIATURE AM/SW TUNER WITH VERNIER TUNING DIAL



14⁹⁵

Makes Superb Superhet AM/SW Radio with Any Transistor Audio Amplifier


- 2 Bands—530-1600 KC, 4.5-12 MC
- Completely Wired Printed Circuit Board
- 4 Transformers: 3 IF Plus 1 Oscillator, for Fine Superheterodyne Performance

Vernier type tuning mechanism makes precise AM/SW tuning a cinch with this extremely powerful and sensitive 4-transistor tuner. Outstanding features include: completely wired printed circuit board, 3 IF and 1 oscillator transformers for exceptional sensitivity and selectivity, built-in ferrite antenna for both AM & SW reception, superhet circuit with BC & SW band switch. S/N Ratio: 14 db on AM; 20 db on SW. Supplied complete with 3 long leads for connecting to external amplifier and/or to a separate 9v battery (only 3 ma. drain), mounting brackets and operating instructions. Overall Dimensions: 6³/₁₆"x3³/₁₆"x2¹/₁₆"H. Shpg. wt., 1 lb. Imported.

99 N 9041

Net 14.95

"MITY-AMP" POWERFUL 2-WATT AUDIO AMPLIFIER MODULE



8⁹⁵

- For Monaural, Stereo, Intercom, P.A. Signal Tracer, etc.
- Full 2-Watt Power
- Ruggedly Constructed & Completely Encapsulated

With Applications Booklet and Schematics


Specifically designed to offer compactness, versatility and quality. Adaptable to hundreds of audio applications. Full 2-watt power yet fits in the palm of your hand. Completely encapsulated in high quality epoxy—will not be affected by high humidity or salt content in air: water-proof and shock-proof. Frequency Response: 20 cycles to 15KC ± 2 db at 1 watt. Input Impedance: 45 ohms to 50K ohms; Output Impedance: 3.2 ohms to 45 ohms; Power Requirements: 6 to 12 volts at 300 to 700 ma. Overall 2x3¹/₂x7⁸". Shpg. wt., 10 oz.

19 N 4401

Net 8.95

Specialties for Hobbyist and Experimenter

1-WATT 4-TRANSISTOR PUSH-PULL AUDIO AMPLIFIER



- 1-Watt Power Output
- 4-Transistors plus Varistor
- Completely Wired—Easy to Connect
- Sturdy Printed Circuit Construction

6⁹⁵


Our most powerful miniature amplifier. It has many direct uses in audio frequency applications for tuners, test equipment, etc. Push-pull circuit is very sensitive and has an output of 1-watt! Using only 4 transistors, it requires a 12-volt source supplied by Standard 'D' cells in series. Outputs from record players with magnetic cartridge, tape heads, microphones, etc. (not exceeding 20 millivolts) can be connected directly. Higher output devices may be easily connected with a resistor in series. Components are neatly laid out on a printed circuit board with pre-drilled holes for mounting the entire unit in a vertical or horizontal position. Built-in leads are supplied for a volume control, on-off switch, battery and 8 ohm loudspeaker. Dimensions: 4 $\frac{1}{8}$ "x1 $\frac{1}{2}$ "x2 $\frac{1}{4}$ "W. Shpg. wt., 12 ozs. Imported.

99 N 9038 Net 6.95

ACCESSORIES FOR ABOVE

32 M 4804 8 "D" Cells Required Net ea. .13
 99 M 6019 5K ohm Volume control w/switch. shpg. wt., 2 oz. Net .69
 32 M 2405 Miniature Knob for above Net .09

3-TRANSISTOR SUBMINIATURE AM BROADCAST TUNER



7⁹⁵

- 4 TRANSFORMERS: 3 IF plus 1 Oscillator Transformer for Exceptional Superhet Sensitivity and Selectivity • 540 KC to 1600 KC
- FEATURES COMPLETELY WIRED PRINTED CIRCUIT BOARD.

USED
IN MANY
IMPORTED
RADIOS!

AN OUTSTANDING AM BROADCAST RADIO WHEN CONNECTED TO ANY TRANSISTOR AUDIO AMPLIFIER ON THESE PAGES OR ELSEWHERE!


A deluxe 3-transistor subminiature AM broadcast tuner that features 3 dependable transistors, 3 IF plus 1 oscillator transformer, and ferrite antenna in an efficient, completely wired superheterodyne circuit on a sturdy printed-circuit board.

Now you can build your own highly efficient broadcast receiver by simply adding this exceptional tuner to any of the transistor audio amplifiers listed. The long tuner leads for connecting to external amplifier and/or to a separate 9-volt battery, makes this easy as pie. Also features a large clearly visible calibrated tuning dial. The printed circuit board layout permits either vertical or horizontal mounting. Supplied complete with mounting brackets and detailed instructions. Size: 4x1 $\frac{1}{4}$ x2 $\frac{1}{4}$ " with brackets. Shpg. wt., 8 oz. Imported.

99 N 9040

Net 7.95

3-TRANSISTOR SUBMINIATURE AUDIO AMPLIFIER



3⁷⁵

• FOR THE EXPERIMENTER, HOBBYIST, AND KIT BUILDER! • PRINTED CIRCUIT • COMPLETE WITH TRANSISTORS

Here is an amazing little audio amplifier with a multitude of challenging applications; i.e., subminiature phono amplifier, tape recorder amplifier, hand-held public address amplifier, telephone pick-up amplifier, etc. Output sufficient for average listening. Has leads for any one of the following inputs: Tape recorder record/playback heads, radio-tuner, crystal or ceramic phono cartridge, and crystal or ceramic microphone. Has lead terminations for ON-OFF switch, Volume Control, 4 to 10 ohm speaker, and leads terminating in clips for a 9-volt miniature battery. Size: 2 $\frac{1}{8}$ "x1 $\frac{1}{4}$ "x $\frac{3}{8}$ ". Can be readily mounted on chassis. Shpg. wt., 8 oz. Imported.

99 N 9039 Net 3.75

99 N 6021 9-Volt Battery Net .21

5K ohm Volume Control with SPST Switch and Knob; Shpg. wt., 2 oz. Net .59

99 N 6019 Net .59

Miniature Crystal Microphone 1 $\frac{1}{8}$ " Diam. x $\frac{3}{8}$ " Deep. Shpg. wt., 6 oz. Net 1.49

99 N 4509 Net 1.49

Miniature Speaker 2 $\frac{1}{2}$ " Diam. 10 ohms Voice Coil Impedance. Shpg. wt., 8 oz. Net 1.49

99 N 6097 Net 1.49

An Exclusive Lafayette Publication



TRANSISTORIZED MINIATURE AMPLIFIER AND TUNER APPLICATIONS

By Rufus P. Turner

Many original Applications
Not Found Elsewhere!

1⁵⁰

96 Pages . . . Over 61 Circuits . . . 60 Illustrations . . . 6 Chapters—Audio, Amateur & Citizens Band, Controls, Test Instruments, Tuners, Hearing Aids, Intercoms, Etc.

An inspiring new book written by a registered Professional Engineer and author of 13 technical books and of more than 2000 magazine articles. Deals primarily with over 60 challenging and interesting applications, many of them original, of the Lafayette transistorized miniature amplifiers and tuners described on these pages. Consists of 6 interesting chapters.

1. Audio Applications—Amplifiers, Preamplifiers, Modular Amplifiers, Stereo Amps, etc.
2. Ham Radio and Citizens Band—Selective Call Alarms, Speech Clipper, Speech Amplifier Modulator, etc.
3. Control—AM RF Relay, Capacitance Relay, Sound Operated Relay, etc.
4. Test Instruments—AF RF Signal Tracer, Percent Modulation Meter, A-F Watt-meter, Sound Level Meter, etc.
5. Tuners—No License Radio Communication System, Broadcast/Short-Wave Tuner, etc.
6. Miscellaneous—Hearing Aids, Intercoms, Electronic Stethoscopes, Light Beam Transmitter & Receive, Gieger Counter, Electronic Annunciator, etc.

An excellent source of information for the kit builder, experimenter and for workers in various areas of electronics.

10 N 0101

Net 1.50

Semiconductors and Modules for



- ALL SOLID STATE • ICE CUBE SIZE
- COMPLETELY WIRED
- SHOCKPROOF • WATERPROOF



PUBLIC ADDRESS AMPLIFIER MODULE

- Will Drive Any PM Speaker with Carbon Mike; 6 Volt Battery

1⁹⁸

Fully encapsulated, this module is complete and ready to operate when connected to a carbon mike, battery and speaker. Its frequency response is tailored for excellent speech intelligibility. Can drive a 15 inch speaker at enough volume to carry several hundred yards. Complete with instructions. Size: 1½x1½x¾". Shpg. wt., 8 oz.
19 N 1509 Net 1.98

DUAL FLASHER MODULE (FLIP FLOP)

1⁹⁸

Build auto road warning lights, display attention getters, model train grade crossing flasher, etc., with this ingeniously constructed Dual Flasher Module (Flip Flop). Using a 6 volt battery (lantern type) and two #47 pilot light bulbs, this module will alternately flash these bulbs about one hundred times per minute. Size: 1½x1½x¾".
19 N 1510 Shpg. wt., 8 oz. Net 1.98
6 Volt Battery for above Net .83
32 N 4818 Net .83
No. 47 lamp (2 req.) ea. Net .10
32 N 7706 ea. Net .10

2-WATT PHONO AMPLIFIER MODULE

- Excellent Tonal Quality

3⁴⁵

A low-cost 2-watt phono amplifier in module form for use with crystal phono cartridges. Needs only a 6 volt battery and any 8 ohm PM speaker to produce far above average volume for listening. One megohm potentiometer recommended for volume control. Excellent tonal quality makes it ideal for use as phonograph amplifier. Very easy to connect—simple instructions included.
19 N 1511 Shpg. wt., 8 oz. Net 3.45

C.B. MICROPHONE PREAMP MODULE

- More Modulation

3⁵⁰

Powered by any 1½ volt battery, this tiny ready-to-use preamp will increase C.B. modulation for more dependable communication. Instructions included. Shpg. wt., 8 oz.
19 N 1517 Net 3.50

METRONOME MODULE

- Low Battery Drain

1⁹⁸

Complete encapsulated solid state circuit for a modern efficient metronome. Needs only a 6 volt battery, any PM speaker, and a 2 megohm potentiometer for speed control. Produces accurate beat tone at adjustable rates from under 40 to over 208 beats per minute. Low battery drain. Simple connecting instructions and schematic included.
19 N 1512 Shpg. wt., 8 oz. Net 1.98

INTERCOM MODULE

- Maximum Speech Intelligibility

3⁵⁰

Just connect two speakers, a battery and a switch to this indestructible, encapsulated, waterproof module for an efficient intercom.
Shpg. wt., 8 oz. Net 3.50
19 N 1510 Net 3.50

BABY NURSE MODULE

- Ultrasensitive

3⁵⁰

Contains all circuitry for an efficient baby nurse. Will amplify all baby's crib movements and even normal breathing sounds.
Shpg. wt., 8 oz. Net 3.50
19 N 1519 Net 3.50

TELEPHONE AMPLIFIER MODULE

3⁵⁰

Permits group listening to any phone conversation simply by connecting a battery, speaker and telephone pickup coil. Simple instructions included. Shpg. wt., 8 oz.
19 N 1520 Net 3.50

ELECTRONIC SIREN MODULE

3⁵⁰

This module is ready for immediate use as a modern efficient high volume siren. When powered by 6 volts D.C. it will drive any 8 ohm PM speaker to a very high level of attention getting volume with an upward scream and downward wail. Complete with instructions. Shpg. wt., 8 oz.
19 N 1528 Net 3.50

MODEL RAILROAD AND TOY SIREN MODULE

3⁵⁰

These modules, when connected to a 6-volt battery and a small P.M. speaker, are designed to reproduce the upward scream and downward wail of police, fire and emergency sirens at a toy volume level. Excellent for model railroad and toy uses. Simple instructions included. Shpg. wt., 8 oz.
19 N 1530 Net 3.50

BURGLAR ALARM MODULE

3⁵⁰

This module contains complete electronic circuitry ready for immediate use as a modern efficient burglar alarm with a built-in electronic high volume upward-screaming siren as the alarm sounder. Requires 8 ohm PM speaker, one 6-volt battery and 2 switches. Complete with simple instructions. Shpg. wt., 8 oz.
19 N 1529 Net 3.50

CODE OSCILLATOR MODULE

- Matchbook Size
- Drives Any PM Speaker
- Produces Clear CW Note
- Operates on 1½ to 6V



98^c

Transistorized code oscillator module ready to connect to your telegraph key, any 1½ to 6 volt battery and any PM speaker. Provides clear tone — ideal for learning Morse code or developing speed in receiving or sending. Produces pleasant room level volume with 1½V battery — volume may be increased by using higher voltage battery up to 6 volts. Simple connecting instructions and schematic included. Shpg. wt., 8 oz.
19 N 1513 Net .98


EXPERIMENTERS' BONANZA /



ONLY

99^c

Pkge. of 3 Boards



PRINTED CIRCUIT TRANSISTOR COMPONENT BOARDS

Manufactured for Famous Brand Computer

PACKAGE OF 3 BOARDS

... CONTAIN ...

- 12 TOP BRAND HIGH GRADE TRANSISTORS
- MANY 1% TOLERANCE RESISTORS ...
- MANY 5% TOLERANCE RESISTORS ...
- GLASS AND MOLDED DIODES ...

plus TOP QUALITY, PRECISION TOLERANCE ASSORTED CAPACITORS.

Each package contains 3 assorted boards. Each board 3¾x2½". Shpg. wt., 8 oz.
19 N 4902 Package of 3 Boards Net .99

SILICON RECTIFIERS



As low as 39c ea.

Top hat lead type silicon rectifiers, excellent for TV Radio and power supplies as half-wave, full wave rectifiers and voltage doublers.

- Type A: 750 Ma, 400 PIV @ 25°C. Net .49
- 500 Ma, 400 PIV @ 90°C. 100 for 39.50
- 19 N 4209 Shpg. wt., 4 oz. Net .49
- Type B: 750 Ma, 200 PIV @ 25°C. Net .39
- 500 Ma, 200 PIV @ 90°C. 100 for 31.20
- 19 N 4210 Shpg. wt., 4 oz. Net .39
- Type C: 750 Ma, 700 PIV @ 25°C. Net .59
- 500 Ma, 700 PIV @ 90°C. 100 for 47.20
- 19 N 5009 Shpg. wt., 4 oz. Net .59
- 100 for 47.20

Kit Builder, Hobbyist, Experimenter




Pkg. 2- 10-WATT POWER of 2 TRANSISTORS

Package of 2 PNP 10 Watt germanium power transistors in popular TO-3 case. Similar to 2N155, 2N171, 2N235, 2N351, 2N242, 2N257, 2N268, 2N301A, 2N255, 2N554, 2N555, etc. 19 N 1501 Pkg. of 2 Shpg. wt., 8 oz. Net .77

2 PNP GERMANIUM TRANSISTORS AF AMPLIFIERS (Up to 12 Volts)

Pkg. of 2 69¢ Pkg. of 2 PNP Germanium AF amplifier transistors that replace: 2N133A, 2N138A, 2N138B, 2N151, 2N186A, 2N187A, 2N215, 2N217, 2N319, 2N320, 2N359, 2N360-363, 2N407, 2N408, 2N1008, A B GT81R, GT-109, 2S56, 2S838, etc. Shpg. wt., 4 oz.



19 N 2701 Pkg. of 2 Net .69

10 SILICON DIODES

Pkg. of 10 89¢

Package of 10 silicon diodes. Replaces 1N34, 1N34A, 1N43, 1N48, 1N51, 1N60, 1N87, 1N295, etc. Shpg. wt., 4 oz.

19 N 6001 Pkg. of 10 Net .89

2 PNP TRANSISTORS

Pkg. of 2 77¢

Mixer/Oscillator Converter—Replaces 2N112, 2N114, 2N135, 2N136, 2N137, 2N140, 2N219, 2N411, 2N412, 2N414B, 2N415, CK760, CK766, 2S52, etc. Shpg. wt., 4 oz.

19 N 4201 Pkg. of 2 Net .77

STUD-MOUNT SILICON POWER RECTIFIERS

All popular models, 3/16" hexagonal mounting studs. Shpg. wt., 8 oz. per package. Pkgs. of 1, 2 or 4 rectifiers.

2 Ampere Rectifiers as low as .39 pkg. of 2

Stock No. PIV Pkg. of Net

19 N 5007	50	4	.49
19 N 5008	100	2	.39
19 N 5005	200	2	.59
19 N 5006	400	2	.97

12 Ampere Rectifiers

Stock No. PIV Pkg. of Net

19 N 5003	50	2	1.19
19 N 5004	100	1	.77
19 N 4207	200	1	.98
19 N 4208	400	1	1.69

50 Ampere Rectifiers 1 1/4" Hex.

Stock No. PIV Pkg. of Net

19 N 1514	50	1	2.49
19 N 1521	100	1	3.45
19 N 1522	200	1	4.25

PNP AUDIO TRANSISTOR AS LOW AS 24¢

Lots of 100

General audio type PNP transistor for experimenters and hobbyists, for code practice oscillators and similar small signal devices. In new JETC-30 welded case. wt., 2 oz.

19 N 4206 Net, singly, each .29
100 for 24.00

4 PNP GERMANIUM TRANSISTORS

Pkg. of 4 88¢

Package of 4 PNP General Purpose Type Transistors similar in performance to: 2N107, 2N218, 2N1265, CK722, GT222, TR722, 2N1191, etc. Shpg. wt., 6 oz. 19 N 1502 Pkg. of 4 Net .88

2 PNP GERMANIUM IF AMPLIFIER TRANSISTORS

Pkg. of 2 59¢

Pkg. of 2 PNP germanium IF amplifier transistors that replace: 2N111, 2N111A, 2N112A, 2N139, 2N218, 2N409, 2N410, 2N413, 2N413A, 2N414, 2N414A, 2N416, GT760, 2S53, etc. Shpg. wt., 4 oz.

19 N 1504 Pkg. of 2 Net .59

1 TOP HAT SILICON RECTIFIER 59¢

750 Mil 750 PIV

Package of 1 top-hat axial lead silicon rectifier rated 750 millamps, 750 Peak Inverse Volts. Shpg. wt., 4 oz.

19 N 4203 Net .59

GENERAL PURPOSE DIODES

ONLY 10¢

Excellent Detector for Transistor and Vacuum Tube Radio Receivers

EQUIVALENT TO: 100 for 850

1N34 1N34A 1N38A 1N48 1N56 1N69

19 N 4901 General Purpose Diode Net .10 each; 10 for .90

POPULAR POWER TRANSISTORS

MEDIUM POWER TRANSISTORS

Beta=30, BV_{cer}=36 Volts: Shpg. wt., 12 oz. Similar to: 2N155, 2N176, 2N235, 2N242, 2N255, 2N256, 2N301, 2N307, 2N554, AR-5, CTP-1104, TS-176, etc.

19 N 1507 Net ea. .59

In Lots of 100, Each Net .49

HIGH POWER TRANSISTORS

Beta=50; BV_{cer}=36 Volts Min. Shpg. wt., 12 oz. Similar to: 2N157A, 2N176B, 2N235B, 2N257, 2N285A, 2N301A, 2N353, 2N399, etc.

19 N 4205 High Power Transistor Net ea. .69

In Lots of 100, Each Net .59

TRANSISTOR MOUNTING KITS FOR "DIAMOND SHAPE" TO-3 TYPE

Includes Diamond Shape mica washer, 2 round mica washers, 2 steel washers, 1 lug, 2 nuts and transistor socket. Shpg. wt., 4 oz.

19 N 1531 Net .30

FOR "DOOR KNOB" TO-36 TYPE

Includes square mica washer, round mica washer, steel washer, lug and nut. Shpg. wt., 4 oz.

19 N 1532 Net .30

40-WATT HIGH POWER TRANSISTOR 87¢

Amazing value is this 40-Watt high power PNP germanium transistor! Excellent for experimenter, hobbyist and kit builder for power supplies, auto replacement, audio output, etc. Similar to 2N173, CTP1504, SFT266, etc. Bolt mounted. Shpg. wt., 8 oz.



19 N 1503 Net .87

2 NPN TRANSISTORS

Pkg. of 2 59¢

Package of 2 NPN germanium transistors similar to 2N170 for Audio & RF. Beta 20 minimum. Shpg. wt., 4 oz.

19 N 2702 Pkg. of 2 Net .59

10 GERMANIUM DIODES

Pkg. of 10 77¢

Package of 10 germanium diodes that replace 1N34, 1N34A, 1N46, 1N48, 1N51, 1N60, 1N64, 1N87, 1N105, 1N109, 1N147, 1N267, 1N268, 1N295, etc. Shpg. wt., 6 oz.

19 N 1505 Pkg. of 10 Net .77

2 TOP HAT SILICON RECTIFIERS

750 MIL - 400 PIV

Pkg. of 2 79¢

Pkg. of 2 top hat type silicon rectifiers rated at 750 millamps, 400 PIV. Shpg. wt., 6 oz.

19 N 4202 Pkg. of 2 Net .79

PHOTO-MULTIPLIER POWER TRANSISTOR

A COMPLETE PHOTOELECTRIC SYSTEM IN ONE UNIT

179

• Photo Electric Cell
• Power Transistor Amplifier
• Electronic Relay

Complete with Instructions, Data and Diagrams for photo control systems, photo-electronic amplifiers; Relays, Alarms, etc. Shpg. wt., 6 oz.

19 N 1506 Ea. Net 1.79 3 for 4.77

30 MC HIGH GAIN TRANSISTOR

High Quality PNP RF transistor — Excellent for 27MC Citizens Band Walkie Talkie Transceivers, etc. 30 to 35 MC. Average Beta — 25. Shpg. wt., 6 oz.

19 N 4211 ea. Net .59

Lots of 10 ea. Net .53

Photocells And Experimenter Items

CADMIUM SULPHIDE PHOTOCELL



1.59

- For Sensitive Relay Actuation
- For Photo Electric Control

A neatly constructed crystal photocell that has countless applications in counting, relay actuation, etc. Resistance varies with light from 1 megohm in total darkness to approx. 1500 ohms at 100 foot candles. Responds to entire visible spectrum and has 1/10 sec. response for relay operation. Minimum current output 60 ma at 50 ft. candles at 90 volts. Power dissipation 2 watts for 5 seconds, 1/2 watt continuous. Output as low as .08 ma at 1 ft. candle at 6 volts, varying with illumination intensity and applied voltage. Neatly capsulated for easy mounting with leads for electrical connection. 1 1/4 x 1/2 x 1/8" overall. Shpg. wt., 4 oz. Imported. 24 N 8827 Net 1.59


LAFAYETTE SUPER-VALUE SUN BATTERY

1.29

- Excellent for Experimenter, Kit Builder, etc. 0.27 ma Output at 100 ft. Candles

Specifications: 0.9 ma Current Output at 100 ft. candles with 100 ohm load; 0.27 ma Current Output at 100 ft. candles with 1000 ohm load. 1 1/2" diameter. With colored pigtail leads. Shpg. wt., 3 ozs. Imported. 99 N 6318 Net 1.29

SELF GENERATING SELENIUM PHOTOELECTRIC CELLS



As Low As 53¢

- Complete with leads
- No external power needed
- Output in sunlight up to 60 MA
- Up to 750 µa at 100 ft. Candles

Sensitive to a wide spectrum including white, colored or ultra-violet light. All unmounted; complete with leads. Outputs in table below taken at 100 foot candle illumination with 100 ohm load. Shpg. wt., 3 oz. Imported.

Stock No.	Out µa	Size	NET EACH	
			1-4	5-9
99 N 6243	100	1 1/4" x 3/4"	.59	.56
99 N 6244	250	1 1/4" x 3/4"	.69	.66
99 N 6245	350	1 1/4" x 3/4"	.89	.85
99 N 6246	750	1 1/4" x 1 1/8"	2.80	2.66

LAFAYETTE CADMIUM SULPHIDE PHOTOCELL

• Only 95¢

New head-type window cadmium sulphide photocell. Maximum Ratings: 200 volts DC or AC peak. Temperature is -40°C and +60°C; Resistance is over 10 megohms at zero ft. candles, 100,000 ohms to 10 megohms 1 foot candle, 100,000 to 350,000 ohms at 10 foot candles; Range of sensitive wave length is 4000 to 8000 angstroms. Size: 3/4" diam. x 1/4" L. o/a. Standard screw mount; miniature base. Imported. 99 N 6309 Shpg. wt., 4 oz. Net .95

SELENIUM PHOTOCELL



- Excellent for Burglar Alarms
- Door Openers
- Counters

OPERATES 600 MICROAMPS RELAYS DIRECTLY

Barrier layer, self-generating type; light striking upon cell generates current sufficient to operate relays that pull in at 600 microamps directly without the use of auxiliary power. Lifetime of cell is unlimited. 600 microamperes output at 100 foot candles, 2 inches in diameter. Mounted in a handsome plug-in plastic case. Imported. 99 N 6305 Photocell, Wt., 8 oz. Net 4.95 32 N 2041 Socket for above Net .14



RESISTOR PHOTOCELL 89¢

A cadmium-sulphide light-activated resistor used to actuate door openers, burglar alarms, relays, light controls, production counters, etc. Resistance varies from 75 ohms at approx. 93 foot-candles to over 10 megohms in total darkness. Maximum volts: 110VAC (peak) 110VDC; maximum dissipation: .2 watt @ 40°C, .1 watt @ 50°C, 0 @ 60°C. Capacity approx. 6 mmf. 1/2" diam. x 3/8" thick. Shpg. wt., 3 oz. Imported. 19 N 2101 Net .89

LAFAYETTE CADMIUM PHOTOCELL



1.19 • 3/8" Light Area

A quality cadmium photocell, perfect for transistor and printed circuit use. Employs sensitive film element with 3/8" light area. Rated at 200V; 10ma; 0.1W power dissipation @ 20°C. Sensitivity is 610±50. Resistance Value Characteristics — 0 Ft. Candles: 2M ohms/up; 1 Ft. Candles: 100K ohms; 10 Ft. Candles: 25K ohms; Size 3/4" Diam. x 1/4" Depth. Imported. 99 N 6315 Net 1.19

PERFORATED COPPER-CLAD AND UNCLAD BOARDS

- Ideal For Transistor And Subminiature Circuitry

These sturdy, perforated boards are the ideal base for builders, experimenters, and labs to mount miniaturized components. Two types available; either high grade bakelite for wired circuits, or one side copper-clad for "printed" circuitry. Holes are 3/16" diameter with 3/16" between hole centers. All boards are 1/8" thick. For contacts, the MS-263 flea clips listed on this page are ideal. Avg. shpg. wt., 6 oz.

COPPER CLAD BOARDS

Stock No.	Size	No. of Holes	Net Each Lots of		
			1	100	250
19 N 3601	2 1/4" x 3 3/8"	17x12	.35	.30	.24
19 N 3602	3 3/8" x 6 3/4"	35x19	.55	.50	.45
19 N 3603	7 3/4" x 6 3/4"	39x35	1.15	.96	.87
19 N 3604	10 1/2" x 7 3/4"	56x38	1.90	1.58	1.42

UNCLAD BOARD

Stock No.	Size	No. of Holes	Net Each Lots of		
			1	100	250
19 N 3605	2 1/4" x 3 3/8"	17x12	.25	.20	.18
19 N 3606	3 3/8" x 6 3/4"	35x19	.45	.40	.35
19 N 3607	7 3/4" x 6 3/4"	39x35	.75	.65	.60
19 N 3608	10 1/2" x 7 3/4"	56x38	1.20	1.08	.97
19 N 3609	18 x 7 3/4"	95x38	1.89	1.71	1.55



FLEA CLIPS FOR TRANSISTOR AND SUBMINIATURE CONTACTS

"Flea" clips are specially designed for subminiature work. Fit perfectly in holes in perforated copper-clad and unclad boards listed above. Made of beryllium copper, silver plated finish. Simply insert wire thru hole for positive grip contact.

19 N 3301	Package of 12	Net .25
19 N 3302	Package of 1000	Net 15.75
19 N 3303	Package of 5000	Net 76.15
19 N 3304	Package of 10,000	Net 149.30

An Exclusive Lafayette Publication



PHOTOCELL APPLICATIONS by RUFUS P. TURNER

1.50

84 Pages . . . over 46 circuits . . . Illustrated 7 Chapters covering Test Instruments, Relays, Control Devices, Communications and Experimental.

Here is an exciting book for the experimenter, Ham, or Technician interested in the world of photocells and their uses. 12 photocells and a photo transistor are utilized in over 46 practical circuits fully illustrated and documented with complete parts lists. All parts for construction are readily available from Lafayette. These are the 7 interesting chapters.

- (1) Photoelectric Devices and Characteristics-Photoelectric action, Basic Connections, Specifications etc.
- (2) Test Instruments — Various Types of Light Meters; Turbidity Meter, Wattmeter, Tachometer etc.
- (3) Signal Generators — AF & RF Oscillators, Frequency Standard, Spinning Disc Tone, Generator etc.
- (4) Photoelectric Relays — Photovoltaic Relays, Phototransistor Relay, Power line operated AC and DC Relays etc.
- (5) Control Devices — Light-coupled Incandescent Switch, Light-coupled Neon Photocell Switch, Photoelectric Potentiometer etc.
- (6) Communications Devices—Sun Powered Broadcast Receiver, Sun Powered Transistor Receivers, Sun Powered Tunnel Diode Transmitter, etc.
- (7) Miscellaneous and Experimental—Sun Powered DC Motor, Light Monitor, DC Voltage Amplifier etc.

10 N 0102 Shpg. wt., 4 1/2 oz. Net 1.50

Experimenter Quality Components

COILMASTER DELUXE

ACCURATE
COIL
WINDER


675



Latest redesigned model gives even greater accuracy than ever to meet modern requirements. Easy-to-use set winds honeycomb, spiderweb and solenoid coils of various widths and diameters—equal in appearance to a factory job. Also suitable for winding chokes, transformers and filter inductors. Indicator counts number of turns on coil. Supplied with accessories including wood spools, metal pegholders and extension for making long solenoid coils. Instructions included, but less coil form and pegs. Shpg. wt., 6 lbs.

32 N 8701 Net 6.75

MINIATURE TRANSISTOR TRANSFORMERS



- Truly Miniature—Only $\frac{3}{4} \times \frac{3}{8} \times \frac{3}{8}$ "
- Matches Any 3.2 Ohm Speaker
- Excellent For Receiver Replacement Transistor Output
- Transistor Output Transformer

Popular transistor output transformer for 3.2 ohm speakers. May be used either single-ended or push-pull. Wound on nylon bobbins with mylar outer wrap with laminations on nickel-steel and silicon-steel. Rated power is 100 milliwatts. Primary impedance is 500 ohms. Center-tapped and secondary 3.2 ohms. DC resistance of primary is 20 ohms and secondary is .3 ohms. Color coded leads. Net wt., $\frac{1}{4}$ oz. Shpg. wt., 4 oz. Imported.

99 N 6123 Net .89

TRANSISTOR DRIVER TRANSFORMER

Single-ended transformer for driving transistor power-stage. Impedances 10-000 ohms pri., 2000 ohm C.T. sec.; dc res. 500 ohms pri., 50 ohms sec. 1.5 ma. dc unbalanced pri. current. Rated 100 mw. $\frac{3}{4} \times \frac{3}{8} \times \frac{3}{8}$ ". Shpg. wt., 4 oz. Imported.

99 N 6124 Net .89

LAFAYETTE HIGH SENSITIVITY METER RELAY




- METER MOVEMENT
- CLOSURES CIRCUIT AT 2 MILS

Extremely sensitive meter type relay. Normally open. Ideally suited for uses with model railroad, photoelectric relay circuit, babyfenders, remote control toys, remote control boats, fire alarm, and many other practical applications. Precision-built meter movement provides virtually friction-free movement. Contact will close at 2 milliamperes. Internal resistance 100 ohms. Meter movement rated 5 ma continuous, 10 ma momentary; contacts rated 500 ma continuous, momentary 1 amp at 3v and 250 ma at 6v with resistive load. Sensitivity: 2.5-.6 mw. Internally adjustable. Relay is enclosed entirely and transparent cover permits observation. Solder pins are placed externally for easy connections. Size: $1\frac{3}{4} \times 1\frac{1}{2} \times 1\frac{3}{4}$ ". Shpg. wt., 8 ozs. Imported

99 N 6199 Net 3.95

TRANSISTOR OUTPUT TRANSFORMERS RATED 150 MW



Here is an outstanding value in the most popular transistor output transformer for 10 to 11 ohm speakers. Rated power is 150 milliwatts. Primary impedance is 400 ohms, center-tapped and secondary 11 ohms. DC resistance of primary is 20 ohms and secondary .9 ohms. Size: $\frac{3}{4} \times \frac{3}{8}$ ". Shpg. wt., 4 ozs. Imported

99 N 6209 Net .89

100 MW TRANSISTOR DRIVER TRANSFORMER

Primary impedance 20,000 ohms. Secondary impedance 1000 ohms. DC resistance of primary 400 ohms, of secondary 50 ohms. Unbalanced primary current 1 ma DC. Rated 100 mw. Size: $\frac{3}{4} \times \frac{3}{8} \times \frac{3}{8}$ ". Shpg. wt., 4 ozs. Imported.

99 N 6002 Net .89

BAKELITE CASES and PANELS

Ideal for building test equipment and small electronic devices. All black bakelite with rounded corners and recessed threaded inserts for mounting panels. Walls $\frac{1}{8}$ " except * is $\frac{3}{16}$ ". Avg. shpg. wt., 11 oz.



Stock No.	Size	Net Each	
		1-4	5-UP
19 N 2001	6 $\frac{1}{4}$ x 3 $\frac{1}{2}$ x 2"	.65	.59
19 N 3701	Panel for above	.39	.36
19 N 2002	6 $\frac{3}{8}$ x 5 $\frac{1}{4}$ x 2 $\frac{1}{4}$ "	1.20	1.08
19 N 3702	Panel for above	.60	.54
19 N 2003	8 $\frac{3}{8}$ x 7 $\frac{3}{8}$ x 3"	1.59	1.43
19 N 3703	Panel for above	.75	.69

REPLACEMENT 5,000 OHM VOLUME CONTROL FOR JAPANESE TRANSISTOR RADIOS

With S.P.S.T. switch. Only $\frac{5}{8}$ " dia., $\frac{1}{2}$ " total depth. Comes with $\frac{1}{16}$ " dia. knob. Shpg. wt., 2 ozs. Imported.




99 N 6019 Net .59

SUBMINIATURE TRANSISTOR AUDIO TRANSFORMERS ONLY $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{1}{2}$ "

A new series of miniature transformers for transistor and experimental miniature circuits. Ideal for miniature radio receivers, amplifiers, hearing aids, etc., using standard transistors. Incorporate special heat-treated high permeability magnetic cores treated to resist corrosion. Designed for improved frequency response with low distortion. 3" color-coded leads. Average shpg. wt., 4 oz. Imported

ONLY
79c




Stock No.	Circuit	Impedance		O.C. Resistance		Sec. Ohms	Net
		Pri. Ohms	Sec. Ohms	Pri. Ohms	Sec. Ohms		
99 N 6125	INPUT	100,000	1000	1000	1000	1000	.79
99 N 6126	DRIVER	10,000	2000 C.T.	240	60 C.T.	60 C.T.	.79
99 N 6127	OUTPUT	500 C.T.	3.2	42 C.T.	0.7	0.7	.79
99 N 6034	INPUT	200,000	1000	1400	50.5	50.5	.89
99 N 6129	OUTPUT	500 C.T.	8	50 C.T.	1.7	1.7	.79

TINY TUNING CONDENSER—with DIAL

- 365 MMF.
- ONLY 1" SQUARE, $\frac{1}{8}$ " DEEP
- POLYETHYLENE DIELECTRIC
- FOR TRANSISTOR & MINIATURE CIRCUITS

A new "Poly-Vari-Con" model for use in TRF broadcast-band and experimental receivers. Complete with good-looking clear plastic tuning dial with calibrations from 530 to 1600 KC. Capacity variable from 10 to 365 mmf. Knurled dial is $1\frac{1}{4}$ " diam.; rotation is 180°. Dial is mounted to condenser shaft by $\frac{3}{16}$ " diam. chrome-plated threaded retainer. Shpg. wt., 5 oz. Imported.

99 N 6217 Net .59




TRANSISTOR MINIATURE 2 GANG SUPER-HET VARIABLE CONDENSER

Lightweight—both the frame and plates are aluminum. Smooth ball bearing action over entire 180° rotation. Bakelite stator insulation. Capacity of 11 plate R.F. section is 6.3 to 123.1 mmfd; 9 plate oscillator section is 5.7 to 78.2 mmf. Effective range of trimmers 15 mmf. These add 2 mmf to minimum capacity. Capacity increases in counter clockwise direction. Flatted shaft, $\frac{1}{4}$ " diameter by $1\frac{1}{4}$ " long.

Frame size only $1\frac{1}{2} \times 1\frac{3}{8} \times 1\frac{1}{2}$ " H. Shpg. wt., 5 oz.

32 N 1106 Net .95



TRANSISTOR LOOP ANTENNA AND OSC. COIL LOOP ANTENNA

A loop antenna with a primary inductance of 700 microhenry, especially designed with the proper tap to match the input impedance required in transistor circuits. Covers the entire broadcast band from 540-1650 KC when used with latest miniature type variable condensers such as used in G.E. Regency and other subminiature sets. (Lafayette 32 N 1106 is ideal). Requires maximum capacity of 123 mmf in RF section of variable condenser. Wound on high efficiency iron core 4" long x $\frac{1}{4}$ " diam. Shpg. wt., 4 ozs.

32 N 4101 Net .95 In lots of 6, Each .89
32 N 4102 Matching Oscillator Coil. In lots of 6, Each .79



Osc. Coil

Singly, Each .89

Quality Radio Marine Equipment

Hartman 30 WATT TRANSISTORIZED MARINE RADIO TELEPHONES



As Low As
199⁵⁰
\$10 Monthly
With Mike
(Crystals Extra)

- 30 Watts Input
- 4 Channels Plus Broadcast
- 30-mile Range Ship-to-Ship
- 50-mile Range Ship-to-Shore

New "Hurricane 30" 30 Watt Marine Radio Telephone

The "Hurricane 30" features maximum transistorization for minimum power drain. Full 30 watts input assures reliable communications at all times. And you get four channels—two ship-to-ship channels, one emergency coast guard, one Marine Telephone Operator, plus standard broadcast reception. Neat front panel has performance meter for achieving best power setting, plus Automatic Noise Limiter. Lifetime Melamine wood-grain cabinet is completely moisture-fungus proof. Includes carbon push-to-talk microphone, built-in 6" speaker. Dimensions: 8½Dx13½Wx7¼"H. Shpg. wt., 19 lbs.
40 N 7203WX H-30 Standard Radio Telephone Net 199.00
Crystals for H-30—specify area crystals required. Net 10.00
40 N 7205Y

H-30 Deluxe Marine Radio Telephone Package

This is the same precision quality deluxe radiotelephone listed above but includes everything necessary for installation: Deluxe center-loaded whip antenna with stand-off bracket and chrome-plated brass swivel-based lay-down hardware, wire harness for power and antenna leads, all crystals, mike, mounting hardware. Choice of wood-grain lifetime melamine cabinet to match the interior of your boat.
Deluxe H-30 Marine Radio Telephone Package—Specify area crystals required. Shpg. wt., 25 lbs.
40 N 7204WX \$15 Monthly Net 299.00

NEW HARTMAN "HURRICANE 100" 100 WATT TRANSISTORIZED MARINE RADIO TELEPHONE



- 100 Watt Input
- 8 Channels Plus Broadcast
- Squelch & Automatic Noise Limiter

365⁰⁰
\$19 Monthly

NEW HARTMAN HAILER/POWER LISTENER



PERFECT FOR:

- Hailing
- Power Listening
- Foghorn
- Prowler Alarm

99⁵⁰
\$5 Monthly

A fully transistorized 12-volt unit with numerous shipboard applications. Features exclusive DYNA-MIKE Microphone Speaker Combination—push to talk for hailing... release for power listening. Deep, powerful tone of the rugged loudspeaker with 360° swivel base carries over a mile with clarity. The Super-Sensitive amplifier picks up normal speaking voices on neighboring boats or docks hundreds of yards away. Has powerful manual foghorn with adjustable volume pitch for use in emergency weather. Can also be used as prowler alarm when ship is moored... protects your boat from vandals. Easily installed. Meets U.S. Coast Guard Class 1 regulations. Shpg. wt., 13 lbs.
40 N 7206WX Hartman Standard Hailer/Power Listener Net 99.50

A 100-watt deluxe radio telephone that is uniquely designed and is constructed to the highest standards. Transistorized for low battery drain and extremely compact. Unit comes with telephone-type handset and wood-grain lifetime melamine cabinet that is completely moisture-fungus proof. Neat front panel has performance meter for achieving best power setting. Also has standard broadcast dial as well as 8-channel selector. Features Automatic Noise Limiter and Squelch circuits for quiet reception. Dimensions: 8½Dx13½Wx7¼"H. Shpg. wt., 21 lbs.
40 N 7207WX Hurricane 100 Net 365.00
Crystals for Hurricane 100—Specify area crystals required. Net 10.00
40 N 7205Y

HARTMAN MC-62 SOLID STATE SHIP-TO-AUTO CONVERTER



19⁹⁵

- Coast Guard • Marine Telephone
- Ship-to-Ship Broadcast • WWV (weather) • Ship-to-Shore Conversations

Now you can listen to marine broadcasts on your car radio. A flick of the switch and your auto radio becomes a powerful, long-range marine receiver. Switch back and it plays the normal broadcast band. All-transistor circuitry uses only 1/2000 of an amp from built-in battery; virtually the battery's entire shelf life. Converter selects any frequency between 2000 KV and 3000 KC. Operates with either 6V or 12V automobile ignition system. Shpg. wt., 2 lbs.
40 N 7202 Net 19.95

ANTENNA SPECIALISTS MARINE WHIP ANTENNA MODEL ASP-194



33⁴²
\$5 Monthly

- For 2000-2830KC
- Heavy Gauge Aluminum

A center-loaded vertical whip antenna for the marine frequency range of 2000 to 2830KC. Designed to operate with any type of marine radio telephone. Built to withstand high winds and corrosion. Mounting brackets attach to cabin or any flat vertical surface. Overall height is 12 ft. 9 inches including stainless steel whip. 21" loading coil is covered with epoxy resin. Mast is 6 feet long, made of 1" O.D. heavy gauge anodized aluminum tubing. Shpg. wt., 6 lbs.
42 N 1028WX Net 33.42

Sonar D-120B DEPTH INDICATOR



139⁵⁰
\$7 Monthly

- Reads Up To 250 Feet
- 360°, 4" Scale With 1-Foot Calibrations
- One-Piece, Non-Magnetic Construction

Highly sensitive, extremely accurate depth indicator for bulkhead mounting. Measures from 1 to 250 feet. Easily installed—even while boat is in water. Requires 6 or 12 VDC. Size: 11¼Wx7½Hx7½"D. Complete with transducer, gimbal and fairing block. Shpg. wt., 10 lbs.
40 N 4312CW Specify 6 or 12 v Net 139.50

SEA SNARK DAY SAILER

- Unsinkable • Lightweight
- Full Size: 11 Foot Length
- One-Piece Molded Construction
- Polystyrene Hull—No Painting Required

Complete, Ready For Fun,
With Red-Striped Nylon Sail,
Daggerboard, Tiller And Fittings

Only
99⁷⁵
\$5 Monthly

Beginner and Expert alike can discover the Fun of sailing with the compact Sea Snark. Fast, trim, easy to sail cat rig. Unsinkable! The snark is made of one-piece tough expanded polystyrene material approved by the Coast Guard for use in life preservers. Care free maintenance, never needs painting, scraping or caulking 30 lb. featherweight bulk is easy to carry from car top to beach. Stores in 12" of space against an attic, garage or basement wall. Beam 38". Seamless aluminum mast, spar and boom. Sail area. 45 sq. ft. Wood parts finished in Spar varnish. Sailing book included. Shpg. wt., 62 lbs. Shipped F.O.B. Rockville, Conn. No C.O.D. Send Full remittance to Lafayette with order. Shpg. charges collected on delivery.

12 N 4901WXY Net 99.75
Same as above, except with unpainted hull, ready for Fiberglassing. Complete with Fiberglass kit, instructions. Shpg. wt., 73 lbs.
12 N 4902WXY Net 109.75



3-STEP ALUMINUM FLOATING LADDER

- Universal Hook Fits 7" to 11" Gunwales
- only **5⁹⁹**



Heavy duty tubular aluminum boat ladder with sealed air that keeps ladder afloat if it drops overboard accidentally. Standoff legs adjust to fit contour of hull, prevents slap. Universal hook is vinyl-sheathed to prevent marring or scratching rail, sure grip. Fits gunwales 7" to 11". 36 1/2" long. Shpg. wt., 4 lbs.

12 N 5303 Net 5.99

ALL-PLASTIC BILGE PUMP

- Non-Corrosive
- Self-Priming
- Floats
- Pumps 10 Gallons Per Minute



Constructed of durable rust-proof, polyethylene. It Floats. Double-action valve maintains a steady water flow—pumps 10 gallons per minute. 25 1/2" L. 18" extra spout for deeper hulls.

12 N 5301 Shpg. wt., 1 lb. Net 3.99

DRY CHEMICAL FIRE EXTINGUISHER

- 2 3/4 lb. Capacity
- Rated 6 B:C Coast Guard, IGC, Marine Testing Institute and UL Approved
- Built-in Pressure indicator

8⁹⁵



Powerful 2 3/4 lb. pressurized extinguisher meets marine and other requirements. Simple, low cost recharging. Easy one-hand operation. Built-in pressure indicator can be read at a glance. Non-toxic dry chemical won't injure fabrics etc. Tamper-proof lock. Meets Coast Guard and ICC. specifications. U.L. listed. Rated 6 B:C. Corrosion resistant construction. 14x3" diameter. Shpg. wt., 5 lbs.

14 N 4500 Net 8.95

AQUA-AID

Only
4⁵⁹



- The Safe Way to Water Play
- Reusable
- Supports Fully Clothed Person

Swimming, skiing, boating or fishing, Aqua-Aid will make these water sports safer. Wear it on wrist or belt—in emergency press button and replaceable CO₂ cartridge inflates float instantly. Holds up a fully clothed person for hours. Light and compact, does not restrict movement. Tough polypropylene case has built-in hinge . . . lasts for years. Protects vinyl air float snags or punctures. 1 1/2" nylon wrist band. Brightly colored float for greater visibility. Includes 2 CO₂ cartridges. Shpg. wt., 1 lb.

12 N 5602 Net 4.59
12 N 5601 Pkg. of 6 CO₂ cartridges Net 1.69

MARINE DISTRESS SIGNAL KIT

- For Day or Night Use
- only **3³⁵**



A must for every boat. Practical distress signal kit can be stored on your boat indefinitely, always ready for emergency use. Waterproof package kit contains (3) 10-shot signals, (2) 10-minute flares, (1) sea whistle, (1) fluorescent dye marker, (1) package waterproof matches and (2) launching handles. Shpg. wt., 2 lbs.

12 N 5302 Net 3.35

50 FT. NYLON ROPE



100% genuine twisted Nylon rope. Excellent for all marine, workshop, farm and camping purposes. Tensile strength 1,800 pounds. Size: 1/4" 100 Feet. Shpg. wt., 2 lbs.

12 N 5900 Net 2.39

2³⁹

QUALITY OUTBOARD MOTORS

- Compact • Lightweight
- Powerful
- Ideal for Trolling

Made in U.S.A.

3 H.P.
SKIPPER 300

6 H.P.
GOLDEN JET 600

GOLDEN JET 600, 6 H.P. only 31 pounds with balanced front and rear ladle for easy carrying and Short 40 inches fits in any car Trunk. Precision quiet air cooled engine throttles down for slow trolling. Full 360 pivot. Automatic rewind starter. Submersible parts salt resistant aluminum. 6" propeller. Shpg. wt., 40 lbs.

12 N 3101WXY Net 99.95

SKIPPER 300, 3 H.P. Similar to above. weighs only 27 lbs. Runs as low as 1 to 2 mph. Shpg. wt., 31 lbs.

12 N 3102WXY Net 69.95

Shipped F.O.B. Dubuque, Iowa. No C.O.D. Send Full remittance to Lafayette with order. Shpg. charges collected on delivery.



99⁹⁵

\$5 Monthly

69⁹⁵

\$5 Monthly

Deluxe LAFAYETTE FM Communications Receivers

MONITOR CALLS FROM STATE, COUNTY AND MUNICIPAL POLICE — FIRE DEPARTMENT —
— CIVIL DEFENSE — RAILROADS — TRUCKING — HIGHWAY MAINTENANCE — FORESTRY
CONSERVATION — PETROLEUM AND INDUSTRIAL ACTIVITIES



Model HA-50 30-50 MC
Model HA-52 152-174 MC

- Variable Squelch
- Solid State Power Supply
- Extremely Sensitive Circuitry
- Built-in 4" Speaker
- 8 Tubes for 10-Tube Performance
- Nuvistor Front End*

59⁹⁵
\$5 monthly

Two deluxe FM communications receivers for the office, field or home. Excellent sensitivity of 4 μ v or less for 20 db quieting and built-in adjustable squelch for dependable all-day monitoring of emergency, commercial, or industrial communications. Both units feature 3 IF stages and fully tuned RF stage. Model HA-52 incorporates 6CW4 nuvistor "front-end". A built-in 4" speaker gives clear voice reproduction . . . and as a special feature a front panel phone jack may be used for private listening. Large, easy-

to-read slide rule dial is illuminated for night operation. Housed in attractive blue-grey metal cabinet . . . makes a handsome addition to any home or office. Power requirements: 117 volts AC at 50/60 cps. Size: 11 $\frac{1}{4}$ "x5 $\frac{1}{4}$ "x7 $\frac{3}{8}$ ". Shpg. wt., 14 lbs. Imported. *Model HA-52 Only.

99 N 2525WX Model HA-50 30-50 mc Net 59.95
99 N 2526WX Model HA-52 152-174 mc Net 59.95

OUTERCOM MINI-MOD FM POCKET TWO-WAY RADIO 1 WATT (OUTPUT) TRANSISTORIZED MODULAR WALKIE-TALKIE



46500
\$24 Monthly

Ideal For FCC Licensed High Band Communications (134-174) In Public Safety, Business And Industrial Communications

- Practically Indestructible
- Solid-State Design With Plug-in Module Circuitry
- Maintenance In Seconds
- Epoxy Sealed Modules

Designed for dependable 2-way radio communications. Also makes an excellent portable add-on to your present FM 2-way radio system. Completely transistorized, uses rugged long-life transistors and epoxy sealed plug-in modules, which keep out moisture dust and abuse. Low maintenance costs . . . modules are easily replaced when necessary. 1 Watt RF power output delivers greater talk-back range. Provides up to 500 MW of audio power for clear message reception, even in noisy areas. Long battery life. Transmitter frequency stability \pm .0005%. Sensitivity .5 mv for 20db quieting, with adjustable squelch. Compact, only 3 $\frac{1}{4}$ "x8 $\frac{1}{2}$ "x1 $\frac{1}{4}$ ". Shpg. wt., 2 $\frac{1}{2}$ lbs.

8 WEEKS DELIVERY TIME ON TRANSCEIVER. CASE, HOLSTER, NICKEL-CADMIUM BATTERY PAK.


SPECIFY FREQUENCY

42 N 2402 Less Battery	Net 465.00
Mercury Batt. 6 Req.	
33 N 1416	Ea. Net 1.22
42 N 2403 Leather Carrying Case	Net 14.00
42 N 2400 Leather Holster	Net 7.25
42 N 2401 Nickel Cad. Batt. Pak	Net 64.00

124 Lafayette Cat. No. 653

DELUXE LAFAYETTE HA-55 AIRCRAFT RECEIVER

*Listen To Aviation Control
Towers and Aircraft*




59⁹⁵
\$5 monthly

- Monitors Aircraft Frequencies from 108 to 136 Mc
- 8 Tubes for 11-Tube Performance
- Two RF Stages with A 6CW4 Nuvistor For High Sensitivity
- Solid State Power Supply
- Built-in Adjustable Squelch
- Illuminated Slide Rule Dial For Night Operation
- Built-in 4" Speaker With Front Panel Phone Jack

Now monitor the exciting frequencies of aircraft communications in your home or office with this deluxe receiver. The use of multi-purpose tubes gives 11 tube performance offering high sensitivity and selectivity. Two RF stages including a 6CW4 nuvistor really pulls in the stations. A variable squelch adjustable from front panel facilitates absolute quieting. A built-in 4" speaker provides excellent voice reproduction, and a front panel phone jack makes private listening possible. Large, easy-to-read slide rule dial is illuminated for night operation. Attractive blue-grey metal cabinet. For 117 volts AC at 50/60 cps. Size 11 $\frac{1}{4}$ "x5 $\frac{1}{4}$ "x7 $\frac{3}{8}$ ". Shpg. wt., 14 lbs. Imported.

99 N 2527WX Model HA-55 108-136 mc Net 59.95

MONITORADIO FM MOBILE RECEIVERS



114⁹⁵
\$6 Monthly

- M-40; Tunable 30-50 MC
- M-160; Tunable 152-174 MC

High quality mobile receivers for governmental, municipal and industrial uses. These tuneable receivers cover the entire FM communications bands with excellent sensitivity. 10 tube circuit features a fully tuned RF amplifier, dual conversion, and two stages of limiting followed by the discriminator. Power output is 8 watts, built-in 4" speaker. For 12v. DC 3.9 amperes. Housed in attractive cabinet, only 4 $\frac{1}{2}$ "x6 $\frac{1}{2}$ "x8 $\frac{3}{4}$ ". Shpg. wt., 10 lbs.

MODEL M-40 Tunable over 30-50 MC band. Net 114.95
40 N 6001WX
MODEL M-160 Tunable over 152-174 MC band. Net 114.95
Sensitivity 4 μ v for 20 db quieting. Wt. 12 lbs.
40 N 6003WX Net 114.95

Boston, Mass. 584 Commonwealth Avenue

LAFAYETTE RADIO ELECTRONICS

All mail orders to: P. O. BOX 88 SYOSSET, L.I., N.Y. 11791

**"ASSOCIATE STORE"
DEALER LOCATIONS**

Lafayette Radio Electronics "Associate Store" Dealers own and operate their own stores as independent franchised dealers. They establish their own terms and prices, which may vary slightly and do not handle mail orders.

ATHENS 120 N. Marion St. BIRMINGHAM 9 North 77 St. FLORENCE U.S. Hwy. 43 & 72 at Shoals Creek HUNTSVILLE 2112 Memorial Pkwy So. MOBILE 174 So. Ann St. NOGALES ARIZONA 136 Grand Ave. N. LITTLE ROCK ARK. 1920 Pike Ave. BAKERSFIELD CALIF. 626 Bernard St. BUENA PARK 6186 Beach Blvd. CULVER CITY 8553 Washington Blvd. FRESNO 4510 E. Belmont SAN CLEMENTE 220-B So. Ola Vista Rd. SAN DIEGO 472 3rd Ave. & Island SAN FRANCISCO 271 9th St. SUNNYVALE 942 W. El Camino Real VAN NUYS 13630 Sherman Way BRIDGEPORT CONN. 2710 Fairfield Ave. GROTON 565 Long Hill Road HAMDEN 913 Dixwell Ave. WATERBURY 386 W. Main St. NEW CASTLE DEL. 1420 Dupont Blvd. Wilmington Manor EAU GALLIE FLA. 418 Harbor City Blvd. (U.S. Hwy. #1) FT. LAUDERDALE 2534 N. Federal H'way. GAINESVILLE 101 S. E. 1st St. JACKSONVILLE 1905 Hendricks Ave. LAKE WORTH 213 N. Dixie H'way N. MIAMI BEACH 346 NE 167 St. (Hwy. 17 & 92 North) ORLANDO 1225 No. MHI St. PENSACOLA 727 N. Warrington Rd. ST. PETERSBURG Central Ave. & 40 St. TALLAHASSEE 505 W. Gaines St. TAMPA 3328 Henderson Bl. VERO BEACH 862 20th Place	ALA. ATLANTA 512 W. Peachtree N.W. COLUMBUS 2611 Lumpkin Rd. HONOLULU HAWAII 1336 Dillingham Blvd. IDAHO FALLS IDAHO 1363 N. Yellow- stone Ave. PEORIA 706 Wayne St. RANTOUL 421 S. Century Blvd. SPRINGFIELD 1413 S. 11 St. FORT WAYNE IND. 3101 N. Clinton St. INDIANAPOLIS 4730 E. 10 St. SIoux CITY IOWA 500 W. 7th St. HUTCHINSON KANS. 508 East Fourth St. OVERLAND PARK 7202 W. 79 St. SALINA 314 West Cloud WICHITA 220 W. Harry St. MADISONVILLE KY. 2408 South Main St. MIDWAY 125 E. Main ALEXANDRIA LA. 1306 Murray St. BATON ROUGE 2610 Florida Blvd. NEW ORLEANS 2231 Banks St. LEWISTON MAINE 131 Lisbon Street ROCKLAND 464 Main St. BALTIMORE MD. 2014 N. Charles St. BEL-AIR 139 Thomas St. SALISBURY 819 Priscilla St. AYER MASS. 45 Groton-Harvard Rd. BROCKTON Westgate Shoppers Park, Rtes. 27 & 24 SPRINGFIELD 461 Sumner Ave. at the "X" WORCESTER 23 Foster St. ANN ARBOR MICH. 3382 Washtenaw Ave. BAY CITY 408 E. Midland St. BIRMINGHAM 315 Hamilton Ave. DETROIT 1326 Broadway FLINT 100 W. Flint Park Blvd. GRAND RAPIDS 7 Burton St., S.E.	GA. IRONWOOD 114 S. Lowell St. KALAMAZOO 519 Mills St. LANSING 805 W. Holmes Rd. PORT HURON 1503 24th St. MINNEAPOLIS MINN. 7815 Southtown Ctr. BILOXI MISS. 3305 Pass Rd. COLUMBUS 1828 Highway 45 No. HATTIESBURG 1106 Hardy St. TUPELO 917 So. Gloster ST. LOUIS MO. 6431 Hampton Ave. GREAT FALLS MONT. 210 4th St., South OMAHA NEB. 4720 S. 24 St. CLAREMONT N. H. 222 Washington St. Shopping Plaza KEENE 55 Main St. Medical Hall Bldg. MANCHESTER 40 Bridge St. SALEM Rte. 28 at H'way 93 ASBURY PARK N. J. 1109 H'way No. 35 CAMDEN 5057 Rte. 38 RIO GRANDE Marlyn Manor Shopping Center, TRENTON 4 Brunswick Circle Extension ALBUQUERQUE N. MEX. 11017 Central, N.E. ALBANY N. Y. 79 Central Ave. BUFFALO 747 Main St. DRYDEN 14 W. Main St. ELMIRA 601 East Church St. POUGHKEEPSIE 105 Dutchess Tpke. ROCHESTER 792 W. Main St. SCHENECTADY 141 Erie Blvd. SYRACUSE 2740 Erie Blvd. E. UTICA 1415 Oriskany St. West VESTAL 253 Vestal Pkway., East WELLSVILLE 50 No. Main St.	MICH. CHARLOTTE NO. CAR. 1310 N. Independence Blvd. FAYETTEVILLE 2733 Bragg Blvd. MORGANTON 407 So. Sterling St. AKRON OHIO 34 North Main CINCINNATI 606 Walnut St. CLEVELAND 2001 Euclid Ave. COLUMBUS 122 E. Long St. LOGAN 31 E. Main St. PROSPECT Highway 318 SPRINGFIELD 217 N. Belmont STEUERENVILLE 411 Washington St. STRONGSVILLE 14484 Pearl Rd. TOLEDO 5429 Detroit St. ZANESVILLE 925 Linden Ave. OKLA. CITY OKLA. 3837 N.W. 10 St. EUGENE ORE. 62 W. B'way MEDFORD 1080 S. Riverside PORTLAND 4001 N. Interstate Ave. AKRON PA. 127 No. 7th St. ALLENTOWN 20 N. 7th St. BURNHAM 622 Freedom Ave. ERIE 24th & French St. GREENSBURG 102 Otterman St. HARRISBURG 1507-09 North 3rd Street NEW KENSINGTON 818 5th Ave. PHILADELPHIA 2546 Cottman Ave. Drexel Hill (Rt. 1 & State St.) SO. DUNCANSVILLE Route 220 WILKES-BARRE 115 No. Main St. YORK 601 W. Market St. PROVIDENCE R. I. 1023 Chalkstone Ave.	COLUMBIA SO. CAR. 948 Harden St. GREENVILLE 2109 Augusta Rd. CHATTANOOGA TENN. 3748 Ringold Rd. MEMPHIS 1057 N. Watkins St. MURFREESBORO 117 South Academy OAK RIDGE 39 E. Tenn. Ave. AUSTIN TEX. 4101 Interregional Hwy. DALLAS 5551 Lovers Lane EL PASO 4317 Dyer St. FT. WORTH 3510 "A" Section— E. Lancaster St. HOUSTON 8601 Long Pt. Rd. 6315 So. Park Blvd. LAREDO 1910 San Bernardo LUBBOCK 1722 Ave. H SAN ANTONIO 5090 Blanco Rd. SALT LAKE CITY UTAH 147 E. Sixth South BLACKSBURG VA. Christiansburg Rd. HAMPTON 802 W. Mercury Blvd. LYNCHBURG 1624 Park Ave. RICHMOND 3012 W. Broad St. BELLEVUE WASH. 10845 N.E. 8 Ave. SEATTLE 1210 First Ave. SPOKANE 5315 N. Market St. TACOMA 8805 Bridgeport Way MARTINSBURG W. VA. 809 N. Queen St. WHEELING 1217 Chapline St. KENOSHA WISC. 620-58th St. SOUTH BELOIT 1016 Blackhawk Blvd. U.S. POSSESSIONS GUAYNABO P. R. San Patricio Shopping Center SAN JUAN The Texas Bldg. 654 Ponce De Leon, Hato Re
---	--	---	---	--

How Would You Like to Own A

**LAFAYETTE
RADIO ELECTRONICS**

"ASSOCIATE STORE"?

EXCLUSIVE FRANCHISES NOW AVAILABLE

Basic Requirements Include:

1. Knowledge of Retailing, or of Radio, Television or Electronics
2. Financial Investment of \$10,000 to \$30,000

If you have the basic requirements, and would like complete details without obligation, write for full information to:


Mr. Robert Laub
Lafayette Radio Electronics Corp.
Dept. AS-653
111 Jericho Turnpike,
Syosset, L.I., N.Y. 11791

Everything In Electronics For Home, Industry and Laboratory

Lafayette Cat. No. 653 125

LAFAYETTE Deluxe "Range Boost" 23-Channel Crystal-Controlled CB Transceiver Model HB-333

Double Side Band Full Carrier — 100% Modulated



1. Illuminated 'S' Meter Indicates Signal Strength and Relative Power Output
2. Push-to-Talk Noise Cancelling Ceramic Microphone for advanced Electronic Switching Circuitry
3. Variable Floating Series Gate Noise Limiter Adjustable Squelch
4. Range Boost ON-OFF
5. Delta Tuning For Increased Crystal Tuning Accuracy
6. Phone Jack for Phones or External Speaker
7. Channel Selector
8. PRIVA-COM Selective Call Socket
9. Illuminated Channel Selector Dial
10. Built-in 117 V AC Power Supply With 12 Volts DC Mobile Vibrator Power Supply

- Exceeds FCC Requirement For Spurious and Harmonic Output
- Includes 2 Section Harmonic Filter to Eliminate TV Interference
- Will Not Become Obsolete—Works with Existing CB Transceivers
- Meets All FCC Regulations

Made in U.S.A.

199⁵⁰

\$10 Monthly

Unlike other types of "range boost" circuitry, the Lafayette system maintains the full carrier at all times ensuring excellent audio at maximum range. The modulation density of the audio contained in both sidebands is increased. In addition, the "Range Boost" features continuous crystal-control for both transmit and receive on all 23 channels. Triple crystal Delta tuning ± 3 KC of channel center frequency assures accurate station tuning when stations transmit slightly off frequency. Its highly efficient transmitter features: 5 watts plate power input to final (20 Watts PEP) with at least 3 watts power output to the antenna; up to 100% modulation at average speaking level, with "Range Boost." Illuminated D'Arsonval "S" Meter reads signal strength and relative RF output. Audio output is 3-4 watts into 3x5" pm speaker. An antenna matching adjustment permits resistive antenna loads of 52 or 72 ohms. Has phone jack on front panel for private listening or for remote external speaker. Includes all crystals, efficient noise cancelling microphone, AC & DC cables, and mobile mounting bracket. Includes 2-section harmonic filter to eliminate TVI. Built-in receptacle accepts Lafayette "Priva-Com" Selective Call unit. Complies with all FCC rules. Dual built-in 117 volt AC, 12 V DC vibrator power supply. Size: 12Wx4½Hx8½D" Shpg. wt., 16 lbs.

42 N 0105WX
42 N 9001WXM

Net 199.50
Net 230.75

LAFAYETTE CB TRANSCEIVER TESTER

Get Top Performance From Your CB Transceiver!



37⁹⁵


\$5 Monthly

Made In U.S.A.

LAFAYETTE AUTHENTIC MECHANICAL FILTER

19⁹⁵

- Super Selectivity
- 60 db Attenuation of Unwanted signals
- Complete Adjacent Channel Rejection
- For 455KC IF Tube Circuits



EXCELLENT FOR: Citizens Band Transceivers; Amateur: AM, CW, SSB Receivers; Shortwave and Standard Broadcast.

Precision Filter Design


The Mechanical Filter consists of input and output Transducer elements plus six carefully machined resonant metal discs which are made of a ferro-nickel chromium alloy for extreme hardness and complete resistance to corrosion.

Now you can achieve razor-sharp selectivity with AM, standard broadcast, shortwave, CW and SSB Communications receivers, and CB transceivers, having an intermediate frequency of 455 Kc. Update your present receiver to cope with today's crowded bands. Pick up distant stations formerly masked by strong signals. The Mechanical Filter provides a steep-skirted, flat top, ideal band pass response. At 2.5 Kc on either side of the center frequency, the filter provides 60 db attenuation. The complete filter network consists of a mechanical filter and 2 coupling transformers. Easily installed between mixer and 1st I.F. stages. Size: 2¾Wx¾Hx1¾"D (overall). Shpg. wt., 8 oz. Imported
99 N 0123

Net 19.95

SPECIFICATIONS

Center Frequency: 455KC
6 db Bandwidth: 2KC
60 db Bandwidth: 6KC
Input/Output Impedance: 10K
Insertion Loss: 1.5-3 db



- Measures:** RF Power Output
Relative Field Strength
Standing Wave Ratio (SWR)
Percent Modulation
Relative Crystal Activity
Generates: Crystal Controlled RF Signal
Modulated Audio Signal
1KC Audio Signal

- Permits:** Aural Monitoring of Local Transmitters
Visual Transmitter Monitoring with "scope"
Provides: In-Circuit instant connection to antenna without removing cables from transmitter.
Sensitive D'Arsonval Meter for Accurate Measurements

CB operators, technicians and servicemen will find the Lafayette CB Transceiver Tester a convenient, highly efficient and accurate instrument for improving the performance and range of CB transceivers. Has front panel jacks for aural and visual monitoring, audio generator output and RF signal generator output; and ceramic jacks for standard miniature crystal sockets. Controls include Function Selector, Antenna selector, Generator Selector, Modulation Calibrate Switch, Modulation Calibrate Control and Meter Adjust Control. Sturdy professional type SO-239 Sockets accept standard PL-259 connectors. Enclosed in a Sturdy attractive molded case with brushed aluminum front panel. 7¾x5¾x2¾". Shpg. wt., 4 lbs. Includes 9 volt battery and 30" telescoping antenna.
42 N 0126

Net 37.95

LAFAYETTE Deluxe 23 Channel Crystal Controlled Dual Conversion 5 Watt CB Transceiver Model HB-400

WITH ADVANCED FULL WAVE "RANGE BOOST" CIRCUIT




169⁵⁰
\$8 monthly

- ★ 17 Tube Performance With 13 Tubes And 8 Diodes
- ★ Low Noise Nuvistor "Front End"
- ★ Frequency Synthesized Circuit Provides 23 Crystal-Controlled Transmit & Receive Channels—No Extra Crystals to Buy!
- ★ Dual Conversion Receiver With 3/10 uv Sensitivity
- ★ Advanced Dual Zener Diode Full-Wave "Range Boost" Circuit
- ★ Triple Crystal Delta Tuning Offers "Fine Tuning" of ± 2.5 KC on Receive
- ★ Push-to-Talk Microphone & Electronic Switching
- ★ Variable Squelch, Variable Noise Limiter
- ★ Built-in 117V AC & 12V DC Power Supply
- ★ "Vari-Tilt" Mounting Bracket for Easy Mobile Installation

Efficient, dependable 2-way communications is assured with this rugged, 5-watt CB transceiver. A frequency synthesizing circuit makes it possible to transmit and receive over 23 channels with crystal-controlled accuracy—no extra crystals to buy and install! A zener diode full wave range-boost circuit increases the average depth of modulation during transmission—let's you transmit further within the 5-watt limitation imposed by the FCC! And, the "Range-Boost" system in the HB-400 is fully compatible with existing CB transceivers. Efficient circuit design uses 13 tubes (including two nuvistors) and 8 diodes to provide top performance. Dual-conversion receiver offers .3 uv sensitivity and low noise, plus excellent adjacent channel rejection. Includes every needed feature for optimum reception—crystal-controlled "fine tuning" capability of ± 2.5 Kc (Delta Tuning), variable noise limiter, variable squelch, and Automatic Volume Control. Also included is an illuminated meter which indicates relative RF power output or received signal strength in "S" units. The transmitter is equipped with ceramic push-to-talk microphone and uses reliable electronic transmit-recvie switching. Operates in a fixed or mobile location with equal ease . . . has built-in power supply for either 117V AC or 12V DC. Specially designed "Vari-Tilt" mounting bracket simplifies mobile installation — permits fast removal of the transceiver too! And, there's nothing else to buy — you get all crystals and a built-in vibrator for 12V DC, plus 2 power cables. Measures a compact 12Wx5Hx10"D. Shpg. wt., 20 lbs.

99 N 3001WX Net 169.50
Model HB-400 plus HA-200 PRIVA-COM Selective Call Unit Net 200.75
40 N 9007WX M Shpg. wt., 23½ lbs.





- 1 Illuminated Meter
- 2 Meter Switch
- 3 Speaker
- 4 Illuminated channel indicator
- 5 Channel Selector
- 6 Phone Jack
- 7 Delta Tune
- 8 Range Boost
- 9 Variable Squelch
- 10 Volume on/off
- 11 Variable noise limiter
- 12 Microphone socket
- 13 Vari-Tilt mounting bracket
- 14 Selective call socket

ADVANCED FULL WAVE "RANGE BOOST" CIRCUIT.

Increases Your Effective Range—Lets You Get Through Where Others Fail!

Want to effectively increase your range? You can — with Range-Boost! A simple turn of a switch on the HB-400 increases the average percentage of modulation and lets your voice cut through QRM and noise to reach further . . . gives you more "talk-power" when you need it—without overmodulating!



LAFAYETTE Dual Conversion Deluxe Citizens Band Transceiver Model HB-200


—ILLUSTRIOUS SUCCESSOR TO FAMOUS HE-20C—



only **109⁵⁰**
\$5.00 Monthly

MADE IN U.S.A.

LOOK AT THESE SPARKLING FEATURES



1. 13 MC Transmit Crystal for Extra Stability
2. Illuminated Meter With 3 Position Switch Indicates "S" Readings, Relative Power Output, and Modulation.
3. Spotting Switch.
4. Dual Cascade Series Gate Noise Limiter.
5. Adjustable Squelch.
6. Relay Switching Push-To-Talk Ceramic Microphone.
7. Tunable Receive or Crystal Selector Switch.
8. Phone Jack for Quiet Listening.
9. Illuminated Dial.
10. Channel Selector Switch
11. Attractive Styling With Chrome Plated Bezel.
12. Supplied With Pair of Transm/Receive Crystals for Channel 14 plus Crystal for Dual Conversion.

- Dual Conversion For Exceptional Selectivity and Gain
- 9 Tubes plus 3 Silicon Diodes plus 2 Crystal Diodes for 17 Tube Performance
- 8-Crystal Receive Positions plus 8-Crystal Transmit Positions plus 23 Channel Tunable Receive
- Spotting Switch for Exact Frequency Location on Tunable Receive
- Wired to Accept "PRIVA-COM" Selective Call Unit
- Super Sensitivity—1 Microvolt or less
- Built-in 117 Volt AC Power Supply with 12 Volt DC Mobile Transistorized Power Supply

Lafayette advances its leadership in the Citizens Band field with this superb Dual Conversion Deluxe Citizens Band Transceiver.

The excellent selectivity and gain of its dual conversion receiver makes the Lafayette HB-200 a natural for efficient fixed and mobile communications over distances of up to 20 miles or more, depending on the terrain and the height of the antenna.

The 5-watt input highly efficient crystal-controlled transmitter may be operated on any 8 of the 23 channels assigned by the FCC. The dual conversion receiver circuit provides for 8 crystal controlled receiving channels plus a tuneable super-heterodyne receiver that covers all 23 assigned channels with a sensitivity of 1 microvolt or less. An adjustable squelch circuit quiets the receiver when no signal is being received. A dual cascade series gate noise limiter effectively reduces ignition, static and unwanted noises. A sensitive illuminated panel meter is utilized with a 3-position switch to indicate incoming signal strength, relative power output and modulation. The HB-200 also features dependable relay switching; a Spotting Switch for locating exact frequency on tunable receive, and a front panel phone jack for quiet listening. It incorporates a Pi-network for matching the output to 30-100 ohm antennas for maximum signal output; input socket on rear of chassis for silent communications between calls when used with Lafayette PRIVACOM selective call unit. A rear mounted low-loss antenna jack accepts PL-259 connector used with dipole, ground plane, rod and direct mounting antennas (listed below).

Attractively styled low silhouette transceiver and rugged case with chrome plated bezel.

Complete with bracket handle, efficient Push-to-Talk Ceramic Microphone, pair of transmit and receive Crystals for channel 14 plus crystal for dual conversion, and built-in 117-volt AC Power Supply with 12 volt DC Mobile Transistorized Power Supply. Size: 12x5x8½"D. Shpg. wt., 15 lbs.

42 N 0118WX	Net	109.50
42 N 4701C 13 MC Transmit Crystal (Specify Channel)	Net	2.25
42 N 4202C Receive Crystal (Specify Channel)	Net	2.25
Direct Plug-in Antenna for Short Distances. Shpg. wt., 1 lb.		
99 N 3015	Net	3.95

SELECTIVE CALL PACKAGE

HB-200 CB Transceiver plus "PRIVA-COM" Selective Call Unit.		
42 N 9006WXM Shpg. wt., 18½ lbs.	Net	140.75

LAFAYETTE HB-115A Push-To-Talk Citizens Band Transceiver



MADE IN U.S.A.

59⁹⁵

\$5.00 monthly

- 12 Tube Functions, Plus 1-Diode, Plus 2 Silicon Rectifiers
- 8 Crystal-Controlled Transmitting Positions
- Tunable Superheterodyne Receiver Over All 23 Channels
- Electronic Push-to-Talk Switching
- Push to Talk Ceramic Microphone

- Pi-Network for Maximum Power Output
- External Speaker Earphone Jack on Front Panel
- Full-Wave Variable Noise Limiter
- Separate On-Off Power Switch
- Supplied with Channel 14 Transmitting Crystal
- Attractively Styled, Ruggedly Built

Lafayette's new CB sensation consists of an attractive compact transceiver with exceptional performance on Class "D" Citizens Band. Two or more HB-115A's will supply you with reliable communications over distances of up to 20 miles or more depending on antenna height and terrain.

The HB-115A features 8 crystal-controlled transmitting channels operating at the maximum legal input power of 5 watts fully modulated; a pi-network output which matches 30-100 ohm antennas for maximum output; RF stage in transmit and receive sections. The superheterodyne receiver is tunable on all 23 channels with over 2 watts audio output, has Automatic Volume Control and a very effective fullwave variable Noise Limiter. Features a front panel speaker/earphone jack for an extra external speaker or for an earphone or headset for quiet listening; a separate on-off power switch for trouble-free economy of operation. The HB-115A has accurate planetary vernier tuning. Controls: Tuning, Volume, Variable Noise Limiter, 8-position Crystal Selector and Power indicator.

Power receptacle in rear for 115-volt AC line cord and 6 or 12 volt external mobile power supply. Supplied complete with Channel 14 transmitting crystal, efficient push-to-talk ceramic microphone, and mounting brackets. 6 or 12-volt power supply optional (see below). Size 11½Wx5Hx6¾"D. Shpg. wt., 13 lbs.

42 N 0101WX Net 59.95

POWER SUPPLY: Adapts HB-115A for mobile operation. Complete with cable and mounting flanges. Size 6Wx4Hx4¼"D. Shpg. wt., 4 lbs.

42 N 0102W For 12 Volts Net 11.50

42 N 0103W For 6 Volts Net 11.50

TRANSMITTING CRYSTALS: For any of the 23 channels.

42 N 4201C Specify channel or frequency Net 2.25

ANTENNA: Base-loaded telescoping whip antenna with PL-259 coax connector. For short distance operation. Mounts directly on rear of cabinet. Telescopes to only 15". Shpg. wt., 2 lbs. Imported.

99 N 3015 Net 3.95

LAFAYETTE "PRIVA-COM"™ Selective Caller

The "Priva-Com" Selective Caller, when in "Standby" position, silences the speaker of the transceivers to which it is connected. When the "Priva-Com" call switch is actuated at either base or mobile, the transmitted dual tone signal is received by the other "Priva-Com". Its indicator light goes on and the speaker is automatically activated. You can now speak or listen to the calling station. The light stays on until manually reset. If the car horn or an external alarm is connected to the "Priva-Com" terminals the received dual-tone signal causes the horn or alarm to sound for 1 second. Both base and mobile stations can initiate calls and monitor the air at anytime. Cable terminates in plug which mates with Lafayette CB Transceiver. Complete with mounting bracket and instructions. Size 3¾Wx3¾Hx5½"D. Shpg. wt., 3½ lbs.

42 N 0110 Each Net 32.50

2 for 62.50

* Not recommended for Transceivers with carbon microphones less preamplifiers.

- For Quiet Private Communications
- Choice of 10 Dual Tone Frequencies—Minimizes Interference by Unwanted Signals
- Activates car Horn or External Alarm for 1 second if Operator is Away from Equipment
- Outstanding Performer with Lafayette HE-20, HE-15, HE-90, HB-111, HB-115, HB-115A, HB-222, HB-333, HB-200 & HB-400 as well as with any Push-to-Talk CB Transceiver*
- Compatible with Lafayette HA-100 "Priva-Com"



32⁵⁰ \$5.00 monthly
2 for 62.50

Model HA-200

LAFAYETTE 9-Transistor Superheterodyne Citizens Band "Walkie Talkie" Model HE-29C



25⁹⁵
2 For 49.95

- Transmits and Receives up to 1.5 Miles
- Crystal Control on Both Transmit and Receive
- 9-Transistor, 1-Diode Circuitry
- Push-To-Talk Operation
- Earphone for Personal Listening
- Leather Case with Shoulder Strap

Complete portable two-way communications for everyone, everywhere—hunting, fishing, boating, virtually all sports; at work in construction, warehouse, office, farm or for in-plant communications. Receives and transmits up to 1.5 miles under average conditions (no intervening obstructions.) Weighs only 16 ounces and slips into your pocket. Two controls provide fast, efficient operation, on/off volume and push-to-talk. Private monitoring or conversation by means of a special jack and earphone.

Full-transistor circuitry employs 9 transistors, 1 diode. Crystal-controlled transmitter section delivers 100 milliwatts of power to the final RF amplifier. Crisp, clear reception furnished by the efficient superheterodyne receiver. Power supplied by 6 penlight batteries with life expectancy of up to 55 hours.

Housed in black and brushed aluminum metal case with leather carrying case and shoulder strap. With earphone, antenna, batteries and a pair of crystals for the channel of your choice. 6 7/8" x 2 1/4" x 1 3/8". Shpg. wt., 2 1/2 lbs. Imported.

99 N 3020CL Model HE-29C Specify Channel Net 25.95

2 for 49.95

42 N 4204C Replacement Transmit Crystal, Specify Channel Net 2.25

42 N 4205C Replacement Receiver Crystal, Specify Channel Net 2.25

99 N 3021 Replacement Earphone for HE-29C Net .49


Replacement batteries for HE-29C "Walkie-Talkie," 6 required

32 N 4802 Z Cells Net ea. .13

AC Power Supply

Use in place of batteries for operation on 110 VAC. Shpg. wt., 2 lbs.

99 N 3012 Net 6.95



No License Required
(FCC Reg. Part 15)

LAFAYETTE 12-Transistor Citizens Band "Walkie Talkie" Model HE-100 With Noise Squelch



39⁹⁵
\$5.00 Monthly
2 For 78.88

- 12 Transistors, 1 Diode and 1 Thermistor
- Crystal Controlled Transmit and Receive
- AVC, Squelch, Push-Pull Audio Output
- Optional Plug-in 117 Volt AC Power Pack

Separate Microphone and Speaker for Better Modulation and Increased Range

The use of a separate microphone and speaker results in excellent modulation with greatly improved transmitting range and maximum effective signal intelligibility. Superhet receiver has variable squelch to reduce background noise. 12-transistor advanced design circuit is crystal-controlled for both receive and transmit functions. Sensitivity is better than 1 microvolt for 10 db signal-to-noise ratio. Easy-to-use, lightweight, carry it anywhere for sports or business. Housed in a rugged hi-impact plastic case. Handy controls include push-to-talk switch, volume and variable squelch. Power is supplied by 8 miniature penlight batteries. To conserve battery power, a 117V AC power pack is available as an optional plug-in accessory. Complete with leather case, earphone, for private monitoring. 44" telescoping antenna, batteries and crystals for channel 10. Size: 3Wx9Hx2 3/4"D. Shpg. wt., 2 lbs. Imported.

99 N 3022L Net 39.95

2 for 78.88

Same as HE-100 but specify channel other than 10 (2-23).

99 N 3023L Net 39.95

2 for 78.88

CRYSTALS FOR HE-100

42 N 4204C Transmit Crystal only. Specify Frequency Net 2.25

42 N 4205C Receive Crystal only. Specify Frequency Net 2.25

AC POWER PACK FOR HE-100

Heavy Duty 117 Volt 60 Cycle AC Power Supply to 12V D.C. Replaces 8 "Z" Cells. Wt. 1 lb.


99 N 3024 Net 7.45

99 N 3025 REPLACEMENT EARPHONE FOR HE-100 Net .49

CANADIAN APPROVED HE-100 D.O.T. Approval No. 169361066.

99 N 3002L Net 39.95

2 for 78.88



No License Required
(FCC Reg. Part 15)

LEATHER
CARRYING
CASE

ANTENNA

BATTERIES

EARPHONE

CRYSTALS
OPTIONAL
AC POWER PACK

LAFAYETTE 10-Transistor Citizens Band "Walkie Talkie" Model HA-60

Separate Microphone and Speaker for
Better Modulation & Increased Range

- Crystal Controlled Superheterodyne Receiver with RF Stage, AVC
- Separate Microphone and Speaker For Better Modulation & Increased Range
- 1 μ V Sensitivity For 10 DB S/N Ratio
- 10 Transistors, Diode, Thermistor
- Crystal Controlled Transmitter
- Range 1-3 Miles

Ideal for use in business, industry, or personal use. Features automatic volume control and push-pull audio. Separate speaker and microphone provides better modulation and improved transmission range. Simple operation is made possible with sturdy push-to-talk switch and volume control. Earphone is provided for private reception. 44" whip antenna collapses fully when not used. Power is supplied by 8 inexpensive penlight batteries. To conserve battery power, a 117V AC power converter is available as an optional plug-in accessory. Housed in rugged hi-impact plastic case. Complete with leather case, earphone, antenna, batteries and crystals for channel 10. Size 3Wx9Hx2 $\frac{3}{4}$ "D. Shpg. wt., 2 lbs. Imported.

99 N 3009L Net 33.95
2 for 62.90

OTHERS ARE AVAILABLE If desired with any channel other than channel 10 order 99 N 3010L and specify channel (2-23). Same as HA-60 but specify channel other than 10 (2-23).

99 N 3010L Net 33.95
2 for 62.90

CRYSTALS FOR HA-60

42 N 4204C Transmit Crystal only. Specify frequency Net 2.25
42 N 4205C Receive Crystal only. Specify frequency Net 2.25

AC POWER PACK FOR HA-60

Heavy duty AC power supply replaces 8 "Z" cells. Wt. 1 lb.
99 N 3024 Net 7.45

99 N 3025 REPLACEMENT EARPHONE FOR HA-60 Net .49

CANADIAN APPROVED HA-60. D.O.T. APPROVAL No. 169361073.

99 N 3003L Net 33.95
2 for 62.90

33⁹⁵
\$5.00 Monthly
2 For 62.90

No License
Required
(FCC Reg. Part 15)



LEATHER
CARRYING
CASE




ANTENNA
BATTERIES



EARPHONE



CRYSTALS



LAFAYETTE HE-75 1-Watt 13-Transistor Citizens Band "Walkie Talkie" with Squelch

- 10 Times More Powerful Than 100MW Units—With Far Greater Range
- Uses Powerful Silicon Transistors in Output Stage
- Crystal-Controlled Receive and Transmit
- Automatic Noise Limiter, Squelch AVC
- Push-Pull Audio Output
- Plug-in Battery Case for Both Penlight and Optional Rechargeable Nickel Cadmium Batteries
- Meets FCC Requirements for Licensed Operation Part 95.

A full 1-watt RF Input Crystal controlled 2-way radio with 13 transistors, 3 diodes and a thermistor that is compact enough to fit in your hand. Powerful 2-stage transmitter delivers a clean signal even at extreme ranges. Superhet receiver features a push-pull audio section for utmost intelligibility and quality voice reproduction. Superior automatic noise limiter effectively reduces ignition & other background noise while a variable squelch silences reception between calls and prolongs battery life. Local/Distance switch and AVC stop distortion at close range— aids in pulling in weak distant signals. Other features include: heavy-duty printed circuit board, rugged high-impact case, push-to-talk switch, and interchangeable battery compartment—for either penlight cells or rechargeable nickel cadmium battery. Also includes plated telescoping whip antenna, plug-in earphone, leather carrying case, 8 penlight batteries and crystals for channel 13. Size 3x8x2" D. Imported.

99 N 3016L Shpg. wt., 2 lbs. Net 59.95
2 for 118.95

Rechargeable nickel cadmium battery in sealed compartment.
99 N 3018 Net 14.50

CRYSTALS FOR HE-75

42 N 4204C Transmit Crystal only. Specify Frequency Net 2.25



42 N 4205C Receive Crystal only. Specify Frequency Net 2.25

99 N 3019 REPLACEMENT EARPHONE FOR HE-75 Net .49

CANADIAN APPROVED HE-75 (D.O.T. Approval No. 169361071)

99 N 3004L Net 59.95
2 for 118.95

with
Squelch
59⁹⁵
\$5 monthly
2 For 118.95




OTHER CHANNELS ARE AVAILABLE if desired with any channel other than channel 13, order 99 N 3029L and specify channel (1-23)

LAFAYETTE 2-Watt, 2-Channel CB "Walkie Talkie" Model HA-300

**A Compact, Hand-Held 2-Way
Radio With All These Features..**

- Powerful 2 Watts
- 2-Channel Operation
- Self-Contained Rechargeable Batteries
- Plug-in Battery Charger
- Provision For External Antenna
- 13 Transistors, 2 Diodes
- Fully Crystal-Controlled
- Lightweight—Weighs Less Than 2½ lbs.




only \$5 monthly

COMPLETE
99⁹⁵
Set of 2 194.95

PRICE INCLUDES

- ✓ Nickel Cadmium Batteries
- ✓ Battery Charger
- ✓ Earphone
- ✓ Crystals for 2 Channels
- ✓ Leather Case



Full 2 watts RF input lets you get through..... offers up to 10 mile range over favorable terrain. 2-channel operation—a flip of a switch lets you transfer from one channel to another. Other extras include 2 built-in heavy-duty nickel-cadmium batteries and a plug-in battery charger that enables you to maintain the transceiver's maximum power capabilities at all times. 13 transistors and 2 diodes are used in a fully miniaturized transmitter and receiver, both crystal-controlled for precise, dependable operation. Receiver employs a superheterodyne circuit with 1 RF and 2 IF stages for high sensitivity, push-pull audio for high output and undistorted sound plus a variable squelch control that silences the receiver on "stand-by." An automatic gain control circuit prevents overloading on strong signals and maintains uniform sound output. A full-time Automatic Noise Limiting circuit reduces ignition and other electrical noise. Powerful 2-stage transmitter output circuit uses two rugged silicon transistors for greater reliability and longer life. The 10-section, chrome-plated telescopic antenna extends to 56½ inches and there's


also a special receptacle that lets you plug in any existing mobile or ground station antenna for extended range! A push-to-talk bar and thumb-operated volume and squelch controls permit simple, one-hand operation.

The HA-300 is equipped with crystals for channels 10 and 15, but may be operated on any two other channels in the Citizens Band by simply changing the plug-in crystals. Supplied complete with 2 self-contained nickel cadmium batteries, 117 volt 50/60 cycle AC operated battery charger, earphone, and leather case with strap. Dimensions: 8¾x3½x2". Black metal case with chrome trim and silvered grill. Imported. Shpg. wt., 4½ lbs.

99 N 3006L	Net	99.95
Set of 2	Net	194.95
EXTRA CRYSTALS FOR HA-300		
42 N 4204C Transmit crystal only. Specify channel	Net	2.25
42 N 4205C Receive crystal only. Specify channel	Net	2.25
99 N 3019 Replacement earphone for HA-300	Net	.49

LAFAYETTE 2-Channel 1-Watt All-Transistor Portable CB Transceiver Model HA-150

**THE SUPER WALKIE-TALKIE . . . A NEW
CONCEPT IN 2-WAY CB RADIO**



79⁹⁵

\$5 monthly

1. EXTERNAL PUSH-TO-TALK DYNAMIC MICROPHONE FOR RELAY SWITCHING
2. CHANNEL SELECTOR
3. SQUELCH
4. AUTOMATIC NOISE LIMITER
5. MODULATION BATTERY INDICATOR SWITCH
6. MODULATION BATTERY INDICATOR METER
7. POWER ON-OFF/VOLUME
8. TELESCOPING WHIP ANTENNA
9. EXTERNAL BATTERY SOCKET
10. EARPHONE SOCKET



Model HA-150 Ideal for Builders, Contractors, Surveyors, Hunters, Campers, Plant Watchmen, etc.

Here is a fully transistorized 2-way CB radio that offers the portability of a walkie-talkie, yet has features found only on large mobile transceivers. It has full 1-watt RF input . . . up to 6-mile range . . . quick-release battery compartment that uses 8 inexpensive flashlight cells for long, heavy-duty service. 4 convenient push buttons give you complete control. It can be used in or out of its leather case . . . as a base station or remote . . . carried, or used on a desk, table, car or boat—its uses are virtually unlimited! It has a high-efficiency 59-inch antenna which collapses to 7½ inches. Receiver has high 1 µv sensitivity, push-pull audio, and large 3-inch speaker for clear, full-tone reproduction. The transceiver has plug-in crystals that let you change to any other 2 channels in the Citizens Band—without any circuit retuning or adjustments. Complete with channel 10 and 15 crystals (2 transmit, 2 receive), batteries, push-to-talk dynamic microphone, a leather carrying case, earphone, cord and plug for external battery connections with shoulder strap for transceiver.

Dimensions: 9½Wx2¼Hx5½D. Operates from self-contained 12-volt battery pack or 12-volt DC external supply. Imported. Shpg. wt., 7 lbs.

99 N 3014L	Net	79.95
Set of 2	Net	154.95
Replacement batteries for HA-150		
32 N 4801 1.5-volt "C" cell (8 required)	Net ea.	.13
42 N 4204C Transmit Crystal. Specify Channel	Net	2.25
42 N 4205C Receive Crystal. Specify Channel	Net	2.25
REPLACEMENT ANTENNA FOR HA-150		
99 N 3017 Antenna	Net	1.95

Improve Your CB and Ham Gear Performance

LAFAYETTE HA-115 AUDIO COMPRESSOR AMPLIFIER FOR CITIZENS BAND TRANSCEIVERS

only 25⁹⁵

- For 6 volt, 12 volt or 117 volt Base and Mobile Transceivers
- Illuminated Meter Directly Reads Modulation Percentage
- Printed Circuitry, Advanced Design
- Works with all Popular CB Units



Made in U.S.A.

The audio compressor instantly and automatically increases the "talking power" by increasing the average modulation of CB transmitters. This, however, is accomplished without the side effects of over modulation. Final power input remains within the legal 5-watt limit (as per FCC decree) but effective talk power is increased many times. This compressor amplifier is easily connected to CB transceivers operating on either 6 or 12 volts DC or 117 volts AC. Requires very little power for operation hence existing power supplies may be utilized. Comes complete with operating and installation instructions. Size: 3Hx3 1/2 Wx5" D. Shpg. wt., 2 lbs.

42 N 0117 Net 25.95

LAFAYETTE SQUELCHER

- Provides full squelch and noise limiting to most superheterodyne transceivers or receivers
- Vastly improves mobile transceivers when vehicle is in traffic
- Reduces noise from ignition systems and other sources

Squelch That Interference



10⁹⁵

Made in U.S.A.

The Lafayette "Squelcher" noise eliminator was carefully designed to improve reception and reliability in most superheterodyne transceivers or receivers other than those using solid-state detectors. Recommended for the Lafayette HE-20A, HE-20B, HE-20C, HE-30, KT-320, HE-45, HE-45B, HE-90, HB-111, HB-200, and HB-222. Reduces noise from ignition systems and other sources. Quiets receiver when no signal is received. Vastly improves sensitivity of mobile transceivers when operating in traffic. Complete with 2 (6AL5 and 12AX7) and instructions for installation. In satin aluminum with blue gray perforated cover. Furnished with cable. Size: 2 1/2 x 3 1/2 x 4 1/4".

42 N 0004 Shpg. wt., 1 1/4 lbs. Net 10.95

NEW! LAFAYETTE CB LOW PASS FILTER



- Avoid TV Set Interference!
- 50 db Attenuation of Radiated Spurious and Undesirable Signals!

5⁹⁵

Designed to effectively reduce TVI which may be emanating from your CB Transmitter. This professional quality filter attenuates radiated spurious and other undesirable harmonic signals higher than .50 MC approximately. 50 db! Minimizes interference with your own or your neighbor's TV Set. Simple to connect with two built-in SO-239 connectors. Impedance 50-75 ohms (reversible). Size: 5x2x1 1/4". Shpg. wt., 1 1/2 lbs.

42 N 0123 Net 5.95

MAGNETIC MICROPHONE HOLDER

99^c

- For CB, Ham and Commercial Mobile Radios

Put your microphone where you want it, when you want it. No holes to drill, no brackets to mount. Holds up to 12 lbs. Either clip to microphone for ready-to-use magnetic mike or attach to any steel surface and slip microphone in holder. Fits most microphones. Shpg. wt., 1/4 lb.

42 N 3201 Net .99

ALTERNATOR NOISE FILTER



4⁴⁹

- For CB, Amateur And Commercial Mobile Communications

A highly effective filter for alternator equipped automobiles. Attenuates alternator noise by 50 db. Can operate up to 32 volts DC. Results in quiet mobile receiver operation. Shpg. wt., 8 oz.

42 N 4900 Net 4.49

LAFAYETTE QUIAT-COM™. SOLID STATE VIBRATOR TRANSISTORIZED 12 VOLT REPLACEMENT CB VIBRATOR . . .

ONLY 5⁹⁵

- No Vibrator Hash Noise
- Much Longer Vibrator Life
- No Mechanical Noise
- More Efficient, Cooler Operation
- Uses Top Grade Transistors from Famous Manufacturer . . . NO Surplus Transistors!



Exceptionally efficient replacement for CB vibrators, as well as for vibrators used in Amateur and communications equipment rated up to 85-watt consumption. Available in POSITIVE Model and in NEGATIVE Model. For 12 Volt operation only. Shpg. wt., 1 lb.

Quiat-Com Positive Model

Replaces vibrators with Pin 1 Positive as in the following units: Bendix CB-12; Citi-fone CD-12, SS; Elco 771, 772; Globe 100, 100A, 200; Gonset G-14, G-12; Hallicrafters CB 3, A; Heath GW-42; Knight C22, Lafayette HE-20, A, B, C, HE-45, B, HB-400; Metroteck All; Dison "Spotter"; "Side Bander"; Raytheon TWR-1.3; RCA Mark 7, 8; Regency "Range Gain"; Realistic TRC8; Sonar E; Utica MC-27 & TC2; Webster 411; etc.


42 N 0121 Positive Quia-Com Net 5.95

Quiat-Com Negative Model

Replaces vibrators with Pin 1 Negative as in the following units: Apelco AR-9; Arkay SQ9, SQ9W; Courier 1-M; Dewald TR-12; Gonset G11; Hallmark 512; Hammarlund CB-23, 500; Heath GW-10, 11; International Executive Model 50; Johnson 127, 128, 129; Messenger 1, 2; Karr TR-322, 327A, 327B; Lafayette HE-15, A, B, HE-90, HB-115, 115A, HB-266, HB-333; Morrow CB-1, 2, 3, Polycorn PCN12, 2-12, SR23, Pro; Regency CB-27, Vocaline FRC-400, 425.

42 N 0122 Negative Quia-Com Net 5.95

LAFAYETTE AUTO-MARINE ENGINE NOISE SUPPRESSOR KIT



- A Must For Mobile CB & Ham Operators
- 14 Components Plus Hook-Up Wire

This easily installed kit will effectively suppress ignition, generator and voltage regulator noise. Consists of 8 spark plug suppressors; 1 distributor suppressor, 1 voltage regulator suppressor; 4 coaxial capacitors; shielded cable and braid for wiring filter system. All necessary hardware and instructions for installation are included. Shpg. wt., 2 lbs.

42 N 0905 Net 9.45

LAFAYETTE GENERATOR NOISE FILTER

- Freq. Range 3-30 mcs
- Simple to Install
- Maximum Current 25 Amps
- Adjustable

Enables quiet receiver operation for Citizens Band, Amateur and industrial frequencies. Standard frequency range 3-30 mcs. Maximum current 25 amps.

99 N 8018 Shpg. wt., 1 lb. Imported Net 2.49

Citizen Band Headsets And Microphones

CB SPECIAL SAFETY HEADSET-MICROPHONE



Only
29⁵⁰

- Keep Both Hands on the Wheel at All Times!
- Listen and Talk with Perfect Ease

For convenience and safety, the earphone is on the right hand side allowing the mobile operator to hear the traffic. The push-to-talk switch can be held in the hand permitting "both hands on the wheel" driving. No longer are mobile communications unsafe! The microphone is an efficient high impedance, high output, noise cancelling, ceramic type. Impedance of the dynamic earphone is 8 ohms and is housed in a high impact cyclolac cup. The headband and earseals are removable permitting cleansing with mild detergents. Easily connects to Lafayette HE-20C, HE-43C, HB-111, and HB-200. Also connects to any other transceiver merely by connecting earphone in place of speaker and the microphone to the microphone input terminals. Full instructions included. Shpg. wt., 2 lbs.

42 N 8401 Net 29.50

CB CRADLE HANDSET



- Attach To Side Of Transceiver Or To Car Dashboard
- Weight-Actuated Cradle Switch Disconnects Speaker and Connects Handset
- Industrial CB—Equip Your Mobile Fleet For Convenient And Private Operation

As Low As **19⁷⁵**



HOME



MOBILE



MOUNT ON UNIT

Modernize your present fixed or mobile CB station with this new telephone style handset. Easily attaches to the dashboard, side of unit or even to a wall or panel in fixed station locations. A switch in the cradle automatically disconnects the speaker when the handset is lifted. This switch also connects the highly-sensitive earpiece element providing no loss in listening time and private—operator-only, listening. The microphone, a high output ceramic type, is activated by means of a push-button push-to-talk switch on the standard model and a push bar switch on the deluxe model. Easily modified, if desired, so that speaker remains on until mike is activated. Ideal for use in heavy traffic, loud background noise areas, at home, or in the office. Easy to install—just plug into microphone jack and attach two wires to speaker circuit. Unit comes complete with coiled cord between handset and cradle and with standard microphone cable between cradle and CB transceiver. Excellent with Lafayette HE-20C, HE-43C, HB-200, HB-400, HB-115A, HB-111, HB-222, HB-333, HE-90, HE-15B. Shpg. wt., 2 lbs.

42 N 8501 Push-Button Actuator type Net 19.75
42 N 8502 Deluxe Push-Bar type Net 21.45

LAFAYETTE CITIZENS BAND PUSH-TO-TALK NOISE CANCELLING CERAMIC MICROPHONE



5⁸⁸

Lafayette's noise cancelling, high output ceramic push-to-talk microphones are designed to reproduce clean, crisp audio with full modulation with as little noise pickup as possible. High level, high impedance output. Molded, tough, gray Cyclolac, TM, case assures long life and protection from accidental shock damage. DPDT switch. Wired for standard Relay Switching as used in Lafayette HE-20, 20A, 20B, HE-43, 43A, 43B, HB-111, HB-222, etc. or for Electronic Switching as used in Lafayette HE-200, HE-90, etc. Size: 2½x7¼x3½". 3-conductor coiled cord, 10' retracted, 1 conductor shielded. Complete with hang-up bracket and Amphenol 91-MPMSL plug attached for Lafayette Transceivers. Shpg. wt., 1 lb. Made in U.S.A.

42 N 0115 For Relay Switching Net 5.88
42 N 0116 For Electronic Switching Net 5.88
44 N 0115 Relay Switching, Less Noise Cancelling Net 5.66

LAFAYETTE CB PUSH-TO-TALK CERAMIC MICROPHONE



Top Quality Mike Used with FAMOUS LAFAYETTE HB-115 SERIES CB TRANSCEIVER

4⁵⁰

Efficient, economical push-to-talk ceramic microphone. Straight 3 conductor plus shield cable terminated in Amphenol type 99MPMSL plug. HI-impact plastic case. Used with Lafayette HB-115 Series CB Transceiver. Shpg. wt., 1 lb.
44 N 3901 Net 4.50


LAFAYETTE DYNAMIC CB PUSH-TO-TALK MICROPHONE



8⁹⁵

Top quality dynamic microphone. Specifically designed for citizens band and communication transceivers. High impedance dynamic transducer will not be adversely affected by heat and smooth frequency response of 100 to 11,000 cycles make it most suitable for communications work — indoors or out. Comes with a momentary push-to-talk switch, coiled rubber cable with a 5-prong plug and a convenient hang-up bracket. Shpg. wt., 1 lb. Imported.
88 N 4533 Net 8.95

TURNER 350C CB COMMUNICATIONS MIKE



5⁷⁵

- Ideal For CB Use
- With Push-To-Talk Switch

A rugged push-to-talk ceramic microphone wired for relay operation. Extra-tough polystyrene case; hanger button and standard dash bracket are included. Also neoprene coiled cord, 11 inch retracted, 5-ft. extended. Output, —54 db. Response, 80-7000 cps. Dark grey finish. Shpg. wt., 1 lb.
44 N 7002 Net 5.75

TURNER 254C CB PUSH-TO-TALK CERAMIC MIKE



- Push-to-Talk plus Lock Switch
- DPDT Switch for Relay or Electronic Switching
- Excellent for Lafayette Push-to-Talk CB Transceivers

Attractive Ceramic microphone with DPDT push-to-talk switch plus lock switch for fixed station operation. 7' 3 conductor (one shielded) cable. Response 60-8,000 cps. Output level—52 db. Gray hammertone finish with chrome trim 7¼x3¼x5¼" base. Shpg. wt., 3 lbs.
44 N 7003 Net 13.82

Popular Citizen Band Transceiver Crystals

LAFAYETTE'S low Price 2²⁵



A complete listing of transmitting and receiving crystals for the most popular Citizen Band Transceiver's and Walkie-Talkies on the market today. These crystals are available for any channel from 1 to 23. When ordering be sure to specify stock number and channel

desired. Extremely accurate 3rd overtone crystals are precision made and meet F.C.C. tolerance requirements of .005%. No crystal required in receiver circuit of these transceivers. Shpg. wt. 3 oz. Specify stock number and channel desired Net ea. 2.25

MODEL	STOCK NUMBER		MODEL	STOCK NUMBER		MODEL	STOCK NUMBER	
	TRANSMIT	RECEIVE		TRANSMIT	RECEIVE		TRANSMIT	RECEIVE
Arkey	42 N 4201C	42 N 4211C	Hallcrafters CB-5A	42 N 4215C	42 N 4227C	Laf'tte HE-88, 100A	42 N 4204C	42 N 4205C
Arvin Mod. 42R99	42 N 4201C	42 N 4233C	Hallmark Duo-Comm.	42 N 4201C	"	Lafayette HA150, 300	42 N 4204C	42 N 4205C
Browning S-9	42 N 4201C	"	Hallmark 212, 512	42 N 4201C	42 N 4233C	Lafayette HB111, 200	42 N 4201C	42 N 4202C
Browning T2700S	42 N 4201C	"	Hammarl HQ105TR	42 N 4201C	"	Lasalle, LA101,	42 N 4201C	42 N 4233C
Browning 23/9	42 N 4212C	"	Heath CB-1	42 N 4201C	"	Lasalle, LA101-AN	42 N 4201C	42 N 4233C
Cadre C-75	42 N 4213C	42 N 4223C	Heath CB-2	42 N 4201C	42 N 4211C	Metrotok Starfire	42 N 4201C	42 N 4211C
Cadre 510, 510A	42 N 4213C	42 N 4224C	Heath GW-10, 11, 12	42 N 4201C	42 N 4211C	Met "Spacestation"	42 N 4201C	42 N 4211C
Citifone CD5, CD6,	42 N 4214C	42 N 4225C	Heath GW-22, 32, 42	42 N 4201C	42 N 4211C	Phimore TC-90	42 N 4201C	42 N 4233C
Citifone CD7	42 N 4214C	42 N 4225C	Heath MW-33	42 N 4201C	42 N 4211C	Phimore TC-11	42 N 4201C	"
Com Pak 800	42 N 4201C	42 N 4233C	Heath GW-51, GW-52	42 N 4216C	42 N 4228C	Phimore TC-6-12	42 N 4201C	"
Daysform DM348	42 N 4201C	42 N 4211C	Heath GW-30, R220	42 N 4216C	"	Poly Comm. PC 11,	42 N 4220C	42 N 4231C
Demco CB 1A	42 N 4701C	"	Heath GW-31	42 N 4216C	"	Poly Comm. PC-11G,	42 N 4220C	42 N 4231C
Demco TW110A	42 N 4701C	"	Int. Exec. 10	42 N 4701C	"	Poly Comm. PC-12G,	42 N 4220C	42 N 4231C
Eico 760, 760A	42 N 4214C	42 N 4210C	Int. Exec. 50, 100,	42 N 4701C	42 N 4230C	Poly Comm. PCN-N,	42 N 4220C	42 N 4231C
Eico 770, 771, 772,	42 N 4214C	42 N 4210C	Int. Exec. 100A	42 N 4701C	42 N 4230C	Poly Comm. PRO	42 N 4220C	42 N 4231C
Eico 777	42 N 4214C	42 N 4210C	Johnson Mess. I, II	42 N 4215C	42 N 4235C	Poly Comm. PC-4	42 N 4220C	42 N 4231C
Fanon FCB-9, MCB-99	42 N 4201C	42 N 4233C	Johnson Mess. III	42 N 4219C	42 N 4237C	Poly Comm. PC-8	42 N 4220C	42 N 4231C
Fonet 101	42 N 4201C	42 N 4233C	Knight C-11	42 N 4201C	"	Radifon RT101	42 N 4201C	42 N 4233C
Fonet 102B	42 N 4204C	42 N 4205C	Knight C-100	42 N 4216C	"	Regency CBM27	42 N 4201C	"
Gen. Rad. MC-1	42 N 4201C	42 N 4233C	Knight 2500	42 N 4201C	42 N 4202C	Sampson T-110A	42 N 4701C	"
Gen. Rad. MC-2, MC-3	42 N 4201C	42 N 4233C	Knight 2550	42 N 4201C	42 N 4202C	Shell CB12	42 N 4201C	"
Gen. Rad. MC-4, MC-5	42 N 4218C	42 N 4233C	Lafayette HE-15, 15B	42 N 4201C	"	Sonar D	42 N 4201C	42 N 4233C
Gen. Rad. Echo 9	42 N 4201C	42 N 4233C	Laf'tte HB-115, 115A	42 N 4201C	"	Sonar G	42 N 4221C	42 N 4232C
Globe CB100	42 N 4201C	42 N 4226C	Laf'tte HE-20, 20-A,	42 N 4201C	42 N 4202C	Tefrad	42 N 4201C	"
Globe CB100A	42 N 4201C	42 N 4233C	Lafayette 20B, 20C,	42 N 4201C	42 N 4202C	Utica MC-27, TC-27,	42 N 4201C	42 N 4226C
Globe Pocket Phone	42 N 4204C	42 N 4205C	Lafayette 43, 90	42 N 4201C	42 N 4202C	Utica T, C11	42 N 4201C	42 N 4226C
Hallcrafters CB-2,	42 N 4215C	42 N 4227C	Laf'tte HE-29, 29A,	42 N 4201C	42 N 4233C	Utica Mariner	42 N 4201C	"
Hallcrafters CB-3,	42 N 4215C	42 N 4227C	Laf'tte HE-29B, 66, 82	42 N 4201C	42 N 4233C	Vocaline ED276,	42 N 4222C	"
Hallcrafters CB-3A,	42 N 4215C	42 N 4227C	Lafayette HE-29C,	42 N 4204C	42 N 4205C	Vocaline ED27M	42 N 4222C	"
Hallcrafters CB-5,	42 N 4215C	42 N 4227C	Lafayette HE-60, 75L,	42 N 4204C	42 N 4205C	World Radio ECBK	42 N 4201C	"



SOLID STATE SUBMINIATURE NOISE LIMITER

- For Hams, CB'ers
- Suppresses Noise From Any Type Ignition System, Motors, Atmosphere

795



The Kolin solid state noise limiter is an extremely effective self-adjusting device, which suppresses impulse noise in your receiver when receiving AM. Small enough to mount directly inside most receivers, it will work on supply voltages of 6 to 220 volts AC or DC. Only 3 connections are required. A switch is used to disable unit in normal quiet areas. Works on all Tube and Hybrid receivers employing a diode detector. All necessary instructions and mounting hardware is supplied. Size: 1 7/8" x 1 1/4" x 1/2".

42 N 4510 Shpg. wt., 8 oz. Net 7.95

AMECO MODEL PV-27 NUVISTOR PREAMPLIFIER FOR 27 MC

1367



• Over 20 DB Gain

The PV-27 NuVistor Preamplifier will improve your gain and noise figure considerably when used ahead of your present citizen band receiver, or transceiver. 2 tuned circuits and a 6DS4 NuVistor are used for a gain of 20 db and a noise figure of 2.0 db at 27 Mc. Power requirements are 100-150 V. at 8 ma. and 6.3 V. at .135A. Only 2 1/2" x 3 1/2" x 7". Shpg. wt., 2 lbs.

42 N 6901 PV-27 wired & tested Net 13.67

UNIVERSAL LAFAYETTE CITIZENS BAND AMATEUR SPRING & SWIVEL BALL-MOUNT BASE

Chrome Plated Swivel Ball Jointed Mount Base

Universal Lafayette chrome plated swivel ball mount base with lug terminals for use with mobile antennas. Can be mounted vertically or horizontally on any surface. With lug terminals for use with mobile antennas. Imported. Shpg. wt., 3 lbs.

99 N 3030 Net 1.85



Heavy-Duty Chrome Plated Stainless Steel Spring

Universal Lafayette Heavy duty chrome plated stainless steel spring. Provide maximum support for long whips and heavy center-loaded whips. Shpg. wt., 2 lbs.

99 N 3036 Imported Net 2.98



395

LAFAYETTE TELESCOPIC CB WHIP ANTENNA


Sturdy, attractive chrome plated whip antenna that telescopes from approx. 45" fully extended to only 15" to facilitate portability and storage. Ideal for shorter distances up to several miles. Has enclosed base loading coil for proper impedance matching. Complete with removable PL-259 connector that permits direct top, side or rear mounting to transceiver. Imported.

89 N 3015 Shpg. wt., 1 lb. Net 3.95



LAFAYETTE CB TO AM ANTENNA COUPLER

595



Specially designed network permits any Citizen's band mobile antenna to be used also for broadcast reception. No switching necessary. With SO-239 antenna receptacle, 2 ft. lead with coaxial auto plug for broadcast radio connection and 2 ft. lead with PL-259 coaxial plug for transceiver connection. Shpg. wt., 1/4 lb.

42 N 0903 Net 5.95

LAFAYETTE CHROME PLATED MOBILE BUMPER MOUNT WITH STAINLESS STEEL STRAP



395

- Completely Adjustable For Use With Most Types of Automobile Bumpers
- Highly Reliable and Durable!


An outstanding Lafayette mobile Bumper Mount featuring chrome plated mount and stainless steel strap which is completely adjustable for vertical mounting on most types of automobile bumpers. Eliminates need of cumbersome link type chain mounts. Shpg. wt., 1 1/2 lbs.

99 N 3035 Imported Net 3.95

Lafayette Cat. No. 653 135

LAFAYETTE Base Station Citizens Band Antennas

Famous LAFAYETTE "Starfire V" Deluxe 5 Element Citizen Band Beam Antenna



ONLY
37⁹⁵

MADE IN U.S.A.

Check these outstanding specifications

ELECTRICAL

- GAIN—10db Forward gain
- F-B ratio: —25 db
- V.S.W.R. under 1.5:1 across 27MC hand
- Gamma Matched to 52 ohm Coax Transmission Lines

MECHANICAL

- Boom Length 17'
- Height: 18'6"
- Turning Radius: 8'6"
- Mounts on Masts up to 2" in diameter
- All aluminum construction

The STARFIRE "V" 5 Element vertical beam is one of the most powerful CB antennas ever offered by Lafayette. Tremendous forward gain multiplies your effective radiated power by as much as 10 times. Front-to-back ratio 25 db, V.S.W.R. under 1.5:1. Gamma matched to 52 ohm coax-transmission lines. All aluminum construction for greater weather resistance. Boom length 17 ft. Reflector element (highest 18½ feet. Mounts on masts up to 2" in diameter. Turning radius 8'6". Vertical wind load 125 lbs. STARFIRE "V" is furnished with complete mounting instructions. Less mast and coax cable. Shpg. wt., 15 lbs.
42 N 0114WX Net 37.95

LAFAYETTE
"Range-Boost"™
End Fed 1/2-Wave
CB Antenna

19⁹⁵

Static Clover Leaf

- Static Clover Leaf Ball Design Reduces Receiver Noise
- 3.75 db True Omni-Directional Gain
- Forward Power Measurement—5 watts
- VSWR—1.17

The "Range-Boost" 1/2-wave CB base station is the latest addition to Lafayette's famous line of high performance CB antennas. Specially designed anti-static clover-leaf ball drastically reduces receiver noise by continuous dissipation of static discharge. Offers a 3.75 db true omni-directional gain. Forward power measurement: full 5 watts; VSWR is 1.17. Includes a phasing transformer, rubber covered for moisture resistance. Vertical radiator consists of 3 seamless aluminum tube sections topped by a solid aluminum 108" top section. 3 5/4" radials provide proper transmission line decoupling. Direct ground lightning protection. 50 ohm. 17'6" over-all length. Accepts PL-259 cable connector. Shpg. wt., 10 lbs.
42 N 0111WX Net 19.95

Made in U.S.A.

LAFAYETTE'S "Star-Fire"™

3-Element Vertical Beam CB Antenna




16⁹⁵

- Multiplies Power 8 Times
- Completely Precision Tuned and Ready to Assemble and Install
- Steel Parts Irridite Treated to MIL Specs

An exceptionally high gain, directional antenna system for Citizen's Band communications. It develops a forward gain of 8 db. Front-to-back ratio is 25 db; front-to-side, 40 db. 50 ohm feedline match for maximum efficiency. Comes with bracket for vertical or horizontal mounting. The 1¼" O.D. aluminum boom is 8 feet long. ¾" to ⅜" O.D. aluminum elements are approximately 16½ ft. long. All steel hardware is irridite treated to MIL specs. Completely factory pretuned, the "Star-Fire" is furnished with complete instructions. Shpg. wt., 11 lbs.
42 N 0113WX Net 16.95

Deluxe LAFAYETTE Ground Plane Antenna



- The Ideal Antenna For Your CB Base Station
- High Efficiency Ground Plane Antenna
- All Aluminum Construction
- Accepts PL-259 Connector

11⁹⁵

Solid aluminum 108" heat-treated radials and radiator. Elements supplied in two 54" lengths joined by threaded coupling nuts. Radials droop for 50 ohm match. Accepts 1¼" tubing RG-58/U cable and PL-259 connector. Shpg. wt., 4 lbs. Imported.
99 N 3031W Net 11.95

60 FT. RG8A/U FOAM POLYETHYLENE COAX CABLE ASSEMBLY



Ready to Use. Extremely Low Line Loss PL-259 Termination on Both Ends. Boost your operating range by increasing the efficiency of your antenna system. Ideal for Citizens Band Amateur or Commercial Fixed Station use. Low loss Impedance 50 ohms. 60 Foot length complete with PL-259 plug on each end. Shpg. wt., 7 lbs.
42 N 7003 9.50



BLITZ BUG LIGHTNING PROTECTOR

Designed to fit any standard coaxial cable, the "Blitz Bug" employs the spark gap principle to eliminate static build up on co-axial cables. Provides a constant drain off, reducing chances of a direct lightning strike and in many cases eliminating noise problems. Constructed of ¾" O.D. brass by 2¼" long. Employs one PL-259 plug and one DKCB connector (takes PL-259 plug.) Shpg. wt., 1 lb.
42 N 2001 Net 3.95

LAFAYETTE Mobile Citizen Band Antennas

LAFAYETTE ALL STAINLESS STEEL CB MOBILE ANTENNA

OUTSTANDING FEATURES

- 102" Stainless Steel Whip For Optimum 11-Meter Performance
- Heavy-Duty Chrome Plated Stainless Steel Spring
- Chrome Plated Swivel Ball Jointed Mount Base

6⁹⁵

Chrome plated swivel mount base designed to be mounted on any surface. Stainless steel spring holds rod in properly adjusted position and prevents rod damage from shocks and blows. Stainless steel whip for resiliency and strength. Shpg. wt. 4 lbs. Has lug terminals for 42 N 7002 cable assembly. Imported

99 N 3034WX

Net 6.95



LAFAYETTE BASE LOADED "AUTO-TOP" CITIZEN BAND ANTENNA

- Automobile rooftop application affects ideal Omnidirectional signal patterns
- Mounts neatly from outside vehicle in 3/4" hole
- Base loaded Phasing Transformer completely weatherproof
- 39" Stainless Steel whip

Only 7⁹⁹

The Lafayette Base Loaded "Auto-Top" Citizens-Band antenna offers the CB'er the ideal omni-directional signal pattern with very low signal to noise. This quality antenna consists of an inconspicuous base loaded, neutral gray weatherproof phasing transformer (only 4" high, and 1" in diameter), a 39" stainless steel whip, and all mounting hardware including complete and simple mounting instruction sheets. Antenna mounts in 3/4" hole. Comes less cable. Shpg. wt. 2 lbs.

42 N 0120

Net 7.99



LAFAYETTE CENTER-LOADED CB COWL MOUNT ANTENNA

6⁹⁵

MADE IN U.S.A.

- Rugged Fiberglass Construction
- Easily Mounts On Cowl or Rear Deck
- Only 48" High

Lafayette makes antenna news with this ideal center loaded fiberglass antenna—only 48" high but performs like 102" antennas. Designed for cowl mounting, this latest development in mobile antennas provides an excellent radiation pattern. Substitutes for conventional 1/4 wave whips as well as base-loaded antennas in the 27 mc band. The four foot whip eliminates the possibility of striking overhead objects. A black plastic covering of whip insures against shorting. Specially designed rocker support assures 8-point grounding and permits mounting up to 35° angle on fender, cowl or rear deck—Fits any 1 1/4" to 1 1/2" mounting hole. Complete with 5 ft. of RC-58/U cable.

42 N 0121W Shpg. wt., 3 lbs. Net 6.95



NEW LAFAYETTE CENTER-LOADED MOBILE CB GUTTER CLAMP ANTENNA

- EASILY SNAPS ON RAIN GUTTER OF AUTOMOBILE
- OFFERS OUTSTANDING 11 METER PERFORMANCE
- PORTABLE—Easily Removable When Not in Use—Prevents Theft or Damage



This portable CB Center-loaded antenna is ideal for the CB'er. Easily removable when not in use—prevents theft or damage. Gutter clamp snaps on rain gutter of automobile. Heavy spring assures positive grip. Clamp is heavily plated to resist corrosion. Only 20 inch in length—outstanding 11 meter performance SWR 1:1. Furnished with 12 ft. of RG58/U cable with PL-259 Connector. Shpg. wt., 3 lbs.

42 N 0125

10.88

ONLY 10⁸⁸

Made in USA



NEW DELUXE LAFAYETTE CB/AM CENTER LOADED COWL MOUNT ANTENNA

13⁹⁹

- Permits outstanding Reception and Transmission on CB —and Reception on AM



Complete With Automatic Dividing Harness

Lafayette's exciting new antenna serves the "CB'er" with two functions in one—CITIZENS BAND AND BROADCAST BAND. Eliminates the need of two antennas. This single, sturdy—heavily chromed centerloaded cowl mount antenna fits easily in the 7/8" to 1 1/4" hole left by the auto antenna. Only 32" long, this superb antenna package incorporates an automatic dividing harness which includes a 1 ft. low loss cable with pin plug to your AM Set, a 2 ft. RG58/U Cable with PL-259 connector to your CB set, and a 5 ft. RG58/U cable with PL-259 connector to your antenna. The dividing harness fits snugly out of sight under the dash. Shpg. wt., 4 lbs.

42 N 0124W

Net 13.99



LAFAYETTE "PROFESSIONAL" DOUBLE CHAIN BUMPER MOUNT CB ANTENNA

- Heavy Duty Double Chain Bumper Mount
- Heavy Duty Aluminum Plated Spring
- 102" Stainless Steel Whip
- Includes Whip Hold-down Clip

15⁹⁵

Complete heavy duty double-chain bumper mount assembly. No holes to drill; assembles in minutes. Consists of professional heavy-duty double-chain bumper mount with "Z" shaped links, cadmium plated shock absorbing springs that can bend through 90° without damage, 102" stainless steel whip with removable plated steel adapter and whip hold-down gutter clip. Built for long, satisfactory service and performance. Less cable. Fits all cars.

42 N 0119WX Shpg. wt., 8 lbs. Net 15.95

MADE IN U.S.A.



LAFAYETTE CB BUMPER MOUNT ANTENNA WITH STAINLESS STEEL STRAP

8⁹⁵

- Chrome Plated Bumper Mount with Stainless Steel Strap
- 102" Stainless Steel Whip, Heavy Duty Chrome Plated Stainless Steel Spring

An outstanding Lafayette CB antenna featuring a full-size 102" stainless steel whip and a fully adjustable chrome plated mount with a stainless steel strap which was specially designed to fit most cars. Heavy duty chrome plated stainless steel spring is built for extremely rugged mobile use. Shpg. wt., 3 lbs. Imported.

99 N 3032WX

Net 8.95



20 FT. COAXIAL CABLE ASSEMBLIES FOR CITIZENS BAND EQUIPMENT



(A) These cable assemblies are necessary for connection (B) between Citizens Band Transceiver and Antenna.

TYPE A—Consists of 20 ft. RG-58/U cable with PL-259 plus UG-175/U on both ends. Required for Ground Plane and Coaxial and Mobile Antennas terminating in a coaxial jack. Shpg. wt., 8 oz. 42 N 7001 Type A; 20 ft. length Net 2.49

TYPE B—Same as type A except one end is terminated with PL-259 plus UG-175/U and other end with universal ring type terminal lugs for mobile antennas. Shpg. wt., 8 oz. RECOMMENDED FOR USE WITH LAFAYETTE ALL STAINLESS STEEL MOBILE ANTENNA ABOVE, 42 N 7002 Type B; 20 ft. length Net 2.15

Selected CB Antennas and Accessories

B & W 550A Antenna Coaxial Switch



- No Loss When Switching Antennas

An inexpensive multi-position coaxial switch transmitters that eliminates screwing and unscrewing coaxial connections. Lets you instantly select any one of five transmitters, transceivers, antennas, exciters, receivers, etc., using 52 or 75 ohm line. The switch handles up to 1 kw of modulated power with a maximum crosstalk of -45 db at 30mc.

40 N 1602 Shpg. wt., 2 lbs. Net 8.25
 Model 902-Knob for 550A

40 N 1603 Net 1.02
 3818-Dial plate for 550A

40 N 1604 Net .75

B&W MODEL 550A-2. Single pole, 2-position switch. Same as 550A except designed for switching one of 2 transmitters, transceivers, antennas, exciters, receivers, etc. Shpg. wt., 1½ lbs.

40 N 1605 Net 7.20

Antenna Specialist Super Magnum Model M-117 ½-Wave CB Base Station Antenna




29³⁵

Rigid aluminum vertical radiator provides; minimum improvement in signal-to-noise of 6 db, a 3.75 db of true gain as compared to a flat ground plane antenna. Top mounted orbital ball drastically reduces static discharge noise. Full ½ wavelength 108" radials offer maximum RF coupling... low radiation angle intensifies signal coupling. Includes powerful phasing transformer and mounting hardware to take up to 1½" masts. Treated against corrosion. Easy to install. Shpg. wt., 14 lbs.

Model M-117 Super Magnum
 42 N 1001WX Net 29.35

New Antenna Specialists M-119 "SCANNER" Multi-Element Directional CB Antenna System



Includes Electronic Scan Control Unit with Indicator Lights

only
 64⁶⁸

- Compact Array of 3 Sector-Phased Vertical Elements
- No Mechanical Rotator Needed

The "Scanner" is a multi-element directional antenna system electrically rotatable for a full 360° in three 120° steps. This is accomplished by use of the "Scanner's" separate electronic Scan Control unit. Compact array of 3 sector-phased 17½ ft. vertical elements extend less than 3 feet from the mounting boom. Full circle scan coverage —no blind spots. Resists over 100 mph winds. 7.75 db directional gain —23 db front to back ratio. Shpg. wt., 18 lbs.

42 N 1029WX Net 64.88
 4 Conductor Rotor Cable for use between Scanner Control Unit and Antenna.
 32 N 8910 100' coil Net 2.50

TENNA TL-3 CONCEALED "TOP LOADED" MOBILE ANTENNA



Deluxe top loaded coil design completely disappears into your cars fender. Adds beauty; prevents theft. Ball-joint permits 40° sweep-back when extended. Large seamless tube construction reduces capacity losses. Extends from 0" to 50". With 54" detachable radar-type polyethylene cable. Shpg. wt., 3 lbs.

42 N 8603W Net 8.14

LAFAYETTE Citizens Band Walkie-Talkie Antenna Replacement Guide


- Fits All Lafayette and many Famous name Walkie-Talkies

Designed for the various Lafayette "Walkie-Talkie" portable CB Transceivers indicated. Will also fit many of the other "Walkie-Talkie" units manufactured by companies other than Lafayette. Check the specs of the antennas listed on the chart below for the antenna best suited to your present "Walkie-Talkie." Average shpg. wt., 1 lb. Imported.

Antenna Stock No.	Sections	Diam. of Base	Collapsed Length	Extended Length	For Lafayette Walkie-Talkie Models	Net-Ea.
99 N 3008	12	½"	6"	52¾"	HE-29, HE-29B	1.95
99 N 3037	11	½"	6¼"	54½"	HA-60, HA-61, HE-86, HE-88	1.95
99 N 3038	9	¾"	7¼"	52¾"	HE-75, HE-88	1.95
99 N 3039	11	¾"	5¾"	50"	HE-66, HE-82, HE-83	1.49
99 N 3040	9	¾"	5¾"	43¼"	HA-70	.98
99 N 3048	9	¾"	5¾"	43¼"	HA-70A	.98
99 N 3041	11	¾"	5¾"	51"	HE-29C	1.95
99 N 3017	10	¾"	7"	58"	HA-150	1.95
99 N 3007	11	¾"	7¼"	62¾"	HA-300	2.25

LOW-COST ECONOMY C B GROUND PLANE ANTENNA

- Lightweight Tubular aluminum elements



790

Made in U.S.A.

Here's rugged performance in a Citizens Band base station antenna at a truly economical price.

Incorporating a special "drooping radial" design for improved impedance characteristics, this excellent ground plane antenna utilizes a 360° polar pattern to provide complete coverage in any direction. Made-to-last construction features a rugged 1 inch diameter radiating element. A double U-bolt arrangement provides the strongest possible mount under the most severe conditions.

42 N 7401WX Shpg. wt., 6 lbs. Net 7.80

CDR AR-22 AUTOMATIC ROTOR FOR CITIZENS BAND

- Ideal for Use with Lafayette and Famous Name 3, 4, and 5 Element Beam Antennas

This heavy-duty rotor unit will handle antennas up to 150 lbs. Simply set the control unit pointer to the desired direction, and the antenna will automatically rotate to this position and stop. Perfect for TV, Ham or Citizen Band application. Rotor unit employs 12 heavy duty ball bearings in two 6½" races. Reversible clamps on rotor will take masts from ¾" to 2" O.D. Control unit is marked in compass points. N.S.E.W. NW, NE, SW, and SE. Housed in attractive brown plastic cabinet with rubber feet. For 110-120 volts, 50-60 cps AC. Requires 4 conductor cable. Shpg. wt., 14 lbs.



31³¹

42 N 8605WX Net 31.31

Deluxe CDR Model TR-44 Rotor

Deluxe version of AR-22. Increased rotational torque. 48-ball bearing movement. Finished with famous CDR "HAM-M" Type control box. Dimensionally identical to AR-22. Shpg. wt., 18 lbs.

42 N 8606WX Net 58.75

4 conductor cable for AR-22 and TR-44

32 N 8910 100' coil Net 2.50

32 N 8911 less than 100' per ft. Net .03

over 100' per foot Net .025




LAFAYETTE "Dummy" Antenna Load For CB Transceivers

A 52 ohm non-inductive load for testing and tuning-up Citizens Band transmitters up to 5 watts. It permits tune-up into a non-radiating element instead of into antenna — in compliance with F.C.C. regulations. Built-in PL-259 coaxial plug is easily connected and disconnected from equipment. Shpg. wt., 1 lb.

42 N 0902 Net .98

LAFAYETTE Deluxe Communications Receivers

LAFAYETTE Professional-Quality 8-Tube Amateur Communications Receiver Model HA-230



4 BANDS:

- 550-1600 Kc
- 4.8-14.5 Mc
- 1.6-4.8 Mc
- 10.5-30 Mc

MODEL HA-230 WIRED

89⁵⁰
\$5 Monthly

MODEL KT-340 KIT

74⁵⁰
\$5 Monthly

NEW "ALWAYS ON" FILAMENT VOLTAGE FOR MIXER AND OSCILLATOR STAGES FOR FREQUENCY STABILITY!

• 8 Tube Superhet Circuit • 1 RF + 2 IF Stages for High Gain Reception • Easy-to-Read, Illuminated, Slide Rule Dial • Built-in Q-Multiplier for Crowded Phone Operation • Antenna Trimmer for Optimum Performance on All Bands • Calibrated Electrical

Outstanding Bandsread, Selectivity with built-in Q-multiplier, and sensitivity combine to make the HA-230 one of the "hottest" general coverage bandsread receivers we have ever offered. Special filament transformer provides continuous voltage on critical oscillator and mixer stages, maintains frequency stability . . . prolongs tube life . . . faster "warmup." For the crowded amateur bands—illuminated Slide Rule Dial, bandsread with markings every 5 KCS on 80 and 40 meters, every 20 KCS on 20 and 15 meters, and every 50 KCS on 10 meters, plus an edgewise S-meter. For the SWL—a 0-100 logging scale for "instant reset" to a desired station, an RF Stage with an antenna trimmer for peak performance PLUS 2 IF stages for improved selectivity. Receiver sensitivity—1.0 microvolts for 10 db Signal-to-Noise Ratio. The Built-in BFO can be used to separate CW stations by means of the pitch control, while the Q-multiplier adds the selectivity needed for crowded phone band operation. Front panel controls: FUNCTION SWITCH, AUDIO GAIN, SELECTIVITY (Q-

Bandsread on Amateur Bands 80 thru 10 Meters • 0-100 Logging Scale for SWL's • Effective Automatic Noise Limiter • AVC-MVC Selector on Front Panel • Stable Oscillator and BFO for Clear AM CW and SSB Reception • Built-in Edgewise S-Meter

Multiplier), FREQUENCY (BFO), BAND SELECTOR, IF GAIN, TRIMMER, AVC-MVC SWITCH, ANL SWITCH, MAIN TUNING, BANDSPREAD TUNING, and headphone jack. Selectivity—60 db at 10KC, 0.8 KC @ 6db (with Q-multiplier), IF—455KC, Speaker—External PM type (not supplied), 4 or 8 ohms impedance, Audio Output—1.5 Watts, Tubes: 3-6BA6, 2-6BE6, 1-6AV8, 1-6AV6, 1-6AQ5, 1-5Y3. Size—7Hx15Wx 10"D. For 105-120. 60 cos AC. 50 watts. Imported.

99 N 2522WX Shpg. wt., 25 lbs. Net 89.50
99 N 2532 Model HE-48 Matching 3x5" speaker. 4 lbs. Net 7.95

KT-340 SEMI-KIT

This receiver is also available in kit form with all major components and front end premounted and pre-calibrated. Minor components are easily installed. Imported


99 N 2521WX Model KT-340. Semi-Kit Net 74.50

RECEIVER SPEAKER MATE MODEL HE-48

795

MATCHING 3x5" speaker in handsomely styled cabinet to match HA-230. Gives clean audio response. 8 ohm impedance. Size: 7³/₄H x 3¹/₂W x 5"D. Shpg. wt., 4 lbs. Imported.

99 N 2532 Net 7.95



LAFAYETTE "BEAT BANDER" EXTERNAL BFO

- Solid State Circuitry

Designed for any receiver that does not have its own BFO. Enables simultaneous use of BFO and receiver's "Q" multiplier. Connects easily to antenna circuit. Frequency range: 3.5 to 4 MC on fundamentals. Harmonics: 7-8 MC, 14-16 MC, 21-24 MC, and 28-32 MC. Stable, reliable transistor circuitry. With coax cable and 9-volt battery. 4¹/₂x3¹/₂x3". Shpg. wt., 1¹/₂ lbs. Imported.

99 N 2502 Net 11.95



LAFAYETTE 10-80 Meter Dual Conversion Amateur Receiver Model HA-350 with Mechanical Filter For High Selectivity



189⁵⁰
as low as
\$9 monthly

5 HAM BANDS PLUS WWV
3.5-4.0Mc 7.0-7.5Mc 14.0-14.5Mc
21.0-21.5Mc 28.5-29.1Mc WWV at 15Mc

- Mechanical Filter for Exceptional Selectivity
- 12 Tubes
- Dual Conversion
- Complete With Crystals For 80, 40, 20, 15 and 10 Meters
- Product Detector — Selectable Upper Lower Sideband Reception
- 100 KC Crystal Calibrator and Crystal BFO
- Automatic Noise Limiter
- "S" Meter—Calibrated in "S" Units 1-9 and DB scale to +40 db
- WWV Reception

The HA-350 is Lafayette's newest and most advanced model in its line of popular communications receivers. Both its performance and appearance are professional-type, designed exclusively for the amateur with the problems of today's crowded ham bands in mind. Features Dual Conversion giving an Image Rejection of more than 40 db and IF Rejection of more than 40 db—important especially on the high frequency bands for correct tuning. One control tuning makes the HA-350 a pleasure to operate and features wide-spread tuning utilizing an 8-position band-switch. Product Detector, providing selectable upper or lower sideband, solves the problems in SSB reception. Tuneable preselector circuit gives sensitivity of less than 1 microvolt for 10 db signal-to-noise ratio. Selectivity: Bandwidth of 2KC at 6 db down and 6KC at 60 db down using Mechanical Filter in IF. Front panel 100KC crystal calibrator reset control used in conjunction with the 15 MC WWV National Bureau of Standards station assures consistent and accurate calibration. Remote

MECHANICAL FILTER

In the HA-350, ultra-sharp selectivity is achieved by means of a true mechanical bandpass filter in the 455 Kc IF section. The filter consists of three sections—an input transducer, 6 non-corrosive nickel alloy resonators and an output transducer. The "skirt" selectivity is greatly increased as shown by the almost rectangular I.F. bandpass curve.

control socket on back permits simultaneous control of HA-350 with a transmitter. Audio output: 1-watt maximum. Speaker impedance: 8; 500 ohms (speaker not supplied). Front panel controls: Preselector; Cal—On/off; Band Selector; Receive/Send; Tuning Cal Reset; Function—Off/AM/SSB1-CW/SSB2; RF gain; AF Gain; ANL; Phone jack. Tube complement: 6B26—RF amp.; 6BL8—Xtal controlled 1st mixer; 6BE6—2nd mixer; 6BA6—VFO; 6BA6—IM amp.; 6BA6—IF amp.; 6AL5—AVC rectifier and AM noise limiter; 6AQ8—product detector and crystal calibrator; 6AV6—1st audio amplifier; 6AQ5 audio output; 6BA6—BFO; OB2—regulator, Silicon Full wave rectifier. Size: 15Wx7½Hx10"D. For 115V 50/60 cps AC. Imported. Shpg. wt., 25 lbs.

99 N 2524WX Net 189.50
Model HE-48 3x5" Speaker in cabinet for HA-350.
99 N 2532 Net 7.95



MODEL HE-48 SPEAKER

795

3x5" speaker in handsome styled cabinet for Lafayette HE-30, KT-320, HE-80, HA-63, HA-350, HA-230, KT-340, HA-225 receivers, also ideal receiver speaker mate for many other communication receivers. Gives clean audio response, 8 ohm impedance. 7¾Hx3½Wx5"D. Shpg. wt., 4 lbs. Imported.
99 N 2532 Net 7.95

Deluxe LAFAYETTE Professional-Quality 14-Tube Amateur Communications Receiver Model HA-225

5 BANDS

- 150-400 Kc
- 1.6-4.8 Mc
- 4.8-14.5 Mc
- 10.5-30 Mc
- 48-54 Mc

139⁵⁰

As Little as \$6 Monthly

NEW "ALWAYS ON" FILAMENT VOLTAGE FOR MIXER AND OSCILLATOR STAGES FOR FREQUENCY STABILITY



Dual Conversion On 6 Meters

- 14-Tube Superheterodyne Circuit
- Extra RF Stage, Mixer/Osc For Dual Conversion On 6 Meters
- 1 RF Plus 2 IF Stages For High Gain Reception On All Other Bands
- New Product Detector Circuit For Improved SSB Reception

The HA-225 features full amateur band coverage of 80 through 6 meters plus Marine Beacon Band. Special filament transformer provides continuous filament voltage to oscillator and mixer tubes . . . maintains critical frequency stability . . . prolongs tube life . . . reduces warmup time. Sensitivity is .5 Microvolt for 10 db s/n ratio. Selectivity is variable from 60 db to 93 db in Q-Multiplier operation with ± 10 KC detuning. Calibrated electrical bandspread on amateur bands 80 thru 10 meters (6 meters is tuned with main tuning controls). Dual conversion on 6 meters provides average of 50 db image rejection. Other features include antenna trimmer for optimum performance on all bands, built-in edgewise "S" meter, special recording jack in rear permits easy connection to tape recorder, remote control socket on the back allows simultaneous control of HA-225 with a transmitter. Front Panel Controls: AF Gain, RF

- Separate BFO And Q-Multiplier Circuits (Can be Used Simultaneously)
- Crystal Calibrator For Checking Receiver Calibration Markings
- Improved Automatic Noise Limiter
- Voltage Regulated Power Supply

Gain, 5-Position Function Switch, BFO Frequency, Band Selector, Q-Multiplier Selectivity, Q-Multiplier Frequency, Band Spread Tuning, Main Tuning, Antenna Trimmer. Power On-Off Switch, MVC-AVC Switch, Rec-Send Switch and Headphone jack, IF — 455 KC. Audio Output — 1.5 Watts. Output Impedance — 8 and 500 ohms (speaker not supplied). Tubes: 4-6AQ8, 3-6BA6, 2-6BE6, 1-6BL8, 1-6AL5, 1-6AQ5, 1-0A2 plus 6CA4 rectifier. Size: 17Wx7½Hx10"D. Shpg. wt., 28 lbs. Imported.

Model HA-225. Less Calibrator Crystal	
99 N 2523WX	Net 139.50
Optional Calibrator Crystal, 100KC, Type HC/13U	
40 N 0901L	Net 3.95
Model HE-48 Matching 3x5" speaker. 4 lbs.	
99 N 2532	Net 7.95




HE-48 SPEAKER

7⁹⁵

3"x5" speaker in handsome styled cabinet for Lafayette HA-225, HE-30, KT-320, HE-80, HA-63, HA-350 receivers, also ideal receiver speaker mate for many other communication receivers. Gives clean audio response. 8 ohm impedance. 7¾Hx3½Wx5"D. Shpg. wt., 4 lbs. Imported.

99 N 2532 Net 7.95



Deluxe LAFAYETTE 7-Tube SWL Broadcast Receiver Model HA-63



A Handsome Feature-Packed Receiver
For the Shortwave Listener and Novice

4 BANDS

- 550-1600 Kc
- 1.6-4.8 Mc
- 4.8-14.5 Mc
- 10.5-30 Mc

A Superb Receiver
At Lafayette's Low Low Price!

64⁵⁰
\$6 monthly

★ Superheterodyne Circuit Including RF Amplifier Stage

Electrical Bandsread
on the
80, 40, 20, 15 and 10
Meter Bands

- Superhet Circuit; Illuminated "S" Meter
- 1.5 Microvolt Sensitivity
- 3-Section Tuning Capacitor With Electrical Bandsread
- Antenna Trimmer For Optimum Performance On All Bands
- Front Panel AVC-MVC Selector, ANL and BFO
- For Headphones or External Speaker
- AC Transformer Operated
- Big Slide Rule Dial

An excellent choice for the beginning shortwave listener or novice amateur. Provides full fingertip coverage of AM broadcast, marine and aeronautical bands, civil defense, WWV, amateur and foreign frequencies. The BFO permits (CW) code reception too. BFO pitch is not variable. 4 bands cover: 1.6-4.8MC; 4.8-14.5MC; 10.5-31MC and 0.55-1.6MC AM band. Full electrical bandsread on all frequencies with 0-100 logging scale and built in "S" meter assures you of accurate tuning. Superheterodyne circuit includes RF amplifier and three-section tuning gang condenser with separate tuning coils for each band. These provide outstanding selectivity and a sensitivity of 1.5 microvolts. Big slide-rule dial is easy-to-read. Other features

are switchable AVC/MVC to reduce blasting or fading; automatic noise limiter (ANL) for maximum noise rejection; and an antenna trimmer control which assures optimum reception on all bands. All controls are conveniently located on front panel. Headphone jack for private listening. An external PM type speaker is required (not supplied). Impedance 4-8 ohms. Beautifully styled in modern steel cabinet. Tubes: (2) 6BA6, (2) 6BE6, (2) 6AV6, (1) 6AR5 plus selenium rectifier. Audio output: 1.5 watts. AC transformer operated. 117 volts 50/60 cycles AC. Size: 13Wx7½Hx10"D. Shpg. wt., 19 lbs. Imported.
99 N 2534WX Net 64.50
99 N 2532 Matching Speaker Net 7.95

LAFAYETTE "Precon" Amateur Preselector Converter



49⁵⁰
\$5.00 Monthly

- Crystal Controlled
- For 80-40-20-15-10 Meter Bands
- As a Converter — Converts Receiver to Dual Conversion Operation
- Improves Selectivity
- Widens Band Spread

The "Precon" is a crystal-controlled dual function unit for the price of one. As a preselector, it can be used ahead of any receiver to greatly improve gain, image rejection, and sensitivity. Tuned inter-stage circuits and 2 stages of RF amplification assures a high signal-to-noise ratio. . . . As a converter, receiver range can be extended to 30 MC (receiver must tune 3.5-5.2 MC). Sensitivity and stability are excellent. Antenna trimmer on front panel. 3 crystals are included for 20, 15 and 10-meter bands. 52-ohm antenna co-axial connector is built-in. PL-259 connector required for output cable. Attractive modern steel cabinet with 4 rubber feet. Operates on 117 V 50/60 cycles. AC. Size: 10Wx6Hx8"D. Shpg. wt., 10 lbs. Imported.
99 N 2530 Net 49.50

LAFAYETTE Deluxe Self-Powered VFO



- Covers 80 through 10 Meter Amateur Bands
- High Output to Drive Any Modern Transmitter

34⁵⁰

A deluxe variable frequency oscillator providing full coverage of the five bands from 80 to 10 meters. Employs a high "Q" series tuned Clapp oscillator, remarkable for its low drift. A VR tube eliminates frequency shift due to variations in line voltage. High output of 10-20 volts is sufficient to drive any modern transmitter. Features large easy-to-read illuminated slide rule dial with smooth tuning drive. Dual output impedance. Low heat silicon diode power supply prevents drain on transmitter power supply. Tubes 6AU6, 6AQ5, OA2. Size: 6½Wx5¼Hx7½"D. For 117 volts 50/60 cps AC Shpg. wt., 7½ lbs. Imported.
99 N 2501 Net 34.50

LAFAYETTE Quality Meters and Testers

for the CB'er and AMATEUR — Improved Performance — Low, Low Prices

LAFAYETTE MINIATURE ILLUMINATED MODULATION "S" METER

- Combination "S" Meter, % Modulation Meter and RF Power Output Meter
- Accurate D'Arsonval Movement
- Jewel Bearings

2⁹⁵



Highly accurate. Features wide viewing angle and 3-color scale. Front panel zero adjustment. Calibrated scales (1 MA full scale), 0 to 100% modulation, "S" units 0-9, also +10 and +30. Linear full scale markings of 0 to 5. Dimensions: dial face, 1 1/4"; depth 1 1/4" overall. Supplied with 4 mounting screws and lugs. For 6 or 12 volts. Dust resistant case. Shpg. wt., 8 oz. Imported.

99 N 2507

Net 2.95

LAFAYETTE RADIO FIELD INDICATOR

- Continuously indicates transmitter output
- Rugged 200 μ a meter movement
- Requires no Electricity, Batteries, or Transmitter Connection
- Powerful Magnet on Bottom Plate for Mounting on Dashboard or Other Metal Surface

6⁷⁵



A MUST FOR ALL
HAM AND CB OPERATORS

Checks performance of your marine, mobile or fixed transmitter. Features a 200 μ a meter movement with variable sensitivity control. Earphones can be plugged in for an aural check of output. Antenna extends from 3 1/4" to 10 3/4". Powerful magnet allows easy mounting. Use anywhere . . . requires no electricity or batteries. Dimensions: (less antenna) 3 1/4" x 2 1/4" x 2" D. Imported.

99 N 2509 Shpg. wt., 7 oz.

Net 6.75

99 N 2515 High output crystal earpiece for above

1.09

LAFAYETTE WAVE-METER for AMATEUR and CITIZENS BAND

- For Amateur and CB Use
- Instant Readings of Transmitter RF Output
- Requires No Power
- Compact, Portable, Accurate

6⁷⁵



A miniature wavemeter for checking transmitter output. Determines relative strength of fundamental frequency and any harmonic or parasitic radiation. Complete and self-contained, requires no power. Telescoping antenna is included. Tunes 1.6 to 150 mc in four calibrated bands. Only 3 1/4" x 2 1/4" x 1 1/2" D. Antenna is 10 3/4" extended. 3 1/4" telescoped, is fitted with a banana plug and is removable. Total shpg. wt., 8 oz. Imported.

99 N 2511

Net 6.75

MINIATURE ILLUMINATED "S" METER

- Jeweled Bearings
- Accuracy 2% of Full Scale
- High Quality D'Arsonval Movement
- Clear Plastic Front

2⁹⁵



Durable wrap-around plastic front panel provides wide-angle readability. Zero adjustment screw on front panel; jeweled bearing movement. Calibrated in "S" units from 0-9 with the scale terminating in +10 and +30 calibrations. Additional full scale calibrations of 0-5 and 0-10 in linear scale divisions. Silvered dials; black numerals and pointers. Illuminating lamp for either 6 or 12 volt operation. 1 1/4" dial face; 1 1/4" overall behind panel. Supplied with mounting screws. Imported. Shpg. wt., 8 oz.


99 N 2513

Net 2.95

SWR BRIDGE AND RF POWER METER

- Measures RF Output Power into Built-in 52 Ohm Dummy Load, Up to 15 Watts
- Direct SWR Measures From 1:1 to 10:1 and REL Power to 1 KW
- 50 μ a Meter Movement

21⁹⁵



Highly accurate SWR and direct power readings up to 50Mc. The unit may be permanently inserted in the transmission line for SWR and relative power monitoring. For 52 or 75 ohm lines. Insertion loss is negligible. Meter has 50 μ a movement; calibrated directly in watts from 0.15 and in SWR from 1 to 10 IF (reads infinity at full scale) . . . Housed in an attractive grey metal cabinet, 3 1/4" x 7 1/4" x 2 3/8". Sits on 4 rubber feet. Imported.


99 N 2508 Shpg. wt., 2 lbs.

Net 21.95

LAFAYETTE TRANSISTORIZED FIELD STRENGTH METER

- Permits Easy Tune-Up for Maximum Transmitter Output
- Earphone Jack to Monitor Audio
- Tuned Input from 2.53 to 57 MC

15⁹⁵



Covers 2.530 Mc to 57.000 Mc in 3 bands. Ideal for use with ham, Citizens Band or other transmitters within this frequency range. Enables user to tune his transmitter and antenna for maximum RF output. 200 μ a meter is calibrated from 0 to 10. Earphone jack provided. Front panel controls: gain on-off switch, tuning, and band selector switch. Battery powered—can be operated anywhere. With telescoping antenna and battery. Imported. Shpg. wt., 2 lbs.

99 N 2510

Net 15.95

99 N 2515 High output earpiece for above

Net 1.09


32 N 4802 Replacement battery for above

Net .13

DELUXE LAFAYETTE "S" METER

- Now for Hams, SWL's and CB'ers—A Signal Strength Meter Using VTVM Principles
- Easy To Install and Operate
- Magnetic Feet for Mobile Dashboard Mounting
- Sensitivity and Zero Adjust Controls

8⁹⁵



Designed for use with any superheterodyne receiver employing AVC. Meter is calibrated in "S" units from 1 to 9, and in db up to 30db over S9. Partial peak clipping is provided for noise limiting. Simple installation—B+, filament and ground. It is adaptable to either 6 or 12-volt equipment, and to receivers using 150 ma or 300 ma series string filament systems. Requires 150-200 VDC for B+. Complete with 12AU7 and installation instructions. Imported. Shpg. wt., 2 lbs.


99 N 2512

Net 8.95

ILLUMINATED COMMUNICATIONS "S" METER

- 2 Jewel Movement
- Clear Plastic Front
- Calibrated to S9 + 40 db

3⁹⁵




A quality "S" meter (basic 1 ma, 2 jewel movement) designed to replace many "S" meters used in communications receivers. Clear plastic front measures 2 3/8" square and meter fits standard 2 1/8" round hole. Perfect for the experimenter and amateur. Complete with mounting screws, instructions for installation and use. For 6 volt or 12 volt operation. Zero adjustment control on front panel. Imported. Shpg. wt., 1 lb.

99 N 2514

Net 3.95

LAFAYETTE For All of

LAFAYETTE 10 TO 80 METERS ALL-BAND VERTICAL TUNEABLE ANTENNA



- 10 To 80 Meters
- For Fixed Operation
- Omni-Directional, Vertically Polarized
- Irridite Treated To Mil. Specs

Made in U. S. A.

LOW LOW PRICE

14⁹⁵

Our best buy multi-band antenna. Can be tuned to any amateur band 10 through 80 meters by a single adjustment. Has amazing efficiency for DX or local contacts. Ground or roof top or tower installation. Can survive winds in excess of 50 mph. Overall height 18'; knocks down to only 5'. Uses 3½" diameter air wound coil as matching inductor. All steel parts irridite treated to Mil. Specs. Impedance 52 ohms. Maximum power 1000

watts AM or CW—2 KW PEP. Omni-directional, vertically polarized. Shpg. wt., 5 lbs.
40 N 0104WX Net 14.95

NEW UNAOILLA 2 ELEMENT QUAD FOR 10-15-20 METERS



44⁹⁵

- Pre-Tuned
- Low Angle Radiation
- Broad Band
- High Gain
- Rated 2 KW PEP

New 2 Element Super quad for outstanding performance on 10-15-20 Meters. High F/B ratio of about 25-30 db. Maximum gain pulls in DX countries, and features 8 selected heavy duty Korean bamboo spreaders, 8 ft. x 2" seamless aluminum boom and aluminum end spiders. 3 air-wound high Q coils. 17Wx 17"H. Turning radius 9' 11". Takes single or 3 line feed. Shpg. wt., 40 lbs.
40 N 4701WX Net 44.95

LAFAYETTE NUVISTOR GRID DIP METER



Complete with All Coils

- Nuvistor Oscillator
- Compact, True One-Hand Operation
- Slim Color-Matched Coils for High Accessibility
- Covers 1.7 to 180 MC in 6 Bands

29⁵⁰

A compact unit designed for easy circuit coupling in hard-to-reach places. Thumb tuning. Sensitive Nuvistor oscillator/detector is ideal for checking resonant frequencies of tuned circuits, detecting stray resonances in transmitters, checking neutralization. Frequency range 1.7 to 180 MC in 6 accurately calibrated ranges. Powered by built-in 117V AC 50/60 cycle transformer power supply with silicon rectifier. Precision plug-in coils supplied in protective case. Solid finish aluminum panel. Size: 2¾Wx5½Lx1¾"D. Shpg. wt., 2 lbs. Imported.
99 N 2503 Net 29.50

LAFAYETTE 6 and 2 METER VFO



A Deluxe Self-Powered VFO For 6 and 2 Meters

29⁹⁵

A high quality variable frequency oscillator designed to operate with modern transmitters using crystal oscillators in the 8-9 Mc region. It provides dependable coverage of both the 6 and 2 meter amateur bands. High electrical stability is achieved by a series-tuned clapp oscillator. OB2 voltage regulator tube protects unit from line voltage variations. Completely self-powered, needs no power from your rig. Uses low-heat half-wave silicon rectifier. Illuminated plexiglass dial is calibrated from 50-54 Mc (6M) and 144-148 Mc (2M). Output voltage is 10-15 V rms. Tubes: 6BA6, OB2. Rigid mechanical construction. Complete with 24" low loss coaxial cable. For 117 Volts 50/60 cycles AC. Size: 6¼Wx4½Hx 4"D. Shpg. wt., 6 lbs. Imported.
99 N 2538 Net 29.95

- Voltage Regulated For Stability

HYGAIN SWL ANTENNAS



(A) SWI INDOOR ANTENNA

Convenient indoor Model SWI improves the performance of any shortwave receiver. Covers 5-30 Mc. Easy to install and operate. Six-foot cable (included) is attached to receiver, the telescoping "rabbit ears" extended, and the "match" and "tune" controls set for maximum signal strength. Attractively housed in unbreakable plastic with chrome-plated antennas. Model SWI. Shpg. wt., 2½ lbs.
40 N 3114 Net 14.75

(B) SWO OUTDOOR ANTENNA

Model SWO is a high efficiency doublet antenna for outdoor use. Peaker for top performance on the important 11, 13, 16, 19, 24, 31 and 49 meter short wave bands. Includes eight trap assemblies, end insulators, 100 ft. of lead-in cable with complete instructions for rapid assembly. Mounts easily under eaves, in attic space, from window to tree, etc. Overall length, 40 ft. Model SWO. Shpg. wt., 2½ lbs.
40 N 3115- Net 14.75

ASTATIC MODEL 0-104 MICROPHONE



18²³

Used extensively by radio amateurs for its high intelligibility and "punch." Responds with rising characteristics from 500-4,000 cps. High output sealed

crystal element. Output level —46 db. Chrome finished mesh grille and body. With 5-ft. cable and adaptor to ¾"—27 thread. Shpg. wt., 1¼ lbs.
44 N 1401 Less Stand Net 18.23

RADIO AMATEUR CALL BOOKS



RADIO AMATEUR CALL BOOK — UNITED STATES SECTION. Lists all (over 264,000) licensed amateurs in the United States possessions and personnel in foreign countries with their call letters and addresses. Published quarterly. Latest edition will be shipped. 11¾x8¾".

10 N 5009 Shpg. wt., 1 lb., 13 oz. Net 5.00
FOREIGN RADIO AMATEUR CALL BOOK. Covers all countries outside of 50 United States. Nearly 100,000 names. Published twice a year. Latest edition will be shipped.
10 N 5010 Shpg. wt., ¾ lb. Net 3.00

B & W "VACATIONER" PORTABLE 2 THRU 20 METER ANTENNA



Lightweight, compact telescoping whip. Mounts anywhere you have a window: motel, trailer, apartment or boat. Low SWR on all bands. Heavy duty, chrome-plated whip, weather proof boot for loading coil. Retracts to 18½". Extends to 57" Power rating 300 watts PEP on SSB; 180 watts CW and AM. Complete with mounting bracket, base and coaxial line (less connector).
40 N 1601 Shpg. wt., 2 lbs. Net 19.55

Your Amateur Radio Accessories

NEW LAFAYETTE CODE PRACTICE OSCILLATOR

3-WAY OPERATION:

Light Indicator -
Variable Pitch Tone
Light-Tone Combined

7⁹⁵



A Terrific aid for the beginning Morse Code learner or experienced hams who wish to improve their code speed. Completely self-contained, it can be carried wherever you go. Efficient built-in speaker provides loud, clear signal. Excellent for group practice sessions. Variable pitch control gives pleasing tone by changing frequency. For private use, without disturbing others, you have a choice of earphone tone operation, flashing light or both together. Uses low drain battery-operated transistor oscillator. Specifications: Tone frequency range: Approx. 500 to 2000 cps, variable Controls: Pitch, Tone, Light and Light/Tone. Terminals: Key, Earphone. Batteries: Includes 2 "C" cells. Case: Hi-import bakelite. Size: 6¼Hx3¼Wx2"D. Shpg. wt., 1¼ lbs. Imported

99 N 2560 Net 7.95
32 N 4801 Extra "C" cells. 2 required Net ea. .13

OPTIONAL ACCESSORIES

Lafayette "Brass-Pounders" Telegraph Key Precision made. Shpg. wt., 1½ lbs. Imported
99 N 2555 Net 1.95

Crystal Headset. Lightweight, 2 earpiece design. Imported
99 N 2550 Shpg. wt., 5 oz. Net 1.39

LAFAYETTE SEMI-AUTOMATIC "BUG"



● SUPER SPEED KEY

A quality "Bug" designed for clear, easy sending and wide range of speed. 7 adjustments for speed and comfort. Precision-tooled, anti-rust nickel-plated brass and stainless steel operating parts. Speed adjustable 10 wpm to as high as desired. ¼" silver contacts; weight scale for reproducible speed settings. 6¾Lx3Wx2¼"H, exclusive of knobs and feet. Shpg. wt., 3½ lbs. Imported.

99 N 2552 Net 9.95

12 LESSON CODE COURSE

12 LESSONS ON A
12" LP RECORD



Learn Morse Code the modern practical way. Supplied with 12 lessons on a nonbreakable high quality 33½ rpm long playing record, recorded with code sound to provide further aid. Perfect for home studying. Speed progresses steadily from 3 to 16½ wpm. Complete with sturdy record album and instruction manual. Shpg. wt., 1½ lbs.
40 N 8901 Code Course Net 3.50

AMECO AC-1T AMATEUR TRANSMITTER KIT



- Ideal for Novice
- Self Contained

The ideal unit for beginner or novice. Contains transformer powered AC power supply. Uses a Pi-network output circuit to load random length wire antenna. No antenna tuner required. Has full 15-watt input on 40 and 80 meters. Easy to build and operate. Complete with punched chassis, all parts, tubes (6V6 and 6X5) and instructions. Shpg. wt., 8 lbs.

40 N 1009 Transmitter Kit Net 19.55
40 N 1010 CK1 extra coil kit Net .73

SUPEREX AMATEUR PHONES 2495

Comfortable poly-foam ear cushions. 600 ohm impedance. High sensitivity and crisp, clear reproduction for that hard to read station. Shpg. wt., 2 lbs.
40 N 8501 Net 24.95



LAFAYETTE SWR and FIELD STRENGTH METER

LOW,
LOW
PRICE

12⁹⁵



- Measures SWR, Relative Forward And Reflected Power to 1 KW
- Reads Field Strength

A handy 2-in-1 meter for use in the amateur radio station to check transmitters for SWR measurements. Can be left continuously in the circuit for monitoring transmitter outputs, SWR: 1:1 to 3:1; Accuracy ±5 db, 2 to 30 MC; Impedance: 52 Ohms; Antenna: 5-section, collapsible. Comparative RF field strengths can be easily determined with this fine meter. Sensitive 100 micro-ammeter movement with easy to read 2-color dial. Impedance matches 52 Ohm coaxial lines. Attractive grey hammertone aluminum case. Size: 1¾Wx5¼Hx2¼"D. Shpg. wt., 1 lb. Imported.

99 N 2537 Net 12.95

FAMOUS DOW-KEY ACCESSORIES



MODEL DK60 COAXIAL RELAYS (Fig. A)

Low-loss coaxial relay designed for dependable antenna switching. Low contact resistance with contact force at least 50 grams in transmit and 35 grams in receive position. Breakdown voltage in excess of 1000 volts rms. Insulation resistance at least 50,000 megohms. Coil impregnated with epoxy resin. Heavy phosphor bronze contact tongue with pure silver contacts. Size: 3¾x2¾x1½". Mtg. holes 6-32 clearance or 8-32 tapping. Shpg. wt., 1 lb. DK60-G2C with 115 VAC Coil
40 N 5201 Net 15.65
DK-60-G2C with 12VDC Coil
40 N 5202 Net 15.65

MODEL DK60-P PANEL MOUNTING COAXIAL CONNECTOR (Fig. B)

A panel mounting coaxial connector that can be permanently installed on panel in just a few minutes, without screws. Only a single ¾" diameter hole is required. Two serrated jam nuts hold connector securely in position. Will not loosen from frequent use. Easy to solder terminal. Shpg. wt., 6 oz.
40 N 5204 Net .70

DRAKE TV-100LP LOW-PASS FILTER




Low-pass filter. Attenuates above 54 MCS. Handles 100 watts, 10-160 meters, 20 watts on 6 meters. For 52Ω line.
40 N 6513 Net 5.83
TV-100LP. As above, but handles 1-KW on 10-160 meters, 200 watts on 6 meters.
40 N 6514 Net 16.61

Deluxe Amateur Packages From LAFAYETTE



**MODEL TX-62 2 AND 6 METER
TRANSMITTER AND FINCO A-62
2 AND 6 METER BEAM ANTENNA PACKAGE**



**Complete Package
TX-62 Transmitter
and A-62 Antenna
Only**
169⁹⁵
\$8 Monthly


- Frequency Coverage 50-54 MC and 144-148MC
- Power Input: 75 Watts CW, 75 Watts peak on Phone
- Meter Reads Final Cathode Current, Final Grid Current and RF Output
- Built-in Solid State Power Supply

A deluxe package for the amateur including the famous Ameco TX-62 2 & 6-meter transmitter and the Finco A-62 2 & 6-meter beam antenna. The Ameco TX-62 is a complete 75-watt phone and CW transmitter with a built-in power supply and modulator. Only the final has to be tuned when you QSY. Crystal controlled or can be used with a VFO. Crystals used are the 8MC type. Power input to the final is 75 watts on CW and 75 watts peak on AM phone. Tube lineup: 6GK6-osc, tripler; 6GK6 doubler, 7688 tripler (on 2 meters); 7984 final; 12AX7 and 6GK6 modulator. Size 11½x9½x6". The Finco A-62 is a high-gain beam antenna for 2 & 6 meters featuring heavy-duty aluminum construction with 10 ft. boom. Turning radius is 6 ft. 11-in. and uses one transmission line for both 2 and 6 meter band. Ameco TX-62 and Finco A-62. Shpg. wt., 48 lbs.

40 N 1043WXM	Net 169.95
Ameco TX-62 Transmitter only. Shpg. wt., 36 lbs.	
40 N 1035WX	Net 146.95
Finco A-62 antenna only. Shpg. wt., 11 lbs.	
40 N 6301WX	Net 33.34

**SWAN- 350 5-BAND SSB
AMATEUR
TRANSCIVER**

**PLUS FREE BONUS
TURNER 454X
SSB MIKE**



395⁰⁰
\$19 Monthly

- 5 BANDS: 3.5-4.0 MC, 7.0-7.5 MC, 13.85-14.35 MC, 21.0-21.5 MC, 28.5-29.0 MC
- 400 WATTS SSB INPUT, 320 WATTS CW INPUT 125 WATTS AM INPUT

A compact 5-band 400-watt SSB transceiver for fixed, portable or mobile operations. Frequency coverage 3.5-4.0 MC, 7.0-7.5MC, 13.85-14.35 MC, 21.0-21.5 MC, 28.5-29.0 MC with lower sideband operation on 80 and 40 Meters, and upper sideband on 20, 15 and 10 meters. Transistorized VFO, temperature and voltage stabilized, precision dual-ratio tuning, crystal lattice filter, ALC and AGC, S-meter, plus provision for plug-in VOX. Sideband suppression is 40 db, carrier suppression 50 db. Dimensions: 5½Hx13Wx11"D. Shpg. wt., 18 lbs.

40 N 7010WXM Model 350 plus Turner 454X	Net 395.00
AC Power Supply with Matching Speaker in Cabinet. Shpg. wt., 11 lbs.	
40 N 7009WX	Net 85.00
12V DC Power Supply for Model 350. Shpg. wt., 8 lbs.	
40 N 7006WX	Net 130.00
40 N 7007 Model VX-1 Plug-in VOX ADAPTER	Net 35.00

TURNER 454X SSB MIKE

Engineered for the SSB operator. Wired for PPT, features two separate switching arrangements—push-to-talk, and a lever-lock switch. Response: 300 to 3000 cps. Output level: —48 db.
44 N 7001 Net 15.58

DELUXE DRAKE R-4 SSB RECEIVER



BONUS

R-4 only
379⁹⁵

Get Matching Drake
MS-4 Speaker For
Only 1c
with Purchase of
R-4 Receiver

R-4 plus MS-4 Speaker
379⁹⁶
\$19 Monthly

- Receives SSB, AM, CW, AND RTTY

The Drake R-4 receiver is an outstanding addition to this already fine line of equipment. Covers the following ham bands: 80, 40, 20 and 15 meters completely and 28.5 to 29.0 MC of 10 meters with crystals furnished. With accessory crystals the receiver will cover 160 meters, MARS, CB, WWV, Marine and SW broadcasts or will give 5 MC of continuous coverage for use with VHF converters. "Write-in" window for frequency of accessory ranges. 4 bandwidths of selectivity: 0.4, 1.2, 2.4 and 4.8 KC. Passband tuning for sideband selection without returning and continuous adjustment of passband relative to BFO. Other features: noise blanker on CW, SSB, and AM; notch-filter; 100KC crystal calibrator; crystal lattice filter; premixed injection; AVC with fast attack and slow release; product detector. Dimensions 5½Hx10¾"W, cabinet depth 11¾". Power consumption 50 watts, 120/240 VAC, 50/60 cycles.

Drake R-4 Receiver plus MS-4 speaker 40 N 6515WXM	Net 379.96
Drake R-4 Receiver only. Shpg. wt., 18 lbs. 40 N 6503WX	Net 379.95
Drake MS-4 Matching Spkr. only. Shpg. wt., 5 lbs. 40 N 6504	Net 19.95

HALLICRAFTERS SX-110 HAM-SWL RECEIVER



BONUS

SX-110 only
169⁹⁵

Matching Hallcrafters
R-47 Speaker for
Only 1c
with Purchase of
SX-110 Receiver

**SX-110 plus
R-47 Speaker**
169⁹⁶
\$8 Monthly


A superheterodyne receiver which covers 540KC (broadcast band) to 34MC in four bands. Incorporates a crystal filter for added selectivity on the amateur bands. Features a slide rule type dial with 0-100 logging scale and has calibrated electrical bandspread over the 10, 15, 20 40 and 80 meter bands. Separate bandspread tuning condenser for accurate tracking. Sensitive circuit with one RF and two IF Stages. Antenna trimmer for optimum reception with antenna. Also has built-in "S" meter for indication of relative signal strength. Seven tubes plus rectifier: 6SG7 (RF), 6SA7 (Converter), 6SG7 (1st IF), 6SK7 (2nd IF), 6SC7 (BFO & 1st Audio), 6K5GT (Audio Output), 6H6 (AHL, AVC, Det.), 5Y3 (Rectifier). Audio output 2 watts (speaker required). Output impedance taps for 3.2 and 500 ohms. Handsome Gray steel cabinet with brushed chrome trim. Size: 18¾Wx8Hx10¼"D. For 117V AC, 50/60 cycles.

SX-110 plus R-47 Speaker. Shpg. wt., 35 lbs. 40 N 2532WXM	Net 169.96
40 N 2509WX SX-110 only. Shpg. wt., 32 lbs.	Net 169.95
40 N 2519 R-47 Speaker only. Shpg. wt., 3 lbs.	Net 12.95

LAFAYETTE Quality Panel Meters



(FIG. A)



(FIG. B)



(FIG. C)

Square and Miniature PANEL METERS with high quality D'Arsonval Movements

- Jewelled Bearings
- Accuracy 2% Full Scale

High quality, precision built meters with better than 2% of full scale accuracy. All meters have 4 threaded mounting studs in corners, zero adjust screw and clear plastic fronts except (Fig. B) which has black bakelite. Terminal polarity on DC models is identified. Fig. A standard 3900 ohm "B" scale VU indicator. Includes full wave bridge rectifier, built-in bulb. Ammeters are highly damped, use linear calibrations. Dimensions: Fig. A, B, — 3 1/4" square, 2 3/4" x 1 3/4" dial faces, 1 1/4" overall depth, 1 3/4" behind panel including terminals. Require 2 1/2" diameter mounting hole. Fig C miniature meters with silvered dials, black pointers — 1 1/2" square fronts, 1 1/2" overall front-to-back, with 1 1/4" behind panel including 1/4" terminals. Require 1 1/2" diameter round hole in panel. 1 1/4" dial face. Supplied with mounting screws. Shpg. wt., 1 lb. Imported.

STOCK NO.	TYPE	FIG.	RANGE	NET EA.
99 N 5043	Square	A	*Illuminated Scale VU	6.75
99 N 5042	Square	B	0-50 DC Microammeter	5.95
99 N 5040	Square	B	0-1 DC Milliammeter	3.25
99 N 5039	Square	B	0-150 AC Voltmeter	2.75
99 N 5052	Miniature	C	0-1 DC Milliammeter	2.95
99 N 5053	Miniature	C	0-5 DC Milliammeter	2.95
99 N 5054	Miniature	C	0-50 DC Milliammeter	2.95
99 N 5055	Miniature	C	0-100 DC Milliammeter	2.95
99 N 5049	Miniature	C	0-50 DC Microammeter	4.45
99 N 5060	Miniature	C	0-10 DC Ammeter	2.75
99 N 5047	Miniature	C	0-15 DC Voltmeter	2.75
99 N 5050	Miniature	C	0-150 AC Voltmeter	2.75
99 N 5051	Miniature	C	0-300 AC Voltmeter	2.75

*Standard 3900 ohm "B" scale volume indicator, 0-100% modulation scale, —20 to +3VU scale.

MINIATURE LAFAYETTE ILLUMINATED VU METER

- O'Arsonval Movements
- Accuracy 2% of Full Scale
- Jewelled Bearings
- Bakelite Case



Illuminated dial for easy, wide-angle readability at all times. Volume level indicator, calibrated in standard —20 to +3 VU and 0-100% ranges. Uses precision carbon film multiplier resistor and full wave rectifier. Damped in accordance with standard VU meter requirements. Reference level 1 mw in 600 ohm line, 3,900 ohms internal resistance. "0" VU is 1.228 volts sine wave AC across meter connected to 600 ohm source with 600 ohm load. May be used with T-pad attenuator. Size: 1 1/4" x 1 1/4" Sq. face, 1 1/4" overall behind panel. Shpg. wt., 8 oz. Imported.

Net 3.95

LAFAYETTE EDGE-WISE PANEL METERS

- 2% FULL SCALE ACCURACY
- PRECISION O'ARSONVAL MOVEMENTS



(FIG. A)



(FIG. B)

Has precision D'Arsonval meter with 2% or better full scale accuracy. Overall depth is 3 1/2" behind panel including terminals. Has stud-type solder terminals and zero adjustment screw. Shpg. wt., 3/4 lbs. Imported.

VU METER (FIG. A)

VU METER—Calibrated and damped in accordance with standard VU meter practice. Upper scale reads —20 to +3 VU. Lower scale reads 0-100% modulation. Accurate to ±0.5 VU from 30-15,000 cps.

99 N 5033 Size 3 1/4" x 1 1/4" H. Imported Net 5.95

0-150 AC VOLTMETER (FIG. A)

0-150 AC VOLTMETER—Full-wave bridge rectifier type. 1000 ohms per volt. 5 volts per division, linear scale.

99 N 5032 Size 3 1/4" x 1 1/4" H. Imported Net 3.75

0-1 DC MILLIAMMETER (FIG. A)

0-1 DC MILLIAMMETER—CALIBRATED from 0-1 ma in 0.02 ma. divisions. Black scale, red pointer.


99 N 5031 Size 1/4" x 1 1/4" H. Imported Net 4.75

BALANCE & TUNING METER (FIG. B)

Use these precision moving coil DC Ammeter meter movements as stereo balance indicators or as tuning indicators for FM tuners. Pointer at center of the scale indicates zero or null position. Current Sensitivity: ±100µa. Complete with installation schematics. 99 N 5034 Shpg. wt., 1 lb. Size 2 3/4" x 1 3/4" x 7/8" H. Imported Net 2.50

MINIATURE LAFAYETTE LEVEL METER

- Highly Sensitive
- Front Panel Area Only 7/8" x 3/4" H
- Rubber Cushion Mount



195

A miniature clear plastic front level meter which will indicate relative audio levels for tape recorders, FM sets or transistorized audio equipment. Actual size of meter is 1 1/4" x 1" x 1". Sensitivity: 250 ma; internal resistance—260 ohms. Full scale 500 microamps. Shpg. wt., 1 oz. Imported. 99 N 5036 Net 1.95

SUB-MINIATURE LAFAYETTE TUNING & BATTERY METER

- FOR TRANSISTOR CIRCUITS
- ONLY 3/4" W x 7/8" H
- 3/4" DEEP



245

Make your miniature transistor radio a deluxe receiver with this tuning and battery meter. Sensitive 300 µ amp. D'Arsonval movement. Easy to read—clearly marked scale — red pointer. Meter has shielded case. Plastic bumpers protect pointer. With hook-up circuit. Scale marked: OFF, TUNE AND BATT. with intermediate graduations. Shpg. wt., 4 ozs. Imported.

99 N 5028 Net 2.45

LAFAYETTE ULTRA-MINIATURE TUNING AND BATTERY METER

150



ONLY 3/4" IN OIA., 3/4" IN LENGTH

This ultra-miniature meter can be installed easily in a 3/4" diameter hole. Its total length (front to back, including lugs for connections) is 3/4" and its reading face is circular, 1/2" in diameter (taking up an area of less than 1/5 square inch!) Current sensitivity: 200 Ma. Internal resistance: 320 ohms ± 10%. Shpg. wt., 3 oz. Imported.

99 N 5035 Net 1.50

LAFAYETTE FILAMENT CONTINUITY TUBE CHECKER

- Compact, Ideal For Tube Caddy




169

Small and compact as a cigarette box. Quickly checks filament continuity in a matter of seconds. Ideal for the serviceman or the technician working in the field. Tests filaments of radio, TV picture tubes. Also can be used to test many other electrical devices and line cords, fuses, lamps and bulbs. Has sockets for TV picture tube and local, octal, 9-pin, as well as 7-pin sockets. Provided with two test leads. Grey hammer-tone finish. Size: 4x3x1 1/2". Shpg. wt., 12 oz. Imported.

99 N 5016 Net 1.69

World Famous LAFAYETTE Multitesters



17⁹⁵
Factory Wired

Deluxe 30,000 Ohms Per Volt Multitester For Precision Measurements

- 30,000 Ohms per Volt DC, 15,000 Ohms per Volt AC
- 1% Precision Resistors for High Accuracy
- Unique "Buzzer" for Fast Short Tests
- 27 Meter Ranges on 2-Color Scale

A deluxe portable Volt-Ohm-Milliammeter with a high order of accuracy. Completely wired and portable, it provides wide voltage, current, resistance and db ranges clearly visible on a big 4" meter with 2 color calibrations. Sensitivity is 30,000 ohms-per-volt DC and 15,000 ohms-per-volt AC. All multipliers used are 1% precision resistors for maximum accuracy and years of dependable service. Sensitive 33-micro-amp meter provides full scale readings down to ¼ volt on DC and 0.05 milliamperes. Features a unique self-contained buzzer to give you fast in-circuit checks on opens, shorts. Audio output jack with DC blocking capacitor. Handsome, dust proof black plastic case. Complete with leads, batteries. Size: 3½" W x 6¼" H x 2¾" D. Shpg. wt., 2 lbs. Imported.

99 N 5004 Net 17.95
99 N 5005 Pigskin Carrying Case for above Net 1.95

SPECIFICATIONS

Sensitivity: 30,000 ohms/volt DC, 15,000 ohms/volt AC. Ranges: DC volts: 0-.25, 1, 2.5, 10, 25, 100, 250, 500, 1000; AC volts: 0-2.5, 10, 25, 100, 250, 500, 1000. Direct Current: 0-0.05, 5, 50, 500 ma; 0-12 amps Ohmmeter: 0-6CK, 6M, 60 Megohms, Decibels: -20 to +56 db. Short Test: Internal Buzzer. Audio Output Jack. Controls: Range Switch, Ohms Adjust. Batteries: 1 type Z cell, 15-volt.



12⁵⁰
Factory Wired

Deluxe 20,000 Ohms-Per-Volt Multitester

- 20,000 Ohms Per Volt DC—10,000 Ohms Per Volt AC
- Measures: 0-1200V DC, 0-1200V AC, 0-10 Megohms, 0-60 ua, 0-600 ma, -20 to +63 db, 200 mmf-0.2 mfd.

Easy visibility is provided by the large 3½" meter with large two color scales. The 40-microampere D'Arsonval meter movement permits a high input resistance on all ranges: 20,000 ohms per volt on DC; 10,000 ohms per volt on AC. 1% tolerance resistors permits the measuring of voltages without unduly loading the circuit, preserving accuracy of readings. Measures 0-0.6, 6, 30, 120, 600, 1200 DC volts, 0-6, 30, 120, 600, 1200 AC volt, Resistance 0-10K, 100K, 1M, 10 Megohms, DC Current 0-60 microamperes, 0-6, 60, 600 milliamperes, -20 to -63 decibels. Features a capacitance measurement range, 200 mmf to 0.2 mfd capacity. Complete with batteries, test leads and operating instructions. Size 5½" x 3¼" x 1½" D. Shpg. wt., 1½ lbs. Imported.

99 N 5006 Net 12.50
99 N 5007 Pigskin Carrying Case for above Net 1.95



9⁹⁵
Factory Wired

20,000 Ohms-Per-Volt Multitester

- 20,000 Ohms/Volt DC, 10,000 Ohms/Volt AC
- 1% Precision Resistors
- Compact, Lightweight, Accurate
- Easy-to-Read 3" Meter

SPECIFICATIONS

Sensitivity: 20,000 ohm/volt DC, 10,000 ohms/volt AC. Range DC Volts: 0-3, 30, 60, 300, 600, 3,000V. AC Volts: 0-6, 60, 120, 1,200V. DC Current: 0-60 µA, 0-12, 0-300 ma. Resistance: 0-60K, 0-6 Megohms. Decibels: -20 to +63db. Audio Output Jack. Type "Z" 1.5V cell for resistance measurements. This handy pocket multi-tester has every needed range. Ideal for repair and service work on appliances, radio, etc. 40 micro-ampere meter movement permits a high input resistance on all ranges—does not load down circuits while testing. Has a single range/function control for quick, simple operation, plus zero ohms adjust. Supplied with 1½V penlight cell and test leads. Rugged, high impact plastic case. Size 3¼" x 4½" x 1". Shpg. wt., 1 lb. Imported.

99 N 5008 Net 9.95
99 N 5007 Pigskin Carrying Case for above Net 1.95



4⁹⁵
Factory Wired

Pocket AC-DC VOM

- Extremely Compact, Measures Only 3¾" x 2½" x 1" • Weighs 5 Ozs.
- 1,000 Ohms Per Volt Sensitivity • 1% Precision Resistors
- Reads: 0-1000 Volts AC-DC, 0-100K Ohms, 0-150 MA

The Lafayette pocket multitester features small physical size, and a wide selection of useful ranges. It can be used for trouble-shooting any type of electronic circuits or electrical appliances such as irons, lamps, radios, television, hi-fi equipment, etc. 1000 ohms per volt sensitivity, and 1% precision resistor components assure accurate, precise readings. Operation is extremely easy, no switching or fidgeting required. Ranges Volts: 0-15-150-1000 AC and DC. Ohms: 0-100K; MA: 0-150. The VOM comes completely wired and tested, and is enclosed in durable plastic case. All accessories including battery are rubber insulated, color coded, flexible test leads are supplied. Shpg. wt., 1 lb. Imported.

99 N 5010 AC-DC POCKET VOM Net 4.95
99 N 5061 Pigskin Carrying Case for above Net 1.75

LAFAYETTE V. T. V. M. With 6½" Meter

**NOT A KIT...
FULLY WIRED
AND TESTED**

**ONLY
26⁹⁵**

Made in U.S.A.



- Wide Band RMS Measurements on any Waveform from 30 cps to Over 5MC, Without Additional Probes or Accessories
- 11 Megohm Input Resistance—Negligible Loading Effects on DC Circuits
- Direct Reading DB Scale
- Balanced Push-Pull Amplifier-Isolates and Protects Meter
- Pilot Light Indicates When Unit is "On"
- Selected 1% Zero Temperature Coefficient Multiplier Resistors for Dependable, Accurate Readings
- Silicon Rectifier in Power Supply Reduces Effects of Heat on Component Values
- Accurately Measures AC Peak-To-Peak Voltage, AC RMS Voltage, DC Voltage and Resistance
- Giant 6½" Full-View Meter With Easy-To-Read Two-Color Scales

This high quality V.T.V.M. is an indispensable test instrument for the service technician, engineer, or experimenter. It is a highly accurate DC voltmeter, AC voltmeter and ohmmeter employing a giant 6½" easy reading 400 μ a meter. With a high input impedance of 11 megohms, this V.T.V.M. can accurately measure DC voltages up to 1500 volts, while presenting a negligible load to the circuit under test. As a wide band AC voltmeter, it will measure AC peak-to-peak voltages up to 800 on any waveform be it sinusoidal, sawtooth, square or of any other complex form; all this from 30 cps to above 5 Mc — without any accessory probes! AC RMS voltages may be read directly up to 1,500 volts if the waveform is sinusoidal. Resistances can be read directly on the Ohms scale from 0 to 1,000 megohms in 5 overlapping scales. A direct reading scale is calibrated from —10 to +45db (reference 1.73 volts, 6 mw into a 500 ohm line). The meter

is isolated from the measuring circuits by a DC amplifier, making it virtually impossible to burn it out. Multiplier resistors are 1% zero temperature coefficient types. Function Selector—selects power off, AC volts, P-P volts, D.C.V. Neg., D.C.V. Positive, Ohms; Range Selector—for 7 voltage and resistance ranges; Ohms Adjust; Balance (zero) Adjustment. There are 3 probes: Common A.C. volts—ohms, and shielded DC volts probe with 1 megohm isolating resistor. Silicon rectifier power supply for 110-120 VAC, 60 cps. Dimensions: 7½xHx 6½xWx5"D. Comes with 1½ volt battery for ohmmeter circuit and complete instructions. Shpg. wt., 7 lbs.

- 38 N 0101 Above V.T.V.M. Net 26.95
- 38 N 0103 Accessory RF probe for V.T.V.M. Net 3.95
- 38 N 1501 Leather Case for V.T.V.M. Net 2.95

SPECIFICATIONS

DC VOLTMEETER RANGES: 0 to 3, 30, 150, 300, 1500 volts. Input resistance: 11 megohms (1 megohm in probe) on all ranges.
A.C. VOLTMEETER RMS RANGES: 0 to 3, 30, 150, 300, 1500 volts.
PEAK-TO-PEAK RANGES: 0 to 8, 80, 400, 800 volts. **DECIBEL RANGES:** —10 to +5, +6 to +25, +26 to +45 db. Response: 30 cps to above 5 Mc.

OHMMETER RANGES: 0 to 1000 megohms in 5 overlapping ranges.
ZERO CENTER VOLTMEETER RANGES: 0-1.5, 15, 75, 150, 750 volts.
TUBES: 1-6211 twin triode balanced meter bridge; 2-9006 peak-to-peak rectifiers; silicon rectifier power supply.
POWER: 110-120 VAC, 60 cps.

LAFAYETTE COMBINATION SIGNAL GENERATOR AND SIGNAL TRACER

NOT A KIT — FACTORY WIRED AND TESTED

SIGNAL GENERATOR

- Covers From 250 KC to 120 MC in 5 Bands
- High Stability Electron Coupled Oscillator
- Attenuator For Both RF and Audio Circuits
- Most Used Frequencies Marked on Panel in Color
- Utilizes New Ruggedized Industrial Types Tubes

SIGNAL TRACER

- Hi-gain Cascode Pre-amplifier
- Front Panel Output For VTVM, Scope or Phones
- Low Distortion Triode Output Stage
- Separate R.F. and Audio Signal Probes

ONLY 24⁹⁵

Two test instruments in one! The Signal Generator will serve as a full service instrument and the Signal Tracer will follow any signal whether generated by a broadcasting station or injected by the Signal Generator section. When used in combination, with no dependence on outside signals, the unit provides ideal service, for unlike any standard signal tracer, it first injects its own signal then traces that controllable signal to locate the source by standard signal tracing technique. Designed for use with AM, FM, TV and audio circuitry. Features 5 frequency ranges and an attenuator switch to control both the R.F. signal (either modulated or unmodulated) and the 400 cycle audio tone. Front panel output jacks which can be used for oscilloscope, VTVM or earphone connections. Housed in a beautiful crackle finish steel cabinet with a deep etched aluminum panel. Dimensions: 7½x9½x5¾". Complete with 2 probes. Shpg. wt., 9 lbs.

38 N 0102 Net 24.95

SPECIFICATIONS

RANGE: Band A: 250KC to 850KC; B: 850KC-3000KC; C: 3.0MC to 11MC; D: 11MC to 45MC; E: 35MC to 120MC; 400cps audio signal; modulation slide switch, RF/AF attenuator and power switch; Signal output jack; AF input jack, 2 Preamp. output jacks, 4½" alnico 5 speaker. Tubes: 5687, 6350, 6AG5 plus sel. rectifier.

Lafayette Supplies Fine Test Equipment at Low Cost



Made in U.S.A.

Exclusive LAFAYETTE Test Equipment

LAFAYETTE TUBE TESTER

for HOME, SHOP BENCH
or LABORATORY

Packed With Features at
A Price You Can Afford

19⁹⁵

Not a Kit—Completely Wired

- Checks New Compactrons, Nuvistors, New T-9 Types 7-pin Miniatures, Octals, Lock-in's and 9-pin Miniatures
- Fast-Setting Slide Switches Covering All Elements of 12-Pin Compactron Tubes
- Accurately Checks Over 1600 Different Tubes
- Tests for Cathode Emission, Leakage and Shorts plus Filament Continuity
- Completely Portable—Weighs Only 6 lbs.
- Highly Accurate Easy-to-Read Meter with Replace—Good Scale
- Slide-Out Tube Chart



FULL
SIZE

9 $\frac{3}{4}$ "Wx8 $\frac{1}{8}$ "Dx2 $\frac{1}{2}$ "H

A modern, dependable tube checker designed for fast, accurate testing—the ideal low-cost tube tester for any radio-TV serviceman, experimenter, technician, etc. This outstanding instrument tests most of the tube types employed in Radio, Hi-Fi, Monochrome and Color TV, including the new 12-pin compactrons, nuvistors, T-9's, 7 and 9-pin miniatures—actually tests over 1600 different tubes! A special alligator clip lead is furnished for testing tubes with top caps. Slide switches are employed to connect the various tube elements to their respective test circuits. A 3-position tube slide switch adjust for checking shorted elements, cathode emission and filament continuity. A leakage indicator light glows when an inter-element short or leakage is present in a tube. A power switch turns the unit on and additionally serves to adjust for various AC

line voltages. Large easy-to-read meter calibrated 0-100 has a red-green "Replace—Good" scale, plus a special scale for checking diodes.

A handy slide out metal tray contains tube charts which facilitate rapid selection of test settings. Metal case is attractively finished in cream and steel gray. Completely portable—weighs only 6 lbs. and measures 8 $\frac{1}{4}$ "Dx9 $\frac{3}{4}$ "Wx 6 $\frac{1}{2}$ "H. Supplied with carrying case. For 105-125 volts, 60 cycle AC. Shpg. wt., 7 lbs. Imported.

99 N 5011 Tube Checker Net 19.95

DELUXE TUBE TESTER IN CARRYING CASE. Same as our Tube Tester above, but housed in portable wood case with grey vinyl trim. Imported.

99 N 5012 Net 23.95

DELUXE LAFAYETTE 20,000 OHMS-PER-VOLT VOM WITH GIANT 6" METER

Not a Kit—Completely Wired and Tested

26⁹⁵

- Giant 6" Full-View Meter
- Expanded Easier-To-Read 2-Color Scale
- 20,000 Ohms-per-volt DC
- 1% Multiplier Resistors
- DC Volts From 0-5000V in 8 Ranges
- AC Volts From 0-5000V in 6 Ranges

A precision VOM with varied ranges for accurate measurement of voltage, current, resistance and decibels. This deluxe VOM gives you accuracy comparable to bench type units, with the added feature of complete portability. Expanded 6" meter scale in red and black gives you top visibility 50-microamp meter sensitivity provides 20,000 ohms per-volt input resistance on DC and 5,000 ohms per-volt on AC—Wide-range frequency response measures 10 to 100,000 cycles within ± 0.5 db. A single 1.5V battery in the ohmmeter circuit prevents burnout to low current drain devices. All multiplier resistors are 1% precision type. Heavy gauge steel case with high impact plastic panel. Includes test leads, batteries and leather carrying handle. Size 6 $\frac{1}{4}$ "Wx7 $\frac{3}{4}$ "Hx3 $\frac{1}{4}$ "D. Shpg. wt., 4 $\frac{1}{2}$ lbs. Imported.

99 N 5013 Net 26.95

SPECIFICATIONS

Sensitivity: 20,000 ohm/volt DC, 5000 ohms/volt AC. Range: AC: 0-5000 volts (in 6 ranges): 2.5, 10, 50, 250, 1000, 5000V; DC: 0-5000 volts (in 8 ranges): 0.25, 1, 2.5, 10, 50, 250, 1000, 5000V. DC Current, 0-10 amps. (in 6 ranges): 0-50 μ a, 1 ma, 10 ma, 100 ma, 500 ma, 10 amps. Ohmmeter: 0-20 megohms (in 3 ranges): 0-2K, 200K, 20M. Decibels: —20 to +50 db. Accuracy: DC: $\pm 3\%$ Full Scale. AC: $\pm 4\%$ Full Scale. Resistance: $\pm 3\%$ Full Scale.



LAFAYETTE RF SIGNAL GENERATOR

- FACTORY CALIBRATED AND TESTED
- SIX BANDS: 120 KC - 260 MC
- DUAL OUTPUT RF TERMINALS
- SEPARATE VARIABLE AUDIO OUTPUT
- DIAL CALIBRATION $\pm 2\%$
- ETCHED CIRCULAR DIAL - (Vernier Tuned)



A stable, wide-range signal generator engineered to fill the need for an accurate low cost service instrument. The delicate oscillator coils and tuning assembly are factory mounted and adjusted for optimum performance. This top-flight unit can be used for IF-RF alignment, audio signal tracing of TV, FM and AM sets. TV linearity checks and 400 cycle audio testing. In addition, it can serve as a marker generator when used with a suitable sweep generator. Incorporates a large 4 1/4" etched circular dial for easy, accurate frequency adjustments. Provides a fundamental frequency output of 120 KC to 130 MC in 6 bands plus a calibrated harmonic output of 120 mc to 260 MC. The built-in audio oscillator operates at 400 KC with adjustable output to 8 volts. Continuously variable RF attenuator for proper signal attenuation and two plug-in RF output terminals provide a choice of high and low outputs for maximum flexibility. High output and tuning dial calibration of $\pm 2\%$. Imported
99 N 5015 Net 27.95

27⁹⁵

SPECIFICATIONS

Full frequency range: 6 Fundamental bands—120-320 Kc 320-1000 Kc. 1-3.5 MC, 3.2-11 MC, 11-38 MC, 36-130 MC; One harmonic band 120-260 MC. Frequency Accuracy: $\pm 2\%$. Audio Output: to 8 volts. Large 4 1/4" Etched Circular Dial (Vernier tuned) High-Low

RF Output Terminals. Tube Complement: 12BH7A, 6AR5, Selenium Rectifier. Power Requirements: 105-125VAC 50/60 Cps., 12 Watts. Attractive gray wrinkle steel case with leather carrying handle. Complete with test leads. Size: 7Hx10 1/2Wx5 3/4"D. Shpg. wt., 9 lbs.

LAFAYETTE SINE/SQUARE WAVE GENERATOR



- FACTORY CALIBRATED AND TESTED
- LOW DISTORTION
- FREQUENCY RANGE - SINE WAVE: 20 cps—200 KC IN 4 BANDS, SQUARE WAVE 20-25 KC (Vernier Tuned)
- ETCHED CIRCULAR DIAL
- FREQUENCY RESPONSE $\pm 1.5\text{DB}$, 60PCS — 150KC 4 1/2" VERNIER DIAL

Especially designed for radio-TV servicemen, Hi-Fi fans and students who require a dependable sine and square wave generator at low prices. An outstanding instrument . . . factory wired, tested and calibrated. Among its many applications are square wave testing of audio amplifiers, determining the frequency and transient response of loudspeakers, TV audio circuit testing and many other uses. Quality features and specifications consist of a frequency range of 20 cps to 200,000 cycles in 4 bands. A large easy-to-read and set etched dial (vernier tuned) adds a professional quality touch. Variable attenuator adjusts amplitude of output signal. A full wave power supply is incorporated to provide low distortion and constant output. Factory wiring and calibration insure accuracy of $\pm 3\%$. Output voltage is 7 volts across a 1 megohm load. Rugged steel cabinet and shock-proof mountings protect components. Complete with instructions and test leads. For 117 V 50/60 cps AC. Size: 10 1/2Wx7 1/2Hx5 3/4"D. Shpg. wt., 10 lbs. Imported.

99 N 5014

..... Net 35.95

SPECIFICATIONS

35⁹⁵
\$5.00 monthly

Frequency range: Sine wave; 20-200,000 cps in 4 bands. Square wave—60-30,000 cps. Output Voltage—Sine: 7V RMS; Square 7V P-P. Output Impedance—0-5000 Ohms. Frequency Accuracy: $\pm 3\%$. Distortion: Less than 2%. Tube

Complement: 1-6BM8, 1-12AT7, 1-6X4. Power requirements: 117V 50/60 cps, 19W. Gray wrinkle steel case with leather carrying handle. Complete with a pair of test leads. Size: 7Hx10 1/2Wx5 3/4"D. Shpg. wt., 10 lbs.

DELUXE SIGNAL GENERATOR

- Genometer—7 Signal Generators in one
- RF Signal Generator for AM
- RF Signal Generator for FM
- Audio Frequency Generator
- Bar Generator
- Cross Hatch Generator
- Color Dot Pattern Generator
- Marker Generator

A versatile all-inclusive Generator which provides all the outputs for servicing: AM Radio, FM Radio, Amplifiers, Black and White TV, Color TV. SPECIFICATIONS: RF Signal Generator—Provides complete coverage for AM and FM alignment. Generates radio frequencies from 250 KC to 45 MC on fundamentals and from 35 MC to 120 MC on powerful harmonics. Cross Hatch Generator—Will project a cross-hatch pattern on any TV picture tube. The pattern will consist of non-shifting, horizontal and vertical lines interlaced to provide a stable cross-hatch effect. Variable AF Generator—Provides a fixed 400 cycle sine-wave or a variable 300-20,000 cycle peaked wave audio signal. Dot Pattern Generator—The dot pattern projected on any Color TV picture tube enables you to adjust for proper color convergence. Bar Generator—Projects an actual bar pattern of 4-16 horizontal bars or 7-20 vertical bars on any TV receiver screen. Marker Generator—Provides 9 most frequently needed marker points (262 KC, 456 KC, 600 KC, 1000 KC, 1600 KC, 2500 KC, 3,579 MC, 4.5 MC, 10.7 MC). Complete with shielded leads and operating instructions. Size: 10Wx7Hx5 3/4"D. Shpg. wt., 7 lbs.
98 N 1001 Net 37.73



ONLY 37⁷³

\$5.00 monthly

MADE IN U.S.A.

Lafayette Supplies Fine Test Equipment at Low Cost

Lafayette Cat. No. 653 151

Factory Assembled Ready-to-Use Test Equipment

LAFAYETTE CAPACITANCE-RESISTANCE ANALYZER



- Capacitance Bridge Circuit
- Direct Reading Scales
- "Magic-Eye" Null Indicator And Meter
- Measures Electrolytic Power Factor

39⁵⁰
\$5 monthly

Tests capacitors of all types for value, shorts, opens, leakage, insulation resistance and power factor. Measures resistance from 2 ohms to 200 Megohms. Invaluable for determining the turns and impedance ratios of audio and power transformers. All readings are made directly on expanded easy-to-read etched dial scales. Leakage current and insulation resistance of capacitors are read directly on meter. Bridge circuit accurately measures resistance and capacity. "Magic-eye" indicator permits fast visual results for "null" opens or shorts. Complete with instructions and test leads. For 117V 50/60 cycles AC. Grey wrinkle finish steel with carrying handle. 10½Wx7Hx5¼"D. Shpg. wt., 12 lbs. Imported.
99 N 5017

Net 39.50

SPECIFICATIONS

Capacity Ranges: 20 mmf to 2000 μ f in 4 ranges. Resistance Ranges: 2 ohms to 200 megohms in 4 ranges. Leakage Test: 3-600 volts; Current 0-1 ma; 0-10 ma. Transformer Turns Ratio: 1:1 to 200:1. Transformer Impedance Ratios: 1:1 to 40K:1.

LAFAYETTE DELUXE CRT REJUVENATOR TESTER



- Checks and Corrects Each Gun of Color Tube Separately
- Rejuvenates All TV Picture Tubes Including Color and 110° Types

39⁵⁰
\$5 monthly


Rapidly checks and corrects black and white and color TV picture tubes including 110° types without removing them from the set. Restores brightness and emission to old CRTs. Determines quality of CRTs by means of an emission test. Large 4½" meter gives legible readings at a glance. Selector switch provides a choice of dual filament voltages of 6.3 V and 12.6 V. Checks and corrects each gun of color tube separately. Repairs interelement shorts and open circuits. Includes 3 additional tube socket adaptors for 110° deflection type tubes. For 105-125V 60 cycle AC. Handsome portable leatherette covered gray case with detachable top. Size: 4¾x7½x13½". Shpg. wt., 9 lbs. Imported.
99 N 5018 Deluxe CRT Tester

Net 39.50

Adapter for 23EP4 picture tube. Shpg. wt., ½ lb. Imported.
99 N 5019

Net 1.50

CAPACITANCE SUBSTITUTION BOX




A must for the serviceman, experimenter or student. Fast accurate selection of any one of 9 capacitor values from .0001 to 22 MFD. Condensers are porcelain cased tubular type impervious to moisture and are rated at

- 36" Color Coded Test Leads & Clips
- 9 Ranges From .0001 to .22 MFD

295

600 volts working capacity. 9 capacitance ranges are .0001, .0022, .0047, .01, .022, .047, .1 plus 22 MFD. Complete with 36" red and black test leads and alligator clips. Size: 4¾x2¾x1¾". Shpg. wt., 1½ lbs. 99 N 5020 Imported Net 2.95

RESISTANCE SUBSTITUTION BOX




Ideal for laboratory or service application. Substitute resistance values fast and accurately in trouble shooting circuits where values may have changed. Easy to find bias resistance in experimental vacuum tube or transistor circuits. Slide switch selects two

- 24 Resistance Ratings
- Two Ranges—Low 15-10K Ohms. High 15K-10 Megohms
- 36" Red & Black Test Leads with Alligator Clips

395

ranges—Low: 15 ohm—10K ohms (1 watt resistors) High: 15K ohm—10 Megohms (½ watt resistors). Two rotary switches (12 steps each) selects 24 separate resistances. Size: 4¾x2¾x1¾". Shpg. wt., 1½ lbs. 99 N 5021 Imported Net 3.95

LAFAYETTE IN-CIRCUIT CAPACITOR CHECKER



14⁹⁵

- Checks Capacitors in Circuit
- Magic Eye Indicator
- Wide Range 10 MMF to 2000 MMF

Allows you to check most capacitors from 10 mmf to 2000 mmf for open or shorted conditions without unsoldering. Just connect the test leads across the component you wish to test, press the switch and note the eye tube's face for an open or short condition. Checks coupling, by-pass, filter and blocking capacitors. Accurate readings are made in seconds—an important factor in today's complex electronic equipment. It also indicates capacitor leakage. Tests for opens on capacitors of 10 mmf. or more; for shorts up to 2,000 MF. Shunted by not less than 10 ohms. Complete with test leads and instructions. For 117 VAC. Size: 7¾Wx5Hx4¼"D. Shpg. wt., 5 lbs. Imported.
99 N 5022

Net 14.95

Selected Top-Quality Test Equipment Kits

LAFAYETTE TRANSISTOR ANALYZER KIT

6-IN-1 TESTER

- In-Circuit and Out-Of-Circuit Transistor Checker (Including Power Types)
- Diode and Rectifier Checker
- Signal Generator
- Battery Tester
- Voltmeter
- Milliammeter

13⁵⁰
MADE IN U.S.A.



Lafayette's 6-in-1 Transistor Analyzer is a tester capable of testing transistors of all types including power types. The in-circuit test couples the transistor to an oscillator circuit within the tester for an actual performance check. Externally the transistor is checked for leakage on a multi-colored scale and for beta gain in 3 ranges up to 200. Makes trouble shooting transistor radios easy by supplying a 5kc test signal with harmonics for checking the RF, IF, and AF circuits. This signal can also be coupled to an oscilloscope for a visual circuit function

test. This analyzer also checks the condition of diodes and rectifiers. Features a voltmeter which can check up to 12 volts DC and for testing transistor radio batteries. This analyzer can check current drain up to 80 milliamperes.

Complete with test leads and step-by-step illustrated instructions. Attractive black case and anodized aluminum front panel. 6 $\frac{1}{2}$ x5 $\frac{3}{4}$ x2 $\frac{1}{2}$ ". Shpg. wt., 3 $\frac{1}{2}$ lbs.

19 N 0901 Complete Kit Net 13.50
Extra 1 $\frac{1}{2}$ volt Battery (2 required) Net ea. .13
32 N 4801

RCA MODEL WV-77EK JUNIOR VOLTOHM METER KIT



29⁹⁵
46.95 WIRED

This kit makes possible substantial savings in a high quality vacuum-tube voltmeter. Its 28 ranges include 7 DC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with $\pm 3\%$ of full scale accuracy and input resistance of 11 megohms; 7rms AC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with $\pm 5\%$ of full scale accuracy; 7 peak-to-peak AC voltages: 0-4, 14, 40, 140, 400, 1400, 4000 volts, with 5% accuracy; 7 overlapping ohms ranges from 0.2 ohms to 1000 megohms with center-scale values of 10, 100, 1000, 10K, 100K, 1 meg. and 10 meg. ohms. Other important features include zero center for discriminator alignment; frequency response of 40 cps to 5mc. flat to within $\pm 5\%$ on the 1.5 to 15 volt rms and 4 to 40 volt p-to-p ranges; 1% deposited-carbon resistors; meter electronically protected against burnout. Power requirement is 5 watts at 105-125 v., 50-60 cps AC and VSD35 battery. Supplied complete with DC and AC/ohms probes and cables and ground leads, battery, and instruction book.

38 N 4602 Shpg. wt., 5 $\frac{1}{2}$ lbs. Net 29.95
WV-77E wired and factory-calibrated.
38 N 4603 Net 46.95

89⁹⁵



EICO DELUXE MODEL 460K 5" WIDE BAND SCOPE KIT

- For Color, Black & White TV Service And Lab Use

Excellent Lab precision scope featuring Push-pull direct coupled vertical amplifier with high sensitivity: 25 mv/in. Response flat from DC to 4.5 MC, useful to 10 MC, ideal for reproduction of 3.58 MC color TV sync. burst. 4-step freq.-compensated attenuator in both AC, DC positions. Also internal voltage calibration. Automatic sync. limiter and amplifier. 2X-full screen horizontal positioning. Sweep-freq.: 10 to 100K cps with external capacitor for lo-freq. sweeps. Preset TV V & H sweep positions (30 and 7875 cps). Variably lit graphed 5" screen. Very hi-input impedance. Complete with all components and instructions for easy assembly. 13x8 $\frac{1}{2}$ x16". For 105-125 VAC, 50-60 cycles. Shpg. wt., 30 lbs.

38 N 2643WX Model 460 Kit Net 89.95
Model 460. As above, but factory wired. Net 129.50
38 N 2644WX

EICO MODEL 667K DYNAMIC CONDUCTANCE TUBE AND TRANSISTOR TESTER KIT

Combines a mutual conductance test with a peak emission test to give a single reading of tube quality. Also checks transistors for leakage and beta. Read directly off the meter. Also checks 5 and 7-pin nuvistor, 9-pin novars; 12-pin compactrons; 7, 9 and new 10-pin miniatures; 5, 6, 7, and 8-pin subminiatures, octals and loctals... almost every domestic or foreign tube made. It will also check many low-power transmitting and special purpose tubes, voltage regulators, cold-cathode regulators, electronray indicators, ballast tubes and CRTs with optional adapter. Good-Bad test of pilot lamps. Extensive roll chart revised periodically. Multi-circuit level switch check individual tube sections and 13 push-button switches test leakage rapidly. Sensitive 4 $\frac{1}{2}$ " 200-ma D'Arsonval meter able to read low cathode current. For 105-130V AC, 60 cycles. Fused. Steel case. 12x15x4 $\frac{1}{2}$ ". Shpg. wt., 20 lbs.

38 N 2652WX Net 79.95
Model 667 as above but factory wired
38 N 2653WX Net 129.95

EMC MODEL 213 TUBE TESTER KIT



- Checks All Latest Tubes
- Large 3-Color Meter
- Portable And For Counter

18⁵²

Checks all new Compactrons, Nuvistors, Novars and 10 prong tubes in addition to Octals, Loctals, Miniatures and 9-prong tubes. Tests for shorts, leakages, intermittents and quality. Quality is indicated directly on 3-color metal dial. Each section of multi-purpose tubes is checked separately. Also tests Magic Eye, Voltage Regulator and Hi-Fi tubes. Supplied complete with high-impact bakelite case and strap, instructions and tube charts in ring bound manual. Size: 8 $\frac{1}{2}$ x7 $\frac{1}{2}$ x4".

Shpg. wt., 5 $\frac{1}{2}$ lbs.
38 N 2403 Model 213 Kit Net 18.52
As above, but factory wired.
38 N 2404 Net 28.42

EICO MODEL 955K IN-CIRCUIT CAPACITOR TESTER KIT

- In or Out of Circuit Short or Open Test, Measures Capacity

Checks for shorts (even in the presence of as little as 1 ohm shunt resistance). Checks for opens; capacitors as small as 15 mmf. in or dur of circuit. Wien bridge circuit measures capacitance with $\pm 10\%$ accuracy between 0.1 mf and 50 mf at any point on the 4" lucite dial-product, convertible into dissipation or power factor-indications visible on electron ray tube. Includes line adjust control. For 105-130 VAC. Size: 8 $\frac{1}{2}$ x5 $\frac{3}{4}$ x6"D. Shpg. wt., 4 lbs.

38 N 2691 Model 955 Kit Net 19.95
Model 955. Same as above but factory wired and tested.
38 N 2692 Net 39.95



19⁹⁵
KIT

LAFAYETTE Stereo And Monaural Phonographs



Smartly designed solid state stereo — folds up into a self-contained suit case for easy portability

69⁹⁵

\$5 monthly

LAFAYETTE SOLID STATE PORTABLE STEREO PHONO

- Garrard 4-Speed Intermix Automation Changer
- Solid State Stereo Amplifier—6 Transistor, 2 Silicon Diode Full Wave Rectifiers
- Instantaneous Warm Up
- Diamond Stylus
- Compatible—Plays Stereo and Monaural

A beautifully designed solid state stereo phonograph. Features famous Garrard 4 speed Intermix automatic changer that will handle all sizes and all speeds of both stereo and monaural records and will intermix different size records of the same speed. Automatic shut off after last record has been played. Contains on-off and reject switch. Deluxe stereo amplifier features 6 transistors and 2 silicon full wave rectifiers. Equipped with heavy "Power transformer," 3 stages of amplification—4 audio control functions—separate full range compensated loudness and balance controls plus separate treble and bass controls. Each detachable speaker wing contains a high efficiency 5" extended range speaker with 1.47 oz. magnet. Turnover Stereo cartridge with synthetic sapphire and diamond stylus—attractive charcoal black case. For 110-120VAC, 60 cycle. Size 17½x13x9½". Shpg. wt., 24 lbs.

24 N 0206WX Net 69.95
21 N 3711 45 RPM Spindle for Garrard changer Net 3.80

MAGNIFICENT LAFAYETTE SOLID STATE "TABLE TYPE" PHONO



119⁹⁵

\$6 monthly

● Elegantly styled genuine walnut wood cabinet with beautiful oiled walnut finish.

- Powerful 24-watt amplifier — 10 Transistors, 2 Silicon Diode Full Wave Rectifiers
- 2 Deluxe Separate Matching Speaker Systems with high Efficiency 8" Extended Range Speakers for Rich Brilliant Sound Reproduction
- Famous Garrard AT-5 4-Speed precision automatic Turntable

An elegantly styled Solid State Stereo "Table Type" phonograph which will enhance the decor of any room. Offers rich brilliant sound reproduction. The control center consists of a 10-transistor integrated amplifier which produces 24 watts peak music output—amplifier features push-pull output, heavy duty power transformer. Four audio control functions—separate variable bass and treble, loudness, and balance. 2 separate matching speaker systems feature high efficiency 8" extended range speakers. Famous Garrard "AT5" 4-speed precision automatic turntable plays 7", 10", and 12" records in all 4 speeds. Intermixes different size records of the same speed. Wide range turnover stereo cartridge is equipped with a diamond stylus for LP and stereo records, and a synthetic sapphire-stylus for standard 78 RPM records. The phonograph and matching speakers are housed in Genuine walnut wood cabinets with beautiful all walnut finish. Dimensions: Cabinet 19¼x14x8". Speaker Encl. 13½x10x4". For 110-120V 60 cycle AC. Shpg. wt., 40 lbs.

24 N 0208WX Net 119.95
21 N 3712 45 RPM Spindle for Garrard AT5 Net 3.80

DELUXE LAFAYETTE AUTOMATIC 4-SPEED MONAURAL PHONOGRAPH

- Features Deluxe "Maestro" 4 Speed Automatic Record Changer
- Plays 16½, 33½, 45, and 78 RPM Records
- Intermixes Different Size Records of the Same Speed
- Automatic Shut-Off After Last Record

37⁹⁵

\$5 Monthly



A deluxe automatic phonograph in a beautiful two-tone interlaced blue and white case. Plays 16½, 33½, 45, and 78 RPM records. Intermixes different size records of the same speed. Automatic shut-off after last record has been played — motor shuts off and arm returns to rest position automatically. Separate tone and volume controls. on-off reject switch. Fine Alnico V PM speaker for magnificent sound reproduction. Turnover cartridge with dual synthetic sapphire stylus. For 110-120 volt 60 cycle AC. Size: 15x14x7". Shpg. wt., 15 lbs.

24 N 4201W Net 37.95

45 RPM Spindle for above phonograph. Net 1.49
24 N 4203 Shpg. wt., ½ lb.



LAFAYETTE "JUNIOR" 4 SPEED MANUAL PHONO

14⁹⁵

- For the young. Plays all records, all speeds

Plays up to 12" monaural records at 16½, 33½, 45 or 78 RPM. A single lever selects any speed. The lightweight pickup arm is equipped with a single all-purpose needle for all records. Has volume control with on-off switch. Retractable 45 RPM chuck. Fine quality Alnico V PM speaker. Attractive 2-tone leatherette covered case. For 110-120 volts, 60 cycles. Size: 11¼x10½x8 5/8" H. Shpg. wt., 8 lbs.

24 N 6101W Net 14.95

LAFAYETTE Model LR-800 70-Watt Complete AM-FM Stereo Receiver



• Nuvistor "Front-end" with 1.5 μ v Sensitivity • FM "Stereo Search" Circuitry—Signals Presence of Stereo Broadcasts • Complete Preamplifier Control Facilities—70-watt Amplifier • Variable AFC control • front Panel Stereo Headphone Jack • Bar-Type Tuning Indicator for AM and FM

199⁵⁰

\$10 monthly

The deluxe Model LR-800 contains on one compact chassis all the electronics necessary for a superb complete home music system. Just add speakers to enjoy the magnificent fidelity of FM, FM Stereo or high quality standard AM broadcast. Addition of a phono or tape transport completes your high fidelity system. Features: Extremely sensitive "Nuvistor" front end pulls in FM stations free of noise and spurious signal interference. Amazing "Stereo Search" circuit pinpoints stereo stations quickly and positively with a tone signal heard through your loudspeakers. Bar-type electron-ray tuning indicator and large easy-to-read slide rule dial, with flywheel tuning action make tuning FM or AM a pleasure. Variable AFC controls "locks-in" stations. Powerful 70-watt stereo amplifier reproduces all program material with clean sound even with inefficient speaker systems. The audio control center features separate friction-lock bass and treble controls for each channel, balance control, rumble and FM noise filter; loudness switch and front panel stereo headphone jack/speaker "off" switch for private listening. Tape monitor lets you evaluate recorded material as you tape it. Separate Mode selector

permits choice of Left channel, Right channel, Stereo, Mix and Reverse. Input selector controls access to AM, FM, FM stereo tuner, Phono, Tape and Auxiliary program sources. Handsome gold extruded aluminum panel and contrasting case go well with any decor. 17Wx 5 7/8x14"D. For 117V 50/60 cycles AC. Shpg. wt., 40 lbs. Imported. \$9 N 9005WX \$10 Monthly Net 199.50

SPECIFICATIONS

Tuner Section—FM Sensitivity: 1.5 μ v for 20 db quieting. MPX Separation: 37 db @ 400 cps. Frequency Response: FM Mono—20-20,000 cps \pm 1db. FM Stereo 50-15,000 cps \pm 1db. Harmonic Distortion: Less than 0.5% @ 1KC. **Amplifier Section**—Power Output: 35 watts per channel Music Power, Hum and Noise: 55 db low level, 80 db high level. Harmonic Distortion: 1% at full output. Output Impedances: 8 & 16 ohms, switch selected. Equalization: RIAA (Mag), NAB (tape Head). **Tapes:** 24 inclu. EM-84 tuning eye, 9 diodes, 1 selenium rectifier, 2 AC receptacles, 1 switched.

LAFAYETTE 70-WATT STEREO SYSTEMS FEATURING MODEL LR-800 AM-FM STEREO RECEIVER

CHOICE OF STEREO CARTRIDGE



AS LOW AS

28850

13.50 Monthly

2 SK-270

- Lafayette LR-800 70 watt AM-FM Stereo Receiver
- Garrard Model AT60 4 Speed Record Changer
- Pickering V15/AT-1 Diamond Needle Cartridge*
- Wood Base for Changer (Specify Oiled Walnut or Mahogany)
- 2 Lafayette SK-300 "Decor-ette V" 5-Speaker Slim Speaker Systems (Oiled Walnut).

Above stereo system with your choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge; complete with all necessary cables and instructions. Shpg. wt., 96 lbs.

21 N 9746CWXM Net 295.50

Same as above except with 2 Lafayette famous SK-58 12" Free Edge Coaxial Speakers instead of SK-300 "Decor-ette V" Speaker systems. Shpg. wt., 84 lbs.

21 N 9753CWXM Net 288.50

Same as 21 N 9753CWXM plus 2 Lafayette famous patented Eliptoflex enclosures. Shpg. wt., 132 lbs. (Specify Oiled Walnut or Mahogany).

21 N 9754CWXM Net 345.95

Same as 21 N 9746CWXM except with 2 Lafayette superb SK-270 Decor-ette II 5-speaker slim speaker systems (oiled walnut) instead of Decor-ette V speaker systems. Shpg. wt., 110 lbs.

21 N 9749CWXM Net 350.50

GARRARD
AT60

2 SK-300 DECOR-ETTE V

2 SK-58

2 ELIPTOFLEX

Prices On This Page May Be Raised April 1st Due To New Excise Tax

Lafayette Cat. No. 653 155


LAFAYETTE
RADIO
ELECTRONICS
 111 JERICO TURNPIKE
 SYOSSET, L.I., N.Y. 11791

CB 12/64 A
 G. DAVIDSON
 107 S MAIN ST
 LEWISBURG OHIO

BULK RATE
 U.S. Postage
PAID
 LOUISVILLE
 KENTUCKY
 Permit No. 599

K L M N P
 R S T W

POSTMASTER
 IF UNDELIVERABLE DO NOT RETURN



No License Required
 (FCC Reg. part 15)

LAFAYETTE All-Transistor Citizens Band "Walkie-Talkie" Model HA-70A

GREAT FOR: HOME, HUNTING, FISHING, PICNICKING,
 CYCLING, CAMPING, GOLFING, ETC.

NOT A KIT — COMPLETELY WIRED

Great fun for the kids!
 At a price even they can afford!

Our Low, Low Price

9⁸⁸
 2 For 18.88

- 3 Transistors
- Crystal Transmit
- Sensitive Super-regenerative Circuit

No Time Wasted in Building—Use This Terrific Little Walkie Talkie
 As Soon As You Receive It! Attractive, Neatly Styled Plastic Case—
 Slip it Into Your Shirt Pocket!


A great new CB challenge to young and old for countless exciting short range applications. This compact Lafayette Citizens Band Walkie Talkie is a 3-transistor transmitter with crystal control on transmit and with an efficient super-regenerative receiver. Super-regenerative has minimum external ignition noise pickup when voice signal is being received. Excellent for camping, picnicking, hunting, fishing, golfing, surveying, cycling, construction and many other applications requiring up to ¼ mile communications. Has Push-to-Talk Button, On-Off Switch and efficient speaker that is used as speaker and microphone. Complete with built in telescope antenna, transmitting crystal, one 9-volt battery and plastic carrying case. Size: Approx. 5½x2½x1¾". Shpg. wt., 1 lb. Imported.

99 N 3011L Model HA-70A	Net ea. 9.88
	2 for 18.88
99 N 6021 Replacement battery for above	Net .21

LAFAYETTE 6-Transistor Superheterodyne CB "Walkie Talkie" Model HA-85

- 6 Transistors plus 2 Diodes
- Transmits and Receives up to 1 Mile
- Crystal Controlled Transmit and Receive
- Efficient Superheterodyne Receiver
- Leather Case with Shoulder Strap
- Earphone for Personal Listening

only
19⁹⁵
 2 For 38.75



Ideal for sports, boating, hunting, fishing etc. Weighs only 15 oz. and is small enough to slip into your pocket. ON-OFF Volume Control and Push-to-Talk switch provides easy one hand operation. Conforms to FCC requirements for 100 milliwatt units. In attractive metal case with leather carrying case and shoulder strap. Complete with earphone in addition to built-in speaker, telescoping antenna, 6 penlight batteries and a pair of crystals for the channel of your choice. 6½x2½x1¾". Shpg. wt., 2½ lbs. Imported.

99 N 3013CL Model HA-85, Specify Channel	Net 19.75
	2 for 38.75
42 N 4204C Replacement Transmit Crystal, Specify Channel	Net 2.25
42 N 4005C Replacement Receive Crystal, Specify Channel	Net 2.25
99 N 3021 Replacement Earphone for HA-85	Net .49
32 N 4802 Replacement "Z" batteries, 6 required	Net ea. .13

AC Power Supply

Use in place of batteries for operation on 110 VAC. Shpg. wt., 2 lbs.	
99 N 3012	Net 6.95

No License Required
 (FCC Reg. Part 15)