

LAFAYETTE'S

GIANT SYOSSET EXPANSION

SALE

That's Right — To serve you better
we've EXPANDED

Our new 120,000 sq. ft. mail order and sales center in Syosset, Long Island, New York is open and ready to serve you with the **BEST BUYS & LARGEST SELECTION** in our 41 year history.



LAFAYETTE
RADIO
ELECTRONICS
CATALOG
NO. 623


LAFAYETTE BREAKS THROUGH THE STEREO PRICE BARRIER!



A COMPLETE MATCHED STEREO PHONO SYSTEM
FEATURING THE PHENOMENAL NEW
LAFAYETTE LA-210 STEREO AMPLIFIER
Outstanding Stereophonic Performance
at a Budget Price.

NOW
FROM LAFAYETTE
THE REVOLUTIONARY
LA-440 ALL-TRANSISTOR
STEREO AMPLIFIER

99.95
NO MONEY
DOWN



Made in U.S.A.


99.50
NO MONEY
DOWN

SYSTEM FEATURES THESE QUALITY COMPONENTS

- LAFAYETTE LA-210 10-WATT STEREO AMPLIFIER. A superb stereo performer providing 5-watts each stereo channel... more than enough power for room filling stereophonic sound. Frequency Response is 30-20,000 cps with Hum & Noise 65 db below rated output. Contains a full range of inputs and controls.
- LAFAYETTE SK-124 2-WAY BOOKSHELF SPEAKER SYSTEMS (Choice of Mahogany or Walnut). These famous Lafayette speakers feature a unique dual cone construction to provide smooth distortion-free response with deep fundamental bass and clear pure highs.
- LAFAYETTE LA-210 10-WATT STEREO AMPLIFIER. A superb stereo performer providing 5-watts each stereo channel... more than enough power for room filling stereophonic sound. Frequency Response is 30-20,000 cps with Hum & Noise 65 db below rated output. Contains a full range of inputs and controls.
- LAFAYETTE PK-605 4-SPEED STEREO RECORD CHANGER. Contains famous Ronette Stereo Cartridge and is complete with your choice of Mahogany or Walnut base. Superior performance without rumble or wow provided by a heavy precision balanced turntable and constant speed motor. Features include full automatic operation with intermix and automatic shut-off after last record.
- 2-LAFAYETTE SK-124 2-WAY BOOKSHELF SPEAKER SYSTEMS (Choice of Mahogany or Walnut). These famous Lafayette speakers feature a unique dual cone construction to provide smooth distortion-free response with deep fundamental bass and clear pure highs.
- Complete stereo system as listed above. Shpg. wt., 67 lbs. LS-210WX Net 99.95

Lafayette Applies Space Age Electronics To High-Fidelity Design

- Dual Concentric Bass & Treble Controls
- Brilliant Design & Performance
- Frequency Response — ± 0.5 db 20 to 20,000 cps
- Instantaneous Operation—No Warm-Up Required
- Hum, Noise & Microphonics Virtually Eliminated
- Place Anywhere—Does Not Require Ventilation as No Heat is Generated




20 Transistors plus
4 Germanium Diodes plus
3 Silicon Diodes plus
2 Thermistors

GENERATES NO HEAT—no need to worry about ventilation, you can place it anywhere and current drain is so low, it will operate efficiently not only at 110 VAC, but even from 12 to 28 volt batteries, **REQUIRES A MINIMUM OF MAINTENANCE**—since transistors last indefinitely maintenance problems are virtually a thing of the past and performance will not deteriorate. **VIRTUALLY ELIMINATES HUM, NOISE AND MICROPHONICS**—performance can best be described as transparent, the only sound you hear is that of the music. **PROVIDES INSTANTANEOUS OPERATION**, no need to wait for warm-up, the LA-440 plays as soon as it is turned on. Front panel controls include: dual concentric Bass and Treble controls, Volume control, Balance control plus selector switch. Slide switches provide for Mono A—Stereo—Mono B, Loudness, Scratch Filter and Rumble Filter. Rear Panel contains 2 switched AC outlets plus 3 tape outputs for recording stereo or mono. Complete with matching enclosure with brushed gold front panel and gold finished aluminum knobs. Size: 3HX10 $\frac{1}{2}$ WX8 $\frac{1}{2}$ "D. Shpg. wt., 10 lbs. LA-440WX Net 99.50

STUDY & COMPARE THESE SPECIFICATIONS
I.H.F.M. Music Power Output: 40 watts (20 watts per channel) based on 4-ohm load impedance.
Frequency Response: ± 0.5 db to 20 to 20,000 cps measured according to IHFM standards.
Intermodulation Distortion: 0.9% at 1 db below clipping 60 and 6,000 cps.
Harmonic Distortion: 0.5% at 1 db below clipping.
Hum and Noise: Completely inaudible at all playing levels.
Phono Input: 72 db Tuner Input: —85 db.
Output Impedance: May be used with 4, 8, 16 ohm loud-speakers.
Power Requirements: 105-120 volts AC, 50-60 cps. 12 to 28 volts DC for battery operation.

LAFAYETTE "MINI" 6 TRANSISTOR RADIO



FS-235L

ONLY 13.98

- 6 Transistors Plus Germanium Diode and Thermistor
- Vest Pocket Size — Only 3 $\frac{1}{2}$ " H x 2 $\frac{1}{2}$ " W x 1" D.
- Weighs only 7 ounces with batteries
- Penlight Powered For Economy — Long Life
- Earphone Jack Built-in For Private Listening
- Trouble-Free Printed Circuit
- Superheterodyne Circuit

FOR COMPLETE DETAILS SEE PAGE 2



NOW! NO MONEY DOWN when you use Lafayette's **NEW EASY-PAY PLAN!**

**LAFAYETTE
RADIO**

111 JERICHO TURNPIKE
SYOSSET, L. I., NEW YORK
Open MON. and FRI., 'til 8:45 P.M.

SHOP BY PHONE DEPT. WALNUT 1-7500

ALL DEPARTMENTS WALNUT 1-7700

JAMAICA	NEW YORK	BRONX	NEWARK	PLAINFIELD	PARAMUS	BOSTON
165-08 Liberty Ave. Jamaica 33, N. Y. AXtel 1-7000	100 6th Avenue New York 13, N.Y. WORTH 6-5300	542 E. Fordham Rd. Bronx 58, N. Y. FORDHAM 7-8813	24 Central Avenue Newark 2, N. J. MARKET 2-1661	139 W. 2nd Street Plainfield, N. J. PLAINFIELD 6-4718	182 Route 17 Paramus, N. J. COIFAX 1-8800	110 Federal Street Boston 10, Mass. HUBBARD 2-7850
Open MON. and FRI., 'til 8:45 P.M.	Open THUR. 'til 8:45 P.M.	Open THUR. 'til 8:45 P.M.	Open WED. 'til 8:45 P.M.	Open THUR. 'til 8:45 P.M.	Open MON., WED. & FRI. 'til 8:45 P.M.	Open MON., WED. 'til 8:45 P.M.

• ASSOCIATE STORES — SEE REAR COVER •

LAFAYETTE 7-Transistor Marine & Broadcast 2-Band Radio



A MUST for
Marine Enthusiasts

22.50

NO DOWN MONEY

9 SECTION
ANTENNA EXTENDED



- Covers AM Broadcast Plus 1.6-4.8 MC. Marine Band • Sensitive Receiver Uses 7 Transistors, 2-Diodes, And 1-Thermistor
- 2 Built-In Antennas, Including 9 Section Telescoping Antenna for Marine Band • Operates on 2 Inexpensive Penlight Batteries
- Complete With Carrying Case, Batteries, and External Earphone • A Must For Marine Enthusiasts • Compact and Light-Weight

With this new sensitive transistorized radio, Lafayette answers the needs of the marine enthusiast. Designed to be used by the week-end sailor as well as the serious yachtsman, the FS-223 is a power-packed, 7 Transistor, superheterodyne receiver. It receives both the standard AM broadcast band and the Marine Band (1.6-4.8 MC). A built-in antenna is used for the broadcast band and a 9 section telescoping antenna for the marine band. The telescoping antenna is readily detachable and may be carried in the same manner as a pocket pen. The receiver circuitry utilizes 7 transistors, 2-diodes and 1-thermistor for power-packed performance. Simple selector switch allows choice of Broadcast or Marine Bands and a clearly marked slide dial makes tuning simple. The built-in speaker can be shut-off by inserting an external earphone (supplied) for personal listening. Operates on 2 inexpensive Z cells giving up to 3 times longer life than ordinary 9 volt batteries. Comes complete with 9 section telescoping antenna, carrying case and earphone. Measures only 5 7/8x3 1/2x1 1/2". Shpg. wt. 2 lbs.

FS-223L Net 22.50
Replacement batteries for FS-223 7 Transistor radio, 2 required.
BA-155 Z Cells Net each .095

New! LAFAYETTE Executive DESK SET




- It's a 7-Transistor Radio!
- It's a Cigarette Box!
- It's a Pen Holder!
- Handsome Black Case with Gold Trim!
- Perfect Gift For The Man On The Way Up!

Now a Three-in-one desk set. A powerful 7 transistor AM broadcast radio specially designed to harmonize with the entire unit. Radio operates on four economical penlight cells to give long dependable service. The dial face is tilted and tuning knobs top mounted for maximum legibility and accessibility. Includes Earphone too for private listening! Right hand portion holds an extra large compartment useful for cigarettes or paper clips, etc. Two convenient penholders complete the set (Pens are not included). Beautiful black and gold finish make a most attractive addition to a desk. The ideal gift. Complete with 4 penlight cells and earphone. Size: 11 3/4 Wx2 3/4 Hx6" D.

FS-238L Shpg. wt., 6 lbs. Net 19.95
Extra "Z" batteries, 4 required. Net ea. .095; 2 for .19
BA-155

LAFAYETTE



NO MONEY DOWN **48.95**

- Three Bands Long Wave Weather Band 190-400 KC Broadcast—540-1600 KC Short Wave Marine Band 1.6—5 MC • Built-In Quality Speaker • Telescoping 9 Section Antenna • Earphone With Cord, Plug, and Leather Case • Sensitivity Control • Tone Control • Powered by 4 Inexpensive 1.5V Batteries • An Outstanding Value At Any Price • Compact, Lightweight, Self-Contained • Jack For External Speaker • Microphone Adapter for P.A. Use

A mighty-mite in any class, the Lafayette 3 band portable outperforms many home radios. Combining extremely sensitive receiver circuitry with compact design, this receiver is the answer to many boatmen, aviators, weather observers, and outdoorsmen. Giving versatility rarely obtainable in other portable receivers, this unit covers Long Wave, Broadcast, and Shortwave Marine Bands. It can be used to receive Weather, Broadcast, Marine, Aviation, Beacon, and Ham Stations. Features a handsome cabinet with clearly marked slide-rule dial. Nine Transistors, 2 diodes, and 1 thermistor. Built for years of trouble-free operation. SPECIFICATIONS: BANDS—190-400 KC, 540-1600 KC, 1.6-5MC. CONTROLS—ON-OFF Switch, Volume, Tuning, Sensitivity, Tone, and Band Switch. Two antennas—A 9-section telescoping antenna for long and short waves and a powerful built-in ferrite antenna for Broadcast stations. PUSH-PULL AUDIO POWER OUTPUT STAGE. OUTPUTS—2 Phone jacks, phono. This compact, highly sensitive receiver comes complete with a handsome leather carrying case, earphone, plug, earphone case, cord, shoulder strap, battery and adapter for an external speaker. Size—8 1/2x4 1/2x1 7/8". Carrying weight—less than 3 lbs. Shpg. wt., 4 1/2 lbs.


FS-93L Net 48.95
Replacement battery for above receiver (Four Required). Net each .13
BA-156

9-TRANSISTOR PORTABLE 3-BAND RECEIVER

WEATHER, AVIATION, BEACON, MARINE,
AND STANDARD BROADCAST BANDS

EMPLOYS 9 TRANSISTORS,
2 DIODES, PLUS A THERMISTOR
FOR HIGH GAIN PERFORMANCE

For The First Time A Radio That
Receives 190-400 KC Weather,
Airplane and Direction
Beacon Band Plus 1.6-5 MC
Marine Band Plus
Broadcast Band



- Adapter for External Speaker
- Earphones with Cord, Plug and Case
- PRECISION DESIGN FOR TOP PERFORMANCE

LAFAYETTE "MINI" 6 TRANSISTOR RADIO

ONLY 13.98

- 6 Transistors Plus Germanium Diode and Thermistor • Vest Pocket Size—Only 3 1/2 H x 2 1/2 W x 1" O. • Weighs only 7 ounces with batteries
- Penlight Powered For Economy—Long Life • Earphone Jack Built-in For Private Listening • Rich Tone Dynamic Speaker • Trouble-Free Printed Circuit • Built-in Ferrite Bar Antenna • Superheterodyne Circuit

A truly remarkable radio, the "MINI" 6 is so compact and lightweight (just 7 oz.) you hardly know you're carrying it—turn it on and get the biggest, clearest sound yet, from a pocket 6 transistor set. Precision engineered—true superheterodyne printed circuit board assures long trouble-free operation. Push-pull audio output, 6 transistors, one diode and one thermistor are utilized to obtain really phenomenal reception across the entire broadcast band. Only 2 two inexpensive penlight cells are required. This cuts down battery drain and lengthens playing time considerably over ordinary single cell radios. 'Jewel' black and gold case of durable plastic and soft attractive black leather carrying case with attached earphone pouch complete this smart set. Includes 2 batteries, carrying case and matched earphone for personal listening. All at our low, low price. Shpg. wt., 1.5 lbs.

FS-235L "MINI" 6 transistor Radio Net 13.98
Extra batteries for FS-235L Type Z (2 required). Shpg. wt., 4 oz. Net ea. .095
BA-155



NEW! *Testest*™

2 TRANSISTOR PORTABLE
with
BUILT-IN
SPEAKER

6.95



- 2-TRANSISTORS + 1 DIODE
- BUILT-IN SPEAKER • COMPLETE WITH TELESCOPING ANTENNA, EARPHONE & CARRYING CASE

A two-transistor powerhouse that will amaze you with its performance and sound quality. Here's the perfect gift for that youngster who has always wanted a portable radio or use it yourself—take it anywhere, it plays everywhere. Equipped with both a ferrite antenna and detachable telescoping antenna to assure outstanding reception. In addition to its own built-in speaker the radio is supplied with an earphone for private listening. Small enough to fit in the palm of your hand, it measures a mere 4x2 1/2x1 1/4". Complete with earphone, telescoping antenna, carrying case and battery. Shpg. wt., 1 lb.

FS-117L Net 6.95
BA-2 Replacement Battery. Shpg. wt., 3 oz. Net .39


BIG SAVINGS VALUES

Tru-test™ SUPER BUY AC/DC TABLE RADIO

- Power-Packed Performance — 5 Tubes (2-dual purpose)
- "Easy-Tune" Dial
- Attractive Decorator Cabinet
- For Home, Store, Office; Wherever Radio Pleasure is desired

This Lafayette SUPER-BUY features 5 tubes (2 Dual Purpose) giving peak performance for clear, steady sound. A sturdy 3 1/2" Alnico PM Speaker gives fine tone response. An unusual "Easy-Tune" dial makes station selection simple. The built-in antenna covers the entire broadcast band from 530 to 1600 KC. Tubes: 1-12BE6, 1-12BD6, 1-12AV6, 1-50C5, 1-35W4. Will operate on 120V AC or DC. Dimensions 4 1/2" high, 6 3/4" wide, 3 1/2" deep. Shpg. wt., 3 lbs. FS-240 Net 8.95

8.95



"CONTEMPORARY" AC/DC RADIO

- Styled For Any Decor!
- Priced For Every Pocket!
- Put One In Every Room!
- 5 Tubes For Peak Performance!
- Swivel Base

10.99

A "better" 5 tube radio — engineered and styled to last. Petite, contemporary design maintains clean, good looks and peak performance. 5 tubes (2 dual purpose), plus a Hi-Q ferrite rod antenna pulls in more distant AM stations. 3 1/2" P.M. speaker, properly baffled in a sturdy, vented cabinet for clear tonal quality. Muted colors to match any color-scheme; gold trim. Pedestal base swivels for sound and reception directivity. Cabinet measures 8 1/2" x 4 1/2" x 4" overall. Tubes: 35W4, 50C5, 12AV6, 12BA6, 12BE6. For 117 V. A.C./DC. Shpg. wt., 3 lbs. FS-233 Net 10.99

NEW! HOUSE N' CAR RADIO

- Plays In Any 12V. Car or Boat or on 117V AC/DC
- No Installation — Just Plug In Lighter
- Needs No Outside Antenna
- Complete With Generator Condenser and Noise Suppressor

Play this radio anywhere! In the home — car — boat — trailer! Any place you can obtain a 12V D.C. or 117 V AC/DC supply! The radio (our FS-233) and the new Dynamo inverter form a customized package to suit a wealth of needs. You can even run your shaver in your car or boat! Shpg., wt., 5 lbs. SP-229 Net 18.66

18.66



NEW FAMOUS BRAND 19 INCH PORTABLE TV

- Big Screen 19" 114° Picture Tube
- Thin-line Briefcase-type Styling
- Hand Wired Chassis
- Filament Transformer—17 Tubes
- Built-in Telescoping Antenna

Only **127.50**
No Money Down



Big screen 19" portable television is now yours at a sensible price. Stylish, with convenient top mounted tuning, 17 tubes—3 video IF stages and 2 sound IF stages plus adjacent channel traps provide sharp, clear pictures and sound even in fringe areas. Quality telescoping antenna is adequate for most reception areas, however a convenient outlet is built in for connection of an external antenna if desired. Features a completely hand-wired chassis and a heavy duty filament transformer for top performance and extended tube life. All components are bolted in—no rivets are used and in addition, the set's tubes are accessible from the rear—important points in keeping down service costs. A full set of controls is included. Channel selector/fine tuning, contrast, off-volume, vert. hold, horiz. hold, brightness, AGC, vert. linearity and height. Finished in Ivory, it will grace any room. Size: 19Wx15 1/4Hx12 1/2"D. Shpg. wt., 60 lbs. FS-500WX Net 127.50

AUTOMATIC 6-TRANSISTOR CLOCK-RADIO with 7-JEWEL PRECISION ALARM-WATCH

- 7-Jewel, 11 Ligne, One-Day Alarm Movement
- Automatically Turns Radio On or Off
- Superhet Circuit — 6 Transistors, 1 Diode, 1 Thermistor
- Pocket Size — 4 3/4x3 1/4x7/8"
- Complete With Earphone, Batteries and Handsome Gift Case

29.95
NO MONEY DOWN



More than just a clock-radio, the FS-124 is an all-transistor clock-radio featuring a patented 7-jewel watch movement with a 11 ligne one-day alarm... automatically turns the radio on at a preset time or lets you go to sleep to music and automatically shuts off. The superhet circuit uses 6 transistors, one diode and one thermistor for more power and better sensitivity. Other advanced engineering features include AVC, push-pull output stage, ferrite rod antenna, 2" speaker, gear vernier tuning, Magnifying optic glass over dial plate for easier selectivity. Operates on 3 inexpensive penlight batteries. High-impact plastic case resists breaking and chipping. Complete with earphone for private listening, batteries, gift case. Shpg. wt., 2 lbs. FS-124L Net 29.95
Extra penlight batteries for above. BA-155 Net ea. .095



NEW!

8" PERSONAL PORTABLE TELEVISION RECEIVER

- Compact Size—Smart Styling
- Front Mounted Speaker For Crystal Clear Sound
- Built-In Telescoping Antenna/earphone Jacks
- Hand Wired Chassis
- 2 Earphones For Private Viewing.



Only **119.50**
No Money Down

Weights just 18 lbs. Carry it Anywhere!!

Tomorrow's portable here today! Imagine a TV only 12 inches at its deepest point and weighing only 18 lbs. It is truly the "second" set you have been looking for. Ideal for sickrooms, den, children's room, bedroom or patio. AC operated, the specially designed chassis is completely handwired and constructed for maximum heat dissipation. Tubes are accessible from the rear for easy replacement. Some outstanding features including a built-in telescoping antenna and jacks for external antenna connections; a front mounted speaker for optimum sound dispersion; a local-distance switch for best reception and built-in earphone jacks which provide a choice of earphone listening only or speaker on, plus earphone listening. Powerful advanced design circuit with 13 tubes plus picture tube and silicon rectifier power supply. Cascade tuner, 3 video IF stages, 2 Sound IF stages and adjacent channel traps. Fused AC line. Complete with earphones. Size: 11 1/4Wx7 3/4Hx12"D. Shpg. wt., 25 lbs. FS-501WX Net 119.50

ULTRA-MINIATURE 3 TRANSISTOR HEARING AID

- Extremely Light In Weight - Less Than One Ounce
- Extremely Compact; Dimensions: 2 3/4" Long, 3/4" Wide and 3/8" Thick
- Uses Inexpensive, Long Lasting Mercury Cell



29.50
with Battery

Only 2 3/4" x 3/4" x 3/8" — almost as small as a tie clasp, this precision unit employs an advanced 3 transistor circuit powered by a tiny inexpensive mercury cell. A 180° rotating volume control provides exactly the amount of amplification necessary, while a MIC lever readjusts sensitivity for telephone use. Supplied with 3 ft. flesh-tinted cord, earpiece, velvet lined leather carrying case. Mercury cell and instructions. Shpg. wt., 1 lb. Net 29.50
F-758L Net .30
BA-523 Extra Battery (Mallory RM 625R)

SUB-MINIATURE 4-TRANSISTOR HEARING AID

- Lightweight—Weights Less than 2 oz. Including Battery
- Small Enough To Be Carried in Breastpocket
- 4-Position Tone Control
- Unique Telephone Switch Allows Telephone Conversation
- Latest Electro-Magnetic Earphone and Miniature Crystal Microphone
- Utilizes Economical Penlight Battery

ONLY 2 1/2" LONG x 1 1/4" WIDE
22.50 x 3/8" THICK



Features an extremely advanced circuit with 4 transistors, a high performance crystal microphone, 3 ft. thin plug-in colorless flexible cord and a unique magnetic earphone providing the clearest reception and sound reproduction yet achieved. Supplied with leather carrying case, earphone and battery. Shpg. wt., 1 lb. F-480L Net 22.50
BA-153 Extra Battery (1 required) Burgess NE type. Shpg. wt., 3 oz. Net .08
F-567 Extra Plug-In Cord For F-480 Net .55
F-568 Extra Earphone For F-480 Net 1.59

NEW GRANCO STEREO MULTIPLEX RADIOS

DR-17 **38.95** DR-20 **28.95**

NO MONEY DOWN

DR-18 **23.95**

STEREO FM/AM RADIO

Compact, smartly styled table radio plays AF, FM and FM stereo multiplex with the SC-3 Speaker-Amplifier companion. Exclusive "Auto-G-Tuner" assures sensitive, drift free performance. Built-in Linetenna requires no installation. Phono input jack. High power 6 tube chassis provides 8 tube performance. Easy-view window dial and vernier tuning. Cabinet is completely enclosed. Attractive gray with white grill. 9 1/2Wx4Dx5"H. Shpg. wt., 7 lbs. DR-17 Granco 703 Net 38.95

attaches the SC-3—no installation necessary. Powerful speaker and amplifier. Volume control and function selector switch. For quality stereo at a modest price. Available in Grey. Size: 9 1/2Wx4Dx5"H. Shpg. wt., 5 lbs. DR-18 Granco SC-3 Net 23.95
Acoustically Matched Stereo Pair Models 703G & SC-3. Shpg. wt., 12 lbs. DR-19 Net 58.95

STEREO COMPANION FOR GRANCO FM RADIOS

- Acoustically Matched
 - Plugs in—No Attachments Necessary
 - Doubles your Sound
- Specifically designed to match Granco radios 603 and 703 both acoustically and aesthetically. For perfect stereo FM reception, an interconnecting plug-in cable DR-21

Low Cost Stereo FM Radio

Super powered, high sensitivity 5 tube chassis provides 7 tube performance. New hand wired detector circuit offers hi-fi and stereo-multiplex at exceptionally low cost with the use of the SC-3, matching FM multiplex speaker/amplifier unit. Other features includes new auto-G tuner for drift free performance, easy-view window dial with vernier tuning, phono input jack and built-in antenna. Decorator cabinet encloses entire set. Gray only. Shpg. wt., 6 lbs. DR-20 Granco Model 603G Net 28.95

Combination of Model 603 FM Radio and SC-3G Stereo Companion. Shpg. wt., 12 lbs. DR-21 Net 51.50

LAFAYETTE SPECIAL PHONOGRAPH SALE

with **FREE DIAMOND STYLUS**

NO MONEY DOWN

49.95



With FREE Diamond Stylus!

LAFAYETTE AUTOMATIC STEREO PHONOGRAPH

• Compatible—Plays Both Stereo and Monaural Records • 4-Speed British Changer

New, attractively styled automatic stereophonic phonograph featuring the latest Monarch 4-speed automatic intermix record changer. Complete with stereo crystal turnover cartridge with dual sapphire styli. Plays both stereo and monaural records. Among many features are automatic record intermix mechanism, automatic motor shut-off at the end of last record, automatic arm return, free-floating motorboard eliminating acoustic feedback. Careful design assures long life and freedom from trouble. Takes all record sizes, and plays all 4 speeds: 16 2/3, 33 1/3, 45 and 78 RPM. Controls include separate volume controls for each channel and dual channel tone control. Built-in Alnico 5 PM speaker provide clean, balanced sound. Second Alnico 5 PM speaker is housed in the removable phonograph cover. 8 ft. cable supplied, permits placement of second speaker for optimum stereo effect. Covered in charcoal linen leatherette with oyster white trim. Tubes 2-50C5, 1-12AX7 and 35W4 rectifier. Size: 19 1/4 x 15 1/2 x 8 1/4". Shpg. wt., 23 lbs. Net 49.95 PH-152WX

NO MONEY DOWN

62.95



WITH FREE DIAMOND STYLUS

LAFAYETTE Deluxe AUTOMATIC STEREO PHONOGRAPH

• 3 Speaker System • 4-Speed V-M Changer • Plays Both Stereo and Monaural Records

New Lafayette deluxe automatic stereophonic phonograph features the famous 4 speed V-M changer. Plays all speeds: 16 2/3, 33 1/3, 45 and 78 RPM. Plays all sizes: 7", 10" and 12" records. Has such features as 4-pole motor, automatic shut-off after last record, etc. Supplied with turnover cartridge. Separate volume controls adjust optimum balance for perfect stereo realism. Separate bass and treble controls permit tonal adjustment of both channels. Has 3 Alnico V PM speakers: 1 in main case and 1 in each wing. Wings may be left in position or can be detached from the sides and placed apart for individual stereo requirement. Tubes: 2-35C5, 1-12AX7, 1-50EH5, 1-35W4 rectifier. Attractive black gold branch leatherette case. Size: 20x15 1/2x9". Shpg. wt., 29 lbs. Net 62.95 PH-153WX

WITH FREE DIAMOND STYLUS

NO MONEY DOWN

39.75



LAFAYETTE AUTOMATIC MONAURAL PORTABLE PHONOGRAPH

• Alnico V PM Speaker • Plays 4 Standard Record Speeds • Complete With Crystal Turnover Cartridge

New, attractively styled automatic monaural portable phonograph featuring 4 speed, 16 2/3, 33 1/3, 45, 78 RPM. Consists of the latest famous British-made Monarch automatic record changer. High-quality Alnico V PM speaker. Uses heavy-duty 4-pole induction type motor for constant speed and minimum "wows". Automatically plays all speeds, and takes all record sizes—7", 10", 12" intermixed in any order. Plays 12" records with lid closed. Arm automatically returns to the rest position and motor shuts off after last record. Lightweight pickup arm has high output crystal turnover cartridge with sapphire styli. Controls: Tone, Off-On Volume. Durable and attractive cabinet covered in fine leatherette, black with white trim. For 110-120 volts, 60 cycles, A.C. Size 15 1/4 x 16 1/2 x 8 1/4". Shpg. wt., 20 lbs. Net 39.75 PH-154W

You get **BOTH** sapphire and diamond styli at no extra cost!

FREE DIAMOND NEEDLE OFFER EXPIRES FEB. 28, 1962

MONAURAL RECORD PLAYERS



13.95

"LEADER" 4-SPEED MANUAL

Plays up to 12" monaural records at 16 2/3, 33 1/3, 45 or 78 RPM. A single lever selects any speed. The lightweight pickup arm is equipped with a single all-purpose needle for all records. Has volume control with on-off switch. Fine quality Alnico 5 PM speaker. Attractive leatherette covered case. For 110-120 volts, 60 cycles. Size 11 3/4 x 10 1/2 x 5". Shpg. wt., 9 lbs. Net 13.95 PH-148W



18.45

STANDARD 4-SPEED MANUAL

With this portable phonograph you can play any record up to 12" size at 33 1/3, 45 or 78 rpm, or at the new "Talking Book" speed of 16 2/3 rpm. A single lever selects any speed. The lightweight pickup arm is equipped with a turnover cartridge with dual sapphire styli. Has both tone control and volume control with on-off switch.

Fine quality Alnico 5 PM speaker. Attractive 2-tone leatherette covered case. For 110-120 volts, 60 cps. A.C. Dimensions 14x11 3/4x6 1/4". Shpg. wt., 10 lbs. Net 18.45 PH-149W

With FREE Diamond Stylus!

OUR finest PORTABLE PHONO!

NO MONEY DOWN!

89.50

- FULLY AUTOMATIC GARRARD CHANGER
- TWO POWERFUL 10 WATT AMPLIFIERS
- SECOND SPEAKER EASILY DETACHED
- 3 SPEAKERS

Plays Both Stereo and Monaural!



9 Ft. Extension Cord

A complete portable and compact stereo phonograph in one convenient case. System uses the well-known Garrard High-Fi 4-speed stereo changer which features true intermix of 12" and 10" records in any order with instant selection of either automatic or full manual operation. Uses a stereo turnover cartridge to play all your records—whether monaural or stereo. Two powerful 10 watt amplifiers provide a frequency response of 50 to 12,000 cps. Controls included: Master Volume; Remote

speaker volume; Master treble; Master bass. Detachable front speaker cabinet houses a 6" x 9" speaker with 9 ft. extension cord. Main unit houses two speakers—one 6" x 9" woofer and one 4" tweeter. Phonograph has easy-grip handle on attractive smart-looking Pyrolylin covered case. Size: 23x16x9 1/4". Shpg. wt., 40 lbs. Available in choice of 2 attractive coverings. Net 89.50 PH-150WX Charcoal Silver Net 89.50 PH-151WX Tan

LAFAYETTE Exclusive 4-TRACK STEREO TAPE

By special arrangement with one of America's finest recording companies, Lafayette presents its own superbly recorded stereo tape. They're complete—about 45 minutes playing time on a 7" reel. Shpg. wt., 1 lb. per tape.

3.49



BIG SAVINGS

STRAUSS WALTZES IN HI-FI. Its a festival of Strauss' Viennese waltzes with the Vienna Festival Orchestra, Rudolph Langer conducting. Old favorites include Emperor Waltz, Gypsy Baron Overture, On the Beautiful Blue Danube, others. STOCK NO. RM-19.

DIXIE. The wonderful sound of Dixieland jazz played by the Empire City Six. Top hits include Limehouse Blues, Muskrat Ramble, Black and Blue, Wolverine, and others. STOCK NO. RM-22.

THE TOMMY DORSEY STORY. It's the great all-time hits of the fabulous Tommy Dorsey in the great Dorsey style. Top favorites include Boogie Woogie, Song of India, Marie, others. STOCK NO. RM-23.

DANCE TIME U.S.A. Memories are made of these great hits, set to dance time by Raymond Porter and The Sheridan Society Orchestra. The pulsating tunes include Somebody Loves Me, Birth of the Blues, Flying Home, and more. STOCK NO. RM-24.

DYORAK. Symphony No. 5 in E Minor, "From The New World." A vibrant performance of Dvorak's classical favorite, by the Prague Symphony Orchestra, conducted by Ladislav Kiras. STOCK NO. RM-70

CHA CHA CHA and MERENGUES. Pupi Campo's great band recreates a dozen authentic Cha-Chas and Merengues for your listening and dancing pleasure. Quiereme. Tea for Two Cha Cha, etc. STOCK NO. RM-71.

THE ROMANTIC THEMES OF TSCHAIKOVSKY. From the great pen of the master, music filled with melody and tenderness. The Rome Symphony Orchestra in excerpts from Capriccio Italien, Violin Concerto in D, and other Tschaikevsky favorites. STOCK NO. RM-72

BEETHOVEN. Symphony No. 6 in F Minor, "Pastoral." A magnificent interpretation of Beethoven's classic "Pastoral." Rudolph Langer conducts the Frankfurt Symphony Orchestra. STOCK NO. RM-73

MOONLIT MOODS. The best of American popular music, played in superbly sophisticated arrangements featuring the lush strings of Donatoni, Stardust, Star Eyes, How High the Moon, etc. STOCK NO. RM-74

FAVORITES FROM FAR AWAY. A collection of the most beloved songs from all over the world, played in beautiful arrangements by Mat Matthews and his orchestra. Dark Eyes, Lili Marlene, Greensleeves, and more. STOCK NO. RM-75

EVERYBODY LOVES A BAND. One of the great bands of Europe, the Royal Artillery Band, in a rousing Salute to America. Thrill to the sound of Anchors Aweigh, El Capitán, Stars and Stripes Forever, and many more. STOCK NO. RM-76

NEW! 4-TRACK FULL STEREO TAPE

Famous popular selections on 300-ft., 3" reels. 3 3/4 IPS, 4 selections per reel, 15 minutes playing time. Splicing labels, title tabs and instructions with each reel.

CONTINENTAL MUSIC • LATIN MUSIC

FAMOUS POPULAR SELECTIONS on 300 ft., 3" REELS

• MOOD MUSIC • SHOW TUNES



LAFAYETTE SPECIAL PRICE **1.69**

Majorca; Brasilia; Mexican Nights; Bygone Times. STOCK NO. RM-35.

Mi Cha Cha Cha; No Me Digas Que No; Manzanillo; Ay Manila. STOCK NO. RM-36.

Starlight Mambo; Silbando; Mambo at the Zenda; Ana Morena. STOCK NO. RM-37.

April in Paris; Mon Coeur est un Violin; The Continental; Monte Carlo Melody. STOCK NO. RM-38.

Old Black Magic; Sleepy Lagoon; I Gave My Heart; Petticoats of Portugal. STOCK NO. RM-40.

Baubles, Bangles and Beads; Two Faces in the Dark; A Certain Smile; Arriverderci Roma. STOCK NO. RM-41.

Spanish Fiesta; La Macarena; La Corrida; Andalucia. STOCK NO. RM-39.

Merry Widow Waltz; Three Coins in the Fountain; September Song; Gigi. STOCK NO. RM-42.

Bess, You is My Woman; Just for Once; Tammy; Que Sera, Sera. STOCK NO. RM-43.

Look Who's in Love; It's Not for Me to Say; I'll Never Stop Loving You; Sweet Sue, Just You. STOCK NO. RM-44.

Blue Waltz; Good Morning, Cindy; Tarantella; Terrible Infant. STOCK NO. RM-45.

Beer Garden Polka; Britta Polka; Petite Polka Parisienne; Amanda Polka. STOCK NO. RM-46.

Magician's Wedding Dinner Polka; Slap Happy; Paganini Polka; Bird Polka. STOCK NO. RM-47.

Look for the Silver Lining; A Fine Romance; Make Believe; Why Do I Love You. STOCK NO. RM-48.

With a Song in My Heart; Manhattan; It Might as Well Be Spring; This Can't Be Love. STOCK NO. RM-50.

Georgia on My Mind; Blue Orchids; Stardust; Two Sleepy People. STOCK NO. RM-51.

Around the World; Love Letters in the Sand; Gondoliers; Dinah. STOCK NO. RM-52.

You Belong to My Heart; Symphony; Twelfth Street Rag; Picnic. STOCK NO. RM-53.

You Made Me Love You; Happy Days are Here Again; Carolina Moon; Sunshine Serenade. STOCK NO. RM-54.

If You Knew Susie; Almost Like Being in Love; Over the Rainbow; Side by Side. STOCK NO. RM-55.

Crazy Feelin'; Take It Easy Boy; Jive After Five; Walking My Baby Back Home. STOCK NO. RM-56.

Lover Come Back to Me; Short Cut; Love Walked In; Ain't She Sweet. STOCK NO. RM-57.

YOUR ORDER RECEIVES PROMPT, EFFICIENT SERVICE AT LAFAYETTE

LAFAYETTE RADIO

ENGINEERED FOR
SUPREMACY



99⁵⁰

NO MONEY DOWN

Made in U.S.A.



"Let Your Own Ears be the Judge"

LAFAYETTE 50-WATT STEREO AMPLIFIER Model LA-250 A

*Impressive Performance... Handsome Styling
... Another Unbeatable Lafayette Value!*

The Stereo 250A... a completely new stereo high fidelity amplifier with a high quality of reproduction, remarkable versatility and new distinctive styling—worthy of a place in the finest stereo hi-fi music system. A full range of controls enables you to enjoy the utmost in listening pleasure in any situation. A unique "blend" control which provides continuously variable channel separation—from full monaural to full stereo—may be used to eliminate the exaggerated channel separation found in some stereo source material. Included is a clutch-type Volume Balance control for independent or simultaneous control of both channels, concentric Bass and Treble controls which provide independent tonal control of each channel and a 4-position switch which selects phono, tuner, auxiliary or tape head stereo inputs. Simple slide switches provide channel reversal and phase reversal—or you can reproduce either channel through both amplifiers. A loudness switch permits the volume balance control to function as a compensated loudness control. The LA-250A also features a 3rd channel output which may be used to feed a 3rd single channel amplifier and speaker to provide a wider sound spread, a Tape Output jack for recording purposes, plus dual terminations for 4, 8 or 16 ohm speakers. Advanced circuitry includes DC operated preamp and tone control tube filaments for hum-free operation, 6CW5/EL86 push-pull output tubes, individual bias and balance adjustments on each channel and a hum balance control.



Clutch-Type Volume-Balance Control — Provides precise effective means of controlling volume and balancing stereo channels.

**brehtaking performance
at a price only LAFAYETTE can offer.**



- 50 WATTS MONAURAL—25 WATTS EACH STEREO CHANNEL
- RESPONSE 15-40,000 CPS ± .5 DB (at normal listening level)
- UNIQUE "BLEND" CONTROL
- PREMIUM EL86 OUTPUT TUBES
- SEPARATE BASS & TREBLE CONTROLS
- CLUTCH-TYPE VOLUME-BALANCE CONTROL
- 3RD CHANNEL OUTPUT

ASSURANCE OF COMPONENT QUALITY

ONE YEAR PARTS GUARANTEE
All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.



Dual Preamplifier Section — Inputs have been provided for every stereo-monaural function.

SPECIFICATIONS:
POWER OUTPUT & DISTORTION: 50 watts—25 per channel ± 1 db at less than 1% Total Harmonic Distortion at 1 KC. Less than 0.25% Total Harmonic Distortion at 1 KC at normal listening level (1 watt); less than 0.5% 1M distortion at normal listening level. FREQUENCY RESPONSE: 15-40,000 cps ± 0.5 db at normal listening level. HUM & NOISE: 70 db below rated output at max. volume (high level inputs). SENSITIVITY: For full output high level inputs 0.5V; Mag. Phono 3.5 MV at 1 KC. CHANNEL SEPARATION: Greater than 55 db at 1 KC; greater than 45 db from 20-20,000 cps. IMPEDANCE: 4, 8 and 16 ohms per channel. POWER: 200 watts; 110-125V AC 50-60 cycles.
Attractive beige vinyl laminated steel case. Handsomely designed three color brass etched front panel. Sienna brown molded legs and matching knobs with polished brass inserts. Dimensions with legs and knobs, 14½x12¾x5½"H. Shpg. wt., 28 lbs.
LA 250AWX Net 99.50

McIntosh Professional Quality HI-FI EQUIPMENT



C-20 STEREO COMPENSATOR

The C-20 is a stereo preamplifier which provides full stereo flexibility while at the same time protecting the stereo investment in monophonic records. Provides listener's investment in monophonic records. Provides Fletcher-Munson compensation, continuously variable. Rumble filter and 2-position (9KC and 5KC) high frequency cutoff. 180° phase reversal control. Input sensitivity: High level—1.25 mv. high 6.25 mv; tape monitor Main—low 1.25 mv. high 6.25 mv; tape monitor Main—0.25V. Freq. response: ± 0.5 db 20 cycles to 20 KC. Distortion less than 0.2% at rated output. Outputs: Main—2.5V with rated input; tape—0.25V with rated input. Power requirements: 117VAC. 35 watts. A.C. Aux. outlets: 1 unswitched and 3 switched. Less case. Size: 14½x12x4¼"H. For 110-120V 50/60 cycle AC. Shpg. wt., 16 lbs.
Net 234.00
G-170WX
Model L-66M Mahogany Cabinet for C-20. Net 25.00
G-177WX



NEW! MCINTOSH MC-225 TWIN 25-WATT STEREO AMPLIFIER

The MC-225 twin stereo amplifier consists of two separate identical 25-watt power amplifiers mounted on a single chassis. Combined monophonic operation, 50 watts output. Frequency response: — 0, and + 0, — 2 db from 14 cycles to 30 Kc at full power output; output. Harmonic and I.M. less than 0.5% at full output. Hum and noise better than 90 db below rated output. A 25 volt and a 70.7 volt output are available for both stereo and monophonic operation. Input level of 0.5 stereo inputs. Tube complement: 1-12AX7, 2-12AU7, 2-12BH7 and 4-7591 output tubes. For 117 VAC, 50-60 cps. 39 lbs.
Net 198.00
G-341WX

H.H. SCOTT STEREOPHONIC COMPONENTS

NEW 299C 72 WATT STEREO AMPLIFIER



A superb unit designed to accommodate every existing signal source. Aluminum chassis and D.C. heated preamp filaments for low hum. Uses 4-7591 Output tubes and rectifier.
FRONT PANEL CONTROLS: Input selector; 6 Mike, NAB tape head, RIAA record equalization, tuner tuner, Stereo Selector Balance A, B, Monophonic Records; Stereo; Reverse Stereo; Channel A, B; Tone Controls; Channels A, B, Stereo Balance; Derived Center channel Level Control; Loudness/Phase-reversal; Pickup Selector; Tape Monitor; Scratch and rumble filters; Phase reverse; Loudness Compensation. Low impedance Stereo headphone output on front panel; High Impedance Stereo headphone output on rear. Dimensions in accessory case 15½x11½x4½"H. Shpg. wt., 28 lbs.
G-635WX (less case) Net 224.95
Leather finish steel case for above. Net 13.95
G-147W

WIDE-BAND FM MULTIPLEX TUNER



Moderately priced, this outstanding FM-multiplex stereo tuner provides the performance you can obtain only from WIDE-BAND design. Its wide-band design gives unparalleled frequency and dynamic ranges with low distortion and noise, even with weak signals. The 350 uses silver plated front end and is absolutely drift free without AFC. Main FM carrier circuit features 150 KC IF bandpass and 2 full stages of limiting. Usable (IHF) sensitivity 2.5 microvolts, low hum and noise and sensitivity 1 microvolt for 20db quieting using balanced 72 ohm antenna Stereo outputs to amplifier and tape recorder. Dimensions in accessory case: 15½x11½x4½"H. Shpg. wt., 10 lbs. Net 199.95
G-630WX (less case) Shpg. wt., 10 lbs. Net 199.95
G-147W Leather Finish steel case for 350 Net 13.95

MARANTZ QUALITY STEREO COMPONENTS



MODEL 7C STEREO CONSOLE PREAMPLIFIER

New self-powered stereo preamplifier combines Marantz's high quality of construction with complete versatility and ease of operation. Front panel features 8-position selector switch, 5 position mode switch, volume balance, 4 independent bass and treble controls, Record Equalizer, Tape Playback on Monitor, High Filter, Rumble filter and power switch. Rear Controls feature: Output Level-sets, 3 pairs of outputs, Tape-head Equalizer Adjustments, 9 Pairs of inputs, 6AC convenience outlets and system grounding point. Frequency Response: 1/2 db 20-20,000 cps. 1M Distortion: 0.1%. Total Noise: In 20-20,000 cps audio range, 80 db below 10 mv. phono input with RIAA. Tubes: 6-ECC83/12AX7. Size: 14½x11½x4½"D. Panel: 15½x11½x4½"H. For 110-120V 50/60 cycle AC. Shpg. wt., 16 lbs.
G-251WX Marantz Model 7C less cabinet Net 264.00
WOOD CABINET FOR ABOVE. Specify Mahogany, Blonde, Walnut.
G-253W Shpg. wt., 4 lbs. Net 24.00



NEW MODEL 8B DUAL 35-WATT STEREOPOWER AMPLIFIER

A professional instrument in every respect. Built-in test meters and bias adjustment assure optimum performance. 35 watts Power output per channel (70-watts peak). "Ultra Linear" operation, 18 watts of triode operation possible by altering 2 connections. Response: 0.1 db from 20-20,000 cps at 35 watts. Distortion: harmonic, less than 0.1%, IM, less than 0.5%. Hum: — 90 db. Input sensitivity 1.3V Heavy duty components throughout. Output impedance: 4, 8 and 16 ohms. Tubes: 2-6BH6, 2-6CH7, 4-EL34/6CA7. Overall size: 13½x11½x4½"D. For 117V, 60 cps. AC. Shpg. wt., 57 lbs.
G-259WX Marantz Model 8B less cabinet Net 249.00
Model 8G Gold Finish Perforated Snap-on Grille for above. Net 9.00
G-257W Shpg. wt., 1 lb.

THE FISHER



NEW X-202-B 75-WATT STEREO AMPLIFIER CONTROL AMPLIFIER

High power and versatility have been incorporated in the X-202-B compact amplifier system. Features exclusive Fisher tape monitor + playback with internal switching; front panel controls: 16 inputs and 10 outputs (3 speaker outputs). Facilities for center channel and low filters plus built-in subsonic filter cut noise. 1/2% harmonic, 1% intermod, at 70 watts RMS. Overall response (at 1 watt) 20-20,000 cps ± 1 db; Hum and noise — 66 (low level) — 80 db (high level), damping deep.
G-401WX Less cabinet, Shpg. wt., 30 lbs. Net 249.50
G-109W MC-2 Metal Cabinet, Shpg. wt., 9 lbs. Net 15.95
G-101W Oiled Walnut Wood Cabinet, Shpg. wt., 6 lbs. Net 25.95

SHERWOOD



S-5000 II 72 WATT STEREO AMPLIFIER

Featuring the same circuits and controls of the highly-rated S-5000. Features dual loudness, bass and treble controls; one knob varies both channels simultaneously. Other features include 12 db/octave scratch and rumble filters, which operate on all channels, presence-rise switch, 1.8 mv phono sensitivity, DC filaments and indicator lights to indicate mode of operation used. SPECIFICATIONS: POWER: 36 watts each channel. 72 watts on monaural. RESPONSE: 20-20,000 cps ± 1/2 db at full power. INPUTS: Phono (RIAA), tape head (NARTB), 6 high level. NOISE: — 80 db (— 60 db for phono). OUTPUTS: Dual 4, 8, 16 ohms, dual cathode followers for tape recorder. 12 Tubes: 4-7591, 6-12AX7, 2-silicon rectifiers. POWER CONSUMPTION: 30 watts, 110-120 volts AC, 50-60 cycles. 14x14x4". Shpg. wt., 30 lbs.
G-296WX Less Case Net 199.50
Brown Flexitone Case for Model S-5000 II. Net 5.00
G-283W Shpg. wt., 8 lbs.

A COMPLETE STEREO SYSTEM BASED ON THE SUPERB LA-250A

breathtaking performance at a price only LAFAYETTE can offer.

THE SMART WAY TO BUY HI-FI!

Lafayette's Most Popular Stereo Phono System



LAFAYETTE LA-250A
50-WATT STEREO AMPLIFIER



GLASER-STEERS GS-77

CHOICE OF CARTRIDGE

Audio Empire S108	Pickering 380C
Shure M7D	GE VR 1000-7



2 LAFAYETTE SK-58
FREE EDGE 12" COAXIAL SPEAKERS



LAFAYETTE
WOOD BASE

ALTERNATE
RECORD
CHANGER



GARRARD 474



ALTERNATE
SPEAKER SYSTEM



LAFAYETTE SK-100
"TRIHELIX" SPEAKERS




CRITERION
EQUIPMENT CABINET
AVAILABLE FOR \$84.50

"LISTEN AT HOME GUARANTEE"

Prove to yourself in your own living room, that the hi-fi system you select sounds as good at home as it does in our showroom.

LISTEN at HOME and BE SURE!

With Lafayette's Famous 30 Day FREE Trial if not completely satisfied with your purchase once you get it home, you can return it within 30 days and get your Full Purchase Price returned to you, less only transportation charges.



(OPTIONAL)
2 LAFAYETTE ELIPTOFLEX SERIES
BOOKSHELF ENCLOSURES

LAFAYETTE MATCHED STEREO SYSTEMS

*Make Certain To Indicate Your Choice of either Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Diamond Needle Cartridge.

System No.	Amplifier	Changer	Cart *	Base†	Speaker Cabinet**	Shpg. Wt.	Net	
LS-251WX	LA-250A	GS-77	CHOICE OF Audio Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	Model A	2 ea SK-58	67 lbs.	199.50	
LS-252WX	LA-250A	AT-6			2 ea SK-58	67 lbs.	199.50	
LS-253WX	LA-250A	GS-77			2 ea SK-58	2 ea Eliptoflex	143 lbs.	265.50
LS-254WX	LA-250A	AT-6			2 ea SK-58	2 ea Eliptoflex	143 lbs.	265.50
LS-255WX	LA-250A	GS-77			2 ea SK-180	67 lbs.	203.50	
LS-256WX	LA-250A	AT-6			2 ea SK-180	67 lbs.	203.50	
LS-257WX	LA-250A	GS-77			2 ea SK-180	2 ea Eliptoflex	143 lbs.	269.50
LS-258WX	LA-250A	AT-6			2 ea SK-180	2 ea Eliptoflex	143 lbs.	269.50
LS-259WX	LA-250A	GS-77			2 ea SK-210	70 lbs.	233.50	
LS-260WX	LA-250A	AT-6			2 ea SK-210	70 lbs.	233.50	
LS-261WX	LA-250A	GS-77			2 ea SK-210	2 ea Eliptoflex	146 lbs.	299.50
LS-262WX	LA-250A	AT-6			2 ea SK-210	2 ea Eliptoflex	146 lbs.	299.50
LS-263WX	LA-250A	Model A			2 ea SK-210	70 lbs.	219.50	
LS-264WX	LA-250A	Model A			2 ea SK-210	2 ea Eliptoflex	146 lbs.	299.50

Any of above systems with addition of Lafayette LT-700 WX Multiplex Stereo Tuner (described on other pages) add \$114.50 to system price. When ordering add the letter T to the prefix.
Example: LS-251WX system with LT-700WX tuner is ordered as LST-251WX.
Eliptoflex—12" shelf type speaker Enclosure.
†—Specify Mahogany, Walnut or Blonde.
**—Specify Walnut, Oiled Walnut, Mahogany or Blonde.
AT-6—Garrard 4-Speed Record Changer. Model A—Garrard 4-Speed Record Changer.

SHURE M3D CARTRIDGE

Any of above systems with Shure M3D Diamond Stereo Cartridge (described on another page), in place of choice of above 4 cartridges, add 18.50 to system price.

MATCHED COMPONENTS

Lafayette LA-250A 50-Watt Stereo Amplifier	99.50
Glaser-Steers GS-77 4-Speed Record Changer	59.50
Lafayette Wood Changer Base	3.95
Audio Empire S108 Diamond Needle Stereo Cartridge	35.00
2-Lafayette SK-58 Famous Free Edge 12" Coaxial Speakers @ 29.50 Each	59.00
Regular Catalog Price	256.95

LAFAYETTE SYSTEM PRICE
You Save 57.45

199.50
NO MONEY DOWN

NEW LAFAYETTE CRITERION Hi-Fi CABINETRY....

decorate your home with music



Lafayette's Criterion Line — the standard of construction and design by which all others are judged.

The Criterion Stereo Furniture Ensemble

The Technical Know-How of Lafayette's Audio Engineers Combined with that of America's Finest Furniture Craftsman, bring to you the new Lafayette Criterion Line of Acoustically Correct Hi-Fi Furniture.


Now your high fidelity listening area can look as good as it sounds. Add the elegance, grace and timeless styling of this decorator inspired furniture grouping to your home music center, but lose nothing in performance. Painstaking acoustical design by Lafayette's audio engi-

neers provides the best possible relationship between equipment and furniture. The meticulous custom craftsmanship, rich, matched, natural wood veneers and custom hand-rubbed finishes of these fine cabinets are bound to please the most discerning taste.

THE CRITERION EQUIPMENT CABINET

Interior Dimensions each upper compartment

10" H
18 3/4" W
15 3/4" D



12 1/4" H
18 3/4" W
15 3/4" D

Interior Dimensions each lower compartment



84.50

NO MONEY DOWN

THE CRITERION ELIPTOFLEX SPEAKER CABINET

55.50
NO MONEY DOWN



The same graceful styling and fine construction as the CRITERION equipment cabinet, which it matches. Designed to accommodate any 12" speaker, this enclosure incorporates the inner construction and acoustic principles of the famous Lafayette "Eliptoflex" enclosure. A specially designed elliptical port with diffracting ring broadens frequency response. This results in natural smoothness and unequalled performance in the low ranges. Constructed of 3/4" lumber core woods with hand-rubbed natural wood veneers. Smartly styled with matching grille cloth, gold trim and tapered legs. Overall Dimensions: 32 1/2" H x 18" W x 16" D. Shpg. wt., 50 lbs.

CAB-140WX Walnut	Net 55.50
CAB-141WX Oiled Walnut	Net 55.50
CAB-142WX Mahogany	Net 55.50

NOW FROM LAFAYETTE
THE REMARKABLE

KT-650 Criterion[™] FM TUNER KIT

NO MONEY DOWN
KT-650 in KIT FORM

54.50

LT-650 Factory
Wired & Tested

79.95



MADE
IN U.S.A.

- Low Noise Front End With Triode Grounded Grid Amplifier and Triode Mixer • Double Tuned Dual Limiters and Foster Seeley Discriminator
- Sensitivity 1.25 uv For 20 db of Quieting • Variable AFC Literally "Lock In" Stations • Frequency Response $\pm 1/2$ db 15-35,000 cps • Multiplex Output For Stereo FM • Easy-To-Build Printed Circuits • Electronic Bar Tuning Indicator Tube • Pre-Aligned IF and Discriminator Coils • 3 Gang Tuning Condenser • Virtually Distortionless Performance—Less than .15% Distortion at 100% Modulation.

MONEY-BACK GUARANTEE

Each Lafayette KIT is guaranteed to meet, or exceed, its published specifications for performance or your money is refunded in full. LAFAYETTE GUARANTEES YOU COMPLETE SATISFACTION.

ASSURANCE OF COMPONENT QUALITY

ONE YEAR PARTS GUARANTEE

All components in this unit are conservatively engineered to operate well within their performance capabilities. As an assurance of this quality, Lafayette guarantees all parts including tubes for one year.

LAFAYETTE LT-200
WIRED MULTIPLEX ADAPTER
WITH KT-650 TUNER KIT
BUY BOTH AND SAVE!

Made in U.S.A.
LT-200

PERFORMANCE
VALUE
COMBINATION!



NO
MONEY
DOWN

104.00

KT-650 KIT PLUS LT-200

Made For Each Other! Purchase your KT-650 tuner in combination with this new Lafayette LT-200 Multiplex Adapter and save \$5.00 off of their combined purchase price. You'll be completely equipped to receive the new FM stereo multiplex broadcasts. Supplied with HTA-14WX cables and instructions. Shpg. wt., 17 1/2 lbs. HTA-14WX KT-650 Kit plus LT-200 Net 104.00 HTA-15WX LT-650 Factory Wired plus LT-200 Net 129.45

* Lafayette supplies this multiplex adaptor fully wired and aligned rather than in kit form, due to alignment difficulties requiring a mpx generator for exact alignment.

READY FOR MULTIPLEX!

Lafayette engineers have succeeded in developing an instrument with performance and flexibility that equals and surpasses factory-wired or kit tuners many times its modest cost. The KT-650 incorporates every desirable FM Tuner feature. A Multiplex jack provides for addition of a Multiplex Adapter for FM Stereo Reception. Flywheel weighted tuning enables effortless station-to-station tuning. Pinpoint tuning accuracy by a special electronic bar tuning indicator tube. A variable AFC (Automatic Frequency Control) is featured—literally "locks in" the station and is adjustable for tuning weak stations adjacent to strong stations. The Tuner Level Control allows precise adjustment of the Tuner output level. Superb circuitry features a low noise front end with triode mixer plus double tuned dual limiters and wide band Foster-Seeley discriminator. Sensitivity is such that in many areas the only antenna needed will be a short piece of wire, except in remote locations. Plate follower

outputs permit using the tuner up to 50 feet from the amplifier. Time-saving printed circuit boards are utilized to make wiring errors almost nonexistent. IF and discriminator coils have been carefully factory prealigned—permits you to play the tuner as soon as assembled. The superbly styled low silhouette enclosure will do justice to any decor. Beige cover is set off by a Cream and Sienna Brown etched panel and knobs with contrasting Black Dial Face. Complete with cage, legs, interconnecting cables with plugs, indoor folded dipole antenna and alignment tool. Overall Dimensions: 14x5 1/2 x 11 1/2". For 117V, 50-60 cycle AC. Power consumption 40 watts. Shpg. wt., 13 1/2 lbs.


KT-650WX FM Tuner Kit Net 54.50
HTA-14WX Combination of KT-650 and LT-200 FM Multiplex Adapter. You Save 5.00 Net 104.00
LT-650WX Factory Wired & Tested Net 79.95
HTA-15WX Combination of LT-650 and LT-200 FM Multiplex Adapter. You Save 5.00 Net 129.45

FREE! LAFAYETTE FM STEREO MULTIPLEX BROCHURE
Lafayette has prepared an informative, fact-filled brochure describing FM stereo Multiplex Broadcasting. Write for your free copy of brochure BK-50, "Facts About FM Stereo Broadcasting."

COMPARE THESE SPECIFICATIONS:

Sensitivity: 1.25 microvolts for 20 db of quieting. Image Rejection: 66 db. AM Suppression: 48 db. Discriminator Linearity: 600 kc. Distortion and Noise: Better than 57 db below 1.5 volts at 100% modulation. Frequency Response: $\pm 1/2$ db from 15 to 35,000 cps with a standard 75 microsecond de-emphasis network. Audio Output: 1.75 volts at 75 KC deviation (100% modulation). Antenna Input: 300 ohm. Controls: Tuning; Level; AFC Control and Power Switch. Outputs: (2) Multiplex Adapter; Amplifier; Tube Complement: ECC85, 6BK7B, 6AL5, 2-7543, 2-6BA6, 6AV6, EM84 Electronic Bar Tuning Indicator Tube and a silicon diode rectifier.

EASY FLY-WHEEL TUNING—Smooth, effortless tuning from one station to another.



FRONT PANEL LEVEL CONTROL—Provides precise control of your tuner output level.

MULTIPLEX AND MAIN OUTPUTS—Plate follower main output allows connection of tuner up to 50 feet from amplifier. Multiplex output for FM stereo.

VARIABLE AFC—"Locks in" the station for positive drift free reception of both weak and strong signals.

The Most Flexible Tuner Ever Designed

LAFAYETTE STEREO-TUNER KT-500A

MADE IN U.S.A.

KT-500A

74.50

NO MONEY DOWN

IN KIT FORM

LT-50A

124.50

NO MONEY DOWN

COMPLETELY WIRED AND TESTED

KT-500 AM-FM
STEREO TUNER KIT
Combined with
NEW LT-200
WIRED MULTIPLEX
ADAPTER
BUY BOTH AND SAVE!



MADE IN U.S.A.



NO
MONEY
DOWN

KT-500

124.00

KT-500A KIT PLUS LT-200

With this outstanding new Lafayette LT-200 Multiplex adapter your KT-500A will be equipped to receive the new FM multiplex stereo broadcasts in addition to monaural AM-FM and simulcast stereo AM, FM. And, by purchasing both units together you save an additional \$5.00 off, their combined purchase price. Supplied with necessary cables and instructions. Shpg. wt., 22 lbs. HTA-12WX KT-500A Kit plus LT-200 Net 124.00 HTA-13WX LT-50 Factory Wired plus LT-200 Net 174.00

* Lafayette supplies this multiplex adaptor fully wired and aligned rather than in kit form, due to alignment difficulties requiring a mpx generator for exact alignment.

Use as a FM-AM Stereophonic Tuner for simulcast stereo or with a multiplex adapter for FM stereo reception



USE AS TWO INDIVIDUAL TUNERS
FM IN ONE ROOM - AM IN THE OTHER

- MULTIPLEX OUTPUT FOR NEW STEREO FM • TWO PRINTED CIRCUIT BOARDS AND IF'S PREALIGNED • FM AFC AND AFC DEFEAT • 17 TUBE PERFORMANCE—11 Tubes (4 dual-purpose) + Tuning Eye & Selenium Rectifier • ARMSTRONG CIRCUIT WITH DUAL LIMITERS AND FOSTER-SEELEY DISCRIMINATOR • 12 TUNED CIRCUITS AND DUAL CATHODE FOLLOWER OUTPUTS • EXTREME SENSITIVITY AND WIDE FREQUENCY RESPONSE

The KT-500A will receive simultaneous FM and AM stereo broadcasts or since the two sections are completely independent it may be utilized for normal FM or AM reception. The Tuner also provides an output for the new multiplex FM stereophonic reception. Apart from its unique flexibility, the KT-500A offers noise-free, drift-free, distortion-free performance the equal and in many instances superior to the highest priced tuners. Each FM & AM section is tuned with its own 3-gang tuning capacitor and is provided with individual cathode follower outputs. This means that long output cables can be used to connect tuner to amplifier or control center without fear of high frequency loss. Also, separate volume controls are provided for each channel so that when used for stereophonic reception, a proper balance between channels can be achieved. Convenient front panel switch changes from stereo to monaural use. Simplified accurate knife-edge tuning is provided by magic eye which operates independently on FM and AM. Automatic frequency control "locks in" FM signal permanently. Ferrite rod antenna with loading ring is supplied to bring in weak AM stations for quality reproduction.

Designed for easy assembly, the kit is built around two printed circuit boards and prealigned. IF's Insuring fast accurate construction even for the beginner. Beautifully styled, the KT-500A employs a cream and brushed brass front panel plus matching brown knobs with copper inserts set in a beige finished vinyl enclosure.

KT-500AWX Stereo Tuner Kit Net 74.50
HTA-12WX Combination of KT-500A and LT-200 Multiplex Adapter You Save 5.00 Net 124.00
LT-50AWX Same as KT-500AWX, completely wired and tested Net 124.50
HTA-13WX Combination of LT-50A and LT-200 Multiplex Adapter You Save 5.00 Net 174.00

ASSURANCE OF COMPONENT QUALITY

ONE YEAR PARTS GUARANTEE

All components in this unit are conservatively engineered to operate well within their performance capabilities. As an assurance of this quality, Lafayette guarantees all parts including tubes for one year.

"... this kit is excellent all the way around. It would be difficult to improve upon."
Robert Meier
Washington, D.C.

"Instructions were very good. Performance is wonderful. Best all around design..."
S. B. Heberlig
Glendora, New Jersey

SPECIFICATIONS

FM CIRCUIT: Armstrong, low noise front end with triode grounded grid amplifier and triode mixer. Double tuned dual limiters, Foster-Seeley discriminator, AFC and AFC defeat. AM CIRCUIT: Superhet with 3 stages AVC, 10kc whistle filter, ferrite antenna. DISTORTION: Under 1% harmonic on FM; under 1% on AM for up to 80% modulation. HUM LEVEL: 60 db below 100% modulation. SENSITIVITY: FM—full limiting on signals as low as 1 uv, 2 uv for 30 db quieting; AM Terminal Sensitivity 5 uv. SELECTIVITY: FM 200 kc bandwidth; 6 db down, AM 8kc BW; 6 db down. FREQUENCY RESPONSE: FM 20-20,000 cps $\pm 1/2$ db, AM 20-5,000 ± 3 db. IMAGE REJECTION: FM 40 db; AM 30 db. I. F. REJECTION: FM 70 db, AM 50 db. CONTROLS: 5 controls; FM VOL, AM VOL, FM Tuning, AM Tuning, and five position function selector switch. TUBES: 3-6BA6, 2-6AU6, 1 each 6BK7B, ECC85, 6AL5, 6BE6, 12AU7 and 6U5 tuning eye. Selenium rectifier. OUTPUT IMPEDANCE: Low impedances cathode follower. Output jacks for FM, AM or Stereo. ANTENNA INPUT: 300 ohms. Size 13 3/4 x 10 3/4 x 4 1/2" H. Shpg. wt., 18 lbs. Kit comes complete with all parts and metal cover, a step-by-step instruction manual, schematic and pictorial diagrams.

FOR FASTEST SERVICE USE LAFAYETTE'S CONVENIENT ORDER BLANK

Now! FROM THE
LAFAYETTE
high-fidelity
RESEARCH LABORATORIES

The ULTIMATE FM STEREO TUNER

THE New LAFAYETTE **Criterion™** LT-700 FM STEREO MULTIPLEX TUNER



MADE IN U.S.A.

124.50
NO MONEY DOWN

FREE! LAFAYETTE FM STEREO MULTIPLEX BROCHURE

Lafayette has prepared an informative, fact-filled brochure describing FM stereo Multiplex Broadcasting. Write for your free copy of brochure BK-50, "Facts About FM Stereo Broadcasting."

- Virtually Distortionless Performance — Less than 0.15% Distortion at 100% Modulation, Monaurally
- Low Noise Front End With Triode Grounded Grid Amplifier and Triode Mixer
- Double-Tuned Dual Limiters and Foster Sealey Discriminator
- Stereo Separation: 35 db at 400 cps.
- Frequency Response $\pm 1/2$ db 15-35,000 cps, Monaurally
- Variable AFC Literally "Locks In" Stations
- Sensitivity 1.25 μ v for 20 db of Quieting
- 3 Gang Tuning Condenser
- Electronic Bar Tuning Indicator

The LT-700 is another impressive example of Lafayette's engineering leadership. For here is a tuner that achieves a level of distortionless performance and flexibility that sets the standard for professional FM multiplex reception. Its superb circuitry features a low noise front end with triode mixer, double-tuned dual limiters and wide band Foster Sealey discriminator. Distortion has virtually been eliminated with less than 0.15% distortion at 100% modulation (monaurally). Sensitivity of the LT-700 is such that in many areas the only antenna needed will be a short piece of wire, except of course in remote locations. Plate follower outputs permit using the tuner up to 50 feet from the amplifier. Designed for maximum versatility, the LT-700 features a convenient front panel volume control for precise adjustment of tuner output level. In addition a variable AFC (automatic frequency control) is provided. Once properly tuned, the AFC literally "locks in" the station and is adjustable for tuning weak stations adjacent to strong stations. Pinpoint tuning accuracy is assured by a special electronic bar tuning indicator that indicates maximum closure at the point of best tuning. Multiplex operation is achieved by a simple front panel switch. This also activates a stereo light when the station tuned to starts broadcasting stereo. Every LT-700 is individually aligned and tested to meet or exceed Lafayette's specifications. Attractively styled with a cream and brushed brass front panel set in a beige finished vinyl enclosure. Size 13 $\frac{3}{4}$ "x10 $\frac{3}{4}$ "x4 $\frac{1}{2}$ "H. For 117V, 50-60 cycle AC. LT-700WX Shpg. wt., 16 lbs. Net 124.50

TECHNICAL SPECIFICATIONS

Sensitivity: 1.25 μ v for 20 db of quieting. Variable AFC. Harmonic Distortion: 0.15% at 1Kc 100% modulation. Signal-to-Noise Ratio: Better than 57 db. Freq. Response: $\pm 1/2$ db 15-35,000 cps monaurally. Image Rejection: —50db. Stereo Separation: Built-in MPX section provides 35db separation at 400 cps. Discriminator Linearity: 600 Kc. Audio output: 1.75v at 75 Kc deviation (100% modulation). Tubes: Simple manual switching for FM multiplex operation. Anode Follower for low impedance wide-band distortion-free output. Automatic FM stereo indicator light. 2—No. 47 Pilot Lights. Tubes: 12AX7, 6C4, 12BZ7, ECC85/6AQ8, 6BK7B, 2-6BA6, 2-7543, 6AL5, EZ-81 rectifier, 2 matched diodes plus EM-84 tuning eye.

Now! LAFAYETTE UNIVERSAL MULTIPLEX ADAPTER



• 35 DB Stereo Separation (at 400 cps)

Made in U.S.A.

Now Enjoy All The Quality & Dynamic Brilliance of Stereo Through Your FM Tuner

54.50 No Money Down

Here's the easiest, most inexpensive way for you to enjoy stereo—records, not tapes, but stereo with all the fidelity and convenience that only FM can provide. Add this exciting new method of stereo reproduction to your component High-Fidelity system with this brilliant new stereo multiplex adapter. Performs beautifully with virtually any late model, wide band tuner, equipped with a multiplex output jack and delivering a mpx output signal from 1.5 to 2 volts. Requires no special knowledge or tools to hook up—as simple and easy to connect as were your original components. Supplied with all necessary audio cables. All that's required is to merely plug the unit into your tuner, amplifier and AC outlet. Engineered for simplicity of operation, a selector switch conveniently located on the front panel provides for ON-OFF, Mono-FM and Stereo-FM. Individual pilot lights indicate when power is on and when adapter is operating stereophonically. Beautifully styled to match any decor in textured beige finish cover and smart brushed brass anodized aluminum front panel. TECHNICAL SPECIFICATIONS: Separation: (at 400 cps) 35db; Harmonic Distortion: Less than 1% from 50 to 15,000 cps; Frequency Response: ± 1 db 50-15,000 cps. Multiplex Input Signal: .15 volts to 2V; Gain: 15 db; Output Impedance: 8000 ohms; Hum: at 60 cps for 1 volt signal input better than 60db; Rejection to 67KC: at least 50db; Rejection to 38 KC: at least 40db. Four tubes (2 dual purpose) 12AX7, 6C4, 12BZ7, EZ80. Features notch filter for 38KC: low impedance plate follower output (for remote amplifier connection); matched diodes for optimum separation. Supplied with a special 15 inch low capacitance input cable for optimum separation. Measures 4 $\frac{1}{2}$ "x8 $\frac{1}{4}$ "x8 $\frac{1}{4}$ "D. For 110-120V, 60 cycle AC. Shpg. wt., 8 lbs. Net 54.50

★ COMPARE THESE ALL STAR FEATURES ★

- Superior Distortion & Stereo Separation Characteristics
- Self Powered
- Matches With Virtually All Recent Model Wide-Band Tuners Equipped With MPX Output Jacks
- Complete With Enclosure & All Necessary Connecting Cables

FM STEREOPHONIC MULTIPLEX ADAPTERS

H. H. SCOTT
MODEL 335

WIDE-BAND MULTIPLEX ADAPTER
Now owners of all H. H. Scott wide-band tuners, regardless of age or model, can enjoy multiplex reception by adding the Model 335 wide band multiplex adapter to their systems. Self-powered (all connections to the tuner are external), so FM tuner alignment is unaffected. The 335 can be switched out of your stereophonic system to allow stereo AM-FM reception with H. H. Scott stereo tuners 330, 331, 399. Controls: SELECTOR (OFF, Monophonic FM, Stereo with subcarrier noise filter, stereo without subcarrier noise filter) LEVEL; ADAPTOR DEFEAT; STEREO NOISE FILTER. Matches H. H. Scott tuners in height and styling. Dimensions in accessory case: 7 $\frac{1}{4}$ "x5 $\frac{1}{4}$ "x13"D. 105-125 V.A.C., 50-60 cycle, self-powered. Shpg. wt., 8 lbs. Uses H size case. Matching panel to LT-10 FM tuner kit available. G-626WX (less case) Net 109.95

Pilot
MODEL 200 AUTOMATIC MULTIPLEXER

• Self-Powered
• Indicator Light
• No Operating Controls

79.50 NO MONEY DOWN

The Pilot 200 multiplex adaptor is completely automatic. No controls are needed or used. When the tuned-to station is broadcasting stereo, the built-in indicator light goes on and the Multiplex automatically switches to stereo reception. All connections are external, made with jack cords simply plugged in. Will not affect reception of monaural FM. Completely self-powered. Contains three tubes plus one rectifier. Housed in an attractive black and brass enclosure (included) designed to match Pilot components. Measures 5Hx3Wx14"L. G-681 Shpg. wt., 4 $\frac{1}{2}$ lbs. Net 79.50 Pilot 100 semi-automatic Multiplexer w/enclosure Net 49.50 G-680 Shpg. wt., 2 $\frac{1}{4}$ lbs.

SHERWOOD
S3MX SELF-POWERED MULTIPLEX ADAPTER

NO MONEY DOWN **69.50**

Designed for use with many FM tuners—having either high or low multiplex signal output. For best performance a wideband FM tuner should be used with the S3MX. Unique features are 67 KC and hiss filters. Subcarrier sensitivity .01 to 2 volts. Audio output 2V @ $1/2\%$ distortion. Power switch disconnects adapter in "off" position. 4 tubes plus rectifier. Size: 5 $\frac{3}{4}$ "x10 $\frac{1}{2}$ "x4". For 110/120 VAC. G-301 Less Case Shpg. wt., 8 lbs. Net 69.50

MODEL A3MX MULTIPLEX ADAPTER (NOT ILLUSTRATED)

Similar to S3MX but less power supply, designed specifically for use within the chassis of Sherwood S-2200 and S-3000III. Can be used with other tuners as well. Less S3MX hiss filter but with 67KC filter (always on). 2 tubes. Shpg. wt., 5 lbs. Net 49.50 G-302

NEW MULTIPLEX RECEIVERS

harman kardon AWARD TA5000X
50 WATT AM/FM STEREO RECEIVER

A complete stereo control center consisting of a sensitive, distortion-free AM/FM Tuner with built-in FM multiplex facilities, 50-watt stereo amplifier (25-watts each channel) plus a versatile stereo preamplifier. All components have been engineered into a single compact unit only 13 $\frac{1}{2}$ inches deep—small enough to place on a bookshelf. The TA-5000X features a full range of controls for every stereo function including separate Bass and Treble controls for each channel plus Blend, Balance, Loudness and Function controls. Slide switches provide for Stereo Reverse, Equalization, Contour plus Hi-cut and Lo-cut filters. Front panel contains a Stereo Headphone Receptacle plus a front panel tuning meter allows precise visual tuning. Size: 16"wx10 $\frac{1}{4}$ "Hx13 $\frac{1}{2}$ "D. Shpg. wt., 40 lbs. Net 299.95 G-656WX Net 12.95 G-657WX CX-80 Metal Case Shpg. wt., 5 lbs. Net 12.95 G-658W WW-80 Walnut Case Shpg. wt., 5 lbs. Net 29.95

FISHER
UNIVERSAL MPX-100 STEREO MULTIPLEX ADAPTER

NO MONEY DOWN **109.50**

Completely self-contained and self powered, the new Fisher MPX-100 is designed to bring FCC approved multiplex reception to all Fisher tuners and receivers including other makes employing wide band design and containing a multiplex output. Unit is equipped with a special "Stereo Beacon" circuit, which automatically signals the moment the station tuned begins broadcasting in stereo. A standby position allows listening to monaural FM program material, at the same time enabling the "Stereo Beacon" to function. Other features include: Front panel Stereo Balance control provides easy adjustment for optimum balance; Selector Switch; separate AUX inputs. Supplied with 3 cables. Front panel is finished in brushed brass. Size: 12Dx4 $\frac{7}{8}$ "x4 $\frac{7}{8}$ "H. G-118WX Shpg. wt., 10 lbs. Net 109.50

NEW! FM MULTIPLEX ADAPTOR MODEL MA-2G

Many G.E. FM tuners are now equipped with an output jack wired to provide an external multiplex adapter with the electrical information necessary for stereophonic reception. The MA-2G is designed to operate in conjunction with such G.E. tuners to provide two stereophonic audio channels which may be connected to the inputs of a stereo amplifying system. Since this adapter is completely self-contained and self-powered, the only required connections to the existing audio system are those to the multiplex output of the tuner and to the separate inputs of the stereo amplifier system. Frequency response of the adapter is ± 3 db from 50 to 15,000 cycles. Hum and noise down 60 db. Mounting base is 10Lx2 $\frac{1}{4}$ "W, with mounting holes spaced 2 $\frac{1}{4}$ ". Clearance of "3" required for tubes and capacitor. G-336 Shpg. wt., 3 lbs. Net 39.15

NEW HARMAN KARDON MULTIPLEX ADAPTER MX700

59.95 NO MONEY DOWN

New self-powered FM multiplex adapter operates with all Harman Kardon tuners having multiplex outputs. Circuit has 2 stage subcarrier, main carrier amplifier followed by 19KC synchronous oscillator m-derived L-R filter, two section RC L + R filter, dual phase L-R detector and precision matrix. Crosstalk —40 db. Response ± 1 db at 15-15,000 cps. Size: 2 $\frac{1}{2}$ "x4 $\frac{9}{16}$ " deep. Shpg. wt., 4 $\frac{1}{2}$ lbs. Net 59.95 G-650 Metal Enclosure for MX700. Shpg. wt., 1 lb. Net 8.95 G-655

MX600 ADAPTER
Converts TA224, TA260 and TA230 into integrated multiplex receivers. Size: 7 $\frac{1}{4}$ "x1 $\frac{3}{4}$ "x3 $\frac{1}{2}$ ". G-651 Shpg. wt., 2 $\frac{1}{4}$ lbs. Not illustrated Net 49.95

Pilot 602M 30 WATT FM MULTIPLEX STEREO RECEIVER

249.50 NO MONEY DOWN

A sensitive FM Tuner, a Multiplexer, a 30-watt Stereo Amplifier (15-watts each channel) plus a versatile stereo preamplifier—all precision engineered into one compact component. Controls: FM Tuning, Master Volume, Stereo Balance, Input Selectors, Phono, Tape Monitor, Loudness and Separate Bass and Treble for each channel. Frequency Response: 20-20,000 cps. Hum and Noise: 80db below full output. Harmonic Distortion 1% at full power. FM tuner section features low noise triode RF amplifier, triode converter, 3 IF amplifier stages, wide band detector and achieves a sensitivity of 3 μ v IHFM standard. Size: 5 $\frac{1}{2}$ "Hx14 $\frac{1}{8}$ "Wx10 $\frac{1}{2}$ "D. For 105-120 volts 60 cycles AC. Complete with cover. Shpg. wt., 26 lbs. Net 249.50 G-682WX

LAFAYETTE ALL TRANSISTOR HI-FI STEREO COMPONENTS

LAFAYETTE 40-WATT ALL TRANSISTOR STEREO AMPLIFIER LA-440



99.50
NO MONEY DOWN

STUDY & COMPARE THESE SPECIFICATIONS

I.H.F.M. Music Power Output: 40 watts (20 watts per channel) based on 4-ohm load impedance. Frequency Response ± 0.5 db 20 to 20,000 cps measured according to IHFM standards. Intermodulation Distortion: 0.9% to 1 db below clipping 60 and 6,000 cps. Harmonic Distortion: 0.5% at 1 db below clipping. Hum and Noise: Completely inaudible at all playing levels. Phono Input: -72 db Tuner Input: -85 db. Output Impedance: May be used with 4, 8, 16 ohm loud-speakers. Power Requirements: 105-120 volts AC, 50-60 cps. 12 to 28 volts DC for battery operation.

- Dual Concentric Bass & Treble Controls • Brilliant Design & Performance • Frequency Response — ± 0.5 db 20 to 20,000 cps • Instantaneous Operation — No Warm-Up Required • Hum, Noise & Microphonics Virtually Eliminated • Place Anywhere — Does Not Require Ventilation as No Heat is Generated.

NEW!

- 20 Transistors plus
- 4 Germanium Diodes plus
- 3 Silicon Diodes plus
- 2 Thermistors



Made In U.S.A.

Now Lafayette applies space-age electronics to high-fidelity design to bring you this superb new 40-watt stereo amplifier (20-watts each channel). Utilizing the most advanced transistor circuitry, the LA-440 completely eliminates tubes and output transformers; substituting in their place a total of 29 solid state devices to provide an unmatched level of stereo high-fidelity performance. Here is an amplifier that: **GENERATES NO HEAT**—no need to worry about ventilation, you can place it anywhere and current drain is so low, it will operate efficiently not only at 110 V AC, but even from 12 to 28 volt batteries. **REQUIRES A MINIMUM OF MAINTENANCE**—since transistors last indefinitely maintenance problems are virtually a thing of the past and performance will not deteriorate, **VIRTUALLY ELIMINATES HUM, NOISE AND MICROPHONICS**—performance can best be described as transparent, the only sound you hear is that of the music. **PRO-**

VIDES INSTANTANEOUS OPERATION, no need to wait for warm-up, the LA-440 plays as soon as it is turned on. Controls are provided for every possible stereo, hi-fi function: Front panel contains dual concentric Bass and Treble controls, Volume control, Balance control and Selector switch for Phono, Tuner, Tape, Aux 1 and Aux 2 with corresponding inputs provided on the rear panel. In addition, slide switches are provided for Mono A—Stereo—Mono B, Loudness, Scratch Filter and Rumble Filter. Rear panel contains 2—switched AC outlets plus 3 tape outputs for recording stereo or mono (Tape A, Tape B, A & B). Superbly styled, the LA-440 measures only 3Hx10 1/4 Wx8 1/2 D. and is finished in a brushed gold front panel, gold finished aluminum knobs and is complete with matching enclosure. Shpg. wt., 10 lbs. **LA-440WX**

Net 99.50

NEW! LAFAYETTE ALL-TRANSISTOR FM-MULTIPLEX STEREO TUNER WITH BUILT IN MULTIPLEX

- 20 Transistors — 9 Diodes Includes 8 Transistor Automatic Multiplex Section • Built-In Tuning Meter • Frequency Response 20-20,000 Cps ± 1 db • Automatic Frequency Control • Interstation Muting • Unmatched Reception of FM and FM Stereo Broadcasts

Years of Trouble free listening are yours with the Lafayette LT-300 all transistor multiplex tuner. A perfect match for the LA-440 amplifier both in appearance and performance. The tuner eliminates hum, heat or microphonics, problems associated with tube units. Super powered transistor circuit provides dazzling reception of FM and Stereophonic FM Multiplex Broadcasts. Wide band design with AFC assures greater selectivity, high sensitivity and an amazingly low signal-to-noise ratio. The built-in multiplex section is completely automatic—no controls to set. Synchronous—gate separation


of channels from composite signal reproduces all the audio information with low distortion. Advanced design keeps circuit exceptionally stable with no adjustments needed. Deluxe signal-strength meter indicates perfect reception at all times. Interstation muting avoids annoying FM hiss and pops found between stations. Power requirements are very small, consumes only 4 watts at 105-120V AC. Brushed brass panel, tan covers—matches companion amplifier LA-440. Size: 3Hx10 1/4 Wx 8 1/2 D. Shpg. wt., 8 lbs. **LT-300WX**

Runs Cool
Place It Anywhere!

Built-In
Tuning
Meter

149.95

Regularly 209.95
NO MONEY DOWN




SPECIFICATIONS:

Sensitivity: 1.8 microvolts for 20db quieting. Selectivity (IF bandwidth) 270 KC at -6 db points. Discriminator Peak-to-Peak separation 1 megacycles. Noise level: 66db below 100% modulation. Antenna Input Impedance 300 ohms.

Made in U.S.A.

40-WATT ALL TRANSISTOR LA-440 AMPLIFIER IN MATCHED STEREO SYSTEMS



MADE IN U.S.A.



194.50
NO MONEY DOWN



LAFAYETTE SK-58 12" COAXIAL SPEAKERS

LAFAYETTE 40-WATT ALL TRANSISTOR AMPLIFIER IN MATCHED STEREO SYSTEMS

Lafayette LA-440 40-Watt All-Transistor Stereo Amp.	99.50
Lesla CD 2/21 4-Speed Record Changer	44.50
Wood Base for Changer (Specify Walnut, Mahog. or Blonde)	4.75
Audio Empire S108 Diamond Needle Cartridge	35.00
2-Lafayette SK-58 Free Edge 12 Coaxial Speaker @ 29.50 each	59.00
LAFAYETTE SYSTEM PRICE	194.50
YOU SAVE 48.25	REGULAR CATALOG PRICE 242.75

System No.	Amplifier	Changer	Cart*	Base	Speaker	Speaker Cabinet**	Shpg. Wt. Lbs.
LS-441WX	LA-440	Lesla CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-58	48	194.50
LS-442WX	LA-440	Garrard Autoslim		+	2 ea. SK-58	48	194.50
LS-443WX	LA-440	Lesla CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-58	96	260.50
LS-444WX	LA-440	Garrard Autoslim		+	2 ea. SK-58	96	260.50
LS-445WX	LA-440	Lesla CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-180	45	198.50
LS-446WX	LA-440	Garrard Autoslim		+	2 ea. SK-180	45	198.50
LS-447WX	LA-440	Lesla CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-180	93	264.50
LS-448WX	LA-440	Garrard Autoslim		+	2 ea. SK-180	93	264.50

Any of above systems with addition of Lafayette LT-300 All-Transistor Multiplex Stereo Tuner (described above), specify System Stock No. plus LT-300 Tuner and add 134.95 to system price.

* Be Sure To Specify Choice of Empire S108, Pickering 380C, Shure M7D or GE-VR1000-7 Cartridge.

LAFAYETTE 40-WATT ALL-TRANSISTOR TUNER AMPLIFIER RECEIVER SYSTEM

LA-440 All-Transistor 40-Watt Amplifier	99.50
LT-300 Transistor FM Multiplex Tuner	149.95
Walnut Enclosure	19.50
Catalog Price	268.95

Lafayette Complete Receiver Price **SPECIAL 259.45**

COMPACT SPACE SAVING COMBINATION OF ULTRA-MODERN DESIGN

Space age electronics has developed this compact system. Small size and no heat generation enable this smart looking ensemble to be placed anywhere in your home. The all-transistor LA-440 amplifier and LT-300 tuner complement each other perfectly for outstanding performance of musical material via records, tape or




YOU SAVE 9.50

MADE IN U.S.A.

FM stereophonic multiplex programs. A beautifully finished walnut cabinet completely encloses the top and sides of the units giving them a "custom built" look. Front panels of brushed brass with black knobs and white switches.

LA-445WX Net 259.45

NEW! OMEGA ALL TRANSISTOR 60 WATT STEREO AMPLIFIER



249.00
NO MONEY DOWN

Made in U.S.A.

- 31 Transistors
- Advanced "Quadra-Power Circuit"
- Flat Frequency Range Beyond Audibility
- Cool Operation
- Full Complement of Stereo Controls
- Unconditional 2-Year Guarantee

SPECIFICATIONS:

Controls: Master Bass and Treble; Independent bass and treble; Mode, Volume Balance, Blend, Loudness; Scratch filter, rumble filter, phase switch; Tape Monitor; 5-position selector switch; and Cartridge output compensator. Frequency response 18-20,000 cps ± 0.3 db at full output. Harmonic and IM distortion: less than 1%; hum and noise: 75 db below full output. Power output 30-watts (IHFM Music Rating) per channel Stereo — 60 watts monaural. 31 transistors, 4 diodes, 1 zener diode, 2 silicon rectifiers.

For the first time an all-transistor 60-watt stereo amplifier with the performance of the finest tube equipment plus all the big listening and maintenance advantages of transistors. Exclusive "Quadra-Power Circuit" employs four power transistors per channel with uniform power dissipation and powerful linear response extending the frequency range to well beyond normal hearing. Since transistors are non-microphonic and there isn't any tube heater hum, there is a wonderfully clear tone to the sound. The Omega provides master bass and treble controls which allow a simple simultaneous balance adjustment of both channels. Another advanced feature is the exclusive cartridge output compensator which permits adjusting the amplifier to the speaker output voltage of your ceramic or magnetic pickup cartridge. Thus all front panel controls operate over their optimum range regardless of the cartridge output level. Trouble free transistor circuit is unconditionally guaranteed for two years. Modern styling is at home in any decor. Only 3H x 15 1/2 W x 9 D. For 117 VAC/60 cycles. Shpg. wt., 12 lbs. **G-685WX**

Net 249.00

AMAZING LAFAYETTE VALUE & PERFORMANCE

MODEL LT-80A FM TUNER



READY FOR MULTIPLEX!

ONLY **49⁵⁰**

A LAFAYETTE SPECIAL VALUE!

COMPARE FEATURE FOR FEATURE WITH THE MOST EXPENSIVE TUNERS

Remarkable . . . Quality, performance and styling that is in every respect the equal and in many instances superior to tuners priced far above the modest cost of this instrument. Designed and constructed of the finest components, with jewel like precision (each unit is hand wired) in order to insure that each tuner will maintain its excellence year after year with a minimum of maintenance. Engineered to provide maximum FM versatility, the LT-80A is provided with a multiplex output, designed to accept a stereo FM multiplex adapter. Flywheel action tuning control. Tube complement consists of 2-6AQ8, 2-6BA6, 2-6AU6, 1 each 6AL5 and 6X4. Handsome low silhouette enclosure will do justice to any decor. Beautifully finished in gold and white with contrasting black dial face. Complete with cage and legs. Dimensions: 11³/₄"x8¹/₂"x4¹/₂".
 LT-80A FM Stereo Tuner . . . Net 49.50
 HTA-11WX Combination of LT-80A and LT-200 FM Multiplex Adapter. . . You Save 5.00
 Net 99.00

STEREO COMBINATION! LT-80A FM TUNER WITH LT-200 MULTIPLEX ADAPTER



You Save **5.00**
99.00

Save by purchasing your LT-80A Tuner together with Lafayette's exciting new LT-200 Multiplex Adapter and be fully equipped to receive the new stereo FM multiplex broadcasts.
 HTA-11WX . . . Net 99.00



PIN-POINT TUNING ACCURACY
 is provided by this precision tuning meter; evaluates relative strength of the incoming signal . . . invaluable when tuning weak stations.

- ARMSTRONG CIRCUIT FOSTER-SEELEY DISCRIMINATOR AND DUAL TUNED LIMITERS • AFC • AFC DEFEAT • EXTREMELY SENSITIVE—1.5 UV FOR 20 DB QUIETING • 10-TUBE PERFORMANCE—8 TUBES (2-DUAL PURPOSE) • 20-20,000 CYCLES ± 1/2 DB • SUPERB LOW SILHOUETTE STYLING • 3 GANG TUNING CONDENSER • TUNED GROUNDED GRID RF STAGE

NOW! LAFAYETTE LA-55 15 WATT MONAURAL AMPLIFIER



44⁵⁰

NO MONEY DOWN
 AN UNBEATABLE VALUE!

The most extraordinary Hi-Fi value ever offered

- Frequency Response: 15-30,000 CPS
- Hum 65 Db Below Rated Output
- Rumble Filter
- Power Output 15 Watts
- Harmonic Distortion Less Than .3%
- EL84 Output Tubes in Push-Pull
- Sensitivity: 3 MV Mag. Phono
- 5 Input Channels
- Beautifully Styled

Outstanding Performance and Engineering + Beautiful Styling + Unbeatable Price—add up to make the Lafayette LA-55 truly the finest Hi-Fi monaural amplifier value today . . . Beautifully styled in gold and white, the LA-55 easily adapts to any room decor. Perfect for that music system in your living room, finished basement, store or office. Ruggedly constructed, this fully integrated amplifier-preamplifier employs premium quality EL84 tubes in push-pull and advanced circuitry for faithful reproduction of all monophonic sources . . . perfect for use as a second amplifier for stereo or for starting out monophonically and adding stereo at a later date. Engineered to include every practical feature . . . a worthwhile contribution to hi-fi reproduction.

sponse 15-30,000 cps ± 1 db (at normal listening level); Sensitivity: For full power, High level inputs 0.5v. Mag. phono 3 mv. Hum and Noise: Volume control at max. High level inputs 65 db below rated output. Mag-Phono 55 db below rated output; Harmonic Distortion less than .3%. Inputs: Total 5—Aux, Tuner, Mag. Phono, Crystal Phono, Tape Head. Outputs: Tape Out, 4, 8 and 16 ohm speaker terminals; Tubes: Total of 5 plus rectifier—2-EL84, 1-6BL8, 1-6AV6, 1-12AX7, and 1-6CA4/WZ81. Controls: Monitor/On-Off; Volume/Power On-Off; Bass; Treble; Rumble Filter. Hum balance control. Selector: 4-position, Aux, Tuner, Phono, Tape Head. Complete with removable case and legs. AC receptacle on rear of chassis. Dimensions: 13³/₄"x4¹/₂"x4¹/₂". Knobs extend 3/8" in front of panel. Shpg. wt., 20 lbs.
 LA-55WX . . . Net 44.50

LAFAYETTE SUPER-VALUE HIGH-FIDELITY PHONO SYSTEM

PLAY STEREO & MONAURAL RECORDS MONAURALLY, NOW — ADD COMPLETE STEREO LATER. This economical high-fidelity system is the performance value of the year. Designed for ruggedness as well as beauty, these components will satisfy even the most critical music listener.

COMPONENTS

LAFAYETTE LA-55 15 Watt Complete Amplifier	44.50
LESA CD 2/21 4-Speed Record Changer	44.50
WOOD BASE FOR CHANGER (Specify Walnut, Mahog. or Blonde)	4.75
AUDIO EMPIRE S108 Diamond Needle Cartridge	35.00
LAFAYETTE SK-128 Full Range 8" Bi-axial Speaker	19.50
Regular Catalog Price	148.25

LAFAYETTE SYSTEM PRICE **109⁵⁰** YOU SAVE **38.75**

LAFAYETTE 15 WATT MATCHED MONAURAL SYSTEMS

*Make certain to indicate your choice of either Audio Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7 Diamond Needle Stereo Cartridge.

System	Amplifier	Changer	Cartridge*	Base†	Speaker	Spkr. Cabinet	Shpg. Wt.	Net
LS-51WX	LA-55	Lesca CD2/21	Your Choice of	Lesca†	SK-128	—	39 lbs.	109.50
LS-52WX	LA-55	Garrard Autoslim	Empire S108.	Laft†	SK-128	—	39 lbs.	109.50
LS-53WX	LA-55	Lesca CD2/21	Pickering 380C.	Lesca†	SK-128	Miniduct†	62 lbs.	132.00
LS-54WX	LA-55	Garrard Autoslim	Shure M7D or	Laft†	SK-128	Miniduct†	62 lbs.	132.00
LS-55WX	LA-55	Lesca CD2/21	GE VR-1000-7	Lesca†	SK-58	—	45 lbs.	119.50
LS-56WX	LA-55	Garrard Autoslim	—	Laft†	SK-58	—	45 lbs.	119.50
LS-57WX	LA-55	Lesca CD2/21	—	Lesca†	SK-58	Eliptoflex	69 lbs.	154.50
LS-58WX	LA-55	Garrard Autoslim	—	Laft†	SK-58	Eliptoflex	69 lbs.	154.50

Lafayette LT-80A FM Tuner with any system above, add 49.50 to Net price. To order, specify system No. plus LT-80A. Autoslim—Garrard 4-Speed Record Changer. Miniduct—Shelf Speaker Enclosure for 8" Speaker. Eliptoflex—Shelf Speaker Enclosure for 12" Speaker—Specify Walnut, Oiled Walnut, Mahogany or Blonde. †—Specify Mahogany, Walnut or Blonde.



FAMOUS H. H. SCOTT 299B 50-WATT STEREO AMPLIFIER



SAVE **60.45** at LAFAYETTE'S

Low, Low PRICE

Regularly 209.95
149⁵⁰
 NO MONEY DOWN

For The First Time At This Price!

QUANTITIES LIMITED
 Check The Specs — Check The Name — Now Check The Price and you'll know why we feel this is the Hi-Fi buy of the year.

Famous for its performance, thousands purchased this sought after stereo amplifier for 209.95. Now you can have this same amplifier for your stereo system and save over \$60. The 299B is rated at 50 watts and includes two complete channels with dual preamps and 25-watt power sections. Offers complete stereo facilities — a third channel output is provided for three channel stereo. Controls include: Master Function Selector; separate Bass and Treble controls for each channel; Balance control; Loudness control; Rumble and Scratch filters; Phase Reversal switch and Input Selector. Stereo Tape Recorder facilities provided for recorder output, playback

input plus a front panel monitor switch. Frequency Response is flat from 20 to 30,000 cps. Hum level is better than 80db below maximum output. Harmonic Distortion is less than 0.8%. The low level stereophonic cartridge input has a 3 millivolt sensitivity for accommodating stereo cartridges with very low output. 4, 8, and 16-ohm speaker taps are furnished for each channel. For 105-125 volts, 50-60 cycle operation. Size including optional accessory case: 15¹/₄"x12¹/₂"x4¹/₂".
 G-135WX Shpg. wt., 25 lbs. Net 149.50
 Accessory Case for Scott 299B. Shpg. wt., 1 lb. G-641W Net 12.95

UNPRECEDENTED STEREO PERFORMANCE VALUE! A COMPLETE MATCHED STEREO SYSTEM FEATURING THE H. H. SCOTT 299B



Lafayette SYSTEM PRICE

257.10
 YOU SAVE 49.85



CHOICE OF CARTRIDGE
 S108 380-C M7D

OPTIONAL LAFAYETTE ELIPTOFLEX BOOKSHELF ENCLOSURES



COMPONENTS

H. H. SCOTT 299B 50-WATT STEREO AMPLIFIER	149.50
GARRARD RC-88 Record Changer	59.50
BASE FOR RC-88 (Specify Finish)	3.95
AUDIO EMPIRE S108 Diamond Needle STEREO Cartridge	35.00
2-LAFAYETTE FAMOUS SK-58 Free Edge 12" COAXIAL SPEAKERS @ 29.50 each	59.00
Regular Catalog Price	308.95

Complete System as above with choice of Audio Empire S108, Pickering 380C or Shure M7D Stereo Cartridges. HS-736WX Shpg. wt., 65 lbs. Net 257.10
 Same as HS-736WX above, plus 2-Lafayette Eliptoflex Series Bookshelf Enclosures (Specify finish). HS-737WX Shpg. wt., 140 lbs. Net 323.10
 Complete system essentially the same as HS-736WX, but with the Garrard Model A Automatic Turntable. HS-738WX Shpg. wt., 67 lbs. Net 272.20
 Same as HS-738WX above, plus 2-Lafayette Eliptoflex Series Bookshelf Enclosures (specify finish). HS-739WX Shpg. wt., 142 lbs. Net 338.20

NOW FROM LAFAYETTE
THE REMARKABLE

KT-650 Criterion FM TUNER KIT

NO MONEY DOWN
KT-650 in KIT FORM

54.50

LT-650 Factory
Wired & Tested

79.95



MADE
IN U.S.A.

ASSURANCE OF
COMPONENT
QUALITY

ONE YEAR PARTS
GUARANTEE

All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

- Low Noise Front End With Triode Grounded Grid Amplifier and Triode Mixer
- Double Tuned Dual Limiters and Foster Seeley Discriminator
- Sensitivity 1.25 uv For 20 db of Quieting
- Variable AFC Literally "Lock In" Stations
- Frequency Response $\pm 1/2$ db 15-35,000 cps
- Multiplex Output For Stereo FM
- Easy-To-Build Printed Circuits
- Electronic Bar Tuning Indicator Tube
- Pre-Aligned IF and Discriminator Coils
- 3 Gang Tuning Condenser
- Virtually Distortionless Performance—Less than .15% Distortion at 100% Modulation.

MONEY-BACK GUARANTEE

Each Lafayette Kit is guaranteed to meet, or exceed, its published specifications for performance or your money is refunded in full. LAFAYETTE GUARANTEES YOU COMPLETE SATISFACTION.

"I congratulate you people on the tremendous job you have done with this FM tuner."
Donald MacKenzie
Marlboro, Mass.

"The KT-650 performed as beautifully as it went together."
Curtis Frets,
Ontario, Calif.

Some Letters
Out of
THOUSANDS

"In this era of loose claims by many reputable manufacturers, you may feel a deep sense of pride in producing this kit. Every claim you made is true."
George F. Schaefer
Ramsey, N. J.

"A pleasure to build."
Francis J. Crowley
Hempstead, N. Y.

LAFAYETTE LT-200
WIRED MULTIPLEX ADAPTER
WITH KT-650 TUNER KIT
BUY BOTH AND SAVE!

Made in U.S.A.
LT-200

PERFORMANCE
VALUE
COMBINATION!



NO
MONEY
DOWN

KT-650



104.00

KT-650 KIT PLUS LT-200

Made For Each Other! Purchase your KT-650 tuner in combination with this new Lafayette LT-200 Multiplex Adapter and save \$5.00 off of their combined purchase price. You'll be completely equipped to receive the new FM stereo multiplex broadcasts. Supplied with necessary cables and instructions. Shpg. wt., 17 1/2 lbs. HTA-14WX KT-650 Kit plus LT-200 Net 104.00 HTA-15WX LT-650 Factory Wired plus LT-200 Net 129.45

* Lafayette supplies this multiplex adaptor fully wired and aligned rather than in kit form, due to alignment difficulties requiring a mpx generator for exact alignment.

READY FOR MULTIPLEX!

Lafayette engineers have succeeded in developing an instrument with performance and flexibility that equals and surpasses factory-wired or kit tuners many times its modest cost.

The KT-650 incorporates every desirable FM Tuner feature. A Multiplex jack provides for addition of a Multiplex Adapter for FM Stereo Reception. Flywheel weighted tuning enables effortless station-to-station tuning. Pinpoint tuning accuracy by a special electronic bar tuning indicator tube. A variable AFC (Automatic Frequency Control) is featured—literally "locks in" the station and is adjustable for tuning weak stations adjacent to strong stations. The Tuner Level Control allows precise adjustment of the Tuner output level. Superb circuitry features a low noise front end with triode mixer plus double tuned dual limiters and wide band Foster-Seeley discriminator. Sensitivity is such that in many areas the only antenna needed will be a short piece of wire, except in remote locations. Plate follower


outputs permit using the tuner up to 50 feet from the amplifier. Time-saving printed circuit boards are utilized to make wiring errors almost nonexistent. IF and discriminator coils have been carefully factory prealigned—permits you to play the tuner as soon as assembled.

The superbly styled low silhouette enclosure will do justice to any decor. Beige cover is set off by a Cream and Sienna Brown etched panel and knobs with contrasting Black Dial Face. Complete with cage, legs, interconnecting cables with plugs, indoor folded dipole antenna and alignment tool. Overall Dimensions: 14x5 1/4x11"D. For 117V, 50-60 cycle AC. Power consumption 40 watts. Shpg. wt., 13 1/2 lbs. KT-650WX FM Tuner Kit Net 54.50 HTA-14WX Combination of KT-650 and LT-200 FM Multiplex Adapter. You Save 5.00 Net 104.00 LT-650WX Factory Wired & Tested Net 79.95 HTA-15WX Combination of LT-650 and LT-200 FM Multiplex Adapter. You Save 5.00 Net 129.45

COMPARE THESE SPECIFICATIONS:

Sensitivity: 1.25 microvolts for 20 db of quieting. Image Rejection: 66 db. AM Suppression: 48 db. Discriminator Linearity: 600 kc. Distortion and Noise: Better than 57 db below 1.5 volts at 100% modulation. Frequency Response: $\pm 1/2$ db from 15 to 35,000 cps with a standard 75 microsecond de-emphasis network. Audio Output: 1.75 volts at 75 KC deviation (100% modulation). Antenna Input: 300 ohm. Controls: Tuning; Level; AFC Control and Power Switch. Outputs: (2) Multiplex Adapter; Amplifier. Tube Complement: ECC85, 6BK7B, 6AL5, 2-7543, 2-6BA6, 6AV6, EM84 Electronic Bar Tuning Indicator Tube and a silicon diode rectifier.

EASY FLY-
WHEEL
TUNING—
Smooth, ef-
fortless tun-
ing from one
station to
another.



FRONT PANEL
LEVEL CON-
TROL—Provides
precise control
of your tuner
output level.

MULTIPLEX AND
MAIN OUTPUTS—Plate
follower main output allows
connection of tuner up to 50
feet from amplifier. Multiplex
output for FM stereo.

VARIABLE AFC
—"Locks in" the
station for posi-
tive drift free re-
ception of both
weak and strong
signals.

FREE! LAFAYETTE FM STEREO MULTIPLEX BROCHURE

Lafayette has prepared an informative, fact-filled brochure describing FM stereo Multiplex Broadcasting. Write, for your free copy of brochure BK-50, "Facts About FM Stereo Broadcasting."

The Most Flexible Tuner Ever Designed

LAFAYETTE STEREO-TUNER

KT-500A

MADE IN U.S.A.

KT-500A

74.50

NO MONEY DOWN

IN KIT FORM

LT-50A

124.50

NO MONEY DOWN

COMPLETELY WIRED AND TESTED



Use as a FM-AM Stereophonic Tuner for simulcast stereo or with a multiplex adapter for FM stereo reception



USE AS TWO INDIVIDUAL TUNERS
FM IN ONE ROOM . . . AM IN THE OTHER

- MULTIPLEX OUTPUT FOR NEW STEREO FM
- TWO PRINTED CIRCUIT BOARDS AND IF'S PREALIGNED
- FM AFC AND AFC DEFEAT
- 17 TUBE PERFORMANCE—11 Tubes (4 dual-purpose) + Tuning Eye & Selenium Rectifier
- ARMSTRONG CIRCUIT WITH DUAL LIMITERS AND FOSTER-SEELEY DISCRIMINATOR
- 12 TUNED CIRCUITS AND DUAL CATHODE FOLLOWER OUTPUTS
- EXTREME SENSITIVITY AND WIDE FREQUENCY RESPONSE

The KT-500A will receive simultaneous FM and AM stereo broadcasts or since the two sections are completely independent it may be utilized for normal FM or AM reception. The Tuner also provides an output for the new multiplex FM stereophonic reception. Apart from its unique flexibility, the KT-500A offers noise-free, drift-free, distortion-free performance the equal and in many instances superior to the highest priced tuners. Each FM & AM section is tuned with its own 3-gang tuning capacitor and is provided with individual cathode follower outputs. This means that long output cables can be used to connect tuner to amplifier or control center without fear of high frequency losses. Also, separate volume controls are provided for each channel so that when used for stereophonic reception, a proper balance between channels can be achieved. Convenient front panel switch changes from stereo to monaural use. Simplified accurate knife-edge tuning is provided by magic eye which operates independently on FM and AM. Automatic frequency control "locks in" FM signal permanently. Ferrite rod antenna with loading ring is supplied to bring in weak AM stations for quality reproduction.

Designed for easy assembly, the kit is built around two printed circuit boards and prealigned. IF's Insuring fast accurate construction even for the beginner. Beautifully styled, the KT-500A employs a cream and brushed brass front panel plus matching brown knobs with copper inserts set in a beige finished vinyl enclosure.

KT-500AWX Stereo Tuner Kit Net 74.50
HTA-12WX Combination of KT-500A and LT-200 Multiplex Adapter You Save 5.00 Net 124.00
LT-50AWX Same as KT-500AWX, completely wired and tested Net 124.50
HTA-13WX Combination of LT-50A and LT-200 Multiplex Adapter You Save 5.00 Net 174.00

ASSURANCE OF
COMPONENT
QUALITY

ONE YEAR PARTS
GUARANTEE

All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

"... this kit is excellent all the way around. It would be difficult to improve upon."
Robert Meier
Washington, D.C.


"Instructions were very good. Performance is wonderful. Best all around design..."
S. B. Heberlig
Glendora, New Jersey

SPECIFICATIONS

FM CIRCUIT: Armstrong, low noise front end with triode grounded grid amplifier and triode mixer. Double tuned dual limiters, Foster-Seeley discriminator, AFC and AFC defeat. AM CIRCUIT: Superhet with 3 stages AVC, 20 kc whistle filter, ferrite antenna. DISTORTION: Under 1% harmonic on FM; under 1% on AM for up to 80% modulation. HUM LEVEL: 60 db below 100% modulation. SENSITIVITY: FM—full limiting on signals as low as 1 uv, 2 uv for 30 db quieting; AM Terminal Sensitivity 5 uv. SELECTIVITY: FM 200 kc bandwidth; 6 db down, AM 8kc BW; 6 db down. FREQUENCY RESPONSE: FM 20-20,000 cps $\pm 1/2$ db, AM 20-5,000 ± 3 db. IMAGE REJECTION: FM 40 db; AM 30 db. I. F. REJECTION: FM 70 db, AM 50 db. CONTROLS: 5 controls; FM VOL, AM VOL, FM Tuning, AM Tuning, and five position function selector switch. TUBES: 3-6BA6, 2-6AU6, 1 each 6BK7B, ECC85, 6AL5, 6BE6, 12AU7 and 6U5 tuning eye. Selenium rectifier. OUTPUT IMPEDANCE: Low impedances cathode follower. Output jacks for FM, AM or Stereo. ANTENNA INPUT: 300 ohms. Size 13 3/4x10 3/4x4 1/2"H. Shpg. wt., 18 lbs. Kit comes complete with all parts and metal cover, a step-by-step instruction manual, schematic and pictorial diagrams.

NO MONEY DOWN

MADE IN U.S.A.



KT-500



124.00

KT-500A KIT PLUS LT-200

With this outstanding new Lafayette LT-200 Multiplex Adapter your KT-500A will be equipped to receive the new FM multiplex stereo broadcasts in addition to monaural AM-FM and simulcast stereo AM, FM, and, by purchasing both units together you save an additional \$5.00 off, their combined purchase price. Supplied with necessary cables and instructions. Shpg. wt., 22 lbs. HTA-12WX KT-500A Kit plus LT-200 Net 124.00 HTA-13WX LT-50 Factory Wired plus LT-200 Net 174.00

* Lafayette supplies this multiplex adaptor fully wired and aligned rather than in kit form, due to alignment difficulties requiring a mpx generator for exact alignment.

FOR FASTEST SERVICE USE LAFAYETTE'S CONVENIENT ORDER BLANK

WorldRadioHistory

Lafayette Catalog No. 623 Page 9

Now! FROM THE
LAFAYETTE
high-fidelity
RESEARCH LABORATORIES

The ULTIMATE FM STEREO TUNER

THE New LAFAYETTE **Criterion**™ LT-700 FM STEREO MULTIPLEX TUNER

- Virtually Distortionless Performance — Less than 0.15% Distortion at 100% Modulation, Monaurally
- Low Noise Front End With Triode Grounded Grid Amplifier and Triode Mixer
- Double-Tuned Dual Limiters and Foster Sealey Discriminator
- Stereo Separation: 35 db at 400 cps.
- Frequency Response $\pm 1/2$ db 15-35,000 cps, Monaurally
- Variable AFC Literally "Locks In" Stations
- Sensitivity 1.25 μ v for 20 db of Quieting
- 3 Gang Tuning Condenser
- Electronic Bar Tuning Indicator

The LT-700 is another impressive example of Lafayette's engineering leadership. For here is a tuner that achieves a level of distortionless performance and flexibility that sets the standard for professional FM multiplex reception. Its superb circuitry features a low noise front end with triode mixer, double-tuned dual limiters and wide band Foster Sealey discriminator. Distortion has virtually been eliminated with less than 0.15% distortion at 100% modulation (monaurally). Sensitivity of the LT-700 is such that in many areas the only antenna needed will be a short piece of wire, except of course in remote locations. Plate follower outputs permit using the tuner up to 50 feet from the amplifier. Designed for maximum versatility, the LT-700 features a convenient front panel volume control for precise adjustment of tuner output level. In addition a variable AFC (automatic frequency control) is provided. Once properly tuned, the AFC literally "locks in" the station and is adjustable for tuning weak stations adjacent to strong stations. Pinpoint tuning accuracy is assured by a special electronic bar tuning indicator that indicates maximum closure at the point of best tuning. Multiplex operation is achieved by a simple front panel switch. This also activates a stereo light when the station tuned to starts broadcasting stereo. Every LT-700 is individually aligned and tested to meet or exceed Lafayette's specifications. Attractively styled with a cream and brushed brass front panel set in a beige finished vinyl enclosure. Size 13 $\frac{3}{4}$ "x10 $\frac{3}{4}$ "x4 $\frac{1}{2}$ "H. For 117V, 50-60 cycle AC. LT-700WX Shpg. wt., 16 lbs.

Net 124.50

TECHNICAL SPECIFICATIONS

Sensitivity: 1.25 μ v for 20 db of quieting. Variable AFC. Harmonic Distortion: 0.15% at 1Kc 100% modulation. Signal-to-Noise Ratio: Better than 57 db. Freq. Response: $\pm 1/2$ db 15-35,000 cps monaurally. Image Rejection: —50db. Stereo Separation: Built-in MPX section provides 35db separation at 400 cps. Discriminator Linearity: 600 Kc. Audio output: 1.75v at 75 Kc deviation (100% modulation). Tubes: Simple manual switching for FM multiplex operation. Anode Follower for low impedance wide-band distortion-free output. Automatic FM stereo indicator light. 2—No. 47 Pilot Lights. Tubes: 12AX7, 6CA, 12BZ7, ECC85/6AQ8, 6BK7B, 2-6BA6, 2-7543, 6AL5, EZ-81 rectifier, 2 matched diodes plus EM-84 tuning eye.



MADE IN U.S.A.

124.50
NO MONEY DOWN

FREE! LAFAYETTE FM STEREO MULTIPLEX BROCHURE

Lafayette has prepared an informative, fact-filled brochure describing FM stereo Multiplex Broadcasting. Write for your free copy of brochure BK-50, "Facts About FM Stereo Broadcasting."

Now!

LAFAYETTE UNIVERSAL MULTIPLEX ADAPTER

Now Enjoy All The Quality & Dynamic Brilliance of Stereo Through Your FM Tuner

54.50 No Money Down



- 35 DB Stereo Separation (at 400 cps)

Made in U.S.A.

Here's the easiest, most inexpensive way for you to enjoy stereo—not records, not tapes, but stereo with all the fidelity and convenience that only FM can provide. Add this exciting new method of stereo reproduction to your component High-Fidelity system with this brilliant new stereo multiplex adapter. Performs beautifully with virtually any late model, wide band tuner, equipped with a multiplex output jack and delivering a mpx output signal from 1.5 to 2 volts. Requires no special knowledge or tools to hook up—as simple and easy to connect as were your original components. Supplied with all necessary audio cables. All that's required is to merely plug the unit into your tuner, amplifier and AC outlet. Engineered for simplicity of operation, a selector switch conveniently located on the front panel provides for ON-OFF, Mono-FM and Stereo-FM. Individual pilot lights indicate when power is on and when adapter is operating stereo-phonically. Beautifully styled to match any decor in textured beige finish cover and smart brushed brass anodized aluminum front panel. TECHNICAL SPECIFICATIONS: Separation: (at 400 cps) 35db; Harmonic Distortion: Less than 1% from 50 to 15,000 cps; Frequency Response: ± 1 db 50-15,000 cps. Multiplex Input Signal: 15 volts to 2V; Gain: 15 db; Output Impedance: 8000 ohms; Hum: at 60 cps for 1 volt signal input better than 60db; Rejection to 67KC: at least 50db; Rejection to 38 KC: at least 40db. Four tubes (2 dual purpose) 12AX7, 6CA, 12BZ7, EZ80. Features notch filter for 38KC; low impedance plate follower output (for remote amplifier connection); matched diodes for optimum separation. Supplied with a special 15 inch low capacitance input cable for optimum separation. Measures 4 $\frac{1}{2}$ "x6 $\frac{1}{4}$ "x4 $\frac{1}{2}$ "H. For 110-120V, 60 cycle AC. Shpg. wt., 8 lbs. LT-200

Net 54.50

★ COMPARE THESE ALL STAR FEATURES ★

- Superior Distortion & Stereo Separation Characteristics
- Self Powered
- Matches With Virtually All Recent Model Wide-Band Tuners Equipped With MPX Output Jacks
- Complete With Enclosure & All Necessary Connecting Cables

FM STEREOPHONIC MULTIPLEX ADAPTERS

NEW MULTIPLEX RECEIVERS



H.H. SCOTT
MODEL 335

WIDE-BAND MULTIPLEX ADAPTER

Now owners of all H. H. Scott wide-band tuners, regardless of age or model, can enjoy multiplex reception by adding the Model 335 wide band multiplex adapter to their systems. Self-powered (all connections to the tuner are external), so FM tuner alignment is unaffected. The 335 can be switched out of your stereophonic system to allow stereo AM-FM reception with H. H. Scott stereo tuners 330, 331, 399. Controls: SELECTOR (Off, Monophonic FM, Stereo with subcarrier noise filter, stereo without subcarrier noise filter); LEVEL; ADAPTOR DEFEAT; STEREO NOISE FILTER. Matches H. H. Scott tuners in height and styling. Dimensions in accessory case: 7 $\frac{1}{4}$ "x5 $\frac{1}{4}$ "x13"D. 105-125 V.A.C., 50-60 cycle, self-powered. Shpg. wt., 8 lbs. Uses H size case. Matching panel to LT-10 FM tuner kit available. G-626WX (less case) Net 109.95



Pilot
MODEL 200
AUTOMATIC
MULTIPLEXER

- Self-Powered
 - Indicator Light
 - No Operating Controls
- 79.50** NO MONEY DOWN

The Pilot 200 multiplex adaptor is completely automatic. No controls are needed or used. When the tuned-to station is broadcasting stereo, the built-in indicator light goes on and the Multiplex automatically switches to stereo reception. All connections are external, made with jack cords simply plugged in. Will not affect reception of monaural FM. Completely self-powered. Contains three tubes plus one rectifier. Housed in an attractive black and brass enclosure (included) designed to match Pilot components. Measures 5Hx3Wx14"L. G-681 Shpg. wt., 4 $\frac{1}{2}$ lbs. Net 79.50 Pilot 100 semi-automatic Multiplexer w/enclosure G-680 Shpg. wt., 2 $\frac{1}{4}$ lbs. Net 49.50



SHERWOOD
S3MX
SELF-POWERED
MULTIPLEX
ADAPTER

NO MONEY DOWN **69.50**

Designed for use with many FM tuners—having either high or low multiplex signal output. For best performance a wideband FM tuner should be used with the S3MX. Unique features are 67 KC and hiss filters. Subcarrier sensitivity .01 to 2 volts. Audio output 2V @ $1/2$ % distortion. Power switch disconnects adapter in "off" position, 4 tubes plus rectifier. Size: 5 $\frac{3}{4}$ "x10 $\frac{1}{2}$ "x4". For 110/120 VAC. G-301 Less Case Shpg. wt., 8 lbs. Net 69.50

MODEL A3MX MULTIPLEX ADAPTER (NOT ILLUSTRATED)

Similar to S3MX but less power supply, designed specifically for use within the chassis of Sherwood S-2200 and S-3000. Can be used with other tuners as well. Less S3MX hiss filter but with 67KC filter (always on). 2 tubes. Shpg. wt., 5 lbs. Net 49.50 G-302



harman kardon
AWARD TA5000X
50 WATT
AM/FM STEREO
RECEIVER

A complete stereo control center consisting of a sensitive, distortion-free AM/FM Tuner with built-in FM multiplex facilities, 50-watt stereo amplifier (25-watts each channel) plus a versatile stereo preamplifier. All components have been engineered into a single compact unit only 13 $\frac{1}{2}$ inches deep—small enough to place on a bookshelf. The TA-5000X features a full range of controls for every stereo function including separate Bass and Treble controls for each channel plus Blend, Balance, Loudness and Function controls. Slide switches provide for Stereo Reverse, Equalization, Contour plus Hi-cut and Lo-cut filters. Front panel contains a Stereo Headphone Receptacle plus a front panel tuning meter allows precise visual tuning. Size: 16"Wx10 $\frac{1}{4}$ "Hx13 $\frac{1}{2}$ "D. Shpg. wt., 40 lbs. Net 299.95 G-656WX Net 12.95 G-657WX CX-80 Metal Case Shpg. wt., 5 lbs. Net 12.95 G-658W WW-80 Walnut Case. Shpg. wt., 5 lbs. Net 29.95



FISHER
UNIVERSAL
MPX-100 STEREO
MULTIPLEX ADAPTER
NO MONEY DOWN **109.50**

Completely self-contained and self powered, the new Fisher MPX-100 is designed to bring FCC approved multiplex reception to all Fisher tuners and receivers including other makes employing wide band design and containing a multiplex output. Unit is equipped with a special "Stereo Beacon" circuit, which automatically signals the moment the station tuned begins broadcasting in stereo. A standby position allows listening to monaural FM program material, at the same time enabling the "Stereo Beacon" to function. Other features include: Front panel Stereo Balance control provides easy adjustment for optimum balance; Selector Switch; separate AUX inputs. Supplied with 3 cables. Front panel is finished in brushed brass. Size: 12Dx7 $\frac{1}{2}$ "x4 $\frac{1}{2}$ "H. B-118WX Shpg. wt., 10 lbs. Net 109.50



**NEW! FM
MULTIPLEX
ADAPTOR
MODEL
MA-2G**

Many G.E. FM tuners are now equipped with an output jack wired to provide an external multiplex adapter with the electrical information necessary for stereophonic reception. The MA-2G is designed to operate in conjunction with such G.E. tuners to provide two stereophonic audio channels which may be connected to the inputs of a stereo amplifying system. Since this adapter is completely self-contained and self-powered, the only required connections to the existing audio system are those to the multiplex output of the tuner and to the separate inputs of the stereo amplifier system. Frequency response of the adaptor is ± 3 db from 50 to 15,000 cycles. Hum and noise down 60 db. Mounting base is 10Lx2 $\frac{1}{4}$ "W, with mounting holes spaced 2 $\frac{1}{4}$ ". Clearance of 3" required for tubes and capacitor. G-336 Shpg. wt., 3 lbs. Net 39.15



**NEW HARMAN KARDON
MULTIPLEX
ADAPTER MX700**
59.95
NO MONEY DOWN

New self-powered FM multiplex adapter operates with all Harman Kardon tuners having multiplex outputs. Circuit has 2 stage subcarrier, main carrier amplifier followed by 19KC synchronous oscillator m-derived L-R filter, two section RC L + R filter, dual phase L-R detector and precision matrix. Crosstalk—40 db. Response ± 1 db at 15-15,000 cps. Size: 2 $\frac{1}{2}$ "x4 $\frac{1}{2}$ " deep. Shpg. wt., 4 $\frac{1}{2}$ lbs. Net 59.95 G-650 Metal Enclosure for MX700. Shpg. wt., 1 lb. Net 8.95 G-655 **MX600 ADAPTER** Converts TA224, TA260 and TA230 into integrated multiplex receivers. Size: 7 $\frac{1}{4}$ "x1 $\frac{3}{4}$ "x3 $\frac{1}{4}$ ". G-651 Shpg. wt., 2 $\frac{1}{4}$ lbs. Not Illustrated Net 49.95



Pilot
602M 30 WATT FM
MULTIPLEX STEREO
RECEIVER
249.50
NO MONEY DOWN

A sensitive FM Tuner, a Multiplexer, a 30-watt Stereo Amplifier (15-watts each channel) plus a versatile stereo preamplifier—all precision engineered into one compact component. Controls: FM Tuning, Master Volume, Stereo Balance, Input Selectors, Phono, Tape Monitor, Loudness and Separate Bass and Treble for each channel. Frequency Response: 20-20,000 cps. Hum and Noise: 80db below full output. Harmonic Distortion 1% at full power. FM tuner section features low noise triode RF amplifier, triode converter, 3 IF amplifier stages, wide band detector and achieves a sensitivity of 3 μ v IHFM standard. Size: 5 $\frac{1}{2}$ "Hx14 $\frac{1}{8}$ "Wx10 $\frac{1}{4}$ "D. For 105-120 volts 60 cycles AC. Complete with cover. Shpg. wt., 26 lbs. G-682WX Net 249.50

LAFAYETTE ALL TRANSISTOR HI-FI STEREO COMPONENTS

LAFAYETTE 40-WATT ALL TRANSISTOR STEREO AMPLIFIER LA-440




99⁵⁰
NO MONEY DOWN

STUDY & COMPARE THESE SPECIFICATIONS
I.H.F.M. Music Power Output: 40 watts (20 watts per channel) based on 4-ohm load impedance. Frequency Response ± 0.5 db 20 to 20,000 cps measured according to IHFM standards. Intermodulation Distortion: 0.9% to 1 db below clipping 60 and 6,000 cps. Harmonic Distortion: 0.5% at 1 db below clipping. Hum and Noise: Completely inaudible at all playing levels. Phono Input: -72 db Tuner Input: -25 db. Output Impedance: May be used with 4, 8, 16 ohm loud-speakers. Power Requirements: 105-120 volts AC, 50-60 cps. 12 to 28 volts DC for battery operation.

• Dual Concentric Bass & Treble Controls • Brilliant Design & Performance • Frequency Response — ± 0.5 db 20 to 20,000 cps • Instantaneous Operation — No Warm-Up Required • Hum, Noise & Microphonics Virtually Eliminated • Place Anywhere — Does Not Require Ventilation as No Heat Is Generated.

NEW!

- 20 Transistors plus
- 4 Germanium Diodes plus
- 3 Silicon Diodes plus
- 2 Thermistors



Made In U.S.A.

Now Lafayette applies space-age electronics to high-fidelity design to bring you this superb new 40-watt stereo amplifier (20-watts each channel). Utilizing the most advanced transistor circuitry, the LA-440 completely eliminates tubes and output transformers; substituting in their place a total of 29 solid state devices to provide an unmatched level of stereo high-fidelity performance. Here is an amplifier that: **GENERATES NO HEAT**—no need to worry about ventilation, you can place it anywhere and current drain is so low, it will operate efficiently not only at 110 V AC, but even from 12 to 28 volt batteries. **REQUIRES A MINIMUM OF MAINTENANCE**—since transistors last indefinitely maintenance problems are virtually a thing of the past and performance will not deteriorate. **VIRTUALLY ELIMINATES HUM, NOISE AND MICROPHONICS**—performance can best be described as transparent, the only sound you hear is that of the music. PRO-

VIDES INSTANTANEOUS OPERATION, no need to wait for warm-up, the LA-440 plays as soon as it is turned on. Controls are provided for every possible stereo, hi-fi function: Front panel contains dual concentric Bass and Treble controls, Volume control, Balance control and Selector switch for Phono, Tuner, Tape, Aux 1 and Aux 2 with corresponding inputs provided on the rear panel. In addition, slide switches are provided for Mono A—Stereo—Mono B, Loudness, Scratch Filter and Rumble Filter. Rear panel contains 2-switched AC outlets plus 3 tape outputs for recording stereo or mono (Tape A, Tape B, A & B). Superbly styled, the LA-440 measures only 3Hx10¹/₂Wx8¹/₂D and is finished in a brushed gold front panel, gold finished aluminum knobs and is complete with matching enclosure. Shpg. wt., 10 lbs. LA-440WX Net 99.50

NEW! LAFAYETTE ALL-TRANSISTOR FM-MULTIPLEX STEREO TUNER WITH BUILT IN MULTIPLEX

- 20 Transistors — 9 Diodes Includes 8 Transistor Automatic Multiplex Section • Built-In Tuning Meter • Frequency Response 20-20,000 Cps ± 1 db • Automatic Frequency Control • Interstation Muting • Unmatched Reception of FM and FM Stereo Broadcasts


Years of Trouble free listening are yours with the Lafayette LT-300 all transistor multiplex tuner. A perfect match for the LA-440 amplifier both in appearance and performance. The tuner eliminates hum, heat or microphonics, problems associated with tube units. Super powered transistor circuit provides dazzling reception of FM and Stereophonic FM Multiplex Broadcasts. Wide band design with AFC assures greater selectivity, high sensitivity and an amazingly low signal-to-noise ratio. The built-in multiplex section is completely automatic... no controls to set. Synchronous—gate separation

of channels from composite signal reproduces all the audio information with low distortion. Advanced design keeps circuit exceptionally stable with no adjustments needed. Deluxe signal-strength meter indicates perfect reception at all times. Interstation muting avoids annoying FM hiss and pops found between stations. Power requirements are very small, consumes only 4 watts at 105-120V AC. Brushed brass panel, tan covers—matches companion amplifier LA-440. Size: 3Hx10¹/₂Wx8¹/₂D. Shpg. wt., 8 lbs. LT-300WX Net 149.95

Runs Cool
Place it Anywhere!


Built-In
Tuning
Meter

149⁹⁵
Regularly 209.95
NO MONEY DOWN



SPECIFICATIONS:
Sensitivity: 1.8 microvolts for 20db quieting. Selectivity (IF bandwidth) 270 KC at -6 db points. Discriminator Peak-to-Peak separation 1 megacycles. Noise level: 66db below 100% modulation. Antenna Input Impedance 300 ohms.
Made in U.S.A.

40-WATT ALL TRANSISTOR LA-440 AMPLIFIER IN MATCHED STEREO SYSTEMS



MADE IN U.S.A.



194⁵⁰
NO MONEY DOWN



LAFAYETTE SK-58 12" COAXIAL SPEAKERS



CHANGER BASE

LESA CD2/21



GARRARD "AUTOSLIM" (ALTERNATE CHANGER)



SK-100 TRIMELIEX SPEAKERS

ELIPTOFLEX

LAFAYETTE 40-WATT ALL TRANSISTOR AMPLIFIER IN MATCHED STEREO SYSTEMS
Lafayette LA-440 40-Watt All-Transistor Stereo Amp. 99.50
Lesla CD 2/21 4-Speed Record Changer 44.50
Wood Base for Changer (Specify Walnut, Mahog. or Blonde) 4.75
Audio Empire S108 Diamond Needle Cartridge 35.00
2-Lafayette SK-58 Free Edge 12 Coaxial Speaker @ 29.50 each 59.00

LAFAYETTE SYSTEM PRICE 194.50 REGULAR CATALOG PRICE 242.75
YOU SAVE 48.25

System No.	Amplifier	Changer	Cart*	Base	Speaker	Speaker Cabinet**	Shpg. Wt. Lbs.
LS-441WX	LA-440	Lesla CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-58		48 194.50
LS-442WX	LA-440	Garrard Autoslim		+	2 ea. SK-58		48 194.50
LS-443WX	LA-440	Lesla CD 2/21		+	2 ea. SK-58	2 ea. Eliptoflex	96 260.50
LS-444WX	LA-440	Garrard Autoslim		+	2 ea. SK-58	2 ea. Eliptoflex	96 260.50
LS-445WX	LA-440	Lesla CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-180		45 198.50
LS-446WX	LA-440	Garrard Autoslim		+	2 ea. SK-180		45 198.50
LS-447WX	LA-440	Lesla CD 2/21		+	2 ea. SK-180	2 ea. Eliptoflex	93 264.50
LS-448WX	LA-440	Garrard Autoslim		+	2 ea. SK-180	2 ea. Eliptoflex	93 264.50

Any of above systems with addition of Lafayette LT-300 All-Transistor Multiplex Stereo Tuner (described above), specify System Stock No. plus LT-300 Tuner and add 134.95 to system price.

* Be Sure To Specify Choice of Empire S108, Pickering 380C, Shure M7D or GE-VR1000-7 Cartridge.

LAFAYETTE 40-WATT ALL-TRANSISTOR TUNER AMPLIFIER RECEIVER SYSTEM

LA-440 All-Transistor 40-Watt Amplifier 99.50
LT-300 Transistor FM Multiplex Tuner 149.95
Walnut Enclosure 19.50
Catalog Price 268.95



YOU SAVE 9.50

Lafayette Complete Receiver Price **SPECIAL 259.45**


COMPACT SPACE SAVING COMBINATION OF ULTRA-MODERN DESIGN

Space age electronics has developed this compact system. Small size and no heat generation enable this smart looking ensemble to be placed anywhere in your home. The all-transistor LA-440 amplifier and LT-300 tuner complement each other perfectly for outstanding performance of musical material via records, tape or

FM stereophonic multiplex programs. A beautifully finished walnut cabinet completely encloses the top and sides of the units giving them a "custom built" look. Front panels of brushed brass with black knobs and white switches. LA-445WX Net 259.45

MADE IN U.S.A.

NEW! OMEGA ALL TRANSISTOR 60 WATT STEREO AMPLIFIER



249.00
NO MONEY DOWN

Made in U.S.A.

- 31 Transistors
- Advanced "Quadra-Power Circuit"
- Flat Frequency Range Beyond Audibility
- Cool Operation
- Full Complement of Stereo Controls
- Unconditional 2-Year Guarantee

SPECIFICATIONS:

Controls: Master Bass and Treble; Independent bass and treble; Mode, Volume Balance; Blend, Loudness; Scratch filter rumble filter; phase switch; tape Monitor; 5-position selector switch; and Cartridge output compensator. Frequency response 18-20,000 cps ± 0.3 db at full output. Harmonic and IM distortion: less than 1%; hum and noise: 75 db below full output. Power output 30-watts (IHFM Music Rating) per channel Stereo — 60 watts monaural. 31 transistors, 4 diodes, 1 zener diode, 2 silicon rectifiers. G-685WX Net 249.00

For the first time an all-transistor 60-watt stereo amplifier with the performance of the finest tube equipment plus all the big listening and maintenance advantages of transistors. Exclusive "Quadra-Power Circuit" employs four power transistors per channel with uniform power dissipation and powerful linear response extending the frequency range to well beyond normal hearing. Since transistors are non-microphonic and there isn't any tube heater hum, there is a wonderfully clear tone to the sound. The Omega provides master bass and treble controls which allow a simple simultaneous balance adjustment of both channels. Another advanced feature is the exclusive cartridge output compensator which permits adjusting the amplifier to the speaker output voltage of your ceramic or magnetic pickup cartridge. Thus all front panel controls operate over their optimum range regardless of the cartridge output level. Trouble free transistor circuit is unconditionally guaranteed for two years. Modern styling is at home in any decor. Only 3H x 15¹/₂W x 9"D. For 117 VAC/60 cycles. Shpg. wt., 12 lbs. G-685WX Net 249.00

AMAZING LAFAYETTE VALUE & PERFORMANCE

MODEL LT-80A FM TUNER



READY FOR MULTIPLEX!

ONLY **49⁵⁰**

A LAFAYETTE SPECIAL VALUE!

COMPARE FEATURE FOR FEATURE WITH THE MOST EXPENSIVE TUNERS

Remarkable... Quality, performance and styling that is in every respect the equal and in many instances superior to tuners priced far above the modest cost of this instrument. Designed and constructed of the finest components, with jewel like precision (each unit is hand wired) in order to insure that each tuner will maintain its excellence year after year with a minimum of maintenance. Engineered to provide maximum FM versatility, the LT-80A is provided with a multiplex output, designed to accept a stereo FM multiplex adapter. Flywheel action tuning control. Tube complement consists of 2-6AQ8, 2-6BA6, 2-6AU6, 1 each 6AL5 and 6X4. Handsome low silhouette enclosure will do justice to any decor. Beautifully finished in gold and white with contrasting black dial face. Complete with cage and legs. Dimensions: 11³/₈Wx8Dx4¹/₂"H. LT-80A FM Stereo Tuner Net 49.50 HTA-11WX Combination of LT-80A and LT-200 FM Multiplex Adapter. You Save 5.00 Net 99.00

STEREO COMBINATION! LT-80A FM TUNER WITH LT-200 MULTIPLEX ADAPTER



You Save 5.00 **99.00**

Save by purchasing your LT-80A Tuner together with Lafayette's exciting new LT-200 Multiplex Adapter and be fully equipped to receive the new stereo FM multiplex broadcasts. HTA-11WX Net 99.00



PIN-POINT TUNING ACCURACY is provided by this precision tuning meter; evaluates relative strength of the incoming signal... invaluable when tuning weak stations.

- ARMSTRONG CIRCUIT FOSTER-SEELEY DISCRIMINATOR AND DUAL TUNED LIMITERS • AFC • AFC DEFEAT • EXTREMELY SENSITIVE—1.5 UV FOR 20 DB QUIETING • 10-TUBE PERFORMANCE—8 TUBES (2-DUAL PURPOSE) • 20-20,000 CYCLES ± 1/2 DB • SUPERB LOW SILHOUETTE STYLING • 3 GANG TUNING CONDENSER • TUNED GROUNDED GRID RF STAGE

NOW! LAFAYETTE LA-55 15 WATT MONAURAL AMPLIFIER



44⁵⁰

NO MONEY DOWN AN UNBEATABLE VALUE!

The most extraordinary Hi-Fi value ever offered

- Frequency Response: 15-30,000 CPS • Hum 65 Db Below Rated Output • Rumble Filter
- Power Output 15 Watts • Harmonic Distortion Less Than .3% • EL84 Output Tubes in Push-Pull
- Sensitivity: 3 MV Mag. Phono • 5 Input Channels • Beautifully Styled

Outstanding Performance and Engineering + Beautiful Styling + Unbeatable Price—add up to make the Lafayette LA-55 truly the finest HI-FI monaural amplifier value today... Beautifully styled in gold and white, the LA-55 easily adapts to any room decor. Perfect for that music system in your living room, finished basement, store or office. Ruggedly constructed, this fully integrated amplifier-preamplifier employs premium quality EL84 tubes in push-pull and advanced circuitry for faithful reproduction of all monophonic sources... perfect for use as a second amplifier for stereo or for starting out monophonically and adding stereo at a later date. Engineered to include every practical feature... a worthwhile contribution to hi-fi reproduction.

SPECIFICATIONS: Power Output 15 watts Institute of High Fidelity Manufacturers Rating (30 watts peak). Frequency Re-

sponse 15-30,000 cps ± 1 db (at normal listening level); Sensitivity: For full power, High level inputs 0.5v. Mag. phono 3 mv. Hum and Noise: Volume control at max. High level inputs 65 db below rated output. Mag-Phono 55 db below rated output; Harmonic Distortion less than .3%. Inputs: Total 5—Aux. Tuner, Mag. Phono, Crystal Phono, Tape Head. Outputs: Tape Out, 4, 8 and 16 ohm speaker terminals; Tubes: Total of 5 plus rectifier—2-EL84, 1-6BL8, 1-6AV6, 1-12AX7, and 1-6CA4/WZ81. Controls: Monitor/On-Off; Volume/Power On-Off; Bass; Treble; Rumble Filter. Hum balance control. Selector: 4-position, Aux. Tuner, Phono, Tape Head. Complete with removable case and legs. AC receptacle on rear of chassis. Dimensions: 13³/₄Wx4Hx8³/₄D. Knobs extend 3³/₄" in front of panel. Shpg. wt., 20 lbs. Net 44.50

LAFAYETTE SUPER-VALUE HIGH-FIDELITY PHONO SYSTEM

PLAY STEREO & MONAURAL RECORDS MONAURALLY NOW — ADD COMPLETE STEREO LATER. This economical high-fidelity system is the performance value of the year. Designed for ruggedness as well as beauty, these components will satisfy even the most critical music listener.

COMPONENTS

LAFAYETTE LA-55 15 Watt Complete Amplifier	44.50
LESA CD 2/21 4-Speed Record Changer	44.50
WOOD BASE FOR CHANGER (Specify Walnut, Mahog. or Blonde)	4.75
AUDIO EMPIRE S108 Diamond Needle Cartridge	35.00
LAFAYETTE SK-128 Full Range 8" Bixial Speaker	19.50
Regular Catalog Price	148.25

LAFAYETTE SYSTEM PRICE **109⁵⁰** YOU SAVE 38.75

LAFAYETTE 15 WATT MATCHED MONAURAL SYSTEMS

*Make certain to indicate your choice of either Audio Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7 Diamond Needle Stereo Cartridge.

System	Amplifier	Changer	Cartridge*	Base†	Speaker	Spkr. Cabinet	Shpg. Wt.	Net
LS-51WX	LA-55	LESA CD2/21	Your Choice of Garrard Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	—	Lesaf SK-128	—	39 lbs.	109.50
LS-52WX	LA-55	Autoslim	—	—	Lafat SK-128	—	39 lbs.	109.50
LS-53WX	LA-55	CD2/21	—	—	Lesaf SK-128	Miniduct†	62 lbs.	132.00
LS-54WX	LA-55	Autoslim	—	—	Lafat SK-128	Miniduct†	62 lbs.	132.00
LS-55WX	LA-55	CD2/21	—	—	Lesaf SK-58	—	45 lbs.	119.50
LS-56WX	LA-55	Autoslim	—	—	Lafat SK-58	—	45 lbs.	119.50
LS-57WX	LA-55	CD2/21	—	—	Lesaf SK-58	Eliptoflex	69 lbs.	154.50
LS-58WX	LA-55	Autoslim	—	—	Lafat SK-58	Eliptoflex	69 lbs.	154.50

Lafayette LT-80A FM Tuner with any system above, add 49.50 to Net price. To order, specify system No. plus LT-80A, Autoslim=Garrard 4-Speed Record Changer. Miniduct=Shelf Speaker Enclosure for 8" Speaker. Eliptoflex=Shelf Speaker Enclosure for 12" Speaker—Specify Walnut, Oiled Walnut, Mahogany or Blonde. †=Specify Mahogany, Walnut or Blonde.



FAMOUS H. H. SCOTT 299B 50-WATT STEREO AMPLIFIER



SAVE 60.45 at LAFAYETTE'S

Low, Low PRICE

Regularly 209.95

149⁵⁰

NO MONEY DOWN

For The First Time At This Price!

QUANTITIES LIMITED

Check The Specs — Check The Name — Now Check The Price and you'll know why we feel this is the Hi-Fi buy of the year.

Famous for its performance, thousands purchased this sought after stereo amplifier for 209.95. Now you can have this same amplifier for your stereo system and save over \$60. The 299B is rated at 50 watts and includes two complete channels with dual preamps and 25-watt power sections. Offers complete stereo facilities — a third channel output is provided for three channel stereo. Controls include: Master Function Selector; separate Bass and Treble controls for each channel; Balance control; Loudness control; Rumble and Scratch filters; Phase Reversal switch and Input Selector. Stereo Tape Recorder facilities provided for recorder output, playback

input plus a front panel monitor switch. Frequency Response is flat from 20 to 30,000 cps. Hum level is better than 80db below maximum output. Harmonic Distortion is less than 0.8%. The low level stereophonic cartridge input has a 3 millivolt sensitivity for accommodating stereo cartridges with very low output. 4, 8, and 16-ohm speaker taps are furnished for each channel. For 105-125 volts, 50-60 cycle operation. Size including optional accessory case: 15¹/₄x12¹/₂x4³/₈" G-135WX Shpg. wt., 25 lbs. Net 149.50 Accessory Case for Scott 299B. Shpg. wt., 1 lb. G-641W Net 12.95

UNPRECEDENTED STEREO PERFORMANCE VALUE! A COMPLETE MATCHED STEREO SYSTEM FEATURING THE H. H. SCOTT 299B



Lafayette SYSTEM PRICE

257.10

YOU SAVE 49.85

LAFAYETTE SK-58 12" COAXIAL SPEAKERS

GARRARD RC88/11 with Base

ALTERNATE RECORD CHANGER GARRARD MODEL A with Base

CHOICE OF CARTRIDGE



OPTIONAL LAFAYETTE ELIPTOFLEX BOOKSHELF ENCLOSURES



COMPONENTS

H. H. SCOTT 299B 50-WATT STEREO AMPLIFIER	149.50
GARRARD RC-88 Record Changer	59.50
BASE FOR RC-88 (Specify Finish)	3.95
AUDIO EMPIRE S108 Diamond Needle Stereo Cartridge	35.00
2-LAFAYETTE FAMOUS SK-58 Free Edge 12" COAXIAL SPEAKERS @ 29.50 each	59.00
Regular Catalog Price	308.95

Complete System as above with choice of Audio Empire S108, Pickering 380C or Shure M7D Stereo Cartridges. HS-736WX Shpg. wt., 65 lbs. Net 257.10 Same as HS-736WX above, plus 2-Lafayette Eliptoflex Series Bookshelf Enclosures (specify finish). HS-737WX Shpg. wt., 140 lbs. Net 323.10 Complete system essentially the same as HS-736WX, but with the Garrard Model A Automatic Turntable. HS-738WX Shpg. wt., 67 lbs. Net 272.20 Same as HS-738WX above, plus 2-Lafayette Eliptoflex Series Bookshelf Enclosures (specify finish). HS-739WX Shpg. wt., 142 lbs. Net 338.20

THE NEW LAFAYETTE LA-240 40-WATT STEREO AMPLIFIER



CRITERION EQUIPMENT CABINET AVAILABLE FOR \$84.50

- Concentric Volume Balance Control
- Less Than 1% Harmonic Distortion at Rated Output
- Hum & Noise 80 db Below Rated Output
- Frequency Response: 12-100,000 cps \pm 1 db at 1 Watt
- Variable Separation Control Eliminates Exaggerated Channel Separation
- Dual Concentric Bass & Treble Controls
- High Sensitivity Allows Use With All Stereo Cartridges

COMPARE THESE FEATURES

Quality, Design and Performance That Are Remarkable—The Lafayette LA-240 represents the highest standards of stereophonic amplifier design—literally creating a new meaning for excellence. Use of the most advanced engineering techniques and finest components have resulted in a powerful 40-watt stereo amplifier incorporating two 20-watt power channels and dual preamplifier. A level of flexibility and performance have been achieved that can only be compared with units twice the price.

Separation Control—Provides continuously variable channel separation from full stereo to full monaural, thus insuring the correct degree of stereo separation for individual listening tastes and room acoustics.

Independent Tone Controls—Concentrically mounted bass and treble controls for each channel.

Volume—Balance Control—Individual level controls for each channel.

Loudness Switch—Allows the volume controls to function as compensated loudness controls and provides the frequency response changes required by the ear at low distortion levels.

Rumble Filter—Reduces rumble from a noisy turntable with a minimum effect on program material.

Mode Switching—Ch A and Ch B slide switches provide for normal stereo, reverse channel, monophonic A or monophonic B.

Selector Switch—Instant selection of Aux, Tuner, Phono or Tape Head Inputs—non-shorting position permits recording and playback using a permanently connected tape recorder.

Hum Balance Controls—Individual hum balance controls for each channel located at the rear for fast, easy minimum hum adjustment.

Full Range of Inputs & Outputs—Inputs: (5 stereo pairs) Dual Aux—Dual Tuner—Dual Ceramic Phono—Dual Mag. Phono—Dual Tape Head; Outputs: Dual Tape Out—Dual 8 and 16 ohm speaker terminals.

Superb Low Silhouette Styling makes the LA-240 an amplifier you'll be proud to display. Gold finish cover is set off by an ivory and gold front panel with gold metal knobs. Complete with cage and legs. Overall Dimensions: 14 $\frac{1}{4}$ "x10 $\frac{1}{2}$ "x5 $\frac{3}{4}$ "H. For 115V AC operation. Power consumption 185 watts. LA-240WX Shpg. wt., 25 lbs. Net 79.95

A COMPLETE STEREO CONTROL CENTER
UNSURPASSED CONSTRUCTION & PERFORMANCE!




Dual 20-Watt Power Amplifiers
Dual Stereo Preamplifier

One Handsome Compact Unit

79.95
NO MONEY DOWN

SPECIFICATIONS

Power Output and Distortion—20 watts per channel at less than 1% total harmonic distortion at 1 Kc. Less than 0.25% total harmonic distortion at 14 watts; less than 0.12% at 1 watt. Intermodulation Distortion: .075% at 1 watt; .34% at 10 watts. Frequency Response: 12 to 100,000 cps \pm 1 db at 1 watt; 50 to 70,000 cps \pm 1 db at full output. Sensitivity: For full output: High Level inputs 0.75v Mag. inputs 5.5 Mv at 1 Kc. Tone Control Range: Treble: 12 db boost or cut at 10 Kc. Bass: 15 db boost or cut at 50 cps. Hum and Noise: Zero volume hum: 80 db below rated output. Maximum volume hum: High level inputs, 78 db below rated output; Mag. Phono inputs, 50 db below rated output. Outputs: Dual 8 and 16 ohm impedance speaker outputs, Dual Tape outputs. Tube Complement: 4—6BQ5/EL84, 2—6BL8/ECF80, 3—12AX7/ECC83, 1—6Z34/SAR4.



Individual Hum Balance Controls for Each Channel

Full Range of Inputs and Outputs

Separation Control from Full Stereo to Full Monaural Volume-Balance Control for Each Channel

LAFAYETTE 40-WATT MATCHED STEREO SYSTEMS

COMPONENTS


Lafayette LA-240 40-Watt Stereo Amplifier	79.95
Lesca CD 2/21 4-Speed Record Changer	44.50
Wood Base For Changer (Specify Walnut, Mahog or Blonde)	4.75
Audio Empire S108 Diamond Needle Cartridge	35.00
2-Lafayette SK-128 Full Range 8" Bi-axial Speakers @ 19.50	39.00
Regular Catalog Price	203.20

LAFAYETTE 40-WATT MATCHED STEREO SYSTEMS

*Specify Choice of Audio Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7 Diamond Needle Stereo Cartridge.

System	Amplifier	Changer	Cartridge*	Base†	Speakers	Cabinet‡	Lbs.	Net
LS-341WX	LA-240	CD2/21	Choice of	Lesca	2 SK-128	—	50	162.95
LS-342WX	LA-240	Garrard Autoslim	of	Laf	2 SK-128	—	50	162.95
LS-343WX	LA-240	CD2/21	Audio Empire S108,	Lesca	2 SK-128	2 Mini-Duct†	95	205.95
LS-344WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-128	2 Mini-Duct†	95	205.95
LS-345WX	LA-240	CD2/21	Pickering 380C,	Lesca	2 SK-180	—	55	186.95
LS-346WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-180	—	55	186.95
LS-347WX	LA-240	CD2/21	Shure M7D	Lesca	2 SK-180	2 Eliofoflex‡	103	252.95
LS-348WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-180	2 Eliofoflex‡	103	252.95
LS-349WX	LA-240	CD2/21	Or	Lesca	2 SK-58	—	58	182.95
LS-350WX	LA-240	Garrard Autoslim	GE VR-1000-7	Laf	2 SK-58	—	58	182.95
LS-351WX	LA-240	CD2/21	Lesca	Lesca	2 SK-58	2 Eliofoflex‡	106	248.95
LS-352WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-58	2 Eliofoflex‡	106	248.95

See Full Descriptions Elsewhere on SK-128, SK-180, SK-58, Mini-Duct & Eliofoflex. † Specify mahogany, walnut or blonde finish. ‡ Specify walnut, oiled walnut, mahogany or blonde finish. Any of above systems with addition of Lafayette LT-700WX Multiplex Stereo Tuner (described on other pages) add 114.50 to system price. When ordering add the letter T to the prefix. Example LS-341WX system with LT-700WX tuner is ordered as LST-341WX.



YOU SAVE
40.25

LAFAYETTE
SYSTEM PRICE


NO
MONEY
DOWN

ONLY
162.95

For any of above systems with Shure M30 Diamond Stylus Stereo Cartridge in place of choice of above cartridges add \$18.50 to System Net Price.

NEW! H. H. SCOTT

H. H. SCOTT
MODEL 355
AM-FM MULTIPLEX
TUNER/PREAMP



A completely revolutionary design concept from H. H. Scott. The 355 all-in-one gives you a wide-band FM multiplex and AM tuner and preamplifier with complete stereo facilities on a self-powered chassis plus an option of adding the Scott 208 modular 80 watt (40/40) stereo amplifier. Each module is self-powered and may be separated. The FM section uses the famous circuitry found in the Scott 350 tuner i.e., silver plated front end with 2MV sensitivity, wide band detector, 5 tube, 11 diodes multiplex section. The preamp-control section includes 2 low-level inputs, separate bass and treble tone controls for each channel, stereo balancing, tape recording and monitoring facilities plus "Stereo-eye" to locate Multiplex broadcasts, wide range AM section, illuminated tuning meter and aluminum chassis. Size in accessory case 17 $\frac{1}{2}$ "x6 $\frac{1}{4}$ "x15 $\frac{1}{2}$ "D. The 355 and 208 were designed for each other but may be used with other existing components. Shpg. wt., 355—19 lbs. 208—28 lbs.

G-644WX Model 355 (less cabinet)	Net 319.95
G-643WX Model 208 80 W. amp	Net 129.95
G-637W "C" metal cabinet for 355	Net 17.95
G-639W "GW" Walnut Cabinet	Net 21.95



SHERWOOD
S-8000 64-WATT FM
MULTIPLEX
STEREO RECEIVER

Model S-8000 includes the same advanced FM Multiplex receiver as the S-3000 IV and in addition it contains two 32 watt power amplifier-preamplifiers. High sensitivity FM tuner provides 20 db of quieting for 0.95 uv input. Available on the front panel are the following controls: Interchannel hush, flywheel FM tuning, friction-locked dual bass and treble controls; ganged loudness control; phono level control; stereo balance control; stereo function selector; input selector switches and 6 slide switches for activating scratch and rumble filters. AMPLIFIER SPECIFICATIONS (See S-3000 IV description for tuner specs.): Power output 32/32 watts music power, 30/30 watts continuous duty @ 1 $\frac{1}{2}$ % IM distortion; frequency response 20-20,000 cps \pm 1 db @ 30 watts. Hum and noise, 60 db below 30 watts. Inputs: tape playback, tape monitor, phono, AM tuner plus 2 auxiliary outputs for recording and 4, 8 and 16 ohm speakers. "Acro-beam" type tuning indicator and 7" FM dial scale. Tube complement: 22 plus 4 silicon rectifiers. Size: 16 $\frac{1}{4}$ "x14 $\frac{1}{2}$ ". Power requirements: 110-120V, 50-60 cycles AC @ 225 watts. Tube filaments are D.C. supplied. Model S-8000 requires just 2 speakers to complete a system for FM stereo listening.

G-300WX Less enclosure Shpg. wt., 36 lbs.	Net 299.50
Brown leatherette case for S-8000.	
G-298WX Shpg. wt. 10 lbs	Net 7.50

FISHER

500-B
65 WATT FM
MULTIPLEX
STEREO RECEIVER



The new 500-B receiver has 18 controls and switches for flexible control of its wideband FM multiplex tuner, dual channel preamplifier and dual channel 65 watt power amplifier. Front panel controls are: FM tuning; MPX filter, dual volume, dual bass, dual treble, high filter, low filter, tape monitor, dual selector, monostereo, channel reverse, balance, loudness, FM circuit has 4 IF stages, advanced multiplex design, special switchable noise filter and "Stereo Beam" tuning indicator. SPECIFICATIONS: Amplifier distortion less than 0.5%. Overall frequency response 25-25,000 cps \pm 1.5 db; FM sensitivity 0.7 uv into 72 ohm load; IHFM sensitivity 2.2 uv; signal/noise & hum 70 db. IF bandwidth 190 Kc; channel selectivity 52 db; FM response (after deemphas) 30-15,000 cps; Tubes: 4-ECC85, 6-6AU6, 4-12AX7, 2-7591, 2-EM84A, 1N-542, plus special multiplex tubes. Size: 17 $\frac{1}{2}$ "x5 $\frac{1}{4}$ "x13 $\frac{1}{4}$ " deep. G-403WX Less cabinet. Shpg. wt., 35 lbs. Net 359.50 FISHER 30-U Oiled Walnut Cabinet for 500-B. G-404W Shpg. wt., 6 lbs. Net 24.95

THE OUTSTANDING

"Stereo 250 A" KIT



Made in U.S.A.

IN EASY-TO-BUILD
KIT FORM

74.50

NO MONEY DOWN

50 WATT INTEGRATED STEREO AMPLIFIER KIT

• DC applied to all preamplifier and tone control tube heaters for hum-free operation • RIAA equalization on phono inputs • NARTB tape equalization on tape head inputs • Individual bias and balance controls • Hum balance Control • Excellent DC power supply regulation provided by silicon diodes • Total of 9 tubes, plus 3 silicon diodes—uses premium 6CW5/EL86 output tubes.

SPECIFICATIONS

POWER OUTPUT: 50 watts (100 watts peak) 25 watts per channel ± 1 db. DISTORTION: Total Harmonic Distortion ± 1 db at less than 1% at 1KC at normal listening level (1 watt); I.M. Distortion less than 0.5% at normal listening level. FREQUENCY RESPONSE: 15-40,000 cps ± 0.5 db at normal listening level. 20-50,000 cps ± 1 db at rated output. HUM & NOISE: Zero volume hum 77 db below rated output; max volume hum high level inputs 70 db below rated output; Mag. phono inputs 50 db below rated output. Sensitivity: For full output high level inputs 0.5V; Mag. phono 3.5 MV at 1KC. CHANNEL SEPARATION: Greater than 55 db at 1KC; greater than 45 db from 20-20,000 cps. SPEAKER AUXILIARY OUTPUT: 1 switched. TUBE COMPLEMENT: 4-6CW5/EL86, 2-7199, 3-12AX7, 3 Silicon diodes. IMPEDANCE: 4, 8 and 16 ohms per channel. POWER: 200 watts; 110-125V AC 50-60 cps.

Net 74.50

ASSURANCE OF COMPONENT QUALITY
ONE YEAR PARTS GUARANTEE
All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

THE new Lafayette KT-250A offers remarkable versatility, high quality of reproduction and new distinctive styling in one convenient low-cost unit. Designed and engineered for ease of assembly, the KT-250A is a fine stereo preamplifier and 50 watt stereo amplifier combined — with all the controls and features to enable you to enjoy the utmost in listening pleasure in any situation. Whether you use it as a stereo amplifier delivering 25 watts per channel or as a powerful 50 watt monophonic amplifier, you are assured of true high fidelity reproduction — free from hum, noise and distortion.

DELUXE FEATURES

- Unique Separation Control**—A new stereo control which provides continuously variable channel separation—from full monophonic to full stereo. Lets you select the amount of separation you want.
- Clutch-Operated Volume Balance Control**—Gives you a choice of independent or simultaneous control of both channels—you can use it as a master volume control without disturbing previously selected settings on each channel.
- 4 Independent Tone Controls**—Independent Bass and Treble adjustment for each channel. Concentric mounting for convenience—
- inner knob controls one channel, outer the other channel.
- Mode Switching**—Two slide switches provide Normal Stereo—Reverse Channel—Mon A (Channel A reproduced through both channels)—Mon B (Channel B reproduced through both channels).
- Input Selector**—4-position switch lets you select instantly any one of your connected monophonic or stereo sources—special non-shorting arrangement on one position permits recording and playback using a permanently connected tape recorder.

Loudness Switch—Provides the frequency response changes required by the ear at low listening levels and permits the Volume-Balance control to function as a compensated loudness control.

Phase Switch—Reverses the phase of one channel electrically—corrects for speakers connected out of phase or for reversed phase recordings sometimes found commercially.

3 Pairs of High Level Inputs—For connection of Crystal or Ceramic phono, Tuner, and auxiliary equipment.

2 Pairs of High Level Inputs—For connection of magnetic phono and Tape Head.

Main Speaker Outputs—Dual 4, 8 and 16 ohm terminals may be paralleled for 4 or 8 ohm operation at 50 watts.

Tape Output—Provides an output for Tape recording—unaffected by Volume and Tone Controls.

Bridged Output—A monophonic blend of both channels which can be fed to a third single channel power amplifier and speaker for a greater sound spread in stereo. May also be used for listening in another room.



Designed for ease of construction, the KT-250A can be assembled in a minimum of time. Assembly manual contains detailed step-by-step instructions... guides you every step of the way. Large full-scale pictorials show you where every wire and component goes.



Made in U.S.A.

NO MONEY DOWN

59.50

Lafayette 36 watt stereo amplifier

Fine wide-range stereo reproduction can be yours when you build this easily constructed 36 watt stereo amplifier (18 watts each channel). The KT-236A provides all the necessary inputs—lets you connect your stereo or monophonic sources permanently, with instant selection provided by the turn of a switch. Has built-in dual preamps for low level phono inputs—RIAA equalized for flat response. It includes a unique "Blend" control which provides continuously variable channel separation from full monophonic to full stereo—you select the exact degree of separation you want. Other features are: Concentric clutch-operated Volume control for independent or simultaneous level adjustment of both channels; Dual concentric Bass and Treble controls—give you 4 independent tonal adjustments; 3-position Selector Switch—Aux-Tuner-Phono; Mode (2 Slide Switches) provide Normal Stereo, Reverse channel, Mon A and Mon B; Phase switch—makes up for reversed-phase recordings sometimes found commercially and also corrects for speakers connected out of phase.

SPECIFICATIONS: POWER OUTPUT: 36 watts—18 watts per channel ± 1 db. Institute of High Fidelity Manufacturers Rating (72 watt peak). FREQUENCY RESPONSE: 15-30,000 cps ± 1 db at normal listening levels. SENSITIVITY: For full output; High level inputs 0.5V; Mag. Phono 3 mv. DISTORTION: Harmonic, less than 0.15% at normal listening level; IM, less than .3%. HUM AND NOISE: (At full volume) High level inputs 70 db below rated output; Mag. phono 53 db below rated output. CHANNEL SEPARATION: Better than 50 db. SPEAKER OUTPUT IMPEDANCE: 8 and 16 ohms. INPUTS: (Total 8) Dual Aux, dual Tuner, dual Crystal Phono, dual Mag. Phono. OUTPUTS: (Total 4) Dual main speaker output, dual Tape out jacks. TUBE COMPLEMENT: 4-EL84, 2-7199, 3-12AX7 plus 2 silicon diodes. Attractive beige vinyl laminated steel cabinet. Handsomely designed brass anodized aluminum front panel. Sienna brown molded legs, matching knobs and knobs). Shpg. wt., 24 lbs. 36 watt integrated Stereo Amplifier Kit, complete with deluxe cabinet and legs, all necessary parts and detailed assembly



MODEL KT-236AWX Net 59.50

THE AMAZING "STEREO 236" KIT

A NEW LOW-COST STEREO AMPLIFIER ANYONE CAN BUILD

Easy to Build!

Anyone can build these superb Lafayette stereo kits—no special skill is needed. Assembly manuals contain clearly worded step-by-step instructions which guide you all the way. Large full-scale pictorials illustrate every stage of assembly—show you exactly where every part goes. Join the thousands who have already discovered this easy low-cost way of owning the finest audio equipment.



Deluxe Stereo Controls

- 3-position Selector switch
- Dual concentric Bass control
- Dual concentric Treble control
- Concentric clutch-operated Volume control
- Unique "Blend" control
- Phase reverse switch
- Mode switches

DO-IT-YOURSELF and SAVE with LAFAYETTE HI-FI STEREO KIT SYSTEMS

BUILD THIS 36-WATT STEREO KIT SYSTEM

COMPONENTS		
Lafayette KT-236A 36 Watt Stereo Amplifier Kit		59.50
Lesa CD2/21 4-Speed Stereo Record Changer (less base)		44.50
Base for Record Changer (Specify Finish)		4.50
Audio Empire S108 Diamond Needle Stereo Cartridge		35.00
2 Lafayette SK-128 8" Ultra-Linear Bi-axial Speakers @ 19.50		39.00
Regular Catalog Price		182.90

ONLY 142.50

YOU SAVE 40.00

LAFAYETTE MATCHED 36-WATT STEREO KIT SYSTEMS

*Be sure to Specify Choice of Audio Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Diamond Needle Cartridges.

System	Amp. Kit	Changer	Cartridge*	Changer Base†	Speakers	Spkr. or Tuner	Cab. Shpg. Wt.	Net
LSK-231WX	KT-236A	Lesa CD2/21	Choice of Audio Empire S108, Pickering 380C, Shure M7D, Or GE VR-1000-7	—	2 SK-128	—	50 lbs.	142.50
LSK-232WX	KT-236A	Garrard Autoslym	—	—	2 SK-128	—	48 lbs.	142.50
LSK-233WX	KT-236A	Lesa CD2/21	—	—	2 SK-128	2 Mini-Duct†	93 lbs.	185.50
LSK-234WX	KT-236A	Garrard Autoslym	—	—	2 SK-128	2 Mini-Duct†	91 lbs.	185.50
LSK-235WX	KT-236A	Lesa CD2/21	—	—	2 SK-58	—	61 lbs.	162.50
LSK-236WX	KT-236A	Garrard Autoslym	—	—	2 SK-58	2 CK-14	109 lbs.	203.50
LSK-237WX	KT-236A	Lesa CD2/21	—	—	2 SK-58	2 CK-14	107 lbs.	203.50
LSK-238WX	KT-236A	Garrard Autoslym	—	—	2 SK-128	KT-650	64 lbs.	192.00
LSK-239WX	KT-236A	Lesa CD2/21	—	—	2 SK-128	KT-650	64 lbs.	192.00
LSK-240WX	KT-236A	Garrard Autoslym	—	—	2 SK-128	KT-650	62 lbs.	192.00


Any of above systems with addition of Lafayette LT-700WX, Multiplex Stereo Tuner, add \$114.50 to system price. When ordering add T to prefix. Example: LSK-231WX system with LT-700WX tuner is ordered as LSKT-231WX.

†: Specify Mahogany, Walnut or Blonde Base. Mini-Duct: 8" Speaker Bookshelf Enclosure. CK-14: Eliptoflex 12" Speaker Enclosure Kit, Unfinished. KT-650: FM Tuner Kit.

CHOICE OF ONE








OPTIONAL



Any system on this page with Shure M30 Diamond Stylus Stereo Cartridge in place of choice of above cartridges add \$18.50 to System Net Price.

CHOICE OF ONE



Deluxe 50-WATT DO-IT-YOURSELF STEREO KIT SYSTEM

MATCHED COMPONENTS		
Lafayette KT-250A 50 Watt Stereo Amplifier		74.50
Glaser-Steers GS-77 4-Speed Record Changer (less base)		59.50
Base for Changer (Specify Finish)		3.95
Audio Empire S108 Diamond Stereo Cartridge		35.00
2-Lafayette SK-58 12" Coaxial Speakers @ 29.50		59.00
REGULAR CATALOG PRICE		234.95

ONLY 184.75

YOU SAVE 47.20

LAFAYETTE MATCHED 50-WATT STEREO KIT SYSTEMS

*Be Sure to Specify Choice of Audio Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Stereo Cartridges.

System	Amp. Kit	Changer	Cartridge*	Changer Base†	Speakers	Spkr. Cabinet	Shpg. Wt. Kit lbs.	Net
LSK-351WX	KT-250A	Glaser-Steers GS-77	Choice of Audio Empire S108, Pickering 380C, Shure M7D, Or GE VR-1000-7	—	2 SK-58	—	80	184.75
LSK-352WX	KT-250A	Garrard AT6	—	—	2 SK-58	—	80	184.75
LSK-353WX	KT-250A	Glaser-Steers GS-77	—	—	2 SK-58	2 CK-14	128	225.75
LSK-354WX	KT-250A	Garrard AT-6	—	—	2 SK-58	2 CK-14	128	225.75
LSK-355WX	KT-250A	Glaser-Steers GS-77	—	—	2 SK-180	—	74	188.75
LSK-356WX	KT-250A	Garrard AT-6	—	—	2 SK-180	—	74	188.75
LSK-357WX	KT-250A	Glaser-Steers GS-77	—	—	2 SK-180	2 CK-14	122	229.75
LSK-358WX	KT-250A	Garrard AT-6	—	—	2 SK-180	2 CK-14	122	229.75

Any of above systems with addition of Lafayette LT-700WX, Multiplex Stereo Tuner, add \$114.50 to system price. When ordering add T to prefix. Example: LSK-351WX system with LT-700WX tuner is ordered as LSKT-351WX.

†: Specify Mahogany, Walnut or Blonde Base. SK-180: "Trihelix" 10" 3-way speakers. AT-6: GARRARD 4-Speed Record Changer. CK-14: Eliptoflex Bookshelf Speaker Enclosure in Kit form, unfinished.

GARRARD • GLASER-STEERS • LESA.....

PICKERING 380C DIAMOND STEREO CARTRIDGE, SHURE M7D DIAMOND STEREO CARTRIDGE, GE VR 1000-7 DIAMOND STEREO CARTRIDGE OR AUDIO EMPIRE S108 DIAMOND STEREO CARTRIDGE FOR ONLY . . .

1¢ SALE!

when you purchase any changer shown below



NEW! GARRARD AUTOSLIM AUTOMATIC INTERMIX CHANGER • 4 Speed
 Wired for Stereo and Monaural PLUS PICKERING, SHURE, AUDIO EMPIRE OR GE CARTRIDGE
39.51

An ultra-compact, automatic-manual changer at a remarkably low price. Only 6 1/4" overall height. Intermixes all records, i.e. records of different sizes can be stacked in any sequence. Separate manual and automatic controls—featuring Garrard's new center-changing mechanism. The Autoslim employs a new type of a turntable and a 4-pole shaded motor, achieving balance and quiet turning. Faun-colored unit plate with white trim. Dimensions: 14 1/4" left to right; 12 1/2" front to rear; 4 1/4" above top of motor-board, 2 3/4" below. For 100-130 VAC, 60 cycles. Imported from England.

- GR-160W Less cartridge. Shpg. wt., 9 lbs. Net 39.50
- Garrard "Autoslim" plus Pickering 380C Diamond Stereo Cartridge. Net 39.51
- PK-556W Shpg. wt., 9 lbs. Net 39.51
- Garrard "Autoslim" plus Empire 108 Diamond Stereo Cartridge. Net 39.51
- PK-557W Shpg. wt., 9 lbs. Net 39.51
- Garrard "Autoslim" plus Shure M7D Diamond Stereo Cartridge. Net 39.51
- PK-558W Shpg. wt., 9 lbs. Net 39.51
- Garrard "Autoslim" plus GE VR1000-7 Diamond Stereo Cartridge. Net 39.51
- PK-559W Shpg. wt., 9 lbs. Net 39.51




NEW! GARRARD AT-6 AUTOMATIC TURNTABLE

Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE

ONLY 54.51

A new, moderately priced automatic turntable combining deluxe features with compactness. Wired for stereo and monaural; plays all 4 speeds. Completely separate automatic and manual controls; 2 spindles with short spindle for single record playing. Built-in gram scale. Shpg. wt., 12 lbs.

- GR-167W AT-6, less base and cartridge. Net 54.50
- Garrard AT-6 PLUS Pickering 380C Diamond Stereo Cartridge. Net 54.51
- PK-552W Shpg. wt., 12 lbs. Net 54.51
- Garrard AT-6 PLUS Audio Empire S-108 Diamond Stereo Cartridge. Net 54.51
- PK-553W Shpg. wt., 12 lbs. Net 54.51
- Garrard AT-6 PLUS Shure M7D Diamond Stereo Cartridge. Net 54.51
- PK-554W Shpg. wt., 12 lbs. Net 54.51
- Garrard AT-6 PLUS GE VR 1000-7 Diamond Stereo Cartridge. Net 54.51
- PK-555W Shpg. wt., 12 lbs. Net 54.51



LESA CD 2/21 AUTOMATIC CHANGER
 Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE

only 44.51

Fully automatic jam-proof Lesa changer plays up to eight records of any size, with automatic intermix. Easy to operate — only two controls for all cycles, speed selection, start, stop and reject. Shpg. wt., 17 lbs.

- G-195W Lesa changer, less base & cartridge. Net 44.50
- LESA CD 2/21 PLUS Pickering 380C Diamond Stereo Cartridge. Net 44.51
- PK-506W Shpg. wt., 17 lbs. Net 44.51
- LESA CD 2/21 PLUS Audio Empire S-108 Diamond Stereo Cartridge. Net 44.51
- PK-507W Shpg. wt., 17 lbs. Net 44.51
- LESA CD 2/21 PLUS GE VR1000-7 Diamond Stereo Cartridge. Net 44.51
- PK-562W Shpg. wt., 17 lbs. Net 44.51
- LESA CD 2/21 PLUS SHURE M7D Diamond Stereo Cartridge. Net 44.51
- PK-538W Shpg. wt., 17 lbs. Net 44.51
- GR-197 Automatic 45 RPM Spindle. Net 3.75
- Base for changer — specify mahogany or blonde. Net 4.75
- GR-196W Shpg. wt., 3 lbs. Net 4.75



GARRARD MODEL "A" AUTOMATIC TURNTABLE

Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE

ONLY 79.51

The Garrard Model "A" is a precision turntable and tone arm with the convenience of automatic record changing. Plays all 4 speeds and is wired for stereo and monaural use. Features a built-in stylus pressure gauge. Complete with line cord, pick-up leads, plug-in shell, mounting hardware, standard and manual spindles, 45 RPM adaptor. Shpg. wt., 19 lbs.

- GR-166WX Garrard Model "A". Net 79.50
- Garrard Model "A" plus Pickering 380C Diamond Stereo Cartridge. Net 79.51
- PK-523WX Shpg. wt., 19 lbs. Net 79.51
- Garrard Model "A" plus Shure M7D Diamond Stereo Cartridge. Net 79.51
- PK-524WX Shpg. wt., 19 lbs. Net 79.51
- Garrard Model "A" plus GE VR1000-7 Diamond Stereo Cartridge. Net 79.51
- PK-551WX Shpg. wt., 19 lbs. Net 79.51
- GARRARD Model "A" plus Audio Empire S108 Diamond Stereo Cartridge. Net 79.51
- PK-548WX Shpg. wt., 19 lbs. Net 79.51



GLASER-STEERS GS-77 RECORD CHANGER

Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE

ONLY 59.51

Fully automatic, 4-speed stereo record changer. Transcription-type tone arm; inaudible wow, rumble and flutter. 4 pole motor. Shpg. wt., 13 lbs.

- GR-50W Changer only, less base, cart. Net 59.50
- GS-77 PLUS PICKERING 380C Diamond Stereo Cartridge, less base. Net 59.51
- PK-540W Shpg. wt., 13 lbs. Net 59.51
- GS-77 PLUS Shure M7D Diamond Stereo Cartridge, less base. Net 59.51
- PK-541W Shpg. wt., 13 lbs. Net 59.51
- GS-77 PLUS GE VR1000-7 Diamond Stereo Cartridge, less base. Net 59.51
- PK-564W Shpg. wt., 13 lbs. Net 59.51
- GS-77 plus Audio Empire S108 Diamond Stereo Cartridge. Net 59.51
- PK-550W Shpg. wt., 13 lbs. Net 59.51
- Wood base for changer. Ebony with gold trim. Shpg. wt., 5 lbs. Net 9.60
- PK-350W Shpg. wt., 5 lbs. Net 9.60
- PK-352 Automatic 45 RPM Spindle. Shpg. wt., 1 1/2 lbs. Net 2.95



GLASER-STEERS GS-400 STEREO RECORD CHANGER

Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE

47.51

Glaser-Steers 4-speed stereo record changer with automatic intermix; acoustically isolated and dynamically balanced transcription type tone arm; idler automatically disengaged in off position.

- GR-52W Changer only, less base. Net 47.50
- GLASER STEERS GS-400 PLUS Pickering 380C Diamond Stereo Cartridge. Net 47.51
- PK-471W Shpg. wt., 14 lbs. Net 47.51
- GLASER STEERS GS-400 PLUS Audio Empire S108 Diamond Stereo Cartridge. Net 47.51
- PK-472W Shpg. wt., 14 lbs. Net 47.51
- GLASER STEERS GS-400 PLUS Shure M7D Diamond Stereo Cartridge. Net 47.51
- PK-545W Shpg. wt., 14 lbs. Net 47.51
- GLASER STEERS GS-400 PLUS GE VR1000-7 Diamond Stereo Cartridge. Net 47.51
- PK-563W Shpg. wt., 14 lbs. Net 47.51
- PK-473W Black wood base for GS-400 changer. Net 5.90
- PK-352 Automatic 45 rpm spindle, 1 1/2 lbs. Net 2.95

PICKERING 380C stereo cartridge with .7 mil diamond stylus with exclusive "V-Guard." Shpg. wt., 5 oz. Net 29.85

SHURE M7D moving magnet stereo cartridge with .7 mil diamond stylus. Shpg. wt., 5 oz. Net 23.52

GE VR1000-7 magnetic, variable reluctance cartridge with .7 mil diamond stylus. Shpg. wt., 6 oz. Net 24.45

AUDIO EMPIRE S108 stereo cartridge with .7 mil diamond stylus. Shpg. wt., 7 oz. Net 35.00

NEW!



LAFAYETTE AUTOMATIC 4-SPEED RECORD CHANGER

RONETTE CERAMIC CARTRIDGE ONLY

22.35

NO MONEY DOWN

Plays Stereo, LP and 78 RPM


Quality Ronette Ceramic Cartridge • Automatic 3-Way Shut-Off • Intermixes Records of Same Speed • Heavy Duty-Constant Speed Motor

Feature for Feature, the Lafayette automatic record changer matches or exceeds costlier units. Built for compatibility with both stereophonic and monaural records, this changer offers superior performance for budget-sparing music systems. The balanced featherweight tone arm operates at only 5-7 grams of needle pressure to minimize record wear. Flip-type, Ronette ceramic stereo cartridge is unaffected by heat and humidity. Heavy precision-balanced turntable and constant speed motor insure smooth rotation without hum rumble or "wow". Plays all 4 record speeds—automatically changes up to fourteen 7", twelve 10" or 12" records. Intermixes 10" and 12" records of same speed. Plays records manually if desired. 45 r.p.m. spindle optional. Automatic 3-way shut-off after last record (returns tone arm to rest, stops

turntable motor, turns set off.) neutral position disengages turntable drive wheel when not in use—prevents rumble producing flat spots. 117 volts AC, 60 cycles. Compact and exceptionally functional, only 13 1/2 x 12 x 7 1/2". 3" below and 5 1/2" above mounting board. Beautiful brown and gold finish. Shpg. wt., 12 lbs.

- PK-605W No Money Down. Net 22.35
- PK-606W Walnut Base. Net 4.50
- PK-607W Mahogany Base. Net 3.95
- PK-608W Mounting Board. Net 1.10
- PK-609 45 R.P.M. Spindle. Net 1.49

4 SPEED TRANSCRIPTION TURNTABLE and TONE ARM



49.50

NO MONEY DOWN

• 3 lb. Balanced 12" Aluminum Turntable • Rumble and Noise Better Than —50 db • Speed Control Provides ± 7% Variation of Each Speed • Wow & Flutter Below 2% • Precision Lightweight 12" Aluminum Tone-Arm • Plug-In Shell For Popular Stereo Cartridges • Adjustable Counterbalance Weight • Perfect Tracking Even at 2 Grams • Automatic On-Off Switch Built Into Tone Arm Rest • Perfect For Both Stereo and Monaural

Features a heavy duty 4 pole induction motor, free-floating and shock mounted to virtually eliminate vibration. 12" aluminum table constructed with a permanently lubricated oilite bronze bearing. Speeds—16 2/3, 33 1/3, 45 and 78 rpm. "Off" positions between all positions. Oversize idler disengages in off positions. Stylus force adjustment accomplished by rotating Knurled Knob. Ball bearing suspensions result in a high compliance lateral, vertical movement. With stroboscope disc, 45 rpm adaptor, shielded hook-up cables and AC line cord. Motor plate is spring suspended and measures 16 1/2 x 12 1/2". Requires 4" below motor board. For 105-120 volts 60 cycles AC. Shpg. wt., 15 lbs.

- PK-449WX Less Base. Net 49.50
- Extra plug in cartridge shell with mounting hardware for PK-449. Net 1.69
- PK-499 Shpg. wt., 1 lb. Net 1.69
- WOOD BASE PK-449WX. Finest selected hardwood veneers. Mitered corners, 3/8" slides, 1/2" top. For turntable and 12" arm. Size 17 1/2 x 13 1/2 x 3 7/8" H. Specify: mahogany, walnut or blonde finish. Net 9.95
- PK-504W Shpg. wt., 5 lbs. Net 9.95

SPECIAL LAFAYETTE COMBINATIONS

- Save \$21.50—PK-449 Turntable and Arm with Empire S-108 Stereo Cartridge. Individually priced total \$84.50. Net 63.00
- PK-516WX. Net 63.00
- Save \$19.85—PK-449 Turntable and Arm with Pickering 380C Stereo Cartridge. Individually priced total \$79.35. Net 59.50
- PK-517WX. Net 59.50

LAFAYETTE COMPLETE STEREO TRANSCRIPTION PLAYER



26.95

LESS BASE

PK-160SW

• 5-CONTACT PLUG IN HEAD FOR ALL STEREO CARTRIDGES • 4-SPEED HEAVY DUTY 4-POLE TRANSCRIPTION TYPE INDUCTION MOTOR • MAGNETIC BRAKE FOR ± 7% SPEED ADJUSTMENT • STYLUS WEIGHT ADJUSTMENT SCREW ON TONE ARM • RUMBLE AND NOISE —40 DB • LESS THAN 0.3% WOW

Features a 5-contact plug-in head to accommodate stereo as well as monaural cartridges. The lightweight tone arm is an integral part of the mounting plate and requires no installation. New 4-speed turntable assembly is equipped with a quiet, heavy duty 4-pole motor, with an exclusive magnetic brake. Stroboscope disc also included. 10" heavy turntable, fitted with rubber mat. Dimensions of mounting plate 12 1/2" left to right, and 10 7/8" front to rear. Requires 2 3/4" below and 3" above motor board. For 105-120V, 60 cps. Accessories: 45 rpm adaptor, output cable to amplifier and plug-in heads. Shpg. wt., 14 lbs.

- PK-160SW Complete stereo transcription player, less cartridge. Net 26.95
- PK-438W Same as above, but with new GE Model VR-225 compatible stereo cartridge with diamond stylus. Net 36.95
- PK-162W Wood base for above, finished in mahogany or blonde (Please Specify). Shpg. wt., 5 lbs. Net 3.95
- PK-163W Unfinished mounting board for above. Strong durable 3/4" gumwood. (Shpg. wt., 1 lb.) Net .95

LAFAYETTE VISCOUS-DAMPED STEREO TONE ARM

— THE PROFESSIONAL 12" PK-90S

7.95



• JEWEL BEARING SUPPORT • INSTANT PLUG-IN CARTRIDGE CHANGE • AUTOMATIC FLUID CONTROL • PERFECT RECORD TRACKING • ACCOMMODATES MOST STEREO & MONAURAL HIGH FIDELITY CARTRIDGES

This Stereo/Monaural transcription arm assures dependable and stable operation, utilizing the floating-action principle of viscous-damping. The arm is supported at a single point by a pivot and jewel bearing having negligible friction. Damping is accomplished by a silicone fluid occupying the gap between a ball and socket. This damping control permits high compliance and negligible tracking error and prevents damage to either record or stylus should the tone arm be accidentally dropped. Low frequency resonance, skidding and groove-jumping are likewise minimized. The tone arm accepts all records up to 12" and accommodates, virtually all Stereo or Monaural hi-fi cartridges by means of precisely engineered adapters which simplify installation and provide proper stylus pressure. The arm has a decorative glossy-black finish. Overall length is 12"; height adjustable from 3/4" to 2 1/4" above motorboard; round mounting base is 2 5/8" in diameter. Shpg. wt., 2 1/2 lbs.

PK-90S—12" Viscous-Damped Stereo Tone Arm. Net 7.95

LAFAYETTE PANASONIC

PERFECT BALANCE—TURNTABLE WILL TRACK RECORDS EVEN AT ANGLES IN EXCESS OF 45°



SALE PRICE 19.95

REG. 32.50

• Distortion Free From 20-16,000 cps • Flat Frequency Response 20-15,000 cps • Feather Light Stylus Pressure—Individually Adjusted For 3-Grams • Hum Free—Entire Arm & Cartridge Case Shielded with Mu Metal

Tone arm resonance is minimized by use of specially designed counter weight, sub weight and lateral damping mechanism. The arm counter balance is floated on a damped suspension bar. Precision bearings assure minimum lateral and vertical friction. Overall height of arm adjusts from 1 1/4" to 2 1/4". Signal to noise level of well over 100 db. Stylus replacement requires only a few seconds, pull out the old stylus and plug in the new. The diamond stylus is capable of supplying up to 2,000 hours of playing time. With .7 mil diamond stylus, mounting instructions, stylus cleaning brush, all hardware. Shpg. wt., 3 lbs.

- PK-448 Complete .7 Mil Diamond Stylus Assembly for PK-448 Lafayette Panasonic Tone Arm. Shpg. wt., 1/4 lb. Net 7.95
- PK-452. Net 7.95

TECHNICAL INFORMATION More than 25 db • S/N Level . . . Over 100 db • Compliance . . . 5x10—6 cm/dyne • Suggested Load Impedance . . . 50,000 ohms • D. C. Resistance . . . 420 ohms • Tracking Force . . . 3 grams • Stylus . . . 7 mil • Frequency Response . . . Distortion free: 20-16,000 cps Flat. ± 2 db 20-15,000 cps • Overall Length . . . 11 1/4"

build your own HI-FI KITS



NEW! MODEL MX-99 FM MULTIPLEX ADAPTER

The EICO MX-99 is a self-powered multiplex adapter. It is free of phase distorting filters and meets or exceeds the required suppression of all spurious signals including the SCA (67KC) background music carrier, reinserted (38KC) sub-carrier, the (19KC) pilot carrier and all harmonics thereof. This factor is very important for high quality stereo tape recording. This adapter will synchronize with any usable output from the FM tuner. Provides automatic stereo-monophonic operation and includes low impedance cathode follower outputs. An indicator lamp turns on when a station is broadcasting multiplex stereo. It can achieve channel separation of 35db. The MX-99 is designed for all EICO FM equipment (HFT-90, HFT-92, ST-96), and any other component quality ratio detector FM tuners provided with a multiplex output. Size: 9 1/4" x 6 3/4" x 3 3/4" H. Shpg. wt., 7 lbs.

G-442 Kit **39.95**
G-443 Factory wired and tested **64.95**



EICO MODEL HFT 90K FM TUNER KIT

Factory pre-wired and pre-aligned front end. Pre-wired tuning eye assembly. Temperature-compensated components, "traveling" tuning indicator, fly-wheel tuning and AGC. SENSITIVITY: 1.5 uv for 20 db quieting; 2.5 uv for 30db quieting; full limiting from 25 uv INPUT: 300 ohm balanced. OUTPUTS: Cathode follower and multiplier. TUBES: 1-ECC85/6AQ8, 3-6AV6, 1-6AL5, AC 50-60 cps. Complete with instructions. 12x8 1/4 x 3 3/4". Shpg. wt., 10 lbs.

HFT-90 Same as above, but factory wired **Net 65.95**
G-423 **Net 65.95**
E-3 Cover for HFT-90 Shpg. wt., 3 lbs. **Net 3.95**
G-431

EICO ST-40K 40-WATT STEREO INTEGRATED AMPLIFIER KIT



The ST-40 contains 2 twenty watt amplifiers and a complete stereophonic hi-fi control center on one chassis. FEATURES: Switched sets of stereo inputs including magnetic phono (2), tape head, preamplified tape, FM-AM stereo tuner, FM-FM

switch, Loudness/level switch, Bass and treble controls. Other controls include: Six position mode selector, tape monitor, scratch and rumble. Output 4, 8, and 16 ohm. Third channel speaker connection. Specifications: IM distortion—2% at 40 watts; Harmonic Distortion—1/2% at 40 watts; Frequency response—± 1/2 db. 20-20,000 cps. Shpg. wt., 27 lbs.

G-520WX **Net 79.95**
Same as above, but wired. **Net 129.95**
G-521WX

EICO ST-70K 70 WATT STEREO INTEGRATED AMPLIFIER KIT



Consists of 2-35 watt amplifiers and a complete stereophonic hi-fi control center on one chassis. Stereo inputs in switched sets including: 2 magnetic phono (one for turntable, one for changer); tape head, preamplified tape, FM-AM stereo tuner, FM-FM

Multiplex, and Auxiliary. Controls: Level with balance check switch and loudness/level switch; bass, treble, six-position mode selector, blend, tape speed, tape monitor, scratch, and rumble. Output: 4, 8, and 16 ohm speaker. Third channel output available. Specifications: IM distortion—2% at 70-watts. Harmonic Distortion—1/2% at 70 watts. Frequency response—± 1/2 db. 20-20,000 cps. Shpg. wt., 35 lbs.

G-519WX **Net 94.95**
As above, but factory wired. **Net 149.95**
G-519WX

EICO MODEL HF85K STEREO PHONIC DUAL PREAMP KIT



Self-powered preamp-control center offering complete switching and control facilities for any stereo program source. SPECIFICATIONS (both channels): Frequency response 5-20,000 cps ± 0.3 db; IM distortion (60 & 7000 cps) .03% @ 1 v. RMS output; Harmonic distortion (20-20,000 cps) 1% @ 3 v. RMS output; Tone-control range ± 15 db @ 50 and 10,000 cps; RIAA phono and NARTB tape head (15, 7.5, and 3.75 ips) equalization; impedance, 8000 ohms. TUBES: 5-12AX7, ECC83's, 1-6X4.

HF85 Same, Factory wired and tested **Net 39.95**
G-492 **Net 64.95**

EICO MODEL HF87K 70-WATT STEREO HIGH FIDELITY DUAL POWER AMPLIFIER KIT



A dual amplifier, this unit provides 35 watts output per channel. Ultra-linear connected, self-biased, push pull EL34 output stages for high stability. SPECIFICATIONS: OUTPUT: 70 watts continuous, 140 watts peak. FREQUENCY RESPONSE: ± 0.5db 5 cps—100KC. HARMONIC DISTORTION: less than 1%. From 20 to 20,000 cps within 1db at 70 watts. DAMPING FACTOR: above 11. STABILITY MARGIN: 17db. SENSITIVITY: 0.38V for 100 ohms. TUBE COMPLEMENT: 1-ECC83/12AX7, 2-6SN7GTB, 4-EL34, 2 silicon diode rectifiers. POWER REQUIREMENTS: 215 watts at 117 volts AC, 60 cps. 15x11x6".

HF87 Same as above, but factory wired **Net 74.95**
G-497WX **Net 114.95**

EICO 12-WATT HI-FI AMPLIFIER . . . PREAMP KIT



Compact, attractively styled amplifier with complete front end facilities and true high fidelity performance. Direct tape head and magnetic phono inputs with NARTB (tape) and RIAA (phono) feedback equalizations. Power output: 12 watts continuous, 25 watts peak. Intermodulation distortion 1.5% at 12 watts, 0.55% at 6 watts, 60 to 6000 cps. Frequency response: 12-50,000 cps ± 0.5 db at 1 watt; 25-20,000 cps ± 0.5 db at 12 watts. Controls: Selector switch, level control, bass and treble controls. Speaker connections for 16, 8, and 4 ohms. TUBES: (2) ECC83/12AX7, ECC82/12AU7, (2) EL84, EZ81. Size: 3 3/4" x 12 1/2" x 8 1/4" D. Shpg. wt., 13 lbs. With instructions.

G-424 Kit **Net 34.95**
HF12 As above, but factory wired. **Net 57.95**
G-425



NEW! EICO RP-100K TAPE DECK KIT

A new, precision stereo/monaural tape deck, the RP-100 provides stereo/mono 1/4 track erase, record, and playback; plus 1/2 track stereo/mono playback. Separate record and playback heads and preamps permit simultaneous stereo playback from tape while recording. Sound-on-Sound recordings can be obtained without changing any connections. Features: Dual meters for monitoring stereo record levels and separate line and mic. (dynamic) mixing controls for each channel; SPECIFICATIONS: Tape speed—7 1/2 or 3 3/4 ips; up to 7" reel size; Flutter and Wow—0.2% at 7 1/2 ips, 0.25% at 3 3/4 ips; Frequency response: 30-17,000 cps at 7 1/2 ips, 40-15,000 cps at 3 3/4 ips; Signal-to-Noise ratio—53 db. or better. Timing accuracy—0.3%. Dimensions: 15 1/4" wide, 13 3/4" front-to-back, 7" deep. Shpg. wt., 28 lbs.

RP-100K semikit; includes transport completely assembled and tested with 3 heads; stereo record, and stereo playback preamps in kit form. **Net 299.95**
RP-100W wired and tested with 3 heads, stereo record, playback preamplifiers. **Net 399.95**
RK-276WX **Net 399.95**
Model CC-2 Luggage Type Carrying Case with detachable cover. For RP-100 **Net 29.95**
RK-277W Shpg. wt., 13 lbs.



FAIRCHILD 440 2-SPEED TURNTABLE KIT

A high fidelity turntable kit. 2-speed operation (33 1/3 and 45 rpm), single belt drive, Speed Sentinel control varies turntable speed ± 1 1/2%, highly styled and precision turntable platter. Strobe disc included to determine correct speed. Size: 19x16x10". Complete with unfinished mounting board, but less base, 19x16". For 110V, 60 cycle, AC. Requires 1 1/4" clearance above turntable, 3 1/2" below. GR-276W Shpg. wt., 21 lbs. **Net 55.00**

Same as above but completely wired and assembled. **Net 69.95**
GR-274WX **Net 69.95**
MODEL 440CBW. Base for above. Includes walnut mounting board, walnut wraparound, 19x16x8". Shpg. wt., 12 lbs. **Net 19.95**
GR-275W



REKO KUT 2 SPEED TURNTABLE KIT

K-34H TWO SPEED STEREO TABLE KIT. The same high quality and performance of the N-33H (described above) but with two speeds. Motor: Lifetime lubricated hysteresis—synchronous. Speeds: 33 1/3 and 45 RPM. Noise Level: 57 db. Wow and Flutter 0-15%. Chassis Deck: 12 1/2 x 19". Shpg. wt., 17 lbs.

GR-260WX **Net 69.95**
KB Walnut finish woodbase for K-34H turntable. **Net 14.95**
GR-262W Shpg. wt., 8 lbs.



Jensen KTF-3 SPEAKER KIT

Provides the necessary speaker components for TF-3 performance in a home-built or separately bought cabinet. Kit includes the woofer, two midrange units and tweeter of the TF-3 system. Includes M-F/H-F balance control, crossover network, wiring cable, enclosure vent tube and full instructions for enclosure construction. SPECIFICATIONS: Frequency Range: 25 cps to beyond audibility. Crossovers: 2,000 and 10,000 cps. Speaker System Power Rating: 25 watts. Impedance 8 ohms. GS-313 Shpg. wt., 1 1/2 lbs. **Net 57.75**

H.H. SCOTT



NEW! LM-35 MULTIPLEX ADAPTER KIT

The LM-35 uses unique kit pack which functions as a fold-a-way work bench. All wires are pre-cut to correct length. Multiplex circuitry pre-wired and pre-aligned at factory. Self-powered (all connections to the tuner are external). The LM-35 can be used with all H. H. Scott wide-band tuners regardless of age or model. Dimensions in accessory case: 7 1/4" x 5 1/4" x 13 1/2". 105-120 V.A.C. 50/60 cycles. Shpg. wt., 8 lbs.

G-642WX LM-35K **Net 79.95**
Metal H Case For LM-35 **Net 9.95**
G-627W **Net 9.95**



MODEL LK-72 72-WATT STEREO AMPLIFIER KIT

The LK-72 has the same output circuitry as the 299C wired stereo amplifier. Aluminum chassis and D.C. heated preamp filaments give low—80 db hum and noise. Frequency response 20 to 20KC ± 1 db; harmonic distortion at full output 0.8%. IM distortion 9.3% (CCIF); IHFM power bandwidth 21 to 20 KC; speaker output impedances 4, 8, 16 ohms. Front panel controls: Input selector (phono or tape head, Tuner, Extra); Equalization (NAB tape head or RIAA record equalization), Stereo Selector Switch; separate tone controls for channels A & B Stereo Balance; Derived Center Channel Level Control; Loudness On-Off; Scratch Filter; Tape Monitor; Loudness Compensation 15 1/2" x 5 1/2" x 13 1/2" D.

G-625WX (less case) Shpg. wt., 35 lbs. **Net 159.95**
Leatherette metal case for LK-72 kit. **Net 12.95**
G-147W Shpg. wt., 5 lbs.

CITATION HI-FI EQUIPMENT

HARMAN-KARDON CITATION I KIT Stereo Preamplifier Control Center

A high quality stereo-monaural preamp-control unit. Inputs: 12 (six pairs)—Aux, Tape Amp, Tuner, low-level phono, high-level phono. Outputs: 5—Two main preamp outputs plus a third channel output, two tape outputs for recording. Mode selector chooses output types: stereo, Channel A, Channel B, Stereo Reverse, IM DISTORTION: Less than 0.05% at 2 volts. RESPONSE: to ± 5 db 5-80,000 cps. TUBES: 9-ECC83/12AX7 plus silicon rect. POWER REQUIREMENTS: 110V AC. SIZE: 14 7/8" x 12 1/4" x 6 1/2" H. Shpg. wt., 20 lbs. Gold & Charcoal brown finish.

G-230WX Kit **Net 159.95**
G-231WX Wired **Net 249.95**
G-232W Walnut Enclosure **Net 29.95**

HARMAN-KARDON CITATION II KIT 120 Watt Stereophonic Hi-Fi Power Amplifier

Two ultra-linear type amplifiers deliver 60 watts each channel or a total of 120 monaural. Frequency Response: 18-40,000 cps ± 0 to -1.0 db @ 60 watts, 2-80,000 cps ± 0 to -1.0 db @ 1 watt; IM Distortion: Less than .5% @ 60 watts; Harmonic Distortion: Less than 0.5%, 20-20,000 cps @ 60 watts, Output 4, 8, 16 ohms. TUBES: 6-12BV72, 4-KT88, plus 4-Silicon Diodes & 1 Selenium rect. Dimensions: 16 3/4" x 9 1/2" x 11 1/2" D. Charcoal Brown & Gold Finish. Shpg. wt., 60 lbs.

G-234WX Kit **Net 159.95**
G-234WX Wired **Net 229.95**
G-235W Charcoal Brown Metal Enclosure **Net 7.95**

HARMAN-KARDON CITATION III KIT PROFESSIONAL FM TUNER KIT

The Citation III is an extremely sensitive tuner, utilizing the revolutionary new "Nuvistor" subminiature tube. Preassembled, factory-aligned Converter-IF subassembly. SENSITIVITY: 0.65 uv for 20 db quieting; 0.85 uv for 30 db quieting. IMAGE REJECTION: 65 db. FREQ. RESPONSE ± 0.5 db, 1-52,000 cps. DISTORTION: less than 0.1% at 100% mod. HUM: 65 db below 100% mod. POWER: 110-120 volts AC, 60 cps. 14 7/8" x 12 1/4" x 6 1/2". Shpg. wt., 24 lbs.

G-365WX Citation III Kit **Net 149.95**
G-366WX Citation III Wired **Net 229.95**
G-232W WC1 Walnut Enclosure for Citation III **Net 29.95**
G-373WX Citation III MA FM Stereo Adapter Wired **Net 79.95**
NEW! Citation III X Kit—Professional FM Stereo Tuner Kit. **Net 219.95**
G-364WX **Net 299.95**
G-374WX Citation III X Wired

NEW MODEL LT-110 WIDE-BAND FM STEREO MULTIPLEX TUNER KIT

FM multiplex tuner in kit form. Both the multiplex section and silver plated front end are factory pre-assembled and prealigned. You need only align the tuner's wide-bandpass IF's and detector using the meter on the tuner itself. Special shielding protects against interaction of tuner and multiplex sections. Unique circuitry eliminates multiplex interference with bias oscillator of any stereo tape recorder. Features stereo Noise Filter, Vernier Tuning; Front panel tuning meter; and Stereo Tape recorder output. IHFM usable sensitivity 2.2 microvolts. 10 Tubes, 11 diodes. Shpg. wt., 20 lbs. 15 1/2" x 5 1/4" x 13 1/4" D.

G-633WX (less case) **Net 159.95**
Leatherette metal case C for LT-110. Shpg. wt., 5 lbs. **Net 12.95**
G-147W

THE FISHER KX-200 80 WATT STEREO CONTROL AMPLIFIER KIT



169.50

Fisher engineers have developed a new concept of kit design known as Stratakit. Major components are pre-mounted and wires are pre-cut. The KX-200 amplifier/preamp specifications are: 80 watts IHFM music power output; (35 watts RMS each channel) Harmonic distortion (at rated output) 0.4%; IM Distortion (SMPT), at rated output 0.8%; Frequency response (overall 20-20,000 cps ± 1 db—total hum and noise 80 db (450mv rep); Channel Separation at 1 KC better than 50 db. TUBES: 6 ECC83, 4-7591, 2-SD95A, 2-SD91A. Built-in D'Arsonval calibration meter. For 117V, 60 cycles AC. Size: 15 1/2" x 12 1/2" x 5 1/4" H. Shpg. wt., 30 lbs.

G-666WX KX-200 Amplifier, less case **Net 169.50**
G-109W MC-2 Metal Cabinet for KX-200 9 lbs. **Net 15.95**

dynakit STEREO KITS



DYNAKIT PAS-2 STEREO PREAMPLIFIER KIT

Includes two independent high gain, low noise preamplifier-control channels. Inputs: 3 stereo low level and 4 stereo high level. Frequency response: ± 0.5 db 6-60,000 cps. Distortion: less than .05%. Noise: less than 3 uv. equivalent noise input on RIAA. Gain: 60 db at 1000 cps on RIAA, 20 db on high level. TUBES: 4-12AX7/ECC-83, 6X4, selenium rectifier. Textured vinyl finish. Size: 13x8x4". Shpg. wt., 11 lbs.

G-453WX Kit **Net 59.95**
Dynakit PAS-2 Stereo Preamp. Same as above, but completely wired. Shpg. wt., 11 lbs. **Net 99.95**
G-454WX **Net 99.95**
Model PM-3 Panel mounting kit for PAS-2. Shpg. wt., 3 lbs. **Net 4.95**
G-468



DYNAKIT STEREO 70 70-WATT STEREO AMPLIFIER KIT

The stereo 70 is rated at 35 watts channel or 70 watts for monophonic. Frequency response: ± 0.5 db 10-40,000 cps. IM distortion: less than 1% at 35 watts. Sensitivity: 1.3 volts rms input for 35 watts output. Output impedance: 4, 8, 16 ohms. Minimum channel separation: 55 db. Vinyl coated charcoal brown cover. Size: 13 1/2" x 6 1/2" x 5 1/2". Shpg. wt., 32 lbs.

G-455WX Kit **Net 99.95**
Dynakit Stereo 70 Stereo Amplifier. Same as above, but completely wired. **Net 129.95**
G-456WX

10 WATT PUSH PULL HI-FI AMPLIFIER KIT

BUILT-IN PREAMPLIFIER • SELECTOR SWITCHES PERMIT CHOICE OF THREE INPUTS • SEPARATE BASS AND TREBLE CONTROLS • 4, 8 AND 16 OHM OUTPUTS • EASY-TO-FOLLOW INSTRUCTIONS

This new, economy hi-fi amplifier has many deluxe features for exceptional performance. The three inputs are radio/crystal phono pickup, magnetic phono pickup and microphone. A selector switches the input from radio/crystal to microphone or magnetic pickup, depending upon the position of a rear apron slide switch. OUTPUT—Rated 10 watts, peak 18. FREQUENCY RESPONSE—± 1 db 30-15,000 cps. DISTORTION—1.5% harmonic, 4% intermodulation at 8 watts. 4 CONTROLS—Input Selector; Volume; Treble; Power-On-Off-Bass. TREBLE CONTROL—Flat response up to 18 db cut—BASS CONTROL—Flat response up to 15 db boost. OUTPUT IMPEDANCES—4, 8 and 16 ohms. TUBES—6SC7, 6SL7GT, 2-6V6GT and 5Y3GT rectifier. AUXILIARY AC OUTLET—Distinctive Hammett finish. SIZE—10 1/2" x 6 1/4" x 5 1/4". WEIGHT—8 1/2 lbs. For 110-120 Volts. Complete kit with coded wire, highest grade solder and detailed instruction manual. **Net 24.50**
KT-91

MONAURAL HI-FI PHONO SYSTEM KIT

Have FUN—SAVE MONEY by assembling this top-value system yourself! Features Lafayette KT-91 10-watt amplifier kit; famous Telefunken 4 speed automatic record changer with intermixing, jam proof operation, and automatic shut off features, crystal turnover cartridge with dual sapphire styli for stereo and monaural records, and 45 rpm automatic spindle adapter plus amazing Lafayette SK-124 Ultra-Compliance 2 way speaker system in mahogany or walnut (specify finish). Tuner can be added at any time for radio program reception. Less changer base. Shpg. wt., 34 lbs.

PK-600WX **Net 62.50**
PK-341W Mahogany base for changer **Net 3.95**
PK-342W Walnut base for changer **Net 4.50**
Unfinished mounting board cut for changer **Net .95**
PK-343W

LAFAYETTE RK-138 2-SPEED 4-TRACK TAPE RECORDER WITH STEREO PLAYBACK



SPECIFICATIONS:
Response: 50-10,000 cps. Wow & Flutter:
less than 0.3%. Signal-to-Noise Ratio:
40db. Outputs: Include 2 output jacks —
1) second-channel external amplifier. 2)
external speaker.

NO MONEY DOWN **99⁹⁵**

- Plays Back 4-Track Stereo & Records Dual Track Monophonically
- Two Speeds—7½ ips & 3¾ ips • Accepts Up To 7" Reel
- Digital Tape Counter • Neon Recording Level Indicator

Loaded with features, precision engineered and built to last, the new Lafayette tape recorder must be classified a best-buy by any standards. Designed for complete flexibility, the RK-138 offers both stereo and monophonic facilities. In addition to being able to record and play back 2-track monaural material, through its own speaker and amplifier, you can use the RK-138 for 4-track playback of the latest stereo tapes through your own component stereo system. Or, if you wish, use its self contained 6-watt amplifier and speakers (5" woofer, 4" tweeter with electronic crossover) as a second stereo channel in association with your monaural hi-fi system, radio, T.V., or with RK-139 matching speaker/amplifier.

Functional design utilizes a single, easy-to-use lever to select "Play-Idle-Record" positions. A special safety interlock in record position insures against accidental erasure of tapes. Fast rewind is accomplished by means of a lock-in lever control with tone and loudness adjusted by a concentric front panel control. Equipped with sensitive microphone, 7" reel of tape with 7" take up reel and patch cord. For 110-120V, 60 cycle AC operation. Shpg. wt., 24 lbs.



MADE IN U.S.A.

MATCHING AMPLIFIER SPEAKER COMBINATION FOR STEREO PLAYBACK

24⁵⁰

8 FOOT HOOK-UP CABLE

This attractive speaker/amplifier is style matched and electronically balanced to provide a second stereo channel for the RK-138 Tape Recorder described above. Contains 6-watt amplifier, 5" woofer and 4" tweeter. Supplied with 8 ft. hook up cable. Shpg. wt., 6 lbs.

RK-139W Net 24.50

LAFAYETTE VALUE COMBINATION

BOTH THE RK-138 TAPE RECORDER AND THE RK-139 AMPLIFIER/SPEAKER COMPLETELY EQUIPPED WITH EVERYTHING YOU NEED FOR FULL TAPE RECORDER ENJOYMENT

124⁴⁵

NO MONEY DOWN

A complete portable tape recorder and stereo playback system which in addition to the regularly supplied equipment contains 3 7" reels of tape, 12 tape storage cans, storage chest plus tape splicer and roll of splicing tape. Shpg. wt., 32 lbs.

RKS-16WX Net 124.45

UNPRECEDENTED TAPE RECORDER

VALUE AND PERFORMANCE!

Sensational New LAFAYETTE 2-SPEED TAPE RECORDER FEATURES 4-TRACK MONAURAL RECORD-PLAYBACK WITH 4-TRACK STEREO PLAYBACK

Contains Every Quality Tape Recorder Feature

- Two Speeds—3¾ & 7½ ips • Sensitive Hand-Held Dynamic Microphone with Swivel Desk Stand • Pause Lever Provides Instant Stop For Editing • Record —Erase Safety Switch • Fast, Rugged Shift Lever Control • Extension Speaker Jack • High Impedance Monitoring Jack • VU Meter Recording Level Indicator • Electronic Track Selector Switch • Specially Designed Heavy Duty 6x4 PM Speaker

We've tested, we've compared and Lafayette's engineers have certified this new RK-137 Tape Recorder as containing one of the finest, quality constructed, smoothest performing tape mechanisms available. And, at its remarkably low price, the RK-137 must be ranked near the top in Lafayette's long history of best buys. Engineered to provide virtually every wanted tape recorder feature, the RK-137 performs brilliantly, with facilities for 4-track monaural record/playback and 4-track stereo playback (when used with a second channel containing a tape head input such as found in a component Hi-Fi system). Controls are completely functional and are designed and arranged to make the RK-137 a genuine pleasure to use. Features include: a rugged, easy to use shift lever for fast rewind, fast forward, play and record functions; a special push-button safety record switch assures against accidental erasure of tapes; velvet-smooth volume and on-off tone controls; a pause button instantly stops tape in motion, especially useful for editing; track switch provides fast, dependable electronic switching between tape tracks 1-4 and 3-2. In addition a VU recording

level meter has been incorporated to indicate correct volume setting for recording. Speeds are adjustable from 3¾ to 7½ inches per second by means of a simple capstan adjustment. Tape economy is unmatched —from a standard 7½" 1200 ft. reel the RK-137 provides over 2 hours monaural record/playback time at 7½ ips and over 4 hours at 3¾ ips. Jacks are furnished for microphone input, High-Impedance Radio-Phono Input, Extension Speaker Output, Monitor Output and Stereo Head Output for a playback of 2nd stereo channel. Response: 50-12,000 cps at 7½ ips, 70-10,000 cps at 3¾ ips. Signal-to-Noise Ratio: 40db. Wow & Flutter: less than 0.3%. Accepts a full size 7" reel of tape. Complete in attractive vinyl covered two-tone case and equipped with a dynamic mike, cable assembly for recording from your phono or radio, stereo head input cable for stereo playback, 1200 ft. 7" Reel recording tape with a 7" take up reel. Size: 13¼Wx6¼Hx10¼"D. For 117 VAC 60 cycles operation.

RK-137WX Shpg. wt., 22 lbs. Net 89.50

ACCEPTS FULL 7" REEL OF TAPE

89.50

NO MONEY DOWN



Delivery Jan. 25, 1962

RK-137

COMPLETE WITH ACCESSORIES



KORDEXTM TRANSISTORIZED TAPE RECORDER IN ECONOMICAL SEMI-ASSEMBLED KIT FORM

- Extra Small • Fully Portable — Battery Powered • A Mere 2½ lbs. in Weight • Prewired 3 Transistor Amplifier • Half Track Recording For Maximum Tape Economy • Records/Playback Up To 20 Minutes With 3" Tape Reel • Record, Rewind, Playback, Erase


SIMPLY ASSEMBLED IN LESS THAN AN HOUR

INCLUDING: Telephone Pickup-Microphone, 3" Reel of Tape, Earphone, Empty Reel, Batteries

17.95

This is a precision full function miniature tape recorder in money saving semi-assembled kit form. In less than one hour the KorDEX Tape Recorder can be assembled — ready for operation. The amplifier comes already wired, so there is no tedious soldering to do. Complete, it weighs only 2½ lbs. and slips easily into a briefcase or handbag. This miniature recorder has been designed for ease of operation, with all controls readily accessible. Forward-rewind-erase selector on front panel. Record — playback switch and volume control appear above amplifier subchassis. In addition, microphone and earphone jacks are located on the front panel. For maximum tape economy, the KorDEX tape recorder employs a half track head. The upper half of the tape is recorded and the tape is turned over to record on the lower half — records and plays up to 20 minutes on a 300 ft. 3" reel of tape. A powerful 3 transistor precision wired amplifier is utilized to drive a 2 x 3" PM speaker. Speaker is built-in. With its attractive carrying case the KorDEX recorder is equally suitable for home, office or travel. Power is supplied by 2 standard "C" flashlight cells and one inexpensive 9 volt transistor battery. Complete with combination microphone-pickup, battery, 3" reels, 100 feet of tape and instructions. Measures 6x8¼x2¾"H. Net 17.95

KT-201 Shpg. wt., 6 lbs. Net .69
RT-20 3" Reel 300 ft. ½ mil Mylar tape. Shpg. wt., 4 oz. Net .39
BA-2 9 volt transistor battery for above. Shpg. wt., 2 oz. Net .13
BA-156 1.5V battery for above (2 req.). Shpg. wt., 2 oz. Net .13




Award-Winning TAPE RECORDER

Lafayette SCOOPS the TAPE RECORDER INDUSTRY



ONLY 49.50



Never Before Such Exceptional Quality and Value!

Voice Recording parties - dancing

- Completely Portable—Carry it Anywhere! • Two Speeds—3¾ or 7½" Per Second • Uses Standard 5" Reel. • Frequency Response 60-8,500 C.P.S.

Perfect for home, school or office. At home, the RK-400 proves ideal for parties or recording your favorite musical performance. Handy foot-proof operation has been provided by a single rugged function control (reverse, stop, play and record) and separate on/off volume control. Speeds are adjustable from 3¾" to 7½" per second by a simple capstan adjustment. At 3¾ ips the RK-400 provides up to one hour of recording time on a standard 600 ft. 5" reel of tape. Special 5" heavy duty permanent magnet speaker furnishes an exceptionally fine tonal quality. Record level indicator light facilitates recording by showing you when volume control is correctly set. Jacks are provided for microphone, phono and extension speaker (special alligator clip cord is supplied). Complete with sensitive crystal microphone. Finished in attractive scuff resistant pyrolytin material. Dimensions: 11¼x9"x7¼". For 110 volts 50-60 cycles. Shpg. wt., 20 lbs.

RK-400WX Net 49.50
LAFAYETTE ACETATE BASE RECORDING TAPE. Features noise-free reproduction, low abrasion, uniform output. 1½-mil thickness; 5" reel; 600-ft Shpg. wt., ½ lb.

lots of 5-24, Net ea. .90

lots of 1-4, Net ea. .99
lots of 25 up, Net ea. .85

NEW! LAFAYETTE 4 TRANSISTOR PORTABLE TAPE RECORDER with BUILT IN SPEAKER



NO MONEY DOWN

29.95

4-TRANSISTOR TAPE RECORDER

Complete with TELEPHONE PICK-UP, EARPHONE, PATCH CORD, MICROPHONE, 3" REEL OF TAPE, EMPTY REEL, BATTERIES

- Camera Size—Only 6"Dx8 1/4"Wx2 3/4"H.
- Weighs a Mere 2 1/2 lbs.
- Fully Transistorized
- Records and Plays Up To 20 Minutes with 1 Standard 3" Reel
- Built-in Speaker and 4-Transistor Amplifier With Push-Pull Output
- Record, Rewind, Playback and Erase
- Powered By 3 Inexpensive Batteries
- 1/2 Track Head Provides Maximum Tape Economy

This is a precision, full function miniature tape recorder perfect for home, office or travel; weighs only 2 1/2 lbs. and slips easily into a briefcase or handbag. Utilizing sophisticated transistor circuitry with 4 transistors, the RK-125AL contains its own 2" x 3" PM speaker and amplifier with push-pull output stage. Engineered for ease of operation, with all controls readily accessible from the front panel. A single function control provides for Rewind, Stop and Forward with a second control furnishing variable Volume. Play or Record functions are chosen by a simple slide switch. In addition microphone and earphone jacks are located on front panel. Designed for maximum tape economy the RK-125 employs a half track tape head—upper half is recorded first and tape is turned over to record on lower half... records and plays up to 20 minutes on a 300 ft. 1/2 mil 3 inch reel of tape.

The attractive two-tone plastic and metal case features a carrying handle and snap open top for fast, easy tape loading. Power is supplied by 2 standard 1.5v flashlight cells and one 9v transistor battery. Complete with crystal lapel microphone, magnetic earphone, batteries, 100 ft. 3" reel of tape and an empty reel. Measures only 6Dx8 1/4Wx2 3/4"H. Shpg. wt., 5 lbs.

RK-125AL	Net	29.95
RT-20 3" REEL 300 Ft. 1/2 MIL MYLAR TAPE. Shpg. wt., 1/4 lb.	Net	.69
BA-2 9V TRANSISTOR BATTERY. Shpg. wt., 2 oz.	Net	.39
BA-156 1.5V BATTERY (2 required). Shpg. wt., 2 oz.	Net	.13

Now From Sweden... LAFAYETTE presents THE OUTSTANDING NEW LUXOR MP-410A 4-TRACK STEREO TAPE RECORDER



279.00 No Money Down

Superb Swedish Craftsmanship

- 40-17,000 C.P.S. at 7 1/2 IPS
- Two & Four Track Stereo & Monaural Record & Playback
- 3 Speeds 7 1/2—3 3/4—1 7/8 IPS
- Completely Self Contained with Built-In Speakers and Amplifiers
- Professional Caliber Laminated Tape Heads
- Separate Recording Level Indicators For Each Channel

Superb performance, virtually unlimited versatility plus flawless Swedish precision construction makes this one of the finest instruments we've ever offered. A completely self contained stereo tape unit, the Luxor is equipped with its own built-in speakers and amplifiers for record playback of both stereo and monaural two and four track tapes. In addition to use as a high performance portable, the Luxor is ideal for utilization with your component stereo system as a tape deck. The unit is equipped with the finest professional quality 4-track fine-laminated record playback tape head and 4-track ferrite core erase head. A full array of monaural and stereo inputs and outputs are incorporated to provide for connection of external amplifiers, speakers, and/or sound sources. Fast forward, fast reverse and play are controlled by a single, 3 position, positive shift lever. A similar control provides for speed changes of 7 1/2, 3 3/4, and 1 7/8 inches per second. The push button record control is furnished with an interlock to prevent accidental erasure. Separate gain controls provide balance for the two built-in stereo speakers. Additional features include: magic eye recording level indicators for each channel and digital tape counter. Frequency Response: 40-17,000 cps @ 7 1/2 ips; 40-14,000 cps @ 3 3/4 ips; 80-8,000 cps @ 1 7/8 ips; Flutter & Wow: ± .09 RMS @ 7 1/2 ips; ± .18% RMS @ 3 3/4 ips; ± .25% RMS @ 1 7/8 ips. Stereo Channel Separation better than 35 db. Crosstalk separation better than 60 db. Supplied with patch cord consisting of five prong Hirschman fitting and standard RCA phono plug to assure easy use with all U.S. made components. Size: 14 1/2" L x 11 1/2" W x 6 1/2" H. Shpg. wt., 30 lbs. For 117 Volts, 60 cycle AC.

RK-477WX Net 279.00

NEW! LAFAYETTE MODEL RK-130 DELUXE DUAL SPEED TAPE RECORDER

- Two Speeds 3 3/4 and 7 1/2 I.P.S.
- Plays Both 7" and 5" Reels
- Built-in Speaker and Amplifier
- Complete with Dynamic Microphone

PLAYS BOTH
7" and
5" REELS

NO MONEY DOWN

79.95

The perfect companion for language work, voice and instrument study, personal and family use, office work—a worthwhile investment for any classroom. This rugged tape recorder plays both 7" and 5" reels at speeds of 3 3/4 and 7 1/2 inches per second. Consists of a double track, high frequency bias recording system with a frequency response range of 80 to 10,000 cycles, and a high frequency erase system. Internal amplifier provides 1.5 watts audio output to a built-in 4 3/4" speaker. An additional speaker may be plugged into the output jack. The RK-130 features simplicity of operation for quick stopping, playing, recording, fast forward winding or rewinding. Two input jacks are provided to permit simultaneous recording from a radio or record player and a microphone. Dynamic microphone is included with the unit. Both volume and tone are adjustable, and a neon tube recording level indicator is provided to facilitate correct settings. A switch allows the user to hear the playback either through the speaker or through a set of headphones (not supplied). A 7" tape reel played on both tracks will last for 120 minutes at 3 3/4 i.p.s., or for 60 minutes at 7 1/2 i.p.s. A 5" reel will last 60 minutes at 3 3/4 i.p.s., or 30 minutes at 7 1/2 i.p.s. Internal amplifier tube complement: 1—12AD7, 1—6BM8, 1—6AR5, plus 1—6X4 rectifier. For 117 VAC, 50-60 cps. Recorder dimensions: 16.4x12.4x8". Complete with 7" empty reel, dynamic microphone, patch cord, instructions, and large, removable strap for easy carrying. Shpg. wt., 28 lbs.

RK-130WX	Net	79.95
7" reel with 1200 ft. of recording tape. Shpg. wt., 1 lb.	Net	1.59



NEW! RK-116WX 4-TRACK STEREO TAPE RECORDER

- Professional Quality Laminated Record Playback Heads
- Records Sound-On-Sound
- 5-Watt Hi-Fi Quality Amplifier
- Electromatic Remote Control
- Response 40-15,000 cps
- 7 1/2 & 3 3/4 ips



149.50 NO MONEY DOWN

Performance and value make this a best buy in stereo tape recorders. Designed for stereo record and playback when used with the RK-117. Speaker/Amplifier as well as monaural record/playback when used singly. Features include: special mu-metal shielded professional type laminated record/playback heads; beltless drive mechanism, magic-eye recording level indicator, electromatic remote control plus self-contained 5 watt amplifier and speaker. Frequency Response: 40-15,000 cps at 7 1/2 ips; 40-10,000 cps at 3 3/4 ips. Wow & Flutter less than .20% at 7 1/2 ips. Controls: Dual type volume control allows adjusting recording and playback level individually for left and right channels and tone control. Accepts up to 7" reel of tape. Complete with dynamic microphone, recording patch cord, monitoring earphone and attractive vinyl covered Philippine mahogany carrying case. For 60 cycles—110-120 volts AC. Shpg. wt., 26 lbs.

RK-116WX	Net	149.50
----------	-----	--------

COMPANION RK-117WX SPEAKER/AMPLIFIER



Identical in appearance to the RK-116 Contains its own 5-watt power amplifier and speaker to operate as a second channel power amplifier and speaker for the RK-116. Also functions as a second channel recording amplifier for making live stereo recordings or recording directly from radio or stereo records. For 60 cycles 110-120 volts AC.

RK-117WX	Shpg. wt., 12 lbs.	Net	59.00
----------	--------------------	-----	-------

LAFAYETTE COMBINATION SPECIAL!

The RK-116WX and RK-117WX combined to make a complete stereo portable tape system and to save you money at this special combination price. SP-247WX Net 199.50

SAVE 9.00

SONY MODEL 101 TRANSISTORIZED DUAL-TRACK TAPE RECORDER

- 2-Speed 7 1/2 & 3 3/4 ips
- Fast Forward & Rewind
- Lightweight

Only
97.50
NO MONEY DOWN



An AC powered bantam weight dual track tape recorder which incorporates the latest design in transistor circuitry. Ideal for those who require a low cost, high fidelity reproduction, the model 101 records and plays back monophonic 2-track tape with a frequency response of 50-12,000 cps at 7 1/2 ips and 50-8,000 cps at 3 3/4 ips. Flutter & wow, less than 0.25% at 7 1/2

ips. Imposing features include: a Vu meter and volume control; inputs for mike and auxiliary units; external speaker output, tape lifters and built-in AC power supply. Plugs directly into wall outlet. Complete with 7" reel, dynamic mike, speaker and case. Size 12Wx10Dx 6 1/2"H. RK-288WX Shpg. wt., 20 lbs. Net 97.50

- 4-Track Stereo Record/Playback & Erase Heads
- 7 1/2 & 3 3/4 ips Tape Speeds
- 30-18,000 cps Response
- Full 7" Diam. Reel Capacity

High quality, precision engineering and construction at a truly economical price make this unit an unbeatable value. Provides for every tape facility—Tape heads are wired to six outputs. With your present stereo amplifier you can play back 4 track stereo tapes or by adding a recording amplifier, make your own 4-track tapes. A 4-track stereo erase head is included. Features include instantaneous selection of 7 1/2 or 3 3/4 ips tape speeds; instant stop lever; safety lock record button, automatic tape lifter and a digital counter. Freq. Response from 30-18,000 cps at 7 1/2 ips, ± 2db 50-15,000 @ 7 1/2 ips and ± 2db 50-12,000 @ 3 3/4 ips. For 110-117 VAC operation. Size: 13Wx10Dx5 1/2"H. Shpg. wt., 15 lbs.

RK-282WX	Net	87.70
Attractive Walnut Base for Sony 262-D described above.		
RK-284W	Net	12.95
Model SRA 2 Stereo Recording Amplifier designed for Sony 262-D.		
RK-287WX	Net	19.50

SONY MODEL 262-D TAPE DECK



87.70
NO MONEY DOWN

LAFAYETTE For Super Tape Recorder VALUES

AMPEX

THE FINE LINE

AMPEX 1200

MODEL 1260 Portable

2-Speed Tape Recorder



545.00

- RECORDS: 4-Track Stereophonic
4-Track Monophonic
- PLAYS: 4-Track Stereophonic
2-Track Stereophonic
4-Track Monophonic

The 1260 is a major advance in 4 track recorders. A tape deck offering superior recording facilities with preamplifier included. Separate erase, record, and playback leads of precision narrow track design eliminate reverse channel cross-talk and provide a signal-to-noise ratio comparable to previous 2-track recording. Features automatic tape take-up, built-in mixer—4 inputs; Precision recording level meter and exclusive "Auto-Set" shutoff which operates for either unattended recording or playback. Specs: Freq. Response 50-15,000 cps ± 2db at 7½ ips; 50-8,000 cps ± 2db, 3¾ ips; Flutter & Wow under 0.2% rms, 7½ ips, S-N ratio: Better than 55db at 7½ ips. Size in case 9x15x17½". For 117V AC 60 cps. Shpg. wt., 38 lbs. RK-303WX Net 545.00

AMPEX MODEL 1250 DECK

Same as Model 1260 but less case. Size: 13Wx6½Dx1¾" above top plate. RK-305WX Net 449.50

AMPEX MODEL 1270
PORTABLE RECORDER SYSTEM

645.00



- Complete 4-Track Recording and Playback Facilities
- Includes Matched Pair of Amplifier/Speakers and Case

A complete 4-track tape recorder with exclusive ampeX fine line alignment for accurate tape guidance. Contains all stereo recording and playback equipment including matched monitor speakers and amplifiers. Records and plays 4-track stereophonic and monophonic tapes and also plays back 2-track stereo at 3¾ and 7½ ips. Other features include exclusive automatic tape take-up and "Auto-Set" shut off. Precision recording level meter for accurate balancing. Other specifications include: Freq. response, 50-15,000 cps ± 2db at 7½ ips; 50-8,000 cps ± 2db at 3¾ ips. 4 inputs. S-N ratio: better than 55db at 7½ ips; better than 50db at 3¾ ips. For 117V 60 cps. Complete in scuff resistant case. Size: 9Hx25½Wx15"D. Shpg. wt., 46 lbs. Complete in scuff resistant case. Size: 9Hx25½Wx15"D. RK-304WX Net 645.00

ROBERTS "1040"
STEREO TAPE RECORDER

RECORDS NEW FM MULTIPLEX STEREOCASTS

299.50 NO MONEY DOWN



30 Reels Lafayette RT-10 1200' 7" Recording Tape

MS-474 Edital Professional Tape Splicing Kit

12 Dustproof Tape Storage Cans With Storage Chest

A compact self contained stereo tape recorder that offers the most advanced tape deck features and professional performance. Operates horizontally or vertically, through two stereo speakers and two amplifiers or through your existing components. Designed to provide 4-track stereo and monaural record/play, 2-track stereo and monaural playback, sound on sound record, and record facilities for the new FM multiplex stereo casts. Interlocking controls prevent accidental erasure of tape in rewind or fast forward. Other features include: push button function switches, professional edit lever, automatic shutoff, index counter, dual concentric volume and tone knobs with clutch controlled balance, professional VU meter with channel switch. Record inputs: 2 high impedance mic inputs, 2 high impedance high level line inputs. Playback Outputs: 2 high impedance outputs independent of volume control for connection to any stereo hi-fi amps; two 8-ohm outputs for external speakers or headphones. Frequency Response: 40-15,000 cps at 7½ ips. ± 2 db. 35-11,000 cps at 3¾ ips. ± 3 db. Signal to Noise Ratio: —42 db. Wow and Flutter: less than 0.18%. Accepts up to 7" reels. Size: 15½x10½x13¾". Shpg. wt., 30 lbs. For 105-125 volts 60 cycles AC. RK-390WX Net 299.50

COMPLETE ROBERTS TAPE RECORDER SYSTEM

324.95 YOU SAVE **32.22**
NO MONEY DOWN

Complete System consists of: Roberts 1040 2 and 4 track Complete Stereo Tape Recorder; 30 reels Lafayette RT-10 1200' 7" Recording Tape; 12 Dustproof Tape Storage Cans with Convenient Storage Chest; 1 MS-474 Edital Professional Tape Splicing Kit with instruction booklet. RKS-11WX Net 324.95

SONY STEREO HI-FI TAPE SYSTEM

MODEL CS-300 STEREO RECORDER

391.50

NO MONEY DOWN

A complete 4 and 2 track stereo tape recording and playback system with built-in stereo preamps, stereo recording amps, stereo playback monitor amps, dual stereo speakers and two dynamic microphones. Recording and playback also for 2 and 4 track monophonic tapes. 2 speeds—7½ and 3¾ ips. 2 built-in VU meters insure accurate playback and record levels. Hysteresis-synchronous drive motor. INPUTS: stereo or monophonic 2 and 4 track recording from 2 or more microphones, AM/FM stereo tuners, stereo record players and tape players. Separate level controls for microphone and auxiliary inputs provide mixing facilities for sound-on-sound recordings. Low impedance outputs to match external preamp or power amp inputs. Instant Stop Lever insures precise editing and cueing. Safety Lock Recording Button prevents accidental erasure of pre-recorded tape. Specs: Freq. Resp: 30-18,000 cps at 7½ ips; 30-13,000 cps at 3¾ ips. Signal-to-Noise Ratio 50 db or more per channel. Low distortion. Size: 17x14x8" high. 117V, 60 cps AC. Includes carrying case. Shpg. wt., 42 lbs. RK-280WX Net 391.50

Model DK-300 Same as CS-300 but without carrying case, speakers, and microphones. Shpg. wt., 35 lbs. RK-281WX Net 342.51

COMPLETE CS-300 TAPE RECORDER SYSTEM

407.95 YOU SAVE **56.95**
NO MONEY DOWN

Complete System consists of: Sony CS-300 Stereo Tape Recorder with carrying case and 2 dynamic mikes; 1 ML-120 professional bulk tape eraser; 12 reels Lafayette RT-13 2400 ft., 7" Mylar recording tape; 12 Dustproof Tape Storage Cans with convenient Storage Chest and the Lafayette MS-474 Edital Professional Splicing Kit. RSK-13WX Net 407.95



12 Reels RT-13 2400 Ft. 7" Mylar Recording Tape

MS-474 Edital Professional Tape Splicing Kit

Carrying Case

ML-120 Professional Tape Eraser

12 Dustproof Tape Storage Cans With Storage Chest

SONY MODEL 262-SL 4-TRACK STEREO RECORDER

195.50

NO MONEY DOWN

A stereo tape recorder with 4 and 2 track stereo playback plus 4-track monaural record facilities. Built-in monophonic preamp, recording amp and monitor power amp. Also second channel playback preamp. Sound-on-Sound recording for language and music training. Instantaneous selection of 7½ or 3¾ ips tape speed. Features include record level indicator, tone control level control for record and playback digital tape counter and safety lock record button. Inputs facilities furnished for Mic, Radio/Aux with outputs for Ext. Speaker and Preamp. Freq. Resp.: ± 2db 50-15,000 at 7½ ips. With portable case, earphone, monitor speaker, dynamic microphone and connecting leads. RK-283WX Net 195.50

COMPLETE TAPE SYSTEM

207.95 YOU SAVE **31.12**
NO MONEY DOWN

System consists of Sony Model 262-SL, 2 Speed Recorder with case, earphone and dynamic mike; 20 reels of Lafayette RT-10 1200' 7" Recording Tape; 12 dustproof tape storage cans with convenient storage chest; Lafayette MS-474 Edital Professional Splicing Kit. RKS-14WX Net 207.95



MS-474 Edital Professional Tape Splicing Kit

12 Dustproof Tape Storage Cans With Storage Chest

20 Reels Lafayette RT-10 1200' 7" Recording Tape

NEW! RK-119WX PROFESSIONAL STEREO TAPE RECORDER

349.50



- Contains 3 Separate Heads—Stereo Erase, 4-Track Stereo Record, 2-Track & 4-Track Stereo Playback
- Sound-on-Sound Recording
- Push-Button Controls
- Individual Tone & Volume Controls For Each Channel
- 3 Speeds—1% ips, 3¾ ips, & 7½ ips
- Two 7" Speakers For Stereo

One of the finest tape recorders Lafayette has ever offered. A completely self contained portable stereo high fidelity music recording and playback system which may be used with its own speakers and amplifiers or through the amplifiers and speakers of your present music system. Features include: individual recording level controls with VU recording level meters for each channel, separate tone and volume controls for each channel, master volume

control and digital tape counter. Mechanism automatically stops at reel end. Interlocked recording controls prevent accidental erasure. Specifications: Frequency Response: 7½ ips—30-20,000 cps, 3¾ ips—30-15,000 cps, 1¾ ips—50-8,000 cps; Signal to noise ratio: Better than 60 db. Flutter and wow less than .15% at 7½ ips. Supplied with the following accessories: 2 professional type sensitive dynamic microphones with stands, recording datch-cords, 1 outchord for sound-on-sound recording, 1 speaker ext. patchcord for right channel ext. speaker, 1 7" empty reel, 1" roll of splicing tape. The attractively styled vinyl covered carrying case is ruggedly constructed of Philippine mahogany. 19½Wx11Hx7"D. Shpg. wt., 50 lbs. Imported. RK-119WX Net 349.50

NEW! VIKING MODEL 86 "STEREO COMPACT" TAPE DECKS

297.50

NO MONEY DOWN

Renown Viking ¼ transport mechanism has been combined with a stereo/playback preamplifier of advanced design. System recording range of 30-16,000 cps is achieved with little roll-off. For minimum spurious noise when recording FM multiplex transmissions the 86 Compact employs a sharp cut-off filter to prevent beating of bias frequency with 38 Kc multiplex carrier frequency. Other Features: "Erase-Protek" recording interlock, monaural-stereo selector switch; automatic equalization for both 3¾ and 7½ ips speeds; variable playback preamplification and "sound on sound" function without patching. Incorporates separate calibrated VU meters, digital tape counter and head shift control. Frequency response 30-16,000 cps ± 3 db. NAB standard equalization for 3¾ and 7½ ips. Microphone and tape head inputs on front panel; high level input on rear panel. Stereo in-line heads of laminated core construction. Multiplex heterodyne trap attenuates 12 db/octave above 20 Kc. Flutter and wow less than 0.2%. Viking Flutter — Filter Capstan belt drive. Size: 13x13x9½" deep. (fits 12½x12½" opening). Requires 110-115 v. 60 cycle AC @ 125 watts.

"STEREO-COMPACT" RMQ. Records, erases and plays back ¼ track stereo and monaural plus ¼ & ½ track stereo playback. Anodized Aluminum. Shpg. wt., 25 lbs. RK-258WX Net 297.50

"STEREO-COMPACT" ESQ. Records, erases and plays back ½ track stereo and monaural plus ¼ & ½ track stereo playback. Anodized Aluminum. Shpg. wt., 25 lbs. RK-257WX Net 297.50

COMPLETE TAPE RECORDER SYSTEM

327.95 YOU SAVE **26.60**
NO MONEY DOWN

System includes Viking 86 Stereo Compact Model RMQ; New Lafayette PA-263 Stereo Dynamic Microphone with desk base and cable; 17 reels of RT-10 1200 ft., 7 inch Recording Tape; 12 dustproof Tape Storage Cans with convenient chest storage and MS-474 Edital Professional Tape Splicing Kit. RNS-15WX Net 327.95



Records Sound-On-Sound

PA-263 Stereo Dynamic Microphone

17 Reels Lafayette RT-10 1200' 7" Recording Tape

MS-474 Edital Professional Tape Splicing Kit

12 Dustproof Tape Storage Cans With Storage Chest



LAFAYETTE TOP QUALITY RECORDING TAPE

LAFAYETTE RECORDING TAPES

LAFAYETTE QUALITY IS BACKED BY OUR MONEY-BACK GUARANTEE



LAFAYETTE'S FAMOUS MONEY-BACK GUARANTEE

Lafayette's tape is made by outstanding nationally known manufacturers. It is first quality, splice free, red oxide coated, with full frequency response, uniform output and no "drop-outs". Resistant to moisture, heat, cold and abrasion. We guarantee absolute satisfaction or your money back. If you do not find it equal to tapes costing up to twice the price, if for any reason you are dissatisfied, return the tape in 30 days and we will refund your money. You are the sole judge.

LAFAYETTE MYLAR BASE RECORDING TAPE

AS LOW AS **1.42** RT-19 900 ft. 25 & up

Mylar base is especially strong, durable and break resistant, and is virtually impervious to heat, cold or humidity. All in clear plastic reels, individually boxed.

Stock No.	Feet	Reel	Mils	WL Lbs.	1-4	5-24	25 Up
RT-19	900	5"	1	3/4	1.75	1.58	1.42
RT-12	1800	7"	1	1 1/4	2.50	2.25	2.13
RT-13	2400	7"	1/2	1 1/4	3.69	3.39	3.22

Tensitized Mylar Prestretched, super-strong mylar base.

Stock No.	Feet	Reel	Mils	WL Lbs.	1-4	5-24	25 Up
RT-16	2400	7"	3/4	1 1/2	4.95	4.45	4.23

AS LOW AS **.63**

YOU BE THE JUDGE! LAFAYETTE ACETATE BASE RECORDING TAPE

AS LOW AS **85¢** RT-17 600 ft. 25 & up

Acetate base magnetic recording tape with uniform standard red oxide coating provides wide range high fidelity response over the audio spectrum. Features noise free reproduction, low abrasion and uniform output. In 1 mil and 1 1/2 mil thickness.

Stock No.	Feet	Reel	Mils	WL Lbs.	1-4	5-24	25 Up
RT-17	600	5"	1 1/2	1/2	.99	.90	.85
RT-18	900	5"	1	3/4	1.35	1.20	1.08
RT-10	1200	7"	1 1/2	1	1.59	1.49	1.35
RT-11	1800	7"	1	1 1/4	1.98	1.88	1.79

LAFAYETTE BULK TAPE ERASER AND DEMAGNETIZER

PROFESSIONAL MODEL

- Erases 1/4" Tapes in One Operation—No Reversing
- For 3", 5", 7" or 10 1/2" Reels
- Completely Erases Tapes
- Two Erasing Coils
- Erases up to 1" Tape

18.95



A carefully designed and precisely manufactured tape "degausser" for complete erasing of tapes. Just place the tape reel on spindle of demagnetizer, slowly rotate 2 or 3 turns, take off, and that's all. Reduce tape hiss to the level of new "virgin" tape. Two completely separate coils are used for doubly-effective erasures, even of large, 10 1/2" reels. Will erase 1" wide tape. An extra powerful unit for heavy-duty use—draws over 9 amperes. Can be used to demagnetize tape, magnetically stripped film, plus tools and watches. Has a heavy, custom finished case, a rugged non-magnetic top, heavy duty on-off switch and power cord. Has built-in fuse. Pilot light prevents accidentally leaving it turned on. Size 6 1/4 x 7 7/8 x 3 1/2". Shpg. wt., 14 lbs.

ML-120 Net 18.95

STANDARD MODEL

- Takes Reels Up To 10 1/2"
- Reduces Noise Level
- Top Value

12.50



A bulk tape demagnetizer that erases existing recorded signals and noise from magnetic tapes quickly and efficiently. Also capable of demagnetizing metal parts and work tools. Ideal for the recording enthusiast desiring clean, noise-free tapes. Simply rotate reel of tape several turns over unit, turn over and repeat once. Has two spindle positions: Inner position for tape reel sizes up to 7" in diameter, and the outer one for 10 1/2" reels. Push button energizes the coil, and a pilot light installed on top of the unit indicates unit in operation. Non-magnetic bakelite plate for tape reel rest. One powerful coil is used for effective erasure of all quarter-inch tapes. Current consumption—5 amps. Heavy duty, rugged gauge metal case. Attractive finish. For 105-125 volts, 60 cycles. Size 7 1/2 x 4 3/4 x 3 1/2" Shpg. wt., 9 lbs.

ML-176 Net 12.50

BUY 12 TWIST LOCK TAPE CANS

NEW! FOR ONLY **4.95**



AND GET STORAGE CHEST FREE!

12 dust-free, moisture-proof unbreakable styrene tape cans in storage chest. Can has foolproof twist lock feature and is ribbed for convenient stacking. Center locking stud prevents reel movement on all 7" reels and most 3" and 5" reels. Shpg. wt., 6 lbs.

ML-302 Net 4.95

TWIST LOCK CANS ONLY ML-151 Lots of 6 ea. .45; Single ea. .49

NEW! Lafayette RECORD, PLAYBACK and ERASE HEADS

3.95 per set

- Ideal for Experimenters
- Half-Track Recording Playback and Erase



A Lafayette special—ideal for the experimenter interested in tape recorders. Recording head has impedance of 9K ohm at 1,000 cps, DC resistance 130 ohms, reproduction level—40, recording at—10db. Bias frequency 30KC, bias 10MA. Frequency 60-12,000 cps ± 5db. SM ratio—40db. Erasing head: DC resistance 10 ohms, erasing current 15-20 milliam, AC bias, DC erase systems. Record head 7/8 x 3/4 x 3/4"; erase head 3/8 x 1 x 3/8". Shpg. wt., 8 oz.

F-687 Net 3.95

LAFAYETTE TAPE HEAD DEMAGNETIZER

3.95 REMOVABLE POLEPIECES EXTRA CONVENIENT



Lafayette Tape Head Demagnetizer uses removable polepieces. Three complete sets are furnished: straight, 45° and 90° (right angle), permitting quick and easy use with any tape head. Far from being a luxury, a tape head demagnetizer is necessary for best tape recorder performance. Although unmagnetized when new, tape heads gradually become magnetized by sharp switching pulses occurring while switching the recorder from play to record or vice versa. The solution is to use a demagnetizer to remove this permanent magnetism from the head, thus reducing the noise level. Periodic head demagnetization is required for all tape recorders to insure optimum signal-to-noise ratio. Now Lafayette enables anyone with even the most modest budget to perform this necessary demagnetization with a minimum of effort. For 110 volts 60 cycles. Shpg. wt., 1 lb.

PK-238 Tape Head Demagnetizer 3.95

CLEAR PLASTIC REELS

.26



IN LOTS OF 6

Individually boxed plastic reels for recording tape. Av. shpg. wt., 4 oz. singly.

MS-692 5" reel. In lots of 6, Ea. .26 Singly, Ea. .29

MS-267. 7" reel. In lots of 6, Ea. .38 Singly, Ea. .45

NEW! STROB-LOOP RECORDER TEST TAPE

CHECKS: SPEED • TIMING • WOW • FLUTTER Accurate within 1/10 of One Percent!

For 7.5 I.P.S. Shpg. wt., 6 oz. Net **.98**



MS-914

REEL LOCKS Set of Two **59¢**

Holds tape recorder reel in place by locking spindle to reel. Especially useful if recorder is in vertical position. Will not interfere with normal operation of reels. Easily removable. Shpg. wt., 6 oz.

MS-564 Set of two 59

TAPE CLEANER

1.49



Simple, unique recorder head cleaner. Tape is impregnated with special formula cleaner. Simply run through like regular roll of tape. Entire job done in 2 minutes. Can be reused many times. 100' roll on plastic reel. Shpg. wt., 8 oz.

PK-283 Net 1.49

NEW TELEPHONE PICKUP COIL



1.89

This telephone pick-up coil is designed to feed into the microphone input of either a tape recorder or any high gain amplifier. The pick up can be easily attached to the telephone by the use of a rubber suction type attachment. The coil is electrostatically shielded to minimize hum pick-up. When properly positioned on telephone handset, the output of this device is more adequate for a fully modulated tape recording. Shpg. wt., 6 oz.


MS-474 Net 1.89

METAL TAPE STORAGE CHEST



STANDARD CASE: Sturdy all steel carrying case. Holds 12 7" or 5" reels and cans. Twin snap locks for positive closure; perfect portability. Guards against exposure and accidental erase. Platinum gray hammerhead finish. Metal separators between reels. Includes index cords. Shpg. wt., 5 lbs.

ML-60 Net 2.99



(A) ROBINS "GIBSON GIRL" SPLICER

Cuts 2 rounded indentations in the tape splice, leaving the edges of the tape which contact parts of the recorder entirely free of adhesive. Adhesive deposited on initial parts of recorder is a frequent cause of wow and flutter. As little as 1/4" tape need be removed. Shpg. wt., 1/2 lb.

MS-288 Net 6.25

MS-473 Replacement Blade 98

(B) EDITALL TAPE EDITING KIT

This kit has all the equipment required to execute a complete editing job on a professional basis. The cutting block supplied is simple to operate but is precise in its application; made of duraluminum precisely machined and polished (makes straight or diagonal cut). All accessories such as grease pencil, blades, splicing tape (66 ft. roll of 1/4") supplied. Comes with instruction booklet—in a smart metal case. Shpg. wt., 1 lb.

MS-474 EDITALL KIT Net 8.82



(B) ROBINS SILICONE TAPE CLOTH

Cleans, lubricates and protects by depositing a microscopic film of silicone on the tape. Reduces head wear, tape wear, tape squeal and chatter. Eliminates "grime distortion". Washable. Shpg. wt., 5 oz.

MS-375 TAPE CLOTH Net .73

(C) ADHESIVE REEL LABELS

Convenient press-on adhesive labels for positive identification of tape reels. Easy to apply or remove. Shpg. wt., 5 oz.

MS-292 Pkg. of 30 .13



RCA TAPE CHESTS

Durable, chipboard storage cases covered in gold stamped simulated leather. Hold 5 reels in separate compartments. Type 501C1 for 5" Reels, size 5 5/8 x 4 3/4 x 5 3/8"; type 502C1 for 7" Reels, size 7 5/8 x 4 3/4 x 5 3/8". Shpg. wt., 1/2 lb.

RT-271 Type 501C1 for 5" Reels Net .75

RT-272 Type 502C1 for 7" Reels Net .82

RCA SPLICING TAPES

Pressure sensitive for editing and splicing. Shpg. wt., 3 oz.

RT-266 Type 515C1 1/4" x 100" Net .17

RT-267 Type 511C1 1/2" x 100" Net .22

RT-268 Type 512C1 1/2" x 150" Net .30

RT-269 Type 513C1 3/4" x 100" Net .32

RT-270 Type 514C1 3/4" x 150" Net .39

MAGNETIC TAPE SPLICER

1.47

- Cut Both Ends Simultaneously
- Easy to Operate
- Durable & Sturdy

An excellent accessory that splices tapes accurately and eliminates joint noise. Both ends cut simultaneously. Nickel plated brass finish. Shpg. wt., 1 lb.

MS-289 Net 1.47

METAL STORAGE CANS



Your best protection for valuable recorded tapes and movie film. Cans are ribbed for easy storage. Precision fit makes opening and closing easy. Attractively finished in grey. 3 sizes to choose from to fit any size reel. Av. shpg. wt., 8 ozs.

ML-154 3" Can. lots of 6, Ea. .18 Singly, Ea. .20

ML-155 5" Can. lots of 6, Ea. .27 Singly, Ea. .30

ML-61 7" Can. lots of 6, Ea. .36 Singly, Ea. .39



(A) ROBINS TAPE THREADER

No more awkward fumbling while threading a reel. Just place the tape against the reel, slip your Robins threader over the capstan shaft and over the empty reel. Tip of threader holds the tape firmly against the reel. A few turns on the crank and you're ready to play or record. Saves time and tape. Shpg. wt., 2 oz.

MS-222 Net .79

(B) TAPE THREADER

For quick and simple tape reel threading. Simply clip on and start recorder. Works on all size reels. Handsome chrome finish. In plastic case. Shpg. wt., 6 oz.

MS-374 TAPE THREADER List 2.50 Net 1.47



SAVE WITH EXCLUSIVE LAFAYETTE HI-FI

now from Great Britain... **LAFAYETTE**
PERFORMANCE, DESIGN & VALUE


THE LAFAYETTE SOVEREIGN 12 . . .

3-Way High Performance

High-Fidelity Speaker



49⁵⁰
NO MONEY DOWN



LAFAYETTE'S FINEST 12" SPEAKER

Constructed by master English craftsmen to Lafayette's rigid specifications, the "Lafayette SK-210 Sovereign 12" must be considered among the very finest 12" speakers available. Engineered to satisfy the most discriminating listener, the SK-210 achieves full 3 speaker performance through its advanced triaxial design. Woofer, midrange radiator and tweeter are all axially mounted within a single rigid, unitized die cast frame, to provide an integrated, efficient wide range speaker system. Construction features incorporate a 3 inch voice coil with an exclusive "Rigidflex" cone-bonding and cone-edge treatment process to form a virtually free-edged cone suspen-


sion. All irregularities of the audible frequency spectrum are smoothed out with standing waves and surround resonances eliminated. High efficiency and low distortion are further assured by use of a specially designed 2 1/4 lb. ceramic magnet. The quality of the Sovereign 12" is immediately evident in its uncompromising performance. Frequency response is 30-20,000 cps with a free-air woofer cone resonance of 35 cps. Bass response is tight and solid without boom or hangover to achieve a phenomenal realism. At 2000 cps, frequencies are channeled into a stiff-coned mid-frequency radiator by means of a smooth mechanical

crossover. High frequencies are reproduced with a silkiness and naturalness to beyond the limits of human hearing by means of a compression driver tweeter. This superb new tweeter incorporates a rigid, die cast, flared, hyperelliptical horn, a 1" diameter aluminum voice coil and diaphragm in a self-aligning assembly with air chamber and phase equalizer. A built in crossover allows the tweeter to take over at 5,000 cps and is provided with a high-frequency L-pad level control with attractive escutcheon and knob. Shpg. wt., 15 lbs. Recommended with Eliploflex® enclosures. SK-210 Net 49.50

NOW FROM LAFAYETTE... THE "BIG 8"

34.95

NO MONEY DOWN



ONLY 8" SPEAKER/WITH
 1 3/4 LB. MAGNET

THE LAFAYETTE SK-212... A new 8-Inch 3-Way High-Fidelity Speaker with Performance and Capabilities of a 12-Inch Speaker

ONLY 8", BUT LOOK AT THESE SPECIFICATIONS AND PERFORMANCE:

- FREQUENCY RESPONSE: 35-20,000 CPS
- CONE RESONANCE: 45 CPS
- MAGNET: 1 3/4 LB. ALCOMAX
- VOICE COIL: 3" DIAM.
- FLUX DENSITY: 175,000 GAUSS
- IMPEDANCE: 16-OHMS
- POWER HANDLING CAPACITY: 25-WATTS
- 2,000 CPS MECHANICAL CROSSOVER 5000 CPS ELECTRONIC
- CROSSOVER WITH BUILT-IN BRILLIANCE CONTROL
- SPECIALLY DEVELOPED "RIGIDFLEX" FREE EDGE CONE SUSPENSION
- DIE-CAST FRAME
- NEW COMPRESSION-DRIVER TWEETER

LAFAYETTE'S "BIG 8"—The remarkable quality and performance of this new speaker provide it with the largest 8" of sound we've ever heard! With almost uncanny ability, the SK-212 easily re-creates the entire musical spectrum from 35 to 40,000 cps; achieving a standard of natural balance distortionless performance and superb transient response normally associated with larger costlier speakers. Every musical tone is there—from powerful orchestral passages and deepest organ tones to the most delicate of solos. Precision engineered to meet Lafayette's uncompromising specifications and constructed by master English craftsmen, the SK-212 incorporates the design and construction features you'd expect to find in the finest speakers. This excellence of design is best demonstrated by its 3 inch voice coil, 1 3/4 lb. Alcomax magnet, and special "rigidflex" free edge cone suspension. Woofer, midrange radiator and tweeter are axially mounted to provide wide range speaker performance. A mechanical crossover separates bass and midrange frequencies at 2,000 cycles while 5,000 cycle electrical crossover provides a smooth transition from midrange to a newly developed compression driver tweeter. A high frequency level control allows matching of sound to individual taste and room acoustics. Recommended with Eliploflex® enclosures. SK-212WX Shpg. wt., 11 1/2 lbs. Net 34.95

LAFAYETTE SK-130 8" WIDE-RANGE HI-FI SPEAKER

Check These Phenomenal Specifications

- ✓ Frequency Response: 40-18,000 cps
- ✓ Magnet Weight: 1 lb. High Efficiency Alcomax Magnet
- ✓ Flux Density: 13,500 Maxwells
- ✓ Voice Coil: 1 Inch
- ✓ Power Handling Capacity: 15 Watts
- ✓ Impedance: 16 Ohms
- ✓ Cone Resonance: 55 cps



NEW!

12⁹⁵

ASTONISHING FIDELITY from a speaker of this size and modest price. Designed and finished with typical British craftsmanship, the SK-130 features an especially designed hyperbolic cone with a plastic surround suspension for wide compliance performance. Bass response is robust and full bodied, while the mid-range and highs are virtually transparent, with never a trace of shrillness or harshness.

The excellent wide-range response of the SK-130 make it ideal for stereo when used in pairs or perfect for use as a high quality extension speaker. Overall Diam. 8 1/2" x 4" Deep. Baffle cut-out 7 1/2". Rigid vibration-free frame is equipped with screw type terminals. See Eliploflex® enclosures recommended for this speaker elsewhere in catalog. SK-130 Shpg. wt., 3 lbs. Net 12.95



ROYAL DANISH 12" DUAL CONE SPEAKER


• HIGH FLUX DENSITY

7.95

Lafayette brings you this fine imported high fidelity speaker at a fraction of the price you would expect to pay for so much quality. Two cones are mounted on a single axis, and provide remarkable wide range frequency response from 45 to 14,000 cps. Reproduction of program material is exceptionally lifelike throughout the entire range. An exclusive, special formula cone rim treatment eliminates cone rim resonance and distortion. Also, the damping effect improves transient response and prevents "hangover." Overall depth, 5 1/4". Completely enclosed. 1" diameter voice coil with an impedance of 6 ohms. Shpg. wt., 6 lbs. SK-86. 12" Dual Cone Hi-Fi Speaker Net 7.95

the Revolutionary LAFAYETTE

Sphericon



SK-146

22⁵⁰

HIGH FREQUENCY SUPER TWEETER

- Frequency response from 3,000 cps to beyond 40,000 cps
- Uniform dispersion over 120 degrees in all directions
- High-sensitivity allows use with any 4-16 ohm speaker
- Requires no high voltage or power supply
- Built-in 3,000 cycle crossover network

Achieve unequalled brilliance and musical warmth from your present speaker system or the system you're now planning. The Lafayette's Sphericon is an entirely new concept in tweeter design. Equipped with a built-in 3,000 cycle crossover network and featuring a specially designed domed phenolic diaphragm with spherical diffractor. The Sphericon produces a virtually linear response from 3,000 cps to beyond 40,000 cps, ± 2 db. to 22,000 cps. High frequencies are radiated in a 120° pattern in all directions, vertically as well as horizontally—with absolutely no trace of stridency or harshness. Unlike electrostatic tweeters the "Sphericon" is highly efficient and may easily be matched with any speaker or speaker systems... especially the low efficiency high compliance type. Precise matching of the "Sphericon" with todays low and medium efficiency speaker is accomplished by means of a special built-in attenuator designed not to affect or lower the efficiency of the woofer. As a result less amplification is needed assuring lower distortion. Power capacity is 30 watts. May be employed with any 4-16 ohm speaker. Beautifully styled with an acoustically designed gold anodized grill set in a sturdy satin black plastic case. Dimensions: 9x4 1/2x2 1/2". SK-146 Shpg. wt., 4 lbs. Net 22.50



HK-3

CONE TYPE METAL-CASED HI-FI TWEETER

5.95

- FREQUENCY RESPONSE 2,000-16,000 CPS
- HANDLES 20 WATTS • IMPORTED TO SAVE YOU MONEY

Without doubt one of the finest cone type high frequency tweeters we have ever tested, and is exceeded in performance only by diaphragm type tweeters. It is particularly efficient in the higher end of the audio spectrum where ordinary cone tweeters tend to lose clarity and volume. With this tweeter added to your present system, you will be able to hear all the fine transients and high notes of the upper register as they were actually recorded. Entirely enclosed in metal case with base for standing by itself, or mounting on a flat surface. Bracket is supplied for mounting on panel or in cabinet. Requires crossover network such as Lafayette LN-2 Diameter 3". Depth 2 1/8". Voice coil impedance 8-16 ohms. HK-3 Hi-Fi Tweeter—Shpg. wt., 4 lbs. Net 5.95



SK-121
 SK-122

NEW! METAL CASED TWEETER

2.95

- FREQUENCY RESPONSE 3,000-16,000 CPS
- HANDLES 20 WATTS OF POWER • CHOICE OF 8 OR 16 OHM IMPEDANCE

The modest price of this tweeter gives no indication as to its high quality. Smooth, silky reproduction of the high frequencies along with an even sound dispersion is insured by the use of the round cone. The tweeter assembly is protected by a heavy wire mesh screen and completely encased in an attractive Satin Gold metal. As a result of the rear casing on the tweeter speaker interaction between speakers has been eliminated allowing for the placement of the tweeter in the same enclosure with the woofer and mid-range speakers. Supplied with sturdy attached mounting stand and 2 1/2" hook-up cord. Size 2 7/8" diam. x 2" deep. SK-121 8 ohm Tweeter. Shpg. wt., 2 1/2 lbs. SK-122 16 ohm Tweeter

SPEAKER AND ENCLOSURE COMBINATIONS

NEW! 12" WIDE-RANGE HI-POWER HI-FI SPEAKER

- 21.5 OZ. ALNICO 5 MAGNET • RATED AT 30 WATTS • RESPONSE 20-14,000 CPS • SEAMLESS CONE • SPECIAL HEAVY-DUTY CONSTRUCTION

ONLY 14.95



Incorporating a full 21.5 oz. magnet of high-flux density Alnico 5, this new wide-range 12" PM high fidelity speaker is rated at 30 watts and is excellent for use with any hi-fi system. With proper baffling, frequency response is 20 to 14,000 cps. Special constructional features include a 1 1/2" voice coil, epoxy bonding of the voice coil to the seamless cone; completely dust-proof enclosed magnet structure; fibre-to-metal bonds made with heat under extreme pressure; heavy cast-metal frame; metal parts heavily cadmium-plated, with exposed surfaces covered with a handsome mar-resistant hammerloid finish. Voice coil impedance 8 ohms. Outside diameter 12 3/4", mounting diameter 11 3/4", depth 6 3/4". Color-coded 4-way binding-post terminals.

SK-137 Shpg. wt., 7 lbs. Net 14.95

NOW FROM LAFAYETTE ADD-ON REVERBERATION



Works With Phono, TV Radio or Tape Recorder

Converts Your
Living Room Sound
to that of Concert
Hall Grandeur

69.95

- Marvelous For Existing Monaural Systems
- Enriches Your Present Stereo Systems
- Adds A Delightful Dimension to Sound Without Affecting Fidelity
- Completely Self-Contained, Has Own Amplifier and Speaker

Changes the acoustic dimensions of your room. A self-contained reverberation speaker-and-amplifier with its own internal power supply, that hooks into any existing stereo or monophone component sound system, FM and AM radio, Tape Recorder, T.V. set, or Electric Organ. More than just a simple "echo device," the "Reverb-Control" takes part of the original signal from a speaker system and feeds this signal through a carefully tuned device which delays the sound for 1/30th of a second. This delayed sound blends with the original sound to add acoustic dimension to your room. Uses 8" Dual diameter speaker. Power output of amplifier 3 watts R.M.S. (will work excellently with systems having up to 60 watt amplifiers). 2 sets of inputs—high level and low level (left and right)—use only one input for monaural. Comes supplied with 2 cables, 15' each with standard phono plugs on one end. Power requirement 110V to 120V AC. Cabinet size 10x20x10 1/2" deep. Available in walnut and mahogany. Shpg. wt., 22 lbs. SK-204WX Walnut Finish Net 69.95 SK-205WX Mahogany Finish Net 69.95

SENSATIONAL SPEAKER SYSTEM

JENSEN speakers + UNIVERSAL WOODCRAFTERS cabinets + LAFAYETTE low prices



38.95

- Heavy 7-Ply Furniture Veneer Cabinets
- Fiberglass-loaded Cabinet for Better Bass Response
- Jensen 12" Woofer, 8" Midrange Driver, 3 1/2" Enclosed Tweeter

Now you can get unparalleled speaker performance at a low, low Lafayette price—the most outstanding value of its kind in the industry. The Uni-Voice hi-fi speaker system is a thrilling blend of fully integrated, unified 3-speaker systems engineered by Jensen with specially developed Jensen components, with cabinetry by Universal Woodcrafters. Contains special 12" woofer; 8" midrange driver independently pneumatically damped in its own hermetically enclosed acoustic surroundings, completely separated from woofer cavity; 3 1/2" fully enclosed, independently baffled tweeter. Woofer electric crossover at 600 cycles, midrange electric crossover at 2000 cycles. Impedance 8 ohms. Response: 35-18,000 cycles. MODEL UV-30. Bookshelf enclosure finished on 4 sides. Speaker grille completely framed with brass inlay. 24Wx14 1/2 Hx13" D. SK-185WX Walnut finish. Shpg. wt., 32 lbs. Net 38.95



Tweeter with baffle

Polyester resin treated tweeter edge



TWEETER Baffle

CONICAL STIFFENER

CROSSOVER NETWORK

Lafayette presents


THE NEW ULTRA-LINEAR SK-128™ full range 8 inch

biaxial speaker with newly developed
tweeter baffle design.

19⁵⁰

- 20 TO 20,000 CPS (40 TO 16,000 CPS ± 3 DB) ■ HIGH EFFICIENCY
- HIGH EXCURSION WOOFER WITH UNIQUE "CONICAL STIFFENER"
- HANDLES HEAVY BASS PASSAGES WITHOUT "DOUBLING"

*Eccentric Tweeter Mounting & Unique Elliptical Baffle
Completely Eliminates Interaction Between Woofer & Tweeter*



The SK-128 combines the best features of a multiple speaker system in one compact and economical unit. It offers full, even coverage of the entire audible range, with no distortion or coloration to mar your listening pleasure. The specially treated woofer cone has a unique "Conical Stiffener" at the apex which, coupled with its high compliance, enables the cone to operate in a piston-like manner—delivering a clean, powerful bass response. The 2-inch tweeter has its own voice coil and magnetic field. Special treatment of cone and cone edge provides even distribution of the high frequencies, with no peaks or resonances. The unusual off-center mounting of the tweeter and its elliptical baffle minimizes interaction between tweeter and woofer and insures an overall response free of intermodulation distortion. Electrical crossover from the woofer cone to the tweeter unit is provided by a built-in network. An adjustable brilliance control permits matching of sound to room acoustics. Efficiency of the speaker is such that it will operate from any amplifier with an output of 1 watt or more. Installed in a bass-reflex type of enclosure, it performs outstandingly, and is recommended for all high-quality music systems—whether monaural or stereophonic. SPECIFICATIONS: Overall Response: 20-20,000 cps (40-16,000 cps ± 3 db). Free air Resonance: 45-65 cps. Impedance: 8 ohms. Power Rating: 20 watts. Integrated Program Material. Crossover: 2,500 cps. Overall Diam. 8 3/4". Overall Depth: 5 1/2". Baffle cut-out: 7 1/2". Rugged, vibration-free speaker frame with color-coded screw-type terminals for quick, easy connection of amplifier leads. Shpg. wt., 5 lbs. SK-128 Full Range 8" Biaxial Speaker.....Net 19.50

LAFAYETTE MINI-DUCT BOOKSHELF ENCLOSURE WITH SK-128 8" ULTRA-LINEAR SPEAKER

The perfect answer for those who demand realistic sound reproduction even where space is limited. Two of these systems are ideal for stereo. Shpg. wt., 28 lbs.

SY-343WX Speaker System in Walnut	Net 39.50
SY-344WX Speaker System in Mahogany	Net 39.50
SY-345WX Speaker System in Blonde	Net 39.50
SY-346WX Speaker System in Oiled Walnut	Net 39.50
SY-347WX Speaker System in Unfinished Birch	Net 37.50

SK-128 SPEAKER & MINI-DUCT FINISHED ON 4 SIDES

SY-403WX MAHOGANY	NET 41.95
SY-404WX WALNUT	NET 41.95




LAFAYETTE MINI-DUCT™ BOOKSHELF ENCLOSURE WITH SK-212 3-WAY SPEAKER

A perfect match: The "Mini-Duct" enclosure and the remarkable Lafayette SK-212 3-way High Fidelity speaker. Reproduces the entire audio spectrum with a marvelous smoothness. Styled in attractive furniture finishes. Shpg. wt., 35 1/4 lbs.

SK-212 SPEAKER AND MINIDUCT ENCLOSURE FINISHED ON 3 SIDES	
SY-431WX UNFINISHED	Net 52.45
SY-432WX MAHOGANY	Net 54.95
SY-433WX WALNUT	Net 54.95
SY-434WX OILED WALNUT	Net 54.95
SY-435WX BLONDE	Net 54.95

SK-212 SPEAKER AND MINI-DUCT FINISHED ON ALL 4 SIDES

SY-436WX MAHOGANY	Net 56.40
SY-437WX WALNUT	Net 56.40



FAMOUS LAFAYETTE MINI-DUCT™ BOOKSHELF ENCLOSURE WITH SK-130 8" WIDE-RANGE SPEAKER

As Low As **33⁹⁵**

A combination that rivals the performance of much larger speaker systems. This fine enclosure assures optimum performance from the SK-130. Only 23" W x 11 1/2" H x 11 1/8" D—ideal for mounting in a bookcase or record shelf. Finished on 3 sides in a variety of fine furniture finishes. Shpg. wt., 27 lbs.

SK-130 SPEAKER & MINI-DUCT ENCLOSURE COMBINATIONS


SY-415WX Unfinished	Net 33.95
SY-416WX Mahogany	Net 35.95
SY-417WX Walnut	Net 35.95
SY-418WX Oiled Walnut	Net 35.95
SY-419WX Blonde	Net 35.95

SK-130 SPEAKER & MINI-DUCT FINISHED ON 4 SIDES

SY-420WX Mahogany	Net 36.95
SY-421WX Walnut	Net 36.95



THE FAMOUS LAFAYETTE ELIPTOFLEX



ELIPTOFLEX®

COMPLETE SPEAKER SYSTEM with ENCLOSURE

NOW IT IS POSSIBLE TO HAVE THE ADVANTAGES OF A HIGH EFFICIENCY 12" SPEAKER IN A BOOKSHELF SIZE ENCLOSURE.

SPECIALLY DESIGNED 12" COAXIAL SPEAKER WITH SHEEPSKIN CONE EDGE SUSPENSION AND 1 1/4 LB. MAGNET PROVIDE A RESPONSE FROM BELOW 30 TO 15,000 CPS.


ENCLOSURE BEAUTIFULLY FINISHED ON FOUR SIDES IN HAND RUBBED VENEERS.

64.50
NO MONEY DOWN

SK-58
FINISHED ON 4 SIDES

Adapts to any room arrangement. Place horizontally on shelves or vertically on the floor.

PHENOMENAL ELIPTOFLEX PERFORMANCE



PERFORMANCE EXPLANATION

The loudspeaker is mounted on a baffle recessed in the cabinet shell with the front-plate extending partially across the front surface of the baffle forming ducts or tubes from the port openings to the outside air. The elliptical cutout changes the effective length of the duct across its area. This variation in path lengths provide an extremely smooth transition from duct to free air; broadens the frequency response and provide better transient response. A triangular shaped diffracting ring mounted on the front of the baffle board virtually eliminates undesirable cancellation effects normally produced by close coupling of front and rear cone radiation. This results in a "lens" effect, changing relative particle velocities and consequently, phase relationships so as to produce a smooth transition from front to rear radiation. Comparative laboratory and listening tests indicate that "Eliptoflex" performance is demonstratively superior throughout the audio spectrum.

Patents applied for in United States, England and Canada

SPECIAL KIT VALUE

Lafayette ELIPTOFLEX in KIT FORM


PRICED EXTRA LOW!
COMPARE FOR VALUE

- Easy To Assemble
- 3 Sides Ready To Finish For Horizontal Placement
- 3/4" Furniture Quality Birch
- Decorative Acoustic Grille
- Interior Acoustic Padding

21.50
NO MONEY DOWN

CK-14AWX Ready-To-Finish "Eliptoflex" Speaker Cabinet Kit in Birch Net 21.50
CK-34WX Kit with Walnut veneer Net 24.50

LAFAYETTE ELIPTOFLEX® BOOKSHELF ENCLOSURE WITH SK-180 10" TRIHELIX 3-WAY SPEAKER




66.50

An ideal combination of speaker and enclosure that furnishes optimum 3-way speaker performance. Eliptoflex enclosures are finished on all four sides for vertical or horizontal placement. Shpg. wt., 32 lbs.

SY-398WX Mahogany Net 66.50
SY-399WX Walnut Net 66.50
SY-400WX Blond Net 66.50
SY-401WX Oiled Walnut Net 66.50

VALUE COMBINATION! LAFAYETTE SK-211 CAVALIER 12" 3-WAY SPEAKER WITH 1 3/4 LB. MAGNET AND FAMOUS ELIPTOFLEX ENCLOSURE




74.50
NO MONEY DOWN

Get the most in both value and performance with these speaker/cabinet combinations. Lafayette's famous Eliptoflex bookshef enclosure assures you of top performance for your SK-211 "Cavalier 12" speaker. Enclosures finished on all four sides for vertical or horizontal placement. Your choice of fine finishes. Size: 14Hx23 1/4 Wx 13-5/11" D. Shpg. wt., 34 lbs.
SY-410WX SK-211 & Eliptoflex in Mahogany Net 74.50
SY-411WX SK-211 & Eliptoflex in Walnut Net 74.50
SY-412WX SK-211 & Eliptoflex in Blond Net 74.50
SY-413WX SK-211 & Eliptoflex in Oiled Walnut Net 74.50
SY-414WX SK-211 & Eliptoflex in Unfinished furniture grade birch Net 67.50


FAMOUS LAFAYETTE ELIPTOFLEX ENCLOSURE AND SK-210 SOVEREIGN 12" 3-WAY SPEAKER WITH 2 1/4 LB. MAGNET

PERFORMANCE MATCHED—Lafayette's famous Eliptoflex bookshelf enclosure matched with the exceptional SK-210 Sovereign 12" 3-way speaker. Finished on four sides in your choice of decorator finishes. Size: 14Hx23 1/4 Wx 13 1/2" D. Shpg. wt., 39 lbs.
SY-405WX SK-210 & Eliptoflex in Mahogany Net 82.50
SY-406WX SK-210 & Eliptoflex in Walnut Net 82.50
SY-407WX SK-210 & Eliptoflex in Blond Net 82.50
SY-408WX SK-210 & Eliptoflex in Oiled Walnut Net 82.50
SY-409WX SK-210 & Eliptoflex in Unfinished furniture grade birch Net 75.50

82.50
NO MONEY DOWN



HI-FIDELITY WOOFERS



SK-67W*

23.95

SK-68

15.50

15" HI-FI WOOFER

• 2 LB. ALNICO MAGNET

• 20 TO 5000 CYCLES—35 WATTS

This efficient 15" low frequency woofer incorporates many exclusive features. For original equipment or replacement, it provides highly efficient extended low-frequency response. Ideal for assembling 2- and 3-way speaker systems. Handles 35 watts of audio power. Frequency response ± 2 db 20 CPS to 1000 CPS, and ± 5 db from 20 CPS to 5,000 CPS with proper baffling. Voice coil dia. 2", impedance 8 ohms, 31.5 oz. Alnico V magnet. Finished in beautiful brown enamel. Cone is seamless type, permanently bound to voice coil. Has 4-way binding posts. Shpg. wt., 13 1/4 lbs. Cone Resonance 45 cycles

Net 23.95

12" HI-FI WOOFER

21.5 OZ. ALNICO V MAGNET—25 WATT

Provides efficient, extended low-frequency response of ± 5 db from 35 to 8000 CPS, and features 25 watts of power handling capacity. Perfect for high-fidelity installations or for modernization of older equipment. Ideal for assembling 2- and 3-way speaker systems at a budget price. Enclosed magnet structure—completely dust-proof. Compliance of outer cone and inner spider carefully calculated for best bass response. 21.5 oz. Alnico V magnet, 1 1/2" dia. voice coil, 8 ohm impedance. All exposed surfaces are finished in beautiful brown enamel. Has 4-way binding posts. Cone Resonance 50 cycles. Shpg. wt., 8 lbs.

Net 15.50

NEW! 2- and 3-way L/C CROSSOVER NETWORK



NETWORK

- 4 CROSSOVER FREQUENCIES: 350, 700, 2000-3000, 5000 CYCLES
- 6 CROSSOVER COMBINATIONS
- 2 OR 3 WAY CROSSOVER
- ATTRACTIVE METAL CASE
- BUILT-IN BRILLIANCE & PRESENT CONTROLS

This versatile unit can be used either as a 2-way or 3-way 6 db per octave network. You can use this network for a 2-way system now, easily and quickly convert to 3-way later. Six crossover combinations are available—2-way crossover with 2000-3000 cycle or 5000 cycle crossover, and 3-way with crossover frequencies of 350 and 5000, 350 and 2000-3000, 700 and 2000-3000 or 700 and 5000 cycles—a total of four different crossover frequencies! Suitable for 8-16 ohm speakers. The network is housed in an attractive metal case, suitable for mounting inside enclosure or leaving out in the open. Two level controls—Brilliance and Presence controls—are mounted on the front panel. If desired, these level controls may be removed, along with the beautiful gleaming copper escutcheon plate, for external mounting; controls are wired with 3-foot long leads. High quality components are used for long life and top performance. Shpg. wt., 6 lbs.

LN-5 Lafayette L/C Crossover Net 14.95

2 OR 3 WAY CROSSOVER NETWORK



- 4 CROSSOVER FREQUENCIES
- L PAD BALANCE CONTROLS
- EASY TO USE
- IMPEDANCE 16-OHMS

The LN-7 Crossover Network combines quality performance, beauty and versatility at an unbeatable price. It can be used in a two-way system by crossing over at 500 cps or 3300 cps, and in a three-way system by utilizing the two simultaneously. The change from a two-way to a 3-way 6 db per octave network may be accomplished easily. Two level balance controls. Size 5 1/2 x 2 7/8 x 2 3/8". Shpg. wt., 2 1/4 lbs.

Net 8.75

HIGH FREQUENCY TWEETER WITH ACOUSTIC LENS

DIRECT IMPORTATION MAKES THIS PRICE POSSIBLE!
• FREQUENCY RESPONSE FROM 2000 CPS TO BEYOND AUDIOABILITY • LOUVERED ACOUSTIC LENS FOR UNIFORM SOUND DISPERSION • HANDLES 25 WATTS OF POWER • PRICED EXCEPTIONALLY LOW

New high frequency tweeter featuring a louvered acoustic lens for uniform sound dispersion and capable of handling up to 25 watts of distortion-free power. The directional tendency of high frequency notes is overcome by the natural wide dispersion angle of the short horn and acoustic lens which disperses and radiates the high notes smoothly throughout the entire listening area. The lens is detachable for panel mounting, with a separate base for the tweeter furnished for external mounting where desired. Aluminum voice coil has 16 ohms impedance. Size 4 1/4" long x 3" diameter, lens extends 2 1/2". Requires a crossover network, preferably one with a level control, such as the LN-2. With full instructions. Shpg. wt., 5 lbs.

HW-7 Net 14.95

WORLD-RENOWNED LAFAYETTE SK-115A 3-WAY 15" HIGH FIDELITY SPEAKER

Custom Built in England
to Lafayette's Rigid
Specifications



79⁵⁰

**MONEY BACK
GUARANTEE
YOU BE THE JUDGE**

Try the SK-115A for 30 days.
If not completely satisfied,
return it for full refund.
1 Year Service Guarantee

**NO MONEY
DOWN**

- Massive 5 lb. Magloy Magnet—The Most Efficient Magnetic Material Available
- Free-Edged Cone Suspension
- 3 Inch Long Main Voice Coil
- 12 DB/Octave Crossover Network with High Frequency Level Control
- Precision Pressure Driven Horn Loaded Tweeter with Aluminum Diaphragm & Coil

SUPERB PERFORMANCE—The finest British craftsmanship and advanced acoustic design, combined by Lafayette to bring you this outstanding 3-way 15" speaker. Designed and constructed to the most exacting laboratory standards, the SK-115A features a patented concentric twin gap magnetic system with a massive 5 lb. Magloy magnet. Woofer mid-range radiator and speaker are axially mounted to achieve unexcelled, efficient, wide-range speaker performance. The woofer section with a cone resonance of 25 cps is vacuum constructed by an exclusive process. The cone rolls and edges are bombarded with minute particles of specially-blended plastic materials, to form a virtually free-edged cone suspension that eliminates standing waves and surround resonances. An automatic mechanical crossover separates bass and mid-range frequencies at 2,000 cps to a high stability mid-range radiator. A 12 db per octave LC crossover network provides smooth transition at 5,000 cps from mid-range to a precision pressure driven horn loaded tweeter employing an aluminum diaphragm and coil in a self-aligning assembly with air chamber and phase equalizer. This crossover is provided with a high frequency level control for matching of sound to room acoustics and individual listening tastes. Dimensions: 8 3/4" Overall depth; 15 3/8" diam. Shpg. wt., 40 lbs.

SK-115AWX Net 79.50

*Repairs which become necessary due to manufacturing defects will be made by Lafayette at no charge during the Guarantee period.

COMPARE THESE SPECIFICATIONS

- Cone Resonance: 25 cps. • Overall Frequency Response: 20-20,000 cps. • Magnet: 5 lb. Magloy Permanent Magnet • Magnetic Flux Density: 306,000 Maxwells
- Crossover: 12db/Octave Twin 1/2 Section LC Network
- Power Capacity: 50-watts • Woofer Voice Coil Diameter: 3 inches • Tweeter Voice Coil Diameter: 1 inch
- Impedance: 16 ohms

LAFAYETTE "MINUETTE" HIGH-FIDELITY SPEAKER SYSTEM

Room Filling Music
Everywhere in Your Home!



TWO FOR 23⁵⁰ SINGLY 12.50

- Shelf Size — 8 1/4 Dx 15 3/4 Lx 5 7/8" H
- Use Two For Stereo—Perfect For the Small Apartment or Listening Area
- Genuine Walnut Finish on 4 Sides
- Complete with 6' Extension Cable and Phone Plug

An exceptional speaker value... the Lafayette "Minuette" Hi-Fi Speaker System will bring music to any room in your home — and for a remarkably low cost. Designed for use where space is at a premium — ideal for the small apartment or listening area. Expand your stereo system to other areas of your home... easily used in the den, kitchen, patio or bedroom. Employs a specially designed 5x7" speaker in a rear loaded reflex type enclosure. Provides an exceptionally fine musical quality yet measures only 8 1/4 Dx 15 3/4 Lx 5 7/8" — small enough to fit anywhere. Superb Walnut finish on 4 sides allows placing speaker horizontally or vertically. Frequency Response 100-12,000 cps. Impedance 8 ohms. Rated at 10 watts. Supplied with 6 ft. of extension cable and phone plug. Shpg. wt., 5 1/2 lbs.

SK-181 Net 12.50

Save — Buy two for stereo. Shpg. wt., 11 lbs. Net 23.50

THE WIDELY ACCLAIMED LAFAYETTE SK-58 12" COAXIAL SPEAKER

Now Offered Exclusively By Lafayette At

Tremendous Savings

**SUPERB PERFORMANCE GUARANTEED
—OR YOUR MONEY BACK!**

THE WORLD-RENOWNED ORIGINAL LAFAYETTE SK-58[®]

- RESPONSE 30-15,000 CPS
- SHEEPSKIN "FREE EDGE" CONE MOUNTING
- 1 1/4 LB MAGNET WEIGHT
- 3" COAXIALLY MOUNTED TWEETER
- BUILT-IN LC NETWORK
- RATED AT 20 WATTS CONTINUOUS POWER

Lafayette's exclusive 12" coaxial is a precision-made high fidelity loudspeaker, universally acclaimed by music lovers, hi-fi enthusiasts and professional experts alike as the greatest performance-value on the hi-fi market. It provides a truly faithful reproduction of sound without any "coloration" or distortion, its excellence being responsible for its use in innumerable high fidelity music systems today. The SK-58 incorporates such features as heavy, high flux density TSK-5 magnets for high efficiency; 3/4" wide sheepskin cone-edge suspension and special composition fibre cone material, specially treated for ultra-linear, distortion-free response; heavy rugged cast metal frame for freedom from resonances and for greater rigidity.

29.50

**NO MONEY
DOWN**



The coaxially-mounted 3" cone-type tweeter has a bell shaped mounting for maximum dispersion of high frequencies with no back radiation. With the built-in 3000 cps crossover network it contributes its share to the smooth delivery of the overall wide range response of 30-15,000 cps. Woofer resonance in free air is 40 cps. Speaker power handling capacity is 20 watts continuous sine wave, 35 watts peak program material. Impedance of the voice coil is 8 ohms, connections being made to chrome-plated screw terminals. Finished in gray-brown opalescent enamel, the speaker is supplied complete with "brilliance" level control. Shpg. wt., 11 lbs. SK-58W 12" COAXIAL SPEAKER Net 29.50

THE LAFAYETTE TRIHELIX[®]

Recreates The Entire Audio Spectrum With Concert Hall Faithfulness—The Lafayette "Trihelix" represents a major breakthrough in three way speaker design. Fresh engineering concepts have resulted in a single 10-inch speaker designed expressly for use in bookshelf size enclosures, that delivers a quality of performance with the unmistakable feel, presence and clarity of a 3-way speaker system. The "Trihelix" is in effect a complete three-way high-fidelity speaker system, with three mechanically and electronically independent speakers mounted within a single 10-inch frame. Although they are individual units the 2-inch tweeter and 5-inch midrange speakers have been especially designed to complement the woofer. Special treatment of the cones and cone edges with polyester resins provides an even distribution of mid and high frequencies without peaks or resonances. To minimize interaction between the three cones both the midrange and tweeter units are mounted eccentrically or off center in relation to the woofer. In addition the midrange and tweeter are completely enclosed by a specially designed baffle. These unusual design features result in effectively eliminating intermodulation distortion due to interaction between woofer, midrange and tweeter cones—a common fault in conventionally designed 3-way speakers. The specially treated woofer cone employs a revolutionary "conical stiffener" located at the apex of the cone in order to stiffen the diaphragm and eliminate "breakup," thus providing a true piston action. This carefully designed cone-stiffening procedure, in addition to its very high compliance, enables the woofer to deliver a smooth, crisp, solid bass that balances naturally against a crystal clear midrange and natural treble. A built-in electrical crossover network with crossover points at 1500 cps and 5000 cps, allows each speaker to reproduce its portion of the audio range smoothly and efficiently. An adjustable brilliance control permits matching of sound to room acoustics. SPECIFICATIONS: Overall Response 20-20,000 cps (30 to 13,000 cps ± 3 db). Free Air Resonance 35-55 cps. Impedance 16 ohms. Power Rating: 20 watts Average Program Material. Crossover Points: 1500 & 5000 cps. Overall Diam: 10". Overall Depth: 7". Baffle cut-out: 8 7/8". Screw type terminals are color coded for quick easy connection of amplifier leads. Shpg. wt., 8 lbs.


SK-180 10" Lafayette "Trihelix" Net 32.50
SB-62W Adaptor Board To Fit SK-180 To 12" Cutout Net .89

3 Completely Independent
Speakers With 3 Separate
Voice Coils In a Single
Compact Unit

- Frequency Response 20 to 20,000 cps (30-18,000 cps ± 3 db)
- Revolutionary "Conical Stiffener"
- Eccentric Baffle Mounting of Midrange & Tweeter Eliminates Interaction Between Speaker Cones
- Built-in Crossover Network and Brilliance Control
- Extremely Efficient
- High Excursion Woofer
- Ideal For Stereo

32.50

NO MONEY DOWN



3-WAY CROSSOVER NETWORK
MIDRANGE & TWEETER Baffles
CONICAL STIFFENER

THE LAFAYETTE CAVALIER 12" High-Fidelity 3-Way Speaker

- 1 1/4 lb. High-Efficiency "Alcomax" Magnet
- Special Design For Distortionless Performance From 30-20,000 cps.
- 1 3/4" Voice Coil
- Handles 25 Watts of Power
- Non-Resonant Rigid Frame Construction
- Crossover Complete With Brilliance Control

39⁹⁵
NO MONEY DOWN



AN OUTSTANDING PERFORMANCE VALUE . . .

This new Lafayette Cavalier 12 integrates the finest acoustic design with precise British craftsmanship. It's advanced 3-way design with woofer, mid-range radiator and tweeter axially mounted within a specially engineered non-resonant rigid frame is capable of faithfully reproducing the complete audio spectrum from 30-20,000 cps. The most violent crescendos are easily handled without tone coloration or distortion, with superior bass response achieved even at the lowest volumes. Construction features include a 1 3/4 lb. high efficiency "Alcomax" magnet, an especially engineered "Rigidflex" cone-bonding and cone edge treatment process for a virtually free-edged cone suspension, 1 3/4 inch voice coil

plus a stiff-coned midrange radiator with a 2,000 cps mechanical crossover. A 5,000 cps LC crossover equipped with brilliance control channels high frequencies into a compression-driver tweeter; incorporating a rigid die cast flared hyperelliptical horn, a 1" diameter aluminum voice coil and diaphragm in a self-aligning assembly with air chamber and phase equalizer. SPECIFICATIONS: Frequency Response: 30-20,000 cps, Fundamental Cone Resonance: 35 cps, Power Handling Capability: 25 watts, Magnet: 1 3/4" lb. "Alcomax," Voice Coil: 1 3/4" diameter; Crossover: Mechanical at 2,000 cps. Electrical at 5,000 cps; Impedance: 16 ohms. Shpg. wt., 10 lbs. SK-211 Lafayette Cavalier 12 Net 39.95



LAFAYETTE

EXTRA LOW COST
AUDIO & PHONO ACCESSORIES

NEW Lafayette BASS REFLEX SPEAKER BOOKSHELF ENCLOSURE KIT FOR 8" or 6" SPEAKERS

COMPARES TO CABINETS PRICED AT \$35

- Precision Cut — Fits Together Smoothly
- Adapts For 8" or 6" Speakers
- Easy To Follow Pictorial Instructions
- Versatile — Use As Floor or Bookshelf Enclosure



As Low As
10.95

Not 1/2", But 3/4" Furniture Grade White Birch Or Walnut Veneer

Smooth, Sanded, Ready for a Fine Finish

Built-In Picture Frame Moulding

Assembles In Less Than 30 Minutes!

Adapter for 6" Speaker

Precut for 8" Speaker

Entire Cabinet 3/4" Plywood

Interior Acoustic Padding

Carefully Designed Bass Reflex Port

Decorative Acoustic Grill Cloth

BUILD IT YOURSELF . . . All that's required to construct this excellent bookshelf speaker enclosure is a screwdriver and thirty minutes of your time. Expensive woodworking equipment isn't needed—each cabinet component has been precision cut and fits together perfectly. There's nothing else to buy . . . acoustic padding, grill cloth and hardware are provided. Use any 8" or 6" speaker; the mounting board has been precut for 8" speakers and an adapter is supplied for 6" speakers.

Designed for horizontal placement in a bookshelf, along a wall etc. Constructed of 3/4" veneers on 3 sides with handsome picture frame moulding. You save even more by finishing this kit yourself—the 3 sides are smoothly sanded furniture grade wood; ready for a finish you'll be proud of. See Lafayette's professional finishing kits). Dimensions: 3x9 1/2 x 11". Available in either birch or walnut unfinished veneers.

CK-31WX Birch Kit Shpg. wt., 15 lbs.	Net 10.95
CK-35WX Walnut Kit	Net 13.95
Speakers for Lafayette CK-31 Cabinet Kit. Lafayette 8" Duo-Cone Speaker; 40-16,000 cps response.	
SK-98 Shpg. wt., 5 1/2 lbs.	Net 9.95
Lafayette 6 1/2" Coaxial Speaker; 50-16,000 cps response.	Net 6.95
SK-97 Shpg. wt., 3 1/2 lbs.	Net 6.95



LAFAYETTE
L PADS
1.39

New L pads for use as "brilliance" controls to vary tweeter level, or as "presence" controls to vary mid-range speaker level. Both wirewound elements are concentrically mounted within one plastic housing. With gold-finished metal escutcheon plate, mtg screws, and attractive black knob. Size: 1 1/4" dia., 7/8" deep (less shaft), 2 1/2" deep overall. Shpg. wt., 6 oz.
VC-49—L pad for 8 ohm circuits Net 1.39
VC-50—L pad for 16 ohm circuits Net 1.39

STEREO LEVEL BALANCE CONTROL
• Dual Concentric 8 ohm L Pads
• Logarithmic Curve
2.89

Provides individual level control for stereo speakers. Varies "brilliance" or "presence" Controls stereo extensions without mismatching. Dual control mounted on concentric shaft. Gold-finished brass plate and attractive black knobs, with gold trimming. L pad for 8 ohm circuits. Plate is 2 1/4" across; overall depth 3 1/4". Shpg. wt., 10 oz.
VC-55 Level Control Net 2.89



STEREO
RUMBLE
FILTER
2.49

Filters out turntable vibration and rumble—makes every low-priced turntable and changer quiet and rumble-free. Designed for use with ceramic or magnetic cartridges. 3-position selector switch—ceramic, magnetic cartridge, off. Just plug it in between cartridge and amplifier inputs. Overall size: 5x2 1/2 x 3/8". Shpg. wt., 14 oz.
PK-444 Stereo Rumble Filter Net 2.49

NEW! LAFAYETTE SK-98® 8" DUO-CONE HI-FI SPEAKER



- MECHANICAL 2-WAY DESIGN
 - OVERALL RESPONSE 40-16,000 CPS.
 - LARGE MAGNET STRUCTURE
 - PATENTED CONE CONSTRUCTION AND MATERIAL
 - HIGH EXCURSION WOOFER
- 9.95**

The dual-cone construction used in these high quality 8" speakers, provides the same type of wide-range response normally found only in true coaxial speakers or multiple speaker systems. Two separate cones act through a common voice coil. The outer edge of the tweeter cone is attached to the mid-section of the woofer cone; both cones "float" on flexible corrugated wedges. This mounting results in true mechanical cross-over, so that both cones operate at low frequencies, but only the tweeter cone operates at high frequencies. This gives improved high frequency directional characteristics and minimum distortion. Patented cone materials provide extremely smooth response over the range of 40-16,000 cps. Magnets are large and heavy, with a flux density of 10,500 gauss and total flux of 56,000 maxwells. Terminals are screw-type for solderless connections. Sensitivity is 99.5 db/watt; free air resonance is 55-70cps; voice coil impedance is 8 ohms. Size is 8" diam., 4 1/4" deep and requires 6 3/4" diam. baffle opening. Shpg. wt., 5 1/2 lbs.
SK-98 8" 2-WAY SPEAKER Net 9.95
FOR STEREO Net 18.95

NEW! 6 1/2" COAXIAL SK-97® HI-FI SPEAKER



- OVERALL RESPONSE 50-16,000 CPS.
 - SPACE SAVING & ECONOMICAL FOR STEREO
 - BUILT-IN L C NETWORK
 - LARGE, HEAVY MAGNETS
- 6.95**

An excellent speaker with all the best features of coaxial design, the SK-97 will provide the finest sound reproduction available from a speaker of this size. It is especially recommended where space and/or cost are factors. The 6 1/2" woofer is equipped with large, heavy magnet for maximum efficiency and low distortion. The 2" tweeter is a separate speaker coaxially mounted in a housing which completely seals off back radiation; a mesh dispersion screen provides smooth, wide-angle high frequency propagation. When properly enclosed, the response of this low cost hi-fi speaker is genuinely impressive. Its small size makes it perfect for use in a wide variety of small enclosures—ideal for use in pairs for stereo music systems of up to 8-10 watts. Frequency range, 50-16,000 cps. Woofer free-air resonance, 70 cps. Voice coil impedance, 8 ohms. Built-in electrical crossover network. Color-coded screw-type terminals. Requires 5 1/2" diam. cutout. Size is 6 1/2" diam., 3 3/4" deep. Shpg. wt., 3 1/2 lbs.
SK-97 6 1/2" COAXIAL SPEAKER Net 6.95
2 FOR STEREO Net 12.95

LAFAYETTE DUCTED-PORT BASS REFLEX SPEAKER ENCLOSURE



14.50

- ACCOMMODATES EITHER AN 8" OR 6" SPEAKER
 - DUCTED PORT DESIGN FOR EXTENDED BASS RESPONSE
 - ECONOMICAL AND SPACE-SAVING
 - RECOMMENDED FOR STEREO
- An acoustically engineered loudspeaker enclosure designed to provide full wide-range response when used with any 8" or 6" wide range or coaxial hi-fi speaker. Incorporates a special long duct over the usual bass-reflex port for performance equal to many enclosures of much greater size. Only 11 1/2" high, 18" wide and 9" deep—perfect for bookshelf, table top or other limited-space applications. Made of hardwood veneers throughout, hand-rubbed to a high finish, and lined with heavy acoustical padding. Available in Blonde Mahogany, Mahogany or Walnut finishes. (Please specify your choice.) Shpg. wt., 15 lbs.
CAB-25W Net 14.50



LAFAYETTE'S ULTRA-COMPLIANCE 2-WAY SPEAKER SYSTEM

VERY SMALL IN SPACE — LESS THAN 1 CU. FT.

Absolutely Gigantic in Performance!


17.50

- Frequency Response 40-16,000 cps
- Especially Designed Vented, Tuned Duct Type Enclosures
- Unique Mechanical 2-Way Speaker With Extra Heavy Magnet
- Enclosure Finished on 4 sides • Excellent For Stereo

FULL SIZE PERFORMANCE — This outstanding Lafayette Ultra-Compliance 2-way speaker system achieves a purity of sound and musical quality that is astounding from a speaker system occupying less than one cu. ft. of space. A perfect speaker for use anywhere in your home or office . . . makes ideal extension units or use in pairs for stereo.

The speaker features a unique dual cone with an extra heavy magnet structure, employed in a specially designed tuned ducted port enclosure. Both tweeter and woofer "float" on flexible, corrugated edges, with the outer edge of the tweeter cone attached to the mid-section of the woofer. This results in a mechanical crossover so that both cones operate in phase at low frequencies, but only the tweeter cone radiates high frequencies. The same type of wide-range frequency response is achieved that normally is found only in true coaxial or multiple speaker systems. Frequency response is 40-16,000 cps — Impedance: 8-16 ohms.

Available in rich mahogany or walnut. Finished on four sides — place it horizontally on its side or vertically on its base. Easily adapts to bookshelf placement or modular use. Dimensions are only 10 3/8" x 18 1/4" x 8 7/8" D. Shpg. wt., 15 lbs.
AVAILABLE IN MAHOGANY OR WALNUT (PLEASE SPECIFY)
Lafayette Ultra-Compliance 2-Way Speaker System SK-124WX Net 17.50
Set of Two SPEAKER SYSTEMS FOR STEREO Net 34.00



GARRARD PRESSURE GAUGE
For accurately measuring tracking force. Large circular scale, transparent plastic window. Gauge reads 0-12 grams with 1/2 gram markings. Scale pan is of swiveling balance type. Measures pressure at the stylus and at the actual record level. Easy to operate. Comes with 5 gram brass weight for checking calibration.
GR-165 Garrard SPG3 Imported from England Net 2.95

DUST COVERS
Molded to the contours of the players from sparkling, clear vinyl, these covers provide complete protection from dust and accidents to the precision bearings, levers and tone arm. Shpg. wt., 1 1/2 lbs.
PK-531 Fits Model A Net 4.95
PK-560 Fits Model AT6 Net 4.95
PK-561 Fits Model ATM Net 4.95
PK-529 Fits Model 210 Net 4.95
PK-530 Fits 88/11 and RC88 Net 4.95



PHONO-TUNER ADAPTER
2 phono jack inputs; simple switch selects either. A convenient phono output jack for connecting to amplifier. Includes mounting screws. Av. shpg. wt. for above units is 1 lb.
MS-795 Net .98

SPEAKER PHASING CONTROL
Allows you to reverse speaker connection to obtain correct phasing without disconnecting leads from speakers. A must for stereo. Complete with screw terminals and all mounting hardware. Shpg. wt., 1 lb.
MS-756 Speaker Phasing Control Net .98

STEREO-MONAUURAL-REVERSE SWITCH
Lets you switch instantly from stereo to monaural or reverses stereo channels. 2 phono jacks input . . . 2 phono jacks output. Completely shielded, ready to mount with all hardware. Shpg. wt., 1 lb.
MS-757 Stereo-Monaural-Reverse Switch Net 1.29

MULTI-INPUT SELECTOR CONTROL
Connects any one of 5 inputs to 1 output AM, FM, phono, tape, aux. Completely shielded to prevent hum. Complete with mounting hardware. 5 phono jacks input, 1 phono jack output. Shpg. wt., 1 lb.
MS-758 Multi Input Selector Net 1.76

REMOTE MICROPHONE VOLUME CONTROL
No more running to the P. A. amplifier to adjust volume when you are using a mike. Now, control volume output right at the microphone. Attached between the microphone and the cable, this completely shielded control has practically no insertion loss and induces no hum. Can be used at any desired distance.
Fitted on one end with a female mike Connector and male mike Connector on the opposite end. Finished in gleaming chrome, its appearance will blend in with the most expensive microphones. Comes completely ready to use. Shpg. wt., 12 oz.
MS-755 Remote Volume Control Net 1.76

BUILD-YOUR-OWN LAFAYETTE SPEAKER ENCLOSURES

EASY-TO-ASSEMBLE HI-FI ENCLOSURE KITS and COMPLETE SPEAKER SYSTEMS

LAFAYETTE UNIVERSAL HI-FI BASS REFLEX ENCLOSURE KITS

Entire Cabinet 3/4" Plywood
Heavier Construction—Fully-Cased 3/4" Plywood
Smoothly Sanded Ready for a Fine Finish
Picture Frame Moulding Built-In
Tweeter adapter
Pre-Cut for Most Tweeters Or No Tweeter, If Desired
Pre-fab 3/4" Baffle for any Lafayette And Almost Any Other Speaker System
For 8 1/2", 8" or 5" Mid-range Or No Mid-range, If Desired
Pre-Cut for 15" Woofer With Adapter for 12"
Acoustic Grille of Decorative Plastic
Precision Design—Parts Fit Air-tight
Supplied With Interior Acoustic Padding
Carefully Designed Bass Reflex Port

HIGHBOY LOWBOY

AT TREMENDOUS SAVINGS TO YOU!

A LAFAYETTE BEST BUY AT ONLY 29.95

NO MONEY DOWN

- EASIEST TO ASSEMBLE—ALL YOU NEED IS A SCREWDRIVER!
- 3/4" WHITE BIRCH
- PRECISION-CUT—FITS TOGETHER SMOOTHLY
- PERFECT FOR SINGLE WIDE RANGE, 2-WAY OR 3-WAY SPEAKER SYSTEMS
- HIGHBOY OR LOWBOY STYLE

All pieces of these carefully designed bass reflex high fidelity speaker enclosures are accurately pre-cut of 3/4" Plywood to fit snugly together and eliminate spurious resonances. Surface is white birch veneer. Front panels have picture-frame moulding and plastic acoustic grilles to blend with any finish and room decor. Tapered offset legs are protected by brass ferrules. Acoustic lining material prevents reverberation and cabinet resonance. Cutouts are provided for 15" speaker plus adapter for 12" 8 1/2" or 8" midrange plus adapter for 5" and blank wood block if no midrange speaker is used; cutout with adapter boards for 2 sizes of rectangular and 3 sizes of round compression horn tweeters plus blank block if no tweeter used. Thus, any single wide-range 12" or 15" speaker may be used, or any Lafayette 2- or 3-way speaker system, or almost any other combination of speakers. Kits are supplied unfinished, smoothly sanded and ready for finishing. The lowboy-style cabinet dimensions are (less legs) 28 7/8" x 23 1/2" x 16 3/4" D; legs are 7" high. Highboy has same dimensions with height and width interchanged. Instructions, all parts, hardware, and grille are included. Shpg. wt., 5 1/2 lbs.

CK-10WX Unfinished Highboy Enclosure Kit Net 29.95
CK-11WX Unfinished Lowboy Enclosure Kit Net 29.95

LAFAYETTE OILED WALNUT FINISHING KIT

AT TREMENDOUS SAVINGS TO YOU!



2.69

Use this professional walnut oiling kit to achieve a beautiful oil finish on all unfinished walnut furniture. Materials are identical to those used by professional finishers; kit contains walnut oiling mixture, walnut paste wax, sandpaper and instructions. Shpg. wt., 2 lbs.

MS-592 Net 2.69

LAFAYETTE HI-FI SPEAKERS AT POCKETBOOK PRICES

SK-183 11.95
SK-138* 5.25

12" THREE-WAY HI-FI SPEAKER

This new 3-way speaker answers the needs of many hi-fi enthusiasts. Featuring an 8 oz. dual-diameter magnet it has a frequency response of 35-17,500 cps. The elliptical tweeter gives improved sound dispersion over cylindrical types. Voice coil: diam-1 1/4", Impedance-8 Ω. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 6 1/2 lbs.

SK-183 Net 11.95

6" MID-RANGE SPEAKER

An excellent mid-range direct-radiator type speaker for installation in 3-way or 4-way speaker systems. Gives clean, distortion-free reproduction at rated power. Features closed back to eliminate interaction with sound waves generated from other speakers in the same enclosure. Rated power handling capacity: 10 watts. Frequency response from 700 to 7000 cps. Magnet weight: 3.16 oz. Voice coil impedance: 8 ohms. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 3 lbs.

SK-138* Net 5.25

SK-106 4.95
SK-93W* 8.75

NEW! LAFAYETTE 8" 3-WAY HI-FI SPEAKER

MADE IN ENGLAND TO OUR SPECS!

For Stereophonic and Monophonic Systems

- Frequency Range: 40-20,000 cps
- Magnet System: 1 lb.
- Voice Coil: Aluminum
- Impedance 16 Ohms
- Power Handling Capacity: 20 Watts

PAY LESS FOR HIGHER QUALITY-PERFORMANCE

24.50

NO MONEY DOWN

- 3-Concentric Radiators
- Unique Wide-Angle Compression Lens Tweeter
- Special "Rigidflex" Free Edge Woofer Cone
- Built-in Brilliance Control
- Die-Cast Frame

The Lafayette SK-213 has been specially designed for us in England to reproduce sound with true fidelity without compromise. It is a complete 3-way system, composed of 3 concentric radiators. The "Rigidflex" bass and midrange radiators accurately reproduce frequencies of from 40 to 5,000 cps. The new wide-angle compressor lens tweeter extends the frequency range from 5,000 up to 20,000 cycles. Here is a speaker capable of a standard of performance previously associated with much larger and more elaborate loud-speaker equipment. Deluxe features such as an aluminum voice coil, heavy 1 lb ceramic magnet system and rigid nonresonant die-cast frame demonstrate the unique mating of Lafayette custom specifications with quality English craftsmanship. Small size makes it an ideal choice for mounting in the famous Lafayette "Mini-Duct" bookshelf enclosure. Use it in pairs for finer stereo reproduction anywhere in your home. A built-in bass-treble attenuator makes it possible to "customize" the SK-213's sound to your individual requirements. Baffle Hole dia., 7"; Front to back dimension, 3 3/4".

SK-213 Shpg. wt., 6 lbs. Net 24.50
SK-213 3-WAY SYSTEM with MATCHING "MINI-DUCT" ENCLOSURES FINISHED ON ALL 4-SIDES
SY-438WX Mahogany Net 46.95
SY-439WX Walnut Net 46.95

LAFAYETTE 8" EXTENDED RANGE SPEAKER

- 45 to 13,000 cps
- SKIVER ROLLED CONE FOR SMOOTH RESPONSE
- 3.16 OZ. NEW TYPE MAGNET

Here is a price buster for the budget-wise hi-fi music lover. This is an extended range domestic speaker whose high sensitivity is achieved through a new hi-efficiency magnetic circuit. Ideally suited for medium and low level monaural or stereo reproduction. It has a 1" voice coil with 8 ohms impedance and will handle musical peaks of 10 watts. Size: O.D. 8 1/2"; Mtg. hole dimensions 7 1/4"; 3 1/2" deep; Brown enamel over heavily plated steel. 4-way binding posts. Shpg. wt., 2 lbs.

SK-106 Net 4.95

12" COAXIAL HI-FI SPEAKER

12" Alnico V PM with 1" voice coil and heavy one-piece cone. Specially designed 3" Alnico V PM tweeter completes this combination speaker. Range 40 to 15,000 cps. Built-in high pass filter. Power rating: 12 watts. 6.8 oz. Alnico V magnet. Impedance 8 ohms. Shpg. wt., 8 lbs.

SK-93W* Net 8.75

SK-69 6.25
SK-164 10.95

8" HI-FI WIDE RANGE SPEAKER

50-13,000 CPS

Answers the need for a good quality but moderately priced speaker with a range of 50-13,000 cycles. An extremely smooth single cone reproducer — ideally suited for Hi-Fi systems. Excellent for limited space—good overall balance—power handling capacity: 10 watts—6.8 oz. Alnico V magnet—frequency response: 50-13,000 CPS when properly baffled. Rim treatment on cone minimizes possibility of diaphragm distortion. Voice coil impedance: 8 ohms. Cone Resonance 85 cycles. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 4 lbs.

SK-69 Net 6.25

LAFAYETTE 8" WOOFER

- Rated 20 watts
- Free edge cone
- 14.7 oz. alnico V magnet
- High Compliance
- 35 to 7500 cps

Ideal for 2 or 3 way systems where space is at a premium, this 8" woofer provides coverage from 35 to 7500 cps. The 14.7 oz. magnet is extraordinarily heavy for this size speaker insuring the efficiency needed for good clean response. Other features include free edge, high compliance cone, 20 watt power dissipation, voice coil dust cover. Cone resonance 50 cycles, 8 ohm Y.C. Has 4-way binding posts. Shpg. wt., 4 1/2 lbs.

SK-164 Net 10.95

8" MID-RANGE SPEAKER

Ideal for use with tweeter and cross-over networks to make up a 2- or 3-way system. This 8" mid-range speaker is capable of producing undistorted response down to 350 cps, the cross-over frequency. Back is enclosed. Power handling capacity: 25 watts. Frequency response: 350-13,500 cycles. Recommended to crossover at 5000 cycles to a tweeter. Cone resonance 150 cycles. Impedance: 8 ohms. Plated steel framed finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 4 lbs.

SK-74 Net 6.50

SK-74 6.50

LAFAYETTE'S Amazing New! MINI-DUCT

A universal ducted-port bookshelf enclosure engineered for use with 1, 2 or 3-way speaker systems.

SOLIDLY CONSTRUCTED OF 3/4" WOODS START WITH A SINGLE SPEAKER AND BUILD INTO A 2- OR 3-WAY SYSTEM LATER ACoustically LINED THROUGHOUT AVAILABLE IN A VARIETY OF FINISHES

23.50

NO MONEY DOWN



MINI-DUCT BOOKSHELF ENCLOSURE

Mounting boards accept all types of tweeters

33.25

NO MONEY DOWN

SK-98

Now limited space need not necessarily mean limited sound. The Lafayette Mini-Duct is acoustically designed to achieve smooth, distortion-free reproduction with a remarkably full, clean extended bass response that gives no indication as to its small size. Reducing boards are supplied so that the Mini-Duct will accept an 8" Woofer, 6" Mid-Range and a variety of tweeters. This versatility makes it possible to start with an 8" speaker and eventually build into a 2-way or 3-way speaker system. Solidly constructed of 3/4" woods the Mini-Duct is beautifully finished in a variety of fine veneers on 3 sides. Designed for attractive placement anywhere in your home with dimensions 23Wx11 1/2Hx11 1/2"D. Shpg. wt., 2 3/4 lbs.

CAB-47WX MINI-DUCT IN WALNUT	Net 23.50
CAB-48WX MINI-DUCT IN MAHOGANY	Net 23.50
CAB-49WX MINI-DUCT IN BLONDE	Net 23.50
CAB-50WX MINI-DUCT IN OILED WALNUT	Net 23.50
CAB-51WX MINI-DUCT UNFINISHED BIRCH	Net 21.50
Mini-Duct Enclosure finished on 4 sides for attractive horizontal or vertical placement. Choice of mahogany or walnut.	
CAB-105WX Mahogany	Net 24.95
CAB-106WX Walnut	Net 24.95

SPEAKER AND ENCLOSURE COMBINATIONS

A PERFECT COMBINATION: The "Mini-Duct" enclosure and the famous Lafayette SK-98 8" mechanical 2-way speaker with patented dual cone construction. This speaker combined with the Lafayette "Mini-Duct" enclosure will give the same wide-range frequency response (40-16,000 cps) normally found only in the coaxial speakers or multiple speaker systems. Shpg. wt., 29 1/2 lbs.

COMBINATION UNFINISHED "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-348WX	Net 31.25
COMBINATION MAHOGANY "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-349WX	Net 33.25
COMBINATION WALNUT "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-350WX	Net 33.25
COMBINATION OILED WALNUT "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-351WX	Net 33.25
COMBINATION BLONDE "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-352WX	Net 33.25

SK-98 SPEAKER AND MINI-DUCT FINISHED ON 4 SIDES

SY-377WX MAHOGANY	Net 34.25
SY-378WX WALNUT	Net 34.25

NEW EASY-PAY-PLAN—SEE PAGE 54 FOR FULL DETAILS

NEW! REVOLUTIONARY pioneer STEREOSCOPE!


SH-100



ATTACHES
in MINUTES!

UNCONDITIONALLY
GUARANTEED

Comes complete with one
headset—up to 4 people can
listen by adding accessory
earphone kits!



NOW! YOU CAN PLAY STEREO RECORDS

ON ANY TURNTABLE WITHOUT ANY AMPLIFIER — WITHOUT SPEAKERS!

—WITH ABSOLUTELY NO ELECTRONIC DEVICES BETWEEN THE RECORD AND YOUR EARS!

ALL YOU NEED IS THE AMAZING PIONEER STEREOSCOPE

AND ANY TURNTABLE OR RECORD PLAYER

15.95

Here is a truly remarkable achievement in stereophonic sound. The Pioneer Stereoscope enables the listener to enjoy his stereo or monaural records through a pair of headphones, with no amplifiers—no electronic devices of any sort—between his ears and the record! Headphones are driven by variations in pressure from the specially designed Stereoscope pick-up arm. The resultant full-bodied, distortion-free sound will make the listener search for the huge speakers he usually associates with such quality. An unconditional guarantee accompanies this amazing unit! A special volume control unit is inserted in the pipe which carries the sound to the earphones, which permits separate adjustment of left and right channel volumes. The mixing control located on the same unit

governs the channel separation and, in effect, can select stereo or monaural operation. Frequency response, 30 to 15,000 cycles. Tracking force for pick-up, 3-6 grams. Self-adjusting rubber rollers are provided to protect needle when pick-up is not on record. Accessory earphone kits permit as many as 4 persons to enjoy the same recording. The SH-100 comes complete with special pick-up arm, sapphire needle, mounting base, suction base, volume control unit, connecting tubes, earphones, and mounting screws. Shpg. wt., 4 lbs.

PK-596 SH-100 Stereoscope Net 15.95
PK-597 SH-101 Additional earphone kit Net 2.95
PS-97L NSH Diamond replacement needle Net 3.49

NEW! pioneer MODEL SE-1 STEREO HEADPHONES


- Actually 2 High Fidelity Dynamic Speakers
- Frequency Response 25 to 15,000 Cycles
- Soft Foam Rubber Ear Pads

F-770 19.95

- Frequency Response 25 to 15,000 Cycles
- Actually 2 High Fidelity Dynamic Speakers
- Soft Foam Rubber Ear Pads

For the audio connoisseur who demands the finest in stereophonic headphone performance, the Pioneer Stereophones combine broad frequency response and faithful reproduction with comfort-oriented design, to fulfill the most exacting requirements. The Stereophones are actually two 2 1/2" high fidelity dynamic speakers with a frequency response range of 25 to 15,000 cycles. Perfect for stereo and monaural operation, the headphones are rated at 1/2 watt maximum input; impedance, 8 ohms per phone. The soft foam rubber ear pads provide extremely comfortable listening, help to keep out noise and maintain an excellent bass response.

F-770 Shpg. wt., 2 lbs. Net 19.95
Model SE-2 resistor box for SE-1. Permits flexible one-switch changeover from speakers to Stereophones. F-800 Net 4.95
Model SE-3 "Y" connector for connecting 2 or more sets of headphones to a single source. F-801 Net 2.45
Model SE-4 12' extension cord for SE-1 phones. F-802 Net 2.95




F-800 4.95

LAFAYETTE MINIATURE HI-FI SPEAKER and ENCLOSURE

- ATTRACTIVE MAHOGANY FINISHED WOOD CABINET
- COMPLETE WITH 25 FEET OF CABLE

Enjoy music everywhere in your home with this amazing Lafayette miniature speaker system. Perfect as an extension speaker for your den, basement, kitchen or bedroom. Use two as extension speaker units for stereo or with your TV and Radio. Housed in a beautiful mahogany—finished wood cabinet with ventilated back cover, the 5-watt 4x6" speaker is designed to work from either 4 or 8 ohm outputs. System is supplied with 25 feet of cable which should meet any hook up requirement. Over-all size: 9 1/2" W x 7 3/4" H (inc. feet) x 3 1/2" D. Shpg. wt., 5 lbs.

SK-109 Miniature Speaker System Net 6.95



6.95

NEW! LAFAYETTE HIGH FIDELITY STEREO HEADPHONES



13.95

- AIR-CUSHIONED HEADBAND
- SOFT FOAM RUBBER EAR CUSHIONS FOR MAXIMUM COMFORT AND BEST BASS RESPONSE
- HIGH SENSITIVITY—INPUT OF 1-2 MW PROVIDES AMPLE LISTENING VOLUME

These headphones will provide excellent high fidelity stereophonic listening and will perform beautifully with monaural equipment as well. They are designed for fatigue-free, comfortable use, even after the longest of listening periods.

The headband is covered with an air-filled vinyl bag which serves as a gentle air cushion, eliminating the discomfort which usually accompanies the weight of the phones on the head. Vinyl bag can be deflated, removed for washing, and re-inflated. Soft foam rubber ear pads keep out external noise, provide maximum bass response and make these headphones extremely comfortable to wear. Sensitivity is very high—a signal power of 1 to 2 mw will produce adequate listening volume. Frequency response, 30-15,000 cycles; impedance, 8 ohms per phone.

The headphones come with a cylindrical junction box to protect the voice coils against power overloads. Phones plug into the box, and the two pairs of leads from the box are connected to a dual or single channel source for stereo or monaural operation. Complete with all cables, wires, overload junction box and 3-conductor phone plug. F-767 Shpg. wt., 2 1/2 lbs. Net 13.95

JUNCTION BOX
For connecting stereo headphones to an existing system without the need of continually disconnecting speakers. Impedance 4-16 ohms. Has separate earphone jacks for stereo or monaural, separate volume controls for each side of the headset, and a speaker on-off switch. 4 3/4" W x 1 3/4" H x 1 3/4" D. F-641 Shpg. wt., 1 1/4 lbs. Net 4.59

LAFAYETTE-GOODMANS

SK-111 1 1/4 LB. 15" MAGNET SPEAKER

Reg. 1961
Catalog Price 54.50

- Frequency Response: 30-20,000 cps.
- Cone Resonance: 35 cps.
- Power Rating: 30 watts



39.50

15" speaker with power rating of 35 watts and cone resonance of 25 cps. Employs 1 1/4 lb. Alcomax magnet and 1 3/4" voice coil, 7" deep, 15 3/4" diam. Shpg. wt., 25 lbs. SK-111WX Net 39.50

NEW! 4-SPEED HI-FI TURNOVER PICK-UP




2.75

- ARM TAKES STEREO OR MONAURAL CARTRIDGES
- WITH WIDE RANGE MONAURAL CARTRIDGE
- ADJUSTABLE ARM HEIGHT AND STYLUS PRESSURE

Arm is wired for stereo, anticipating future conversion. Has a wide range turnover monaural crystal cartridge with dual sapphire styli. Output is 1 1/2 V. Easy height adjustment at base, 1 1/4" to 1 3/4". Also stylus pressure adjustment. Plastic arm 9 1/2" long overall. Base 1 3/4" with mounting holes on 1 3/8" centers. Shielded leads. Satin smooth light maroon finish. Shpg. wt., 2 lbs.

PK-146 Net 2.75
PK-158 Sapphire LP replacement Needle Net .49
PK-159 Sapphire STD replacement Needle Net .49

MODERN RECORD RACK



1.79

Attractive, brass plated rack carries 60 records of all sizes. Spring steel separators numbered 1 to 60. Heavy carrying handle. Rubber tipped feet. Size 17 1/2 x 5 3/4 x 7" D. Shpg. wt., 4 lbs. PK-227 Net 1.79

KOSS STEREO HEADSETS and ACCESSORIES



Model SP-3 Stereophones (Fig. A)

The Koss SP-3 Stereophones are a specially constructed headset that provide a wide frequency range of 30-15,000 cycles by means of unusual 3 1/2" dynamic reproducers incorporated into each earphone. They are extremely comfortable to wear, light and rugged. Ideal for Stereo, they can also be used for monaural sound. Since they have an impedance of 4 ohms, they can be connected directly to amplifier outputs or across speaker voice coil leads. Shipping weight 2 lbs. G-600 Net 24.95

MODEL A-1220 AMPLIFIER

An Amplifier especially designed for use with the Stereophones. Can be connected directly to a Stereo ceramic cartridge or to the outputs of the pre-amps of a stereo recorder or tuner. Equipped with 2 Phono jacks, a gain control for each channel, and 2 Phone jacks. Attractively made and compact, this unit lends itself to a wide variety of uses. Three tubes plus rectifier. Transformer powered. Shipping weight, 4 lbs. G-603 Net 34.95

MODEL T-1

Contains matching transformers for monitoring 600 to 10,000 ohm outputs to output jacks for Stereophones and a terminal board is provided for connection to various types of equipment. Shipping weight 1 1/2 lbs. G-604 Net 6.95

MODEL T-5 JUNCTION BOX (Fig. B)

Junction Box for connecting stereophones to existing stereo or monaural system. Impedance 4-16 ohms. Contains 2 Volume controls for changing the Volume of each side of the headset independently. Has 2 output jacks for stereo or monaural use. Equipped with speaker on-off switch for personalized listening. Shipping weight 1 1/4 lbs. G-605 Net 7.95

KOSS PERSONAL LISTENER

An outstanding 4-speed phono with ceramic turnover stereo cartridge, diamond stylus for LP, and sapphire stylus for 78 r.p.m. Includes a set of the famous Koss Stereophones to form a complete, personalized stereo high fidelity system of the finest quality. Each channel has a separate volume control; phono has automatic shut-off feature. Portable, in brown leatherette case. 21 1/2" L x 13 1/2" W x 6" H. G-606WX Shpg. wt., 22 lbs. Net 99.50

PLASTIC RECORD COVERS



75c per pkg. of 15

Soft pliable plastic covers to protect records from dirt, dust and moisture. Available in square beaded bottom to fit 12" records in jackets and in round beaded bottom to cover 12" records without jackets. Shpg. wt., 1/2 lb. PK-456 Pkg. of 15 Square PK-455 Pkg. of 15 Round Any Pkg. Net 75



STEREO AUDIO ANALYST™
Single Needle
Dual Channel
VU BALANCE
METER

11.95

- UNIQUE TWO COIL GALVANOMETER TYPE PRECISION METER MOVEMENT
- SEVEN RANGES OF METER SENSITIVITY
- PROVISION FOR USE AS VU METER AND TAPE RECORDER LEVEL INDICATOR
- MAXIMUM METER SENSITIVITY 120 ua

Provides the solution to all stereo balancing problems. When both signals are equal and balanced the resultant deflection on the scale will measure 0. Individual channels may be measured by two slide switches. Stable meter action and protection from peak voltages is provided by special damping networks. Single seven-step range control serves for both channels and facilitates use of meter with all amplifier power levels. By properly positioning this control the movements may be used as VU meters when terminated across the 600-ohm load. The scales are calibrated in "Volume Units". Sensitivity is 1.2 volts for 0 vu or 100 percent indication. Finished in a rich satin gold. Overall size is 4 3/4" L x 5 1/4" H x 4 1/4" W. TM-66 Audio Analyst Net 11.95



LAFAYETTE HIGH FIDELITY STEREO-MONAURAL TEST RECORD

2.95

- TESTS RUMBLE EACH CHANNEL
- TESTS LEVEL EACH CHANNEL
- TESTS RESONANCE
- TESTS EQUALIZATION
- STYLUS WEAR TEST
- TESTS BALANCE
- INCORPORATES PHASE CHECK

For stereo testing this two-sided 12" LP stereo record has on its stereo side two 1000 cycle bands to check the level of each channel separately; balance check to set the level of each channel using special metronome recordings on both outer and inner edges of each side to check both stereo and monaural stylus. For monaural testing it provides an RIAA equalization test in 9 steps from 30 to 15,000 cycles, a continuous glide band from 10 to 35,000 cycles, to test for resonances of tone arm or of cabinet. Also features sections of stereo sound effects of jet planes, boat whistles, etc. A terrific value and a "must" for the Hi-Fi enthusiast. Comes with complete instructions for use. Shpg. wt., 1 lb. PR-14 Net 2.95

DIAMOND STYLI AT LOWEST PRICES ANYWHERE

LAFAYETTE DIAMOND and DIAMOND-SAPPHIRE STYLI

MADE FOR LAFAYETTE BY THE FOREMOST AMERICAN MANUFACTURERS

KEY TO POINT CODES HOW TO ORDER

The symbols in the column headed "PT SIZE" are explained in the table below.

LP = SINGLE 1 MIL MICROGROOVE FOR 33 1/3 AND 45 RPM
COMB = DUAL 1 MIL DIAMOND AND 3 MIL SAPPHIRE

Identify your needle by cartridge number and illustration and order by stock no. Note that all needles listed here are for monaural cartridges.

ALL DIAMOND STYLI ARE NOT ALIKE
MADE FROM WHOLE DIAMONDS • PRECISION GROUND AND POLISHED • VERTICALLY AND EDGEWISE GRAIN ORIENTED • SHADOWGRAPHED



Each of Lafayette's diamond stylus is made from individual diamonds, properly oriented and ground to close tolerance; shadowgraph tested to give you less wear per play and long service life.


The synthetic sapphire used in these styli are of the same fine quality used in precision watch bearings.

FULL 1 YEAR REPLACEMENT GUARANTEE AGAINST DEFECTS IN WORKMANSHIP AND MATERIAL ON ALL DIAMOND STYLI

2.39

ANY DIAMOND or DIAMOND-SAPPHIRE NEEDLE IN THIS LISTING

STEREO DIAMOND STYLI AT LAFAYETTE'S 2³⁹ Low Prices!



Stylus Stock No. Fig. For Cartridges

PS-88L G ACOS 73
7 mil diamond and 3 mil sapphire stylus No. 73-1

ADMIRAL CARTRIDGES
PS-80L C 409B33-1-1(2-1)
PS-81L B 409C37-1

ASTATIC CARTRIDGES
PS-92L N 17, 17D

COLUMBIA CARTRIDGES
PS-84L J SC-1-2-7-8

ELECTROVOC CARTRIDGES
PS-80L C 21 and 26 Series

EUPHONICS CARTRIDGES
PS-93L K E-1-3

GENERAL ELECTRIC CARTRIDGES
PS-87L A 6C7
PS-89L A VR227

MAGNAVOX CARTRIDGES
PS-80L C 560233-3-4
PS-94L D 560260-1

MONARCH (BSR)
PS-86L F TC8S, TC-8SH

MOTOROLA CARTRIDGE
PS-80L C 59K64335
PS-81L B 59B645397

PERPETUUM-EBNER
PS-81L B PE90 (M, N)

PHILCO CARTRIDGES
PS-80L C { 35-2809-1, 35-2824-1,
325-8047, 35-2825-1,
325-8036

PS-81L B { 35-2820-1, 35-2826-1,
325-8048, 325-8049

PS-86L F { 35-2827-1, 35-2829-1,
325-8051, 325-8052

RCA CARTRIDGES
PS-81L B T, T-1
PS-85L E { 106770-1, 106690,
108213,
108718

PS-86L { 106770-1, 106690,
108213,
108718

RONETTE CARTRIDGES
PS-81L B { 0V, 0V1, T1 Single BF40
105, 105-1 (2,3,4),
106-1(2,3,4)

SONOTONE CARTRIDGE
PS-82L D { Combination .7 Mil
(stereo) diamond and 3
mil (78RPM) sapphire
for 8T and 8TA

PS-95L L { Same as above
but for 9T Series

PS-96L M { Same as above
but for 12T Series


PS-83L D { Same as above but
with .7 mil (stereo di-
amond and 1 mil (mon-
aural LP) sapphire

TELEFUNKEN CARTRIDGE
PS-90L H T20-2

VM CARTRIDGES
PS-80L C 16707-A
PS-82L D 16708-F

WEBOR CARTRIDGES
PS-80L C 21P573
PS-81L B 21P596, 21P598
PS-82L D 21P700-1-2-3-4

ZENITH CARTRIDGES
PS-81L B 142-99B



DIAMOND NEEDLES

Stock No.	Size Pt.	Fig.	Cartridge	REPLACES JENSEN NO.	Stock No.	Size Pt.	Fig.	Cartridge	REPLACES JENSEN NO.	Stock No.	Size Pt.	Fig.	Cartridge	REPLACES JENSEN NO.
FOR ADMIRAL CARTRIDGES														
PS-10L	LP	1	409A11, 409A30, 98A54-1	JPS-30LPD	PS-35L	LP	54	560176, 560180	CRA-55LPD	PS-35L	LP	53	TO-200, TO-222, TO-284, or TO-400 series, RA284, DT60 series.	CRA-55LPD
PS-16L	COMB	6	409B21	JPS-35SD	PS-70L	COMB	51	560161	S-66SD	PS-69L	LP	38	TX88, A	CRA-56LPD
PS-17L	LP	7	409A30	AB1LPD										
FOR ASTATIC CARTRIDGES														
PS-20L	LP	3	{ AC Series, 40T, 41T, 40-1, 41-1, 42-1, 90T series, 10-L-3, 11L-3	A-75LPD	PS-56L	COMB	43	45-9612, 76-4649, 425-0016	PH-13SD	PS-16L	COMB	6	{ WC10, WC10D, PC2 series, PC3 series, PC4 series, PC5 series P-72, P-73, P-73R, P-75, P-76, P-77, P-80, W-21, W-21AR, W-22A, WC-24, WC-25 Series	JPS-35SD
PS-23L	LP	12	408	M-70LPD	PS-56L	COMB	43	45-0009, 425-0011, 425-0014	PH-13SD	PS-10L	LP	1	{ 1P-LB-10, 2T0, 2TS, 2T-LB-SD, 9980-S, 9980- SD, 9980D, 5T, 57-LB-S, 57-LB-SD.	S-66SD
PS-25L	COMB	14	GCD, 409, 55-T, 55TJ, 55TM	M-70LPD										
PS-23L	LP	12	410	M-70LPD										
FOR PERPETUUM EBNER CARTRIDGES														
PS-17L	LP	7	{ CAC, CQ, CQ-1, LQD, LQD-1, QT, QT-33, 44-T, 46-1, 48-1, 166T Series	A-81LPD	PS-64L	COMB	47	P12/RG	RX550SD	PS-32L	COMB	51	3T, 3TS, 3TD	S-61SD
PS-35L	LP	54	{ 118, 120, 124 series, 310T, 312T, 420, 422, 424TS series, 310-1, 310-TB, TS, 312-TB, TS, 414-1	CRA-55LPD	PS-65L	COMB	48	PE-8, PE10	RX551SD	PS-17L	LP	7	BX	A-811LPD
FOR R.C.A. CARTRIDGES														
PS-23L	LP	12	74067	M-70LPD	PS-66L	LP	22	P7000 (MJ, MD) (LP only)	RX552LPD	PS-10L	LP	1	F11	JPS-30LPD
PS-10L	LP	1	S5652, 76257, (988370-1), 75044	JPS-30LPD										
PS-20L	LP	3	76257, (988370-2)	A-75LPD										
PS-10L	COMB	51	78748, 79807, 100653	S-66SD										
PS-25L	COMB	14	100329	A-71SD										

REPLACEMENT STYLI FOR GE CARTRIDGES

FOR GE VR II CARTRIDGES (FIG. 35)

Direct replacements for clip-in styli in GE VR II series models 46-050, 46-052, 46-053, 46-040, 46-041, 46-043, 46-061 cartridges. Avg. shpg. wt., 2 oz.

PS-48L-1 mil diamond LP clip-in stylus. Replaces GE 46-010 Net 2.39
PS-540-1 mil sapphire LP clip-in stylus. Replaces GE 46-015 Net 1.15
PS-548-3 mil sapphire 78 clip-in stylus. Replaces GE 46-035 Net 1.15

MODERNIZATION ASSEMBLIES (FIG. 33)

Modernize your old triple-play cartridge. These assemblies replace both the old and new series "A." Once installed, you can replace one point at a time.

DIAMOND SAPPHIRE. Replaces old RPJ-013 and new RPJ-013A. Avg. wt., 2 oz. Net 2.39

DUAL DIAMOND. Replaces old GE RPJ-012 and new RPJ-012A. Net 4.50

DUAL SAPPHIRE. Replaces old GE RPJ-010 and new RPJ-010A. Net 2.10

STYLI FOR OLD TYPE GE CARTRIDGES (FIG. 32)

Exact replacement for all old type single needle GE cartridges. Avg. wt., 2 oz.

PS-45L-Diamond 1 mil (LP) replaces GE RPJ-004 Net 2.39

PS-54L-Sapphire 1 mil (LP) replaces GE RPJ-005 Net .99

PS-540-Sapphire 3 mil (78) replaces GE RPJ-001 Net .99

FOR GE SERIES A CARTRIDGES (FIG. 34)

Individual styli replacements that clip in to all GE "A" series. Avg. wt., 2 oz.

PS-47L-Diamond 1 mil (LP) replaces GE RPJ-010 Net 2.39

PS-543-Sapphire 1 mil (LP) replaces GE RPJ-015 Net 1.15

PS-542-Sapphire 3 mil (78) replaces GE RPJ-035 Net 1.15

DIAMOND STYLI FOR

G.E.

AS LOW AS

2.39

A LAFAYETTE SPECIAL!

1.95 TONE ARM CONTROL



An absolutely essential addition for every Hi-Fi enthusiast. Ends groove and stylus damage caused by accidental dropping of tone arm onto record, greatly extending record life. Accurately and smoothly lowers tone arm into run-in groove and lifts arm off record at end of play. Ideal for "cueing." Designed to fit practically every known turntable arm as well as record changer with manual features. Supplied with adhesive mounting base to keep unit in position and with both wood and metal mounting screws for permanent installation. Shpg. wt., 6 oz. Net 1.95

NEW! EXCLUSIVE LAFAYETTE STYLOCHRON



- PROTECT YOUR PRECIOUS RECORDINGS.
- NO MORE GUESS WORK KEEPS AN ACCURATE RECORD OF NEEDLE USE.

More precious recordings are ruined by tardy replacement of the needle than by any other cause. Now, there is no need to let this happen, especially to your doubly precious stereo recordings. Lafayette Stylochron lets you know just how long your needle has been in use so that you can replace the worn needle at the proper time, before it can do damage to your records. The Stylochron is quickly and easily mounted on your motor board or other convenient place. The moment your record changer or turntable starts, the Stylochron begins to register. It stops when the turntable stops. The 1000 hour dial will tell you at any time how long you have been using the needle. Dial is marked off in 50 hour units. You can remove your stylus for inspection at any predetermined number of hours. Diameter of the face plate is 2 3/8". Extends 1 7/8" below or behind panel. Complete with instructions. Shpg. wt., 2 lbs. Net 4.95

MULTILINGUAL LANGUAGE COURSE

GERMAN SPANISH
FRENCH ITALIAN

You can now learn to speak French, Italian, German or Spanish easily and pleasantly in your own home and progress at your own speed. Features the new simplified participation method that helps you to learn the lessons faster and retain them longer. It is a complete language course with 48 lessons on two 12" hi-fi long playing records. You learn with native speakers! The recorded lessons are printed in an illustrated conversation manual. Also included is a combination of grammar and dictionary book. When ordering, please specify the language desired. Shpg. wt., 4 lbs. PR-15 Net 5.75

SPECIAL VALUE! INCLUDES RUSSIAN

5 language combination course. French, Italian, German, Spanish, and Russian. 9-12" LP records, 216 lessons, 2 books. Shpg. wt., 10 lbs. PR-16 Net 9.50



4 SPEED PHONO MOTOR WITH TURNTABLE

Quiet, dependable A-C operation assured by rubber shock-mounted friction drive motor. Speed change control through idler driving an 8" turntable. Mounting centers 4 1/2 x 3 3/4"; 2 1/2" depth below base plate. Shpg. wt., 3 1/2 lbs. ML-24 Phono and turntable Net 5.35
PK-149 Mounting board for motor Net .95

5.35



STATI-CLEAN .88

Sprays a fine mist which keeps your record clear of surface noise created by static (common to all vinyl records) and clean of dust attracted by the static charge. Prevents groove and needle wear caused by static-dust and keeps records lustrous. Extends their life. Two applications a year is sufficient. Enough for hundreds of records. Shpg. wt., 8 oz. PK-105 Net .88

LAFAYETTE RECORD CLEANING KIT EXCELLENT VALUE! 1.29

Clean your valuable records the professional way with this Lafayette Kit. Contains a non-gumming anti-static detergent in polyethylene bottle. Squeeze to apply for complete elimination of static in the record grooves. Supplied with special velvet applicator in plastic pouch. Shpg. wt., 10 oz. PK-508 Net 1.29

PHONO AMPLIFIERS


THREE TUBE AC-DC PHONO AMPLIFIER

(Fig. A) Equipped with a variable tone control and a separate volume control. Delivers two watts output. Phono motor connects to the amplifier. Uses 12AV6, 50G5, and 35W4 rectifier. For 110-120V, 60 cycles AC or 110-120V DC. Supplied with line cord and plug, but less tubes. Shpg. wt., 2 lbs. PK-23 2.95

2 TUBE AMPLIFIER WITH TUBES

(Fig. B) A two tube phono amplifier using a 50L6 and 35Z5 tube as rectifier. Well-built, good tone and volume. Contains volume control with switch. AT A BIG SAVING! Shpg. wt., 3 lbs. PK-24 with tubes Net 4.50

(Fig. C) Output transformer matches output tube to 3-4 ohm voice coil. Shpg. wt., 1/2 lb. TR-10 Singly ea. .49
In lots of 5, ea. .45



NEW! .7 MIL DIAMOND STYLUS FOR SHURE M7D STEREO CARTRIDGE

PS-91L Net 6.25

ELECTROSONIC LAB "DUST BUG"

Automatically removes dirt and dust on each playing. Light plastic arm mounts by suction cup. Can be permanently mounted by rubber cement. The bottle of anti-static cleaning fluid has a built-in wick for application to a brush and pad at the end of arm. Shpg. wt., 6 oz. PK-156 Standard model (A) Net 5.63

ESL CHANGER DUST BUG (B). The tuft and pad assembly clips onto arm of changer. Performs the same as the standard model. Shpg. wt., 4 oz. PK-246 Changer model (B) Net 4.65

DISPENSER OF ACTIVATING FLUID. For Dust Bugs. PK-247 Net 1.22
PK-173 Replacement plush pad .78
PK-174 Replacement nylon brush .98

MOTOROLA RADIOS for FOREIGN & DOMESTIC CARS

ALL NEW TRANSISTORIZED AUTOMOBILE RADIOS Complete with Mounting Kit



UNIVERSAL 5-TRANSISTOR MANUAL CAR RADIO

- In-dash or Under-dash Mounting
- All-Transistor, Hand-Wired Chassis

A tremendous value in an all-transistor car radio. Hand-wired chassis with 5 transistors, 2 diodes, 1 thermistor. Built-in, Golden-Voice hi-fi speaker. Set plays as soon as you turn it on—no warm-up time required. Custom fits most cars, sport cars, trucks and boats—in-dash or under-dash installation. Low battery drain. Features full variable tone control, cool chassis operation, band pass circuit, automatic gain control. For 12-volt cars, reverse polarity. Size: 6 7/8" x 2 1/2" x 7 1/4" D. Shpg. wt., 7 lbs. CR-128 Model 320T Net 39.95



6-TRANSISTOR MANUAL CAR RADIO

- Custom Fits "Difficult to Fit" Cars
- Push/Pull Audio System for Hi-Fi Sound

A flexible car radio with movable control shafts to accommodate the most difficult-to-fit cars. Push/Pull audio system gives smooth high-fidelity sound and delivers a full 12 watts of peak power output. Employs 6 transistors, 2 diodes and 1 thermistor in a hand-wired chassis. Low battery drain of only .5 amp. Features Golden-Voice hi-fi speaker, full variable tone control, automatic gain control. Plays as soon as you turn it on—no warm-up needed. 12-volt cars, negative ground. Size: 7 5/8" x 2 1/2" x 5" D. Shpg. wt., 7 lbs. CR-129 Model 2MT Net 51.95



UNIVERSAL ALL-TRANSISTOR PUSHBUTTON CAR RADIO

- Pushbutton Convenience
- 5 Transistors, 2 Diodes, 1 Thermistor

Simple, pushbutton convenience with all-transistor power and dependability. Hand-wired, transistor chassis means instant play without warm-up, cool chassis operation, and 64% less battery drain, only .7 amp. Full variable tone control, automatic gain control, band pass circuit, plus the exclusive Golden-Voice hi-fi speaker. For 12-volt cars, reversible polarity. Size: 6 7/8" x 2 1/2" x 7 1/4" D. Shpg. wt., 8 lbs. CR-130 Model 520T Net 54.95



MODEL 406 — TUBE & TRANSISTOR AUTO RADIO

- For 6-Volt System

Compact radio set that is ideal for custom underdash or in-dash installation. "Golden Transistor" circuit employs 2 transistors and 4 tubes. "Volumatic" constant level output eliminates fading and distortion. Antenna band pass filter. Reverse polarity. Size: 6 7/8" x 2 1/2" x 7 1/4" D. Shpg. wt., 6 lbs. CR-28 Model 406 Net 39.95

Full 1-year warranty on all parts and labor. Manufacturer's guarantee covers free exchange or repair of any component power defective in normal use. Removal and re-installation labor extra. Arranged through your local service dealer.

CARDIO-MASTER

- Convert your Transistor Radio into a Car Radio
- For all Makes of Cars — Cabs — Trucks

2.98

Cardio master is a magnetic device designed to hold a portable transistor radio in the area of a car's windshield to make it operate as an auto radio. Car's owner can remove a radio from the Cardio master for use as portable or to avoid theft while the car is parked. Fits any "pocket" transistor radio. Will not come loose in the bumpiest roads. Includes magnetic base, brackets, hardware, adjustable band and complete, illustrated instructions. AA-45 Shpg. wt., 2 lbs. Net 2.98

NEW! RADIO TRANSVERTER
Converts Transistor Radio to Car Radio

Only 1.47

- For all 9-Volt Transistor Radios
- Plugs into Cigarette Lighter
- Fits all Cars

Now you can avoid the expense of buying a car radio with this new radio transverter. Simple to operate—remove 9-volt battery from your transistor radio, connect contacts from transverter to battery contacts in the radio, and then plug into the cigarette lighter. Fits all cars. Shpg. wt., 6 ozs. AA-102 For 12-volt Cars Net 1.47
AA-103 For 6-volt Cars Net 1.47

Consult This Chart To Determine Which Sets Fit American Cars, Sports Cars and Foreign Cars. This chart shows the make and model of all cars for which Motorola Car Radios are available. The "Use-Set" column shows the Stock Number of Radios Listed on this page. Use this stock number when ordering. Also show your make, model and year and voltage of your car. *SPECIFY VOLTAGE!!

MAKE, MODEL AND YEAR	USE SET	MAKE, MODEL AND YEAR	USE SET	MAKE, MODEL AND YEAR	USE SET
Austin Healy 1957-62	CR-128	Falcon 1960-62	CR-128, CR-129	Plymouth 1956-62	CR-128, CR-129
Borgward 1957-62	CR-28	Fiat 600-1100 1957-62	CR-128	Rambler 1959-62	CR-128, CR-129
Buick 1954-62	CR-128, CR-129	Ford 1957-62	CR-128	Rambler-American 1960-62	CR-128, CR-129
Buick Special (Compact) 1961-62	CR-128, CR-129	Hillman Minx 1957-62	CR-128	Renault Dauphine 6 Volt 1955-58	CR-28
Chevrolet 1958-60	CR-128	Karmann-Ghia (V.W.) 58-62	CR-28	Renault Dauphine 12 Volt 1958-62	CR-128
Chevrolet 1961-62	CR-128, CR-129	Mercedes Benz 1958-62	CR-128, CR-130	Studebaker Lark 1959-62	CR-128, CR-129
Citroen 10-19, DS-19 6 Volt	CR-28	M. G. Magnette MGA 1957-62	CR-128, CR-130	Sunbeam Rapier 1957-62	CR-128
Citroen 1958-62 12 Volt	CR-128	Morris Minor 1957-62	CR-128, CR-130	Taunus 1958-62	CR-28
Comet, 1960-62	CR-128, CR-129	Oldsmobile F-85 1961-62	CR-128, CR-129	Triumph TR-3 1958-62	CR-128, CR-130
Corvair 1960-62	CR-128, CR-129	Opel 1957-62	CR-28	Valiant 1960-62	CR-128
Dodge Dart 1957-62	CR-129	Peugeot 1958-62	CR-128, CR-130	Volkswagen 1952-62	CR-28
Dodge Lancer 1961-62	CR-128, CR-129	Pontiac Tempest 1961-62	CR-128, CR-129	Volkswagen Bus 1952-62	CR-28
English Ford 1957-62	CR-128, CR-130	Porsche 1957-62	CR-28	Volvo PV-444, PV-544 1957-62	CR-28
				Volvo 12 Volt	CR-128

INSTANT FLAT TIRE REPAIR

- No Jacks, No Tools, No Removing Tires
- Seals and Inflates Tires in ONLY 2 MINUTES
- For Tube-Type and Tubeless Tires

2.79

You'll never change a punctured flat on the road again. Just attach the valve of any tube or tubeless tire and the amazing sealant instantly plugs the puncture as the tire is inflated to a satisfactory driving pressure. Will not affect wheel balance. No tools needed, no removing tires, no dirty hands—any woman can use it too. Road tested for performance. Shpg. wt., 3 lbs. AA-B4 Net 2.79

REAR SEAT AUTO SPEAKER KITS

6" x 9" KIT WITH CHROME OR GOLD GRILLE

Complete kit for adding second speaker in rear of your car. Includes a 6x9" PM speaker, 3-position selector switch for cutting in front, rear, or both speakers; dial plate with mounting bracket, knob, and hardware; chrome or gold grille; wire; and wiring instructions. Simple to install. Shpg. wt., 5 lbs. SK-94 Speaker kit chrome grille Net 3.45
SK-196 With gold grille Net 3.45

HI-FI REAR SEAT AUTO SPEAKER KITS

- ADD HI-FI LISTENING TO YOUR CAR
- FEATURING 6x9 COAXIAL SPEAKER WITH TWIN TWEETERS

Identical to SK-37 auto speaker kit shown on this page except has hi-fi 6x9" coax speaker instead of single-cone unit. Excellent for music lover who wants quality reproduction. Shpg. wt., 6 lbs. SK-77 With Chrome Grille Net 8.80
SK-202 With Gold Grille Net 8.80

DELAYED ACTION SWITCHES FOR HOME AND CAR

2.19

- Keeps lights on for 60 seconds after turning off switch

For the car. Keeps car lights on for 60 seconds while you walk to house then turns them off automatically. Easy to install in any 6 or 12 volt car. 3/4" x 1 1/2" diam. Shpg. wt., 6 ozs. SW-25 Net 2.19

DELUXE 6" x 9" KIT with 2.15 oz. ANICO V MAGNET

Same as above but with deluxe speaker with extra-heavy Alnico V magnet (2.15 oz.). This is same speaker used in kits selling at twice the price. Shpg. wt., 5 lbs. SK-37 Speaker kit chrome grille Net 4.65
SK-197 With gold grille Net 4.65

5" x 7" KIT

Same as SK-94 but with 5x7" speaker and grille. 5 lbs. SK-42 Chrome grille Net 3.05
SK-198 With gold grille Net 3.05

FADER TYPE AUTO KITS

Rear-seat speaker kits identical to those above except with fader-type controls to cut either speaker in or out or balance both. Shpg. wt., 5 lbs. SK-55 5x7" kit. Same as SK-42 but with fader control. Chrome grille Net 3.29
SK-199 With gold grille Net 3.29
SK-95 6x9" kit. Same as SK-94 but with fader control Chrome grille Net 3.69
SK-200 With gold grille Net 3.69

DELUXE 6" x 9" FADER KIT

Deluxe kit with extra-heavy-magnet 6x9" speaker, plus fader control. Shpg. wt., 5 lbs. SK-56 6x9" kit. Same as SK-37 but with fader. Chrome grille Net 4.89
SK-201 With gold grille Net 4.89

FADER TYPE AUTO KIT

Coaxial speaker kit (same as SK-77) with fader for flexible control of both front seat and rear speakers and sound balancing. Shpg. wt., 6 lbs. SK-78 With Chrome Grille Net 9.00
SK-203 With Gold Grille Net 9.00

ADJUSTABLE AUTO HEADREST

- Fits Any Car Seat
- Comfortable Foam Pillow Cushion
- Washable Zippered Cover

5.93

Avoid auto fatigue with this adjustable headrest. Used by driver or passenger to relieve neck strain—ideal for long or short trips. Completely adjustable for any car or position. Comfortable foam pillow cushions with removable, washable zippered covers. Strong chrome frame fits any car seat. Hold-on-bars are latex coated. AA-90 Shpg. wt., 3 lbs. Net 5.93

3-WAY PUSH-BUTTON SWITCH

89¢ ea.

Lots **75¢** of 3 ea.

Just push a button to select either front speaker alone, rear speaker alone or both together. Comes completely assembled on black & silver metal plate with cable, hardware and simple instructions. Imported. Shpg. wt., 1/2 lb. MS-890 Lots of 3, ea. .75 singly, each .89

GRANCO FM CAR CONVERTER

NEW!

Add Hi-Fi to Your Present Car Radio

- Exclusive "Auto-G" Coaxial Tuner
- Automatic Frequency Control
- Quick, Under-Dash Installation

39.50

Get added pleasure from your auto radio listening with the new Granco FM car converter—lets the incomparable richness of High Fidelity FM travel with you. Features the exclusive "Auto-G" coaxial tuner for highest sensitivity and selectivity. Automatic frequency control locks in stations. Economical to operate too—uses the existing car radio antenna and circuits. Complete 12-volt battery operation. Compact design—book size, 1 1/4" thick. Stays in place with just 2 screws, 1 wire and antenna plug-in. (In lots of 6, Each 33.46) Net 39.50
CR-105 Shpg. wt., 10 lbs.

STEREO-MATIC HIGH FIDELITY FREQUENCY CHANNELIZER

Convert Your Monaural Car Radio to Exciting 3-D Sound

- Easy to Install
- Works With Any Car Radio

5.95

Now you can enjoy big stereo sound in your car. This STEREO-MATIC kit contains everything you need to convert your front and rear speaker to exciting three dimensional sound. You can make the adaptation quickly and easily. A flick of the switch and the thin, colorless monaural music erupts into a magnificent, full bodied three dimensional sound that is fresh and alive. Full directions with each unit. Easy to convert. No tubes to burn out. Shpg. wt., 1 lb. AA-59 Net 5.95

NEW! POCKET TIMER

Set It and Forget It

2.95

- Set Timer Up to 60 Minutes
- Swiss Precision Watch Movement
- Hairline Accuracy
- Hundreds of Uses

The new pocket timer is an invaluable aid for most anyone, anywhere. With its 60 minute time set, it can be used as a reminder when parking meter runs out, for appointments, take pills or medicines, etc. Also use as a timer on phone calls, cooking, photography, etc. Shpg. wt., 1/2 lb. MS-888L Net 2.95

MAGNETIC UTILITY LIGHT

4.95

- Hi-Intensity Lamp
- Powerful Magnet Holds Anywhere on The Car
- Leaves Both Hands Free to Work

High intensity trouble lamp for car or boat. Powerful magnetic base holds easily to metal surface. Double ball joint for use at every possible angle. Folds down to an "egg" sized unit. Long life, horizontal filament lamp, gives more light than conventional types. Heavy chrome plate over brass plated steel for exceptional corrosion resistance. 15 ft. cord gives plenty of leeway in positioning. Includes red filter for use as a warning light, lighter plug and vinyl case for storage. For 12V. DC only. Shpg. wt., 1 lb. F-631 Net 4.95
Spare Bulb for F-631 F-632 Shpg. wt., 2 oz. Net .28



LAFAYETTE'S LOW COST AUTOMOTIVE ACCESSORIES



NEW! LAFAYETTE TE-40 IGNITION ANALYZER



- Does the Work of Expensive Oscilloscopes
- Simple Direct Readings — No Complicated Patterns to Interpret
- Checks Your Car's Ignition System — Plugs, Coil, Condenser, Points, Wiring
- Special Capacitive Clip Prevents Overloads and Shocks
- Large, Easy-To-Read Dial Face
- Operates Off 12-Volt Car Battery

39⁹⁵
NO MONEY DOWN

The new easy-to-use Lafayette Ignition Analyzer will pinpoint auto ignition troubles quickly and accurately. Designed to do the work of expensive oscilloscopes, the TE-40 converts the complicated, indefinite curves of the scope to easy-to-read meter reading. Incorporates a highly sensitive vacuum tube voltmeter for locating troubles in coils, plugs, points, condensers, etc., without any circuit drain whatsoever. Enables you to use "simulated load" test to locate coil trouble. Unique safety device for making high voltage measurements without chance of a shock. Complete, ready-to-use with detailed operating instructions. Shpg. wt., 16 lbs. TE-40 Net 39.95



Lafayette HOT CAR-GO
Starts Your Car INSTANTLY

- Starts Wet or Cold Motors Instantly
- Saves Battery and Gasoline
- Installs Easily and Quickly
- 6 and 12 Volt Cars

3.49

Avoid excess wear and tear on your motor and battery—install Lafayette's Hot Car-Go. Provides 5 times the normal spark for fast starting in any weather, and automatically disconnects when engine is running. Will not damage plugs or distributor. Simple to install—instructions included. Shpg. wt., 1 lb. MS-784 Net 3.49

2-IN-1 BATTERY CHARGER




4.95

- Full 1 Amp Charge Rate on 6 or 12 Volt Batteries
- Automatic Taper Rate—Can't Overcharge
- Manual Reset Circuit Breaker

End dead battery trouble in your car, boat, truck or tractor. This powerhouse battery charger keeps all 6 and 12 volt batteries fully charged for peak performance even at 40° below freezing. Full 1 amp, "safe" charge rate prevents flaking and plate buckling—same method used by storage battery dealers. Easy to use—plug the line cord into any 110V outlet, connect the two terminals and forget it. Warning trouble light indicates incorrect terminal connection. Can't overcharge—automatically tapers off. Welded constructed steel. Shpg. wt., 3½ lbs. CV-56 Net 4.95

8 ft. BATTERY BOOSTER CABLES



BATTERY BOOSTER CABLES
Standard equipment for starting stalled cars, charging batteries, etc. Made with heavy duty, flexible rubber-covered cable. Rugged copper-clad positive action grips identified by Black and Red heavy vinyl covered handles. Shpg. wt., 3 lbs.
MS-766 8 ft. long, set of 2 Net 1.78
MS-767 12 ft. long, set of 2 Net 2.25
MS-491 12 ft. long, 6 gauge copper cable Net 3.15
MS-492 Battery Booster Clip only (specify Red or Black) Net .49

THE GAUGES DETROIT LEFT OUT!

LAFAYETTE AMMETER & OIL PRESSURE GAUGES

4.49



DON'T trust flashing indicator lights—a burned out bulb can ruin your motor or strand you with a dead battery. All cars with warning lights for oil and battery need these precision gauges. Lights only indicate when oil pressure falls below 15 lbs. or whether or not the generator is working. These Lafayette gauges will replace your panel lights (or if you wish to use both lights and gauges, buy the Tee fitting listed below). Keep a constant check on the condition and performance of your car's electrical and oil pressure systems. The ammeter calibrated in a 60-0-60 scale measures the actual rate of current flow... helps prevent generators from burning out and overcharging or discharging the battery. Exact oil pressure from 0 to 80 lbs. is indicated. Easily installs in any 6 or 12 volt car below the dash, without drilling or can be mounted right in the dash. Both meters are mounted in an attractive chrome panel. Easy to read meters feature 1½" diam. black dial faces with calibrations in white. Size: 5½Wx2½Hx2¼"D. Supplied with all necessary fittings plus full instructions.
MS-788 Shpg. wt., 1¼ lbs. Net 4.49
MS-912 Tee fitting Net .49

ILLUMINATED TYPE
Same as above, but gauges are illuminated. Supplied with lamp sockets and both 6 and 12 volt bulbs. MS-792 Shpg. wt., 1½ lbs. Net 6.49

NEW! VOLKSWAGEN GAS TANK GAUGE ASSEMBLY

12.29

- Tells Amount of Fuel in Tank
- Illuminated Type Gauge
- Complete Installation Instructions

The VW is factory equipped with a valve operated reserve fuel tank but no fuel gauge. The gas tank gauge assembly prevents running out of gas when reserve valve is accidentally left open. Float operated electrical fuel gauge. Sending unit mounts by simply drilling a 11/30" hole. Receiving unit is furnished with chrome stripe panel for dash mounting. Complete with light mounting bracket, socket, 6-volt bulb, and installation instructions. Shpg. wt., 2 lbs. MS-889 Net 12.29

PROFESSIONAL BATTERY CHARGER

8.95

- 3 Amp Tapering Charge
- For Both 6 and 12 Volts
- Positive Automatic Overload Protection

A professional type 6 - 12 volt battery charger with reset circuit breaker. Indicator light flashes on when circuit breaker trips. Front panel switch for charge over from 6 to 12 volts. Delivers a tapering charge starting at 3 amps for 6 volts. Noiseless, air-cooled construction. Oversized components and vented case for troublefree operation. Runs cool even under constant use. 4½ ft. charging cables with heavy duty, 25 amp battery clips. Measures 5x3½x3". For 105-125 volt, 50-60 cycle A.C. Shpg. wt., 5 lbs. CV-50 Net 8.95

AUTO SAFETY BELT

Exceeds 5,000 Lbs. Protection
Metal To Metal Buckle for Instant Release
For all cars except Cadillac


This 2" wide, 100% Nylon Webbing belt provides the maximum protection needed for automobile driver and passenger. Exceeds SAE & GSA strength specifications to provide better than 5000 lbs. protection. The metal to metal buckle eliminates slippage of webbing within the buckle and gives instant positive action without danger of accidental release. Each belt has 100 inches of easy-to-adjust nylon webbing so that one size fits everyone. It is also equipped with single bolt fittings for easy installation and 3" load distributing metal washers for cars where frame mounting is not available. Shpg. wt., 2 lbs. AA-61 Net 7.95

NYLON "BULLDOG" 10 FT. TOW CABLE

100% DuPont Nylon • 10-ft. Long
Guaranteed 5,000 lb. Test Strength
Attaches Instantly to Any Bumper

The perfect cable for towing ANYTHING UP TO 5,000 LBS. Constructed of heavy-duty, 1" wide, DuPont Nylon webbing that stretches 25% to take up shocks for smooth, safe towing. Oil, grease and water resistant too! Dual, self-aligning clip attaches to any bumper. Shpg. wt., 3 lbs. AA-57 Net 3.75

AUTOMOTIVE TESTING EQUIPMENT



(A) MOTOR ANALYZER
All the advantages of a well-equipped service shop in a light, hand-held package. Ideal for do-it-yourselfers, sports car Rallyers, etc. The Analyzer enables you to test ignition coil output, spark plugs, insulation breakdowns; locates poorly adjusted carburetor, sticky or burnt valves, weak valve springs; checks valve timing, choke, muffler, vacuum tank, manifold, fuel pump vacuum and pressure and vacuum operated equipment. 14Wx7¼Hx3¼"D. Shpg. wt., 5½ lbs. AA-49 Net 15.95

(B) REMOTE STARTER SWITCH
Eliminates the need of a second man when making compression, fuel pump, generator, starter, and electrical tests. Permits the mechanic to crank the engine from any position. Shpg. wt., ½ lb. AA-50 Net 2.59

(C) MOTOR GUIDE-VACUUM FUEL PUMP TESTER
Combination motor guide, vacuum and fuel pump tester, 4 color zones: Economy Driving, Fast Pick-up, Coasting and Idle. Promotes good driving habits and economical gas mileage. Warns when tuneups are necessary. Shpg. wt., 12 oz. AA-51 Net 3.75

(D) COMPRESSION TESTER
Gives quick, accurate readings of compression pressure. Merely unscrew the spark plug, plug tester into spark plug hole and read pressure. 2½" dial reads to 300 lbs. Stem is offset 15° for reaching back cylinders. Complete with instructions. Shpg. wt., 12 oz. AA-52 Net 3.75

(E) STANDARD TIMING LIGHT
Employs the stroboscopic principle of light synchronized with motion for adjustment and setting of ignition timing under actual operating conditions. Shpg. wt., 1 lb. AA-53 Net 3.25

(F) TACHOMETER
Here's the instrument for the most important check of an engine's performance: the RPM test. Tests 4, 6 and 8 cylinder engines with both 6 and 12 volt systems. Operated by two inexpensive penlight batteries which last about a year. Large dial reads 0-1000 and 0-5000 RPM. Shpg. wt., 2½ lbs. AA-54 Net 28.50

CAM-DWELL INDICATOR



3.95

A high quality instrument for solving all CAM-DWELL problems. Checks the number of degrees a distributor can rotate while the breaker points remain closed. Too much rotation means points are set too close, too little means breaker points are not closed long enough for adequate build up of the magnetic field in primary coil, permitting arcing across points. Requires no electrical outlet. Distributor need not be removed. Compact, portable. Complete with case and includes chart showing specifications for all popular cars. AA-98 Shpg. wt., 2 lbs. Net 3.95

MODEL A-8410 CHARGER PLUG FOR CAR



1.15

Permits charger to be plugged into convenient cigarette lighter receptacle. A real convenience.
MS-707 Model A-8410 For 6v cars Shpg. wt., 8 oz. Net 1.15
MS-708 Model A-8412 For 12v cars Shpg. wt., 8 oz. Net 1.15

SPRAY DE-ICER



NOW .89 3 for 2.40

- Defrosts Instantly
- Melts Ice Fast
- Prevents Ice Formation
- Harmless to Car Finish

Defrosts the auto windshield and windows instantly, giving you complete visibility—melts ice fast. Prevents frost and ice forming for hours. Also ideal for unfreezing frozen locks and doors. The big 14-oz. aerosol bomb sprays an ideal pattern at least four feet, even in zero weather—cannot harm the car finish. Shpg. wt., 1½ lbs. AA-100 Net each, .89, 3 for 2.40

SPRAY ON LIQUID TIRE TRACTION



Go on Ice and Snow

NOW 1.19 2 for 2.14

- Just Spray it on Tires
- Eliminates Chains and Snow Tires
- Works on Any Kind of Tire
- Cannot Harm Rubber or Car Finish

A safe, speedy, harmless way to keep your car moving on ice or snow. If you're stuck, simply spray it on your rear tires, and away you go. Will not freeze and one application will last for miles. A must for every motorist, every winter. Shpg. wt., 1½ lbs. AA-101 Net each, 1.19, 2 for 2.14

EMERGENCY BLINKER



1.49

- MAGNETIC BASE
- VISIBLE FOR 1000 FEET
- OPERATES ON 2 FLASHLIGHT BATTERIES

Every motorist needs it. Bulb flashes 60 times a minute. Stands by itself on road; has hanger or magnetic base which holds it firmly to any metal surface. Rugged plastic dome, 5¾" diam. x 3¼" high. Shpg. wt., 2 lbs. With spare, non-blinking bulb for steady light, less batteries. AA-99 Net 1.49
BA-157 #2 batteries (2 needed) ea. Net .13

NEW! IMPACT DRIVER



SPEEDY! TIGHTENS! LOOSENS!

Ever have trouble loosening a tightly turned, rusty screw, or a screw with the groove deformed? With this device, a small hammer rap is all that is required to loosen any corroded or rusty fastener. The driver will not damage the screw. Can be used to tighten screws also. Complete set consists of the driver tool, an adapter, ¾" bit, ½" bit, No. 2 and No. 3 bit and cam. Comes complete with necessary instructions for use and metal tool case. Shpg. wt., 2 lbs. HD-971 Net 6.95



NEW! LAFAYETTE HE-20A CLASS D Deluxe CITIZENS BAND TRANSCEIVER




LAFAYETTE'S SENSATIONAL CITIZENS BAND TRANSCEIVER—NOW WITH THESE ADDED DELUXE FEATURES!

Built-in 6 or 12 Volt Power Supply

- Pi-Network gives optimum line and antenna matching for greater power output.
- Improved Series Gate Noise Limiter
- Calibrated "S" Meter

EXCELLENT FOR BUSINESS, FARM, INDUSTRY, CAR, BOAT, PERSONAL AND SPORTS USE



LOOK AT THESE QUALITY FEATURES

- 1 14 Tube Performance, 3 Diodes
- 2 } 4 Crystal-Controlled Transmit Positions
4 Crystal-Controlled Receive Positions
- 3 Tuneable Receiver over all 23 channels
Calibrated "S" Meter with Switch To Measure Signal Strength and To Check on Wattage Input to Final
- 4 Dependable Push-To-Talk Ceramic Microphone & Relay
- 5 Adjustable Squelch Control
- 6 Highly Effective Automatic Series Gate Noise Limiter
- 7 Illuminated Dial
- 8 Built-in 12 or 6 volt Power Supply for Mobile Use
- 9 Comes Complete with Matched Crystals For Channel 9

Not A Kit!
COMPLETELY WIRED!

109⁵⁰

NO MONEY DOWN

WITH Foolproof Dependable Relay Switching As Found In Most Expensive Equipment. NOT Electrical Switching With It's Voltage Hazards. NOT Electronic Switching With Inefficiency Due To Tube and Parts Deterioration.

Quality engineering, design, and features give this Deluxe transceiver a place all-its-own in the Citizens Band Field. Operating within the limits prescribed by the FCC, the HE-20A supplies you with a highly efficient 2-way radio-telephone communications system from your office, truck, auto, boat, store, home, etc. Two or more will serve as an effective communications system over a distance of up to 20 miles or more, depending on the terrain and the height of the antenna.




3 dual function tubes, 1-Quadri-purpose tube, 3 tubes, and 2 Silicon rectifiers give 14 tube performance. The transmitter section features precision engineering to insure power-packed communications. The 5 watt-input crystal-controlled transmitter may be operated on any 4 of the 23 channels assigned by the FCC. The operating channel can be selected by a knob on the front panel (transceiver comes with pair of crystals for channel 9). The receiver circuits provide for 4 crystal controlled receiving channels plus 3 tuneable superheterodyne receiver that covers all 23 assigned channels, with a sensitivity of 1 microvolt. Effective built-in Squelch circuit quiets the receiver when no signal is being received. Series Gate Noise Limiter materially reduces ignition noise and other unwanted interference. An illuminated dial with planetary vernier tuning is clearly marked with channel numbers and lights up when tuned to any channel. The receiver terminates in 4" speaker amply supplied by a 2-watt audio power output section. The unit comes complete with a push-to-talk ceramic microphone and a bracket for convenient mounting to the side of the transceiver.

Push-to-Talk operation is accomplished with a sturdy, dependable relay. An "S" meter calibrated in S units 1-9 and to 30 db. above S-9, allows measurement of incoming signal strength. The meter is wired with a switch to enable monitoring of final amplifier wattage. Incorporates Pi-network for optimum matching to 30-100 ohm antenna for high signal output. A low-loss antenna jack is mounted at the rear of the cabinet to accept the popular PL-259 connector used with dipole, ground plane, rod, and direct mounting (Lafayette HE-19) Antennas. Rugged, low silhouette case with a bracket handle for installation at any location and in any position. Tube line up 1-6AW8A, Oscillator/Amplifier; 1-6BA6, RF Amplifier; 1-6BA6 1st IF Amplifier; 1-6BE6, Converter 1-6EAB, 2nd IF Amplifier and 1st Audio Amplifier; 1-6AQ5 Audio Output/Modulator; 1-6T8, ANL, Detector, AGC, Squelch Clamp and 2nd Audio Amplifier. Size 12x5x8 1/2"D. With 115 Volts AC/12 Volts DC or 115 Volts AC/6 Volts DC Power supply. Shpg. wt., 14 lbs.


HE-20AWX 115 Volts AC/12 Volts DC	Net 109.50
HE-43WX 115 Volts AC/6 Volts DC	Net 109.50
HE-830L Transmit Crystal (Specify Channel or Frequency)	Net 2.25
HE-22L Receive Crystal (Specify Channel)	Net 2.25
Direct plug in antenna for short distance communications.	
HE-19 Shpg. wt., 1 lb.	Net 3.95



New! LAFAYETTE HE-15A 2-WAY SUPERHET CITIZENS BAND TRANSCEIVER!



Completely Wired - NOT A KIT!



Outstanding Performance, Design, and Ease-Of-Operation. Meets All FCC Requirements

ONLY **59.50** NO MONEY DOWN

COMPLETE 2-WAY COMMUNICATIONS FOR BUSINESS, HOME, FARM, BOAT, AND SPORTS
Not Superregenerative but SUPERHET!

NOW WITH ADDED FEATURES

- Improved Selectivity and Power Output
- Effective Full-Wave Variable Noise Limiter
- RF Jack on Front Panel
- Ceramic Temperature-Free Microphone
- 5 Crystal-Controlled Transmitting Positions • Superheterodyne Tuneable Receiver Over Full 23 Channels • 4 Dual Function Tubes, plus 2 Single Function Tubes, plus 2 Rectifiers for 12 Tube Performance • Planetary Vernier Tuning
- Complete with Transmitting Crystal for Channel 9

The Lafayette HE-15A Superheterodyne Transceiver is both a compact precision transmitter and receiver designed to operate on the new class D "Citizens Band." Two or more of these units furnish your own communications system covering up to a 20 mile or more radius depending on antenna height and terrain. The Transceiver features 5 crystal controlled transmitting channels operating at a maximum legal power input of 5 watts fully modulated. RF stage in both transmitter and receiver. The 5 position crystal selector on the front panel selects any one of 5 transmitting frequencies. These 5 crystals are readily accessible by means of a removable front plate. The superheterodyne receiver is tuneable over the full 23 channel band with 3 watts audio output, AVC, and an amazingly effective Full-Wave Variable Noise Limiter. The Noise Limiter is continuously variable from the front panel for diminishing ignition and other unwanted noise pickup. RF jack on the front panel may be used to monitor the current in the final tube using external meter. Controls include a 3 position function switch (transmit, receive, and transmit with spring return), planetary vernier tuning plus variable noise limiter. Output impedance matches 52 and 72 ohm antenna with Amphenol type coax connector. Has large PM speaker; input jack for crystal or ceramic microphone; power receptacle in rear for AC

line and 6 or 12 volt external power supply. Supplied with single transmitting crystal for channel 9, high output ceramic microphone, and brackets for easy mounting of units in auto, boat, etc. Operates on 115 volts AC. Addition of 6 or 12 volt power supply (separately supplied) adapts transceiver, for mobile operation. Size 10 1/4" W x 5 1/2" H x 6 3/4" D. Tube complement: 2-6U8A 6EA8, 1-6AL5, 1-6V6, 1-12AX7, 1-6AW8.

HE-15A WX Shpg. wt., 11 lbs. Net 59.50

POWER SUPPLY: Adapts HE-15A for mobile operation. Complete with cable, 6 or 12 volt vibrator and mounting flanges. Completely enclosed. Size 4 1/2" D x 6 W x 4 1/2" H. Shpg. wt., 4 lbs. Net 10.95

HE-16 W For 12 Volts Net 10.95

HE-18 W For 6 Volts Net 10.95

ANTENNA: Base loaded telescoping whip antenna with PL259 coax connector. Mounts directly on rear of cabinet. Telescopes to only 15". For short distances. HE-19 Shpg. wt., 2 lbs. Net 3.95

TRANSMITTING CRYSTALS: For any of the 23 channels. Specify channel or frequency. HE-830L Net 2.25

THE GREATEST VALUE in the CITIZENS BAND FIELD

NEW! LAFAYETTE 6 and 10 METER TRANSCEIVERS

NEW! LAFAYETTE Deluxe 6 METER TRANSCEIVER MODEL HE-45

- Highly Sensitive Superheterodyne Receiver Section for 50-54 Mc
- Effective Series Gate Noise Limiter
- 3-Stage, 12-Watt Transmitter with 2E26 Final
- Built-in 117 VAC and 12 VDC Power Supplies
- Pi-Network Transmitter Output
- Illuminated Panel Meter for Plate Current and "S" Readings
- Complete With Push-To-Talk Ceramic Microphone

Now, for 6 meters, Lafayette offers a deluxe transmitter-receiver in a single package, with features which make the low price hard to believe. Provides maximum convenience and flexibility in either mobile or fixed operation. The superheterodyne receiver section employs an RF stage with peaking control on front panel, and two i.f. stages at 1650 Kc. for 1 μ v sensitivity and 35 db image rejection. Tunes the entire 6 meter band from 50 to 54 Mc. with calibrated illuminated vernier tuning dial. Features an adjustable series gate noise limiter, built-in speaker. Illuminated panel meter serves as an "S" meter when meter function switch is set to the proper position. Transmitter section employs a 6U8 oscillator and buffer/multiplier, driving a 2E26 final with a plate input of approximately 12 watts on AM. Pi-network coaxial output is adjustable for matching a wide range of antenna impedances. Sockets for five 8 Mc fundamental crystals plus an input for external VFO on the front panel, with corresponding 6-position selector switch. A spotting switch is provided for zero beating or for locating the transmitting frequency in the receiver. Panel meter reads plate current when switch is set to proper position. A dual power supply for 117 VAC and 12 VDC is built in, making the HE-45 perfect for mobile operation. Push-to-talk operation provided. Tube complement: 1-6BA6 RF amplifier, 1-6U8/6EA8 osc./mixer, 1-6BA6 1st i.f. amp., 1-6U8/6EA8 2nd i.f. amp./1st audio, 1-6CN7 detector/noise limiter, 1-6AQ5 audio output and transmitter modulator, 1-6U8/6EA8 transmitter oscillator and buffer/multiplier, and 1-2E26 transmitter final amplifier. Housed in a rugged, low-silhouetted case with attractive, metal panel, the HE-45 comes complete with push-to-talk ceramic microphone, crystal for 50.12 Mc, detachable mounting bracket, and all power cables. Only 12x5x8 1/2"D. Shpg. wt., 15 lbs. HE-45WX

109.50

Net 109.50



MADE IN U.S.A.



NEW! LAFAYETTE 6 METER TRANSCEIVER

SMALL, COMPACT COMPLETE 6 METER STATION-TAKE IT WITH YOU ANYWHERE!

57.50

- Ceramic Temperature-Free Microphone

Meet the enjoyable challenge of 6 meter operation efficiently and economically with the Lafayette HE-35 6 meter transceiver. This small, compact transceiver features a Transmitter with 7 watts input to a 6CX8 pentode final, high quality plate modulation, built-in adjustable TV filter, and antenna matching network for 30 to 100 ohm antenna; Superheterodyne receiver tunes entire 6 meter band (50-54 mc) and includes variable noise limiter. The transmitter uses a 3rd overtone crystal in easily accessible socket located on front panel; has RF output and modulation indicator. Low-loss SO-239 coaxial antenna output jack. Complete with attractive high output ceramic microphone, crystal for 50.2 Mc, and mounting brackets for mobile mtg. 6 or 12 volt power supply separately available for mobile operation. Built-in power supply operates on 110-120 volts, 60 cycle, 10 3/4 x 5 1/4 x 6 3/4"D. Tubes: 2-6U8A/6EA8, 6AL5, 12AX7, 6V6GT, 6CX8. Shpg. wt., 11 lbs. HE-35 AWX

MOBILE POWER SUPPLIES
5 3/4 x 4 3/4 x 2 1/4", Shpg. wt., 4 lbs. Net 57.50
HE-16W 12 Volts Net 10.95
HE-18W 6 Volts Net 10.95
Additional Crystals—Specify Frequency
HE-36L Shpg. wt., 4 oz. Delivery 3 wks. Net 4.95

NEW! LAFAYETTE 10 METER TRANSCEIVER MODEL HE-50


- Effective Series Gate Noise Limiter
- With Push-To-Talk Ceramic Microphone
- 12-Watt Transmitter with Pi-Network Output
- Built-in Dual Power Supply for 117 VAC and 12 VDC—Ideal for Mobile or Fixed Operation
- Superhet Receiver Tunes 10 Meter Phone Band from 28 to 30 Mc

109.50
NO MONEY DOWN

Here is a new transceiver with the deluxe mechanical and electrical features of the HE-45, applied to the 10 meter amateur phone band. Receiver has 1 μ v sensitivity. The i.f. of 1650 Kc results in a 45 db image rejection on 10 meters. Includes automatic series gate noise limiter. Transmitter runs 12 watts input to a 2E26 final, with pi-network coax output to match any antenna. Uses 7 Mc fundamental crystals or external VFO. Sockets for 5 crystals plus VFO input, with corresponding 6-position selector switch, located on front panel. Physical layout is identical to that of the HE-45. Includes big illuminated tuning dial and illuminated panel meter which serves as "S" meter and final plate current meter. Built-in dual power supply for 117 VAC and 12VDC make the HE-50 the ideal solution to the problem of finding a compact, completely self-contained 10 meter rig which can be operated mobile or used at home without modification. The many transmitter and receiver features which are combined in this single package make it a value that is hard to beat, at a price designed for the conservative budget. Tube complement: 1-6BA6 RF amplifier, 1-6U8/6EA8 osc./mixer, 1-6BA6 1st i.f. amp., 1-6U8/6EA8 2nd i.f. amp 1st audio, 1-6CN7 detector/noise limiter, 1-6AQ5 audio output and transmitter modulator, 1-6U8/6EA8 transmitter oscillator and buffer/multiplier, and 1-2E26 transmitter final amplifier. Housed in a rugged, low-silhouetted case with attractive, metal panel, the HE-50 comes complete with push-to-talk ceramic microphone, crystal for 28.30 Mc, detachable mounting bracket, and all power cables. Only 12x5x8 1/2"D. Shpg. wt., 15 lbs. HE-50WX

MADE IN U.S.A.

Net 109.50



LAFAYETTE NEW UNIVERSAL 6 METER AND BROADCAST MOBILE ANTENNA

ONE ANTENNA FOR BROADCAST AND 6 METERS!
AT A SENSATIONALLY LOW PRICE OF

4.75

Here is a highly efficient 6 meter antenna that replaces your Auto radio antenna for operation on both 6 meters and for regular AM broadcast reception. 59" stainless steel mast, all chrome ball type base adjustable to 180° for front rear or side mount. Complete with 54" lead. Highly versatile and durable. Shpg. wt., 4 lbs. Imported HE-801WX

Net 4.75

Hi-Par "SATURN 6" MOBILEER

A compact, horizontally polarized mobile antenna for 6 meters. It is essentially an end-loaded folded dipole with 3 ring design, approximately 20" in diameter, 5" high. Design center is 50.5 Mc but resonant frequency may be varied between 50.5 and 53.0 Mc. Easily fed with RG58/U coax. Rigid aluminum construction; net weight under 2 lbs. Easily supported on pipe, tubing or stiff rod. Model S-1 "Saturn 6" Antenna, 2-piece adjustable aluminum mast, mast bracket, universal bumper hitch. No holes to drill. Less coax feed line. Shpg. wt., 5 lbs. HE-805W

Net 16.99

5 ELEMENT 6 METER BEAM

A rugged, full size 6 meter beam constructed of 3/4" 0.090 wall aluminum tubing with hardwood dowling at high stress points. Boom is 0.958 wall drawn aluminum. Driven element is concentric gamma matched for direct coax feed. Light enough for any heavy duty TV rotator. Turning radius — 7'6"; Forward Gain — 9.5 db; F/B ratio — 29 db. Comes with all parts marked for quick, neat assembly and center band operation. Shpg. wt., 15 lbs. HE-746WX

Net 19.50

LAFAYETTE 6 METER

HALO ANTENNA



Available in Feb. 1957

9.95

Single halo, horizontal, polarized, provides extreme broadband coverage without the use of bulky wave traps. Loop weight only 1 lb. Standing wave ratio is 1:1 at frequency. 5-15 DB gain over vertical whip types when working fixed stations with arrays. Includes 3 section, 9 ft. telescoping aluminum mast to fit any standard mobile mount. HE-46W Shpg. wt., 4 lbs. Net 9.95

MARK MOBILE HELIWHIP ANTENNAS FOR 6 & 10 METERS

9.95



Fiberglass molded continuously loaded whip antennas designed to replace conventional stainless steel 3/4 wave whips. The Heliwhip can be positioned on the upper portion of the vehicle such as trunk lid, cowl, fender or hood without danger of shorting to power lines. Offers superior performance on 49-55 KC bandwidth (6 meters) plus blends in with auto styling. Produces 50 ohm match at resonant frequency. Shpg. wt., 1 lb. HE-740W 6 meter Heliwhip Net 9.95 HE-739W 10 Meter Heliwhip Net 9.95 HE-896 HWM-1 Antenna Mount for above. Shpg. wt., 2 lbs. Net 7.50

Lafayette OUTSTANDING VALUES FOR CITIZENS BAND ANTENNAS & ACCESSORIES




NEW ALL STAINLESS STEEL CITIZEN BAND MOBILE ANTENNA

- OUTSTANDING FEATURES**
- 102 1/2" Stainless Steel Whip For Optimum 11 Meter Performance
 - Heavy-Duty Chrome Plated Stainless Steel Spring
 - Chrome Plated Swivel Ball Jointed Mount Base

6.95

Chrome swivel ball mount base designed to be mounted on any surface. Stainless steel spring holds rod in properly adjusted position and prevents rod damage from shocks and blows. Stainless steel whip for maximum resiliency and strength. Shpg. wt., 4 lbs. Has lug terminals for HP-52 cable assembly. HE-800WX Net 6.95

20 FT. RF COAXIAL CABLE ASSEMBLIES FOR CITIZENS BAND EQUIPMENT



• 2.95

• 2.45

These cable assemblies are necessary for connection between Citizens Band Transceiver and Antenna.

TYPE A—Consists of 20 ft. RG-58/U cable with PL-259 plus UG-175/U on both ends. Required for Ground Plane and Coaxial and Mobile Antennas terminating in a coaxial jack. Shpg. wt., 8 oz. Net 2.95

TYPE B—Same as type A except one end is terminated with PL-259 plus UG-175/U and other end with universal ring type terminal lugs for mobile antennas. Shpg. wt., 8 oz. RECOMMENDED FOR USE WITH HE-800WX MOBILE ANTENNA

HP-52 Type B 20 ft. length Net 2.45

LAFAYETTE GENERATOR NOISE FILTER

- Frequency Range 3-30 mcs
- Maximum Current 25 Amps
- Adjustable
- Simple to install



Eliminates whining and grinding noises created from generator brushes. Enables quiet receiver operation for Citizens Band, Amateur and industrial frequencies. Standard frequency range 3-30 mcs. Maximum current 25 amps. Installs quickly and easily. CF-135 Shpg. wt. 1 lb. Net 2.49

NEW! LAFAYETTE AUTO-MARINE ENGINE NOISE SUPPRESSOR KIT

- A Must For Mobile CB & Ham Operators
- 14 Components Plus Hook-Up Wire

This easily installed kit will effectively suppress ignition, generator and voltage regulator noise. Consists of 8 spark plug suppressors; 1 distributor suppressor; 1 voltage regulator suppressor; 4 coaxial capacitors; shielded cable and braid for wiring filter system. All necessary hardware and instructions for installation are included. Shpg. wt., 2 lbs. Net 9.45

NEW! "NOISTOP" IGNITION NOISE ELIMINATOR

Effective as both a noise limiter and a positive squealch the "Noistop" improves reliability and operating pleasure, when vehicle is in traffic. Measures only 1 1/2 x 2 1/2 x 4". Complete with tubes (6AL5 and 12AX7) and instructions for easy installation in most available transceivers. For use with super-heterodyne type transceivers. Furnished with cable and gold anodized cabinet with black perforated cover. Mounts in any position. Shpg. wt., 10 oz. Net 15.63

GENERATOR REGULATOR FEED-THRU NOISE SUPPRESSORS .95

These 3-terminal network feed-thru capacitors act as extremely effective R.F. filters above 2 MC. Eliminates and suppresses the majority of noises due to regulators and generators interfering with 27MC citizens band frequencies. Rated .1 MFD/600 Volts DC 20 Amps.

- Feed-Thru Suppressor (Screw Terminals) 1/4" Diam. x 1 1/4" length. Shpg. wt., 4 oz. SP-221 Net .95
- Feed-Thru Suppressor 1/4" Diam. x 1 1/4" length. Shpg. wt., 4 oz. SP-222 Net .95

NEW LAFAYETTE 12 POSITION CRYSTAL SELECTOR

Houses and selects up to 12 crystals - increases channel coverage. Chassis has 12 ceramic crystal sockets, wired to a 12 position, no stop selector switch. Long reach shaft permits practical mounting. Chassis size: 2 1/4" D x 2 1/4" W x 2 1/4" H. Shpg. wt., 1 lb. Net 8.50

NEW! CB BEAM AND ROTATOR A Real Package Deal!



Get Both for only **33.75!**


Nothing equals a yagi type beam antenna to pinpoint communications. Nothing adds to its directional capabilities, like a rotator with an easy-to-read direction indicating meter. And nobody but Lafayette has the package at a price to save the CB'er dollars. The antenna is a rugged, all aluminum, 3 element beam. Full 108x1" boom. Elements of 1/2" O.D. seamless aluminum, reinforcing inserts at strain points. Double boom brace for added support. The rotator features a meter type directional indicator, instantly reversible. 360° revolution in 50 seconds. Takes masts up to 1 1/2" O.D. Instant locking to prevent drift. Fully sealed against weather. Uses 4 wire cable. Shpg. wt., 25 lbs. Net 33.75

SP-248WX Net 33.75

WR-24 4 cond. flat cable per ft. .03; per C ft. 2.39

3 element CB Beam only. Shpg. wt., 12 lbs. Net 14.95

LAFAYETTE TELESCOPIC CITIZEN'S BAND WHIP ANTENNA




SENSATIONAL VALUE IN A DIRECT MOUNTING CITIZENS ANTENNA

3.95

Sturdy, attractive chrome plated whip antenna that telescopes from approx. 45" fully extended to only 15" to facilitate portability and storage. Ideal for shorter distances up to several miles. Has enclosed base loading coil for proper impedance matching. Complete with removable PL-259 connector that permits direct top, side or rear mounting to transceiver. Shpg. wt., 1 lb. Net 3.95

GROUND PLANE ANTENNA



Solid aluminum 108 inch heat-treated radials and radiator. Elements supplied in two 54 inch lengths joined by threading coupling nuts. Radials droop for 50 ohm match. Accepts 1 1/4 inch tubing RG-58/U cable and PL-259 connector. Shpg. wt., 4 lbs. Net 15.63

ANTENNA SPECIALISTS M-38 ANTENNA ISOLATING SKIRT

Improves Performance Of All Citizen Band Ground Plane Antennas

Isolating skirt for use with Citizen's Band Ground Plane Antennas. Mounts 9 feet (1/4 wave length) below ground plane (i.e. 27 MC). Lowers angle of radiation and minimizes effect of mounting structure. Improves performance of ground plane. Clamps to 1 1/4 inch tubing or 1 inch pipe. Shpg. wt., 4 lbs. Net 11.14

CITIZENS BAND RADIO MANUAL HANDBOOK H. W. SAMS


Includes PHOTOFACT® schematics, chassis photos, parts lists, etc., for 46 1960-61 CB Transceiver models. Special features on servicing CB equipment. BK-331 Net 2.95

1962 CITIZENS BAND CALL-BOOK

160 PAGES 8 1/2 x 11"

Up-to-date list of "Q" calls, special do-it-yourself section and 16 page CB equipment directory. Also lists CB clubs in U.S. and includes a log section. BK-1323 Net 3.95

MOSLEY A-311 3-ELEMENT CITIZEN'S BAND BEAM ANTENNA




36.75

- NO MONEY DOWN**
- Durable Light Weight Aluminum
 - Delivers the Equivalent Power Input of 40-Watts from your 5-Watt Citizens Band Transmitter

Unequaled point-to-point communications for Citizens Band operators. 9.3 db gain over dipole means the effective radiated power is multiplied by 8. This means your 5 watt Citizens Band Transmitter can actually achieve a legal effective power input of 40 watts. Boom is 12" long with maximum turning ratio of 9.5 ft. Requires 1 1/4" mast and RG-8/U or R9-58/U Cable. Lugs are supplied for the other end. Shpg. wt., 30 lbs. AN-57WX Net 36.75

CDR AR-22 AUTOMATIC ROTOR FOR CITIZENS BEAM



This heavy-duty rotor unit will handle antennas up to 150 lbs. Simply set the control unit pointer to the desired direction, and the antenna will automatically rotate to this position and stop. Perfect for TV, Ham or Citizen Band application. Rotor unit employs 12 heavy duty ball bearings in two 6 1/2" races. Weather-proof motor reverses instantly and is factory lubricated for life. Reversible clamps on rotor will take masts from 7/8" to 2" O.D. Control unit is marked in compass points. N.S.E.W. NW, NE, SW, and SE. Housed in attractive brown plastic cabinet with rubber feet. Complete with rotor, control unit and instructions. For 110-120 volts 50-60 cps AC. Requires 4 conductor cable. HE-476WX Net 32.77


4-Conductor cable for HE-476WX rotor WR-24 ea. ft. Net .03; 100 foot length Net 2.39

NEW! hy-gain CLR COLINEAR GROUND PLANE ANTENNA



A new concept in CB antenna design. Achieves gain through colinear action which concentrates more power at lower angles to the horizon. Performs equally well receiving or transmitting, greatly increasing the range of consistent CB communications. Precision tuned and matched for 52-ohm coaxial cable, either RG-8/U or RG-58/U Overall only 20-ft. high; radiator is 1 1/4" O.D. to 3/4" O.D. heavy wall heat-treated aluminum tubing. 9-ft. long radials of 3/8" O.D. aluminum tubing. Accepts all masts up to 1 1/2" diameter. Complete with matching stub and complete assembly instructions. Shpg. wt., 10 lbs. Net 29.37

MARK MOBILE HELIWHIP & MOUNT



The HW-11-4 "Heliwhip" is a fiberglass molded, continuously loaded whip antenna, four feet in length for the 11 meter Citizen Band. The HW-11-4 mounts in a HWM-1 molded mount or can be used with any good commercial mobile ball mount which will accept the 3/8" - 24 thread HE-895-WX HW-11-4 Fiberglass Antenna. Shpg. wt., 3 lbs. Net 9.95

HE-896 HWM-1 Antenna Mount for HW-11-4 Shpg. wt., 2 lbs. Net 7.50

NEW! LAFAYETTE BROADCAST TO CITIZEN BAND COUPLER



Specially designed network permits any Citizen's band mobile antenna to be used also for broadcast reception. No switching necessary. With SO-239 antenna receptacle, 2 ft. lead with coaxial auto plug for broadcast radio connection and 2 ft. lead with PL-259 coaxial plug for transceiver connection. Shpg. wt., 1/4 lb. Net 6.95

NEW! LAFAYETTE "DUMMY" ANTENNA LOAD FOR CB TRANSCEIVERS

A 52 ohm non-inductive load for testing and tuning-up Citizens Band transmitters up to 5 watts. It permits tune-up into a non-radiating element instead of into antenna - in compliance with F.C.C. regulations. Built-in PL-259 coaxial plug is easily connected and disconnected from equipment. Shpg. wt., 1 lb. Net .98

RG COAXIAL CABLES

These high quality coaxial cables are branded with RG type standard type numbers. Meets specifications outlined by U. S. Government Qualified Products List. R.G. 52-ohm cable is required for Ham and Citizens Band hook-up from the transceiver to antenna.

Stock No.	Type	Impedance	Net Per Ft.
WR 143	RG-8/U	52-ohms	.11
WR-144	RG-58/U	52-ohms	.05
WR-145	RG-59/U	72-ohms	.05

RIDERS CITIZEN BAND HANDBOOK No. 273

By Allan Lytel. Written for the user, prospective buyer and the service technician. Describes historical development, applications, classifications, and types of available equipment. Design features of different types of equipment are compared and analyzed in detail. The various elements of a CB station, and their maintenance, are all thoroughly treated. Includes a discussion of relevant FCC regulations. Soft cover. 160 pages, 5 1/2 x 8 1/2". BK-741 Postpaid in U.S.A. Net 3.82

NEW! LAFAYETTE CHROME PLATED MOBILE BUMPER MOUNT WITH STAINLESS STEEL STRAP

- Completely Adjustable For Use With Most Types of Automobile Bumpers
- Highly Reliable and Durable!

An outstanding new Lafayette chrome plated bumper mount featuring chrome plated mount and stainless steel strap which is completely adjustable for vertical mounting on most type of automobile bumpers. Eliminates need of cumbersome link type chain mounts. Shpg. wt., 1 1/2 lbs. HE-33 Net 3.95

NEW! hy-gain BPR UNIVERSAL BUMPER MOUNT with STRAP

- Chrome-Plated Mount
- Stainless Steel Strap

6.44

An attractive new bumper mount, heavily chrome-plated and attaches easily and quickly to most auto bumpers. Stainless steel mounting strap replaces the old-fashioned bulky bumper chain. Fully adjustable for vertical alignment. Shpg. wt., 1 1/2 lbs. HE-774 Net 6.44

MAGNUM-27 1/2 WAVE CB 27MC ANTENNA

Compact vertical radiator with an actual 6 DB gain over any single element omni-directional antenna. Constructed of rigid aluminum and cadmium plated steel, it is corrosion resistant, waterproof and fits on most masts or directly into wooden areas. Hi-Q phasing transformer provides proper resonance over entire CB band. Direct ground lightning protection. 50 ohm feed. Total height is only 18" 2" (17" 3" radiator, 4-54" radials. Shpg. wt., 12 lbs. HE-487WX Net 27.88

LAFAYETTE 27MC WALKIE-TALKIE TELESCOPING ANTENNA

Attractive and highly efficient 12 section chrome plated brass telescoping antenna for "walkie talkie" transceivers. Measures 52" fully extended and 57" retracted. Has #8-32 threaded stud and nut at bottom for easy mounting, and soldering lug for electrical connection. F-703 wt., 10 oz. Net 1.95

LAFAYETTE CITIZENS BAND 27MC COLLAPSIBLE ANTENNA

Ideal for mobile or fixed transceivers, miniature portable and pocket transistor radios, and a host of similar applications. The 4 section antenna is made of chrome-plated brass and plugs into a jack. Measures 48" fully extended and retracted is 11" to facilitate carrying in pocket. Complete with a flexible plastic case and slip-under protecting flap. Shpg. wt., 8 oz. F-440 Net .79

RF COAXIAL CONNECTORS

Stock No.	Type	Description	Net
SP-174	PL-259	Male conn. for direct connection into transceiver or antenna	.59
SP-175	UG-175/U	Reducer—Adapts PL-259 to RG-58/U Diam.	.16
SP-176	PL-258	Junction Adapter—Accepts PL-259 on both ends for cable extension	.89

CITIZENS BAND CONNECTOR ADAPTERS

Stock No.	Type	Description	Net
HP-53	SO-239	Adapts an SO-239 Socket to a Standard auto radio (Motorola type) socket. Av. Shpg. wt., 2 oz.	Net .44
HP-54	PL-259	Adapts a PL-259 Plug to a standard auto radio (Motorola type) plug. Avg. shpg. wt., 4 oz.	Net .54

LAFAYETTE 27 MC CITIZENS BAND CRYSTALS FOR POPULAR CB TRANSCEIVERS

Selected Lafayette Receive and Transmit Crystals

Stock No.	Type	Description	Net
HE-830	(Specify Channel)	Transmit crystals for Lafayette HE-15A, HE-29A, HE-20A, RCA, Mark VII, E. F. Johnson Messengers	Net 2.25
HE-255L	(Specify Channel)	Transmit Crystal for Vocaline ED27M	Net 2.25
HE-22	(Specify Channel)	Receive Crystal for Lafayette HE-20A, RCA Mark VII	Net 2.25
HE-758L	(Specify Channel)	Receive Crystal for Lafayette HE-29A	Net 2.25
HE-833L	(Specify Channel)	Receive Crystals for E. F. Johnson Messengers	Net 2.25
HE-538L	(Specify Channel)	Selected Lafayette Matched Crystals (Receive/Transmit) For Gonset G12 and G14 Transceivers	Net 4.50
HE-297L	(Specify Channel)	For Polytronics PCIG and PCN Transceivers	Net 4.50
HE-831L	(Specify Channel)	For Osborne 300 (all transistorized) CB Transceiver	Net 4.50
HE-832L	(Specify Channel)	For Sonar Model E	Net 4.50

Sensational Values In Lafayette Communication Receivers!

LAFAYETTE AMATEUR COMMUNICATIONS RECEIVER

SUPERHETERODYNE CIRCUIT UTILIZING 8 TUBES & RECTIFIER TUBE



KT-200 SEMI-KIT

64.50

HE-10 WIRED 79.95

- BAND SPREAD FOR EASY TUNING • BUILT-IN "S" METER WITH ADJUSTMENT CONTROL • EXCELLENT SELECTIVITY • ACCESSORY POWER SOCKET PROVIDED • ALL TRIMMERS PRE-ALIGNED • COVERS 550KC. TO 31MC. IN FOUR BANDS • VARIABLE BFO AND AF + IF GAIN CONTROLS • SWITCHABLE AVC & AUTOMATIC NOISE LIMITER • ALL MAJOR COMPONENTS PRE-MOUNTED • DUAL 4 AND 8 OHM OUTPUT IMPEDANCES • 1 RF + 2 IF STAGES FOR HIGH GAIN RECEPTION

The KT-200 represents a significant departure from usual kit designs. As soon as it is unpacked, it is already half finished. All of the mechanical mounting is completed. Tube sockets, transformers, main tuning capacitor, filter capacitor, controls, even knobs and pilot lamps are all in place. The tuning assembly is installed and operative. Most important of all, the complex coil assembly and alignment capacitors for the oscillator, mixer and rf amplifier stages are factory mounted and pre-aligned. Thus only a slight touch up will be required to achieve maximum sensitivity and selectivity. Features such as built-in "S" meter with

adjustment control, switchable AVC and automatic noise limiter make the KT-200 worth many times its low price. Supplied with all components.

KT-200WX Net 64.50

HE-10WX Same as above, factory wired & Tested Net 79.95

Ideal "SPEAKER MATE" for HE-10 and other communications receivers. Special 4" speaker in handsome, tapered, grey metal cabinet reduces QRN and peaks voice frequencies. Impedance 8 ohms. 7 1/2 x 5 3/8 x 4 3/4". Shpg. wt., 4 lbs.

HE-11 Net 7.95


SPECIFICATIONS:

AM, 80-40-20-15-10 meter bands. Pre-calibrated band spread. Sensitivity: 1.25 mv for 10 db Signal-to-noise ratio. Selectivity: ± 10KC. -60db (at 1MC). Audio Output: 1.5 watts. Tubes: 3-6BD6, 2-6BE6, 2-6AV6, 1-6AR5, 1-5Y3. Power: 100-125 V AC 50 60 cps. Size: 15 1/2 L x 8 1/2 H x 12" D. Shpg. wt., 22 lbs.

ELECTRONICS ILLUSTRATED

"... even the most inexperienced constructor should have no trouble."
"Sensitivity was so great the IF gain had to be turned all the way down to prevent overloading."

15 73
"... excellent value"
"... rugged, well made, and uses good components"



RECEIVER SPEAKER-MATE

HE-11 7.95



NEW! LAFAYETTE Professional QUALITY AMATEUR COMMUNICATIONS RECEIVER

HE-30 WIRED 99.95

NO MONEY DOWN

KT-320 SEMI-KIT

79.95

SUPERHETERODYNE CIRCUIT UTILIZING 8 TUBES & RECTIFIER TUBE

- 8 TUBES PLUS RECTIFIER TUBE
- 1 RF + 2 IF STAGES FOR HIGH GAIN RECEPTION
- EASY-TO-READ, ILLUMINATED, SLIDE RULE DIAL
- BUILT-IN Q-MULTIPLIER FOR CROWDED PHONE OPERATION
- ANTENNA TRIMMER FOR OPTIMUM PERFORMANCE ON ALL BANDS
- CALIBRATED ELECTRICAL BANDSPREAD ON AMATEUR BANDS 80 THRU 10 METERS
- 0-100 LOGGING SCALE FOR SWL'S
- EFFECTIVE AUTOMATIC NOISE LIMITER
- AVC-MVC SELECTOR ON FRONT PANEL
- STABLE OSCILLATOR AND BFO FOR CLEAR CW AND SSB RECEPTION
- BUILT-IN EDGEWISE S-METER



HE-11 7.95
RECEIVER SPEAKER-MATE



Designed for today's crowded amateur bands and the discerning Short Wave Listener, the new Lafayette HE-30 offers features and performance previously unheard of at this price. Outstanding Bandspread, Selectivity with a built-in Q-multiplier, and sensitivity combine to make the HE-30 one of the "hottest" general coverage bandspread receivers ever priced below \$200. For the crowded amateur bands—ILLUMINATED SLIDE RULE DIAL, bandspread with markings every 5 KCS on 80 and 40 meters (IT TAKES 16 REVOLUTIONS OF THE BANDSPREAD DIAL TO COVER EACH OF THESE BANDS), every 20 KCS on 20 and 15 meters, and every 50 KCS on 10 meters, plus an edgewise S-meter. For the SWL—a 0-100 logging scale for "instant reset" to a desired station plus coverage from 0.55-30 MCS. The 8 tube (plus a husky 5Y3 Rectifier) circuit provides an RF stage with an antenna trimmer for peak performance PLUS 2 IF stages for improved selectivity. Far from an "empty shell" receiver, the HE-30 utilizes a 5Y3 tube in a transformer Full Wave rectifier power supply. This suppresses ripple and hum that often produces poor CW and SSB reception in "stripped down" receivers. Receiver sensitivity—that important difference between hearing and not hearing

stations—1.0 microvolts for 100db Signal-to-Noise Ratio. The Built-in BFO can be used to separate CW stations by means of the pitch control, while the Q-multiplier adds the selectivity needed for crowded phone band operation. The front panel controls speak or themselves—FUNCTION SWITCH, AUDIO GAIN, SELECTIVITY (Q-Multiplier), FREQUENCY (BFO), BAND SELECTOR, IF GAIN, TRIMMER, AVC-MVC SWITCH, ANL SWITCH, MAIN TUNING BANDSPREAD TUNING, and headphone jack. We invite comparison. Selectivity—60db at 10KC. 0.8 KC @ 6db (with Q-multiplier), IF—455KCS. Speaker—External PM type (not supplied), 4 or 8 ohms impedance. Audio Output—1.5 watts. Tubes—6BA6—RF Amplifier. 6BE6 Mixer. 6BE6—Oscillator, 6AV6-Q-Multiplier—BFO, 2-6BA6—IF Amplifier, 6AV6—Detector—AF Amplifier—ANL 6A05—Audio Output. 5Y3—Rectifier. Size—7Hx15Wx10"D. For 105-120. 60 cps AC. 50 watts.

HE-30WX Shpg. wt., 25 lbs. Net 99.95

NEW! KT-320 SEMI-KIT

This receiver is also available in kit form with all major components and front end pre-mounted and pre-calibrated. All other components supplied for easy mounting.


KT-320 Semi-Kit Net 79.95

54.50
NO MONEY DOWN

NEW!

LOW COST 4-BAND SHORTWAVE BROADCAST RECEIVER

- Electrical Bandsread • Built-in "S" Meter
- 3 Short-Wave Bands, 1 BC Band • AVC — Noiselimiter • Big 5 Inch Speaker • BFO
- Phone Jack



IN A SMARTLY STYLED DURABLE METAL CABINET

Now, you can tune in the world with this fabulous, new Lafayette HE-40 BC-SW receiver. Keep up to date with on the spot news coverage. Power packed superheterodyne circuit covers the broadcast band (550-1600 KC) and short-wave from 1600 KC to 30 MC in four bands. The perfect radio for shortwave listeners. Features a precision electrical bandsread with slide rule bandsread dial, 0-100 logging scale for easy self-calibration. Separate bandsread tuning condenser and calibrated "S" meter for accurate tuning. Meter can be electrically adjusted by rear panel control. Sensitive circuit features AVC (Automatic Volume Control) to minimize blasting and/or fade out; Automatic noise limiter to reduce annoying interference. Includes convenient front panel B.F.O./selectivity control to allow for reception of CW (telegraphy). Also has convenient front panel headphone jack which automatically disconnects

speaker. Jack can be used to drive an external speaker. Built-in 5" PM speaker provides big, clear sound on all stations. Useful tone switch is included to vary sound to suit conditions, or taste. Three antennas (ferrite loop for broadcast band, adjustable 58" whip for short wave and wire antenna) provide high sensitivity and flexibility for best reception. Low impedance phones are recommended for use with this unit. Evenly illuminated dial for nighttime tuning. Attractively styled steel cabinet with silver trim. Powered by 4 tubes plus a selenium rectifier. 1-12BE6; Converter, 1-12BA6; IF Amplifier, B.F.O., 1-12AU6; Audio Amplifier AVC detector; 1-50CS; Audio output. Operates on 105-125V; 50/60 cycle AC/DC. Size 13 1/2 W x 5 7/8 H x 8 3/4" D. Shpg. wt., 12 lbs.

HE-40 Net 54.50



AMATEUR SHORTWAVE EQUIPMENT and ACCESSORIES

New!
National
105



A new general coverage receiver which features remarkable performance for the amateur, shortwave listener and hi-fi enthusiast. An efficient fixed tuned peaking type Q multiplier provides continuously variable IF selectivity to meet any listening requirement—from 7 KC for full fidelity music reception to 500 cycles for crowded CW band conditions. Large edge-type illuminated S-meter operates during AM, SSB and CW reception. Separate combination BFO/product detector assures maximum performance during SSB and CW reception. Calibration charts are provided for all popular amateur and foreign broadcast bands. Exclusive tuner output permits detector to be fed into hi-fi amplifier for quality reception for taping SW. Tunes 550K to 30MC in four bands. Available in either a functional steel cabinet or custom oiled walnut enclosure. Dimensions (in steel cabinet) 7 1/2" H x 13 1/2" W x 8 5/8" D. For 105-125 A.C., 60/60 cycles. Shpg. wt., 27 lbs.
 HE-222WX Steel Cabinet Net 119.95
 HE-223WX Oiled Walnut Cabinet Net 139.95

New HAMMARLUND
HQ-100A



Continuously tunable from 540 Kc to 30 Mc in four bands. Accurately calibrated electrical bandspread on the 80, 40, 20, 15 and 10 meter bands. Sensitivity: 1.75 microvolts for 10-1 signal-to-noise ratio. One r.f., 2 i.f. stages. Temperature compensation, voltage regulation and rugged construction in the separate high-frequency oscillator section result in high stability. Other features: Q-multiplier for variable selectivity, AVC, variable BFO, effective series noise limiter. "S" meter, panel-controlled antenna compensator. "Auto-Response" feature automatically adjusts audio bandwidth to fit receiving conditions. For 105-125V, 50/60 cps. Dimensions: 16 1/4" x 9 3/4" x 4 1/8" D. Shpg. wt., 33 lbs. Net 189.00
 MODEL HQ-100 AC Receiver w/clock Net 199.00
 HE-174WX Shpg. wt., 33 lbs.
 MODEL S-100. Matching speaker Net 14.95
 HE-152 Shpg. wt., 10 lbs.
 MODEL XC-100, 100 KC crystal calibrator. Net 15.95
 HE-153 Shpg. wt., 3 lbs.

SENSATIONAL LAFAYETTE
ANTENNA PACKAGE FOR AMATEURS
YOU SAVE 24.83
 Reg. Price 144.78 Lafayette Price **119.95**

ON SYSTEM CONSISTING OF:
 • CDR AR-22 Heavy Duty Automatic Rotor
 • Hy-Gain TH-3 3 Element Antenna
 • 100' RG-8/U Cable • 100' Rotor Cable

CDR AR-22 AUTOMATIC ROTOR
 This heavy-duty rotor unit will handle antennas up to 150 lbs. Simply set the control unit pointer to the desired direction, and the antenna will automatically rotate to this position and stop. Perfect for TV, Ham or Citizen Band application. Rotor unit employs 12 heavy duty ball bearings in two 6 1/2" races. Weather-proof motor reverses instantly and is factory lubricated for life. Reversible clamps on rotor will take masts from 7/8" to 2" O.D. Control unit is marked in compass points. N.S.E.W. NW. NE. SW, and SE. Housed in attractive brown plastic cabinet with rubber feet. Complete with rotor, control unit and instructions. For 110-120 volts 50-60 cps AC. Requires 4 conductor cable. Net 32.77

NEW! Hy-gain TH-3 3-ELEMENT ANTENNA
 The finest 3-element trap tribander for amateur communications on 10, 15 and 20 meters. All-aluminum construction of 2" OD beams and 1 1/4" telescoping to 3/4" OD elements. Plastic and steel gusset bracket assemblies, all steel fixtures and hardware. 100% rust proof. Less than 2 to 1 SWR on all bands. New "solid state" slim traps (1 1/2" in diam.). Withstand 1000 watts CW or AM and 2000 watts SSB. Overall beam length 14 ft., longest element 26 ft. Shpg. wt., 29 lbs. Net 99.75
 HE-773WX Net 9.87
 WR-131 100-Ft. RG-8/U Coaxial Cable Net 9.87
 WR-151 100-Ft. 4 Cond. Rotor Cable Net 2.39

SPECIAL LAFAYETTE PACKAGE
 Includes: AR-22 Rotor; TH-3 3 Element antenna; 100' RG-8/U; 100' 4 Cond. Rotor Cable. Net 119.95
 SP-228WX Shpg. wt., 61 lbs.

hallicrafter




NEW! HALLICRAFTER S-120 RECEIVER



Covers Broadcast Band 550-1600 KC plus 3 Short Wave Bands 1600 Kc to 30 Mc. 3 Antennas, Slide Rule Bandspread Dial, New Compact Styling.
 This new precision built receiver features electrical bandspread with slide rule bandspread dial and separate bandspread tuning condenser. Front panel headphone jack which automatically disconnects self-contained speaker may be used to drive remote 8 ohm speaker. Has 3 antennas (ferrite loop for broadcast band; adjustable whip for short wave; wire antenna). Tube complement: 12BE6 Converter, 12BA6 I-F amplifier, B.F.O., 12AV6 Audio amplifier, AVC detector, 50C5 Audio, plus Selenium Rectifier, 455KC IF. Attractive gray steel cabinet with silver trim. 13 1/2" W x 5 7/8" H x 8 3/4" D. (U/L Approved). Operates on 105-125V 50/60 cycles AC/DC. HE-127 Shpg. wt., 12 lbs. Net 69.95

HY-GAIN SWI INDOOR SHORTWAVE ANTENNA



Convenient indoor Model SWI improves the performance of any shortwave receiver. Covers 5-30 Mc. Easy to install and operate. Six-foot cable (included) is attached to receiver, the telescoping "rabbit ears" extended, and the "match" and "tune" controls set for maximum signal strength. Attractively housed in unbreakable plastic with chrome-plated antennas. Model SWI. HE-973 Shpg. wt., 2 1/2 lbs. Net 14.35

AMECO HP-45 FILTER



HE 402 High-pass TVI filter. Shpg. wt., 3 oz. Net ea. .93

LAFAYETTE AMATEUR COMBINATION SPECIAL



By purchasing Hallicrafters S120 Receiver plus Hy Gain SWI Indoor Antenna plus Ameco HP45 High Pass Filter. Net 74.95

Multi-ELMAC
AMATEUR EQUIPMENT
AF-68 TRANS-CITER



Covering the 80, 40, 20, 15, 10 and 6 meter amateur bands on CW and AM, the AF-68 can be used as a VFO or crystal controlled exciter, speech amplifier, driver, or complete low powered transmitter. Ideal for mobile or fixed operation. Input, 60 watts to a 6146 final, with pi network coaxial output matching a wide range of impedances. Single control bandswitching. Five circuit illuminated panel meter indicates grid current P.A. off, grid current P.A. on, plate voltage, modulator plate current, and final plate current. Built-in temperature compensated VFO has output on 3.5-4.0 Mc, 7.0-7.5 Mc, or 12.5-13.5 Mc. VFO spotting switch provided. Crystal socket holds two crystals. Audio output of 30 watts at 600 ohms available, as well as various combinations of RF output, such as RF driver, buffer, and VFO. Filaments operate on 6 or 12 volts. External power supply and microphone required. Size: 13 1/2" W x 6 1/2" H x 7 1/2" D. Shpg. wt., 21 lbs. Net 205.00
 HE-940WX

PMR-8 RECEIVER
MOBILE OR FIXED



Highly sensitive and selective double conversion receiver for mobile or fixed stations, covering 80, 40, 20, 15, 10, and 6 meters (50-52 Mc), plus the standard broadcast band. Ideal companion to the AF-68. Sensitivity: 0.5 microvolt for 10 db quieting. Selectivity: 3 Kc at 6 db down, 12 Kc at 60 db down. Second conversion oscillator crystal controlled; first conversion (variable) oscillator temperature compensated, with regulated voltages on plate and filament. Other features: tuned RF stage, delayed AVC, effective noise limiter, calibrated BFO. Antenna input 52 or 72 ohms. Filaments operate on 6 or 12 volts. Headphone jack included. External speaker and power supply required. HE-941WX Size 4 1/2" x 9 1/2" x 7" Shpg. wt., 11 lbs. Net 189.50
 HE-1070 Power supply for AF-68 and PMR-8. For 6 or 12 volts DC, or 115 volts, 50/60 cps AC. Shpg. wt., 15 lbs. Net 69.50
 HE-942WX

HAMMARLUND HQ-105TR CB AND HAM BAND TRANSCEIVER FOR 10 & 11 METERS



NEW
219.50
NO MONEY DOWN

Versatile citizens band transceiver with built-in provision for ham band operation. Transmitter can easily be retuned for 10 meter operation—ideal for the citizens band operator who wishes to have immediate access to an amateur band upon the arrival of his general class license. Also ideal for the amateur operator wishing to use a single unit for both his hobby and his business. Transmitter has 5 watt input, 100% amplitude modulated, for both CB and 10 meter operation. Receiver is continuously tunable from 540 Kc to 30Mc, with accurately calibrated electrical bandspread on the 80, 40, 20, 15 and 10 meter bands, plus the citizens band. Other receiver features approximately equivalent to those of the new HQ-100A. Size 16 1/4" L x 9 3/4" H x 9 1/8" D.
 HE-148WX HQ-105TR, less clock. Net 219.50
 Shpg. wt., 34 lbs. Net 9.87
 HE-149WX HQ-105TRC, w/clock timer Net 229.50
 Model S-100 Matching speaker. shpg. wt., 10 lbs. Net 14.95
 HE-152

NEW! HE-34 SWR AND FORWARD POWER METER



A compact SWR and relative power meter which can be permanently inserted into a 52 ohm coaxial line to monitor transmitter and antenna performance. The ideal aid in adjusting beams, trap antennas, matching networks, etc., or for tuning transmitters for maximum output. Designed for the frequency range from 3 to 200 mc, and for powers from 25 watts to a full kilowatt. Above 7 Mc, as little as 10 watts will provide adequate sampling; above 100 Mc, as little as 5 watts. The unit is installed by means of a standard coaxial connector on each side, and becomes part of the 52 ohm line. Insertion loss is negligible. Once installed the unit need never be reversed. A switch on the front panel is set to SWR SET for relative forward power readings up to 1 KW on a scale calibrated from 0 to 10, and for adjustment of the sensitivity control for SWR readings. The switch is set to SWR for measurement of reflected power, on an SWR scale calibrated from 1:1 to 100:1. The HE-34 measures only 2 1/2 x 5 x 2 1/2", excluding coax connectors. Imported. Net 16.95
 HE-34 Shpg. wt., 1 1/4 lbs.

National **60 SPECIAL "B" RECEIVER**



National's new all-wave low-priced receiver which features continuous coverage of AM Broadcast, Amateur and World Wide Short Wave Bands; brilliantly styled by Peter Quay Yang for easy operation, ready reading and attractive decor. Features include: 4 separate bands—540 Kc-1600 Kc; 1.6-4.5 Mc; 4-12 Mc; 10.5-31 Mc with police, CD, marine, aircraft, amateur, etc. stations clearly marked; plus 0-100 logging and bandspread scale. Bandspread operative on all bands. Audio section drives built-in speaker or front panel phone jack. Has AM, CW switch, standby-receive switch, 2 degrees of selectivity, complement of 4 tubes plus rectifier, superheterodyne circuit. Finish is two tone black and gray enamel. Size: 7 3/8" x 8 5/8" x 13 1/2". Shpg. wt., 15 lbs. Net 59.95
 HE-200WX

FREE WITH PURCHASE
OF NC-60 SPECIAL "B"

ME-42
KT-77
REGULAR PRICE 3.40

KT-77 Shortwave Antenna Kit. Shpg. wt., 1 1/2 lbs. Net 1.05
 ME-42 Headset. Shpg. wt., 1 1/2 lbs. Net 2.35
SPECIAL LAFAYETTE OFFER
 HE-200WX plus KT-77 plus ME-42. Shpg. wt., 18 lbs. Net 59.95
 SP-178WX

HARTMAN SHIP-TO-AUTO ALL TRANSISTOR CONVERTER



ONLY 19.95
LISTEN TO:
 • Ship-to-Ship Broadcast • Marine Telephone • WWV • Coast Guard (weather) • Ship-to-Shore Conversations

Now you can listen to marine broadcasts on your car radio. A flick of the switch and your auto radio becomes a powerful long range marine receiver. Switch back and it plays the normal broadcast band. All transistor circuitry uses only 1/2000 of an amp from built-in battery; virtually the batteries entire shelf life. Converter selects any frequency between 2000 KC and 3000 KC. Operates with either 6V or 12V automobile ignition system. Net 19.95
 HE-646

NEW! TM-58 SWR BRIDGE & RF POWER METER



• Measures RF output Power Into Built-in 52 Ohm Dummy Load, Up to 15 Watts
 • Measures SWR and Relative Power Up To 1 KW

Here is a quality instrument which will give highly accurate SWR and direct power readings up to 50 Mc. The unit may be permanently inserted in the transmission line for SWR and relative power monitoring. When the 3-position selector switch is set to POWER, the meter will indicate the RF power up to 15 watts, into a built-in 52 ohm resistive load employing quality non-inductive resistors. Full scale accuracy is 10%. The selector switch is set to SWR SET to read relative forward power up to 1 KW and to adjust the sensitivity control for SWR measurements. For direct SWR measurements from 1:1 to 4:1 with powers up to a kilowatt, the selector switch is set to SWR. Unit is inserted into the transmission line by means of two standard coax connectors, and 2 slide switches are set to 52 or 75 to correspond with line impedances of 52 or 75 ohms, respectively. Insertion loss is negligible. Meter has 50 μ a movement; calibrated directly in watts from 0-15, and in SWR from 1 to 4 (reads infinity at full scale). Housed in an attractive grey metal cabinet, 3 1/2" x 7 1/4" x 2 3/8". Sits on 4 rubber feet. TM-58 Shpg. wt., 2 lbs. Net 27.95

NEW! LAFAYETTE TM-26 ILLUMINATED COMMUNICATIONS 2 3/8 "S" METER



Only 3.95

• Replaces Many Communications Receiver "S" Meters
 • 2 Jewel Movement • Clear Plastic Front
 • Calibrated to S9 + 40 db
 • BIG BROTHER TO THE LAFAYETTE TM-11

A new signal strength meter (basic 1 ma, 2 jewel movement) designed to replace many "S" meters used in communications receivers. Clear plastic front measures 2 3/8" square and meter fits standard 2 1/2" round hole. Perfect for the experimenter and amateur. Complete with mounting screws, instructions for installation and use. For 6 volt or 12 volt operation. Zero adjustment control on front panel. Imported. Shpg. wt., 1 lb. Net 3.95
 TM-26

NEW LAFAYETTE HE-26 HYBRID PHONE PATCH



Enjoy the pleasure of handling phone patch traffic with this deluxe hybrid patch. Hybrid circuit permits use of AM or SSB with voice control by effectively isolating the receiver audio output from the transmitter audio input. Provides an accurate balance between 500 ohm line and station equipment—with negligible insertion loss. Four connections on rear for receiver output (voice coil, 3-4 ohms), transmitter input, Station microphone, and telephone. Easy to operate after a few preliminary adjustments, all from the front panel. Null and balance controls are adjusted, with the aid of readings on the edgewise panel VU meter, for balance and maximum receiver-transmitter isolation. Thus the receiver audio signal, which would ordinarily trip the VOX circuit, is balanced out from the transmitter audio section. The gain control is adjusted for proper transmitter and receiver audio level, VU meter continuously monitors line level. The patch can be switched in and out by means of a front panel switch, so that it may be permanently installed. Compact, sloping cabinet will fit into any station arrangement. Sits on 4 non-slip rubber feet. Size: 3 1/2" H x 5 1/2" W x 4" D. Net 24.50
 HE-26 Shpg. wt., 3 lbs.

LAFAYETTE
HYBRID PHONE PATCH



24.50

LAFAYETTE—Build Your Own KITS....

NEW!
LAFAYETTE KT-199
2-TRANSISTOR
DIODE BROADCAST
RADIO KIT

Made in U.S.A. + **POWERFUL REFLEX CIRCUIT**


AR-50

- No Soldering—A Child Could Build It!
- Pre-wired Switch and Control
- 50 Mile Range
- Beautifully Styled Cabinet

Absolutely no soldering or hole punching is necessary. All wiring and components are connected to fahnstock clips mounted on a pre-punched board. It is the ideal kit for beginners interested in transistor circuits. The on-off switch and level control are already pre-wired—just clip them in. A clear construction manual is included with simple How-To-Do-It instructions so that a child could build it. And that's not all. Lafayette engineers have designed this transistor radio to have a receiving radius of approximately 50 miles! Only one 9 volt battery powers its 2-transistor reflex circuit. Ferrite core loop antenna and a variable gang tuning condenser insure crisp reception on the entire AM broadcast band from 550-1600KC. Will accept any high impedance earphone for private listening. Size: 5½x2½x4¾"D. 2-2N165 PNP transistors, 1N48A diode. Complete with instruction manual Shpg. wt., 1½ lbs. KT-199 Complete 2 transistor kit—less earphone and less battery Net 9.95

AR-50 Dynamic earphone 3,000 ohm Net 1.39
 BA-2 9-volt battery Net .39

New! LAFAYETTE KT-196 2-STATION INTERCOM SYSTEM KIT



Made in U.S.A.

- Attractive, Modern Styling
- Complete—One Master and One Remote Station Plus 50 Ft. of Cable
- Perfect as Baby Sitter or Sickroom Watcher
- 2 Complete Stages of Amplification

14.75

The perfect 2-station intercom kit beautifully styled and engineered by Lafayette's Kit Divisions, it will grace any room in the home, office, shop, school, etc. Consisting of a Master Station and a Remote station, most useful to communicate with the basement, garage, playroom or nursery. The master unit features a highly sensitive 3-tube circuit with 2 complete stages of audio amplification for maximum talk-power and sensitive reception. Makes a marvelous "baby-sitter." Remote unit may be left in permanent "Talk" position. Master Station has a 3-way lever switch which provides Momentary Talk, Listen, and a lock-in talk position to free hands for other duties or for extended conversation. Master station front panel also includes a combined on/off switch, volume control. Only the master unit need be plugged into outlet—remote may be placed anywhere. The system may use up to 3 remotes. Famous Lafayette instruction manual simplifies assembly. Size of each unit: 4Hx8Wx4¾"D. Attractive metal enclosures. Tubes: 36AM3A, 60FX5, 18FY6. Complete with all parts necessary and 50 feet of 3-wire cable. For 105-125V 50-60 cycles AC or DC.

KT-196 2-Station Intercom Kit. Shpg. wt., 7 lbs. Net 14.75
 LA-196 Factory Wired Net 19.50
 Extra Remote Station Kit—For use with above. Less cable. Net 3.45
 KT-197 Shpg. wt., 2½ lbs. Net 3.45
 LA-197 Factory Wired Remote Net 3.95
 Hook-up wire for above. per ft. Net .03
 WR-160

NEW!
LAFAYETTE
KT-195
WIRELESS BROADCAST
AMPLIFIER KIT

Made in U.S.A.

Use it either as a Wireless Broadcaster or AM Audio Amplifier!

- POWERFUL SIGNAL
- PLAYS THROUGH ALL AM RADIOS
- WORKS WITH ALL CRYSTAL AND MAGNETIC MIKES AND PHONO CARTRIDGES

11.95

Treat yourself and your family to hours of fun with this new Lafayette Kit. Make your own radio programs, announcements, etc. through AM radios anywhere in the house, without wires or extra gadgets. Designed for easy construction by youngsters or adults, the KT-195 combines in one compact unit a powerful 3-tube wireless broadcaster and an audio amplifier. Clearly written instruction manual makes it a cinch to build. Operates on any frequency between 900 and 1600 kilocycles on your radio dial. It will accept any crystal or magnetic microphone. In addition, the KT-195 may be used directly as a phono or microphone amplifier. No external preamp is required. Simple slide switch permits either form of operation. Just connect it to a PM speaker (4-16 ohms). Conforms to FCC regulations and is designed to provide high quality voice record broadcasts. Within this range, however, the unit can produce high quality voice or record broadcasts. No license or permit is necessary. Complete with crystal clear in-styled metal cabinet suitable for any decor. Size 4Hx8Wx4¾"D.

KT-195 Shpg. wt., 3 lbs. Net 11.95
 Same as above, but factory wired and tested. Net 14.45
 LA-23 Crystal microphone for above. Desk or hand held. 8 ft. cable. Net 2.95
 PA-73 Shpg. wt., 1 lb.

New! 20-in-1 TRANSISTOR Experimenters KIT

FUN TO BUILD — EDUCATIONAL — and all 20 projects result in a useful working instrument

SUPER-SENSITIVE PHOTOCELL
ELECTRONIC RELAY KIT

• WITH CLAIREX CADMIUM SULPHIDE PHOTOCELL • ADJUSTABLE SUPER SENSITIVITY—WORKS WITH JUST A FLASHLIGHT AT 250 FEET!
 • NEEDS NO SPECIAL HIGH-INTENSITY LIGHTS • INSTANTANEOUS OR SUSTAINED OPERATION ON THE FLIP OF A SWITCH!

MADE IN U.S.A.

12.95

Ideal for sustained operation required for burglar alarms, door buzzers and for instantaneous on-off operation required for counters, packaging, door opening, motor activation plus countless industrial applications. Switch converts unit from instantaneous "on-off" to sustained "on" operation. "RESET" switch renews "on-off" and turns off the alarm. The unit opens the external circuit and incorporates the efficient 5823 operates on 110 volts AC and incorporates the efficient 5823 cold cathode tube. A simple change in wiring (in instructions) as well as convenient input terminals, enable you to supply the external circuit with any desired voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on 110 volts AC. Complete with all parts, photocell, tube, chassis, silk-screened metal cabinet and easy-to-follow illustrated instructions. Size: 3x4x5" Net 12.95
 KT-133A Kit, Complete. Shpg. wt., 3 lbs.

PROJECTS YOU BUILD

MADE IN U.S.A.

SIMPLE TO FOLLOW SCHEMATICS

1. TRANSISTOR TESTER
 2. VOICE ACTUATED ALARM
 3. PHOTO TIMER
 4. AUDIO AMPLIFIER
 5. CRYSTAL SET
 6. SOLAR RADIO
 7. RAIN ALARM
 8. TIMER
 9. ONE TRANSISTOR RECEIVER
 10. CODE PRACTICE OSCILLATOR
 11. METRONOME
 12. TWO TRANSISTOR RECEIVER
 13. ELECTRONIC GAME
 14. HOME BROADCASTER
 15. PHOTO ELECTRIC RELAY
 16. BURGLAR ALARM
 17. WIRELESS TRANSMITTER
 18. REGENERATIVE RECEIVER
 19. CITIZENS BAND MONITOR
 20. AUDIO OSCILLATOR
- This new Educational Kit opens the field of transistor-electronics, with all its fascinating circuits and gadgets, in a simple, easy-to-follow manner. Excellent for beginners as well as advanced experimenters, this kit enables you to build and learn about 20 interesting and useful transistor circuits. By utilizing "Breadboard" construction, each project can be simply wired and traced. After building the basic circuit, any of the 20 projects can be built by simply inserting a few preassembled component blocks and interconnecting leads between them. A soldering iron is only required for the basic wiring and not for subsequent projects. All wiring is covered in a step-by-step manner by the instruction manual. Each of the 20 projects is clearly presented with step-by-step instructions, large easy-to-read pictorial wiring diagrams, schematic diagrams, and an explanation of the circuit behavior. There are no AC voltages to produce shock hazard. Amaze your friends with a Voice-Actuated Alarm, Rain Alarm, Home Broadcaster, and other projects. Build useful projects for the home—Metronome, Burglar Alarm, and Timer. Learning Morse Code with the Code Practice Oscillator and receiving Short-Wave Citizens Band Stations. The kit is complete with perforated mounting board, 2-transistors, 1-diode, earphone, light sensitive plate, and all other parts required for construction. The detailed 28 page instruction manual contains a wealth of information about each project. Less batteries and tools. Shpg. wt., 6 lbs. Net 18.95
 KT-173 Complete Net .095
 BA-155 Z Cell Battery for Kit projects Net 1.61
 BA-270 22½ Volt Battery for Kit projects

LAFAYETTE 10-IN-1 LABORATORY KIT



WITH THIS KIT YOU CAN BUILD

1. RADIO RECEIVER
2. PHONO-MICROPHONE AMPLIFIER
3. PHONO OSCILLATOR
4. BROADCAST STATION
5. CODE PRACTICE OSCILLATOR
6. SIGNAL TRACER
7. CAPACITY OPERATED RELAY
8. ELECTRONIC TIMER
9. ELECTRONIC SWITCH
10. PHOTOCELL RELAY

Here is a new laboratory tested experimenters kit designed to provide maximum instruction and entertainment and which is ideal for both the beginner and advanced experimenter. Features practical and interesting circuits which enable you to do many novel and interesting things while learning how these circuits function. You can broadcast your voice or play a phonograph through your radio from anywhere in the house, send code through a headphone or radio, or use light or body capacitance to activate electrical circuits. Safe, low voltage is utilized. Kit is complete with perforated mounting board, 3 vacuum tubes, microphone and all parts necessary for construction. A detailed 12 page instruction manual contains simple-to-follow pictorial and schematic diagrams for each project. Less headphone, photoelectric cell and socket, wire and solder. Net 15.50
 KT-36A Shpg. wt., 5 lbs. Net 15.50
 PHOTOELECTRIC CELL TUBE TYPE 868. Shpg. wt., 8 oz. 3.75
 CM-70 AMPHENOL 77MIP4 SOCKET FOR ABOVE. Shpg. wt., 1 oz. .13
 ME-33 CANNON AM-15-1 1000 OHM SINGLE HEADPHONE. Shpg. wt., 1 lb. 1.18

LAFAYETTE STEREO
PHONO AMPLIFIER KIT

Made in U.S.A.

- 4 WATTS STEREO OUTPUT
- ISOLATION TRANSFORMER
- SEPARATE VOLUME CONTROLS
- GANGED TONE CONTROLS
- STEREO-MONAUROAL SWITCH

18.95

This is a complete 4-watt hi-fi stereo amplifier having 2 watts output per channel. Features separate volume control for each channel; ganged tone controls; stereo-monaural switch to feed right for use anywhere a small stereo amplifier is required—ideal for small apartments. Complete with instructions. Excellent for 8 ohm speakers. Tubes: 2-50C5, 2-12AX7 plus selenium rectifier. For 110-120 volts, 60 cycle AC. Net 18.95
 KT-126 Kit, Complete. Shpg. wt., 7 lbs.

NEW! ELECTRONICS EDUCATIONAL KIT

Complete With 116 Page Instruction Manual — Virtually A Textbook & Laboratory Manual

- 194 ILLUSTRATIONS
- INCLUDES QUESTIONS & ANSWERS FOR EACH SECTION
- CLEARLY WORDED STEP-BY-STEP INSTRUCTIONS
- COVERS BOTH AC & DC IN THEIR ENTIRETY
- TEACHES, AS YOU BUILD
- 12 COMPLETE EXPERIMENTS RESULT IN A FINISHED AC & DC TEST INSTRUMENT
- ENABLES REPAIR OF HOUSEHOLD APPLIANCES

The fascinating world of electronics introduced in a simple, easy-to-follow manner through this new Lafayette KT-180 Electronic Educational Kit. Not a toy—this kit is a complete beginners electronics laboratory course featuring an extremely useful AC/DC Multimeter.

In the process of constructing this test meter, the fundamental principles of electricity and electronics are introduced in a "learn-by-doing" method. The focus of attention is on the basic sensitive meter for measuring the flow of electrical current. From this simple measurement, the meter is built up to indicative voltage and resistance. The detailed 116 page instruction manual contains 194 illustrations and is written in a simple, easy-to-read, step-by-step manner with questions and answers supplied for each section. Providing a virtual "guided tour" of electrical fundamentals, this kit furnishes a complete course in AC and DC including ohms law, series and parallel connections, making electro-magnets, producing electricity by induction and testing house appliances. The kit is supplied less batteries. Net 24.50
 KT-180 Shpg. wt., 5 lbs. Net 24.50
 BA-155 (Burgess Z type battery, 2 required) Net ea. .095



COMPLETE STEREO PHONO SYSTEM KIT

• Save By Building This Excellent Stereo Amplifier

• Plays Both Stereo and Monaural Records

39.95

Enjoy fine stereo performance with this "easy-to-assemble" exclusive Lafayette package. The complete system consists of the Lafayette KT-126 Stereo Phono Amplifier Kit (as described above), Lafayette ML-24 4-speed Turntable for 162A, 33½, 45 and 78 rpm records, Lafayette PK-171 Stereo Tone Arm with the wide range Plug-in Crystal Cartridge and .75 mil sapphire stylus for stereo and monaural records. Completing the system are 2 of Lafayette's amazing SK-109 miniature mahogany veneer enclosures, each speaker is supplied with 25 feet of hookup cable and measures only 9½x7¾x3½"D. PK-454WX Shpg. wt., 22 lbs. Net 39.95
 Unfinished mounting board for ML-24 Turntable. Shpg. wt., 1 lb. Net .95
 PK-149W



LAFAYETTE Amateur, SWL Equipment & Kits



Made in U.S.A.

21⁹⁵

The most sensational shortwave economy receiver kit ever offered. A complete shortwave and standard broadcast set which covers the entire region from 550 kilocycles to 30 megacycles. Four whole bands of fascinating programming unavailable elsewhere. Perfect for language students and radio amateurs. Only a regenerative circuit can offer such amazing performance and yet be so simple to build. Building this fine kit is an absolute pleasure — it's so well designed you can't go wrong. Kit includes all the parts you need, and the detailed step-by-step instruction book with its giant pictorial drawings shows you just how to put them together. One front panel knob does all the bandswitching at the flick of the wrist, immediately taking you from band to band. All coils are prewound for greater accuracy. This kit is so easy to build a child who can read would do it (and many already have!) The chassis is completely isolated from the circuit, so there is no shock hazard.

BUILD YOUR OWN NEW! EXCITING "EXPLOR-AIR" 4 BAND RECEIVER KIT



TUNE IN the WORLD

• 4 Bands for total coverage: • 550-1600 Kc broadcast band • 1.7-5.0 Mc., 5.0-14 Mc., 14-30 Mc. shortwave bands • Complete band-switching from front panel • Built-in Big 4" PM Loudspeaker

This precision radio kit is just full of extra features. Complete 4 band coverage of broadcast stations, international broadcast bands, amateur, maritime, fire and police services, yes, even satellite signals. Big 4" speaker and sensitive circuit with 50C5 output stage, 35W4 rectifier and 12AT7 regenerative detector and amplifier stages give you all the volume you want. Phone jack for privacy automatically disconnects speaker. All controls are on the front panel: On Off Volume, Main Tuning, Band Spread, Bandswitch, Antenna Tuning, and Regeneration. 110 volt 50-60 cycle AC-DC power supply lets you use this fine set anywhere. Size: 10x7x5". Everything needed for unexcelled reception is combined in a compact, economical package.

KT-135 EXPLOR-AIR RECEIVER KIT (Less Cabinet) wt., 5 lbs. **21.95**
ML-150 Leatherette covered Wooden Cabinet for above, 1 lb. **Net 2.75**



EICO
720K
TRANSMITTER
KIT

Brand new 90 watt band switching rig for 80 through 10 meters. Features a 6146 final amplifier for 90 watts CW input, up to 65 watts phone with external modulation. 6AQ5 clamper tube protects final in case of loss of excitation. Variable pitch Pi-net output matches 50-1000 ohm loads. Oscillator keying permits full break-in operation. Panel meter indicates exact operating current and helps in tuning up. Its "novice limit" call-75 watt power limit. Tubes: 6CL6 Colpitts oscillator, 6AQ5 buffer-multiplier, 6146 final amplifier, 6AQ5 clamper, and GZ34 rectifier. Copper plated chassis, ceramic switches, ingenious metal case with complete parts and instructions. 5Hx15Wx9 1/2"D. Shpg. wt., 27 lbs. With all HE-310WX Kit **Net 79.95**
MODEL 720 above factory wired. **Net 119.95**
HE-311WX

"ON THE AIR" ILLUMINATION SIGN




Flip to transmit and the sign tells them you're "On The Air." Snap-out back plate for easy accessibility. Durable baked black finish in heavy gauge steel. 110V, AC. Size: 10 1/2" L. 3 1/2" H. 3" D. Shpg. wt., 6 lbs. **HE-645 Net 6.95**



**LAFAYETTE
MODEL HE-11
SPEAKER FOR AMATEUR
and SHORT WAVE
RECEIVERS
7.95**


Efficient and attractive speaker especially designed as ideal mate for communications receivers. 4" speaker housed in handsome, tapered, grey metal cabinet reduces QRN and peaks voice frequencies. Impedance 8 ohms. 7 3/8 x 5 3/8 x 4 3/4" HE-11 Shpg. wt., 4 lbs. **Net 7.95**
HE-14 As above, except 4 ohms impedance **Net 7.95**

NEW! AC/DC BROADCAST RADIO SEMI-KIT



Only

9.95




- ALL MAJOR COMPONENTS PRE-MOUNTED
- CONTEMPORARY STYLING
- 5 TUBE SUPERHETERODYNE CIRCUIT
- FUSED POWER LINE

Imagine the joy of building your own full size table model radio. The perfect kit for beginners. Everything but tools is included in the kit to build this fine radio. All the major components are pre-mounted on the chassis by the factory. Two clearly marked cards identify the few resistors and capacitors necessary to complete the set. No special tools are required for alignment either. A simple procedure is outlined in the Lafayette illustrated instruction manual which will enable you to achieve excellent reception across the entire broadcast band (540-1600 KC) Sounds as good as it looks too. Styled in a beautiful contemporary plastic cabinet with a finished back. Vented back provides proper baffling and ventilation for components. 5 tubes (2 dual purpose) plus a high "Q" ferrite rod antenna for better AM reception. Cabinet measures 8 1/2 x 4 1/4 x 4" overall. Muted colors match any color scheme. Tubes: 35W4, 12AV6, 12BA6, 12BE6 and 50C5. For 117 V AC/DC. Shpg. wt., 3 lbs. **KT-204 Net 9.95**

NEW! Lafayette 6 TRANSISTOR POCKET RADIO SEMI-KIT



14⁹⁵



- 6 TRANSISTORS + DIODE AND THERMISTOR
- RUGGED PRINTED CIRCUIT BOARD
- EASY ASSEMBLY WITH MAJOR COMPONENTS PRE-MOUNTED
- PUSH PULL OUTPUT AND 2 1/2" PREMOUNTED SPEAKER FOR RICH TONE
- MODERN COMPACT STYLING

The last word in transistor kit engineering and design. Play it everywhere; at the beach, ball game or any outdoor event. Packed with all the advanced features plus the extra enjoyment of building it yourself. All major components are pre-mounted to simplify assembly. Push-Pull output stage, Ferrite loop-antenna and provision for external antenna are just a few of the many quality features found in this set. Rugged superheterodyne printed circuit board is easy to install and will provide many enjoyable hours of trouble-free life. Six transistors plus a diode and thermistor combine to pull in stations miles away across the entire broadcast band. Only four inexpensive pen light cells assure plenty of power — longer. Two controls — on-off/volume and tuning. Complete with illustrated step-by-step instruction manual, magnetic earphone, batteries and telescoping rod antenna. Attractive molded plastic case. Size 5Lx3 3/8x1 1/2". **KT-207 Shpg. wt., 2 1/2 lbs. Net 14.95**
Replacement Batteries for Above (4 required) **BA-155 Shpg. wt., 8 oz. Net ea. .095**

B & W 550A COAXIAL SWITCH 8.25



An inexpensive multi-position coaxial switch that eliminates the annoyance of screwing and unscrewing coaxial connections. The B & W 550A permits you to instantly select any one of five transmitters, antennas, exciters, receivers, and other r-f generating devices using 52 or 75 ohm line. The switch handles up to 1 kw of modulated power with a maximum cross-talk of —45db at 30mc. **HP-91 Shpg. wt., 2 lbs. Net 8.25**


New! CODOME AUTOMATIC MORSE CODE INSTRUCTION MACHINE FOR THE NOVICE



The CODOME and its accompanying manual provide all the materials necessary to prepare the beginner for his Novice class amateur license examination. The machine itself sends groups of letters and numbers automatically, in random order. Built-in key permits the student to develop his sending technique in step with his receiving technique. As each group of characters is being practiced, the student is introduced, by means of the accompanying manual, to the basic concepts of electricity and radio, and to the FCC regulations pertinent to amateur communications. Each code group has a corresponding lesson in the manual, with exam-type questions and answers. Once the code and theory are mastered, the student should have no difficulty in fulfilling the Novice requirements. For 117 VAC. 2 1/4 x 5 1/4 x 6 3/4" **HE-696 Shpg. wt., 2 1/2 lbs. Net 17.95**


COMPLETE 5 WATT PHONO SYSTEM KIT

23⁷⁵



Everything required for a complete Hi-Fi system in this "easy-to-assemble" package—and Lafayette brings it to you at an unbeatable price. The system is centered about the excellent Lafayette KT-92 5 watt amplifier kit (as described above). The ML-24 4 speed turntable employs a rubber shock-mounted friction drive motor for quiet dependable operation. Tone arm is the Lafayette PK-157 containing turnover crystal cartridge with dual sapphire styli. Completing the system in the Lafayette SK-109 miniature hi-fi speaker system beautifully finished in mahogany veneers and supplied with 25 feet of hookup cable. Speaker measures only 9 1/2 x 7 3/4 x 3 1/4" D. Shpg. wt., 15 lbs. **Net 23.75**
PK-333WX Unfinished mounting board for ML-24 turntable. Shpg. wt., 1 lb. **Net .95**
PK-149W

PHONO AMPLIFIER KITS



LAFAYETTE KT-92 5 WATT PUSH-PULL AMPLIFIER KIT

Made
in
U.S.A.

10⁹⁵

- PUSH-PULL AUDIO OUTPUT STAGE
- INVERSE FEEDBACK CIRCUIT
- SEPARATE VOLUME, BASS & TREBLE CONTROLS
- AC OR DC OPERATION

Here in kit form is an AC-DC hi-fi amplifier that presents unusual features despite its amazingly low price. The separate bass and treble controls permit adjustment of both low and high frequency response and balance. Works equally well with both crystal or ceramic cartridges. Has a 4-tube line up—a 12AX7 amplifier and phase inverter, a 35W4 rectifier and a pair of 35C5's in

push-pull, having a power-packed low distortion output. The circuit utilizes an inverse feedback loop to reduce the level of hum and distortion. Kit is complete containing all essential parts, tubes and detailed instruction manual showing pictorial and schematic diagrams. Shpg. wt., 4 lbs. **KT-92 Net 10.95**



teleSpan™

CITIZENS BAND "WALKIE TALKIE"



TRANSISTORIZED

- No License, Test or Age Limit • Superregen Receiver, Xtal Controlled Transmitter • Transmits and Receives up to 1/4 Mile . . . More under favorable conditions • Plastic Carrying Case, Earphone, Battery Included


A compact, portable, low cost transceiver set with truly amazing performance. Simple enough for a child to operate—it requires no licenses or tests of any kind under Federal law. Perfect for camping, sports, etc. Rugged 2 transistor circuit features a powerful super-regenerative receiver with plug-in earphone for private listening. Will receive and transmit up to 1/4 mile under average conditions. Fingertip push-to-talk switch provides instant X-tal controlled transmitter operation. Durable printed circuit and 9-volt battery shock mounted, assure reliable operation. A removable telescoping antenna can be carried separately in the carrying case pouch when not being used. On-off switch is only other control. Complete with carrying cases, earphones, antennas and 1.9V battery. Nothing else to buy!

Size: 5 1/2" H x 2 1/4" W x 1 1/8" D. Shpg. wt., 3 lbs.

HE-37L Set of 2 Transceivers	Net 29.95
HE-38L 1 Transceiver	Net ea. 15.45
BA-2 Extra batteries for above.	ea. .39

Weights only 8 oz. with battery and case!

15.45
Each
2 FOR 29.95
NO MONEY DOWN



The Ideal Set For Young People

NEW! LAFAYETTE HI-FI "THIN LINE" CEILING & WALL BAFFLE SPEAKER



Absolutely Incredible Sound Quality! **5.95**

- Measures Only 2 1/4" Deep • Employs New Inverted Magnet
- Perfect for Hi-Fi Extension Speaker or P.A. Use
- Only 2 1/4" Deep • New Inverted Magnet

Frankly we were amazed at the phenomenal musical quality of this speaker. Never before have we heard a speaker of this size reproduce the true sounds of loud orchestral passages, drums, etc. with such definition and clarity. The perfect speaker to furnish music or paging throughout your home, office or factory. Advanced design employs an inverted magnet, placing the 12 oz. magnetic structure in front of the speaker rather than behind as in conventional speakers. Only 2 1/4" deep with its own metal baffle plate, the SK-175 easily mounts in any wall, ceiling, closet or ordinary wood enclosure. Two are perfect for stereo. Voice coil is 1" diam. Frequency Response: 90-9,000 cps. Impedance: 8 ohms. Overall Dimensions including metal baffle is 9 1/2". Requires 6 5/8" wall cutout. Shpg. wt., 3 lbs.

Net 5.95

LAFAYETTE POWER MEGAPHONE



QUANTITY LIMITED!

Formerly **24.95**

19.95

SENSATIONAL VALUE!

- One Complete Hand-Held Unit—Including Battery and Microphone
- Employs Powerful Low Drain Circuit • Range Extends Over Hundreds of Yards • Low Power—High Power Selection For Extra Battery Life • Weighs Only 3 1/2 lbs. Complete With Battery

A new compact megaphone with a balanced trigger grip for one hand operation. Complete self-contained unit includes high efficiency horn speaker, battery pack and built-in microphone. Inexpensive to operate—it uses 4 standard "D" flashlight cells. High-Low power push-buttons allow battery conservation with reduced power or full power when it is needed. Rugged microphone is encased in metal. The perfect announcer for traffic direction in parking lots, boat to boat contact, life-guard use—any place where a penetrating voice is required. Battery can be replaced in seconds, without tools. Specifications: Battery current 200 ma @ 6V. max. Battery life 6 hours use approx., Horn diam. 6 1/2". Horn length 11 3/4"; Handle length 5". Less Batteries. Shpg. wt., 6 lbs. PA-223 Net 19.95

Battery for Above. Burg-No. 2 or equiv. (4 cells required). Shpg. wt., 1 oz. ea. BA-157 Net ea. .13

FAMOUS BRAND 2-STATION INTERCOM



- SMART STYLING
- ALL-METAL CABINET
- 4" SPEAKERS
- CABLE SUPPLIED

13.95

New! Low cost intercom system that combines smart new styling with quality performance. A Lafayette special, this 2-station intercom is a must for your home, store, or business office. Units come complete with 50 feet of interconnecting cable and will save you thousands of steps and needed energy. An additional remote station may be added if needed at very low cost. The Master unit has its own volume control with "on-off" switch. No switch is necessary on remote. Power consumption is only 29 watts. This set uses a 12AT7 Dual-triode amplifier plus a Selenium rectifier. 4" Alnico speakers are used in both Master and Remote. 110 Volts AC or DC. Measures only 6 1/2" x 4 1/2" x 4 1/2". Shpg. wt., 6 lbs. PA-269 2-Station Intercom complete Net 13.95

PA-270 Extra Remote Station Net 5.83

TRANSISTOR POWER 'PHONE



2-STATION TELEPHONE SYSTEM


24.95

- AVAILABLE FOR THE FIRST TIME—TRANSISTOR AMPLIFIED TELEPHONE HANDSETS!
- 125 MILE RANGE ON A SINGLE PAIR OF WIRES!
- EACH HANDSET HAS A COMPLETELY SELF-CONTAINED TRANSISTOR AMPLIFIER & BATTERY!
- WORKS WITH STANDARD "PENLIGHT" CELLS
- ANY NUMBER OF HANDSETS MAY BE USED IN A COMMON TALKING SYSTEM!

Lafayette brings you these unique transistorized telephone handsets at extremely low cost. Each handset is complete with its own transistor amplifier, buzzer, press-to-talk pushbutton switch, buzzer pushbutton switch and shielded coiled cord (extendable to 6') with male and female connectors ready to connect to 2-wire cable. Each handset is handsomely styled in heavy, high impact resistance, moulded plastic. All stations are connected to the same 2-wire cable, and good signals can be received up to 125 miles with #22 wire! Everything is self-contained in each handset, and any number of handsets can be utilized. SPECIFICATIONS: IMPEDANCE (INPUT AND OUTPUT)—600 ohms; OUTPUT VOLTAGE—approx. 2.44V. max.; POWER OUTPUT—10 mw. (approx. +10 db.) max.; MINIMUM POWER INPUT (SENSITIVITY)—0.002 mw. (approx. -27 db.); DISTANCE FOR COMMUNICATION—200 km. (125 miles); POWER SUPPLY—Burgess "Z" or RCA VS034 battery cell. SHIPPING WEIGHT (PER PAIR)—3 1/2 lbs. Complete with Batteries. PA-8—2-Station Transistor Telephone System (2 units) Net 24.95

PA-6—Single Transistor Telephone Unit. Shpg. wt., 2 lbs. Net 13.95
BA-155—Burg. Z or equiv. (1 per handset) Net ea. .095
Shpg. wt., ea. 1 lb. Extra battery Net ea. .095
WR-221 ALPHA 1172—2-wire cable for telephone systems. Shpg. wt., 1 lb. per 100' Net 2.41

BRAND NEW! TRANSISTORIZED



HUNTERS CAMPERS BOATING SPORTS

ONLY **10.99**

"BULL HORN"

- Weighs only 2 1/2 lbs. • Range up to 2,000 ft.
- Completely Transistorized • Can be Used as Long-Range Listening Device

Considered the most modern development in bull horns because it is completely transistorized—instantly operates on 6 standard 1 1/2V. "C" flashlight batteries (not incl.). With its range up to 2,000 ft., it is ideal for all outdoorsmen, for work or sports. Trigger switch is simple to operate—just press to talk. May be used as a sound detector and amplifier as well as a voice amplifier. Shpg. wt., 3 lbs. PA-271 Net 10.99

BA-274 1.5 Volt Batteries (6 req.) Net ea. .16



EASY-PHONE TELEPHONE AMPLIFIER



- Lends A Valuable Helping Hand
- Amplifies Telephone To Room Volume
- 4 Transistors + Varistor
- No Dangling Wires, Pickups To Connect
- A Reminder That Caller is Waiting On The Wire
- No Warm-Up, Instant Operation

17.50

with batteries

Why keep running over to the receiver to maintain contact with the other party? Instead, place the receiver on the Easy-Phone telephone amplifier and then proceed with important business while still within earshot of the telephone party. There is no need to use up one hand to hold phone, or grab receiver between neck and shoulder. With the receiver cradled on the Easy-Phone, there is complete freedom to take notes the party dictates, using either long hand, short hand or typewriter. When engaged in long distance conversation, Easy-Phone will clearly amplify the communication so relatives or business associates can hear every word as it is said. On occasion the search for some pertinent article of information prevents "holding on to the wire". Easy-Phone permits the information to be sought while keeping an ear "on the wire". Easy-Phone can be kept at office or at home—ready at all times for instant action. A four transistor, battery powered amplifier and inductive pickup, compactly in-

stalled in a most attractive plastic case, compose the Easy-Phone. Completely self-contained with no protruding plugs and twisted hook-up cords, it will not disarrange the orderliness of work space. Operation is this simple: Placing the receiver on Easy-Phone turns amplifier on, then adjust volume to the proper level. Volume control is independent of on/off switch (which is depressed by receiver's weight). SPECIFICATIONS: 4 transistor circuit with 1 varistor; powered by 4 pen-light, 1.5 volt cells, self-contained; 3" dynamic speaker, out of view under amplifier; battery life 6 months with moderate usage. Weight 25 ozs. Heavy black bakelite case measures: 8 1/4" L x 3 1/2" W x 2 1/4" H. Easy-Phone rests on two sturdy chrome plated runners. With miniature plug and jack for recorder input. Shpg. wt., 3 lbs. F-759 With Batteries Net 17.50

EXTRA BATTERIES FOR ABOVE
BA-155 Penlite cell Net .095

LAFAYETTE 2 AND 3 STATION TRANSISTOR INTERCOM SYSTEMS

FOR HOME! SHOP! OFFICE! FACTORY!

Intercom Buy of The Year!



Formerly ~~36.50~~ NOW **26.95**

QUANTITIES LIMITED




Formerly ~~24.95~~ **18.95**

- FEATURES: • All-Transistor Printed Circuit • True 3 Station System (PA-265) • Small Size and Lightweight • May Be Wall Mounted

Now have a deluxe 2 or 3 station system which is durable, versatile and attractive too! Easy to operate: with master unit—just push the press-to-talk button to speak and release it to listen. When talk is finished press Wait button. Remote unit to Master—just press Call button. In addition, the PA-265 is a true 3 station system; there is no call interference—each remote may be called separately, thus assuring privacy and less confusion. Three transistors in a rugged printed circuit and 3 1/4" speakers provide ample volume and low drain on 4—1.5 volt size C flashlight batteries (not included). Light in weight, units may be desk or wall mounted as desired. Plastic body is finished in gray and dark blue, styled to match any decor. Shpg. wt., 5 lbs. Size 1 1/4" H x 5 1/2" W x 6 3/4" D. PA-264 2-Station Intercom Net 18.95
PA-265 3-Station Intercom Net 26.95
WR-12 100 Ft. 2 conductor wire Net .89
WR-13 250 Ft. 2 conductor wire Net 1.95
BA-156 Batteries for above—4 required Net ea. .13

LAFAYETTE PUBLIC ADDRESS and MUSIC AMPLIFIERS

NEW! LAFAYETTE 40-WATT PUBLIC ADDRESS AMPLIFIER



- Power Output Sufficient to Drive Many Speakers Simultaneously
- Flat Response from 30 Cps to 15 Kc
- Two Microphone Inputs, One Phonomograph Input
- Separate Volume Control for Each Input
- Excellent Hum and Noise Suppression
- Attractive New Styling

69⁹⁵


NO MONEY DOWN

Here is a powerful new public address amplifier suitable for use in large department stores, stadiums, amusement parks, industrial plants, summer camps, etc. Power output is a full 40 watts. Three inputs are provided: Two microphone inputs for crystal or dynamic mikes, and one phono input for a crystal or ceramic pickup, a tape recorder, tuner or other high level program source. Frequency response: ± 2 db from 30 cycles to 15 Kc. Input sensitivity: mike inputs, 5 mv for full output; phono 300 mv. Input impedance: mike, 1 megohm; phono, 500,000 ohms. Hum and noise are 64 db below rated output with mike inputs and 74 db below with phono input. Hum balance control provided in rear. Each input has its own volume control to permit proper blending and balance when two or three inputs are in use simultaneously. Separate bass and treble controls. Output impedances: 4, 8, 16 or 250 ohms, taken either from a terminal strip in the rear, or from two 6-prong sockets provided for rapid connection and disconnection. The 250 ohm output is a constant voltage tap for a 70 volt line. Groups of speakers may be connected directly to the amplifier in various series, parallel, and series-parallel configurations. Tube complement: 1-12AX7/ECC83 microphone preamplifier, 1-6AV6 tone control, 2-6A08's and 4-6BQ5/EL84 output tubes (two parallel pairs operating push-pull). For 110-120 volts, 50-60 cycles AC. In an unusually attractive metal cabinet with modern black and gray panel, 5 1/4" H x 13 3/4" W x 9 3/4" D. Shpg. wt., 30 lbs.

PA-268WX

Net 69.95

NEW! LAFAYETTE MODEL LA-75 20-WATT MUSIC AMPLIFIER



INSTRUMENT CONTROL PANEL RECESSED FOR EASY ACCESSIBILITY

- 20 Watt High-Fidelity Amplifier
- For Presenting Amplified Live Music and Voice to an Audience
- Adjustable Tremolo for "Quivering" Effect
- Built-in 12" Heavy-Duty Hi-Fi Speaker
- Separate Volume and Tone Controls for Instrument and Voice Inputs

69⁵⁰

NO MONEY DOWN

Here is a music amplifier which will deliver 20 watts of clean power, to a built-in 12" heavy-duty 20 watt speaker or to an external 4, 8 or 16 ohm speaker. There are 3 inputs: two instrument inputs and one microphone input for voice. The two instrument inputs have volume and tone controls separate from the corresponding controls on the voice input. Built-in tremolo circuit super-imposes an oscillator signal on the audio signal to create a periodic fluctuation or "quiver" whose frequency and amplitude may be adjusted by the "speed" and "strength" controls, respectively. There is a jack provided for turning the tremolo on and off by means of a foot switch (available as an accessory). Frequency response: ± 3 db from 33 cycles to 20 Kc on voice

input; ± 3 db from 33 cycles to 15 Kc on instrument inputs. Mike input sensitivity is 9 mv RMS; mike jack is shorting type to minimize hum pickup when mike is not plugged in. Tube complement: 2-12AX7's, 1-6AU6, 2-7189 output tubes, 1-6CA4 rectifier. Dimensions: 15 3/4" H (including rubber feet) x 19 1/2" W x 8 3/4" D. With carrying handle. Shpg. wt., 30 lbs.

LA-75 WX

Net 69.50

FOOT SWITCH to remotely control the tremolo in the LA-75. Equipped with cable terminated in standard phone plug to fit corresponding jack on LA-75. Shpg. wt., 1 1/2 lbs.

SW-103

Net 5.95

FOOT PEDAL



LAFAYETTE MODEL PA 62 30 WATT PA AMPLIFIER

PA-62 with PA-65 Phono Top

Less phono-top

52⁵⁰

NO MONEY DOWN

FEATURES: Ideal for use in churches, schools, small theaters, lecture halls and industrial plants. Priced extremely low to give extra profits to rentals and sales. Separate bass and treble tone controls, permits adjustments to meet all acoustic requirements. Two mike inputs; optional 4-speed phono top. 70 volt constant voltage output tap. Provides coverage up to 100,000 square feet when used with trumpet type speakers. Chassis is equipped with 2-speaker plug-in output sockets. Unit is housed in sturdy steel, well-ventilated cabinet. Modern streamlined styling. Fin-

ished in baked hammerloid enamel. Removable escutcheon plate for rack and panel mounting. **SPECIFICATIONS:** TUBES: 3-6EU7, 2-6L6GB, 5U4GB (Rectifier). **POWER OUTPUT:** 30 Watts. **INPUT GAIN:** Microphone 125 db. Phono 80 db. **FREQUENCY RESPONSE:** 30 to 15,000 cps. ± 1 db. **TONE CONTROLS:** Bass ± 15 db at 50 cps; Treble ± 15 db at 10,000 cps. **HUM LEVEL:** 70 db below rated output. **INPUTS:** 3: 2-Microphone and 1-Phono. **CONTROLS:** 6: Microphone-1, Microphone-2, Power off-on, Phono-Bass, Treble, Slide Switch for operating magnetic phono thru channel 2. **OUTPUT IMPEDANCES:** 4, 8, 16, and 250 ohms (70 volt line). **High impedance output for coupling booster amplifier.** **POWER CONSUMPTION:** 135 Watts, 110/120 V.A.C. 50-60 cycles. **Fused.** **SIZE:** 14Wx8Dx6"H. **SHIPPING WEIGHT:** 20 lbs.

PA-62WX Complete with Tubes

Net 52.50

4-SPEED PHONO TOP

For above amplifier. Fits in place of cover. Plays all speeds—16 2/3, 33 1/3, 45 and 78 rpm. Has constant 4-speed motor, with turnover cartridge, complete with two precious metal needles. Has arm-rest and plug connection; for 110 Volt 60 cycle. Shpg. wt., 10 lbs.

PA-65W 4-Speed Phono Top

Net 17.95

NEW! 40 WATT DUAL SPEAKER PA SYSTEMS

- New Lafayette Powerful 40 Watt Public Address Amplifier
- 2 University or Electro-Voice Horns For Outdoor Systems
- 2 25-Watt Speakers & Wall Baffles For Indoor Systems
- Choice of Deluxe Dynamic Mikes
- 70 Ft. of Speaker Cable

Highly efficient permanent sound systems for large halls, department store music and paging systems, railroad stations, restaurant music, etc. The outstanding Lafayette PA-268 40 watt amplifier assures top performance under all operating conditions. For 117 volts, 60 cps AC.

40-WATT PERMANENT INDOOR SYSTEM

Consists of the PA-268 40-watt amplifier, two 12" PM speakers, two attractive walnut wood baffles, two 35" speaker cables with plugs, an Atlas MS-10C floor mike stand and Argonne AR-3 dual impedance dynamic microphone with ball-joint desk stand, for hand-held, desk stand or floor stand use. Shpg. wt., 75 lbs.

PA-284WX Net 125.95

Same as above, except with Electro-Voice 664 mike. in place of AR-3

PA-283WX Net 149.95

40-WATT OUTDOOR PA SYSTEM

Consists of a PA-268 40-watt amplifier, two Lafayette PA-57 driver units and two University PH trumpets, two 35" speaker cables with plugs, and an Argonne AR-3 dynamic mike with desk stand. Shpg. wt., 75 lbs.

PA-282WX Net 139.45

Same as PA-282WX, except with Electro-Voice 664 dual impedance cardioid dynamic mike and MS-10C floor stand. in place of AR-3

PA-281WX Net 168.45

Same as PA-282WX except with 2 Electro-Voice 848 projectors in place of PA-57 and University PH.

PA-280WX Net 157.95

Same as PA-280WX with Electro-Voice 664 mike and floor stand. in place of AR-3

PA-279WX Net 186.95



PA-268WX

LAFAYETTE WOOD WALL BAFFLES AND 25 WATT 12" SPEAKERS

E-V 664 CARDIOID DYNAMIC


LAFAYETTE PA-57 DRIVERS AND UNIVERSITY PH TRUMPETS

ARGONNE AR-3 DYNAMIC MIKE

ATLAS MS-10C FLOOR STAND

ELECTRO-VOICE 848 CDP PROJECTORS

DUAL-SPEAKER 30-WATT PORTABLE SYSTEMS



ATLAS MS-10C FLOOR STAND

CHOICE OF DYNAMIC MICROPHONES

ARGONNE AR-3 DUAL IMPEDANCE DYNAMIC MIKE

ELECTRO-VOICE 664 DELUXE CARDIOID DYNAMIC MIKE



The most popular system for schools, RR waiting rooms, gyms, churches, noisy factories. Ideal for rentals.

AS LOW AS

110⁵⁰

NO MONEY DOWN

- CHOICE OF DELUXE DYNAMIC MIKES
- TWO 25-WATT SPEAKERS • MONEY-BACK GUARANTEE

This 30-watt system is one of our most popular models. Large enough for the majority of sound system applications — used in thousands of school auditoriums, churches, theatres, dance halls, dance studios and lecture halls. The Ideal system for rentals; these systems have been sold to many hundreds of dealers, AND REMEMBER OUR MONEY-BACK GUARANTEE AND OUR LOW, LOW PRICE! **DUAL SPEAKER 30-WATT PORTABLE SYSTEMS INCLUDE:** The outstanding feature-filled Lafayette Model PA-62 30-watt amplifier; 2-25-watt PM speakers; 2-35" speaker cables and plugs; your choice of the popular Argonne AR-3 All-Purpose Dynamic microphone for hand-held, desk stand or floor stand use, with removable ball-joint desk stand and floor stand adapter and 8' cable; or the deluxe dual-impedance Electro-Voice 664 Cardioid dynamic microphone for use where high-feedback problems exist, with 40-15,000 cps response, on-off switch and 18' cable; the famous Atlas MS-10C floor mike stand; and the handsomely designed split-type portable carrying case covered in high quality dark blue leatherette. Size of case 22 1/2" H x 16 1/2" W x 15" D — provides a secure place for the system components. For 110-130 volts, 60 cps AC operation. Shpg. wt., 75 lbs. less phono; with phono 85 lbs.

PA-232WX 30-watt Portable System, Less Phono Top and less MS-10C floor stand, complete as described with Argonne AR-3 dynamic mike

Net 110.50

PA-233WX Same as above, with E-V 664 dynamic microphone and MS-10C floor mike stand

Net 140.50

PA-234WX Same as PA-232WX with 4-speed phono top

Net 128.50

PA-235WX Same as PA-233WX with 4-speed phono top

Net 158.50

LAFAYETTE 10-WATT FIXED P.A. SYSTEMS



• COMPLETE PERMANENT SYSTEM

• CHOICE OF CRYSTAL OR DYNAMIC MIKE

• AMPLIFIER HAS LAFAYETTE'S MONEY-BACK GUARANTEE

High quality, low cost system engineered for smaller permanent installations. For areas up to 5500 sq. ft. For office, store, garage, small factory paging and music systems. **THE COMPLETE SYSTEMS INCLUDE:** The new Lafayette Model PA-60, 10-watt amplifier complete; your choice of either the Electro-Voice 727 crystal microphone complete with detachable desk stand and 5' cable—or the new Lafayette Model PA-29 weatherproof, blast-proof slim dynamic mike complete with high or low impedance selector switch and detachable swivel-type stand adaptor; 8" heavy duty PM speaker; 35" speaker cable and plug; and attractive polished walnut speaker wall baffle. For 110-120 volts, 60 cps AC operation. Shpg. wt., 25 lbs. (Any other microphone may be substituted in all systems at additional cost. See microphones in index.)

PA-140WX Complete 10-watt Permanent System as described with E-V 727 Crystal Microphone. Shpg. wt., 24 lbs.

Net 45.50

PA-141WX Same as above, with Lafayette PA-29 dual impedance dynamic microphone. Shpg. wt., 24 lbs.

Net 44.00

LAFAYETTE Career Building SCIENCE HOBBY SETS

NEW!

**LAFAYETTE
27.255 MC
CITIZENS BAND
REMOTE
CONTROL
TRANSMITTER
KIT KT-127A**



17.25

WITH .005% TOLERANCE CRYSTAL TWICE AS GOOD AS FCC REQUIRES! OVER 1 MILE LINE-OF-SIGHT TRANSMISSION! EXCEPTIONAL STABILITY FOR FOOL-PROOF CONTROL OF MODEL PLANES, BOATS AND CARS.

MADE IN U.S.A.

You'll marvel at the neatness, simplicity and dependability of Lafayette's RC Citizens Band Transmitter. Crystal-controlled with a .005% tolerance crystal for extra frequency stability; exceeds FCC tolerance requirements. Fits comfortably in the palm of your hand, yet is unaffected by hand capacitance or motion. Has new attractive wide scale meter for visually tuning transmitter. Wide, non-critical tuning for optimum foolproof performance. Tuning for proper output and antenna loading easily accessible. Complete with telescoping antenna, meter, tube, crystal, alignment tool, all parts and easy step-by-step instructions. FCC license application forms enclosed. Size 10x4x2 1/2". Shpg. wt., 5 lbs.

KT-127A less batteries Net 17.25
BA-157 Burgess No. 2 battery Net .13
BA-1 BATTERY (2 needed) 1.59 ea.

**NEW! LAFAYETTE'S
SUPER-TROL R/C
EQUIPMENT RADIO
CONTROL TRANSMITTER
MEETS FCC REGULATIONS**

14.95

Assembled-tested-guaranteed. Crystal controlled with .01% tolerance crystal as per FCC regulations. Uses powerful 3A5 tube for range of approximately one mile. Will operate any 27.255 MC R/C receiver. Overall dimensions only 8 1/2 x 2 3/4 x 1 3/4" — A neat little handful! Includes antenna, tube, crystal with FCC approved tolerance, and instructions. FCC license applications enclosed—no examination required. Less batteries. Shpg. wt., 2 1/2 lbs.

F-249 Net 14.95
BA-124 Batteries Burgess U30 (3 Needed) ea. 1.75
BA-157 #2 Batteries (1 Needed) ea. .13

**RADIO CONTROL
RECEIVER**



8.95

RADIO CONTROL RECEIVER: Completely wired and tested receiver—extremely sensitive and stable. Completely enclosed—ideal in boats—or case may be removed if desired. Ingeniously constructed to withstand vibration and shock. Features external fine tuning—antenna "snap" lead—plug for power and actuator connections. Ideal Companion for F-249 Transmitter and F-327 Servo shown elsewhere on this page. Requires one 1.5V battery and one 67.5 Volt battery. Size determined by use. Measures only 3x2 3/4 x 1 1/2". Complete with tube and instructions. Less batteries. Shpg. wt., 8 oz.

F-208 Net 8.95
BATTERIES REQUIRED:
BA-5 LAFAYETTE (1 needed) 1.29
Burgess No. 2 (1 needed) BA-157 .13 ea.

SPECIAL COMBINATION OFFER
Consists of R/C Transmitter (F-249), and R/C Receiver (F-208) F-259—Combination 22.90

**"DOUBLE"
NEW! GENIAC®**



Over 800 Parts **15.95**

For Schools Science Fairs
Advanced Experimenters.

- Computes • Reasons • Plays Games
- Composes Music • Forecasts Weather
- Design Your Own Computers

The newest kit in famous Geniac® series! The "Double" Geniac contains over 800 parts. Two of everything in the Standard model. Offers the advanced experimenter a far wider range of activities. Perfect for school demonstration. Multiple setup is ideal for Science Fair projects—submit one or more designs. Build "electric trains" that test intelligence—code and decode—add, subtract, multiply and divide—solve puzzles—play games—forecast weather—reason in syllogisms—information and logic circuits. No soldering required. Easily assembled and operated. 64 page guide and reference book, beginners manual, wiring diagrams and many extra pamphlets outlining projects and methods. Complete with mounting rack and batteries. Shpg. wt., 12 lbs.

KT-176 Net 15.95

Standard GENIAC

COMPUTES, REASONS, PLAYS GAMES
COMPOSES MUSIC FORECASTS WEATHER
DESIGN YOUR OWN COMPUTERS
OVER 400 PARTS & COMPONENTS **9.95**

You build up to 125 exciting "electric brain" machines. Has special circuits for forecasting weather. No soldering required. Comes complete with extra pamphlets including 64-page "Simple Electronic Brains and How To Make Them", "Symbolic Analysis of Relay and Switching Circuits", "Beginner's Manual, Machine to Compose Music, Wiring Diagrams, etc. Complete with battery. 16 1/2 x 11 1/2". Shpg. wt., 6 lbs.

KT-175 Net 9.95

NEW! ANALOG COMPUTER KIT



9.95

- Ideal Introduction to Basic Elements of Analog Computers
- Work Over 50 Experiments
- Easy-to-Assemble with Screwdriver and Pliers
- Learn the Way to Sound Scientific Knowledge

The latest Analog Computer Kit offering a basic introduction to computer theory—gives accurate answers to practical problems. Perform over 50 experiments—multiplication, division, powers, square roots, rocketry, interest, radioactive decay, light, kinetic energy, etc. Level of accuracy better than 5%. The computer consists of a masonite, solid instrument panel, kits, potentiometers, meter, specially calibrated scales, guide and operating booklet. Easy-to-assemble. Shpg. wt., 6 lbs.

KT-178 Net 9.95


**ELECTRONIC
GAMES
& TOYS
YOU CAN BUILD**

2.50

A Howard W. Sams Photofact Publication by Len Buckwalter. Complete, easy-to-follow instructions for building 15 projects that will provide hours of fun and enjoyment for your family and friends. Some of the unique projects include a Reaction Timer, Penny Pitch, Electronic Card Trick, Space Shot and others. 128 pages. BK-332 Postpaid in U.S.A. Net 2.50

LAFAYETTE MAGNETICS KIT

Made in U.S.A.



2.95

- FASCINATING MAGNETIC EXPERIMENTS
- STEP-BY-STEP ILLUSTRATED INSTRUCTION MANUAL
- COMPLETE WITH QUESTIONS & ANSWERS

Unlock the mysteries of magnetism with these fascinating, fun-filled experiments. Teach yourself by doing. Every phase of magnetism is covered: 1. Discovery and History of Magnetism. 2. Development of the Compass. 3. Discovery of Magnetic Poles. 4. How to Determine North and South Magnetic Poles. 5. Magnetic Attraction and Repulsion. 6. Terrestrial Magnetism. 7. Difference Between Magnetic and Geographic Poles. 8. The Magnetic Field. 9. Lines of Force. 10. Permeability. 11. "Molecular Magnets." 12. Artificial Magnets. Each experiment is fully detailed and illustrated. The kit contains a plexiglass viewing plate; a specially designed observation deck; two bar magnets; iron filings; compass; iron bar; lodestone; steel pins; aluminum and brass samples; wood float. Shpg. wt., 2 lbs.

KT-181 Net 2.95

NEW ELECTRONIC LIE-DETECTO



9.77

An Action Packed
Electronic Sensation!

- Employs The Same Method As The Famous Polygraph Machine
- Registers Emotions, Feelings and Reactions
- Absolutely Safe

Here's fascinating fun for the whole family. An exciting, different device that will provide hours of conversation and enjoyment. Based on the principles of the famous Polygraph Machine, the Lie-Detecto measures the change in resistance in the skin due to emotional response by means of a special hand-band which detects the amount of perspiration on the skin. Emotions, Feelings and Reactions are registered on an indicator which swings from Start thru Could Be, Are You Kidding, Little Whopper and Big Whopper, depending on the reaction of the person tested. In addition two panel controls provide for Sensitivity and Adjustment. Unit is enclosed in an attractive, rugged enclosure of non-breakable Norolon. Supplied with simple instructions and sample questions, hand-band and batteries. Shpg. wt., 4 lbs.

AP-84 Net 9.77

**1/4 Scale CHRYSLER CORP.
SLANT SIX
ENGINE**



9.55

- Real Engine's Moving Parts—Move in The Model
- "Breakaway" Block—See What It Does And Why!
- Spark Plugs "Fire"
- Slant Six Powers The Lancer, Valiant, Dodge Dart & Plymouth

Except for size, this Revell motorized plastic 1/4" scale working model kit of a Slant Six Chrysler engine duplicates its full size prototype. The more than 200 individual parts are precise in detail with those of the remarkable new engine powering the Valiant and Lancer automobiles. It can be built up and taken down as often as desired. A section of the block can be removed to see the interior parts actually working. Included is an elaborate educational instruction booklet and a sturdy stand for mounting the engine. Battery operated to provide realistic engine movements. Economical "C" cells are used.

F-769 Shpg. wt., 2 1/2 lbs. Net 9.55
BA-156 Extra "C" Cells, 2 required Net ea. .13

**MAGIC-GLO BLACK LIGHT
TEKNIKIT™**




- Educational—Scientific
- Enjoyable—Interesting
- Earn Invisible Detection
- Write Secret Messages

This new Black Light Kit enables you to see the invisible. Guaranteed completely safe and harmless. This kit allows children to study the phenomena of fluorescence and phosphorescence. Set contains black light, socket and cord, laboratory lamp stand, 4 jars of fluorescent paints, invisible ink, invisible crayon, tracer powder, 3 fluorescent mineral specimens, phosphorogram, optical bleach, brushes and pen, and a box of fluorescent specimens. Enables the student to perform endless numbers of fascinating experiments. The amply illustrated 48 page booklet "The Story of Black Light—The Unseen World Around Us," explains the use of black light in fields such as mineralogy, electronics, crime detection, medicine, stamp collecting, and many others. Shpg. wt., 41 lbs.

AP-61 Net 11.95
AP-73 Replacement U.V. Bulb for AP-61 Net 2.70

MINERAL "TEKNIKIT"™, VOL. I



- 48 Carefully Selected Specimens
- Named—Tagged—and Classified
- Removable for Study

Forty-eight specimens—pre-selected to illustrate such physical characteristics as cleavage, hardness, color, luster, specific gravity, crystal form, etc. Contains specimens of ore—organics—fossils—elements—Plutonics—oxides—volcanics—hypabyssals—effusives crystals—common and uncommon minerals. An aid in the study of mineralogy, petrology, structural geology, physiography, economic geology. Each specimen is tagged and removable from its compartment. Each compartment is correspondingly tagged and named. All are named as well as classified. An excellent introduction to rock and mineral identification. Handy reference for the advanced "rock hound." Shpg. wt., 1 lb.

F-566 Net 2.95

NEW! MINERAL TEKNIKIT™ VOL. II

- 48 Additional Specimens! • No Two Alike!
- Many Uncommon Minerals! **2.95**

Volume 2 of Lafayette's popular Mineral TEKNIKIT has been as carefully pre-selected and packaged as its predecessor. Includes specimens of Carbonates—Tantalum—Phosphates—Gemstones—as well as additional Plutonics—Volcanics—Sulphides—Metamorphics—Silicates—Oxides and many others. Specimens are tagged, compartments identified and the entire collection is indexed for type and classification. Shpg. wt., 1 lb.

F-676 Net 2.95

**NOVATRON
A SCIENTIFIC
INSTRUMENT FOR
THE EXPERIMENTERS**

- POWERFUL, 110 VOLT AC/DC MOTOR
- MINIATURE ATOM SMASHER
- PRODUCES 75,000 VOLTS
- ABSOLUTELY SAFE




COMPLETELY WIRED
(NOT A KIT)

In no sense of the word a toy or gadget. This machine is a scientific instrument capable of producing 75,000 volts—makes sparks up to 2" long—yet it is absolutely safe because the current is infinitesimal. The science teacher—science lover—or hobbyist can perform experiments to astound students—friends—family. Makes smoke disappear—defy gravity—turns propellers at a distance—transforms atomic energy into light—makes artificial lightning—smashes atoms—demonstrates ionic space ship drive—and many other experiments. Constructed of the finest materials. Will do exactly—for instruction purposes—what generators that cost \$3 to 10 times more will do. The perfect device to teach the secrets of atomic physics and electricity. Will hold an audience spellbound as it performs trick after amazing trick. Includes an experiment kit and illustrated experiment manual. Manual explains the "how" and "why". You will invent many new experiments of your own. A fine research tool that will give years of beneficial service to the institution or individual who owns one. 110 V. AC or DC.

F-371 Assembled—Shpg. wt., 4 lbs. Net 11.95

NEW MIRACLE Astro-Phone



Talk on an Invisible Beam of Light

- Sends Voices Hundreds of Yards • Self-contained, Transistorized Sender/Receiver • Use Day or Night, Indoors or Out

Now you can project your voice hundreds of yards, without wire, even through glass and around corners with mirrors. With the amazing Astro-Phone you just aim and talk... indoors or out... day or night... anywhere, anytime. Absolutely private, tap-proof, jam-proof line of sight communication. Each unit sends and receives. All-transistor amplifiers ready for instant use. Absolutely safe. Housed in unbreakable, high-impact styrene. Operated by 3 ordinary flashlight batteries (included).

AP-65W Shpg. wt., 5 lbs. Net, per pair 19.95
BA-157 Extra Batteries, Burgess #2 (6 req.) Net each .13




REMOTE ENGINE CONTROL ESCAPEMENT
Lafayette's exciting new air-bleed self-neutralizing remote engine control. Varies engine speed of your model. Neutral position of one arm is low speed, neutral position of 2nd arm is high speed, and maintained activated position of either arm (armature activated) stops motor. Perfect mate for Lafayette F-256. Compact and weighs only 3/4 oz. Requires 1 1/2 volt battery. Low current drain. Size: 1 5/8 x 1 1/4". Shpg. wt., 5 oz.

F-257 Net 2.45

COMPOUND REMOTE CONTROL ESCAPEMENT
• LAFAYETTE'S AMAZING VALUE IN A 4-ARM SELF-NEUTRALIZING COMPOUND ESCAPEMENT! • NO NEED TO WORRY ABOUT LOSING YOUR MODEL!
You have no sequence of operation to worry about! Simple as A B C! One pulse always gives right turn; two pulses always gives left turn. Three pulses closes the circuit for the supplementary control such as motor (F-257) or elevator, if used. The rudder always returns to neutral position after any turn as soon as transmitter keying button is released. With ratchet governor for foolproof operation. Sturdy construction—low current drain. Uses 1 1/2 volt battery. Weighs 1 1/4 oz. Size: 2 7/8 x 1 1/4" overall. Shpg. wt., 6 oz.

F-256 Net 3.45

SAVE! "HAM" CODE EQUIPMENT BATTERIES CHARGERS SAVE!



SUPER SPEED TELEGRAPH KEY

9.95

SEMI-AUTOMATIC "BUG"

Fully the equal of keys selling at almost twice the price! 7 adjustments for speed and comfort. Precision-tooled, anti-rust nickel-plated brass and stainless steel operating parts. Speed adjustable 10 wpm to as high as desired. 1/2" silver contacts; weight scale for reproducible speed settings. A real bargain for radio amateurs and professional CW operators! 6 3/4" x 3 1/2" x 2 1/4" H, exclusive of knobs and feet. Shpg. wt., 3 1/2 lbs. MS-435—Net 9.95



CODE PRACTICE SET

1.79

LAFAYETTE SPECIAL

A budget item for the beginning amateur and code practice groups. Key has adjustable spring tension, and adjustable contact clearance. High frequency buzzer has frequency, and tension adjustment with lock nuts to assure constant frequency. There is provision for insertion of head set by means of binding posts with knurled tightening screws. For individual, group or remote listening. Uses Burgess #2 1 1/2 Volt battery. Base 6 3/4" x 2 3/4" x 1 3/8" D, overall length 8 1/2". Shpg. wt., 2 lbs. (less battery). MS-438—Code practice set Net 1.79 BA-157—Burgess #2 Net .13 MS-369—Stethoscope Headset Net 1.39



LAFAYETTE SPECIAL

69¢

SAVE ON NEW TELEGRAPH KEY

Economical key for beginning amateurs. Solid, heavily chrome and nickel plated metal parts, molded phenolic base. Adjustable spring tension and adjustable metal parts, molded phenolic base. Adjustable spring tension and adjustable contact clearance. 2 mounting holes in base. Base 3 1/4" x 1 1/4" x 1/2" W. Overall length 5"; height 1 3/4". Shpg. wt., 12 oz. MS-319—Telegraph Key Net .69



LAFAYETTE SPECIAL

1.95

LAFAYETTE "BRASS POUNDER'S" KEY

- WITH BALL-BEARING PIVOTS
- SOLID POLISHED-BRASS BASE

A better quality precision-made key designed for hard usage. Spring tension and contact clearance adjustments; 3/4" silver contacts; adjustable ball-bearing pivots; Circuit closing switch. Base 3x2"; overall size 5x2 3/4"x1 1/4" Shpg. wt., 1 1/2 lbs. MS-428—Telegraph Key Net 1.95



79¢

HIGH FREQUENCY CODE PRACTICE BUZZER

Adjustable frequency buzzer ideal for individual or group code practice. Perfect code item for the ham shack. Black molded phenolic housing. Works with 1 1/2 volt battery. Screw adjustment for changing tone. 1 1/4" diam. x 1 1/4" high. Shpg. wt., 6 oz. MS-436—Buzzer Net .79



TELEGRAPH TRANSMITTER

And Code Practice Oscillator

Only 2.95 2 for 4.90 4 for 8.75

- Send and receive for miles on one wire!
- Ideal for Network Practice
- For individuals, Group, Classrooms, Hams, etc.

An ideal communications instrument that can be set up, with others, for network practice in classrooms, groups, house to house, etc. Adjustable spring tension and contact clearance. Crystal earphone—high output—lightweight. Molded Bakelite base. Lightweight, only 6 oz., yet designed to give good stability while in use. Complete with 50 ft. of wire on reel, ground spike, ground wire, earphone and Morse code sheet. Uses 1.5V battery (not included). Overall 4 1/4" x 4 1/2" high. Shpg. wt., 1 lb. #552 Telegraph Transmitter Net 2.95 #A-157 Battery for above Net .13

TELEGRAPH TRANSMITTER

Prerecorded magnetic tapes containing a complete course in the International Morse Code. The tapes are 7 1/2" 1200 ft. and can be played on any standard tape recorder. Playing time 2 hours per tape. Shpg. wt., 1 1/2 lbs. NOVICE Basic instructions & code 4-8 WPM. RT-14 Net 6.35 ADVANCED Code at 9-18 WPM. RT-15 Net 5.39



TAPED CODE

Prerecorded magnetic tapes containing a complete course in the International Morse Code. The tapes are 7 1/2" 1200 ft. and can be played on any standard tape recorder. Playing time 2 hours per tape. Shpg. wt., 1 1/2 lbs. NOVICE Basic instructions & code 4-8 WPM. RT-14 Net 6.35 ADVANCED Code at 9-18 WPM. RT-15 Net 5.39

TAPED CODE

Prerecorded magnetic tapes containing a complete course in the International Morse Code. The tapes are 7 1/2" 1200 ft. and can be played on any standard tape recorder. Playing time 2 hours per tape. Shpg. wt., 1 1/2 lbs. NOVICE Basic instructions & code 4-8 WPM. RT-14 Net 6.35 ADVANCED Code at 9-18 WPM. RT-15 Net 5.39



TRANSISTORIZED CODE PRACTICE OSCILLATOR

- MINIATURE-PORTABLE
- SELF CONTAINED BATTERY POWER SUPPLY
- PRODUCES CLEAR, CRISP, CW NOTE

Here is an ideal, inexpensive code practice oscillator for the amateur radio enthusiast. Long 38 inch wire from oscillator to earpiece, allows two persons to practice without interference. The unit is completely portable, and weighs only 6 oz. Tone produced is clear and crisp, similar to that received during F.C.C. licensing examinations. Low voltage transistorized circuit utilize 1.5 volt penlight type battery which completely eliminates any possible shock hazard. Earpiece is crystal type, and housed in sanitary plastic. Shpg. wt., 5 oz. F-429 Oscillator only Net 2.29

CODE PRACTICE OSCILLATOR WITH KEY

Above oscillator plus adjustable telegraph key (MS-319). Key has spade lug connectors, making it possible to disconnect the key from the oscillator and use it separately if desired. Shpg. wt., 9 oz. F-479 MS-319 Key and Oscillator Net 2.95

2.29



AMECO RECORD CODE COURSES

Fast, simple way to learn code for commercial and amateur licenses. Junior course designed to take you from start to 7 1/2 words per minute; Senior course from start to 18 words per minute; Advanced course from 8 to 18 words per minute. Junior set consists of 5 records for 78 and 45 rpm; 1 for 33 1/3 rpm. Senior set consists of 11 records for 78 and 45 rpm; 2 for 33 1/3 rpm. Advanced set consists of 6 records for 78 and 45 rpm; 1 for 33 1/3 rpm. Number in bracket indicates shpg. wt.

Type	33 1/3 RPM	Net	45 RPM	Net	78 RPM	Net
JR.	PR-47 (1 lb.)	4.95	PR-41 (2 lb.)	5.95	PR-40 (4 lb.)	6.95
SR.	PR-48 (2 lb.)	9.50	PR-43 (3 lb.)	10.50	PR-42 (7 lb.)	11.50
ADV.	PR-49 (1 lb.)	4.95	PR-45 (2 lb.)	4.95	PR 44 (4 lb.)	5.95



LAFAYETTE SPECIAL CODE COURSE

Learn Morse Code the modern practical way. Supplied with 10 lessons and a non-breakable high quality 33 1/3 rpm long playing record, recorded with code sound to provide further aid. Perfect for home studying. Speed progresses steadily from 2 to 15 wpm. Complete with sturdy record album and instruction manual. Shpg. wt., 1 1/2 lbs. PR-13 Lafayette Code Course Net 3.50

3.50



TRANSISTOR CODE PRACTICE OSCILLATOR KIT

3.95

COMPLETE WITH TELEGRAPH KEY & TRANSISTOR

For those interested in mastering the international code, an audio tone oscillator is essential. The circuit of this transistorized feedback oscillator has the simplicity of the neon glow, the signal strength of the vacuum tube, and requires only two penlight cells for weeks of service. It may be used for solo practice, or two may send and receive with the same unit. Kit comes complete with Transistor, Telegraph Key, Resistors, Condensers, Masonite Board, etc., and Schematic Diagram. KT-72 LESS BATTERY, Shpg. wt., 1 1/2 lbs. Net 3.95 ME-33 Cannon AM-15-1—Single headset Net 1.18 BA-154 Battery Burg. #7 or eq. (2 required) wt., ea. 1/2 oz. Net ea. .10



REMOTE CONTROL FOR SILENT TV VIEWING

- SIMPLE TO ATTACH TO ANY TV SET OR RADIO
- SEE AND HEAR—NOISELESSLY—CONVENIENTLY
- LOOK AT THESE FEATURES!

1. FOR LATE LISTENERS: One or two people can both see and hear the program with the loudspeaker cut off.
2. FOR HARD-OF-HEARING: They can see and hear without turning the set volume so high that others can't stand the noise.
3. FOR NOISY PROGRAMS: Don't let the kids' "Wild Westers" bother you. Let them view and listen with the speaker off.
4. FOR NORMAL OPERATION: Does not affect your regular use of the T.V. set. Does not have to be disconnected from set.
5. REMOTE CONTROL: Comes complete with 20 ft. of cable so it can be operated comfortably from a distance. Has its own volume control, speaker on-off switch, and two sets of jacks so either 1 or 2 ear phones can be connected.
6. DYNAMIC EAR PHONE: Set is supplied with one of ARGONNE exclusive Hi-Fi dynamic miniature earphone. Highly sensitive and efficient. Phone is complete with 3 ft. cord and tips, ready to insert in control box.
7. CONVENIENT: Size only 3 3/8" x 2 1/2". Complete with 1 ear phone and 20 ft. cable. Completely wired with instructions. MODEL MS-125 Shpg. wt., 3 lbs. Net 6.50

EXTRA EARPHONE

MS-591 Shpg. wt., 8 oz. Net .79
10' extension cord for above. Net .39
MS-590 Shpg. wt., 4 oz. Net .39



ECONOMY ALL-PURPOSE DYNAMIC EARPHONE

- For Transistor and Subminiature Receivers
- For Silent Radio and TV Listening

A sensitive all-purpose earphone designed with both your listening pleasure and pocket-book in mind. Extensive range and excellent tone combine, to provide excellent reproduction. Lightweight, equipped with a practically invisible ear support, that slips comfortably over either ear, from which the earphone can't slip out or fall. Ideal for use with TV and radio sets, amplifiers, miniature and transistor receivers, etc. Attractive unit with shiny chrome finish. Complete with a 3 ft. cord. A super value at this price. Shpg. wt., 5 oz. 6 ohm impedance, with subminiature phone plug. MS-591 Net .79


ONLY 79¢



LAFAYETTE "B" BATTERY ELIMINATOR and CHARGER for TRANSISTOR RADIOS

2.95

This simple "B" battery and eliminator has provision for replacing snap terminals on all 9-volt transistor batteries. Now when indoors you can operate your portable transistor set on regular 110V AC house current without using up your expensive "B" battery... Best of all you may also recharge your used battery for many extra hours of use. Complete with AC cord and assorted snap terminals to fit all 9-volt transistor batteries. Size 3 1/2" x 3 3/8" x 2 1/2" D. Shpg. wt., 1 lb. F-790 Net 2.95




NEW! LAFAYETTE AUTOMATIC PHOTO-ELECTRIC LUMINATOR

- Automatic Light Switch
- Lights on at sunset—off at sunrise

New photo-electronic, light sensitive switch turns lights on and off at dusk and dawn. Better than a clock—no setting and resetting of timer. Variance in "on-off" cycle adds extra protection when away from home. You need never come home to a darkened house. The controlled lamps go on as darkness falls—stay on until sufficient day light returns or until manually turned off. Just plug it in for protection from prowlers—to turn on night lights—illuminate outdoor areas—light up brooders—green houses—displays—show windows—any place you require automatic illumination. Mounts most anywhere on rubber suction cup feet. Unobtrusive—measures only 3 3/4" x 2 1/2" x 2 1/4". Use on 117 volt AC only. Maximum 300 watts lamp load. Instructions included. MS-790 Shpg. wt., 1 lb. Net 4.95

4.95




LAFAYETTE BATTERIES AT TREMENDOUS SAVINGS

These popular batteries are for Portable and Transistor radios, R/C equipment, experimenters, labs, and hobbyists, etc.

FRESH STOCK — BRAND NEW GUARANTEED

Here are six of the most popular types used and at RIDICULOUSLY LOW PRICES


Stock No.	Voltage	Singly	Lots 10 Each	RCA	REPLACEMENTS FOR Burgess	Eveready	Others
BA-1	67 1/2	1.59	1.49	VS215 VS216 VS218	P45 P45M	477	BL-M145
BA-2	9	.39	.35	VS312 VS323	2U6	216	BL-006F
BA-3	9	.49	.44	VS300A VS314	P6 P6M	226	BL-M106
BA-5	67 1/2	1.29	1.19	VS318	UX4E	416	BL-045
BA-6	67 1/2	1.45	1.35	VS016	XX45	467	BL-145
BA-7	9	.59	.53	VS309A	YL-6	E-177	TR-177



"B" BATTERY ELIMINATOR and CHARGER

2.45

Replaces Eveready 416, Burgess UX-45, and RCA VS 318 67 1/2V B batteries used in Radio Control units and many portables. Just plug in the AC cord and you can save your battery for outdoor use. Also recharges your battery. 110 volts. 3 1/2" x 1 3/8". Shpg. wt., 7 oz. F-550 Net 2.45




NEW! "STORAGE CELL" for TRANSISTOR RADIOS!

ONE CHARGEABLE BATTERY OUTLASTS 100 CONVENTIONAL BATTERIES

- Replaces 2U6, 216, BL-006F and BA-2
- Fluid Storage Type—Can't Leak Out
- Plays About 15 Hours on One Charging
- Battery Recharges Overnight
- Battery Can Be Used Over and Over Again
- Complete—Battery Plus Charger

ONLY 2.69

The next best thing to a battery that will last a lifetime—this battery can be used for 1100 to 1500 hours of playing time, AND MORE, its long life is based on 2 new features: 1. A fine storage battery that cannot have fluid leakage; 2. Recharges Overnight—just plug the battery into the charger, the charger into your electrical outlet. Let it charge for 10-12 hours... it cannot burn out on recharge. After charging, the battery is good for about 15 hours of playing time. When the battery runs down, just charge it up and it's ready to play. Will outlast more than 100 conventional batteries. 9V Battery complete with charger. Battery 1 7/8" x 1 5/8"; charger 3 3/8" x 1 3/4". F-619 Battery and Charger. Shpg. wt., 6 oz. Net 2.69 BA-8 Battery Replacement for above. Net 1.48



LAFAYETTE PHOTOFLASH, BC AND HEARING AID BATTERIES

Stock No.	V.	Singly	Lots 10 Ea.	Fig.	Replacements for Burgess	Eveready	RCA	Shpg. Wt.
BA-11	15	.49	.44	A	Y10	504	—	3 oz.
BA-14	22 1/2	.59	.53	A	Y15	505	—	3 oz.
BA-12	22 1/2	.59	.53	B	U15	412	VS084	3 oz.
BA-16	45	1.98	1.83	C	M30	482	VS013	2 lb.
BA-15	90	2.36	2.12	D	N60	490	VS090	1 lb.
BA-13	240	4.50	—	E	U160	491	—	1 lb.

REPLACEMENT BATTERIES FOR BATTERY OPERATED TOYS

Stock No.	Eveready	Burgess	RCA	Size	Voltage	Wt.	Net.
BA-154	912	7	VS074	1 1/2" Diam. x 1 3/4"	1 1/2	1/8	.10
BA-155	915	7	VS034	1 1/2" Diam. x 1 3/4"	1 1/2	3/8	.095
BA-156	935	1	VS035	1 1/2" Diam. x 1 3/4"	1 1/2	1/4	.13
BA-157	950	2	VS036	1 1/2" Diam. x 2 1/4"	1 1/2	1/2	.13

NEW! LAFAYETTE

PEAK-to-PEAK

V.T.V.M. KIT



**An Outstanding Development In V.T.V.M. Design
The Only V.T.V.M. Available With These Features**

NO MONEY DOWN



MADE IN U.S.A.

- Special Low AC Ranges Provide Noise & Gain Measurements (as low as 1 mv) for Audio & Hi-Fidelity Applications
- Scope Monitor Terminals For Direct Connection To Oscilloscope
- Newly Designed Lafayette Push-Button AC/DC Omni-Probe
- Calibration Controls—Accessible Without Removing Cabinet
- Measures AC Peak-To-Peak, AC RMS, DC Voltage & Resistance
- Direct Reading DB Scale
- Regulated & Balanced Bridge Circuit Provides Unequaled Accuracy & Stability
- Circuit Employs 12AU7 Twin Triode Operating Only Within Its Linear Capabilities • 1% Precision Multiplier Resistors
- Accurate 200 μ a Meter Movement with Large 4 1/2" face

In Every Respect A Professional Test Instrument—Engineered to meet and exceed the rugged standards, accuracy plus required sensitivity demanded in laboratory, industrial and service applications. The KT-174 offers in remarkably easy-to-build kit form, a Vacuum Tube Volt Meter that achieves a level of performance and versatility rivaling factory wired equipment many times its price. Unquestionably The Finest VTVM in its class. Utilizing a printed circuit board, Lafayette's famous step-by-step instructions and huge pictorial diagrams assure ease of assembly. Attractive dark grey front panel is set in a contrasting textured light grey metal case. Complete with tubes, battery and special Lafayette Omni-Probe. Size: 8 1/2 x 6 x 5 1/2". For 105-125 volts, 60 cycles AC. Shpg. wt., 8 lbs.

KT-174 | TE-31
44.50 | **57.00**
IN KIT FORM | COMPLETELY WIRED AND TESTED

LABORATORY TEST EQUIPMENT IN EASY-TO-BUILD KIT FORM

COMPARE THESE SPECIFICATIONS

DC VOLTMETER—Ranges: 0-1.5, 5, 15, 50, 150, 500, 1500V. Input Resistance: All ranges—11 Megohms. Sensitivity—1.5V Range: 7.3 Megohms/Volt. Accuracy: \pm 2% of full scale at 117VAC—deviation due to line voltage variation between 105-125 volts is negligible.
AC VOLTMETER—LOW AC—Ranges: RMS—0 to 50 mv, 0-150 mv, 0-500 mv. Peak-To-Peak—0-140 mv, 0-420 mv, 0-1400 mv. Accuracy: \pm 5% of full scale. Input Impedance: 1 megohm at 1 KC. Freq. Response: \pm 1 db from 20 to 300,000 cps from 600-ohm source.
REGULAR AC—Ranges: RMS—0-1.5, 5, 15, 50, 150, 500, 1500 volts. Peak-To-Peak: 0-4.2, 14.0, 42, 140, 420, 1400, 4200V. Accuracy: 3% on all ranges except 5% on 0 to 5V. Freq. Response: \pm 1 db 20 cps to 4 mc from 600-ohm source. Input Impedance at 1 KC: 0-1.5V, 5V, 15, 50-83 Meg. 0-150V, 1.3 meg—0-500V, 1500V—1.5 meg. Db.—10 to +5 OHMMETER—7 Ranges: 0-1000 RX1, RX10, RX100, RX1000, RX10K, RX100K, RX1M using precision 1% dividing resistors. Meter Movement: 200 μ a for full scale deflection. Tubes: 1—6BN8, AC full-wave peak rectifier and low AC amplifier; 1—12AU7 twin triode meter DC amplifier and balanced bridge. Incorporates Half Wave Selenium Rectifier and Well Filtered Fused Power Supply.

KT-174 Kit Form Net 44.50
TE-31 Same as above, wired and tested Net 57.00
KT-205 RF Probe Kit For KT-174 and any Other Net 3.75
11 meg Ohm Impedance VTVM

NEW! LAFAYETTE V.T.V.M. KIT



MADE IN U.S.A.

- Wide Band—AC Measurements on any Waveform from 30 Cycles to Over 5 MC, Without Additional Probes or Accessories
- 11 Megohm Input Resistance—Negligible Loading Effects on DC Circuits
- Direct Reading DB Scale
- Balanced Push-Pull Amplifier—Isolates and Protects Meter
- Etched Circuit Design Simplifies Construction
- Selected 1% Zero Temperature Coefficient Multiplier Resistors for Dependable, Accurate Readings
- Giant 6" Full-View Meter With Easy-To-Read Two-Color Scales



An indispensable test instrument for the service technician, experimenter or hobbyist. The KT-202 is a high quality V.T.V.M. in easy-to-build kit form, which offers features unusual at this low price. It is a highly accurate DC voltmeter, AC voltmeter and ohmmeter employing a giant 6", 400 μ a meter with clear black and red scales. High input impedance of 11 megohms, accurately measure DC voltages up to 1500 volts while presenting a negligible load to the circuit under test. As a wide band AC voltmeter, it will measure AC peak-to-peak voltages up to 2,000 volts on any waveform. All this from 30 cycles to above 5 Mc—without any accessory probes! AC RMS voltages may be read directly up to 1,500 volts if the waveform is sinusoidal. The wide frequency response makes this meter ideal in audio, radio and TV applications. Resistances can be read directly on the Ohms scale from 0.2 ohms to 1,000 megohms. A direct reading decibel scale is calibrated from -10 to +18 db (reference 1.73 volts, 6 mw into 500 ohm line). In addition, zero center measurements can be made. The KT-202 utilizes a 12AU7 balanced push-pull DC amplifier and two 9006 tubes as peak-to-peak voltage rectifiers. The meter is isolated making it virtually impossible to burn it out. Multiplier resistors are 1% zero temperature coefficient types, to assure maximum accuracy and minimum variation due to heat. Front panel controls: Function Selector—selects Pwr. Off, A.C.V./P-PV, D.C.V. Neg., D.C.V. Pos., Ohms; Range Selector—for 7 voltage and resistance ranges; Ohms Adjustment; Balance (zero) Adjustment. There are 3 probes: Common, A.C.V.—Ohms, and a shielded D.C.V. probe with 1

megohm isolating resistor. Printed circuitry makes construction of this kit easy. Selenium rectifier transformer—operated power supply for 110-120 VAC, 60 cps. Dimensions: 7 1/2 x 6 1/2 x 5 1/2" overall. Kit comes with 1 1/2 volt battery for ohmmeter circuit and complete instructions. Shpg. wt., 7 lbs.

MODEL KT 202

25.95

NO MONEY DOWN

KT-202 Net 25.95
Accessory RF probe for KT-202 or other 11 megohm V.T.V.M. Net 3.75
KT-205 Carrying case for KT-202, complete with handle. Net 2.95
KT-203 Shpg. wt., 1 lb.

SPECIFICATIONS

DC VOLTMETER RANGES: 0-3, 15, 75, 150, 300, 750, 1500 volts. Input resistance: 11 megohms (1 megohm in probe) on all ranges.
AC VOLTMETER RMS RANGES: 0-3, 15, 75, 150, 300, 750, 1500 volts. PEAK-TO-PEAK RANGES: 0-8, 40, 200, 400, 800, 2000 volts.
DECIBEL RANGES: -10 to +18db, +10 to +38db, +30 to +58db. Response: 30 cycles to above 5 Mc.
OHMMETER RANGES: 0-1000, 10,000, 100,000 ohms; 0-1, 10, 100, 1000, megohms. CENTER SCALES: 10, 100, 1000, 10,000, 100,000 ohms, 1 megohm, 10 megohms.
TUBES: 1—12AU7 twin triode balanced meter bridge, 2—9006 peak to peak rectifiers, 1 power supply selenium rectifier.
POWER: 110-120 VAC, 60 cycles.

NEW! LAFAYETTE COMBINATION SIGNAL GENERATOR AND SIGNAL TRACER KIT

NEW!

MODEL KT-208



MADE IN U.S.A.

Another Outstanding Achievement by Lafayette Test Equipment Engineers

SEMI-KIT CONSTRUCTION !!! This unit uses proven semi-kit construction with all major components premounted and tested at the factory.

SIGNAL TRACER

- Hi-gain Cascode Pre-amplifier
- Front Panel Output For VTVM, Scope or Phones
- Low Distortion Triode Output Stage
- 4 1/2" Permanent Magnet Speaker
- Separate R.F. and Audio Signal Probes

SIGNAL GENERATOR

- Covers From 250 KC to 120 MC in 5 Bands
- High Stability Electron Coupled Oscillator
- Attenuator For Both RF and Audio Circuits
- Most Used Frequencies Marked on Panel in Color
- Utilizes New Ruggedized Industrial Type Tubes

Two test instruments in one! And available in easy-to-build kit form. The Signal Generator will serve as a full service instrument and the Signal Tracer will follow any signal whether generated by a broadcasting station or injected by the Signal Generator section of the Model KT-208. When used in combination, with no dependence on outside signals, the compatibility of Model KT-208 provides ideal service, for unlike any standard signal tracer, it first injects its own signal then traces that controllable signal to locate the source by standard signal tracing technique. Designed for use with AM, FM, TV and audio circuitry. Features 5 frequency ranges and an attenuator switch to control both the R.F. signal (either modulated or unmodulated) and the 400 cycle audio tone. Front panel output jacks which can be used for oscilloscope, VTVM or earphone connections. Famous Lafayette kit building manual with large pictorials will make it a pleasure to build. Housed in a beautiful crackle finish steel cabinet with a deep

etched aluminum panel. Dimensions: 7 1/2 x 9 1/2 x 5 3/4". Complete with 2 probes. Shpg. wt., 9 lbs.

This unit uses proven semi-kit construction with all major components premounted and tested at the factory.

KT-208 Kit Net 19.95

MADE IN U.S.A.

19.95

SPECIFICATIONS

RANGE: BAND A: 250KC to 2500KC; B: 850KC—300MC; C: 3.0MC to 11MC; D: 11MC to 45MC; E: 35MC to 120MC: 400cps audio signal; modulation slide switch, RF/AF attenuator and power switch; Signal output jack; AF input jack. 2 Preamp. output jacks. 4 1/2" alnico 5 speaker. Tubes: 5965, 5687, 6350, 6AG5

NEW!

MODEL KT-209



MADE IN U.S.A.

SEMI-KIT CONSTRUCTION !!! This unit uses proven semi-kit construction with all major components premounted and tested at the factory.

- Test Over 1,000 Tube Types
- Checks For Shorts and Leakages Between All Elements
- Tests Filament Continuity
- Checks All Modern Tubes
- Five Year Free Tube Data
- 7 and 9 Pin Tube Straighteners
- Rugged, Accurate. Meter Movement With Sealed Air Damping Chamber

Features & Specifications:

The KT-209 is a complete portable tube tester designed to test the modern tubes found in radio, TV and hi-fi amplifier systems. Speedy operation is assured by use of a single rotary switch in place of one-at-a-time slide switches normally used. Just insert tube in one of the seven panel sockets, set filament selector switch and then rotate the Element switch. Shorts show up instantly on the "leakage indicator" lamp. Tube emission quality is indicated on the highly damped meter's calibrated "Good—?—Bad" scale. A two position slide switch for regular or special higher voltage tubes sets up the meter test. 7 and 9 pin straighteners are provided to insure long life for these sockets. Superbly detailed, step-by-step

Lafayette instruction manuals with giant diagrams will assure you of factory-type assembly. This unit uses proven semi-kit construction with all major components premounted and tested at the factory. All you have to do is wire it up! American made, and replacement parts are always available if needed. No finer value available anywhere. Housed in a portable leatherette carrying case with removable cover for easy accessibility. Dimensions: 10 1/2 x 8 3/4 x 3 1/2". Shpg. wt., 6 lbs.

KT-209 Kit Net 17.95

MADE IN U.S.A.

17.95

NEW!

LAFAYETTE—RF SIGNAL GENERATOR

- Perfect for Engineers, Servicemen, Students and Experimenters
- Quality Assembled Equipment at a KIT PRICE!



- FACTORY CALIBRATED AND TESTED
- SIX BANDS: 120 KC - 260 MC
- DUAL OUTPUT RF TERMINALS
- SEPARATE VARIABLE AUDIO OUTPUT
- DIAL CALIBRATION $\pm 2\%$
- ETCHED CIRCULAR DIAL - (Vernier Tuned)

A stable, wide-range signal generator engineered to fill the need for an accurate, low cost service instrument. Saves you time and money compared to spent building a kit of lesser quality. Since the delicate oscillator coils and tuning assembly are factory mounted and adjusted for optimum performance, the TE-20 is ready to go to work for you the instant you unpack it. This top-flight signal generator can be used for IF-RF alignment, audio signal tracing of TV, FM and AM sets, TV linearity checks and 400 cycle audio testing. In addition, it can serve as a marker generator when used with a suitable sweep generator. Look at some of the TE-20's features which make it the service instrument buy of the year. Incorporates a large 4 1/4" etched circular dial for easy, accurate frequency adjustments. Provides a fundamental frequency output of 120 KC to 130 MC in 6 bands plus a calibrated harmonic output of 130 MC to 260 MC. The built-in audio oscillator operates at 400 KC with adjustable output to 8 volts. Continuously variable RF attenuator for proper signal attenuation and two plug-in RF output terminals provide a choice of high and low outputs for maximum flexibility. High output and tuning dial calibration of $\pm 2\%$ give evidence of features not found elsewhere at twice its price.

Net 27.95

NO MONEY DOWN

27.95

SPECIFICATIONS

Full frequency range: 6 Fundamental bands—120-320 Kc 320-1000 Kc. 1-3.4 MC, 3.2-11 MC, 11-38 MC, 36-130 MC. One harmonic band 130-260 MC. Frequency Accuracy: $\pm 2\%$. Audio Output: to 8 volts. Large 4 1/4" Etched Circular Dial (Vernier tuned) High-Low RF Output Terminals. Tube Complement: 12BH7A, 6AR5, Selenium Rectifier. Power Requirements: 105-125VAC 50/60 Cps., 12 Watts. Attractive gray wrinkle steel case with leather carrying handle. Complete with test leads. Size: 7Hx10 1/2Wx5 3/8"D. Shpg. wt., 9 lbs.

NEW!

LAFAYETTE—SINE SQUARE WAVE AUDIO GENERATOR

- FACTORY CALIBRATED AND TESTED
- LOW DISTORTION
- FREQUENCY RANGE - SINE: 20 cps—200 KC IN 4 BANDS; SQUARE WAVE RANGE: 20-25 KC (Vernier Tuned)
- ETCHED CIRCULAR DIAL
- FREQUENCY RESPONSE - ± 1.5 DB, 60CPS - 150KC 4 1/2" VERNIER DIAL



The Lafayette TE-22 is especially designed for radio-TV servicemen, Hi-Fi fans and students who require a dependable sine and square wave generator at low prices. A completely wired and tested instrument, it is equal in quality to higher priced separate generators and far more convenient to use. A terrific buy, this generator will outperform most higher priced kits with ease. Among its many applications are accurate wave testing of audio amplifiers, determining the frequency and transient response of loudspeakers, TV audio circuit testing and many other uses. Quality features consist of a frequency response of ± 1.5 db from 20 cps to 200,000 cycles in 4 bands. A large easy-to-read etched dial (vernier tuned) adds a professional quality touch. Variable attenuator prevents overloading circuits and permits proper tracking of frequency and constant output. Factory wiring and calibration insure its accuracy to be within 5%. High output voltage is 7 volts (max.) across a 1 megohm load. A rugged steel cabinet and shock proof mountings protect components, complete with instructions and test leads. A handsome instrument—one which you will be proud to own.

Net 32.50

COMPLETELY WIRED NOT A KIT!

NO MONEY DOWN

32.50

SPECIFICATIONS

Frequency range: Sine wave: 20-200,000 cps in 4 bands. Square wave—20-25,000 cps. Output Voltage—Sine: 7V P-P. Output Impedance—0-5000 Ohms. Frequency Accuracy: $\pm 5\%$. Distortion: Less than 2%. Tube Complement: 1-6BM8, 1-12AT7, 1-6X4. Power requirements: 117V 50/60 cps. 19W. Gray wrinkle steel case with leather carrying handle. Complete with a pair of test leads. Size: 7Hx10 1/2Wx5 3/8"D. Shpg. wt., 10 lbs.

NEW!

NEW! LAFAYETTE CAPACITANCE-RESISTANCE ANALYZER

- Factory Wired and Tested
- Capacitance Bridge Circuit
- Direct Reading Scales for Capacitance and Resistance
- "Magic-Eye" Null Indicator and Meter
- Checks Opens, Shorts, Leakage and Intermittents
- Determines Power Factor of Electrolytics
- 2 Turns Ratio Scales
- Measures Impedance



Here is a real service value which can do wonders in your shop or lab. The TE-25 is a completely self-contained AC operated, bridge-type capacitance-resistance analyzer which has a number of time saving applications. It is a high caliber, factory built instrument, not a kit. All readings are made directly without complex, time wasting calculations. "Lab" accuracy within $\pm 5\%$ for values to 200 mfd and $\pm 5\%$ from 200 mfd up. It measures capacity and resistance in 4 separate ranges—from 1 mmf—5000 Mfd and from 0.5 ohms—500 megohms on a large permanently etched circular metal scale. You will find it invaluable for the following jobs: Measurement of Capacitance for paper, mica, ceramic and electrolytic capacitors. Resistance measurement. Power Factor measurement on electrolytics from 0-55%; shorts, opens and leaky capacitors. Also determines turn and impedance ratio of audio and power transformers. Read insulation resistance of paper, mica and ceramic capacitors directly on meter to 500 megohms. Eliminates guessing with neon lamps. DC voltage may be varied up to 600 volts to find leakage current of electrolytics. Two ranges (0-6) (0-60) ma is directly read on meter. No guesswork is necessary. Ratio scales are provided to measure impedance and turns ratio of power and audio transformers (to 500:1) in 2 ranges. "Magic-Eye" tube shows capacitance null indication—opens, shorts for electrolytics, a calibrated power factor control is provided to check capacitor efficiency. No service shop or laboratory should be without one. Shpg. wt., 12 lbs.

Net 34.95

COMPLETELY WIRED NOT A KIT!

NO MONEY DOWN

34.95

SPECIFICATIONS

Capacity, 4 Ranges — .00001 mfd — .005 mfd; .001 mfd — 5 mfd; 1 mfd — 50 mfd; 50 mfd — 5000 mfd. Resistance — 4 Ranges — 0.5 ohms — 500 ohms; 50 ohms — 50K ohms; 5K ohms — 5 megohms; 5 megohms — 500 megohms. Transformer Turns Ratio — 1:1 — 10:1; 10:1 — 500:1. Impedance Ratio — 1:1 — 100:1; 100:1 — 250K:1. DC Leakage Test — Voltages: 0-600 Volts DC. Leakage Current — 6MA — 60 MA — 2 Ranges. DC Insulation Test — 600 Volts Constant — 10 megohms — 500 megohms. Tube Complement: — 1-6R4; 1-6E5. Power: — 117V; 50/60 cps AC. Size: 10 1/2Wx7Hx 5 1/4"D. Complete with instructions and test leads. Handsome grey wrinkle steel case with leather carrying handle.

EICO MODEL 666K DYNAMIC CONDUCTANCE TUBE AND TRANSISTOR TESTER KIT

An ideal tube tester for color and monochrome TV servicing. Tests all receiving tubes, including 4, 5, 6, 7-pin, octal, loctal, miniature 7 and 9-pin, sub-miniature, 5, 6, 7-pin (in-line base) and 8-pin (circular base) receiving tubes, transmitting and special purpose tubes. TV picture tubes with accessory adaptor. Measures transistor collector current and shows current amplification factor. Measures Gp, Gm and also leakage in ohms. For 105-130 volts, AC 50/60 cps. 12x15x4 1/2". TE-151WX Kit Shpg. wt., 18 lbs. Net 69.95 Model 666. As above, but factory wired and tested. TE-152WX Net 109.95



EICO MODEL 460K WIDE BAND SCOPE KIT

Excellent Lab precision scope featuring Push-pull direct coupled vertical amplifier with high sensitivity: 25 mv/in. Response flat from DC to 4.5 mc, useful to 10 MC, ideal for reproduction of 3.58 mc color TV sync. burst, 4 step freq.-compensated attenuator in both AC, DC positions. Also internal voltage calibration. Automatic sync. limiter and amplifier. 2X-full screen horizontal positioning. Sweep-freq: 10 to 100K cps with external capacitor for lo-freq. sweeps. Variably lit graphed 5" screen. Complete with all components and instructions for easy assembly. 13x8 1/2x16". For 105-125 vac, 50-60 cycles. Shpg. wt., 30 lbs. Net 79.95 TE-222WX Kit Net 129.50 Model 460. As above, but factory wired and tested. TE-223WX



New SUPERIOR MODEL 88 Transistor Radio TESTER & DYNAMIC TRANSISTOR TESTER

• Features Built-in Transistor Signal Injector and Signal Tracer

The Model 88 was designed specifically to test all transistors, transistor radios, transistor recorders, and other transistor devices under dynamic conditions. Self-contained oscillator provides stable harmonic signal injection up to 30 megacycles. Dynamically measures leakage and gain (beta) of all transistor types, including NPN, PNP, germanium, silicon, gallium arsenide and the newer diffused junction and mesa types. Complete with cables, R-F diode probe, audio probe and battery. 11x6 3/4x4". Shpg. wt., 5 lbs. TE-516 Net 37.73



SIMPSON MODEL 260 SERIES III AC-DC V-O-M

43.07 NO MONEY DOWN

Now offered in a new and improved form. Sensitivity — 20,000 ohms; V.D.C., 5,000 ohms—V.A.C. Ranges: DC: 0-25V, 2.5V, 10V, 50V, 250V, 1000V, 5000V; AC: 0-25V, 10V, 50V, 250V, 1000V, 5000V; AF: 0-2.5V, 10V, 50V, 250V; DB: 20 to +10 db; —8 to +22 db; +6 to 36 db; +20 to +50 db. DC current ranges from 0.50 u amps, 0.1, .10, .100, .500 ma; 0-10 amps, DC resistance from 0-2000 ohms, 0-200,000 ohms, 0-20 megohms. Accuracies: DC volts $\pm 3\%$ F.S.; AC volts $\pm 5\%$ F.S.; DC resistance $\pm 3\%$ of arc from absolute value of resistance measured. Meter housed in Bakelite case, measures 5 1/4x7 3/8". Comes with battery and test leads. Shpg. wt., 6 lbs. TE-310 Net 43.07




EICO MODEL 1060K EXTRA-FILTERED BATTERY ELIMINATOR & CHARGER KIT

This versatile, rugged unit incorporates an extra low-ripple filter circuit. Ideal for latest all-transistor 6 or 12 volt equipments and any conventional ones using vacuum tubes. Selection of voltage range automatically provides appropriate current range. Fused transformer primary. Continuous voltage adjustment with Variac. 2 DC ranges and dual-range ammeter for accurate readings. Ranges: high range = 0-16V, 6 amps continuous, low range = 0-8V, 10 amps continuous. For 105-125 volts 50/60 cycle a.c. All components and instructions included. 8 3/4x10 1/2x7 3/8". TE-193 Kit Shpg. wt., 19 lbs. Net 38.95 Model 1060. As above, but factory wired and tested. TE-194 Net 47.95



PARALAN IN CIRCUIT TRANSISTOR TESTER

This amazing instrument can check all types of transistors (including power types), while they are still soldered in their respective circuits! Checks for shorts, open circuits, leakage, oscillation and comparative gain. Will test diodes and rectifiers of all types, and indicate whether a transistor is a PNP or NPN type. The in-circuit transistor checker comes complete with insulated test leads marked "emitter", "base", "collector", and is powered by two standard penlight cells (included). Ready to operate—test leads are connected to their respective transistor elements, and condition of the transistor is shown by neon indicators on front panel. Unit is extremely compact—only 6 1/4x3 3/4x2 3/4". TE-502 Shpg. wt., 1 1/2 lbs. Net 15.95 Replacement batteries for above (2 required) BA-155 Net ea .095



SUPERIOR MODEL 70 UTILITY TESTER

15.53 Test Appliances and Utilities

Appliance and utility tester. Will test toasters, irons, broilers, clocks, fans, fluorescent lamps, auto systems. Measures AC and DC voltages, AC and DC current, resistance, leakage (ohms scale from 0-5 Meg-ohms). Voltage scales 0-150; 0-300. Amps Scales 0-15 amps. Comes with instructions and leads. Shpg. wt., 3 lbs. TE-513 Net 15.53 TE-517 7.5V Battery Pack for Model 70 Net 1.00



RCA WV-77E(K) VOLT-Ohm-MYST IN KIT FORM

43.95 ONLY **29.95** KIT WIRED

Its 28 ranges include 7DC and 7 rms AC Voltages 0-1.5, 5, 15, 50, 150, 500, 1500; 7 peak-to-peak AC voltages: 0-4, 14, 40, 140, 400, 1400, 4000 volts, 7 overlapping ohms ranges from 0.2 ohms to 1000 megohms with center-scale values of 10, 100, 1000, 10K, 100K, 1 meg, and 10 meg. ohms. Zero-center for discriminator alignment; frequency response of 40 cps to 5mc. flat to within $\pm 5\%$ on the 1.5 to 15 volt rms and 4 to 40 volt p-to-p ranges; meter electronically protected against burnout. Supplied complete with DC and AC/ohms probes and cables and ground leads, battery, and instruction book. TE-141 Shpg. wt., 5 1/2 lbs. Net 29.95 WV-77E Same, completely wired and factory-calibrated. TE-142 Net 43.95



The Sensational LAFAYETTE TE-15 TUBE TESTER



COMPLETELY WIRED — NOT A KIT

- Accurately Checks Over 1000 Different Tubes
- Tests for Cathode Emission, Leakage and Shorts plus Filament Continuity
- Completely Portable—Weights Only 6 lbs.
- Highly Accurate Easy-to-Read Meter with Replace—Good Scale
- Fast-Setting Slide Switches
- Slide Out Tube Chart

Highly dependable, the Lafayette TE-15 is equipped to test most of the tube types employed in Radio, Hi-Fi, Monochrome, Color TV, etc. Sockets have been provided for 7-pin miniature, 9-pin miniature, octal base, loctal base, hoval and sub-miniature types. A special alligator clip lead is furnished for testing tubes with top caps. Slide switches are employed to connect the various tube elements to their respective test circuits. A 3-position tube slide switch adjust for checking shorted elements, cathode emission and filament continuity. In conjunction with the leakage-quality switch a leakage indicator light is employed which glows when an interelement short or leakage is present in a tube. A power switch turns the unit on and additionally serves to adjust for various AC line voltages. Large easy-to-read meter calibrated 0-100 has a red-green "Replace—Good" scale, plus a special scale for checking diodes.

A handy slide out metal tray contains tube charts which facilitate rapid selection of test settings. Metal case is attractively finished in cream and steel gray. Completely portable—weights only 6 lbs. and measures 8 1/2" D x 9 3/4" W x 2 3/4" H. Supplied with carrying case. For 105-125 volts, 60 cycle AC. Shpg. wt., 7 lbs.

TE-15 Tube Checker Net 19.95

LOW,
LOW PRICE!


19.95

FULL
SIZE
9 3/4" W
x 8 1/2" D
x 2 3/4" H

NO MONEY
DOWN

An accurate, versatile, precision instrument that actually tests over 1000 different tubes. The low cost and superior performance of the Lafayette TE-15 Tube Tester combine to make it the outstanding test instrument value today—the ideal tube tester for any radio-TV serviceman, experimenter, technician, etc.

20,000 OHM PER VOLT SEMI-KIT MULTITESTER



ONLY
11.95

The semi-kit is a new concept in test equipment kits. All the important or difficult parts are already mounted. All that remains to be done is to mount and wire in a few small parts—a job so simple you'll finish before you realize it, and best of all, you'll have one of the finest high sensitivity multimeters on the market. When used in a circuit, the high input resistance on all DC and AC ranges does away with the highly inaccurate readings common to low resistance testers which load the circuit. Ranges: DC Volts, 0-10-50-250-500-1000; AC Volts, 0-10-50-250-500-1000; DC CURRENT, 0-500 ua, 0-10-250 ma; OHMS, 0-10K-100K-1 meg; DECIBELS, —20 to +36; PLUS 0-5000 henries and 250 mfd. to .02 mfd. Black case 5 3/4 x 3 1/2 x 1 1/2". Complete with test leads, all parts, and instructions and battery. Shpg. wt., 3 lbs.

Net 11.95

FILAMENT CONTINUITY TUBE CHECKER



1.69

Small and compact as a cigarette box. Quickly checks filament continuity in a matter of seconds. Ideal for the serviceman or the technician working in the field. Tests filaments of radio, TV picture tubes. Also can be used to test many other electrical devices and line cords, fuses, lamps and bulbs. Has sockets for TV picture tube and loctal, octal, 9-pin, as well as 7-pin sockets. Provided with two test leads. Grey hammer-tone finish. Size: 4x3x1 1/2". Shpg. wt., 12 oz.

TE-11

Net 1.69

NEW! 10,000 OHMS PER VOLT MULTITESTER

OUTPERFORMS INSTRUMENTS
MANY TIMES ITS SIZE

9.95

- EXTRA LARGE 3 1/2" METER FACE
- ALL ACCESSORIES INCLUDED

• COMPLETELY WIRED (NOT A KIT)

FULL SCALE RANGES

DC VOLTS: 0-6; 0-30; 0-120; 0-600; 0-1200; AC VOLTS: 0-6; 0-30; 0-120; 0-600; 0-1200; DC CURRENT: 0-1200 uA; 0-3M; 0-300M RESISTANCE: 0-30K; 0-3 MEG DECIBELS —20 to +63 in 5 scales; Capacity 50 uF to .01 uF; and .001 uF to .15 uF; OUTPUT RANGES 0-6; 0-30; 0-120; 0-600; 0-1200.

Unbelievable Bargain. Lafayette's new multimeter is a complete factory wired and tested instrument (not a kit). It can be conveniently carried in the pocket, and features unusually sensitive 10,000 ohms-per-volt AC-DC meter, 1% precision resistors, and the largest meter ever placed on an instrument of this size. Single easy-to-use range selector switch can be appreciated by the novice and the engineer alike. Case and panel are made of durable bakelite. First capacity range requires 120 volts AC, second range requires 6 volts AC. Probes and flexible leads are plastic coated and color coded. Size: 4 1/2 x 3 1/2 x 1 1/2". Complete with leads and battery. Shpg. wt., 1 1/2 lbs.

TE-10

Rigskin carrying case for TE-10. Shpg. wt., 8 ozs.

TE-14

Net 9.95

Net 1.95

Net 1.95

NEW HIGH SENSITIVITY MULTITESTER



- 20,000 OHMS PER VOLT DC
- 10,000 OHMS PER VOLT AC
- RESISTANCE RANGE 0-60 MEGOHMS
- 40 uA MOVEMENT
- 1% RESISTORS
- 0-0.6 VOLT DC RANGE FOR AUDIO AND TRANSISTOR WORK
- COMPLETELY WIRED
- 28 RANGES

17.95

A new high-quality, low-priced multimeter. Its light weight makes it a perfect portable instrument for technicians, servicemen, etc. Rugged design withstands hard use. Features large easy-to-read meter and sensitive 40 microamp meter movement. 1% tolerance resistors provide extreme accuracy of measurements. Housed in rugged bakelite case. Single knob selector and clearly marked positions permit easy operation. Recess zero-ohms knob adjustment provided. Features sensitivity of 20,000 ohms/volt DC, and 10,000 ohms/volt AC. Ranges: DC volts: 0-0.6, 0-6, 0-30, 0-120, 0-660, 0-1200, 0-3000, 0-6000 volts. AC volts: 0-6, 0-30, 0-120, 0-600, 0-1200 volts. Resistance: RX1, RX100, RX1K, RX10K. DC current: 0-0.06, 0-6, 0-60, 0-600 ma. Decibels: —20 to +17 (0 db — 0.774 V). Capacity: .0001-.01, .005-.20 mfd. Output ranges: 0-6, 0-30, 0-120, 0-600, 0-1200 volts. Complete with color-coded heavy duty test probes and battery. Size: 6x3 3/4 x 1 3/4". Shpg. Wt., 1 1/2 lbs.

TE-12

Net 17.95

Net 17.95

Net 17.95

TE-37 Felt-lined carrying case for above instrument Net 2.95

NEW! POCKET AC-DC VOM

ONLY

5.95



- Extremely Compact, Measures Only 3 1/2 x 2 1/2 x 1 1/2"
- Weighs 5 Ozs. • 1,000 Ohms Per Volt Sensitivity
- Completely Wired (Not A Kit) • 1% Precision Resistors
- Reads 0-1000 Volts AC-DC 0-100KΩ, 0-150 MA

Lafayette's new, pocket multimeter features small physical size, and a wide selection of useful ranges. It can be used for trouble-shooting any type of electronic circuits or electrical appliances such as irons, lamps, radios, television, hi-fi equipment, etc. It is also useful for testing complex electrical circuits. Extreme portability allows unlimited usage either at home or in the field.

1000 ohms per volt sensitivity, and 1% precision resistor components assure accurate, precise readings. Operation is extremely easy, simply plug the leads into the desired scale, and you are ready to go, no switching or fiddling required. Ranges Volts: 0-15-150-1000 AC and DC. Ohms: 0-100K MA: 0-150. The VOM comes completely wired and tested, and is enclosed in durable plastic case. All accessories including battery are rubber insulated, color coded, flexible test leads are supplied.

TE-13 AC POCKET VOM Shpg. wt., 1 lb. Net 5.95

NEW! CAPACITANCE SUBSTITUTION BOX



2.95

- 36" Color Coded Test Leads & Clips


- 9 Ranges From .0001 to .22 MFD

A must for the serviceman, experimenter or student. Fast accurate selection of any one of 9 capacitor values from .0001 to 22 MFD. Condensers are porcelain cased tubular type impervious to moisture and are rated at 600 volts working capacity. 9 capacitance ranges are .0001, .0022, .0047, .01, .022, .047, .1 plus 22 MFD. Complete with 36" red and black test leads and alligator clips. Size: 4 3/4 x 2 3/4 x 1 3/8". Shpg. wt., 1 1/2 lbs.

TE-16

Net 2.95

NEW! RESISTANCE SUBSTITUTION BOX



3.95

- 24 Resistance Ratings
- Two Ranges — Low 15-10K Ohms. High 15K-10 Megohms.
- 36" Red & Black Test Leads with Alligator Clips

Ideal for laboratory or service application. Substitute resistance values fast and accurately in trouble shooting circuits where values may have changed. Easy to find bias resistance in experimental vacuum tube or transistor circuits. Slide switch selects two ranges—Low: 15 ohm—10K ohm (1 watt resistors) High: 15 K ohm—10 Megohms (1/2 watt resistors). Two rotary switches (12 steps each) selects 24 separate resistances. Size: 4 3/4 x 2 3/4 x 1 3/8". Shpg. wt., 1 1/2 lbs.

TE-17

Net 3.95

SPECIAL

SENIOR V.T.V.M. with 6 1/2" METER

Not a Kit . . .
This is a
completely wired
and calibrated
instrument

29.35

- ± 3% Accuracy of Full Scale
- Giant 6 1/2" Meter Face
- Direct Reading DB Scale

COMPARE THESE FEATURES
D.C. VOLTMEETER. Ranges 0 to 3, 30, 150, 300, 1500 volts. Accuracy ± 3% of full scale. Input resistance: 11 megohms. ZERO CENTER VOLTMEETER (for discriminator alignment) Ranges 0 to 1.5, 15, 75, 150, 750 volts. Accuracy ± 3% of full scale. Input resistance: 11 megohms. AC VOLTMEETER. RMS RANGE: 0 to 3, 30, 150, 300, 1500 volts. Peak to Peak Ranges: 0 to 8, 80, 400, 800 volts. Accuracy ± 3% of full scale. OHMMETER. Ranges 0 to 1000 megohms (5 overlapping ranges). Center scale values: 10, 100, 1000, 100,000 ohms. 10 megohms. DECIBEL METER (for all audio measurements) Ranges: —10 to +5, +6 to +25, +26 to +45 decibels. All bases on zero db. at 1.73 volts on 500 ohm line. Pilot light indicates when unit is "on." Complete with D.C. V.T.V.M. probe and cable plus pair of standard test leads. Housed in a rugged grey high-impact case, with color matched etched aluminum panel and portable handle. Size: 5 1/2 x 2 1/2 x 1 1/2".

TE-500 Shpg. wt., 6 lbs. Net 29.35

Lafayette for ELECTRONICS, Science and Technology PHOTOCELL SPECIALS for Experimenters & Engineers

OCTAL BASED PHOTO-CONDUCTOR



- High Sensitivity
- Perfect For The Experimenters

3.95

A cadmium photo-conductor cell mounted in an octal type tube base for versatility in application. Ideal for cell relay, Rated: 4900 ohms at 10 ft. candles; 200 4000 to 8000 Angstroms. Spectral response covers from 4000 to 8000 Angstroms. Maximum power dissipation at 25°C: 0.5 Watts; ambient temperature —40 to 60°C. Maximum voltage ratings: 200 volts DC or AC peak. Resistance value characteristics: at 0 ft. candles — 500,000 ohms; at 1 ft. candle — 5,000 to 30,000 ohms; at 10 ft. candles — 90 ohms to 5,000 ohms. Size 2-1/10" H overall. MS-882

Net 3.95

INFINITE DARK RESISTANCE PHOTO-CONDUCTOR



- Mount This Lafayette Special In Any Position
- 1 1/2" Diam. 1 1/2" High

4.95

This Lafayette cadmium sulfide PHOTO-CONDUCTOR special can be mounted in many positions through two leads from the base of the cell. An ideal cell for the experimenter requiring extreme versatility. Spectral response covers from 4,000 to 8,000 Angstroms. Maximum power dissipation (25°C): 1.0. Ambient temperature (C): —40 to 60. Maximum voltage 200 volts DC or AC peak. Resistance Value Characteristics — 0 Ft. candles: above 200K ohms; 1 Ft. Candle: 500 to 40K 1-7/10" H. Shpg. wt., 4 oz. MS-881

Net 4.95



POLARIS "MAJ-I" RESISTOR PHOTOCELL

2.19

A cadmium-sulphide light-dependent resistor used to actuate door openers, burglar alarms, smoke detectors, light controls, production counters, etc. Resistance varies from 200 ohms at approx. 93 foot-candles to over 10 megohms in total darkness. Maximum voltage: 110VAC 1 watt @ 50°C, 0 @ 60°C. Capacity approx. 6 mmf. 1/8" diam. x 1/4" thick. Shpg. wt., 3 oz. MS-791

Net 2.19

SELF GENERATING PHOTOELECTRIC CELLS



BELOW DISTRIBUTOR COST!

.53

- Complete with leads
- No external power needed
- Output in sunlight up to 60 MA
- Up To 750 ua at 100 ft. Candles

Selenium, self-generating photocells convert sunlight or artificial light energy into electrical energy without any auxiliary source of power. Sensitive to a wide spectrum including white, colored or ultra-violet light. AM unmounted; complete with leads. Outputs in table below taken at 100 foot candle illumination with 100 ohm load. Higher outputs obtainable with greater light. Shpg. wt., 3 oz.

Stock No.	Out. ua	Size	Net Each
MS-771	100	1-4"	5.9
MS-772	250	1-1/2" x 1-1/2"	.59
MS-773	350	1-1/2" x 1-1/2"	.79
MS-774	750	1-1/2" x 1-1/2"	.89
			3.18
			3.03
			2.89

NEW! LAFAYETTE CADMIUM SULPHIDE PHOTOCELL



.95

New head-type window cadmium sulphide photocell. Maximum Ratings: 200 volts DC or AC peak. Temperature is —40°C and 60°C. Resistance is over 10 megohms at zero ft. candles. Resistance is over 10 megohms at 10 ft. candles. 100,000 ohms to 10 at 10 foot candles. Range of sensitive wave length is 4000 to 8000 Angstroms. Size: 3/8" diam. x 1/4" L. o.a. Standard screw mount; miniature base. MS-855 Shpg. wt., 4 oz.

Net .95

POWERMASTER TYPE CDS-10 CADMIUM SULPHIDE PHOTOCELL



2.50

A miniature crystal photocell that is ideal for actuating, counting, measuring photo-electric control. Acts as a resistor that varies with the intensity of light from over 1 megohm in total darkness to under 1500 ohms at 100 relays in 1 to 10 second. Rapid response fast enough to operate at 50 ft. candles. Minimum current output 66 ma at 1 ft. candle at 6 volts. Output varies with illumination intensity and applied voltage to as low as .08 ma continuous, 2 watts for 5 seconds. Usable response to green light and good red response. Response to infra-red is low. Size 1/2" x 3/8" x 1/4". MS-739

Net 2.50

CADMIUM SULPHIDE PHOTOCELL



1.59

- For Sensitive Relay Actuation
- For Photo Electric Control

A neatly constructed crystal photocell that has countless applications in counting, relay actuation, etc. Resistance varies with light from 1 megohm in total darkness to entire visible spectrum and has 1 to 10 sec. response to relay operation. Minimum current output 60 ma at 50 ft. candles at 90 volts. Power dissipation 2 watts for 5 seconds, 1/2 watt continuous. Output as low as .08 ma intensity and applied voltage, varying with illumination and applied voltage. Neatly encapsulated for easy mounting with leads for electrical connection. 1 1/2" x 1 1/2" overall. MS-827

Net 1.59

LAFAYETTE SUPER-VALUE SUN BATTERY



1.95

- Excellent For Experimenter, Kit Builder, etc.

Sensational buy enables Lafayette to offer this amazing selenium photocell at a fraction of the price of similar photocells! Surpasses by far, specifications: 0.9 ma Current Output at 100 ft. candles with 100 ohm load; 0.27 ma Current Output at 100 ft. candles with 1000 ohm load; 1 1/2" diameter. With colored pigtail leads. MS-891

Net 1.95

SELENIUM PHOTOCELL

- Excellent for Burglar Alarms
- Door Openers
- Counters

8.75

OPERATES RELAYS DIRECTLY

Barrier layer, self-generating type; light striking upon cell generates current sufficient to operate relays directly without the use of auxiliary power. Lifetime of cell is unlimited; 600 microamperes output at 100 foot candles. 2 inches in diameter. Mounted in a handsome plastic case. MS-826 Photocell, Wt., 8 oz.

CM-70 Socket for MS-826

Net 8.75

Net .13

NEW! SELENIUM PHOTOCELL FOR HEAVY DUTY OPERATION

2.45

- 3/4" Light Area

An efficient selenium photocell utilizing an extremely sensitive film element with 3/4" light area. Ideal for relay operation, use door openers, counters, etc. Rated at 200V: 20-mA; 0.2W power dissipation at 20°C. Sensitivity is 610 @ 50. Resistance Characteristics — 0 Ft. Candles: 33K ohms; 9.29 Ft. Candles: 8K ohms; Size 1/4" Diam. x 3/8" depth. MS-886

Net 2.45

NEW! LAFAYETTE SELENIUM PHOTOCELL

1.95

- 3/8" Light Area

A quality selenium photocell, perfect for transistor and printed circuit use. Employs sensitive film element with 3/8" light area. Rated at 200V: 10ma; 0.1W, power dissipation @ 20°C. Sensitivity is 610 @ 50. Resistance Value Characteristics — 0 Ft. Candles: 2M ohms/up; 0.929 Ft. Candles: 100K ohms; 9.29 Ft. Candles: 25K ohms; Size 3/8" Diam. x 3/8" Depth. MS-885

Net 1.95

NEW! LAFAYETTE MINIATURE SILICON RECTIFIER

.49

- ONLY 3/4" D x 1/2" W

Premium quality and small size make this precision rectifier ideal for prototype and miniature applications. Measures 3/4" D x 1/2" W plus 1/2" mounting lip. Rated AC input voltage 100V, DC output current 20ma. Intermittent 40ma. Maximum Input Capacitance 80MF. MS-887

Net .49



NEW! 1/10 WATT SUB-MINIATURE CARBON FILM RESISTORS

10% TOLERANCE • High Quality • Low Cost

- Really Miniature—Only .28" L x .08" D.
- Tremendously Low Temperature Coefficient

Specifically designed for those applications requiring high quality at the lowest cost. True miniaturization combined with the advantages of carbon-film resistors. Rated at 1/10 Watt, tolerance ±10%, they have a special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

MASTER CHART EIA (RETMA) VALUES SPECIFY RESISTANCE WANTED

Ohms	Ohms	Ohms	Ohms	Ohms	Ohms	Ohms
5.1	22	91	390	1600	6800	30,000
5.6	24	100	430	1800	7500	33,000
6.2	27	110	470	2000	8200	36,000
6.8	30	120	510	2200	9100	39,000
7.5	33	130	560	2400	10,300	43,000
8.2	36	150	620	2700	11,000	47,000
9.1	39	160	680	3000	12,000	51,000
10	43	180	750	3300	13,000	56,000
11	47	200	820	3600	14,000	62,000
12	51	220	910	3900	15,000	68,000
13	56	240	1000	4300	16,000	75,000
15	62	270	1100	4700	18,000	82,000
16	68	300	1200	5100	20,000	91,000
18	75	330	1300	5600	22,000	99,000
20	82	360	1500	6200	24,000	109,000

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic resin insulation, withstand high degrees of heat, humidity and shock. Very low temperature coefficient and noise factor. Imported to sell at these low prices. SPECIFY RESISTANCE VALUE.

RESISTANCE VALUE CHARACTERISTICS • Excellent Stability Characteristics • Ex-

Special synthetic

LAFAYETTE

SEMICONDUCTOR SPECIALS FOR EXPERIMENTER, KIT BUILDER, HOBBYIST

QUALITY SEMICONDUCTORS AT ECONOMY 'PACKAGE' PRICES

10 GERMANIUM DIODES

Pkg. of 10 germanium diodes that replace 1N34, 1N34A, 1N46, 1N48, 1N51, 1N60, 1N64, 1N64A, 1N87, 1N105, 1N109, 1N147, 1N267, 1N268, 1N295, etc. Shpg. wt., 6 oz.

SP-234

10 SILICON DIODES

Package of 10 silicon diodes. Replaces 1N34, 1N34A, 1N46, 1N48, 1N51, 1N60, 1N64, 1N87, 1N295, etc. Shpg. wt., 4 oz.

SP-235

TRANSISTOR - DIODE PACKAGE SPECIAL

.79 Pkg.

3 Pkgs. (can assort.) 2.09

4 PNP GERMANIUM TRANSISTORS

Package of 4 PNP Germanium Transistors similar to 2N107, 2N218, 2N1265, CK722, GT222, TR722, 2N1191, etc. Shpg. wt., 6 ozs.

SP-236

.98 per pkg.
Any 4 Ass't. Pkgs. 3.29

2 PNP TRANSISTORS

Mixer/Oscillator Converter - Replaces 2N112, 2N114, 2N135, 2N136, 2N137, 2N140, 2N219, 2N411, 2N412, 2N414B, 2N415, CK760, CK766, 2S52, etc. Shpg. wt., 4 oz.

SP-237

5 GENERAL PURPOSE DIODES

Package of 5 germanium glass diodes similar to 1N34A, 1N60, 1N64, 1N87A, etc.

SP-218

4 PNP TRANSISTORS

Package of 4 PNP Audio transistors similar to 2N107. Beta 15 minimum.

SP-220

2 NPN TRANSISTORS

Package of 2 NPN germanium transistors similar to 2N170 for Audio & RF. Beta 20 minimum.

SP-219

2 PNP GERMANIUM TRANSISTORS IF AMPLIFIER

Pkg. of 2 PNP germanium IF amplifier transistors that replace: 2N111, 2N111A, 2N112A, 2N139, 2N218, 2N409, 2N410, 2N413, 2N413A, 2N414, 2N414A, 2N416, GT760, 2S53, etc. Shpg. wt., 4 oz.

SP-238

2 PNP GERMANIUM TRANSISTORS AF AMPLIFIERS (Up to 12 Volts)

Pkg. of 2 PNP Germanium AF amplifier transistors that replace: 2N133A, 2N138A, 2N138B, 2N151, 2N186A, 2N187A, 2N215, 2N217, 2N319, 2N320, 2N359, 2N360-363, 2N407, 2N408, 2N1008, A, B, GT81R, GT109, 2S56, 2S838, etc. Shpg. wt., 4 oz.

SP-239

2 GOLD PLATED SILICON RECTIFIERS 500 MIL - 400 PIV

Pkg. of 2 miniature size exceptional 24 karat gold plated silicon rectifiers rated at 500 milliamperes, 400 PIV. Shpg. wt., 4 oz.

SP-240

2 TOP HAT SILICON RECTIFIERS 750 MIL - 400 PIV

Pkg. of 2 top hat type silicon rectifiers rated at 750 milliamperes, 400 PIV. Shpg. wt., 6 oz.

SP-241

STUD MOUNT SILICON RECTIFIER 2 AMPERE 400 PIV

Outstanding Buy! 2 amp. 400 Peak-Inverse-Volts Silicon Rectifier, stud mounting. $\frac{3}{4}$ " long less lug, $\frac{1}{4}$ " hex nut. Shpg. wt., 6 oz.

SP-242

2 10 WATT POWER TRANSISTORS

Package of 2 PNP 10 Watt germanium power transistors in popular TO-3 case. Similar to 2N155, 2N176, 2N235, 2N351, 2N242, 2N257, 2N268, 2N301A, 2N255, 2N554, 2N555, etc. Shpg. wt., 8 oz.



40 WATT HIGH POWER TRANSISTOR

Amazing value is this 40-Watt high power PNP germanium transistor! Excellent for experimenter, hobbyist and kit builder for power supplies, auto

replacement, audio output, etc. Similar to 2N173, CTP1504, SFT266, etc. Bolt mounted. Shpg. wt., 8 oz.

SP-244

LAFAYETTE SPECIAL SILICON POWER RECTIFIERS

Top hat lead type silicon rectifiers excellent for TV Radio and power supplies as half-wave, full wave rectifiers and voltage doublers.

Type A: 750 Ma, 400 PIV @ 25°C.
500 Ma, 400 PIV @ 90°C.

SP-196 Shpg. wt., 4 oz. Net .57
10 for 5.13; 100 for 47.00

Type B: 750 Ma, 200 PIV @ 25°C.
500 Ma, 200 PIV @ 90°C.

SP-197 Shpg. wt., 4 oz. Net .47
10 for 4.25; 100 for 38.50

LAFAYETTE PNP AUDIO TRANSISTOR SPECIAL!

AS LOW AS **.31**

General audio type PNP transistor for experimenters and hobbyists, for code practice oscillators and similar small signal devices. In new JETC 30 welded case. Net, singly, each .39

SP-146 10 for 3.89 50 for 16.95, 100 for 31.00

LAFAYETTE SPECIAL 7-TRANSISTOR SUPERHET PACKAGE

3.89

6 Transistors plus Transistor Diode Matched for Superheterodyne Push-Pull Circuit • Can Work on 9-Volts with Minimum Battery Drain • Highest Quality — All PNP Consists of 1 converter, 2 IF's, 1 driver, 2 push-pull output and 1 transistor diode. Packed in handy plastic case. Shpg. wt., 6 ozs.

SP-202

GENERAL PURPOSE DIODES

.19

EXCELLENT DETECTOR FOR TRANSISTOR AND VACUUM TUBE RADIO RECEIVERS

EQUIVALENT TO: 100 for 16.50

1N34 1N34A 1N38A 1N48 1N56 1N69

SP-148 General Purpose Diode Net .19 each 10 for 1.75

NEW! SAM'S TRANSISTOR SUBSTITUTION HANDBOOK

- Over 8800 Direct Transistor Substitutions
- 800 Substitutes For Japanese Types
- 630 Diode Substitutions

Includes basing diagrams, polarity identifications and manufacturers for over 3000 transistor types. BK-289 Postpaid in U.S.A. Net 1.50

POWER TRANSISTORS


EACH UNIT Similar To: 2N256 2N307 2N554

TESTED TO MEET SPECIFICATIONS

As Low As **.59** Lots of 100

SP-147 Power Transistor In lots of 100, Each Net 69c Net 59c

NEW! ULTRA SUB-MINIATURE TRANSISTOR COIL KIT



- Smallest 2 Gang Variable Ever Made!
- Size: $\frac{1}{8}$ " Square, $\frac{3}{8}$ " Deep
- 3 I.F.'s and OSC: $\frac{1}{4}$ " Square, $\frac{3}{8}$ " High
- Ferrite Loop Antenna

All in one kit—a complete set of matched micro-miniature coils, ferrite loop antenna, ultra-compact 2 gang variable condenser, tuning dial and schematic diagram for building a subminiature 6 transistor radio. Kit includes: Shielded and impregnated high-Q 455 KC IF transformers and oscillator coil—all slug tuned. Proper impedances are provided for optimum circuit performance. Variable condenser has protective case and rear trimmer adjustment. Flat ferrite loop antenna measures $2\frac{1}{2} \times \frac{1}{4} \times \frac{1}{8}$ " thick. Clearly-printed circuit diagram indicates all parts necessary for a powerful 6 transistor receiver. Tuning dial and knob ($1\frac{1}{4}$ " dia.) fits securely on V.C. shaft. The ultra-compactness and quality of these essential components allow you to construct a broadcast radio, miniature by today's standards, at tremendous savings. Shpg. wt. of kit is 1 lb.

MS-828

Net 3.45

SUBMINIATURE TRANSISTOR AUDIO TRANSFORMERS



A new series of miniature transformers for transistor and experimental miniature circuits. Ideal for miniature radio receivers, amplifiers, hearing aids, etc., using standard transistors. Incorporate special heat-treated high permeability magnetic cores-treated to resist corrosion. Designed for improved frequency response with low distortion. 3" color-coded leads. Average shpg. wt., 4 oz.

ONLY $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{1}{2}$ "

Stock No.	Circuit	Impedance	Sec. Ω	D.C. Resistance	Net
TR-97	INPUT	100,000	1000	1000	.79
TR-98	DRIVER	10,000	2000 C.T.	240	60 C.T. .79
TR-99	OUTPUT	500 C.T.	3.2	42 C.T.	0.7 .79
TR-120	INPUT	200,000	1000	1400	50.5 .89
TR-116	OUTPUT	500 C.T.	8	50 C.T.	1.7 .79

NEW LOW PRICES!

GENERAL ELECTRIC 2N107 NOW **.55** PNP GENERAL PURPOSE TRANSISTOR

2N107 Net .55

NEW! PHILCO UNIVERSAL TRANSISTORS

T2163 MADT Type Universal Transistor. Excellent for RF, Mixer, Converter, Oscillator or IF. Net .99
T2333 Alloy Junction Type Universal Transistor. Excellent in Push-Pull Audio Output. Net Per Pair 1.69
T2333 (Push-Pull)

NEW! 4 TRANSISTOR SUBMINIATURE PUSH-PULL AUDIO AMPLIFIER—

OUTPUT 100 MW

4.95




- TERRIFIC FOR THE EXPERIMENTER, HOBBYIST AND KIT BUILDER!
- COMPLETELY WIRED, NOT A KIT!
- PRINTED CIRCUIT BOARD
- COMPLETE WITH TRANSISTORS

A tiny, transistorized push-pull audio amplifier with a multitude of applications. Only $3" \times 1\frac{1}{4}" \times \frac{1}{4}"$, it can be mounted inside other equipment to serve as a subminiature phono amplifier, tape recorder, amplifier, etc. Can be the complement of a homebuilt project which needs only an audio amplifier to make it complete and self-contained. Two stages of audio are followed by a push-pull output stage designed to deliver 100 mw to an 8-11 ohm impedance. Low impedance input, with a sensitivity of 0.9 mv. Input transformer for matching high impedances to the amplifier available as an accessory (see below). Includes leads for input, speaker, and volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Shpg. wt., 5 oz.

ACCESSORIES FOR ABOVE

BA-2 5 volt battery. Shpg. wt., 2 oz. Net .39
VC-31 50K ohm volume control w/switch. Shpg. wt., 2 oz. Net .69
SK-193 8 ohm voice coil speaker. 3" Shpg. wt., 10 oz. Net 1.49
SK-189 8 ohm voice coil speaker. 2" Shpg. wt., 8 oz. Net 1.49
SK-191 8 ohm voice coil speaker. 2 1/2" Shpg. wt., 8 oz. Net 1.49
Input transformer for matching high impedance (mike, etc.) to amplifier. Net .49

NEW! 5 TRANSISTOR PUSH-PULL AUDIO AMPLIFIER



- ONLY $3\frac{1}{2}" \times 1\frac{1}{4}" \times \frac{1}{4}"$
- 360 MW OUTPUT
- COMPLETELY WIRED
- DIRECT WIRING


6.95

A more powerful and more sensitive version of the PK-543, this amplifier employs 3 stages of audio driving a push-pull output stage. Power output is 360 mw, designed for speakers with a voice coil impedance of 8-11 ohms. Low impedance input has sensitivity of 300 microvolts. Input transformer for matching high impedance to the amplifier input available as an accessory (see below). Comes with leads for low impedance input, speaker, volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Shpg. wt., 5 oz.

ACCESSORIES FOR ABOVE

BA-2 9 volt battery. Shpg. wt., 2 oz. Net .39
VC-28 10,000 ohm volume control w/switch. Shpg. wt., 2 oz. Net .69
SK-193 8 ohm speaker. 3" Shpg. wt., 10 oz. Net 1.49
SK-189 8 ohm speaker. 2" Shpg. wt., 8 oz. Net 1.49
SK-191 8 ohm speaker. 2 1/2" Shpg. wt., 8 oz. Net 1.49
Input transformer for matching high impedance (mike, etc.) to amplifier. Net .49

3 TRANSISTOR SUBMINIATURE AUDIO AMPLIFIER



- FOR THE EXPERIMENTER, HOBBYIST, AND KIT BUILDER!
- PRINTED CIRCUIT
- COMPLETE WITH TRANSISTORS

Here is an amazing little audio amplifier with a multitude of challenging applications; i.e., subminiature phono amplifier, tape recorder amplifier, hand-held public address amplifier, telephone pick-up amplifier, etc. Output sufficient for average listening. Has leads for any one of the following inputs: Tape recorder record/playback heads, radio-tuner, crystal or ceramic phono cartridge, and crystal or ceramic microphone. Has lead terminations for ON-OFF switch, Volume Control, 4 to 10 ohm speaker, and leads terminating in clips for a 9 volt miniature battery. Size $2\frac{1}{4}" \times 1\frac{1}{4}" \times \frac{3}{4}"$. Can be readily mounted on chassis. Shpg. wt., 8 oz.

PK-522 Net 3.75
BA-2 9 Volt Battery Net .39
5K ohm Volume Control with SPST Switch and Knob; Shpg. wt., 2 oz. Net .59
VC-62 Miniature Crystal Microphone $1\frac{1}{8}"$ Diam. x $\frac{1}{4}"$ Deep. Shpg. wt., 6 oz. Net 1.49
MS-108 Miniature Speaker $2\frac{1}{2}"$ Diam. 10 ohms Voice Coil Impedance. Shpg. wt., 8 oz. Net .49



take a closer look with ...

Lafayette PRECISION MICROSCOPE




19⁹⁵



14⁹⁵



34⁵⁰



44⁵⁰



89⁹⁵

FOR THE INTERMEDIATE STUDENT

FOR STUDENT RESEARCH

CLINICAL AND ADVANCED ACADEMIC

New! 1200X "MICRO-TECH" MICROSCOPE

- 80X to 1200X in 8 Ranges
- Built-in Sub-State Illuminator
- Dual Knob Lever Type Fine Focus
- Complete Set of Dissecting Instruments

Hardcoated, Huygenian eyepieces; 4 achromatic objective lenses in a revolving "click-stop" turret. Available magnifications of 80X, 100X, 160X, 200X, 800X and 1200X Dual knob. Stage includes optical condenser and revolving, 5 aperture, disc diaphragm. Sub-stage illuminator-mirror combination. Adjustable down-stop on body tube. Accessories include 2 prepared slides, 4 blank slides, spatula, scalpel, probe, scissors, tweezers and magnifying glass. All housed in a handsome wooden case. Shpg. wt., 6 lbs.

- F-700 "Micro-Tech" Net 19.95
- F-701 Replacement bulb for F-700 Net .11
- BA-155 Battery (2 required) Net ea. .095
- Transformer. Permits use of house current for illumination of F-700 "Micro-Tech" microscope. Net 1.80
- F-761 Shpg. wt., 8 ozs.

NEW! 50X STEREO-SCOPE

- STEREOSCOPE BINOCULAR MICROSCOPE
- WIDE FIELD—3 DIMENSION VIEW
- VERTICALLY ERECT IMAGE

Indispensable for the examination of surface features of gross objects. Excellent hobby aid for the coin and stamp collector. Prismatic, binocular head with interpupillary adjustment. Ground glass stage, 3 1/4 x 2 3/4". Heavy modified horseshoe base. Overall height 8". Complete with wooden carrying case. Shpg. wt., 5 lbs. F-762 Net 14.95

- Earth-Science Combination. Includes 50X Stereo-Scope (F-762) and 96 selected specimens, named, tagged and classified. (Vol. I and Vol. II Mineral Teknits.) Shpg. wt., 8 lbs. F-763 Net 17.76

900X MICROBE "HUNTER"

- THE ONLY MICROSCOPE IN ITS CLASS FEATURING GRADE A OPTICS!
- POWER RANGE 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 900X

All of the most needed features for diversified micro-studies. Power range from 25X to 900X in 12 possible combinations. Micro-motion fine focusing—12 complete revolutions. 36mm (plano/concave) mirror. Fixed square stage, 70mm x 80mm. Rotating 5-hole, disc diaphragm. Three Huygenian eyepieces of 5X, 10X and 15X. Four achromatic objectives of 5X, 10X, 40X and 60X. Complete with upright, wooden carrying case. Shpg. wt., 8 lbs. F-338 Net 34.50

- F-613 Mechanical stage for above Net 6.95

1200X "RESEARCHER"

- 25X TO 1200X IN 12 RANGES
- FULL RANGE FINE FOCUS ADJUSTMENT
- INTEGRAL MECHANICAL STAGE

Closely parallels the "Society" grade microscope. Four Huygenian eyepieces, combine with four achromatic objectives to yield 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 800X, 900X, 1200X. Micro-motion fine focusing adjustment. Spring loaded to prevent objective from driving through slide. 85mm x 85mm stage can be moved in any direction. Sub-stage has rotating, 5 position diaphragm. Complete with set of 5 basic dissecting instruments, 10 slides, pack of cover slips, tube of mounting fluid. Wooden carrying case. Shpg. wt., 10 lbs. F-369 Net 44.50

1500X "MICRO-STANDARD" ADVANCED ACADEMIC MICROSCOPE

- 25X TO 1500X IN 11 RANGES
- INTEGRAL MECHANICAL STAGE
- VARIABLE SUB-STAGE CONDENSER WITH IRIS DIAPHRAGM
- FULL RANGE FINE ADJUSTMENT
- STANDARD SOCIETY SIZE OPTICS - BOTH OBJECTIVES AND EYEPIECES

OPTICAL SPECIFICATIONS: Three Huygenian eyepieces: 5X, 10X, 15X. Four achromatic objectives: 5X, 10X, 40X, 100X (oil immersion). BODY: Monocular tube 140mm long. STAGE: Square stage 95mm x 95mm. Integral mechanical stage. Adjustable in any direction. FOCUSING: Coarse focus with adjustable tension. Fine focus vernier adjustment. Spring loaded safety device prevents objective from driving through slide. SUBSTAGE: Focusing Condenser with variable iris diaphragm. 41mm plano/concave mirror. Overall 12 1/2" high, 6 1/2" deep, 5" wide. Includes fitted cabinet with lock and key, specimen slide, blank slide, bottle of cedar oil. Shpg. wt., 11 1/2 lbs. F-602X Net 89.95

500X "MICRO-MECH" MICROSCOPE

- BUILT-IN MECHANICAL STAGE
- 100X - 500X - 800X - 900X
- QUADRIPOLE REVOLVING TURRET

5⁹⁵



For the student — hobbyist — or budding scientist. Featuring a built-in, micro-drive mechanical stage. Permits the micro-movement necessary to properly examine micro objects. Promotes learning through ease of operation. Four achromatic objective lenses giving magnifications of 100X, 200X, 300X and 500X. Complete with wooden carrying case and slides. Shpg. wt., 4 1/2 lbs. F-357 Net 5.95

- "MICRO-MECH" LAB KIT: Consists of F-357 500X "Micro-Mech" microscope and F-454 Micro-Lab Kit, with accessories and cabinet plus latest edition of "Hunting with the Microscope." Shpg. wt., 12 lbs. F-622 Net 13.90



MICROSCOPE ACCESSORIES

A. SLIDE PREPARATION KIT. 30 glass slides, 3x1", in container. Slotted for easy indexing. Includes slide covers and vial of mounting fluid. Shpg. wt., 1 lb. F-533 Net .98

B. HUNTING WITH THE MICROSCOPE. How the microscope works. How to prepare and study cultures—set up a microscope zoo and garden—grow micro organisms—perform micro surgery. Profusely illustrated with photographs and drawings. BK-1440 Net .89

C. MICRO SLIDE PREPARATION TEKNIKIT™ Seven dissecting instruments. 3 well slides, 22 blank slides, 25 cover glasses, 25 blank labels, blue stain, mounting fluid, pins and descriptive booklet. F-659 in fitted wooden case. Shpg. wt., 1 1/2 lbs. Net 3.49

WELL SLIDE TEKNIKIT™ 6 single well slides, 6 double well slides, all 3x1". 20 cover glasses, vial of neutral red solution. Shpg. wt., 8 ozs. F-691 Net 1.29

E. DISSECTING TEKNIKITS™ 2 scalpels, spatula, 2 dissecting needles, 2 dissecting forceps, blowpipe, magnifier, scissors, pins. In fitted case. Shpg. wt., 1 lb. F-451 Net 3.79

D. SR. DISSECTING TEKNIKIT™ All above plus 6" probe with eye, fine scissors, 2 cc syringe, slip on needle, large fitted case. F-450 Shpg. wt., 1 1/2 lbs. Net 5.49

F. MICRO-SLIDE STAINING TEKNIKIT™ Each vial is a "dropper" type for direct application of stain to specimen. Kit consists of one vial each of Safranin, Methylene Blue, Fuchsin, Gentian Violet, Eosin and First Green. Complete detailed instructions. Shpg. wt., 8 ozs. F-605 Net 1.79

ADVANCED STAINING TEKNIKIT™ Three additional dyeing fluids. For staining blood smears, spirochaetes, bacteria, etc. With instructions. Shpg. wt., 6 ozs. F-624 Net 1.69

G. MICROSCOPY TEKNIKIT™ Contains equipment for collecting — fixing — dyeing — dehydrating — clearing — mounting — finishing — labeling — drying and storing subjects. 24 1x3" slides, cover slips, labels, tweezers, scalpel, dropper, probe, rod, 2 collecting vials, 2 small dishes, 4 bottles of dehydrating fluid (70%, 80%, 90%, 100% alcohol), bottle of acid alcohol, xylol clearing fluid, Gates' fixing fluid, Canada balsam mounting fluid, 2 vials of dyeing fluid (acid fuchsin and gentian violet). With detailed instructions. Shpg. wt., 2 lbs. F-604 Net 3.95

H. MICROLITE. Provides a bright, evenly lighted field of view. Adjustable for transparent or opaque specimens, direct or indirect illumination. Invaluable where oblique light is necessary. Operates on 110-120 volts AC/DC. Self contained switch, cord and plug. Lamp is 5 1/2" long. Stand is 5 1/2" high. Shpg. wt., 1 lb. F-268 Net 2.95

J. SUBSTAGE "MICRO-LUMINATOR". Mounts in mirror forks of 35 to 40 mm (1 1/4" to 1 1/2"). Mirror forks of other sizes are readily spread or compressed to fit. Blue filter glass corrects light to proper color for micro-illumination. Complete with 5 1/2 ft. cord, plug, switch and spare bulb. For 110-120V. AC/DC. Shpg. wt., 8 ozs. F-612 Net 2.89

500X "BI-OCULAR" MICROSCOPE

- NEW TWIN LENS "BI-OCULAR" TURRET
- BUILT-IN SUB-STAGE MICRO-LITE
- 100X - 500X - 800X - 900X

8⁴⁹



Bi-Ocular turret permits instant variation of magnification without disturbing subject set-up. Triple objective click-stop turret in concert with 10X and 15X "Bi-Oculars" give six ranges of magnifications. "Micro-Lite"™ with automatic on-off switch, Dual knob, rack and pinion focusing, 8 1/2" high overall. All optics are achromatic. Ocular lenses are Huygenian type. Includes sub-stage mirror for viewing by reflected light. Dove-tailed wooden carrying case and sample slides. Shpg. wt., 5 lbs. Less batteries. F-334 Net 8.49

- BA-155 Battery (2 required) Net ea. .095



5²⁹

Direct viewing "projection" microscope affords viewing ease to small groups. Less tiring than viewing through a conventional microscope. The image is projected onto a self contained, translucent glass screen. Finger tip control switches from 50X to 100X. Thumb wheel focus for sharp definition. Projects the full colors present in the slide or specimen. Illumination by means of a battery powered, pre-focused bulb. Requires 2 standard flashlight batteries (not included). Overall size 4 1/2 x 3 x 6 1/2". Hooded viewing screen, inclined to 55°. Optimum viewing angle. Supplied with bulb and three prepared slides. Shpg. wt., 1 1/2 lbs. F-760 Net 5.29

- BA-157 Batteries (2 required) Net ea. .13



6⁹⁵

Attaches to any square microscope stage 70 mm x 80 mm or larger. Accommodates slides up to 75 mm x 50 mm. Both lateral and front-to-back movement by rack and pinion. Adjustment scales are graduated in single millimeters with verniers reading to 1/10th mm. Essential accessory for all high magnification examination. Permits relocating any portion of a slide or charting the entire slide. Spring clip automatically accommodates slides of varying dimensions. Shpg. wt., 12 ozs. F-613 Net 6.95



AS LOW AS 89¢ PER SET

Specially selected slides of universal interest. Slides are professional size. Set includes 12 prepared slides and slotted, covered box for filling and storing. Shpg. wt., 8 ozs.


F-123 Parts of Insects	Net 1.49
F-124 Spiders, Disease Carriers	Net 1.69
F-125 Tiny Creatures	Net 1.59
F-126 Sea Life	Net 1.39
*F-128 Structure of Blood	Net 1.15
F-130 Life cycle of Insects	Net 1.59
F-131 Bacteria	Net 1.79
F-132 Sea Life, Plankton	Net 1.59
F-134 Micro-Animals	Net 1.29
F-135 Micro-Organisms	Net 1.29
*F-136 Substance of Cells	Net .89

*—Set of 6 Slides



10⁹⁵

Essential tool for free hand sectioning of biological specimens. Equally suitable for the serious hobbyist and student as well as lab applications where the accuracy of a hand operated feed is sufficient. The micro-fine pitch screw feed is graduated in 10 micron intervals. The dense, composition stage is absolutely flat. 75 mm in diameter. "Straight razor" type micrometer knife of surgical quality steel. Ground and tempered to take and hold a keen cutting edge. Supplied with microtome knife, pitch and compartmented wooden storage cabinet. Shpg. wt., 2 lbs. F-803 Net 10.95



A 72 specimen library of slides carefully pre-selected to maintain continuing interest in microscopy. Consisting of 6 correlated series of subject matter in biology, zoology and botany. Each specimen is cultivated, cleaned, dissected, embalmed, stained, mounted, labeled and covered for permanence. All are large (1x3") size. Ideal ready-reference for the science-hobbyist. Shpg. wt., 2 lbs. F-803 Net 7.50

SR. Slide Library. 120 slides, all above plus bacteria, cell structure, blood structure, micro-organisms and animals. Total eleven volumes. Shpg. wt., 3 1/4 lbs. F-804 Net 11.90

LAFAYETTE DIRECT IMPORTS Compare for VALUE!

TESTED AND SELECTED FOR CONSISTENT QUALITY

35mm "RANGEFINDER III"



NO MONEY DOWN
28⁸⁸

- 4 ELEMENT F2.8 COATED LENS! • COUPLED RANGEFINDER
- LUMINOUS BRIGHT FRAME VIEW-RANGE FINDER! • SINGLE STROKE RAPID FILM TRANSPORT! • NINE SHUTTER SPEEDS TO 1/300!
- F2.8 45mm COATED LENS! • HI-SPEED REWIND! • STANDARD PC FLASH TERMINAL! • DOUBLE EXPOSURE PREVENTION • BUILT-IN SELF TIMER!

Check the features — then compare Lafayette's price with any other brand. Fast 12.8 coated anastigmat lens and extra-wide lens aperture for brilliant, sharper full color or black and white even in poor light. Sight and focus through coupled range-view finder. Fully synchronized at all speeds for class M and electronic flash. Speeds from 1 sec. to 1/300th. Rapid advance sets shutter, counts exposure and transports film. Built-in delayed action timer — automatic electronic counter and film stop. Hi-speed rewind with folding lever. Standard accessory shoe. All metal body with brushed chrome trim—black leatherette covering. 20 or 36 exposures on black and white or color 35mm film. PC flash terminal. Expertly made in Japan. Shpg. wt., 3 lbs. Use series 6 accessories.

F-779L Less Case Net 28.88
F-779L Leather Eveready Case. Shpg. wt., 1/2 lb. Net 3.95
Auxiliary Wide Angle and Telephoto Lens Set for "Rangefinder III." Net 15.96
F-808L Shpg. wt., 1 1/2 lbs. Net 3.39
Optical viewfinder for Wide Angle and Telephoto Lenses. Net 3.39
F-647L Shpg. wt., 6 ozs.

MATCHED FILTER AND HOOD SET

Includes Type "A" conversion, "F" conversion, "808" photohood, adapter ring and lens hood. Complete with leather case with room for additional filters. Net 14.95
F-781L Shpg. wt., 8 ozs.
Special Combination Offer: Includes camera above—Eveready case—folding BC flash gun—and clip-on exposure meter. Shpg. wt., 4 lbs. Net 38.95
F-780L

NEW! TRANSISTORIZED ELECTRONIC STROBE FLASH



Operates from Batteries and AC

24⁹⁵

NO MONEY DOWN

- Lightweight & Compact—No Power Pack Needed
- Fully Transistorized
- Operates on 4 Economical "Z" Cell Batteries
- Fits any Camera Shoe

Now you can have a high-powered, transistorized electronic flash that operates from standard AC house current or 4 economical "Z" cell batteries. Compact and featherweight—no power pack is required. Flash duration of 1/2000 sec. for fast pictures. Recycling time: 6-10 seconds; color temperature: 6000° Kelvin. Guide number dial for F stop on back. Complete with AC cord. Less batteries.

F-807 Shpg. wt., 2 lbs. Net 24.95
Batteries for above (4 required). Net each .095
BA-155

AUTO-DIAL EXPOSURE METER

Holds its reading indefinitely. Meter is aimed and dial stopper depressed. The dial then swings to correct reading and remains fixed when stopper is released. Ideal for widely variant light conditions. Color and black and white calibration with ASA speeds to 25,000. Reflected and incident light read on same scale. EVS 1 to 19. Lens: f/1.0 to f/32. Direct reading cine speeds 8-64 fps. Meter has zero adjust. Leather carrying case and neck strap.

6.75



F-791L Shpg. wt., 1 lb. Net 6.75

PRICED EXTRA LOW! COMPARE FOR VALUE!

35MM LAFAYETTE "ELECTRICK 2.8"



NO MONEY DOWN

49⁹⁵

- Automatic Exposure Control
- Built-in, Cross Coupled, Exposure Meter
- Match The Pointer—Focus and Shoot!
- Coupled Rangefinder

Perfect exposure every time is assured by the cross coupled photoelectric exposure meter; merely set shutter speed and ASA film speed, aim camera, and line up light meter needle with colored mark on meter scale. Now a single twist gives perfect exposure at any speed. Superimposed coupled range finder with automatic parallax correction enables accurate focusing from 2.5 ft. to infinity on the fast f2.8 coated anastigmat lens. Shutter features speeds from a full second to 1/500, or black-and-white. Made in Japan to Lafayette's own specifications. 35mm film, color

F-656L Less Case Shpg. wt., 3 lbs. Net 49.95
F-656L Leather Eveready Case Shpg. wt., 1/2 lb. Net 4.95
Auxiliary Wide Angle and Telephoto Lens Set for "Electrick 2.8." Shpg. wt., 1 1/2 lbs. Net 15.96
F-809L Shpg. Net 3.39
Optical viewfinder for Wide Angle and Telephoto lenses. Shpg. Net 3.39
F-647L Shpg. Net 3.99
Folding BC flash gun. With battery and leather case. Shpg. wt., 1 lb. Net 3.99

LAFAYETTE AG FLASH GUN

- Compact in Size
- Made for the New AG Bulbs
- Dependable B-C Operation

2.99




The new Lafayette AG flash gun is a compact, palm size yet offers dependable B-C operation. Made for the new AG flashbulbs which are small in size and big in performance. The Lafayette flash gun has a fan-type reflector which measures 2" in diameter when opened. Standard shoe fits all standard accessory clips. Features a Computer Dial for determining correct F stop. Testlight for checking battery and bulb, and Bulb Ejector. Complete with cord. Operates on 15V battery (not incl.). Shpg. wt., 8 ozs.

F-699 Net 2.99
BA-116 15-Volt Battery for above Net .81

BOOSTER EXPOSURE METER

- Includes booster—Leather cases—neck cord
- Stills or Movies • ASA Scale—LVS Scale

6.45



Extremely versatile—extremely simple. Highly legible direct reading dial. Speeds from 4 sec. to 1/1000 sec. Lens aperture settings from f:1 to f:32. ASA scale 6 to 800. LVS scale 1 to 18. Cine scale 8, 16, 24 and 32 frames per second. Booster cell makes possible readings at extremely low light levels. Small-rugged-lightweight. Includes booster cell, leather cases, neck cord and instructions. Shpg. wt., 1 lb.

F-349L Net 6.45

"35" CLIP-ON EXPOSURE METER

3.95

- FITS CAMERA ACCESSORY SHOE
- ASA SCALE 10 TO 1000
- MEASURES REFLECTED AND INCIDENT LIGHT

Exceptionally convenient exposure meter. Clips right on camera—quick easy reading. Gives better, more accurately exposed pictures with a minimum of effort. Speeds 1/1000 to 1 Sec. Lens aperture f:1.4 to f:22. Mounts on camera or may be hand held. Complete with leather case and instructions. Shpg. wt., 1/2 lb.

F-351L Net 3.95

MANSFIELD 300 WATT 35MM PROJECTOR

Self Contained Case

- Brilliant 300 Watt—Turbo Blower Cooled
- 4 Inch, 13.5 Coated, Corrected Lens
- Designed for Easy Operation

28.95
NO DOWN PAYMENT



- For All 35 mm, 2 x 2 and Super Slides

Compact, convenient, semi-automatic, plus big-picture, 300 watt brilliance. Takes all 2x2 inch slides—35mm 828 (bantam) and 127 (super-slides). Semi-automatic "Presto-Matic" changer, one push-pull movement picks, shows and replaces 36 slides in sequence. Self-contained storage for over 100 slides. Die cast aluminum. Self-contained case. All optics hard coated. Designed for optimum projection brilliance. For 110-120V. AC/DC. Shpg. wt., 12 lbs.

F-667 Net 28.95

PROJECT-A-SCOPE

- Projects Giant Pictures in Color Or Black and White — Without Films or Negatives
- For Lectures — Study — Classroom or Just Plain Fun!

5.95



Amazingly versatile! Delightfully simple! Adjustable professional lenses. Just place it over anything flat—magazines, books, photos, drawings, coins, stamps, documents, maps, natural objects—and see a brilliant giant enlargement projected on any white wall or screen in glowing true-to-life color or black and white. A boon to students, artists, collectors, lecturers, demonstrators. Children can project their favorite comics or story books to amuse themselves and their friends. Molded of heat resistant, hi-impact polypropylene. Rigid transparent base, flattens and protects photos, prints and stamps. Uses ordinary household bulbs. U/L Approved 110V. AC/OC. Shpg. wt., 2 lbs.

F-694 Net 5.95

ELEVATOR TRIPOD

- Folds to 16" including Panhead!
- Extends to 47" PLUS 7" Elevator!
- Tri-Tilt head — Moves in 3 planes!

8.59



For any small camera—35 mm—reflex—or movie. Professional quality for professional results. Strong—steady—lightweight. Pencil slim, chrom plated, brass legs. Lock securely in place—fold down readily. Single action tilt-pan—and swing over for taking pictures in vertical or horizontal format. Geared elevator center-post with positive lock and folding crank. Weighs only 31 ozs. All the most wanted features in one tripod. Shpg. wt., 2 1/2 lbs.

F-339 Net 8.59

MATCHED 35MM CAMERA OUTFIT

Complete, ONLY **65.95**

Reg. catalog price 83.21 YOU SAVE 16.26



A complete 35mm camera outfit for indoor and outdoor picture taking, in color or black-and-white. You save: \$16.26. You get: Lafayette "Electrick 2.8" 35mm camera with automatic exposure control (F-655L); leather carrying case for the camera (F-656L); transistorized electronic strobe flash that operates on batteries and AC (F-807); 4 batteries for the flash (BA-155); roll 35mm Kodachrome film with processing (F-581L).
F-810L No Money Down. Shpg. wt., 6 lbs. Net 65.95

PHOTOFLASH BULBS



BUY IN QUANTITY AND SAVE

- "My-T-Myte" and "Synchro Sure" Photoflash Bulbs
- Standard Sizes — Highest Quality — Pre-Tested

Stock No.	Lamp Type	Pkg. Quan.	Per Pkg.	Each Pkg. In Lots of 3	Each Pkg. In Lots of 6
F-798	AG-1	12	.99	.93	.88
F-471	M2	12	1.17	1.05	.95
F-472	M2B	12	1.35	1.20	1.10
F-473	PF-1	8	.66	.63	.59
F-474	SM	10	1.35	1.20	1.10
F-475	5	8	.90	.85	.80
F-476	5B	8	1.08	.96	.90
F-477	6	10	1.35	1.20	1.10
F-478	Adapter for PF-1				.15

GENUINE LEATHER GADGET BAG



4⁹⁵

Genuine plgskin—not plastic. Full 10x8x4". Holds your camera and all accessories. 20" zipper top. Pouch in lid holds filters, etc. Outside pouch with strap and buckle. All brass hardware. Loops and straps on bottom to hold tripod. Includes shoulder strap and pad. Shpg. wt., 1 lb.

F-320 Net 4.95

FLASHLIGHT SCREEN POINTER



4.88

FLASHLIGHT SCREEN POINTER (M)
An excellent lecture tool. Points out subject material without creating shadows. Adjustable arrow focus. Black hood prevents light spread. With cells. From W. Germany.
F-792 Shpg. wt., 12 oz. Net 4.88
BA-156 No. 2 cell for above (2 req.) Net .13

KODAK FILM WITH PROCESSING INCLUDED

- Slides Returned Mounted, Ready for Viewing or Showing!
- Rigid Processing Controls Assure Highest Quality
- Convenient, direct-mail "mailers" in every roll
- A full number of Prints guaranteed for Kodachrome and black and white.



You get factory-fresh film plus a convenient direct-mail mailer. After the complete roll has been filmed, put it into the mailer, drop into a mailbox and in a few days your finished films are delivered postpaid to your door. You get 3 1/2" square or 3 1/2x5" giant prints with Kodachrome and Black & White—and a full number of prints is guaranteed. Should you get less than the full number of prints of Kodachrome or Black & White printable negatives per roll, you will receive coupons for additional FREE prints. DO NOT MAIL FILM TO LAFAYETTE RADIO.

KODACHROME COLOR MOVIE FILM

Stock No.	Description	Net ea.	Net ea. lots of 6
F-575L	8mm, 25 ft. roll, Daylight	3.55	3.40
F-576L	8mm, 25 ft. roll, Indoor	3.55	3.40
F-577L	8mm, 25 ft. Mag., Daylight	4.60	4.42
F-578L	8mm, 25 ft. Mag., Indoor	4.60	4.42

NEW! KODACHROME II COLOR MOVIE FILM

- 2 1/2 Times Faster; ASA Index Daylight 25, Indoor 40

F-794L	8mm, 25 ft. roll Daylight	4.49	4.22
F-795L	8mm, 25 ft. roll, Indoor	4.49	4.22

KODACHROME 35mm COLOR SLIDE FILM

F-580L	35mm, 20 Exp. Daylight	2.98	2.85
F-581L	35mm, 20 Exp. Indoor	2.98	2.85
F-582L	35mm, 36 Exp. Daylight	4.38	4.20
F-583L	35mm, 36 Exp. Indoor	4.38	4.20

NEW! KODACHROME II 35mm COLOR SLIDE FILM

- ASA Index Daylight 25, Indoor 40.

F-796L	35mm, Daylight, 20 Exp.	3.59	3.39
F-797L	35mm, Daylight, 36 Exp.	5.49	4.98

KODACHROME II 35mm COLOR SLIDE FILM

F-584L	127 Indoor/Outdoor	3.72	3.56
F-585L	120 Indoor/Outdoor	3.72	3.56
F-586L	620 Indoor/Outdoor	3.72	3.56

KODAK BLACK & WHITE ROLL FILM

F-587L	127 Verichrome Pan	1.28	1.17
F-588L	120 Verichrome Pan	1.28	1.17
F-589L	620 Verichrome Pan	1.28	1.17
F-590L	35mm, 20 Exp., Plus X	2.32	2.24
F-591L	35mm, 36 Exp., Plus X	3.45	3.35



take a closer look with . . .

Lafayette PRECISION MICROSCOPE



19⁹⁵




14⁹⁵



34⁵⁰



44⁵⁰



89⁹⁵

FOR THE INTERMEDIATE STUDENT

FOR STUDENT RESEARCH

CLINICAL AND ADVANCED ACADEMIC

New! 1200X "MICRO-TECH" MICROSCOPE

- 80X to 1200X in 8 Ranges
 - Built-in Sub-State Illuminator
 - Dual Knob Lever Type Fine Focus
 - Complete Set of Dissecting Instruments
- Hardcoated, Huygenian eyepieces; 4 achromatic objective lenses in a revolving "click-stop" turret. Available magnifications of 80X, 100X, 160X, 200X, 800X and 1200X Dual knob. Stage includes optical condenser and revolving, 5 aperture, disc diaphragm. Sub-stage illuminator-mirror combination. Adjustable down-stop on body tube. Accessories include 2 prepared slides, 4 blank slides, spatula, scalpel, probe, scissors, tweezers and magnifying glass. All housed in a handsome wooden case. Shpg. wt., 6 lbs.
- F-700 "Micro-Tech" Net 19.95
 F-701 Replacement bulb for F-700 Net .11
 BA-155 Battery (2 required) Net ea. .095
 Transformer. Permits use of house current for illumination of F-700 "Micro-Tech" microscope.
 F-761 Shpg. wt., 8 ozs. Net 1.80

NEW! 50X STEREO-SCOPE

- STEREOSCOPE BINOCULAR MICROSCOPE
 - WIDE FIELD—3 DIMENSION VIEW
 - VERTICALLY ERECT IMAGE
- Indispensable for the examination of surface features of gross objects. Excellent hobby aid for the coin and stamp collector. Prismatic, binocular head with interpupillary adjustment. Ground glass stage, 3 1/4 x 2 3/4". Heavy modified horseshoe base. Overall height "B". Complete with wooden carrying case. Shpg. wt., 5 lbs. F-762 Net 14.95
- Earth-Science Combination. Includes 50X Stereo-Scope (F-762) and 96 selected specimens, named, tagged and classified. (Vol. I and Vol. II Mineral Teknikits.) Shpg. wt., 8 lbs. F-763 Net 17.76

900X MICROBE "HUNTER"

- THE ONLY MICROSCOPE IN ITS CLASS FEATURING GRADE A OPTICS!
 - PDWER RANGE 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 900X
- All of the most needed features for diversified micro-studies. Power range from 25X to 900X in 12 possible combinations. Micro-motion fine focusing—12 complete revolutions. 36mm (plano/concave) mirror. Fixed square stage, 70mm x 80mm. Rotating 5-hole, disc diaphragm. Three Huygenian eyepieces of 5X, 10X and 15X. Four achromatic objectives of 5X, 10X, 40X and 60X. Complete with upright, wooden carrying case. Shpg. wt., 8 lbs. F-450 Net 5.49
- F-451 Net 3.79
 D. S.R. DISSECTING TEKNIKIT™ All above plus 6" probe with eye, fine scissors, 2 cc syringe, slip on needle, large fitted case. F-450 Shpg. wt., 1 1/2 lbs. Net 5.49
- F. MICRO-SLIDE STAINING TEKNIKIT™ Each vial is a "dropper" type for direct application of stain to specimen. Kit consists of one vial each of Safranin, Methylene Blue, Fuchsin, Gentian Violet, Eosin and First Green. Complete detailed instructions. Shpg. wt., 8 ozs. F-605 Net 1.79
- ADVANCED STAINING TEKNIKIT™ Three additional dyeing fluids. For staining blood smears, spirochaetes, bacteria, etc. With instructions. Shpg. wt., 6 ozs. F-624 Net 1.69
- G. MICROSCOPY TEKNIKIT™ Contains equipment for collecting — fixing — dyeing — dehydrating — clearing — mounting — finishing — labeling — drying and storing subjects. 24 1x3" slides, cover slips, labels, tweezers, scalpel, dropper, probe, rod, 2 collecting vials, 2 small dishes, 4 bottles of dehydrating fluid (70%, 80%, 90%, 100% alcohol), bottle of acid alcohol, xylol clearing fluid, Gates' fixing fluid. Canada balsam mounting fluid, 2 vials of dyeing fluid (acid fuchsin and gentian violet). With detailed instructions. Shpg. wt., 2 lbs. F-604 Net 3.95
- H. MICROLITE. Provides a bright, evenly lighted field of view. Adjustable for transparent or opaque specimens, direct or indirect illumination. Invaluable where oblique light is necessary. Operates on 110-120 volts AC/DC. Self contained switch, cord and plug. Lamp is 5 1/2" long. Stand is 5 1/2" high. Shpg. wt., 1 lb. F-268 Net 2.95
- J. SUBSTAGE "MICRO-LUMINATOR". Mounts in mirror forks of 35 to 40 mm (1 1/4 to 1 3/4"). Mirror forks of other sizes are readily spread or compressed to fit. Blue filter glass corrects light to proper color for micro-illumination. Complete with 5 1/2 ft. cord, plug, switch and spare bulb. For 110-120V. AC/DC. Shpg. wt., 8 ozs. F-612 Net 2.89

1200X "RESEARCHER"

- 25X TO 1200X IN 12 RANGES
 - FULL RANGE FINE FOCUS ADJUSTMENT
 - INTEGRAL MECHANICAL STAGE
- Closely parallels the "Society" grade microscope. Four Huygenian eyepieces, combine with four achromatic objectives to yield 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 800X, 900X, 1200X. Micro-motion fine focusing adjustment. Spring loaded to prevent objective from driving through slide. 85mm x 85mm stage can be moved in any direction. Sub-stage has rotating, 5 position diaphragm. Complete with set of 5 basic dissecting instruments, 10 slides, pack of cover slips, tube of mounting fluid. Wooden carrying case. Shpg. wt., 10 lbs. F-369 Net 44.50

1500X "MICRO-STANDARD" ADVANCED ACADEMIC MICROSCOPE

- 25X TO 1500X IN 11 RANGES
 - INTEGRAL MECHANICAL STAGE
 - VARIABLE SUB-STAGE CONDENSER WITH IRIS DIAPHRAGM
 - FULL RANGE FINE ADJUSTMENT
 - STANDARD SOCIETY SIZE OPTICS - BOTH OBJECTIVES AND EYEPIECES
- OPTICAL SPECIFICATIONS: Three Huygenian eyepieces: 5, 10X, 15X. Four achromatic objectives: 5X, 10X, 40X, 100X (oil immersion).
- BODY: Monocular tube 140mm long. STAGE: Square stage 95mm x 95mm. Integral mechanical stage. Adjustable in any direction.
- FOCUSING: Coarse focus with adjustable tension. Fine focus vernier adjustment. Spring loaded safety device prevents objective from driving through slide.
- SUBSTAGE: Focusing Condenser with variable iris diaphragm. 41mm plano/concave mirror.
- Overall 12 1/2" high, 6 1/2" deep, 5" wide. Includes fitted cabinet with lock and key, specimen slide, blank slide, bottle of cedar oil. Shpg. wt., 11 1/2 lbs. F-602X Net 89.95

500X "MICRO-MECH" MICROSCOPE

- BUILT IN MECHANICAL STAGE
 - 100X - 500X - 2000X
 - SUBSTAGE REVOLVING TURRET
- For the student — hobbyist — or budding scientist. Featuring a built-in, micro-drive mechanical stage. Permits the micro-movement necessary to properly examine micro objects. Promotes learning through ease of operation. Four achromatic objective lenses giving magnifications of 100X, 200X, 300X and 500X. Complete with wooden carrying case and slides. Shpg. wt., 4 1/2 lbs. F-357 Net 5.95
- "MICRO-MECH" LAB KIT: Consists of F-357 500X "Micro-Mech" microscope and F-454 Micro-Lab Kit, with accessories and cabinet plus latest edition of "Hunting with the Microscope." Shpg. wt., 12 lbs. F-622 Net 13.90

MICROSCOPE ACCESSORIES

- A. SLIDE PREPARATION KIT. 30 glass slides, 3x1", in container. Slotted for easy indexing. Includes slide covers and vial of mounting fluid. Shpg. wt., 1 lb. F-533 Net .98
- B. HUNTING WITH THE MICROSCOPE. How the microscope works. How to prepare and study cultures—set up a microscope zoo and garden—grow micro organism—perform micro surgery. Profusely illustrated with photographs and drawings. BK-1440 Net .89
- C. MICRO SLIDE PREPARATION TEKNIKIT™ Seven dissecting instruments. 3 well slides, 22 blank slides, 25 cover glasses, 25 blank labels, blue stain, mounting fluid, pins and descriptive booklet. F-659 in fitted wooden case. Shpg. wt., 1 1/2 lbs. Net 3.49
- WELL SLIDE TEKNIKIT™ 6 single well slides, 6 double well slides, all 3x1". 20 cover glasses, vial of neutral red solution. Shpg. wt., 8 ozs. F-691 Net 1.29
- E. DISSECTING TEKNIKITS™ 2 scalpels, spatula, 2 dissecting needles, 2 dissecting forceps, blowpipe, magnifier, scissors, pins. In fitted case. Shpg. wt., 1 lb. F-451 Net 3.79
- D. S.R. DISSECTING TEKNIKIT™ All above plus 6" probe with eye, fine scissors, 2 cc syringe, slip on needle, large fitted case. F-450 Shpg. wt., 1 1/2 lbs. Net 5.49
- F. MICRO-SLIDE STAINING TEKNIKIT™ Each vial is a "dropper" type for direct application of stain to specimen. Kit consists of one vial each of Safranin, Methylene Blue, Fuchsin, Gentian Violet, Eosin and First Green. Complete detailed instructions. Shpg. wt., 8 ozs. F-605 Net 1.79
- ADVANCED STAINING TEKNIKIT™ Three additional dyeing fluids. For staining blood smears, spirochaetes, bacteria, etc. With instructions. Shpg. wt., 6 ozs. F-624 Net 1.69
- G. MICROSCOPY TEKNIKIT™ Contains equipment for collecting — fixing — dyeing — dehydrating — clearing — mounting — finishing — labeling — drying and storing subjects. 24 1x3" slides, cover slips, labels, tweezers, scalpel, dropper, probe, rod, 2 collecting vials, 2 small dishes, 4 bottles of dehydrating fluid (70%, 80%, 90%, 100% alcohol), bottle of acid alcohol, xylol clearing fluid, Gates' fixing fluid. Canada balsam mounting fluid, 2 vials of dyeing fluid (acid fuchsin and gentian violet). With detailed instructions. Shpg. wt., 2 lbs. F-604 Net 3.95
- H. MICROLITE. Provides a bright, evenly lighted field of view. Adjustable for transparent or opaque specimens, direct or indirect illumination. Invaluable where oblique light is necessary. Operates on 110-120 volts AC/DC. Self contained switch, cord and plug. Lamp is 5 1/2" long. Stand is 5 1/2" high. Shpg. wt., 1 lb. F-268 Net 2.95
- J. SUBSTAGE "MICRO-LUMINATOR". Mounts in mirror forks of 35 to 40 mm (1 1/4 to 1 3/4"). Mirror forks of other sizes are readily spread or compressed to fit. Blue filter glass corrects light to proper color for micro-illumination. Complete with 5 1/2 ft. cord, plug, switch and spare bulb. For 110-120V. AC/DC. Shpg. wt., 8 ozs. F-612 Net 2.89

800X "BI-OCULAR" MICROSCOPE

- NEW TWIN LENS "BI-OCULAR" TURRET!
 - BUILT IN SUB-STAGE MICRO-LITE!
 - 100X-800X-2000X
- BI-Ocular turret permits instant variation of magnification without disturbing subject set-up. Triple objective click-stop turret in concert with 10X and 15X "Bi-Oculars" give six ranges of magnifications. "Micro-Life" with automatic on-off switch. Dual knob, rack and pinion focusing, 8 1/2" high overall. All optics are achromatic. Ocular lenses are Huygenian type. Includes sub-stage mirror for viewing by reflected light. Dovetailed wooden carrying case and sample slides. Shpg. wt., 5 lbs. Less batteries. F-334 Net 8.49
- BA-155 Battery (2 required) Net ea. .095

500X "MICRO-MECH" MICROSCOPE

- Direct viewing "projection" microscope affords viewing ease to small groups. Less tiring than viewing through a conventional microscope. The image is projected onto a self contained, translucent glass screen. Finger tip control switches from 50X to 100X. Thumb wheel focus for sharp definition. Projects the full colors present in the slide or specimen. Illumination by means of a battery powered, pre-focused bulb. Requires 2 standard flashlight batteries (not included). Overall size 4 1/2 x 3 1/2". Hooded viewing screen, inclined to 55°, optimum viewing angle. Supplied with bulb and three prepared slides. Shpg. wt., 1 1/2 lbs. F-760 Net 5.29
- BA-157 Batteries (2 required) Net ea. .13

MICROSCOPE MECHANICAL STAGE

- Attaches to any square microscope stage 70 mm x 80 mm or larger. Accommodates slides up to 75 mm x 50 mm. Both lateral and front-to-back movement by rack and pinion. Adjustment scales are graduated in single millimeters with verniers reading to 1/10th mm. Essential accessory for all high magnification examination. Permits relocating any portion of a slide or charting the entire slide. Spring clip automatically accommodates slides of varying dimensions. Shpg. wt., 12 ozs. F-613 Net 6.95

MICRO-SLIDE TEKNIKIT™

- Specially selected slides of universal interest. Slides are professional size. Set includes 12 prepared slides and slotted, covered box for filing and storing. Shpg. wt., 8 ozs.
- F-123 Parts of Insects Net 1.49
 - F-124 Spiders, Disease Carriers Net 1.69
 - F-125 Tiny Creatures Net 1.59
 - F-126 Sea Life Net 1.39
 - F-128 Structure of Blood Net 1.15
 - F-130 Life cycle of Insects Net 1.59
 - F-131 Bacteria Net 1.79
 - F-132 Sea Life, Plankton Net 1.59
 - F-134 Micro-Animals Net 1.29
 - F-135 Micro-Organisms Net 1.29
 - F-136 Substance of Cells Net .89
- Set of 6 Slides

MICROTOME TEKNIKIT™

- Essential tool for free hand sectioning of biological specimens. Equally suitable for the serious hobbyist and student as well as lab applications where the accuracy of a hand operated feed is sufficient. The micro-fine pitch screw feed is graduated in 10 micron intervals. The dense, composition stage is absolutely flat, 75 mm in diameter. "Straight razor" type micrometer knife of surgical quality steel. Ground and tempered to take and hold a keen cutting edge. Supplied with microtome knife, pitch and compartmented wooden storage cabinet. Shpg. wt., 2 lbs. F-603 Net 10.95

TEKNIKIT™ SLIDE LIBRARIES

- 72 Different Slides
 - 6 Volumes of Subjects
 - Reference Set for Various Subjects
- A 72 specimen library of slides carefully pre-selected to maintain continuing interest in microscopy. Consisting of 6 correlated series of subject matter in biology, zoology and botany. Each specimen is cultivated, cleaned, dissected, embalmed, stained, mounted, labeled and covered for permanence. All are large (1x3") size. Ideal ready-reference for the science-hobbyist. Shpg. wt., 2 lbs. F-803 Net 7.50
- SR. Slide Library. 120 slides, all above plus bacteria, cell structure, blood structure, micro-organisms and animals. Total eleven volumes. Shpg. wt., 3 1/4 lbs. F-804 Net 11.90

LAFAYETTE

TELESCOPES

are WORTH LOOKING INTO!

269.50
NO MONEY DOWN



Arcturus
• 454x with Barlow Lens

3" EQUATORIAL REFRACTOR

- Ultra Precise Helicoid Focusing • 7 Coated Eyepieces Plus Barlow Lens • 76.2 mm Clear Aperture
- Most Advanced Equatorial Mount • 25x, 42 mm Finder Scope

79-mm hard coated, air-spaced Fraunhofer achromat of 910-mm focal length with 3" clear aperture, focal ratio of f/12 and resolving power of 1.6". Seven coated eyepieces provide magnifications of 227x, 152x, 101x, 73x, 45x, 35x plus 25x through viewfinder. Helicoid focusing by means of a massive wheel and helical gear. Finder Scope, with rack and pinion focusing, features a 1.6 inch clear aperture objective of 500-mm focal length. Micro-motion controls with extended flexible shafts and compression locks in all axes. Accessories: include three sunglasses, moon-glass, sun diagonal, two star diagonals, sun projection screen, erecting prism, heavy extensible field tripod, brace accessory shelf, separate wooden cases for telescope and mount. Shpg. wt., 100 lbs. VIA EXPRESS ONLY F-385WX

Net 269.50

RESEARCH QUALITY 3" EQUATORIAL REFRACTOR

- Viewfinder Scope 25x, 42-mm • 910 mm Focal Length • 76.2 mm Clear Aperture • Micromotion Controls for Declination and Right Ascension • Resolving Power 1.6 • Barlow Lens Included

189.00 No Money Down!

The objective lens is a 79-mm, hard coated, air spaced Fraunhofer achromat with a clear aperture of 76.2 mm (3"). Focal length 910 mm, focal ratio f/12, resolving power 1.6". Seven coated eyepieces provide magnifications of 227x, 152x, 101x, 73x, 45x, 35x plus 25x through the viewfinder. Barlow lens add ranges of 454x, 304x, 202x, 146x, 90x, 70x and 50x. Focusing by means of micro-precision rack and pinion drive. The viewfinder scope has a 42-mm (1.6 in. clear aperture) objective—500-mm focal length-rack and pinion focusing—and will accommodate various eyepieces. Finely calibrated hour and declination circles for rapid finding and setting. Body tube of white enameled aluminum. Accessories include three sunglasses, moon-glass, two star diagonals, sun diagonal, erecting prism, sun projecting screen, extensible field tripod, chain brace, accessory shelf, wooden cabinet. VIA EXPRESS ONLY. F-384WX Shpg. wt., 60 lbs. Net 189.00

Galactic
• 454x with Barlow Lens

Polaris
• 320x with Barlow Lens

2.4" EQUATORIAL REFRACTOR

- Eyepieces for 160x, 88x, 40x, Barlow Lens gives 320x, 176x, 80x • 800 mm. focal length • 62-mm objective • Micromotion adjustments on both axes
- Coated optics throughout • Equatorial mount

79.50 No Money Down!

Objective: Fraunhofer-type achromat, hard coated, 62.5-mm., 800-mm. focal length. Collects about 75 times as much light as the naked eye, resolving power 2 seconds, faintest discernible star 10.7 magnitude. Eyepieces are hard-coated Huygenians. 160x (5-mm), 88x (9-mm), 40x (20-mm). Barlow Lens included give ranges of 320x, 176x and 80x. Finder scope is 6x, 30-mm. Tripod head with latitude adjustment. Clamp lever for declination and inclination. Accessories include sunglasses, star diagonal, erecting prism, sun projection screen, field tripod, wooden case. Rack-and-pinion focusing. Heavy plating to prevent rusting.

F-342WX Shpg. wt., 30 lbs. Net 79.50

F-391 4-mm. orthoscopic eyepiece for 200x (400x with Barlow Lens) Net 8.95



(A) ZOOM SPOTTING SCOPE

- Any Power from 15X to 30X!
- Ideal for any "Spotting" Need!
- Pan-Head, elevator Tripod

True Zoom action—finger tip control—from 15 power to 30 power. Choose the right power for any "spotting" or viewing need. Brilliant image at any power. 50mm objective, hard coated for maximum light gathering power. Prismatic system greatly reduces length—only 15" overall. Precisely machined, all metal body. Lightweight scope alone weighs only 2 lbs. May be hand held or used with tripod supplied. Precision finger-tip focusing with oversized, milled ring. Aluminum and chrome-brass tripod adjustable from 12" to 18". Locking pan-head swivels and tilts to any angle. Optical train is fully hard coated. Shpg. wt., 5 lbs. F-685 Net 39.95

(B) 30x, 60mm SPOTTING SCOPE

• Coated Optics • Complete With Leather Case
Field of view is 85 feet at 1000 yds.! Both front and rear optics are coated. High relative brilliance due to 60mm objective lens. Exceptionally small and light—weighs only 2 lbs. including metal tripod! The perfect companion for shooting—hunting—viewing—naturalists—and hobbyists. Equipped with 11½" tripod and zippered leather carrying case. Shpg. wt., 3 lbs. F-149 Net 16.95

LAFAYETTE BINOCULARS LOWEST PRICES • HIGHEST QUALITY



17.95

7X 35
CENTER
FOCUS



Precise design—quality material—and expert workmanship. All lenses are hard coated—prisms clamped in lightweight alloy frame and body—sealed against dust and moisture—properly collimated and aligned. All are center focus with adjustable right eyepiece. Hard leather case and neckstraps included.

7X35 Popular, versatile, all purpose binoculars. For the sportsmen—hunter—bird watcher—vacationer. High luminosity. Compact design. Shpg. wt., 3 lbs. F-183 Net 17.95

7X55 Wide Angle. Top performance—highest quality. Almost twice the field of view of ordinary 7X35 binoculars. Spots and holds a moving target faster and easier. Oversize oculars and prisms. Shpg. wt., 3½ lbs. F-184 Net 27.50

7X50 Navy style night glasses. Favored for marine use. The choice of professionals because of exceptionally high light gathering power. Superior image brightness. Shpg. wt., 3½ lbs. F-164 Net 21.95

20X50 King of the long range. Hunters, mountain climbers, plane spotters, forest rangers—any long distance viewing and observation requirement. Shpg. wt., 4½ lbs. F-185 Net 27.50

Add 10% Fed. Tax to the above prices.

TRU-ZOOM BINOCULARS



39.95

NO MONEY
DOWN

• Not a
"Vari-Power"—
One Control
Zooms both
barrels!

- Center Focus—right Eye Adjust—Plus Single Synchronous Zoom Control!
- The Perfect Power For Any View!

Sensational Zoom action holds even fast-moving subjects in perfect view. Sight in any subject at 7 power—then Zoom up to 12 power (or any four in between) for closeup viewing. Full 40mm, objective lenses, hard coated achromats. Field of view is 290 feet at 1000 yds. at 12 power (5.5°). Prisms clamped in shock-resistant mounts. Lightweight alloy frame and body. Sealed against dust and moisture. Includes plush-lined, hard leather case and straps. Shpg. wt., 5 lbs. F-793 Net 39.95*

*Add 10% Fed. Tax

STAR SPECTROSCOPE WITH 3 EYEPIECES

- Observe the spectra of magnitudes—1 to 3
- Identify Fraunhofer lines from C to G
- Drawtube focus arrangement
- Fits threads of 25.4mm O.D. and 24.5mm O.D. eyepieces

The Star Spectroscope (Amici-prism type) is excellent for visual observations of the spectra of bright stars, comets, and novae. The dispersion angle between the Fraunhofer C line (wave length 6600 angstroms) and the G line (4300 angstroms) is 9°. The resolution is enough to separate the yellow D lines of sodium. Body is made of black-coated brass. Fits Lafayette telescopes F-342, F-384 and F-385. All in plush-lined case. Shpg. wt., 8 oz. F-569 Net 29.95

ACHROMATIC BARLOW LENS

- Provides Greater Eye Relief!
- Improves Definition!
- Greater Illumination—Wider Field!
- Makes Any Good Telescope Better!
- Doubles Your Telescope's Power!

The Barlow Lens is a negative (diverging) lens which can increase the range of magnification of any given set of eyepieces. Sharpens definition and reduces image deterioration by permitting use of low-power eyepieces to achieve high magnification. Lafayette's Barlow lens will make any good telescope perform like a much larger one. Fits all Lafayette telescopes except F-330 Explorer. Accepts eyepieces of 24.5mm (.97") O.D. and fits draw tubes of that size. Shpg. wt., 1 lb. F-423 Net 4.95



These are the same fine viewfinders used on Lafayette's refractor telescopes. All have coated, achromatic objectives and eyepieces. Equipped with mounting brackets, and centering screws for collimation.

(A) 30 mm (1.2"), 6X: Duraluminum tube finished in white enamel. Draw tube focusing. Eyepiece is interchangeable, 24mm (.97") O.D. Single mounting bracket, as shown with the Polaris, F-342. Shpg. wt., 2 lbs. F-629 Net 6.95

(B) 32 mm (1.6"), 25X: Air spaced objective, 500 mm focal lengths. Dual mounting brackets, as shown on the Arcturus, F-385. Suitable for use as a small celestial and/or terrestrial telescope. Duraluminum tube, finished in white enamel. Standard rack and pinion focusing. Chrome plated brass draw tube. 20 mm eyepiece supplied can be interchanged with eyepieces of other focal lengths. Shpg. wt., 8 lbs. F-628 Net 17.95

"MICRO'DAPTER"



19.75

- Micro-photography!
- Astro-photography!
- Inexpensive—accurate—easy to use
- Use any camera/microscope or camera/telescope setup
- Photo-record your observations.

Permits the use of any camera—even movie cameras—with practically all microscopes and telescopes. No need to remove the camera lens. Cross hairs are superimposed on the image for centering. The image is automatically in focus for the camera when viewed in focus through the MICRO'DAPTER. Accessory sleeves permit the MICRO'DAPTER to be used with other than Society size microscopes. The MICRO'DAPTER may be used with any telescope by attaching to eyepieces of 29mm (1½") maximum diameter. Shpg. wt., 1½ lbs. F-506 Net 19.75


LAFAYETTE 14" TRANSPARENT CELESTIAL GLOBE

Basic Aid for Students and Teachers of Astronomy

39.50

- Adjustable Satellite Orbits
- Satellites Travel around Earth Automatically
- 80 Constellations

The sphere will illustrate how the sky will appear at any hour—on any date—from any point on earth. With it you can tell time by the stars—learn to tell time by the sky—clearly illustrate and help solve navigational problems. Traces the orbits of man made satellites and finds their overhead positions. Sun and moon positioned by external controls. Artificial satellites automatically circle around the globe. The celestial globe is 14" in diameter with the terrestrial globe centered within. Equipped with horizon ring—time ring—fixed meridian ring—swinging meridian ring—sun and moon pointers—fixed ecliptic—detachable "planet" indications—universal base—and complete instructions. Shpg. wt., 15 lbs. F-400WX Net 39.50



(A) AMATEUR ASTRONOMER'S HANDBOOK. Covers the essential characteristics of telescopes and other factors affecting telescopic observation. Treats topics as magnification and resolution of telescopes, aberrations of lenses, types of telescope mountings and drives, micrometers, photometers. 580 pages, illustrated. BK-1455 Postpaid in U.S.A. Net 12.50

(B) OPTICS AND OPTICAL INSTRUMENTS: AN INTRODUCTION WITH SPECIAL REFERENCE TO PRACTICAL APPLICATIONS BY B. K. Johnson, 3rd Ed. Practical applications of optical theory for student, teacher, amateur lens designer, hobbyist. How to construct working models of optical instruments. 224 pp. 5½x8". Paperbound. BK-817 Postpaid in U.S.A. Net 1.65

(C) THE SCIENTIFIC AMERICAN BOOK OF PROJECTS FOR THE AMATEUR SCIENTIST BY C. L. Strong. Volume of experiments in major areas of science, astronomy, biology, natural sciences, earth sciences, nuclear physics, mathematics, electronics, etc. Measuring metabolism in animals; electric seismograph; magnetic-resonance spectrometer; amateur rocketry. Illustrated. 608 pages. BK-39 Postpaid in U.S.A. Net 5.95

(D) DISCOVER THE STARS • BUILD A MODEL SATELLITE. Explains Astronomy in simple terms. Illustrated instructions on building a sextant, clinometer, sundial planetarium. Photograph star trails—tell time by stars—latitude, longitude. Discusses radio astronomy—navigation, satellites, etc. Illustrated. 146 pages. 5½x8". BK-1441 Postpaid in U.S.A. Net .89

ILLUMINATED BEARING 'SCOPE

24.95

- Take Instant—Accurate Bearings!
- Pin-Point Your Position, Day or Night!
- Combines Compass Bearing and Land-mark Sighting!



A precision-crafted "navigating" instrument, for the small boat owner—fisherman—hunter—camper. A combination of an "alidade" type sighting tube and a jeweled pivot, liquid compass. Takes accurate sightings on landmarks and converts them into compass bearings. By recording two bearings you can return to the precise position at any time. Fixes your position automatically without complicated instruments. Plots your position on a map—establishes compass course to get you to a point. Graduated in increments of 1° with each 10° called out. Heavy brass throughout, anti-magnetic and corrosion-proof. With instructions and fitted hardwood storage chest. F-660 Shpg. wt., 3 lbs. Net 24.95

Battery for F-660 BA-155 Net .095

LAFAYETTE 9-TRANSISTOR CITIZENS BAND "WALKIE TALKIE"

"MIGHTY 9"

The MOST POWERFUL

9 TRANSISTOR PERSONAL PORTABLE

with 2 DIODES and 1 THERMISTOR

ONLY **25⁸⁸**

NO MONEY DOWN

- LIGHTWEIGHT SHIRT-POCKET SIZE • PLAYS FOR HOURS ON 2 MOST INEXPENSIVE BATTERIES • SEPARATE MIXER AND OSCILLATOR • 2 IF STAGES • 4 AUDIO STAGES • 2 DIODES • AVC AMPLIFIER • PERSONAL, BUILT-IN EARPHONE JACK • COMPLETE WITH LEATHER CARRYING CASE, BATTERIES, EARPHONE & FULL-TONE SPEAKER

Lafayette's new "Mighty-9" portable, the most powerful transistor radio, is the answer for those who want the best, without spending the most. Compare this portable with others selling for much more—compare feature for feature and you'll see why the Lafayette "Mighty-9" is your best buy. Inside the sturdy, attractive plastic case you'll find an engineer's dream—separate mixer and oscillator, diode detector and diode bias stabilizer, 2 IF stages, AVC amplifier, 4 audio stages including push-pull audio output. Lightweight (only 9 ozs.), pocket size (4½Hx3Wx1¼"D); self-contained stand. Best of all it operates on two of the most inexpensive "Z" cell batteries—plays up to 3 times longer than on other 9 volt batteries. Complete with leather carrying case, batteries and earphone for private listening. Shpg. wt., 2 lbs.

FS-91L Net 25.88
BA-155 (Burgess Z type battery 2 required) Net ea. .095

NO MONEY DOWN!



Complete with carrying case, batteries and earphone

plus Diode and Thermistor

NO LICENSES, TESTS OR AGE LIMITS



Complete with LEATHER CASE, EARPHONE, ANTENNA & BATTERIES

- Transmits & Receives Up to 1.5 Miles
- Crystal Control on Both Transmit & Receive
- Leather Case with Shoulder Strap
- Requires 8 Inexpensive Penlight Batteries
- Up to 70 Hours Battery Life
- 46" Telescoping Antenna
- Push-To-Talk Operation
- Earphone For Personal Listening

OTHER CHANNELS ARE AVAILABLE
If desired with any channel other than channel 10, order HE-91L and specify channel.

NOW NO MONEY DOWN
39⁹⁵
2 for 78.88

Give Your Family The Protection They Need and Deserve



FAMILY RADIATION DETECTION SET

24.95

NO MONEY DOWN

Measures Radiation Fallout — Tells You When It's Safe To Leave Shelter

In event of a Civil Defense emergency, knowledge of radiation fallout is necessary for survival. As part of your personal and defense preparedness, Lafayette offers the Bendix Family Radiation Detection Set. Complete with ratemeter, dosimeter, changer and instruction manual, it is designed to

help you in deciding when to enter and leave shelter for protection against radiation fallout. The Federal Government recommends that each family has a radiation measurement instrument. Send for yours today.

YE-666 Shpg. wt., 2 lbs. Net 24.95

No License or Permit Required—Complete portable two-way communications for everyone, everywhere. Perfect for hunting, fishing, boating, virtually all sports; use at work in construction, warehouse, office, on the farm or for in plant communications. Receives and transmits up to 1.5 miles under average conditions (no intervening obstructions.)

As simple and easy to use as your telephone and twice as handy—weighs only 18 ounces and slips easily into your pocket. Just two controls provide fast, efficient operation, on/off volume and push-to-talk. When push-to-talk button is depressed for transmitting the built-in-speaker acts as a sensitive microphone. Private monitoring of conversation is made possible by means of a special jack and earphone. Telescoping antenna extends to 46 inches.

Constructed with the care and precision of a fine watch, this new Lafayette Citizens Band "Walkie Talkie" achieves optimum reliability and performance by use of sophisticated transistor techniques and advanced design. Full transistor circuitry employs 9 transistors plus 1 diode. Transmitter section is crystal controlled and delivers a power input of 100 milliwatts, meeting FCC specifications for unlicensed units in the 27mc Citizens Band spectrum. Crisp-clear reception is furnished by the efficient superheterodyne receiver. Power is supplied by 8 miniature standard penlight batteries with a life expectancy of up to 70 hours.

Housed in a handsome black and gold aluminum case with leather carrying case and shoulder strap. Supplied with earphone, antenna, batteries and crystals for channel 10. Size 6½x3¼x1½". Shpg. wt., 3 lbs.

HE-29AL Net 39.95
Set of 2 Net 78.88

Replacement batteries for HE-29 "Walkie-Talkie," 8 required Net Each .095
BA-155 Z Cells

CRYSTALS FOR HE-29A
HE-830L TRANSMITTING CRYSTAL (Specify Channel) Net 2.25
HE-758L RECEIVE CRYSTAL (Specify Channel) Net 2.25

FAMOUS PICKERING MARK IIC CARTRIDGE

SPECIAL SALE PRICE

9.88

Complete with D9007 Diamond Stylus

REG. 24.00

with D3707A Stylus

QUANTITY LIMITED

- .7 Mil Diamond Stylus
- Response ± 2 db 10-30,000 CPS

Here is the famous Pickering Mark II C Cartridge with .7 mil diamond stylus that reproduces both mono and stereo perfectly. Uses "T-Guard" stylus assembly. Tracking force: 3-7 grams; separation: 25 db; output: .025 volts per channel. Shpg. wt., 3 ozs. Net 9.88
PK-603L

NOW! NO MONEY DOWN when you use LAFAYETTE'S NEW EASY-PAY PLAN!

LAFAYETTE RADIO ELECTRONICS "ASSOCIATE STORE" DEALER LOCATIONS

Lafayette Radio Electronics "Associate Store" Dealers own and operate their own stores as independent franchised dealers. They establish their own terms and prices, which may vary slightly, and do not handle mail orders.

SAN FRANCISCO, CALIF.
1480 Market St.

DENVER, COLO.
1455 So. Sheridan Blvd.

BRIDGEPORT, CONN.
2710 Fairfield Ave.

GROTON, CONN.
171 Thames St.

STAMFORD, CONN.
85 Prospect St.

WATERBURY, CONN.
386 West Main St.

TAMPA, FLA.
3328 Henderson Blvd.

SPRINGFIELD, MASS.
527 Belmont Ave.

BALTIMORE, MD.
2014 No. Charles St.

BEL AIR, MD.
139 Thomas St.

DETROIT, MICH.
1326 Broadway

ASBURY PARK, N. J.
1027 Highway No. 35

CAMDEN, N. J.
305 Broadway

NORTHFIELD (Atlantic City), N. J.
Tilton Shopping Center
Tilton Road

TRENTON, N. J.
229 South Warren St.

ALBANY, N. Y.
335 Central Ave.

ROCHESTER, N. Y.
792 W. Main St.

AKRON, OHIO
34 North Main

CANTON, OHIO
300 Walnut St.

CLEVELAND, OHIO
2001 Euclid Ave.

COLUMBUS, OHIO
122 E. Long St.

ALLENTOWN, PA.
20 North 7th St.

HARRISBURG, PA.
1419 No. 3rd St.

PITTSBURGH, PA.
640 Grant St.

MAIL ORDERS NOT FILLED BY "ASSOCIATE STORE" DEALERS

LAFAYETTE RADIO

111 JERICO TURNPIKE
SYOSSET, LONG ISLAND, NEW YORK

BULK RATE
U. S. POSTAGE
PAID
New York, N. Y.
Permit No. 8486

ABC
123