# RADIO AM-FM-TY MAINTENANCE



# the battery that's made for the Radio Trade ...

• The selective distribution of RCA Batteries primarily through radio dealers and servicemen adds up to more repeat business for you.

Remember, too, that RCA Batteries are radio engineered for extra listening hours...that this completely rounded line covers virtually all renewal requirements.


ALWAYS KEEP IN TOUCH WITH YOUR RCA DISTRIBUTOR



RADIO CORPORATION of AMERICA

HARRISON, N. J.

# **AUTO RADIO and HYTRON** go together



A Ford in your future?" There will probably be a fine new radio receiver on the dash. Chances are good this receiver will be equipped with tubes by Hytron. For Hytron is a major supplier of Ford auto radio tubes. That is only natural. Hytron specializes in auto radio tubes—both GT and miniature. Close engineering co-operation with leaders like Ford help make Hytron auto radio tubes leaders, too. 'Nuff said. Hytron and auto radio go together.

SPECIALISTS IN RADIO RECEIVING TUBES SINCE 1921.



RADIO AND ELECTRONICS CORP.

MAIN OFFICE: SALEM, MASSACHUSETTS





# Television and FM Servicing

#### Practical On-the-Job Training Program for the Better Serviceman Who Wants Greater Earnings and Security In This Expanding Field

THIS basic CREI Servicing Course paves the way to greater earnings for you. Since 1927 thousands of professional radiomen have enrolled for our home study courses in Practical Radio Engineering. Now. CREI supplies the answer to the need for a Practical Servicing Course. You do not have to be, or want to be, an engineer to benefit from this course. It is written for you—the average good serviceman! It's not too elementary for the experienced. It's not "over the head" of those who have limited experience—if they have real ambition and natural ability.

CREI developed this course at the request of several large industrial organizations. The urgent need of capable, trained servicemen is one of the big problems of the industry. Hundreds of thousands of Television

Radio Service Division of

# CAPITOL RADIO ENGINEERING INSTITUTE

An Accredited Technical Institute

Dept. 221A, 16th & Park Rd., N. W., Wash. 10, D. C. Branch Offices: New York (7) 170 Broadway • San Francisco (2) 760 Market St.

Receivers will be marketed in 1949. By 1951 two million TV units are expected to be flowing into American homes. With Television comes FM receivers and circuits. This new field demands a tremendous increase in the number of properly trained television and FM technicians to install and service this equipment.

## CREI EQUIPS YOU TO INSTALL AND SERVICE ALL TYPES OF TELEVISION AND FM RECEIVERS

Now . . . with the help of this new CREI streamlined Service course you can move ahead to unlimited opportunities in your chosen field. CREI has again taken the lead by offering a course so entirely new that for the first time in our twenty-one year history we can offer a down-to-earth course of training for servicemen. In offering this course at a popular price. CREI is enabling thousands

of the "top third" now engaged in service work to enter the ultimate profitable field of television and FM installation and service.

This can be your big year! Don't waste another day. CREI has the answer to your future security in this new servicing course. Write today for complete information. The cost is popular. The terms are easy. The information is free. Write today.

CAPITOL	RAD!O	ENGINEERING	INSTITUT
4011102	MMDIU	FIGUREEKING	114.2111.01

16th E. Park Road N.W. Dept. 221A, Washington 10, D.C.

Cantlaman	

Please send me complete details of your new home study course in Television and FM Servicing. I am attaching a brief resume of my experience, education and present position.

NAME

STREET

ZONE

STATE

☐ I AM ENTITLED TO TRAINING UNDER G. I. BILL

# Test Pointers

#### ON INTERMITTENTS

One of the greatest single problems encountered by the radio technician in his daily work is the intermittent radio set.

However, when suitable instruments are used to monitor intermittent receivers, the regular shop schedule can be maintained. Other service jobs can be completed while monitor instruments stand watch for any change in the functioning of an intermittent receiver.


Less effective methods are also used to shoot intermittent trouble. In an attempt to save man-hours, some technicians habitually replace a majority of the capacitors in an intermittent receiver at the outset. This remedy is frequently unsuccessful because many intermittents are caused by defective resistors, coils, switches, tubes, etc. Even after all of the suspected items are replaced, an appreciable percentage of receivers remain intermittent. In such cases, man-hour costs are pyramided on top of component costs; if these costs are passed on to the customer, good will suffers.

Artificial acceleration of the intermittent cycle is helpful in some cases. High line voltage will hasten the breakdown of certain marginal components. Low line voltage frequently causes a defective oscillator to cease operation. Some intermittents can be speeded up by increasing the operating temperature of the chassis by placing it in a carton with an incandescent lamp.

Although all of these methods work at times, signal-monitoring techniques have been found to be the best answer to the intermittent problem. Occasional checks of the monitor indicators show whether gradual operating changes are taking place. After the intermittent occurs, it can be localized to a particular section of the receiver by analysis of the monitor instruments.

Monitoring instruments have the advantage of providing a continuous check of the oscillator frequency and voltage, of the intermediate signal frequency and amplitude, of the audio input and output, of the receiver power consumption, and of the ave supply voltage.


Oscillator frequency shift is one of the most elusive causes of intermittent operation. Other obscure intermittents are caused by defective power-supply components, which show up on the monitor chiefly as a change in power consumption.



Valtage indicator detects ascillator frequency shift

This brief discussion illustrates the important fact that many hours of time can be saved if the receiver is divided into five main sections, or channels, which can be monitored continuously. These are the ht oscillator, the rt or if channel, the audio system, the power supply, and the ave channel. After the intermittent has been localized to one of these sections, the instrument probes can be used to "close in" on the defective component.

Continuous monitoring places intermittent trouble-shooting on a firm technical basis.



## The RCA-162-C Chanalyst

Electronic Analyzer

# makes the difference between profit and loss

THE RCA-162-C Chanalyst Electronic Analyzer solves once and for all the problem of time-consuming intermittents. It works for you unattended—and spots the fault in any receiver whenever it shows—leaving you free for other work. That's why the RCA Chanalyst more than pays for itself in the time it saves.

The RCA-162-C will give you a positive check of any fault which takes place in the receiver under test. Its four electron-ray tubes plus an electronic voltmeter give an immediate indication of any change when it occurs. Once the trouble is localized it is a simple matter to determine the cause.

Find out today how the RCA-162-C Chanalyst Analyzer can make more money for you. Ask your RCA Test and Measuring Equipment Distributor for the new bulletin on the 162-C, or write RCA, Commercial Engineering, Section 51AX, Harrison, New Jersey.

#### SPECIFICATIONS

Always keep in touch with your RCA Distributor



RADIO CORPORATION OF AMERICA
TEST AND MEASURING EQUIPMENT HARRISON, N. J.

# AAINTENANCE ELECTRONIC MAINTENANCE

Volume 5

Editorial

JANUARY 1949

Number 1

#### CONTENTS

Eultulia!	7
Audio Systems in FM	12
TV Tuning Systems	14
Advertise, Win Customers and Prosper Victor M. Turner An introduction to business promotion	18
Roof-to-Receiver, Over	21
Over the Bench John T. Frye	22
Electronically Speaking	31

WILLIAM F. BOYCE

MORTON SCHERAGA Contributing Editor

JOSEPH J. ROCHE Editor

THOMAS A. BYRNES Director of Field Services VICTOR M. TURNER Art Director

> AL JOHNSTON Circulation Manager

#### ADVERTISING REPRESENTATIVES

Eastern

Herbert J. Olsow 480 Lexington Ave. New York 17, N. Y. Plaza 9-0861

Midwestern

Stuart J. Osten 333 No. Michigan Ave. Chicago I, III. Dearborn 2-3507

Copyright 1948, Boland & Boyce, Inc.

Radio Maintenance is published monthly by Boland & Boyce, Inc., at 34 No. Crystal St., East Stroudsburg, Pa., U.S.A.; Executive and Editorial Office, 460 Bloomfield Ave., Montclair, N. J. Subscription Rates: In U. S., Mexico, South and Central America, and U. S. possessions, \$3.00 for 1 year, \$5.00 for two years, single copies 40 cents; in Canada, \$3.50 for 1 year, \$6.00 for 2 years, single copies 45 cents; in British Empire, \$4.00 for 1 year, \$7.00 for 2 years, single copies 60 cents; all other foreign countries, \$5.00 for 1 year.

Entered as second class matter July 13, 1946, at Post Office, East Stroudsburg. Pa., under the Act of March 3, 1879.

Change of address: Four weeks' notice required for change of address. When of change, please furnish an address stencil impression from a recent issue if you can changes cannot be made without the old stencil as well as the new one. When ordering a

RADIO MAINTENANCE . JANUARY 1949



Just Out!

#### SERVICING THE MODERN CAR RADIO, by A. L. Hurlbut

Second edition, 702 pages, 81/2 x 11, 222 illus., over 500 circuit diagrams ....\$7.50

Here—written by a practical auto radio expert of 20 years' standing—is everything to help the beginner or experienced serviceman gain profitable skill in the fast-growing field of car radio servicing. A complete guide to the work. Book not only describes installation, testing, and repair methods fully, but also gives needed special facts of car radio circuits, differences between car and home radio servicing problems, shop set-up and business-getting ideas, etc. And invaluable for all jobs is the big gallery of circuit diagrams on hundreds of models, old and new.

#### Practical facts and methods on:

- —getting into the car radio business —differences between mo-
- bile and home radios antennas and input
- circuits

  —power supplies

  —circuit features
- —auto electrical systems
- —setting up shop
  —car set installations
- —antenna installation —loudspeaker installa-
- tion —remedying inter-

- ference
  —servicing procedure
  —vibrator maintenance
  —loudspeaker servicing
  —car-radio alignment
  —push-button tuming,
- e°c.

#### "OPPORTUNITY OF A LIFETIME FOR ALERT SERVICEMEN"

Says A. A. Ghirardi author of famous radio servicing books and articles



ALFRED A. GHIRARDI

"SERVICING THE MODERN CAR RADIO represents an opportunity no wide awake serviceman can afford to miss. There are over 9,000,000 car radios—approximately 16 out of every 100 radio receivers in use — a wonderful field for increasing business; stepping ahead of competition! Good auto radio mener scarce, and this book gives you a gold mine of information you need to cash in on this profitable, fast-growing business."

#### 10 DAYS' FREE EXAMINATION

Murray Nill Books, Inc. (Division of Rinehart & Co.) Dest. RNd-19, 232 Madisun Ave., New York 16, N. Y. Send me Hurlbut's Yervicing the W Radio for 10 days' examination on In 10 days. I will send \$7.50, plus polage, or return book postpaid, on cash orders; same return privile sent on approval in U. S. snly. Pr U. S., \$8.00, postpaid.)	approval. few cents stage paid ge, (Books
Name	*** *****
Andress	
City (Zone) & State	
Occupation	


## **NEW Television Kits, and Equipment**

Important Advances in TV Reception and Servicing! NEW 10" TV KIT



MODEL IDA TV KIT

ALL-CHANNEL BOOSTER



REMOTE CONTROL UNIT KIT



SWEEP SIGNAL GENERATOR

at amazingly LOW PRICE! The new Transvision Model 10A electromagnetic TV Kit gives a bright, stable 52 sq. in, picture. Has 10" picture the, and CONTINUOUS TUNING on all channels. Its bigh sensitivity makes for improved long distance reception; especially good on high channels. Complete with all-channel double-folded dipole antenna

#### **NEW STREAMLINED CABINETS**

for Transvision Model 10A or 12A TV Kit. Made of select grain watnut with beautiful rubbed finish. Fully drilled, ready for installation of assembled receiver. Watnut Cabinet for 10A or 12A (Specify)...Not \$44.95 Mahogany and Blonde slightly higher.

#### TRANSVISION ALL-CHANNEL TELEVISION BOOSTER

To assure television reception in weak signal areas, or areas which are out of range of certain broadcast stations, Transvision engineers have designed this new booster. It decreases signal strength on all television channels, Tunes all television channels, Can be used with any type of television receiver. Unusually high gain in upper television channels.

Model B-1.

#### TRANSVISION REMOTE CONTROL UNIT KIT

Will operate any TV receiver from a distance. Turns set on, times in stations, controls contrast and brightness, turns set off. Ideal for installations where the television receiver is inaccessible, Tuner unit is a high gain, all-channel unit with about 50 micro-volt sensitivity. Easy to assemble in about 50 micro-volt sensitivity.

#### NEW . . . TRANSVISION SWEEP SIGNAL GENERATOR FOR TELEVISION AND F.M.

Complete frequency coverage from 0.227 MC with no hand switching. Sweep width from 0.12 MC completely variable. Accurately calibrated built-in marker generator.

OUTSTANDING FEATURES: (1) Frequency range from: 0.227 MC. (2) Dial calibrated in frequency. (3) Sweep width from 0.12 MC completely variable. (4) Self-contained markers readiable directly on the dial to 5% or better. (No external generator required to provide the marker signals). (5) Crystal controlled output makes possible any crystal controlled frequency from 5-230 MC. (6) Plenty of voltage output—permits stage-by-stage alignment. (7) Output impedance 6.125 ohns. (8) Directly calibrated markers 20-30 MC for trap. (8) Directly calibrated markers 20-30 MC for trap. sound and video 1F alignment. (9) RF for alignment of traps for 1F channels when a Dr volt meter is used as the indicating medium. (10) Umodulated RF signal to provide marker ptps simultaneously with the main variable oscillator. (11) Markers can be controlled as to output strength in the pip oscillator. (12) Power supply completely shielded and filtered to prevent leakage. (13) All active tubes are the new modern miniature type. (14) Phasing control incorporated in the generator.

Radiomen . . . You Can Get Into The TELEVISION BUSINESS In a BIG WAY with the TRANSVISION DEALER PLAN

WRITE FOR FOLDER D-I

NEW 8-PAGE CATALOG showing complete Transvision line now available at your distributor, or write to:

New Rochelle, N. Y. TRANSVISION, Inc. Dept. RM

In Calif.: Transvision of California, 8572 Santa Monica Blvd., Hollywood 46 All prices 5% higher west of Mississippi; all prices fair traded. All prices subject to change without notice.

## LOOKING AHEAD

THE future of the service technician has never looked as bright as it does today. It has always been apparent that the need for radio servicing would increase as the years went on, but just how much opportunity for expansion the next few years would bring was an unknown factor. Television and FM have provided the answer to the service industry's prayers. They are golden opportunities with which the service technician can build himself a better future.

Television, which two years ago faced a difficult and, in the minds of many, uncertain future, has had the opportunity to prove itself. Its success to date has been beyond the expectations of its most optimistic prophets. FM has made steady progress; and although it has not expanded as rapidly as it might, it is moving forward toward universal acceptance.

One of the factors which has caused some to doubt the importance of television, has been the difficulties blocking the path to national coverage. These problems are sure to be overcome since the means have already been developed and demonstrated. You can be sure that in the not too distant future, television coverage will equal that of present radio broadcasting.

Television cannot succeed without many thousands of trained service technicians. This fact has already been demonstrated in those areas where television receivers are being sold in large numbers. Without expert technicians to install receivers and keep them working, this new industry would be destined to complete failure. A television receiver cannot be delivered to the customer's door and forgotten. If a fault develops, the television receiver cannot be disregarded as was the \$9.95 midget. It represents a very substantial investment, and its owner is willing to pay a reasonable price to have it repaired.

Exactly what does this mean to the service technician and the owner of a service establishment? It means that the opportunity to expand and earn more money is literally being forced upon you. This opportunity brings with it the necessity for increasing your ability both as a technician and as a business man. It will also bring greater competition, as is inevitable in an industry which offers the newcomer so much.

To help you make the most of your opportunities, the editors of Radio Maintenance are preparing to present an increasing number of articles on the business aspects of radio servicing. Subjects such as advertising, salesmanship, business management, and bookkeeping will be covered.

In this issue you will find an article on advertising by Vic Turner. Read it. It won't solve all your advertising problems or answer all your questions. No magazine article can. It will give you, however, some idea of what advertising can do for you. If each article you read gives you one new idea, the time and effort it took to read it will have been well spent.

Incidentally, Vic Turner has agreed to answer as many letters regarding advertising problems as he can. Here is a valuable opportunity. Mr. Turner knows his stuff. So don't miss the chance to get some expert advice. People usually have to pay for it.

Television will receive more editorial attention than it has in the past, because it is the biggest technical hurdle the industry must cross to assure success.

Read these articles, they are important to you. Make them part of your plan for the future and remember this—Progress is inevitable, those who grasp the opportunity will assume a more important place in their community, they will render a greater service to their fellows and they will reap greater rewards. Those who do not rise to the occasion will fall by the wayside. There is no third course.



# SPRAGUE PHENOLIC MOLDED TUBULAR CAPACITORS

## Types TM and MB

(600 Volts)

(1600 Volts)

Take a look at Sprague Type TM and MB Phenolic Molded Tubular Capacitors! See how their sturdy phenolic jackets offer complete protection against moisture, vibration and heat—the three factors that cause 9 out of 10 failures in ordinary wax tubulars. Then try Sprague TM's and MB's on your toughest jobs—and you'll quickly understand why these little units represent the greatest capacitor development in modern radio servicing history! Sprague TM's and MB's are a "must" for auto radio, aircraft radio and television applications. And because they cost exactly the same as ordinary wax cardboard tubulars, wise servicemen use them exclusively for all service replacements. There are no service complaints, no dissatisfied customers when you use Sprague TM's and MB's.

Get the genuine article! Be sure and ask for Sprague TM's and MB's by name!

#### SPRAGUE PRODUCTS COMPANY

North Adams • Massachusetts

JOBBING DISTRIBUTING ORGANIZATION FOR PRODUCTS OF THE SPRAGUE ELECTRIC COMPANY

<u>JJR</u>

#### 50 YEARS OF PROGRESS WITH KESTER SOLDER

The present type of cored solder used by industry was first made by J. F. Kester in 1899. From the simple beginning of its first application . . . a few soldered connections in the old hand-crank telephone . . . it has continued to grow by keeping pace with new techniques as demanded by industry. Today's modern production would not be possible without cored solder.

## Standard for Industry and Home Since 1899





RADIO-TELEVISION — The early commercial amateur. and pro fessional builders of radios accepted Kester Rosin-Core Solder as standard. Then as now, Kester still leads in this field.



AUTOMOTIVE — Ever since its inception Kester Acid-Core Sol der has been and still is the standard in the automotive field and for the trade. Mechanics and repairmen insist upon it.



ELECTRICAL-ELECTRONIC – Kester makes a great variety of "specialized" core solders and solder preforms—even those suitable for the fine touch required in electronic work.




of KESTER
Flux-Cored
SOLDER



AGRICULTURAL—For a half century Kester Cored Solder has been the farmer's standard for maintenance and repair. He uses Kester because his soldering must be fast and reliable.



HOMECRAFT—In hobbycraft as well as home repair, good sol der bonds are essential. Kester Metal Mender and Radio Solder are the standards for all homecraft workers.



INDUSTRIAL—Kester Cored Solders have met every requirement for the past half century. They have earned the reputation for and are recognized as standard for industry.

Free —Technical Manual. Send for Kester's new 28-page manual. "Solder and Soldering Technique." A complete analysis of the application and properties of soft alloys and soldering fluxes.



#### KESTER SOLDER COMPANY

4201 Wrightwood Avenue, Chicago 39, Illinois FACTORIES ALSO AT NEWARK, NEW JERSEY • BRANTFORD, CANADA

# Cash in - on the PHILCO LP RECORD PLAYER



# TREMENDOUS NEW PROFIT OPPORTUNITY FOR RADIO SERVICEMEN

Here's a brand new avenue to big profits for radio servicemen everywhere! Yes, every service customer is a prospect for the revolutionary new Philco M-15 record player that equips any radio or phonograph, old or new, to play the amazing 45 minute non-breakable Vinylite records.

Now...start at once making these big, extra profits on service calls...

- 1. Profits on sales of the Philco M-15.
- **2.** Profits on installing jacks in customers' radios and phonographs. A simple, easily installed jack is all they need to plug in and play the Philco M-15.

Get the facts about this red hot, nationally advertised Philco product.

Millions want it! See your Philco Distributor today!

# Build YOUR OWN TEST EQUIPMENT

# Heathkit ELECTRONIC SWITCH KIT DOUBLES THE UTILITY OF ANY SCOPE

two separately controllable fraces adividual inputs on any scope.

See both the input and output traces, locate distortion, phase shift, etc., immediately.

Individual gain controls and positioning control. Coarse and fine sweeping rate cantrols. Complete Heathkit matches others, with 5 tubes, All metal parts are punched, farmed and cadmium plated. Complete with tubes, all parts, detailed blueprints and instruc ns, Shipping Wt. 13 lbs.

Nothing ELSE TO BUY

#### HEATHKIT CONDENSER CHECKER KIT

\$ 7 9 50

Nothing ELSE TÓ BUY



condenser checker anyone can afford to own. Measures capacity and leakage from .00001 to 1000 MFD on calibrated scales with test voltage up to 500 volts. No need for tables or multipliers. Reads resistance 500 ohms to 2 megohms. 110V 60 cycle transformer operate. A condenser checker anyone can afford

60 cycle transformer operated complete with rectifier and magiceye indicator tubes. Easy quick ossembly with clear detailed blueprints and instructions. Small convenient size 9" x 6" x 474". Wt.4 lbs.

#### HEATHKIT SIGNAL GENERATOR KIT



NOTHING ELSE

Every shop needs a good signal generator. The Heathkit fulfills every servicing need, fundamentals from 150 Kc. to 30 megacycles with strong harmonics over 100 megacycles covering the new television and FM bands. 110V 60 cycle transformer operated power supply.

400 cycle audio available for 30% modulation or audio testing. Uses 6\$N7 as RF oscillator and audio amplifier. Complete kit has every part necessary and detailed blueprints and instructions enable the builder to assemble it in a few hours. Large easy to read calibration. Convenient size 9" x 6" x 4\%". Wt. 4\% lbs.

#### HEATHKIT SIGNAL TRACER KIT



Nothing ELSE TO BUY

RACER KIT

Reduces service time and greatly increoses prafits of any service shop. Uses crystal diode to follow signal from antenna to speaker. Locates faults immediately. Internal amplifier ovailable for speaker testing and internal speaker available for amplifier testing. Connection for VTVM on panel allows visual trocing and goin measurements. Also tests phonagraph pickups, mitrophones, PA systems, etc. Frequency range to 200 Mc. Complete ready to assemble. 110V 60 cycle transformer operated. Supplied with 3 tubes, diode probe, 2 color panel, all ather parts. Easy talassemble, detailed blueprints and instructions.

Small portable 9" x 6" x 434". Wt. 6 pounds. Ideal for taking on service calls. Complete your service shop with this instrument.

#### HEATHKIT SINE AND SQUARE WAVE AUDIO GENERATOR KIT

The ideal instrument for checking oudin amplifiers, television response, distortion, etc. Supplies excellent sine wave 20 cycles to 20,000 cycles and in addition supplies square wove over same ronge. Extremely low distortion, less than 1%, large calibrated dial, beautiful 2 color panel, 1% precision calibrating resistors, 110 V 60 cycle power transformer, 5 tubes, detailed blueprints and instructions, R.C. type circuit with excellent stability. Shipping weight 15 pounds



ELSE TO BUY

#### THE NEW HEATHKIT VACUUM TUBE VOLTMETER KIT

The most essential tool a rodio man con have, now within the reach of his pocketbook. The Meath-kit YTVM is equal in quality to instruments selling for \$75.00 or more. Features 500 microomp meter, transformer power supply, 1% gloss enclosed divider resistors, ceramic selector switches, 11 megohms input resistance, linear AC and DC scole, electronic AC reading RMS. Circuit uses 65N7 in balanced bridge circuit, a 6H6 as AC rectifier and 6 x5 as transfarmer power supply rectifier. Included is means of calibrating without standards. Average assembly time less than four pleasant hours and you have the most useful test instrument you will ever own. Ranges 0-3, 30, 100, 300, 1000 volts AC and DC. Ohmmeter has ranges of scale times 1, 100, 1000, 10M and 1 megohm, giving range .1 ohm to 1000 megohms. Complete with detailed instructions. Add postage for 8 lbs.



Nothing ELSE TO BUY

#### HEATHKIT FM AND TELEVISION SWEEP GENERATOR KIT



\$24.50

NOTHING ELSE TO BUY

#### THE BASIC FM AND TELEVISION SERVICE INSTRUMENT

At the lowest cost possible, anyone can now FM and television receivers. The Heathkit sweep generator kit operates with oscilloscope and covers all necessary frequencies. A few pleasant hours assembling this kit puts any organization in position to share the profits of the FM and TV boom.

Every part supplied — grey crackle cabinet, two color calibrated panel, all metal parts punched, formed and plated. 5 tubes, complete detailed instructions for assembly and use. Shipping weight 6 lbs.

#### The NEW 1948 HEATHKIT 5 INCH OSCILLOSCOPE KIT



NOTHING ELSE TO BUY

New improved model of the famous Heathkit Oscilloscope, Building on oscillascope is the finest training for television and newer servicing technique and you save two-thirds the cost. All the features and quality of instruments selling for \$100.00 ar more. Supplied complete with cabinet, two color panel, 58P1 tube, 2 5Y3 tubes, 2 6SJ7

tubes and 884 sweep generator tube. Power transformer supplies 1000V negative and 350 volt positive. Sweep generator 15 cycles to 30 M. cycles. Has vertical and horizontal amplifiers. Oil filled filter condensers for long life. Complete blueprints and instructions included.




### The

... BENTON HARBOR 10.

MICHIGAN



# SYLVANIA ADVERTISING HELPS SERVICE DEALERS INCREASE THEIR SERVICE BUSINESS!



# APRIL CAMPAIGN IS NOW READY.

- 3 Postal Card Mailings—one for each month.
- 3 Window Displays one for each month.
- 3 Window Streamers one for each month.
- 6 Newspaper Ad Mats—two sizes for each month.
- Radio Spot Announcements—several for each month.

#### SEND FOR FULL INFORMATION NOW!

Remember, this campaign designed for your use ties up directly with Sylvania's ad campaigns on a national scale. You pay only the postage on the government postal cards you mail. Sylvania supplies everything else free! Mail coupon today!

# SYLVANIA ELECTRIC

LAMPS, FIXTURES, WIRING DEVICES; LIGHT BULBS; PHOTOLAMPS

	Myore Radio Service Co.
Sylvania Electric Advertising Depo Room R-2001 Emporium, Pa.	
Centlemen: Please April Service Dealer	send me full details an your February, March and Campaigns.
Nome	
Campany	
Address	
City	Zone
State	



Reputation is not built overnight! Radiart's reputation has grown over the years because of its many points of superiority! Beyond the fact that the quality and design of every one of the 82 types of Radiart Vibrators . . . is beyond compare . . . the solid completeness of the line makes them the favorite wherever good vibrators are sold FOR MOST EVERY NEED TO ORIGINAL SPECIFICATIONS . . . there is a CORRECT Rodiart replacement vibrator! NO OTHER VIBRATOR MANUFACTURER CAN MAKE THAT STATEMENT! Guess work is eliminated . . . all good jobbers carry most all numbers in stock . . . if your jobber does not have the number you want . . . he can get it, FAST . . . as special orders are given speedy attention . . . with immediate shipment of his order! Insist on Radiart for the EXACT REPLACEMENT Vibrator . . .



IT'S RIGHT WHEN IT'S RADIART

**LEADING THE FIELD SINCE 1935** 

## THE RADIART CORPORATION

CLEVELAND 2. OHIO

**EXPORT...SCHEEL INTERNATIONAL... CHICAGO 18, ILLINOIS** 

TV Test Equipment that covers all present and future bands.

The Mega-Sweep, a high quality instrument, is now being used by these and other leading manufacturers.





THE MEGA-PIPPER

Precise crystal positioned marker generator. Used with the Mega-Sweep, the Mega-Pipper generates four sharp marker pips which are displayed on the response curve on the oscilloscope. These pips appear simultaneously at sound and picture i.f. carrier and adjacent sound and picture i.f. carrier frequencies. Pips are applied directly to oscilloscope and do not disappear when tuned into traps. Fast, precise tuning of traps and positioning of i.f. characteristics possible. Plug in crystals make it possible to change Mega-Pipper to any i.f. frequency in the RMA bands.

Price \$150.00 f.o.b. factory



THE MEGA-SWEEP

Expert opinion says, "Yes, you must have a Sweeping oscillator to do TV service work." Why not buy the best and assure the best quality work. The Mega-Sweep is the only sweep capable of operation in the UHF-TV bands now being discussed. Wide Sweep (up to 30 mc) continuously variable attenuator with flat frequency response, low amplitude modulation while sweeping. The sawtooth type sweep is entirely electronic. Only one r.f. sweeping voltage in output. No spurious signals, no phasing or synchronizing problems.

Price \$395.00 f.o.b. factory



THE MEGA-MARKER

Experts say, "A marker is essential for use with your sweeping oscillator." The Mega-Marker is a precision variable oscillator (accuracy 0.25%) which operates with the Mega-Sweep. Crystal oscillator (4.5 mc) included for calibrating instrument's variable oscillator and supplying accurate marker for lining up video sound trap and intercarrier i.f. and discriminator. Includes output amplitude control, provision for mixing Mega-Sweep and Mega-Marker outputs for application to the receiver under test.

Price \$60.00 f.o.b. factory




THE MEGA-MARKER SR.

This unit provides a crystal controlled high accuracy (0.01%) sound r.f. carrier for each of the twelve television channels. The carriers can be used tone modulated or unmodulated by setting a panel switch. Includes amplitude control and switched channel tuning. Contains independent power supply and can be used either with Mega-Sweep or as an independent test instrument for tuning TV receiver local oscillator on all twelve channels.

\*\*Price \$195.00 f.o.b. factory\*\*

WRITE FOR FULL SPECIFICATIONS

KAY ELECTRIC CO., 24 Maple Ave., Pine Brook, N. J.



# Audio Systems in FM

In the servicing of modern f-m receivers, the radio service technician has found a new opportunity for profit. At the same time, however, he is dealing with a new kind of customer. Many of the owners of f-m receivers are severe critics of the quality of reproduction available from these receivers. They have been taught that f-m reception should be nearly perfect and, since they have been induced to buy their receivers on that premise, certainly no one can blame them for expecting the best.

We know that f-m reception can be so good that it will delight even the most fastidious ear. At the same time, we know that much of the f-m receiving equipment commercially available does not even pretend to provide any more than part of the advantages of the f-m system of communication. However, confusion between claims for the performance of very elaborate expensive receivers and the small compact types often leads to a misconception of the quality to be expected from the latter.

Although maladjustments of the r-f and i-f sections of the f-m receiver can cause distortion, with reasonable care almost any standard tuning section (in a receiver or as a separate unit) can produce an audio output signal with a high degree of fidelity. The quality of the acoustic output (sound waves) from the loud-speaker is largely determined in practice by the characteristics of the audio frequency section, including amplifier stages, tone and compensation controls, and the loudspeaker unit or system.

by J. Richard Johnson

Continuing our series on f-m servicing with a discussion of high fidelity performance in the acoustic output of the f-m receiver

It is by a proper knowledge of this portion of the receiver that the servicemen can judge what should be expected in the way of high quality reproduction. He is then in a position to advise the customer as to whether his receiver is performing properly and to check the condition of service jobs as they leave the shop.

Accordingly, before we continue with our detailed circuit analysis of the a-f amplifier sections of f-m receivers, we will consider in this article what we really mean by "good quality" and "high fidelity" so that the circuit features we will discuss in later articles will take on their full meaning.

#### What is High Fidelity?

F-M has brought the fidelity of reproduction possible to such a point that people's personal, biological, and psychological reactions play an important part in the determination of whether their reaction is favorable. The scientific factors involved affect different people differently. However, it has been found that people are rapidly becoming educated to high fidelity. At one time it was felt that

the average listener would not appreciate good fidelity; the very favorable response to high fidelity f-m receivers has proven, however, that this idea is wrong and that all that is needed is a certain amount of contact with good quality for full appreciation.

Let's consider the technical features of high fidelity. With the great amount of emphasis that has been placed on frequency response, one might be led to believe that if a system has a wide frequency response, high fidelity is assured. Nothing is further from the truth. In fact, attempts to increase the range of frequencies fed through an amplifier often result in much poorer quality, because high frequencies are more subject to distortion effects than low Actually, there are frequencies. several factors, all of which determine fidelity.

The measure of fidelity, is the degree to which the sound waves reaching the listener's ears are identical to those produced in the studio of the broadcasting station. As we will see later, parts of may actually be designed to distortion (modification of to compensate for other parts, but the ultimate objective is the same.

The basic electrical factors involved in high fidelity are as follows:

#### **Harmonic Distortion**

1. A minimum of harmonic distortion. Harmonic distortion manifests itself as a change of the wave form of the audio frequency voltage being amplified, the wave form change being due to its passage through the system. Harmonic distortion is, of course, a factor to be considered in both a-m and f-m receivers, but the added frequency response range desired makes it more important in f-m receivers.

All distorted or undistorted wave forms can be considered as composed of pure sine wave components, even though (as in ordinary practice) the distortion has not come about by actual addition of any signals to the desired one.

Fig. 1 illustrates one way in which harmonic distortion can be introduced in the audio amplifier section of a receiver. In this example, the bias resistor has dropped to too low a value and the input signal is too strong, producing distortion of the wave form as shown at the right (output circuit). Of course, in practice a *complex* wave form is handled because of the many components contained in voice and music waves, but the effect can be more clearly seen by using the sine wave signal of Fig. 1 for testing.

That the distorted wave form of Fig. 1 is the same as an undistorted wave with harmonics added is illustrated in Fig. 2. This graph shows that the fundamental sine wave A combined with a certain quantity of third harmonic (signal having a frequency exactly three times that of wave A) wave B, produces a distorted wave similar to that of the output signal in Fig. 1.

Thus, even though in the example of Fig. 1 no additional signals are added, harmonic signals are actually created because of the non-linear nature of the amplifier response. This non-linear response is due in turn to the improper bias (in this particular case).

Harmonic signals are signals having a frequency which is any whole multiple of the frequency of the fundamental, or main signal. When harmonic components which were not in the original desired signal are added by its passage through an amplifier, that amplifier is said to introduce harmonic distortion.

Harmonics are rated by the percentage of their voltage compared to the voltage of the main, or fundamental signal. Until recently, it was felt that harmonic distortion could not be detected by the listener until




Fig. 1 How harmonic distortion is produced in an amplifier tube by maladjustment of circuit voltages, as shown in the waveform (right). Here, distortion is produced by an input signal which is too strong and a bias resistor which has too low a value




Fig. 2 The above graph shows that the addition of a third harmonic frequency (Wave B) to a fundamental sine wave (Wave A), can produce distorted signals. Note that the distorted wave form shown here is very similar in shape to that produced in Fig. I





Fig. 3 Illustration of production of intermodulation distortion when two or more waves of different frequencies pass through an amplifier with a non-linear input-output voltage amplitude characteristic. Only two of the input signal components are shown

→ To page 24



# TV TUNING SYSTEMS

by John B. Ledbetter

You have to understand them in order to work on them efficiently

I N ANY receiver, efficiency in the tuning system or "front end" is extremely important. This is especially true in television receivers, which must have a practically uniform response over a very wide range of frequencies (44 Mc to 216 Mc), while maintaining a 4.5 Me band width for each of the 13 television channels. In this article we will discuss the various types of tuning systems which have been developed to meet

these requirements and some of the problems involved in their development.

### Fundamental Circuit Requirements

Briefly, here are some of the requirements a good television tuning unit must meet in order to give satisfactory service: (1) a high signal-to-noise ratio, (2) an i-f bandwidth of 4.5 Me. (3) high gain in the r-f

and i-f stages, (4) good oscillator stability, (5) lack of microphonics in the tubes and tuning controls, (6) suppression of images, re-radiation from the oscillator, etc. There are a number of other considerations which must also be satisfied in a good television tuner, but these become rather involved technically, and are beyond the scope of this article. We are more concerned with the way in which the requirements listed




Fig. 1 Schematic diagram of Sarkes Tarzian TT 2 tuner, using a 300-ohm input feeding into 68H6 pentode r-f stage




Fig. 2 This Sarkes Tarzian television tuner, a typical low cost unit, uses a simulated transmission as the tuning element




Fig. 3 Above is RCA tuner, using variable-inductance tuning. In such systems, highest frequency coil must be aligned first




Fig. 4 Philco tuner shown features removable interchangeable coils and provides 8 channel coverage. Coils snap in place

above are met, since the majority are problems which affect the operation of every receiver, television or otherwise.

There are a number of ways in which these requirements can be satisfied. Actually, a good receiver engineer can produce a television tuning system which would outperform anything now being mass-produced, as far as operation is concerned. Such a unit, however, generally would be prohibitive in cost and would necessarily have to be custom built. In practice, such factors as price range, ease of assembly, adaptability to mass production, etc., must be taken into consideration and the tuning system worked out accordingly. Since there is always more than one solution to every problem, different receiver engineers have come up with their own pet systems.

Simply, here is how some of the front-end problems are solved: The


signal - to - noise ratio can be made high by using a good r-f circuit and employing a high-frequency pentode such as the 6AU6 connected as a grounded-grid triode. Grounding the grid prevents oscillation in the r-f stage by isolating the output circuit from the input. This not only makes the tuning circuit more stable, but at the same time prevents oscillator re-radiation into the antenna system via the r-f stage. Operating a highgain pentode as a triode, also cuts tube noise in half without reducing the gain of the stage. Oscillator harmonics, images, etc., as well as oscillator radiation, can be eliminated or kept very low by building the tuner around a good r-f stage and employing a sufficient number of i-f stages. Gain, band width, and microphonics, too, can be controlled by careful selection of tuned circuits and the types of tubes to be used in each stage. In most tuners, oscillator

drift is compensated by using an oscillator series condenser having a negative coefficient.

#### Methods of Tuning

Basically, tuning in all receivers must be accomplished by varying either the capacity or inductance, or both, in the r-f detector and oscillator circuits. Various combinations may include permeability tuning, switch-type inductive tuning, continuously - variable inductive tuning, and either switch-type or continuously-variable capacity tuning.

Ordinarily, losses in a switch-type inductance - tuned circuit would be excessive, due to contact resistance of the switch blades and distributed capacity in the selector switch and coil leads. In practice, however, this advantage is offset by placing all coils in each respective circuit in series and making each section operate as a quarter-wavelength trans-



The "Inductuner" shown above makes possible a continuous tuning r-f front end. It is used in Allen B. DuMont receivers




Fig. 5 A typical circuit for use with the "Inductuner". It provides continuous coverage for the 44-216 megacycle band




Fig. 6 The Motorola tuner circuit, shown above, utilizes pre-tuned trimmer condensers to cover Channels 1 through 6. Channels 7 through 13 are tuned by using fixed capacitors and factory-set slug-tuned coils

mission line at its proper channel frequency. All unused sections of the line are shorted.

#### **Capacity Tuning**

Some of the advantages of capacity-tuned systems are: simplicity, low cost, long life, troublefree service, and easy to produce. Disadvantages include: common coupling between gang sections, excessive stray capacities, rotor contact resistance, large size, and a tendency to be microphonic in operation. These problems have been overcome in several low-cost tuners, however, and operation seems to justify the use of capacity tuning. General Instrument Corporation, for instance. uses two separate condensers, each with three push-pull sections, ganged to a common shaft. One condenser tunes the 54-88 Mc band (disregarding Channel 1), and the other covers the 174-216 Mc range. Fine oscillator adjustment is accomplished by a vernier condenser operated from a concentric shaft on the regular bandswitching shaft. Link-coupling for each band simplifies r-f adjustments. Only two adjustments are required.

This tuner uses an untuned input feeding into a 6]6 twin triode operated as a double-tuned push-pull r-f stage. A 6]6 converter, with push-pull grids and parallel-connected plates allows working into either a single or double tuned i-f coil. Link coupling is also used in the oscillator stage.

#### Inductance Tuning

Advantages of variable-inductance tuning are: improved "Q," low distributed capacity, increased tuning range, minimum of coupling between stages, freedom from microphonics, increased efficiency, and better stability.

Many receiver manufacturers use some form of switch-type inductance tuning, employing a simulated transmission line as the tuning element. The Sarkes Tarzian TT - 2 tuner (Fig. 1 and 2) is typical of a low-cost tuner of this type. Individually-tuned series inductances are arranged to form a parallel-wire transmission line, whereby a quarter-wave section is switched into the circuit for each channel. Switching is accomplished by a shorting-bar type rotary selector switch. This tuner uses a 300-ohm input feeding into a 6BH6 pen-

tode r-f stage. The plate of the 6BH6 and the grid of the 6AG5 mixer are inductance-tuned successively from Channel 13 to Channel 1. The 6C4 oscillator has adjustable inductances for each channel and a small variable capacity for fine tuning.

A similar system is employed by RCA (Fig. 3). In both the above tuners, the highest-frequency coil must be aligned *first*, progressing in order to the lowest-frequency coil. The RCA tuner uses 6]6 double triodes in the r-f, converter, and oscillator stages.

#### Switch-Type Inductance Tuning

This method of tuning differs from the above only in that *separate* coils are used for each channel. Phileo, for instance, employs an 8-position turret-tuner into which coils for any 8 channels can be snapped. Use of the turret (Fig. 4) allows extremely short leads and low distributed capacity. In Phileo's system, the mixer and oscillator coils are located in the front section of the turret drum. R-F and antenna coils are in the back section. Oscillator a.f.c. and a.v.c. for picture and sound circuits is also included.

#### **Continuous Inductance Tuning**

A continuously-variable inductance system has these advantages; minimum distributed capacity, since no switch contacts are present; minimum of mechanical operation and microphonic tendencies; and longer life. DuMont and Transvision, Inc., employ the "Inductuner" (Fig. 5) as their basic tuning system. The "Inductuner," which consists of three separate variable inductance units ganged on a common shaft, covers a continuous range of 44 Mc to 216 Mc. The "Inductuner" is highly accurate and capable of good mechanical and electrical stability.

#### Switch-Type L/C Tuning

Motorola (Fig. 6) uses a combination L/C arrangement to cover both television bands. Pretuned trimmer condensers are used to tune the low-frequency winding for Channels 1 through 6. High-frequency Channels 7 through 13 are tuned by effectively shorting the low-frequency winding (LFS) out of the resonant circuit by connecting C11, C10, and C9, respectively, across it. By using these condensers in a series-resonant circuit, a more effective short of LFS can be obtained than by grounding various turns through a band switch. C2 is permanently connected across LFS to aid in shorting it above Channel 6. Damping resistors R1 and R2 are used to obtain a constant input impedance. The double-tuned 6AG5 r-f stage is inductance slugtuned by L1 through L26. C18 and C19 help maintain a constant 4.5 Mc bandwidth and are made an integral

→ To page 29




Fig. 7 The Belmont tuner shown above utilizes continuous permeability tuning.

A mechanical system automatically stops at each station



A DVERTISING plays an important part in our national economy, It is a vital factor in the welfare of any business, and the more we know about it, the more successful our business enterprises will be.

In order to help radio servicemen with their business promotion, Radio Maintenance is presenting a series of articles on the subject, of which this is the first. In this series we will endeavor to give radio servicemen a complete outline of advertising principles and practice. We will try to answer all your questions on the subject, and present a clear picture of the benefits of advertising. In the course of the series you will find detailed plans for tested and proven advertising campaigns.

Our aim is to help you make more money—which you certainly will by advertising, if you are not already doing so. If you do advertise, you will find in this series many helpful pointers on how to improve your program.

#### **Importance of Advertising**

First of all, we want to stress the necessity of advertising in some form. No matter how small your shop or how small a community you're located in, advertising is a must.

Despite the fact that America is the most advertising-conscious country in the world, thousands of businessmen in all trade do *not* advertise, and do not reap the benefits of ad-

#### by Victor M. Turner

Advertising Manager, Radio Maintenance

vertising. Among these non-advertisers, we're sorry to say, are quite a few radio servicemen.

If you fail to advertise, you're throwing away dollars—dollars in profits that should be yours.

"O. K." says Joe Doe who makes only twenty-five bucks a week in a hamlet in the hinterlands, "where do I get the money to spend on advertising?"

The answer is that advertising is not necessarily expensive to inaugurate. There are two highly effective means of advertising which cost next to nothing one: your classified telephone directory. If you're not in it with the minimum line or more, you're just plain batty. For only a few dollars extra, the phone company will list your name and services in bold-face type.—Two: penny postcards. A hundred cost only a dollar and if you haven't the cash to pay for printing write your message on each one yourself. Personalized messages are powerful. Direct-mail or-

"It pays to advertise."

Yes—you've heard that timeworn slogan before and you'll
hear it again. It's always quoted
because it's always true

ganizations have gone to painstaking lengths to develop reproduction processes which make it possible to turn out mass letters that appear to be individually typed and signed.

In addition, many of the manufacturers whose lines you carry provide free advertising and selling aids in all forms. You should take advantage of the opportunities they offer.

There are many other low-cost ways of advertising. We will present them in detail later.


#### Your Market is not Saturated

Along about there our struggling friend (and others who are in a better-than-struggling position) may ask: "But where should I mail these things? I'm in a district where everyone knows me—I'm the only radio serviceman in these parts. They have to come to me!"

To that we can smugly say, "Not so, brother, not so!"

You must advertise not bring in new customers, but to prod the old ones into action. For example: Do you know of someone who owns an extra radio receiver which is not working and which will remain that way until the receiver they are now using fails. The proper kind of advertising can induce them to get the extra set fixed now. Why do you suppose the old family dentist keeps sending out those little "reminder" cards?

These two examples are the extreme cases, but they serve to defeat two inevitable arguments against ad-



The first principle of successful advertising is to get your customer's attention

vertising used by small business men. Fortunately, most servicemen are above the \$25 a week Joe Doe class, but far too many will still say they "can't afford" to advertise when actually they can't afford not to! While the majority of servicemen is up against competition of varying degrees in their neighborhoods, here again too many feel they've built up as much business as the area can provide. Oh, how wrong they are!

### The Strongest Weapon in Competition

When it comes to real competition in the bigger towns and cities, advertising can very well mean the difference between staying in business and being forced out. When there are three or four other independent servicemen on the same street, plus multiple-product retailers and department stores who send out their own radio servicemen, the guy with the good ad in the newspaper and/or the

smart mailing piece will be the one making the most money. It isn't enough to give better service, because people won't know you're better unless you get them to try you out.

So much for those who are not advertising. Now let's meet another radio serviceman who has this to say:


"I have tried advertising, but it doesn't seem to do any good!"

This is a typical state of mind with many men who have small business establishments. It brings up the problem of effectiveness in advertising and how to *check* the results of this advertising.


#### Don't Form Hasty Conclusions

Our serviceman is probably wrong in saying the advertising doesn't do him any good. His ad, whether it was in the daily paper or in the form of a mailing piece, probably carried a message that said (in general): "I do reliable, high-quality repair work. Try me when your radio needs fixing." This advertising is low-pressure and will not induce immediate action on the part of the recipient. The serviceman does not know whether his ad is bringing in customers or not, and he is making a mistake if he swears off advertising. An immediate check on your advertising's effectiveness can be made by inserting a "hook" of some kind, such as a limited time special offer. Later on in this series of articles, we will explain in detail the various ways to check the returns on your promotion.

Perhaps our disillusioned friend is right when he says his ad didn't do him any good. It may have been a very poorly planned promotion piece that had no effect on anyone. But if it was, he should find out just what was bad about it and then make up another ad that is effective. There never is any case where advertising, properly done, is wasted effort. We intend to show you specific examples



Then impress your name upon him, as often and in as many ways as possible



Tell a convincing story to get the confidence and trust of your customer

of good and bad advertising, for we realize that proper advertising makeup is a tough job. There's no disgrace in having put out an ad or even a complete campaign that was a flop. Failing to learn from your mistake is, however, a cardinal sin. A lot of money can go down the drain on poor advertising, but there seldom is an ad that didn't benefit the advertiser in some way. One thing, though, is sure—NO advertising brings in NO business.

#### Rare Cases— But There are Some

Since we are now living in a prosperous time, there may be some servicemen who are working to their present capacity. Hence they may feel that they cannot handle more work and therefore should not advertise for more.

As this article is not one on business management, we won't attempt to tell you how and when to expand, but we do want to say this: Allow-

ing business to be turned away for lack of help or operating space is a poor policy. Make a careful estimate of how you can branch out without taking much of a risk-then advertise for the new customers. When the lean times comes, the individual customer will let his minor repairs go, so there will be fewer calls from him. He'll wait longer before buying that new set, so you won't make as many sales to him. That's when a longer list of clients will mean that you can take up some of the slack. Don't let any opportunity for establishing yourself securely go by!

We've focused our attention on some of the more obvious reasons for advertising. Now let's look into some of the longer-range advantages derived from it.

#### Look at Your Neighboring Businessmen


There's a lot of concrete evidence available to show the radio servicing trade as a whole why it should do much more advertising than it does. This evidence can be found right in your own neighborhood. Just take a look around.

See that big super-market? Food is something people have to buy whether it was promoted or not. True! But some of the food retailers were not content to sit around and wait for the customers to arrive. They took to full-page advertising in the local press, and now these retailers have expanded from little holes-in-the-wall grocery stores to the huge, modern markets with customers and money rolling in.

And take a look at the auto-parts stores. Through smart merchandising and consistent advertising in the daily papers these tradesmen have built up big volume businesses.

There are lots of others—clothing stores, furniture dealers, department stores—all of which advertise heavily. In 1947 almost four billion dollars was spent for advertising in

To page 27




And keep reminding him, day after day, week after week, season after season

# ROOF TO RECEIVER, OVER

by C. T. Josephs

With installation of television receivers, a means of roof-receiver communication is needed. The author tells us how he solved this problem.



WITH the event of television, there arose a great need for a communication system between the roof and receiver for the many installations required. Hence, servicemen have tried and are using many schemes. Some use Walkie-Talkies, battery or electric inter-coms, battery powered phones, etc. One of the simplest methods is the use of the sound-powered phone set used by the Navy in the last war. These phone sets do not require any battery power and can be purchased in most surplus stores. This system, however, has a disadvantage in that sufficient two-conductor cable or line must be carried by the serviceman in addition to all the other equipment necessary on an installation job. Often, the cable gets tangled and brings forth some incoherent language because, as a rule, the serviceman does not wind the cable into a neat coil or on a small reel after each job.

Having a couple of ordinary

a scheme to use these and eliminate the inter-connecting leads usually required. This method proved quite satisfactory by using two ordinary blocking coils, and two 1.5 volt flashfrom the antenna to the receiver is used as the inter-connecting cable or leads. The connection of these units is shown in Figure 1. The blocking coils are hand wound on a 1/2 watt, 1 megohm insulated type resistor. Seven turns of #18 enamel covered wire are equally spaced on the body of the resistor and the ends are soldered to the pigtails of the resistor. Two of these coils are soldered permanently in series with each lead from the phone to be used on the roof and the lose ends of the leads are provided with alligator clips. The parts at the receiver end (shown in the dotted lines) are combined into a small box with proper clips to hold the flashlight cells. The box is provided with the four terminals required, that is, two terminals for the line to the roof and two terminals for a short line to the receiver.

If a set of sound powered phones can be purchased, the system will become simpler. The flashlight cells and the blocking condensers which blocked the 3 volts d.c. from the receiver, are no longer required. Therefore, the box to house these parts is also not required. The coils may be soldered into the phone leads as previously performed on the other phone and the leads similarly provided with alligator clips. In this case, all the serviceman has to carry for his intercommunication system is a set of sound-powered phones provided with the blocking coils.

The author has found that the system described here is very simple to operate. It has proven of great value in the actual installation of TV antennas by considerably simplifying the problem of Roof-to-Receiver communication.





Fig. 1. Circuit of roof-to-receiver communication systems.





by John T. Frye

JUST how much electric current do you think is necessary to cause death? It really does not matter what you think, except that the wrong idea may be leading you to be careless with voltages that are potentially deadly. What does matter is this fact agreed upon by the medical fraternity: Any current from seventy to ninety milliamperes or above may cause death

That is not very much, is it? It is less than the current requirements of a =47 pilot lamp. Any receiver you put on your bench, be it an ac-de midget, a three-way portable, or a chassis from a standard console can supply this much lethal current without straining itself.

The amount of current that passes through your body is a function of the applied voltage and the skin resistance. Dr. George 1. Nichols, the cardiologist, says that skin resistance varies from as low as 300 ohms when drenched with sweat, to as high as a megohm. The average resistance is around 5,000 ohms.

Using that 300 ohm value, Ohm's law will tell you that twenty-one volts could drive the deadly seventy mils through your body. You do not service many receivers that do not have at least twenty-one volts running around loose in them, do you? Even the smallest hearing aid battery can provide this much voltage.

The serviceman should let these facts sink into his mind, for they should make him realize that every set he places on his bench could kill bim. Working, as he does, with electricity every day, he is likely to become careless. It is the old story of "familiarity breeds contempt." He laughs about being bitten, not realizing, apparently, that one of those bites could be as deadly as that of a cobra.

Let me earnestly urge you right now to make yours a "safe" service bench. First, do not work on a cement floor. If the floor of your shop is cement, see to it that the place where you stand when working at the bench is covered with a good insulating material, such as rubber. Remember that one side of the 110 volt line is grounded; so if you are standing on a cement floor, all you have to do is touch the hot wire of the a-c input and your body will be bridged right across the line.

Use an isolation transformer between the line and the set upon which you work. This will give you added protection against one of those hotwire-to-ground electrocutions, and it will also have other advantages when working with ac-de sets. Make sure that none of your service tools, such as electric drills, service lamps, soldering irons, etc., have their frames grounded to one side of the line cord. A few minutes of checking with the ohmmeter can set your mind at rest

on this score.

See to it that all of the power to the bench is cut off by a single, easilyaccessible switch. Recently I saw a setup that I particularly liked. The power switch was mounted on the wall at one end of the bench, and a strong cord ran from the handle of this switch through screweyes along the whole front edge of the bench. When the switch was closed, all of the slack was taken out of the cord; so in case of an emergency, a single tug at this cord from any position along the bench would cut off the power. Since two men normally worked at this bench, if either were frozen by the grip of an electric current, the other could release him without any loss of precious time. Furthermore, if a set were dragged from the bench, in falling it would cut the current.

With the advent of television, the serviceman is encountering dangers even greater than those to which he bas been exposed. Many TV receivers have potentials well above those used on an electric chair. In fact, the potentials are so high that insulation which ordinarily provides a good margin of safety against shock can no longer be depended upon to do this. Special probes are necessary, and the use of a good pair of lineman's gloves when working on such a set is no affectation.

In addition to looking out for his own safety, the serviceman has a very definite responsibility to protect his customers against accidental shock. They are admittedly ignorant about things electrical, and they depend upon him to see to it that their receiver not only plays well, but that it is also safe to use.

In general, line cords that are fraved or on which the rubber insulation has deteriorated should always be replaced. When replacing parts, no unprotected high-voltage point should be allowed to appear above the chassis or at any other place where it can be reached with the chassis in position in the cabinet. Women will dust the back of receivers with the power turned on. (One told me she could see better when the pilot lamp was burning!)

AC-DC sets are particularly dangerous because of the fact that the B-minus point—often the chassis—is tied to one side of the line. This means that the full line voltage may appear between the chassis and the ground. Under such conditions, any exposed bit of metal that is connected to the chassis is a source of danger. This includes protruding set-screws of dial knobs and chassis mounting bolts that are not covered with insulation.

Whenever possible. I see to it that every ac-dc set that leaves my shop has push-on knobs; and if set-screws knobs have to be used, they are of the type in which the set-screw is well down in a hole in the knob. High-voltage tape is used to cover exposed chassis-mounting boltheads, A cardboard rear cover is alreavs in

-→ To page 29



## Notice to Service Organizations!

#### RADIO MAINTENANCE Magazine Special Group Plan

Radio Servicemen enrolled in service trade organizations may subscribe to RADIO MAINTENANCE at a special Group Plan price, WRITE US FOR PRICES, Here's how it's done:

- 1. Offer open to members of Radio Servicemen's Associations, societies or organizations.
- 2. Applies to all orders from these organizations containing fire or more names.
- 3. Orders must be on the organization letterhead and must give the name and address of each subscriber. State subscriber's service status (is he a shop owner, employee of service department, service manager, etc?) Magazines will be delivered to subscriber's address.
  - 4. Payment must accompany each order.
- 5. If a serviceman already has a subscription be may renew it through this group plan, but be sure to mark plainly "RENEWAL" in these cases.
  - 6. Address all orders to:

RADIO MAINTENANCE Magazine, 460 Bloomfield Ave., Montclair, N. J.



See Your Jobber


TWO COMPLETE FACTORIES TO SERVE YOU PIONEER MANUFACTURERS OF PERMANENT MAGNET DYNAMIC TRANSDUCERS

**PERM**FLUX

WRITE FOR

4900 W. Grand Ave., Chicago 39, Ill.

236 S. Verdugo Rd., Glendale 5, Calif.



f course, you'd never attempt to use a loudspeaker for this purpose...but, it is true that in just 10 hours an average loudspeaker does exert an amount of energy that will move a loaded box car 50 feet! This means that although OPERADIO builds speakers with the skill and care of a watchmaker... these speakers are sturdily constructed to stand up under heavy continuous use. OPERADIO speakers are delicately balanced to authentically reproduce the sweetest high notes

of a piccolo, yet, carry the tremendous power of a full orchestra crescendo!

ASK FOR OPERADIO SPEAKERS — A FULL LINE OF OUTSTANDING SPEAKERS FOR EVERY PURPOSE!

# oPERADIo

RADIO REPLACEMENT and PUBLIC ADDRESS SPEAKERS

OPERADIO MFG. COMPANY • St. Charles, Illinois

#### **Audio Systems in FM**

→ From page 13

it had reached a value of 5% or more. However, since the advent of f-m and modern high fidelity system, experience implies that the public is educated to recognize somewhat lower values, perhaps even as low as 2%.

#### Intermodulation Distortion

2. Another way in which the wave from a signal may be distorted by the presence of unwanted signal components of other frequencies is by intermodulation.

Intermodulation is the result of the heterodyning of two or more of the components of the desired signal which have different frequencies. These two signal components mix in any portion of an amplifier which has non-linear impedance characteristies, to produce "sum" and "difference" signals in the output wave. This action is exactly the same as that which takes place in the mixer section of the superheterodyne receiver. In the superheterodyne, the mixing action is desirable and purposeful, to obtain the i-f signal. In audio frequency amplifiers, however, the intermodulation creates unwanted distortion of the wave and is naturally to be avoided as much as possible.

Fig. 3 gives an example of the production of intermodulation distortion. The input signal to the a-f amplifier, ordinarily made up of a large number of different frequency components, is represented here with only two components for the sake of simplicity. In a perfect amplifier, these two components, one having a frequency of 2000 cps and the other a frequency of 500 cps, would pass through the amplifier without distortion. But if the relation between voltage input and voltage output for different amplitudes is not linear, these signals modulate each other and produce the beat notes shown. One beat signal has a frequency equal to the sum of the frequencies (2500) cps) and the other has a frequency equal to their difference (1500 cps). These additional components are not supposed to be in the signal and their presence causes them to combine with the desired signal components, distorting the wave form.

Thus harmonic distortion and intermodulation distortion both affect the wave form of the signal by the addition of undesired signal components. They are distinguished by the fact that harmonic distorting components all have frequencies equal to a whole multiple (2, 3, 4, etc.) of the desired signal frequencies, whereas intermodulation distorting components have frequencies equal to the sum and difference of the frequencies of the desired components producing them. Secondary intermodulation, that is, interaction between the products of intermodulation, also occurs, but unless the amplifier is exceptionally poor, the distortion will be negligible from this source.

The causes of intermodulation distortion are generally the same as the causes of harmonic distortion. These causes are any factors which lead to a non-linear condition. Examples would be improper bias, such as illustrated in Fig. 1, or wrong component or voltage values in the plate or grid circuits of the amplifier tubes.

One of the most common causes of both harmonic and intermodulation distortion is the use of an output transformer of inadequate ratings. Also, improper loading and adjustment of power amplifiers, especially those using pentodes, can have the same effect.

#### Frequency Response

3. The third factor in the production of a high fidelity signal is that the system, including the tuner, the a-f amplifier, and the loudspeaker must reproduce equally well the signal components of all frequencies in the audible range or, at least, all the frequencies produced in the program in the station studio.

F-M stations are required by law to radiate a signal whose modulation is equally strong and undistorted (after allowing for de-emphasis) for all modulation signal components between the frequencies of 50 cps and 15,000 cps.

A flat response (meaning equal output) over the range 50—15,000 cps does not necessarily produce high fidelity! Since harmonic distortion components are higher in frequency than the fundamentals, addition of more high frequency response to a to page 26

# Be an FCC Licensed Radio Technician and

## DOUBLE YOUR PAY

# Which Do You Want?





Get Your FCC Ticket
Jobs worth
\$3,000 to \$7,500
are opening up
right now for
FCC Licensed
Radiomen.

Add Technical Training to your Practical Experience and

# Get Your FCC COMMERCIAL LICENSE RADIO OPERATOR LICENSE in a Few Short Weeks

It's EASY if you use CIRE Simplified Training and Coaching
AT HOME in SPARE TIME

Get This Amazing New Booklet

Get your license easily and quickly and be ready for the \$3000 to \$7500 jobs that are open to ticket holders. CIRE training is the only planned course of coaching and training that leads directly to an FCC license.

Your FCC Ticket is always recognized in all radio fields as proof of your technical ability.



2. TELLS HOW YOU WILL BENEFIT BY HOLDING AN FCC COMMERCIAL LICENSE.

- 3. TELLS HOW YOU CANGET YOUR FCC COMMER-CIAL RADIO OPERATOR LICENSE IN A FEW SHORT WEEKS — EASILY AND QUICKLY, BY USING CIRE SIMPLIFIED TRAINING AND COACHING AT HOME IN YOUR SPARE TIME.
- 4. TELLS OF HUNDREDS OF OUR SUCCESSFUL STUDENTS WHO NOW HAVE LICENSES AND NEW, BETTER PAYING JOBS.
- 5. TELLS HOW WE PREPARE YOU TO PASS THE NEW FCC COMMERCIAL LICENSE EXAMINATIONS, WHICH NOW INCLUDE FM AND TELEVISION.
- TELLS HOW WE GUARANTEE TO TRAIN AND COACH YOU UNTIL YOU GET YOUR LICENSE TELLS HOW WE HELP YOU TO GET A BETTER-PAYING, LICENSED JOB, WITH OUR FREE AND EXCLUSIVE SERVICE, WHICH PREPARES YOUR EMPLOYMENT APPLICATION FOR MAILING TO HUNDREDS OF EMPLOYERS, INCLUDING FM, AM AND TELEVISION BROADCAST STATIONS, RADIO MANUFACTURERS, POBLICE RADIO STATIONS, AND RADIO-EQUIPPED TAXI, BUS AND PUBLIC LIVILITY COMPANIES.



CIRE Graduates Find FCC License Pays Off

FCC License Pays Off

"I now hold ticket P-10-3787,
and holding the license has
helped me to obtain the type
of job I've always dreamed
of having. Yes, thanks to
CIRE, I am now working for
CAA as Radio Maintenance
Technician, at a far better
salary than I've ever had before. I am deeply grafeful."
Student No. 3319N12

Student No. 3319N12
"I was issued License P-2-11188
on November 4. The next day
I was signed on board a
tanker as Radio OperatorPurser. Besides radio operating, I handle the payrolls,
etc., which is all over-time
and brings my monthly pay
up to between \$500 and \$650."
Student No. 2355N12

Get All 3 FREE!

#### CLEVELAND INSTITUTE OF RADIO ELECTRONICS Desk RM-1, 4900 Euclid Bldg., Cleveland 3, Ohio

Desk RM-1, 4900 Euclid Bldg., Cleveland 3, Ohlo (Address to Desk No. to avoid delay)

I want to know how I can get my FCC ticket in a few short weeks by training at home in spare time. Send me your FREE booklet "Money Making FCC License Information," as well as a sample FCC-type exam and free booklet, "How to Pass FCC License Examination" (does not cover exams for Amateur License). Approved for Veteran Training under "G.I. Bill of

Name
Address
City ZoneState



Replacements for ALL SETS!

Television creates new opportunities of profit for servicemen and a new need for replacement speakers. Now Utah announces two new ovals especially designed for TV. Both are 4x6's, the \$E46T6 with a 60 ohm field and the \$E46T10 with 100 ohms resistance. Other ovals in the Utah line qualify for use in television sets. Many permanent magnet weights and various field coil resistances are available in 4x6's, 5x7's and 6x9's. TV is big business — see your jobber today.



#### **UTAH RADIO PRODUCTS** HUNTINGTON, INDIANA

DIVISION OF INTERNATIONAL DETROLA CORPORATION EXPORT DIVISION: MORHAN EXPORTING CORP. N.Y., N.Y.

UTAH FOR AM, FM, VIDEO

#### PROGRESSIVE MARKETERS

Dave Kubrick - Irv Brown

#### RADIO-TELEVISION SALES SPECIALISTS

Eastern Factory Sales Representatives for:

Transvision Television

Precision Transformer Co. Boland & Boyce, Inc.

American Condenser Co.

Harrison Wire Recorder

41 Union Square, N. Y. 3, N. Y.

ALgonquin 4-7486

#### **Audio Systems in FM**

slightly distorted (say 5%) amplifier, will make the distortion much worse, since many of the harmonics which were previously inaudible are now heard.

Thus we find that frequency response and harmonic and intermodulation distortion are intimately related. If the harmonic and intermodulation distortion effects are not kept to a very low level, a wider frequency response only makes an amplifier worse rather than better.

#### **Phase Response and Transients**

4. Phase shift distortion, which has a bad effect on video amplifiers in television receivers, is never bad enough in a-f amplifiers in f-m receivers to cause servicing or maintenance troubles. In the more elaborate high fidelity systems, however, some consideration is paid to keeping transient response to a minimum. Transients results from the tendency of certain combination of components (say, a resistor and a condenser) to be shocked into oscillation for a few eycles at their natural frequency. This effect is noticeable in some amplifiers when a cymbal or bass drum causes a sudden electrical impact on the system; the sound is not sharp and definite. Investigation and remedy of such trouble may at present be outside the scope of the service engineer, but it is important that he notice and recognize such symptoms.

#### **Practical Applications**

The foregoing information about the definition and nature of high fidelity is important to the practical service man for the following rea-

- 1. The public is becoming educated to the benefits and enjoyment possible from high fidelity reproduction. The service engineer must keep his customers well-informed on the subiect.
- 2. In advising the prospective purchaser of a receiver, the serviceman must be prepared to discuss in detail and explain in simple language the advantages and the limitations of various f-m receiver models.
- 3. In making replacements, alignment jobs and other operations, the serviceman must be aware of the various factors necessary to assure that proper fidelity is maintained after the job is complete and the receiver returned to the customer.

Advertise 

From page 20 the U. S., of which nearly one and a half million was for local advertising.

A radio service shop may never reach the stage where it has as many daily customers as does a super food market, but we want to get across the incontestable fact that promotion can build up a trade and the demand for the products or services of that trade.

Some of the above mentioned local businesses built up their volume and increased the demand for their goods by a laborious and costly reorganization based on existing conditions.

#### You Have the Opportunity

The radio service field does not have to do this, because two new developments-FM and Televisionhave come along. These new additions are revitalizing shots in the arm that make a new era for servicemen a certainty. Home receivers, as a result of these developments, are much more complex and will require more expert maintenance. From here on, the radio and television service technician assumes an increasingly important position in his community. His services will be more essential and vastly more respected. What an opportunity this is!

In advertising campaign planning there's a never-ending search for "new angles" from which to present a story. You—the service technician—have had FM and Television handed to you on a solid silver platter. These are new opportunities, the like of which any industry would give millions to have.

It is inevitable that the sudden appearance of a golden opportunity will cause a stampede in the direction of the bright light. Some of the participants will be trampled to death and others will be left behind on the barren ground. You can bet that the men who come out on top will be those who not only gave their customers better service, but who knew how to advertise that service.

(Article number two in this series will cover the planning of an advertising program for your radio service shop, based on small and large income. In the meantime, why not write in your questions on advertising? We'll try to print and answer as many letters as we can. You will help yourself and others by doing this—let's hear from you!)



Brach antennas . . . long known for dependability . . . maximum reception . . . trouble-free operation . . . durability and ease of installation . . . now feature an added extra . . . Flexibility. Unique construction features aid the service man in making a more rapid installation to which future additions or modifications can be easily made.

**1. FLEXIBILITY** A complete line designed with basic antenna parts which are convertible to more complex arrays as required by location and reception problems.

2. COMPLETE KITS Each antenna model is independently designed and furnished in a completely packaged kit containing all necessary hardware, downlead (when desired) and the Universal Base Mount . . . ready for installation.

3. PRE-ASSEMBLY Each antenna is factory pre-assembled as far as possible, ready to erect. Complete and simple installation instructions. Saves valuable man-hours on the roof.

**4. MECHANICAL STRENGTH** Weather - tested for durability, Brach Antennas feature a husky steel mast, rigid connections, sturdy base mount, neat appearance. All parts corrosion resistant.


5. SUPERIOR RECEPTION Designed with engineering "know-how". All Brach antennas are factory pre-tuned, matched for 300 ohm transmission line with large diameter aluminum elements for better signal pick-up. Directivity patterns and standing wave ratios available upon request.

#### New! Tops in TV! HI-LO ROTATABLE Antenna

Here it is! A rotatob'e ontenno to provide peak performance with any station at any time. Broch introduces the new "Superview" Rotatoble, covering both high (174 MC to 216 MC) and law (88 MC to 108 MC) TV bands. High band extension available for easy addition to standard dipole array for separate orientation. No more multiple images. No more "weak" stations, Broch's Superview HI-LO assures television reception that's tops, Make sure and investigate the new Superview line taday.

Write for Free Broch cotolog showing complete line of TV and FM antennos and accessories.

WRITE FOR CATALOG NO. RM 304





L. S. BRACH MFG. CORP.

200 CENTRAL AVENUE, NEWARK, N. J.

WORLD'S OLDEST AND LARGEST MANUFACTURERS OF RADIO ANTENNAS AND ACCESSORIES

# Astatic FL SERIES Pickups

# Play BOTH 33½ and 78 RPM Records WITHOUT changing Needle Pressure or similar adjustments

NOT HAVING to change needle pressure or make similar adjust-ments—in switching from 33-1/3 to 78 RPM Records with Astatic FL Series Pickups—has done much to put these revolutionary phonograph playing arms in a leading position in the new longplaying equipment field. All that the user need do is change cartridges. Takes only a second, because they are designed to fix themselves in playing position on the same slip-in principle which firmly joins barrel and cap of many modern fountain pens. New engineering, mechanically and electrically, assures perfect tracking, unparalleled reproduction, at the featherlight needle pressure of five grams. Comparable reproduction quality at lower cost is available in other Astatic units, which round out the complete Astatic Long-Playing Line Write for new brochure, giving full details, illustrations.



Astatic Crystal Devices manufactured under Brush Development Co. patents



#### TWO GREAT BOOKS . . . **COVERING EVERYTHING IN RADIO & TELEVISION**

EVERYTHING IN RADIO AND **ELECTRONICS IN ONE BOOK!** THE MOST COMPLETE TELEVISION MANUAL



#### THE RADIO DATA BOOK

the only radio handbook of its kind . . . 1148 pages . . . 12 sections, each covering a radio subject more completely than any other book!

12 complete books in one only Less than 42c per book!

\$5.00

#### THE VIDEO **HANDBOOK**

768 pages . . . 14 sections, covering every phase in television . . . over 800 illustrations . . . . handsomely bound in Du Pont Fabrikoid with red and silver letters.

ADVANCE SALE ORDER NOW!

\$5.00

<b>40.00</b>										
Mail This Coupon to Your Jobber Today — BOLAND & BOYCE, 460 Bloomfield Ave., Mon	or direct to: RM-1									
Send me 1 RADIO DATA BOOK  I enclose \$5.00 (\$5.50 Foreign)  I enclosed \$1.00 and will pay postman \$4.00 on delivery (in U. S. only)	Send me 1 VIDEO HANDBOOK  I enclosed \$5.00 (\$5.50 Foreign)  I enclosed \$1.00 and will pay postman \$4.00 nn delivery (in U. S. only)									
	ZONE									

#### BACK NUMBERS . . . . . . get them while they last

☐ February 1948

LET'S WORK TOGETHER HOW TO USE SWEEP GENERATORS VOLTAGE REGULATORS

☐ March 1948

HOW TO ELIMINATE HUM
TELEVISION INTERCARRIER SYSTEM
SWEEP GENERATORS OR FM ALIGNMENT
PART II

□ April 1948

NEW FM SIGNAL GENERATOR DB CALCULATORS MADE EASY GET THE MOST FROM YOUR VTVM AFC IN FM

☐ May 1948

TROUBLESHOOTING RECEIVER
DISTORTION
INTERFERENCE
A POCKET FM SIGNAL GENERATOR
A SWEEP GENERATOR FOR F.M. & T.V.

☐ June 1948

INTERFERENCE PART II HEATER-CATHODE HUM SUPER SERVICE F. M. AND YOU

☐ July 1948

OHM'S LAW IN RADIO SERVICING INTERFERENCE PART III HOME SERVICE CALLS . . . DO THEY PAY? SERVICING RC FILTERS

August 1948

ADVERTISING WILL BUILD YOUR BUSINESS INSTALLATION OF F.M. ANTENNAS CUSTOM BUILDING YGS-3 SIGNAL GENERATOR

September 1948

SERVICING WITH VTVM
TRANSMISSION LINE PROBLEMS
RADIO PHOTOGRAPHS
RECEPTION UNLIMITED

☐ November 1948

RECORD CHANGER REPAIRS SIGNAL TRACING TV NEW TV INSTRUMENTS F.M. DETECTORS

RADIO MAINTEN	ANCE MAGAZINE
460 BLOOMFIELD	AVE.,
MONTOLAID N	

Please send me checked here	the	back	numbers
I am enclosing 35c \$2 for any 8 copies.	for	each	сору, ег
☐ February 1948 ☐ March 1948 ☐ April 1948 ☐ May 1948		June July I Augus Septer Noven	1948 948 † 1948 mber 1948 nber 1948

NAME .....

ADDRESS

CITY

....STATE

#### **TV Tuning Systems**

→ From page 17

part of the waveband switch in order to keep lead inductance at a minimum. A twin 6J6 is used as a triode mixer and Colpitts oscillator. Fine tuning adjustments are made with a small condenser (C25). The major frequency changes are made by switching the oscillator coils, which also are slug-tuned and pre-set at the factory.

#### Permeability Tuning

Advantages of permeability-tuned systems are the same as with other variable inductances. The main disadvantage is the problem involved in mass production. It is extremely difficult to turn out permeabilitytuned units which have uniform tracking and calibration, due to the small number of turns involved, the large wire size required, and the extremely wide frequency range to be covered in such a short motion of the tuning slugs. One manufacturer uses braided tinsel to overcome this difficulty. Zenith, in its f-m tuners, uses four parallel wires for each coil winding as the solution. Other disadvantages of permeability systems are mounting and wiring arrangements, the necesity for thin-walled forms, termination, etc. Belmont, however, employs a continuously-tuned, mechanically-ganged permeability tuner in their model 21A21 receiver (Fig. 7) with excellent results.

Many variations of the above systems are being used and developed. Basically, the principles and operation will remain the same, but it will be interesting to note the circuit arrangements and tuning systems to be employed in future television receivers.

#### **Over the Bench**

→ From page 23


place. If the original one has been lost or thrown away, a new one is made.

Quite often a little casual conversation with a customer will reveal a condition that is highly dangerous. For example, as a customer of mine was leaving the shop recently with his little ac-dc set under his arm, he mentioned that he always liked this

particular little set because it would sit on a narrow shelf just above the bathtub and enable him to listen to a favorite morning program while he was bathing.

I picked up a magazine I had been reading that morning and showed him a story about a woman who had been doing exactly the same thing and who had been electrocuted when the radio toppled into the tub. When he finished reading the story, he was in a receptive mood to hear this cardinal safety rule: Never have any electrical appliance where you can reach it while in a bathtub.

Remember, having a healthy respect for electricity is a good way to stay healthy.



The usual objective of Antenna Stacking is for the purpose of acquiring db gain—with Amphenol's 114-302 Stacked Array there is a plus value, another adaptation, one which is very important in congested TV areas. Both the upper and lower bays provide all-channel reception and each bay may be individually oriented. Overlapping signals or station interference on same channels within receiving areas may now be separated—if and when the bays are stacked for orientation. In the smaller illustration lower right, observe the same array stacked for db gain on all channels. Amphenol Antennas offer many plus values in being perfected electrically and mechanically in every detail.





arc-back shield directly grounded.

All critical high potential and ground connections within the probe are positively accomplished via high

compression contact springs.

cite internal components

★ Special helical film-type cartridge

multiplier, developed specifically for very high potentials.

Custom molded polystyrene probe head, bakelite handle and barrier Specially machined and tooled lu-

Application Engineered" to meet the

directly grounded.

🛊 External arc-back barrier

# Fully shielded instrument

### SAFE..SIMPL

HIGH VOLTAGE TV Tests to 60,000 VOLTS

WITH THE NEW

#### PRECISION SERIES TV

Super High Voltage Sofety Test Probes

. Test high voltages with safety and confidence. Series TV super high voltage test probe is Extended high dielectric custom designed for YOUR safety FIRST and provides anti-leakage paths. the accuracy and dependability you expect from prod-★ Multi-channelled guard barrier ucts bearing the "Precision" name. # Full handle length internal

> \* Series TVP. Prohe less cartridge.
> Net Price \$12.35

Series TV-1...Probe with cartridge for Pre-cision EV-10VTVM Net Price \$15.45

Series TV-2 .. Probe with carried for Pre-cision (or any) 20.000 ohms per volt lest set with a 6000 volt range Net Price \$15.45

★ Multiplier cartridges are available to match most popular 20 000 ohms/vol test sets and vacuum tube voltmeters



YOUR ANSWER TO TV & FM See your Precision Distributor NOW



Voltage Test Probes provide direct kilo-voltmeter facilities with your present high sensitivity test set and vacuum tube voltmeter such as the "Precision" instruments illustrated below.

See them on display at all leading radio equipment distributors along with the complete Precision line of modern electronic test instruments for all phases of AM-FM-TV service and maintenance



Model 85 - 20,000 ohms per volt AC-DC test set. Rotary range and func-tion selection, 34 ranges to 6000 volts, 60 megs, 12 amps., 70 DB. 41/2" meter. Net Price \$38.75



Model 858-L 20,000 ohms per volt Multi-Master High Speed, push button operated 54 ranges to 6000 volts 600 megs 12 amps., 70 DB 41/2" meter.

Net Price \$54.10

Model EV-10 MCP High sensitivity, zero-center VTVM plus com-plete AC-DC V-O-M facilities to 6000 volts, 2000 megs., 12 amps., 70 DB with 7" meter. Net Price \$89.95



Model 10-54-P -Combination Electronamic Tube Tester, and 20,000 ohms per volt V-O-M Ranges to 6000 volts, 12 amps., 60 megs., 70 DB

#### PRECISION APPARATUS COMPANY, INC.

92-27 Horace Harding Bouleward • Elmhurst, New York Export Division: 458 Broadway, New York, U. S. A.

#### SPEAKER SPECIALIST

Build yourself a reputation for improved tone of every speaker job you handle. A.G. will back you with the finest reconing service.

- Cones and fields in stock for any speaker
- Full range frequency test
- Audio test at full power rating
- Professional workmanship

Send a trial speaker, parcel post, for quick reconing and return in perfect condition . . . 5"—\$1.50 . . . 12"—\$3.00 . . . others

#### A. G. RADIO PARTS CO.

3515 N. 17th St.

Philadelphia 40, Pa.

#### CORRECTION

The formula appearing on page 42 of the December 1948 issue of Radio Maintenance has been printed in error. The correct formula should read as follows:

$$E_{t} = \frac{E_{t} \times (F - 1)}{F - \left(\frac{E_{t}}{E_{s}}\right)}$$

### BINDERS!

PRESERVE YOUR RADIO MAINTENANCE MAGAZINES IN **THEM** 

RADI 160 l Monte	3100	unt	iel	el												_		
Please each.		nd	n	ie.				hi	n	de	r	-	at		S	2.	0	0
Total	am	1) (1	n t	e	ne	lo	 ·d				٠			١.				
Name							 											
Addre							 											
City				. ,							z	o I	10	1				
State														1		٠		

30,000 **TECHNICIANS** 

Read

#### RADIO MAINTENANCE

Every Month

Every day is RADIO MAINTENANCE day in your shop!

RADIO MAINTENANCE 460 Bloomfield Ave., Montclair I, N. J.
Please send me RADIO MAINTE- NANCE for:
2 years at \$5.00 I year at \$3.00 Check enclosed Bill me later
Name
Occupation . =
Address
City Zone
State

# ELECTRONICALLY SPEAKING

Sales of radio receiving tubes continue to climb. September sales totalled over 18 million, representing an increase of 1.7 million over August and more than 2 million over September 1947, it was reported by the Radio Manufacturers Association. Of the total, 13 million tubes seld for new sets, 5 million went for replacements. The remainder was taken up by export and government agencies. Total sales of receiving tubes for the first nine months of 1547 exceeded 144 million.

Television in the operating room. Actual operations were televised for purposes of demonstrating new surgical techniques at the recent meeting of the American College of Surgeons in Los Angeles. Instead of having to depend on verbal descriptions, surgeons were able to watch operations actually being performed over ten receivers provided by G.E. According to the President of the College, TV contributed a major share to the success of the meeting.

Television has gone Navy. Early this year, weekly schedules of lectures will be telecast four miles to large screen receivers at the Merchant Marine Academy at Kings Point, N. Y. This experimental program will be compared in results with the standard method of instruction. The experiments are being conducted by the Special Devices center at Sands Point and are under the direction of the Office of Naval Research. General Electric Co. is supplying complete studio equipment and monitoring receivers for the project.





Makes Sales and Service Easy!



#### SELL MORE CARTRIDGES

It's a colorful display . . . creates interest . . . and action . . . helps you sell *more* replacements to old and new customers.

#### SATISFY MORE CUSTOMERS

You give faster replacement service. Your customers get more pleasure and more good plays . . . even from old, worn records!

#### SIMPLIFY YOUR SERVICE JOB

It's a complete service Kit, too. Contains everything for time-saving, labor-saving replacement. Gives you 3 basic models that replace over 150 standard types.

#### MAKE MORE MONEY

Saves ordering time and service time. Cuts overhead. You make a good profit on every cartridge sale . . . and every service job. Builds needle sales, too! Put the Kit on display . . . take one with you on your service calls. Available in Kit "A" (Osmium) and Kit "B" (Sapphire). Each Kit contains 6 cartridges, 4 extra needles, mounting plates, replacement chart.

Order from your E-V Distributor or write for Bulletin No. 142

ELECTRO-VOICE, INC., BUCHANAN, MICH.


Export: 13 East 40th St., New York 16, N. Y., U.S. A. Cables: Arlab

E-V Pat. Pend. Licensed under Brush Patents.

NEW MODEL LI4 MICROGROOVE CRYSTAL CARTRIDGE AND NEW MODELS 20 AND 22 MAGNETIC CARTRIDGE FOR REGULAR AND MICROGROOVE ALSO AVAILABLE



# TV+FM+AM... We're making sure that we get all of this business..."



# All Leading Servicemen Use RIDER MANUALS

A ready reference for all sets from 1930 to 1948 — Volumes 1 to 17 are at your Jobber's Now. He also has Volume 1 of the Rider Television Manual.

# At Your Jobber's Soon!

VOLUME



#### RIDER TELEVISION MANUAL

PLUS 2 Separate Books, "HOW IT WORKS" and INDEX

Even though most of your business is now done on servicing AM and FM, it doesn't take one on servicing AM and FM, it doesn't take of the service of the serv schemotics, to guide you and your men quick and easy methods of servicing TY

## Available Now!

RIDER PA MANUAL

The first industry-wide public address equipment Manual incorporating the amplifier production of 147 manufacturers from 1938 to 1948.

2024 pages; plus "How It Works" book which explains theory of various PA circuits and method of rapidly locating faults; plus Index.

31800 All complete for .......

#### RIDER MANUALS

Television Manual, Volume I, (plus HOW IT WORKS and INDEX) \$18,00 Volume XVII ......\$16.50 Volume XVI ......\$ 8.40 Volume XV ..... .....\$19.80 Volume XIV to VII (each volume) ......\$16.50 Volume VI ......\$12.50 Abridged Manuals I to V (one volume) ......\$19.80 Record Changers and Recorders ..... .....\$ 9.00 Master Index, covering

At Your Jobber's Soon!

VOLUME



2000 Pages PLUS Separate "How It Works" Book and cumulative Volomes XVI, XVII and XVIII INDEX

Rider Manuals are absolutely dependable because they contain the OFFICIAL AUTHENTIC DATA of the set manufacturers themselves. Only in Rider Manuals will you find this increased the set down in an easy-to-follow form Only in Rider Monuals will you find this information—set down in an easy-to-follow form to save you time; to save you money, and to holp you do a real, factory-type servicing that you con tell your customers, too service. All leading servicemen use Rider Monsive "Clerified Schemolics" provide time. Yolume XVIII even wire recorders are covchangers.

Both Books, Complete..... \$1980


JOHN F. RIDER, PUBLISHER, Inc., 480 Canal Street, New York 13, N. Y. Export Agent: Rocke International Corp., 13 E. 40th St., N.Y.C., Cable, ARLAB.

Manuals, Vols. 1 to XV..\$1.50

ANOTHER NOTE: The C-D Copocitor Monuol for Rodio Servicing, 1948 edition No. 4, makes reference to paly one source of receiver schemotics—Rider Monuols.

# MAKES FRIENDS...AND KEEPS THEM!





How to make more money in the servicing business!

Your local jobber believes in helping you—his best customer—to make more money, because then you will become a bigger customer and everyone will be happy!

In line with this policy, he pledges his high standard of service and better buys for radio servicemen . . . AND he will present ideas to help you expand your business. In the months to come he will feature a different subject each month on this back cover of RADIO MAINTENANCE. This may be in the nature of new moneymaking ideas, or announcements of special sales in his store, or suggestions on the proper equipment for your work. In all cases, the idea will be to help you—the radio serviceman—make more profit.

Of course his staff of experienced clerks are ready to serve you every day.

Drop in his store today—browse around. He has all kinds of good buys you may want to look over. Just mention RADIO MAINTENANCE—and watch this back cover for extra profit for you!

# RADIO MAINTENANCE

460 Bloomfield Ave.

Montdair, N. J.